



# Storage backend

## Astra Automation

NetApp  
June 28, 2024

# Inhalt

- Storage backend ..... 1
  - Storage backend overview ..... 1
  - Create a new storage backend ..... 1
  - List all storage backends ..... 15
  - Retrieve a storage backend ..... 29
  - Modify a storage backend ..... 41
  - Delete a storage backend ..... 54

# Storage backend

## Storage backend overview

The Storage Backend API provides CRUD (Create-Read-Update-Delete) access to representations of providers of storage services (storage backends) that can be used by managed clusters and applications.

## Create a new storage backend

POST /accounts/{account\_id}/topology/v1/storageBackends

Indicates desired values for the Storage Backend API resource to be created.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"><li>example: {{.Account}}</li></ul>

### Request Body

Indicates desired values for the Storage Backend API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>"application/astra-storageBackend"</li></ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"><li>"1.0"</li><li>"1.1"</li><li>"1.2"</li></ul>

Name	Type	Required	Description
backendName	string	False	JSON string containing a user-specified name for the storage backend. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
backendType	string	True	JSON string containing a value indicating the type of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> <li>• "ontap" - The storage backend represents a NetApp ONTAP system</li> <li>• enum: ["ontap"]</li> <li>• example: ontap</li> </ul>
backendVersion	string	False	JSON string containing a value indicating the version of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
backendCredentialsName	string	False	JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

Name	Type	Required	Description
metadata	<a href="#">type_astra_metadata_update</a>	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

### Example request

```
{
  "type": "application/astra-storageBackend",
  "version": "1.2",
  "backendName": "st1-45",
  "backendType": "ontap",
  "backendCredentialsName": "st1-45-cred"
}
```

### Response

Status: 201, Returns the newly created storageBackend resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• "application/astra-storageBackend"</li> </ul>

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
backendName	string	True	JSON string containing a user-specified name for the storage backend. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
backendType	string	True	JSON string containing a value indicating the type of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> <li>• "ontap" - The storage backend represents a NetApp ONTAP system</li> <li>• enum: ["ontap"]</li> <li>• example: ontap</li> </ul>
backendVersion	string	True	JSON string containing a value indicating the version of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

Name	Type	Required	Description
backendCredentialsName	string	True	<p>JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
configVersion	string	False	<p>JSON string containing a value indicating the active configuration to be used by the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
state	string	True	<p>JSON string containing a value indicating the operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "discovered" - The storage backend has been discovered from a managed cluster</li> <li>• "running" - The storage backend is running normally</li> <li>• "unknown" - The state of the storage backend cannot be determined</li> <li>• "failed" - The storage backend is in an unavailable state</li> </ul>

Name	Type	Required	Description
stateDesired	string	False	<p>JSON string containing a value indicating the desired operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "running" - The storage backend will be in a normal running state</li> </ul>
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a storage backend is unable to transition to "running", why it has transitioned to "failed" or "unknown", and/or why it is at risk of transitioning to "failed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>
managedState	string	True	<p>JSON string containing a value indicating the management state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The storage backend is scheduled to be discovered or added</li> <li>• "unmanaged" - The storage backend is in a "discovered" state, is not under management, and is eligible for management</li> <li>• "managed" - The storage backend is in a "running" or "unknown" state and is under management</li> </ul>



Name	Type	Required	Description
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the storage backend is ineligible to be managed. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>
healthState	string	False	<p>JSON string containing a value indicating the health state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)</li> <li>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification</li> <li>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification</li> <li>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification</li> </ul>

Name	Type	Required	Description
healthStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is not in a normal health state. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the storage backend. "unknown" for ONTAP. Defined values are:</p> <ul style="list-style-type: none"> <li>• "protected" - The storage backend has a protection policy defined and is in conformance with that policy</li> <li>• "partial" - The storage backend has a protection policy defined but is out of conformance with that policy</li> <li>• "none" - The storage backend is not protected</li> <li>• "unknown" - The storage backend protection policy conformance cannot be determined</li> <li>• enum: ["protected", "partial", "none", "unknown"]</li> <li>• example: protected</li> </ul>

Name	Type	Required	Description
protectionStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a protection policy is out of conformance. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>
ontap	ontap	False	<p>JSON object containing specific information related to ONTAP clusters.</p> <ul style="list-style-type: none"> <li>• additionalProperties: false</li> </ul>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

## Example response

```
{
  "type": "application/astra-storageBackend",
  "version": "1.2",
  "id": "ad238443-2bc7-54f5-bd7f-5d1668377cd7",
  "backendName": "st1-45",
  "backendType": "ontap",
  "backendVersion": "9.8",
  "backendCredentialsName": "st1-45-cred",
  "state": "running",
  "stateUnready": [],
  "managedState": "managed",
  "managedStateUnready": [],
  "protectionState": "unknown",
  "protectionStateUnready": [
    "Waiting for storage backend discovery"
  ],
  "ontap": {
    "backendManagementIP": "10.193.179.105",
    "managementIPs": [
      "10.193.188.110",
      "10.193.179.105",
      "10.193.179.106"
    ]
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

## Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

## Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

## Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

ontap

JSON object containing specific information related to ONTAP clusters.

Name	Type	Required	Description
backendManagementIP	string	False	JSON string containing the IP address used to connect to this ONTAP cluster.
managementIPs	array[string]	False	JSON array of JSON strings containing the list of all possible management IPs used to connect to this ONTAP cluster. This is used to correlate backends detected through Trident and storage backends in Astra. <ul style="list-style-type: none"><li>• uniqueItems: 1</li></ul>

invalidParams



Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

## List all storage backends

GET /accounts/{account\_id}/topology/v1/storageBackends

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> <li>example: id,name,state</li> </ul>
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

## Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: <a href="#">storageBackend_1.2_get_response_body</a> , array[]]	True	
metadata	<a href="#">type_astra_metadata_list</a>	True	

## Example response

```
{
  "type": "application/astra-storageBackends",
  "version": "1.2",
  "items": [
    [
      "d6ee1e51-d65f-415a-a3d4-6d7fa8b64943",
      "st1-45",
      "running"
    ],
    [
      "a5c508b7-aacd-4d19-9455-53c0d183ab4e",
      "st2-67",
      "discovered"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

# Definitions

## See Definitions

ontap

JSON object containing specific information related to ONTAP clusters.

Name	Type	Required	Description
backendManagementIP	string	False	JSON string containing the IP address used to connect to this ONTAP cluster.
managementIPs	array[string]	False	JSON array of JSON strings containing the list of all possible management IPs used to connect to this ONTAP cluster. This is used to correlate backends detected through Trident and storage backends in Astra.  • <code>uniqueItems: 1</code>

type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

storageBackend\_1.2\_get\_response\_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "application/astra-storageBackend"</li> </ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
backendName	string	True	JSON string containing a user-specified name for the storage backend. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
backendType	string	True	JSON string containing a value indicating the type of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> <li>• "ontap" - The storage backend represents a NetApp ONTAP system</li> <li>• enum: ["ontap"]</li> <li>• example: ontap</li> </ul>



Name	Type	Required	Description
backendVersion	string	True	<p>JSON string containing a value indicating the version of the storage backend being represented. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
backendCredentialsName	string	True	<p>JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
configVersion	string	False	<p>JSON string containing a value indicating the active configuration to be used by the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "discovered" - The storage backend has been discovered from a managed cluster</li> <li>• "running" - The storage backend is running normally</li> <li>• "unknown" - The state of the storage backend cannot be determined</li> <li>• "failed" - The storage backend is in an unavailable state</li> </ul>
stateDesired	string	False	<p>JSON string containing a value indicating the desired operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "running" - The storage backend will be in a normal running state</li> </ul>
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a storage backend is unable to transition to "running", why it has transitioned to "failed" or "unknown", and/or why it is at risk of transitioning to "failed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The storage backend is scheduled to be discovered or added</li> <li>• "unmanaged" - The storage backend is in a "discovered" state, is not under management, and is eligible for management</li> <li>• "managed" - The storage backend is in a "running" or "unknown" state and is under management</li> </ul>
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the storage backend is ineligible to be managed. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)</li> <li>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification</li> <li>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification</li> <li>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification</li> </ul>
healthStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is not in a normal health state. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the storage backend. "unknown" for ONTAP. Defined values are:</p> <ul style="list-style-type: none"> <li>• "protected" - The storage backend has a protection policy defined and is in conformance with that policy</li> <li>• "partial" - The storage backend has a protection policy defined but is out of conformance with that policy</li> <li>• "none" - The storage backend is not protected</li> <li>• "unknown" - The storage backend protection policy conformance cannot be determined</li> <li>• enum: ["protected", "partial", "none", "unknown"]</li> <li>• example: protected</li> </ul>
protectionStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a protection policy is out of conformance. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>

Name	Type	Required	Description
ontap	ontap	False	JSON object containing specific information related to ONTAP clusters.  <ul style="list-style-type: none"> <li>additionalProperties: false</li> </ul>
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are:  <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

#### type\_astra\_metadata\_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

## Retrieve a storage backend

GET /accounts/{account\_id}/topology/v1/storageBackends/{storageBackend\_id}

Returns the stored Storage Backend API resource in the JSON response body.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>
storageBackend_id	string	path	True	ID of the storageBackend collection to list

### Response

Status: 200, Returns the stored Storage Backend API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>"application/astra-storageBackend"</li> </ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>"1.0"</li> <li>"1.1"</li> <li>"1.2"</li> </ul>

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
backendName	string	True	JSON string containing a user-specified name for the storage backend. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
backendType	string	True	JSON string containing a value indicating the type of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> <li>• "ontap" - The storage backend represents a NetApp ONTAP system</li> <li>• enum: ["ontap"]</li> <li>• example: ontap</li> </ul>
backendVersion	string	True	JSON string containing a value indicating the version of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>



Name	Type	Required	Description
backendCredentialsName	string	True	<p>JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
configVersion	string	False	<p>JSON string containing a value indicating the active configuration to be used by the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
state	string	True	<p>JSON string containing a value indicating the operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "discovered" - The storage backend has been discovered from a managed cluster</li> <li>• "running" - The storage backend is running normally</li> <li>• "unknown" - The state of the storage backend cannot be determined</li> <li>• "failed" - The storage backend is in an unavailable state</li> </ul>

Name	Type	Required	Description
stateDesired	string	False	<p>JSON string containing a value indicating the desired operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "running" - The storage backend will be in a normal running state</li> </ul>
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a storage backend is unable to transition to "running", why it has transitioned to "failed" or "unknown", and/or why it is at risk of transitioning to "failed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>
managedState	string	True	<p>JSON string containing a value indicating the management state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The storage backend is scheduled to be discovered or added</li> <li>• "unmanaged" - The storage backend is in a "discovered" state, is not under management, and is eligible for management</li> <li>• "managed" - The storage backend is in a "running" or "unknown" state and is under management</li> </ul>

Name	Type	Required	Description
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the storage backend is ineligible to be managed. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>
healthState	string	False	<p>JSON string containing a value indicating the health state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)</li> <li>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification</li> <li>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification</li> <li>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification</li> </ul>

Name	Type	Required	Description
healthStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is not in a normal health state. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the storage backend. "unknown" for ONTAP. Defined values are:</p> <ul style="list-style-type: none"> <li>• "protected" - The storage backend has a protection policy defined and is in conformance with that policy</li> <li>• "partial" - The storage backend has a protection policy defined but is out of conformance with that policy</li> <li>• "none" - The storage backend is not protected</li> <li>• "unknown" - The storage backend protection policy conformance cannot be determined</li> <li>• enum: ["protected", "partial", "none", "unknown"]</li> <li>• example: protected</li> </ul>

Name	Type	Required	Description
protectionStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a protection policy is out of conformance. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>
ontap	ontap	False	<p>JSON object containing specific information related to ONTAP clusters.</p> <ul style="list-style-type: none"> <li>• additionalProperties: false</li> </ul>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

## Example response

```
{
  "type": "application/astra-storageBackend",
  "version": "1.2",
  "id": "ad238443-2bc7-54f5-bd7f-5d1668377cd7",
  "backendName": "st1-45",
  "backendType": "ontap",
  "backendVersion": "9.8",
  "backendCredentialsName": "st1-45-cred",
  "state": "discovered",
  "stateUnready": [],
  "managedState": "unmanaged",
  "managedStateUnready": [],
  "protectionState": "unknown",
  "protectionStateUnready": [
    "Waiting for storage backend discovery"
  ],
  "ontap": {
    "backendManagementIP": "10.193.179.105",
    "managementIPs": [
      "10.193.188.110",
      "10.193.179.105",
      "10.193.179.106"
    ]
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	



## Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

ontap

JSON object containing specific information related to ONTAP clusters.

Name	Type	Required	Description
backendManagementIP	string	False	JSON string containing the IP address used to connect to this ONTAP cluster.
managementIPs	array[string]	False	JSON array of JSON strings containing the list of all possible management IPs used to connect to this ONTAP cluster. This is used to correlate backends detected through Trident and storage backends in Astra.  • <code>uniqueItems: 1</code>

type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Modify a storage backend

PUT /accounts/{account\_id}/topology/v1/storageBackends/{storageBackend\_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Side Effects

- Specifying a configuration version results in storage backend type-specific configuration changes being applied, which can include the initial installation of a storage backend.
- Specifying a configuration version might result in storageClass resources being added, modified, or removed.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>• example: <code>{{.Account}}</code></li> </ul>
storageBackend_id	string	path	True	ID of the storageBackend collection to list

### Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Side Effects

- Specifying a configuration version results in storage backend type-specific configuration changes being applied, which can include the initial installation of a storage backend.
- Specifying a configuration version might result in storageClass resources being added, modified, or removed.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "application/astra-storageBackend"</li> </ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
backendName	string	False	JSON string containing a user-specified name for the storage backend. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
backendType	string	False	JSON string containing a value indicating the type of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> <li>• "ontap" - The storage backend represents a NetApp ONTAP system</li> <li>• enum: ["ontap"]</li> <li>• example: ontap</li> </ul>

Name	Type	Required	Description
backendVersion	string	False	<p>JSON string containing a value indicating the version of the storage backend being represented. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
backendCredentialsName	string	False	<p>JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
configVersion	string	False	<p>JSON string containing a value indicating the active configuration to be used by the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "discovered" - The storage backend has been discovered from a managed cluster</li> <li>• "running" - The storage backend is running normally</li> <li>• "unknown" - The state of the storage backend cannot be determined</li> <li>• "failed" - The storage backend is in an unavailable state</li> </ul>
stateDesired	string	False	<p>JSON string containing a value indicating the desired operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "running" - The storage backend will be in a normal running state</li> </ul>
stateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is unable to transition to "running", why it has transitioned to "failed" or "unknown", and/or why it is at risk of transitioning to "failed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>

Name	Type	Required	Description
managedState	string	False	<p>JSON string containing a value indicating the management state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The storage backend is scheduled to be discovered or added</li> <li>• "unmanaged" - The storage backend is in a "discovered" state, is not under management, and is eligible for management</li> <li>• "managed" - The storage backend is in a "running" or "unknown" state and is under management</li> </ul>
managedStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why the storage backend is ineligible to be managed. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> <li>• "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity)</li> <li>• "normal" - The resource has no known issues and can provide services in accordance with the interface specification</li> <li>• "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification</li> <li>• "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification</li> </ul>
healthStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is not in a normal health state. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>



Name	Type	Required	Description
protectionState	string	False	<p>JSON string containing a value indicating the protection state of the storage backend. "unknown" for ONTAP. Defined values are:</p> <ul style="list-style-type: none"> <li>• "protected" - The storage backend has a protection policy defined and is in conformance with that policy</li> <li>• "partial" - The storage backend has a protection policy defined but is out of conformance with that policy</li> <li>• "none" - The storage backend is not protected</li> <li>• "unknown" - The storage backend protection policy conformance cannot be determined</li> <li>• enum: ["protected", "partial", "none", "unknown"]</li> <li>• example: protected</li> </ul>
protectionStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a protection policy is out of conformance. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>

Name	Type	Required	Description
ontap	ontap	False	<p>JSON object containing specific information related to ONTAP clusters.</p> <ul style="list-style-type: none"> <li>additionalProperties: false</li> </ul>
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

### Example request

```
{
  "type": "application/astra-storageBackend",
  "version": "1.2",
  "backendName": "st1-46"
}
```

### Response

Status: 204, Indicates if the storageBackend resource was updated.

### Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

# Definitions

## See Definitions

ontap

JSON object containing specific information related to ONTAP clusters.

Name	Type	Required	Description
backendManagementIP	string	False	JSON string containing the IP address used to connect to this ONTAP cluster.
managementIPs	array[string]	False	JSON array of JSON strings containing the list of all possible management IPs used to connect to this ONTAP cluster. This is used to correlate backends detected through Trident and storage backends in Astra.  • <code>uniqueItems: 1</code>

type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

## Delete a storage backend

DELETE /accounts/{account\_id}/topology/v1/storageBackends/{storageBackend\_id}

Removes the specified Storage Backend API resource.

### Side Effects

- All backendConfig resources associated with the storage backend are removed.
- All backendNode resources associated with the storage backend are removed.
- The storage backend might be removed.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>• example: <code>{{.Account}}</code></li> </ul>
storageBackend_id	string	path	True	ID of the storageBackend collection to list

### Response



Status: 204, Indicates if the storageBackend resource was deleted.

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

## Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	False	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

### See Definitions

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Copyright-Informationen

Copyright © 2024 NetApp. Alle Rechte vorbehalten. Gedruckt in den USA. Dieses urheberrechtlich geschützte Dokument darf ohne die vorherige schriftliche Genehmigung des Urheberrechtinhabers in keiner Form und durch keine Mittel – weder grafische noch elektronische oder mechanische, einschließlich Fotokopieren, Aufnehmen oder Speichern in einem elektronischen Abrufsystem – auch nicht in Teilen, vervielfältigt werden.

Software, die von urheberrechtlich geschütztem NetApp Material abgeleitet wird, unterliegt der folgenden Lizenz und dem folgenden Haftungsausschluss:

DIE VORLIEGENDE SOFTWARE WIRD IN DER VORLIEGENDEN FORM VON NETAPP ZUR VERFÜGUNG GESTELLT, D. H. OHNE JEGLICHE EXPLIZITE ODER IMPLIZITE GEWÄHRLEISTUNG, EINSCHLIESSLICH, JEDOCH NICHT BESCHRÄNKT AUF DIE STILLSCHWEIGENDE GEWÄHRLEISTUNG DER MARKTGÄNGIGKEIT UND EIGNUNG FÜR EINEN BESTIMMTEN ZWECK, DIE HIERMIT AUSGESCHLOSSEN WERDEN. NETAPP ÜBERNIMMT KEINERLEI HAFTUNG FÜR DIREKTE, INDIREKTE, ZUFÄLLIGE, BESONDERE, BEISPIELHAFT SCHÄDEN ODER FOLGESCHÄDEN (EINSCHLIESSLICH, JEDOCH NICHT BESCHRÄNKT AUF DIE BESCHAFFUNG VON ERSATZWAREN ODER -DIENSTLEISTUNGEN, NUTZUNGS-, DATEN- ODER GEWINNVERLUSTE ODER UNTERBRECHUNG DES GESCHÄFTSBETRIEBS), UNABHÄNGIG DAVON, WIE SIE VERURSACHT WURDEN UND AUF WELCHER HAFTUNGSTHEORIE SIE BERUHEN, OB AUS VERTRAGLICH FESTGELEGTER HAFTUNG, VERSCHULDENSUNABHÄNGIGER HAFTUNG ODER DELIKTSHAFTUNG (EINSCHLIESSLICH FAHRLÄSSIGKEIT ODER AUF ANDEREM WEGE), DIE IN IRGEND EINER WEISE AUS DER NUTZUNG DIESER SOFTWARE RESULTIEREN, SELBST WENN AUF DIE MÖGLICHKEIT DERARTIGER SCHÄDEN HINGEWIESEN WURDE.

NetApp behält sich das Recht vor, die hierin beschriebenen Produkte jederzeit und ohne Vorankündigung zu ändern. NetApp übernimmt keine Verantwortung oder Haftung, die sich aus der Verwendung der hier beschriebenen Produkte ergibt, es sei denn, NetApp hat dem ausdrücklich in schriftlicher Form zugestimmt. Die Verwendung oder der Erwerb dieses Produkts stellt keine Lizenzierung im Rahmen eines Patentrechts, Markenrechts oder eines anderen Rechts an geistigem Eigentum von NetApp dar.

Das in diesem Dokument beschriebene Produkt kann durch ein oder mehrere US-amerikanische Patente, ausländische Patente oder anhängige Patentanmeldungen geschützt sein.

ERLÄUTERUNG ZU „RESTRICTED RIGHTS“: Nutzung, Vervielfältigung oder Offenlegung durch die US-Regierung unterliegt den Einschränkungen gemäß Unterabschnitt (b)(3) der Klausel „Rights in Technical Data – Noncommercial Items“ in DFARS 252.227-7013 (Februar 2014) und FAR 52.227-19 (Dezember 2007).

Die hierin enthaltenen Daten beziehen sich auf ein kommerzielles Produkt und/oder einen kommerziellen Service (wie in FAR 2.101 definiert) und sind Eigentum von NetApp, Inc. Alle technischen Daten und die Computersoftware von NetApp, die unter diesem Vertrag bereitgestellt werden, sind gewerblicher Natur und wurden ausschließlich unter Verwendung privater Mittel entwickelt. Die US-Regierung besitzt eine nicht ausschließliche, nicht übertragbare, nicht unterlizenzierbare, weltweite, limitierte unwiderrufliche Lizenz zur Nutzung der Daten nur in Verbindung mit und zur Unterstützung des Vertrags der US-Regierung, unter dem die Daten bereitgestellt wurden. Sofern in den vorliegenden Bedingungen nicht anders angegeben, dürfen die Daten ohne vorherige schriftliche Genehmigung von NetApp, Inc. nicht verwendet, offengelegt, vervielfältigt, geändert, aufgeführt oder angezeigt werden. Die Lizenzrechte der US-Regierung für das US-Verteidigungsministerium sind auf die in DFARS-Klausel 252.227-7015(b) (Februar 2014) genannten Rechte beschränkt.

## Markeninformationen

NETAPP, das NETAPP Logo und die unter <http://www.netapp.com/TM> aufgeführten Marken sind Marken von NetApp, Inc. Andere Firmen und Produktnamen können Marken der jeweiligen Eigentümer sein.