



# Application Snapshot

## Astra Automation

NetApp  
December 01, 2023

# Inhalt

- Application Snapshot ..... 1
  - Application Snapshot overview ..... 1
  - Create a new application snapshot for an app ..... 1
  - List the application snapshots for an app ..... 12
  - Retrieve an application snapshot ..... 22
  - Delete an application snapshot ..... 30

# Application Snapshot

## Application Snapshot overview

The Application Snapshot API enables a user to create and view snapshots of a managed application.

## Create a new application snapshot for an app

POST /accounts/{account\_id}/k8s/v1/apps/{app\_id}/appSnaps

Indicates the desired values for the Application Snapshot API resource to be created.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"><li>example: <code>{{.Account}}</code></li></ul>
app_id	string	path	True	ID of the containing app resource

### Request Body

Indicates the desired values for the Application Snapshot API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>"application/astra-appSnap"</li></ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"><li>"1.0"</li><li>"1.1"</li><li>"1.2"</li></ul>

Name	Type	Required	Description
name	string	False	<p>JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system assigns a name for the snapshot. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• Conforms to the DNS 1123 Label Schema</li> </ul>
metadata	<a href="#">type_astra_metadata</a>	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels.</li> </ul>

### Example request

```
{
  "type": "application/astra-appSnap",
  "version": "1.2",
  "name": "app-name-245"
}
```

### Response

Status: 201, Returns the newly created appSnap resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "application/astra-appSnap"</li> </ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
name	string	True	JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system assigns a name for the snapshot. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• Conforms to the DNS 1123 Label Schema</li> </ul>

Name	Type	Required	Description
scheduleID	string	False	<p>JSON string containing an optional schedule ID that indicates that the snapshot was triggered by a schedule and specifies which schedule triggered the snapshot. Only present for snapshots initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>
snapshotAppAsset	string	False	<p>JSON string containing the ID of the application asset corresponding to the snapshot. This field will be returned when the state of the application snapshot is "completed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the snapshot. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The application snapshot is scheduled for discovery</li> <li>• "discovering" - The application snapshot is in the process of being discovered</li> <li>• "running" - The application snapshot is running normally</li> <li>• "completed" - The application snapshot has completed</li> <li>• "failed" - The application snapshot is in a permanent failure state</li> <li>• "removed" - The application snapshot is not currently accessible</li> <li>• "unknown" - The application snapshot state cannot be determined</li> </ul>
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application snapshot is unable to transition to "running", or why it has transitioned to "failed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>

Name	Type	Required	Description
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hook or hooks running as a part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> <li>• "failed" - One or more execution hooks have failed</li> <li>• "success" - There were zero or more applicable hooks and all were successful</li> </ul>
hookStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> <li>• Minimum items: 0</li> </ul>
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.</li> </ul>



## Example response

```
{
  "type": "application/astra-appSnap",
  "version": "1.2",
  "id": "4f56a1df-8f47-541a-bd81-77260053a2f6",
  "name": "app-name-245",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

### Definitions

## See Definitions

### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

### type\_astra\_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

### type\_astra\_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

### invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field

Name	Type	Required	Description
reason	string	True	Reason why the request body field is invalid

## List the application snapshots for an app

GET /accounts/{account\_id}/k8s/v1/apps/{app\_id}/appSnaps

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource  • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection.  URL examples: "include=id", "include=id,name"  OpenAPI examples: "id"  • example: id,name,state

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection.  URL examples: "limit=2"  OpenAPI examples: "2"

## Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: <a href="#">appSnap_1.2_get_response_body</a> , array[]]	True	
metadata	<a href="#">type_astra_metadata_list</a>	True	

## Example response

```
{
  "type": "application/astra-appSnaps",
  "version": "1.2",
  "items": [
    [
      "2b6dafc3-2172-4431-a482-6306b2703130",
      "app-name-245",
      "pending"
    ],
    [
      "6fd9b31a-3924-4c9a-878b-175fa9538b8c",
      "app-name-244",
      "completed"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	



### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

# Definitions

## See Definitions

### type\_astra\_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

### type\_astra\_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

### appSnap\_1.2\_get\_response\_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-appSnap"</li></ul>

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
name	string	True	JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system assigns a name for the snapshot. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• Conforms to the DNS 1123 Label Schema</li> </ul>
scheduleID	string	False	JSON string containing an optional schedule ID that indicates that the snapshot was triggered by a schedule and specifies which schedule triggered the snapshot. Only present for snapshots initiated by a schedule. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>

Name	Type	Required	Description
snapshotAppAsset	string	False	<p>JSON string containing the ID of the application asset corresponding to the snapshot. This field will be returned when the state of the application snapshot is "completed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>
state	string	True	<p>JSON string containing a value indicating the operational state of the snapshot. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The application snapshot is scheduled for discovery</li> <li>• "discovering" - The application snapshot is in the process of being discovered</li> <li>• "running" - The application snapshot is running normally</li> <li>• "completed" - The application snapshot has completed</li> <li>• "failed" - The application snapshot is in a permanent failure state</li> <li>• "removed" - The application snapshot is not currently accessible</li> <li>• "unknown" - The application snapshot state cannot be determined</li> </ul>

Name	Type	Required	Description
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application snapshot is unable to transition to "running", or why it has transitioned to "failed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hook or hooks running as a part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> <li>• "failed" - One or more execution hooks have failed</li> <li>• "success" - There were zero or more applicable hooks and all were successful</li> </ul>
hookStateDetails	array[type_astra_stateDe tail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> <li>• Minimum items: 0</li> </ul>

Name	Type	Required	Description
metadata	<a href="#">type_astra_metadata</a>	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.</li> </ul>

#### type\_astra\_metadata\_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Retrieve an application snapshot

GET /accounts/{account\_id}/k8s/v1/apps/{app\_id}/appSnaps/{appSnap\_id}

Returns the stored Application Snapshot API resource in the JSON response body.



## Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"><li>example: {{.Account}}</li></ul>
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the appSnap collection to list

## Response

Status: 200, Returns the stored Application Snapshot API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>"application/astra-appSnap"</li></ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"><li>"1.0"</li><li>"1.1"</li><li>"1.2"</li></ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>Conforms to the UUIDv4 Schema</li></ul>

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system assigns a name for the snapshot. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• Conforms to the DNS 1123 Label Schema</li> </ul>
scheduleID	string	False	<p>JSON string containing an optional schedule ID that indicates that the snapshot was triggered by a schedule and specifies which schedule triggered the snapshot. Only present for snapshots initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>
snapshotAppAsset	string	False	<p>JSON string containing the ID of the application asset corresponding to the snapshot. This field will be returned when the state of the application snapshot is "completed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the snapshot. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The application snapshot is scheduled for discovery</li> <li>• "discovering" - The application snapshot is in the process of being discovered</li> <li>• "running" - The application snapshot is running normally</li> <li>• "completed" - The application snapshot has completed</li> <li>• "failed" - The application snapshot is in a permanent failure state</li> <li>• "removed" - The application snapshot is not currently accessible</li> <li>• "unknown" - The application snapshot state cannot be determined</li> </ul>
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application snapshot is unable to transition to "running", or why it has transitioned to "failed". Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>

Name	Type	Required	Description
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hook or hooks running as a part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> <li>• "failed" - One or more execution hooks have failed</li> <li>• "success" - There were zero or more applicable hooks and all were successful</li> </ul>
hookStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> <li>• Minimum items: 0</li> </ul>
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.</li> </ul>

## Example response

```
{
  "type": "application/astra-appSnap",
  "version": "1.2",
  "id": "4f56a1df-8f47-541a-bd81-77260053a2f6",
  "name": "app-name-245",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

### type\_astra\_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

### type\_astra\_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Delete an application snapshot

DELETE /accounts/{account\_id}/k8s/v1/apps/{app\_id}/appSnaps/{appSnap\_id}

Removes the specified Application Snapshot API resource.



## Side Effects

- If a snapshot is in progress, the snapshot is cancelled.
- If a snapshot is complete, the snapshot data is deleted.

## Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource  • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the appSnap collection to list

## Response

Status: 204, Indicates if the appSnap resource was deleted.

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/144",
  "title": "Backup in progress",
  "detail": "The snapshot wasn't deleted because it is currently being
  used by a backup.",
  "status": "409"
}
```

## Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

### See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Copyright-Informationen

Copyright © 2023 NetApp. Alle Rechte vorbehalten. Gedruckt in den USA. Dieses urheberrechtlich geschützte Dokument darf ohne die vorherige schriftliche Genehmigung des Urheberrechtinhabers in keiner Form und durch keine Mittel – weder grafische noch elektronische oder mechanische, einschließlich Fotokopieren, Aufnehmen oder Speichern in einem elektronischen Abrufsystem – auch nicht in Teilen, vervielfältigt werden.

Software, die von urheberrechtlich geschütztem NetApp Material abgeleitet wird, unterliegt der folgenden Lizenz und dem folgenden Haftungsausschluss:

DIE VORLIEGENDE SOFTWARE WIRD IN DER VORLIEGENDEN FORM VON NETAPP ZUR VERFÜGUNG GESTELLT, D. H. OHNE JEGLICHE EXPLIZITE ODER IMPLIZITE GEWÄHRLEISTUNG, EINSCHLIESSLICH, JEDOCH NICHT BESCHRÄNKT AUF DIE STILLSCHWEIGENDE GEWÄHRLEISTUNG DER MARKTGÄNGIGKEIT UND EIGNUNG FÜR EINEN BESTIMMTEN ZWECK, DIE HIERMIT AUSGESCHLOSSEN WERDEN. NETAPP ÜBERNIMMT KEINERLEI HAFTUNG FÜR DIREKTE, INDIREKTE, ZUFÄLLIGE, BESONDERE, BEISPIELHAFT SCHÄDEN ODER FOLGESCHÄDEN (EINSCHLIESSLICH, JEDOCH NICHT BESCHRÄNKT AUF DIE BESCHAFFUNG VON ERSATZWAREN ODER -DIENSTLEISTUNGEN, NUTZUNGS-, DATEN- ODER GEWINNVERLUSTE ODER UNTERBRECHUNG DES GESCHÄFTSBETRIEBS), UNABHÄNGIG DAVON, WIE SIE VERURSACHT WURDEN UND AUF WELCHER HAFTUNGSTHEORIE SIE BERUHEN, OB AUS VERTRAGLICH FESTGELEGTER HAFTUNG, VERSCHULDENSUNABHÄNGIGER HAFTUNG ODER DELIKTSHAFTUNG (EINSCHLIESSLICH FAHRLÄSSIGKEIT ODER AUF ANDEREM WEGE), DIE IN IRGEND EINER WEISE AUS DER NUTZUNG DIESER SOFTWARE RESULTIEREN, SELBST WENN AUF DIE MÖGLICHKEIT DERARTIGER SCHÄDEN HINGEWIESEN WURDE.

NetApp behält sich das Recht vor, die hierin beschriebenen Produkte jederzeit und ohne Vorankündigung zu ändern. NetApp übernimmt keine Verantwortung oder Haftung, die sich aus der Verwendung der hier beschriebenen Produkte ergibt, es sei denn, NetApp hat dem ausdrücklich in schriftlicher Form zugestimmt. Die Verwendung oder der Erwerb dieses Produkts stellt keine Lizenzierung im Rahmen eines Patentrechts, Markenrechts oder eines anderen Rechts an geistigem Eigentum von NetApp dar.

Das in diesem Dokument beschriebene Produkt kann durch ein oder mehrere US-amerikanische Patente, ausländische Patente oder anhängige Patentanmeldungen geschützt sein.

ERLÄUTERUNG ZU „RESTRICTED RIGHTS“: Nutzung, Vervielfältigung oder Offenlegung durch die US-Regierung unterliegt den Einschränkungen gemäß Unterabschnitt (b)(3) der Klausel „Rights in Technical Data – Noncommercial Items“ in DFARS 252.227-7013 (Februar 2014) und FAR 52.227-19 (Dezember 2007).

Die hierin enthaltenen Daten beziehen sich auf ein kommerzielles Produkt und/oder einen kommerziellen Service (wie in FAR 2.101 definiert) und sind Eigentum von NetApp, Inc. Alle technischen Daten und die Computersoftware von NetApp, die unter diesem Vertrag bereitgestellt werden, sind gewerblicher Natur und wurden ausschließlich unter Verwendung privater Mittel entwickelt. Die US-Regierung besitzt eine nicht ausschließliche, nicht übertragbare, nicht unterlizenzierbare, weltweite, limitierte unwiderrufliche Lizenz zur Nutzung der Daten nur in Verbindung mit und zur Unterstützung des Vertrags der US-Regierung, unter dem die Daten bereitgestellt wurden. Sofern in den vorliegenden Bedingungen nicht anders angegeben, dürfen die Daten ohne vorherige schriftliche Genehmigung von NetApp, Inc. nicht verwendet, offengelegt, vervielfältigt, geändert, aufgeführt oder angezeigt werden. Die Lizenzrechte der US-Regierung für das US-Verteidigungsministerium sind auf die in DFARS-Klausel 252.227-7015(b) (Februar 2014) genannten Rechte beschränkt.

## Markeninformationen

NETAPP, das NETAPP Logo und die unter <http://www.netapp.com/TM> aufgeführten Marken sind Marken von NetApp, Inc. Andere Firmen und Produktnamen können Marken der jeweiligen Eigentümer sein.