



# Setting

## Astra Automation

NetApp  
March 17, 2024

This PDF was generated from [https://docs.netapp.com/es-es/astra-automation/reference/setting\\_overview.html](https://docs.netapp.com/es-es/astra-automation/reference/setting_overview.html) on March 17, 2024. Always check docs.netapp.com for the latest.

# Tabla de contenidos

- Setting ..... 1
  - Setting overview ..... 1
  - List all settings ..... 1
  - Retrieve a setting ..... 14
  - Modify a setting ..... 25

# Setting

## Setting overview

An account setting is a collection of key/value pairs that are important for a known feature in an Astra account. The Setting API provides access to important information about an account setting.

## List all settings

GET `/accounts/{account_id}/core/v1/settings`

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

### Parameters

| Name       | Type   | In    | Required | Description  |
|------------|--------|-------|----------|--|
| account_id | string | path  | True     | ID of the containing account resource<br><br>• example:<br>{{.Account}}  |
| include    | string | query | False    | Indicates which fields should be returned when listing a collection.<br><br>URL examples:<br>"include=id",<br>"include=id,name"<br><br>OpenAPI examples:<br>"id" |
| limit      | string | query | False    | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples:<br>"limit=2"<br><br>OpenAPI examples:<br>"2"                 |

| Name    | Type   | In    | Required | Description  |
|---------|--------|-------|----------|--|
| filter  | string | query | False    | <p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> <li>• eq - Equality</li> <li>• lt/gt - Less than/Greater than</li> <li>• lte/gte - Less than or equals to/Greater than or equals to</li> </ul> <p>URL example:<br/>"filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples:<br/>"field eq 'value'"</p> |
| count   | string | query | False    | <p>Indicates if the total number of resources should be returned in the metadata object.</p> <p>URL examples:<br/>"count=true"</p> <p>OpenAPI examples:<br/>"true"</p>   |
| orderBy | string | query | False    | <p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples:<br/>"orderBy=name",<br/>"orderBy=name%20desc"</p> <p>OpenAPI examples:<br/>"name desc"</p>   |

| Name | Type   | In    | Required | Description   |
|------|--------|-------|----------|---|
| skip | string | query | False    | <p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples:<br/>"skip=1"</p> <p>OpenAPI examples:<br/>"1"</p> |

## Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name     | Type   | Required | Description |
|----------|--|----------|-------------|
| items    | array[Any of: <a href="#">setting_1.1_get_response_body</a> , array[]] | True     |             |
| metadata | <a href="#">type_astra_metadata_list</a>                               | True     |             |

## Example response

```
{
  "type": "application/astra-settings",
  "version": "1.1",
  "items": [
    {
      "type": "application/astra-setting",
      "version": "1.0",
      "id": "5da0a2ed-c51d-4d91-8b98-ed3aa8a88cc5",
      "name": "astra.account.smtp",
      "currentConfig": {
        "credential": "",
        "isEnabled": "false",
        "port": 587,
        "relayServer": "smtp.sendgrid.net"
      },
      "configSchema": {
        "$schema": "http://json-schema.org/draft-07/schema#",
        "title": "astra.account.smtp",
        "type": "object",
        "properties": {
          "credential": {
            "type": "string",
            "description": "The credential ID for SMTP authentication."
          },
          "isEnabled": {
            "type": "string",
            "description": "This property determines if this setting is
enabled or not."
          },
          "port": {
            "type": "integer",
            "description": "The SMTP port. For an unencrypted or a TLS
connection, use port 25, 2525, or 587."
          },
          "relayServer": {
            "type": "string",
            "description": "This setting is sometimes referred to as
the external SMTP server or the SMTP relay."
          }
        },
        "additionalProperties": false,
        "required": [
          "relayServer",
          "port",
```

```

        "isEnabled"
      ]
    },
    "state": "valid",
    "stateUnready": [],
    "metadata": {
      "labels": [],
      "creationTimestamp": "2021-06-04T20:14:52Z",
      "modificationTimestamp": "2021-06-04T20:14:52Z",
      "createdBy": "c9550bbb-e70b-4578-8504-07397f875bcb",
      "modifiedBy": "65e1571b-1b46-4f05-95b0-7d7f5a93da6a"
    }
  }
],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden



| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Response

Status: 503, Service unavailable

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

## Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

### type\_json

JSON object containing keys and values that make up the current configuration for this setting. The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.

### type\_json

JSON object containing keys and values that make up the requested configuration for this setting. The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration.

### properties

### type\_json\_schema

JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7. If config values are present in the resource, validation against the indicated configSchema is mandatory. As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").

| Name                 | Type                       | Required | Description |
|----------------------|----------------------------|----------|-------------|
| \$schema             | string                     | True     |             |
| type                 | string                     | True     |             |
| properties           | <a href="#">properties</a> | True     |             |
| additionalProperties | boolean                    | True     |             |
| required             | array[string]              | True     |             |

### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name   | Type                                      | Required | Description |
|--------|---|----------|-------------|
| labels | array[ <a href="#">type_astra_label</a> ] | False    |             |

| Name                  | Type   | Required | Description |
|-----------------------|--------|----------|-------------|
| creationTimestamp     | string | False    |             |
| modificationTimestamp | string | False    |             |
| createdBy             | string | False    |             |
| modifiedBy            | string | False    |             |

#### setting\_1.1\_get\_response\_body

| Name    | Type   | Required | Description   |
|---------|--------|----------|---|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>"application/astra-setting"</li> </ul>                   |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>"1.0"</li> <li>"1.1"</li> </ul>                             |
| id      | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>Conforms to the UUIDv4 Schema</li> </ul> |

| Name          | Type      | Required | Description   |
|---------------|-----------|----------|---|
| name          | string    | True     | <p>JSON string containing a name for the setting, in hierarchal dot notation (.). Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. This value is specified by the configmap that is loaded at runtime and cannot be updated by the user.</li> </ul> |
| currentConfig | type_json | True     | <p>JSON object containing keys and values that make up the current configuration for this setting. The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.</p>   |

| Name          | Type                             | Required | Description   |
|---------------|----------------------------------|----------|---|
| desiredConfig | <a href="#">type_json</a>        | False    | JSON object containing keys and values that make up the requested configuration for this setting. The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration. |
| configSchema  | <a href="#">type_json_schema</a> | True     | JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7. If config values are present in the resource, validation against the indicated configSchema is mandatory. As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").  |

| Name         | Type                                       | Required | Description   |
|--------------|--|----------|---|
| state        | string                                     | True     | <p>JSON string containing a value indicating the operational state of the application. Defined values are:</p> <ul style="list-style-type: none"> <li>"valid" - The current configuration matches the desired config.</li> <li>"pending" - The desired configuration is being applied.</li> <li>"error" - The desired configuration cannot be applied.</li> </ul> |
| stateUnready | array[string]                              | True     | <p>JSON array of JSON strings, each indicating a reason why the setting was not successfully applied. Defined values are:</p> <ul style="list-style-type: none"> <li>Minimum length: 1</li> <li>Maximum length: 127</li> </ul>  |
| metadata     | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>  |

[type\\_astra\\_metadata\\_list](#)

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| continue              | string                  | False    |             |
| count                 | number                  | False    |             |
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

## Retrieve a setting

GET /accounts/{account\_id}/core/v1/settings/{setting\_id}

Returns the stored Setting API resource in the JSON response body.

### Parameters

| Name       | Type   | In   | Required | Description  |
|------------|--------|------|----------|--|
| account_id | string | path | True     | ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul> |
| setting_id | string | path | True     | ID of the setting collection to list   |

### Response

Status: 200, Returns the stored Setting API resource in the JSON response body.



| Name    | Type   | Required | Description  |
|---------|--------|----------|--|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "application/astra-setting"</li> </ul>  |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> </ul>  |
| id      | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>  |
| name    | string | True     | JSON string containing a name for the setting, in hierarchal dot notation (.). Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. This value is specified by the configmap that is loaded at runtime and cannot be updated by the user.</li> </ul> |

| Name          | Type                      | Required | Description   |
|---------------|---------------------------|----------|---|
| currentConfig | <a href="#">type_json</a> | True     | JSON object containing keys and values that make up the current configuration for this setting. The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.  |
| desiredConfig | <a href="#">type_json</a> | False    | JSON object containing keys and values that make up the requested configuration for this setting. The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration. |

| Name         | Type                             | Required | Description  |
|--------------|----------------------------------|----------|--|
| configSchema | <a href="#">type_json_schema</a> | True     | JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7. If config values are present in the resource, validation against the indicated configSchema is mandatory. As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false"). |
| state        | string                           | True     | <p>JSON string containing a value indicating the operational state of the application. Defined values are:</p> <ul style="list-style-type: none"> <li>• "valid" - The current configuration matches the desired config.</li> <li>• "pending" - The desired configuration is being applied.</li> <li>• "error" - The desired configuration cannot be applied.</li> </ul>  |
| stateUnready | array[string]                    | True     | <p>JSON array of JSON strings, each indicating a reason why the setting was not successfully applied. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>   |

| Name     | Type                                       | Required | Description   |
|----------|--|----------|---|
| metadata | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

## Example response

```
{
  "type": "application/astra-setting",
  "version": "1.1",
  "id": "ea510866-47d3-5130-8468-563df4cd6a28",
  "name": "astra.account.smtp",
  "currentConfig": {
    "credential": "",
    "isEnabled": "false",
    "port": 587,
    "relayServer": "smtp.sendgrid.net"
  },
  "configSchema": {
    "$schema": "http://json-schema.org/draft-07/schema#",
    "title": "astra.account.smtp",
    "type": "object",
    "properties": {
      "credential": {
        "type": "string",
        "description": "The credential ID for SMTP authentication."
      },
      "isEnabled": {
        "type": "string",
        "description": "This property determines if this setting is
enabled or not."
      },
      "port": {
        "type": "integer",
        "description": "The SMTP port. For an unencrypted or a TLS
connection, use port 25, 2525, or 587."
      },
      "relayServer": {
        "type": "string",
        "description": "This setting is sometimes referred to as the
external SMTP server or the SMTP relay."
      }
    },
    "additionalProperties": false,
    "required": [
      "relayServer",
      "port",
      "isEnabled"
    ]
  },
  "state": "valid",
}
```

```

"stateUnready": [],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

## Example response

```

{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}

```

## Response

Status: 400, Bad request

| Name   | Type   | Required | Description |
|--------|--------|----------|-------------|
| type   | string | True     |             |
| title  | string | True     |             |
| detail | string | True     |             |

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Response

Status: 503, Service unavailable

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

## Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |



### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

### Definitions

## See Definitions

### type\_json

JSON object containing keys and values that make up the current configuration for this setting. The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.

### type\_json

JSON object containing keys and values that make up the requested configuration for this setting. The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration.

### properties

### type\_json\_schema

JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7. If config values are present in the resource, validation against the indicated configSchema is mandatory. As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").

| Name                 | Type                       | Required | Description |
|----------------------|----------------------------|----------|-------------|
| \$schema             | string                     | True     |             |
| type                 | string                     | True     |             |
| properties           | <a href="#">properties</a> | True     |             |
| additionalProperties | boolean                    | True     |             |
| required             | array[string]              | True     |             |

### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name   | Type                                      | Required | Description |
|--------|---|----------|-------------|
| labels | array[ <a href="#">type_astra_label</a> ] | False    |             |

| Name                  | Type   | Required | Description |
|-----------------------|--------|----------|-------------|
| creationTimestamp     | string | False    |             |
| modificationTimestamp | string | False    |             |
| createdBy             | string | False    |             |
| modifiedBy            | string | False    |             |

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

## Modify a setting

PUT /accounts/{account\_id}/core/v1/settings/{setting\_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Parameters

| Name       | Type   | In   | Required | Description  |
|------------|--------|------|----------|--|
| account_id | string | path | True     | ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul> |
| setting_id | string | path | True     | ID of the setting collection to list   |

### Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

| Name    | Type   | Required | Description  |
|---------|--------|----------|--|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "application/astra-setting"</li> </ul>  |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> </ul>  |
| id      | string | False    | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>  |
| name    | string | False    | JSON string containing a name for the setting, in hierarchal dot notation (.). Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. This value is specified by the configmap that is loaded at runtime and cannot be updated by the user.</li> </ul> |

| Name          | Type                      | Required | Description   |
|---------------|---------------------------|----------|---|
| currentConfig | <a href="#">type_json</a> | False    | JSON object containing keys and values that make up the current configuration for this setting. The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.  |
| desiredConfig | <a href="#">type_json</a> | False    | JSON object containing keys and values that make up the requested configuration for this setting. The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration. |

| Name         | Type                             | Required | Description  |
|--------------|----------------------------------|----------|--|
| configSchema | <a href="#">type_json_schema</a> | False    | JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7. If config values are present in the resource, validation against the indicated configSchema is mandatory. As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false"). |
| state        | string                           | False    | <p>JSON string containing a value indicating the operational state of the application. Defined values are:</p> <ul style="list-style-type: none"> <li>• "valid" - The current configuration matches the desired config.</li> <li>• "pending" - The desired configuration is being applied.</li> <li>• "error" - The desired configuration cannot be applied.</li> </ul>  |
| stateUnready | array[string]                    | False    | <p>JSON array of JSON strings, each indicating a reason why the setting was not successfully applied. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 127</li> </ul>   |

| Name     | Type                       | Required | Description  |
|----------|----------------------------|----------|--|
| metadata | type_astra_metadata_update | False    | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

### Example request

```
{
  "type": "application/astra-setting",
  "version": "1.1",
  "desiredConfig": {
    "credential": "e3d2ea77-398e-49be-85fd-ec66d9426a06",
    "port": 587,
    "relayServer": "<a href="
http://smtp.sendgrid.net">smtp.sendgrid.net</a>",
    "isEnabled": "true"
  }
}
```

### Response

Status: 204, Indicates if the setting resource was updated.

### Response

Status: 401, Unauthorized

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| type  | string | True     |             |
| title | string | True     |             |

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```



## Response

Status: 409, Conflict

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

## Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Response

Status: 503, Service unavailable

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

## Error

Status: 404, Not found

| Name   | Type   | Required | Description |
|--------|--------|----------|-------------|
| type   | string | True     |             |
| title  | string | True     |             |
| detail | string | True     |             |

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

### type\_json

JSON object containing keys and values that make up the current configuration for this setting. The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.

### type\_json

JSON object containing keys and values that make up the requested configuration for this setting. The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration.

### properties

### type\_json\_schema

JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7. If config values are present in the resource, validation against the indicated configSchema is mandatory. As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").

| Name                 | Type                       | Required | Description |
|----------------------|----------------------------|----------|-------------|
| \$schema             | string                     | True     |             |
| type                 | string                     | True     |             |
| properties           | <a href="#">properties</a> | True     |             |
| additionalProperties | boolean                    | True     |             |
| required             | array[string]              | True     |             |

### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name   | Type                                      | Required | Description |
|--------|---|----------|-------------|
| labels | array[ <a href="#">type_astra_label</a> ] | False    |             |

| Name                  | Type   | Required | Description |
|-----------------------|--------|----------|-------------|
| creationTimestamp     | string | False    |             |
| modificationTimestamp | string | False    |             |
| createdBy             | string | False    |             |
| modifiedBy            | string | False    |             |

#### invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

#### invalidFields

| Name   | Type   | Required | Description                                  |
|--------|--------|----------|--|
| name   | string | True     | Name of the invalid request body field       |
| reason | string | True     | Reason why the request body field is invalid |

## Información de copyright

Copyright © 2024 NetApp, Inc. Todos los derechos reservados. Imprimido en EE. UU. No se puede reproducir este documento protegido por copyright ni parte del mismo de ninguna forma ni por ningún medio (gráfico, electrónico o mecánico, incluidas fotocopias, grabaciones o almacenamiento en un sistema de recuperación electrónico) sin la autorización previa y por escrito del propietario del copyright.

El software derivado del material de NetApp con copyright está sujeto a la siguiente licencia y exención de responsabilidad:

ESTE SOFTWARE LO PROPORCIONA NETAPP «TAL CUAL» Y SIN NINGUNA GARANTÍA EXPRESA O IMPLÍCITA, INCLUYENDO, SIN LIMITAR, LAS GARANTÍAS IMPLÍCITAS DE COMERCIALIZACIÓN O IDONEIDAD PARA UN FIN CONCRETO, CUYA RESPONSABILIDAD QUEDA EXIMIDA POR EL PRESENTE DOCUMENTO. EN NINGÚN CASO NETAPP SERÁ RESPONSABLE DE NINGÚN DAÑO DIRECTO, INDIRECTO, ESPECIAL, EJEMPLAR O RESULTANTE (INCLUYENDO, ENTRE OTROS, LA OBTENCIÓN DE BIENES O SERVICIOS SUSTITUTIVOS, PÉRDIDA DE USO, DE DATOS O DE BENEFICIOS, O INTERRUPCIÓN DE LA ACTIVIDAD EMPRESARIAL) CUALQUIERA SEA EL MODO EN EL QUE SE PRODUJERON Y LA TEORÍA DE RESPONSABILIDAD QUE SE APLIQUE, YA SEA EN CONTRATO, RESPONSABILIDAD OBJETIVA O AGRAVIO (INCLUIDA LA NEGLIGENCIA U OTRO TIPO), QUE SURJAN DE ALGÚN MODO DEL USO DE ESTE SOFTWARE, INCLUSO SI HUBIEREN SIDO ADVERTIDOS DE LA POSIBILIDAD DE TALES DAÑOS.

NetApp se reserva el derecho de modificar cualquiera de los productos aquí descritos en cualquier momento y sin aviso previo. NetApp no asume ningún tipo de responsabilidad que surja del uso de los productos aquí descritos, excepto aquello expresamente acordado por escrito por parte de NetApp. El uso o adquisición de este producto no lleva implícita ninguna licencia con derechos de patente, de marcas comerciales o cualquier otro derecho de propiedad intelectual de NetApp.

Es posible que el producto que se describe en este manual esté protegido por una o más patentes de EE. UU., patentes extranjeras o solicitudes pendientes.

LEYENDA DE DERECHOS LIMITADOS: el uso, la copia o la divulgación por parte del gobierno están sujetos a las restricciones establecidas en el subpárrafo (b)(3) de los derechos de datos técnicos y productos no comerciales de DFARS 252.227-7013 (FEB de 2014) y FAR 52.227-19 (DIC de 2007).

Los datos aquí contenidos pertenecen a un producto comercial o servicio comercial (como se define en FAR 2.101) y son propiedad de NetApp, Inc. Todos los datos técnicos y el software informático de NetApp que se proporcionan en este Acuerdo tienen una naturaleza comercial y se han desarrollado exclusivamente con fondos privados. El Gobierno de EE. UU. tiene una licencia limitada, irrevocable, no exclusiva, no transferible, no sublicenciable y de alcance mundial para utilizar los Datos en relación con el contrato del Gobierno de los Estados Unidos bajo el cual se proporcionaron los Datos. Excepto que aquí se disponga lo contrario, los Datos no se pueden utilizar, desvelar, reproducir, modificar, interpretar o mostrar sin la previa aprobación por escrito de NetApp, Inc. Los derechos de licencia del Gobierno de los Estados Unidos de América y su Departamento de Defensa se limitan a los derechos identificados en la cláusula 252.227-7015(b) de la sección DFARS (FEB de 2014).

## Información de la marca comercial

NETAPP, el logotipo de NETAPP y las marcas que constan en <http://www.netapp.com/TM> son marcas comerciales de NetApp, Inc. El resto de nombres de empresa y de producto pueden ser marcas comerciales de sus respectivos propietarios.