



Bucket

Astra Automation

NetApp
June 28, 2024

Sommaire

- Bucket 1
 - Bucket overview 1
 - Create a new bucket 1
 - List all buckets 13
 - Retrieve a bucket 24
 - Modify a bucket 34
 - Delete a bucket 44

Bucket

Bucket overview

The Bucket API provides access to buckets used to store application backups in Astra.

Create a new bucket

POST /accounts/{account_id}/topology/v1/buckets

Indicates the desired values for the Bucket API resource to be created.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}} |

Request Body

Indicates the desired values for the Bucket API resource to be created.

| Name | Type | Required | Description |
|---------|--------|----------|--|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-bucket" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2" |

| Name | Type | Required | Description |
|------------------|----------------------------------|----------|---|
| name | string | False | JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256 |
| credentialID | string | True | JSON string containing the identifier of the credentials used to access the bucket. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| provider | string | True | JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are: <ul style="list-style-type: none"> • "ontap-s3" • "storagegrid-s3" • "generic-s3" • "gcp" • "azure" • "aws" |
| bucketParameters | bucketParameters | True | JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider. |

| Name | Type | Required | Description |
|----------|--|----------|--|
| metadata | type_astra_metadata_update | False | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example request

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "name": "Test Bucket",
  "credentialID": "d5b3854c-38de-42c6-9269-b5c052aba76f",
  "provider": "gcp",
  "bucketParameters": {
    "gcp": {
      "bucketName": "bucketName"
    }
  }
}
```

Response

Status: 201, Returns the newly created bucket resource in the JSON response body.

| Name | Type | Required | Description |
|--------------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-bucket" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256 |
| credentialID | string | True | JSON string containing the identifier of the credentials used to access the bucket. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|-------------------------------|----------|--|
| state | string | True | <p>JSON string containing a value indicating the operational state of the bucket. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The bucket is scheduled for discovery • "available" - The bucket is available for use • "failed" - The bucket is in a permanent failure state • "removed" - The bucket is not currently accessible • "unknown" - The bucket state cannot be determined |
| stateDetails | array[type_astra_stateDetail] | True | <p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| provider | string | True | <p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> • "ontap-s3" • "storagegrid-s3" • "generic-s3" • "gcp" • "azure" • "aws" |

| Name | Type | Required | Description |
|------------------|--|----------|--|
| bucketParameters | bucketParameters | True | JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider. |
| metadata | type_astra_metadata_update | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example response

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "id": "9b296ce0-c545-5022-acfa-1980c5aeea97",
  "name": "Test Bucket",
  "credentialID": "8f039324-7795-40bf-a5ca-4442580f7ab0",
  "state": "available",
  "stateDetails": [],
  "provider": "gcp",
  "bucketParameters": {
    "gcp": {
      "bucketName": "bucketName"
    }
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

| Name | Type | Required | Description |
|------------|--------|----------|--|
| serverURL | string | True | JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 1023 |
| bucketName | string | True | JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

gcp

JSON object that provides Google Cloud protocol parameters.

| Name | Type | Required | Description |
|------------|--------|----------|---|
| bucketName | string | True | JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

azure

JSON object that provides Azure protocol parameters.

| Name | Type | Required | Description |
|----------------|--------|----------|---|
| storageAccount | string | True | JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 |
| bucketName | string | True | JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 |

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

| Name | Type | Required | Description |
|-------|-------|----------|---|
| s3 | s3 | False | JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers). |
| gcp | gcp | False | JSON object that provides Google Cloud protocol parameters. |
| azure | azure | False | JSON object that provides Azure protocol parameters. |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

type_astra_stateDetail

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|--------|--------|----------|--|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

List all buckets

GET /accounts/{account_id}/topology/v1/buckets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource • example: {{.Account}} |

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name | Type | Required | Description |
|----------|---|----------|-------------|
| items | array[Any of: bucket_1.2_get_response_body , array[]] | True | |
| metadata | type_astra_metadata_list | True | |

Example response

```
{
  "type": "application/astra-buckets",
  "version": "1.2",
  "items": [
    [
      "4c753e39-25e9-4b36-a8de-69f168aa59cd",
      "Test Bucket",
      "gcp"
    ],
    [
      "d8fd585d-6429-4c08-a308-af193a88eac7",
      "Local",
      "ontap-s3"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

| Name | Type | Required | Description |
|------------|--------|----------|--|
| serverURL | string | True | JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 1023 |
| bucketName | string | True | JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

gcp

JSON object that provides Google Cloud protocol parameters.

| Name | Type | Required | Description |
|------------|--------|----------|---|
| bucketName | string | True | JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

azure

JSON object that provides Azure protocol parameters.

| Name | Type | Required | Description |
|----------------|--------|----------|--|
| storageAccount | string | True | JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |
| bucketName | string | True | JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

| Name | Type | Required | Description |
|-------|-------|----------|---|
| s3 | s3 | False | JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers). |
| gcp | gcp | False | JSON object that provides Google Cloud protocol parameters. |
| azure | azure | False | JSON object that provides Azure protocol parameters. |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

bucket_1.2_get_response_body

| Name | Type | Required | Description |
|---------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-bucket" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 256 |

| Name | Type | Required | Description |
|--------------|-------------------------------|----------|--|
| credentialID | string | True | <p>JSON string containing the identifier of the credentials used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| state | string | True | <p>JSON string containing a value indicating the operational state of the bucket. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The bucket is scheduled for discovery • "available" - The bucket is available for use • "failed" - The bucket is in a permanent failure state • "removed" - The bucket is not currently accessible • "unknown" - The bucket state cannot be determined |
| stateDetails | array[type_astra_stateDetail] | True | <p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |

| Name | Type | Required | Description |
|------------------|--|----------|---|
| provider | string | True | JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are: <ul style="list-style-type: none"> "ontap-s3" "storagegrid-s3" "generic-s3" "gcp" "azure" "aws" |
| bucketParameters | bucketParameters | True | JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider. |
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

[type_astra_metadata_list](#)

| Name | Type | Required | Description |
|----------|--------|----------|-------------|
| continue | string | False | |
| count | number | False | |

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Retrieve a bucket

GET /accounts/{account_id}/topology/v1/buckets/{bucket_id}

Returns the stored Bucket API resource in the JSON response body.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource • example: {{.Account}} |
| bucket_id | string | path | True | ID of the bucket collection to list |

Response

Status: 200, Returns the stored Bucket API resource in the JSON response body.

| Name | Type | Required | Description |
|--------------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-bucket" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256 |
| credentialID | string | True | JSON string containing the identifier of the credentials used to access the bucket. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|-------------------------------|----------|--|
| state | string | True | <p>JSON string containing a value indicating the operational state of the bucket. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The bucket is scheduled for discovery • "available" - The bucket is available for use • "failed" - The bucket is in a permanent failure state • "removed" - The bucket is not currently accessible • "unknown" - The bucket state cannot be determined |
| stateDetails | array[type_astra_stateDetail] | True | <p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| provider | string | True | <p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> • "ontap-s3" • "storagegrid-s3" • "generic-s3" • "gcp" • "azure" • "aws" |

| Name | Type | Required | Description |
|------------------|--|----------|--|
| bucketParameters | bucketParameters | True | JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider. |
| metadata | type_astra_metadata_update | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example response

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "id": "9b296ce0-c545-5022-acfa-1980c5aeea97",
  "name": "Test Bucket",
  "credentialID": "8f039324-7795-40bf-a5ca-4442580f7ab0",
  "state": "available",
  "stateDetails": [],
  "provider": "gcp",
  "bucketParameters": {
    "gcp": {
      "bucketName": "bucketName"
    }
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```


Definitions

See Definitions

type_astra_stateDetail

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

| Name | Type | Required | Description |
|------------|--------|----------|--|
| serverURL | string | True | JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 1023 |
| bucketName | string | True | JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

gcp

JSON object that provides Google Cloud protocol parameters.

| Name | Type | Required | Description |
|------------|--------|----------|---|
| bucketName | string | True | JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

azure

JSON object that provides Azure protocol parameters.

| Name | Type | Required | Description |
|----------------|--------|----------|---|
| storageAccount | string | True | JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 |
| bucketName | string | True | JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 |

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

| Name | Type | Required | Description |
|-------|-------|----------|---|
| s3 | s3 | False | JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers). |
| gcp | gcp | False | JSON object that provides Google Cloud protocol parameters. |
| azure | azure | False | JSON object that provides Azure protocol parameters. |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Modify a bucket

PUT /accounts/{account_id}/topology/v1/buckets/{bucket_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|--|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">• example: {{.Account}} |
| bucket_id | string | path | True | ID of the bucket collection to list |

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are

not user-modifiable.

| Name | Type | Required | Description |
|--------------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-bucket" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2" |
| id | string | False | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema |
| name | string | False | JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 256 |
| credentialID | string | False | JSON string containing the identifier of the credentials used to access the bucket. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|-------------------------------|----------|--|
| state | string | False | <p>JSON string containing a value indicating the operational state of the bucket. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The bucket is scheduled for discovery • "available" - The bucket is available for use • "failed" - The bucket is in a permanent failure state • "removed" - The bucket is not currently accessible • "unknown" - The bucket state cannot be determined |
| stateDetails | array[type_astra_stateDetail] | False | <p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| provider | string | False | <p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> • "ontap-s3" • "storagegrid-s3" • "generic-s3" • "gcp" • "azure" • "aws" |

| Name | Type | Required | Description |
|------------------|--|----------|--|
| bucketParameters | bucketParameters | False | JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider. |
| metadata | type_astra_metadata_update | False | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example request

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "name": "New Bucket Name"
}
```

Response

Status: 204, Indicates if the bucket resource was updated.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

| Name | Type | Required | Description |
|------------|--------|----------|--|
| serverURL | string | False | JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 1023 |
| bucketName | string | False | JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

gcp

JSON object that provides Google Cloud protocol parameters.

| Name | Type | Required | Description |
|------------|--------|----------|---|
| bucketName | string | False | JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

azure

JSON object that provides Azure protocol parameters.

| Name | Type | Required | Description |
|----------------|--------|----------|--|
| storageAccount | string | False | JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |
| bucketName | string | False | JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63 |

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

| Name | Type | Required | Description |
|-------|-------|----------|---|
| s3 | s3 | False | JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers). |
| gcp | gcp | False | JSON object that provides Google Cloud protocol parameters. |
| azure | azure | False | JSON object that provides Azure protocol parameters. |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|--------|--------|----------|--|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

Delete a bucket

DELETE /accounts/{account_id}/topology/v1/buckets/{bucket_id}

Removes the specified Bucket API resource.

Side Effects

- Internal data structures are cleaned up.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource • example: {{.Account}} |
| bucket_id | string | path | True | ID of the bucket collection to list |

Response

Status: 204, Indicates if the bucket resource was deleted.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Informations sur le copyright

Copyright © 2024 NetApp, Inc. Tous droits réservés. Imprimé aux États-Unis. Aucune partie de ce document protégé par copyright ne peut être reproduite sous quelque forme que ce soit ou selon quelque méthode que ce soit (graphique, électronique ou mécanique, notamment par photocopie, enregistrement ou stockage dans un système de récupération électronique) sans l'autorisation écrite préalable du détenteur du droit de copyright.

Les logiciels dérivés des éléments NetApp protégés par copyright sont soumis à la licence et à l'avis de non-responsabilité suivants :

CE LOGICIEL EST FOURNI PAR NETAPP « EN L'ÉTAT » ET SANS GARANTIES EXPRESSES OU TACITES, Y COMPRIS LES GARANTIES TACITES DE QUALITÉ MARCHANDE ET D'ADÉQUATION À UN USAGE PARTICULIER, QUI SONT EXCLUES PAR LES PRÉSENTES. EN AUCUN CAS NETAPP NE SERA TENU POUR RESPONSABLE DE DOMMAGES DIRECTS, INDIRECTS, ACCESSOIRES, PARTICULIERS OU EXEMPLAIRES (Y COMPRIS L'ACHAT DE BIENS ET DE SERVICES DE SUBSTITUTION, LA PERTE DE JOUISSANCE, DE DONNÉES OU DE PROFITS, OU L'INTERRUPTION D'ACTIVITÉ), QUELLES QU'EN SOIENT LA CAUSE ET LA DOCTRINE DE RESPONSABILITÉ, QU'IL S'AGISSE DE RESPONSABILITÉ CONTRACTUELLE, STRICTE OU DÉLICTEUELLE (Y COMPRIS LA NÉGLIGENCE OU AUTRE) DÉCOULANT DE L'UTILISATION DE CE LOGICIEL, MÊME SI LA SOCIÉTÉ A ÉTÉ INFORMÉE DE LA POSSIBILITÉ DE TELS DOMMAGES.

NetApp se réserve le droit de modifier les produits décrits dans le présent document à tout moment et sans préavis. NetApp décline toute responsabilité découlant de l'utilisation des produits décrits dans le présent document, sauf accord explicite écrit de NetApp. L'utilisation ou l'achat de ce produit ne concède pas de licence dans le cadre de droits de brevet, de droits de marque commerciale ou de tout autre droit de propriété intellectuelle de NetApp.

Le produit décrit dans ce manuel peut être protégé par un ou plusieurs brevets américains, étrangers ou par une demande en attente.

LÉGENDE DE RESTRICTION DES DROITS : L'utilisation, la duplication ou la divulgation par le gouvernement sont sujettes aux restrictions énoncées dans le sous-paragraphe (b)(3) de la clause Rights in Technical Data-Noncommercial Items du DFARS 252.227-7013 (février 2014) et du FAR 52.227-19 (décembre 2007).

Les données contenues dans les présentes se rapportent à un produit et/ou service commercial (tel que défini par la clause FAR 2.101). Il s'agit de données propriétaires de NetApp, Inc. Toutes les données techniques et tous les logiciels fournis par NetApp en vertu du présent Accord sont à caractère commercial et ont été exclusivement développés à l'aide de fonds privés. Le gouvernement des États-Unis dispose d'une licence limitée irrévocable, non exclusive, non cessible, non transférable et mondiale. Cette licence lui permet d'utiliser uniquement les données relatives au contrat du gouvernement des États-Unis d'après lequel les données lui ont été fournies ou celles qui sont nécessaires à son exécution. Sauf dispositions contraires énoncées dans les présentes, l'utilisation, la divulgation, la reproduction, la modification, l'exécution, l'affichage des données sont interdits sans avoir obtenu le consentement écrit préalable de NetApp, Inc. Les droits de licences du Département de la Défense du gouvernement des États-Unis se limitent aux droits identifiés par la clause 252.227-7015(b) du DFARS (février 2014).

Informations sur les marques commerciales

NETAPP, le logo NETAPP et les marques citées sur le site <http://www.netapp.com/TM> sont des marques déposées ou des marques commerciales de NetApp, Inc. Les autres noms de marques et de produits sont des marques commerciales de leurs propriétaires respectifs.