



# Bucket

## Astra Automation

NetApp  
August 11, 2025

This PDF was generated from [https://docs.netapp.com/it-it/astra-automation/reference/bucket\\_overview.html](https://docs.netapp.com/it-it/astra-automation/reference/bucket_overview.html) on August 11, 2025. Always check docs.netapp.com for the latest.

# Sommario

- Bucket . . . . . 1
  - Bucket overview . . . . . 1
  - Create a new bucket . . . . . 1
    - Parameters . . . . . 1
    - Request Body . . . . . 1
    - Response . . . . . 3
    - Response . . . . . 7
    - Response . . . . . 8
    - Response . . . . . 8
    - Response . . . . . 9
    - Error . . . . . 10
    - Definitions . . . . . 10
  - List all buckets . . . . . 13
    - Parameters . . . . . 14
    - Response . . . . . 14
    - Response . . . . . 15
    - Response . . . . . 16
    - Response . . . . . 16
    - Error . . . . . 17
    - Definitions . . . . . 18
  - Retrieve a bucket . . . . . 25
    - Parameters . . . . . 25
    - Response . . . . . 25
    - Response . . . . . 29
    - Response . . . . . 29
    - Response . . . . . 30
    - Error . . . . . 30
    - Definitions . . . . . 31
  - Modify a bucket . . . . . 34
    - Parameters . . . . . 35
    - Request Body . . . . . 35
    - Response . . . . . 38
    - Response . . . . . 38
    - Response . . . . . 38
    - Response . . . . . 39
    - Response . . . . . 40
    - Error . . . . . 40
    - Definitions . . . . . 41
  - Delete a bucket . . . . . 45
    - Parameters . . . . . 45
    - Response . . . . . 45
    - Response . . . . . 45
    - Response . . . . . 46

|                   |    |
|-------------------|----|
| Response .....    | 46 |
| Error .....       | 47 |
| Definitions ..... | 48 |

# Bucket

## Bucket overview

The Bucket API provides access to buckets used to store application backups in Astra.

## Create a new bucket

POST /accounts/{account\_id}/topology/v1/buckets

Indicates the desired values for the Bucket API resource to be created.

### Parameters

| Name       | Type   | In   | Required | Description                                                                                                     |
|------------|--------|------|----------|-----------------------------------------------------------------------------------------------------------------|
| account_id | string | path | True     | ID of the containing account resource <ul style="list-style-type: none"><li>example:<br/>{{.Account}}</li></ul> |

### Request Body

Indicates the desired values for the Bucket API resource to be created.

| Name    | Type   | Required | Description                                                                                                                    |
|---------|--------|----------|--------------------------------------------------------------------------------------------------------------------------------|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>"application/astra-bucket"</li></ul>     |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"><li>"1.0"</li><li>"1.1"</li><li>"1.2"</li></ul> |

| Name             | Type                             | Required | Description                                                                                                                                                                                                                                                                          |
|------------------|----------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| name             | string                           | False    | <p>JSON string containing a user-assigned name for the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 256</li> </ul>                                                                                          |
| credentialID     | string                           | True     | <p>JSON string containing the identifier of the credentials used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>                                                                           |
| provider         | string                           | True     | <p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• "ontap-s3"</li> <li>• "storagegrid-s3"</li> <li>• "generic-s3"</li> <li>• "gcp"</li> <li>• "azure"</li> <li>• "aws"</li> </ul> |
| bucketParameters | <a href="#">bucketParameters</a> | True     | <p>JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.</p>                                                                                                                           |

| Name     | Type                                       | Required | Description                                                                                                                                                                                                                                                                                                                                                                                              |
|----------|--------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| metadata | <a href="#">type_astra_metadata_update</a> | False    | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

#### Example request

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "name": "Test Bucket",
  "credentialID": "d5b3854c-38de-42c6-9269-b5c052aba76f",
  "provider": "gcp",
  "bucketParameters": {
    "gcp": {
      "bucketName": "bucketName"
    }
  }
}
```

#### Response

Status: 201, Returns the newly created bucket resource in the JSON response body.

| Name         | Type   | Required | Description                                                                                                                                                                                         |
|--------------|--------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| type         | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "application/astra-bucket"</li> </ul>                                                                      |
| version      | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>                                                            |
| id           | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>                                                   |
| name         | string | True     | JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 256</li> </ul>                |
| credentialID | string | True     | JSON string containing the identifier of the credentials used to access the bucket. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul> |

| Name          | Type                          | Required | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------|-------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| state         | string                        | True     | <p>JSON string containing a value indicating the operational state of the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The bucket is scheduled for discovery</li> <li>• "available" - The bucket is available for use</li> <li>• "failed" - The bucket is in a permanent failure state</li> <li>• "removed" - The bucket is not currently accessible</li> <li>• "unknown" - The bucket state cannot be determined</li> </ul> |
| stateDetails  | array[type_astra_stateDetail] | True     | <p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> <li>• Minimum items: 0</li> </ul>                                                                                                                                                                                                                 |
| retentionTime | number                        | False    | <p>Number of seconds representing the time a file on this bucket will be retained for. Defined values are:</p> <ul style="list-style-type: none"> <li>• -1 (Unsupported bucket)</li> <li>• 0 (No known retention policy)</li> <li>• 0 (Known retention policy)</li> </ul>                                                                                                                                                                                            |

| Name             | Type                                       | Required | Description                                                                                                                                                                                                                                                                                                                                                                                               |
|------------------|--------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| provider         | string                                     | True     | <p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• "ontap-s3"</li> <li>• "storagegrid-s3"</li> <li>• "generic-s3"</li> <li>• "gcp"</li> <li>• "azure"</li> <li>• "aws"</li> </ul>                                                                                                                      |
| bucketParameters | <a href="#">bucketParameters</a>           | True     | <p>JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.</p>                                                                                                                                                                                                                                                |
| metadata         | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

## Example response

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "id": "9b296ce0-c545-5022-acfa-1980c5aaea97",
  "name": "Test Bucket",
  "credentialID": "8f039324-7795-40bf-a5ca-4442580f7ab0",
  "state": "available",
  "stateDetails": [],
  "provider": "gcp",
  "bucketParameters": {
    "gcp": {
      "bucketName": "bucketName"
    }
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 409, Conflict

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

## Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

## Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

## See Definitions

### s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

| Name       | Type   | Required | Description                                                                                                                                                                          |
|------------|--------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| serverURL  | string | True     | JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 0</li><li>• Maximum length: 1023</li></ul> |
| bucketName | string | True     | JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 0</li><li>• Maximum length: 63</li></ul>               |

### gcp

JSON object that provides Google Cloud protocol parameters.

| Name       | Type   | Required | Description                                                                                                                                                                                   |
|------------|--------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bucketName | string | True     | JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 0</li><li>• Maximum length: 63</li></ul> |

### azure

JSON object that provides Azure protocol parameters.

| Name           | Type   | Required | Description                                                                                                                                                                             |
|----------------|--------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| storageAccount | string | True     | JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul>          |
| bucketName     | string | True     | JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul> |

#### bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

| Name  | Type  | Required | Description                                                                                                             |
|-------|-------|----------|-------------------------------------------------------------------------------------------------------------------------|
| s3    | s3    | False    | JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers). |
| gcp   | gcp   | False    | JSON object that provides Google Cloud protocol parameters.                                                             |
| azure | azure | False    | JSON object that provides Azure protocol parameters.                                                                    |

#### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

#### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                                      | Required | Description |
|-----------------------|-------------------------------------------|----------|-------------|
| labels                | array[ <a href="#">type_astra_label</a> ] | False    |             |
| creationTimestamp     | string                                    | False    |             |
| modificationTimestamp | string                                    | False    |             |
| createdBy             | string                                    | False    |             |
| modifiedBy            | string                                    | False    |             |

additionalDetails

type\_astra\_stateDetail

| Name              | Type                              | Required | Description |
|-------------------|-----------------------------------|----------|-------------|
| type              | string                            | True     |             |
| title             | string                            | True     |             |
| detail            | string                            | True     |             |
| additionalDetails | <a href="#">additionalDetails</a> | False    |             |

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|-------------------------------------------|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

invalidFields

| Name   | Type   | Required | Description                                  |
|--------|--------|----------|----------------------------------------------|
| name   | string | True     | Name of the invalid request body field       |
| reason | string | True     | Reason why the request body field is invalid |

## List all buckets

GET /accounts/{account\_id}/topology/v1/buckets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name       | Type   | In   | Required | Description                                                             |
|------------|--------|------|----------|-------------------------------------------------------------------------|
| account_id | string | path | True     | ID of the containing account resource<br><br>• example:<br>{{.Account}} |

## Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name     | Type                                                                  | Required | Description |
|----------|-----------------------------------------------------------------------|----------|-------------|
| items    | array[Any of: <a href="#">bucket_1.2_get_response_body</a> , array[]] | True     |             |
| metadata | <a href="#">type_astra_metadata_list</a>                              | True     |             |

## Example response

```
{
  "type": "application/astra-buckets",
  "version": "1.2",
  "items": [
    [
      "4c753e39-25e9-4b36-a8de-69f168aa59cd",
      "Test Bucket",
      "gcp"
    ],
    [
      "d8fd585d-6429-4c08-a308-af193a88eac7",
      "Local",
      "ontap-s3"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

#### Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

**Definitions**

## See Definitions

additionalDetails

type\_astra\_stateDetail

| Name              | Type                              | Required | Description |
|-------------------|-----------------------------------|----------|-------------|
| type              | string                            | True     |             |
| title             | string                            | True     |             |
| detail            | string                            | True     |             |
| additionalDetails | <a href="#">additionalDetails</a> | False    |             |

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

| Name       | Type   | Required | Description                                                                                                                                                                          |
|------------|--------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| serverURL  | string | True     | JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 0</li><li>• Maximum length: 1023</li></ul> |
| bucketName | string | True     | JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 0</li><li>• Maximum length: 63</li></ul>               |

gcp

JSON object that provides Google Cloud protocol parameters.

| Name       | Type   | Required | Description                                                                                                                                                                                      |
|------------|--------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bucketName | string | True     | JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul> |

#### azure

JSON object that provides Azure protocol parameters.

| Name           | Type   | Required | Description                                                                                                                                                                             |
|----------------|--------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| storageAccount | string | True     | JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul>          |
| bucketName     | string | True     | JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul> |

#### bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

| Name | Type | Required | Description                                                                                                             |
|------|------|----------|-------------------------------------------------------------------------------------------------------------------------|
| s3   | s3   | False    | JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers). |
| gcp  | gcp  | False    | JSON object that provides Google Cloud protocol parameters.                                                             |

| Name  | Type                  | Required | Description                                          |
|-------|-----------------------|----------|------------------------------------------------------|
| azure | <a href="#">azure</a> | False    | JSON object that provides Azure protocol parameters. |

type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                                      | Required | Description |
|-----------------------|-------------------------------------------|----------|-------------|
| labels                | array[ <a href="#">type_astra_label</a> ] | False    |             |
| creationTimestamp     | string                                    | False    |             |
| modificationTimestamp | string                                    | False    |             |
| createdBy             | string                                    | False    |             |
| modifiedBy            | string                                    | False    |             |

bucket\_1.2\_get\_response\_body

| Name    | Type   | Required | Description                                                                                                                              |
|---------|--------|----------|------------------------------------------------------------------------------------------------------------------------------------------|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "application/astra-bucket"</li> </ul>           |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul> |

| Name         | Type   | Required | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------|--------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| id           | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>                                                                                                                                                                                                                                                                                                             |
| name         | string | True     | JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 256</li> </ul>                                                                                                                                                                                                                                                                          |
| credentialID | string | True     | JSON string containing the identifier of the credentials used to access the bucket. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>                                                                                                                                                                                                                                                           |
| state        | string | True     | JSON string containing a value indicating the operational state of the bucket. Defined values are: <ul style="list-style-type: none"> <li>• "pending" - The bucket is scheduled for discovery</li> <li>• "available" - The bucket is available for use</li> <li>• "failed" - The bucket is in a permanent failure state</li> <li>• "removed" - The bucket is not currently accessible</li> <li>• "unknown" - The bucket state cannot be determined</li> </ul> |

| Name             | Type                           | Required | Description                                                                                                                                                                                                                                                                          |
|------------------|--------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| stateDetails     | array[type_astra_stateDe tail] | True     | <p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> <li>• Minimum items: 0</li> </ul>                                 |
| retentionTime    | number                         | False    | <p>Number of seconds representing the time a file on this bucket will be retained for. Defined values are:</p> <ul style="list-style-type: none"> <li>• -1 (Unsupported bucket)</li> <li>• 0 (No known retention policy)</li> <li>• 0 (Known retention policy)</li> </ul>            |
| provider         | string                         | True     | <p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• "ontap-s3"</li> <li>• "storagegrid-s3"</li> <li>• "generic-s3"</li> <li>• "gcp"</li> <li>• "azure"</li> <li>• "aws"</li> </ul> |
| bucketParameters | bucketParameters               | True     | <p>JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.</p>                                                                                                                           |

| Name     | Type                                       | Required | Description                                                                                                                                                                                                                                                                                                                                                                                              |
|----------|--------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| metadata | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

#### type\_astra\_metadata\_list

| Name                  | Type                                      | Required | Description |
|-----------------------|-------------------------------------------|----------|-------------|
| continue              | string                                    | False    |             |
| count                 | number                                    | False    |             |
| labels                | array[ <a href="#">type_astra_label</a> ] | False    |             |
| creationTimestamp     | string                                    | False    |             |
| modificationTimestamp | string                                    | False    |             |
| createdBy             | string                                    | False    |             |
| modifiedBy            | string                                    | False    |             |

#### invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|-------------------------------------------|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

# Retrieve a bucket

GET /accounts/{account\_id}/topology/v1/buckets/{bucket\_id}

Returns the stored Bucket API resource in the JSON response body.

## Parameters

| Name       | Type   | In   | Required | Description                                                                                                                |
|------------|--------|------|----------|----------------------------------------------------------------------------------------------------------------------------|
| account_id | string | path | True     | ID of the containing account resource <ul style="list-style-type: none"><li>• example: <code>{{.Account}}</code></li></ul> |
| bucket_id  | string | path | True     | ID of the bucket collection to list                                                                                        |

## Response

Status: 200, Returns the stored Bucket API resource in the JSON response body.

| Name    | Type   | Required | Description                                                                                                                                     |
|---------|--------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-bucket"</li></ul>                    |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"><li>• "1.0"</li><li>• "1.1"</li><li>• "1.2"</li></ul>            |
| id      | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the UUIDv4 Schema</li></ul> |

| Name         | Type                          | Required | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------|-------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| name         | string                        | True     | <p>JSON string containing a user-assigned name for the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 256</li> </ul>                                                                                                                                                                                                                                                                          |
| credentialID | string                        | True     | <p>JSON string containing the identifier of the credentials used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>                                                                                                                                                                                                                                                           |
| state        | string                        | True     | <p>JSON string containing a value indicating the operational state of the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The bucket is scheduled for discovery</li> <li>• "available" - The bucket is available for use</li> <li>• "failed" - The bucket is in a permanent failure state</li> <li>• "removed" - The bucket is not currently accessible</li> <li>• "unknown" - The bucket state cannot be determined</li> </ul> |
| stateDetails | array[type_astra_stateDetail] | True     | <p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> <li>• Minimum items: 0</li> </ul>                                                                                                                                                                                                                 |

| Name             | Type                             | Required | Description                                                                                                                                                                                                                                                                          |
|------------------|----------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| retentionTime    | number                           | False    | <p>Number of seconds representing the time a file on this bucket will be retained for. Defined values are:</p> <ul style="list-style-type: none"> <li>• -1 (Unsupported bucket)</li> <li>• 0 (No known retention policy)</li> <li>• 0 (Known retention policy)</li> </ul>            |
| provider         | string                           | True     | <p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• "ontap-s3"</li> <li>• "storagegrid-s3"</li> <li>• "generic-s3"</li> <li>• "gcp"</li> <li>• "azure"</li> <li>• "aws"</li> </ul> |
| bucketParameters | <a href="#">bucketParameters</a> | True     | <p>JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.</p>                                                                                                                           |

| Name     | Type                                       | Required | Description                                                                                                                                                                                                                                                                                                                                                                                              |
|----------|--------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| metadata | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

#### Example response

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "id": "9b296ce0-c545-5022-acfa-1980c5aaea97",
  "name": "Test Bucket",
  "credentialID": "8f039324-7795-40bf-a5ca-4442580f7ab0",
  "state": "available",
  "stateDetails": [],
  "retentionTime": 57627,
  "provider": "gcp",
  "bucketParameters": {
    "gcp": {
      "bucketName": "bucketName"
    }
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

| Name   | Type   | Required | Description |
|--------|--------|----------|-------------|
| type   | string | True     |             |
| title  | string | True     |             |
| detail | string | True     |             |

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

additionalDetails

type\_astra\_stateDetail

| Name              | Type                              | Required | Description |
|-------------------|-----------------------------------|----------|-------------|
| type              | string                            | True     |             |
| title             | string                            | True     |             |
| detail            | string                            | True     |             |
| additionalDetails | <a href="#">additionalDetails</a> | False    |             |

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

| Name       | Type   | Required | Description                                                                                                                                                                          |
|------------|--------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| serverURL  | string | True     | JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 0</li><li>• Maximum length: 1023</li></ul> |
| bucketName | string | True     | JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 0</li><li>• Maximum length: 63</li></ul>               |

gcp

JSON object that provides Google Cloud protocol parameters.

| Name       | Type   | Required | Description                                                                                                                                                                                      |
|------------|--------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bucketName | string | True     | JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul> |

azure

JSON object that provides Azure protocol parameters.

| Name           | Type   | Required | Description                                                                                                                                                                             |
|----------------|--------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| storageAccount | string | True     | JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul>          |
| bucketName     | string | True     | JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul> |

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

| Name | Type | Required | Description                                                                                                             |
|------|------|----------|-------------------------------------------------------------------------------------------------------------------------|
| s3   | s3   | False    | JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers). |
| gcp  | gcp  | False    | JSON object that provides Google Cloud protocol parameters.                                                             |

| Name  | Type                  | Required | Description                                          |
|-------|-----------------------|----------|------------------------------------------------------|
| azure | <a href="#">azure</a> | False    | JSON object that provides Azure protocol parameters. |

type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                                      | Required | Description |
|-----------------------|-------------------------------------------|----------|-------------|
| labels                | array[ <a href="#">type_astra_label</a> ] | False    |             |
| creationTimestamp     | string                                    | False    |             |
| modificationTimestamp | string                                    | False    |             |
| createdBy             | string                                    | False    |             |
| modifiedBy            | string                                    | False    |             |

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|-------------------------------------------|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

## Modify a bucket

PUT /accounts/{account\_id}/topology/v1/buckets/{bucket\_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

## Parameters

| Name       | Type   | In   | Required | Description                                                                                                              |
|------------|--------|------|----------|--------------------------------------------------------------------------------------------------------------------------|
| account_id | string | path | True     | ID of the containing account resource <ul style="list-style-type: none"><li>example: <code>{{.Account}}</code></li></ul> |
| bucket_id  | string | path | True     | ID of the bucket collection to list                                                                                      |

## Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

| Name    | Type   | Required | Description                                                                                                                                                                   |
|---------|--------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>"application/astra-bucket"</li></ul>                                                    |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"><li>"1.0"</li><li>"1.1"</li><li>"1.2"</li></ul>                                                |
| id      | string | False    | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>Conforms to the UUIDv4 Schema</li></ul>                                 |
| name    | string | False    | JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none"><li>Minimum length: 1</li><li>Maximum length: 256</li></ul> |

| Name         | Type                          | Required | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------|-------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| credentialID | string                        | False    | <p>JSON string containing the identifier of the credentials used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>                                                                                                                                                                                                                                                           |
| state        | string                        | False    | <p>JSON string containing a value indicating the operational state of the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The bucket is scheduled for discovery</li> <li>• "available" - The bucket is available for use</li> <li>• "failed" - The bucket is in a permanent failure state</li> <li>• "removed" - The bucket is not currently accessible</li> <li>• "unknown" - The bucket state cannot be determined</li> </ul> |
| stateDetails | array[type_astra_stateDetail] | False    | <p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> <li>• Minimum items: 0</li> </ul>                                                                                                                                                                                                                 |

| Name             | Type                                       | Required | Description                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------|--------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| provider         | string                                     | False    | <p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> <li>• "ontap-s3"</li> <li>• "storagegrid-s3"</li> <li>• "generic-s3"</li> <li>• "gcp"</li> <li>• "azure"</li> <li>• "aws"</li> </ul>                                                                                                                       |
| bucketParameters | <a href="#">bucketParameters</a>           | False    | <p>JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.</p>                                                                                                                                                                                                                                                 |
| metadata         | <a href="#">type_astra_metadata_update</a> | False    | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

### Example request

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "name": "New Bucket Name"
}
```

### Response

Status: 204, Indicates if the bucket resource was updated.

### Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 409, Conflict

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

## Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| type  | string | True     |             |
| title | string | True     |             |

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

### Definitions

## See Definitions

additionalDetails

type\_astra\_stateDetail

| Name              | Type                              | Required | Description |
|-------------------|-----------------------------------|----------|-------------|
| type              | string                            | True     |             |
| title             | string                            | True     |             |
| detail            | string                            | True     |             |
| additionalDetails | <a href="#">additionalDetails</a> | False    |             |

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

| Name       | Type   | Required | Description                                                                                                                                                                          |
|------------|--------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| serverURL  | string | False    | JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 0</li><li>• Maximum length: 1023</li></ul> |
| bucketName | string | False    | JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 0</li><li>• Maximum length: 63</li></ul>               |

gcp

JSON object that provides Google Cloud protocol parameters.

| Name       | Type   | Required | Description                                                                                                                                                                                      |
|------------|--------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bucketName | string | False    | JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul> |

azure

JSON object that provides Azure protocol parameters.

| Name           | Type   | Required | Description                                                                                                                                                                             |
|----------------|--------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| storageAccount | string | False    | JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul>          |
| bucketName     | string | False    | JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> </ul> |

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

| Name | Type | Required | Description                                                                                                             |
|------|------|----------|-------------------------------------------------------------------------------------------------------------------------|
| s3   | s3   | False    | JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers). |
| gcp  | gcp  | False    | JSON object that provides Google Cloud protocol parameters.                                                             |

| Name  | Type                  | Required | Description                                          |
|-------|-----------------------|----------|------------------------------------------------------|
| azure | <a href="#">azure</a> | False    | JSON object that provides Azure protocol parameters. |

type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                                      | Required | Description |
|-----------------------|-------------------------------------------|----------|-------------|
| labels                | array[ <a href="#">type_astra_label</a> ] | False    |             |
| creationTimestamp     | string                                    | False    |             |
| modificationTimestamp | string                                    | False    |             |
| createdBy             | string                                    | False    |             |
| modifiedBy            | string                                    | False    |             |

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|-------------------------------------------|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

invalidFields

| Name   | Type   | Required | Description                                  |
|--------|--------|----------|----------------------------------------------|
| name   | string | True     | Name of the invalid request body field       |
| reason | string | True     | Reason why the request body field is invalid |

# Delete a bucket

DELETE /accounts/{account\_id}/topology/v1/buckets/{bucket\_id}

Removes the specified Bucket API resource.

## Side Effects

- Internal data structures are cleaned up.

## Parameters

| Name       | Type   | In   | Required | Description                                                                                                                   |
|------------|--------|------|----------|-------------------------------------------------------------------------------------------------------------------------------|
| account_id | string | path | True     | ID of the containing account resource<br><ul style="list-style-type: none"><li>• example: <code>{{.Account}}</code></li></ul> |
| bucket_id  | string | path | True     | ID of the bucket collection to list                                                                                           |

## Response

Status: 204, Indicates if the bucket resource was deleted.

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

#### Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

### See Definitions

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|-------------------------------------------|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

## Informazioni sul copyright

Copyright © 2025 NetApp, Inc. Tutti i diritti riservati. Stampato negli Stati Uniti d'America. Nessuna porzione di questo documento soggetta a copyright può essere riprodotta in qualsiasi formato o mezzo (grafico, elettronico o meccanico, inclusi fotocopie, registrazione, nastri o storage in un sistema elettronico) senza previo consenso scritto da parte del detentore del copyright.

Il software derivato dal materiale sottoposto a copyright di NetApp è soggetto alla seguente licenza e dichiarazione di non responsabilità:

IL PRESENTE SOFTWARE VIENE FORNITO DA NETAPP "COSÌ COM'È" E SENZA QUALSIVOGLIA TIPO DI GARANZIA IMPLICITA O ESPRESSA FRA CUI, A TITOLO ESEMPLIFICATIVO E NON ESAUSTIVO, GARANZIE IMPLICITE DI COMMERCIALIZZABILITÀ E IDONEITÀ PER UNO SCOPO SPECIFICO, CHE VENGONO DECLINATE DAL PRESENTE DOCUMENTO. NETAPP NON VERRÀ CONSIDERATA RESPONSABILE IN ALCUN CASO PER QUALSIVOGLIA DANNO DIRETTO, INDIRETTO, ACCIDENTALE, SPECIALE, ESEMPLARE E CONSEGUENZIALE (COMPRESI, A TITOLO ESEMPLIFICATIVO E NON ESAUSTIVO, PROCUREMENT O SOSTITUZIONE DI MERCI O SERVIZI, IMPOSSIBILITÀ DI UTILIZZO O PERDITA DI DATI O PROFITTI OPPURE INTERRUZIONE DELL'ATTIVITÀ AZIENDALE) CAUSATO IN QUALSIVOGLIA MODO O IN RELAZIONE A QUALUNQUE TEORIA DI RESPONSABILITÀ, SIA ESSA CONTRATTUALE, RIGOROSA O DOVUTA A INSOLVENZA (COMPRESA LA NEGLIGENZA O ALTRO) INSORTA IN QUALSIASI MODO ATTRAVERSO L'UTILIZZO DEL PRESENTE SOFTWARE ANCHE IN PRESENZA DI UN PREAVVISO CIRCA L'EVENTUALITÀ DI QUESTO TIPO DI DANNI.

NetApp si riserva il diritto di modificare in qualsiasi momento qualunque prodotto descritto nel presente documento senza fornire alcun preavviso. NetApp non si assume alcuna responsabilità circa l'utilizzo dei prodotti o materiali descritti nel presente documento, con l'eccezione di quanto concordato espressamente e per iscritto da NetApp. L'utilizzo o l'acquisto del presente prodotto non comporta il rilascio di una licenza nell'ambito di un qualche diritto di brevetto, marchio commerciale o altro diritto di proprietà intellettuale di NetApp.

Il prodotto descritto in questa guida può essere protetto da uno o più brevetti degli Stati Uniti, esteri o in attesa di approvazione.

LEGENDA PER I DIRITTI SOTTOPOSTI A LIMITAZIONE: l'utilizzo, la duplicazione o la divulgazione da parte degli enti governativi sono soggetti alle limitazioni indicate nel sottoparagrafo (b)(3) della clausola Rights in Technical Data and Computer Software del DFARS 252.227-7013 (FEB 2014) e FAR 52.227-19 (DIC 2007).

I dati contenuti nel presente documento riguardano un articolo commerciale (secondo la definizione data in FAR 2.101) e sono di proprietà di NetApp, Inc. Tutti i dati tecnici e il software NetApp forniti secondo i termini del presente Contratto sono articoli aventi natura commerciale, sviluppati con finanziamenti esclusivamente privati. Il governo statunitense ha una licenza irrevocabile limitata, non esclusiva, non trasferibile, non cedibile, mondiale, per l'utilizzo dei Dati esclusivamente in connessione con e a supporto di un contratto governativo statunitense in base al quale i Dati sono distribuiti. Con la sola esclusione di quanto indicato nel presente documento, i Dati non possono essere utilizzati, divulgati, riprodotti, modificati, visualizzati o mostrati senza la previa approvazione scritta di NetApp, Inc. I diritti di licenza del governo degli Stati Uniti per il Dipartimento della Difesa sono limitati ai diritti identificati nella clausola DFARS 252.227-7015(b) (FEB 2014).

## Informazioni sul marchio commerciale

NETAPP, il logo NETAPP e i marchi elencati alla pagina <http://www.netapp.com/TM> sono marchi di NetApp, Inc. Gli altri nomi di aziende e prodotti potrebbero essere marchi dei rispettivi proprietari.