Installare il pacchetto software Tiebreaker

ONTAP MetroCluster

NetApp
February 13, 2026

This PDF was generated from https://docs.netapp.com/it-it/ontap-metrocluster/tiebreaker/install-choose-procedure.html on February 13, 2026. Always check docs.netapp.com for the latest.

Sommario

Installare il pacchetto software Tiebreaker . . . 1
- Scegliere la procedura di installazione . . . 1
- Installa MetroCluster Tiebreaker 1.7 . . . 1
- Installa Tiebreaker 1.6 o 1.6P1 . . . 11
  - Installare o aggiornare a tiebreaker 1.6P1 . . . 11
  - Installare o aggiornare a tiebreaker 1,6 . . . 33
- Installare il Tiebreaker 1,5 . . . 52
  - Configurare l'accesso amministratore all'API e all'SSH ONTAP . . . 52
  - Installare le dipendenze di MetroCluster tiebreaker 1,5 . . . 53
  - Installare o aggiornare a tiebreaker 1,5 . . . 72
- Installare il Tiebreaker 1,4 . . . 78
  - Installare le dipendenze di MetroCluster tiebreaker 1,4 . . . 78
  - Installare o aggiornare a tiebreaker 1,4 . . . 91

Installare il pacchetto software Tiebreaker

Scegliere la procedura di installazione

La procedura di installazione di Tiebreaker che segue dipende dalla versione di Tiebreaker che si sta installando.

Versione Tiebreaker	Vai a…
Spareggio 1.7	"Installa Tiebreaker 1.7"
Spareggio 1.6 o 1.6P1	"Installa Tiebreaker 1.6 o 1.6P1"
Tiebreaker 1,5	"Installare il Tiebreaker 1,5"
Tiebreaker 1,4	"Installare il Tiebreaker 1,4"

Installa MetroCluster Tiebreaker 1.7

Installa o esegui l'aggiornamento a Tiebreaker 1.7 sul tuo host Linux per monitorare le configurazioni MetroCluster .

A proposito di questa attività

- Il sistema storage deve eseguire ONTAP 9.12.1 o versione successiva.
- È possibile passare da Tiebreaker 1.6P1 a Tiebreaker 1.7 solo. Fare riferimento a"Installa Tiebreaker 1.6 o 1.6P1" .
- È possibile installare MetroCluster Tiebreaker come utente non root con privilegi amministrativi sufficienti per eseguire l'installazione di tiebreaker, creare tabelle e utenti e impostare la password utente.

Fasi

1. Scarica il software MetroCluster Tiebreaker 1.7.

   "MetroCluster Tiebreaker (Download) - Sito di supporto NetApp"

2. Accedere all'host come utente root.
3. Se stai effettuando l'aggiornamento, controlla quale versione di Tiebreaker stai utilizzando:

   L'esempio seguente mostra Tiebreaker 1.6P1

   ```
   [root@mcctb ~] # netapp-metrocluster-tiebreaker-software-cli
   NetApp MetroCluster Tiebreaker :> version show
   NetApp MetroCluster Tiebreaker 1.6P1: Sun Mar 13 09:59:02 IST 2022
   NetApp MetroCluster Tiebreaker :> exit
   ```

4. Installare o aggiornare il software Tiebreaker.

Installa Tiebreaker 1.7

Per una nuova installazione di Tiebreaker 1.7, attenersi alla seguente procedura.

Fasi

a. Eseguire il seguente comando nella `[root@mcctb ~] #` prompt per iniziare l'installazione:

```
sh MetroClusterTiebreakerInstall-1.7
```

Il sistema visualizza i seguenti output per una corretta installazione:

Esempio

```
Extracting the MetroCluster Tiebreaker installation/upgrade
archive
Install digest hash is Ok
Performing the MetroCluster Tiebreaker code signature check
Install code signature is Ok
Enter unix user account to use for the installation:
mcctbadminuser
Unix user account "mcctbadminuser" doesn't exist. Do you wish
to create "mcctbadminuser" user account? [Y/N]: y
useradd: warning: the home directory already exists.
Not copying any file from skel directory into it.
Creating mailbox file: File exists
Unix account "mcctbadminuser" created.
Changing password for user mcctbadminuser.
New password:
Retype new password:
passwd: all authentication tokens updated successfully.
MetroCluster Tiebreaker requires unix user account
"mcctbadminuser" to be added to the group "mcctbgrp" for admin
access.
Do you wish to add ? [Y/N]: y
Unix user account "mcctbadminuser" added to "mcctbgrp".
Do you wish to generate your own public-private key pair for
encrypting audit log? [Y/N]: y
Generating public-private key pair...
Configuring Vault...
Starting vault server...
==> Vault server configuration:

             Api Address: <api_address>
                     Cgo: disabled
         Cluster Address: <cluster_address>
   Environment Variables: BASH_FUNC_which%%,
DBUS_SESSION_BUS_ADDRESS, GODEBUG, HISTCONTROL, HISTSIZE,
HOME, HOSTNAME, HOST_ACCOUNT, LANG, LESSOPEN, LOGNAME,
LS_COLORS, MAIL, PATH, PWD, SHELL, SHLVL, SSH_CLIENT,
SSH_CONNECTION, SSH_TTY, STAF_TEMP_DIR, TERM, USER,
VAULT_ADDR, VAULT_TOKEN, XDG_RUNTIME_DIR, XDG_SESSION_ID, _,
vault_Addr, which_declare
              Go Version: go1.20.5
              Listener 1: tcp (addr: "0.0.0.0:8200", cluster
address: "0.0.0.0:8201", max_request_duration: "1m30s",
max_request_size: "33554432", tls: "enabled")
               Log Level:
```

```
                  Mlock: supported: true, enabled: true
          Recovery Mode: false
                Storage: file
                Version: Vault v1.14.0, built 2023-06-
19T11:40:23Z
            Version Sha:
13a649f860186dffe3f3a4459814d87191efc321

==> Vault server started! Log data will stream in below:

2023-11-23T15:14:28.532+0530 [INFO]  proxy environment:
http_proxy="" https_proxy="" no_proxy=""
2023-11-23T15:14:28.577+0530 [INFO]  core: Initializing
version history cache for core
2023-11-23T15:14:38.552+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:14:38.552+0530 [INFO]  core: seal configuration
missing, not initialized
2023-11-23T15:14:38.554+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:14:38.555+0530 [INFO]  core: security barrier
initialized: stored=1 shares=5 threshold=3
2023-11-23T15:14:38.556+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:14:38.577+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:14:38.577+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:14:38.577+0530 [INFO]  core: no mounts; adding
default mount table
2023-11-23T15:14:38.578+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:14:38.578+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:14:38.578+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:14:38.581+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-11-23T15:14:38.581+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:14:38.581+0530 [INFO]  core: restoring leases
2023-11-23T15:14:38.582+0530 [INFO]  expiration: lease restore
```

```
complete
2023-11-23T15:14:38.582+0530 [INFO]  identity: entities
restored
2023-11-23T15:14:38.582+0530 [INFO]  identity: groups restored
2023-11-23T15:14:38.583+0530 [INFO]  core: Recorded vault
version: vault version=1.14.0 upgrade time="2023-11-23
09:44:38.582881162 +0000 UTC" build date=2023-06-19T11:40:23Z
2023-11-23T15:14:38.583+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:14:38.998+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:14:38.999+0530 [INFO]  core: root token
generated
2023-11-23T15:14:38.999+0530 [INFO]  core: pre-seal teardown
starting
2023-11-23T15:14:38.999+0530 [INFO]  rollback: stopping
rollback manager
2023-11-23T15:14:38.999+0530 [INFO]  core: pre-seal teardown
complete
2023-11-23T15:14:39.311+0530 [INFO]  core.cluster-
listener.tcp: starting listener: listener_address=0.0.0.0:8201
2023-11-23T15:14:39.311+0530 [INFO]  core.cluster-listener:
serving cluster requests: cluster_listen_address=[::]:8201
2023-11-23T15:14:39.312+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:14:39.312+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:14:39.312+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:14:39.313+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:14:39.313+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:14:39.313+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:14:39.314+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-11-23T15:14:39.314+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:14:39.314+0530 [INFO]  core: restoring leases
2023-11-23T15:14:39.314+0530 [INFO]  identity: entities
restored
```

```
2023-11-23T15:14:39.314+0530 [INFO]  expiration: lease restore
complete
2023-11-23T15:14:39.314+0530 [INFO]  identity: groups restored
2023-11-23T15:14:39.315+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:14:39.316+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:14:39.316+0530 [INFO]  core: vault is unsealed
Success! Uploaded policy: mcctb-policy
2023-11-23T15:14:39.795+0530 [INFO]  core: enabled credential
backend: path=approle/ type=approle version=""
Success! Enabled approle auth method at: approle/
2023-11-23T15:14:39.885+0530 [INFO]  core: successful mount:
namespace="" path=mcctb/ type=kv version=""
Success! Enabled the kv secrets engine at: mcctb/
Success! Data written to: auth/approle/role/mcctb-app
Installing the NetApp-MetroCluster-Tiebreaker-Software-1.7-
1.x86_64.rpm
Preparing...                          #
################################# # [100%]

Updating / installing...

1:NetApp-MetroCluster-Tiebreaker-So#
################################# # [100%]
Performing file integrity check
etc/cron.weekly/metrocluster-tiebreaker-support is Ok
etc/cron.weekly/metrocluster-tiebreaker-support-cov is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software-cov is Ok
etc/logrotate.d/mcctb is Ok
opt/netapp/mcctb/lib/common/activation-1.1.1.jar is Ok
opt/netapp/mcctb/lib/common/aopalliance.jar is Ok
opt/netapp/mcctb/lib/common/args4j.jar is Ok
opt/netapp/mcctb/lib/common/aspectjrt.jar is Ok
opt/netapp/mcctb/lib/common/aspectjweaver.jar is Ok
opt/netapp/mcctb/lib/common/asup.jar is Ok
opt/netapp/mcctb/lib/common/bcpkix-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bctls-fips-1.0.13.jar is Ok
opt/netapp/mcctb/lib/common/bctls-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcutil-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/cglib.jar is Ok
opt/netapp/mcctb/lib/common/commons-codec.jar is Ok
opt/netapp/mcctb/lib/common/commons-collections4.jar is Ok
```

```
opt/netapp/mcctb/lib/common/commons-compress.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.src.jar is Ok
opt/netapp/mcctb/lib/common/commons-dbcp2.jar is Ok
opt/netapp/mcctb/lib/common/commons-io.jar is Ok
opt/netapp/mcctb/lib/common/commons-lang3.jar is Ok
opt/netapp/mcctb/lib/common/commons-logging.jar is Ok
opt/netapp/mcctb/lib/common/commons-pool2.jar is Ok
opt/netapp/mcctb/lib/common/guava.jar is Ok
opt/netapp/mcctb/lib/common/httpclient.jar is Ok
opt/netapp/mcctb/lib/common/httpcore.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.activation.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.xml.bind-api.jar is Ok
opt/netapp/mcctb/lib/common/java-xmlbuilder.jar is Ok
opt/netapp/mcctb/lib/common/javax.inject.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-api-2.3.1.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-core.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-impl.jar is Ok
opt/netapp/mcctb/lib/common/jline.jar is Ok
opt/netapp/mcctb/lib/common/jna.jar is Ok
opt/netapp/mcctb/lib/common/joda-time.jar is Ok
opt/netapp/mcctb/lib/common/jsch.jar is Ok
opt/netapp/mcctb/lib/common/json.jar is Ok
opt/netapp/mcctb/lib/common/jsvc.zip is Ok
opt/netapp/mcctb/lib/common/junixsocket-common.jar is Ok
opt/netapp/mcctb/lib/common/junixsocket-native-common.jar is
Ok
opt/netapp/mcctb/lib/common/logback-classic.jar is Ok
opt/netapp/mcctb/lib/common/logback-core.jar is Ok
opt/netapp/mcctb/lib/common/mail-1.6.2.jar is Ok
opt/netapp/mcctb/lib/common/mariadb-java-client.jar is Ok
opt/netapp/mcctb/lib/common/mcctb-mib.jar is Ok
opt/netapp/mcctb/lib/common/mcctb.jar is Ok
opt/netapp/mcctb/lib/common/mockito-core.jar is Ok
opt/netapp/mcctb/lib/common/slf4j-api.jar is Ok
opt/netapp/mcctb/lib/common/snmp4j.jar is Ok
opt/netapp/mcctb/lib/common/spring-aop.jar is Ok
opt/netapp/mcctb/lib/common/spring-beans.jar is Ok
opt/netapp/mcctb/lib/common/spring-context-support.jar is Ok
opt/netapp/mcctb/lib/common/spring-context.jar is Ok
opt/netapp/mcctb/lib/common/spring-core.jar is Ok
opt/netapp/mcctb/lib/common/spring-expression.jar is Ok
opt/netapp/mcctb/lib/common/spring-web.jar is Ok
opt/netapp/mcctb/lib/common/vault-java-driver.jar is Ok
opt/netapp/mcctb/lib/common/xz.jar is Ok
opt/netapp/mcctb/lib/org.jacoco.agent-0.8.8-runtime.jar is Ok
```

```
opt/netapp/mcctb/bin/mcctb-asup-invoke is Ok
opt/netapp/mcctb/bin/mcctb_postrotate is Ok
opt/netapp/mcctb/bin/netapp-metrocluster-tiebreaker-software-
cli is Ok
/

Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable
netapp-metrocluster-tiebreaker-software
Created symlink /etc/systemd/system/multi-
user.target.wants/netapp-metrocluster-tiebreaker-
software.service → /etc/systemd/system/netapp-metrocluster-
tiebreaker-software.service.

Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully installed NetApp MetroCluster Tiebreaker software
version 1.7.
```

Aggiorna 1.6P1 a 1.7

Per aggiornare la versione del software Tiebreaker 1.6P1 alla versione Tiebreaker 1.7, procedere come segue.

Fasi

a. Eseguire il seguente comando nella `[root@mcctb ~] #` richiesta di aggiornamento del software:

```
sh MetroClusterTiebreakerInstall-1.7
```

Il sistema visualizza il seguente output per un aggiornamento riuscito:

Esempio

```
Extracting the MetroCluster Tiebreaker installation/upgrade
archive
Install digest hash is Ok
Performing the MetroCluster Tiebreaker code signature check
Install code signature is Ok
NetApp-MetroCluster-Tiebreaker-Software-1.6P1-1.x86_64
Upgrading... to NetApp-MetroCluster-Tiebreaker-Software-1.7-
1.x86_64.rpm
Preparing...
################################## [100%]
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################## [ 50%]
Performing file integrity check
etc/cron.weekly/metrocluster-tiebreaker-support is Ok
etc/cron.weekly/metrocluster-tiebreaker-support-cov is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software-cov is Ok
etc/logrotate.d/mcctb is Ok
opt/netapp/mcctb/lib/common/aopalliance.jar is Ok
opt/netapp/mcctb/lib/common/args4j.jar is Ok
opt/netapp/mcctb/lib/common/aspectjrt.jar is Ok
opt/netapp/mcctb/lib/common/aspectjweaver.jar is Ok
opt/netapp/mcctb/lib/common/asup.jar is Ok
opt/netapp/mcctb/lib/common/bcpkix-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bctls-fips-1.0.19.jar is Ok
opt/netapp/mcctb/lib/common/bctls-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcutil-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/cglib.jar is Ok
opt/netapp/mcctb/lib/common/commons-codec.jar is Ok
opt/netapp/mcctb/lib/common/commons-collections4.jar is Ok
opt/netapp/mcctb/lib/common/commons-compress.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.src.jar is Ok
opt/netapp/mcctb/lib/common/commons-dbcp2.jar is Ok
opt/netapp/mcctb/lib/common/commons-io.jar is Ok
opt/netapp/mcctb/lib/common/commons-lang3.jar is Ok
opt/netapp/mcctb/lib/common/commons-logging.jar is Ok
opt/netapp/mcctb/lib/common/commons-pool2.jar is Ok
opt/netapp/mcctb/lib/common/guava.jar is Ok
opt/netapp/mcctb/lib/common/httpclient.jar is Ok
opt/netapp/mcctb/lib/common/httpcore.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.activation.jar is Ok
```

```
opt/netapp/mcctb/lib/common/jakarta.mail-2.0.1.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.xml.bind-api.jar is Ok
opt/netapp/mcctb/lib/common/java-xmlbuilder.jar is Ok
opt/netapp/mcctb/lib/common/javax.inject.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-api-2.3.1.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-core.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-impl.jar is Ok
opt/netapp/mcctb/lib/common/jline.jar is Ok
opt/netapp/mcctb/lib/common/jna.jar is Ok
opt/netapp/mcctb/lib/common/joda-time.jar is Ok
opt/netapp/mcctb/lib/common/jsch.jar is Ok
opt/netapp/mcctb/lib/common/json.jar is Ok
opt/netapp/mcctb/lib/common/jsvc.zip is Ok
opt/netapp/mcctb/lib/common/junixsocket-common.jar is Ok
opt/netapp/mcctb/lib/common/junixsocket-native-common.jar is
Ok
opt/netapp/mcctb/lib/common/logback-classic.jar is Ok
opt/netapp/mcctb/lib/common/logback-core.jar is Ok
opt/netapp/mcctb/lib/common/mail-1.6.2.jar is Ok
opt/netapp/mcctb/lib/common/mariadb-java-client.jar is Ok
opt/netapp/mcctb/lib/common/mcctb-mib.jar is Ok
opt/netapp/mcctb/lib/common/mcctb.jar is Ok
opt/netapp/mcctb/lib/common/mockito-core.jar is Ok
opt/netapp/mcctb/lib/common/slf4j-api.jar is Ok
opt/netapp/mcctb/lib/common/snmp4j.jar is Ok
opt/netapp/mcctb/lib/common/spring-aop.jar is Ok
opt/netapp/mcctb/lib/common/spring-beans.jar is Ok
opt/netapp/mcctb/lib/common/spring-context-support.jar is Ok
opt/netapp/mcctb/lib/common/spring-context.jar is Ok
opt/netapp/mcctb/lib/common/spring-core.jar is Ok
opt/netapp/mcctb/lib/common/spring-expression.jar is Ok
opt/netapp/mcctb/lib/common/spring-web.jar is Ok
opt/netapp/mcctb/lib/common/vault-java-driver.jar is Ok
opt/netapp/mcctb/lib/common/xz.jar is Ok
opt/netapp/mcctb/lib/org.jacoco.agent-0.8.8-runtime.jar is Ok
opt/netapp/mcctb/bin/mcctb-asup-invoke is Ok
opt/netapp/mcctb/bin/mcctb_postrotate is Ok
opt/netapp/mcctb/bin/netapp-metrocluster-tiebreaker-software-
cli is Ok
/


Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully upgraded NetApp MetroCluster Tiebreaker software
```

```
to version 1.7.
Cleaning up / removing...
   2:NetApp-MetroCluster-Tiebreaker-
So################################ [100%]
```

Se l'aggiornamento non riesce con un errore dovuto a certificati mancanti, fare riferimento a"Certificati di importazione" . Dopo aver importato i certificati, puoi provare a effettuare nuovamente l'aggiornamento.

Installa Tiebreaker 1.6 o 1.6P1

Eseguire una nuova installazione o un aggiornamento a tiebreaker 1,6 o tiebreaker 1.6P1 sul sistema operativo Linux host per monitorare le configurazioni MetroCluster.

A proposito di questa attività

- Il sistema storage deve eseguire ONTAP 9.12.1 o versione successiva.
- È possibile installare MetroCluster Tiebreaker come utente non root con privilegi amministrativi sufficienti per eseguire l'installazione di tiebreaker, creare tabelle e utenti e impostare la password utente.

Installare o aggiornare a tiebreaker 1.6P1

È possibile installare Tiebreaker 1.6P1 o eseguire l'aggiornamento a Tiebreaker 1.6P1 da Tiebreaker 1,6, 1,5 o 1,4.

Fasi

1. Scaricare il software MetroCluster Tiebreaker 1.6P1.

   "MetroCluster Tiebreaker (Download) - Sito di supporto NetApp"

2. Accedere all'host come utente root.
3. Se si sta eseguendo un aggiornamento, verificare la versione di tiebreaker in esecuzione:

   L'esempio seguente mostra il tiebreaker 1,5.

   ```
   [root@mcctb ~] # netapp-metrocluster-tiebreaker-software-cli
   NetApp MetroCluster Tiebreaker :> version show
   NetApp MetroCluster Tiebreaker 1.5: Sun Mar 13 09:59:02 IST 2022
   NetApp MetroCluster Tiebreaker :> exit
   ```

4. Installare o aggiornare il software Tiebreaker.

Installare il Tiebreaker 1.6P1

Per una nuova installazione di Tiebreaker 1.6P1, procedere come segue.

Fasi

a. Eseguire il seguente comando nella `[root@mcctb ~] #` prompt per iniziare l'installazione:

```
sh MetroClusterTiebreakerInstall-1.6P1
```

Il sistema visualizza i seguenti output per una corretta installazione:

Esempio

```
Extracting the MetroCluster Tiebreaker installation/upgrade
archive
Install digest hash is Ok
Performing the MetroCluster Tiebreaker code signature check
Install code signature is Ok
Enter unix user account to use for the installation:
mcctbadminuser
Unix user account "mcctbadminuser" doesn't exist. Do you wish
to create "mcctbadminuser" user account? [Y/N]: y
useradd: warning: the home directory already exists.
Not copying any file from skel directory into it.
Creating mailbox file: File exists
Unix account "mcctbadminuser" created.
Changing password for user mcctbadminuser.
New password:
Retype new password:
passwd: all authentication tokens updated successfully.
MetroCluster Tiebreaker requires unix user account
"mcctbadminuser" to be added to the group "mcctbgrp" for admin
access.
Do you wish to add ? [Y/N]: y
Unix user account "mcctbadminuser" added to "mcctbgrp".
Do you wish to generate your own public-private key pair for
encrypting audit log? [Y/N]: y
Generating public-private key pair...
Configuring Vault...
Starting vault server...
==> Vault server configuration:

             Api Address: <api_address>
                     Cgo: disabled
         Cluster Address: <cluster_address>
   Environment Variables: BASH_FUNC_which%%,
DBUS_SESSION_BUS_ADDRESS, GODEBUG, HISTCONTROL, HISTSIZE,
HOME, HOSTNAME, HOST_ACCOUNT, LANG, LESSOPEN, LOGNAME,
LS_COLORS, MAIL, PATH, PWD, SHELL, SHLVL, SSH_CLIENT,
SSH_CONNECTION, SSH_TTY, STAF_TEMP_DIR, TERM, USER,
VAULT_ADDR, VAULT_TOKEN, XDG_RUNTIME_DIR, XDG_SESSION_ID, _,
vault_Addr, which_declare
              Go Version: go1.20.5
              Listener 1: tcp (addr: "0.0.0.0:8200", cluster
address: "0.0.0.0:8201", max_request_duration: "1m30s",
max_request_size: "33554432", tls: "enabled")
               Log Level:
```

```
                  Mlock: supported: true, enabled: true
          Recovery Mode: false
                Storage: file
                Version: Vault v1.14.0, built 2023-06-
19T11:40:23Z
            Version Sha:
13a649f860186dffe3f3a4459814d87191efc321

==> Vault server started! Log data will stream in below:

2023-11-23T15:14:28.532+0530 [INFO]  proxy environment:
http_proxy="" https_proxy="" no_proxy=""
2023-11-23T15:14:28.577+0530 [INFO]  core: Initializing
version history cache for core
2023-11-23T15:14:38.552+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:14:38.552+0530 [INFO]  core: seal configuration
missing, not initialized
2023-11-23T15:14:38.554+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:14:38.555+0530 [INFO]  core: security barrier
initialized: stored=1 shares=5 threshold=3
2023-11-23T15:14:38.556+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:14:38.577+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:14:38.577+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:14:38.577+0530 [INFO]  core: no mounts; adding
default mount table
2023-11-23T15:14:38.578+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:14:38.578+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:14:38.578+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:14:38.581+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-11-23T15:14:38.581+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:14:38.581+0530 [INFO]  core: restoring leases
2023-11-23T15:14:38.582+0530 [INFO]  expiration: lease restore
```

```
complete
2023-11-23T15:14:38.582+0530 [INFO]  identity: entities
restored
2023-11-23T15:14:38.582+0530 [INFO]  identity: groups restored
2023-11-23T15:14:38.583+0530 [INFO]  core: Recorded vault
version: vault version=1.14.0 upgrade time="2023-11-23
09:44:38.582881162 +0000 UTC" build date=2023-06-19T11:40:23Z
2023-11-23T15:14:38.583+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:14:38.998+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:14:38.999+0530 [INFO]  core: root token
generated
2023-11-23T15:14:38.999+0530 [INFO]  core: pre-seal teardown
starting
2023-11-23T15:14:38.999+0530 [INFO]  rollback: stopping
rollback manager
2023-11-23T15:14:38.999+0530 [INFO]  core: pre-seal teardown
complete
2023-11-23T15:14:39.311+0530 [INFO]  core.cluster-
listener.tcp: starting listener: listener_address=0.0.0.0:8201
2023-11-23T15:14:39.311+0530 [INFO]  core.cluster-listener:
serving cluster requests: cluster_listen_address=[::]:8201
2023-11-23T15:14:39.312+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:14:39.312+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:14:39.312+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:14:39.313+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:14:39.313+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:14:39.313+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:14:39.314+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-11-23T15:14:39.314+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:14:39.314+0530 [INFO]  core: restoring leases
2023-11-23T15:14:39.314+0530 [INFO]  identity: entities
restored
```

```
2023-11-23T15:14:39.314+0530 [INFO]  expiration: lease restore
complete
2023-11-23T15:14:39.314+0530 [INFO]  identity: groups restored
2023-11-23T15:14:39.315+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:14:39.316+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:14:39.316+0530 [INFO]  core: vault is unsealed
Success! Uploaded policy: mcctb-policy
2023-11-23T15:14:39.795+0530 [INFO]  core: enabled credential
backend: path=approle/ type=approle version=""
Success! Enabled approle auth method at: approle/
2023-11-23T15:14:39.885+0530 [INFO]  core: successful mount:
namespace="" path=mcctb/ type=kv version=""
Success! Enabled the kv secrets engine at: mcctb/
Success! Data written to: auth/approle/role/mcctb-app
Installing the NetApp-MetroCluster-Tiebreaker-Software-1.6P1-
1.x86_64.rpm
Preparing...                          #
################################# # [100%]

Updating / installing...

1:NetApp-MetroCluster-Tiebreaker-So#
################################# # [100%]
Performing file integrity check
etc/cron.weekly/metrocluster-tiebreaker-support is Ok
etc/cron.weekly/metrocluster-tiebreaker-support-cov is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software-cov is Ok
etc/logrotate.d/mcctb is Ok
opt/netapp/mcctb/lib/common/activation-1.1.1.jar is Ok
opt/netapp/mcctb/lib/common/aopalliance.jar is Ok
opt/netapp/mcctb/lib/common/args4j.jar is Ok
opt/netapp/mcctb/lib/common/aspectjrt.jar is Ok
opt/netapp/mcctb/lib/common/aspectjweaver.jar is Ok
opt/netapp/mcctb/lib/common/asup.jar is Ok
opt/netapp/mcctb/lib/common/bcpkix-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bctls-fips-1.0.13.jar is Ok
opt/netapp/mcctb/lib/common/bctls-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcutil-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/cglib.jar is Ok
opt/netapp/mcctb/lib/common/commons-codec.jar is Ok
opt/netapp/mcctb/lib/common/commons-collections4.jar is Ok
```

```
opt/netapp/mcctb/lib/common/commons-compress.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.src.jar is Ok
opt/netapp/mcctb/lib/common/commons-dbcp2.jar is Ok
opt/netapp/mcctb/lib/common/commons-io.jar is Ok
opt/netapp/mcctb/lib/common/commons-lang3.jar is Ok
opt/netapp/mcctb/lib/common/commons-logging.jar is Ok
opt/netapp/mcctb/lib/common/commons-pool2.jar is Ok
opt/netapp/mcctb/lib/common/guava.jar is Ok
opt/netapp/mcctb/lib/common/httpclient.jar is Ok
opt/netapp/mcctb/lib/common/httpcore.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.activation.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.xml.bind-api.jar is Ok
opt/netapp/mcctb/lib/common/java-xmlbuilder.jar is Ok
opt/netapp/mcctb/lib/common/javax.inject.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-api-2.3.1.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-core.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-impl.jar is Ok
opt/netapp/mcctb/lib/common/jline.jar is Ok
opt/netapp/mcctb/lib/common/jna.jar is Ok
opt/netapp/mcctb/lib/common/joda-time.jar is Ok
opt/netapp/mcctb/lib/common/jsch.jar is Ok
opt/netapp/mcctb/lib/common/json.jar is Ok
opt/netapp/mcctb/lib/common/jsvc.zip is Ok
opt/netapp/mcctb/lib/common/junixsocket-common.jar is Ok
opt/netapp/mcctb/lib/common/junixsocket-native-common.jar is
Ok
opt/netapp/mcctb/lib/common/logback-classic.jar is Ok
opt/netapp/mcctb/lib/common/logback-core.jar is Ok
opt/netapp/mcctb/lib/common/mail-1.6.2.jar is Ok
opt/netapp/mcctb/lib/common/mariadb-java-client.jar is Ok
opt/netapp/mcctb/lib/common/mcctb-mib.jar is Ok
opt/netapp/mcctb/lib/common/mcctb.jar is Ok
opt/netapp/mcctb/lib/common/mockito-core.jar is Ok
opt/netapp/mcctb/lib/common/slf4j-api.jar is Ok
opt/netapp/mcctb/lib/common/snmp4j.jar is Ok
opt/netapp/mcctb/lib/common/spring-aop.jar is Ok
opt/netapp/mcctb/lib/common/spring-beans.jar is Ok
opt/netapp/mcctb/lib/common/spring-context-support.jar is Ok
opt/netapp/mcctb/lib/common/spring-context.jar is Ok
opt/netapp/mcctb/lib/common/spring-core.jar is Ok
opt/netapp/mcctb/lib/common/spring-expression.jar is Ok
opt/netapp/mcctb/lib/common/spring-web.jar is Ok
opt/netapp/mcctb/lib/common/vault-java-driver.jar is Ok
opt/netapp/mcctb/lib/common/xz.jar is Ok
opt/netapp/mcctb/lib/org.jacoco.agent-0.8.8-runtime.jar is Ok
```

```
opt/netapp/mcctb/bin/mcctb-asup-invoke is Ok
opt/netapp/mcctb/bin/mcctb_postrotate is Ok
opt/netapp/mcctb/bin/netapp-metrocluster-tiebreaker-software-
cli is Ok
/

Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable
netapp-metrocluster-tiebreaker-software
Created symlink /etc/systemd/system/multi-
user.target.wants/netapp-metrocluster-tiebreaker-
software.service → /etc/systemd/system/netapp-metrocluster-
tiebreaker-software.service.

Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully installed NetApp MetroCluster Tiebreaker software
version 1.6P1.
```

Aggiornamento da 1,6 a 1.6P1

Per aggiornare la versione del software Tiebreaker 1,6 a tiebreaker 1.6P1, procedere come segue.

> Dopo aver eseguito l'aggiornamento a tiebreaker 1.6P1 da 1,6, rimuovere i monitor esistenti e aggiungere nuovamente la configurazione MetroCluster per il monitoraggio.

Fasi

a. Eseguire il seguente comando nella `[root@mcctb ~] #` richiesta di aggiornamento del software:

```
sh MetroClusterTiebreakerInstall-1.6P1
```

Il sistema visualizza il seguente output per un aggiornamento riuscito:

Esempio

```
Extracting the MetroCluster Tiebreaker installation/upgrade
archive
Install digest hash is Ok
Performing the MetroCluster Tiebreaker code signature check
Install code signature is Ok
NetApp-MetroCluster-Tiebreaker-Software-1.6P1-1.x86_64
Error making API request.

URL: GET
https://127.0.0.1:8200/v1/sys/internal/ui/mounts/mcctb/data/db
Code: 403. Errors:

* permission denied
Upgrading to NetApp-MetroCluster-Tiebreaker-Software-1.6P1-
1.x86_64.rpm
Preparing...
################################## [100%]
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################## [ 50%]
Performing file integrity check
etc/cron.weekly/metrocluster-tiebreaker-support is Ok
etc/cron.weekly/metrocluster-tiebreaker-support-cov is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software-cov is Ok
etc/logrotate.d/mcctb is Ok
opt/netapp/mcctb/lib/common/aopalliance.jar is Ok
opt/netapp/mcctb/lib/common/args4j.jar is Ok
opt/netapp/mcctb/lib/common/aspectjrt.jar is Ok
opt/netapp/mcctb/lib/common/aspectjweaver.jar is Ok
opt/netapp/mcctb/lib/common/asup.jar is Ok
opt/netapp/mcctb/lib/common/bcpkix-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bctls-fips-1.0.19.jar is Ok
opt/netapp/mcctb/lib/common/bctls-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcutil-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/cglib.jar is Ok
opt/netapp/mcctb/lib/common/commons-codec.jar is Ok
opt/netapp/mcctb/lib/common/commons-collections4.jar is Ok
opt/netapp/mcctb/lib/common/commons-compress.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.src.jar is Ok
opt/netapp/mcctb/lib/common/commons-dbcp2.jar is Ok
opt/netapp/mcctb/lib/common/commons-io.jar is Ok
```

```
opt/netapp/mcctb/lib/common/commons-lang3.jar is Ok
opt/netapp/mcctb/lib/common/commons-logging.jar is Ok
opt/netapp/mcctb/lib/common/commons-pool2.jar is Ok
opt/netapp/mcctb/lib/common/guava.jar is Ok
opt/netapp/mcctb/lib/common/httpclient.jar is Ok
opt/netapp/mcctb/lib/common/httpcore.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.activation.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.mail-2.0.1.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.xml.bind-api.jar is Ok
opt/netapp/mcctb/lib/common/java-xmlbuilder.jar is Ok
opt/netapp/mcctb/lib/common/javax.inject.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-api-2.3.1.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-core.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-impl.jar is Ok
opt/netapp/mcctb/lib/common/jline.jar is Ok
opt/netapp/mcctb/lib/common/jna.jar is Ok
opt/netapp/mcctb/lib/common/joda-time.jar is Ok
opt/netapp/mcctb/lib/common/jsch.jar is Ok
opt/netapp/mcctb/lib/common/json.jar is Ok
opt/netapp/mcctb/lib/common/jsvc.zip is Ok
opt/netapp/mcctb/lib/common/junixsocket-common.jar is Ok
opt/netapp/mcctb/lib/common/junixsocket-native-common.jar is
Ok
opt/netapp/mcctb/lib/common/logback-classic.jar is Ok
opt/netapp/mcctb/lib/common/logback-core.jar is Ok
opt/netapp/mcctb/lib/common/mail-1.6.2.jar is Ok
opt/netapp/mcctb/lib/common/mariadb-java-client.jar is Ok
opt/netapp/mcctb/lib/common/mcctb-mib.jar is Ok
opt/netapp/mcctb/lib/common/mcctb.jar is Ok
opt/netapp/mcctb/lib/common/mockito-core.jar is Ok
opt/netapp/mcctb/lib/common/slf4j-api.jar is Ok
opt/netapp/mcctb/lib/common/snmp4j.jar is Ok
opt/netapp/mcctb/lib/common/spring-aop.jar is Ok
opt/netapp/mcctb/lib/common/spring-beans.jar is Ok
opt/netapp/mcctb/lib/common/spring-context-support.jar is Ok
opt/netapp/mcctb/lib/common/spring-context.jar is Ok
opt/netapp/mcctb/lib/common/spring-core.jar is Ok
opt/netapp/mcctb/lib/common/spring-expression.jar is Ok
opt/netapp/mcctb/lib/common/spring-web.jar is Ok
opt/netapp/mcctb/lib/common/vault-java-driver.jar is Ok
opt/netapp/mcctb/lib/common/xz.jar is Ok
opt/netapp/mcctb/lib/org.jacoco.agent-0.8.8-runtime.jar is Ok
opt/netapp/mcctb/bin/mcctb-asup-invoke is Ok
opt/netapp/mcctb/bin/mcctb_postrotate is Ok
opt/netapp/mcctb/bin/netapp-metrocluster-tiebreaker-software-
cli is Ok
```

```
/


Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully upgraded NetApp MetroCluster Tiebreaker software
to version 1.6P1.
Cleaning up / removing...
    2:NetApp-MetroCluster-Tiebreaker-
So################################## [100%]
```

b. Rimuovere e aggiungere nuovamente la configurazione MetroCluster seguendo la procedura descritta in "Configurare il software Tiebreaker".

Aggiornamento da 1,5 a 1.6P1

Per aggiornare la versione del software Tiebreaker 1,5 a tiebreaker 1.6P1, procedere come segue.

Fasi

a. Eseguire il seguente comando nella `[root@mcctb ~] #` richiesta di aggiornamento del software:

```
sh MetroClusterTiebreakerInstall-1.6P1
```

Il sistema visualizza il seguente output per un aggiornamento riuscito:

Esempio

```
Extracting the MetroCluster Tiebreaker installation/upgrade
archive
Install digest hash is Ok
Performing the MetroCluster Tiebreaker code signature check
Install code signature is Ok

Enter database user name : root

Please enter database password for root
Enter password:

Password updated successfully in the database.

Do you wish to generate your own public-private key pair for
encrypting audit log? [Y/N]: y
Generating public-private key pair...
Configuring Vault...
==> Vault shutdown triggered
2023-07-21T00:30:22.335+0530 [INFO]  core: marked as sealed
2023-07-21T00:30:22.335+0530 [INFO]  core: pre-seal teardown
starting
2023-07-21T00:30:22.335+0530 [INFO]  rollback: stopping
rollback manager
2023-07-21T00:30:22.335+0530 [INFO]  core: pre-seal teardown
complete
2023-07-21T00:30:22.335+0530 [INFO]  core: stopping cluster
listeners
2023-07-21T00:30:22.335+0530 [INFO]  core.cluster-listener:
forwarding rpc listeners stopped
2023-07-21T00:30:22.375+0530 [INFO]  core.cluster-listener:
rpc listeners successfully shut down
2023-07-21T00:30:22.375+0530 [INFO]  core: cluster listeners
successfully shut down
2023-07-21T00:30:22.376+0530 [INFO]  core: vault is sealed
Starting vault server...
==> Vault server configuration:

             Api Address: <api_address>
                     Cgo: disabled
         Cluster Address: <cluster_address>
   Environment Variables: BASH_FUNC_which%%,
DBUS_SESSION_BUS_ADDRESS, GODEBUG, HISTCONTROL, HISTSIZE,
HOME, HOSTNAME, HOST_ACCOUNT, LANG, LESSOPEN, LOGNAME,
LS_COLORS, MAIL, PATH, PWD, SHELL, SHLVL, SSH_CLIENT,
```

```
SSH_CONNECTION, SSH_TTY, STAF_TEMP_DIR, TERM, USER,
VAULT_ADDR, VAULT_TOKEN, XDG_RUNTIME_DIR, XDG_SESSION_ID, _,
vault_Addr, which_declare
              Go Version: go1.20.5
              Listener 1: tcp (addr: "0.0.0.0:8200", cluster
address: "0.0.0.0:8201", max_request_duration: "1m30s",
max_request_size: "33554432", tls: "enabled")
               Log Level:
                   Mlock: supported: true, enabled: true
           Recovery Mode: false
                 Storage: file
                 Version: Vault v1.14.0, built 2023-06-
19T11:40:23Z
             Version Sha:
13a649f860186dffe3f3a4459814d87191efc321

==> Vault server started! Log data will stream in below:

2023-07-21T00:30:33.065+0530 [INFO]  proxy environment:
http_proxy="" https_proxy="" no_proxy=""
2023-07-21T00:30:33.098+0530 [INFO]  core: Initializing
version history cache for core
2023-07-21T00:30:43.092+0530 [INFO]  core: security barrier
not initialized
2023-07-21T00:30:43.092+0530 [INFO]  core: seal configuration
missing, not initialized
2023-07-21T00:30:43.094+0530 [INFO]  core: security barrier
not initialized
2023-07-21T00:30:43.096+0530 [INFO]  core: security barrier
initialized: stored=1 shares=5 threshold=3
2023-07-21T00:30:43.098+0530 [INFO]  core: post-unseal setup
starting
2023-07-21T00:30:43.124+0530 [INFO]  core: loaded wrapping
token key
2023-07-21T00:30:43.124+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-07-21T00:30:43.124+0530 [INFO]  core: no mounts; adding
default mount table
2023-07-21T00:30:43.125+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-07-21T00:30:43.126+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-07-21T00:30:43.126+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
```

```
path=identity/ namespace="ID: root. Path: "
2023-07-21T00:30:43.129+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-07-21T00:30:43.130+0530 [INFO]  rollback: starting
rollback manager
2023-07-21T00:30:43.130+0530 [INFO]  core: restoring leases
2023-07-21T00:30:43.130+0530 [INFO]  identity: entities
restored
2023-07-21T00:30:43.130+0530 [INFO]  identity: groups restored
2023-07-21T00:30:43.131+0530 [INFO]  core: usage gauge
collection is disabled
2023-07-21T00:30:43.131+0530 [INFO]  expiration: lease restore
complete
2023-07-21T00:30:43.131+0530 [INFO]  core: Recorded vault
version: vault version=1.14.0 upgrade time="2023-07-20
19:00:43.131158543 +0000 UTC" build date=2023-06-19T11:40:23Z
2023-07-21T00:30:43.371+0530 [INFO]  core: post-unseal setup
complete
2023-07-21T00:30:43.371+0530 [INFO]  core: root token
generated
2023-07-21T00:30:43.371+0530 [INFO]  core: pre-seal teardown
starting
2023-07-21T00:30:43.371+0530 [INFO]  rollback: stopping
rollback manager
2023-07-21T00:30:43.372+0530 [INFO]  core: pre-seal teardown
complete
2023-07-21T00:30:43.694+0530 [INFO]  core.cluster-
listener.tcp: starting listener: listener_address=0.0.0.0:8201
2023-07-21T00:30:43.695+0530 [INFO]  core.cluster-listener:
serving cluster requests: cluster_listen_address=[::]:8201
2023-07-21T00:30:43.695+0530 [INFO]  core: post-unseal setup
starting
2023-07-21T00:30:43.696+0530 [INFO]  core: loaded wrapping
token key
2023-07-21T00:30:43.696+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-07-21T00:30:43.697+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-07-21T00:30:43.698+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-07-21T00:30:43.698+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
```

```
2023-07-21T00:30:43.701+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-07-21T00:30:43.701+0530 [INFO]  rollback: starting
rollback manager
2023-07-21T00:30:43.702+0530 [INFO]  core: restoring leases
2023-07-21T00:30:43.702+0530 [INFO]  identity: entities
restored
2023-07-21T00:30:43.702+0530 [INFO]  expiration: lease restore
complete
2023-07-21T00:30:43.702+0530 [INFO]  identity: groups restored
2023-07-21T00:30:43.702+0530 [INFO]  core: usage gauge
collection is disabled
2023-07-21T00:30:43.703+0530 [INFO]  core: post-unseal setup
complete
2023-07-21T00:30:43.703+0530 [INFO]  core: vault is unsealed
Success! Uploaded policy: mcctb-policy
2023-07-21T00:30:44.226+0530 [INFO]  core: enabled credential
backend: path=approle/ type=approle version=""
Success! Enabled approle auth method at: approle/
2023-07-21T00:30:44.315+0530 [INFO]  core: successful mount:
namespace="" path=mcctb/ type=kv version=""
Success! Enabled the kv secrets engine at: mcctb/
Success! Data written to: auth/approle/role/mcctb-app
Upgrading to NetApp-MetroCluster-Tiebreaker-Software-1.6P1-
1.x86_64.rpm
Preparing...
################################## [100%]
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################## [ 50%]
Performing file integrity check
etc/cron.weekly/metrocluster-tiebreaker-support is Ok
etc/cron.weekly/metrocluster-tiebreaker-support-cov is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software-cov is Ok
etc/logrotate.d/mcctb is Ok
opt/netapp/mcctb/lib/common/activation-1.1.1.jar is Ok
opt/netapp/mcctb/lib/common/aopalliance.jar is Ok
opt/netapp/mcctb/lib/common/args4j.jar is Ok
opt/netapp/mcctb/lib/common/aspectjrt.jar is Ok
opt/netapp/mcctb/lib/common/aspectjweaver.jar is Ok
opt/netapp/mcctb/lib/common/asup.jar is Ok
opt/netapp/mcctb/lib/common/bcpkix-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk18on.jar is Ok
```

```
opt/netapp/mcctb/lib/common/bctls-fips-1.0.13.jar is Ok
opt/netapp/mcctb/lib/common/bctls-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcutil-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/cglib.jar is Ok
opt/netapp/mcctb/lib/common/commons-codec.jar is Ok
opt/netapp/mcctb/lib/common/commons-collections4.jar is Ok
opt/netapp/mcctb/lib/common/commons-compress.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.src.jar is Ok
opt/netapp/mcctb/lib/common/commons-dbcp2.jar is Ok
opt/netapp/mcctb/lib/common/commons-io.jar is Ok
opt/netapp/mcctb/lib/common/commons-lang3.jar is Ok
opt/netapp/mcctb/lib/common/commons-logging.jar is Ok
opt/netapp/mcctb/lib/common/commons-pool2.jar is Ok
opt/netapp/mcctb/lib/common/guava.jar is Ok
opt/netapp/mcctb/lib/common/httpclient.jar is Ok
opt/netapp/mcctb/lib/common/httpcore.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.activation.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.xml.bind-api.jar is Ok
opt/netapp/mcctb/lib/common/java-xmlbuilder.jar is Ok
opt/netapp/mcctb/lib/common/javax.inject.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-api-2.3.1.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-core.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-impl.jar is Ok
opt/netapp/mcctb/lib/common/jline.jar is Ok
opt/netapp/mcctb/lib/common/jna.jar is Ok
opt/netapp/mcctb/lib/common/joda-time.jar is Ok
opt/netapp/mcctb/lib/common/jsch.jar is Ok
opt/netapp/mcctb/lib/common/json.jar is Ok
opt/netapp/mcctb/lib/common/jsvc.zip is Ok
opt/netapp/mcctb/lib/common/junixsocket-common.jar is Ok
opt/netapp/mcctb/lib/common/junixsocket-native-common.jar is
Ok
opt/netapp/mcctb/lib/common/logback-classic.jar is Ok
opt/netapp/mcctb/lib/common/logback-core.jar is Ok
opt/netapp/mcctb/lib/common/mail-1.6.2.jar is Ok
opt/netapp/mcctb/lib/common/mariadb-java-client.jar is Ok
opt/netapp/mcctb/lib/common/mcctb-mib.jar is Ok
opt/netapp/mcctb/lib/common/mcctb.jar is Ok
opt/netapp/mcctb/lib/common/mockito-core.jar is Ok
opt/netapp/mcctb/lib/common/slf4j-api.jar is Ok
opt/netapp/mcctb/lib/common/snmp4j.jar is Ok
opt/netapp/mcctb/lib/common/spring-aop.jar is Ok
opt/netapp/mcctb/lib/common/spring-beans.jar is Ok
opt/netapp/mcctb/lib/common/spring-context-support.jar is Ok
opt/netapp/mcctb/lib/common/spring-context.jar is Ok
```

```
opt/netapp/mcctb/lib/common/spring-core.jar is Ok
opt/netapp/mcctb/lib/common/spring-expression.jar is Ok
opt/netapp/mcctb/lib/common/spring-web.jar is Ok
opt/netapp/mcctb/lib/common/vault-java-driver.jar is Ok
opt/netapp/mcctb/lib/common/xz.jar is Ok
opt/netapp/mcctb/bin/mcctb_postrotate is Ok
opt/netapp/mcctb/bin/netapp-metrocluster-tiebreaker-software-
cli is Ok
/

Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable
netapp-metrocluster-tiebreaker-software

Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully upgraded NetApp MetroCluster Tiebreaker software
to version 1.6P1.
Cleaning up / removing...
   2:NetApp-MetroCluster-Tiebreaker-
So################################## [100%]
```

Aggiornamento da 1,4 a 1.6P1

Per aggiornare la versione del software Tiebreaker 1,4 a tiebreaker 1.6P1, procedere come segue.

Fasi

a. Eseguire il seguente comando nella `[root@mcctb ~] #` richiesta di aggiornamento del software:

```
sh MetroClusterTiebreakerInstall-1.6P1
```

Il sistema visualizza il seguente output per un aggiornamento riuscito:

Esempio

```
Extracting the MetroCluster Tiebreaker installation/upgrade
archive
Install digest hash is Ok
Performing the MetroCluster Tiebreaker code signature check
Install code signature is Ok
Enter unix user account to use for the installation:
mcctbuseradmin1
Unix user account "mcctbuseradmin1" doesn't exist. Do you wish
to create "mcctbuseradmin1" user account? [Y/N]: y
Unix account "mcctbuseradmin1" created.
Changing password for user mcctbuseradmin1.
New password:
Retype new password:
passwd: all authentication tokens updated successfully.

Enter database user name : root

Please enter database password for root
Enter password:

Password updated successfully in the database.

MetroCluster Tiebreaker requires unix user account
"mcctbuseradmin1" to be added to the group "mcctbgrp" for
admin access.
Do you wish to add ? [Y/N]: y
Unix user account "mcctbuseradmin1" added to "mcctbgrp".
Do you wish to generate your own public-private key pair for
encrypting audit log? [Y/N]: y
Generating public-private key pair...
Configuring Vault...
Starting vault server...
==> Vault server configuration:

             Api Address: <api_addess>
                     Cgo: disabled
         Cluster Address: <cluster_address>
   Environment Variables: BASH_FUNC_which%%,
DBUS_SESSION_BUS_ADDRESS, GODEBUG, HISTCONTROL, HISTSIZE,
HOME, HOSTNAME, HOST_ACCOUNT, LANG, LESSOPEN, LOGNAME,
LS_COLORS, MAIL, PATH, PWD, SHELL, SHLVL, SSH_CLIENT,
SSH_CONNECTION, SSH_TTY, STAF_TEMP_DIR, TERM, USER,
VAULT_ADDR, VAULT_TOKEN, XDG_RUNTIME_DIR, XDG_SESSION_ID, _,
vault_Addr, which_declare
```

```
              Go Version: go1.20.5
              Listener 1: tcp (addr: "0.0.0.0:8200", cluster
address: "0.0.0.0:8201", max_request_duration: "1m30s",
max_request_size: "33554432", tls: "enabled")
               Log Level:
                   Mlock: supported: true, enabled: true
           Recovery Mode: false
                 Storage: file
                 Version: Vault v1.14.0, built 2023-06-
19T11:40:23Z
             Version Sha:
13a649f860186dffe3f3a4459814d87191efc321

==> Vault server started! Log data will stream in below:

2023-11-23T15:58:10.400+0530 [INFO]  proxy environment:
http_proxy="" https_proxy="" no_proxy=""
2023-11-23T15:58:10.432+0530 [INFO]  core: Initializing
version history cache for core
2023-11-23T15:58:20.422+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:58:20.422+0530 [INFO]  core: seal configuration
missing, not initialized
2023-11-23T15:58:20.424+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:58:20.425+0530 [INFO]  core: security barrier
initialized: stored=1 shares=5 threshold=3
2023-11-23T15:58:20.427+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:58:20.448+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:58:20.448+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:58:20.448+0530 [INFO]  core: no mounts; adding
default mount table
2023-11-23T15:58:20.449+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:58:20.449+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:58:20.449+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:58:20.451+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
```

```
path=token/ namespace="ID: root. Path: "
2023-11-23T15:58:20.452+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:58:20.452+0530 [INFO]  core: restoring leases
2023-11-23T15:58:20.453+0530 [INFO]  identity: entities
restored
2023-11-23T15:58:20.453+0530 [INFO]  identity: groups restored
2023-11-23T15:58:20.453+0530 [INFO]  expiration: lease restore
complete
2023-11-23T15:58:20.453+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:58:20.453+0530 [INFO]  core: Recorded vault
version: vault version=1.14.0 upgrade time="2023-11-23
10:28:20.453481904 +0000 UTC" build date=2023-06-19T11:40:23Z
2023-11-23T15:58:20.818+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:58:20.819+0530 [INFO]  core: root token
generated
2023-11-23T15:58:20.819+0530 [INFO]  core: pre-seal teardown
starting
2023-11-23T15:58:20.819+0530 [INFO]  rollback: stopping
rollback manager
2023-11-23T15:58:20.819+0530 [INFO]  core: pre-seal teardown
complete
2023-11-23T15:58:21.116+0530 [INFO]  core.cluster-
listener.tcp: starting listener: listener_address=0.0.0.0:8201
2023-11-23T15:58:21.116+0530 [INFO]  core.cluster-listener:
serving cluster requests: cluster_listen_address=[::]:8201
2023-11-23T15:58:21.117+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:58:21.117+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:58:21.117+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:58:21.119+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:58:21.120+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:58:21.120+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:58:21.123+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
```

```
2023-11-23T15:58:21.123+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:58:21.124+0530 [INFO]  core: restoring leases
2023-11-23T15:58:21.124+0530 [INFO]  identity: entities
restored
2023-11-23T15:58:21.124+0530 [INFO]  identity: groups restored
2023-11-23T15:58:21.124+0530 [INFO]  expiration: lease restore
complete
2023-11-23T15:58:21.125+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:58:21.125+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:58:21.125+0530 [INFO]  core: vault is unsealed
Success! Uploaded policy: mcctb-policy
2023-11-23T15:58:21.600+0530 [INFO]  core: enabled credential
backend: path=approle/ type=approle version=""
Success! Enabled approle auth method at: approle/
2023-11-23T15:58:21.690+0530 [INFO]  core: successful mount:
namespace="" path=mcctb/ type=kv version=""
Success! Enabled the kv secrets engine at: mcctb/
Success! Data written to: auth/approle/role/mcctb-app
Upgrading to NetApp-MetroCluster-Tiebreaker-Software-1.6P1-
1.x86_64.rpm
Preparing...
################################## [100%]
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################## [ 50%]
Performing file integrity check
etc/cron.weekly/metrocluster-tiebreaker-support is Ok
etc/cron.weekly/metrocluster-tiebreaker-support-cov is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software-cov is Ok
etc/logrotate.d/mcctb is Ok
opt/netapp/mcctb/lib/common/activation-1.1.1.jar is Ok
opt/netapp/mcctb/lib/common/aopalliance.jar is Ok
opt/netapp/mcctb/lib/common/args4j.jar is Ok
opt/netapp/mcctb/lib/common/aspectjrt.jar is Ok
opt/netapp/mcctb/lib/common/aspectjweaver.jar is Ok
opt/netapp/mcctb/lib/common/asup.jar is Ok
opt/netapp/mcctb/lib/common/bcpkix-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bctls-fips-1.0.13.jar is Ok
opt/netapp/mcctb/lib/common/bctls-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcutil-jdk18on.jar is Ok
```

```
opt/netapp/mcctb/lib/common/cglib.jar is Ok
opt/netapp/mcctb/lib/common/commons-codec.jar is Ok
opt/netapp/mcctb/lib/common/commons-collections4.jar is Ok
opt/netapp/mcctb/lib/common/commons-compress.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.src.jar is Ok
opt/netapp/mcctb/lib/common/commons-dbcp2.jar is Ok
opt/netapp/mcctb/lib/common/commons-io.jar is Ok
opt/netapp/mcctb/lib/common/commons-lang3.jar is Ok
opt/netapp/mcctb/lib/common/commons-logging.jar is Ok
opt/netapp/mcctb/lib/common/commons-pool2.jar is Ok
opt/netapp/mcctb/lib/common/guava.jar is Ok
opt/netapp/mcctb/lib/common/httpclient.jar is Ok
opt/netapp/mcctb/lib/common/httpcore.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.activation.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.xml.bind-api.jar is Ok
opt/netapp/mcctb/lib/common/java-xmlbuilder.jar is Ok
opt/netapp/mcctb/lib/common/javax.inject.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-api-2.3.1.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-core.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-impl.jar is Ok
opt/netapp/mcctb/lib/common/jline.jar is Ok
opt/netapp/mcctb/lib/common/jna.jar is Ok
opt/netapp/mcctb/lib/common/joda-time.jar is Ok
opt/netapp/mcctb/lib/common/jsch.jar is Ok
opt/netapp/mcctb/lib/common/json.jar is Ok
opt/netapp/mcctb/lib/common/jsvc.zip is Ok
opt/netapp/mcctb/lib/common/junixsocket-common.jar is Ok
opt/netapp/mcctb/lib/common/junixsocket-native-common.jar is
Ok
opt/netapp/mcctb/lib/common/logback-classic.jar is Ok
opt/netapp/mcctb/lib/common/logback-core.jar is Ok
opt/netapp/mcctb/lib/common/mail-1.6.2.jar is Ok
opt/netapp/mcctb/lib/common/mariadb-java-client.jar is Ok
opt/netapp/mcctb/lib/common/mcctb-mib.jar is Ok
opt/netapp/mcctb/lib/common/mcctb.jar is Ok
opt/netapp/mcctb/lib/common/mockito-core.jar is Ok
opt/netapp/mcctb/lib/common/slf4j-api.jar is Ok
opt/netapp/mcctb/lib/common/snmp4j.jar is Ok
opt/netapp/mcctb/lib/common/spring-aop.jar is Ok
opt/netapp/mcctb/lib/common/spring-beans.jar is Ok
opt/netapp/mcctb/lib/common/spring-context-support.jar is Ok
opt/netapp/mcctb/lib/common/spring-context.jar is Ok
opt/netapp/mcctb/lib/common/spring-core.jar is Ok
opt/netapp/mcctb/lib/common/spring-expression.jar is Ok
opt/netapp/mcctb/lib/common/spring-web.jar is Ok
```

```
opt/netapp/mcctb/lib/common/vault-java-driver.jar is Ok
opt/netapp/mcctb/lib/common/xz.jar is Ok
opt/netapp/mcctb/lib/org.jacoco.agent-0.8.8-runtime.jar is Ok
opt/netapp/mcctb/bin/mcctb-asup-invoke is Ok
opt/netapp/mcctb/bin/mcctb_postrotate is Ok
opt/netapp/mcctb/bin/netapp-metrocluster-tiebreaker-software-
cli is Ok
/

Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable
netapp-metrocluster-tiebreaker-software

Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully upgraded NetApp MetroCluster Tiebreaker software
to version 1.6P1.
Cleaning up / removing...
   2:NetApp-MetroCluster-Tiebreaker-
So################################## [100%]
```

Installare o aggiornare a tiebreaker 1,6

È possibile installare Tiebreaker 1,6 o eseguire l'aggiornamento a Tiebreaker 1,6 da Tiebreaker 1,5 o 1,4.

Fasi

1. Scaricare il software MetroCluster Tiebreaker 1,6.

   "MetroCluster Tiebreaker (Download) - Sito di supporto NetApp"

2. Accedere all'host come utente root.
3. Se si sta eseguendo un aggiornamento, verificare la versione di tiebreaker in esecuzione:

   L'esempio seguente mostra il tiebreaker 1,5.

   ```
   [root@mcctb ~] # netapp-metrocluster-tiebreaker-software-cli
   NetApp MetroCluster Tiebreaker :> version show
   NetApp MetroCluster Tiebreaker 1.5: Sun Mar 13 09:59:02 IST 2022
   NetApp MetroCluster Tiebreaker :> exit
   ```

4. Installare o aggiornare il software Tiebreaker.

Installare il Tiebreaker 1,6

Per una nuova installazione di Tiebreaker 1,6, procedere come segue.

Fasi

a. Eseguire il seguente comando nella `[root@mcctb ~] #` prompt per iniziare l'installazione:

```
sh MetroClusterTiebreakerInstall-1.6
```

Il sistema visualizza i seguenti output per una corretta installazione:

Esempio

```
Extracting the MetroCluster Tiebreaker installation/upgrade
archive
Install digest hash is Ok
Performing the MetroCluster Tiebreaker code signature check
Install code signature is Ok
Enter unix user account to use for the installation:
mcctbadminuser
Unix user account "mcctbadminuser" doesn't exist. Do you wish
to create "mcctbadminuser" user account? [Y/N]: y
useradd: warning: the home directory already exists.
Not copying any file from skel directory into it.
Creating mailbox file: File exists
Unix account "mcctbadminuser" created.
Changing password for user mcctbadminuser.
New password:
Retype new password:
passwd: all authentication tokens updated successfully.
MetroCluster Tiebreaker requires unix user account
"mcctbadminuser" to be added to the group "mcctbgrp" for admin
access.
Do you wish to add ? [Y/N]: y
Unix user account "mcctbadminuser" added to "mcctbgrp".
Do you wish to generate your own public-private key pair for
encrypting audit log? [Y/N]: y
Generating public-private key pair...
Configuring Vault...
Starting vault server...
==> Vault server configuration:

             Api Address: <api_address>
                     Cgo: disabled
         Cluster Address: <cluster_address>
   Environment Variables: BASH_FUNC_which%%,
DBUS_SESSION_BUS_ADDRESS, GODEBUG, HISTCONTROL, HISTSIZE,
HOME, HOSTNAME, HOST_ACCOUNT, LANG, LESSOPEN, LOGNAME,
LS_COLORS, MAIL, PATH, PWD, SHELL, SHLVL, SSH_CLIENT,
SSH_CONNECTION, SSH_TTY, STAF_TEMP_DIR, TERM, USER,
VAULT_ADDR, VAULT_TOKEN, XDG_RUNTIME_DIR, XDG_SESSION_ID, _,
vault_Addr, which_declare
              Go Version: go1.20.5
              Listener 1: tcp (addr: "0.0.0.0:8200", cluster
address: "0.0.0.0:8201", max_request_duration: "1m30s",
max_request_size: "33554432", tls: "enabled")
               Log Level:
```

```
                  Mlock: supported: true, enabled: true
          Recovery Mode: false
                Storage: file
                Version: Vault v1.14.0, built 2023-06-
19T11:40:23Z
            Version Sha:
13a649f860186dffe3f3a4459814d87191efc321

==> Vault server started! Log data will stream in below:

2023-11-23T15:14:28.532+0530 [INFO]  proxy environment:
http_proxy="" https_proxy="" no_proxy=""
2023-11-23T15:14:28.577+0530 [INFO]  core: Initializing
version history cache for core
2023-11-23T15:14:38.552+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:14:38.552+0530 [INFO]  core: seal configuration
missing, not initialized
2023-11-23T15:14:38.554+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:14:38.555+0530 [INFO]  core: security barrier
initialized: stored=1 shares=5 threshold=3
2023-11-23T15:14:38.556+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:14:38.577+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:14:38.577+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:14:38.577+0530 [INFO]  core: no mounts; adding
default mount table
2023-11-23T15:14:38.578+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:14:38.578+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:14:38.578+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:14:38.581+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-11-23T15:14:38.581+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:14:38.581+0530 [INFO]  core: restoring leases
2023-11-23T15:14:38.582+0530 [INFO]  expiration: lease restore
```

```
complete
2023-11-23T15:14:38.582+0530 [INFO]  identity: entities
restored
2023-11-23T15:14:38.582+0530 [INFO]  identity: groups restored
2023-11-23T15:14:38.583+0530 [INFO]  core: Recorded vault
version: vault version=1.14.0 upgrade time="2023-11-23
09:44:38.582881162 +0000 UTC" build date=2023-06-19T11:40:23Z
2023-11-23T15:14:38.583+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:14:38.998+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:14:38.999+0530 [INFO]  core: root token
generated
2023-11-23T15:14:38.999+0530 [INFO]  core: pre-seal teardown
starting
2023-11-23T15:14:38.999+0530 [INFO]  rollback: stopping
rollback manager
2023-11-23T15:14:38.999+0530 [INFO]  core: pre-seal teardown
complete
2023-11-23T15:14:39.311+0530 [INFO]  core.cluster-
listener.tcp: starting listener: listener_address=0.0.0.0:8201
2023-11-23T15:14:39.311+0530 [INFO]  core.cluster-listener:
serving cluster requests: cluster_listen_address=[::]:8201
2023-11-23T15:14:39.312+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:14:39.312+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:14:39.312+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:14:39.313+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:14:39.313+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:14:39.313+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:14:39.314+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-11-23T15:14:39.314+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:14:39.314+0530 [INFO]  core: restoring leases
2023-11-23T15:14:39.314+0530 [INFO]  identity: entities
restored
```

```
2023-11-23T15:14:39.314+0530 [INFO]  expiration: lease restore
complete
2023-11-23T15:14:39.314+0530 [INFO]  identity: groups restored
2023-11-23T15:14:39.315+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:14:39.316+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:14:39.316+0530 [INFO]  core: vault is unsealed
Success! Uploaded policy: mcctb-policy
2023-11-23T15:14:39.795+0530 [INFO]  core: enabled credential
backend: path=approle/ type=approle version=""
Success! Enabled approle auth method at: approle/
2023-11-23T15:14:39.885+0530 [INFO]  core: successful mount:
namespace="" path=mcctb/ type=kv version=""
Success! Enabled the kv secrets engine at: mcctb/
Success! Data written to: auth/approle/role/mcctb-app
Installing the NetApp-MetroCluster-Tiebreaker-Software-1.6-
1.x86_64.rpm
Preparing...                          #
################################# # [100%]

Updating / installing...

1:NetApp-MetroCluster-Tiebreaker-So#
################################# # [100%]
Performing file integrity check
etc/cron.weekly/metrocluster-tiebreaker-support is Ok
etc/cron.weekly/metrocluster-tiebreaker-support-cov is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software-cov is Ok
etc/logrotate.d/mcctb is Ok
opt/netapp/mcctb/lib/common/activation-1.1.1.jar is Ok
opt/netapp/mcctb/lib/common/aopalliance.jar is Ok
opt/netapp/mcctb/lib/common/args4j.jar is Ok
opt/netapp/mcctb/lib/common/aspectjrt.jar is Ok
opt/netapp/mcctb/lib/common/aspectjweaver.jar is Ok
opt/netapp/mcctb/lib/common/asup.jar is Ok
opt/netapp/mcctb/lib/common/bcpkix-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bctls-fips-1.0.13.jar is Ok
opt/netapp/mcctb/lib/common/bctls-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcutil-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/cglib.jar is Ok
opt/netapp/mcctb/lib/common/commons-codec.jar is Ok
opt/netapp/mcctb/lib/common/commons-collections4.jar is Ok
```

```
opt/netapp/mcctb/lib/common/commons-compress.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.src.jar is Ok
opt/netapp/mcctb/lib/common/commons-dbcp2.jar is Ok
opt/netapp/mcctb/lib/common/commons-io.jar is Ok
opt/netapp/mcctb/lib/common/commons-lang3.jar is Ok
opt/netapp/mcctb/lib/common/commons-logging.jar is Ok
opt/netapp/mcctb/lib/common/commons-pool2.jar is Ok
opt/netapp/mcctb/lib/common/guava.jar is Ok
opt/netapp/mcctb/lib/common/httpclient.jar is Ok
opt/netapp/mcctb/lib/common/httpcore.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.activation.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.xml.bind-api.jar is Ok
opt/netapp/mcctb/lib/common/java-xmlbuilder.jar is Ok
opt/netapp/mcctb/lib/common/javax.inject.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-api-2.3.1.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-core.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-impl.jar is Ok
opt/netapp/mcctb/lib/common/jline.jar is Ok
opt/netapp/mcctb/lib/common/jna.jar is Ok
opt/netapp/mcctb/lib/common/joda-time.jar is Ok
opt/netapp/mcctb/lib/common/jsch.jar is Ok
opt/netapp/mcctb/lib/common/json.jar is Ok
opt/netapp/mcctb/lib/common/jsvc.zip is Ok
opt/netapp/mcctb/lib/common/junixsocket-common.jar is Ok
opt/netapp/mcctb/lib/common/junixsocket-native-common.jar is
Ok
opt/netapp/mcctb/lib/common/logback-classic.jar is Ok
opt/netapp/mcctb/lib/common/logback-core.jar is Ok
opt/netapp/mcctb/lib/common/mail-1.6.2.jar is Ok
opt/netapp/mcctb/lib/common/mariadb-java-client.jar is Ok
opt/netapp/mcctb/lib/common/mcctb-mib.jar is Ok
opt/netapp/mcctb/lib/common/mcctb.jar is Ok
opt/netapp/mcctb/lib/common/mockito-core.jar is Ok
opt/netapp/mcctb/lib/common/slf4j-api.jar is Ok
opt/netapp/mcctb/lib/common/snmp4j.jar is Ok
opt/netapp/mcctb/lib/common/spring-aop.jar is Ok
opt/netapp/mcctb/lib/common/spring-beans.jar is Ok
opt/netapp/mcctb/lib/common/spring-context-support.jar is Ok
opt/netapp/mcctb/lib/common/spring-context.jar is Ok
opt/netapp/mcctb/lib/common/spring-core.jar is Ok
opt/netapp/mcctb/lib/common/spring-expression.jar is Ok
opt/netapp/mcctb/lib/common/spring-web.jar is Ok
opt/netapp/mcctb/lib/common/vault-java-driver.jar is Ok
opt/netapp/mcctb/lib/common/xz.jar is Ok
opt/netapp/mcctb/lib/org.jacoco.agent-0.8.8-runtime.jar is Ok
```

```
opt/netapp/mcctb/bin/mcctb-asup-invoke is Ok
opt/netapp/mcctb/bin/mcctb_postrotate is Ok
opt/netapp/mcctb/bin/netapp-metrocluster-tiebreaker-software-
cli is Ok
/

Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable
netapp-metrocluster-tiebreaker-software
Created symlink /etc/systemd/system/multi-
user.target.wants/netapp-metrocluster-tiebreaker-
software.service → /etc/systemd/system/netapp-metrocluster-
tiebreaker-software.service.

Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully installed NetApp MetroCluster Tiebreaker software
version 1.6.
```

Aggiornamento da 1,5 a 1,6

Per aggiornare la versione software di Tiebreaker 1,5 a Tiebreaker 1,6, procedere come segue.

Fasi

a. Eseguire il seguente comando nella `[root@mcctb ~] #` richiesta di aggiornamento del software:

```
sh MetroClusterTiebreakerInstall-1.6
```

Il sistema visualizza il seguente output per un aggiornamento riuscito:

Esempio

```
Extracting the MetroCluster Tiebreaker installation/upgrade
archive
Install digest hash is Ok
Performing the MetroCluster Tiebreaker code signature check
Install code signature is Ok

Enter database user name : root

Please enter database password for root
Enter password:

Password updated successfully in the database.

Do you wish to generate your own public-private key pair for
encrypting audit log? [Y/N]: y
Generating public-private key pair...
Configuring Vault...
==> Vault shutdown triggered
2023-07-21T00:30:22.335+0530 [INFO]  core: marked as sealed
2023-07-21T00:30:22.335+0530 [INFO]  core: pre-seal teardown
starting
2023-07-21T00:30:22.335+0530 [INFO]  rollback: stopping
rollback manager
2023-07-21T00:30:22.335+0530 [INFO]  core: pre-seal teardown
complete
2023-07-21T00:30:22.335+0530 [INFO]  core: stopping cluster
listeners
2023-07-21T00:30:22.335+0530 [INFO]  core.cluster-listener:
forwarding rpc listeners stopped
2023-07-21T00:30:22.375+0530 [INFO]  core.cluster-listener:
rpc listeners successfully shut down
2023-07-21T00:30:22.375+0530 [INFO]  core: cluster listeners
successfully shut down
2023-07-21T00:30:22.376+0530 [INFO]  core: vault is sealed
Starting vault server...
==> Vault server configuration:

             Api Address: <api_address>
                     Cgo: disabled
         Cluster Address: <cluster_address>
   Environment Variables: BASH_FUNC_which%%,
DBUS_SESSION_BUS_ADDRESS, GODEBUG, HISTCONTROL, HISTSIZE,
HOME, HOSTNAME, HOST_ACCOUNT, LANG, LESSOPEN, LOGNAME,
LS_COLORS, MAIL, PATH, PWD, SHELL, SHLVL, SSH_CLIENT,
```

```
SSH_CONNECTION, SSH_TTY, STAF_TEMP_DIR, TERM, USER,
VAULT_ADDR, VAULT_TOKEN, XDG_RUNTIME_DIR, XDG_SESSION_ID, _,
vault_Addr, which_declare
              Go Version: go1.20.5
              Listener 1: tcp (addr: "0.0.0.0:8200", cluster
address: "0.0.0.0:8201", max_request_duration: "1m30s",
max_request_size: "33554432", tls: "enabled")
               Log Level:
                   Mlock: supported: true, enabled: true
           Recovery Mode: false
                 Storage: file
                 Version: Vault v1.14.0, built 2023-06-
19T11:40:23Z
             Version Sha:
13a649f860186dffe3f3a4459814d87191efc321

==> Vault server started! Log data will stream in below:

2023-07-21T00:30:33.065+0530 [INFO]  proxy environment:
http_proxy="" https_proxy="" no_proxy=""
2023-07-21T00:30:33.098+0530 [INFO]  core: Initializing
version history cache for core
2023-07-21T00:30:43.092+0530 [INFO]  core: security barrier
not initialized
2023-07-21T00:30:43.092+0530 [INFO]  core: seal configuration
missing, not initialized
2023-07-21T00:30:43.094+0530 [INFO]  core: security barrier
not initialized
2023-07-21T00:30:43.096+0530 [INFO]  core: security barrier
initialized: stored=1 shares=5 threshold=3
2023-07-21T00:30:43.098+0530 [INFO]  core: post-unseal setup
starting
2023-07-21T00:30:43.124+0530 [INFO]  core: loaded wrapping
token key
2023-07-21T00:30:43.124+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-07-21T00:30:43.124+0530 [INFO]  core: no mounts; adding
default mount table
2023-07-21T00:30:43.125+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-07-21T00:30:43.126+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-07-21T00:30:43.126+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
```

```
path=identity/ namespace="ID: root. Path: "
2023-07-21T00:30:43.129+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-07-21T00:30:43.130+0530 [INFO]  rollback: starting
rollback manager
2023-07-21T00:30:43.130+0530 [INFO]  core: restoring leases
2023-07-21T00:30:43.130+0530 [INFO]  identity: entities
restored
2023-07-21T00:30:43.130+0530 [INFO]  identity: groups restored
2023-07-21T00:30:43.131+0530 [INFO]  core: usage gauge
collection is disabled
2023-07-21T00:30:43.131+0530 [INFO]  expiration: lease restore
complete
2023-07-21T00:30:43.131+0530 [INFO]  core: Recorded vault
version: vault version=1.14.0 upgrade time="2023-07-20
19:00:43.131158543 +0000 UTC" build date=2023-06-19T11:40:23Z
2023-07-21T00:30:43.371+0530 [INFO]  core: post-unseal setup
complete
2023-07-21T00:30:43.371+0530 [INFO]  core: root token
generated
2023-07-21T00:30:43.371+0530 [INFO]  core: pre-seal teardown
starting
2023-07-21T00:30:43.371+0530 [INFO]  rollback: stopping
rollback manager
2023-07-21T00:30:43.372+0530 [INFO]  core: pre-seal teardown
complete
2023-07-21T00:30:43.694+0530 [INFO]  core.cluster-
listener.tcp: starting listener: listener_address=0.0.0.0:8201
2023-07-21T00:30:43.695+0530 [INFO]  core.cluster-listener:
serving cluster requests: cluster_listen_address=[::]:8201
2023-07-21T00:30:43.695+0530 [INFO]  core: post-unseal setup
starting
2023-07-21T00:30:43.696+0530 [INFO]  core: loaded wrapping
token key
2023-07-21T00:30:43.696+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-07-21T00:30:43.697+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-07-21T00:30:43.698+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-07-21T00:30:43.698+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
```

```
2023-07-21T00:30:43.701+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
2023-07-21T00:30:43.701+0530 [INFO]  rollback: starting
rollback manager
2023-07-21T00:30:43.702+0530 [INFO]  core: restoring leases
2023-07-21T00:30:43.702+0530 [INFO]  identity: entities
restored
2023-07-21T00:30:43.702+0530 [INFO]  expiration: lease restore
complete
2023-07-21T00:30:43.702+0530 [INFO]  identity: groups restored
2023-07-21T00:30:43.702+0530 [INFO]  core: usage gauge
collection is disabled
2023-07-21T00:30:43.703+0530 [INFO]  core: post-unseal setup
complete
2023-07-21T00:30:43.703+0530 [INFO]  core: vault is unsealed
Success! Uploaded policy: mcctb-policy
2023-07-21T00:30:44.226+0530 [INFO]  core: enabled credential
backend: path=approle/ type=approle version=""
Success! Enabled approle auth method at: approle/
2023-07-21T00:30:44.315+0530 [INFO]  core: successful mount:
namespace="" path=mcctb/ type=kv version=""
Success! Enabled the kv secrets engine at: mcctb/
Success! Data written to: auth/approle/role/mcctb-app
Upgrading to NetApp-MetroCluster-Tiebreaker-Software-1.6-
1.x86_64.rpm
Preparing...
################################# [100%]
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################# [ 50%]
Performing file integrity check
etc/cron.weekly/metrocluster-tiebreaker-support is Ok
etc/cron.weekly/metrocluster-tiebreaker-support-cov is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software-cov is Ok
etc/logrotate.d/mcctb is Ok
opt/netapp/mcctb/lib/common/activation-1.1.1.jar is Ok
opt/netapp/mcctb/lib/common/aopalliance.jar is Ok
opt/netapp/mcctb/lib/common/args4j.jar is Ok
opt/netapp/mcctb/lib/common/aspectjrt.jar is Ok
opt/netapp/mcctb/lib/common/aspectjweaver.jar is Ok
opt/netapp/mcctb/lib/common/asup.jar is Ok
opt/netapp/mcctb/lib/common/bcpkix-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk18on.jar is Ok
```

```
opt/netapp/mcctb/lib/common/bctls-fips-1.0.13.jar is Ok
opt/netapp/mcctb/lib/common/bctls-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcutil-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/cglib.jar is Ok
opt/netapp/mcctb/lib/common/commons-codec.jar is Ok
opt/netapp/mcctb/lib/common/commons-collections4.jar is Ok
opt/netapp/mcctb/lib/common/commons-compress.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.src.jar is Ok
opt/netapp/mcctb/lib/common/commons-dbcp2.jar is Ok
opt/netapp/mcctb/lib/common/commons-io.jar is Ok
opt/netapp/mcctb/lib/common/commons-lang3.jar is Ok
opt/netapp/mcctb/lib/common/commons-logging.jar is Ok
opt/netapp/mcctb/lib/common/commons-pool2.jar is Ok
opt/netapp/mcctb/lib/common/guava.jar is Ok
opt/netapp/mcctb/lib/common/httpclient.jar is Ok
opt/netapp/mcctb/lib/common/httpcore.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.activation.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.xml.bind-api.jar is Ok
opt/netapp/mcctb/lib/common/java-xmlbuilder.jar is Ok
opt/netapp/mcctb/lib/common/javax.inject.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-api-2.3.1.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-core.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-impl.jar is Ok
opt/netapp/mcctb/lib/common/jline.jar is Ok
opt/netapp/mcctb/lib/common/jna.jar is Ok
opt/netapp/mcctb/lib/common/joda-time.jar is Ok
opt/netapp/mcctb/lib/common/jsch.jar is Ok
opt/netapp/mcctb/lib/common/json.jar is Ok
opt/netapp/mcctb/lib/common/jsvc.zip is Ok
opt/netapp/mcctb/lib/common/junixsocket-common.jar is Ok
opt/netapp/mcctb/lib/common/junixsocket-native-common.jar is
Ok
opt/netapp/mcctb/lib/common/logback-classic.jar is Ok
opt/netapp/mcctb/lib/common/logback-core.jar is Ok
opt/netapp/mcctb/lib/common/mail-1.6.2.jar is Ok
opt/netapp/mcctb/lib/common/mariadb-java-client.jar is Ok
opt/netapp/mcctb/lib/common/mcctb-mib.jar is Ok
opt/netapp/mcctb/lib/common/mcctb.jar is Ok
opt/netapp/mcctb/lib/common/mockito-core.jar is Ok
opt/netapp/mcctb/lib/common/slf4j-api.jar is Ok
opt/netapp/mcctb/lib/common/snmp4j.jar is Ok
opt/netapp/mcctb/lib/common/spring-aop.jar is Ok
opt/netapp/mcctb/lib/common/spring-beans.jar is Ok
opt/netapp/mcctb/lib/common/spring-context-support.jar is Ok
opt/netapp/mcctb/lib/common/spring-context.jar is Ok
```

```
opt/netapp/mcctb/lib/common/spring-core.jar is Ok
opt/netapp/mcctb/lib/common/spring-expression.jar is Ok
opt/netapp/mcctb/lib/common/spring-web.jar is Ok
opt/netapp/mcctb/lib/common/vault-java-driver.jar is Ok
opt/netapp/mcctb/lib/common/xz.jar is Ok
opt/netapp/mcctb/bin/mcctb_postrotate is Ok
opt/netapp/mcctb/bin/netapp-metrocluster-tiebreaker-software-
cli is Ok
/

Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable
netapp-metrocluster-tiebreaker-software

Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully upgraded NetApp MetroCluster Tiebreaker software
to version 1.6.
Cleaning up / removing...
   2:NetApp-MetroCluster-Tiebreaker-
So################################## [100%]
```

Aggiornamento da 1,4 a 1,6

Per aggiornare la versione software di Tiebreaker 1,4 a Tiebreaker 1,6, procedere come segue.

Fasi

a. Eseguire il seguente comando nella `[root@mcctb ~] #` richiesta di aggiornamento del software:

```
sh MetroClusterTiebreakerInstall-1.6
```

Il sistema visualizza il seguente output per un aggiornamento riuscito:

Esempio

```
Extracting the MetroCluster Tiebreaker installation/upgrade
archive
Install digest hash is Ok
Performing the MetroCluster Tiebreaker code signature check
Install code signature is Ok
Enter unix user account to use for the installation:
mcctbuseradmin1
Unix user account "mcctbuseradmin1" doesn't exist. Do you wish
to create "mcctbuseradmin1" user account? [Y/N]: y
Unix account "mcctbuseradmin1" created.
Changing password for user mcctbuseradmin1.
New password:
Retype new password:
passwd: all authentication tokens updated successfully.

Enter database user name : root

Please enter database password for root
Enter password:

Password updated successfully in the database.

MetroCluster Tiebreaker requires unix user account
"mcctbuseradmin1" to be added to the group "mcctbgrp" for
admin access.
Do you wish to add ? [Y/N]: y
Unix user account "mcctbuseradmin1" added to "mcctbgrp".
Do you wish to generate your own public-private key pair for
encrypting audit log? [Y/N]: y
Generating public-private key pair...
Configuring Vault...
Starting vault server...
==> Vault server configuration:

             Api Address: <api_addess>
                     Cgo: disabled
         Cluster Address: <cluster_address>
   Environment Variables: BASH_FUNC_which%%,
DBUS_SESSION_BUS_ADDRESS, GODEBUG, HISTCONTROL, HISTSIZE,
HOME, HOSTNAME, HOST_ACCOUNT, LANG, LESSOPEN, LOGNAME,
LS_COLORS, MAIL, PATH, PWD, SHELL, SHLVL, SSH_CLIENT,
SSH_CONNECTION, SSH_TTY, STAF_TEMP_DIR, TERM, USER,
VAULT_ADDR, VAULT_TOKEN, XDG_RUNTIME_DIR, XDG_SESSION_ID, _,
vault_Addr, which_declare
```

```
              Go Version: go1.20.5
              Listener 1: tcp (addr: "0.0.0.0:8200", cluster
address: "0.0.0.0:8201", max_request_duration: "1m30s",
max_request_size: "33554432", tls: "enabled")
               Log Level:
                   Mlock: supported: true, enabled: true
           Recovery Mode: false
                 Storage: file
                 Version: Vault v1.14.0, built 2023-06-
19T11:40:23Z
             Version Sha:
13a649f860186dffe3f3a4459814d87191efc321

==> Vault server started! Log data will stream in below:

2023-11-23T15:58:10.400+0530 [INFO]  proxy environment:
http_proxy="" https_proxy="" no_proxy=""
2023-11-23T15:58:10.432+0530 [INFO]  core: Initializing
version history cache for core
2023-11-23T15:58:20.422+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:58:20.422+0530 [INFO]  core: seal configuration
missing, not initialized
2023-11-23T15:58:20.424+0530 [INFO]  core: security barrier
not initialized
2023-11-23T15:58:20.425+0530 [INFO]  core: security barrier
initialized: stored=1 shares=5 threshold=3
2023-11-23T15:58:20.427+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:58:20.448+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:58:20.448+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:58:20.448+0530 [INFO]  core: no mounts; adding
default mount table
2023-11-23T15:58:20.449+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:58:20.449+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:58:20.449+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:58:20.451+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
```

```
path=token/ namespace="ID: root. Path: "
2023-11-23T15:58:20.452+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:58:20.452+0530 [INFO]  core: restoring leases
2023-11-23T15:58:20.453+0530 [INFO]  identity: entities
restored
2023-11-23T15:58:20.453+0530 [INFO]  identity: groups restored
2023-11-23T15:58:20.453+0530 [INFO]  expiration: lease restore
complete
2023-11-23T15:58:20.453+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:58:20.453+0530 [INFO]  core: Recorded vault
version: vault version=1.14.0 upgrade time="2023-11-23
10:28:20.453481904 +0000 UTC" build date=2023-06-19T11:40:23Z
2023-11-23T15:58:20.818+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:58:20.819+0530 [INFO]  core: root token
generated
2023-11-23T15:58:20.819+0530 [INFO]  core: pre-seal teardown
starting
2023-11-23T15:58:20.819+0530 [INFO]  rollback: stopping
rollback manager
2023-11-23T15:58:20.819+0530 [INFO]  core: pre-seal teardown
complete
2023-11-23T15:58:21.116+0530 [INFO]  core.cluster-
listener.tcp: starting listener: listener_address=0.0.0.0:8201
2023-11-23T15:58:21.116+0530 [INFO]  core.cluster-listener:
serving cluster requests: cluster_listen_address=[::]:8201
2023-11-23T15:58:21.117+0530 [INFO]  core: post-unseal setup
starting
2023-11-23T15:58:21.117+0530 [INFO]  core: loaded wrapping
token key
2023-11-23T15:58:21.117+0530 [INFO]  core: successfully setup
plugin catalog: plugin-directory=""
2023-11-23T15:58:21.119+0530 [INFO]  core: successfully
mounted: type=system version="v1.14.0+builtin.vault" path=sys/
namespace="ID: root. Path: "
2023-11-23T15:58:21.120+0530 [INFO]  core: successfully
mounted: type=identity version="v1.14.0+builtin.vault"
path=identity/ namespace="ID: root. Path: "
2023-11-23T15:58:21.120+0530 [INFO]  core: successfully
mounted: type=cubbyhole version="v1.14.0+builtin.vault"
path=cubbyhole/ namespace="ID: root. Path: "
2023-11-23T15:58:21.123+0530 [INFO]  core: successfully
mounted: type=token version="v1.14.0+builtin.vault"
path=token/ namespace="ID: root. Path: "
```

```
2023-11-23T15:58:21.123+0530 [INFO]  rollback: starting
rollback manager
2023-11-23T15:58:21.124+0530 [INFO]  core: restoring leases
2023-11-23T15:58:21.124+0530 [INFO]  identity: entities
restored
2023-11-23T15:58:21.124+0530 [INFO]  identity: groups restored
2023-11-23T15:58:21.124+0530 [INFO]  expiration: lease restore
complete
2023-11-23T15:58:21.125+0530 [INFO]  core: usage gauge
collection is disabled
2023-11-23T15:58:21.125+0530 [INFO]  core: post-unseal setup
complete
2023-11-23T15:58:21.125+0530 [INFO]  core: vault is unsealed
Success! Uploaded policy: mcctb-policy
2023-11-23T15:58:21.600+0530 [INFO]  core: enabled credential
backend: path=approle/ type=approle version=""
Success! Enabled approle auth method at: approle/
2023-11-23T15:58:21.690+0530 [INFO]  core: successful mount:
namespace="" path=mcctb/ type=kv version=""
Success! Enabled the kv secrets engine at: mcctb/
Success! Data written to: auth/approle/role/mcctb-app
Upgrading to NetApp-MetroCluster-Tiebreaker-Software-1.6-
1.x86_64.rpm
Preparing...
################################# [100%]
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################# [ 50%]
Performing file integrity check
etc/cron.weekly/metrocluster-tiebreaker-support is Ok
etc/cron.weekly/metrocluster-tiebreaker-support-cov is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software is Ok
etc/init.d/netapp-metrocluster-tiebreaker-software-cov is Ok
etc/logrotate.d/mcctb is Ok
opt/netapp/mcctb/lib/common/activation-1.1.1.jar is Ok
opt/netapp/mcctb/lib/common/aopalliance.jar is Ok
opt/netapp/mcctb/lib/common/args4j.jar is Ok
opt/netapp/mcctb/lib/common/aspectjrt.jar is Ok
opt/netapp/mcctb/lib/common/aspectjweaver.jar is Ok
opt/netapp/mcctb/lib/common/asup.jar is Ok
opt/netapp/mcctb/lib/common/bcpkix-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk15on.jar is Ok
opt/netapp/mcctb/lib/common/bcprov-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bctls-fips-1.0.13.jar is Ok
opt/netapp/mcctb/lib/common/bctls-jdk18on.jar is Ok
opt/netapp/mcctb/lib/common/bcutil-jdk18on.jar is Ok
```

```
opt/netapp/mcctb/lib/common/cglib.jar is Ok
opt/netapp/mcctb/lib/common/commons-codec.jar is Ok
opt/netapp/mcctb/lib/common/commons-collections4.jar is Ok
opt/netapp/mcctb/lib/common/commons-compress.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.jar is Ok
opt/netapp/mcctb/lib/common/commons-daemon.src.jar is Ok
opt/netapp/mcctb/lib/common/commons-dbcp2.jar is Ok
opt/netapp/mcctb/lib/common/commons-io.jar is Ok
opt/netapp/mcctb/lib/common/commons-lang3.jar is Ok
opt/netapp/mcctb/lib/common/commons-logging.jar is Ok
opt/netapp/mcctb/lib/common/commons-pool2.jar is Ok
opt/netapp/mcctb/lib/common/guava.jar is Ok
opt/netapp/mcctb/lib/common/httpclient.jar is Ok
opt/netapp/mcctb/lib/common/httpcore.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.activation.jar is Ok
opt/netapp/mcctb/lib/common/jakarta.xml.bind-api.jar is Ok
opt/netapp/mcctb/lib/common/java-xmlbuilder.jar is Ok
opt/netapp/mcctb/lib/common/javax.inject.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-api-2.3.1.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-core.jar is Ok
opt/netapp/mcctb/lib/common/jaxb-impl.jar is Ok
opt/netapp/mcctb/lib/common/jline.jar is Ok
opt/netapp/mcctb/lib/common/jna.jar is Ok
opt/netapp/mcctb/lib/common/joda-time.jar is Ok
opt/netapp/mcctb/lib/common/jsch.jar is Ok
opt/netapp/mcctb/lib/common/json.jar is Ok
opt/netapp/mcctb/lib/common/jsvc.zip is Ok
opt/netapp/mcctb/lib/common/junixsocket-common.jar is Ok
opt/netapp/mcctb/lib/common/junixsocket-native-common.jar is
Ok
opt/netapp/mcctb/lib/common/logback-classic.jar is Ok
opt/netapp/mcctb/lib/common/logback-core.jar is Ok
opt/netapp/mcctb/lib/common/mail-1.6.2.jar is Ok
opt/netapp/mcctb/lib/common/mariadb-java-client.jar is Ok
opt/netapp/mcctb/lib/common/mcctb-mib.jar is Ok
opt/netapp/mcctb/lib/common/mcctb.jar is Ok
opt/netapp/mcctb/lib/common/mockito-core.jar is Ok
opt/netapp/mcctb/lib/common/slf4j-api.jar is Ok
opt/netapp/mcctb/lib/common/snmp4j.jar is Ok
opt/netapp/mcctb/lib/common/spring-aop.jar is Ok
opt/netapp/mcctb/lib/common/spring-beans.jar is Ok
opt/netapp/mcctb/lib/common/spring-context-support.jar is Ok
opt/netapp/mcctb/lib/common/spring-context.jar is Ok
opt/netapp/mcctb/lib/common/spring-core.jar is Ok
opt/netapp/mcctb/lib/common/spring-expression.jar is Ok
opt/netapp/mcctb/lib/common/spring-web.jar is Ok
```

```
opt/netapp/mcctb/lib/common/vault-java-driver.jar is Ok
opt/netapp/mcctb/lib/common/xz.jar is Ok
opt/netapp/mcctb/lib/org.jacoco.agent-0.8.8-runtime.jar is Ok
opt/netapp/mcctb/bin/mcctb-asup-invoke is Ok
opt/netapp/mcctb/bin/mcctb_postrotate is Ok
opt/netapp/mcctb/bin/netapp-metrocluster-tiebreaker-software-
cli is Ok
/

Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable
netapp-metrocluster-tiebreaker-software

Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully upgraded NetApp MetroCluster Tiebreaker software
to version 1.6.
Cleaning up / removing...
   2:NetApp-MetroCluster-Tiebreaker-
So################################## [100%]
```

Installare il Tiebreaker 1,5

Configurare l'accesso amministratore all'API e all'SSH ONTAP

È possibile configurare l'accesso admin alle API e SSH ONTAP.

Fasi

1. Creare un utente amministratore con accesso API ONTAP: `security login create -user-or -group-name` *`mcctb`* `-application ontapi -authentication-method` *`password`*
2. Creare un utente amministratore con accesso SSH: `security login create -user-or-group -name` *`mcctb`* `-application` *`ssh`* `-authentication-method` *`password`*
3. Verificare che siano stati creati i nuovi utenti admin: `security login show`
4. Ripetere questi passaggi sul cluster partner.

> "Autenticazione amministratore e RBAC" è implementato.

Installare le dipendenze di MetroCluster tiebreaker 1,5

A seconda del sistema operativo Linux host, è necessario installare un server MySQL o MariaDB prima di installare o aggiornare il software tiebreaker.

Fasi

1. Installare JDK
2. Installare e configurare il vault
3. Installare il server MySQL o MariaDB:

Se l'host Linux è	Quindi…
Red Hat Enterprise Linux 7/CentOS 7	Installare MySQL Server 5.5.30 o versioni successive e 5,6.x su Red Hat Enterprise Linux 7 o CentOS 7
Red Hat Enterprise Linux 8	Installare il server MariaDB su Red Hat Enterprise Linux 8

Installare JDK

È necessario installare JDK sul sistema host prima di installare o aggiornare il software tiebreaker. Tiebreaker 1,5 e versioni successive supporta OpenJDK 17, 18 o 19.

Fasi

1. Accedere come utente "root" o come utente sudo che può passare alla modalità avanzata dei privilegi.

```
login as: root
root@mcctb's password:
Last login: Fri Jan  8 21:33:00 2017 from host.domain.com
```

2. Controllare le versioni JDK disponibili:

```
yum search openjdk
```

3. Installare JDK 17,18 o 19.

   Il seguente comando installa JDK 17:

```
yum install java-17-openjdk
```

4. Verificare l'installazione:

```
java -version
```

   Una corretta installazione visualizza il seguente output:

```
openjdk version "17.0.2" 2022-01-18 LTS
OpenJDK Runtime Environment 21.9 (build 17.0.2+8-LTS)
OpenJDK 64-Bit Server VM 21.9 (build 17.0.2+8-LTS, mixed mode, sharing)
```

Installare e configurare il vault

Se non si dispone o si desidera utilizzare il server del vault locale, è necessario installare Vault. Si può fare riferimento a questa procedura standard per l'installazione del vault o fare riferimento alle istruzioni di installazione di Hashicorp per linee guida alternative.

> Se si dispone di un server vault nella rete, è possibile configurare l'host MetroCluster Tiebreaker per l'utilizzo dell'installazione del vault. In questo caso, non è necessario installare Vault sull'host.

Fasi

1. Passare a. `/bin` directory:

```
[root@mcctb] cd /bin
```

2. Scaricare il file zip del vault.

```
[root@mcctb /bin]#  curl -sO
https://releases.hashicorp.com/vault/1.12.2/vault_1.12.2_linux_amd64.zip
```

3. Decomprimere il file del vault.

```
[root@mcctb /bin]# unzip vault_1.12.2_linux_amd64.zip
Archive:  vault_1.12.2_linux_amd64.zip
  inflating: vault
```

4. Verificare l'installazione.

```
[root@mcctb /bin]# vault -version
Vault v1.12.2 (415e1fe3118eebd5df6cb60d13defdc01aa17b03), built 2022-11-
23T12:53:46Z
```

5. Passare a. `/root` directory:

```
[root@mcctb /bin] cd /root
```

6. Creare un file di configurazione del vault in `/root` directory.

Su `[root@mcctb ~]` prompt, copiare ed eseguire il comando seguente per creare `config.hcl` file:

```
# cat > config.hcl << EOF
 storage "file" {
  address = "127.0.0.1:8500"
  path    = "/mcctb_vdata/data"
 }
 listener "tcp" {
   address     = "127.0.0.1:8200"
   tls_disable = 1
 }
EOF
```

7. Avviare il server del vault:

```
[root@mcctb ~] vault server -config config.hcl &
```

8. Esportare l'indirizzo del vault.

```
[root@mcctb ~]# export VAULT_ADDR="http://127.0.0.1:8200"
```

9. Inizializzare il vault.

```
[root@mcctb ~]# vault operator init
2022-12-15T14:57:22.113+0530 [INFO]  core: security barrier not
initialized
2022-12-15T14:57:22.113+0530 [INFO]  core: seal configuration missing,
not initialized
2022-12-15T14:57:22.114+0530 [INFO]  core: security barrier not
initialized
2022-12-15T14:57:22.116+0530 [INFO]  core: security barrier initialized:
stored=1 shares=5 threshold=3
2022-12-15T14:57:22.118+0530 [INFO]  core: post-unseal setup starting
2022-12-15T14:57:22.137+0530 [INFO]  core: loaded wrapping token key
2022-12-15T14:57:22.137+0530 [INFO]  core: Recorded vault version: vault
version=1.12.2 upgrade time="2022-12-15 09:27:22.137200412 +0000 UTC"
build date=2022-11-23T12:53:46Z
2022-12-15T14:57:22.137+0530 [INFO]  core: successfully setup plugin
catalog: plugin-directory=""
2022-12-15T14:57:22.137+0530 [INFO]  core: no mounts; adding default
mount table
2022-12-15T14:57:22.143+0530 [INFO]  core: successfully mounted backend:
type=cubbyhole version="" path=cubbyhole/
```

```
2022-12-15T14:57:22.144+0530 [INFO]  core: successfully mounted backend:
type=system version="" path=sys/
2022-12-15T14:57:22.144+0530 [INFO]  core: successfully mounted backend:
type=identity version="" path=identity/
2022-12-15T14:57:22.148+0530 [INFO]  core: successfully enabled
credential backend: type=token version="" path=token/ namespace="ID:
root. Path: "
2022-12-15T14:57:22.149+0530 [INFO]  rollback: starting rollback manager
2022-12-15T14:57:22.149+0530 [INFO]  core: restoring leases
2022-12-15T14:57:22.150+0530 [INFO]  expiration: lease restore complete
2022-12-15T14:57:22.150+0530 [INFO]  identity: entities restored
2022-12-15T14:57:22.150+0530 [INFO]  identity: groups restored
2022-12-15T14:57:22.151+0530 [INFO]  core: usage gauge collection is
disabled
2022-12-15T14:57:23.385+0530 [INFO]  core: post-unseal setup complete
2022-12-15T14:57:23.387+0530 [INFO]  core: root token generated
2022-12-15T14:57:23.387+0530 [INFO]  core: pre-seal teardown starting
2022-12-15T14:57:23.387+0530 [INFO]  rollback: stopping rollback manager
2022-12-15T14:57:23.387+0530 [INFO]  core: pre-seal teardown complete
Unseal Key 1: <unseal_key_1_id>
Unseal Key 2: <unseal_key_2_id>
Unseal Key 3: <unseal_key_3_id>
Unseal Key 4: <unseal_key_4_id>
Unseal Key 5: <unseal_key_5_id>

Initial Root Token: <initial_root_token_id>


Vault initialized with 5 key shares and a key threshold of 3. Please
securely
distribute the key shares printed above. When the Vault is re-sealed,
restarted, or stopped, you must supply at least 3 of these keys to
unseal it
before it can start servicing requests.

Vault does not store the generated root key. Without at least 3 keys to
reconstruct the root key, Vault will remain permanently sealed!

It is possible to generate new unseal keys, provided you have a quorum
of
existing unseal keys shares. See "vault operator rekey" for more
information.
```

È necessario registrare e memorizzare gli ID della chiave e il token principale iniziale in una posizione sicura per poterli utilizzare successivamente nella procedura.

10. Esportare il token root del vault.

```
[root@mcctb ~]#  export VAULT_TOKEN="<initial_root_token_id>"
```

11. Rimuovere il sigillo del vault usando tre delle cinque chiavi create.

    È necessario eseguire `vault operator unseal` comando per ciascuna delle tre chiavi:

    a. Rimuovere il sigillo del vault usando la prima chiave:

```
[root@mcctb ~]# vault operator unseal
Unseal Key (will be hidden):
Key                Value
---                -----
Seal Type          shamir
Initialized        true
Sealed             true
Total Shares       5
Threshold          3
Unseal Progress    1/3
Unseal Nonce       <unseal_key_1_id>
Version            1.12.2
Build Date         2022-11-23T12:53:46Z
Storage Type       file
HA Enabled         false
```

    b. Rimuovere il sigillo del vault usando la seconda chiave:

```
[root@mcctb ~]# vault operator unseal
Unseal Key (will be hidden):
Key                Value
---                -----
Seal Type          shamir
Initialized        true
Sealed             true
Total Shares       5
Threshold          3
Unseal Progress    2/3
Unseal Nonce       <unseal_key_2_id>
Version            1.12.2
Build Date         2022-11-23T12:53:46Z
Storage Type       file
HA Enabled         false
```

c. Rimuovere il sigillo del vault usando la terza chiave:

```
[root@mcctb ~]# vault operator unseal
Unseal Key (will be hidden):
2022-12-15T15:15:00.980+0530 [INFO]  core.cluster-listener.tcp:
starting listener: listener_address=127.0.0.1:8201
2022-12-15T15:15:00.980+0530 [INFO]  core.cluster-listener: serving
cluster requests: cluster_listen_address=127.0.0.1:8201
2022-12-15T15:15:00.981+0530 [INFO]  core: post-unseal setup starting
2022-12-15T15:15:00.981+0530 [INFO]  core: loaded wrapping token key
2022-12-15T15:15:00.982+0530 [INFO]  core: successfully setup plugin
catalog: plugin-directory=""
2022-12-15T15:15:00.983+0530 [INFO]  core: successfully mounted
backend: type=system version="" path=sys/
2022-12-15T15:15:00.984+0530 [INFO]  core: successfully mounted
backend: type=identity version="" path=identity/
2022-12-15T15:15:00.984+0530 [INFO]  core: successfully mounted
backend: type=cubbyhole version="" path=cubbyhole/
2022-12-15T15:15:00.986+0530 [INFO]  core: successfully enabled
credential backend: type=token version="" path=token/ namespace="ID:
root. Path: "
2022-12-15T15:15:00.986+0530 [INFO]  rollback: starting rollback
manager
2022-12-15T15:15:00.987+0530 [INFO]  core: restoring leases
2022-12-15T15:15:00.987+0530 [INFO]  expiration: lease restore
complete
2022-12-15T15:15:00.987+0530 [INFO]  identity: entities restored
2022-12-15T15:15:00.987+0530 [INFO]  identity: groups restored
2022-12-15T15:15:00.988+0530 [INFO]  core: usage gauge collection is
disabled
2022-12-15T15:15:00.989+0530 [INFO]  core: post-unseal setup complete
2022-12-15T15:15:00.989+0530 [INFO]  core: vault is unsealed
Key             Value
---             -----
Seal Type       shamir
Initialized     true
Sealed          false
Total Shares    5
Threshold       3
Version         1.12.2
Build Date      2022-11-23T12:53:46Z
Storage Type    file
Cluster Name    vault-cluster
Cluster ID      <cluster_id>
HA Enabled      false
```

12. Verificare che lo stato del Vault Sealed sia falso.

```
[root@mcctb ~]# vault status
Key             Value
---             -----
Seal Type       shamir
Initialized     true
Sealed          false
Total Shares    5
Threshold       3
Version         1.12.2
Build Date      2022-11-23T12:53:46Z
Storage Type    file
Cluster Name    vault-cluster
Cluster ID      <cluster_id>
HA Enabled      false
```

13. Configurare il servizio Vault per avviarlo all'avvio.
    a. Eseguire il seguente comando: `cd /etc/systemd/system`

    ```
    [root@mcctb ~]#  cd /etc/systemd/system
    ```

    b. Su `[root@mcctb system]` Richiedere, copiare ed eseguire il comando seguente per creare il file di servizio del vault.

    ```
    # cat > vault.service << EOF
    [Unit]
    Description=Vault Service
    After=mariadb.service

    [Service]
    Type=forking
    ExecStart=/usr/bin/vault server -config /root/config.hcl &
    Restart=on-failure

    [Install]
    WantedBy=multi-user.target
    EOF
    ```

    c. Eseguire il seguente comando: `systemctl daemon-reload`

    ```
    [root@mcctb system]#  systemctl daemon-reload
    ```

d. Eseguire il seguente comando: `systemctl enable vault.service`

```
[root@mcctb system]#  systemctl enable vault.service
Created symlink /etc/systemd/system/multi-
user.target.wants/vault.service → /etc/systemd/system/vault.service.
```

Viene richiesto di utilizzare questa funzione durante l'installazione di MetroCluster Tiebreaker. Se si desidera modificare il metodo per dissigillare il vault, è necessario disinstallare e reinstallare il software MetroCluster Tiebreaker.

Installare MySQL Server 5.5.30 o versioni successive e 5,6.x su Red Hat Enterprise Linux 7 o CentOS 7

È necessario installare MySQL Server 5.5.30 o versione successiva e la versione 5.6.x sul sistema host prima di installare o aggiornare il software Tiebreaker. Per Red Hat Enterprise Linux 8, Installare il server MariaDB.

Fasi

1. Accedere come utente root o sudo che può passare alla modalità avanzata dei privilegi.

```
login as: root
root@mcctb's password:
Last login: Fri Jan  8 21:33:00 2016 from host.domain.com
```

2. Aggiungi il repository MySQL al tuo sistema host:

```
[root@mcctb ~]# yum localinstall https://dev.mysql.com/get/mysql57-community-
release-el6-11.noarch.rpm
```

```
Loaded plugins: product-id, refresh-packagekit, security, subscription-
manager
Setting up Local Package Process
Examining /var/tmp/yum-root-LLUw0r/mysql-community-release-el6-
5.noarch.rpm: mysql-community-release-el6-5.noarch
Marking /var/tmp/yum-root-LLUw0r/mysql-community-release-el6-
5.noarch.rpm to be installed
Resolving Dependencies
--> Running transaction check
---> Package mysql-community-release.noarch 0:el6-5 will be installed
--> Finished Dependency Resolution
Dependencies Resolved
================================================================================
========
Package               Arch   Version
                                    Repository
Size
================================================================================
========
Installing:
mysql-community-release
                       noarch el6-5 /mysql-community-release-el6-
5.noarch 4.3 k
Transaction Summary
================================================================================
========
Install       1 Package(s)
Total size: 4.3 k
Installed size: 4.3 k
Is this ok [y/N]: y
Downloading Packages:
Running rpm_check_debug
Running Transaction Test
Transaction Test Succeeded
Running Transaction
  Installing : mysql-community-release-el6-5.noarch
1/1
  Verifying  : mysql-community-release-el6-5.noarch
1/1
Installed:
  mysql-community-release.noarch 0:el6-5
Complete!
```

3. Disattivare il repository MySQL 57:

```
[root@mcctb ~]# yum-config-manager --disable mysql57-community
```

4. Abilitare il repository MySQL 56:

```
[root@mcctb ~]# yum-config-manager --enable mysql56-community
```

5. Abilitare il repository:

```
[root@mcctb ~]# yum repolist enabled | grep "mysql.-community."
```

```
mysql-connectors-community           MySQL Connectors Community
21
mysql-tools-community                MySQL Tools Community
35
mysql56-community                    MySQL 5.6 Community Server
231
```

6. Installare il server della community MySQL:

```
[root@mcctb ~]# yum install mysql-community-server
```

```
Loaded plugins: product-id, refresh-packagekit, security, subscription-
manager
This system is not registered to Red Hat Subscription Management. You
can use subscription-manager
to register.
Setting up Install Process
Resolving Dependencies
--> Running transaction check
 .....Output truncated.....
---> Package mysql-community-libs-compat.x86_64 0:5.6.29-2.el6 will be
obsoleting
--> Finished Dependency Resolution
Dependencies Resolved
================================================================================
======
Package                          Arch   Version       Repository
Size
================================================================================
======
Installing:
 mysql-community-client         x86_64  5.6.29-2.el6  mysql56-community
18  M
     replacing  mysql.x86_64 5.1.71-1.el6
 mysql-community-libs           x86_64  5.6.29-2.el6  mysql56-community
1.9 M
```

```
     replacing  mysql-libs.x86_64 5.1.71-1.el6
 mysql-community-libs-compat    x86_64  5.6.29-2.el6  mysql56-community
1.6 M
     replacing  mysql-libs.x86_64 5.1.71-1.el6
 mysql-community-server         x86_64  5.6.29-2.el6  mysql56-community
53  M
     replacing  mysql-server.x86_64 5.1.71-1.el6
Installing for dependencies:
mysql-community-common          x86_64  5.6.29-2.el6  mysql56-community
308 k

Transaction Summary
================================================================================
=======
Install       5 Package(s)
Total download size: 74 M
Is this ok [y/N]: y
Downloading Packages:
(1/5): mysql-community-client-5.6.29-2.el6.x86_64.rpm       |  18 MB
00:28
(2/5): mysql-community-common-5.6.29-2.el6.x86_64.rpm       | 308 kB
00:01
(3/5): mysql-community-libs-5.6.29-2.el6.x86_64.rpm         | 1.9 MB
00:05
(4/5): mysql-community-libs-compat-5.6.29-2.el6.x86_64.rpm  | 1.6 MB
00:05
(5/5): mysql-community-server-5.6.29-2.el6.x86_64.rpm       |  53 MB
03:42
 --------------------------------------------------------------------------
--------
Total                                                289 kB/s |  74 MB
04:24
warning: rpmts_HdrFromFdno: Header V3 DSA/SHA1 Signature, key ID
<key_id> NOKEY
Retrieving key from file:/etc/pki/rpm-gpg/RPM-GPG-KEY-mysql
Importing GPG key 0x5072E1F5:
 Userid : MySQL Release Engineering <mysql-build@oss.oracle.com>
Package: mysql-community-release-el6-5.noarch
         (@/mysql-community-release-el6-5.noarch)
 From   : file:/etc/pki/rpm-gpg/RPM-GPG-KEY-mysql
Is this ok [y/N]: y
Running rpm_check_debug
Running Transaction Test
Transaction Test Succeeded
Running Transaction
  Installing : mysql-community-common-5.6.29-2.el6.x86_64
```

```
....Output truncated....
1.el6.x86_64
7/8
  Verifying  : mysql-5.1.71-1.el6.x86_64
8/8
Installed:
  mysql-community-client.x86_64 0:5.6.29-2.el6
  mysql-community-libs.x86_64 0:5.6.29-2.el6
  mysql-community-libs-compat.x86_64 0:5.6.29-2.el6
  mysql-community-server.x86_64 0:5.6.29-2.el6

Dependency Installed:
  mysql-community-common.x86_64 0:5.6.29-2.el6

Replaced:
  mysql.x86_64 0:5.1.71-1.el6 mysql-libs.x86_64 0:5.1.71-1.el6
  mysql-server.x86_64 0:5.1.71-1.el6
Complete!
```

7. Avviare il server MySQL:

```
[root@mcctb ~]# service mysqld start
```

```
Initializing MySQL database:  2016-04-05 19:44:38 0 [Warning] TIMESTAMP
with implicit DEFAULT value is deprecated. Please use
--explicit_defaults_for_timestamp server option (see documentation
for more details).
2016-04-05 19:44:38 0 [Note] /usr/sbin/mysqld (mysqld 5.6.29)
        starting as process 2487 ...
2016-04-05 19:44:38 2487 [Note] InnoDB: Using atomics to ref count
        buffer pool pages
2016-04-05 19:44:38 2487 [Note] InnoDB: The InnoDB memory heap is
disabled
....Output truncated....
2016-04-05 19:44:42 2509 [Note] InnoDB: Shutdown completed; log sequence
       number 1625987

PLEASE REMEMBER TO SET A PASSWORD FOR THE MySQL root USER!
To do so, start the server, then issue the following commands:

  /usr/bin/mysqladmin -u root password 'new-password'
  /usr/bin/mysqladmin -u root -h mcctb password 'new-password'

Alternatively, you can run:
  /usr/bin/mysql_secure_installation

which will also give you the option of removing the test
databases and anonymous user created by default.  This is
strongly recommended for production servers.
.....Output truncated.....
WARNING: Default config file /etc/my.cnf exists on the system
This file will be read by default by the MySQL server
If you do not want to use this, either remove it, or use the
--defaults-file argument to mysqld_safe when starting the server

                                                           [  OK  ]
Starting mysqld:                                           [  OK  ]
```

8. Verificare che MySQL Server sia in esecuzione:

```
[root@mcctb ~]# service mysqld status
```

```
mysqld (pid  2739) is running...
```

9. Configurare le impostazioni di sicurezza e password:

```
[root@mcctb ~]# mysql_secure_installation
```

```
NOTE: RUNNING ALL PARTS OF THIS SCRIPT IS RECOMMENDED FOR ALL MySQL
      SERVERS IN PRODUCTION USE!  PLEASE READ EACH STEP CAREFULLY!

 In order to log into MySQL to secure it, we'll need the current
 password for the root user.  If you've just installed MySQL, and
 you haven't set the root password yet, the password will be blank,
 so you should just press enter here.

 Enter current password for root (enter for none):   <== on default
install
                                                        hit enter here
 OK, successfully used password, moving on...

 Setting the root password ensures that nobody can log into the MySQL
 root user without the proper authorization.

 Set root password? [Y/n] y
 New password:
 Re-enter new password:
 Password updated successfully!
 Reloading privilege tables..
  ... Success!

 By default, a MySQL installation has an anonymous user, allowing anyone
 to log into MySQL without having to have a user account created for
 them.  This is intended only for testing, and to make the installation
 go a bit smoother.  You should remove them before moving into a
 production environment.

 Remove anonymous users? [Y/n] y
  ... Success!

 Normally, root should only be allowed to connect from 'localhost'.
This
 ensures that someone cannot guess at the root password from the
network.

 Disallow root login remotely? [Y/n] y
  ... Success!

 By default, MySQL comes with a database named 'test' that anyone can
 access.  This is also intended only for testing, and should be removed
 before moving into a production environment.

 Remove test database and access to it? [Y/n] y
  - Dropping test database...
 ERROR 1008 (HY000) at line 1: Can't drop database 'test';
```

```
database doesn't exist
 ... Failed!  Not critical, keep moving...
 - Removing privileges on test database...
 ... Success!

Reloading the privilege tables will ensure that all changes made so far
will take effect immediately.

Reload privilege tables now? [Y/n] y
 ... Success!

All done!  If you've completed all of the above steps, your MySQL
installation should now be secure.

Thanks for using MySQL!

Cleaning up...
```

10. Verificare che l'accesso MySQL funzioni:

```
[root@mcctb ~]# mysql -u root -p
```

```
Enter password: <configured_password>
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 17
Server version: 5.6.29 MySQL Community Server (GPL)

Copyright (c) 2000, 2016, Oracle and/or its affiliates. All rights
reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input
statement.
mysql>
```

Se il login MySQL funziona, l'output terminerà con `mysql>` prompt.

Abilitare l'impostazione di avvio automatico di MySQL

Verificare che la funzionalità di autostart sia attivata per il daemon MySQL. L'attivazione del daemon MySQL riavvia automaticamente MySQL se il sistema su cui risiede il software MetroCluster Tiebreaker si riavvia. Se il daemon MySQL non è in esecuzione, il software Tiebreaker continua a funzionare, ma non può essere riavviato e non è possibile apportare modifiche alla configurazione.

Fase

1. Verificare che MySQL sia abilitato all'avvio automatico all'avvio:

```
[root@mcctb ~]# systemctl list-unit-files mysqld.service
```

```
UNIT FILE          State
------------------ ----------
mysqld.service     enabled
```

Se MySQL non è abilitato all'avvio automatico all'avvio, consultare la documentazione di MySQL per abilitare la funzione di avvio automatico per l'installazione.

Installare il server MariaDB su Red Hat Enterprise Linux 8

È necessario installare il server MariaDB sul sistema host prima di installare o aggiornare il software Tiebreaker. Per Red Hat Enterprise Linux 7 o CentOS 7, Installare MySQL Server.

Prima di iniziare

Il sistema host deve essere in esecuzione su Red Hat Enterprise Linux (RHEL) 8.

Fasi

1. Accedere come a. `root` utente o utente che può passare alla modalità avanzata dei privilegi.

```
login as: root
root@mcctb's password:
Last login: Fri Jan  8 21:33:00 2017 from host.domain.com
```

2. Installare il server MariaDB:

```
[root@mcctb ~]# yum install mariadb-server.x86_64
```

```
[root@mcctb ~]# yum install mariadb-server.x86_64
Loaded plugins: fastestmirror, langpacks
 ...
 ...

================================================================================
===
 Package                       Arch    Version         Repository
Size
================================================================================
===
Installing:
mariadb-server                x86_64   1:5.5.56-2.el7   base
11 M
```

```
Installing for dependencies:

Transaction Summary
================================================================================
===
Install  1 Package  (+8 Dependent packages)
Upgrade             ( 1 Dependent package)

Total download size: 22 M
Is this ok [y/d/N]: y

Downloading packages:
No Presto metadata available for base warning:
/var/cache/yum/x86_64/7/base/packages/mariadb-libs-5.5.56-
2.el7.x86_64.rpm:
Header V3 RSA/SHA256 Signature,
key ID f4a80eb5: NOKEY] 1.4 MB/s | 3.3 MB  00:00:13 ETA
Public key for mariadb-libs-5.5.56-2.el7.x86_64.rpm is not installed
(1/10): mariadb-libs-5.5.56-2.el7.x86_64.rpm  | 757 kB  00:00:01
..
..
(10/10): perl-Net-Daemon-0.48-5.el7.noarch.rpm|  51 kB  00:00:01
--------------------------------------------------------------------------------
-----------------
Installed:
  mariadb-server.x86_64 1:5.5.56-2.el7

Dependency Installed:
mariadb.x86_64 1:5.5.56-2.el7
perl-Compress-Raw-Bzip2.x86_64 0:2.061-3.el7
perl-Compress-Raw-Zlib.x86_64 1:2.061-4.el7
perl-DBD-MySQL.x86_64 0:4.023-5.el7
perl-DBI.x86_64 0:1.627-4.el7
perl-IO-Compress.noarch 0:2.061-2.el7
perl-Net-Daemon.noarch 0:0.48-5.el7
perl-PlRPC.noarch 0:0.2020-14.el7

Dependency Updated:
  mariadb-libs.x86_64 1:5.5.56-2.el7
Complete!
```

3. Avviare il server MariaDB:

```
[root@mcctb ~]# systemctl start mariadb
```

4. Verificare che il server MariaDB sia stato avviato:

```
[root@mcctb ~]# systemctl status mariadb
```

```
[root@mcctb ~]# systemctl status mariadb
mariadb.service - MariaDB database server
...
Nov 08 21:28:59 mcctb systemd[1]: Starting MariaDB database server...
...
Nov 08 21:29:01 mcctb systemd[1]: Started MariaDB database server.
```

5. Configurare le impostazioni di sicurezza e password:

> Quando viene richiesta la password di root, lasciarla vuota e premere Invio per continuare a configurare le impostazioni di sicurezza e password.

```
[root@mcctb ~]# mysql_secure_installation
```

```
root@localhost systemd]# mysql_secure_installation

 NOTE: RUNNING ALL PARTS OF THIS SCRIPT IS RECOMMENDED FOR ALL MariaDB
      SERVERS IN PRODUCTION USE!  PLEASE READ EACH STEP CAREFULLY!

In order to log into MariaDB to secure it, we'll need the current
password for the root user.  If you've just installed MariaDB, and
you haven't set the root password yet, the password will be blank,
so you should just press enter here.

Enter current password for root (enter for none):
OK, successfully used password, moving on...

Setting the root password ensures that nobody can log into the MariaDB
root user without the proper authorisation.

Set root password? [Y/n] y
New password:
Re-enter new password:
Password updated successfully!
Reloading privilege tables..
 ... Success!


By default, a MariaDB installation has an anonymous user, allowing
anyone
to log into MariaDB without having to have a user account created for
them.  This is intended only for testing, and to make the installation
go a bit smoother.  You should remove them before moving into a
```

```
production environment.

Remove anonymous users? [Y/n] y
 ... Success!

Normally, root should only be allowed to connect from 'localhost'.  This
ensures that someone cannot guess at the root password from the network.

Disallow root login remotely? [Y/n] y
 ... Success!

By default, MariaDB comes with a database named 'test' that anyone can
access.  This is also intended only for testing, and should be removed
before moving into a production environment.

Remove test database and access to it? [Y/n] y
 - Dropping test database...
  ... Success!
 - Removing privileges on test database...
   ... Success!

Reloading the privilege tables will ensure that all changes made so far
will take effect immediately.

Reload privilege tables now? [Y/n]

 ... Success!

Cleaning up...

All done!  If you've completed all of the above steps, your MariaDB
installation should now be secure.

Thanks for using MariaDB!
```

Attivare l'impostazione di avvio automatico per il server MariaDB

Verificare che la funzione di avvio automatico sia attivata per il server MariaDB. Se non si attiva la funzione di avvio automatico e il sistema su cui risiede il software MetroCluster Tiebreaker deve essere riavviato, il software Tiebreaker continua a funzionare, ma il servizio MariaDB non può essere riavviato e non è possibile apportare modifiche alla configurazione.

Fasi

1. Attivare il servizio di avvio automatico:

```
[root@mcctb ~]# systemctl enable mariadb.service
```

2. Verificare che MariaDB sia abilitato all'avvio automatico all'avvio:

```
[root@mcctb ~]# systemctl list-unit-files mariadb.service
```

```
UNIT FILE          State
------------------ ----------
mariadb.service    enabled
```

Installare o aggiornare a tiebreaker 1,5

Eseguire una nuova installazione o un aggiornamento a tiebreaker 1,5 sul sistema operativo Linux host per monitorare le configurazioni MetroCluster.

A proposito di questa attività

- Nel tuo sistema storage deve essere in esecuzione una versione supportata di ONTAP. Vedere "Requisiti software" tabella per ulteriori dettagli.
- OpenJDK deve essere installato utilizzando `yum install java-x.x.x-openjdk` comando. Tiebreaker 1,5 e versioni successive supporta OpenJDK 17, 18 o 19.
- È possibile installare MetroCluster Tiebreaker come utente non root con privilegi amministrativi sufficienti per eseguire l'installazione di tiebreaker, creare tabelle e utenti e impostare la password utente.

Fasi

1. Scaricare il software MetroCluster Tiebreaker e la chiave MetroCluster_tiebreaker_RPM_GPG.

   La chiave MetroCluster_tiebreaker_RPM_GPG è disponibile per il download dalla stessa pagina in cui è stato scaricato il pacchetto software per tiebreaker 1,5 sul sito di supporto NetApp.

   "MetroCluster Tiebreaker (Download) - Sito di supporto NetApp"

2. Accedere all'host come utente root.
3. Creare un utente non root e. `mcctbgrp` gruppo.

   a. Creare un utente non root e impostare la password.

      I seguenti comandi di esempio creano un utente non root denominato `mcctbuser1`:

      ```
      [root@mcctb ~]# useradd mcctbuser1
      [root@mcctb ~]# passwd mcctbuser1
      Changing password for user mcctbuser1.
      New password:
      Retype new password:
      passwd: all authentication tokens updated successfully.
      ```

   b. Creare un gruppo denominato `mcctbgrp`:

```
[root@mcctb ~~]# groupadd mcctbgrp
```

c. Aggiungere l'utente non root creato al `mcctbgrp` gruppo.

Viene aggiunto il seguente comando `mcctbuser1` al `mcctbgrp` gruppo:

```
[root@mcctb ~]# usermod -a -G mcctbgrp mcctbuser1
```

4. Verificare il file RPM.

Eseguire i seguenti passaggi secondari dalla directory che contiene la chiave RPM.

a. Scaricare e importare il file della chiave RPM:

```
[root@mcctb ~]# rpm --import MetroCluster_Tiebreaker_RPM_GPG.key
```

b. Verificare che sia stata importata la chiave corretta controllando l'impronta digitale.

L'esempio seguente mostra un'impronta digitale della chiave corretta:

```
root@mcctb:~/signing/mcctb-rpms# gpg --show-keys --with-fingerprint
MetroCluster_Tiebreaker_RPM_GPG.key
pub   rsa3072 2022-11-17 [SCEA] [expires: 2025-11-16]
      65AC 1562 E28A 1497 7BBD  7251 2855 EB02 3E77 FAE5
uid                      MCCTB-RPM (mcctb RPM production signing)
<mcctb-rpm@netapp.com>
```

a. Verificare la firma: `rpm --checksig NetApp-MetroCluster-Tiebreaker-Software-1.5-1.x86_64.rpm`

```
NetApp-MetroCluster-Tiebreaker-Software-1.5-1.x86_64.rpm: digests OK
```

ⓘ È necessario procedere con l'installazione solo dopo aver verificato la firma.

5. Installa o aggiorna il software tiebreaker:

ⓘ È possibile eseguire l'aggiornamento alla versione 1.5 di Tiebreaker solo quando si esegue l'aggiornamento dalla versione 1.4 di Tiebreaker. L'aggiornamento da versioni precedenti a tiebreaker 1.5 non è supportato.

Selezionare la procedura corretta a seconda che si stia eseguendo una nuova installazione o aggiornando un'installazione esistente.

Eseguire una nuova installazione

a. Recuperare e registrare il percorso assoluto per Java:

```
[root@mcctb ~]# readlink -f /usr/bin/java
/usr/lib/jvm/java-19-openjdk-19.0.0.0.36-
2.rolling.el8.x86_64/bin/java
```

b. Eseguire il seguente comando: `rpm -ivh NetApp-MetroCluster-Tiebreaker-Software-1.5-1.x86_64.rpm`

Il sistema visualizza i seguenti output per una corretta installazione:

Quando richiesto durante l'installazione, fornire l'utente non root precedentemente creato e assegnato al `mcctbgrp` gruppo.

Esempio

```
Verifying...
################################# [100%]
Preparing...
################################# [100%]
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################# [100%]
Enter the absolute path for Java : /usr/lib/jvm/java-19-
openjdk-19.0.0.0.36-2.rolling.el8.x86_64/bin/java
Verifying if Java exists...
Found Java. Proceeding with the installation.
Enter host user account to use for the installation:
mcctbuser1
User account mcctbuser1 found. Proceeding with the
installation
Enter database user name:
root
Please enter database password for root
Enter password:
Sealed          false
Do you wish to auto unseal vault(y/n)?y
Enter the key1:
Enter the key2:
Enter the key3:
Success! Uploaded policy: mcctb-policy
Error enabling approle auth: Error making API request.
URL: POST http://127.0.0.1:8200/v1/sys/auth/approle
Code: 400. Errors:
* path is already in use at approle/
Success! Enabled the kv secrets engine at: mcctb/
Success! Data written to: auth/approle/role/mcctb-app
Password updated successfully in the vault.
Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable
netapp-metrocluster-tiebreaker-software
Created symlink /etc/systemd/system/multi-
user.target.wants/netapp-metrocluster-tiebreaker-
software.service → /etc/systemd/system/netapp-metrocluster-
tiebreaker-software.service.
Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
```

```
Successfully installed NetApp MetroCluster Tiebreaker software
version 1.5.
```

Aggiornamento di un'installazione esistente

a. Verificare che sia installata una versione supportata di OpenJDK e che sia la versione corrente di Java presente sull'host.

> Per gli aggiornamenti a tiebreaker 1.5, è necessario installare OpenJDK versione 17, 18 o 19.

```
[root@mcctb ~]# readlink -f /usr/bin/java
/usr/lib/jvm/java-19-openjdk-19.0.0.0.36-
2.rolling.el8.x86_64/bin/java
```

b. Verificare che il servizio Vault sia dissigillato e in esecuzione: `vault status`

```
[root@mcctb ~]# vault status
Key             Value
---             -----
Seal Type       shamir
Initialized     true
Sealed          false
Total Shares    5
Threshold       3
Version         1.12.2
Build Date      2022-11-23T12:53:46Z
Storage Type    file
Cluster Name    vault
Cluster ID      <cluster_id>
HA Enabled      false
```

c. Aggiornare il software Tiebreaker.

```
[root@mcctb ~]# rpm -Uvh NetApp-MetroCluster-Tiebreaker-Software-
1.5-1.x86_64.rpm
```

Il sistema visualizza il seguente output per un aggiornamento riuscito:

Esempio

```
Verifying...
################################# [100%]
Preparing...
################################# [100%]
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################# [ 50%]

Enter the absolute path for Java : /usr/lib/jvm/java-19-
openjdk-19.0.0.0.36-2.rolling.el8.x86_64/bin/java
Verifying if Java exists...
Found Java. Proceeding with the installation.
Enter host user account to use for the installation:
mcctbuser1
User account mcctbuser1 found. Proceeding with the
installation
Sealed          false
Do you wish to auto unseal vault(y/n)?y
Enter the key1:
Enter the key2:
Enter the key3:
Success! Uploaded policy: mcctb-policy
Error enabling approle auth: Error making API request.
URL: POST http://127.0.0.1:8200/v1/sys/auth/approle
Code: 400. Errors:
* path is already in use at approle/
Success! Enabled the kv secrets engine at: mcctb/
Success! Data written to: auth/approle/role/mcctb-app
Enter database user name : root
Please enter database password for root
Enter password:
Password updated successfully in the database.
Password updated successfully in the vault.
Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable
netapp-metrocluster-tiebreaker-software
Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Successfully upgraded NetApp MetroCluster Tiebreaker software
to version 1.5.
Cleaning up / removing...
```

```
   2:NetApp-MetroCluster-Tiebreaker-
So################################ [100%]
```

Se si immette la password root MySQL errata, il software Tiebreaker indica che è stato installato correttamente, ma visualizza i messaggi "Access denied" (accesso negato). Per risolvere il problema, è necessario disinstallare il software Tiebreaker utilizzando `rpm -e` E quindi reinstallare il software utilizzando la password root corretta di MySQL.

6. Verificare la connettività di Tiebreaker al software MetroCluster aprendo una connessione SSH dall'host di Tiebreaker a ciascuna delle LIF di gestione dei nodi e delle LIF di gestione dei cluster.

Informazioni correlate

"Supporto NetApp"

Installare il Tiebreaker 1,4

Installare le dipendenze di MetroCluster tiebreaker 1,4

A seconda del sistema operativo Linux host, installare un server MySQL o MariaDB prima di installare o aggiornare il software tiebreaker.

Fasi

1. Installare JDK.
2. Installare il server MySQL o MariaDB:

Se l'host Linux è	Quindi…
Red Hat Enterprise Linux 7/CentOS 7	Installare MySQL Server 5.5.30 o versioni successive e 5,6.x su Red Hat Enterprise Linux 7 o CentOS 7
Red Hat Enterprise Linux 8	Installare il server MariaDB su Red Hat Enterprise Linux 8

Installare JDK

È necessario installare JDK sul sistema host prima di installare o aggiornare il software tiebreaker. Tiebreaker 1,4 e versioni precedenti supporta JDK 1,8.0. (JRE 8).

Fasi

1. Accedere come utente "root".

```
login as: root
root@mcctb's password:
Last login: Fri Jan  8 21:33:00 2017 from host.domain.com
```

2. Installare JDK 1,8.0:

```
yum install java-1.8.0-openjdk.x86_64
```

```
[root@mcctb ~]# yum install java-1.8.0-openjdk.x86_64
Loaded plugins: fastestmirror, langpacks
Loading mirror speeds from cached hostfile
... shortened....
Dependencies Resolved

================================================================================
Package               Arch   Version                 Repository    Size
================================================================================
Installing:
 java-1.8.0-openjdk  x86_64  1:1.8.0.144-0.b01.el7_4 updates      238 k
 ..
 ..
Transaction Summary
================================================================================
Install  1 Package  (+ 4 Dependent packages)

Total download size: 34 M
Is this ok [y/d/N]: y

Installed:
java-1.8.0-openjdk.x86_64 1:1.8.0.144-0.b01.el7_4
Complete!
```

Installare MySQL Server 5.5.30 o versioni successive e 5,6.x su Red Hat Enterprise Linux 7 o CentOS 7

È necessario installare MySQL Server 5.5.30 o versione successiva e la versione 5.6.x sul sistema host prima di installare o aggiornare il software Tiebreaker. Per Red Hat Enterprise Linux 8, Installare il server MariaDB.

Fasi

1. Accedere come utente root.

```
login as: root
root@mcctb's password:
Last login: Fri Jan  8 21:33:00 2016 from host.domain.com
```

2. Aggiungi il repository MySQL al tuo sistema host:

```
[root@mcctb ~]# yum localinstall https://dev.mysql.com/get/mysql57-community-
release-el6-11.noarch.rpm
```

```
Loaded plugins: product-id, refresh-packagekit, security, subscription-
manager
Setting up Local Package Process
Examining /var/tmp/yum-root-LLUw0r/mysql-community-release-el6-
5.noarch.rpm: mysql-community-release-el6-5.noarch
Marking /var/tmp/yum-root-LLUw0r/mysql-community-release-el6-
5.noarch.rpm to be installed
Resolving Dependencies
--> Running transaction check
---> Package mysql-community-release.noarch 0:el6-5 will be installed
--> Finished Dependency Resolution
Dependencies Resolved
================================================================================
========
Package               Arch   Version
                                    Repository
Size
================================================================================
========
Installing:
mysql-community-release
                       noarch el6-5 /mysql-community-release-el6-
5.noarch 4.3 k
Transaction Summary
================================================================================
========
Install       1 Package(s)
Total size: 4.3 k
Installed size: 4.3 k
Is this ok [y/N]: y
Downloading Packages:
Running rpm_check_debug
Running Transaction Test
Transaction Test Succeeded
Running Transaction
  Installing : mysql-community-release-el6-5.noarch
1/1
  Verifying  : mysql-community-release-el6-5.noarch
1/1
Installed:
  mysql-community-release.noarch 0:el6-5
Complete!
```

3. Disattivare il repository MySQL 57:

```
[root@mcctb ~]# yum-config-manager --disable mysql57-community
```

4. Abilitare il repository MySQL 56:

```
[root@mcctb ~]# yum-config-manager --enable mysql56-community
```

5. Abilitare il repository:

```
[root@mcctb ~]# yum repolist enabled | grep "mysql.-community."
```

```
mysql-connectors-community           MySQL Connectors Community
21
mysql-tools-community                MySQL Tools Community
35
mysql56-community                    MySQL 5.6 Community Server
231
```

6. Installare il server della community MySQL:

```
[root@mcctb ~]# yum install mysql-community-server
```

```
Loaded plugins: product-id, refresh-packagekit, security, subscription-
manager
This system is not registered to Red Hat Subscription Management. You
can use subscription-manager
to register.
Setting up Install Process
Resolving Dependencies
--> Running transaction check
 .....Output truncated.....
---> Package mysql-community-libs-compat.x86_64 0:5.6.29-2.el6 will be
obsoleting
--> Finished Dependency Resolution
Dependencies Resolved
================================================================================
======
Package                          Arch   Version       Repository
Size
================================================================================
======
Installing:
 mysql-community-client         x86_64  5.6.29-2.el6  mysql56-community
18  M
     replacing  mysql.x86_64 5.1.71-1.el6
 mysql-community-libs           x86_64  5.6.29-2.el6  mysql56-community
1.9 M
```

```
     replacing  mysql-libs.x86_64 5.1.71-1.el6
 mysql-community-libs-compat    x86_64  5.6.29-2.el6  mysql56-community
1.6 M
     replacing  mysql-libs.x86_64 5.1.71-1.el6
 mysql-community-server         x86_64  5.6.29-2.el6  mysql56-community
53  M
     replacing  mysql-server.x86_64 5.1.71-1.el6
Installing for dependencies:
mysql-community-common          x86_64  5.6.29-2.el6  mysql56-community
308 k

Transaction Summary
================================================================================
=======
Install       5 Package(s)
Total download size: 74 M
Is this ok [y/N]: y
Downloading Packages:
(1/5): mysql-community-client-5.6.29-2.el6.x86_64.rpm       |  18 MB
00:28
(2/5): mysql-community-common-5.6.29-2.el6.x86_64.rpm       | 308 kB
00:01
(3/5): mysql-community-libs-5.6.29-2.el6.x86_64.rpm         | 1.9 MB
00:05
(4/5): mysql-community-libs-compat-5.6.29-2.el6.x86_64.rpm  | 1.6 MB
00:05
(5/5): mysql-community-server-5.6.29-2.el6.x86_64.rpm       |  53 MB
03:42
 ------------------------------------------------------------------------
--------
Total                                              289 kB/s |  74 MB
04:24
warning: rpmts_HdrFromFdno: Header V3 DSA/SHA1 Signature, key ID
<key_id> NOKEY
Retrieving key from file:/etc/pki/rpm-gpg/RPM-GPG-KEY-mysql
Importing GPG key 0x5072E1F5:
 Userid : MySQL Release Engineering <mysql-build@oss.oracle.com>
Package: mysql-community-release-el6-5.noarch
         (@/mysql-community-release-el6-5.noarch)
 From   : file:/etc/pki/rpm-gpg/RPM-GPG-KEY-mysql
Is this ok [y/N]: y
Running rpm_check_debug
Running Transaction Test
Transaction Test Succeeded
Running Transaction
  Installing : mysql-community-common-5.6.29-2.el6.x86_64
```

```
....Output truncated....
1.el6.x86_64
7/8
  Verifying  : mysql-5.1.71-1.el6.x86_64
8/8
Installed:
  mysql-community-client.x86_64 0:5.6.29-2.el6
  mysql-community-libs.x86_64 0:5.6.29-2.el6
  mysql-community-libs-compat.x86_64 0:5.6.29-2.el6
  mysql-community-server.x86_64 0:5.6.29-2.el6

Dependency Installed:
  mysql-community-common.x86_64 0:5.6.29-2.el6

Replaced:
  mysql.x86_64 0:5.1.71-1.el6 mysql-libs.x86_64 0:5.1.71-1.el6
  mysql-server.x86_64 0:5.1.71-1.el6
Complete!
```

7. Avviare il server MySQL:

```
[root@mcctb ~]# service mysqld start
```

```
Initializing MySQL database:  2016-04-05 19:44:38 0 [Warning] TIMESTAMP
with implicit DEFAULT value is deprecated. Please use
--explicit_defaults_for_timestamp server option (see documentation
for more details).
2016-04-05 19:44:38 0 [Note] /usr/sbin/mysqld (mysqld 5.6.29)
        starting as process 2487 ...
2016-04-05 19:44:38 2487 [Note] InnoDB: Using atomics to ref count
        buffer pool pages
2016-04-05 19:44:38 2487 [Note] InnoDB: The InnoDB memory heap is
disabled
....Output truncated....
2016-04-05 19:44:42 2509 [Note] InnoDB: Shutdown completed; log sequence
       number 1625987

PLEASE REMEMBER TO SET A PASSWORD FOR THE MySQL root USER!
To do so, start the server, then issue the following commands:

  /usr/bin/mysqladmin -u root password 'new-password'
  /usr/bin/mysqladmin -u root -h mcctb password 'new-password'

Alternatively, you can run:
  /usr/bin/mysql_secure_installation

which will also give you the option of removing the test
databases and anonymous user created by default.  This is
strongly recommended for production servers.
.....Output truncated.....
WARNING: Default config file /etc/my.cnf exists on the system
This file will be read by default by the MySQL server
If you do not want to use this, either remove it, or use the
--defaults-file argument to mysqld_safe when starting the server

                                                           [  OK  ]
Starting mysqld:                                           [  OK  ]
```

8. Verificare che MySQL Server sia in esecuzione:

```
[root@mcctb ~]# service mysqld status
```

```
mysqld (pid  2739) is running...
```

9. Configurare le impostazioni di sicurezza e password:

```
[root@mcctb ~]# mysql_secure_installation
```

```
NOTE: RUNNING ALL PARTS OF THIS SCRIPT IS RECOMMENDED FOR ALL MySQL
      SERVERS IN PRODUCTION USE!  PLEASE READ EACH STEP CAREFULLY!

 In order to log into MySQL to secure it, we'll need the current
 password for the root user.  If you've just installed MySQL, and
 you haven't set the root password yet, the password will be blank,
 so you should just press enter here.

 Enter current password for root (enter for none):   <== on default
install
                                                        hit enter here
 OK, successfully used password, moving on...

 Setting the root password ensures that nobody can log into the MySQL
 root user without the proper authorization.

 Set root password? [Y/n] y
 New password:
 Re-enter new password:
 Password updated successfully!
 Reloading privilege tables..
  ... Success!

 By default, a MySQL installation has an anonymous user, allowing anyone
 to log into MySQL without having to have a user account created for
 them.  This is intended only for testing, and to make the installation
 go a bit smoother.  You should remove them before moving into a
 production environment.

 Remove anonymous users? [Y/n] y
  ... Success!

 Normally, root should only be allowed to connect from 'localhost'.
This
 ensures that someone cannot guess at the root password from the
network.

 Disallow root login remotely? [Y/n] y
  ... Success!

 By default, MySQL comes with a database named 'test' that anyone can
 access.  This is also intended only for testing, and should be removed
 before moving into a production environment.

 Remove test database and access to it? [Y/n] y
  - Dropping test database...
 ERROR 1008 (HY000) at line 1: Can't drop database 'test';
```

```
database doesn't exist
 ... Failed!  Not critical, keep moving...
 - Removing privileges on test database...
 ... Success!

Reloading the privilege tables will ensure that all changes made so far
will take effect immediately.

Reload privilege tables now? [Y/n] y
 ... Success!

All done!  If you've completed all of the above steps, your MySQL
installation should now be secure.

Thanks for using MySQL!

Cleaning up...
```

10. Verificare che l'accesso MySQL funzioni:

```
[root@mcctb ~]# mysql -u root -p
```

```
Enter password: <configured_password>
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 17
Server version: 5.6.29 MySQL Community Server (GPL)

Copyright (c) 2000, 2016, Oracle and/or its affiliates. All rights
reserved.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input
statement.
mysql>
```

Quando il login MySQL funziona come previsto, l'output termina al `mysql>` prompt.

Abilitare l'impostazione di avvio automatico di MySQL

Verificare che la funzionalità di autostart sia attivata per il daemon MySQL. L'attivazione del daemon MySQL riavvia automaticamente MySQL se il sistema su cui risiede il software MetroCluster Tiebreaker si riavvia. Se il daemon MySQL non è in esecuzione, il software Tiebreaker continua a funzionare, ma non può essere riavviato e non è possibile apportare modifiche alla configurazione.

Fase

1. Verificare che MySQL sia abilitato all'avvio automatico all'avvio:

```
[root@mcctb ~]# systemctl list-unit-files mysqld.service
```

```
UNIT FILE          State
------------------ ----------
mysqld.service     enabled
```

Se MySQL non è abilitato all'avvio automatico all'avvio, consultare la documentazione di MySQL per abilitare la funzione di avvio automatico per l'installazione.

Installare il server MariaDB su Red Hat Enterprise Linux 8

È necessario installare il server MariaDB sul sistema host prima di installare o aggiornare il software Tiebreaker. Per Red Hat Enterprise Linux 7 o CentOS 7, Installare MySQL Server.

Prima di iniziare

Il sistema host deve essere in esecuzione su Red Hat Enterprise Linux (RHEL) 8.

Fasi

1. Accedere come a. `root` utente.

```
login as: root
root@mcctb's password:
Last login: Fri Jan  8 21:33:00 2017 from host.domain.com
```

2. Installare il server MariaDB:

```
[root@mcctb ~]# yum install mariadb-server.x86_64
```

```
[root@mcctb ~]# yum install mariadb-server.x86_64
Loaded plugins: fastestmirror, langpacks
 ...
 ...

================================================================================
===
 Package                       Arch    Version         Repository
Size
================================================================================
===
Installing:
mariadb-server                x86_64   1:5.5.56-2.el7   base
11 M
```

```
Installing for dependencies:

Transaction Summary
================================================================================
===
Install  1 Package  (+8 Dependent packages)
Upgrade             ( 1 Dependent package)

Total download size: 22 M
Is this ok [y/d/N]: y

Downloading packages:
No Presto metadata available for base warning:
/var/cache/yum/x86_64/7/base/packages/mariadb-libs-5.5.56-
2.el7.x86_64.rpm:
Header V3 RSA/SHA256 Signature,
key ID f4a80eb5: NOKEY] 1.4 MB/s | 3.3 MB  00:00:13 ETA
Public key for mariadb-libs-5.5.56-2.el7.x86_64.rpm is not installed
(1/10): mariadb-libs-5.5.56-2.el7.x86_64.rpm  | 757 kB  00:00:01
..
..
(10/10): perl-Net-Daemon-0.48-5.el7.noarch.rpm|  51 kB  00:00:01
--------------------------------------------------------------------------------
-----------------
Installed:
  mariadb-server.x86_64 1:5.5.56-2.el7

Dependency Installed:
mariadb.x86_64 1:5.5.56-2.el7
perl-Compress-Raw-Bzip2.x86_64 0:2.061-3.el7
perl-Compress-Raw-Zlib.x86_64 1:2.061-4.el7
perl-DBD-MySQL.x86_64 0:4.023-5.el7
perl-DBI.x86_64 0:1.627-4.el7
perl-IO-Compress.noarch 0:2.061-2.el7
perl-Net-Daemon.noarch 0:0.48-5.el7
perl-PlRPC.noarch 0:0.2020-14.el7

Dependency Updated:
  mariadb-libs.x86_64 1:5.5.56-2.el7
Complete!
```

3. Avviare il server MariaDB:

```
[root@mcctb ~]# systemctl start mariadb
```

4. Verificare che il server MariaDB sia stato avviato:

```
[root@mcctb ~]# systemctl status mariadb
```

```
[root@mcctb ~]# systemctl status mariadb
mariadb.service - MariaDB database server
...
Nov 08 21:28:59 mcctb systemd[1]: Starting MariaDB database server...
...
Nov 08 21:29:01 mcctb systemd[1]: Started MariaDB database server.
```

5. Configurare le impostazioni di sicurezza e password:

> Quando viene richiesta la password di root, lasciarla vuota e premere Invio per continuare a configurare le impostazioni di sicurezza e password.

```
[root@mcctb ~]# mysql_secure_installation
```

```
root@localhost systemd]# mysql_secure_installation

 NOTE: RUNNING ALL PARTS OF THIS SCRIPT IS RECOMMENDED FOR ALL MariaDB
      SERVERS IN PRODUCTION USE!  PLEASE READ EACH STEP CAREFULLY!

In order to log into MariaDB to secure it, we'll need the current
password for the root user.  If you've just installed MariaDB, and
you haven't set the root password yet, the password will be blank,
so you should just press enter here.

Enter current password for root (enter for none):
OK, successfully used password, moving on...

Setting the root password ensures that nobody can log into the MariaDB
root user without the proper authorisation.

Set root password? [Y/n] y
New password:
Re-enter new password:
Password updated successfully!
Reloading privilege tables..
 ... Success!


By default, a MariaDB installation has an anonymous user, allowing
anyone
to log into MariaDB without having to have a user account created for
them.  This is intended only for testing, and to make the installation
go a bit smoother.  You should remove them before moving into a
```

```
production environment.

Remove anonymous users? [Y/n] y
 ... Success!

Normally, root should only be allowed to connect from 'localhost'.  This
ensures that someone cannot guess at the root password from the network.

Disallow root login remotely? [Y/n] y
 ... Success!

By default, MariaDB comes with a database named 'test' that anyone can
access.  This is also intended only for testing, and should be removed
before moving into a production environment.

Remove test database and access to it? [Y/n] y
 - Dropping test database...
  ... Success!
 - Removing privileges on test database...
   ... Success!

Reloading the privilege tables will ensure that all changes made so far
will take effect immediately.

Reload privilege tables now? [Y/n]

  ... Success!

Cleaning up...

All done!  If you've completed all of the above steps, your MariaDB
installation should now be secure.

Thanks for using MariaDB!
```

Attivare l'impostazione di avvio automatico per il server MariaDB

Verificare che la funzione di avvio automatico sia attivata per il server MariaDB. Se non si attiva la funzione di avvio automatico e il sistema su cui risiede il software MetroCluster Tiebreaker deve essere riavviato, il software Tiebreaker continua a funzionare, ma il servizio MariaDB non può essere riavviato e non è possibile apportare modifiche alla configurazione.

Fasi

1. Attivare il servizio di avvio automatico:

```
[root@mcctb ~]# systemctl enable mariadb.service
```

2. Verificare che MariaDB sia abilitato all'avvio automatico all'avvio:

```
[root@mcctb ~]# systemctl list-unit-files mariadb.service
```

```
UNIT FILE          State
------------------ ----------
mariadb.service    enabled
```

Installare o aggiornare a tiebreaker 1,4

Eseguire una nuova installazione o un aggiornamento a tiebreaker 1,4 sul sistema operativo Linux host per monitorare le configurazioni MetroCluster.

A proposito di questa attività

- Nel tuo sistema storage deve essere in esecuzione una versione supportata di ONTAP. Vedere "Requisiti software" tabella per ulteriori dettagli.
- OpenJDK deve essere installato utilizzando `yum install java-x.x.x-openjdk` comando. Tiebreaker 1,4 e versioni precedenti supporta JDK 1.8.0 (JRE 8).

Fasi

1. Scaricare il software MetroCluster Tiebreaker.

   "MetroCluster Tiebreaker (Download) - Sito di supporto NetApp"

2. Accedere all'host come utente root.
3. Installa o aggiorna il software tiebreaker:

   Selezionare la procedura corretta a seconda che si stia eseguendo una nuova installazione o aggiornando un'installazione esistente.

Eseguire una nuova installazione

a. Installare il software Tiebreaker eseguendo :

```
rpm -ivh NetApp-MetroCluster-Tiebreaker-Software-1.4-1.x86_64.rpm
```

Il sistema visualizza i seguenti output per una corretta installazione:

```
Verifying...
################################# [100%]
Preparing...
################################# [100%]
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################# [100%]
Post installation start Fri Apr  5 02:28:09 EDT 2024
Enter MetroCluster Tiebreaker user password:

Please enter mysql root password when prompted
Enter password:
Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable netapp-
metrocluster-tiebreaker-software
Created symlink /etc/systemd/system/multi-
user.target.wants/netapp-metrocluster-tiebreaker-software.service
→ /etc/systemd/system/netapp-metrocluster-tiebreaker-
software.service.
Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Enabled autostart of NetApp MetroCluster Tiebreaker software
daemon during boot
Created symbolic link for NetApp MetroCluster Tiebreaker software
CLI
Post installation end Fri Apr  5 02:28:22 EDT 2024
Successfully installed NetApp MetroCluster Tiebreaker software
version 1.4.
```

Aggiornare un'installazione esistente

a. Aggiornare il software Tiebreaker.

```
[root@mcctb ~]# rpm -Uvh NetApp-MetroCluster-Tiebreaker-Software-
1.4-1.x86_64.rpm
```

Il sistema visualizza il seguente output per un aggiornamento riuscito:

```
Verifying...
################################# [100%]
Preparing...
################################# [100%]
Upgrading NetApp MetroCluster Tiebreaker software....
Stopping NetApp MetroCluster Tiebreaker software services before
upgrade.
Updating / installing...
   1:NetApp-MetroCluster-Tiebreaker-
So################################# [ 50%]
Post installation start Mon Apr  8 06:29:51 EDT 2024
Synchronizing state of netapp-metrocluster-tiebreaker-
software.service with SysV service script with
/usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable netapp-
metrocluster-tiebreaker-software
Attempting to start NetApp MetroCluster Tiebreaker software
services
Started NetApp MetroCluster Tiebreaker software services
Enabled autostart of NetApp MetroCluster Tiebreaker software
daemon during boot
Created symbolic link for NetApp MetroCluster Tiebreaker software
CLI
Post upgrade end Mon Apr  8 06:29:51 EDT 2024
Successfully upgraded NetApp MetroCluster Tiebreaker software to
version 1.4.
Cleaning up / removing...
   2:NetApp-MetroCluster-Tiebreaker-
So################################# [100%]
```

Se si immette la password root MySQL errata, il software Tiebreaker indica che è stato installato correttamente, ma visualizza i messaggi "Access denied" (accesso negato). Per risolvere il problema, è necessario disinstallare il software Tiebreaker utilizzando `rpm -e` E quindi reinstallare il software utilizzando la password root corretta di MySQL.

4. Verificare la connettività di Tiebreaker al software MetroCluster aprendo una connessione SSH dall'host di Tiebreaker a ciascuna delle LIF di gestione dei nodi e delle LIF di gestione dei cluster.

Informazioni correlate

"Supporto NetApp"

Informazioni sul copyright

Copyright © 2026 NetApp, Inc. Tutti i diritti riservati. Stampato negli Stati Uniti d'America. Nessuna porzione di questo documento soggetta a copyright può essere riprodotta in qualsiasi formato o mezzo (grafico, elettronico o meccanico, inclusi fotocopie, registrazione, nastri o storage in un sistema elettronico) senza previo consenso scritto da parte del detentore del copyright.

Il software derivato dal materiale sottoposto a copyright di NetApp è soggetto alla seguente licenza e dichiarazione di non responsabilità:

IL PRESENTE SOFTWARE VIENE FORNITO DA NETAPP "COSÌ COM'È" E SENZA QUALSIVOGLIA TIPO DI GARANZIA IMPLICITA O ESPRESSA FRA CUI, A TITOLO ESEMPLIFICATIVO E NON ESAUSTIVO, GARANZIE IMPLICITE DI COMMERCIABILITÀ E IDONEITÀ PER UNO SCOPO SPECIFICO, CHE VENGONO DECLINATE DAL PRESENTE DOCUMENTO. NETAPP NON VERRÀ CONSIDERATA RESPONSABILE IN ALCUN CASO PER QUALSIVOGLIA DANNO DIRETTO, INDIRETTO, ACCIDENTALE, SPECIALE, ESEMPLARE E CONSEQUENZIALE (COMPRESI, A TITOLO ESEMPLIFICATIVO E NON ESAUSTIVO, PROCUREMENT O SOSTITUZIONE DI MERCI O SERVIZI, IMPOSSIBILITÀ DI UTILIZZO O PERDITA DI DATI O PROFITTI OPPURE INTERRUZIONE DELL'ATTIVITÀ AZIENDALE) CAUSATO IN QUALSIVOGLIA MODO O IN RELAZIONE A QUALUNQUE TEORIA DI RESPONSABILITÀ, SIA ESSA CONTRATTUALE, RIGOROSA O DOVUTA A INSOLVENZA (COMPRESA LA NEGLIGENZA O ALTRO) INSORTA IN QUALSIASI MODO ATTRAVERSO L'UTILIZZO DEL PRESENTE SOFTWARE ANCHE IN PRESENZA DI UN PREAVVISO CIRCA L'EVENTUALITÀ DI QUESTO TIPO DI DANNI.

NetApp si riserva il diritto di modificare in qualsiasi momento qualunque prodotto descritto nel presente documento senza fornire alcun preavviso. NetApp non si assume alcuna responsabilità circa l'utilizzo dei prodotti o materiali descritti nel presente documento, con l'eccezione di quanto concordato espressamente e per iscritto da NetApp. L'utilizzo o l'acquisto del presente prodotto non comporta il rilascio di una licenza nell'ambito di un qualche diritto di brevetto, marchio commerciale o altro diritto di proprietà intellettuale di NetApp.

Il prodotto descritto in questa guida può essere protetto da uno o più brevetti degli Stati Uniti, esteri o in attesa di approvazione.

LEGENDA PER I DIRITTI SOTTOPOSTI A LIMITAZIONE: l'utilizzo, la duplicazione o la divulgazione da parte degli enti governativi sono soggetti alle limitazioni indicate nel sottoparagrafo (b)(3) della clausola Rights in Technical Data and Computer Software del DFARS 252.227-7013 (FEB 2014) e FAR 52.227-19 (DIC 2007).

I dati contenuti nel presente documento riguardano un articolo commerciale (secondo la definizione data in FAR 2.101) e sono di proprietà di NetApp, Inc. Tutti i dati tecnici e il software NetApp forniti secondo i termini del presente Contratto sono articoli aventi natura commerciale, sviluppati con finanziamenti esclusivamente privati. Il governo statunitense ha una licenza irrevocabile limitata, non esclusiva, non trasferibile, non cedibile, mondiale, per l'utilizzo dei Dati esclusivamente in connessione con e a supporto di un contratto governativo statunitense in base al quale i Dati sono distribuiti. Con la sola esclusione di quanto indicato nel presente documento, i Dati non possono essere utilizzati, divulgati, riprodotti, modificati, visualizzati o mostrati senza la previa approvazione scritta di NetApp, Inc. I diritti di licenza del governo degli Stati Uniti per il Dipartimento della Difesa sono limitati ai diritti identificati nella clausola DFARS 252.227-7015(b) (FEB 2014).

Informazioni sul marchio commerciale

NETAPP, il logo NETAPP e i marchi elencati alla pagina http://www.netapp.com/TM sono marchi di NetApp, Inc. Gli altri nomi di aziende e prodotti potrebbero essere marchi dei rispettivi proprietari.