



Registri eventi XCP

XCP

NetApp
May 21, 2024

Sommario

- Registri eventi XCP 1
- Registri eventi NFS XCP 1
- Registri eventi SMB XCP 13

Registri eventi XCP

Registri eventi NFS XCP

Esaminare i log eventi di esempio per XCP NFS.

La tabella seguente mostra i registri eventi per XCP NFS.

ID evento	Modello di evento	Esempio di evento
401	Mounted on NFS export <mount path> with maximum read block size <read block size> bytes, maximum write block size <write block size> bytes. Mount point has mode value<mode bits> and type: <fattr3 type>.	2020-07-14 03:53:59,811 - INFO {"Event ID":401, "Event Category": "Mounting unmounting file system", "Event Type": "Mount file system information", "ExecutionId": 408249379415, "Event Source": "NETAPP-01", "Description": "Mounted on NFS export <IPaddress of NFS server>:/test1 with maximum read block size 65536 bytes, maximum write block size 65536 bytes. Mount point has mode value 493 and type : Directory"}
181	This license is issued to <username>of <company name>,license type is <license type> with <license status> status, license will expire on <expire date>	2020-07-14 03:53:59,463 - INFO {"Event ID": 181, "Event Category": "Authentication and authorization", "Event Type": "License information", "ExecutionId": 408249379415, "Event Source": "NETAPP-01", "Description": "This license is issued to NetApp User of Network Appliance, Inc, license type is SANDBOX with ACTIVE status, license will expire on Thu Jul 1 00:00:00 2021"}

ID evento	Modello di evento	Esempio di evento
183	The license issued to <username> of <company name> will expire in less than one week	2020-07-14 04:02:55,151 - WARNING {"Event ID": 183, "Event Category": "Authentication and authorisation", "Event Type": "License warning", "ExecutionId": 408249519546, "Event Source": "NETAPP-01", "Description": "The license issued to NetApp User of Network Appliance, Inc will expire in less than one week"}
581	Catalog path <catalog volume path> to store catalog directory is not accessible. Refer user guide for configuring catalog volume.	2020-07-14 04:05:00,857 - ERROR {"Event ID": 581, "Event Category": "Catalog and indexing", "Event Type": "Catalog exporting error", "ExecutionId": 408249552351, "Event Source": "NETAPP-01", "Description": "Catalog path <IP address of NFS server>:/test11 to store catalog directory is not accessible. Refer user guide for configuring catalog volume."}
582	Failed creating catalog directory in catalog volume path <catalog volume path>	2020-07-14 04:10:12,895 - ERROR {"Event ID": 582, "Event Category": "Catalog and indexing", "Event Type": "Catalog directory creation error", "ExecutionId": 408249630498, "Event Source": "NETAPP-01", "Description": "Failed creating catalog directory in catalogvolume path 10.234.104.250:/cat_vol"}

ID evento	Modello di evento	Esempio di evento
584	Error in creating index directory <index id> for <command>	2020-07-14 04:52:15,918 - ERROR {"Event ID":584, "Event Category": "Catalog and indexing", "Event Type": "Error in index creation", "ExecutionId": 408250278214, "Event Source": "NETAPP-01", "Description": "Error in creating index directory abc7 for scan"}
586	Failed to create index <index id> in catalog volume while executing command : <command>	2020-07-14 04:45:46,275 - ERROR {"Event ID": 586, "Event Category": "Catalog and indexing", "Event Type": "Error in index creation", "ExecutionId": 408250177021, "Event Source": "NETAPP-01", "Description": "Failed to create index abc6 in catalog volume while executing command : scan {- newid: 'abc6'}"}
351	System resources available while executing xcp command: <command>, are : <CPU info>, <memory info>	2020-07-14 05:08:35,393 - INFO {"Event ID":351, "Event Category": "System resource utilization", "Event Type": "Resources available for scan", "ExecutionId": 408250529264, "Event Source": "NETAPP-01", "Description": "System resources available while executing xcp command : scan , are : CPU: count 4, load avg (1/5/15m) 0.0, 0.0, 0.0, System memory (GiB): avail 7.3, total 7.8, free 6.6, buffer 0.1, cache 0.5"}

ID evento	Modello di evento	Esempio di evento
13	XCP <command> is running on platform <platform info> for source <source info>	2020-07-14 05:08:35,478 - INFO {"Event ID": 13, "Event Category": "XCP job status", "Event Type": "Starting xcp scan operation", "ExecutionId": 408250529264, "Event Source": "NETAPP-01", "Description": "XCP command : scan {-newid: 'abc7'} is running on platform Linux-2.6.26-2-amd64-x86_64-with-debian- 5.0.10 for source 10.234.104.250:/test1"}
14	XCP scan completed successfully after scanning <scan item count> items. Source : <source scanned>	2020-07-14 05:08:35,653 - INFO {"Event ID": 14, "Event Category": "XCP job status", "Event Type": "XCP scan completion", "ExecutionId": 408250529264, "Event Source": "NETAPP-01", "Description": "XCP scan completed successfully after scanning 479 items. Source : 10.234.104.250:/test1"}
354	System resources available while executing xcp command: <command>, are : <CPU info>, <memory info>	2020-07-14 05:15:13,562 - INFO {"Event ID": 354, "Event Category": "System resource utilization", "Event Type": "Resources available for copy", "ExecutionId": 408250596708, "Event Source": "NETAPP-01", "Description": "System resources available while executing xcp command : copy , are : CPU: count 4, load avg (1/5/15m) 0.0, 0.0, 0.0, System memory (GiB): avail 7.3, total 7.8, free 6.6, buffer 0.1, cache 0.5"}

ID evento	Modello di evento	Esempio di evento
25	XCP <command> is running on platform <platform info> for source <copy source> and destination <copy destination/target>	2020-07-14 05:15:13,647 - INFO {"Event ID": 25, "Event Category": "XCP job status", "Event Type": "Starting xcp copy operation", "ExecutionId": 408250596708, "Event Source": "NETAPP-01", "Description": "XCP command : copy {} is running on platform Linux-2.6.26- 2-amd64-x86 64-with-debian-5.0.10 for source <IP address of NFS server>:/source_vol and destination <NFS destination source>:/test1"}
26	XCP copy completed successfully after scanning <scanned item count> of which <matched item count> are matched and <copied item count> items are copied to the destination. Source : <copy source>, destination :<copy destination/target	2020-07-14 05:15:13,885 - INFO {"Event ID":26, "Event Category": "XCP job status", "Event Type": "XCP copy completion", "ExecutionId": 408250596708, "Event Source": "NETAPP-01", "Description": "XCP copy completed successfully after scanning 3 of which 0 are matched and 2 items are copied to the destination. Source : <IP address of NFS server>:/source_vol, destination : <NFS destination source>:/test1"}

ID evento	Modello di evento	Esempio di evento
16	XCP <command> is running on platform <platform info> for source <sync source> and destination <sync destination>	2020-07-14 06:41:20,145 - INFO {"Event ID": 16, "Event Category": "XCP job status", "Event Type": "Starting xcp sync operation", "ExecutionId": 408251920146, "Event Source": "NETAPP-01", "Description": "XCP command : sync {-id: 'autoname_copy_2020-07-14_06.22.07.233271'} is running on platform Linux-2.6.26-2-amd64-x86_64-with-debian-5.0.10 for source <IP address of NFS server>:/src_vol and destination <NFS destination source>:/dest_vol"}
352	System resources available while executing xcp command: <command>, are : <CPU info>, <memory info>	2020-07-14 06:41:28,728 - INFO {"Event ID": 352, "Event Category": "System resource utilization", "Event Type": "Resource available for sync", "ExecutionId": 408251920146, "Event Source": "NETAPP-01", "Description": "System resources available while executing xcp command : sync {-id: 'autoname_copy_2020-07-14_06.22.07.233271'} , are : CPU: count 4, load avg (1/5/15m) 0.1, 0.0, 0.0, System memory (GiB): avail 7.2, total 7.8, free 6.6, buffer 0.1, cache 0.5"}

ID evento	Modello di evento	Esempio di evento
17	XCP sync is completed. Total scanned <scanned item count>, copied <copied item count>, modification <modification item count>, new file <new file count>, delete item <delete item count>. Command executed : <command>	2020-07-14 06:41:29,245 - INFO {"Event ID":17, "Event Category": "XCP job status", "Event Type": "XCP sync completion", "ExecutionId": 408251920146, "Event Source": "NETAPP-01", "Description": "XCP sync is completed. Total scanned 66, copied 0, modification 1, new file 0, delete item 0. Command executed : sync {-id: 'autoname_copy_2020-07-14_06.22.07.233271'}"}
19	XCP <command> is running on platform <platform info> for source <verify source> and destination <verify destination>	2020-07-14 06:54:59,084 - INFO {"Event ID": 19, "Event Category": "XCP job status", "Event Type": "Starting xcp verify operation", "ExecutionId": 408252130477, "Event Source": "NETAPP-01", "Description": "XCP command : verify {} is running on platform Linux-2.6.26-2-amd64-x86_64-with- debian-5.0.10 for source <IP address of NFS server>:/src_vol and destination <IP address of NFS destination server>:/dest_vol"}
353	System resources available while executing xcp command: <command>, are : <CPU info>, <memory info>	2020-07-14 06:54:59,085 - INFO {"Event ID": 353, "Event Category": "System resource utilization", "Event Type": "Resources available for verify", "ExecutionId": 408252130477, "Event Source": "NETAPP-01", "Description": "System resources available while executing xcp command : verify , are : CPU: count 4, load avg (1/5/15m) 0.0, 0.0, 0.0, System memory (GiB): avail 7.3, total 7.8, free 6.6, buffer 0.1, cache 0.5"}

ID evento	Modello di evento	Esempio di evento
211	log file path : <file path> , severity filter level <severity level>, log message sanitization is set as <sanitization value>	2020-07-14 06:40:59,104 - INFO {"Event ID": 211, "Event Category": "Logging and supportability", "Event Type": "XCP logging information", "ExecutionId": 408251920146, "Event Source": "NETAPP-01", "Description": "Log file path : /opt/NetApp/xFiles/xcp/xcplogs/xcp.log, severity filter level INFO, log message sanitization is set as False"}
215	Event file path: <file path>, severity filter level <severity level>, event message sanitization is set as <sanitization value>	2020-07-14 06:40:59,105 - INFO {"Event ID": 215, "Event Category": "Logging and supportability", "Event Type": "XCP event information", "ExecutionId": 408251920146, "Event Source": "NETAPP-01", "Description": "Event file path : /opt/NetApp/xFiles/xcp/xcplogs/xcp_event.log, severity filter level INFO, event message sanitization is set as False"}
54	Catalog volume is left with no free space please increase the size of catalog volume <catalog volume running out of space>	2020-07-14 04:10:12,897 - ERROR {"Event ID":54, "Event Category": "Application failure", "Event Type": "No space left on Catalog volume error", "ExecutionId": 408249630498, "Event Source": "NETAPP-01", "Description": "Catalog volume is left with no free space. Please increase the size of catalog volume<IP address of NFS destination server>:/cat_vol"}

ID evento	Modello di evento	Esempio di evento
53	Catalog volume <catalog volume> is left with no free space to store index <index id> while executing <command>. Please increase the size of the catalog volume <catalog volume running out of space>	2020-07-14 04:52:15,922 - ERROR {"Event ID": 53, "Event Category": "Application failure", "Event Type": "No space left for catalog volume error", "ExecutionId": 408250278214, "Event Source": "NETAPP-01", "Description": "Catalog volume 10.234.104.250:/cat_vol is left with no free space to store index abc7 while executing : scan {-newid: 'abc7'}. Please increase the size of the catalog volume <IP address of NFS destination server>:/cat_vol"}
61	NFS LIF <LIF IP> is not reachable for path <volume path without IP> while executing <command>. Please check volume is not offline and is reachable.	2020-07-14 07:38:20,100 - ERROR {"Event ID":61, "Event Category": "Application failure", "Event Type": "NFS mount has failed", "ExecutionId": 408252799101, "Event Source": "NETAPP-01", "Description": "NFS LIF <IP address of NFS destination server> is not reachable for path /test11 while executing : scan {}. Please check volume is not offline and is reachable"}
71	TCP connection could not be established for IP address <IP>. Check network setting and configuration.	2020-07-14 07:44:44,578 - ERROR {"Event ID": 71, "Event Category": "Application failure", "Event Type": "IP is not active", "ExecutionId": 408252889541, "Event Source": "NETAPP-01", "Description": "TCP connection could not be established to the address <IP address of NFS destination server>. Check network setting and configuration."} (UT done)

ID evento	Modello di evento	Esempio di evento
51	Target volume is left with no free space while executing: <command>. Please increase the size of target volume <volume running out of space>.	2020-07-14 07:07:07,286 - ERROR {"Event ID": 51, "Event Category": "Application failure", "Event Type": "No space left on destination error", "ExecutionId": 408252316712, "Event Source": "NETAPP-01", "Description": "Target volume is left with no free space while executing : copy {}. Please increase the size of target volume <IP address of NFS destination server>:/cat_vol"}
76	Index id {} is already present . Use new index id and rerun command : <command>	2020-07-14 09:18:41,441 - ERROR {"Event ID": 76, "Event Category": "Application failure", "Event Type": "Index ID problem", "ExecutionId": null, "Event Source": "NETAPP-01", "Description": "Index id asd is already present . Use new index id and rerun command: scan {-newid: 'asd'} "}
362	CPU usage has crossed <percentage CPU used>%	2020-06-16 00:17:28,294 - ERROR {"Event ID": 362, "Event Category": "System resource utilization", "Event Type": "resources available for xcp", "Event Source": "NETAPP- 01 ", "Description": "CPU Usage has crossed 90.07%"}
363	Memory Usage has crossed <percentage memory used>%	2020-06-16 00:17:28,300 - ERROR {"Event ID": 363, "Event Category": "System resource utilization", "Event Type": "resources available for xcp", "Event Source": "NETAPP- 01", "Description": "Memory Usage has crossed 95%"}

ID evento	Modello di evento	Esempio di evento
22	XCP <command> is running on platform <platform information> for source <resume source> and destination <resume destination>	2020-07-14 06:24:26,768 - INFO {"Event ID": 22, "Event Category": "XCP job status", "Event Type": "Starting xcp resume operation", "ExecutionId": 408251663404, "Event Source": "NETAPP-01", "Description": "XCP command : resume {-id: 'autoname_copy_2020-07-14_06.22.07.233271'} is running on platform Linux-2.6.26-2-amd64- x86_64-with-debian-5.0.10 for source <IP address for NFS sever>:/src_vol and destination <IP address of NFS destination server>:/dest_vol"}
356	System resources available while executing xcp command: <command> , are : <CPU info>, <memory information>	2020-07-14 06:24:26,837 - INFO {"Event ID": 356, "Event Category": "System resource utilization", "Event Type": "Resource available for resume", "ExecutionId": 408251663404, "Event Source": "NETAPP-01", "Description": "System resources available while executing xcp command : resume {-id: 'autoname_copy_2020-07-14_06.22.07.233271'} , are : CPU: count 4, load avg (1/5/15m) 0.1, 0.1, 0.0, System memory (GiB): avail 7.2, total 7.8, free 6.6, buffer 0.1, cache 0.5"}

ID evento	Modello di evento	Esempio di evento
23	XCP resume is completed. Total scanned items <scanned item count>, total copied items <copied item count>. Command executed :<command>	2020-07-14 06:26:15,608 - INFO {"Event ID": 23, "Event Category": "XCP job status", "Event Type": "XCP resume completion", "ExecutionId": 408251663404, "Event Source": "NETAPP-01", "Description": "XCP resume is completed. Total scanned items 5982, total copied items 5973. Command executed : resume {-id: 'autoname_copy_2020-07-14_06.22.07.233271'} "}
76	Index id <index id> is already present. Use new index id and rerun command : <command>	2020-07-14 09:43:08,381 - ERROR {"Event ID": 76, "Event Category": "Application failure", "Event Type": "Index ID problem", "ExecutionId": null, "Event Source": "NETAPP-01", "Description": "Index id asd is already present . Use new index id and rerun command : scan {-newid: 'asd'} "}
82	Index id <index id> used while executing sync is incomplete. Try resume on the existing index id <index id>	2020-07-14 10:33:09,307 - ERROR {"Event ID": 82, "Event Category": "Application failure", "Event Type": "Incomplete index used for sync", "ExecutionId": null, "Event Source": "NETAPP-01", "Description": "Index id autoname_copy_2020-07-14_10.28.22.323897 used while executing sync is incomplete. Try resume on the existing index id autoname_copy_2020-07-14_10.28.22.323897."}

ID evento	Modello di evento	Esempio di evento
365	CPU utilization reduced to <CPU percentage used>%	2020-07-14 09:43:08 381 - ERROR {"Event ID": 364, "Event Category": "System resource utilization", "Event Type": "Resources available for xcp", "ExecutionId": 408251663404, "Event Source": "NETAPP-01", "Description": " CPU utilization reduced to 26%}
364	Memory utilization reduced to <CPU percentage used>%	2020-07-14 09:43:08,381 - INFO {"Event ID": 364, "Event Category": " Resources available for xcp", "Event Type": "Resources available for xcp", "ExecutionId": 408351663478, "Event Source": "NETAPP-01", "Description": " Memory utilization reduced to 16.2%"}
10	XCP command <command> has failed	2020-07-14 09:43:08,381 - INFO {"Event ID": 10, "Event Category": " Xcp job status", "Event Type": "XCP command failure", "ExecutionId":4082516634506, "Event Source": "NETAPP-01", "Description": " XCP command verify has failed"

Registri eventi SMB XCP

Esaminare i registri eventi di esempio per XCP SMB.

La tabella seguente mostra i registri eventi per XCP SMB.

ID evento	Modello di evento	Esempio di evento
355	CPU usage has crossed <CPU percentage use>%	2020-06-23 12:42:02,705 - INFO {"Event ID": 355, "Event Category": "System resource utilization", "Event Type": "CPU usage for xcp", "Event Source": "NETAPP-01", "Description": "CPU usage has crossed 96%"}

ID evento	Modello di evento	Esempio di evento
356	Memory usage has crossed <memory percentage use>%	2020-06-23 12:42:02,705 - INFO { "Event ID": 356, "Event Category": "System resource utilization", "Event Type": "Memory usage for xcp", "Event Source": "NETAPP-01", "Description": "CPU usage has crossed92.5%" }
61	Address was not found: <complete address over which command is fired>	2020-07-15 02:57:06,466 - ERROR { "Event ID": 61, "Event Category": "Application Failure", "Event Type": "Address was not found", "ExecutionId": 408264113696, "Event Source": "NETAPP-01", "Description": "Address was not found: \\\"\\\\\\<IP address of SMB server>\\\\cifs1\""} }
62	Interface cannot be found: < complete address over which command is fired >	2020-07-15 02:52:00,603 - ERROR { "Event ID": 62, "Event Category": "Application Failure", "Event Type": "Interface was not found", "ExecutionId": 408264071616, "Event Source": "NETAPP-01", "Description": "Interface cannot be found: \\\"\\\\\\<IP address of SMB server>\\\\cifs11\""} }
63	Invalid Address. Please make sure that the Address starts with '\\'	2020-07-15 03:00:10,422 - ERROR { "Event ID": 63, "Event Category": "Application Failure", "Event Type": "Invalid Address", "ExecutionId": 408264197308, "Event Source": "NETAPP-01", "Description": "Invalid Address. Please make sure that the Address starts with '\\'" }

ID evento	Modello di evento	Esempio di evento
41	Destination volume is left with no free space please increase the size target volume:<destination volume>	2020-06-15 17:12:46,413 - ERROR { "Event ID": 41, "Event Category": "Application Failure", "Event Type": "No space left on destination error", "Event Source": "NETAPP-01", "Description": "Destination volume is left with no free space please increase the size of target volume: <IP address of SMB server>\\to" }
211	Log file path : <file path>, severity filter level <severity level>, log message sanitization is set as <value of sanitization option>	{ "Event ID": 211, "Event Category": "Logging and supportability", "Event Type": "XCP logging information", "ExecutionId": 408252673852, "Event Source": "NETAPP-01", "Description": "Log file path : C:\\NetApp\\XCP\\Logs\\xcp.log, severity filter level DEBUG, log message sanitization is set as False" }
215	Event file path : <file path>, severity filter level <severity level>, Event message sanitization is set as <sanitization option>	{ "Event ID": 215, "Event Category": "Logging and supportability", "Event Type": "XCP event information", "ExecutionId": 408252673852, "Event Source": "NETAPP-01", "Description": "Event file path : C:\\NetApp\\XCP\\Logs\\xcp_event.log, severity filter level INFO, Event message sanitization is set as False" }

ID evento	Modello di evento	Esempio di evento
181	This license is issued to <user name> of <company name>, license type is <license type> with <status> status, license will expire expires on <expiration date>	{"Event ID": 181, "Event Category": "Authentication and authorization", "Event Type": "license information", "ExecutionId": 408252673852, "Event Source": "NETAPP-01", "Description": "This license is issued to calin of NetApp Inc, license type is SANDBOX with ACTIVE status, license will expire on Mon Dec 31 00:00:00 2029"}
13	XCP <command> is running on platform <platform information> for source <scan source>	2020-07-15 02:12:56,917 - INFO {"Event ID": 13, "Event Category": "XCP job status", "Event Type": "Starting xcp scan operation", "ExecutionId": 408263470688, "Event Source": "NETAPP-01", "Description": "XCP {scan} is running on platform Windows- 8.1-6.3.9600-SP0 for source \\\\ <ip address="" of="" server="" smb="">\\cifs"}</ip>
351	System resources available while command : <command>, are : cpu <CPU information>, total memory <total memory on system>, available memory	2020-07-15 02:12:56,917 - INFO {"Event ID": 351, "Event Category": "System resource utilization", "Event Type": "Resources available for scan", "ExecutionId": 408263470688, "Event Source": "NETAPP-01", "Description": "System resources available while executing xcp command : scan, are : cpu 4, total memory 8.00GiB, available memory 6.81GiB"}

ID evento	Modello di evento	Esempio di evento
14	XCP scan completed successfully after scanning <scanned items count> items. Source :<scan source>	2020-07-15 02:12:57,932 - INFO {"Event ID": 14, "Event Category": "XCP job status", "Event Type": "XCP scan completion", "ExecutionId": 408263470688, "Event Source": "NETAPP-01", "Description": "XCP scan completed successfully after scanning 29 items. Source : \\ \\ \\ <IP address of SMB server> \\ \cifs"}
25	XCP <command> is running on platform <platform information> for source <copy source> and destination <copy destination>	2020-07-15 02:19:06,562 - INFO {"Event ID": 25, "Event Category": "XCP job status", "Event Type": "Starting xcp copy operation", "ExecutionId": 408263563552, "Event Source": "NETAPP-01", "Description": "XCP {copy} is running on platform Windows- 8.1-6.3.9600-SP0 for source \\ \\ \\ <IP address of SMB server> \\ \cifs and destination \\ \\ \\ <IP address of SMB destination server> \\ \source_vol"}
352	System resources available while executing command :<command>, are : cpu <CPU information>, total memory <Total memory>, available memory <memory available for execution>	2020-07-15 02:19:06,562 - INFO {"Event ID": 352, "Event Category": "System resource utilization", "Event Type": "Resources available for copy", "ExecutionId": 408263563552, "Event Source": "NETAPP-01", "Description": "System resources available while executing xcp command : copy, are : cpu 4, total memory 8.00GiB, available memory 6.82GiB"}

ID evento	Modello di evento	Esempio di evento
26	XCP copy completed successfully after copying <copied items count> items. Source :<copy source>, destination : <copy destination>	2020-07-15 02:19:14,500 - INFO {"Event ID": 26, "Event Category": "XCP job status", "Event Type": "XCP copy completion", "ExecutionId": 408263563552, "Event Source": "NETAPP-01", "Description": "XCP copy completed successfully after copying 0 items. Source :
16	XCP <command> is running on platform <platform> for source <sync source> and destination <sync destination>	2020-07-15 02:27:10,490 - INFO {"Event ID": 16, "Event Category": "XCP job status", "Event Type": "Starting xcp sync operation", "ExecutionId": 408263688308, "Event Source": "NETAPP-01", "Description": "XCP {sync} is running on platform Windows- 8.1-6.3.9600-SP0 for source \\<IP address of SMB server>\\cifs and destination \\<IP address of SMB destination server>\\source_vol"}
353	System resources available while executing xcp command: <command>, are : cpu <CPU information>, total memory <total memory>, available memory <available memory>	2020-07-15 02:27:10,490 - INFO {"Event ID": 353, "Event Category": "System resource utilization", "Event Type": "Resources available for sync", "ExecutionId": 408263688308, "Event Source": "NETAPP-01", "Description": "System resources available while executing xcp command : sync, are : cpu 4, total memory 8.00GiB, available memory 6.83GiB"}

ID evento	Modello di evento	Esempio di evento
17	XCP sync completed successfully after scanning <scanned item count> items, copying <copied item count> items, comparing <compared item count> items, removing <removed item count> items. Source : <sync source>, destination : <sync destination>	2020-07-15 03:04:14,269 - INFO {"Event ID": 17, "Event Category": "XCP job status", "Event Type": "XCP sync completion", "ExecutionId": 408264256392, "Event Source": "NETAPP-01", "Description": "XCP sync completed successfully after scanning30 items, copying 20 items, comparing 30 items, removing 0 items. Source : \\\\<IP address of SMB server>\\cifs, destination :\\\\<IP address of SMB destination server>\\source_vol"}
19	XCP <command> is running on platform <platform information> for source <verify source> and destination <verify destination>	2020-07-15 03:14:04,854 - INFO {"Event ID": 19, "Event Category": "XCP job status", "Event Type": "Starting xcp verify operation", "ExecutionId": 408264409944, "Event Source": "NETAPP-01", "Description": "XCP {verify -noacl} is running on platform Windows-8.1-6.3.9600-SP0 for source \\\\<IP address of SMB server>\\cifs and destination \\\\<IP address of SMB destination server>\\source_vol"}
354	System resources available for command : <command>, are : cpu <CPU information>, total memory <total memory>, available memory <available memory for execution>	2020-07-15 03:14:04,854 - INFO {"Event ID": 354, "Event Category": "System resource utilization", "Event Type": "Resources available for verify", "ExecutionId": 408264409944, "Event Source": "NETAPP-01", "Description": "System resources available while executing xcp command : verify, are : cpu 4, total memory 8.00GiB, available memory 6.80GiB"}

ID evento	Modello di evento	Esempio di evento
20	XCP verify is completed by scanning <scanned item count> items, comparing <compared item count> items	{"Event ID": 20, "Event Category": "XCP job status", "Event Type": "XCP verify completion", "command Id": 408227440800, "Event Source": "NETAPP-01", "Description": "XCP verify is completed by scanning 59 items, comparing 0 items"}
357	CPU utilization reduced to <CPU utilization percentage>%	{"Event ID": 357, "Event Category": "System resource utilization", "Event Type": "CPU usage for xcp", "Event Source": "NETAPP- 01", "Description": "CPU utilization reduced to 8.2%"}
358	Memory utilization reduced to <memory utilization percentage>%	{"Event ID": 358, "Event Category": "System resource utilization", "Event Type": "Memory usage for xcp", "Event Source": "NETAPP-01", "Description": "Memory utilization reduced to 19%"}
10	XCP command <command> has failed	2020-07-14 09:43:08,381 - INFO {"Event ID": 10, "Event Category": " Xcp job status", "Event Type": "XCP command failure", "Event Source": "NETAPP-01", "Description": " XCP command H:\\console_msg\\xcp_cifs\\xcp\\ main .py verify \\\\<IP address of SMB server>\\cifs \\\\<IP address of SMB destination server>\\source_vol has failed"

Informazioni sul copyright

Copyright © 2024 NetApp, Inc. Tutti i diritti riservati. Stampato negli Stati Uniti d'America. Nessuna porzione di questo documento soggetta a copyright può essere riprodotta in qualsiasi formato o mezzo (grafico, elettronico o meccanico, inclusi fotocopie, registrazione, nastri o storage in un sistema elettronico) senza previo consenso scritto da parte del detentore del copyright.

Il software derivato dal materiale sottoposto a copyright di NetApp è soggetto alla seguente licenza e dichiarazione di non responsabilità:

IL PRESENTE SOFTWARE VIENE FORNITO DA NETAPP "COSÌ COM'È" E SENZA QUALSIVOGLIA TIPO DI GARANZIA IMPLICITA O ESPRESSA FRA CUI, A TITOLO ESEMPLIFICATIVO E NON ESAUSTIVO, GARANZIE IMPLICITE DI COMMERCIALIZZABILITÀ E IDONEITÀ PER UNO SCOPO SPECIFICO, CHE VENGONO DECLINATE DAL PRESENTE DOCUMENTO. NETAPP NON VERRÀ CONSIDERATA RESPONSABILE IN ALCUN CASO PER QUALSIVOGLIA DANNO DIRETTO, INDIRETTO, ACCIDENTALE, SPECIALE, ESEMPLARE E CONSEGUENZIALE (COMPRESI, A TITOLO ESEMPLIFICATIVO E NON ESAUSTIVO, PROCUREMENT O SOSTITUZIONE DI MERCI O SERVIZI, IMPOSSIBILITÀ DI UTILIZZO O PERDITA DI DATI O PROFITTI OPPURE INTERRUZIONE DELL'ATTIVITÀ AZIENDALE) CAUSATO IN QUALSIVOGLIA MODO O IN RELAZIONE A QUALUNQUE TEORIA DI RESPONSABILITÀ, SIA ESSA CONTRATTUALE, RIGOROSA O DOVUTA A INSOLVENZA (COMPRESA LA NEGLIGENZA O ALTRO) INSORTA IN QUALSIASI MODO ATTRAVERSO L'UTILIZZO DEL PRESENTE SOFTWARE ANCHE IN PRESENZA DI UN PREAVVISO CIRCA L'EVENTUALITÀ DI QUESTO TIPO DI DANNI.

NetApp si riserva il diritto di modificare in qualsiasi momento qualunque prodotto descritto nel presente documento senza fornire alcun preavviso. NetApp non si assume alcuna responsabilità circa l'utilizzo dei prodotti o materiali descritti nel presente documento, con l'eccezione di quanto concordato espressamente e per iscritto da NetApp. L'utilizzo o l'acquisto del presente prodotto non comporta il rilascio di una licenza nell'ambito di un qualche diritto di brevetto, marchio commerciale o altro diritto di proprietà intellettuale di NetApp.

Il prodotto descritto in questa guida può essere protetto da uno o più brevetti degli Stati Uniti, esteri o in attesa di approvazione.

LEGENDA PER I DIRITTI SOTTOPOSTI A LIMITAZIONE: l'utilizzo, la duplicazione o la divulgazione da parte degli enti governativi sono soggetti alle limitazioni indicate nel sottoparagrafo (b)(3) della clausola Rights in Technical Data and Computer Software del DFARS 252.227-7013 (FEB 2014) e FAR 52.227-19 (DIC 2007).

I dati contenuti nel presente documento riguardano un articolo commerciale (secondo la definizione data in FAR 2.101) e sono di proprietà di NetApp, Inc. Tutti i dati tecnici e il software NetApp forniti secondo i termini del presente Contratto sono articoli aventi natura commerciale, sviluppati con finanziamenti esclusivamente privati. Il governo statunitense ha una licenza irrevocabile limitata, non esclusiva, non trasferibile, non cedibile, mondiale, per l'utilizzo dei Dati esclusivamente in connessione con e a supporto di un contratto governativo statunitense in base al quale i Dati sono distribuiti. Con la sola esclusione di quanto indicato nel presente documento, i Dati non possono essere utilizzati, divulgati, riprodotti, modificati, visualizzati o mostrati senza la previa approvazione scritta di NetApp, Inc. I diritti di licenza del governo degli Stati Uniti per il Dipartimento della Difesa sono limitati ai diritti identificati nella clausola DFARS 252.227-7015(b) (FEB 2014).

Informazioni sul marchio commerciale

NETAPP, il logo NETAPP e i marchi elencati alla pagina <http://www.netapp.com/TM> sono marchi di NetApp, Inc. Gli altri nomi di aziende e prodotti potrebbero essere marchi dei rispettivi proprietari.