



Application Backup

Astra Automation

NetApp
December 01, 2023

This PDF was generated from https://docs.netapp.com/ja-jp/astra-automation-2304/reference/application_backup_overview.html on December 01, 2023. Always check docs.netapp.com for the latest.

目次

| | |
|--|----|
| Application Backup | 1 |
| Application Backup overview | 1 |
| List all application backups | 1 |
| Retrieve an application backup | 12 |
| Delete an application backup | 20 |
| Create a new application backup for an app | 25 |
| List the application backups for an app | 38 |
| Retrieve an application backup for an app | 50 |
| Delete an application backup for an app | 59 |

Application Backup

Application Backup overview

The Application Backup API enables a user to create and view backups of a managed application.

List all application backups

GET /accounts/{account_id}/topology/v1/appBackups

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|-------|----------|---|
| account_id | string | path | True | ID of the containing account resource • example: {{.Account}} |
| include | string | query | False | Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: id,name,state |
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2" |

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name | Type | Required | Description |
|----------|--|----------|-------------|
| items | array[Any of: appBackup_1.2_get_response_body , array[]] | True | |
| metadata | type_astra_metadata_list | True | |

Example response

```
{
  "type": "application/astra-appBackups",
  "version": "1.2",
  "items": [
    [
      "5cb608f9-571b-492e-a520-5bfb900a9b9c",
      "app-name-245",
      "pending"
    ],
    [
      "f8faa690-7e09-48a4-b33c-7965712acd0c",
      "app-name-244",
      "completed"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/96",
  "title": "Backups not listed",
  "detail": "The backups didn't list because of an internal server issue.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

| Name | Type | Required | Description |
|-----------------------|---|----------|-------------|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

appBackup_1.2_get_response_body

| Name | Type | Required | Description |
|------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-appBackup" |

| Name | Type | Required | Description |
|----------|--------|----------|--|
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema |
| bucketID | string | True | JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|------------|--------|----------|---|
| snapshotID | string | False | <p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| scheduleID | string | False | <p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|---------------|----------|--|
| state | string | True | <p>JSON string containing a value indicating the operational state of the backup. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined |
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|-------------------------|--------------------------------|----------|---|
| hookState | string | False | <p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful |
| hookStateDetails | array[type_astra_stateDe tail] | False | <p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| backupCreationTimestamp | string | False | <p>JSON string containing a timestamp indicating when the backup was taken. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| totalBytes | number | False | <p>JSON number containing the total number of bytes in the backup.</p> |
| bytesDone | number | False | <p>JSON number containing the number of bytes backed up for a running backup. When the backup is completed, it matches with the totalBytes field.</p> |

| Name | Type | Required | Description |
|-------------|-------------------------------------|----------|--|
| percentDone | number | False | JSON number containing the percentage complete for a running backup. When the backup is completed, it is set to "100". |
| metadata | type_astra_metadata | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. |

type_astra_metadata_list

| Name | Type | Required | Description |
|-----------------------|---|----------|-------------|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Retrieve an application backup

GET /accounts/{account_id}/topology/v1/appBackups/{appBackup_id}

Returns the stored Application Backup API resource in the JSON response body.

Parameters

| Name | Type | In | Required | Description |
|--------------|--------|------|----------|--|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}} |
| appBackup_id | string | path | True | ID of the appBackup collection to list |

Response

Status: 200, Returns the stored Application Backup API resource in the JSON response body.

| Name | Type | Required | Description |
|---------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appBackup" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema |

| Name | Type | Required | Description |
|------------|--------|----------|---|
| name | string | True | <p>JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema |
| bucketID | string | True | <p>JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| snapshotID | string | False | <p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|------------|--------|----------|--|
| scheduleID | string | False | <p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| state | string | True | <p>JSON string containing a value indicating the operational state of the backup. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined |

| Name | Type | Required | Description |
|-------------------------|-------------------------------|----------|---|
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |
| hookState | string | False | <p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful |
| hookStateDetails | array[type_astra_stateDetail] | False | <p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| backupCreationTimestamp | string | False | <p>JSON string containing a timestamp indicating when the backup was taken. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| totalBytes | number | False | <p>JSON number containing the total number of bytes in the backup.</p> |

| Name | Type | Required | Description |
|-------------|---------------------|----------|--|
| bytesDone | number | False | JSON number containing the number of bytes backed up for a running backup. When the backup is completed, it matches with the totalBytes field. |
| percentDone | number | False | JSON number containing the percentage complete for a running backup. When the backup is completed, it is set to "100". |
| metadata | type_astra_metadata | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. |

Example response

```
{
  "type": "application/astra-appBackup",
  "version": "1.2",
  "id": "bab39d53-2d04-5297-b92e-58df89a2117b",
  "name": "app-name-245",
  "bucketID": "0afbe357-a717-4c7a-8b3d-d0368959c8de",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/95",
  "title": "Backup not retrieved",
  "detail": "The backup wasn't retrieved because of an internal server issue.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Delete an application backup

DELETE /accounts/{account_id}/topology/v1/appBackups/{appBackup_id}

Removes the specified Application Backup API resource. Backups in progress will be canceled, and then

deleted.

Side Effects

- If a backup is complete, the backup data is deleted.

Parameters

| Name | Type | In | Required | Description |
|--------------|--------|------|----------|--|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">• example: {{.Account}} |
| appBackup_id | string | path | True | ID of the appBackup collection to list |

Response

Status: 204, Indicates if the appBackup resource was deleted.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/97",
  "title": "Backup not deleted",
  "detail": "The backup wasn't deleted because of an internal server issue.",
  "status": "500"
}
```

Response

Status: 409, Conflict

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/128",
  "title": "Backup cancellation not allowed",
  "detail": "A pending backup can't be canceled.",
  "status": "409"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Create a new application backup for an app

POST /accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups

Indicates the desired values for the Application Backup API resource to be created.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code> |
| app_id | string | path | True | ID of the containing app resource |

Request Body

Indicates the desired values for the Application Backup API resource to be created.

| Name | Type | Required | Description |
|------|--------|----------|--|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appBackup" |

| Name | Type | Required | Description |
|----------|--------|----------|---|
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" |
| name | string | False | JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema |
| bucketID | string | False | JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|------------|-------------------------------------|----------|---|
| snapshotID | string | False | <p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| metadata | type_astra_metadata | False | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. |

Example request

```
{
  "type": "application/astra-appBackup",
  "version": "1.2",
  "name": "app-name-245"
}
```

Response

Status: 201, Returns the newly created appBackup resource in the JSON response body.

| Name | Type | Required | Description |
|---------|--------|----------|--|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-appBackup" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema |

| Name | Type | Required | Description |
|------------|--------|----------|---|
| bucketID | string | True | <p>JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| snapshotID | string | False | <p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| scheduleID | string | False | <p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|---------------|----------|--|
| state | string | True | <p>JSON string containing a value indicating the operational state of the backup. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined |
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|-------------------------|-------------------------------|----------|---|
| hookState | string | False | <p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful |
| hookStateDetails | array[type_astra_stateDetail] | False | <p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| backupCreationTimestamp | string | False | <p>JSON string containing a timestamp indicating when the backup was taken. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| totalBytes | number | False | <p>JSON number containing the total number of bytes in the backup.</p> |
| bytesDone | number | False | <p>JSON number containing the number of bytes backed up for a running backup. When the backup is completed, it matches with the totalBytes field.</p> |

| Name | Type | Required | Description |
|-------------|---------------------|----------|---|
| percentDone | number | False | JSON number containing the percentage complete for a running backup. When the backup is completed, it is set to "100". |
| metadata | type_astra_metadata | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. |

Example response

```
{
  "type": "application/astra-appBackup",
  "version": "1.2",
  "id": "bab39d53-2d04-5297-b92e-58df89a2117b",
  "name": "app-name-245",
  "bucketID": "0afbe357-a717-4c7a-8b3d-d0368959c8de",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/94",
  "title": "Backup not created",
  "detail": "The backup wasn't created because of an internal server issue.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

type_astra_stateDetail

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|------|--------|----------|--|
| name | string | True | Name of the invalid request body field |

| Name | Type | Required | Description |
|--------|--------|----------|--|
| reason | string | True | Reason why the request body field is invalid |

List the application backups for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|-------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code> |
| app_id | string | path | True | ID of the containing app resource |
| include | string | query | False | Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>id,name,state</code> |

| Name | Type | In | Required | Description |
|-------|--------|-------|----------|---|
| limit | string | query | False | <p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p> |

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name | Type | Required | Description |
|----------|--|----------|-------------|
| items | array[Any of: appBackup_1.2_get_response_body , array[]] | True | |
| metadata | type_astra_metadata_list | True | |

Example response

```
{
  "type": "application/astra-appBackups",
  "version": "1.2",
  "items": [
    [
      "5cb608f9-571b-492e-a520-5bfb900a9b9c",
      "app-name-245",
      "pending"
    ],
    [
      "f8faa690-7e09-48a4-b33c-7965712acd0c",
      "app-name-244",
      "completed"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/96",
  "title": "Backups not listed",
  "detail": "The backups didn't list because of an internal server issue.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

appBackup_1.2_get_response_body

| Name | Type | Required | Description |
|------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-appBackup" |

| Name | Type | Required | Description |
|----------|--------|----------|--|
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema |
| bucketID | string | True | JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|------------|--------|----------|---|
| snapshotID | string | False | <p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| scheduleID | string | False | <p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|---------------|----------|--|
| state | string | True | <p>JSON string containing a value indicating the operational state of the backup. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined |
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|-------------------------|--------------------------------|----------|---|
| hookState | string | False | <p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful |
| hookStateDetails | array[type_astra_stateDe tail] | False | <p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| backupCreationTimestamp | string | False | <p>JSON string containing a timestamp indicating when the backup was taken. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| totalBytes | number | False | <p>JSON number containing the total number of bytes in the backup.</p> |
| bytesDone | number | False | <p>JSON number containing the number of bytes backed up for a running backup. When the backup is completed, it matches with the totalBytes field.</p> |

| Name | Type | Required | Description |
|-------------|-------------------------------------|----------|---|
| percentDone | number | False | JSON number containing the percentage complete for a running backup. When the backup is completed, it is set to "100". |
| metadata | type_astra_metadata | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. |

type_astra_metadata_list

| Name | Type | Required | Description |
|-----------------------|---|----------|-------------|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Retrieve an application backup for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups/{appBackup_id}

Returns the stored Application Backup API resource in the JSON response body.

Parameters

| Name | Type | In | Required | Description |
|--------------|--------|------|----------|--|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| appBackup_id | string | path | True | ID of the appBackup collection to list |

Response

Status: 200, Returns the stored Application Backup API resource in the JSON response body.

| Name | Type | Required | Description |
|---------|--------|----------|--|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appBackup" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2" |

| Name | Type | Required | Description |
|----------|--------|----------|---|
| id | string | True | <p>Globally unique identifier of the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | <p>JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema |
| bucketID | string | True | <p>JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|------------|--------|----------|---|
| snapshotID | string | False | <p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| scheduleID | string | False | <p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|---------------|----------|--|
| state | string | True | <p>JSON string containing a value indicating the operational state of the backup. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined |
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|-------------------------|-------------------------------|----------|---|
| hookState | string | False | <p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful |
| hookStateDetails | array[type_astra_stateDetail] | False | <p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| backupCreationTimestamp | string | False | <p>JSON string containing a timestamp indicating when the backup was taken. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| totalBytes | number | False | <p>JSON number containing the total number of bytes in the backup.</p> |
| bytesDone | number | False | <p>JSON number containing the number of bytes backed up for a running backup. When the backup is completed, it matches with the totalBytes field.</p> |

| Name | Type | Required | Description |
|-------------|-------------------------------------|----------|--|
| percentDone | number | False | JSON number containing the percentage complete for a running backup. When the backup is completed, it is set to "100". |
| metadata | type_astra_metadata | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. |

Example response

```
{
  "type": "application/astra-appBackup",
  "version": "1.2",
  "id": "bab39d53-2d04-5297-b92e-58df89a2117b",
  "name": "app-name-245",
  "bucketID": "0afbe357-a717-4c7a-8b3d-d0368959c8de",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/95",
  "title": "Backup not retrieved",
  "detail": "The backup wasn't retrieved because of an internal server issue.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | True | |
| creationTimestamp | string | True | |
| modificationTimestamp | string | True | |
| createdBy | string | True | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Delete an application backup for an app

DELETE /accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups/{appBackup_id}

Removes the specified Application Backup API resource. Backups in progress will be canceled, and then

deleted.

Side Effects

- If a backup is complete, the backup data is deleted.

Parameters

| Name | Type | In | Required | Description |
|--------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code> |
| app_id | string | path | True | ID of the containing app resource |
| appBackup_id | string | path | True | ID of the appBackup collection to list |

Response

Status: 204, Indicates if the appBackup resource was deleted.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/97",
  "title": "Backup not deleted",
  "detail": "The backup wasn't deleted because of an internal server issue.",
  "status": "500"
}
```


Response

Status: 409, Conflict

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/128",
  "title": "Backup cancellation not allowed",
  "detail": "A pending backup can't be canceled.",
  "status": "409"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

著作権に関する情報

Copyright © 2023 NetApp, Inc. All Rights Reserved. Printed in the U.S. このドキュメントは著作権によって保護されています。著作権所有者の書面による事前承諾がある場合を除き、画像媒体、電子媒体、および写真複写、記録媒体、テープ媒体、電子検索システムへの組み込みを含む機械媒体など、いかなる形式および方法による複製も禁止します。

ネットアップの著作物から派生したソフトウェアは、次に示す使用許諾条項および免責条項の対象となります。

このソフトウェアは、ネットアップによって「現状のまま」提供されています。ネットアップは明示的な保証、または商品性および特定目的に対する適合性の暗示的保証を含み、かつこれに限定されないいかなる暗示的な保証も行いません。ネットアップは、代替品または代替サービスの調達、使用不能、データ損失、利益損失、業務中断を含み、かつこれに限定されない、このソフトウェアの使用により生じたすべての直接的損害、間接的損害、偶発的損害、特別損害、懲罰的損害、必然的損害の発生に対して、損失の発生の可能性が通知されていたとしても、その発生理由、根拠とする責任論、契約の有無、厳格責任、不法行為（過失またはそうでない場合を含む）にかかわらず、一切の責任を負いません。

ネットアップは、ここに記載されているすべての製品に対する変更を随時、予告なく行う権利を保有します。ネットアップによる明示的な書面による合意がある場合を除き、ここに記載されている製品の使用により生じる責任および義務に対して、ネットアップは責任を負いません。この製品の使用または購入は、ネットアップの特許権、商標権、または他の知的所有権に基づくライセンスの供与とはみなされません。

このマニュアルに記載されている製品は、1つ以上の米国特許、その他の国の特許、および出願中の特許によって保護されている場合があります。

権利の制限について：政府による使用、複製、開示は、DFARS 252.227-7013（2014年2月）およびFAR 5252.227-19（2007年12月）のRights in Technical Data -Noncommercial Items（技術データ - 非商用品目に関する諸権利）条項の(b)(3)項、に規定された制限が適用されます。

本書に含まれるデータは商用製品および / または商用サービス（FAR 2.101の定義に基づく）に関係し、データの所有権はNetApp, Inc.にあります。本契約に基づき提供されるすべてのネットアップの技術データおよびコンピュータ ソフトウェアは、商用目的であり、私費のみで開発されたものです。米国政府は本データに対し、非独占的かつ移転およびサブライセンス不可で、全世界を対象とする取り消し不能の制限付き使用权を有し、本データの提供の根拠となった米国政府契約に関連し、当該契約の裏付けとする場合にのみ本データを使用できます。前述の場合を除き、NetApp, Inc.の書面による許可を事前に得ることなく、本データを使用、開示、転載、改変するほか、上演または展示することはできません。国防総省にかかる米国政府のデータ使用权については、DFARS 252.227-7015(b)項（2014年2月）で定められた権利のみが認められます。

商標に関する情報

NetApp、NetAppのロゴ、<http://www.netapp.com/TM>に記載されているマークは、NetApp, Inc.の商標です。その他の会社名と製品名は、それを所有する各社の商標である場合があります。