



Cluster

Astra Automation

NetApp
June 28, 2024

목차

| | |
|--|-----|
| Cluster | 1 |
| Cluster overview | 1 |
| Create a new cluster for a cloud | 1 |
| List the clusters for a cloud | 21 |
| Retrieve a cluster for a cloud | 40 |
| Modify a cluster for a cloud | 56 |
| Delete a cluster for a cloud | 72 |
| List all clusters | 76 |
| Retrieve a cluster | 95 |
| Modify a cluster | 111 |
| Delete a cluster | 127 |

Cluster

Cluster overview

The Cluster API provides CRUD (Create-Read-Update-Delete) access to cluster resources in order to represent unmanaged Kubernetes clusters.

Create a new cluster for a cloud

POST /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters

Indicates the desired values for the Cluster API resource to be created.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|--|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}} |
| cloud_id | string | path | True | ID of the containing cloud resource |

Request Body

Indicates the desired values for the Cluster API resource to be created.

| Name | Type | Required | Description |
|---------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-cluster" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2""1.3" |

| Name | Type | Required | Description |
|--------------|--------|----------|---|
| name | string | False | <p>JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks |
| accHost | string | False | <p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed. |
| credentialID | string | True | <p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|----------|--|----------|--|
| metadata | type_astra_metadata_update | False | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example request

```
{
  "type": "application/astra-cluster",
  "version": "1.3",
  "name": "GKE-22",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31"
}
```

Response

Status: 201, Returns the newly created cluster resource in the JSON response body.

| Name | Type | Required | Description |
|------|--------|----------|--|
| type | string | True | <p>Media type of the resource. Defined values are:</p> <ul style="list-style-type: none"> "application/astra-cluster" |

| Name | Type | Required | Description |
|---------|--------|----------|--|
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks |

| Name | Type | Required | Description |
|--------------|---------------|----------|---|
| state | string | True | <p>JSON string containing a value indicating the operational state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined |
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| managedState | string | True | <p>JSON string containing a value indicating the management state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management |

| Name | Type | Required | Description |
|------------------------|--------------------------------|----------|---|
| protectionState | string | True | <p>JSON string containing a value indicating the protection state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots |
| protectionStateDetails | array[type_astra_stateDetails] | True | <p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0 |
| restoreTargetSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations. |

| Name | Type | Required | Description |
|---------------------|---------------|----------|---|
| snapshotSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations. |
| managedStateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |
| managedTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed". |

| Name | Type | Required | Description |
|----------------------------|--|----------|--|
| tridentVersion | string | False | <p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema |
| tridentManagedState | string | False | <p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra |
| tridentManagedStateDesired | string | False | <p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster |
| tridentManagedStateDetails | array[type_astra_stateDetails] | False | <p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |

| Name | Type | Required | Description |
|----------------------------|---------------|----------|--|
| tridentManagedStateAllowed | array[string] | False | <p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged" |
| inUse | string | True | <p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it |
| accHost | string | False | <p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed. |

| Name | Type | Required | Description |
|----------------|--------|----------|---|
| clusterType | string | True | <p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes |
| clusterVersion | string | False | <p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |

| Name | Type | Required | Description |
|--------------------------|---------------|----------|---|
| clusterVersionString | string | False | <p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |
| clusterCreationTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| namespaces | array[string] | False | <p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 |
| defaultStorageClass | string | False | <p>JSON string containing a storageClass ID that corresponds to the default storage class set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| cloudID | string | True | <p>JSON string containing a value indicating the ID of the cloud the cluster is running on. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| credentialID | string | False | <p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| location | string | False | <p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 |
| isMultizonal | string | False | <p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone |

| Name | Type | Required | Description |
|----------------|----------------------------|----------|---|
| privateRouteID | string | False | <p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255 |
| apiServiceID | string | False | <p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p> |
| metadata | type_astra_metadata_update | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example response

```
{
  "type": "application/astra-cluster",
  "version": "1.3",
  "id": "01eaddc3-75b9-5606-97ae-0aa468b59492",
  "name": "GKE-22",
  "state": "running",
  "stateUnready": [],
  "managedState": "unmanaged",
  "managedStateUnready": [],
  "protectionState": "full",
  "protectionStateDetails": [],
  "tridentVersion": "21.07.2",
  "tridentManagedState": "managed",
  "tridentManagedStateDetails": [],
  "inUse": "false",
  "clusterType": "kubernetes",
  "clusterVersion": "1.91.1",
  "clusterVersionString": "1.19.1",
  "clusterCreationTimestamp": "2020-08-06T12:24:52.256624Z",
  "namespaces": [
    "kube-system",
    "kube-public",
    "my-app-1"
  ],
  "defaultStorageClass": "31c95aba-99d9-4987-b1bb-000dfce5952c",
  "cloudID": "548bdc1f-f00e-4a23-a062-83265d224d46",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31",
  "location": "europe-west4",
  "isMultizonal": "false",
  "apiServiceID": "6bf33af2-872a-4553-a891-26b510c3edbe",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/64",
  "title": "Storage classes not found",
  "detail": "Storage classes from Trident weren't found.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

type_astra_stateDetails

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|--------|--------|----------|--|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

List the clusters for a cloud

GET /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|-------|----------|--|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code> |
| cloud_id | string | path | True | ID of the containing cloud resource |
| include | string | query | False | Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>id,name,managedState</code> |

| Name | Type | In | Required | Description |
|--------|--------|-------|----------|--|
| limit | string | query | False | <p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p> |
| filter | string | query | False | <p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p> |

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name | Type | Required | Description |
|----------|--|----------|-------------|
| items | array[Any of: cluster_1.3_get_response_body , array[]] | True | |
| metadata | type_astra_metadata_list | True | |

Example response

```
{
  "type": "application/astra-clusters",
  "version": "1.3",
  "items": [
    [
      "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
      "GKE-21",
      "managed"
    ],
    [
      "04dc80fa-d1d8-4850-a49f-3b70d0ec1369",
      "GKE-22",
      "unmanaged"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetails

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|---|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

cluster_1.3_get_response_body

| Name | Type | Required | Description |
|------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cluster" |

| Name | Type | Required | Description |
|---------|--------|----------|--|
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks |

| Name | Type | Required | Description |
|--------------|---------------|----------|---|
| state | string | True | <p>JSON string containing a value indicating the operational state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined |
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| managedState | string | True | <p>JSON string containing a value indicating the management state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management |

| Name | Type | Required | Description |
|------------------------|--------------------------------|----------|---|
| protectionState | string | True | <p>JSON string containing a value indicating the protection state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> "full" - The clusters default storage class supports snapshots "partial" - The cluster has only storageClasses that do not support snapshots "atRisk" - The default storage class of the cluster does not support snapshots |
| protectionStateDetails | array[type_astra_stateDetails] | True | <p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> Minimum Items: 0 |
| restoreTargetSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations. Defined values are:</p> <ul style="list-style-type: none"> "true" - Cluster is an eligible target for app data management operations. "false" - Cluster is <i>not</i> an eligible target for app data management operations. |

| Name | Type | Required | Description |
|---------------------|---------------|----------|---|
| snapshotSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations. |
| managedStateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |
| managedTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed". |

| Name | Type | Required | Description |
|----------------------------|--------|----------|--|
| tridentVersion | string | False | <p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema |
| tridentManagedState | string | False | <p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra |
| tridentManagedStateDesired | string | False | <p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster |

| Name | Type | Required | Description |
|----------------------------|--------------------------------|----------|--|
| tridentManagedStateDetails | array[type_astra_stateDetails] | False | <p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| tridentManagedStateAllowed | array[string] | False | <p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged" |
| inUse | string | True | <p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it |

| Name | Type | Required | Description |
|-------------|--------|----------|---|
| accHost | string | False | <p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed. |
| clusterType | string | True | <p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes |

| Name | Type | Required | Description |
|--------------------------|---------------|----------|---|
| clusterVersion | string | False | <p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |
| clusterVersionString | string | False | <p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |
| clusterCreationTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| namespaces | array[string] | False | <p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 |

| Name | Type | Required | Description |
|---------------------|--------|----------|--|
| defaultStorageClass | string | False | <p>JSON string containing a storageClass ID that corresponds to the default storage class set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| cloudID | string | True | <p>JSON string containing a value indicating the ID of the cloud the cluster is running on. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| credentialID | string | False | <p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| location | string | False | <p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 |

| Name | Type | Required | Description |
|----------------|--------|----------|--|
| isMultizonal | string | False | <p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone |
| privateRouteID | string | False | <p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255 |
| apiServiceID | string | False | <p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p> |

| Name | Type | Required | Description |
|----------|--|----------|---|
| metadata | type_astra_metadata_update | True | Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

type_astra_metadata_list

| Name | Type | Required | Description |
|-----------------------|---|----------|-------------|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Retrieve a cluster for a cloud

GET /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}

Returns the stored Cluster API resource in the JSON response body.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|--|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}} |
| cloud_id | string | path | True | ID of the containing cloud resource |
| cluster_id | string | path | True | ID of the cluster collection to list |

Response

Status: 200, Returns the stored Cluster API resource in the JSON response body.

| Name | Type | Required | Description |
|---------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-cluster" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2""1.3" |

| Name | Type | Required | Description |
|------|--------|----------|--|
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks |

| Name | Type | Required | Description |
|--------------|---------------|----------|---|
| state | string | True | <p>JSON string containing a value indicating the operational state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined |
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| managedState | string | True | <p>JSON string containing a value indicating the management state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management |

| Name | Type | Required | Description |
|------------------------|--------------------------------|----------|---|
| protectionState | string | True | <p>JSON string containing a value indicating the protection state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots |
| protectionStateDetails | array[type_astra_stateDetails] | True | <p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0 |
| restoreTargetSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations. |

| Name | Type | Required | Description |
|---------------------|---------------|----------|---|
| snapshotSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations. |
| managedStateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |
| managedTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed". |

| Name | Type | Required | Description |
|----------------------------|--------------------------------|----------|--|
| tridentVersion | string | False | <p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema |
| tridentManagedState | string | False | <p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra |
| tridentManagedStateDesired | string | False | <p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster |
| tridentManagedStateDetails | array[type_astra_stateDetails] | False | <p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |

| Name | Type | Required | Description |
|----------------------------|---------------|----------|--|
| tridentManagedStateAllowed | array[string] | False | <p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged" |
| inUse | string | True | <p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it |
| accHost | string | False | <p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed. |

| Name | Type | Required | Description |
|----------------|--------|----------|---|
| clusterType | string | True | <p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes |
| clusterVersion | string | False | <p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |

| Name | Type | Required | Description |
|--------------------------|---------------|----------|---|
| clusterVersionString | string | False | <p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |
| clusterCreationTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| namespaces | array[string] | False | <p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 |
| defaultStorageClass | string | False | <p>JSON string containing a storageClass ID that corresponds to the default storage class set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| cloudID | string | True | <p>JSON string containing a value indicating the ID of the cloud the cluster is running on. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| credentialID | string | False | <p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| location | string | False | <p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 |
| isMultizonal | string | False | <p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone |

| Name | Type | Required | Description |
|----------------|--|----------|--|
| privateRouteID | string | False | <p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255 |
| apiServiceID | string | False | <p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p> |
| metadata | type_astra_metadata_update | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example response

```
{
  "type": "application/astra-cluster",
  "version": "1.3",
  "id": "01eaddc3-75b9-5606-97ae-0aa468b59492",
  "name": "GKE-22",
  "state": "running",
  "stateUnready": [],
  "managedState": "unmanaged",
  "managedStateUnready": [],
  "protectionState": "full",
  "protectionStateDetails": [],
  "tridentVersion": "21.07.2",
  "tridentManagedState": "managed",
  "tridentManagedStateDetails": [],
  "inUse": "false",
  "clusterType": "kubernetes",
  "clusterVersion": "1.91.1",
  "clusterVersionString": "1.19.1",
  "clusterCreationTimestamp": "2020-08-06T12:24:52.256624Z",
  "namespaces": [
    "kube-system",
    "kube-public",
    "my-app-1"
  ],
  "defaultStorageClass": "31c95aba-99d9-4987-b1bb-000dfce5952c",
  "cloudID": "548bdc1f-f00e-4a23-a062-83265d224d46",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31",
  "location": "europe-west4",
  "isMultizonal": "false",
  "apiServiceID": "6bf33af2-872a-4553-a891-26b510c3edbe",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/65",
  "title": "Cluster GET not performed",
  "detail": "The cluster GET call didn't perform the lookup operation
on the cluster.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetails

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Modify a cluster for a cloud

PUT /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the cluster is in a managed state, an update to credentialID will eventually trigger another attempt to collect the cluster.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code> |
| cloud_id | string | path | True | ID of the containing cloud resource |
| cluster_id | string | path | True | ID of the cluster collection to list |

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the cluster is in a managed state, an update to credentialID will eventually trigger another attempt to collect the cluster.

| Name | Type | Required | Description |
|---------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cluster" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"• "1.3" |

| Name | Type | Required | Description |
|------|--------|----------|--|
| id | string | False | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | False | JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks |

| Name | Type | Required | Description |
|--------------|---------------|----------|---|
| state | string | False | <p>JSON string containing a value indicating the operational state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined |
| stateUnready | array[string] | False | <p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| managedState | string | False | <p>JSON string containing a value indicating the management state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management |

| Name | Type | Required | Description |
|------------------------|--------------------------------|----------|---|
| protectionState | string | False | <p>JSON string containing a value indicating the protection state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots |
| protectionStateDetails | array[type_astra_stateDetails] | False | <p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0 |
| restoreTargetSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations. |

| Name | Type | Required | Description |
|---------------------|---------------|----------|---|
| snapshotSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations. |
| managedStateUnready | array[string] | False | <p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |
| managedTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed". |

| Name | Type | Required | Description |
|----------------------------|--|----------|--|
| tridentVersion | string | False | <p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema |
| tridentManagedState | string | False | <p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra |
| tridentManagedStateDesired | string | False | <p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster |
| tridentManagedStateDetails | array[type_astra_stateDetails] | False | <p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |

| Name | Type | Required | Description |
|----------------------------|---------------|----------|--|
| tridentManagedStateAllowed | array[string] | False | <p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged" |
| inUse | string | False | <p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it |
| accHost | string | False | <p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed. |

| Name | Type | Required | Description |
|----------------|--------|----------|---|
| clusterType | string | False | <p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes |
| clusterVersion | string | False | <p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |

| Name | Type | Required | Description |
|--------------------------|---------------|----------|---|
| clusterVersionString | string | False | <p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |
| clusterCreationTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| namespaces | array[string] | False | <p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 |
| defaultStorageClass | string | False | <p>JSON string containing a storageClass ID that corresponds to the default storage class set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| cloudID | string | False | <p>JSON string containing a value indicating the ID of the cloud the cluster is running on. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| credentialID | string | False | <p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| location | string | False | <p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 |
| isMultizonal | string | False | <p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone |

| Name | Type | Required | Description |
|----------------|--|----------|---|
| privateRouteID | string | False | JSON string containing the location ID for private clusters. <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255 |
| apiServiceID | string | False | JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster. |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example request

```
{
  "type": "application/astra-cluster",
  "version": "1.3"
}
```

Response

Status: 204, Indicates if the cluster resource was updated.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/65",
  "title": "Cluster GET not performed",
  "detail": "The cluster GET call didn't perform the lookup operation
on the cluster.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetails

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Delete a cluster for a cloud

DELETE /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}

Removes the specified Cluster API resource.

Side Effects

- Internal data structures are cleaned up.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code> |
| cloud_id | string | path | True | ID of the containing cloud resource |
| cluster_id | string | path | True | ID of the cluster collection to list |

Response

Status: 204, Indicates if the cluster resource was deleted.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

List all clusters

GET /accounts/{account_id}/topology/v1/clusters

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|-------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}} |
| include | string | query | False | Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name,managedState |

| Name | Type | In | Required | Description |
|--------|--------|-------|----------|--|
| limit | string | query | False | <p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p> |
| filter | string | query | False | <p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p> |

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name | Type | Required | Description |
|----------|--|----------|-------------|
| items | array[Any of: cluster_1.3_get_response_body , array[]] | True | |
| metadata | type_astra_metadata_list | True | |

Example response

```
{
  "type": "application/astra-clusters",
  "version": "1.3",
  "items": [
    [
      "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
      "GKE-21",
      "managed"
    ],
    [
      "04dc80fa-d1d8-4850-a49f-3b70d0ec1369",
      "GKE-22",
      "unmanaged"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetails

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

cluster_1.3_get_response_body

| Name | Type | Required | Description |
|------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cluster" |

| Name | Type | Required | Description |
|---------|--------|----------|--|
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | True | JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks |

| Name | Type | Required | Description |
|--------------|---------------|----------|---|
| state | string | True | <p>JSON string containing a value indicating the operational state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined |
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| managedState | string | True | <p>JSON string containing a value indicating the management state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management |

| Name | Type | Required | Description |
|------------------------|--------------------------------|----------|---|
| protectionState | string | True | <p>JSON string containing a value indicating the protection state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> "full" - The clusters default storage class supports snapshots "partial" - The cluster has only storageClasses that do not support snapshots "atRisk" - The default storage class of the cluster does not support snapshots |
| protectionStateDetails | array[type_astra_stateDetails] | True | <p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> Minimum Items: 0 |
| restoreTargetSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations. Defined values are:</p> <ul style="list-style-type: none"> "true" - Cluster is an eligible target for app data management operations. "false" - Cluster is <i>not</i> an eligible target for app data management operations. |

| Name | Type | Required | Description |
|---------------------|---------------|----------|---|
| snapshotSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations. |
| managedStateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |
| managedTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed". |

| Name | Type | Required | Description |
|----------------------------|--------|----------|--|
| tridentVersion | string | False | <p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema |
| tridentManagedState | string | False | <p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra |
| tridentManagedStateDesired | string | False | <p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster |

| Name | Type | Required | Description |
|----------------------------|--------------------------------|----------|--|
| tridentManagedStateDetails | array[type_astra_stateDetails] | False | <p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |
| tridentManagedStateAllowed | array[string] | False | <p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged" |
| inUse | string | True | <p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it |

| Name | Type | Required | Description |
|-------------|--------|----------|---|
| accHost | string | False | <p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed. |
| clusterType | string | True | <p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes |

| Name | Type | Required | Description |
|--------------------------|---------------|----------|---|
| clusterVersion | string | False | <p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |
| clusterVersionString | string | False | <p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |
| clusterCreationTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| namespaces | array[string] | False | <p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 |

| Name | Type | Required | Description |
|---------------------|--------|----------|--|
| defaultStorageClass | string | False | <p>JSON string containing a storageClass ID that corresponds to the default storage class set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| cloudID | string | True | <p>JSON string containing a value indicating the ID of the cloud the cluster is running on. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| credentialID | string | False | <p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| location | string | False | <p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 |

| Name | Type | Required | Description |
|----------------|--------|----------|--|
| isMultizonal | string | False | <p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone |
| privateRouteID | string | False | <p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255 |
| apiServiceID | string | False | <p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p> |

| Name | Type | Required | Description |
|----------|--|----------|--|
| metadata | type_astra_metadata_update | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

type_astra_metadata_list

| Name | Type | Required | Description |
|-----------------------|---|----------|-------------|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Retrieve a cluster

GET /accounts/{account_id}/topology/v1/clusters/{cluster_id}

Returns the stored Cluster API resource in the JSON response body.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|--|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}} |
| cluster_id | string | path | True | ID of the cluster collection to list |

Response

Status: 200, Returns the stored Cluster API resource in the JSON response body.

| Name | Type | Required | Description |
|---------|--------|----------|--|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-cluster" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2""1.3" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema |

| Name | Type | Required | Description |
|-------|--------|----------|---|
| name | string | True | <p>JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks |
| state | string | True | <p>JSON string containing a value indicating the operational state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined |

| Name | Type | Required | Description |
|--------------|---------------|----------|---|
| stateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 127 |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| managedState | string | True | <p>JSON string containing a value indicating the management state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management |

| Name | Type | Required | Description |
|------------------------|--------------------------------|----------|---|
| protectionState | string | True | <p>JSON string containing a value indicating the protection state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots |
| protectionStateDetails | array[type_astra_stateDetails] | True | <p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0 |
| restoreTargetSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations. |

| Name | Type | Required | Description |
|---------------------|---------------|----------|---|
| snapshotSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations. |
| managedStateUnready | array[string] | True | <p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |
| managedTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed". |

| Name | Type | Required | Description |
|----------------------------|--|----------|--|
| tridentVersion | string | False | <p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema |
| tridentManagedState | string | False | <p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra |
| tridentManagedStateDesired | string | False | <p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster |
| tridentManagedStateDetails | array[type_astra_stateDetails] | False | <p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |

| Name | Type | Required | Description |
|----------------------------|---------------|----------|--|
| tridentManagedStateAllowed | array[string] | False | <p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged" |
| inUse | string | True | <p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it |
| accHost | string | False | <p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed. |

| Name | Type | Required | Description |
|----------------|--------|----------|---|
| clusterType | string | True | <p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes |
| clusterVersion | string | False | <p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |

| Name | Type | Required | Description |
|--------------------------|---------------|----------|---|
| clusterVersionString | string | False | <p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |
| clusterCreationTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| namespaces | array[string] | False | <p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 |
| defaultStorageClass | string | False | <p>JSON string containing a storageClass ID that corresponds to the default storage class set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| cloudID | string | True | <p>JSON string containing a value indicating the ID of the cloud the cluster is running on. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| credentialID | string | False | <p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| location | string | False | <p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 |
| isMultizonal | string | False | <p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone |

| Name | Type | Required | Description |
|----------------|----------------------------|----------|---|
| privateRouteID | string | False | <p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255 |
| apiServiceID | string | False | <p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p> |
| metadata | type_astra_metadata_update | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example response

```
{
  "type": "application/astra-cluster",
  "version": "1.3",
  "id": "01eaddc3-75b9-5606-97ae-0aa468b59492",
  "name": "GKE-22",
  "state": "running",
  "stateUnready": [],
  "managedState": "unmanaged",
  "managedStateUnready": [],
  "protectionState": "full",
  "protectionStateDetails": [],
  "tridentVersion": "21.07.2",
  "tridentManagedState": "managed",
  "tridentManagedStateDetails": [],
  "inUse": "false",
  "clusterType": "kubernetes",
  "clusterVersion": "1.91.1",
  "clusterVersionString": "1.19.1",
  "clusterCreationTimestamp": "2020-08-06T12:24:52.256624Z",
  "namespaces": [
    "kube-system",
    "kube-public",
    "my-app-1"
  ],
  "defaultStorageClass": "31c95aba-99d9-4987-b1bb-000dfce5952c",
  "cloudID": "548bdc1f-f00e-4a23-a062-83265d224d46",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31",
  "location": "europe-west4",
  "isMultizonal": "false",
  "apiServiceID": "6bf33af2-872a-4553-a891-26b510c3edbe",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

```
Status: 401, Unauthorized
```

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/65",
  "title": "Cluster GET not performed",
  "detail": "The cluster GET call didn't perform the lookup operation
on the cluster.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetails

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Modify a cluster

PUT /accounts/{account_id}/topology/v1/clusters/{cluster_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the cluster is in a managed state, an update to credentialID will eventually trigger another attempt to collect the cluster.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|--|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">• example: {{.Account}} |
| cluster_id | string | path | True | ID of the cluster collection to list |

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the cluster is in a managed state, an update to credentialID will eventually trigger another attempt to collect the cluster.

| Name | Type | Required | Description |
|---------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cluster" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"• "1.3" |

| Name | Type | Required | Description |
|------|--------|----------|--|
| id | string | False | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| name | string | False | JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks |

| Name | Type | Required | Description |
|--------------|---------------|----------|---|
| state | string | False | <p>JSON string containing a value indicating the operational state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined |
| stateUnready | array[string] | False | <p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| managedState | string | False | <p>JSON string containing a value indicating the management state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management |

| Name | Type | Required | Description |
|------------------------|--------------------------------|----------|---|
| protectionState | string | False | <p>JSON string containing a value indicating the protection state of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots |
| protectionStateDetails | array[type_astra_stateDetails] | False | <p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0 |
| restoreTargetSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations. |

| Name | Type | Required | Description |
|---------------------|---------------|----------|---|
| snapshotSupported | string | False | <p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations. |
| managedStateUnready | array[string] | False | <p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127 |
| managedTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed". |

| Name | Type | Required | Description |
|----------------------------|--------------------------------|----------|--|
| tridentVersion | string | False | <p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema |
| tridentManagedState | string | False | <p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra |
| tridentManagedStateDesired | string | False | <p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster |
| tridentManagedStateDetails | array[type_astra_stateDetails] | False | <p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0 |

| Name | Type | Required | Description |
|----------------------------|---------------|----------|--|
| tridentManagedStateAllowed | array[string] | False | <p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged" |
| inUse | string | False | <p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it |
| accHost | string | False | <p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed. |

| Name | Type | Required | Description |
|----------------|--------|----------|---|
| clusterType | string | False | <p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes |
| clusterVersion | string | False | <p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |

| Name | Type | Required | Description |
|--------------------------|---------------|----------|---|
| clusterVersionString | string | False | <p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 |
| clusterCreationTimestamp | string | False | <p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema |
| namespaces | array[string] | False | <p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 |
| defaultStorageClass | string | False | <p>JSON string containing a storageClass ID that corresponds to the default storage class set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|--------------|--------|----------|--|
| cloudID | string | False | <p>JSON string containing a value indicating the ID of the cloud the cluster is running on. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| credentialID | string | False | <p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |
| location | string | False | <p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 |
| isMultizonal | string | False | <p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone |

| Name | Type | Required | Description |
|----------------|--|----------|---|
| privateRouteID | string | False | JSON string containing the location ID for private clusters. <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255 |
| apiServiceID | string | False | JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster. |
| metadata | type_astra_metadata_update | False | Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example request

```
{
  "type": "application/astra-cluster",
  "version": "1.3"
}
```

Response

Status: 204, Indicates if the cluster resource was updated.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/65",
  "title": "Cluster GET not performed",
  "detail": "The cluster GET call didn't perform the lookup operation
on the cluster.",
  "status": "500"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetails

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|---|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Delete a cluster

DELETE /accounts/{account_id}/topology/v1/clusters/{cluster_id}

Removes the specified Cluster API resource.

Side Effects

- Internal data structures are cleaned up.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource • example: {{.Account}} |
| cluster_id | string | path | True | ID of the cluster collection to list |

Response

Status: 204, Indicates if the cluster resource was deleted.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | False | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

저작권 정보

Copyright © 2024 NetApp, Inc. All Rights Reserved. 미국에서 인쇄된 본 문서의 어떠한 부분도 저작권 소유자의 사전 서면 승인 없이는 어떠한 형식이나 수단(복사, 녹음, 녹화 또는 전자 검색 시스템에 저장하는 것을 비롯한 그래픽, 전자적 또는 기계적 방법)으로도 복제될 수 없습니다.

NetApp이 저작권을 가진 자료에 있는 소프트웨어에는 아래의 라이선스와 고지사항이 적용됩니다.

본 소프트웨어는 NetApp에 의해 '있는 그대로' 제공되며 상품성 및 특정 목적에의 적합성에 대한 명시적 또는 묵시적 보증을 포함하여(이에 제한되지 않음) 어떠한 보증도 하지 않습니다. NetApp은 대체품 또는 대체 서비스의 조달, 사용 불능, 데이터 손실, 이익 손실, 영업 중단을 포함하여(이에 국한되지 않음), 이 소프트웨어의 사용으로 인해 발생하는 모든 직접 및 간접 손해, 우발적 손해, 특별 손해, 징벌적 손해, 결과적 손해의 발생에 대하여 그 발생 이유, 책임론, 계약 여부, 엄격한 책임, 불법 행위(과실 또는 그렇지 않은 경우)와 관계없이 어떠한 책임도 지지 않으며, 이와 같은 손실의 발생 가능성이 통지되었다 하더라도 마찬가지입니다.

NetApp은 본 문서에 설명된 제품을 언제든지 예고 없이 변경할 권리를 보유합니다. NetApp은 NetApp의 명시적인 서면 동의를 받은 경우를 제외하고 본 문서에 설명된 제품을 사용하여 발생하는 어떠한 문제에도 책임을 지지 않습니다. 본 제품의 사용 또는 구매의 경우 NetApp에서는 어떠한 특허권, 상표권 또는 기타 지적 재산권이 적용되는 라이선스도 제공하지 않습니다.

본 설명서에 설명된 제품은 하나 이상의 미국 특허, 해외 특허 또는 출원 중인 특허로 보호됩니다.

제한적 권리 표시: 정부에 의한 사용, 복제 또는 공개에는 DFARS 252.227-7013(2014년 2월) 및 FAR 52.227-19(2007년 12월)의 기술 데이터-비상업적 품목에 대한 권리(Rights in Technical Data -Noncommercial Items) 조항의 하위 조항 (b)(3)에 설명된 제한사항이 적용됩니다.

여기에 포함된 데이터는 상업용 제품 및/또는 상업용 서비스(FAR 2.101에 정의)에 해당하며 NetApp, Inc.의 독점 자산입니다. 본 계약에 따라 제공되는 모든 NetApp 기술 데이터 및 컴퓨터 소프트웨어는 본질적으로 상업용이며 개인 비용만으로 개발되었습니다. 미국 정부는 데이터가 제공된 미국 계약과 관련하여 해당 계약을 지원하는 데에만 데이터에 대한 전 세계적으로 비독점적이고 양도할 수 없으며 재사용이 불가능하며 취소 불가능한 라이선스를 제한적으로 가집니다. 여기에 제공된 경우를 제외하고 NetApp, Inc.의 사전 서면 승인 없이는 이 데이터를 사용, 공개, 재생산, 수정, 수행 또는 표시할 수 없습니다. 미국 국방부에 대한 정부 라이선스는 DFARS 조항 252.227-7015(b)(2014년 2월)에 명시된 권한으로 제한됩니다.

상표 정보

NETAPP, NETAPP 로고 및 <http://www.netapp.com/TM>에 나열된 마크는 NetApp, Inc.의 상표입니다. 기타 회사 및 제품 이름은 해당 소유자의 상표일 수 있습니다.