



Execution Hook Override

Astra Automation

NetApp
December 01, 2023

목차

| | |
|--|----|
| Execution Hook Override | 1 |
| Execution Hook Override overview | 1 |
| Create a new execution hook override resource for an app | 1 |
| List the execution hook override resources for an app | 10 |
| Retrieve an execution hook override resource | 19 |
| Modify an execution hook override resource | 25 |
| Delete an execution hook override resource | 33 |

Execution Hook Override

Execution Hook Override overview

The Execution Hook Override API allows a user to disable the preloaded "netapp" execution hooks for a specific application. (**NOTE BELOW API DEPRECATIONS**)

Create a new execution hook override resource for an app

POST /accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides

Indicates the desired values for the Execution Hook Override API resource to be created.



This operation is deprecated.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code> |
| app_id | string | path | True | ID of the containing app resource |

Request Body

Indicates the desired values for the Execution Hook Override API resource to be created.

| Name | Type | Required | Description |
|---------|--------|----------|--|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-executionHookOverride" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0" |

| Name | Type | Required | Description |
|-----------------|----------------------------|----------|---|
| executionHookID | string | True | <p>JSON string containing the ID of an execution hook. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp". |
| enabled | string | True | <p>JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will run in a specified order • "false" - The execution hook is disabled and cannot run |
| metadata | type_astra_metadata_update | False | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example request

```
{
  "type": "application/astra-executionHookOverride",
  "version": "1.0",
  "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
  "enabled": "false"
}
```

Response

Status: 201, Returns the newly created executionHookOverride resource in the JSON response body.

| Name | Type | Required | Description |
|---------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-executionHookOverride" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema |

| Name | Type | Required | Description |
|-----------------|--------|----------|--|
| executionHookID | string | True | <p>JSON string containing the ID of an execution hook. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp". |
| enabled | string | True | <p>JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will run in a specified order • "false" - The execution hook is disabled and cannot run |
| appID | string | True | <p>JSON string containing the associated ID of the application with which the override is linked. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|----------|--|----------|---|
| metadata | type_astra_metadata_update | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example response

```
{
  "type": "application/astra-executionHookOverride",
  "version": "1.0",
  "id": "c11af802-5e53-5897-8cd9-2de730494be3",
  "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
  "enabled": "false",
  "appID": "4b43c2f7-bffa-4f60-b595-d98a05b64bc9",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|------|--------|----------|-------------|
| type | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```


Response

Status: 409, Conflict

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|--------|--------|----------|--|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

List the execution hook override resources for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.



This operation is deprecated.

Parameters

| Name | Type | In | Required | Description |
|------------|--------|-------|----------|--|
| account_id | string | path | True | ID of the containing account resource • example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| include | string | query | False | Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" |
| limit | string | query | False | Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2" |

| Name | Type | In | Required | Description |
|--------|--------|-------|----------|--|
| filter | string | query | False | <p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p> |

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name | Type | Required | Description |
|----------|--|----------|-------------|
| items | array[Any of: executionHookOverride_1 .0_get_response_body, array[]] | True | |
| metadata | type_astra_metadata_list | True | |

Example response

```
{
  "type": "application/astra-executionHookOverrides",
  "version": "1.0",
  "items": [
    {
      "type": "application/astra-executionHookOverride",
      "version": "1.0",
      "id": "36d06222-bd0c-4897-89c2-c16dd9265e12",
      "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
      "enabled": "false",
      "appID": "4b43c2f7-bffa-4f60-b595-d98a05b64bc9",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "863feb92-8619-4298-b222-c48a886024f8"
      }
    },
    {
      "type": "application/astra-executionHookOverride",
      "version": "1.0",
      "id": "f8d1ce66-6c0e-4d3a-96c5-a5e76669442d",
      "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
      "enabled": "false",
      "appID": "36b076ae-b7c4-4e96-a323-ed167ede74ba",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "863feb92-8619-4298-b222-c48a886024f8"
      }
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

executionHookOverride_1.0_get_response_body

| Name | Type | Required | Description |
|---------|--------|----------|---|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-executionHookOverride" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0" |
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema |

| Name | Type | Required | Description |
|-----------------|--------|----------|--|
| executionHookID | string | True | <p>JSON string containing the ID of an execution hook. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp". |
| enabled | string | True | <p>JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will run in a specified order • "false" - The execution hook is disabled and cannot run |
| appID | string | True | <p>JSON string containing the associated ID of the application with which the override is linked. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|----------|--|----------|--|
| metadata | type_astra_metadata_update | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

type_astra_metadata_list

| Name | Type | Required | Description |
|-----------------------|---|----------|-------------|
| continue | string | False | |
| count | number | False | |
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Retrieve an execution hook override resource

GET

/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides/{executionHookOverride_id}

Returns the stored Execution Hook Override API resource in the JSON response body.



This operation is deprecated.

Parameters

| Name | Type | In | Required | Description |
|--------------------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code> |
| app_id | string | path | True | ID of the containing app resource |
| executionHookOverride_id | string | path | True | ID of the executionHookOverride collection to list |

Response

Status: 200, Returns the stored Execution Hook Override API resource in the JSON response body.

| Name | Type | Required | Description |
|---------|--------|----------|--|
| type | string | True | Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-executionHookOverride" |
| version | string | True | Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0" |

| Name | Type | Required | Description |
|-----------------|--------|----------|---|
| id | string | True | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| executionHookID | string | True | JSON string containing the ID of an execution hook. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp". |
| enabled | string | True | JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are: <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will run in a specified order • "false" - The execution hook is disabled and cannot run |
| appID | string | True | JSON string containing the associated ID of the application with which the override is linked. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|----------|--|----------|---|
| metadata | type_astra_metadata_update | True | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example response

```
{
  "type": "application/astra-executionHookOverride",
  "version": "1.0",
  "id": "c11af802-5e53-5897-8cd9-2de730494be3",
  "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
  "enabled": "false",
  "appID": "4b43c2f7-bffa-4f60-b595-d98a05b64bc9",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|------|--------|----------|-------------|
| type | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```


Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

Modify an execution hook override resource

PUT

/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides/{executionHookOverride_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Any execution hook with a hookType value of "netapp" that applies to the specified application will be disabled if the value of enabled is changed from "true" to "false" during the replace operation.

- Any execution hook with a hookType value of "netapp" that applies to the specified application will be enabled if the value of enabled is changed from "false" to "true" during the replace operation.



This operation is deprecated.

Parameters

| Name | Type | In | Required | Description |
|--------------------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource • example: {{.Account}} |
| app_id | string | path | True | ID of the containing app resource |
| executionHookOverride_id | string | path | True | ID of the executionHookOverride collection to list |

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Any execution hook with a hookType value of "netapp" that applies to the specified application will be disabled if the value of enabled is changed from "true" to "false" during the replace operation.
- Any execution hook with a hookType value of "netapp" that applies to the specified application will be enabled if the value of enabled is changed from "false" to "true" during the replace operation.

| Name | Type | Required | Description |
|---------|--------|----------|--|
| type | string | True | Media type of the resource. Defined values are: • "application/astra-executionHookOverride" |
| version | string | True | Version of the resource. Defined values are: • "1.0" |

| Name | Type | Required | Description |
|-----------------|--------|----------|---|
| id | string | False | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema |
| executionHookID | string | False | JSON string containing the ID of an execution hook. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp". |
| enabled | string | False | JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are: <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will run in a specified order • "false" - The execution hook is disabled and cannot run |
| appID | string | False | JSON string containing the associated ID of the application with which the override is linked. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema |

| Name | Type | Required | Description |
|----------|--|----------|--|
| metadata | type_astra_metadata_update | False | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification. |

Example request

```
{
  "type": "application/astra-executionHookOverride",
  "version": "1.0",
  "enabled": "false"
}
```

Response

Status: 204, Indicates if the executionHookOverride resource was updated.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

| Name | Type | Required | Description |
|---------------|----------------------|----------|-------------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidFields | array[invalidFields] | False | List of invalid request body fields |

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

| Name | Type | Required | Description |
|-------|--------|----------|-------------|
| name | string | True | |
| value | string | True | |

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name | Type | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels | array[type_astra_label] | False | |
| creationTimestamp | string | False | |
| modificationTimestamp | string | False | |
| createdBy | string | False | |
| modifiedBy | string | False | |

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

invalidFields

| Name | Type | Required | Description |
|--------|--------|----------|--|
| name | string | True | Name of the invalid request body field |
| reason | string | True | Reason why the request body field is invalid |

Delete an execution hook override resource

DELETE

/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides/{executionHookOverride_id}

Removes the specified Execution Hook Override API resource.

Side Effects

- Any execution hook with a hookType value of "netapp" that applies to the specified application will be enabled when a new execution hook override is deleted if it had an enabled value of "false".



This operation is deprecated.

Parameters

| Name | Type | In | Required | Description |
|--------------------------|--------|------|----------|---|
| account_id | string | path | True | ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code> |
| app_id | string | path | True | ID of the containing app resource |
| executionHookOverride_id | string | path | True | ID of the executionHookOverride collection to list |

Response

Status: 204, Indicates if the executionHookOverride resource was deleted.

Response

Status: 401, Unauthorized

| Name | Type | Required | Description |
|--------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

| Name | Type | Required | Description |
|---------------|----------------------|----------|----------------------------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |
| invalidParams | array[invalidParams] | False | List of invalid query parameters |

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

| Name | Type | Required | Description |
|---------------|--------|----------|-------------|
| type | string | True | |
| title | string | True | |
| detail | string | True | |
| status | string | True | |
| correlationID | string | False | |

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

| Name | Type | Required | Description |
|--------|--------|----------|---|
| name | string | True | Name of the invalid query parameter |
| reason | string | True | Reason why the query parameter is invalid |

저작권 정보

Copyright © 2023 NetApp, Inc. All Rights Reserved. 미국에서 인쇄된 본 문서의 어떠한 부분도 저작권 소유자의 사전 서면 승인 없이는 어떠한 형식이나 수단(복사, 녹음, 녹화 또는 전자 검색 시스템에 저장하는 것을 비롯한 그래픽, 전자적 또는 기계적 방법)으로도 복제될 수 없습니다.

NetApp이 저작권을 가진 자료에 있는 소프트웨어에는 아래의 라이선스와 고지사항이 적용됩니다.

본 소프트웨어는 NetApp에 의해 '있는 그대로' 제공되며 상품성 및 특정 목적에의 적합성에 대한 명시적 또는 묵시적 보증을 포함하여(이에 제한되지 않음) 어떠한 보증도 하지 않습니다. NetApp은 대체품 또는 대체 서비스의 조달, 사용 불능, 데이터 손실, 이익 손실, 영업 중단을 포함하여(이에 국한되지 않음), 이 소프트웨어의 사용으로 인해 발생하는 모든 직접 및 간접 손해, 우발적 손해, 특별 손해, 징벌적 손해, 결과적 손해의 발생에 대하여 그 발생 이유, 책임론, 계약 여부, 엄격한 책임, 불법 행위(과실 또는 그렇지 않은 경우)와 관계없이 어떠한 책임도 지지 않으며, 이와 같은 손실의 발생 가능성이 통지되었다 하더라도 마찬가지입니다.

NetApp은 본 문서에 설명된 제품을 언제든지 예고 없이 변경할 권리를 보유합니다. NetApp은 NetApp의 명시적인 서면 동의를 받은 경우를 제외하고 본 문서에 설명된 제품을 사용하여 발생하는 어떠한 문제에도 책임을 지지 않습니다. 본 제품의 사용 또는 구매의 경우 NetApp에서는 어떠한 특허권, 상표권 또는 기타 지적 재산권이 적용되는 라이선스도 제공하지 않습니다.

본 설명서에 설명된 제품은 하나 이상의 미국 특허, 해외 특허 또는 출원 중인 특허로 보호됩니다.

제한적 권리 표시: 정부에 의한 사용, 복제 또는 공개에는 DFARS 252.227-7013(2014년 2월) 및 FAR 52.227-19(2007년 12월)의 기술 데이터-비상업적 품목에 대한 권리(Rights in Technical Data -Noncommercial Items) 조항의 하위 조항 (b)(3)에 설명된 제한사항이 적용됩니다.

여기에 포함된 데이터는 상업용 제품 및/또는 상업용 서비스(FAR 2.101에 정의)에 해당하며 NetApp, Inc.의 독점 자산입니다. 본 계약에 따라 제공되는 모든 NetApp 기술 데이터 및 컴퓨터 소프트웨어는 본질적으로 상업용이며 개인 비용만으로 개발되었습니다. 미국 정부는 데이터가 제공된 미국 계약과 관련하여 해당 계약을 지원하는 데에만 데이터에 대한 전 세계적으로 비독점적이고 양도할 수 없으며 재사용이 불가능하며 취소 불가능한 라이선스를 제한적으로 가집니다. 여기에 제공된 경우를 제외하고 NetApp, Inc.의 사전 서면 승인 없이는 이 데이터를 사용, 공개, 재생산, 수정, 수행 또는 표시할 수 없습니다. 미국 국방부에 대한 정부 라이선스는 DFARS 조항 252.227-7015(b)(2014년 2월)에 명시된 권한으로 제한됩니다.

상표 정보

NETAPP, NETAPP 로고 및 <http://www.netapp.com/TM>에 나열된 마크는 NetApp, Inc.의 상표입니다. 기타 회사 및 제품 이름은 해당 소유자의 상표일 수 있습니다.