



## User

### Astra Automation

NetApp  
June 28, 2024

# 목차

User .....	1
User overview .....	1
Create a new user for a group .....	1
List the users for a group .....	18
Retrieve a user for a group .....	35
Modify a user for a group .....	48
Delete a user for a group .....	61
Create a new user .....	64
List all users .....	82
Retrieve a user .....	99
Modify a user .....	112
Delete a user .....	125

# User

## User overview

The User API represents users who are able to interact with the system.

## Create a new user for a group

POST /accounts/{account\_id}/core/v1/groups/{group\_id}/users

Indicates desired values for the User API resource to be created.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"><li>example: <code>{{.Account}}</code></li></ul>
group_id	string	path	True	ID of the containing group resource

### Request Body

Indicates desired values for the User API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>"application/astra-user"</li></ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"><li>"1.0"</li><li>"1.1"</li><li>"1.2"</li></ul>

Name	Type	Required	Description
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "ldap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "ldap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "ldap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>

Name	Type	Required	Description
firstName	string	False	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
lastName	string	False	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>

Name	Type	Required	Description
email	string	True	JSON strings containing a user-specified email address.
phone	string	False	JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.
postalAddress	<a href="#">postalAddress</a>	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	False	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>

Name	Type	Required	Description
metadata	<a href="#">type_astra_metadata_update</a>	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

### Example request

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "firstName": "John",
  "lastName": "Doe",
  "email": "<a href='mailto:jd@example.com'>jd@example.com</a>"
}
```

### Response

Status: 201, Returns the newly created user resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>"application/astra-user"</li> </ul>

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
state	string	True	JSON string containing a value indicating the operational state of the user. Defined values are: <ul style="list-style-type: none"> <li>• "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value).</li> <li>• This state is not valid for a user with "authProvider" as "local"</li> <li>• "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true").</li> <li>• This is the default value for a user with "authProvider" as "local"</li> <li>• "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).</li> </ul>



Name	Type	Required	Description
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - The user is allowed to log in; default value on create.</li> <li>• "false" - The user is not allowed to log in.</li> </ul>
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>
firstName	string	True	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>

Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

## Example response

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "id": "5bad8e04-e2fd-5c43-98d7-300580993f49",
  "state": "pending",
  "isEnabled": "true",
  "authID": "HteLK3hk28sdbDLKHReB",
  "authProvider": "cloud-central",
  "firstName": "John",
  "lastName": "Doe",
  "email": "<a href='mailto:jdoe@example.com'>jdoe@example.com</a>",
  "sendWelcomeEmail": "true",
  "lastActTimestamp": "2020-08-05T14:24:54.128427Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	



## Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

### postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 2</li><li>• Maximum length: 2</li></ul>
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

#### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

#### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

## List the users for a group

GET /accounts/{account\_id}/core/v1/groups/{group\_id}/users

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>
group_id	string	path	True	ID of the containing group resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples:  "include=id",  "include=id,name"</p> <p>OpenAPI examples:  "id"</p> <ul style="list-style-type: none"> <li>• example: id,email</li> </ul>
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples:  "limit=2"</p> <p>OpenAPI examples:  "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> <li>• eq - Equality</li> <li>• lt/gt - Less than/Greater than</li> <li>• lte/gte - Less than or equals to/Greater than or equals to</li> </ul> <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object.  URL examples: "count=true"  OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from.  URL examples: "continue=<continue token="" from="" collection="" metadata=""></continue>  OpenAPI examples: "<continue token="" from="" collection="" metadata=""></continue>&lt;/continue&gt;"

## Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: <a href="#">user_1.2_get_response_body</a> , array[]]	True	
metadata	<a href="#">type_astra_metadata_list</a>	True	

## Example response

```
{
  "type": "application/astra-users",
  "version": "1.2",
  "items": [
    [
      "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa",
      "<a href='mailto:jdoe@example.com'>jdoe@example.com</a>"
    ],
    [
      "e324ec3a-706d-4f57-a95d-1d88c03e7b73",
      "<a href='mailto:ssmith@example.com'>:ssmith@example.com</a>"
    ],
    [
      "3070c84d-129b-4017-82a8-2c26a42dd77e",
      "<a href='mailto:wjohns@example.com'>wjohns@example.com</a>"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	



### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

# Definitions

## See Definitions

### postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 2</li><li>• Maximum length: 2</li></ul>
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

#### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

#### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### user\_1.2\_get\_response\_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-user"</li></ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"><li>• "1.0"</li><li>• "1.1"</li><li>• "1.2"</li></ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the UUIDv4 Schema</li></ul>

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the user. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value).</li> <li>• This state is not valid for a user with "authProvider" as "local"</li> <li>• "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true").</li> <li>• This is the default value for a user with "authProvider" as "local"</li> <li>• "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).</li> </ul>
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - The user is allowed to log in; default value on create.</li> <li>• "false" - The user is not allowed to log in.</li> </ul>

Name	Type	Required	Description
authID	string	False	JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.



Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "ldap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "ldap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "ldap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>
firstName	string	True	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>

Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>

Name	Type	Required	Description
lastActTimestamp	string	False	JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are: <ul style="list-style-type: none"> <li>Conforms to the ISO-8601 Date Time Schema</li> </ul>
metadata	<a href="#">type_astra_metadata_update</a>	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

type\_astra\_metadata\_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Retrieve a user for a group

GET /accounts/{account\_id}/core/v1/groups/{group\_id}/users/{user\_id}

Returns the stored User API resource in the JSON response body.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the user collection to list

### Response

Status: 200, Returns the stored User API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>"application/astra-user"</li> </ul>

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
state	string	True	JSON string containing a value indicating the operational state of the user. Defined values are: <ul style="list-style-type: none"> <li>• "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value).</li> <li>• This state is not valid for a user with "authProvider" as "local"</li> <li>• "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true").</li> <li>• This is the default value for a user with "authProvider" as "local"</li> <li>• "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).</li> </ul>

Name	Type	Required	Description
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - The user is allowed to log in; default value on create.</li> <li>• "false" - The user is not allowed to log in.</li> </ul>
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>
firstName	string	True	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>



Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

## Example response

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "id": "5bad8e04-e2fd-5c43-98d7-300580993f49",
  "state": "active",
  "isEnabled": "true",
  "authID": "HteLK3hk28sdbDLKHReB",
  "authProvider": "cloud-central",
  "firstName": "John",
  "lastName": "Doe",
  "companyName": "NetApp, Inc.",
  "email": "<a href='mailto:jd@exampl.com'>jd@exampl.com</a>",
  "phone": "408-555-2222",
  "postalAddress": {
    "addressCountry": "US",
    "addressLocality": "Sunnyvale",
    "addressRegion": "California",
    "postalCode": "94089",
    "streetAddress1": "495 East Java Drive"
  },
  "sendWelcomeEmail": "true",
  "enableTimestamp": "2020-08-05T14:24:54.128427Z",
  "lastActTimestamp": "2020-08-05T14:24:54.128427Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

### postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 2</li><li>• Maximum length: 2</li></ul>
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>



Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

#### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

#### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Modify a user for a group

PUT /accounts/{account\_id}/core/v1/groups/{group\_id}/users/{user\_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the user collection to list

### Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>"application/astra-user"</li> </ul>

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
state	string	False	JSON string containing a value indicating the operational state of the user. Defined values are: <ul style="list-style-type: none"> <li>• "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value).</li> <li>• This state is not valid for a user with "authProvider" as "local"</li> <li>• "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true").</li> <li>• This is the default value for a user with "authProvider" as "local"</li> <li>• "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).</li> </ul>

Name	Type	Required	Description
isEnabled	string	False	<p>JSON string indicating if the user is allowed to log in. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - The user is allowed to log in; default value on create.</li> <li>• "false" - The user is not allowed to log in.</li> </ul>
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>
firstName	string	False	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>

Name	Type	Required	Description
lastName	string	False	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
email	string	False	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	False	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

### Example request

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "firstName": "John",
  "lastName": "Dale",
  "email": "<a href='mailto:jdale@example.com'>jdale@example.com</a>"
}
```

### Response



Status: 204, Indicates if the user resource was updated.

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

# Definitions

## See Definitions

### postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 2</li><li>• Maximum length: 2</li></ul>
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

#### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

#### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

## Delete a user for a group

DELETE /accounts/{account\_id}/core/v1/groups/{group\_id}/users/{user\_id}

Removes the specified User API resource.

### Side Effects

- The following resources associated with the user are deleted: notificationMarks, tokens, and all roleBindings referring to the user.
- For a user with "authProvider" as "local", the linked credential with "keyType" as "passwordHash" will also be deleted.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource  • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the user collection to list

## Response

Status: 204, Indicates if the user resource was deleted.

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters



### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

### See Definitions

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Create a new user

POST /accounts/{account\_id}/core/v1/users

Indicates desired values for the User API resource to be created.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>

## Request Body

Indicates desired values for the User API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-user"</li></ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"><li>• "1.0"</li><li>• "1.1"</li><li>• "1.2"</li></ul>
authID	string	False	JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>
firstName	string	False	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>

Name	Type	Required	Description
lastName	string	False	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	<a href="#">postalAddress</a>	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	False	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>

Name	Type	Required	Description
metadata	<a href="#">type_astra_metadata_update</a>	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

### Example request

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "firstName": "John",
  "lastName": "Doe",
  "email": "<a href='mailto:jd@example.com'>jd@example.com</a>"
}
```

### Response

Status: 201, Returns the newly created user resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• "application/astra-user"</li> </ul>

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
state	string	True	JSON string containing a value indicating the operational state of the user. Defined values are: <ul style="list-style-type: none"> <li>• "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value).</li> <li>• This state is not valid for a user with "authProvider" as "local"</li> <li>• "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true").</li> <li>• This is the default value for a user with "authProvider" as "local"</li> <li>• "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).</li> </ul>



Name	Type	Required	Description
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - The user is allowed to log in; default value on create.</li> <li>• "false" - The user is not allowed to log in.</li> </ul>
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>
firstName	string	True	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>

Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

## Example response

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "id": "5bad8e04-e2fd-5c43-98d7-300580993f49",
  "state": "pending",
  "isEnabled": "true",
  "authID": "HteLK3hk28sdbDLKHReB",
  "authProvider": "cloud-central",
  "firstName": "John",
  "lastName": "Doe",
  "email": "<a href='mailto:jdoe@example.com'>jdoe@example.com</a>",
  "sendWelcomeEmail": "true",
  "lastActTimestamp": "2020-08-05T14:24:54.128427Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	



## Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

### postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 2</li><li>• Maximum length: 2</li></ul>
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

#### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

#### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

## List all users

GET /accounts/{account\_id}/core/v1/users

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples:  "include=id",  "include=id,name"</p> <p>OpenAPI examples:  "id"</p> <ul style="list-style-type: none"> <li>example: id,email</li> </ul>
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples:  "limit=2"</p> <p>OpenAPI examples:  "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> <li>• eq - Equality</li> <li>• lt/gt - Less than/Greater than</li> <li>• lte/gte - Less than or equals to/Greater than or equals to</li> </ul> <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object.  URL examples: "count=true"  OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from.  URL examples: "continue=<continue token="" from="" collection="" metadata=""></continue>  OpenAPI examples: "<continue token="" from="" collection="" metadata=""></continue>&lt;/continue&gt;"

## Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: <a href="#">user_1.2_get_response_body</a> , array[]]	True	
metadata	<a href="#">type_astra_metadata_list</a>	True	

## Example response

```
{
  "type": "application/astra-users",
  "version": "1.2",
  "items": [
    [
      "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa",
      "<a href='mailto:jdoe@example.com'>jdoe@example.com</a>"
    ],
    [
      "e324ec3a-706d-4f57-a95d-1d88c03e7b73",
      "<a href='mailto:ssmith@example.com'>:ssmith@example.com</a>"
    ],
    [
      "3070c84d-129b-4017-82a8-2c26a42dd77e",
      "<a href='mailto:wjohns@example.com'>wjohns@example.com</a>"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	



### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

# Definitions

## See Definitions

### postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 2</li><li>• Maximum length: 2</li></ul>
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

#### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

#### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### user\_1.2\_get\_response\_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "application/astra-user"</li> </ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the user. Defined values are:</p> <ul style="list-style-type: none"> <li>• "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value).</li> <li>• This state is not valid for a user with "authProvider" as "local"</li> <li>• "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true").</li> <li>• This is the default value for a user with "authProvider" as "local"</li> <li>• "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).</li> </ul>
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - The user is allowed to log in; default value on create.</li> <li>• "false" - The user is not allowed to log in.</li> </ul>

Name	Type	Required	Description
authID	string	False	JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.



Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "ldap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "ldap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "ldap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>
firstName	string	True	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>

Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>

Name	Type	Required	Description
lastActTimestamp	string	False	JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are: <ul style="list-style-type: none"> <li>Conforms to the ISO-8601 Date Time Schema</li> </ul>
metadata	<a href="#">type_astra_metadata_update</a>	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

type\_astra\_metadata\_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Retrieve a user

GET /accounts/{account\_id}/core/v1/users/{user\_id}

Returns the stored User API resource in the JSON response body.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>
user_id	string	path	True	ID of the user collection to list

### Response

Status: 200, Returns the stored User API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>"application/astra-user"</li> </ul>

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
state	string	True	JSON string containing a value indicating the operational state of the user. Defined values are: <ul style="list-style-type: none"> <li>• "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value).</li> <li>• This state is not valid for a user with "authProvider" as "local"</li> <li>• "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true").</li> <li>• This is the default value for a user with "authProvider" as "local"</li> <li>• "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).</li> </ul>

Name	Type	Required	Description
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - The user is allowed to log in; default value on create.</li> <li>• "false" - The user is not allowed to log in.</li> </ul>
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>
firstName	string	True	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>



Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

## Example response

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "id": "5bad8e04-e2fd-5c43-98d7-300580993f49",
  "state": "active",
  "isEnabled": "true",
  "authID": "HteLK3hk28sdbDLKHReB",
  "authProvider": "cloud-central",
  "firstName": "John",
  "lastName": "Doe",
  "companyName": "NetApp, Inc.",
  "email": "<a href='mailto:jd@exampl.com'>jd@exampl.com</a>",
  "phone": "408-555-2222",
  "postalAddress": {
    "addressCountry": "US",
    "addressLocality": "Sunnyvale",
    "addressRegion": "California",
    "postalCode": "94089",
    "streetAddress1": "495 East Java Drive"
  },
  "sendWelcomeEmail": "true",
  "enableTimestamp": "2020-08-05T14:24:54.128427Z",
  "lastActTimestamp": "2020-08-05T14:24:54.128427Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

### postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 2</li><li>• Maximum length: 2</li></ul>
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>



Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

#### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

#### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Modify a user

PUT /accounts/{account\_id}/core/v1/users/{user\_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>
user_id	string	path	True	ID of the user collection to list

### Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>"application/astra-user"</li> </ul>

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> <li>• "1.1"</li> <li>• "1.2"</li> </ul>
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>
state	string	False	JSON string containing a value indicating the operational state of the user. Defined values are: <ul style="list-style-type: none"> <li>• "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value).</li> <li>• This state is not valid for a user with "authProvider" as "local"</li> <li>• "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true").</li> <li>• This is the default value for a user with "authProvider" as "local"</li> <li>• "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).</li> </ul>

Name	Type	Required	Description
isEnabled	string	False	<p>JSON string indicating if the user is allowed to log in. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - The user is allowed to log in; default value on create.</li> <li>• "false" - The user is not allowed to log in.</li> </ul>
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier. Defined values are:</p> <ul style="list-style-type: none"> <li>• "cloud-central" - User authentication comes from the NetApp Cloud Central service</li> <li>• "local" - User authentication comes from the local user/password store</li> <li>• "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".</li> </ul>
firstName	string	False	<p>JSON string containing a user-specified long form first name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>

Name	Type	Required	Description
lastName	string	False	<p>JSON string containing a user-specified long-form last name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 0</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks</li> </ul>
email	string	False	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	False	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> <li>• "true" - A welcome email will be sent; default value on create</li> <li>• "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".</li> </ul>
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the ISO-8601 Date Time Schema</li> </ul>
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul>

### Example request

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "firstName": "John",
  "lastName": "Dale",
  "email": "<a href='mailto:jdale@example.com'>jdale@example.com</a>"
}
```

### Response



Status: 204, Indicates if the user resource was updated.

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

# Definitions

## See Definitions

### postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 2</li><li>• Maximum length: 2</li></ul>
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li></ul>

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> </ul>

#### type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

#### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[ <a href="#">type_astra_label</a> ]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

## Delete a user

DELETE /accounts/{account\_id}/core/v1/users/{user\_id}

Removes the specified User API resource.

### Side Effects

- The following resources associated with the user are deleted: notificationMarks, tokens, and all roleBindings referring to the user.
- For a user with "authProvider" as "local", the linked credential with "keyType" as "passwordHash" will also be deleted.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>• example: <code>{{.Account}}</code></li> </ul>
user_id	string	path	True	ID of the user collection to list

### Response

Status: 204, Indicates if the user resource was deleted.

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

## Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters



### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

### See Definitions

#### invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## 저작권 정보

Copyright © 2024 NetApp, Inc. All Rights Reserved. 미국에서 인쇄된 본 문서의 어떠한 부분도 저작권 소유자의 사전 서면 승인 없이는 어떠한 형식이나 수단(복사, 녹음, 녹화 또는 전자 검색 시스템에 저장하는 것을 비롯한 그래픽, 전자적 또는 기계적 방법)으로도 복제될 수 없습니다.

NetApp이 저작권을 가진 자료에 있는 소프트웨어에는 아래의 라이선스와 고지사항이 적용됩니다.

본 소프트웨어는 NetApp에 의해 '있는 그대로' 제공되며 상품성 및 특정 목적에의 적합성에 대한 명시적 또는 묵시적 보증을 포함하여(이에 제한되지 않음) 어떠한 보증도 하지 않습니다. NetApp은 대체품 또는 대체 서비스의 조달, 사용 불능, 데이터 손실, 이익 손실, 영업 중단을 포함하여(이에 국한되지 않음), 이 소프트웨어의 사용으로 인해 발생하는 모든 직접 및 간접 손해, 우발적 손해, 특별 손해, 징벌적 손해, 결과적 손해의 발생에 대하여 그 발생 이유, 책임론, 계약 여부, 엄격한 책임, 불법 행위(과실 또는 그렇지 않은 경우)와 관계없이 어떠한 책임도 지지 않으며, 이와 같은 손실의 발생 가능성이 통지되었다 하더라도 마찬가지입니다.

NetApp은 본 문서에 설명된 제품을 언제든지 예고 없이 변경할 권리를 보유합니다. NetApp은 NetApp의 명시적인 서면 동의를 받은 경우를 제외하고 본 문서에 설명된 제품을 사용하여 발생하는 어떠한 문제에도 책임을 지지 않습니다. 본 제품의 사용 또는 구매의 경우 NetApp에서는 어떠한 특허권, 상표권 또는 기타 지적 재산권이 적용되는 라이선스도 제공하지 않습니다.

본 설명서에 설명된 제품은 하나 이상의 미국 특허, 해외 특허 또는 출원 중인 특허로 보호됩니다.

제한적 권리 표시: 정부에 의한 사용, 복제 또는 공개에는 DFARS 252.227-7013(2014년 2월) 및 FAR 52.227-19(2007년 12월)의 기술 데이터-비상업적 품목에 대한 권리(Rights in Technical Data -Noncommercial Items) 조항의 하위 조항 (b)(3)에 설명된 제한사항이 적용됩니다.

여기에 포함된 데이터는 상업용 제품 및/또는 상업용 서비스(FAR 2.101에 정의)에 해당하며 NetApp, Inc.의 독점 자산입니다. 본 계약에 따라 제공되는 모든 NetApp 기술 데이터 및 컴퓨터 소프트웨어는 본질적으로 상업용이며 개인 비용만으로 개발되었습니다. 미국 정부는 데이터가 제공된 미국 계약과 관련하여 해당 계약을 지원하는 데에만 데이터에 대한 전 세계적으로 비독점적이고 양도할 수 없으며 재사용이 불가능하며 취소 불가능한 라이선스를 제한적으로 가집니다. 여기에 제공된 경우를 제외하고 NetApp, Inc.의 사전 서면 승인 없이는 이 데이터를 사용, 공개, 재생산, 수정, 수행 또는 표시할 수 없습니다. 미국 국방부에 대한 정부 라이선스는 DFARS 조항 252.227-7015(b)(2014년 2월)에 명시된 권한으로 제한됩니다.

## 상표 정보

NETAPP, NETAPP 로고 및 <http://www.netapp.com/TM>에 나열된 마크는 NetApp, Inc.의 상표입니다. 기타 회사 및 제품 이름은 해당 소유자의 상표일 수 있습니다.