



Documentação do Astra Control Automation 23,04

Astra Automation

NetApp
October 23, 2024

Índice

Documentação do Astra Control Automation 23,04	1
Notas de lançamento	2
Sobre esta versão	2
Novidades da API REST do Astra Control	2
Problemas conhecidos	7
Visão geral dos recursos e benefícios	8
Comece agora	9
Antes de começar	9
Obtenha um token de API	9
Sua primeira chamada de API	10
Prepare-se para usar os fluxos de trabalho	11
Conceitos básicos do Kubernetes	13
Referência de API online	14
Implementação principal do REST	16
Serviços web REST	16
Recursos e coleções	17
Detalhes HTTP	18
Formato de URL	21
Recursos e endpoints	23
Resumo dos RECURSOS REST do Astra Control	23
Recursos e endpoints adicionais	26
Considerações de uso adicionais	27
Segurança RBAC	27
Trabalhe com coleções	27
Diagnóstico e suporte	28
Revogar um token de API	28
Workflows de infraestrutura	30
Antes de começar	30
Identidade e acesso	30
Configuração LDAP	35
Clusters	54
Nuvens	61
Balões	61
Armazenamento	62
Fluxos de trabalho de gerenciamento	69
Antes de começar	69
Controlo de aplicações	70
Proteção da aplicação	74
Clonar e restaurar um aplicativo	82
Namespaces	87
Suporte	89
Usando Python	92
O NetApp já está disponível	92

Python nativo	93
Referência da API	99
Overview	99
ASUP	99
Account	133
App	185
AppMirror	439
Application Asset	609
Application Backup	704
Application Snapshot	769
Bucket	802
Certificate	849
Cloud	898
Cluster	940
Cluster node	1078
Credential	1144
Entitlement	1190
Event	1208
Execution Hook	1242
Execution Hook Override	1351
Feature	1387
Group	1402
Hook source	1469
Kubernetes API Resource	1509
LDAP Group	1523
LDAP User	1537
License	1551
Managed cluster	1603
Metrics	1682
Namespace	1684
Notification	1772
Package	1805
Role binding	1866
Schedule	2090
Setting	2140
Storage backend	2174
Storage class	2235
Subscription	2292
Task	2344
Token	2370
Unread Notification	2438
Upgrade	2481
User	2513
Volume	2641
Recursos adicionais	2730

Astra	2730
Recursos de nuvem da NetApp	2730
Conceitos DE REST e nuvem	2730
Versões anteriores da documentação do Astra Control Automation	2732
Avisos legais	2733
Direitos de autor	2733
Marcas comerciais	2733
Patentes	2733
Política de privacidade	2733
Licença de API Astra Control	2733

Documentação do Astra Control Automation 23,04

Notas de lançamento

Sobre esta versão

A documentação neste local descreve a API REST do Astra Control e as tecnologias de automação relacionadas incluídas nos dois modelos de implantação do Astra Control, conforme descrito abaixo.



A cada versão do Astra Control é atribuído um número de versão do formulário **YY.MM**. Este valor identifica a versão com base no ano (*YY*) e no mês (*MM*) que ficou disponível. Por exemplo, o Astra Control Center 23,04 foi lançado em abril de 2023.

Cadência de libertação

Em geral, as atualizações do Astra Control Service e do Astra Control Center ocorrem ao mesmo tempo. No entanto, o Astra Control Service tem uma cadência de lançamento acelerada que pode resultar em uma ou mais atualizações incrementais além da versão mais recente do Astra Control Center.

Como este site documenta a API REST para ambos os modelos de implantação, talvez haja alguns recursos disponíveis apenas com a versão mais recente do Astra Control Service. Quaisquer diferenças entre os dois modelos de implantação são observadas conforme necessário.

Implantações do Astra Control

A documentação neste local se aplica aos seguintes lançamentos do Astra Control:

- Astra Control Center 23,04
- Astra Control Service 23,06

Mais informações

Consulte as páginas e sites a seguir para obter mais informações sobre os lançamentos atuais e anteriores do Astra Control.

- ["Novidades da API REST do Astra Control"](#)
- ["Recursos REST e endpoints"](#)
- ["Documentação do Astra Control Center 23,04"](#)
- ["Versões anteriores da documentação do Astra Automation"](#)

Ajude-nos a melhorar a documentação

Siga-nos no Twitter para receber notificações sobre a documentação do NetApp. Você também pode fornecer feedback tornando-se um ["Colaborador do GitHub"](#) ou enviando um e-mail para NetApp.com_.

Novidades da API REST do Astra Control

O NetApp atualiza regularmente a API REST do Astra Control para oferecer novos recursos, melhorias e correções de bugs.

27 de junho de 2023 (23,06)

Esta versão inclui atualizações seletivas para a API REST.

Azure Marketplace

As assinaturas do Azure Marketplace agora são cobradas por hora em vez de por minuto. Consulte também ["Configure a faturação"](#).

Otimização Restic

Você pode habilitar a otimização de desempenho para backups usando o `useResticParallel` sinalizador no novo `astra.datamover` recurso de API de configurações. Quando definido como `true`, o número `backendConnections` de utilizações de repetição aumenta ao efetuar cópias de segurança de volumes grandes para um contentor Azure. Para volumes de 1TB a 4TB, são utilizadas 128 ligações. Para volumes maiores que 4TB, 512 conexões de back-end são usadas.

30 de maio de 2023 (23,05)

Esta versão inclui atualizações seletivas para a API REST.

Operações de restauração seletiva

Você pode selecionar a classe de storage de destino durante operações de restauração ou clone.

Habilite pools de ANF dinâmicos para clusters autogerenciados

Ao fazer backup de uma aplicação gerenciada em um cluster privado no local que tenha um back-end de storage do ANF, agora você pode ativar o recurso Dynamic ANF Pools com uma ID de assinatura. Consulte ["Habilite pools de ANF dinâmicos"](#) para obter mais informações.

25 de abril de 2023 (23,04)

Esta versão inclui atualizações seletivas para a API REST.

Operações de restauração seletiva

Você pode incluir ou excluir seletivamente recursos de aplicativos durante as operações de restauração. Isso é feito usando uma regra de filtro baseada em um namespace específico, nome, rótulo ou `GroupVersionKind` valor.

Suporte para aplicativos somente de dados

O suporte para gerenciamento de aplicativos foi estendido para aplicativos somente de dados.

17 de janeiro de 2023 (23,01)

Esta versão inclui uma pequena atualização para a API REST.

Funcionalidade aprimorada de ganchos de execução com filtros

Ao usar ganchos de execução, agora você pode adicionar filtros para controlar quais contentores um gancho irá corresponder. Se você criar vários filtros para um único gancho de execução, eles serão combinados com

um operador LÓGICO E. Você pode definir até 10 filtros ativos por gancho de execução.

22 de novembro de 2022 (22,11)

Esta versão inclui uma expansão e atualização da API REST, bem como namespace aprimorado e suporte a LDAP.

Recursos novos e aprimorados do Astra

Quatro novos tipos de recursos foram adicionados: **ApiResource**, **IdapGroup**, **IdapUser** e **task**. Além disso, vários recursos e endpoints existentes foram aprimorados.

Suporte de monitoramento para tarefas de longa duração

Os novos endpoints de tarefa fornecem acesso a recursos de tarefas gerenciadas e podem ser usados para exibir o status de tarefas internas de longa execução.

Cenários aprimorados de uso de namespace

Foi adicionado suporte a aplicativos que abrangem vários namespaces, bem como recursos de cluster associados a recursos qualificados para namespace.

Subscrições de nuvem expandidas

Várias assinaturas de conta agora podem ser adicionadas para cada um dos provedores de nuvem.

Fluxos de trabalho adicionais

Foram adicionados fluxos de trabalho adicionais que ilustram a API REST do Astra Control. "[Workflows de infraestrutura](#)" Consulte e "[Fluxos de trabalho de gerenciamento](#)" para obter mais informações.

Informações relacionadas

- "[Astra Control Center: Novidades](#)"

10 de agosto de 2022 (22,08)

Esta versão inclui uma expansão e atualização da API REST, bem como recursos administrativos e de segurança aprimorados.

Recursos novos e aprimorados do Astra

Três novos tipos de recursos foram adicionados: **Certificado**, **Grupo** e **AppMirror**. Além disso, as versões de vários recursos existentes foram atualizadas.

Autenticação LDAP

Opcionalmente, é possível configurar o Astra Control Center para integração com um servidor LDAP para autenticar usuários selecionados do Astra. Consulte "[Configuração LDAP](#)" para obter mais informações.

Gancho de execução melhorado

O suporte para ganchos de execução foi adicionado com a versão Astra Control 21,12. Além dos ganchos de execução pré-snapshot e pós-snapshot existentes, agora você pode configurar os seguintes tipos de ganchos de execução com a versão 22,08:

- Pré-backup
- Pós-backup
- Pós-restauração

O Astra Control agora também permite que o mesmo script seja usado para vários ganchos de execução.

Replicação de aplicativos usando o SnapMirror

Agora é possível replicar alterações de dados e aplicações entre clusters usando a tecnologia NetApp SnapMirror. Esse aprimoramento pode ser usado para melhorar a continuidade dos negócios e os recursos de recuperação.

Informações relacionadas

- ["Astra Control Center 22,08: Novidades"](#)

26 de abril de 2022 (22,04)

Esta versão inclui uma expansão e atualização da API REST, bem como recursos administrativos e de segurança aprimorados.

Recursos novos e aprimorados do Astra

Dois novos tipos de recursos foram adicionados: **Pacote** e **Upgrade**. Além disso, as versões de vários recursos existentes foram atualizadas.

RBAC aprimorado com granularidade de namespace

Ao vincular uma função a um usuário associado, você pode limitar os namespaces aos quais o usuário tem acesso. Consulte a referência **Role Binding API** e "[Segurança RBAC](#)" para obter mais informações.

Remoção do balde

Você pode remover um balde quando ele não for mais necessário ou não estiver funcionando corretamente.

Suporte para Cloud Volumes ONTAP

Agora, o Cloud Volumes ONTAP é compatível como um back-end de storage.

Melhorias adicionais do produto

Há vários aprimoramentos adicionais nas duas implementações de produtos Astra Control, incluindo:

- Entrada genérica para Astra Control Center
- Cluster privado em AKS
- Suporte para Kubernetes 1,22
- Suporte ao portfólio VMware Tanzu

Consulte a página **Novidades** nos sites de documentação do Astra Control Center e do Astra Control Service.

Informações relacionadas

- ["Astra Control Center 22,04: Novidades"](#)

14 de dezembro de 2021 (21,12)

Esta versão inclui uma expansão da API REST, juntamente com uma alteração na estrutura de documentação para dar suporte à evolução do Astra Control com as futuras atualizações de versões.

Documentação separada do Astra Automation para cada versão do Astra Control

Todas as versões do Astra Control incluem uma API REST distinta que foi aprimorada e adaptada aos recursos da versão específica. A documentação para cada versão da API REST do Astra Control agora está disponível em seu próprio site dedicado, juntamente com o repositório de conteúdo associado do GitHub. O site principal do doc "[Automação do Astra Control](#)" sempre contém a documentação para a versão mais atual. "[Versões anteriores da documentação do Astra Control Automation](#)" Consulte para obter informações sobre versões anteriores.

Expansão dos tipos de recursos REST

O número de tipos de recursos REST continuou a se expandir com ênfase em ganchos de execução e backends de armazenamento. Os novos recursos incluem: Conta, gancho de execução, fonte de gancho, substituição de gancho de execução, nó de cluster, back-end de storage gerenciado, namespace, dispositivo de storage e nó de storage. Consulte "[Recursos](#)" para obter mais informações.

O NetApp já está disponível

O NetApp é um pacote de código aberto que facilita o desenvolvimento de código de automação para seu ambiente Astra Control. No centro está o SDK Astra, que inclui um conjunto de classes para abstrair a complexidade das chamadas de API REST. Há também um script de kit de ferramentas para executar tarefas administrativas específicas, envolvendo e abstraindo as classes Python. Consulte "[O NetApp já está disponível](#)" para obter mais informações.

Informações relacionadas

- "[Astra Control Center 21,12: Novidades](#)"

5 de agosto de 2021 (21,08)

Esta versão inclui a introdução de um novo modelo de implantação Astra e uma grande expansão da API REST.

Modelo de implantação do Astra Control Center

Além da oferta existente do Astra Control Service fornecida como serviço de nuvem pública, esta versão também inclui o modelo de implantação no local do Astra Control Center. Você pode instalar o Astra Control Center no seu local para gerenciar seu ambiente Kubernetes local. Os dois modelos de implantação do Astra Control compartilham a mesma API REST, com pequenas diferenças observadas conforme necessário na documentação.

Expansão dos tipos de recursos REST

O número de recursos acessíveis por meio da API REST Astra Control foi muito ampliado, com muitos dos novos recursos fornecendo a base para a oferta do Astra Control Center no local. Os novos recursos incluem: ASUP, direito, recurso, licença, configuração, assinatura, bucket, nuvem, cluster, cluster gerenciado, back-end de storage e classe de storage. Consulte "[Recursos](#)" para obter mais informações.

Pontos de extremidade adicionais compatíveis com a implantação do Astra

Além dos recursos REST expandidos, há vários outros pontos de extremidade de API novos disponíveis para dar suporte à implantação do Astra Control.

Suporte ao OpenAPI

Os endpoints OpenAPI fornecem acesso ao documento JSON OpenAPI atual e a outros recursos relacionados.

Suporte ao OpenMetrics

Os endpoints OpenMetrics fornecem acesso às métricas da conta por meio do recurso OpenMetrics.

Informações relacionadas

- ["Astra Control Center 21,08: Novidades"](#)

15 de abril de 2021 (21,04)

Esta versão inclui os seguintes novos recursos e aprimoramentos.

Introdução da API REST

A API REST do Astra Control está disponível para uso com a oferta do Astra Control Service. Ele foi criado com base em TECNOLOGIAS REST e nas melhores práticas atuais. A API fornece uma base para a automação das implantações do Astra e inclui os recursos e benefícios a seguir.

Recursos

Existem quatorze tipos de recursos REST disponíveis.

Acesso ao token de API

O acesso à API REST é fornecido por meio de um token de acesso à API que você pode gerar na interface de usuário da Web Astra. O token de API fornece acesso seguro à API.

Suporte para coleções

Há um conjunto rico de parâmetros de consulta que podem ser usados para acessar as coleções de recursos. Algumas das operações suportadas incluem filtragem, classificação e paginação.

Problemas conhecidos

Você deve analisar todos os problemas conhecidos da versão atual relacionada à API REST do Astra Control. Os problemas conhecidos identificam problemas que podem impedi-lo de usar o produto com sucesso.



Não há novos problemas conhecidos com a versão 23,06 da API REST do Astra Control. Essa versão da API é usada com o Astra Control Center 23,04 e o Astra Control Service 23,06. Quaisquer problemas descritos abaixo foram descobertos em versões anteriores e ainda são aplicáveis com a versão atual.

Veja uma das páginas a seguir com base no modelo de implantação.

- ["Problemas conhecidos do Astra Control Service"](#)
- ["Problemas conhecidos do Astra Control Center"](#)

Visão geral dos recursos e benefícios

O Astra Control Center e o Astra Control Service fornecem uma API REST comum que você pode acessar diretamente por meio de uma linguagem de programação ou utilitário, como o Curl. Os principais destaques e benefícios da API são apresentados abaixo.



Para acessar a API REST, você precisa primeiro fazer login na interface de usuário da Web Astra e gerar um token de API. Você deve incluir o token em cada solicitação de API.

Desenvolvido com base na TECNOLOGIA REST

A API Astra Control foi criada usando a TECNOLOGIA REST e as práticas recomendadas atuais. A tecnologia principal inclui HTTP, JSON e RBAC.

Suporte para os dois modelos de implantação do Astra Control

O Astra Control Service é usado no ambiente de nuvem pública enquanto o Astra Control Center é para suas implantações locais. Há uma API REST compatível com ambos os modelos de implantação.

Limpar o mapeamento entre os recursos de endpoint REST e o modelo de objeto

Os pontos de extremidade REST externos usados para acessar o mapa de recursos a um modelo de objeto consistente mantido internamente pelo serviço Astra. O modelo de objeto é projetado usando modelagem de relacionamento de entidade (ER) que ajuda a definir claramente as ações e respostas da API.

Conjunto rico de parâmetros de consulta

A API REST fornece um conjunto rico de parâmetros de consulta que você pode usar para acessar as coleções de recursos. Algumas das operações suportadas incluem filtragem, classificação e paginação.

Alinhamento com a IU da Web Astra Control

O design da interface de usuário da Web Astra está alinhado com a API REST e, portanto, há consistência entre os dois caminhos de acesso e a experiência do usuário.

Depuração robusta e dados de determinação de problemas

A API REST do Astra Control fornece um recurso robusto de depuração e determinação de problemas, incluindo eventos do sistema e notificações do usuário.

Processos de fluxo de trabalho

Um conjunto de fluxos de trabalho é fornecido para ajudar no desenvolvimento de seu código de automação. Os fluxos de trabalho são organizados em duas categorias principais: Infraestrutura e gerenciamento.

Base para tecnologias avançadas de automação

Além de acessar a API REST diretamente, você pode usar outras tecnologias de automação baseadas na API REST.

Parte da documentação da família Astra

A documentação do Astra Control Automation é parte da documentação maior da família Astra. Consulte "[Documentação do Astra](#)" para obter mais informações.

Comece agora

Antes de começar

Você pode se preparar rapidamente para começar a usar a API REST do Astra Control revisando as etapas abaixo.

Ter credenciais de conta Astra

Você precisará de credenciais Astra para fazer login na interface de usuário da Web Astra e gerar um token de API. Com o Astra Control Center, você gerencia essas credenciais localmente. Com o Astra Control Service, as credenciais da conta são acessadas pelo serviço **Auth0**.

Familiarize-se com os conceitos básicos do Kubernetes

Você deve estar familiarizado com vários conceitos básicos do Kubernetes. Consulte "[Conceitos básicos do Kubernetes](#)" para obter mais informações.

Rever conceitos REST e implementação

Certifique-se de consultar "[Implementação principal do REST](#)" informações sobre conceitos REST e detalhes sobre como a API REST do Astra Control foi projetada.

Obtenha mais informações

Você deve estar ciente dos recursos de informações adicionais, conforme sugerido no "[Recursos adicionais](#)".

Obtenha um token de API

Você precisa obter um token da API Astra para usar a API REST do Astra Control.

Introdução

Um token de API identifica o chamador para o Astra e deve ser incluído em todas as chamadas da API REST.

- Você precisa gerar um token de API usando a interface de usuário da Web Astra.
- O procedimento para gerar um token é o mesmo para ambos os modelos de implantação do Astra. Somente o URL usado para acessar o Astra é diferente.
- A identidade do usuário carregada com o token e as permissões associadas são determinadas pelo usuário que criou o token.
- O token deve ser incluído no `Authorization` cabeçalho de solicitação HTTP.
- Um token nunca expira depois que ele é criado.
- Você pode revogar um token na interface de usuário da Web Astra.

Informações relacionadas

- "[Revogar um token de API](#)"

Crie um token da API Astra

As etapas a seguir descrevem como criar um token da API Astra.

Antes de começar

Você precisa de credenciais para uma conta Astra.

Sobre esta tarefa

Essa tarefa gera um token de API na interface Web do Astra. Você também deve recuperar o ID da conta que também é necessário ao fazer chamadas de API.

Passos

1. Faça login no Astra usando suas credenciais de conta da seguinte maneira:
 - Astra Control Service: "<https://astra.netapp.io>"
 - Astra Control Center: Use o URL do seu ambiente local, conforme estabelecido durante a instalação
2. Clique no ícone de figura no canto superior direito da página e selecione **Acesso à API**.
3. Clique em **Generate API token** na página e, em seguida, clique em **Generate API token** na janela pop-up.
4. Clique no ícone para copiar a string de token para a área de transferência e salvá-la no editor.
5. Copie e salve o ID da conta que está disponível na mesma página.

Depois de terminar

Quando você acessa a API REST do Astra Control por meio de curl ou uma linguagem de programação, você deve incluir o token portador da API no cabeçalho da solicitação HTTP `Authorization`.

Sua primeira chamada de API

Você pode emitir um comando curl simples na CLI da estação de trabalho para começar a usar a API REST Astra Control e confirmar sua disponibilidade.

Antes de começar

O utilitário Curl deve estar disponível na estação de trabalho local. Você também deve ter um token de API e o identificador de conta associado. Consulte "[Obtenha um token de API](#)" para obter mais informações.

Curl exemplo

O seguinte comando Curl recupera uma lista de usuários Astra. Forneça o <ACCOUNT_ID> e o <API_TOKEN> apropriados, conforme indicado.

```
curl --location --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/users' --header
'Content-Type: application/json' --header 'Authorization: Bearer
<API_TOKEN>'
```

Exemplo de saída JSON

```
{
  "items": [
    [
      "David",
      "Anderson",
      "844ec6234-11e0-49ea-8434-a992a6270ec1"
    ],
    [
      "Jane",
      "Cohen",
      "2a3e227c-fda7-4145-a86c-ed9aa0183a6c"
    ]
  ],
  "metadata": {}
}
```

Prepare-se para usar os fluxos de trabalho

Você deve estar familiarizado com a organização e o formato dos workflows do Astra antes de usá-los em uma implantação ao vivo.

Introdução

Um *workflow* é uma sequência de uma ou mais etapas necessárias para realizar uma tarefa ou objetivo administrativo específico. Cada etapa em um fluxo de trabalho do Astra Control é uma das seguintes:

- Chamada de API REST (com detalhes como exemplos curl e JSON)
- Invocação de outro fluxo de trabalho Astra
- Tarefa relacionada diversos (como tomar uma decisão de projeto necessária)

Os fluxos de trabalho incluem as etapas principais e os parâmetros necessários para realizar cada tarefa. Eles fornecem um ponto de partida para personalizar seu ambiente de automação.

Parâmetros de entrada comuns

Os parâmetros de entrada descritos abaixo são comuns a todas as amostras curl usadas para ilustrar uma chamada de API REST.



Como esses parâmetros de entrada são universalmente necessários, eles não são descritos mais detalhadamente nos fluxos de trabalho individuais. Se forem utilizados parâmetros de entrada adicionais para um exemplo de curl específico, estes são descritos na seção **parâmetros de entrada adicionais**.

Parâmetros do caminho

O caminho do endpoint usado com cada chamada de API REST inclui os seguintes parâmetros. Consulte também ["Formato de URL"](#) para obter mais informações.

ID da conta

Esse é o valor UUIDv4 que identifica a conta Astra onde a operação da API é executada. ["Obtenha um token de API"](#) Consulte para obter mais informações sobre como localizar o ID da sua conta.

Cabeçalhos de solicitação

Existem vários cabeçalhos de solicitação que você pode precisar incluir dependendo da chamada da API REST.

Autorização

Todas as chamadas de API nos fluxos de trabalho precisam de um token de API para identificar o usuário. Você deve incluir o token no `Authorization` cabeçalho da solicitação. Consulte ["Obtenha um token de API"](#) para obter mais informações sobre como gerar um token de API.

Tipo de conteúdo

Com as solicitações HTTP POST e PUT em que JSON é incluído no corpo da solicitação, você deve declarar o tipo de Mídia com base no recurso Astra. Por exemplo, você pode incluir o cabeçalho `Content-Type: application/astra-appSnap+json` ao criar um snapshot para um aplicativo gerenciado.

Aceitar

Você pode declarar o tipo de Mídia específico do conteúdo esperado na resposta com base no recurso Astra. Por exemplo, você pode incluir o cabeçalho `Accept: application/astra-appBackup+json` ao listar os backups de um aplicativo gerenciado. No entanto, para simplificar, as amostras curl nos fluxos de trabalho aceitam todos os tipos de Mídia.

Apresentação de tokens e identificadores

O token API e outros valores de ID usados com os exemplos curl são opacos sem significado discernível. E assim, para melhorar a legibilidade das amostras, os valores reais de token e ID não são usados. Em vez disso, palavras-chave reservadas menores são usadas que tem vários benefícios:

- As amostras curl e JSON são mais claras e fáceis de entender.
- Como todas as palavras-chave usam o mesmo formato com colchetes e letras maiúsculas, você pode identificar rapidamente o local e o conteúdo a ser inserido ou extraído.
- Nenhum valor é perdido porque os parâmetros originais não podem ser copiados e usados com uma implantação real.

Aqui estão algumas das palavras-chave reservadas comuns usadas nos exemplos curl. Esta lista não é exaustiva e palavras-chave adicionais são usadas conforme necessário. Seu significado deve ser óbvio com base no contexto.

Palavra-chave	Tipo	Descrição
<ACCOUNT_ID>	Caminho	O valor UUIDv4 identificando a conta onde a operação da API é executada.
<API_TOKEN>	Colhedor	O token do portador identificando e autorizando o chamador.

Palavra-chave	Tipo	Descrição
<APP_ID>	Caminho	O valor UUIDv4 identificando o aplicativo para a chamada API.

Categorias de fluxo de trabalho

Há duas grandes categorias de workflows do Astra disponíveis com base no seu modelo de implantação. Se você estiver usando o Astra Control Center, comece com os workflows de infraestrutura e prossiga para os workflows de gerenciamento. Ao usar o Astra Control Service, você costuma ir diretamente aos workflows de gerenciamento.



As amostras curl nos fluxos de trabalho usam o URL do Astra Control Service. Você precisa alterar o URL ao usar o Astra Control Center no local, conforme apropriado para seu ambiente.

Workflows de infraestrutura

Esses workflows lidam com a infraestrutura Astra, incluindo credenciais, buckets e back-ends de storage. Elas são necessárias com o Astra Control Center, mas na maioria dos casos também podem ser usadas com o Astra Control Service. Os fluxos de trabalho concentram-se nas tarefas necessárias para estabelecer e manter um cluster gerenciado do Astra.

Fluxos de trabalho de gerenciamento

Você pode usar esses fluxos de trabalho depois de ter um cluster gerenciado. Os workflows se concentram em operações de suporte e proteção de aplicativos, como backup, restauração e clonagem de um aplicativo.

Conceitos básicos do Kubernetes

Há vários conceitos do Kubernetes que são relevantes ao usar a API REST do Astra.

Objetos

Os objetos mantidos em um ambiente Kubernetes são entidades persistentes que representam a configuração do cluster. Esses objetos descrevem coletivamente o estado do sistema, incluindo a carga de trabalho do cluster.

Namespaces

Namespaces fornecem uma técnica para isolar recursos em um único cluster. Essa estrutura organizacional é útil ao dividir os tipos de trabalho, usuários e recursos. Objetos com um escopo *namespace* precisam ser exclusivos dentro do namespace, enquanto aqueles com um escopo *cluster* devem ser exclusivos em todo o cluster.

Etiquetas

Os rótulos podem ser associados aos objetos Kubernetes. Eles descrevem atributos usando pares de chave-valor e podem impor uma organização arbitrária no cluster que pode ser útil para uma organização, mas estão fora da operação principal do Kubernetes.

Referência de API online

Acesse a documentação de referência da API Astra

Você pode acessar os detalhes das chamadas da API REST do Astra Control, incluindo os métodos HTTP, parâmetros de entrada e respostas. Essa referência completa é útil ao desenvolver aplicativos de automação usando a API REST.

Antes de começar

Você precisa de credenciais para fazer login na interface de usuário da Web Astra para sua implantação. O procedimento para acessar a documentação de referência é o mesmo para o Astra Control Service e o Astra Control Center. Apenas o URL é diferente. Não é necessário um token de API para acessar e visualizar o documento de referência

Passos

1. Faça login no Astra usando suas credenciais de conta da seguinte maneira:
 - Astra Control Service: "<https://astra.netapp.io>"
 - Astra Control Center: Use o URL do seu ambiente local, conforme estabelecido durante a instalação
2. Clique no ícone de figura no canto superior direito da página e selecione **Acesso à API**.
3. Na parte superior da página, clique no URL exibido em **Documentação da API**.

Resultado

A página Swagger é iniciada em uma nova janela ou guia. Aviso o URL inclui o ID da conta para a conta com a qual você entrou.

O que se segue?

Você pode opcionalmente executar uma chamada de API a partir da página Swagger. Consulte "[Emitir uma chamada de API REST do Astra](#)" para obter mais informações.

Emitir uma chamada de API REST do Astra

Você pode emitir uma chamada da API REST do Astra Control na página de documentação de referência da API.

Antes de começar

Você precisa fazer login no Astra e acessar a página de referência da API. Consulte "[Acesse a documentação de referência da API Astra](#)" para obter mais informações. Você também precisa de um token para usar a API REST. "[Obtenha um token de API](#)" Consulte para obter detalhes sobre como gerar um token de API.

Passos

1. Na parte superior da página de referência da API, clique em **autorizar**.
2. Copie e cole o valor do token da API no campo na janela pop-up e clique em **autorizar** e, em seguida, clique em **Fechar**.
3. Role a página para baixo e abra a chamada de API desejada.
4. Clique com o botão direito em **Experimente**.
5. Role para baixo dentro da mesma chamada de API. Forneça os valores de parâmetros necessários e clique em **execute** para emitir a chamada.

Resultado

A chamada API é executada e o código de status HTTP é exibido.

Implementação principal do REST

Serviços web REST

Representational State Transfer (REST) é um estilo para a criação de aplicações web distribuídas. Quando aplicado ao design de uma API de serviços da Web, ele estabelece um conjunto de tecnologias e práticas recomendadas principais para expor recursos baseados em servidor e gerenciar seus estados. Embora O REST forneça uma base consistente para o desenvolvimento de aplicativos, os detalhes de cada API podem variar com base nas escolhas específicas de design. Você deve estar ciente das características da API REST do Astra Control antes de usá-la com uma implantação ativa.

Recursos e representação do Estado

Os recursos são os componentes básicos de um sistema baseado na Web. Ao criar um aplicativo REST de serviços da Web, as tarefas iniciais de design incluem:

- Identificação de recursos baseados em sistema ou servidor

Cada sistema usa e mantém recursos. Um recurso pode ser um arquivo, transação comercial, processo ou entidade administrativa. Uma das primeiras tarefas no projeto de um aplicativo baseado em serviços web REST é identificar os recursos.

- Definição de estados de recursos e operações de estado associadas

Os recursos estão sempre em um de um número finito de estados. Os estados, bem como as operações associadas usadas para afetar as mudanças de estado, devem ser claramente definidos.

Pontos de extremidade URI

Todos os recursos REST devem ser definidos e disponibilizados usando um esquema de endereçamento bem definido. Os endpoints onde os recursos estão localizados e identificados usam um URI (Uniform Resource Identifier). O URI fornece uma estrutura geral para criar um nome exclusivo para cada recurso na rede. O Uniform Resource Locator (URL) é um tipo de URI usado com serviços da Web para identificar e acessar recursos. Os recursos são normalmente expostos em uma estrutura hierárquica semelhante a um diretório de arquivos.

Mensagens HTTP

O Hypertext Transfer Protocol (HTTP) é o protocolo usado pelo cliente e servidor de serviços da Web para trocar mensagens de solicitação e resposta sobre os recursos. Como parte do projeto de um aplicativo de serviços da Web, os métodos HTTP são mapeados para os recursos e as ações de gerenciamento de estado correspondentes. HTTP está sem estado. Portanto, para associar um conjunto de solicitações e respostas relacionadas como parte de uma transação, informações adicionais devem ser incluídas nos cabeçalhos HTTP carregados com os fluxos de dados de solicitação e resposta.

Formatação JSON

Embora as informações possam ser estruturadas e transferidas entre um cliente e um servidor de serviços da Web de várias maneiras, a opção mais popular é JavaScript Object Notation (JSON). JSON é um padrão da indústria para representar estruturas de dados simples em texto simples e é usado para transferir informações de estado descrevendo os recursos. A API REST DO Astra Control usa JSON para formatar os dados transportados no corpo de cada solicitação e resposta HTTP.

Recursos e coleções

A API REST do Astra Control fornece acesso a instâncias de recursos e coleções de instâncias de recursos.



Conceitualmente um resource * REST é semelhante a um objeto * conforme definido com as linguagens e sistemas de programação orientada a objetos (OOP). Às vezes, esses termos são usados de forma intercambiável. Mas, em geral, "recurso" é preferível quando usado no contexto da API REST externa enquanto "objeto" é usado para os dados de instância com estado correspondente armazenados no servidor.

Atributos dos recursos do Astra

A API REST do Astra Control está em conformidade com os princípios de design RESTful. Cada instância de recurso Astra é criada com base em um tipo de recurso bem definido. Um conjunto de instâncias de recursos do mesmo tipo é chamado de **Collection**. As chamadas API atuam sobre recursos individuais ou coleções de recursos.

Tipos de recursos

Os tipos de recursos incluídos na API REST do Astra Control têm as seguintes características:

- Cada tipo de recurso é definido usando um esquema (normalmente em JSON)
- Cada esquema de recursos inclui o tipo de recurso e a versão
- Os tipos de recursos são globalmente únicos

Instâncias de recursos

As instâncias de recursos disponíveis pela API REST do Astra Control têm as seguintes características:

- As instâncias de recurso são criadas com base em um único tipo de recurso
- O tipo de recurso é indicado utilizando o valor tipo de material
- As instâncias são compostas por dados com estado que são mantidos pelo serviço Astra
- Cada instância é acessível através de uma URL única e de longa duração
- Nos casos em que uma instância de recurso pode ter mais de uma representação, diferentes tipos de Mídia podem ser usados para solicitar a representação desejada

Coleções de recursos

As coleções de recursos disponíveis pela API REST do Astra Control têm as seguintes características:

- O conjunto de instâncias de recursos de um único tipo de recurso é conhecido como uma coleção
- Coleções de recursos têm uma URL única e de longa duração

Identificadores de instância

Cada instância de recurso recebe um identificador quando é criada. Este identificador é um valor UUIDv4 de 128 bits. Os valores UUIDv4 atribuídos são globalmente únicos e imutáveis. Depois de emitir uma chamada de API que cria uma nova instância, um URL com o ID associado é retornado ao chamador em um `Location` cabeçalho da resposta HTTP. Você pode extrair o identificador e usá-lo em chamadas subsequentes quando se refere à instância de recurso.



O identificador de recurso é a chave primária usada para coleções.

Estrutura comum para recursos do Astra

Todos os recursos do Astra Control são definidos usando uma estrutura comum.

Dados comuns

Cada recurso Astra contém os valores-chave mostrados na tabela a seguir.

Chave	Descrição
tipo	Um tipo de recurso globalmente único que é conhecido como tipo de recurso .
versão	Um identificador de versão que é conhecido como a versão resource .
id	Um identificador global único que é conhecido como resource identifier .
metadados	Um objeto JSON contendo várias informações, incluindo rótulos de usuário e sistema.

Objeto de metadados

O objeto JSON de metadados incluído com cada recurso Astra contém os valores-chave mostrados na tabela a seguir.

Chave	Descrição
etiquetas	Matriz JSON de rótulos especificados pelo cliente associados ao recurso.
CriaçãoTimestamp	String JSON contendo um carimbo de data/hora indicando quando o recurso foi criado.
Alteração do Timestamp	String JSON contendo um carimbo de data/hora formatado ISO-8601 indicando quando o recurso foi alterado pela última vez.
CreatedBy	String JSON contendo o identificador UUIDv4 do ID do usuário que criou o recurso. Se o recurso foi criado por um componente interno do sistema e não houver UUID associado à entidade criadora, o UUID null é usado.

Estado do recurso

Recursos selecionados um `state` valor que é usado para orquestrar transições de ciclo de vida e controlar o acesso.

Detalhes HTTP

A API REST do Astra Control usa HTTP e parâmetros relacionados para agir nas instâncias e coleções de recursos. Detalhes da implementação HTTP são apresentados abaixo.

Transações de API e o modelo CRUD

A API REST do Astra Control implementa um modelo transacional com operações bem definidas e transições de estado.

Transação de API de solicitação e resposta

Cada chamada de API REST é executada como uma solicitação HTTP para o serviço Astra. Cada solicitação gera uma resposta associada de volta ao cliente. Esse par de solicitação-resposta pode ser considerado uma transação de API.

Suporte para o modelo operacional CRUD

Cada uma das instâncias e coleções de recursos disponíveis por meio da API REST do Astra Control é acessada com base no modelo **CRUD**. Existem quatro operações, cada uma delas mapeia para um único método HTTP. As operações incluem:

- Criar
- Leia
- Atualização
- Eliminar

Para alguns recursos do Astra, apenas um subconjunto dessas operações é suportado. Você deve revisar o ["Referência de API online"](#) para obter mais informações sobre uma chamada de API específica.

Métodos HTTP

Os métodos HTTP ou verbos suportados pela API são apresentados na tabela abaixo.

Método	CRUD	Descrição
OBTER	Leia	Recupera propriedades de objeto para uma instância ou coleção de recursos. Isso é considerado uma operação list quando usado com uma coleção.
POST	Criar	Cria uma nova instância de recurso com base nos parâmetros de entrada. O URL de longo prazo é retornado em um <code>Location</code> cabeçalho de resposta.
COLOQUE	Atualização	Atualiza uma instância de recurso inteira com o corpo de solicitação JSON fornecido. Os valores-chave que não são modificáveis pelo usuário são preservados.
ELIMINAR	Eliminar	Exclui uma instância de recurso existente.

Cabeçalhos de solicitação e resposta

A tabela a seguir resume os cabeçalhos HTTP usados com a API REST do Astra Control.



"RFC 7232" Consulte e "RFC 7233" para obter mais informações.

Colhedor	Tipo	Notas de utilização
Aceitar	Pedido	Se o valor for "/" ou não for fornecido, <code>application/json</code> será retornado no cabeçalho de resposta <code>Content-Type</code> . Se o valor estiver definido para o tipo de Mídia de recurso Astra, o mesmo tipo de Mídia será retornado no cabeçalho <code>Content-Type</code> .
Autorização	Pedido	Token de portador com a chave API para o usuário.
Tipo de conteúdo	Resposta	Devolvido com base no <code>Accept</code> cabeçalho da solicitação.
ETAG	Resposta	Incluído com um sucesso como definido com RFC 7232. O valor é uma representação hexadecimal do valor MD5 para todo o recurso JSON.
If-Match	Pedido	Um cabeçalho de solicitação de pré-condição implementado conforme descrito na seção 3,1 RFC 7232 e suporte para solicitações PUT .
Se-modificado-desde	Pedido	Um cabeçalho de solicitação de pré-condição implementado conforme descrito na seção 3,4 RFC 7232 e suporte para solicitações PUT .
If-Unmodified-since	Pedido	Um cabeçalho de solicitação de pré-condição implementado conforme descrito na seção 3,4 RFC 7232 e suporte para solicitações PUT .
Localização	Resposta	Contém a URL completa do recurso recém-criado.

Parâmetros de consulta

Os seguintes parâmetros de consulta estão disponíveis para uso com coleções de recursos. Consulte "[Trabalhe com coleções](#)" para obter mais informações.

Parâmetro de consulta	Descrição
incluir	Contém os campos que devem ser retornados ao ler uma coleção.
filtro	Indica os campos que devem corresponder para que um recurso seja retornado ao ler uma coleção.
Ordenar	Determina a ordem de classificação dos recursos retornados ao ler uma coleção.
limite	Limita o número máximo de recursos retornados ao ler uma coleção.
ignorar	Define o número de recursos para passar e pular ao ler uma coleção.
contar	Indica se o número total de recursos deve ser retornado no objeto metadados.

Códigos de status HTTP

Os códigos de status HTTP usados pela API REST do Astra Control são descritos abaixo.



A API REST do Astra Control também usa o padrão **Detalhes do problema para APIs HTTP**. Consulte "[Diagnóstico e suporte](#)" para obter mais informações.

Código	Significado	Descrição
200	OK	Indica sucesso para chamadas que não criam uma nova instância de recurso.
201	Criado	Um objeto é criado com sucesso e o cabeçalho de resposta de localização inclui o identificador exclusivo para o objeto.
204	Nenhum conteúdo	A solicitação foi bem-sucedida, embora nenhum conteúdo tenha sido retornado.
400	Pedido incorreto	A entrada de solicitação não é reconhecida ou é inadequada.
401	Não autorizado	O usuário não está autorizado e deve autorizar.
403	Proibido	O acesso é negado devido a um erro de autorização.
404	Não encontrado	O recurso referido na solicitação não existe.
409	Conflito	Uma tentativa de criar um objeto falhou porque o objeto já existe.
500	Erro interno	Ocorreu um erro interno geral no servidor.
503	Serviço indisponível	O serviço não está pronto para lidar com a solicitação por algum motivo.

Formato de URL

A estrutura geral da URL usada para acessar uma instância ou coleção de recursos através da API REST é composta por vários valores. Esta estrutura reflete o modelo de objeto subjacente e o design do sistema.

Conta como raiz

A raiz do caminho do recurso para cada endpoint REST é a conta Astra. E assim todos os caminhos no URL começam com `/account/{account_id}` onde `account_id` é o valor UUIDv4 exclusivo para a conta. Estrutura interna isso reflete um design em que todo o acesso a recursos é baseado em uma conta específica.

Categoria de recurso de endpoint

Os pontos de extremidade de recursos do Astra se enquadram em três categorias diferentes:

- (`/core`Núcleo`)
- Aplicativo gerenciado (`/k8s`)
- Topologia (`/topology`)

Consulte "[Recursos](#)" para obter mais informações.

Versão da categoria

Cada uma das três categorias de recursos tem uma versão global que controla a versão dos recursos acessados. Por convenção e definição, mover para uma nova versão principal de uma categoria de recurso (como, de `/v1` para `/v2`) introduzirá alterações de quebra na API.

Instância ou coleção de recursos

Uma combinação de tipos de recursos e identificadores pode ser usada no caminho, com base no acesso a uma instância ou coleção de recursos.

Exemplo

- Caminho do recurso

Com base na estrutura apresentada acima, um caminho típico para um endpoint é:
`/accounts/{account_id}/core/v1/users.`

- URL completo

O URL completo para o endpoint correspondente é:

`https://astra.netapp.io/accounts/{account_id}/core/v1/users.`

Recursos e endpoints

Você pode acessar os recursos fornecidos pela API REST do Astra Control para automatizar uma implantação Astra. Cada recurso está disponível por meio de um ou mais endpoints. Uma introdução aos RECURSOS REST que você pode usar como parte de uma implantação de automação é fornecida abaixo.



O formato do caminho e URL completo usados para acessar os recursos do Astra Control é baseado em vários valores. Consulte "[Formato de URL](#)" para obter mais informações. Consulte também "[Referência de API online](#)" para obter mais detalhes sobre como usar os recursos e pontos de extremidade do Astra.

Resumo dos RECURSOS REST do Astra Control

Os principais pontos de extremidade de recurso fornecidos na API REST do Astra Control são organizados em três categorias. Cada recurso pode ser acessado com o conjunto completo de operações CRUD (criar, ler, atualizar, excluir), exceto onde indicado.

A coluna **Release** indica a versão Astra quando o recurso foi introduzido pela primeira vez. Esse campo é em negrito para os recursos adicionados mais recentemente à API REST.

Recursos básicos

Os principais pontos de extremidade dos recursos fornecem os serviços básicos necessários para estabelecer e manter o ambiente de tempo de execução do Astra.

Recurso	Solte	Descrição
Conta	21,12	Os recursos da conta permitem gerenciar locatários isolados no ambiente de implantação com alocação a vários clientes Astra Control.
ASUP	21,08	Os recursos do ASUP representam os pacotes do AutoSupport encaminhados para o suporte do NetApp.
Certificado	22,08	Os recursos de certificado representam os certificados instalados usados para autenticação forte para conexões de saída.
Credencial	21,04	Os recursos de credenciais contêm informações relacionadas à segurança que podem ser usadas com usuários, clusters, buckets e back-ends de storage do Astra.
Direitos	21,08	Os recursos de direito representam os recursos e capacidades disponíveis para uma conta com base nas licenças e assinaturas ativas.
Evento	21,04	Os recursos do evento representam todos os eventos que ocorrem no sistema, incluindo o subconjunto classificado como notificações.
Gancho de execução	21,12	Os recursos do gancho de execução representam scripts personalizados que você pode executar antes ou depois que um snapshot de um aplicativo gerenciado é executado.
Recurso	21,08	Os recursos do recurso representam os recursos selecionados do Astra que você pode consultar para determinar se eles estão ativados ou desativados no sistema. O acesso é limitado a somente leitura.

Recurso	Solte	Descrição
Grupo	22,08	Os recursos do grupo representam os grupos Astra e os recursos associados. Apenas os grupos LDAP são suportados na versão atual.
Fonte do gancho	21,12	Os recursos de origem do gancho representam o código-fonte real usado com um gancho de execução. Separar o código-fonte do controle de execução tem vários benefícios, como permitir que os scripts sejam compartilhados.
Grupo LDAP	22,11	Pode listar os grupos no servidor LDAP configurado. O acesso aos grupos LDAP é somente leitura.
Utilizador LDAP	22,11	Pode listar os utilizadores no servidor LDAP configurado. O acesso aos utilizadores LDAP é apenas de leitura.
Licença	21,08	Os recursos de licença representam as licenças disponíveis para uma conta Astra.
Notificação	21,04	Os recursos de notificação representam eventos Astra que têm um destino de notificação. O acesso é fornecido por usuário.
Pacote	22,04	Os recursos do pacote fornecem o Registro e o acesso às definições do pacote. Pacotes de software consistem em vários componentes, incluindo arquivos, imagens e outros artefatos.
Vinculação de função	21,04	Os recursos de vinculação de função representam as relações entre pares específicos de usuários e contas. Além da ligação entre os dois, um conjunto de permissões é especificado para cada um através de uma função específica.
Definição	21,08	A configuração de recursos representa um conjunto de pares de valor-chave que descrevem um recurso para uma conta Astra específica.
Subscrição	21,08	Os recursos de subscrição representam as subscrições ativas de uma conta Astra.
Tarefa	22,11	Os recursos de tarefa fornecem acesso somente leitura à tarefa gerenciada e podem ser usados para exibir o status das tarefas internas de longa execução.
Token	21,04	Os recursos do token representam os tokens disponíveis para acessar programaticamente a API REST DO Astra Control.
Notificação não lida	21,04	Os recursos de notificação não lidos representam notificações atribuídas a um usuário específico, mas ainda não lidas.
Atualização	22,04	Os recursos de atualização fornecem acesso a componentes de software e a capacidade de iniciar atualizações.
Utilizador	21,04	Os recursos de usuário representam usuários do Astra capazes de acessar o sistema com base em sua função definida.

Recursos de aplicativos gerenciados

Os pontos de extremidade de recursos de aplicação gerenciados fornecem acesso às aplicações Kubernetes gerenciadas.

Recurso	Solte	Descrição
Ativo da aplicação	21,04	Os recursos de ativos da aplicação representam coleções internas de informações de estado necessárias para gerenciar as aplicações Astra.
Backup de aplicativos	21,04	Os recursos de backup de aplicativos representam backups dos aplicativos gerenciados.
Snapshot da aplicação	21,04	Os recursos de snapshot do aplicativo representam snapshots dos aplicativos gerenciados.
Substituição do gancho de execução	21,12	Os recursos de substituição do gancho de execução permitem desativar os ganchos de execução predefinidos do NetApp pré-carregados para aplicações específicas, conforme necessário.
Programação	21,04	Os recursos do cronograma representam operações de proteção de dados agendadas para os aplicativos gerenciados como parte de uma política de proteção de dados.

Recursos de topologia

Os pontos de extremidade dos recursos de topologia fornecem acesso aos aplicativos não gerenciados e aos recursos de storage.

Recurso	Solte	Descrição
Recurso de API	22,11	Os endpoints de recursos da API fornecem acesso somente leitura aos recursos do Kubernetes em um cluster gerenciado específico.
Aplicação	21,04	Os recursos da aplicação representam todas as aplicações Kubernetes, incluindo as não gerenciadas pelo Astra.
AppMirror	22,08	Os recursos do AppMirror representam os recursos do AppMirror a fornecer para o gerenciamento de relacionamentos de espelhamento de aplicativos.
Balde	21,08	Os recursos de bucket representam os buckets em nuvem do S3 usados para armazenar backups das aplicações gerenciadas pelo Astra.
Nuvem	21,08	Os recursos de nuvem representam nuvens às quais os clientes Astra podem se conectar para gerenciar clusters e aplicações.
Cluster	21,08	Os recursos do cluster representam os clusters do Kubernetes não gerenciados pelo Kubernetes.
Nó de cluster	21,12	Os recursos do nó do cluster fornecem resolução adicional, permitindo que você acesse os nós individuais em um cluster do Kubernetes.
Cluster gerenciado	21,08	Os recursos do cluster gerenciado representam os clusters do Kubernetes atualmente gerenciados pelo Kubernetes.
Namespace	21,12	Os recursos de namespace fornecem acesso aos namespaces usados em um cluster do Kubernetes.
Back-end de storage	21,08	Os recursos de back-end de storage representam fornecedores de serviços de storage que podem ser usados pelos clusters e aplicações gerenciados do Astra.
Classe de armazenamento	21,08	Os recursos da classe de armazenamento representam diferentes classes ou tipos de armazenamento descobertos e disponíveis para um cluster gerenciado específico.

Recurso	Solte	Descrição
Volume	21,04	Os recursos de volume representam os volumes de storage do Kubernetes associados às aplicações gerenciadas.

Recursos e endpoints adicionais

Há vários recursos e pontos de extremidade adicionais que você pode usar para dar suporte a uma implantação do Astra.



Esses recursos e pontos de extremidade não estão incluídos atualmente na documentação de referência da API REST do Astra Control.

OpenAPI

Os endpoints OpenAPI fornecem acesso ao documento JSON OpenAPI atual e a outros recursos relacionados.

OpenMetrics

Os endpoints OpenMetrics fornecem acesso às métricas da conta por meio do recurso OpenMetrics. O suporte está disponível com o modelo de implantação do Astra Control Center.

Considerações de uso adicionais

Segurança RBAC

A API REST do Astra dá suporte ao controle de acesso baseado em funções (RBAC) para conceder e restringir o acesso às funções do sistema.

Funções do Astra

Cada usuário do Astra é atribuído a uma única função que determina as ações que podem ser executadas. As funções são organizadas em uma hierarquia conforme descrito na tabela abaixo.

Função	Descrição
Proprietário	Tem todas as permissões da função Admin e também pode excluir contas Astra.
Administrador	Tem todas as permissões da função Membro e também pode convidar os usuários para participar de uma conta.
Membro	Pode gerenciar totalmente a aplicação Astra e os recursos de computação.
Visualizador	Restrito à visualização apenas de recursos.

RBAC aprimorado com granularidade de namespace



Esse recurso foi introduzido com a versão 22,04 da API REST do Astra.

Quando uma vinculação de função é estabelecida para um usuário específico, uma restrição pode ser aplicada para limitar os namespaces aos quais o usuário tem acesso. Existem várias maneiras de definir essa restrição como descrito na tabela abaixo. Consulte o parâmetro `roleConstraints` na API de vinculação de função para obter mais informações.

Namespaces	Descrição
Tudo	O usuário pode acessar todos os namespaces através do parâmetro curinga <code>***</code> . Este é o valor padrão para manter a compatibilidade com versões anteriores.
Nenhum	A lista de restrições é especificada embora esteja vazia. Isso indica que o usuário não pode acessar nenhum namespace.
Lista de namespace	O UUID de um namespace está incluído, o que restringe o usuário ao namespace único. Uma lista separada por vírgulas também pode ser usada para permitir o acesso a vários namespaces.
Etiqueta	Um rótulo é especificado e o acesso é permitido a todos os namespaces correspondentes.

Trabalhe com coleções

A API REST do Astra Control fornece várias maneiras diferentes de acessar coleções de recursos por meio dos parâmetros de consulta definidos.

Selecionar valores

Você pode especificar quais pares de chave-valor devem ser retornados para cada instância de recurso usando o `include` parâmetro. Todas as instâncias são retornadas no corpo de resposta.

Filtragem

A filtragem de recursos de coleta permite que um usuário da API especifique condições que determinam se um recurso é retornado no corpo da resposta. O `filter` parâmetro é usado para indicar a condição de filtragem.

Ordenação

A classificação de recursos de coleta permite que um usuário da API especifique a ordem em que os recursos são retornados no corpo de resposta. O `orderBy` parâmetro é usado para indicar a condição de filtragem.

Paginação

Você pode impor a paginação restringindo o número de instâncias de recursos retornadas em uma solicitação usando o `limit` parâmetro.

Contar

Se você incluir o parâmetro booleano `count` definido como `true`, o número de recursos na matriz retornada para uma determinada resposta será fornecido na seção metadados.

Diagnóstico e suporte

Há vários recursos de suporte disponíveis com a API REST do Astra Control que podem ser usados para diagnósticos e depuração.

Recursos de API

Há vários recursos do Astra expostos por meio de recursos de API que fornecem informações de diagnóstico e suporte.

Tipo	Descrição
Evento	Atividades do sistema registradas como parte do processamento do Astra.
Notificação	Um subconjunto dos Eventos que são considerados importantes o suficiente para ser apresentado ao usuário.
Notificação não lida	As notificações que ainda não foram lidas ou recuperadas pelo usuário.

Revogar um token de API

Você pode revogar um token de API na interface da Web Astra quando não for mais necessário.

Antes de começar

Você precisa de uma conta Astra. Você também deve identificar os tokens que deseja revogar.

Sobre esta tarefa

Depois que um token é revogado, ele é imediatamente e permanentemente inutilizável.

Passos

1. Faça login no Astra usando suas credenciais de conta.

Acesse o seguinte site do Astra Control Service: "<https://astra.netapp.io>"

2. Clique no ícone de figura no canto superior direito da página e selecione **Acesso à API**.

3. Selecione o token ou tokens que você deseja revogar.

4. Na caixa suspensa **ações**, clique em **revogar tokens**.

Workflows de infraestrutura

Antes de começar

Use esses workflows para criar e manter a infraestrutura usada com uma implantação do Astra Control Center. Em muitos casos, os workflows também podem ser usados com o Astra Control Service.



Esses fluxos de trabalho podem ser expandidos e aprimorados pelo NetApp a qualquer momento, portanto, você deve revisá-los periodicamente.

Preparação geral

Antes de usar qualquer um dos workflows do Astra, revise "[Prepare-se para usar os fluxos de trabalho](#)".

Categorias de fluxo de trabalho

Os fluxos de trabalho de infraestrutura são organizados em diferentes categorias para facilitar a localização do que você deseja.

Categoria	Descrição
Identidade e acesso	Esses fluxos de trabalho permitem gerenciar identidade e como o Astra é acessado. Os recursos incluem usuários, credenciais e tokens.
Configuração LDAP	Opcionalmente, você pode configurar o Astra Control Center para usar o LDAP para autenticar usuários selecionados.
Clusters	É possível adicionar clusters gerenciados do Kubernetes que permitem proteger e dar suporte às aplicações que eles contêm.
Nuvens	Esses workflows fornecem acesso às nuvens disponíveis por meio da API REST Astra Control.
Baldes	Você pode usar esses fluxos de trabalho para criar e gerenciar os buckets do S3 usados para armazenar backups.
Armazenamento	Esses fluxos de trabalho permitem adicionar e manter backends e volumes de armazenamento.

Identidade e acesso

Liste os usuários

Você pode listar os usuários que estão definidos para uma conta Astra específica.

1. Liste os usuários

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
OBTER	/accounts/_id/core/v1/users

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
incluir	Consulta	Não	Opcionalmente, selecione os valores que você deseja retornar na resposta.

Curl exemplo: Retorna todos os dados para todos os usuários

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/users' --header
'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Curl exemplo: Retorna o primeiro nome, sobrenome e id para todos os usuários

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/users?include=first
Name,lastName,id' --header 'Accept: */*' --header 'Authorization: Bearer
<API_TOKEN>'
```

Exemplo de saída JSON

```
{
  "items": [
    [
      "David",
      "Anderson",
      "844ec6234-11e0-49ea-8434-a992a6270ec1"
    ],
    [
      "Jane",
      "Cohen",
      "2a3e227c-fda7-4145-a86c-ed9aa0183a6c"
    ]
  ],
  "metadata": {}
}
```

Crie um usuário

Você pode criar um usuário com credenciais específicas e uma função predefinida. Você também pode, opcionalmente, restringir o acesso do usuário a namespaces específicos.

1. Selecione um nome de utilizador

Execute o fluxo de trabalho "[Listar usuários](#)" e selecione um nome disponível que não esteja atualmente em uso.

2. Crie o usuário

Execute a seguinte chamada de API REST para criar um usuário. Após a conclusão bem-sucedida da chamada, o novo usuário ainda não será utilizável.

Método HTTP	Caminho
POST	/accounts/_id/core/v1/users

Exemplo de entrada JSON

```
{
  "type" : "application/astra-user",
  "version" : "1.1",
  "firstName" : "John",
  "lastName" : "West",
  "email" : "jwest@example.com"
}
```

Curl exemplo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/users' --header
'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>' --data
@JSONinput
```

Exemplo de saída JSON

```

{
  "metadata": {
    "creationTimestamp": "2022-11-20T17:23:15Z",
    "modificationTimestamp": "2022-11-20T17:23:15Z",
    "createdBy": "a20e91f3-2c49-443b-b240-615d940ec5f3",
    "labels": []
  },
  "type": "application/astra-user",
  "version": "1.2",
  "id": "d07dac0a-a328-4840-a216-12de16bbd484",
  "authProvider": "local",
  "authID": "jwest@example.com",
  "firstName": "John",
  "lastName": "West",
  "companyName": "",
  "email": "jwest@example.com",
  "postalAddress": {
    "addressCountry": "",
    "addressLocality": "",
    "addressRegion": "",
    "streetAddress1": "",
    "streetAddress2": "",
    "postalCode": ""
  },
  "state": "active",
  "sendWelcomeEmail": "false",
  "isEnabled": "true",
  "isInviteAccepted": "true",
  "enableTimestamp": "2022-11-20T17:23:15Z",
  "lastActTimestamp": ""
}

```

3. Opcionalmente, selecione os namespaces permitidos

Execute o fluxo de trabalho ["Liste os namespaces"](#) e selecione os namespaces aos quais você deseja restringir o acesso.

4. Vincule o usuário a uma função

Execute a seguinte chamada de API REST para vincular o usuário a uma função. O exemplo abaixo não coloca restrições no acesso ao namespace. Consulte ["RBAC aprimorado com granularidade de namespace"](#) para obter mais informações.

Método HTTP	Caminho
POST	/Accounts/_id/core/v1/roleBindings

Exemplo de entrada JSON

```
{
  "type" : "application/astra-roleBinding",
  "version" : "1.1",
  "userID" : "d07dac0a-a328-4840-a216-12de16bbd484",
  "accountID" : "29e1f39f-2bf4-44ba-a191-5b84ef414c95",
  "role" : "viewer",
  "roleConstraints": [ "*" ]
}
```

Curl exemplo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/roleBindings'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>' --data
@JSONinput
```

5. Crie uma credencial

Execute a seguinte chamada de API REST para criar uma credencial e associá-la ao usuário. Este exemplo usa uma senha que é fornecida como um valor base64. A name propriedade deve conter o ID do usuário retornado na etapa anterior. A propriedade de entrada `change` também deve ser codificada em base64 e determina se o usuário deve alterar sua senha no primeiro login (`true` ou `false`).



Essa etapa só é necessária com implantações do Astra Control Center que usam autenticação local. Não é necessário com implantações Astra Control Center que usam LDAP ou com implantações Astra Control Service.

Método HTTP	Caminho
POST	/accounts/_id/core/v1/credentials

Exemplo de entrada JSON

```
{
  "type" : "application/astra-credential",
  "version" : "1.1",
  "name" : "d07dac0a-a328-4840-a216-12de16bbd484",
  "keyType" : "passwordHash",
  "keyStore" : {
    "cleartext" : "TmV0QXBwMTIz",
    "change" : "ZmFsc2U="
  },
  "valid" : "true"
}
```

Curl exemplo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/credentials'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>' --data
@JSONinput
```

Configuração LDAP

Prepare-se para a configuração LDAP

Opcionalmente, é possível integrar o Astra Control Center a um servidor LDAP (Lightweight Directory Access Protocol) para executar a autenticação para usuários selecionados do Astra. O LDAP é um protocolo padrão do setor para acessar informações de diretórios distribuídos e uma escolha popular para autenticação empresarial.

Informações relacionadas

- ["Mapa rodoviário da especificação técnica LDAP"](#)
- ["LDAP versão 3"](#)

Visão geral do processo de implementação

Em um alto nível, há várias etapas que você precisa executar para configurar um servidor LDAP para fornecer autenticação para usuários Astra.



Enquanto as etapas apresentadas abaixo estão em uma sequência, em alguns casos você pode executá-las em uma ordem diferente. Por exemplo, você pode definir os usuários e grupos Astra antes de configurar o servidor LDAP.

1. Revise ["Requisitos e limitações"](#) para entender as opções, os requisitos e as limitações.
2. Selecione um servidor LDAP e as opções de configuração desejadas (incluindo segurança).

3. Execute o fluxo de trabalho ["Configure o Astra para usar um servidor LDAP"](#) para integrar o Astra ao servidor LDAP.
4. Reveja os utilizadores e grupos no servidor LDAP para se certificar de que estão definidos corretamente.
5. Execute o fluxo de trabalho apropriado em ["Adicionar entradas LDAP ao Astra"](#) para identificar os usuários a serem autenticados usando LDAP.

Requisitos e limitações

Antes de configurar o Astra para usar LDAP para autenticação, você deve consultar os fundamentos de configuração do Astra apresentados abaixo, incluindo limitações e opções de configuração.

Compatível apenas com Astra Control Center

A plataforma Astra Control oferece dois modelos de implantação. A autenticação LDAP só é compatível com implantações do Astra Control Center.

Configuração usando API REST ou interface de usuário da Web

A versão atual do Astra Control Center é compatível com a configuração de autenticação LDAP usando a API REST Astra Control e a interface de usuário web Astra.

Servidor LDAP necessário

É necessário ter um servidor LDAP para aceitar e processar as solicitações de autenticação Astra. O ativo Directory da Microsoft é compatível com a versão atual do Astra Control Center.

Ligação segura ao servidor LDAP

Ao configurar o servidor LDAP no Astra, você pode definir opcionalmente uma conexão segura. Neste caso, é necessário um certificado para o protocolo LDAPS.

Configurar usuários ou grupos

Você precisa selecionar os usuários a serem autenticados usando LDAP. Você pode fazer isso identificando os usuários individuais ou um grupo de usuários. As contas devem ser definidas no servidor LDAP. Eles também precisam ser identificados no Astra (tipo LDAP), o que permite que as solicitações de autenticação sejam encaminhadas para LDAP.

Restrição de função ao vincular um usuário ou grupo

Com a versão atual do Astra Control Center, o único valor suportado para `roleConstraint` é `""`. Isso indica que o usuário não está restrito a um conjunto limitado de namespaces e pode acessar todos eles. Consulte ["Adicionar entradas LDAP ao Astra"](#) para obter mais informações.

Credenciais LDAP

As credenciais usadas pelo LDAP incluem o nome de usuário (endereço de e-mail) e a senha associada.

Endereços de e-mail exclusivos

Todos os endereços de e-mail atuando como nomes de usuário em uma implantação do Astra Control Center devem ser exclusivos. Não é possível adicionar um usuário LDAP com um endereço de e-mail que já esteja definido para Astra. Se houver um e-mail duplicado, você precisará primeiro excluí-lo do Astra. Consulte ["Remover usuários"](#) o site de documentação do Astra Control Center para obter mais informações.

Opcionalmente, defina primeiro os usuários e grupos LDAP

Você pode adicionar os usuários e grupos LDAP ao Astra Control Center mesmo que eles ainda não existam no LDAP ou se o servidor LDAP não estiver configurado. Isto permite pré-configurar os utilizadores e grupos antes de configurar o servidor LDAP.

Um usuário definido em vários grupos LDAP

Se um usuário LDAP pertencer a vários grupos LDAP e os grupos tiverem sido atribuídos diferentes funções no Astra, a função efetiva do usuário ao autenticar será a mais privilegiada. Por exemplo, se um usuário for atribuído a `viewer` função com `group1`, mas tiver a `member` função em `group2`, a função do usuário será `member`. Isso é baseado na hierarquia usada pelo Astra (mais alto a mais baixo):

- Proprietário
- Administrador
- Membro
- Visualizador

Sincronização periódica de contas

O Astra sincroniza os usuários e grupos de TI com o servidor LDAP aproximadamente a cada 60 segundo. Portanto, se um usuário ou grupo for adicionado ou removido do LDAP, pode levar até um minuto antes de estar disponível no Astra.

Desativar e repor a configuração LDAP

Antes de tentar repor a configuração LDAP, tem de desativar primeiro a autenticação LDAP. Além disso, para alterar o servidor LDAP (`connectionHost`), é necessário executar ambas as operações. Consulte "[Desativar e repor LDAP](#)" para obter mais informações.

Parâmetros da API REST

Os fluxos de trabalho de configuração LDAP fazem chamadas de API REST para realizar as tarefas específicas. Cada chamada de API pode incluir parâmetros de entrada como mostrado nas amostras fornecidas. Consulte "[Referência de API online](#)" para obter informações sobre como localizar a documentação de referência.

Configure o Astra para usar um servidor LDAP

Você precisa selecionar um servidor LDAP e configurar o Astra para usar o servidor como um provedor de autenticação. A tarefa de configuração consiste nos passos descritos abaixo. Cada etapa inclui uma única chamada de API REST.

1. Adicione um certificado de CA

Execute a seguinte chamada de API REST para adicionar um certificado de CA ao Astra.



Esta etapa é opcional e somente necessária se você quiser que o Astra e o LDAP se comuniquem em um canal seguro usando o LDAPS.

Método HTTP	Caminho
POST	<code>/accounts//core/v1/certificates</code>

Exemplo de entrada JSON

```
{
  "type": "application/astra-certificate",
  "version": "1.0",
  "certUse": "rootCA",
  "cert": "LS0tLS1CRUdJTiBDRVJUSUZJQ0FURS0tLS0tCk1JSUMyVEN",
  "isSelfSigned": "true"
}
```

Observe o seguinte sobre os parâmetros de entrada:

- `cert` É uma string JSON contendo um certificado formatado PKCS-11 codificado base64 (codificado PEM).
- `isSelfSigned` deve ser definido como `true` se o certificado for auto-assinado. A predefinição é `false`.

Curl exemplo

```
curl --location -i --request POST --data @JSONinput
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/certificates'
--header 'Content-Type: application/astra-certificate+json' --header
'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Exemplo de resposta JSON

```

{
  "type": "application/astra-certificate",
  "version": "1.0",
  "id": "a5212e7e-402b-4cff-bba0-63f3c6505199",
  "certUse": "rootCA",
  "cert": "LS0tLS1CRUdJTlBDRVJUSUZJQ0FURS0tLS0tCk1JSUMyVEN",
  "cn": "adldap.example.com",
  "expiryTimestamp": "2023-07-08T20:22:07Z",
  "isSelfSigned": "true",
  "trustState": "trusted",
  "trustStateTransitions": [
    {
      "from": "untrusted",
      "to": [
        "trusted",
        "expired"
      ]
    },
    {
      "from": "trusted",
      "to": [
        "untrusted",
        "expired"
      ]
    },
    {
      "from": "expired",
      "to": [
        "untrusted",
        "trusted"
      ]
    }
  ],
  "trustStateDesired": "trusted",
  "trustStateDetails": [],
  "metadata": {
    "creationTimestamp": "2022-07-21T04:16:06Z",
    "modificationTimestamp": "2022-07-21T04:16:06Z",
    "createdBy": "8a02d2b8-a69d-4064-827f-36851b3e1e6e",
    "modifiedBy": "8a02d2b8-a69d-4064-827f-36851b3e1e6e",
    "labels": []
  }
}

```

2. Adicione as credenciais de vinculação

Execute a seguinte chamada de API REST para adicionar as credenciais de vinculação.

Método HTTP	Caminho
POST	/accounts/_id/core/v1/credentials

Exemplo de entrada JSON

```
{
  "name": "ldapBindCredential",
  "type": "application/astra-credential",
  "version": "1.1",
  "keyStore": {
    "bindDn": "dWlkPWFkbWluLG91PXM5c3RlbQ==",
    "password": "cGFzc3dvcmQ="
  }
}
```

Observe o seguinte sobre os parâmetros de entrada:

- `bindDn` E `password` são as credenciais de vinculação codificadas base64 do usuário de administrador LDAP que é capaz de conectar e pesquisar o diretório LDAP. `bindDn` É o endereço de e-mail do usuário LDAP.

Curl exemplo

```
curl --location -i --request POST --data @JSONinput
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/credentials'
--header 'Content-Type: application/astra-credential+json' --header
'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Exemplo de resposta JSON

```

{
  "type": "application/astra-credential",
  "version": "1.1",
  "id": "3bd9c8a7-f5a4-4c44-b778-90a85fc7d154",
  "name": "ldapBindCredential",
  "metadata": {
    "creationTimestamp": "2022-07-21T06:53:11Z",
    "modificationTimestamp": "2022-07-21T06:53:11Z",
    "createdBy": "527329f2-662c-41c0-ada9-2f428f14c137"
  }
}

```

Observe os seguintes parâmetros de resposta:

- `id` da credencial é utilizado em etapas subsequentes do fluxo de trabalho.

3. Recupere o UUID da configuração LDAP

Execute a seguinte chamada de API REST para recuperar o UUID da `astra.account.ldap` configuração incluída no Astra Control Center.



O exemplo curl abaixo usa um parâmetro de consulta para filtrar a coleção de configurações. Em vez disso, você pode remover o filtro para obter todas as configurações e, em seguida, procurar `astra.account.ldap`.

Método HTTP	Caminho
GET	/accounts/_id/core/v1/settings

Curl exemplo

```

curl --location -i --request GET
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/settings?filter=name%20eq%20'astra.account.ldap'&include=name,id' --header 'Accept: */*'
--header 'Authorization: Bearer <API_TOKEN>'

```

Exemplo de resposta JSON

```
{
  "items": [
    ["astra.account.ldap",
     "12072b56-e939-45ec-974d-2dd83b7815df"]
  ],
  "metadata": {}
}
```

4. Atualize a definição LDAP

Execute a seguinte chamada de API REST para atualizar a configuração LDAP e concluir a configuração. Use o `id` valor da chamada de API anterior para o `<SETTING_ID>` valor no caminho de URL abaixo.



Você pode emitir uma SOLICITAÇÃO GET para a configuração específica primeiro para ver o `configSchema`. Isso fornecerá mais informações sobre os campos obrigatórios na configuração.

Método HTTP	Caminho
COLOQUE	/accounts/_id/core/v1/settings//setting_id

Exemplo de entrada JSON

```
{
  "type": "application/astra-setting",
  "version": "1.0",
  "desiredConfig": {
    "connectionHost": "myldap.example.com",
    "credentialId": "3bd9c8a7-f5a4-4c44-b778-90a85fc7d154",
    "groupBaseDN": "OU=groups,OU=astra,DC=example,DC=com",
    "isEnabled": "true",
    "port": 686,
    "secureMode": "LDAPS",
    "userBaseDN": "OU=users,OU=astra,DC=example,dc=com",
    "userSearchFilter": "((objectClass=User))",
    "vendor": "Active Directory"
  }
}
```

Observe o seguinte sobre os parâmetros de entrada:

- `isEnabled` deve ser definido como `true` ou pode ocorrer um erro.
- `credentialId` é o id da credencial de ligação criada anteriormente.
- `secureMode` deve ser definido como `LDAP` ou `LDAPS` com base na sua configuração na etapa anterior.

- Apenas o 'Active Directory' é suportado como provedor.

Curl exemplo

```
curl --location -i --request PUT --data @JSONinput
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/settings/<SETTING_ID>' --header 'Content-Type: application/astra-setting+json' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Se a chamada for bem-sucedida, a resposta HTTP 204 será retornada.

5. Recuperar a definição LDAP

Opcionalmente, você pode executar a seguinte chamada de API REST para recuperar as configurações LDAP e confirmar a atualização.

Método HTTP	Caminho
GET	/accounts/_id/core/v1/settings//setting_id

Curl exemplo

```
curl --location -i --request GET
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/settings/<SETTING_ID>' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Exemplo de resposta JSON

```
{
  "items": [
    {
      "type": "application/astra-setting",
      "version": "1.0",
      "metadata": {
        "creationTimestamp": "2022-06-17T21:16:31Z",
        "modificationTimestamp": "2022-07-21T07:12:20Z",
        "labels": [],
        "createdBy": "system",
        "modifiedBy": "00000000-0000-0000-0000-000000000000"
      },
      "id": "12072b56-e939-45ec-974d-2dd83b7815df",
      "name": "astra.account.ldap",
      "desiredConfig": {
        "connectionHost": "10.193.61.88",
        "credentialId": "3bd9c8a7-f5a4-4c44-b778-90a85fc7d154",
        "groupBaseDN": "ou=groups,ou=astra,dc=example,dc=com",
      }
    }
  ]
}
```

```

    "isEnabled": "true",
    "port": 686,
    "secureMode": "LDAPS",
    "userBaseDN": "ou=users,ou=astra,dc=example,dc=com",
    "userSearchFilter": "((objectClass=User))",
    "vendor": "Active Directory"
  },
  "currentConfig": {
    "connectionHost": "10.193.160.209",
    "credentialId": "3bd9c8a7-f5a4-4c44-b778-90a85fc7d154",
    "groupBaseDN": "ou=groups,ou=astra,dc=example,dc=com",
    "isEnabled": "true",
    "port": 686,
    "secureMode": "LDAPS",
    "userBaseDN": "ou=users,ou=astra,dc=example,dc=com",
    "userSearchFilter": "((objectClass=User))",
    "vendor": "Active Directory"
  },
  "configSchema": {
    "$schema": "http://json-schema.org/draft-07/schema#",
    "title": "astra.account.ldap",
    "type": "object",
    "properties": {
      "connectionHost": {
        "type": "string",
        "description": "The hostname or IP address of your LDAP server."
      },
      "credentialId": {
        "type": "string",
        "description": "The credential ID for LDAP account."
      },
      "groupBaseDN": {
        "type": "string",
        "description": "The base DN of the tree used to start the group
search. The system searches the subtree from the specified location."
      },
      "groupSearchCustomFilter": {
        "type": "string",
        "description": "Type of search that controls the default group
search filter used."
      },
      "isEnabled": {
        "type": "string",
        "description": "This property determines if this setting is
enabled or not."
      }
    }
  }
}

```



```

    "port": {
      "type": "integer",
      "description": "The port on which the LDAP server is running."
    },
    "secureMode": {
      "type": "string",
      "description": "The secure mode LDAPS or LDAP."
    },
    "userBaseDN": {
      "type": "string",
      "description": "The base DN of the tree used to start the user
search. The system searches the subtree from the specified location."
    },
    "userSearchFilter": {
      "type": "string",
      "description": "The filter used to search for users according a
search criteria."
    },
    "vendor": {
      "type": "string",
      "description": "The LDAP provider you are using.",
      "enum": ["Active Directory"]
    }
  },
  "additionalProperties": false,
  "required": [
    "connectionHost",
    "secureMode",
    "credentialId",
    "userBaseDN",
    "userSearchFilter",
    "groupBaseDN",
    "vendor",
    "isEnabled"
  ]
},
"state": "valid",
}
],
"metadata": {}
}

```

Localize o state campo na resposta que terá um dos valores na tabela abaixo.

Estado	Descrição
pendente	O processo de configuração ainda está ativo e ainda não foi concluído.
válido	A configuração foi concluída com sucesso e <code>currentConfig</code> na resposta corresponde <code>desiredConfig</code> .
erro	O processo de configuração LDAP falhou.

Adicionar entradas LDAP ao Astra

Depois que o LDAP é configurado como um provedor de autenticação para o Astra Control Center, você pode selecionar os usuários LDAP que o Astra autenticará usando as credenciais LDAP. Cada usuário precisa ter uma função no Astra antes de poder acessar o Astra por meio da API REST Astra Control.

Há duas maneiras de configurar o Astra para atribuir funções. Escolha o que é apropriado para o seu ambiente.

- ["Adicione e vincule um usuário individual"](#)
- ["Adicione e vincule um grupo"](#)



As credenciais LDAP estão na forma de um nome de usuário como endereço de e-mail e a senha LDAP associada.

Adicione e vincule um usuário individual

Você pode atribuir uma função a cada usuário Astra que é usado após a autenticação LDAP. Isso é apropriado quando há um pequeno número de usuários e cada um pode ter características administrativas diferentes.

1. Adicionar um utilizador

Execute a seguinte chamada de API REST para adicionar um usuário ao Astra e indicar que o LDAP é o provedor de autenticação.

Método HTTP	Caminho
POST	/accounts/_id/core/v1/users

Exemplo de entrada JSON

```
{
  "type" : "application/astra-user",
  "version" : "1.1",
  "authID" : "cn=JohnDoe,ou=users,ou=astra,dc=example,dc=com",
  "authProvider" : "ldap",
  "firstName" : "John",
  "lastName" : "Doe",
  "email" : "john.doe@example.com"
}
```

Observe o seguinte sobre os parâmetros de entrada:

- São necessários os seguintes parâmetros:
 - authProvider
 - authID
 - email
- authID É o nome distinto (DN) do usuário no LDAP
- email Deve ser exclusivo para todos os usuários definidos no Astra

Se o email valor não for exclusivo, ocorrerá um erro e um código de status HTTP 409 será retornado na resposta.

Curl exemplo

```
curl --location -i --request POST --data @JSONinput
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/users' --header
'Content-Type: application/astra-user+json' --header 'Accept: */*'
--header 'Authorization: Bearer <API_TOKEN>'
```

Exemplo de resposta JSON

```

{
  "metadata": {
    "creationTimestamp": "2022-07-21T17:44:18Z",
    "modificationTimestamp": "2022-07-21T17:44:18Z",
    "createdBy": "8a02d2b8-a69d-4064-827f-36851b3e1e6e",
    "labels": []
  },
  "type": "application/astra-user",
  "version": "1.2",
  "id": "a7b5e674-a1b1-48f6-9729-6a571426d49f",
  "authProvider": "ldap",
  "authID": "cn=JohnDoe,ou=users,ou=astra,dc=example,dc=com",
  "firstName": "John",
  "lastName": "Doe",
  "companyName": "",
  "email": "john.doe@example.com",
  "postalAddress": {
    "addressCountry": "",
    "addressLocality": "",
    "addressRegion": "",
    "streetAddress1": "",
    "streetAddress2": "",
    "postalCode": ""
  },
  "state": "active",
  "sendWelcomeEmail": "false",
  "isEnabled": "true",
  "isInviteAccepted": "true",
  "enableTimestamp": "2022-07-21T17:44:18Z",
  "lastActTimestamp": ""
}

```

2. Adicione uma vinculação de função para o usuário

Execute a seguinte chamada de API REST para vincular o usuário a uma função específica. Você precisa ter o UUID do usuário criado na etapa anterior.

Método HTTP	Caminho
POST	/Accounts/_id/core/v1/roleBindings

Exemplo de entrada JSON

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "accountID": "{account_id}",
  "userID": "a7b5e674-a1b1-48f6-9729-6a571426d49f",
  "role": "member",
  "roleConstraints": ["*"]
}
```

Observe o seguinte sobre os parâmetros de entrada:

- O valor utilizado acima para `roleConstraint` é a única opção disponível para a versão atual do Astra. Ele indica que o usuário não está restrito a um conjunto limitado de namespaces e pode acessá-los todos.

Curl exemplo

```
curl --location -i --request POST --data @JSONinput
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/roleBindings'
--header 'Content-Type: application/astra-roleBinding+json' --header
'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Exemplo de resposta JSON

```
{
  "metadata": {
    "creationTimestamp": "2022-07-21T18:08:24Z",
    "modificationTimestamp": "2022-07-21T18:08:24Z",
    "createdBy": "8a02d2b8-a69d-4064-827f-36851b3e1e6e",
    "labels": []
  },
  "type": "application/astra-roleBinding",
  "principalType": "user",
  "version": "1.1",
  "id": "b02c7e4d-d483-40d1-aaff-e1f900312114",
  "userID": "a7b5e674-a1b1-48f6-9729-6a571426d49f",
  "groupID": "00000000-0000-0000-0000-000000000000",
  "accountID": "d0fdbfa7-be32-4a71-b59d-13d95b42329a",
  "role": "member",
  "roleConstraints": ["*"]
}
```

Observe o seguinte sobre os parâmetros de resposta:

- O valor `user` para o `principalType` campo indica que a vinculação de função foi adicionada para um

usuário (não para um grupo).

Adicione e vincule um grupo

Você pode atribuir uma função a um grupo Astra que é usado após a autenticação LDAP. Isso é apropriado quando há um grande número de usuários e cada um pode ter características administrativas semelhantes.

1. Adicionar um grupo

Execute a seguinte chamada de API REST para adicionar um grupo ao Astra e indicar que o LDAP é o provedor de autenticação.

Método HTTP	Caminho
POST	/accounts//core/v1/groups

Exemplo de entrada JSON

```
{
  "type": "application/astra-group",
  "version": "1.0",
  "name": "Engineering",
  "authProvider": "ldap",
  "authID": "CN=Engineering,OU=groups,OU=astra,DC=example,DC=com"
}
```

Observe o seguinte sobre os parâmetros de entrada:

- São necessários os seguintes parâmetros:
 - authProvider
 - authID

Curl exemplo

```
curl --location -i --request POST --data @JSONinput
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/groups' --header
'Content-Type: application/astra-group+json' --header 'Accept: */*'
--header 'Authorization: Bearer <API_TOKEN>'
```

Exemplo de resposta JSON

```

{
  "type": "application/astra-group",
  "version": "1.0",
  "id": "8b5b54da-ae53-497a-963d-1fc89990525b",
  "name": "Engineering",
  "authProvider": "ldap",
  "authID": "CN=Engineering,OU=groups,OU=astra,DC=example,DC=com",
  "metadata": {
    "creationTimestamp": "2022-07-21T18:42:52Z",
    "modificationTimestamp": "2022-07-21T18:42:52Z",
    "createdBy": "8a02d2b8-a69d-4064-827f-36851b3e1e6e",
    "labels": []
  }
}

```

2. Adicione uma vinculação de função para o grupo

Execute a seguinte chamada de API REST para vincular o grupo a uma função específica. Você precisa ter o UUID do grupo criado na etapa anterior. Os usuários que são membros do grupo poderão fazer login no Astra após o LDAP executar a autenticação.

Método HTTP	Caminho
POST	/Accounts/_id/core/v1/roleBindings

Exemplo de entrada JSON

```

{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "accountID": "{account_id}",
  "groupID": "8b5b54da-ae53-497a-963d-1fc89990525b",
  "role": "viewer",
  "roleConstraints": ["*"]
}

```

Observe o seguinte sobre os parâmetros de entrada:

- O valor utilizado acima para `roleConstraint` é a única opção disponível para a versão atual do Astra. Ele indica que o usuário não está restrito a certos namespaces e pode acessá-los todos.

Curl exemplo

```
curl --location -i --request POST --data @JSONinput
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/roleBindings'
--header 'Content-Type: application/astra-roleBinding+json' --header
'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Exemplo de resposta JSON

```
{
  "metadata": {
    "creationTimestamp": "2022-07-21T18:59:43Z",
    "modificationTimestamp": "2022-07-21T18:59:43Z",
    "createdBy": "527329f2-662c-41c0-ada9-2f428f14c137",
    "labels": []
  },
  "type": "application/astra-roleBinding",
  "principalType": "group",
  "version": "1.1",
  "id": "2f91b06d-315e-41d8-ae18-7df7c08fbb77",
  "userID": "00000000-0000-0000-0000-000000000000",
  "groupID": "8b5b54da-ae53-497a-963d-1fc89990525b",
  "accountID": "d0fdbfa7-be32-4a71-b59d-13d95b42329a",
  "role": "viewer",
  "roleConstraints": ["*"]
}
```

Observe o seguinte sobre os parâmetros de resposta:

- O valor `group` para o `principalType` campo indica que a vinculação de função foi adicionada para um grupo (não para um usuário).

Desativar e repor LDAP

Há duas tarefas administrativas opcionais relacionadas que você pode executar conforme necessário para uma implantação do Astra Control Center. Pode desativar globalmente a autenticação LDAP e repor a configuração LDAP.

Ambas as tarefas de fluxo de trabalho exigem o `id` para a `astra.account.ldap` configuração Astra. Detalhes sobre como recuperar o ID de configuração estão incluídos em **Configurar o servidor LDAP**. Consulte ["Recupere o UUID da configuração LDAP"](#) para obter mais informações.

- ["Desativar a autenticação LDAP"](#)
- ["Redefina a configuração de autenticação LDAP"](#)

Desativar a autenticação LDAP

Você pode executar a seguinte chamada de API REST para desativar globalmente a autenticação LDAP para uma implantação específica do Astra. A chamada atualiza a `astra.account.ldap` configuração e o `isEnabled` valor é definido como `false`.

Método HTTP	Caminho
COLOQUE	/accounts/_id/core/v1/settings//setting_id

Exemplo de entrada JSON

```
{
  "type": "application/astra-setting",
  "version": "1.0",
  "desiredConfig": {
    "connectionHost": "myldap.example.com",
    "credentialId": "3bd9c8a7-f5a4-4c44-b778-90a85fc7d154",
    "groupBaseDN": "OU=groups,OU=astra,DC=example,DC=com",
    "isEnabled": "false",
    "port": 686,
    "secureMode": "LDAPS",
    "userBaseDN": "OU=users,OU=astra,DC=example,dc=com",
    "userSearchFilter": "((objectClass=User))",
    "vendor": "Active Directory"
  }
}
```

```
curl --location -i --request PUT --data @JSONinput
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/settings/<SETTING_ID>' --header 'Content-Type: application/astra-setting+json' --header
'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Se a chamada for bem-sucedida, a HTTP 204 resposta será retornada. Opcionalmente, você pode recuperar as configurações novamente para confirmar a alteração.

Redefina a configuração de autenticação LDAP

Você pode executar a seguinte chamada de API REST para desconectar o Astra do servidor LDAP e redefinir a configuração LDAP no Astra. A chamada atualiza a `astra.account.ldap` configuração e o valor de `connectionHost` é apagado.

O valor de `isEnabled` também deve ser definido como `false`. Você pode definir esse valor antes de fazer a chamada de redefinição ou como parte de fazer a chamada de redefinição. No segundo caso, `connectionHost` deve ser limpo e `isEnabled` definido como `false` na mesma chamada de redefinição.



Esta é uma operação disruptiva e você deve prosseguir com cuidado. Elimina todos os utilizadores e grupos LDAP importados. Ele também exclui todos os usuários, grupos e roleBindings relacionados do Astra (tipo LDAP) que você criou no Astra Control Center.

Método HTTP	Caminho
COLOQUE	/accounts/_id/core/v1/settings//setting_id

Exemplo de entrada JSON

```
{
  "type": "application/astra-setting",
  "version": "1.0",
  "desiredConfig": {
    "connectionHost": "",
    "credentialId": "3bd9c8a7-f5a4-4c44-b778-90a85fc7d154",
    "groupBaseDN": "OU=groups,OU=astra,DC=example,DC=com",
    "isEnabled": "false",
    "port": 686,
    "secureMode": "LDAPS",
    "userBaseDN": "OU=users,OU=astra,DC=example,dc=com",
    "userSearchFilter": "((objectClass=User))",
    "vendor": "Active Directory"
  }
}
```

Observe o seguinte:

- Para alterar o servidor LDAP, você deve desabilitar e redefinir a alteração LDAP `connectHost` para um valor nulo, como mostrado no exemplo acima.

```
curl --location -i --request PUT --data @JSONinput
'https://astra.example.com/accounts/<ACCOUNT_ID>/core/v1/settings/<SETTING_ID>' --header 'Content-Type: application/astra-setting+json' --header
'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Se a chamada for bem-sucedida, a HTTP 204 resposta será retornada. Opcionalmente, você pode recuperar a configuração novamente para confirmar a alteração.

Clusters

Liste os clusters

É possível listar os clusters disponíveis em uma nuvem específica.

1. Selecione a nuvem

Execute o fluxo de trabalho "Liste as nuvens" e selecione a nuvem que contém os clusters.

2. Liste os clusters

Execute a seguinte chamada de API REST para listar os clusters em uma nuvem específica.

Método HTTP	Caminho
OBTER	/accounts//topology/v1/clouds/ /cloud_id/clusters

Exemplo de curl: Retorna todos os dados de todos os clusters

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/clouds/<CLOUD_ID>/clusters' --header 'Accept: */*' --header 'Authorization: Bearer
<API_TOKEN>'
```

Exemplo de saída JSON

```
{
  "items": [
    {
      "type": "application/astra-cluster",
      "version": "1.1",
      "id": "7ce83fba-6aa1-4e0c-a194-26e714f5eb46",
      "name": "openshift-clstr-ol-07",
      "state": "running",
      "stateUnready": [],
      "managedState": "managed",
      "protectionState": "full",
      "protectionStateDetails": [],
      "restoreTargetSupported": "true",
      "snapshotSupported": "true",
      "managedStateUnready": [],
      "managedTimestamp": "2022-11-03T15:50:59Z",
      "inUse": "true",
      "clusterType": "openshift",
      "accHost": "true",
      "clusterVersion": "1.23",
      "clusterVersionString": "v1.23.12+6b34f32",
      "namespaces": [
        "default",
        "kube-node-lease",
        "kube-public",
        "kube-system",
```

```
"metallb-system",
"mysql",
"mysql-clone1",
"mysql-clone2",
"mysql-clone3",
"mysql-clone4",
"netapp-acc-operator",
"netapp-monitoring",
"openshift",
"openshift-apiserver",
"openshift-apiserver-operator",
"openshift-authentication",
"openshift-authentication-operator",
"openshift-cloud-controller-manager",
"openshift-cloud-controller-manager-operator",
"openshift-cloud-credential-operator",
"openshift-cloud-network-config-controller",
"openshift-cluster-csi-drivers",
"openshift-cluster-machine-approver",
"openshift-cluster-node-tuning-operator",
"openshift-cluster-samples-operator",
"openshift-cluster-storage-operator",
"openshift-cluster-version",
"openshift-config",
"openshift-config-managed",
"openshift-config-operator",
"openshift-console",
"openshift-console-operator",
"openshift-console-user-settings",
"openshift-controller-manager",
"openshift-controller-manager-operator",
"openshift-dns",
"openshift-dns-operator",
"openshift-etcd",
"openshift-etcd-operator",
"openshift-host-network",
"openshift-image-registry",
"openshift-infra",
"openshift-ingress",
"openshift-ingress-canary",
"openshift-ingress-operator",
"openshift-insights",
"openshift-kni-infra",
"openshift-kube-apiserver",
"openshift-kube-apiserver-operator",
"openshift-kube-controller-manager",
```

```

    "openshift-kube-controller-manager-operator",
    "openshift-kube-scheduler",
    "openshift-kube-scheduler-operator",
    "openshift-kube-storage-version-migrator",
    "openshift-kube-storage-version-migrator-operator",
    "openshift-machine-api",
    "openshift-machine-config-operator",
    "openshift-marketplace",
    "openshift-monitoring",
    "openshift-multus",
    "openshift-network-diagnostics",
    "openshift-network-operator",
    "openshift-node",
    "openshift-oauth-apiserver",
    "openshift-openstack-infra",
    "openshift-operator-lifecycle-manager",
    "openshift-operators",
    "openshift-ovirt-infra",
    "openshift-sdn",
    "openshift-service-ca",
    "openshift-service-ca-operator",
    "openshift-user-workload-monitoring",
    "openshift-vsphere-infra",
    "pcloud",
    "postgresql",
    "trident"
  ],
  "defaultStorageClass": "4bacbb3c-0727-4f58-b13c-3a2a069baf89",
  "cloudID": "4f1e1086-f415-4451-a051-c7299cd672ff",
  "credentialID": "7ffd7354-b6c2-4efa-8e7b-cf64d5598463",
  "isMultizonal": "false",
  "tridentManagedStateAllowed": [
    "unmanaged"
  ],
  "tridentVersion": "22.10.0",
  "apiServiceID": "98df44dc-2baf-40d5-8826-e198b1b40909",
  "metadata": {
    "labels": [
      {
        "name": "astra.netapp.io/labels/read-
only/cloudName",
        "value": "private"
      }
    ]
  },
  "creationTimestamp": "2022-11-03T15:50:59Z",
  "modificationTimestamp": "2022-11-04T14:42:32Z",

```

```
      "createdBy": "00000000-0000-0000-0000-000000000000"
    }
  }
]
}
```

Adicione um cluster usando credenciais

Você pode adicionar um cluster para que ele fique disponível para ser gerenciado pelo Astra. A partir do lançamento do Astra 22,11, você pode adicionar um cluster com Astra Control Center e Astra Control Service.



A adição de um cluster não é necessária ao usar um serviço Kubernetes de um dos principais fornecedores de nuvem (AKS, EKS, GKE).

1. Obtenha o arquivo kubeconfig

Você precisa obter uma cópia do arquivo **kubeconfig** do administrador ou serviço do Kubernetes.

2. Prepare o arquivo kubeconfig

Antes de usar o arquivo **kubeconfig**, você deve executar as seguintes operações:

Converter arquivo do formato YAML para JSON

Se você receber o arquivo kubeconfig formatado como YAML, você precisará convertê-lo para JSON.

Codificar JSON em base64

Você deve codificar o arquivo JSON em base64.

Exemplo

Aqui está um exemplo de conversão do arquivo kubeconfig de YAML para JSON e depois codificá-lo em base64:

```
yq -o=json ~/.kube/config | base64
```

3. Selecione a nuvem

Execute o fluxo de trabalho "[Liste as nuvens](#)" e selecione a nuvem em que o cluster será adicionado.



A única nuvem que você pode selecionar é a nuvem **privada**.

4. Crie uma credencial

Execute a seguinte chamada de API REST para criar uma credencial usando o arquivo kubeconfig.

Método HTTP	Caminho
POST	/accounts/_id/core/v1/credentials

Exemplo de entrada JSON

```
{
  "type" : "application/astra-credential",
  "version" : "1.1",
  "name" : "Cloud One",
  "keyType" : "kubeconfig",
  "keyStore" : {
    "base64": encoded_kubeconfig
  },
  "valid" : "true"
}
```

Curl exemplo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/credentials'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>' --data
@JSONinput
```

5. Adicione o cluster

Execute a seguinte chamada de API REST para adicionar o cluster à nuvem. O valor do `credentialID` campo de entrada é obtido a partir da chamada API REST na etapa anterior.

Método HTTP	Caminho
POST	/accounts//topology/v1/clouds/ /cloud_id/clusters

Exemplo de entrada JSON

```
{
  "type" : "application/astra-cluster",
  "version" : "1.1",
  "credentialID": credential_id
}
```

Curl exemplo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/clouds/<CLOUD_I
D>/clusters' --header 'Accept: */*' --header 'Authorization: Bearer
<API_TOKEN>' --data @JSONinput
```

Listar clusters gerenciados

É possível listar os clusters de Kubernetes gerenciados atualmente pelo Astra.

1. Listar os clusters gerenciados

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
GET	/Accounts/_id/topology/v1/managedclusters

Exemplo de curl: Retorna todos os dados de todos os clusters

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/managedClusters
' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Gerenciar um cluster

É possível gerenciar um cluster do Kubernetes para que a proteção de dados possa ser executada.

1. Selecione o cluster a gerir

Execute o fluxo de trabalho "[Listar clusters](#)" e selecione o cluster desejado. A propriedade `managedState` do cluster deve ser `unmanaged`.

2. Opcionalmente, selecione a classe de armazenamento

Opcionalmente, execute o fluxo de trabalho "[Listar classes de armazenamento](#)" e selecione a classe de armazenamento desejada.



Se você não fornecer uma classe de armazenamento na chamada para gerenciar o cluster, sua classe de armazenamento padrão será usada.

3. Gerenciar o cluster

Execute a seguinte chamada de API REST para gerenciar o cluster.

Método HTTP	Caminho
POST	/Accounts/_id/topology/v1/managedclusters

Exemplo de entrada JSON


```
{
  "type": "application/astra-managedCluster",
  "version": "1.0",
  "id": "d0fdf455-4330-476d-bb5d-4d109714e07d"
}
```

Curl exemplo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/managedClusters
' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
--data @JSONinput
```

Nuvens

Liste as nuvens

Você pode listar as nuvens definidas e disponíveis de uma conta específica do Astra.

1. Liste as nuvens

Execute a seguinte chamada de API REST para listar as nuvens.

Método HTTP	Caminho
OBTER	/accounts/_id/topology/v1/clouds

Curl exemplo: Retorna todos os dados para todas as nuvens

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/clouds'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Baldes

Liste os buckets

Você pode listar os buckets do S3 definidos para uma conta específica do Astra.

1. Liste os buckets

Execute a seguinte chamada de API REST para listar os buckets.

Método HTTP	Caminho
OBTER	/accounts/_id/topology/v1/buckets

Curl exemplo: Retorna todos os dados para todos os buckets

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/buckets'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Armazenamento

Listar classes de armazenamento

Você pode listar as classes de armazenamento disponíveis.

1. Selecione a nuvem

Execute o fluxo de trabalho "[Liste as nuvens](#)" e selecione a nuvem na qual você estará trabalhando.

2. Selecione o cluster

Execute o fluxo de trabalho "[Liste os clusters](#)" e selecione o cluster.

3. Liste as classes de armazenamento de um cluster específico

Execute a seguinte chamada de API REST para listar as classes de armazenamento de um cluster e nuvem específicos.

Método HTTP	Caminho
OBTER	/Accounts/(account_id)/topology/v1/clouds/<CLOUD_ID>/clusters/<CLUSTER_ID>/storageClasses

Curl exemplo: Retorna todos os dados para todas as classes de armazenamento

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/clouds/<CLOUD_ID>/clusters/<CLUSTER_ID>/storageClasses' --header 'Accept: */*' --header
'Authorization: Bearer <API_TOKEN>'
```

Exemplo de saída JSON

```
{
  "items": [
    {
      "type": "application/astra-storageClass",
```

```

    "version": "1.1",
    "id": "4bacbb3c-0727-4f58-b13c-3a2a069baf89",
    "name": "ontap-basic",
    "provisioner": "csi.trident.netapp.io",
    "available": "eligible",
    "allowVolumeExpansion": "true",
    "reclaimPolicy": "Delete",
    "volumeBindingMode": "Immediate",
    "isDefault": "true",
    "metadata": {
      "createdBy": "system",
      "creationTimestamp": "2022-10-26T05:16:19Z",
      "modificationTimestamp": "2022-10-26T05:16:19Z",
      "labels": []
    }
  },
  {
    "type": "application/astra-storageClass",
    "version": "1.1",
    "id": "150fe657-4a42-47a3-abc6-5dafba3de8bf",
    "name": "thin",
    "provisioner": "kubernetes.io/vsphere-volume",
    "available": "ineligible",
    "reclaimPolicy": "Delete",
    "volumeBindingMode": "Immediate",
    "metadata": {
      "createdBy": "system",
      "creationTimestamp": "2022-10-26T04:46:08Z",
      "modificationTimestamp": "2022-11-04T14:58:19Z",
      "labels": []
    }
  },
  {
    "type": "application/astra-storageClass",
    "version": "1.1",
    "id": "7c6a5c58-6a0d-4cb6-98a0-8202ad2de74a",
    "name": "thin-csi",
    "provisioner": "csi.vsphere.vmware.com",
    "available": "ineligible",
    "allowVolumeExpansion": "true",
    "reclaimPolicy": "Delete",
    "volumeBindingMode": "WaitForFirstConsumer",
    "metadata": {
      "createdBy": "system",
      "creationTimestamp": "2022-10-26T04:46:17Z",
      "modificationTimestamp": "2022-10-26T04:46:17Z",

```

```

        "labels": []
    }
},
{
    "type": "application/astra-storageClass",
    "version": "1.1",
    "id": "7010ef09-92a5-4c90-a5e5-3118e02dc9a7",
    "name": "vsim-san",
    "provisioner": "csi.trident.netapp.io",
    "available": "eligible",
    "allowVolumeExpansion": "true",
    "reclaimPolicy": "Delete",
    "volumeBindingMode": "Immediate",
    "metadata": {
        "createdBy": "system",
        "creationTimestamp": "2022-11-03T18:40:03Z",
        "modificationTimestamp": "2022-11-03T18:40:03Z",
        "labels": []
    }
}
]
}

```

Listar backends de armazenamento

Você pode listar os backends de armazenamento disponíveis.

1. Liste os backends

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
OBTER	/Accounts/_id/topology/v1/storageBackends

Curl exemplo: Retorna todos os dados para todos os backends de armazenamento

```

curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/storageBackends
' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'

```

Exemplo de saída JSON

```

{
  "items": [
    {
      "backendCredentialsName": "10.191.77.177",
      "backendName": "myinchunhcluster-1",
      "backendType": "ONTAP",
      "backendVersion": "9.8.0",
      "configVersion": "Not applicable",
      "health": "Not applicable",
      "id": "46467c16-1585-4b71-8e7f-f0bc5ff9da15",
      "location": "nalab2",
      "metadata": {
        "createdBy": "4c483a7e-207b-4f9a-87b7-799a4629d7c8",
        "creationTimestamp": "2021-07-30T14:26:19Z",
        "modificationTimestamp": "2021-07-30T14:26:19Z"
      },
      "ontap": {
        "backendManagementIP": "10.191.77.177",
        "managementIPs": [
          "10.191.77.177",
          "10.191.77.179"
        ]
      },
      "protectionPolicy": "Not applicable",
      "region": "Not applicable",
      "state": "Running",
      "stateUnready": [],
      "type": "application/astra-storageBackend",
      "version": "1.0",
      "zone": "Not applicable"
    }
  ]
}

```

Habilite pools de ANF dinâmicos para clusters autogerenciados

Ao fazer backup de uma aplicação gerenciada em um cluster privado no local que tenha um back-end de storage do ANF, você precisa ativar o recurso Dynamic ANF Pools. Isso é feito fornecendo um ID de assinatura para usar ao expandir e contratar os pools de capacidade.



Os pools de ANF dinâmicos são recursos das aplicações gerenciadas pelo Astra que usam um back-end de storage do Azure NetApp Files (ANF). Ao fazer backup dessas aplicações, o Astra expande e contrai automaticamente os pools de capacidade aos quais os volumes persistentes pertencem por um fator de 1,5. Isso garante que haja espaço suficiente para o backup sem incorrer em uma carga permanente adicional. Consulte "[Backups de aplicativos do Azure](#)" para obter mais informações.

1. Adicione o identificador de assinatura do Azure

Execute a seguinte chamada de API REST.



Você precisa atualizar o exemplo de entrada JSON conforme apropriado para o seu ambiente, incluindo o ID de assinatura e o valor base64 para o responsável pelo serviço.

Método HTTP	Caminho
POST	/accounts/_id/core/v1/credentials

Exemplo de entrada JSON

```
{
  "keyStore": {
    "privKey": "SGkh",
    "pubKey": "UGhpcyCpcyBhbiBleGFtcGxlLg==",
    "base64":
    "fwogICAgJmFwcElkIjogIjY4ZmSiODFiLTU0YWYtNDdjNC04ZjUzLWE2NDdlZTUzMGZkZCIsc
    iAgICAgIzG1zcGxheU5hbWUiOiAic3AtYXN0cmEtZGV2LXFhIiwKICAgICJuYW11IjogImh0dHA
    6Ly9zcC1hc3RyYS1kZXYtcWEiLAogICAgInBhc3N3b3JkIjogIlllLQThRfk9IVVJkZWZYM0pST
    WJlLnUeFBleVE0UnNwTG9DcUJjazAiLAogICAgInRlbnFudCI6ICIwMTFjZGY2Yy03NTEyLTQ
    3MDUtYjI0ZS03NzIxYWZkOGNhMzciLAogICAgInN1YnNjcmlwdGlvbklkIjogImIyMDAxNTVmL
    TAwmWEtNDNiZS04N2JlLTNlZGRlODNhY2VmNCIKfQ=="
  },
  "name": "myCert",
  "type": "application/astra-credential",
  "version": "1.1",
  "metadata": {
    "labels": [
      {
        "name": "astra.netapp.io/labels/read-only/credType",
        "value": "service-account"
      },
      {
        "name": "astra.netapp.io/labels/read-only/cloudName",
        "value": "OCP"
      },
      {
        "name": "astra.netapp.io/labels/read-only/azure/subscriptionID",
        "value": "b212156f-001a-43be-87be-3edde83acef5"
      }
    ]
  }
}
```

Curl exemplo

```
curl --location -i --request POST --data @JSONinput
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/credentials'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
--header 'Content-Type: application/astra-credential+json'
```

2. Adicione um balde, se necessário

Você deve adicionar um bucket ao aplicativo gerenciado, se necessário.

3. Faça um backup do aplicativo gerenciado

Execute o fluxo de ["Crie uma cópia de segurança para uma aplicação"](#) trabalho . O pool de capacidade onde o volume persistente original está presente irá expandir e diminuir automaticamente.

4. Reveja o registo de eventos

Os eventos de atividade são registados durante a cópia de segurança. Execute o fluxo de trabalho ["Liste as notificações"](#) para exibir as mensagens.

Fluxos de trabalho de gerenciamento

Antes de começar

Use esses workflows como parte da administração das aplicações em um cluster gerenciado do Astra.



Esses fluxos de trabalho podem ser expandidos e aprimorados pelo NetApp a qualquer momento, portanto, você deve revisá-los periodicamente.

Preparação geral

Antes de usar qualquer um dos workflows do Astra, revise "[Prepare-se para usar os fluxos de trabalho](#)".

Categorias de fluxo de trabalho

Os fluxos de trabalho de gerenciamento são organizados em diferentes categorias para facilitar a localização do que você deseja.

Categoria	Descrição
Controle de aplicação	Esses fluxos de trabalho permitem que você controle os aplicativos gerenciados e não gerenciados. Você pode listar os aplicativos, bem como criar e remover um aplicativo gerenciado.
Proteção de aplicação	Use esses fluxos de trabalho para proteger suas aplicações gerenciadas por meio de snapshots e backups.
Clonagem e restauração de aplicações	Esse fluxo de trabalho descreve como clonar e restaurar aplicativos gerenciados.
Suporte	Há vários fluxos de trabalho disponíveis para depurar e dar suporte às suas aplicações, bem como o ambiente geral do Kubernetes.

Considerações adicionais

Há várias considerações adicionais ao usar os fluxos de trabalho de gerenciamento.

Clonar uma aplicação

Há algumas coisas a considerar ao clonar um aplicativo. Os parâmetros descritos abaixo fazem parte da entrada JSON.

Identificador do cluster de origem

O valor de `sourceClusterID` sempre identifica o cluster onde o aplicativo original está instalado.

Identificador de cluster

O valor de `clusterID` identifica o cluster onde o novo aplicativo será instalado.

- Ao clonar dentro do mesmo cluster `clusterID` e `sourceClusterID` ter o mesmo valor.
- Ao clonar entre clusters, os dois valores são diferentes e `clusterID` devem ser a ID do cluster de

destino.

Namespaces

O namespace valor deve ser diferente do aplicativo de origem original. Além disso, o namespace para o clone não pode existir e o Astra o criará.

Backups e snapshots

Opcionalmente, você pode clonar um aplicativo a partir de um backup ou snapshot existente usando os `backupID` parâmetros ou `snapshotID`. Se você não fornecer um backup ou snapshot, o Astra criará primeiro um backup da aplicação e, em seguida, clonará a partir do backup.

Restaurar uma aplicação

Aqui estão algumas coisas a considerar ao restaurar um aplicativo.

- Restaurar um aplicativo é muito semelhante à operação clone.
- Ao restaurar um aplicativo, você deve fornecer um backup ou um snapshot.

Controlo de aplicações

Liste as aplicações

Você pode listar as aplicações que atualmente são gerenciadas pelo Astra. Você pode fazer isso como parte de encontrar os snapshots ou backups de um aplicativo específico.

1. Liste os aplicativos

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
OBTER	/account//k8s/v2/apps

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
incluir	Consulta	Não	Opcionalmente, selecione os valores que você deseja retornar na resposta.

Curl exemplo: Retorna todos os dados para todos os aplicativos

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v2/apps' --header
'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Curl exemplo: Retorna o nome, id e estado de todos os aplicativos

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v2/apps?include=name,id
,state' --header 'Accept: */*' --header 'Authorization: Bearer
<API_TOKEN>'
```

Exemplo de saída JSON

```
{
  "items": [
    [
      "mysql",
      "4ee2b8fa-3696-4f32-8879-399792f477c3",
      "ready"
    ],
    [
      "postgresql",
      "3b984474-e5c9-4b64-97ee-cdeb9bcd212e",
      "ready"
    ],
  ],
  "metadata": {}
}
```

Obtenha uma aplicação

Você pode recuperar todas as variáveis de recurso descrevendo um único aplicativo.

Antes de começar

Você deve ter o ID do aplicativo que deseja recuperar. Se necessário, você pode usar o fluxo de trabalho ["Liste as aplicações"](#) para localizar o aplicativo.

1. Obtenha o aplicativo

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
OBTER	/accounts/_id/k8s/v2/apps//app_id

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
id da aplicação	Caminho	Sim	Valor de ID da aplicação a recuperar.

Curl exemplo: Retorna todos os dados para o aplicativo

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v2/apps/<APP_ID>'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Gerenciar um aplicativo

Você pode criar uma aplicação gerenciada com base em uma aplicação já conhecida pelo Astra em um namespace específico. Quando uma aplicação é gerenciada ou definida no Astra, você pode protegê-la fazendo backups e snapshots.

1. Selecione o namespace

Execute o fluxo de trabalho "[Liste os namespaces](#)" e selecione o namespace.

2. Selecione o cluster

Execute o fluxo de trabalho "[Liste os clusters](#)" e selecione o cluster.

3. Gerencie o aplicativo

Execute a seguinte chamada de API REST para gerenciar o aplicativo.

Método HTTP	Caminho
POST	/accounts/_id/k8s/v2/apps

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
JSON	Corpo	Sim	Fornecer os parâmetros necessários para identificar o aplicativo a ser gerenciado. Veja o exemplo abaixo.

Exemplo de entrada JSON

```
{
  "clusterID": "7ce83fba-6aa1-4e0c-a194-26e714f5eb46",
  "name": "subtext",
  "namespaceScopedResources": [{"namespace": "kube-matrix"}],
  "type": "application/astra-app",
  "version": "2.0"
}
```

Curl exemplo: Gerencie um aplicativo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v2/apps' --header
'Content-Type: application/astra-app+json' --header 'Accept: */*' --header
'Authorization: Bearer <API_TOKEN>' --data @JSONinput
```

Desgerenciar um aplicativo

Você pode remover um aplicativo gerenciado quando não for mais necessário. A remoção de um aplicativo gerenciado também exclui as programações associadas.

Antes de começar

Você deve ter o ID do aplicativo que deseja desgerenciar. Se necessário, você pode usar o fluxo de trabalho ["Liste as aplicações"](#) para localizar o aplicativo.

Os backups e snapshots do aplicativo não são removidos automaticamente quando são excluídos. Se você não precisar mais dos backups e snapshots, exclua-os antes de remover o aplicativo.

1. Não gerido a aplicação

Execute a seguinte chamada de API REST para remover o aplicativo.

Método HTTP	Caminho
ELIMINAR	/accounts/_id/k8s/v2/apps//app_id

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
id da aplicação	Caminho	Sim	Identifica o aplicativo a ser removido.

Curl exemplo: Remover um aplicativo gerenciado

```
curl --location -i --request DELETE
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v2/apps/<APP_ID>'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Proteção da aplicação

Liste os instantâneos

Você pode listar os snapshots que foram obtidos para um aplicativo específico.

Antes de começar

Você deve ter o ID do aplicativo para o qual deseja listar os snapshots. Se necessário, você pode usar o fluxo de trabalho "[Liste as aplicações](#)" para localizar o aplicativo.

1. Liste os instantâneos

Execute a seguinte chamada de API REST para listar os snapshots.

Método HTTP	Caminho
OBTER	/Accounts/_id/k8s/v1/apps//app_id/appSnaps

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
id da aplicação	Caminho	Sim	Identifica o aplicativo que possui os snapshots listados.
contar	Consulta	Não	Se <code>count=true</code> o número de instantâneos estiver incluído na seção metadados da resposta.

Curl exemplo: Retornar todos os snapshots para o aplicativo

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v1/apps/<APP_ID>/appSnaps'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Curl exemplo: Retorna todos os instantâneos para o aplicativo e a contagem

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v1/apps/<APP_ID>/appSnap
s?count=true' --header 'Accept: */*' --header 'Authorization: Bearer
<API_TOKEN>'
```

Exemplo de saída JSON

```
{
  "items": [
    {
      "type": "application/astra-appSnap",
      "version": "1.1",
      "id": "1ce34da4-bb0a-4926-b925-4a5d85dda8c2",
      "hookState": "success",
      "metadata": {
        "createdBy": "a530e865-23e8-4e2e-8020-e92c419a3867",
        "creationTimestamp": "2022-10-30T22:44:20Z",
        "modificationTimestamp": "2022-10-30T22:44:20Z",
        "labels": []
      },
      "snapshotAppAsset": "0ebfe3f8-40ed-4bdc-88c4-2144fbda85a0",
      "snapshotCreationTimestamp": "2022-10-30T22:44:33Z",
      "name": "snapshot-david-1",
      "state": "completed",
      "stateUnready": []
    }
  ],
  "metadata": {}
}
```

Liste os backups

Você pode listar os backups que foram criados para um aplicativo específico.

Antes de começar

Você deve ter o ID do aplicativo para o qual deseja listar os backups. Se necessário, você pode usar o fluxo de trabalho ["Liste as aplicações"](#) para localizar o aplicativo.

1. Liste os backups

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
OBTER	/Accounts/_id/k8s/v1/apps//app_id/appBackups

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
id da aplicação	Caminho	Sim	Identifica o aplicativo gerenciado que possui os backups listados.

Curl exemplo: Retornar todos os backups para o aplicativo

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v1/apps/<APP_ID>/appBackups' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Exemplo de saída JSON


```

{
  "items": [
    {
      "type": "application/astra-appBackup",
      "version": "1.1",
      "id": "8edeb4a4-fd8b-4222-a559-1013145b28fc",
      "name": "backup-david-oct28-1",
      "bucketID": "a443e58f-59bd-4d45-835a-1bc7813f659a",
      "snapshotID": "dfe237cb-57b7-4576-af4d-00ba3a8f2828",
      "state": "completed",
      "stateUnready": [],
      "hookState": "success",
      "totalBytes": 205219132,
      "bytesDone": 205219132,
      "percentDone": 100,
      "metadata": {
        "labels": [
          {
            "name": "astra.netapp.io/labels/read-
only/triggerType",
            "value": "backup"
          }
        ],
        "creationTimestamp": "2022-10-28T21:58:37Z",
        "modificationTimestamp": "2022-10-28T21:58:55Z",
        "createdBy": "a530e865-23e8-4e2e-8020-e92c419a3867"
      }
    }
  ],
  "metadata": {}
}

```

Crie um instantâneo para um aplicativo

Você pode criar um instantâneo para um aplicativo específico.

Antes de começar

Você deve ter o ID do aplicativo para o qual deseja criar um instantâneo. Se necessário, você pode usar o fluxo de trabalho ["Liste as aplicações"](#) para localizar o aplicativo.

1. Criar um instantâneo

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
POST	/Accounts/_id/k8s/v1/apps//app_id/appSnaps

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
id da aplicação	Caminho	Sim	Identifica o aplicativo gerenciado onde o snapshot será criado.
JSON	Corpo	Sim	Fornece os parâmetros para o instantâneo. Veja o exemplo abaixo.

Exemplo de entrada JSON

```
{
  "type": "application/astra-appSnap",
  "version": "1.1",
  "name": "snapshot-david-1"
}
```

Curl exemplo: Crie um instantâneo para o aplicativo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v1/apps/<APP_ID>/appSnaps' --header 'Content-Type: application/astra-appSnap+json' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>' --data @JSONinput
```

Crie uma cópia de segurança para uma aplicação

Você pode criar um backup para um aplicativo específico e usar o backup para restaurar ou clonar o aplicativo.

Antes de começar

Você deve ter o ID do aplicativo que deseja fazer backup. Se necessário, você pode usar o fluxo de trabalho ["Liste as aplicações"](#) para localizar o aplicativo.

1. Crie uma cópia de segurança

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
POST	/Accounts/_id/k8s/v1/apps//app_id/appBackups

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
id da aplicação	Caminho	Sim	Identifica o aplicativo onde o backup será criado.
JSON	Corpo	Sim	Fornecer os parâmetros para o backup. Veja o exemplo abaixo.

Exemplo de entrada JSON

```
{
  "type": "application/astra-appBackup",
  "version": "1.1",
  "name": "backup-david-1"
}
```

Curl exemplo: Crie um backup para o aplicativo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v1/apps/<APP_ID>/appBackups' --header 'Content-Type: application/astra-appBackup+json' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>' --data @JSONinput
```

Eliminar um instantâneo

Pode eliminar um instantâneo associado a uma aplicação.

Antes de começar

Você deve ter o seguinte:

- ID do aplicativo que possui o snapshot. Se necessário, você pode usar o fluxo de trabalho ["Liste as aplicações"](#) para localizar o aplicativo.
- ID do instantâneo que pretende eliminar. Se necessário, você pode usar o fluxo de trabalho ["Liste os instantâneos"](#) para localizar o instantâneo.

1. Eliminar o instantâneo

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
ELIMINAR	/Accounts/_id/k8s/v1/apps//app_id/appSnaps//appSnap_id

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
id da aplicação	Caminho	Sim	Identifica o aplicativo gerenciado que possui o snapshot.
id do instantâneo	Caminho	Sim	Identifica o instantâneo a ser eliminado.

Curl exemplo: Exclua um único snapshot para o aplicativo

```
curl --location -i --request DELETE
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v1/apps/<APP_ID>/appSnaps/<SNAPSHOT_ID>' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Eliminar uma cópia de segurança

Pode eliminar uma cópia de segurança associada a uma aplicação.

Antes de começar

Você deve ter o seguinte:

- ID do aplicativo que possui o backup. Se necessário, você pode usar o fluxo de trabalho "[Liste as aplicações](#)" para localizar o aplicativo.
- ID da cópia de segurança que pretende eliminar. Se necessário, você pode usar o fluxo de trabalho "[Liste os backups](#)" para localizar o instantâneo.

1. Eliminar a cópia de segurança

Execute a seguinte chamada de API REST.



Você pode forçar a exclusão de um backup com falha usando o cabeçalho de solicitação opcional, conforme descrito abaixo.

Método HTTP	Caminho
ELIMINAR	/Accounts/ k8s/v1/apps//app_id/appBackups/ appBackup_id

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
id da aplicação	Caminho	Sim	Identifica o aplicativo gerenciado que possui o backup.
id de cópia de segurança	Caminho	Sim	Identifica o backup a ser excluído.
forçar a eliminação	Colhedor	Não	Usado para forçar a exclusão de um backup com falha.

Curl exemplo: Exclua um único backup para o aplicativo

```
curl --location -i --request DELETE
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v1/apps/<APP_ID>/appBackups/<BACKUP_ID>' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Curl exemplo: Exclua um único backup para o aplicativo com a opção forçar

```
curl --location -i --request DELETE
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v1/apps/<APP_ID>/appBackups/<BACKUP_ID>' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>' --header 'Force-Delete: true'
```

Crie uma política de proteção de dados

Você pode criar uma política de proteção de dados com base em um ou mais horários.

1. Selecione a aplicação

Execute o fluxo de trabalho "[Liste as aplicações](#)" e selecione a aplicação pretendida.

2. Crie a proteção

Execute a seguinte chamada de API REST para criar uma política de proteção para um aplicativo específico.

Método HTTP	Caminho
POST	/accounts//k8s/v1/apps//app_id/programações

Exemplo de entrada JSON

```
{
  "type": "application/astra-schedule",
  "version": "1.3",
  "name": "Backup Schedule",
  "enabled": "true",
  "granularity": "monthly",
  "minute": "0",
  "hour": "0",
  "dayOfMonth": "1",
  "snapshotRetention": "12",
  "backupRetention": "12"
}
```

Curl exemplo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v1/apps/<APP_ID>/schedules' --header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
--data @JSONinput
```

Clonar e restaurar um aplicativo

Clonar uma aplicação

É possível criar uma nova aplicação clonando uma aplicação existente.

Antes de começar

Observe o seguinte sobre este fluxo de trabalho:

- Não é utilizado um backup ou instantâneo da aplicação
- A operação de clone é executada no mesmo cluster
- O novo aplicativo é colocado em um namespace diferente



Para clonar um aplicativo para um cluster diferente, você precisa atualizar o `clusterId` parâmetro na entrada JSON conforme apropriado para o seu ambiente.

1. Selecione o aplicativo para clonar

Execute o fluxo de trabalho "[Liste as aplicações](#)" e selecione a aplicação que deseja clonar. Vários dos valores de recursos são necessários para a chamada REST usada para clonar o aplicativo.

2. Clonar a aplicação

Execute a seguinte chamada de API REST para clonar o aplicativo.

Método HTTP	Caminho
POST	/accounts/_id/k8s/v2/apps

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
JSON	Corpo	Sim	Fornecer os parâmetros para o aplicativo clonado. Veja o exemplo abaixo.

Exemplo de entrada JSON

```
{
  "type": "application/astra-app",
  "version": "2.0",
  "name": "mysql-clone",
  "clusterID": "30880586-d579-4d27-930f-a9633e59173b",
  "sourceClusterID": "30880586-d579-4d27-930f-a9633e59173b",
  "namespace": "mysql-ns",
  "sourceAppID": "e591ee59-ea90-4a9f-8e6c-d2b6e8647096"
}
```

Curl exemplo: Clonar um aplicativo

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v2/apps' --header
'Content-Type: application/astra-app+json' --header '*/*' --header
'Authorization: Bearer <API_TOKEN>' --data @JSONinput
```

Clonar um aplicativo a partir de um snapshot

Crie uma nova aplicação clonando-a a partir de um snapshot.

Antes de começar

Observe o seguinte sobre este fluxo de trabalho:

- É utilizado um instantâneo da aplicação
- A operação de clone é executada no mesmo cluster



Para clonar um aplicativo para um cluster diferente, você precisa atualizar o `clusterId` parâmetro na entrada JSON conforme apropriado para o seu ambiente.

1. Selecione o aplicativo para clonar

Execute o fluxo de trabalho "[Liste as aplicações](#)" e selecione a aplicação que deseja clonar. Vários dos valores de recursos são necessários para a chamada REST usada para clonar o aplicativo.

2. Selecione o instantâneo a utilizar

Execute o fluxo de trabalho "[Liste os instantâneos](#)" e selecione instantâneo que deseja usar.

3. Clonar a aplicação

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
POST	/accounts/_id/k8s/v2/apps

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
JSON	Corpo	Sim	Fornecer os parâmetros para o aplicativo clonado. Veja o exemplo abaixo.

Exemplo de entrada JSON

```
{
  "type": "application/astra-app",
  "version": "2.0",
  "name": "mysql-clone2",
  "clusterID": "30880586-d579-4d27-930f-a9633e59173b",
  "sourceClusterID": "30880586-d579-4d27-930f-a9633e59173b",
  "namespace": "mysql",
  "snapshotID": "e24515bd-a28e-4b28-b832-f3c74dbf32fb"
}
```

Curl exemplo: Clonar um aplicativo a partir de um snapshot

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v2/apps' --header
'Content-Type: application/astra-app+json' --header '*/*' --header
'Authorization: Bearer <API_TOKEN>' --data @JSONinput
```


Clonar um aplicativo a partir de um backup

Crie uma nova aplicação clonando-a a partir de um backup.

Antes de começar

Observe o seguinte sobre este fluxo de trabalho:

- Um backup de aplicativo é usado
- A operação de clone é executada no mesmo cluster



Para clonar um aplicativo para um cluster diferente, você precisa atualizar o `clusterId` parâmetro na entrada JSON conforme apropriado para o seu ambiente.

1. Selecione o aplicativo para clonar

Execute o fluxo de trabalho "[Liste as aplicações](#)" e selecione a aplicação que deseja clonar. Vários dos valores de recursos são necessários para a chamada REST usada para clonar o aplicativo.

2. Selecione a cópia de segurança a utilizar

Execute o fluxo de trabalho "[Liste os backups](#)" e selecione cópia de segurança que pretende utilizar.

3. Clonar a aplicação

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
POST	/accounts//k8s/v2/qpps

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
JSON	Corpo	Sim	Fornece os parâmetros para o aplicativo clonado. Veja o exemplo abaixo.

Exemplo de entrada JSON

```
{
  "type": "application/astra-app",
  "version": "2.0",
  "name": "mysql-clone3",
  "clusterID": "30880586-d579-4d27-930f-a9633e59173b",
  "sourceClusterID": "30880586-d579-4d27-930f-a9633e59173b",
  "namespace": "mysql",
  "backupID": "e24515bd-a28e-4b28-b832-f3c74dbf32fb"
}
```

Curl exemplo: Clonar um aplicativo a partir de um backup

```
curl --location -i --request POST
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v2/apps' --header
'Content-Type: application/astra-app+json' --header '*/*' --header
'Authorization: Bearer <API_TOKEN>' --data @JSONinput
```

Restaurar uma aplicação a partir de uma cópia de segurança

Você pode restaurar um aplicativo criando um novo aplicativo a partir de um backup.

1. Selecione a aplicação a restaurar

Execute o fluxo de trabalho "[Liste as aplicações](#)" e selecione a aplicação que deseja clonar. Vários dos valores de recursos são necessários para a chamada REST usada para restaurar o aplicativo.

2. Selecione a cópia de segurança a utilizar

Execute o fluxo de trabalho "[Liste os backups](#)" e selecione cópia de segurança que pretende utilizar.

3. Restaure a aplicação

Execute a seguinte chamada de API REST. Você deve fornecer o ID para um backup (como mostrado abaixo) ou snapshot.

Método HTTP	Caminho
COLOQUE	/accounts/_id/k8s/v2/apps//app_id

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
JSON	Corpo	Sim	Fornecer os parâmetros para o aplicativo clonado. Veja o exemplo abaixo.

Exemplo de entrada JSON

```
{
  "type": "application/astra-app",
  "version": "2.0",
  "backupID": "e24515bd-a28e-4b28-b832-f3c74dbf32fb"
}
```

Curl exemplo: Restaure um aplicativo no lugar a partir de um backup

```
curl --location -i --request PUT
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/k8s/v2/apps/<APP_ID>'
--header 'Content-Type: application/astra-app+json' --header '*/*'
--header 'ForceUpdate: true' --header 'Authorization: Bearer <API_TOKEN>'
--data @JSONinput
```

Namespaces

Liste os namespaces

Você pode listar os namespaces disponíveis.

1. Liste os namespaces

Execute a seguinte chamada de API REST para listar os namespaces.

Método HTTP	Caminho
OBTER	/accounts/_id/topology/v1/namespaces

Curl exemplo: Retorna todos os dados para todos os namespaces

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/namespaces'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'
```

Curl exemplo: Retorna nome, estado e ID de cluster para todos os namespaces

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/topology/v1/namespaces?include=name,namespaceState,clusterID' --header 'Accept: */*' --header
'Authorization: Bearer <API_TOKEN>'
```

Exemplo de saída JSON

```
{
  "items": [
    [
      "default",
      "discovered",
      "922f924a-a476-4a79-97f6-472571698154"
    ],
    [
      "kube-node-lease",
      "discovered",
      "922f924a-a476-4a79-97f6-472571698154"
    ],
    [
      "kube-public",
      "discovered",
      "922f924a-a476-4a79-97f6-472571698154"
    ],
    [
      "kube-system",
      "discovered",
      "922f924a-a476-4a79-97f6-472571698154"
    ],
    [
      "mysql",
      "discovered",
      "922f924a-a476-4a79-97f6-472571698154"
    ],
    [
      "mysql-clone1",
      "discovered",
      "922f924a-a476-4a79-97f6-472571698154"
    ],
    [
      "netapp-acc-operator",
      "discovered",
      "922f924a-a476-4a79-97f6-472571698154"
    ]
  ],
}
```

```

    [
      "openshift",
      "discovered",
      "922f924a-a476-4a79-97f6-472571698154"
    ],
    [
      "trident",
      "discovered",
      "922f924a-a476-4a79-97f6-472571698154"
    ]
  ],
  "metadata": {}
}

```

Suporte

Liste as notificações

Você pode listar as notificações de uma conta Astra específica. Você pode fazer isso como parte do monitoramento da atividade do sistema ou depuração de um problema.

1. Liste as notificações

Execute a seguinte chamada de API REST.

Método HTTP	Caminho
OBTER	/accounts/_id/core/v1/notificações

Parâmetros de entrada adicionais

Além dos parâmetros comuns com todas as chamadas de API REST, os seguintes parâmetros também são usados nos exemplos curl para esta etapa.

Parâmetro	Tipo	Obrigatório	Descrição
filtro	Consulta	Não	Opcionalmente, filtre as notificações que você deseja retornar na resposta.
incluir	Consulta	Não	Opcionalmente, selecione os valores que você deseja retornar na resposta.

Curl exemplo: Retornar todas as notificações

```

curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/notifications'
--header 'Accept: */*' --header 'Authorization: Bearer <API_TOKEN>'

```

Curl exemplo: Retorne a descrição para notificações com gravidade de aviso

```
curl --location -i --request GET
'https://astra.netapp.io/accounts/<ACCOUNT_ID>/core/v1/notifications?filter=severity%20eq%20'warning'&include=description' --header 'Accept: */*'
--header 'Authorization: Bearer <API_TOKEN>'
```

Exemplo de saída JSON

```
{
  "items": [
    [
      "Trident on cluster david-ie-00 has failed or timed out;
installation of the Trident operator failed or is not yet complete;
operator failed to reach an installed state within 300.00 seconds;
container trident-operator not found in operator deployment"
    ],
    [
      "Trident on cluster david-ie-00 has failed or timed out;
installation of the Trident operator failed or is not yet complete;
operator failed to reach an installed state within 300.00 seconds;
container trident-operator not found in operator deployment"
    ]
  ],
  "metadata": {}
}
```

Eliminar uma aplicação com falha

Talvez você não consiga remover um aplicativo gerenciado se ele tiver um backup ou snapshot em um estado com falha. Neste caso, você pode remover manualmente o aplicativo usando o fluxo de trabalho descrito abaixo.

1. Selecione a aplicação a eliminar

Execute o fluxo de trabalho ["Liste as aplicações"](#) e selecione a aplicação que pretende remover.

2. Liste os backups existentes para o aplicativo

Execute o fluxo de ["Liste os backups"](#) trabalho .

3. Exclua todos os backups

Exclua todos os backups de aplicativos executando o fluxo de trabalho ["Eliminar uma cópia de segurança"](#) para cada backup na lista.

4. Liste os instantâneos existentes para o aplicativo

Execute o fluxo de "[Liste os instantâneos](#)"trabalho .

5. Eliminar todos os instantâneos

Execute o fluxo de trabalho "[Eliminar um instantâneo](#)"de cada instantâneo na lista.

6. Remova a aplicação

Execute o fluxo de trabalho "[Desgerenciar um aplicativo](#)" para remover a aplicação.

Usando Python

O NetApp já está disponível

O NetApp é um pacote de código aberto que você pode usar para automatizar uma implantação do Astra Control. O pacote também é um recurso valioso para aprender sobre a API REST do Astra Control, talvez como parte da criação de sua própria plataforma de automação.



Para simplificar, o SDK do NetApp será referido como o **SDK** ao longo do restante desta página.

Duas ferramentas de software relacionadas

O SDK inclui duas ferramentas diferentes, embora relacionadas, que operam em diferentes níveis de abstração ao acessar a API REST do Astra Control.

SDK do Astra

O Astra SDK fornece a funcionalidade principal da plataforma. Ele inclui um conjunto de classes Python que abstraem as chamadas de API REST subjacentes. As classes dão suporte a ações administrativas em vários recursos do Astra Control, incluindo aplicações, backups, snapshots e clusters.

O Astra SDK é uma parte do pacote e é fornecido em um único `astraSDK.py` arquivo. Você pode importar esse arquivo para o seu ambiente e usar as classes diretamente.



O **NetApp** é o nome de todo o pacote. O ***Astra SDK** refere-se às classes Python principais no único arquivo `astraSDK.py`.

Script do Toolkit

Além do arquivo Astra SDK, o `toolkit.py` script também está disponível. Este script opera em um nível mais alto de abstração, fornecendo acesso a ações administrativas discretas definidas internamente como funções Python. O script importa o Astra SDK e faz chamadas para as classes conforme necessário.

Como aceder

Você pode acessar o SDK das seguintes maneiras.

Pacote Python

O SDK está disponível em "[Índice do Pacote Python](#)" sob o nome **actoolkit**. O pacote recebe um número de versão e continuará a ser atualizado conforme necessário. Você deve usar o utilitário de gerenciamento de pacotes **PIP** para instalar o pacote em seu ambiente.

Uma vez instalado, as classes `astraSDK.py` podem ser utilizadas colocando `import astraSDK` em seus scripts. Além disso, `actoolkit` pode ser invocado diretamente no seu prompt de comando e é equivalente a `toolkit.py` (`actoolkit list clusters` é igual a `./toolkit.py list clusters`a`).

Consulte "[PyPI: NetApp é um dos nossos selecionados Jogos de Plataforma](#)" para obter mais informações.

Código-fonte do GitHub

O código-fonte do SDK também está disponível no GitHub. O repositório inclui o seguinte:

- `astraSDK.py` (Astra SDK com classes Python)
- `toolkit.py` (script baseado em funções de nível superior)
- Requisitos e instruções de instalação detalhadas
- Scripts de instalação
- Documentação adicional

Você pode clonar o "[GitHub: NetApp/NetApp-astra-toolkits](#)" repositório para o seu ambiente local.

Instalação e requisitos básicos

Existem várias opções e requisitos a considerar como parte da instalação do pacote e preparação para usá-lo.

Resumo das opções de instalação

Você pode instalar o SDK de uma das seguintes maneiras:

- Use a imagem preparada "[Docker: Kits de ferramentas NetApp/astra](#)", que tem todas as dependências necessárias instaladas, incluindo `actoolkit`
- Use o PIP para instalar o `actoolkit` pacote do PyPI em seu ambiente Python
- Clone o repositório do GitHub e copie/modifique os dois arquivos Python principais para que eles estejam acessíveis ao seu código de cliente Python

Consulte as páginas PyPI e GitHub para obter mais informações.

Requisitos para o ambiente Astra Control

Seja usando diretamente as classes Python no Astra SDK ou as funções no `toolkit.py` script, você estará acessando a API REST em uma implantação do Astra Control. Por causa disso, você precisará de uma conta Astra juntamente com um token de API. Consulte "[Antes de começar](#)" e as outras páginas na seção **Introdução** desta documentação para obter mais informações.

Requisitos para o SDK Python do NetApp

O SDK tem vários pré-requisitos relacionados ao ambiente Python local. Por exemplo, você deve usar Python 3,8 ou posterior. Além disso, existem vários pacotes Python que são necessários. Consulte a página do repositório do GitHub ou a página do pacote PyPI para obter mais informações.

Resumo dos recursos úteis

Aqui estão alguns dos recursos que você precisará para começar.

- "[PyPI: NetApp é um dos nossos selecionados Jogos de Plataforma](#)"
- "[GitHub: NetApp/NetApp-astra-toolkits](#)"
- "[Docker: Kits de ferramentas NetApp/astra](#)"

Python nativo

Antes de começar

Python é uma linguagem de desenvolvimento popular para automação de data center. Antes de usar os recursos nativos do Python juntamente com vários pacotes comuns, você precisa preparar o ambiente e os arquivos de entrada necessários.



Além de acessar a API REST do Astra Control diretamente usando Python, o NetApp também fornece um pacote de kit de ferramentas que abstrai a API e remove algumas das complexidades. Consulte "[O NetApp já está disponível](#)" para obter mais informações.

Prepare o ambiente

Os requisitos básicos de configuração para executar os scripts Python são descritos abaixo.

Python 3

Você precisa ter a versão mais recente do Python 3 instalada.

Bibliotecas adicionais

As bibliotecas **requests** e **urllib3** devem ser instaladas. Você pode usar o pip ou outra ferramenta de gerenciamento Python conforme apropriado para o seu ambiente.

Acesso à rede

A estação de trabalho onde os scripts são executados deve ter acesso à rede e ser capaz de alcançar o Astra Control. Ao usar o Astra Control Service, você deve estar conectado à Internet e ser capaz de se conectar ao serviço em <https://astra.netapp.io>.

Informações de identidade

Você precisa de uma conta Astra válida com o identificador de conta e token de API. Consulte "[Obtenha um token de API](#)" para obter mais informações.

Crie os arquivos de entrada JSON

Os scripts Python dependem de informações de configuração contidas em arquivos de entrada JSON. Os arquivos de amostra são fornecidos abaixo.



Você precisa atualizar as amostras conforme apropriado para o seu ambiente.

Informações de identidade

O arquivo a seguir contém o token de API e a conta Astra. Você precisa passar esse arquivo para scripts Python usando o `-i` parâmetro CLI (ou `--identity`).

```
{
  "api_token": "kH4CA_uVIa8q9UuPzhJaAHaG1aR7-no901DkkrVjIXk=",
  "account_id": "5131dfdf-03a4-5218-ad4b-fe84442b9786"
}
```

Liste as aplicações

Você pode usar o script a seguir para listar os aplicativos da sua conta Astra.



"Antes de começar" Consulte para obter um exemplo do arquivo de entrada JSON necessário.

```
#!/usr/bin/env python3
##-----
-----
#
# Usage: python3 list_man_apps.py -i identity_file.json
#
# (C) Copyright 2022 NetApp, Inc.
#
# This sample code is provided AS IS, with no support or warranties of
# any kind, including but not limited for warranties of merchantability
# or fitness of any kind, expressed or implied. Permission to use,
# reproduce, modify and create derivatives of the sample code is granted
# solely for the purpose of researching, designing, developing and
# testing a software application product for use with NetApp products,
# provided that the above copyright notice appears in all copies and
# that the software application product is distributed pursuant to terms
# no less restrictive than those set forth herein.
#
##-----
-----

import argparse
import json
import requests
import urllib3
import sys

# Global variables
api_token = ""
account_id = ""

def get_managed_apps():
    ''' Get and print the list of apps '''

    # Global variables
    global api_token
    global account_id

    # Create an HTTP session
    sess1 = requests.Session()
```

```

# Suppress SSL unsigned certificate warning
urllib3.disable_warnings(urllib3.exceptions.InsecureRequestWarning)

# Create URL
url1 = "https://astra.netapp.io/accounts/" + account_id +
"/k8s/v2/apps"

# Headers and response output
req_headers = {}
resp_headers = {}
resp_data = {}

# Prepare the request headers
req_headers.clear
req_headers['Authorization'] = "Bearer " + api_token
req_headers['Content-Type'] = "application/astra-app+json"
req_headers['Accept'] = "application/astra-app+json"

# Make the REST call
try:
    resp1 = sess1.request('get', url1, headers=req_headers,
allow_redirects=True, verify=False)

except requests.exceptions.ConnectionError:
    print("Connection failed")
    sys.exit(1)

# Retrieve the output
http_code = resp1.status_code
resp_headers = resp1.headers

# Print the list of apps
if resp1.ok:
    resp_data = json.loads(resp1.text)
    items = resp_data['items']
    for i in items:
        print(" ")
        print("Name: " + i['name'])
        print("ID: " + i['id'])
        print("State: " + i['state'])
else:
    print("Failed with HTTP status code: " + str(http_code))

print(" ")

```

```

# Close the session
sess1.close()

return

def read_id_file(idf):
    ''' Read the identity file and save values '''

    # Global variables
    global api_token
    global account_id

    with open(idf) as f:
        data = json.load(f)

    api_token = data['api_token']
    account_id = data['account_id']

    return

def main(args):
    ''' Main top level function '''

    # Global variables
    global api_token
    global account_id

    # Retrieve name of JSON input file
    identity_file = args.id_file

    # Get token and account
    read_id_file(identity_file)

    # Issue REST call
    get_managed_apps()

    return

def parseArgs():
    ''' Parse the CLI input parameters '''

    parser = argparse.ArgumentParser(description='Astra REST API -
List the apps',
                                   add_help = True)
    parser.add_argument("-i", "--identity", action="store", dest
="id_file", default=None,
                        help='(Req) Name of the identity input file',

```

```
required=True)

    return parser.parse_args()

if __name__ == '__main__':
    ''' Begin here '''

    # Parse input parameters
    args = parseArgs()

    # Call main function
    main(args)
```

Referência da API

Overview

The Astra Control REST API reference documentation contains the details of all the REST API calls, including the endpoints, HTTP methods, input parameters, and responses. This complete reference is helpful when developing automation applications using the API.

The Astra REST API provides CRUD (Create-Read-Update-Delete) access to all the Astra Control resources except where noted for a specific resource category. This reference documentation applies to the 23.06 release of Astra Control REST API.

ASUP

ASUP overview

The ASUP API provides access to ASUP resources in order to create and optionally upload the AutoSupport bundles.

Create a new ASUP resource

POST `/accounts/{account_id}/core/v1/asups`

Indicates the desired values for the ASUP API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates the desired values for the ASUP API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-asup"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
upload	string	True	JSON string containing a value indicating whether to upload the AutoSupport bundle after successful creation. Defined values are: <ul style="list-style-type: none"> "true" - Upload the AutoSupport bundle. "false" - Do not upload the AutoSupport bundle.
dataWindowStart	string	False	JSON string containing a timestamp indicating the start time of the AutoSupport bundle data collection window. Defaults to 24 hours before the "dataWindowEnd" key value. Must occur before the "dataWindowEnd" key value. Maximum is 7 days before the current time of the request. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
dataWindowEnd	string	False	JSON string containing a timestamp indicating the end time of the AutoSupport bundle data collection window. Defaults to the current time of the request. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
metadata	type_astra_metadata	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example request

```
{
  "type": "application/astra-asup",
  "version": "1.0",
  "upload": "true"
}
```

Response

Status: 201, Returns the newly created asup resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "application/astra-asup"
version	string	True	<p>Version of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "1.0"

Name	Type	Required	Description
id	string	True	<p>Globally unique identifier of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
creationState	string	True	<p>JSON string containing a value indicating the creation state of the AutoSupport bundle. For "completed" and "partial" states, the bundle can be downloaded by performing a GET of the resource URI with an Accept header containing "/" or "application/gzip".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "running" - AutoSupport bundle generation is running normally. • "completed" - AutoSupport bundle generation has completed. • "partial" - AutoSupport bundle generation has completed but some data was not included in the bundle. • "failed" - AutoSupport bundle generation is in a permanent failure state.
creationStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about why "creationState" transitioned into "partial" or "failed".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
upload	string	True	<p>JSON string containing a value indicating whether to upload the AutoSupport bundle after successful creation.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "true" - Upload the AutoSupport bundle.• "false" - Do not upload the AutoSupport bundle.

Name	Type	Required	Description
uploadState	string	False	<p>JSON string containing a value that indicates the state of the AutoSupport bundle upload if it was requested.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - AutoSupport bundle upload is scheduled for when AutoSupport bundle creation completes ("creationState" is "running"). • "blocked" - AutoSupport bundle upload was not attempted because the bundle was not created ("creationState" is "failed") or upload was blocked because there is no license. • "running" - AutoSupport bundle upload is running normally ("creationState" is "completed" or "partial"). • "completed" - AutoSupport bundle upload has completed. • "failed" - AutoSupport bundle upload is in a permanent failure state.

Name	Type	Required	Description
uploadStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why "uploadState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
triggerType	string	True	<p>JSON string containing a value that indicates what triggered the creation of the ASUP resource. Defined values are:</p> <ul style="list-style-type: none"> • "manual" - The ASUP resource and associated AutoSupport bundle were created manually. • "scheduled" - The ASUP resource and associated AutoSupport bundle were created according to a configured schedule.
dataWindowStart	string	True	<p>JSON string containing a timestamp indicating the start time of the AutoSupport bundle data collection window. Defaults to 24 hours before the "dataWindowEnd" key value. Must occur before the "dataWindowEnd" key value. Maximum is 7 days before the current time of the request. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
dataWindowEnd	string	True	<p>JSON string containing a timestamp indicating the end time of the AutoSupport bundle data collection window. Defaults to the current time of the request. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-asup",
  "version": "1.0",
  "id": "9950003f-a1c7-5ca7-8930-06eec25f60aa",
  "creationState": "running",
  "creationStateDetails": [],
  "upload": "true",
  "uploadState": "pending",
  "uploadStateDetails": [],
  "triggerType": "manual",
  "dataWindowStart": "2020-08-05T12:24:00.000000Z",
  "dataWindowEnd": "2020-08-06T12:24:52.000000Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all ASUP resources

GET /accounts/{account_id}/core/v1/asups

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p>
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: asup_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-asups",
  "version": "1.0",
  "items": [
    {
      "type": "application/astra-asup",
      "version": "1.0",
      "id": "80796606-79ba-480b-966c-e4c600fbf623",
      "creationState": "completed",
      "creationStateDetails": [],
      "upload": "true",
      "uploadState": "running",
      "uploadStateDetails": [],
      "triggerType": "manual",
      "dataWindowStart": "2020-08-05T12:24:00.000000Z",
      "dataWindowEnd": "2020-08-06T12:24:52.000000Z",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "1b32a508-cc6f-4f1b-809f-c42fd91b4848"
      }
    },
    {
      "type": "application/astra-asup",
      "version": "1.0",
      "id": "6503131d-8b36-4434-b34f-73661ae8100b",
      "creationState": "completed",
      "creationStateDetails": [],
      "upload": "true",
      "uploadState": "completed",
      "uploadStateDetails": [],
      "triggerType": "scheduled",
      "dataWindowStart": "2020-08-04T13:30:00.000000Z",
      "dataWindowEnd": "2020-08-05T13:30:00.000000Z",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-05T13:30:00.012321Z",
        "modificationTimestamp": "2020-08-05T13:30:00.012321Z",
        "createdBy": "1b32a508-cc6f-4f1b-809f-c42fd91b4848"
      }
    }
  ],
  "metadata": {
```

```
"labels": [],
"creationTimestamp": "2022-10-06T20:58:16.305662Z",
"modificationTimestamp": "2022-10-06T20:58:16.305662Z",
"createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Name	Type	Required	Description
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

asup_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-asup"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
creationState	string	True	JSON string containing a value indicating the creation state of the AutoSupport bundle. For "completed" and "partial" states, the bundle can be downloaded by performing a GET of the resource URI with an Accept header containing "/" or "application/gzip". Defined values are: <ul style="list-style-type: none"> • "running" - AutoSupport bundle generation is running normally. • "completed" - AutoSupport bundle generation has completed. • "partial" - AutoSupport bundle generation has completed but some data was not included in the bundle. • "failed" - AutoSupport bundle generation is in a permanent failure state.

Name	Type	Required	Description
creationStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects that lists additional details about why "creationState" transitioned into "partial" or "failed".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
upload	string	True	<p>JSON string containing a value indicating whether to upload the AutoSupport bundle after successful creation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Upload the AutoSupport bundle. • "false" - Do not upload the AutoSupport bundle.

Name	Type	Required	Description
uploadState	string	False	<p>JSON string containing a value that indicates the state of the AutoSupport bundle upload if it was requested.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - AutoSupport bundle upload is scheduled for when AutoSupport bundle creation completes ("creationState" is "running"). • "blocked" - AutoSupport bundle upload was not attempted because the bundle was not created ("creationState" is "failed") or upload was blocked because there is no license. • "running" - AutoSupport bundle upload is running normally ("creationState" is "completed" or "partial"). • "completed" - AutoSupport bundle upload has completed. • "failed" - AutoSupport bundle upload is in a permanent failure state.

Name	Type	Required	Description
uploadStateDetails	array[type_astra_stateDe tail]	False	<p>JSON array of JSON objects that lists additional details about why "uploadState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
triggerType	string	True	<p>JSON string containing a value that indicates what triggered the creation of the ASUP resource. Defined values are:</p> <ul style="list-style-type: none"> • "manual" - The ASUP resource and associated AutoSupport bundle were created manually. • "scheduled" - The ASUP resource and associated AutoSupport bundle were created according to a configured schedule.
dataWindowStart	string	True	<p>JSON string containing a timestamp indicating the start time of the AutoSupport bundle data collection window. Defaults to 24 hours before the "dataWindowEnd" key value. Must occur before the "dataWindowEnd" key value. Maximum is 7 days before the current time of the request. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
dataWindowEnd	string	True	JSON string containing a timestamp indicating the end time of the AutoSupport bundle data collection window. Defaults to the current time of the request. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

Retrieve an ASUP resource

GET /accounts/{account_id}/core/v1/asups/{asup_id}

Returns the stored ASUP API resource in the JSON response body. If the AutoSupport bundle "creationState" is "completed" or "partial", the AutoSupport bundle can be downloaded by specifying an Accept header containing "/" or "application/gzip".

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
asup_id	string	path	True	ID of the asup collection to list

Response

Status: 200, Returns the stored ASUP API resource in the JSON response body. If the AutoSupport bundle "creationState" is "completed" or "partial", the AutoSupport bundle can be downloaded by specifying an Accept header containing "*/*" or "application/gzip".

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-asup"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"

Name	Type	Required	Description
id	string	True	<p>Globally unique identifier of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
creationState	string	True	<p>JSON string containing a value indicating the creation state of the AutoSupport bundle. For "completed" and "partial" states, the bundle can be downloaded by performing a GET of the resource URI with an Accept header containing "/" or "application/gzip".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "running" - AutoSupport bundle generation is running normally. • "completed" - AutoSupport bundle generation has completed. • "partial" - AutoSupport bundle generation has completed but some data was not included in the bundle. • "failed" - AutoSupport bundle generation is in a permanent failure state.
creationStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about why "creationState" transitioned into "partial" or "failed".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
upload	string	True	<p>JSON string containing a value indicating whether to upload the AutoSupport bundle after successful creation.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "true" - Upload the AutoSupport bundle.• "false" - Do not upload the AutoSupport bundle.

Name	Type	Required	Description
uploadState	string	False	<p>JSON string containing a value that indicates the state of the AutoSupport bundle upload if it was requested.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - AutoSupport bundle upload is scheduled for when AutoSupport bundle creation completes ("creationState" is "running"). • "blocked" - AutoSupport bundle upload was not attempted because the bundle was not created ("creationState" is "failed") or upload was blocked because there is no license. • "running" - AutoSupport bundle upload is running normally ("creationState" is "completed" or "partial"). • "completed" - AutoSupport bundle upload has completed. • "failed" - AutoSupport bundle upload is in a permanent failure state.

Name	Type	Required	Description
uploadStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why "uploadState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
triggerType	string	True	<p>JSON string containing a value that indicates what triggered the creation of the ASUP resource. Defined values are:</p> <ul style="list-style-type: none"> • "manual" - The ASUP resource and associated AutoSupport bundle were created manually. • "scheduled" - The ASUP resource and associated AutoSupport bundle were created according to a configured schedule.
dataWindowStart	string	True	<p>JSON string containing a timestamp indicating the start time of the AutoSupport bundle data collection window. Defaults to 24 hours before the "dataWindowEnd" key value. Must occur before the "dataWindowEnd" key value. Maximum is 7 days before the current time of the request. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
dataWindowEnd	string	True	<p>JSON string containing a timestamp indicating the end time of the AutoSupport bundle data collection window. Defaults to the current time of the request. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-asup",
  "version": "1.0",
  "id": "9950003f-a1c7-5ca7-8930-06eec25f60aa",
  "creationState": "completed",
  "creationStateDetails": [],
  "upload": "false",
  "triggerType": "manual",
  "dataWindowStart": "2020-08-05T12:24:00.000000Z",
  "dataWindowEnd": "2020-08-06T12:24:52.000000Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Account

Account overview

The Account API represents isolated tenants in a multitenant system.

Create a new account

POST /accounts

Indicates the desired values for the Account API resource to be created.

Request Body

Indicates the desired values for the Account API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-account"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
name	string	True	JSON string containing a name for the account. Defined values are: <ul style="list-style-type: none">Minimum length: 1Maximum length: 63This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-account",
  "version": "1.0",
  "name": "Testing 123"
}
```

Response

Status: 201, Returns the newly created account resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> "application/astra-account"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the account. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 63 This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
state	string	True	JSON string containing a value indicating the operational state of the account. Defined values are: <ul style="list-style-type: none"> "pending" - Changes can only be made to user and role resources under the account (default value) "active" - Changes can be made to any resource under the account "deletePending" - Users cannot log in, data protection operations are suspended, charges no longer accrue

Name	Type	Required	Description
isEnabled	string	True	<p>JSON string indicating the account is enabled. Defined values are:</p> <ul style="list-style-type: none"> • "false" - Users are not permitted to use this account • "true" - Users are permitted to use this account
enabledTimestamp	string	False	<p>JSON string containing the timestamp indicating when the account was last enabled. If the account has never been enabled, this field is absent. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
accountContact	accountContact	False	<p>JSON object containing user contact information to create an owner user at the time of account activation.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-account",
  "version": "1.0",
  "id": "666a3f38-d4fa-5b62-a391-a69029758d32",
  "name": "fraught-pines",
  "state": "pending",
  "isEnabled": "false",
  "enabledTimestamp": "2020-08-06T12:24:52.256624Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

postalAddress

JSON object containing a collection of JSON strings specifying an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained JSON strings will be present. If you provide nothing, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2

Name	Type	Required	Description
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and more. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

accountContact

JSON object containing user contact information to create an owner user at the time of account activation.

Name	Type	Required	Description
firstName	string	True	JSON string containing a user specified long-form first name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
lastName	string	True	JSON string containing a user specified long-form last name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
companyName	string	False	JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
email	string	True	JSON strings containing a user specified email address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
phone	string	False	JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
postalAddress	postalAddress	True	JSON object containing a collection of JSON strings specifying an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained JSON strings will be present. If you provide nothing, the string will be empty.

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field

Name	Type	Required	Description
reason	string	True	Reason why the request body field is invalid

List all accounts

GET /accounts

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id"
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata=""></continue> OpenAPI examples: "<continue token="" from="" collection="" metadata=""></continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: account_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-accounts",
  "version": "1.0",
  "items": [
    {
      "type": "application/astra-account",
      "version": "1.0",
      "id": "70796606-79ba-480b-966c-e4c600fbf622",
      "name": "fraught-pines",
      "state": "active",
      "isEnabled": "true",
      "enabledTimestamp": "2020-08-06T12:24:52.256624Z",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "1723a17e-9fd1-4636-86e1-2ec9e04bce51"
      }
    },
    {
      "type": "application/astra-account",
      "version": "1.0",
      "id": "7976114d-35ec-48a7-ba31-22d8e94a8bb2",
      "name": "sad-dino",
      "state": "active",
      "isEnabled": "true",
      "enabledTimestamp": "2020-08-06T12:24:52.256624Z",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "1723a17e-9fd1-4636-86e1-2ec9e04bce51"
      }
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of JSON strings specifying an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained JSON strings will be present. If you provide nothing, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 31

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and more. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

accountContact

JSON object containing user contact information to create an owner user at the time of account activation.

Name	Type	Required	Description
firstName	string	True	JSON string containing a user specified long-form first name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
email	string	True	<p>JSON strings containing a user specified email address.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
phone	string	False	JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
postalAddress	postalAddress	True	JSON object containing a collection of JSON strings specifying an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained JSON strings will be present. If you provide nothing, the string will be empty.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	

Name	Type	Required	Description
modifiedBy	string	False	

account_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-account"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the account. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the account.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - Changes can only be made to user and role resources under the account (default value) • "active" - Changes can be made to any resource under the account • "deletePending" - Users cannot log in, data protection operations are suspended, charges no longer accrue
isEnabled	string	True	<p>JSON string indicating the account is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "false" - Users are not permitted to use this account • "true" - Users are permitted to use this account
enabledTimestamp	string	False	<p>JSON string containing the timestamp indicating when the account was last enabled.</p> <p>If the account has never been enabled, this field is absent.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
accountContact	accountContact	False	JSON object containing user contact information to create an owner user at the time of account activation.
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

Retrieve an account

GET /accounts/{account_id}

Returns the stored Account API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the account collection to list <ul style="list-style-type: none"> example: <code>{{.Account}}</code>

Response

Status: 200, Returns the stored Account API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-account"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a name for the account. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
state	string	True	<p>JSON string containing a value indicating the operational state of the account. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - Changes can only be made to user and role resources under the account (default value) • "active" - Changes can be made to any resource under the account • "deletePending" - Users cannot log in, data protection operations are suspended, charges no longer accrue
isEnabled	string	True	<p>JSON string indicating the account is enabled. Defined values are:</p> <ul style="list-style-type: none"> • "false" - Users are not permitted to use this account • "true" - Users are permitted to use this account

Name	Type	Required	Description
enabledTimestamp	string	False	<p>JSON string containing the timestamp indicating when the account was last enabled.</p> <p>If the account has never been enabled, this field is absent.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
accountContact	accountContact	False	<p>JSON object containing user contact information to create an owner user at the time of account activation.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-account",
  "version": "1.0",
  "id": "666a3f38-d4fa-5b62-a391-a69029758d32",
  "name": "fraught-pines",
  "state": "active",
  "isEnabled": "true",
  "enabledTimestamp": "2020-08-06T12:24:52.256624Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of JSON strings specifying an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained JSON strings will be present. If you provide nothing, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 31

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and more. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

accountContact

JSON object containing user contact information to create an owner user at the time of account activation.

Name	Type	Required	Description
firstName	string	True	JSON string containing a user specified long-form first name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
email	string	True	<p>JSON strings containing a user specified email address.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
phone	string	False	JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
postalAddress	postalAddress	True	JSON object containing a collection of JSON strings specifying an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained JSON strings will be present. If you provide nothing, the string will be empty.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	

Name	Type	Required	Description
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify an account

PUT /accounts/{account_id}

Replaces the entire stored resource with the supplied JSON request body while preserving the key values that are not user-modifiable.

Side Effects

- Changing "isEnabled" from "false" to "true" sets "enabledTimestamp" to the current time.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the account collection to list <ul style="list-style-type: none"> • example: <code>{{.Account}}</code>

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving the key values that are not user-modifiable.

Side Effects

- Changing "isEnabled" from "false" to "true" sets "enabledTimestamp" to the current time.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-account"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	False	JSON string containing a name for the account. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the account.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - Changes can only be made to user and role resources under the account (default value) • "active" - Changes can be made to any resource under the account • "deletePending" - Users cannot log in, data protection operations are suspended, charges no longer accrue
isEnabled	string	False	<p>JSON string indicating the account is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "false" - Users are not permitted to use this account • "true" - Users are permitted to use this account
enabledTimestamp	string	False	<p>JSON string containing the timestamp indicating when the account was last enabled.</p> <p>If the account has never been enabled, this field is absent.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
accountContact	accountContact	False	JSON object containing user contact information to create an owner user at the time of account activation.
metadata	type_astra_metadata_update	False	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-account",
  "version": "1.0",
  "name": "frightened-pine"
}
```

Response

Status: 204, Indicates if the account resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of JSON strings specifying an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained JSON strings will be present. If you provide nothing, the string will be empty.

Name	Type	Required	Description
addressCountry	string	False	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	False	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	False	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	False	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 31

Name	Type	Required	Description
streetAddress1	string	False	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and more. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

accountContact

JSON object containing user contact information to create an owner user at the time of account activation.

Name	Type	Required	Description
firstName	string	False	JSON string containing a user specified long-form first name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
lastName	string	False	<p>JSON string containing a user specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
email	string	False	<p>JSON strings containing a user specified email address.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
phone	string	False	JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
postalAddress	postalAddress	False	JSON object containing a collection of JSON strings specifying an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained JSON strings will be present. If you provide nothing, the string will be empty.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	

Name	Type	Required	Description
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete an account

DELETE /accounts/{account_id}

Removes the specified Account API resource.

Side Effects

- "deletePending" is set to "true" and the account can no longer be accessed.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the account collection to list <ul style="list-style-type: none"> • example: <code>{{.Account}}</code>

Response

Status: 204, Indicates if the account resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

App

App overview

The App API represents Kubernetes applications, including those unmanaged by Astra.

Create a new app for a managed cluster

POST /accounts/{account_id}/topology/v2/managedClusters/{managedCluster_id}/apps

Indicates the desired values for the App API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
managedCluster_id	string	path	True	ID of the containing managedCluster resource

Request Body

Indicates the desired values for the App API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-app"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "2.0" "2.1" "2.2"
name	string	True	JSON string containing a name for the application. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 63 This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
clusterScopedResources	array[clusterScopedResources]	False	JSON array of JSON objects describing the cluster-scoped resources that are part of this app
namespaceScopedResources	array[namespaceScopedResources]	False	JSON array of JSON objects describing the resources that are part of this app
namespaceMapping	array[namespaceMapping]	False	JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation. Defined values are: <ul style="list-style-type: none"> • Minimum Items: 0
storageClassMapping	array[storageClassMapping]	False	JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used. Defined values are: <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot.</p> <p>When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail.</p> <p>Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on.</p> <p>Only returned if the application was cloned from another cluster.</p> <p>When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-app",
  "version": "2.2",
  "name": "jenkins",
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "namespaceScopedResources": [
    {
      "namespace": "production"
    }
  ]
}
```

Response

Status: 201, Returns the newly created app resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-app"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "2.0" "2.1" "2.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.
name	string	True	JSON string containing a name for the application. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 63 This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. Conforms to the DNS 1123 Label Schema
clusterScopedResources	array[clusterScopedResources]	False	JSON array of JSON objects describing the cluster-scoped resources that are part of this app

Name	Type	Required	Description
namespaceScopedResources	array[namespaceScopedResources]	True	JSON array of JSON objects describing the resources that are part of this app
lastResourceCollectionTimestamp	string	False	<p>JSON string containing the timestamp when the last resource collection was performed. This field is unset if no resource collection has been performed for this application yet. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application is scheduled for discovery • "discovering" - The application is in the process of being discovered • "provisioning" - The application is in the process of being provisioned • "ready" - The application is running normally • "failed" - The application is in a permanent failure state • "restoring" - The application is being restored from backup or snapshot • "unavailable" - The application is not currently accessible • "unknown" - The application state cannot be determined • "deleting" - The application is in the process of being deleted

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state.</p> <p>Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The application has a protection policy defined and is in conformance with that policy • "partial" - The application has a protection policy defined, but is out of conformance with that policy • "none" - The application does not have a protection policy defined • "atRisk" - The default storage class on the cluster does not support snapshots, the application is at risk of gaining an unsupported volume
protectionStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
appDetectedType	string	False	<p>JSON string that uniquely represents the specific type of application that is detected.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "system" - The application contains a resource that identifies it as part of the Kubernetes environment • "acc" - The application contains resources that identify it as an Astra Control Center instance
namespaces	array[string]	True	<p>JSON array of JSON strings containing the names of the namespaces in which the application is running.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
namespaceMapping	array[namespaceMapping]	False	<p>JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
storageClassMapping	array[storageClassMapping]	False	<p>JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
clusterName	string	False	<p>JSON string containing the name of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p>
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "gke" - Kubernetes hosted on Google Kubernetes Engine (GKE)• "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service (AKS)• "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service (Amazon EKS)• "openshift" - The cluster is of type OpenShift• "kubernetes" - The cluster is generic Kubernetes

Name	Type	Required	Description
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot.</p> <p>When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail.</p> <p>Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterName	string	False	<p>JSON string containing the name of the cluster the application was previously running on. Only returned if the application was cloned from another cluster.</p>

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on.</p> <p>Only returned if the application was cloned from another cluster.</p> <p>When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicationSourceAppID	string	False	<p>JSON string containing the ID of the application that is being replicated to this application.</p> <p>Only returned if the application is currently the destination in an AppMirror relationship, and the relationship is not in the failedOver state. When the relationship is in the failedOver state, this field is not returned.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-app",
  "version": "2.2",
  "id": "39c1c79f-efab-5357-88fb-20e628c4dd96",
  "links": [],
  "name": "jenkins",
  "namespaceScopedResources": [
    {
      "namespace": "production",
      "labelSelectors": []
    }
  ],
  "state": "pending",
  "stateDetails": [],
  "protectionState": "none",
  "protectionStateDetails": [],
  "namespaces": [
    "production"
  ],
  "clusterName": "GKE-22",
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "clusterType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

- This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
group	string	True	JSON string containing a group identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources
kind	string	True	JSON string containing a kind identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources
version	string	True	JSON string containing a version identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources

clusterScopedResources

Name	Type	Required	Description
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind. <ul style="list-style-type: none">• This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector for the cluster-scoped GroupVersionKinds (GVKs) within the cluster. If this is empty, then all GVK instances on the cluster are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

namespaceScopedResources

Name	Type	Required	Description
namespace	string	True	<p>JSON string containing the name of a namespace in which the application is defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"] — Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"] — Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"] — Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"] — Select all resources that have a label named app • ["!app"] — Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

namespaceMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the namespace on the source cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
destination	string	True	<p>JSON string containing the name of the namespace on the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

storageClassMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the source storage class. Can also be '*' to specify all source storage classes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema if Storage Class name is used • '*' to specify all storage classes

Name	Type	Required	Description
destination	string	True	<p>JSON string containing the name of the destination storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema

GVKN

Name	Type	Required	Description
group	string	False	<p>JSON string containing a group identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
version	string	False	<p>JSON string containing a version identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
kind	string	False	<p>JSON string containing a kind identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources

Name	Type	Required	Description
namespaces	array[string]	False	<p>JSON array of JSON strings describing namespaces to include or exclude resources from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
names	array[string]	False	<p>JSON array of JSON strings describing Kubernetes resource names to include or exclude from the selective restore.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings describing Kubernetes label selectors used to include or exclude resources from the selective restore.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	True	JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.

Name	Type	Required	Description
GVKN	array[GVKN]	True	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	

Name	Type	Required	Description
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

namespaceScopedResources

Name	Type	Required	Description
namespace	string	True	<p>JSON string containing the name of a namespace in which the application is defined. Defined values are:</p> <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 253• Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	True	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"] — Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"] — Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"] — Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"] — Select all resources that have a label named app • ["!app"] — Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

l
"app=mysql,version=
2"] — Select all
resources that have

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	False	JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.

Name	Type	Required	Description
GVKN	array[GVKN]	False	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the apps for a managed cluster

GET /accounts/{account_id}/topology/v2/managedClusters/{managedCluster_id}/apps

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name,state
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: app_2.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-apps",
  "version": "2.2",
  "items": [
    [
      "2ff50f4b-fe40-4980-913f-8a4469184822",
      "mysql",
      "ready"
    ],
    [
      "ae1e6561-9e22-406c-8a5a-762f4604da00",
      "jenkins",
      "ready"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

GVK

JSON object containing a Kubernetes group/version/kind.

- This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
group	string	True	JSON string containing a group identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources

Name	Type	Required	Description
kind	string	True	JSON string containing a kind identifier assigned by Kubernetes. <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources
version	string	True	JSON string containing a version identifier assigned by Kubernetes. <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources

clusterScopedResources

Name	Type	Required	Description
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind. <ul style="list-style-type: none"> This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector for the cluster-scoped GroupVersionKinds (GVKs) within the cluster. If this is empty, then all GVK instances on the cluster are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

namespaceScopedResources

Name	Type	Required	Description
namespace	string	True	<p>JSON string containing the name of a namespace in which the application is defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	True	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"]— Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"]— Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"]— Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"]— Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"]— Select all resources that have a label named app • ["!app"]— Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

namespaceMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the namespace on the source cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
destination	string	True	<p>JSON string containing the name of the namespace on the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

storageClassMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the source storage class. Can also be '*' to specify all source storage classes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema if Storage Class name is used • '*' to specify all storage classes
destination	string	True	<p>JSON string containing the name of the destination storage class. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema

GVKN

Name	Type	Required	Description
group	string	False	<p>JSON string containing a group identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources

Name	Type	Required	Description
version	string	False	<p>JSON string containing a version identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
kind	string	False	<p>JSON string containing a kind identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
namespaces	array[string]	False	<p>JSON array of JSON strings describing namespaces to include or exclude resources from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
names	array[string]	False	<p>JSON array of JSON strings describing Kubernetes resource names to include or exclude from the selective restore.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings describing Kubernetes label selectors used to include or exclude resources from the selective restore.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	False	<p>JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.</p>

Name	Type	Required	Description
GVKN	array[GVKN]	False	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	

Name	Type	Required	Description
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

app_2.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-app"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "2.0" "2.1" "2.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.

Name	Type	Required	Description
name	string	True	<p>JSON string containing a name for the application. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. • Conforms to the DNS 1123 Label Schema
clusterScopedResources	array[clusterScopedResources]	False	JSON array of JSON objects describing the cluster-scoped resources that are part of this app
namespaceScopedResources	array[namespaceScopedResources]	True	JSON array of JSON objects describing the resources that are part of this app
lastResourceCollectionTimestamp	string	False	<p>JSON string containing the timestamp when the last resource collection was performed. This field is unset if no resource collection has been performed for this application yet. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application is scheduled for discovery • "discovering" - The application is in the process of being discovered • "provisioning" - The application is in the process of being provisioned • "ready" - The application is running normally • "failed" - The application is in a permanent failure state • "restoring" - The application is being restored from backup or snapshot • "unavailable" - The application is not currently accessible • "unknown" - The application state cannot be determined • "deleting" - The application is in the process of being deleted

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The application has a protection policy defined and is in conformance with that policy • "partial" - The application has a protection policy defined, but is out of conformance with that policy • "none" - The application does not have a protection policy defined • "atRisk" - The default storage class on the cluster does not support snapshots, the application is at risk of gaining an unsupported volume
protectionStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
appDetectedType	string	False	<p>JSON string that uniquely represents the specific type of application that is detected.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "system" - The application contains a resource that identifies it as part of the Kubernetes environment • "acc" - The application contains resources that identify it as an Astra Control Center instance
namespaces	array[string]	True	<p>JSON array of JSON strings containing the names of the namespaces in which the application is running.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
namespaceMapping	array[namespaceMapping]	False	<p>JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
storageClassMapping	array[storageClassMapping]	False	<p>JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
clusterName	string	False	<p>JSON string containing the name of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p>
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "gke" - Kubernetes hosted on Google Kubernetes Engine (GKE)• "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service (AKS)• "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service (Amazon EKS)• "openshift" - The cluster is of type OpenShift• "kubernetes" - The cluster is generic Kubernetes

Name	Type	Required	Description
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot. When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterName	string	False	<p>JSON string containing the name of the cluster the application was previously running on. Only returned if the application was cloned from another cluster.</p>

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on. Only returned if the application was cloned from another cluster. When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicationSourceAppID	string	False	<p>JSON string containing the ID of the application that is being replicated to this application. Only returned if the application is currently the destination in an AppMirror relationship, and the relationship is not in the failedOver state. When the relationship is in the failedOver state, this field is not returned. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an app for a managed cluster

GET

/accounts/{account_id}/topology/v2/managedClusters/{managedCluster_id}/apps/{app_id}

Returns the stored App API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
app_id	string	path	True	ID of the app collection to list

Response

Status: 200, Returns the stored App API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-app"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"2.0""2.1""2.2"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.
name	string	True	JSON string containing a name for the application. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. • Conforms to the DNS 1123 Label Schema
clusterScopedResources	array[clusterScopedResources]	False	JSON array of JSON objects describing the cluster-scoped resources that are part of this app
namespaceScopedResources	array[namespaceScopedResources]	True	JSON array of JSON objects describing the resources that are part of this app

Name	Type	Required	Description
lastResourceCollectionTimestamp	string	False	<p>JSON string containing the timestamp when the last resource collection was performed. This field is unset if no resource collection has been performed for this application yet.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application is scheduled for discovery • "discovering" - The application is in the process of being discovered • "provisioning" - The application is in the process of being provisioned • "ready" - The application is running normally • "failed" - The application is in a permanent failure state • "restoring" - The application is being restored from backup or snapshot • "unavailable" - The application is not currently accessible • "unknown" - The application state cannot be determined • "deleting" - The application is in the process of being deleted

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state.</p> <p>Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The application has a protection policy defined and is in conformance with that policy • "partial" - The application has a protection policy defined, but is out of conformance with that policy • "none" - The application does not have a protection policy defined • "atRisk" - The default storage class on the cluster does not support snapshots, the application is at risk of gaining an unsupported volume
protectionStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
appDetectedType	string	False	<p>JSON string that uniquely represents the specific type of application that is detected.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "system" - The application contains a resource that identifies it as part of the Kubernetes environment • "acc" - The application contains resources that identify it as an Astra Control Center instance
namespaces	array[string]	True	<p>JSON array of JSON strings containing the names of the namespaces in which the application is running.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
namespaceMapping	array[namespaceMapping]	False	<p>JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
storageClassMapping	array[storageClassMapping]	False	<p>JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
clusterName	string	False	<p>JSON string containing the name of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p>
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine (GKE) • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service (AKS) • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service (Amazon EKS) • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes

Name	Type	Required	Description
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot.</p> <p>When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail.</p> <p>Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterName	string	False	<p>JSON string containing the name of the cluster the application was previously running on. Only returned if the application was cloned from another cluster.</p>

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on.</p> <p>Only returned if the application was cloned from another cluster.</p> <p>When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicationSourceAppID	string	False	<p>JSON string containing the ID of the application that is being replicated to this application.</p> <p>Only returned if the application is currently the destination in an AppMirror relationship, and the relationship is not in the failedOver state.</p> <p>When the relationship is in the failedOver state, this field is not returned.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-app",
  "version": "2.2",
  "id": "39c1c79f-efab-5357-88fb-20e628c4dd96",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/topology/v2/managedClusters/6a358976-c3ac-49aa-b043-9c9b425c90ac/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f"
    },
    {
      "rel": "collection",
      "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/topology/v1/clouds/892814c9-77a1-46f3-b54a-82c34cdf0032/clusters/6a358976-c3ac-49aa-b043-9c9b425c90ac/namespaces/da78daf6-8e11-4220-a461-6b1d4a6dc231/apps"
    },
    {
      "rel": "related",
      "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v1/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f/appBackups",
      "type": "application/astra-appBackup",
      "title": "disruptiveBackup",
      "hints": {
        "allow": [],
        "permissions": [
          "appBackup-create"
        ]
      }
    },
    {
      "rel": "related",
      "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v1/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f/appBackups",
      "type": "application/astra-appBackup",
      "title": "nonDisruptiveBackup",
      "hints": {
        "allow": [
          "POST"
        ],
        "permissions": [
```

```
        "appBackup-create"
    ]
}
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v2/apps",
    "type": "application/astra-app",
    "title": "restore",
    "hints": {
        "allow": [
            "POST"
        ],
        "permissions": [
            "app-create"
        ]
    }
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v1/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f/appSnaps",
    "type": "application/astra-appSnap",
    "title": "snapshot",
    "hints": {
        "allow": [
            "POST"
        ],
        "permissions": [
            "appSnap-create"
        ]
    }
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v2/apps",
    "type": "application/astra-app",
    "title": "clone",
    "hints": {
        "allow": [
            "POST"
        ],
        "permissions": [
```

```

        "app-create"
    ]
}
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v2/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f",
    "type": "application/astra-app",
    "title": "inPlaceRestore",
    "hints": {
        "allow": [
            "PUT"
        ],
        "permissions": [
            "app-update"
        ]
    }
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v1/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f/appMirrors",
    "type": "application/astra-appMirror",
    "title": "replication",
    "hints": {
        "allow": [
            "POST"
        ],
        "permissions": [
            "appMirror-create"
        ]
    }
},
],
"name": "jenkins",
"namespaceScopedResources": [
    {
        "namespace": "production-clone",
        "labelSelectors": [
            "app = jenkins,release = production"
        ]
    }
],
"namespaceMapping": [

```



```

    {
      "source": "production",
      "destination": "production-clone"
    }
  ],
  "state": "ready",
  "stateDetails": [],
  "protectionState": "none",
  "protectionStateDetails": [],
  "namespaces": [
    "production-clone"
  ],
  "snapshotID": "8d561930-0437-4647-b3e6-49b8a5362e3d",
  "clusterName": "GKE-24",
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "clusterType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

GVK

JSON object containing a Kubernetes group/version/kind.

- This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
group	string	True	JSON string containing a group identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources

Name	Type	Required	Description
kind	string	True	JSON string containing a kind identifier assigned by Kubernetes. <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources
version	string	True	JSON string containing a version identifier assigned by Kubernetes. <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources

clusterScopedResources

Name	Type	Required	Description
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind. <ul style="list-style-type: none"> This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector for the cluster-scoped GroupVersionKinds (GVKs) within the cluster. If this is empty, then all GVK instances on the cluster are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

namespaceScopedResources

Name	Type	Required	Description
namespace	string	True	<p>JSON string containing the name of a namespace in which the application is defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	True	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"] — Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"] — Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"] — Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"] — Select all resources that have a label named app • ["!app"] — Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

namespaceMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the namespace on the source cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
destination	string	True	<p>JSON string containing the name of the namespace on the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

storageClassMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the source storage class. Can also be '*' to specify all source storage classes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema if Storage Class name is used • '*' to specify all storage classes
destination	string	True	<p>JSON string containing the name of the destination storage class. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema

GVKN

Name	Type	Required	Description
group	string	False	<p>JSON string containing a group identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources

Name	Type	Required	Description
version	string	False	<p>JSON string containing a version identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
kind	string	False	<p>JSON string containing a kind identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
namespaces	array[string]	False	<p>JSON array of JSON strings describing namespaces to include or exclude resources from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
names	array[string]	False	<p>JSON array of JSON strings describing Kubernetes resource names to include or exclude from the selective restore.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings describing Kubernetes label selectors used to include or exclude resources from the selective restore.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	False	<p>JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.</p>

Name	Type	Required	Description
GVKN	array[GVKN]	False	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	

Name	Type	Required	Description
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify an app for a managed cluster

PUT

/accounts/{account_id}/topology/v2/managedClusters/{managedCluster_id}/apps/{app_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
managedCluster_id	string	path	True	ID of the containing managedCluster resource
app_id	string	path	True	ID of the app collection to list

Name	Type	In	Required	Description
forceUpdate	string	header	False	Flag that enables destructive overwrites. Only include this when requesting an in-place restore (IPR). • example: true

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-app"
version	string	True	Version of the resource. Defined values are: • "2.0" • "2.1" • "2.2"
id	string	False	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>JSON string containing a name for the application. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. • Conforms to the DNS 1123 Label Schema
clusterScopedResources	array[clusterScopedResources]	False	JSON array of JSON objects describing the cluster-scoped resources that are part of this app
namespaceScopedResources	array[namespaceScopedResources]	False	JSON array of JSON objects describing the resources that are part of this app
lastResourceCollectionTimestamp	string	False	<p>JSON string containing the timestamp when the last resource collection was performed. This field is unset if no resource collection has been performed for this application yet. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application is scheduled for discovery • "discovering" - The application is in the process of being discovered • "provisioning" - The application is in the process of being provisioned • "ready" - The application is running normally • "failed" - The application is in a permanent failure state • "restoring" - The application is being restored from backup or snapshot • "unavailable" - The application is not currently accessible • "unknown" - The application state cannot be determined • "deleting" - The application is in the process of being deleted

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state.</p> <p>Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
stateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
protectionState	string	False	<p>JSON string containing a value indicating the protection state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The application has a protection policy defined and is in conformance with that policy • "partial" - The application has a protection policy defined, but is out of conformance with that policy • "none" - The application does not have a protection policy defined • "atRisk" - The default storage class on the cluster does not support snapshots, the application is at risk of gaining an unsupported volume
protectionStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
appDetectedType	string	False	<p>JSON string that uniquely represents the specific type of application that is detected.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "system" - The application contains a resource that identifies it as part of the Kubernetes environment • "acc" - The application contains resources that identify it as an Astra Control Center instance
namespaces	array[string]	False	<p>JSON array of JSON strings containing the names of the namespaces in which the application is running.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
namespaceMapping	array[namespaceMapping]	False	<p>JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
storageClassMapping	array[storageClassMapping]	False	<p>JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
clusterName	string	False	<p>JSON string containing the name of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p>
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine (GKE) • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service (AKS) • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service (Amazon EKS) • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes

Name	Type	Required	Description
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot.</p> <p>When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail.</p> <p>Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterName	string	False	<p>JSON string containing the name of the cluster the application was previously running on. Only returned if the application was cloned from another cluster.</p>

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on.</p> <p>Only returned if the application was cloned from another cluster.</p> <p>When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicationSourceAppID	string	False	<p>JSON string containing the ID of the application that is being replicated to this application. Only returned if the application is currently the destination in an AppMirror relationship, and the relationship is not in the failedOver state. When the relationship is in the failedOver state, this field is not returned. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-app",
  "version": "2.2",
  "name": "mysql-old"
}
```

Response

Status: 204, Indicates if the app resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

- This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources
version	string	False	JSON string containing a version identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources

clusterScopedResources

Name	Type	Required	Description
GVK	GVK	False	JSON object containing a Kubernetes group/version/kind. <ul style="list-style-type: none">• This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector for the cluster-scoped GroupVersionKinds (GVKs) within the cluster. If this is empty, then all GVK instances on the cluster are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

namespaceScopedResources

Name	Type	Required	Description
namespace	string	False	<p>JSON string containing the name of a namespace in which the application is defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"] — Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"] — Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"] — Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"] — Select all resources that have a label named app • ["!app"] — Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

namespaceMapping

Name	Type	Required	Description
source	string	False	<p>JSON string containing the name of the namespace on the source cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
destination	string	False	<p>JSON string containing the name of the namespace on the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

storageClassMapping

Name	Type	Required	Description
source	string	False	<p>JSON string containing the name of the source storage class. Can also be '*' to specify all source storage classes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema if Storage Class name is used • '*' to specify all storage classes
destination	string	False	<p>JSON string containing the name of the destination storage class. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema

GVKN

Name	Type	Required	Description
group	string	False	<p>JSON string containing a group identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources

Name	Type	Required	Description
version	string	False	<p>JSON string containing a version identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
kind	string	False	<p>JSON string containing a kind identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
namespaces	array[string]	False	<p>JSON array of JSON strings describing namespaces to include or exclude resources from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
names	array[string]	False	<p>JSON array of JSON strings describing Kubernetes resource names to include or exclude from the selective restore.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings describing Kubernetes label selectors used to include or exclude resources from the selective restore.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	True	JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.

Name	Type	Required	Description
GVKN	array[GVKN]	True	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	

Name	Type	Required	Description
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete an app for a managed cluster

DELETE

/accounts/{account_id}/topology/v2/managedClusters/{managedCluster_id}/apps/{app_id}

Removes the specified App API resource.

Side Effects

- If the application is still running on a cluster, the application is no longer considered to be under management and will no longer appear under /apps.
- First, the application goes into the deleting state and then deletes all associated schedules, snapshots, backups, and the stored application state.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
app_id	string	path	True	ID of the app collection to list

Response

Status: 204, Indicates if the app resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/91",
  "title": "Application not deleted",
  "detail": "The application wasn't deleted because of an internal
server issue.",
  "status": "500"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/112",
  "title": "Application not ready",
  "detail": "The application is currently unavailable.",
  "status": "409"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new app

POST /accounts/{account_id}/k8s/v2/apps

Indicates the desired values for the App API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates the desired values for the App API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-app"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"2.0""2.1""2.2"

Name	Type	Required	Description
name	string	True	<p>JSON string containing a name for the application. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. • Conforms to the DNS 1123 Label Schema
clusterScopedResources	array[clusterScopedResources]	False	JSON array of JSON objects describing the cluster-scoped resources that are part of this app
namespaceScopedResources	array[namespaceScopedResources]	False	JSON array of JSON objects describing the resources that are part of this app
namespaceMapping	array[namespaceMapping]	False	<p>JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation. Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
storageClassMapping	array[storageClassMapping]	False	<p>JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used. Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot.</p> <p>When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail.</p> <p>Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on.</p> <p>Only returned if the application was cloned from another cluster.</p> <p>When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-app",
  "version": "2.2",
  "name": "jenkins",
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "namespaceScopedResources": [
    {
      "namespace": "production"
    }
  ]
}
```

Response

Status: 201, Returns the newly created app resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-app"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "2.0" • "2.1" • "2.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.
name	string	True	JSON string containing a name for the application. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. • Conforms to the DNS 1123 Label Schema
clusterScopedResources	array[clusterScopedResources]	False	JSON array of JSON objects describing the cluster-scoped resources that are part of this app

Name	Type	Required	Description
namespaceScopedResources	array[namespaceScopedResources]	True	JSON array of JSON objects describing the resources that are part of this app
lastResourceCollectionTimestamp	string	False	<p>JSON string containing the timestamp when the last resource collection was performed. This field is unset if no resource collection has been performed for this application yet. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application is scheduled for discovery • "discovering" - The application is in the process of being discovered • "provisioning" - The application is in the process of being provisioned • "ready" - The application is running normally • "failed" - The application is in a permanent failure state • "restoring" - The application is being restored from backup or snapshot • "unavailable" - The application is not currently accessible • "unknown" - The application state cannot be determined • "deleting" - The application is in the process of being deleted

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state.</p> <p>Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The application has a protection policy defined and is in conformance with that policy • "partial" - The application has a protection policy defined, but is out of conformance with that policy • "none" - The application does not have a protection policy defined • "atRisk" - The default storage class on the cluster does not support snapshots, the application is at risk of gaining an unsupported volume
protectionStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
appDetectedType	string	False	<p>JSON string that uniquely represents the specific type of application that is detected.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "system" - The application contains a resource that identifies it as part of the Kubernetes environment • "acc" - The application contains resources that identify it as an Astra Control Center instance
namespaces	array[string]	True	<p>JSON array of JSON strings containing the names of the namespaces in which the application is running.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
namespaceMapping	array[namespaceMapping]	False	<p>JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
storageClassMapping	array[storageClassMapping]	False	<p>JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
clusterName	string	False	<p>JSON string containing the name of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p>
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine (GKE) • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service (AKS) • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service (Amazon EKS) • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes

Name	Type	Required	Description
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot.</p> <p>When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail.</p> <p>Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterName	string	False	<p>JSON string containing the name of the cluster the application was previously running on. Only returned if the application was cloned from another cluster.</p>

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on.</p> <p>Only returned if the application was cloned from another cluster.</p> <p>When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicationSourceAppID	string	False	<p>JSON string containing the ID of the application that is being replicated to this application. Only returned if the application is currently the destination in an AppMirror relationship, and the relationship is not in the failedOver state. When the relationship is in the failedOver state, this field is not returned. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-app",
  "version": "2.2",
  "id": "39c1c79f-efab-5357-88fb-20e628c4dd96",
  "links": [],
  "name": "jenkins",
  "namespaceScopedResources": [
    {
      "namespace": "production",
      "labelSelectors": []
    }
  ],
  "state": "pending",
  "stateDetails": [],
  "protectionState": "none",
  "protectionStateDetails": [],
  "namespaces": [
    "production"
  ],
  "clusterName": "GKE-22",
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "clusterType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

- This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
group	string	True	JSON string containing a group identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources
kind	string	True	JSON string containing a kind identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources
version	string	True	JSON string containing a version identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources

clusterScopedResources

Name	Type	Required	Description
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind. <ul style="list-style-type: none">• This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector for the cluster-scoped GroupVersionKinds (GVKs) within the cluster. If this is empty, then all GVK instances on the cluster are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

namespaceScopedResources

Name	Type	Required	Description
namespace	string	True	<p>JSON string containing the name of a namespace in which the application is defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"]— Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"]— Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"]— Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"]— Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"]— Select all resources that have a label named app • ["!app"]— Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

namespaceMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the namespace on the source cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
destination	string	True	<p>JSON string containing the name of the namespace on the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

storageClassMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the source storage class. Can also be '*' to specify all source storage classes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema if Storage Class name is used • '*' to specify all storage classes

Name	Type	Required	Description
destination	string	True	<p>JSON string containing the name of the destination storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema

GVKN

Name	Type	Required	Description
group	string	False	<p>JSON string containing a group identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
version	string	False	<p>JSON string containing a version identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
kind	string	False	<p>JSON string containing a kind identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources

Name	Type	Required	Description
namespaces	array[string]	False	<p>JSON array of JSON strings describing namespaces to include or exclude resources from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
names	array[string]	False	<p>JSON array of JSON strings describing Kubernetes resource names to include or exclude from the selective restore.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings describing Kubernetes label selectors used to include or exclude resources from the selective restore.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	True	JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.

Name	Type	Required	Description
GVKN	array[GVKN]	True	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	

Name	Type	Required	Description
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

namespaceScopedResources

Name	Type	Required	Description
namespace	string	True	<p>JSON string containing the name of a namespace in which the application is defined. Defined values are:</p> <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 253• Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	True	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"]— Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"]— Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"]— Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"]— Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"]— Select all resources that have a label named app • ["!app"]— Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

l
"app=mysql,version=
2"] — Select all
resources that have

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	False	JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.

Name	Type	Required	Description
GVKN	array[GVKN]	False	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all apps

GET /accounts/{account_id}/k8s/v2/apps

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name,state
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: app_2.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-apps",
  "version": "2.2",
  "items": [
    [
      "2ff50f4b-fe40-4980-913f-8a4469184822",
      "mysql",
      "ready"
    ],
    [
      "ae1e6561-9e22-406c-8a5a-762f4604da00",
      "jenkins",
      "ready"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

GVK

JSON object containing a Kubernetes group/version/kind.

- This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
group	string	True	JSON string containing a group identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources

Name	Type	Required	Description
kind	string	True	JSON string containing a kind identifier assigned by Kubernetes. <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources
version	string	True	JSON string containing a version identifier assigned by Kubernetes. <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources

clusterScopedResources

Name	Type	Required	Description
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind. <ul style="list-style-type: none"> This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector for the cluster-scoped GroupVersionKinds (GVKs) within the cluster. If this is empty, then all GVK instances on the cluster are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

namespaceScopedResources

Name	Type	Required	Description
namespace	string	True	<p>JSON string containing the name of a namespace in which the application is defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	True	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"] — Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"] — Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"] — Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"] — Select all resources that have a label named app • ["!app"] — Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

namespaceMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the namespace on the source cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
destination	string	True	<p>JSON string containing the name of the namespace on the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

storageClassMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the source storage class. Can also be '*' to specify all source storage classes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema if Storage Class name is used • '*' to specify all storage classes
destination	string	True	<p>JSON string containing the name of the destination storage class. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema

GVKN

Name	Type	Required	Description
group	string	False	<p>JSON string containing a group identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources

Name	Type	Required	Description
version	string	False	<p>JSON string containing a version identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
kind	string	False	<p>JSON string containing a kind identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
namespaces	array[string]	False	<p>JSON array of JSON strings describing namespaces to include or exclude resources from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
names	array[string]	False	<p>JSON array of JSON strings describing Kubernetes resource names to include or exclude from the selective restore.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings describing Kubernetes label selectors used to include or exclude resources from the selective restore.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	False	<p>JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.</p>

Name	Type	Required	Description
GVKN	array[GVKN]	False	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	

Name	Type	Required	Description
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

app_2.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-app"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "2.0" "2.1" "2.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.

Name	Type	Required	Description
name	string	True	<p>JSON string containing a name for the application. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. • Conforms to the DNS 1123 Label Schema
clusterScopedResources	array[clusterScopedResources]	False	<p>JSON array of JSON objects describing the cluster-scoped resources that are part of this app</p>
namespaceScopedResources	array[namespaceScopedResources]	True	<p>JSON array of JSON objects describing the resources that are part of this app</p>
lastResourceCollectionTimestamp	string	False	<p>JSON string containing the timestamp when the last resource collection was performed. This field is unset if no resource collection has been performed for this application yet. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "pending" - The application is scheduled for discovery• "discovering" - The application is in the process of being discovered• "provisioning" - The application is in the process of being provisioned• "ready" - The application is running normally• "failed" - The application is in a permanent failure state• "restoring" - The application is being restored from backup or snapshot• "unavailable" - The application is not currently accessible• "unknown" - The application state cannot be determined• "deleting" - The application is in the process of being deleted

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current state, including why the current state was reached. If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The application has a protection policy defined and is in conformance with that policy • "partial" - The application has a protection policy defined, but is out of conformance with that policy • "none" - The application does not have a protection policy defined • "atRisk" - The default storage class on the cluster does not support snapshots, the application is at risk of gaining an unsupported volume
protectionStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
appDetectedType	string	False	<p>JSON string that uniquely represents the specific type of application that is detected.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "system" - The application contains a resource that identifies it as part of the Kubernetes environment • "acc" - The application contains resources that identify it as an Astra Control Center instance
namespaces	array[string]	True	<p>JSON array of JSON strings containing the names of the namespaces in which the application is running.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
namespaceMapping	array[namespaceMapping]	False	<p>JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
storageClassMapping	array[storageClassMapping]	False	<p>JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
clusterName	string	False	<p>JSON string containing the name of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p>
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "gke" - Kubernetes hosted on Google Kubernetes Engine (GKE)• "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service (AKS)• "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service (Amazon EKS)• "openshift" - The cluster is of type OpenShift• "kubernetes" - The cluster is generic Kubernetes

Name	Type	Required	Description
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot. When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterName	string	False	<p>JSON string containing the name of the cluster the application was previously running on. Only returned if the application was cloned from another cluster.</p>

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on. Only returned if the application was cloned from another cluster. When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicationSourceAppID	string	False	<p>JSON string containing the ID of the application that is being replicated to this application. Only returned if the application is currently the destination in an AppMirror relationship, and the relationship is not in the failedOver state. When the relationship is in the failedOver state, this field is not returned. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an app

GET /accounts/{account_id}/k8s/v2/apps/{app_id}

Returns the stored App API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the app collection to list

Response

Status: 200, Returns the stored App API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-app"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"2.0""2.1""2.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
links	array[type_astra_link]	True	Links describing supported operations against the resource.
name	string	True	<p>JSON string containing a name for the application. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. • Conforms to the DNS 1123 Label Schema
clusterScopedResources	array[clusterScopedResources]	False	JSON array of JSON objects describing the cluster-scoped resources that are part of this app
namespaceScopedResources	array[namespaceScopedResources]	True	JSON array of JSON objects describing the resources that are part of this app
lastResourceCollectionTimestamp	string	False	<p>JSON string containing the timestamp when the last resource collection was performed. This field is unset if no resource collection has been performed for this application yet. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application is scheduled for discovery • "discovering" - The application is in the process of being discovered • "provisioning" - The application is in the process of being provisioned • "ready" - The application is running normally • "failed" - The application is in a permanent failure state • "restoring" - The application is being restored from backup or snapshot • "unavailable" - The application is not currently accessible • "unknown" - The application state cannot be determined • "deleting" - The application is in the process of being deleted

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state.</p> <p>Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The application has a protection policy defined and is in conformance with that policy • "partial" - The application has a protection policy defined, but is out of conformance with that policy • "none" - The application does not have a protection policy defined • "atRisk" - The default storage class on the cluster does not support snapshots, the application is at risk of gaining an unsupported volume
protectionStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
appDetectedType	string	False	<p>JSON string that uniquely represents the specific type of application that is detected.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "system" - The application contains a resource that identifies it as part of the Kubernetes environment • "acc" - The application contains resources that identify it as an Astra Control Center instance
namespaces	array[string]	True	<p>JSON array of JSON strings containing the names of the namespaces in which the application is running.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
namespaceMapping	array[namespaceMapping]	False	<p>JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
storageClassMapping	array[storageClassMapping]	False	<p>JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
clusterName	string	False	<p>JSON string containing the name of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p>
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine (GKE) • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service (AKS) • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service (Amazon EKS) • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes

Name	Type	Required	Description
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot.</p> <p>When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail.</p> <p>Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterName	string	False	<p>JSON string containing the name of the cluster the application was previously running on. Only returned if the application was cloned from another cluster.</p>

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on.</p> <p>Only returned if the application was cloned from another cluster.</p> <p>When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicationSourceAppID	string	False	<p>JSON string containing the ID of the application that is being replicated to this application. Only returned if the application is currently the destination in an AppMirror relationship, and the relationship is not in the failedOver state. When the relationship is in the failedOver state, this field is not returned. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-app",
  "version": "2.2",
  "id": "39c1c79f-efab-5357-88fb-20e628c4dd96",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/topology/v2/managedClusters/6a358976-c3ac-49aa-b043-9c9b425c90ac/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f"
    },
    {
      "rel": "collection",
      "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/topology/v1/clouds/892814c9-77a1-46f3-b54a-82c34cdf0032/clusters/6a358976-c3ac-49aa-b043-9c9b425c90ac/namespaces/da78daf6-8e11-4220-a461-6b1d4a6dc231/apps"
    },
    {
      "rel": "related",
      "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v1/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f/appBackups",
      "type": "application/astra-appBackup",
      "title": "disruptiveBackup",
      "hints": {
        "allow": [],
        "permissions": [
          "appBackup-create"
        ]
      }
    },
    {
      "rel": "related",
      "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v1/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f/appBackups",
      "type": "application/astra-appBackup",
      "title": "nonDisruptiveBackup",
      "hints": {
        "allow": [
          "POST"
        ],
        "permissions": [
```

```

        "appBackup-create"
    ]
}
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v2/apps",
    "type": "application/astra-app",
    "title": "restore",
    "hints": {
        "allow": [
            "POST"
        ],
        "permissions": [
            "app-create"
        ]
    }
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v1/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f/appSnaps",
    "type": "application/astra-appSnap",
    "title": "snapshot",
    "hints": {
        "allow": [
            "POST"
        ],
        "permissions": [
            "appSnap-create"
        ]
    }
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v2/apps",
    "type": "application/astra-app",
    "title": "clone",
    "hints": {
        "allow": [
            "POST"
        ],
        "permissions": [

```

```

        "app-create"
    ]
}
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v2/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f",
    "type": "application/astra-app",
    "title": "inPlaceRestore",
    "hints": {
        "allow": [
            "PUT"
        ],
        "permissions": [
            "app-update"
        ]
    }
},
{
    "rel": "related",
    "href": "/accounts/652f7a18-d4ed-47b2-b467-15bf2154d079/k8s/v1/apps/27467088-2e99-4bd8-aa9b-014d5f44a62f/appMirrors",
    "type": "application/astra-appMirror",
    "title": "replication",
    "hints": {
        "allow": [
            "POST"
        ],
        "permissions": [
            "appMirror-create"
        ]
    }
},
],
"name": "jenkins",
"namespaceScopedResources": [
    {
        "namespace": "production-clone",
        "labelSelectors": [
            "app = jenkins,release = production"
        ]
    }
],
"namespaceMapping": [

```

```

    {
      "source": "production",
      "destination": "production-clone"
    }
  ],
  "state": "ready",
  "stateDetails": [],
  "protectionState": "none",
  "protectionStateDetails": [],
  "namespaces": [
    "production-clone"
  ],
  "snapshotID": "8d561930-0437-4647-b3e6-49b8a5362e3d",
  "clusterName": "GKE-24",
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "clusterType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

GVK

JSON object containing a Kubernetes group/version/kind.

- This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
group	string	True	JSON string containing a group identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources

Name	Type	Required	Description
kind	string	True	JSON string containing a kind identifier assigned by Kubernetes. <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources
version	string	True	JSON string containing a version identifier assigned by Kubernetes. <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources

clusterScopedResources

Name	Type	Required	Description
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind. <ul style="list-style-type: none"> This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector for the cluster-scoped GroupVersionKinds (GVKs) within the cluster. If this is empty, then all GVK instances on the cluster are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

namespaceScopedResources

Name	Type	Required	Description
namespace	string	True	<p>JSON string containing the name of a namespace in which the application is defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	True	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"] — Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"] — Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"] — Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"] — Select all resources that have a label named app • ["!app"] — Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

namespaceMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the namespace on the source cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
destination	string	True	<p>JSON string containing the name of the namespace on the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

storageClassMapping

Name	Type	Required	Description
source	string	True	<p>JSON string containing the name of the source storage class. Can also be '*' to specify all source storage classes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema if Storage Class name is used • '*' to specify all storage classes
destination	string	True	<p>JSON string containing the name of the destination storage class. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema

GVKN

Name	Type	Required	Description
group	string	False	<p>JSON string containing a group identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources

Name	Type	Required	Description
version	string	False	<p>JSON string containing a version identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources
kind	string	False	<p>JSON string containing a kind identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> This string is internally validated against Astra /apiResources
namespaces	array[string]	False	<p>JSON array of JSON strings describing namespaces to include or exclude resources from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 63 Conforms to the DNS 1123 Label Schema
names	array[string]	False	<p>JSON array of JSON strings describing Kubernetes resource names to include or exclude from the selective restore.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 253 Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings describing Kubernetes label selectors used to include or exclude resources from the selective restore.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	False	<p>JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.</p>

Name	Type	Required	Description
GVKN	array[GVKN]	False	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	

Name	Type	Required	Description
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify an app

PUT /accounts/{account_id}/k8s/v2/apps/{app_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the app collection to list
forceUpdate	string	header	False	Flag that enables destructive overwrites. Only include this when requesting an in-place restore (IPR). <ul style="list-style-type: none"> example: true

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-app"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "2.0"• "2.1"• "2.2"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	False	JSON string containing a name for the application. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.• Conforms to the DNS 1123 Label Schema
clusterScopedResources	array[clusterScopedResources]	False	JSON array of JSON objects describing the cluster-scoped resources that are part of this app

Name	Type	Required	Description
namespaceScopedResources	array[namespaceScopedResources]	False	JSON array of JSON objects describing the resources that are part of this app
lastResourceCollectionTimestamp	string	False	<p>JSON string containing the timestamp when the last resource collection was performed. This field is unset if no resource collection has been performed for this application yet. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application is scheduled for discovery • "discovering" - The application is in the process of being discovered • "provisioning" - The application is in the process of being provisioned • "ready" - The application is running normally • "failed" - The application is in a permanent failure state • "restoring" - The application is being restored from backup or snapshot • "unavailable" - The application is not currently accessible • "unknown" - The application state cannot be determined • "deleting" - The application is in the process of being deleted

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state.</p> <p>Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
stateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
protectionState	string	False	<p>JSON string containing a value indicating the protection state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The application has a protection policy defined and is in conformance with that policy • "partial" - The application has a protection policy defined, but is out of conformance with that policy • "none" - The application does not have a protection policy defined • "atRisk" - The default storage class on the cluster does not support snapshots, the application is at risk of gaining an unsupported volume
protectionStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
appDetectedType	string	False	<p>JSON string that uniquely represents the specific type of application that is detected.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "system" - The application contains a resource that identifies it as part of the Kubernetes environment • "acc" - The application contains resources that identify it as an Astra Control Center instance
namespaces	array[string]	False	<p>JSON array of JSON strings containing the names of the namespaces in which the application is running.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
namespaceMapping	array[namespaceMapping]	False	<p>JSON array of JSON objects, each mapping a source namespace to a destination namespace for a clone operation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
storageClassMapping	array[storageClassMapping]	False	<p>JSON array of JSON objects, each mapping a source storage class to a destination storage class for a restore operation. If no elements or not present, original source storage class names will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
clusterName	string	False	<p>JSON string containing the name of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p>
clusterID	string	False	<p>JSON string containing the ID of the cluster that the application is running on.</p> <p>Not returned if the application is not currently running.</p> <p>When specified on create, clusterID indicates which cluster the application must be cloned into. If the specified cluster does not exist, or if the cluster specified does not match the clusterID specified in the request URI, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "gke" - Kubernetes hosted on Google Kubernetes Engine (GKE)• "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service (AKS)• "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service (Amazon EKS)• "openshift" - The cluster is of type OpenShift• "kubernetes" - The cluster is generic Kubernetes

Name	Type	Required	Description
sourceAppID	string	False	<p>JSON string containing the ID of a source application. Only returned if the application was cloned from another application, or was restored from a backup or snapshot.</p> <p>When specified on create, the sourceAppID is used in conjunction with the sourceClusterID and indicates which running application will be cloned. If the specified application does not exist on the specified source cluster, the clone will fail.</p> <p>Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterName	string	False	<p>JSON string containing the name of the cluster the application was previously running on. Only returned if the application was cloned from another cluster.</p>

Name	Type	Required	Description
sourceClusterID	string	False	<p>JSON string containing the ID of the cluster the application was previously running on.</p> <p>Only returned if the application was cloned from another cluster.</p> <p>When specified on create, the sourceClusterID is used in conjunction with the sourceAppID and indicates the source cluster of the application to be cloned. If the specified source cluster does not exist, the clone will fail.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
backupID	string	False	<p>JSON string containing the ID of the backup that the application was restored from.</p> <p>Only returned if the application was restored from a backup.</p> <p>When specified on create, backupID indicates that an application will be cloned from an existing backup. If the specified backup does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, backupID indicates the application backup from which the application will be in-place restored. If the specified backup does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the ID of the snapshot that the application was restored from.</p> <p>Only returned if the application was restored from a snapshot.</p> <p>When specified on create, snapshotID indicates that an application will be cloned from an existing snapshot. If the specified snapshot does not exist, the clone will fail. Only one of sourceAppID, backupID, or snapshotID can be specified when creating an application.</p> <p>When specified on a replace, snapshotID indicates the application snapshot from which the application will be in-place restored. If the specified snapshot does not exist, the restore will fail. Only one of backupID or snapshotID can be specified when updating an application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicationSourceAppID	string	False	<p>JSON string containing the ID of the application that is being replicated to this application. Only returned if the application is currently the destination in an AppMirror relationship, and the relationship is not in the failedOver state. When the relationship is in the failedOver state, this field is not returned. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
restoreFilter	restoreFilter	False	<p>JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.</p>
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-app",
  "version": "2.2",
  "name": "mysql-old"
}
```

Response

Status: 204, Indicates if the app resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

- This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources
version	string	False	JSON string containing a version identifier assigned by Kubernetes. <ul style="list-style-type: none">• This string is internally validated against Astra /apiResources

clusterScopedResources

Name	Type	Required	Description
GVK	GVK	False	JSON object containing a Kubernetes group/version/kind. <ul style="list-style-type: none">• This object is internally validated against Astra /apiResources.

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector for the cluster-scoped GroupVersionKinds (GVKs) within the cluster. If this is empty, then all GVK instances on the cluster are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

namespaceScopedResources

Name	Type	Required	Description
namespace	string	False	<p>JSON string containing the name of a namespace in which the application is defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings representing a label selector within the namespace. If this is empty, then all resources in the namespace are included.</p> <p>Each element in this array is a Kubernetes label selector string and follows the grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"]— Select all resources that have a label whose name is app and whose value is mysql • ["app != mysql"]— Select all resources that have a label whose name is app and whose value is not mysql • ["app in (mysql, mariadb)"]— Select all resources that have a label whose name is app and value is mysql or mariadb • ["app notin (nginx, wordpress)"]— Select all resources that do not have a label whose name is app and whose values are nginx or wordpress • ["app"]— Select all resources that have a label named app • ["!app"]— Select all resources that do not have a label named app <p>Note that multiple selection operators can be included in a single selector, separated by commas. In that</p>

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

namespaceMapping

Name	Type	Required	Description
source	string	False	<p>JSON string containing the name of the namespace on the source cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema
destination	string	False	<p>JSON string containing the name of the namespace on the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

storageClassMapping

Name	Type	Required	Description
source	string	False	<p>JSON string containing the name of the source storage class. Can also be '*' to specify all source storage classes. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema if Storage Class name is used • '*' to specify all storage classes
destination	string	False	<p>JSON string containing the name of the destination storage class. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema

GVKN

Name	Type	Required	Description
group	string	False	<p>JSON string containing a group identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources

Name	Type	Required	Description
version	string	False	<p>JSON string containing a version identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
kind	string	False	<p>JSON string containing a kind identifier assigned by Kubernetes.</p> <ul style="list-style-type: none"> • This string is internally validated against Astra /apiResources
namespaces	array[string]	False	<p>JSON array of JSON strings describing namespaces to include or exclude resources from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
names	array[string]	False	<p>JSON array of JSON strings describing Kubernetes resource names to include or exclude from the selective restore.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
labelSelectors	array[string]	False	<p>JSON array of JSON strings describing Kubernetes label selectors used to include or exclude resources from the selective restore.</p> <p>Each element in this array is a Kubernetes label selector string and follows the same grammar for those values.</p> <p>Examples:</p> <ul style="list-style-type: none"> • ["app=mysql"] — Select all resources that have a label whose name is app and whose value is mysql <p>More examples can be found here: https://kubernetes.io/docs/concepts/overview/working-with-objects/labels/#set-based-requirement</p>

restoreFilter

JSON object containing a list of filters that describe which resources are included or excluded from a selective restore operation. Include and exclude are mutually exclusive, and a selective restore can only use one kind of filter.

Name	Type	Required	Description
resourceSelectionCriteria	string	True	JSON string containing a value that indicates how resource filters select resources. Valid values are include or exclude.

Name	Type	Required	Description
GVKN	array[GVKN]	True	JSON array of JSON objects that describe resources to filter during a selective restore. A resource matches a single GVKN filter element if all of the specified filter fields match the corresponding resource field. Filter fields that are arrays (for example, namespaces and names) match if any of its elements match the corresponding resource field. The labelSelectors field requires that all selectors match. A resource that matches any filter in the array of GVKN filter objects is included or excluded from the restore based on the resourceSelectionCriteria value. Specifying empty GVKN objects results in a validation error.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	

Name	Type	Required	Description
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete an app

DELETE /accounts/{account_id}/k8s/v2/apps/{app_id}

Removes the specified App API resource.

Side Effects

- If the application is still running on a cluster, the application is no longer considered to be under management and will no longer appear under /apps.
- First, the application goes into the deleting state and then deletes all associated schedules, snapshots, backups, and the stored application state.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the app collection to list

Response

Status: 204, Indicates if the app resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/91",
  "title": "Application not deleted",
  "detail": "The application wasn't deleted because of an internal
server issue.",
  "status": "500"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/112",
  "title": "Application not ready",
  "detail": "The application is currently unavailable.",
  "status": "409"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

AppMirror

AppMirror overview

The AppMirror API enables management of AppMirror relationships.

Create a new AppMirror resource

POST /accounts/{account_id}/k8s/v1/appMirrors

Indicates the desired values for the AppMirror API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates the desired values for the AppMirror API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appMirror"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
sourceAppID	string	True	Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationClusterID	string	True	Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2
stateDesired	string	True	<p>The desired state for the relationship.</p> <p>At creation, the only valid value is "established".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-appMirror",
  "version": "1.0",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "stateDesired": "established"
}
```

Response

Status: 201, Returns the newly created appMirror resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "application/astra-appMirror"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
sourceAppID	string	True	Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterID	string	True	Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
destinationAppID	string	False	<p>Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationClusterID	string	True	<p>Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs).</p> <p>Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
state	string	True	<p>The state of the relationship.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "establishing" - The relationship is being created. • "established" - The relationship is created. • "failingOver" - Failover of the application to the destination cluster is in progress. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleting" - Resources created by the relationship are being cleaned up. • "deleted" - The relationship was cleaned up and deleted.

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions. The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleting" • "established": "failingOver", "deleting" • "failingOver": "failedOver", "deleting" • "failedOver": "establishing", "deleting" • "deleting": "deleted" • "deleted":
stateDesired	string	True	<p>The desired state for the relationship. At creation, the only valid value is "established". Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
stateAllowed	array[string]	False	<p>States that can be requested in a given state.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleted" • "established": "failedOver", "deleted" • "failingOver": "failedOver", "deleted" • "failedOver": "established", "deleted" • "deleting": "deleted" • "deleted": "deleted"
stateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
transferState	string	False	<p>State of the current or most recent snapshot transfer.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried. • "idle" - There is currently no transfer in progress.
transferStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "transferring": "idle" • "idle": "transferring"
transferStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
healthState	string	True	<p>Health state of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateTransitions	array[type_astra_stateTransition]	True	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "indeterminate": "normal", "warning", "critical" • "normal": "indeterminate", "warning", "critical" • "warning": "indeterminate", "normal", "critical" • "critical": "indeterminate", "normal", "warning"
healthStateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-appMirror",
  "version": "1.0",
  "id": "c5fbadd4-5d9e-5942-bb7f-f5386b6b6253",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
  "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "state": "establishing",
  "stateTransitions": [
    {
      "from": "establishing",
      "to": [
        "established",
        "deleting"
      ]
    },
    {
      "from": "established",
      "to": [
        "failingOver",
        "deleting"
      ]
    },
    {
      "from": "failingOver",
      "to": [
        "failedOver",
        "deleting"
      ]
    },
    {
      "from": "failedOver",
      "to": [
        "establishing",
        "deleting"
      ]
    },
    {
      "from": "deleting",
      "to": [
        "deleted"
      ]
    }
  ]
}
```

```
],
"stateDesired": "established",
"stateAllowed": [
  "deleted"
],
"stateDetails": [
  {
    "type": "https://astra.netapp.io/stateDetails/3",
    "title": "AppMirror is being established",
    "detail": "The AppMirror relationship is in the process of being
established."
  }
],
"healthState": "warning",
"healthStateTransitions": [
  {
    "from": "indeterminate",
    "to": [
      "normal",
      "warning",
      "critical"
    ]
  },
  {
    "from": "normal",
    "to": [
      "indeterminate",
      "warning",
      "critical"
    ]
  },
  {
    "from": "warning",
    "to": [
      "indeterminate",
      "normal",
      "critical"
    ]
  },
  {
    "from": "critical",
    "to": [
      "indeterminate",
      "normal",
      "warning"
    ]
  }
]
```

```

    }
  ],
  "healthStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/4",
      "title": "AppMirror not yet established",
      "detail": "The relationship is in the process of being
established, so it's not protecting the app data yet."
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```

{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}

```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

namespaceMapping

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the namespaces are specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
namespaces	array[string]	False	List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Conforms to the DNS 1123 Label Schema

storageClasses

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the storage class is specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
storageClassName	string	False	Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all AppMirror resources

GET /accounts/{account_id}/k8s/v1/appMirrors

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p>
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appMirror_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appMirrors",
  "version": "1.0",
  "items": [
    {
      "type": "application/astra-appMirror",
      "version": "1.0",
      "id": "f1c98c2e-6391-42d3-8b21-3e75dac048a3",
      "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
      "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
      "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
      "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
      "namespaceMapping": [
        {
          "clusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
          "namespaces": [
            "ns1-src",
            "ns2-src"
          ]
        },
        {
          "clusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
          "namespaces": [
            "ns1-dest",
            "ns2-dest"
          ]
        }
      ],
      "state": "established",
      "stateTransitions": [
        {
          "from": "establishing",
          "to": [
            "established",
            "deleting"
          ]
        },
        {
          "from": "established",
          "to": [
            "failingOver",
            "deleting"
          ]
        }
      ],
    }
  ],
}
```

```

    {
      "from": "failingOver",
      "to": [
        "failedOver",
        "deleting"
      ]
    },
    {
      "from": "failedOver",
      "to": [
        "establishing",
        "deleting"
      ]
    },
    {
      "from": "deleting",
      "to": [
        "deleted"
      ]
    }
  ],
  "stateDesired": "established",
  "stateAllowed": [
    "failedOver",
    "deleted"
  ],
  "stateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/1",
      "title": "AppMirror relationship established",
      "detail": "The AppMirror relationship has been successfully
established."
    }
  ],
  "healthState": "normal",
  "healthStateTransitions": [
    {
      "from": "indeterminate",
      "to": [
        "normal",
        "warning",
        "critical"
      ]
    }
  ],
  {
    "from": "normal",

```

```

    "to": [
      "indeterminate",
      "warning",
      "critical"
    ]
  },
  {
    "from": "warning",
    "to": [
      "indeterminate",
      "normal",
      "critical"
    ]
  },
  {
    "from": "critical",
    "to": [
      "indeterminate",
      "normal",
      "warning"
    ]
  }
],
"healthStateDetails": [
  {
    "type": "https://astra.netapp.io/stateDetails/2",
    "title": "SnapMirror syncing successfully",
    "detail": "All SnapMirror relationships are synchronizing as
expected."
  }
],
"metadata": {
  "labels": [],
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
  "createdBy": "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa"
}
],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

namespaceMapping

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the namespaces are specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
namespaces	array[string]	False	List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Conforms to the DNS 1123 Label Schema

storageClasses

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the storage class is specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
storageClassName	string	False	Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

appMirror_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appMirror"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
sourceAppID	string	True	Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema

Name	Type	Required	Description
sourceClusterID	string	True	<p>Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationAppID	string	False	<p>Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
destinationClusterID	string	True	<p>Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
state	string	True	<p>The state of the relationship.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "establishing" - The relationship is being created.• "established" - The relationship is created.• "failingOver" - Failover of the application to the destination cluster is in progress.• "failedOver" - Failover of the application to the destination cluster has completed.• "deleting" - Resources created by the relationship are being cleaned up.• "deleted" - The relationship was cleaned up and deleted.

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleting" • "established": "failingOver", "deleting" • "failingOver": "failedOver", "deleting" • "failedOver": "establishing", "deleting" • "deleting": "deleted" • "deleted":
stateDesired	string	True	<p>The desired state for the relationship.</p> <p>At creation, the only valid value is "established".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
stateAllowed	array[string]	False	<p>States that can be requested in a given state.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleted" • "established": "failedOver", "deleted" • "failingOver": "failedOver", "deleted" • "failedOver": "established", "deleted" • "deleting": "deleted" • "deleted": "deleted"
stateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
transferState	string	False	<p>State of the current or most recent snapshot transfer.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried. • "idle" - There is currently no transfer in progress.
transferStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "transferring": "idle" • "idle": "transferring"
transferStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
healthState	string	True	<p>Health state of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateTransitions	array[type_astra_stateTransition]	True	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "indeterminate": "normal", "warning", "critical" • "normal": "indeterminate", "warning", "critical" • "warning": "indeterminate", "normal", "critical" • "critical": "indeterminate", "normal", "warning"
healthStateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an AppMirror resource

GET /accounts/{account_id}/k8s/v1/appMirrors/{appMirror_id}

Returns the stored AppMirror API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
appMirror_id	string	path	True	ID of the appMirror collection to list

Response

Status: 200, Returns the stored AppMirror API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appMirror"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
sourceAppID	string	True	<p>Identifier of the source application.</p> <p>Only updated when swapping the sourceAppID with the destinationAppID.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterID	string	True	<p>Identifier of the managed cluster hosting the source application.</p> <p>This field is read-only and is determined based on the host cluster of the source application.</p> <p>If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationAppID	string	False	<p>Identifier of the destination application.</p> <p>Cannot be provided on create because a new app ID will be generated as part of relationship initialization.</p> <p>Can only be updated when swapping sourceAppID with the destinationAppID.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
destinationClusterID	string	True	<p>Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs).</p> <p>Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
state	string	True	<p>The state of the relationship.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "establishing" - The relationship is being created. • "established" - The relationship is created. • "failingOver" - Failover of the application to the destination cluster is in progress. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleting" - Resources created by the relationship are being cleaned up. • "deleted" - The relationship was cleaned up and deleted.

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions. The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleting" • "established": "failingOver", "deleting" • "failingOver": "failedOver", "deleting" • "failedOver": "establishing", "deleting" • "deleting": "deleted" • "deleted":
stateDesired	string	True	<p>The desired state for the relationship. At creation, the only valid value is "established". Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
stateAllowed	array[string]	False	<p>States that can be requested in a given state.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleted" • "established": "failedOver", "deleted" • "failingOver": "failedOver", "deleted" • "failedOver": "established", "deleted" • "deleting": "deleted" • "deleted": "deleted"
stateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
transferState	string	False	<p>State of the current or most recent snapshot transfer.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried. • "idle" - There is currently no transfer in progress.
transferStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "transferring": "idle" • "idle": "transferring"
transferStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
healthState	string	True	<p>Health state of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateTransitions	array[type_astra_stateTransition]	True	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "indeterminate": "normal", "warning", "critical" • "normal": "indeterminate", "warning", "critical" • "warning": "indeterminate", "normal", "critical" • "critical": "indeterminate", "normal", "warning"
healthStateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-appMirror",
  "version": "1.0",
  "id": "c5fbadd4-5d9e-5942-bb7f-f5386b6b6253",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
  "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "namespaceMapping": [
    {
      "clusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
      "namespaces": [
        "ns1-src",
        "ns2-src"
      ]
    },
    {
      "clusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
      "namespaces": [
        "ns1-dest",
        "ns2-dest"
      ]
    }
  ],
  "state": "established",
  "stateTransitions": [
    {
      "from": "establishing",
      "to": [
        "established",
        "deleting"
      ]
    },
    {
      "from": "established",
      "to": [
        "failingOver",
        "deleting"
      ]
    },
    {
      "from": "failingOver",
      "to": [
        "failedOver",

```

```

        "deleting"
    ]
},
{
    "from": "failedOver",
    "to": [
        "establishing",
        "deleting"
    ]
},
{
    "from": "deleting",
    "to": [
        "deleted"
    ]
}
],
"stateDesired": "established",
"stateAllowed": [
    "failedOver",
    "deleted"
],
"stateDetails": [
    {
        "type": "https://astra.netapp.io/stateDetails/1",
        "title": "AppMirror relationship established",
        "detail": "The AppMirror relationship has been successfully
established."
    }
],
"healthState": "normal",
"healthStateTransitions": [
    {
        "from": "indeterminate",
        "to": [
            "normal",
            "warning",
            "critical"
        ]
    },
    {
        "from": "normal",
        "to": [
            "indeterminate",
            "warning",
            "critical"
        ]
    }
]

```

```

    ]
  },
  {
    "from": "warning",
    "to": [
      "indeterminate",
      "normal",
      "critical"
    ]
  },
  {
    "from": "critical",
    "to": [
      "indeterminate",
      "normal",
      "warning"
    ]
  }
],
"healthStateDetails": [
  {
    "type": "https://astra.netapp.io/stateDetails/2",
    "title": "SnapMirror syncing successfully",
    "detail": "All SnapMirror relationships are synchronizing as
expected."
  }
],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

namespaceMapping

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the namespaces are specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
namespaces	array[string]	False	List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Conforms to the DNS 1123 Label Schema

storageClasses

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the storage class is specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
storageClassName	string	False	Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify an AppMirror resource

PUT /accounts/{account_id}/k8s/v1/appMirrors/{appMirror_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Various side effects based on desiredState.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> • example: <code>{{.Account}}</code>
appMirror_id	string	path	True	ID of the appMirror collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Various side effects based on desiredState.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appMirror"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
sourceAppID	string	False	Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema
sourceClusterID	string	False	Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema

Name	Type	Required	Description
destinationAppID	string	False	<p>Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationClusterID	string	False	<p>Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs).</p> <p>Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
state	string	False	<p>The state of the relationship.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "establishing" - The relationship is being created.• "established" - The relationship is created.• "failingOver" - Failover of the application to the destination cluster is in progress.• "failedOver" - Failover of the application to the destination cluster has completed.• "deleting" - Resources created by the relationship are being cleaned up.• "deleted" - The relationship was cleaned up and deleted.

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleting" • "established": "failingOver", "deleting" • "failingOver": "failedOver", "deleting" • "failedOver": "establishing", "deleting" • "deleting": "deleted" • "deleted":
stateDesired	string	False	<p>The desired state for the relationship.</p> <p>At creation, the only valid value is "established".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
stateAllowed	array[string]	False	<p>States that can be requested in a given state.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleted" • "established": "failedOver", "deleted" • "failingOver": "failedOver", "deleted" • "failedOver": "established", "deleted" • "deleting": "deleted" • "deleted": "deleted"
stateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
transferState	string	False	<p>State of the current or most recent snapshot transfer.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried. • "idle" - There is currently no transfer in progress.
transferStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "transferring": "idle" • "idle": "transferring"
transferStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
healthState	string	False	<p>Health state of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "indeterminate": "normal", "warning", "critical" • "normal": "indeterminate", "warning", "critical" • "warning": "indeterminate", "normal", "critical" • "critical": "indeterminate", "normal", "warning"
healthStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-appMirror",
  "version": "1.0",
  "stateDesired": "failedOver"
}
```

Response

Status: 204, Indicates if the appMirror resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

namespaceMapping

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the namespaces are specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
namespaces	array[string]	False	List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Conforms to the DNS 1123 Label Schema

storageClasses

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the storage class is specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
storageClassName	string	False	Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete an AppMirror resource

DELETE /accounts/{account_id}/k8s/v1/appMirrors/{appMirror_id}

Removes the specified AppMirror API resource.

Starts a process to asynchronously remove the AppMirror resource, along with any resources on the source and destination clusters that were created as a result of the AppMirror relationship. The resources removed are dependent on the state of the relationship at the time of deletion.

Side Effects

- The stateDesired field is set to "deleted".
- The state field is set to "deleting".
- If state is "established", the TridentMirrorRelationships and PersistentVolumeClaims created by the AppMirror relationship will be deleted.
- If state is "failedOver", the TridentMirrorRelationships created by the AppMirror relationship will be deleted and the PersistentVolumeClaims in the destination application will be left in place.
- When the asynchronous delete operation is completed, the AppMirror API resource will be removed from both the source and destination applications.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
appMirror_id	string	path	True	ID of the appMirror collection to list

Response

Status: 204, Indicates if the appMirror resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new AppMirror resource for an app

POST /accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors

Indicates the desired values for the AppMirror API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource

Request Body

Indicates the desired values for the AppMirror API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appMirror"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"

Name	Type	Required	Description
sourceAppID	string	True	<p>Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationClusterID	string	True	<p>Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs).</p> <p>Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2
stateDesired	string	True	<p>The desired state for the relationship.</p> <p>At creation, the only valid value is "established".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-appMirror",
  "version": "1.0",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "stateDesired": "established"
}
```

Response

Status: 201, Returns the newly created appMirror resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "application/astra-appMirror"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
sourceAppID	string	True	Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterID	string	True	Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
destinationAppID	string	False	<p>Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationClusterID	string	True	<p>Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs).</p> <p>Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
state	string	True	<p>The state of the relationship.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "establishing" - The relationship is being created. • "established" - The relationship is created. • "failingOver" - Failover of the application to the destination cluster is in progress. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleting" - Resources created by the relationship are being cleaned up. • "deleted" - The relationship was cleaned up and deleted.

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleting" • "established": "failingOver", "deleting" • "failingOver": "failedOver", "deleting" • "failedOver": "establishing", "deleting" • "deleting": "deleted" • "deleted":
stateDesired	string	True	<p>The desired state for the relationship.</p> <p>At creation, the only valid value is "established".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
stateAllowed	array[string]	False	<p>States that can be requested in a given state.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleted" • "established": "failedOver", "deleted" • "failingOver": "failedOver", "deleted" • "failedOver": "established", "deleted" • "deleting": "deleted" • "deleted": "deleted"
stateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
transferState	string	False	<p>State of the current or most recent snapshot transfer.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried. • "idle" - There is currently no transfer in progress.
transferStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "transferring": "idle" • "idle": "transferring"
transferStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
healthState	string	True	<p>Health state of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateTransitions	array[type_astra_stateTransition]	True	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "indeterminate": "normal", "warning", "critical" • "normal": "indeterminate", "warning", "critical" • "warning": "indeterminate", "normal", "critical" • "critical": "indeterminate", "normal", "warning"
healthStateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-appMirror",
  "version": "1.0",
  "id": "c5fbadd4-5d9e-5942-bb7f-f5386b6b6253",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
  "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "state": "establishing",
  "stateTransitions": [
    {
      "from": "establishing",
      "to": [
        "established",
        "deleting"
      ]
    },
    {
      "from": "established",
      "to": [
        "failingOver",
        "deleting"
      ]
    },
    {
      "from": "failingOver",
      "to": [
        "failedOver",
        "deleting"
      ]
    },
    {
      "from": "failedOver",
      "to": [
        "establishing",
        "deleting"
      ]
    },
    {
      "from": "deleting",
      "to": [
        "deleted"
      ]
    }
  ]
}
```

```

],
"stateDesired": "established",
"stateAllowed": [
  "deleted"
],
"stateDetails": [
  {
    "type": "https://astra.netapp.io/stateDetails/3",
    "title": "AppMirror is being established",
    "detail": "The AppMirror relationship is in the process of being
established."
  }
],
"healthState": "warning",
"healthStateTransitions": [
  {
    "from": "indeterminate",
    "to": [
      "normal",
      "warning",
      "critical"
    ]
  },
  {
    "from": "normal",
    "to": [
      "indeterminate",
      "warning",
      "critical"
    ]
  },
  {
    "from": "warning",
    "to": [
      "indeterminate",
      "normal",
      "critical"
    ]
  },
  {
    "from": "critical",
    "to": [
      "indeterminate",
      "normal",
      "warning"
    ]
  }
]

```



```

    }
  ],
  "healthStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/4",
      "title": "AppMirror not yet established",
      "detail": "The relationship is in the process of being
established, so it's not protecting the app data yet."
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```

{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}

```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

namespaceMapping

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the namespaces are specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
namespaces	array[string]	False	List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Conforms to the DNS 1123 Label Schema

storageClasses

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the storage class is specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
storageClassName	string	False	Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the AppMirror resources for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p>
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appMirror_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appMirrors",
  "version": "1.0",
  "items": [
    {
      "type": "application/astra-appMirror",
      "version": "1.0",
      "id": "f1c98c2e-6391-42d3-8b21-3e75dac048a3",
      "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
      "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
      "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
      "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
      "namespaceMapping": [
        {
          "clusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
          "namespaces": [
            "ns1-src",
            "ns2-src"
          ]
        },
        {
          "clusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
          "namespaces": [
            "ns1-dest",
            "ns2-dest"
          ]
        }
      ],
      "state": "established",
      "stateTransitions": [
        {
          "from": "establishing",
          "to": [
            "established",
            "deleting"
          ]
        },
        {
          "from": "established",
          "to": [
            "failingOver",
            "deleting"
          ]
        }
      ],
    }
  ],
}
```

```

    {
      "from": "failingOver",
      "to": [
        "failedOver",
        "deleting"
      ]
    },
    {
      "from": "failedOver",
      "to": [
        "establishing",
        "deleting"
      ]
    },
    {
      "from": "deleting",
      "to": [
        "deleted"
      ]
    }
  ],
  "stateDesired": "established",
  "stateAllowed": [
    "failedOver",
    "deleted"
  ],
  "stateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/1",
      "title": "AppMirror relationship established",
      "detail": "The AppMirror relationship has been successfully
established."
    }
  ],
  "healthState": "normal",
  "healthStateTransitions": [
    {
      "from": "indeterminate",
      "to": [
        "normal",
        "warning",
        "critical"
      ]
    }
  ],
  {
    "from": "normal",

```

```

        "to": [
            "indeterminate",
            "warning",
            "critical"
        ]
    },
    {
        "from": "warning",
        "to": [
            "indeterminate",
            "normal",
            "critical"
        ]
    },
    {
        "from": "critical",
        "to": [
            "indeterminate",
            "normal",
            "warning"
        ]
    }
],
"healthStateDetails": [
    {
        "type": "https://astra.netapp.io/stateDetails/2",
        "title": "SnapMirror syncing successfully",
        "detail": "All SnapMirror relationships are synchronizing as
expected."
    }
],
"metadata": {
    "labels": [],
    "creationTimestamp": "2020-08-06T12:24:52.256624Z",
    "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
    "createdBy": "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa"
}
},
"metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

namespaceMapping

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the namespaces are specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
namespaces	array[string]	False	List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Conforms to the DNS 1123 Label Schema

storageClasses

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the storage class is specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
storageClassName	string	False	Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

appMirror_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appMirror"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
sourceAppID	string	True	Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema

Name	Type	Required	Description
sourceClusterID	string	True	<p>Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationAppID	string	False	<p>Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
destinationClusterID	string	True	<p>Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs). Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
state	string	True	<p>The state of the relationship.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• "establishing" - The relationship is being created.• "established" - The relationship is created.• "failingOver" - Failover of the application to the destination cluster is in progress.• "failedOver" - Failover of the application to the destination cluster has completed.• "deleting" - Resources created by the relationship are being cleaned up.• "deleted" - The relationship was cleaned up and deleted.

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleting" • "established": "failingOver", "deleting" • "failingOver": "failedOver", "deleting" • "failedOver": "establishing", "deleting" • "deleting": "deleted" • "deleted":
stateDesired	string	True	<p>The desired state for the relationship.</p> <p>At creation, the only valid value is "established".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
stateAllowed	array[string]	False	<p>States that can be requested in a given state.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleted" • "established": "failedOver", "deleted" • "failingOver": "failedOver", "deleted" • "failedOver": "established", "deleted" • "deleting": "deleted" • "deleted": "deleted"
stateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
transferState	string	False	<p>State of the current or most recent snapshot transfer.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried. • "idle" - There is currently no transfer in progress.
transferStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "transferring": "idle" • "idle": "transferring"
transferStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
healthState	string	True	<p>Health state of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateTransitions	array[type_astra_stateTransition]	True	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "indeterminate": "normal", "warning", "critical" • "normal": "indeterminate", "warning", "critical" • "warning": "indeterminate", "normal", "critical" • "critical": "indeterminate", "normal", "warning"
healthStateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an AppMirror resource for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors/{appMirror_id}

Returns the stored AppMirror API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
appMirror_id	string	path	True	ID of the appMirror collection to list

Response

Status: 200, Returns the stored AppMirror API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appMirror"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
sourceAppID	string	True	<p>Identifier of the source application.</p> <p>Only updated when swapping the sourceAppID with the destinationAppID.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterID	string	True	<p>Identifier of the managed cluster hosting the source application.</p> <p>This field is read-only and is determined based on the host cluster of the source application.</p> <p>If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationAppID	string	False	<p>Identifier of the destination application.</p> <p>Cannot be provided on create because a new app ID will be generated as part of relationship initialization.</p> <p>Can only be updated when swapping sourceAppID with the destinationAppID.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
destinationClusterID	string	True	<p>Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs).</p> <p>Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
state	string	True	<p>The state of the relationship.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "establishing" - The relationship is being created. • "established" - The relationship is created. • "failingOver" - Failover of the application to the destination cluster is in progress. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleting" - Resources created by the relationship are being cleaned up. • "deleted" - The relationship was cleaned up and deleted.

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleting" • "established": "failingOver", "deleting" • "failingOver": "failedOver", "deleting" • "failedOver": "establishing", "deleting" • "deleting": "deleted" • "deleted":
stateDesired	string	True	<p>The desired state for the relationship.</p> <p>At creation, the only valid value is "established".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
stateAllowed	array[string]	False	<p>States that can be requested in a given state.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleted" • "established": "failedOver", "deleted" • "failingOver": "failedOver", "deleted" • "failedOver": "established", "deleted" • "deleting": "deleted" • "deleted": "deleted"
stateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
transferState	string	False	<p>State of the current or most recent snapshot transfer.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried. • "idle" - There is currently no transfer in progress.
transferStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "transferring": "idle" • "idle": "transferring"
transferStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
healthState	string	True	<p>Health state of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateTransitions	array[type_astra_stateTransition]	True	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "indeterminate": "normal", "warning", "critical" • "normal": "indeterminate", "warning", "critical" • "warning": "indeterminate", "normal", "critical" • "critical": "indeterminate", "normal", "warning"
healthStateDetails	array[type_astra_stateDetail]	True	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-appMirror",
  "version": "1.0",
  "id": "c5fbadd4-5d9e-5942-bb7f-f5386b6b6253",
  "sourceAppID": "efd639b6-fc92-4112-8841-0c0ab7890ae0",
  "sourceClusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
  "destinationAppID": "cd7b6d91-fc19-4983-a754-9a7bb4d80a7b",
  "destinationClusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
  "namespaceMapping": [
    {
      "clusterID": "5789e026-c2e2-41e9-ab00-9766bcfa8951",
      "namespaces": [
        "ns1-src",
        "ns2-src"
      ]
    },
    {
      "clusterID": "c5d023a9-4061-4a8a-bfbf-3be11ff06226",
      "namespaces": [
        "ns1-dest",
        "ns2-dest"
      ]
    }
  ],
  "state": "established",
  "stateTransitions": [
    {
      "from": "establishing",
      "to": [
        "established",
        "deleting"
      ]
    },
    {
      "from": "established",
      "to": [
        "failingOver",
        "deleting"
      ]
    },
    {
      "from": "failingOver",
      "to": [
        "failedOver",

```



```

        "deleting"
    ]
},
{
    "from": "failedOver",
    "to": [
        "establishing",
        "deleting"
    ]
},
{
    "from": "deleting",
    "to": [
        "deleted"
    ]
}
],
"stateDesired": "established",
"stateAllowed": [
    "failedOver",
    "deleted"
],
"stateDetails": [
    {
        "type": "https://astra.netapp.io/stateDetails/1",
        "title": "AppMirror relationship established",
        "detail": "The AppMirror relationship has been successfully
established."
    }
],
"healthState": "normal",
"healthStateTransitions": [
    {
        "from": "indeterminate",
        "to": [
            "normal",
            "warning",
            "critical"
        ]
    },
    {
        "from": "normal",
        "to": [
            "indeterminate",
            "warning",
            "critical"
        ]
    }
]

```

```

    ]
  },
  {
    "from": "warning",
    "to": [
      "indeterminate",
      "normal",
      "critical"
    ]
  },
  {
    "from": "critical",
    "to": [
      "indeterminate",
      "normal",
      "warning"
    ]
  }
],
"healthStateDetails": [
  {
    "type": "https://astra.netapp.io/stateDetails/2",
    "title": "SnapMirror syncing successfully",
    "detail": "All SnapMirror relationships are synchronizing as
expected."
  }
],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

namespaceMapping

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the namespaces are specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
namespaces	array[string]	False	List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Conforms to the DNS 1123 Label Schema

storageClasses

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the storage class is specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
storageClassName	string	False	Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify an AppMirror resource for an app

PUT /accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors/{appMirror_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Various side effects based on desiredState.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appMirror_id	string	path	True	ID of the appMirror collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Various side effects based on desiredState.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-appMirror"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
sourceAppID	string	False	Identifier of the source application. Only updated when swapping the sourceAppID with the destinationAppID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceClusterID	string	False	Identifier of the managed cluster hosting the source application. This field is read-only and is determined based on the host cluster of the source application. If provided in an update, it must match the cluster ID of the source application, so it can only change when swapping the sourceAppID with destinationAppID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
destinationAppID	string	False	<p>Identifier of the destination application. Cannot be provided on create because a new app ID will be generated as part of relationship initialization. Can only be updated when swapping sourceAppID with the destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
destinationClusterID	string	False	<p>Identifier of the managed cluster to host the destination application. Must be provided on create because it determines what cluster the destination application will be created on. If provided on update, it must match the cluster ID of the destination application, so it can only change when swapping sourceAppID with destinationAppID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
namespaceMapping	array[namespaceMapping]	False	<p>The namespace or namespaces to use when creating the destination application, corresponding to the namespaces of the source application. Each JSON object contains the fields "clusterID" and "namespaces", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "namespaces" value is a JSON array of JSON strings. There must be exactly one JSON object for each cluster, and the namespaces will be correlated by index. If not provided, the same namespace from the source cluster will be used in the destination cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
storageClasses	array[storageClasses]	False	<p>The storage class to be used on the destination cluster when creating new Persistent Volume Claims (PVCs).</p> <p>Each JSON object contains the fields "clusterID" and "storageClassName", where the "clusterID" value is the JSON string ID of the source or destination cluster, and the "storageClassName" is the storage class to use when creating PVCs on that cluster.</p> <p>If not provided or if the value is missing for a cluster, the default storage class will be used for that cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 2

Name	Type	Required	Description
state	string	False	<p>The state of the relationship.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "establishing" - The relationship is being created. • "established" - The relationship is created. • "failingOver" - Failover of the application to the destination cluster is in progress. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleting" - Resources created by the relationship are being cleaned up. • "deleted" - The relationship was cleaned up and deleted.

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleting" • "established": "failingOver", "deleting" • "failingOver": "failedOver", "deleting" • "failedOver": "establishing", "deleting" • "deleting": "deleted" • "deleted":
stateDesired	string	False	<p>The desired state for the relationship.</p> <p>At creation, the only valid value is "established".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "established" - The relationship is created. • "failedOver" - Failover of the application to the destination cluster has completed. • "deleted" - The relationship was successfully cleaned up and deleted.

Name	Type	Required	Description
stateAllowed	array[string]	False	<p>States that can be requested in a given state.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "establishing": "established", "deleted" • "established": "failedOver", "deleted" • "failingOver": "failedOver", "deleted" • "failedOver": "established", "deleted" • "deleting": "deleted" • "deleted": "deleted"
stateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
transferState	string	False	<p>State of the current or most recent snapshot transfer.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "transferring" - A new snapshot was created and is now being replicated to the destination cluster. This state also covers the transfers that have failed on previous attempts and are being continually retried. • "idle" - There is currently no transfer in progress.
transferStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "transferring": "idle" • "idle": "transferring"
transferStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
healthState	string	False	<p>Health state of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateTransitions	array[type_astra_stateTransition]	False	<p>Permitted state transitions from a given defined state.</p> <p>The following state transitions are possible for this resource:</p> <ul style="list-style-type: none"> • "indeterminate": "normal", "warning", "critical" • "normal": "indeterminate", "warning", "critical" • "warning": "indeterminate", "normal", "critical" • "critical": "indeterminate", "normal", "warning"
healthStateDetails	array[type_astra_stateDetail]	False	<p>Additional details about the current state including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-appMirror",
  "version": "1.0",
  "stateDesired": "failedOver"
}
```

Response

Status: 204, Indicates if the appMirror resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{  
  "type": "https://astra.netapp.io/problems/1",  
  "title": "Resource not found",  
  "detail": "The resource specified in the request URI wasn't found.",  
  "status": "404"  
}
```

Definitions

See Definitions

namespaceMapping

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the namespaces are specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
namespaces	array[string]	False	List of namespaces to use on the cluster. Correlated with the other cluster namespace list by index. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Conforms to the DNS 1123 Label Schema

storageClasses

Name	Type	Required	Description
clusterID	string	False	Identifier of the cluster for which the storage class is specified. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
storageClassName	string	False	Name of the storage class to use when creating PVCs on the cluster specified in "clusterID". Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete an AppMirror resource for an app

```
DELETE /accounts/{account_id}/k8s/v1/apps/{app_id}/appMirrors/{appMirror_id}
```

Removes the specified AppMirror API resource.

Starts a process to asynchronously remove the AppMirror resource, along with any resources on the source and destination clusters that were created as a result of the AppMirror relationship. The resources removed are dependent on the state of the relationship at the time of deletion.

Side Effects

- The stateDesired field is set to "deleted".
- The state field is set to "deleting".
- If state is "established", the TridentMirrorRelationships and PersistentVolumeClaims created by the AppMirror relationship will be deleted.
- If state is "failedOver", the TridentMirrorRelationships created by the AppMirror relationship will be deleted and the PersistentVolumeClaims in the destination application will be left in place.
- When the asynchronous delete operation is completed, the AppMirror API resource will be removed from both the source and destination applications.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appMirror_id	string	path	True	ID of the appMirror collection to list

Response

Status: 204, Indicates if the appMirror resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Application Asset

Application Asset overview

The Application Asset API provides access to internal collections of state information used to manage applications.

List the application assets for an application backup

GET /accounts/{account_id}/topology/v1/appBackups/{appBackup_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
appBackup_id	string	path	True	ID of the containing appBackup resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: assetType,asset Name
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset from an application backup

GET

/accounts/{account_id}/topology/v1/appBackups/{appBackup_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
appBackup_id	string	path	True	ID of the containing appBackup resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the application assets for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/apps/{app_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: assetType,asset Name

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/apps/{app_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
app_id	string	path	True	ID of the containing app resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the application assets for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>assetType,asset Name</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^[a-z0-9A-Z_-]{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the application assets from an application backup for an app

GET

/accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups/{appBackup_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appBackup_id	string	path	True	ID of the containing appBackup resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: assetType,asset Name

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset from an application backup for an app

GET

/accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups/{appBackup_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appBackup_id	string	path	True	ID of the containing appBackup resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List application assets for an application snapshot

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps/{appSnap_id}/appAssets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the containing appSnap resource
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>assetType,assetName</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appAsset_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appAssets",
  "version": "1.1",
  "items": [
    [
      "Pod",
      "mediawiki-69c6fcf864-2wx6l"
    ],
    [
      "ReplicaSet",
      "mediawiki-69c6fcf864"
    ],
    [
      "Service",
      "mediawiki"
    ],
    [
      "Deployment",
      "mediawiki"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^[a-z0-9A-Z_-]{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appAsset_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application asset for an application snapshot and app

GET

/accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps/{appSnap_id}/appAssets/{appAsset_id}

Returns the stored Application Asset API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the containing appSnap resource
appAsset_id	string	path	True	ID of the appAsset collection to list

Response

Status: 200, Returns the stored Application Asset API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appAsset"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
assetType	string	True	JSON string containing a value indicating what type of asset is being described as obtained from Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
creationTimestamp	string	True	JSON string containing a timestamp indicating when the Kubernetes metadata was created. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
GVK	GVK	True	JSON object containing a Kubernetes group/version/kind.
resource	type_json	False	JSON object containing the entire content of the Kubernetes resource definition.
assetID	string	True	JSON string containing an identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
labels	array[labels]	True	JSON array of JSON objects, each containing a Kubernetes labels associated with the asset. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
assetName	string	True	JSON string containing a name assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
namespace	string	False	JSON string containing a namespace assigned by Kubernetes. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-appAsset",
  "version": "1.1",
  "id": "6415e851-b820-553b-9432-ebd057d1917d",
  "assetType": "Pod",
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "GVK": {
    "group": "apps",
    "kind": "Pod",
    "version": "v1"
  },
  "assetID": "93ec0c61-d993-4aa1-bb08-f4dcdd5e97f6",
  "labels": [
    {
      "name": "app",
      "value": "mediawiki"
    },
    {
      "name": "pod-template-hash",
      "value": "69c6fcf864"
    }
  ],
  "assetName": "mediawiki-69c6fcf864-2wx61",
  "namespace": "wiki",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

GVK

JSON object containing a Kubernetes group/version/kind.

Name	Type	Required	Description
group	string	False	JSON string containing a group identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
kind	string	False	JSON string containing a kind identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
version	string	False	JSON string containing a version identifier assigned by Kubernetes. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

type_json

JSON object containing the entire content of the Kubernetes resource definition.

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^([\S.]{1,253}V)?([a-z0-9A-Z_-]){1,63}\$"</code>
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^{[a-z0-9A-Z_-]}{1,63}\$"</code>

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Application Backup

Application Backup overview

The Application Backup API enables a user to create and view backups of a managed application.

List all application backups

GET /accounts/{account_id}/topology/v1/appBackups

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>id,name,state</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appBackup_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appBackups",
  "version": "1.2",
  "items": [
    [
      "5cb608f9-571b-492e-a520-5bfb900a9b9c",
      "app-name-245",
      "pending"
    ],
    [
      "f8faa690-7e09-48a4-b33c-7965712acd0c",
      "app-name-244",
      "completed"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/96",
  "title": "Backups not listed",
  "detail": "The backups didn't list because of an internal server issue.",
  "status": "500"
}
```


Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appBackup_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-appBackup"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
bucketID	string	True	JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
scheduleID	string	False	<p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDe tail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
backupCreationTimestamp	string	False	<p>JSON string containing a timestamp indicating when the backup was taken.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
totalBytes	number	False	<p>JSON number containing the total number of bytes in the backup.</p>
bytesDone	number	False	<p>JSON number containing the number of bytes backed up for a running backup. When the backup is completed, it matches with the totalBytes field.</p>

Name	Type	Required	Description
percentDone	number	False	JSON number containing the percentage complete for a running backup. When the backup is completed, it is set to "100".
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application backup

GET /accounts/{account_id}/topology/v1/appBackups/{appBackup_id}

Returns the stored Application Backup API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
appBackup_id	string	path	True	ID of the appBackup collection to list

Response

Status: 200, Returns the stored Application Backup API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appBackup"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
bucketID	string	True	<p>JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
snapshotID	string	False	<p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
scheduleID	string	False	<p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
state	string	True	<p>JSON string containing a value indicating the operational state of the backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined

Name	Type	Required	Description
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
backupCreationTimestamp	string	False	<p>JSON string containing a timestamp indicating when the backup was taken.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
totalBytes	number	False	<p>JSON number containing the total number of bytes in the backup.</p>

Name	Type	Required	Description
bytesDone	number	False	<p>JSON number containing the number of bytes backed up for a running backup.</p> <p>When the backup is completed, it matches with the totalBytes field.</p>
percentDone	number	False	<p>JSON number containing the percentage complete for a running backup.</p> <p>When the backup is completed, it is set to "100".</p>
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-appBackup",
  "version": "1.2",
  "id": "bab39d53-2d04-5297-b92e-58df89a2117b",
  "name": "app-name-245",
  "bucketID": "0afbe357-a717-4c7a-8b3d-d0368959c8de",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/95",
  "title": "Backup not retrieved",
  "detail": "The backup wasn't retrieved because of an internal server issue.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete an application backup

DELETE /accounts/{account_id}/topology/v1/appBackups/{appBackup_id}

Removes the specified Application Backup API resource. Backups in progress will be canceled, and then deleted.

Side Effects

- If a backup is complete, the backup data is deleted.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code>
appBackup_id	string	path	True	ID of the appBackup collection to list

Response

Status: 204, Indicates if the appBackup resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/97",
  "title": "Backup not deleted",
  "detail": "The backup wasn't deleted because of an internal server issue.",
  "status": "500"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/128",
  "title": "Backup cancellation not allowed",
  "detail": "A pending backup can't be canceled.",
  "status": "409"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new application backup for an app

POST /accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups

Indicates the desired values for the Application Backup API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource

Request Body

Indicates the desired values for the Application Backup API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-appBackup"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
name	string	False	JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
bucketID	string	False	JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
metadata	type_astra_metadata	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example request

```
{
  "type": "application/astra-appBackup",
  "version": "1.2",
  "name": "app-name-245"
}
```

Response

Status: 201, Returns the newly created appBackup resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-appBackup"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
bucketID	string	True	<p>JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
snapshotID	string	False	<p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
scheduleID	string	False	<p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
backupCreationTimestamp	string	False	<p>JSON string containing a timestamp indicating when the backup was taken. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
totalBytes	number	False	<p>JSON number containing the total number of bytes in the backup.</p>
bytesDone	number	False	<p>JSON number containing the number of bytes backed up for a running backup. When the backup is completed, it matches with the totalBytes field.</p>

Name	Type	Required	Description
percentDone	number	False	JSON number containing the percentage complete for a running backup. When the backup is completed, it is set to "100".
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-appBackup",
  "version": "1.2",
  "id": "bab39d53-2d04-5297-b92e-58df89a2117b",
  "name": "app-name-245",
  "bucketID": "0afbe357-a717-4c7a-8b3d-d0368959c8de",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

```
Status: 401, Unauthorized
```

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/94",
  "title": "Backup not created",
  "detail": "The backup wasn't created because of an internal server issue.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the application backups for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>id,name,state</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appBackup_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appBackups",
  "version": "1.2",
  "items": [
    [
      "5cb608f9-571b-492e-a520-5bfb900a9b9c",
      "app-name-245",
      "pending"
    ],
    [
      "f8faa690-7e09-48a4-b33c-7965712acd0c",
      "app-name-244",
      "completed"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/96",
  "title": "Backups not listed",
  "detail": "The backups didn't list because of an internal server issue.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appBackup_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-appBackup"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
bucketID	string	True	JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
scheduleID	string	False	<p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDe tail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
backupCreationTimestamp	string	False	<p>JSON string containing a timestamp indicating when the backup was taken.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
totalBytes	number	False	<p>JSON number containing the total number of bytes in the backup.</p>
bytesDone	number	False	<p>JSON number containing the number of bytes backed up for a running backup. When the backup is completed, it matches with the totalBytes field.</p>

Name	Type	Required	Description
percentDone	number	False	JSON number containing the percentage complete for a running backup. When the backup is completed, it is set to "100".
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application backup for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups/{appBackup_id}

Returns the stored Application Backup API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appBackup_id	string	path	True	ID of the appBackup collection to list

Response

Status: 200, Returns the stored Application Backup API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-appBackup"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the backup. If not specified, or when backups are initiated by a schedule, the system assigns a name for the backup. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
bucketID	string	True	JSON string containing an optional bucket ID that indicates where the backup will be stored on create. If not specified, a system-selected bucket is used. If no buckets are available, an error will be returned on create. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotID	string	False	<p>JSON string containing the snapshot that was used to create the backup. To create the backup, a snapshot ID associated with the application being backed up can be specified on create. If not specified, a new snapshot will be created for the backup. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
scheduleID	string	False	<p>JSON string containing an optional schedule ID that indicates that the backup was triggered by a schedule and which schedule triggered the backup. Only present for backups initiated by a schedule. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application backup is scheduled for discovery • "discovering" - The application backup is in the process of being discovered • "running" - The application backup is running normally • "completed" - The application backup has completed successfully • "failed" - The application backup is in a permanent failure state • "removed" - The application backup is not currently accessible • "unknown" - The application backup state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application backup is unable to transition to "running", or why it has transitioned to "failed" or "removed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hooks run as part of a snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
backupCreationTimestamp	string	False	<p>JSON string containing a timestamp indicating when the backup was taken. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
totalBytes	number	False	<p>JSON number containing the total number of bytes in the backup.</p>
bytesDone	number	False	<p>JSON number containing the number of bytes backed up for a running backup. When the backup is completed, it matches with the totalBytes field.</p>

Name	Type	Required	Description
percentDone	number	False	JSON number containing the percentage complete for a running backup. When the backup is completed, it is set to "100".
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-appBackup",
  "version": "1.2",
  "id": "bab39d53-2d04-5297-b92e-58df89a2117b",
  "name": "app-name-245",
  "bucketID": "0afbe357-a717-4c7a-8b3d-d0368959c8de",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

```
Status: 401, Unauthorized
```

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/95",
  "title": "Backup not retrieved",
  "detail": "The backup wasn't retrieved because of an internal server issue.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete an application backup for an app

DELETE /accounts/{account_id}/k8s/v1/apps/{app_id}/appBackups/{appBackup_id}

Removes the specified Application Backup API resource. Backups in progress will be canceled, and then deleted.

Side Effects

- If a backup is complete, the backup data is deleted.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
appBackup_id	string	path	True	ID of the appBackup collection to list

Response

Status: 204, Indicates if the appBackup resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/97",
  "title": "Backup not deleted",
  "detail": "The backup wasn't deleted because of an internal server issue.",
  "status": "500"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/128",
  "title": "Backup cancellation not allowed",
  "detail": "A pending backup can't be canceled.",
  "status": "409"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Application Snapshot

Application Snapshot overview

The Application Snapshot API enables a user to create and view snapshots of a managed application.

Create a new application snapshot for an app

POST /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps

Indicates the desired values for the Application Snapshot API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>

Name	Type	In	Required	Description
app_id	string	path	True	ID of the containing app resource

Request Body

Indicates the desired values for the Application Snapshot API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-appSnap"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1" "1.2"
name	string	False	JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system assigns a name for the snapshot. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 63 Conforms to the DNS 1123 Label Schema

Name	Type	Required	Description
metadata	type_astra_metadata	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example request

```
{
  "type": "application/astra-appSnap",
  "version": "1.2",
  "name": "app-name-245"
}
```

Response

Status: 201, Returns the newly created appSnap resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "application/astra-appSnap"
version	string	True	<p>Version of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system assigns a name for the snapshot. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
scheduleID	string	False	JSON string containing an optional schedule ID that indicates that the snapshot was triggered by a schedule and specifies which schedule triggered the snapshot. Only present for snapshots initiated by a schedule. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
snapshotAppAsset	string	False	JSON string containing the ID of the application asset corresponding to the snapshot. This field will be returned when the state of the application snapshot is "completed". Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the snapshot.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application snapshot is scheduled for discovery • "discovering" - The application snapshot is in the process of being discovered • "running" - The application snapshot is running normally • "completed" - The application snapshot has completed • "failed" - The application snapshot is in a permanent failure state • "removed" - The application snapshot is not currently accessible • "unknown" - The application snapshot state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application snapshot is unable to transition to "running", or why it has transitioned to "failed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hook or hooks running as a part of a snapshot.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-appSnap",
  "version": "1.2",
  "id": "4f56a1df-8f47-541a-bd81-77260053a2f6",
  "name": "app-name-245",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the application snapshots for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>id,name,state</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: appSnap_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-appSnaps",
  "version": "1.2",
  "items": [
    [
      "2b6dafc3-2172-4431-a482-6306b2703130",
      "app-name-245",
      "pending"
    ],
    [
      "6fd9b31a-3924-4c9a-878b-175fa9538b8c",
      "app-name-244",
      "completed"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

appSnap_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-appSnap"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system assigns a name for the snapshot. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
scheduleID	string	False	JSON string containing an optional schedule ID that indicates that the snapshot was triggered by a schedule and specifies which schedule triggered the snapshot. Only present for snapshots initiated by a schedule. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
snapshotAppAsset	string	False	<p>JSON string containing the ID of the application asset corresponding to the snapshot. This field will be returned when the state of the application snapshot is "completed". Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
state	string	True	<p>JSON string containing a value indicating the operational state of the snapshot. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application snapshot is scheduled for discovery • "discovering" - The application snapshot is in the process of being discovered • "running" - The application snapshot is running normally • "completed" - The application snapshot has completed • "failed" - The application snapshot is in a permanent failure state • "removed" - The application snapshot is not currently accessible • "unknown" - The application snapshot state cannot be determined

Name	Type	Required	Description
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application snapshot is unable to transition to "running", or why it has transitioned to "failed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hook or hooks running as a part of a snapshot.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDe tail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an application snapshot

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps/{appSnap_id}

Returns the stored Application Snapshot API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the appSnap collection to list

Response

Status: 200, Returns the stored Application Snapshot API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-appSnap"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-specified name for the snapshot. If not specified, or when snapshots are initiated by a schedule, the system assigns a name for the snapshot.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Conforms to the DNS 1123 Label Schema
scheduleID	string	False	<p>JSON string containing an optional schedule ID that indicates that the snapshot was triggered by a schedule and specifies which schedule triggered the snapshot. Only present for snapshots initiated by a schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
snapshotAppAsset	string	False	<p>JSON string containing the ID of the application asset corresponding to the snapshot. This field will be returned when the state of the application snapshot is "completed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the snapshot.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The application snapshot is scheduled for discovery • "discovering" - The application snapshot is in the process of being discovered • "running" - The application snapshot is running normally • "completed" - The application snapshot has completed • "failed" - The application snapshot is in a permanent failure state • "removed" - The application snapshot is not currently accessible • "unknown" - The application snapshot state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why an application snapshot is unable to transition to "running", or why it has transitioned to "failed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
hookState	string	False	<p>JSON string containing a value indicating the state of any execution hook or hooks running as a part of a snapshot.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "failed" - One or more execution hooks have failed • "success" - There were zero or more applicable hooks and all were successful
hookStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about why "hookState" transitioned into "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-appSnap",
  "version": "1.2",
  "id": "4f56a1df-8f47-541a-bd81-77260053a2f6",
  "name": "app-name-245",
  "scheduleID": "1fe83650-9b3c-41ef-bb25-a2910c19c33e",
  "state": "pending",
  "stateUnready": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete an application snapshot

DELETE /accounts/{account_id}/k8s/v1/apps/{app_id}/appSnaps/{appSnap_id}

Removes the specified Application Snapshot API resource.

Side Effects

- If a snapshot is in progress, the snapshot is cancelled.
- If a snapshot is complete, the snapshot data is deleted.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
appSnap_id	string	path	True	ID of the appSnap collection to list

Response

Status: 204, Indicates if the appSnap resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/144",
  "title": "Backup in progress",
  "detail": "The snapshot wasn't deleted because it is currently being
  used by a backup.",
  "status": "409"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Bucket

Bucket overview

The Bucket API provides access to buckets used to store application backups in Astra.

Create a new bucket

POST /accounts/{account_id}/topology/v1/buckets

Indicates the desired values for the Bucket API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates the desired values for the Bucket API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-bucket"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2"
name	string	False	JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none">Minimum length: 1Maximum length: 256

Name	Type	Required	Description
credentialID	string	True	<p>JSON string containing the identifier of the credentials used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
provider	string	True	<p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> • "ontap-s3" • "storagegrid-s3" • "generic-s3" • "gcp" • "azure" • "aws"
bucketParameters	bucketParameters	True	<p>JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.</p>
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "name": "Test Bucket",
  "credentialID": "d5b3854c-38de-42c6-9269-b5c052aba76f",
  "provider": "gcp",
  "bucketParameters": {
    "gcp": {
      "bucketName": "bucketName"
    }
  }
}
```

Response

Status: 201, Returns the newly created bucket resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-bucket"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-assigned name for the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256
credentialID	string	True	<p>JSON string containing the identifier of the credentials used to access the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
state	string	True	<p>JSON string containing a value indicating the operational state of the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The bucket is scheduled for discovery • "available" - The bucket is available for use • "failed" - The bucket is in a permanent failure state • "removed" - The bucket is not currently accessible • "unknown" - The bucket state cannot be determined
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
provider	string	True	<p>JSON string indicating the bucket protocol that can be used to access the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "ontap-s3" • "storagegrid-s3" • "generic-s3" • "gcp" • "azure" • "aws"
bucketParameters	bucketParameters	True	<p>JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "id": "9b296ce0-c545-5022-acfa-1980c5aeea97",
  "name": "Test Bucket",
  "credentialID": "8f039324-7795-40bf-a5ca-4442580f7ab0",
  "state": "available",
  "stateDetails": [],
  "provider": "gcp",
  "bucketParameters": {
    "gcp": {
      "bucketName": "bucketName"
    }
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

Name	Type	Required	Description
serverURL	string	True	JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 1023
bucketName	string	True	JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

gcp

JSON object that provides Google Cloud protocol parameters.

Name	Type	Required	Description
bucketName	string	True	JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

azure

JSON object that provides Azure protocol parameters.

Name	Type	Required	Description
storageAccount	string	True	JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63
bucketName	string	True	JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

Name	Type	Required	Description
s3	s3	False	JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).
gcp	gcp	False	JSON object that provides Google Cloud protocol parameters.
azure	azure	False	JSON object that provides Azure protocol parameters.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

If not specified on create, a metadata object will be created with no labels.

If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all buckets

GET /accounts/{account_id}/topology/v1/buckets

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: bucket_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-buckets",
  "version": "1.2",
  "items": [
    [
      "4c753e39-25e9-4b36-a8de-69f168aa59cd",
      "Test Bucket",
      "gcp"
    ],
    [
      "d8fd585d-6429-4c08-a308-af193a88eac7",
      "Local",
      "ontap-s3"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

Name	Type	Required	Description
serverURL	string	True	JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 1023
bucketName	string	True	JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

gcp

JSON object that provides Google Cloud protocol parameters.

Name	Type	Required	Description
bucketName	string	True	JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

azure

JSON object that provides Azure protocol parameters.

Name	Type	Required	Description
storageAccount	string	True	JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63
bucketName	string	True	JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

Name	Type	Required	Description
s3	s3	False	JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).
gcp	gcp	False	JSON object that provides Google Cloud protocol parameters.
azure	azure	False	JSON object that provides Azure protocol parameters.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

bucket_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-bucket"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256
credentialID	string	True	JSON string containing the identifier of the credentials used to access the bucket. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
state	string	True	JSON string containing a value indicating the operational state of the bucket. Defined values are: <ul style="list-style-type: none"> • "pending" - The bucket is scheduled for discovery • "available" - The bucket is available for use • "failed" - The bucket is in a permanent failure state • "removed" - The bucket is not currently accessible • "unknown" - The bucket state cannot be determined

Name	Type	Required	Description
stateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
provider	string	True	<p>JSON string indicating the bucket protocol that can be used to access the bucket. Defined values are:</p> <ul style="list-style-type: none"> • "ontap-s3" • "storagegrid-s3" • "generic-s3" • "gcp" • "azure" • "aws"
bucketParameters	bucketParameters	True	<p>JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a bucket

GET /accounts/{account_id}/topology/v1/buckets/{bucket_id}

Returns the stored Bucket API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
bucket_id	string	path	True	ID of the bucket collection to list

Response

Status: 200, Returns the stored Bucket API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-bucket"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-assigned name for the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256
credentialID	string	True	<p>JSON string containing the identifier of the credentials used to access the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
state	string	True	<p>JSON string containing a value indicating the operational state of the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The bucket is scheduled for discovery • "available" - The bucket is available for use • "failed" - The bucket is in a permanent failure state • "removed" - The bucket is not currently accessible • "unknown" - The bucket state cannot be determined
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
provider	string	True	<p>JSON string indicating the bucket protocol that can be used to access the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "ontap-s3" • "storagegrid-s3" • "generic-s3" • "gcp" • "azure" • "aws"
bucketParameters	bucketParameters	True	<p>JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "id": "9b296ce0-c545-5022-acfa-1980c5aeea97",
  "name": "Test Bucket",
  "credentialID": "8f039324-7795-40bf-a5ca-4442580f7ab0",
  "state": "available",
  "stateDetails": [],
  "provider": "gcp",
  "bucketParameters": {
    "gcp": {
      "bucketName": "bucketName"
    }
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

Name	Type	Required	Description
serverURL	string	True	JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 1023
bucketName	string	True	JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

gcp

JSON object that provides Google Cloud protocol parameters.

Name	Type	Required	Description
bucketName	string	True	JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

azure

JSON object that provides Azure protocol parameters.

Name	Type	Required	Description
storageAccount	string	True	JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63
bucketName	string	True	JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

Name	Type	Required	Description
s3	s3	False	JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).
gcp	gcp	False	JSON object that provides Google Cloud protocol parameters.
azure	azure	False	JSON object that provides Azure protocol parameters.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
 - If not specified on create, a metadata object will be created with no labels.
 - If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a bucket

PUT /accounts/{account_id}/topology/v1/buckets/{bucket_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code>
bucket_id	string	path	True	ID of the bucket collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-bucket"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	False	JSON string containing a user-assigned name for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 256
credentialID	string	False	JSON string containing the identifier of the credentials used to access the bucket. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The bucket is scheduled for discovery • "available" - The bucket is available for use • "failed" - The bucket is in a permanent failure state • "removed" - The bucket is not currently accessible • "unknown" - The bucket state cannot be determined
stateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why "state" transitioned to "removed" or "failed".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
provider	string	False	<p>JSON string indicating the bucket protocol that can be used to access the bucket.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "ontap-s3" • "storagegrid-s3" • "generic-s3" • "gcp" • "azure" • "aws"

Name	Type	Required	Description
bucketParameters	bucketParameters	False	JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-bucket",
  "version": "1.2",
  "name": "New Bucket Name"
}
```

Response

Status: 204, Indicates if the bucket resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

s3

JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).

Name	Type	Required	Description
serverURL	string	False	JSON string containing a URL to the base path for the bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 1023
bucketName	string	False	JSON string containing the name of the S3 bucket. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

gcp

JSON object that provides Google Cloud protocol parameters.

Name	Type	Required	Description
bucketName	string	False	JSON string containing the name of the backing Google Cloud bucket name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

azure

JSON object that provides Azure protocol parameters.

Name	Type	Required	Description
storageAccount	string	False	JSON string containing the Azure storage account name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63
bucketName	string	False	JSON string containing the name of the backing Azure blob name. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

bucketParameters

JSON object that provides bucket provider-specific information required to access the bucket. The specific values in this bucket vary per provider.

Name	Type	Required	Description
s3	s3	False	JSON object that provides Simple Storage Service (S3) protocol parameters. (Use this object for all S3 type providers).
gcp	gcp	False	JSON object that provides Google Cloud protocol parameters.
azure	azure	False	JSON object that provides Azure protocol parameters.

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a bucket

DELETE /accounts/{account_id}/topology/v1/buckets/{bucket_id}

Removes the specified Bucket API resource.

Side Effects

- Internal data structures are cleaned up.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
bucket_id	string	path	True	ID of the bucket collection to list

Response

Status: 204, Indicates if the bucket resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Certificate

Certificate overview

The Certificate App API represents admin-trusted certificates that are used for establishing outgoing connections.

Create a new certificate

POST /accounts/{account_id}/core/v1/certificates

Indicates the desired values for the Certificate API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates the desired values for the Certificate API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-certificate"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
certUse	string	False	JSON string indicating the use of the certificate. If not specified, defaults to "rootCA". Defined values are: <ul style="list-style-type: none"> • "rootCA" - The certificate is a certificate authority (CA) certificate used to trust any certificate signed by that CA. • "intermediateCA" - The certificate is an intermediate CA certificate issued by a root CA.
cert	string	True	JSON string containing a base64 encoded PKCS-11 formatted certificate (PEM). Defined values are: <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema

Name	Type	Required	Description
isSelfSigned	string	False	<p>JSON string indicating whether the certificate is self-signed.</p> <p>If not provided on create, the value defaults to "false".</p> <p>On update:</p> <ul style="list-style-type: none"> • If the value is provided, that value will be used. • If the value is not provided and the "cert" field is included in the update, the value will be set to "false". • If the value is not provided and the "cert" field is not included in the update, the existing value will be retained. Defined values are: <ul style="list-style-type: none"> • "true" - The certificate is self-signed. • "false" - The certificate is not self-signed.
trustStateDesired	string	False	<p>JSON string containing a value indicating whether the certificate is trusted.</p> <p>If not specified on create, the default value is "trusted".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "untrusted" - The certificate is not trusted. • "trusted" - The certificate is marked as trusted.

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-certificate",
  "version": "1.1",
  "certUse": "rootCA",
  "cert":
  "LS0tLS1CRUdJTiBDRVJUSUZJQ0FURS0tLS0tCk1JSUZyVENDQTVXZ0F3MVJHbnFGbUJSSW
  RyV1kwPQotLS0tLUVORCBDRVJUSUZJQ0FURS0tLS0t"
}
```

Response

Status: 201, Returns the newly created certificate resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> "application/astra-certificate"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
certUse	string	True	JSON string indicating the use of the certificate. If not specified, defaults to "rootCA". Defined values are: <ul style="list-style-type: none"> • "rootCA" - The certificate is a certificate authority (CA) certificate used to trust any certificate signed by that CA. • "intermediateCA" - The certificate is an intermediate CA certificate issued by a root CA.
cert	string	True	JSON string containing a base64 encoded PKCS-11 formatted certificate (PEM). Defined values are: <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema
cn	string	True	JSON string containing a common name extracted from the certificate. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511

Name	Type	Required	Description
expiryTimestamp	string	True	<p>JSON string containing a timestamp indicating when the certificate expires.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
isSelfSigned	string	True	<p>JSON string indicating whether the certificate is self-signed.</p> <p>If not provided on create, the value defaults to "false".</p> <p>On update:</p> <ul style="list-style-type: none"> • If the value is provided, that value will be used. • If the value is not provided and the "cert" field is included in the update, the value will be set to "false". • If the value is not provided and the "cert" field is not included in the update, the existing value will be retained. <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The certificate is self-signed. • "false" - The certificate is not self-signed.

Name	Type	Required	Description
trustState	string	True	<p>JSON string containing one of a set of enumerated values indicating whether the certificate is trusted. Defined values are:</p> <ul style="list-style-type: none"> • "untrusted" - The certificate is not trusted. • "trusted" - The certificate is marked as trusted. • "expired" - The certificate is expired, so is neither trusted or not trusted.
trustStateTransitions	array[type_astra_stateTransition]	True	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
trustStateDesired	string	False	<p>JSON string containing a value indicating whether the certificate is trusted. If not specified on create, the default value is "trusted". Defined values are:</p> <ul style="list-style-type: none"> • "untrusted" - The certificate is not trusted. • "trusted" - The certificate is marked as trusted.

Name	Type	Required	Description
trustStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the trust state of the certificate. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-certificate",
  "version": "1.1",
  "id": "a26cbcd4-2183-58ce-aa19-e37ca8b0531a",
  "certUse": "rootCA",
  "cert":
  "LS0tLS1CRUdJTtIBDRVJUSUZJQ0FURStLS0tCk1JSUZyVENDQTVXZ0F3MVJHbnFGbUJSSW
  RyV1kwPQotLS0tLUVORCBDRVJUSUZJQ0FURStLS0t",
  "cn": "vcenter.example.com",
  "isSelfSigned": "false",
  "expiryTimestamp": "2022-03-23T16:48:38.5233461Z",
  "trustState": "trusted",
  "trustStateTransitions": [
    {
      "from": "untrusted",
      "to": [
        "trusted"
      ]
    },
    {
      "from": "trusted",
      "to": [
        "untrusted"
      ]
    }
  ],
  "trustStateDesired": "trusted",
  "trustStateDetails": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/7",
  "title": "Invalid JSON payload",
  "detail": "The request body is not valid JSON.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Error

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field

Name	Type	Required	Description
reason	string	True	Reason why the request body field is invalid

List all certificates

GET /accounts/{account_id}/core/v1/certificates

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
continue		query	False	Indicates the token to resume listing from. <p>URL examples:</p> <pre>"continue=<continue token="" from="" collection="" metadata="">"</continue></pre> <p>OpenAPI examples:</p> <pre>"<continue token="" from="" collection="" metadata="">"</continue>&lt;/continue&gt;</pre>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p> <ul style="list-style-type: none"> • example: certUse%20eq%20'rootCA'
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> • example: id,cn,isSelfSigned

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"
orderBy	string	query	False	Indicates the sort order of resource when listing a collection. URL examples: "orderBy=name", "orderBy=name%20desc" OpenAPI examples: "name desc"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: certificate_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-certificates",
  "version": "1.1",
  "items": [
    [
      "f97f3441-075e-4f9b-9d1e-47f9f62a3fc4",
      "prod.region-1.example.com",
      "true"
    ],
    [
      "5e365b4d-034f-4f13-95ef-d3a7fbc0df3d",
      "prod.region-2.example.com",
      "false"
    ],
    [
      "11ceb350-1999-4b79-80a6-46a980a27856",
      "prod.example.com",
      "false"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/164",
  "title": "Requested resource in unexpected state",
  "detail": "The requested resource can't be returned because it isn't in the expected state. Wait for the conflict to be resolved and retry the request.",
  "status": "409"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

certificate_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-certificate"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
certUse	string	True	JSON string indicating the use of the certificate. If not specified, defaults to "rootCA". Defined values are: <ul style="list-style-type: none"> "rootCA" - The certificate is a certificate authority (CA) certificate used to trust any certificate signed by that CA. "intermediateCA" - The certificate is an intermediate CA certificate issued by a root CA.
cert	string	True	JSON string containing a base64 encoded PKCS-11 formatted certificate (PEM). Defined values are: <ul style="list-style-type: none"> Conforms to the base64 Encoded Data Schema

Name	Type	Required	Description
cn	string	True	JSON string containing a common name extracted from the certificate. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 511
expiryTimestamp	string	True	JSON string containing a timestamp indicating when the certificate expires. Defined values are: <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
isSelfSigned	string	True	<p>JSON string indicating whether the certificate is self-signed.</p> <p>If not provided on create, the value defaults to "false".</p> <p>On update:</p> <ul style="list-style-type: none">• If the value is provided, that value will be used.• If the value is not provided and the "cert" field is included in the update, the value will be set to "false".• If the value is not provided and the "cert" field is not included in the update, the existing value will be retained. <p>Defined values are:</p> <ul style="list-style-type: none">• "true" - The certificate is self-signed.• "false" - The certificate is not self-signed.

Name	Type	Required	Description
trustState	string	True	<p>JSON string containing one of a set of enumerated values indicating whether the certificate is trusted. Defined values are:</p> <ul style="list-style-type: none"> • "untrusted" - The certificate is not trusted. • "trusted" - The certificate is marked as trusted. • "expired" - The certificate is expired, so is neither trusted or not trusted.
trustStateTransitions	array[type_astra_stateTransition]	True	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
trustStateDesired	string	False	<p>JSON string containing a value indicating whether the certificate is trusted. If not specified on create, the default value is "trusted". Defined values are:</p> <ul style="list-style-type: none"> • "untrusted" - The certificate is not trusted. • "trusted" - The certificate is marked as trusted.

Name	Type	Required	Description
trustStateDetails	array[type_astra_stateDe tail]	True	JSON array of JSON objects that lists additional details about the trust state of the certificate. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_up date	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a certificate

GET /accounts/{account_id}/core/v1/certificates/{certificate_id}

Returns the stored Certificate API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
certificate_id	string	path	True	ID of the certificate collection to list

Response

Status: 200, Returns the stored Certificate API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-certificate"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
certUse	string	True	JSON string indicating the use of the certificate. If not specified, defaults to "rootCA". Defined values are: <ul style="list-style-type: none"> • "rootCA" - The certificate is a certificate authority (CA) certificate used to trust any certificate signed by that CA. • "intermediateCA" - The certificate is an intermediate CA certificate issued by a root CA.
cert	string	True	JSON string containing a base64 encoded PKCS-11 formatted certificate (PEM). Defined values are: <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema
cn	string	True	JSON string containing a common name extracted from the certificate. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511

Name	Type	Required	Description
expiryTimestamp	string	True	<p>JSON string containing a timestamp indicating when the certificate expires.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
isSelfSigned	string	True	<p>JSON string indicating whether the certificate is self-signed.</p> <p>If not provided on create, the value defaults to "false".</p> <p>On update:</p> <ul style="list-style-type: none"> • If the value is provided, that value will be used. • If the value is not provided and the "cert" field is included in the update, the value will be set to "false". • If the value is not provided and the "cert" field is not included in the update, the existing value will be retained. <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The certificate is self-signed. • "false" - The certificate is not self-signed.

Name	Type	Required	Description
trustState	string	True	<p>JSON string containing one of a set of enumerated values indicating whether the certificate is trusted. Defined values are:</p> <ul style="list-style-type: none"> • "untrusted" - The certificate is not trusted. • "trusted" - The certificate is marked as trusted. • "expired" - The certificate is expired, so is neither trusted or not trusted.
trustStateTransitions	array[type_astra_stateTransition]	True	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
trustStateDesired	string	False	<p>JSON string containing a value indicating whether the certificate is trusted. If not specified on create, the default value is "trusted". Defined values are:</p> <ul style="list-style-type: none"> • "untrusted" - The certificate is not trusted. • "trusted" - The certificate is marked as trusted.

Name	Type	Required	Description
trustStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the trust state of the certificate. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-certificate",
  "version": "1.1",
  "id": "a26cbcd4-2183-58ce-aa19-e37ca8b0531a",
  "certUse": "rootCA",
  "cert":
  "LS0tLS1CRUdJTtiBDRVJUSUZJQ0FURS0tLS0tCk1JSUZyVENDQTVXZ0F3MVJHbnFGbUJSSW
  RyV1kwPQotLS0tLUVORCBDRVJUSUZJQ0FURS0tLS0t",
  "cn": "vcenter.example.com",
  "expiryTimestamp": "2022-03-23T16:48:38.5233461Z",
  "isSelfSigned": "true",
  "trustState": "untrusted",
  "trustStateTransitions": [
    {
      "from": "untrusted",
      "to": [
        "trusted"
      ]
    },
    {
      "from": "trusted",
      "to": [
        "untrusted"
      ]
    }
  ],
  "trustStateDetails": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/164",
  "title": "Requested resource in unexpected state",
  "detail": "The requested resource can't be returned because it isn't in the expected state. Wait for the conflict to be resolved and retry the request.",
  "status": "409"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

Modify a certificate

PUT /accounts/{account_id}/core/v1/certificates/{certificate_id}

Replaces the entire stored resource with the supplied JSON request body.

Side Effects

- An updated CA certificate will be updated in the trust store.
- If an existing trusted CA certificate becomes untrusted, it will be removed from the trust store.
- If a certificate body is updated ("cert" field), the "isSelfSigned" indicator must be included to indicate the state of the new certificate. If the "isSelfSigned" indicator is not included in this case, the value will be set to "false".
- If an update does not modify the certificate body ("cert" field), the "isSelfSigned" indicator is optional and the existing value will be retained if not provided.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
certificate_id	string	path	True	ID of the certificate collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body.

Side Effects

- An updated CA certificate will be updated in the trust store.
- If an existing trusted CA certificate becomes untrusted, it will be removed from the trust store.
- If a certificate body is updated ("cert" field), the "isSelfSigned" indicator must be included to indicate the state of the new certificate. If the "isSelfSigned" indicator is not included in this case, the value will be set to "false".
- If an update does not modify the certificate body ("cert" field), the "isSelfSigned" indicator is optional and the existing value will be retained if not provided.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-certificate"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
certUse	string	False	JSON string indicating the use of the certificate. If not specified, defaults to "rootCA". Defined values are: <ul style="list-style-type: none"> • "rootCA" - The certificate is a certificate authority (CA) certificate used to trust any certificate signed by that CA. • "intermediateCA" - The certificate is an intermediate CA certificate issued by a root CA.
cert	string	False	JSON string containing a base64 encoded PKCS-11 formatted certificate (PEM). Defined values are: <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema

Name	Type	Required	Description
cn	string	False	<p>JSON string containing a common name extracted from the certificate.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511
expiryTimestamp	string	False	<p>JSON string containing a timestamp indicating when the certificate expires.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
isSelfSigned	string	False	<p>JSON string indicating whether the certificate is self-signed.</p> <p>If not provided on create, the value defaults to "false".</p> <p>On update:</p> <ul style="list-style-type: none"> • If the value is provided, that value will be used. • If the value is not provided and the "cert" field is included in the update, the value will be set to "false". • If the value is not provided and the "cert" field is not included in the update, the existing value will be retained. <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The certificate is self-signed. • "false" - The certificate is not self-signed.

Name	Type	Required	Description
trustState	string	False	<p>JSON string containing one of a set of enumerated values indicating whether the certificate is trusted. Defined values are:</p> <ul style="list-style-type: none"> • "untrusted" - The certificate is not trusted. • "trusted" - The certificate is marked as trusted. • "expired" - The certificate is expired, so is neither trusted or not trusted.
trustStateTransitions	array[type_astra_stateTransition]	False	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p>
trustStateDesired	string	False	<p>JSON string containing a value indicating whether the certificate is trusted. If not specified on create, the default value is "trusted". Defined values are:</p> <ul style="list-style-type: none"> • "untrusted" - The certificate is not trusted. • "trusted" - The certificate is marked as trusted.

Name	Type	Required	Description
trustStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about the trust state of the certificate. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-certificate",
  "version": "1.1",
  "trustStateDesired": "trusted"
}
```

Response

Status: 204, Indicates if the certificate resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a certificate

DELETE /accounts/{account_id}/core/v1/certificates/{certificate_id}

Removes the specified Certificate API resource.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
certificate_id	string	path	True	ID of the certificate collection to list

Response

Status: 204, Indicates if the certificate resource was deleted.

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Error

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Cloud

Cloud overview

The Cloud API provides access to cloud resources to allow clients to connect to specific clouds to manage clusters and applications.

Create a new cloud

POST /accounts/{account_id}/topology/v1/clouds

Indicates the desired values for the Cloud API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>

Request Body

Indicates the desired values for the Cloud API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-cloud"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"

Name	Type	Required	Description
name	string	True	<p>JSON string containing the name of the cloud. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
cloudType	string	True	<p>JSON string containing a value indicating the type of cloud. Defined values are:</p> <ul style="list-style-type: none"> • "gcp" - The cloud is provided by Google • "azure" - The cloud is provided by Microsoft • "aws" - The cloud is provided by Amazon • "private" - The cloud is customer managed
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the service account for the cloud. This is required for cloudType "gcp", "azure" and "aws". Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
defaultBucketID	string	False	<p>JSON string containing the ID of a bucket that is to be used by default when creating backups for applications within the cloud. This is required when cloning applications across clusters and is used as a default if a bucket is not specified when creating backups and schedules.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```

{
  "type": "application/astra-cloud",
  "version": "1.1",
  "name": "GKE",
  "cloudType": "gcp",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31"
}

```


Response

Status: 201, Returns the newly created cloud resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cloud"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing the name of the cloud. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cloud.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cloud is scheduled for discovery • "discovering" - The cloud is in the process of being discovered • "provisioning" - The cloud is in the process of being provisioned • "running" - The cloud is running normally • "failed" - The cloud is in a permanent failure state • "removed" - The cloud is not currently accessible • "unknown" - The cloud state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a cloud is unable to transition to "running" or why it has transitioned to "failed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
cloudType	string	True	<p>JSON string containing a value indicating the type of cloud.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "gcp" - The cloud is provided by Google • "azure" - The cloud is provided by Microsoft • "aws" - The cloud is provided by Amazon • "private" - The cloud is customer managed
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the service account for the cloud. This is required for cloudType "gcp", "azure" and "aws".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
defaultBucketID	string	False	<p>JSON string containing the ID of a bucket that is to be used by default when creating backups for applications within the cloud. This is required when cloning applications across clusters and is used as a default if a bucket is not specified when creating backups and schedules.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-cloud",
  "version": "1.1",
  "id": "1c9512c3-ec62-5ed8-8013-02fc090b9d03",
  "name": "GKE",
  "state": "discovering",
  "stateUnready": [
    "Cloud discovery in progress"
  ],
  "cloudType": "gcp",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all clouds

GET /accounts/{account_id}/topology/v1/clouds

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name,state
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: cloud_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-clouds",
  "version": "1.1",
  "items": [
    [
      "2f9e63fa-8ba8-414a-a57c-0f3042b80682",
      "gcp",
      "discovering"
    ],
    [
      "f723febe-b167-44dd-b07d-c075a8bbe4f3",
      "aws",
      "failed"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

cloud_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cloud"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing the name of the cloud. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cloud.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cloud is scheduled for discovery • "discovering" - The cloud is in the process of being discovered • "provisioning" - The cloud is in the process of being provisioned • "running" - The cloud is running normally • "failed" - The cloud is in a permanent failure state • "removed" - The cloud is not currently accessible • "unknown" - The cloud state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a cloud is unable to transition to "running" or why it has transitioned to "failed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
cloudType	string	True	<p>JSON string containing a value indicating the type of cloud.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "gcp" - The cloud is provided by Google • "azure" - The cloud is provided by Microsoft • "aws" - The cloud is provided by Amazon • "private" - The cloud is customer managed
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the service account for the cloud. This is required for cloudType "gcp", "azure" and "aws".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
defaultBucketID	string	False	<p>JSON string containing the ID of a bucket that is to be used by default when creating backups for applications within the cloud. This is required when cloning applications across clusters and is used as a default if a bucket is not specified when creating backups and schedules.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a cloud

GET /accounts/{account_id}/topology/v1/clouds/{cloud_id}

Returns the stored Cloud API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
cloud_id	string	path	True	ID of the cloud collection to list

Response

Status: 200, Returns the stored Cloud API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-cloud"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing the name of the cloud. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
state	string	True	<p>JSON string containing a value indicating the operational state of the cloud. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cloud is scheduled for discovery • "discovering" - The cloud is in the process of being discovered • "provisioning" - The cloud is in the process of being provisioned • "running" - The cloud is running normally • "failed" - The cloud is in a permanent failure state • "removed" - The cloud is not currently accessible • "unknown" - The cloud state cannot be determined

Name	Type	Required	Description
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a cloud is unable to transition to "running" or why it has transitioned to "failed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
cloudType	string	True	<p>JSON string containing a value indicating the type of cloud. Defined values are:</p> <ul style="list-style-type: none"> • "gcp" - The cloud is provided by Google • "azure" - The cloud is provided by Microsoft • "aws" - The cloud is provided by Amazon • "private" - The cloud is customer managed
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the service account for the cloud. This is required for cloudType "gcp", "azure" and "aws". Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
defaultBucketID	string	False	<p>JSON string containing the ID of a bucket that is to be used by default when creating backups for applications within the cloud. This is required when cloning applications across clusters and is used as a default if a bucket is not specified when creating backups and schedules.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-cloud",
  "version": "1.1",
  "id": "1c9512c3-ec62-5ed8-8013-02fc090b9d03",
  "name": "GKE",
  "state": "discovering",
  "stateUnready": [
    "Cloud discovery in progress"
  ],
  "cloudType": "gcp",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a cloud

PUT /accounts/{account_id}/topology/v1/clouds/{cloud_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- An update will trigger a rediscovery of SAs and clusters.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
cloud_id	string	path	True	ID of the cloud collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- An update will trigger a rediscovery of SAs and clusters.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-cloud"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>JSON string containing the name of the cloud. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
state	string	False	<p>JSON string containing a value indicating the operational state of the cloud. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cloud is scheduled for discovery • "discovering" - The cloud is in the process of being discovered • "provisioning" - The cloud is in the process of being provisioned • "running" - The cloud is running normally • "failed" - The cloud is in a permanent failure state • "removed" - The cloud is not currently accessible • "unknown" - The cloud state cannot be determined

Name	Type	Required	Description
stateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a cloud is unable to transition to "running" or why it has transitioned to "failed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
cloudType	string	False	<p>JSON string containing a value indicating the type of cloud. Defined values are:</p> <ul style="list-style-type: none"> • "gcp" - The cloud is provided by Google • "azure" - The cloud is provided by Microsoft • "aws" - The cloud is provided by Amazon • "private" - The cloud is customer managed
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the service account for the cloud. This is required for cloudType "gcp", "azure" and "aws". Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
defaultBucketID	string	False	<p>JSON string containing the ID of a bucket that is to be used by default when creating backups for applications within the cloud. This is required when cloning applications across clusters and is used as a default if a bucket is not specified when creating backups and schedules.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-cloud",
  "version": "1.1"
}
```

Response

Status: 204, Indicates if the cloud resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a cloud

DELETE /accounts/{account_id}/topology/v1/clouds/{cloud_id}

Deletes the requested cloud instance and any non-managed clusters and volumes associated with that specific cloud.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
cloud_id	string	path	True	ID of the cloud collection to list

Response

```
Status: 204, Indicates if the cloud resource was deleted.
```

Response

```
Status: 401, Unauthorized
```

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/141",
  "title": "Action blocked: Delete cloud instance",
  "detail": "The cloud instance wasn't deleted because there are managed clusters associated with this cloud instance.",
  "status": "409"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Cluster

Cluster overview

The Cluster API represents unmanaged Kubernetes clusters.

Create a new cluster for a cloud

POST /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters

Indicates the desired values for the Cluster API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
cloud_id	string	path	True	ID of the containing cloud resource

Request Body

Indicates the desired values for the Cluster API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cluster"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"• "1.3"• "1.4"• "1.5"
name	string	False	JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If privateRouteID and connectorCapabilities with at least the relay option are provided, credentialID is optional. If they are not provided, credentialID is required, otherwise, an error is generated. If credentialID and a relay capable connector is provided, an error is generated.
privateRouteID	string	False	<p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
connectorCapabilities	array[string]	False	Capabilities of the connector that is associated with this cluster. Optional for backwards compatibility. If not present, proxy is the assumed capability.
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-cluster",
  "version": "1.5",
  "name": "GKE-22",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31"
}
```

Response

Status: 201, Returns the newly created cluster resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-cluster"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3" • "1.4" • "1.5"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots
protectionStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.

Name	Type	Required	Description
snapshotSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
managedTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was brought under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This key is only returned when a cluster has a managedState of "managed".</p>

Name	Type	Required	Description
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"
inUse	string	True	<p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	True	<p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	False	<p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	False	<p>JSON string containing a value indicating the extended versioning information for the cluster environment.</p> <p>For Kubernetes clusters, this is the full Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class set in Kubernetes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
cloudID	string	True	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema <p>If privateRouteID and connectorCapabilities with at least the relay option are provided, credentialID is optional. If they are not provided, credentialID is required, otherwise, an error is generated. If credentialID and a relay capable connector is provided, an error is generated.</p>
location	string	False	<p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
isMultizonal	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone
privateRouteID	string	False	<p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
connectorCapabilities	array[string]	False	<p>Capabilities of the connector that is associated with this cluster. Optional for backwards compatibility. If not present, proxy is the assumed capability.</p>
apiServiceID	string	False	<p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-cluster",
  "version": "1.5",
  "id": "547e24b9-ddf4-558f-8397-e97e732868e4",
  "name": "GKE-22",
  "state": "running",
  "stateUnready": [],
  "managedState": "unmanaged",
  "managedStateUnready": [],
  "protectionState": "full",
  "protectionStateDetails": [],
  "tridentVersion": "21.07.2",
  "tridentManagedState": "managed",
  "tridentManagedStateDetails": [],
  "inUse": "false",
  "clusterType": "kubernetes",
  "clusterVersion": "1.91.1",
  "clusterVersionString": "1.19.1",
  "clusterCreationTimestamp": "2020-08-06T12:24:52.256624Z",
  "namespaces": [
    "kube-system",
    "kube-public",
    "my-app-1"
  ],
  "defaultStorageClass": "31c95aba-99d9-4987-b1bb-000dfce5952c",
  "cloudID": "548bdc1f-f00e-4a23-a062-83265d224d46",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31",
  "location": "europe-west4",
  "isMultizonal": "false",
  "apiServiceID": "6bf33af2-872a-4553-a891-26b510c3edbe",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/64",
  "title": "Storage classes not found",
  "detail": "Storage classes from Trident weren't found.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the clusters for a cloud

GET /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
cloud_id	string	path	True	ID of the containing cloud resource
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>id,name,managedState</code>

Name	Type	In	Required	Description
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: cluster_1.5_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-clusters",
  "version": "1.5",
  "items": [
    [
      "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
      "GKE-21",
      "managed"
    ],
    [
      "04dc80fa-d1d8-4850-a49f-3b70d0ec1369",
      "GKE-22",
      "unmanaged"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

cluster_1.5_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cluster"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3" • "1.4" • "1.5"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots
protectionStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.
snapshotSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.

Name	Type	Required	Description
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
managedTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was brought under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This key is only returned when a cluster has a managedState of "managed".</p>
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema

Name	Type	Required	Description
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"
inUse	string	True	<p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	True	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	False	<p>JSON string containing a value indicating the semantic versioning representation of the cluster environment.</p> <p>For Kubernetes clusters, this is the Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	False	<p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
cloudID	string	True	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema <p>If privateRouteID and connectorCapabilities with at least the relay option are provided, credentialID is optional. If they are not provided, credentialID is required, otherwise, an error is generated.</p> <p>If credentialID and a relay capable connector is provided, an error is generated.</p>
location	string	False	<p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
isMultizonal	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone
privateRouteID	string	False	<p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
connectorCapabilities	array[string]	False	<p>Capabilities of the connector that is associated with this cluster. Optional for backwards compatibility. If not present, proxy is the assumed capability.</p>
apiServiceID	string	False	<p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a cluster for a cloud

GET /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}

Returns the stored Cluster API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
cloud_id	string	path	True	ID of the containing cloud resource
cluster_id	string	path	True	ID of the cluster collection to list

Response

Status: 200, Returns the stored Cluster API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-cluster"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2""1.3""1.4""1.5"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots
protectionStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.

Name	Type	Required	Description
snapshotSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
managedTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was brought under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This key is only returned when a cluster has a managedState of "managed".</p>

Name	Type	Required	Description
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"
inUse	string	True	<p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	True	<p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	False	<p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	False	<p>JSON string containing a value indicating the extended versioning information for the cluster environment.</p> <p>For Kubernetes clusters, this is the full Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class set in Kubernetes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
cloudID	string	True	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If privateRouteID and connectorCapabilities with at least the relay option are provided, credentialID is optional. If they are not provided, credentialID is required, otherwise, an error is generated. If credentialID and a relay capable connector is provided, an error is generated.
location	string	False	<p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
isMultizonal	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone
privateRouteID	string	False	<p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
connectorCapabilities	array[string]	False	<p>Capabilities of the connector that is associated with this cluster. Optional for backwards compatibility. If not present, proxy is the assumed capability.</p>
apiServiceID	string	False	<p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-cluster",
  "version": "1.5",
  "id": "547e24b9-ddf4-558f-8397-e97e732868e4",
  "name": "GKE-22",
  "state": "running",
  "stateUnready": [],
  "managedState": "unmanaged",
  "managedStateUnready": [],
  "protectionState": "full",
  "protectionStateDetails": [],
  "tridentVersion": "21.07.2",
  "tridentManagedState": "managed",
  "tridentManagedStateDetails": [],
  "inUse": "false",
  "clusterType": "kubernetes",
  "clusterVersion": "1.91.1",
  "clusterVersionString": "1.19.1",
  "clusterCreationTimestamp": "2020-08-06T12:24:52.256624Z",
  "namespaces": [
    "kube-system",
    "kube-public",
    "my-app-1"
  ],
  "defaultStorageClass": "31c95aba-99d9-4987-b1bb-000dfce5952c",
  "cloudID": "548bdc1f-f00e-4a23-a062-83265d224d46",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31",
  "location": "europe-west4",
  "isMultizonal": "false",
  "apiServiceID": "6bf33af2-872a-4553-a891-26b510c3edbe",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/65",
  "title": "Cluster GET not performed",
  "detail": "The cluster GET call didn't perform the lookup operation on the cluster.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a cluster for a cloud

PUT /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the cluster is in a managed state, an update to credentialID will eventually trigger another attempt to collect the cluster.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: {{.Account}}
cloud_id	string	path	True	ID of the containing cloud resource
cluster_id	string	path	True	ID of the cluster collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the cluster is in a managed state, an update to credentialID will eventually trigger another attempt to collect the cluster.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cluster"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3" • "1.4" • "1.5"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	False	JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined
stateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	False	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management

Name	Type	Required	Description
protectionState	string	False	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots
protectionStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.

Name	Type	Required	Description
snapshotSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.
managedStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
managedTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was brought under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This key is only returned when a cluster has a managedState of "managed".</p>

Name	Type	Required	Description
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"
inUse	string	False	<p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	False	<p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	False	<p>JSON string containing a value indicating the extended versioning information for the cluster environment.</p> <p>For Kubernetes clusters, this is the full Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class set in Kubernetes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
cloudID	string	False	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema <p>If privateRouteID and connectorCapabilities with at least the relay option are provided, credentialID is optional. If they are not provided, credentialID is required, otherwise, an error is generated. If credentialID and a relay capable connector is provided, an error is generated.</p>
location	string	False	<p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
isMultizonal	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone
privateRouteID	string	False	<p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
connectorCapabilities	array[string]	False	<p>Capabilities of the connector that is associated with this cluster. Optional for backwards compatibility. If not present, proxy is the assumed capability.</p>
apiServiceID	string	False	<p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-cluster",
  "version": "1.5"
}
```

Response

Status: 204, Indicates if the cluster resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/65",
  "title": "Cluster GET not performed",
  "detail": "The cluster GET call didn't perform the lookup operation on the cluster.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete a cluster for a cloud

DELETE /accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}

Removes the specified Cluster API resource.

Side Effects

- Internal data structures are cleaned up.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
cloud_id	string	path	True	ID of the containing cloud resource
cluster_id	string	path	True	ID of the cluster collection to list

Response

Status: 204, Indicates if the cluster resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List all clusters

GET /accounts/{account_id}/topology/v1/clusters

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name,managedState

Name	Type	In	Required	Description
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: cluster_1.5_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-clusters",
  "version": "1.5",
  "items": [
    [
      "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
      "GKE-21",
      "managed"
    ],
    [
      "04dc80fa-d1d8-4850-a49f-3b70d0ec1369",
      "GKE-22",
      "unmanaged"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

cluster_1.5_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cluster"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3" • "1.4" • "1.5"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots
protectionStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.
snapshotSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.

Name	Type	Required	Description
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
managedTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was brought under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This key is only returned when a cluster has a managedState of "managed".</p>
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema

Name	Type	Required	Description
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"
inUse	string	True	<p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	True	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	False	<p>JSON string containing a value indicating the semantic versioning representation of the cluster environment.</p> <p>For Kubernetes clusters, this is the Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	False	<p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
cloudID	string	True	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema <p>If privateRouteID and connectorCapabilities with at least the relay option are provided, credentialID is optional. If they are not provided, credentialID is required, otherwise, an error is generated.</p> <p>If credentialID and a relay capable connector is provided, an error is generated.</p>
location	string	False	<p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
isMultizonal	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone
privateRouteID	string	False	<p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
connectorCapabilities	array[string]	False	<p>Capabilities of the connector that is associated with this cluster. Optional for backwards compatibility. If not present, proxy is the assumed capability.</p>
apiServiceID	string	False	<p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a cluster

GET /accounts/{account_id}/topology/v1/clusters/{cluster_id}

Returns the stored Cluster API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
cluster_id	string	path	True	ID of the cluster collection to list

Response

Status: 200, Returns the stored Cluster API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-cluster"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2""1.3""1.4""1.5"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots
protectionStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.

Name	Type	Required	Description
snapshotSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
managedTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was brought under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This key is only returned when a cluster has a managedState of "managed".</p>

Name	Type	Required	Description
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"
inUse	string	True	<p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	True	<p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	False	<p>JSON string containing a value indicating the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	False	<p>JSON string containing a value indicating the extended versioning information for the cluster environment.</p> <p>For Kubernetes clusters, this is the full Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class set in Kubernetes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
cloudID	string	True	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema <p>If privateRouteID and connectorCapabilities with at least the relay option are provided, credentialID is optional. If they are not provided, credentialID is required, otherwise, an error is generated. If credentialID and a relay capable connector is provided, an error is generated.</p>
location	string	False	<p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
isMultizonal	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone
privateRouteID	string	False	<p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
connectorCapabilities	array[string]	False	<p>Capabilities of the connector that is associated with this cluster. Optional for backwards compatibility. If not present, proxy is the assumed capability.</p>
apiServiceID	string	False	<p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-cluster",
  "version": "1.5",
  "id": "547e24b9-ddf4-558f-8397-e97e732868e4",
  "name": "GKE-22",
  "state": "running",
  "stateUnready": [],
  "managedState": "unmanaged",
  "managedStateUnready": [],
  "protectionState": "full",
  "protectionStateDetails": [],
  "tridentVersion": "21.07.2",
  "tridentManagedState": "managed",
  "tridentManagedStateDetails": [],
  "inUse": "false",
  "clusterType": "kubernetes",
  "clusterVersion": "1.91.1",
  "clusterVersionString": "1.19.1",
  "clusterCreationTimestamp": "2020-08-06T12:24:52.256624Z",
  "namespaces": [
    "kube-system",
    "kube-public",
    "my-app-1"
  ],
  "defaultStorageClass": "31c95aba-99d9-4987-b1bb-000dfce5952c",
  "cloudID": "548bdc1f-f00e-4a23-a062-83265d224d46",
  "credentialID": "6fa2f917-f730-41b8-9c15-17f531843b31",
  "location": "europe-west4",
  "isMultizonal": "false",
  "apiServiceID": "6bf33af2-872a-4553-a891-26b510c3edbe",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/65",
  "title": "Cluster GET not performed",
  "detail": "The cluster GET call didn't perform the lookup operation
on the cluster.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a cluster

PUT /accounts/{account_id}/topology/v1/clusters/{cluster_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the cluster is in a managed state, an update to credentialID will eventually trigger another attempt to collect the cluster.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: {{.Account}}
cluster_id	string	path	True	ID of the cluster collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the cluster is in a managed state, an update to credentialID will eventually trigger another attempt to collect the cluster.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-cluster"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3" • "1.4" • "1.5"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	False	JSON string containing a name for the cluster. If not specified, the Kubernetes name of the cluster will be used. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster state cannot be determined
stateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to "failed" or "removed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	False	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in "running" state, is not under management, and is not eligible for management. The reasons for this ineligibility are provided in the unready key value • "unmanaged" - The cluster is in "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in "running" state and is in the process of being managed • "managed" - The cluster is in "running", "failed", or "removed" state, and is under management

Name	Type	Required	Description
protectionState	string	False	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The clusters default storage class supports snapshots • "partial" - The cluster has only storageClasses that do not support snapshots • "atRisk" - The default storage class of the cluster does not support snapshots
protectionStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects which lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.

Name	Type	Required	Description
snapshotSupported	string	False	<p>JSON string containing a value indicating the ability of the cluster to perform application data management backup-like operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.
managedStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed, or that the cluster is managed but non-fatal errors were encountered while managing the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
managedTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was brought under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This key is only returned when a cluster has a managedState of "managed".</p>

Name	Type	Required	Description
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why the state transitioned to "managed" or "unmanaged". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0

Name	Type	Required	Description
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState. The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"
inUse	string	False	<p>JSON string containing a value indicating if the cluster has any managed applications and therefore cannot be deleted. Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed or is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed. Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	False	<p>JSON string containing a value indicating the semantic versioning representation of the cluster environment.</p> <p>For Kubernetes clusters, this is the Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	False	<p>JSON string containing a value indicating the extended versioning information for the cluster environment.</p> <p>For Kubernetes clusters, this is the full Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class set in Kubernetes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
cloudID	string	False	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema <p>If privateRouteID and connectorCapabilities with at least the relay option are provided, credentialID is optional. If they are not provided, credentialID is required, otherwise, an error is generated. If credentialID and a relay capable connector is provided, an error is generated.</p>
location	string	False	<p>JSON string containing a value provided by the cloud that the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
isMultizonal	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone
privateRouteID	string	False	<p>JSON string containing the location ID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
connectorCapabilities	array[string]	False	<p>Capabilities of the connector that is associated with this cluster. Optional for backwards compatibility. If not present, proxy is the assumed capability.</p>
apiServiceID	string	False	<p>JSON string containing the UUID from the Kubernetes (k8s) API service object. Used to uniquely identify a cluster.</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-cluster",
  "version": "1.5"
}
```

Response

Status: 204, Indicates if the cluster resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/65",
  "title": "Cluster GET not performed",
  "detail": "The cluster GET call didn't perform the lookup operation on the cluster.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete a cluster

DELETE /accounts/{account_id}/topology/v1/clusters/{cluster_id}

Removes the specified Cluster API resource.

Side Effects

- Internal data structures are cleaned up.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
cluster_id	string	path	True	ID of the cluster collection to list

Response

Status: 204, Indicates if the cluster resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Cluster node

Cluster node overview

The Cluster Node API provides access to the nodes associated with a cluster.

List the cluster nodes for a cloud

GET

/accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}/clusterNodes

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
cloud_id	string	path	True	ID of the containing cloud resource
cluster_id	string	path	True	ID of the containing cluster resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: name,instanceType
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: clusterNode_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-clusterNodes",
  "version": "1.0",
  "items": [
    [
      "test-0",
      "e2-medium"
    ],
    [
      "test-1",
      "e2-medium"
    ],
    [
      "test-2",
      "e2-medium"
    ],
    [
      "test-3",
      "e2-micro"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "^[\\S.]{1,253}V?([a-z0-9A-Z_-.]){1,63}\$"
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "^[a-z0-9A-Z_-.]{1,63}\$"

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

clusterNode_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-clusterNode"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a value that indicates the Kubernetes name for the node. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
role	string	True	JSON string containing a value that indicates the Kubernetes role for the node. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

Name	Type	Required	Description
labels	array[labels]	True	<p>JSON array of JSON objects, each containing Kubernetes labels associated with the node.</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
creationTime	string	True	<p>JSON string containing an ISO 8601 timestamp that indicates when the node was created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
externalIP	string	True	<p>JSON string containing a value that indicates the internal IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
internalIP	string	True	<p>JSON string containing a value that indicates the external IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
zone	string	True	<p>JSON string containing a value that indicates the Kubernetes zone for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
region	string	True	JSON string containing a value that indicates the Kubernetes region for the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
instanceType	string	True	JSON string containing a value that indicates the Kubernetes instance type for the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
kernelVersion	string	True	JSON string containing a value that indicates the kernel version used by the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
osImage	string	True	JSON string containing a value that indicates the operating system image used by the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
numCpus	string	True	JSON string containing a value that indicates the number of CPUs assigned to the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
memory	string	True	JSON string containing a value that indicates the amount of memory assigned to the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
state	string	True	JSON string containing a value indicating the operational state of the node. Defined values are: <ul style="list-style-type: none"> • "running" - The node is running normally • "provisioning" - The node is in the process of being provisioned • "discovering" - Aspects of the node are in the process of being discovered • "pending" - The node is scheduled for discovery • "failed" - The node is in a failure state • "unknown" - The state of the node cannot be determined

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a cluster node for a cloud

GET

/accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}/clusterNodes/{clusterNode_id}

Returns the stored Cluster Node API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
cloud_id	string	path	True	ID of the containing cloud resource
cluster_id	string	path	True	ID of the containing cluster resource
clusterNode_id	string	path	True	ID of the clusterNode collection to list

Response

Status: 200, Returns the stored Cluster Node API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-clusterNode"
version	string	True	Version of the resource. Defined values are: • "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a value that indicates the Kubernetes name for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
role	string	True	<p>JSON string containing a value that indicates the Kubernetes role for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
labels	array[labels]	True	<p>JSON array of JSON objects, each containing Kubernetes labels associated with the node. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
creationTime	string	True	<p>JSON string containing an ISO 8601 timestamp that indicates when the node was created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
externalIP	string	True	<p>JSON string containing a value that indicates the internal IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
internalIP	string	True	<p>JSON string containing a value that indicates the external IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
zone	string	True	<p>JSON string containing a value that indicates the Kubernetes zone for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
region	string	True	<p>JSON string containing a value that indicates the Kubernetes region for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
instanceType	string	True	<p>JSON string containing a value that indicates the Kubernetes instance type for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
kernelVersion	string	True	<p>JSON string containing a value that indicates the kernel version used by the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
osImage	string	True	<p>JSON string containing a value that indicates the operating system image used by the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
numCpus	string	True	<p>JSON string containing a value that indicates the number of CPUs assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
memory	string	True	<p>JSON string containing a value that indicates the amount of memory assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "running" - The node is running normally • "provisioning" - The node is in the process of being provisioned • "discovering" - Aspects of the node are in the process of being discovered • "pending" - The node is scheduled for discovery • "failed" - The node is in a failure state • "unknown" - The state of the node cannot be determined
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-clusterNode",
  "version": "1.0",
  "id": "5df0e09f-2c30-5b8a-b6b6-4fb4063525e4",
  "name": "test-0",
  "role": "node-role.kubernetes.io/worker",
  "labels": [],
  "creationTime": "2020-09-06T04:35:23.593845Z",
  "externalIP": "192.168.12.44",
  "internalIP": "10.0.1.1",
  "zone": "us-west1-c",
  "region": "us-east1",
  "instanceType": "e2-medium",
  "kernelVersion": "4.18.0-147.0.3.el8_1.x86_64",
  "osImage": "Red Hat Enterprise Linux CoreOS 42.81.20191203.0",
  "numCpus": "2",
  "memory": "67108864Ki",
  "state": "running",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "<code>^[\\S.]{1,253}V?([a-z0-9A-Z_-.]){1,63}\$</code>"
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "<code>^[a-z0-9A-Z_-.]{1,63}\$</code>"

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the cluster nodes for a cluster

GET /accounts/{account_id}/topology/v1/clusters/{cluster_id}/clusterNodes

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
cluster_id	string	path	True	ID of the containing cluster resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: <code>name,instanceType</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: clusterNode_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-clusterNodes",
  "version": "1.0",
  "items": [
    [
      "test-0",
      "e2-medium"
    ],
    [
      "test-1",
      "e2-medium"
    ],
    [
      "test-2",
      "e2-medium"
    ],
    [
      "test-3",
      "e2-micro"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "<code>^([\S.]{1,253}V)?([a-z0-9A-Z_-.]){1,63}\$</code>"
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "<code>^[a-z0-9A-Z_-.]{1,63}\$</code>"

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

clusterNode_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-clusterNode"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a value that indicates the Kubernetes name for the node. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
role	string	True	JSON string containing a value that indicates the Kubernetes role for the node. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

Name	Type	Required	Description
labels	array[labels]	True	<p>JSON array of JSON objects, each containing Kubernetes labels associated with the node.</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
creationTime	string	True	<p>JSON string containing an ISO 8601 timestamp that indicates when the node was created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
externalIP	string	True	<p>JSON string containing a value that indicates the internal IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
internalIP	string	True	<p>JSON string containing a value that indicates the external IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
zone	string	True	<p>JSON string containing a value that indicates the Kubernetes zone for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
region	string	True	JSON string containing a value that indicates the Kubernetes region for the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
instanceType	string	True	JSON string containing a value that indicates the Kubernetes instance type for the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
kernelVersion	string	True	JSON string containing a value that indicates the kernel version used by the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
osImage	string	True	JSON string containing a value that indicates the operating system image used by the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
numCpus	string	True	<p>JSON string containing a value that indicates the number of CPUs assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
memory	string	True	<p>JSON string containing a value that indicates the amount of memory assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
state	string	True	<p>JSON string containing a value indicating the operational state of the node. Defined values are:</p> <ul style="list-style-type: none"> • "running" - The node is running normally • "provisioning" - The node is in the process of being provisioned • "discovering" - Aspects of the node are in the process of being discovered • "pending" - The node is scheduled for discovery • "failed" - The node is in a failure state • "unknown" - The state of the node cannot be determined

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a cluster node for a cluster

GET

/accounts/{account_id}/topology/v1/clusters/{cluster_id}/clusterNodes/{clusterNode_id}

Returns the stored Cluster Node API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
cluster_id	string	path	True	ID of the containing cluster resource
clusterNode_id	string	path	True	ID of the clusterNode collection to list

Response

Status: 200, Returns the stored Cluster Node API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-clusterNode"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	JSON string containing a value that indicates the Kubernetes name for the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
role	string	True	JSON string containing a value that indicates the Kubernetes role for the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
labels	array[labels]	True	JSON array of JSON objects, each containing Kubernetes labels associated with the node. If no details are available, this array will be empty. <ul style="list-style-type: none"> • Minimum items: 0
creationTime	string	True	JSON string containing an ISO 8601 timestamp that indicates when the node was created. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
externalIP	string	True	JSON string containing a value that indicates the internal IP address for the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
internalIP	string	True	<p>JSON string containing a value that indicates the external IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
zone	string	True	<p>JSON string containing a value that indicates the Kubernetes zone for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
region	string	True	<p>JSON string containing a value that indicates the Kubernetes region for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
instanceType	string	True	<p>JSON string containing a value that indicates the Kubernetes instance type for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
kernelVersion	string	True	<p>JSON string containing a value that indicates the kernel version used by the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
osImage	string	True	<p>JSON string containing a value that indicates the operating system image used by the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
numCpus	string	True	<p>JSON string containing a value that indicates the number of CPUs assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
memory	string	True	<p>JSON string containing a value that indicates the amount of memory assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "running" - The node is running normally • "provisioning" - The node is in the process of being provisioned • "discovering" - Aspects of the node are in the process of being discovered • "pending" - The node is scheduled for discovery • "failed" - The node is in a failure state • "unknown" - The state of the node cannot be determined
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-clusterNode",
  "version": "1.0",
  "id": "5df0e09f-2c30-5b8a-b6b6-4fb4063525e4",
  "name": "test-0",
  "role": "node-role.kubernetes.io/worker",
  "labels": [],
  "creationTime": "2020-09-06T04:35:23.593845Z",
  "externalIP": "192.168.12.44",
  "internalIP": "10.0.1.1",
  "zone": "us-west1-c",
  "region": "us-east1",
  "instanceType": "e2-medium",
  "kernelVersion": "4.18.0-147.0.3.el8_1.x86_64",
  "osImage": "Red Hat Enterprise Linux CoreOS 42.81.20191203.0",
  "numCpus": "2",
  "memory": "67108864Ki",
  "state": "running",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "<code>^[\\S.]{1,253}V?([a-z0-9A-Z_-.]){1,63}\$</code>"
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "<code>^[a-z0-9A-Z_-.]{1,63}\$</code>"

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the cluster nodes for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/clusterNodes

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
managedCluster_id	string	path	True	ID of the containing managedCluster resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: <code>name,instanceType</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: clusterNode_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-clusterNodes",
  "version": "1.0",
  "items": [
    [
      "test-0",
      "e2-medium"
    ],
    [
      "test-1",
      "e2-medium"
    ],
    [
      "test-2",
      "e2-medium"
    ],
    [
      "test-3",
      "e2-micro"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "^[\\S.]{1,253}V?([a-z0-9A-Z_-.]){1,63}\$"
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "^[a-z0-9A-Z_-.]{1,63}\$"

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

clusterNode_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-clusterNode"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a value that indicates the Kubernetes name for the node. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254
role	string	True	JSON string containing a value that indicates the Kubernetes role for the node. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 254

Name	Type	Required	Description
labels	array[labels]	True	<p>JSON array of JSON objects, each containing Kubernetes labels associated with the node.</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
creationTime	string	True	<p>JSON string containing an ISO 8601 timestamp that indicates when the node was created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
externalIP	string	True	<p>JSON string containing a value that indicates the internal IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
internalIP	string	True	<p>JSON string containing a value that indicates the external IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
zone	string	True	<p>JSON string containing a value that indicates the Kubernetes zone for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
region	string	True	JSON string containing a value that indicates the Kubernetes region for the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
instanceType	string	True	JSON string containing a value that indicates the Kubernetes instance type for the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
kernelVersion	string	True	JSON string containing a value that indicates the kernel version used by the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
osImage	string	True	JSON string containing a value that indicates the operating system image used by the node. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
numCpus	string	True	<p>JSON string containing a value that indicates the number of CPUs assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
memory	string	True	<p>JSON string containing a value that indicates the amount of memory assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
state	string	True	<p>JSON string containing a value indicating the operational state of the node. Defined values are:</p> <ul style="list-style-type: none"> • "running" - The node is running normally • "provisioning" - The node is in the process of being provisioned • "discovering" - Aspects of the node are in the process of being discovered • "pending" - The node is scheduled for discovery • "failed" - The node is in a failure state • "unknown" - The state of the node cannot be determined

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a cluster node for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/clusterNodes/{clusterNode_id}

Returns the stored Cluster Node API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
clusterNode_id	string	path	True	ID of the clusterNode collection to list

Response

Status: 200, Returns the stored Cluster Node API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-clusterNode"
version	string	True	Version of the resource. Defined values are: • "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a value that indicates the Kubernetes name for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
role	string	True	<p>JSON string containing a value that indicates the Kubernetes role for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
labels	array[labels]	True	<p>JSON array of JSON objects, each containing Kubernetes labels associated with the node. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum items: 0
creationTime	string	True	<p>JSON string containing an ISO 8601 timestamp that indicates when the node was created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
externalIP	string	True	<p>JSON string containing a value that indicates the internal IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
internalIP	string	True	<p>JSON string containing a value that indicates the external IP address for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
zone	string	True	<p>JSON string containing a value that indicates the Kubernetes zone for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
region	string	True	<p>JSON string containing a value that indicates the Kubernetes region for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
instanceType	string	True	<p>JSON string containing a value that indicates the Kubernetes instance type for the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
kernelVersion	string	True	<p>JSON string containing a value that indicates the kernel version used by the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
osImage	string	True	<p>JSON string containing a value that indicates the operating system image used by the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
numCpus	string	True	<p>JSON string containing a value that indicates the number of CPUs assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254
memory	string	True	<p>JSON string containing a value that indicates the amount of memory assigned to the node. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 254

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the node.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "running" - The node is running normally • "provisioning" - The node is in the process of being provisioned • "discovering" - Aspects of the node are in the process of being discovered • "pending" - The node is scheduled for discovery • "failed" - The node is in a failure state • "unknown" - The state of the node cannot be determined
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-clusterNode",
  "version": "1.0",
  "id": "5df0e09f-2c30-5b8a-b6b6-4fb4063525e4",
  "name": "test-0",
  "role": "node-role.kubernetes.io/worker",
  "labels": [],
  "creationTime": "2020-09-06T04:35:23.593845Z",
  "externalIP": "192.168.12.44",
  "internalIP": "10.0.1.1",
  "zone": "us-west1-c",
  "region": "us-east1",
  "instanceType": "e2-medium",
  "kernelVersion": "4.18.0-147.0.3.el8_1.x86_64",
  "osImage": "Red Hat Enterprise Linux CoreOS 42.81.20191203.0",
  "numCpus": "2",
  "memory": "67108864Ki",
  "state": "running",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

labels

Name	Type	Required	Description
name	string	True	JSON string containing the label name Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "<code>^[\\S.]{1,253}V?([a-z0-9A-Z_-.]){1,63}\$</code>"
value	string	True	JSON string containing the label value Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• Defined regex is: "<code>^[a-z0-9A-Z_-.]{1,63}\$</code>"

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Credential

Credential overview

The Credential API provides access to securely persist objects containing sensitive information.

Create a new credential

POST `/accounts/{account_id}/core/v1/credentials`

Indicates the desired values for the Credential API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates the desired values for the Credential API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-credential"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
name	string	True	JSON string containing a user-specified name. When a credential is created for a user, the name will be set to the UUID of that user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
keyType	string	False	<p>JSON string containing an optional user-specified data validation type descriptor for the contents of the keyStore.</p> <p>Extended update constraints:</p> <ul style="list-style-type: none"> • If a keyType does not exist in the resource and is not specified in an update, the keyType must not continue to exist in the updated resource. • If a keyType does not exist in the resource and is specified in an update, the keyType must be added to the resource and validation must be performed. If the validation fails, the update will fail. • If a keyType exists in the resource and is not specified in an update, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified matches the existing keyType, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified is different from the existing keyType, the update will fail. <p>Defined values are:</p> <ul style="list-style-type: none"> • "generic" - The credential is a generic collection of data. This is equivalent to not including a keyType.

Name	Type	Required	Description
keyStore	keyStore	True	<p>JSON object containing JSON strings. Each string in the keyStore represents part of the credential. The name of each string represents the credential part, and the corresponding key-value stores the value of that part of the credential in base64 format.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema No limits are placed on the lengths of the strings.
valid	string	False	<p>JSON string describing whether the credential is valid for use. Default value, if omitted, is "true".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The credential is eligible for use. • "false" - The credential must not be used.
validFromTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is valid. These are used for credential rotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

- stored as a hash.
- A "change" string must exist within the keyStore with a value containing a base64-encoded string "true" or "false".
- A credential of type passwordHash can only be deleted if the user ID indicated by¹⁴⁷ the name does not

Name	Type	Required	Description
validUntilTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is no longer valid. These are used for credential rotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

- "certificate" - The credential is a PEM-

```
{
  "type": "application/astra-credential",
  "version": "1.1",
  "name": "myCert",
  "keyStore": {
    "privKey": "SGkh",
    "pubKey": "VGhpcyBpcyBhbiBleGFtcGxlLg=="
  }
}
```

- Extended validation is performed as follows:
- A "privkey" string must exist within the keyStore, with a value containing a base64-encoded PEM private

Response

Status: 201, Returns the newly created credential resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-credential"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name. When a credential is created for a user, the name will be set to the UUID of that user. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 127

Name	Type	Required	Description
keyType	string	False	<p>JSON string containing an optional user-specified data validation type descriptor for the contents of the keyStore.</p> <p>Extended update constraints:</p> <ul style="list-style-type: none"> • If a keyType does not exist in the resource and is not specified in an update, the keyType must not continue to exist in the updated resource. • If a keyType does not exist in the resource and is specified in an update, the keyType must be added to the resource and validation must be performed. If the validation fails, the update will fail. • If a keyType exists in the resource and is not specified in an update, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified matches the existing keyType, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified is different from the existing keyType, the update will fail. <p>Defined values are:</p> <ul style="list-style-type: none"> • "generic" - The credential is a generic collection of data. This is equivalent to not including a keyType.

Name	Type	Required	Description
valid	string	True	<p>JSON string describing whether the credential is valid for use. Default value, if omitted, is "true". Defined values are:</p> <ul style="list-style-type: none"> • "true" - The credential is eligible for use. • "false" - The credential must not be used.
validFromTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is valid. These are used for credential rotation. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
validUntilTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is no longer valid. These are used for credential rotation. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

password.

- The password cleartext must conform to the account's password policy.
- The password is stored as a hash.
- A "change" string must exist within the keyStore with a value containing a base64-encoded string "true" or "false".
- A credential of type passwordHash can only be deleted if the user ID indicated by `by151` the name does not

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-credential",
  "version": "1.1",
  "id": "58e26f6a-a631-5122-8e0e-7afe306675c0",
  "name": "myCert",
  "valid": "true",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

keyStore, with a value containing a base64-encoded PEM

encoded private key

exist within the keyStore, with a value containing a base64-encoded PEM private

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Service (S3) access.

Example response

- Extended validation is

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

with a value containing a base64-encoded S3 access

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

keyStore

JSON object containing JSON strings. Each string in the keyStore represents part of the credential. The name of each string represents the credential part, and the corresponding key-value stores the value of that part of the credential in base64 format.

Defined values are:

- Conforms to the base64 Encoded Data Schema
No limits are placed on the lengths of the strings.

Hash mapping strings to string

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all credentials

GET /accounts/{account_id}/core/v1/credentials

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
continue		query	False	Indicates the token to resume listing from. <p>URL examples:</p> <pre>"continue=<continue token="" from="" collection="" metadata="">"</continue></pre> <p>OpenAPI examples:</p> <pre>"<continue token="" from="" collection="" metadata="">"</continue>&lt;/continue&gt;</pre>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> • example: id,name

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"
orderBy	string	query	False	Indicates the sort order of resource when listing a collection. URL examples: "orderBy=name", "orderBy=name%20desc" OpenAPI examples: "name desc"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: credential_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-credentials",
  "version": "1.1",
  "items": [
    [
      "f97f3441-075e-4f9b-9d1e-47f9f62a3fc4",
      "myCert"
    ],
    [
      "5e365b4d-034f-4f13-95ef-d3a7fbc0df3d",
      "kubeconfig"
    ],
    [
      "11ceb350-1999-4b79-80a6-46a980a27856",
      "password"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

credential_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-credential"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name. When a credential is created for a user, the name will be set to the UUID of that user. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 127

Name	Type	Required	Description
keyType	string	False	<p>JSON string containing an optional user-specified data validation type descriptor for the contents of the keyStore. Extended update constraints:</p> <ul style="list-style-type: none"> • If a keyType does not exist in the resource and is not specified in an update, the keyType must not continue to exist in the updated resource. • If a keyType does not exist in the resource and is specified in an update, the keyType must be added to the resource and validation must be performed. If the validation fails, the update will fail. • If a keyType exists in the resource and is not specified in an update, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified matches the existing keyType, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified is different from the existing keyType, the update will fail. <p>Defined values are:</p> <p>"generic" - The credential is a generic collection of data. This is</p>

Name	Type	Required	Description
valid	string	True	<p>JSON string describing whether the credential is valid for use. Default value, if omitted, is "true".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The credential is eligible for use. • "false" - The credential must not be used.
validFromTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is valid. These are used for credential rotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
validUntilTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is no longer valid. These are used for credential rotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

must exist within the keyStore with a value containing a base64-encoded cleartext password:

- The password cleartext must conform to the account's password policy.
- The password is stored as a hash.
- A "change" string must exist within the keyStore with a value containing a

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

is performed as follows:

- A "certificate" string must exist within the keyStore, with a value containing a base64-encoded

Retrieve a credential

GET /accounts/{account_id}/core/v1/credentials/{credential_id}

Returns the stored Credential API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
credential_id	string	path	True	ID of the credential collection to list

Response

Status: 200, Returns the stored Credential API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-credential"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-specified name. When a credential is created for a user, the name will be set to the UUID of that user. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

value containing a base64-encoded PEM private key.

- "s3" - Indicates the credentials are for Simple Storage Service (S3) access.
- Extended validation is performed as follows:
 - An "accessKey" string must exist within the keyStore with a value containing a base64-encoded S3 access key.
 - An "accessSecret" string must exist within the keyStore with a value containing a base64-encoded S3 access secret.

Name	Type	Required	Description
keyType	string	False	<p>JSON string containing an optional user-specified data validation type descriptor for the contents of the keyStore.</p> <p>Extended update constraints:</p> <ul style="list-style-type: none"> • If a keyType does not exist in the resource and is not specified in an update, the keyType must not continue to exist in the updated resource. • If a keyType does not exist in the resource and is specified in an update, the keyType must be added to the resource and validation must be performed. If the validation fails, the update will fail. • If a keyType exists in the resource and is not specified in an update, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified matches the existing keyType, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified is different from the existing keyType, the update will fail. <p>Defined values are:</p> <ul style="list-style-type: none"> • "generic" - The credential is a generic collection of data. This is equivalent to not including a keyType.

Name	Type	Required	Description
valid	string	True	<p>JSON string describing whether the credential is valid for use. Default value, if omitted, is "true". Defined values are:</p> <ul style="list-style-type: none"> • "true" - The credential is eligible for use. • "false" - The credential must not be used.
validFromTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is valid. These are used for credential rotation. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
validUntilTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is no longer valid. These are used for credential rotation. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

password.

- The password cleartext must conform to the account's password policy.
- The password is stored as a hash.
- A "change" string must exist within the keyStore with a value containing a base64-encoded string "true" or "false".
- A credential of type passwordHash can only be deleted if the user ID indicated by171 the name does not

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-credential",
  "version": "1.1",
  "id": "58e26f6a-a631-5122-8e0e-7afe306675c0",
  "name": "myCert",
  "valid": "true",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

keyStore, with a value containing a base64-encoded PEM

encoded private key

exist within the keyStore, with a value containing a base64-encoded PEM private

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Service (S3) access.

Example response

- Extended validation is

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

with a value containing a base64-encoded S3 access

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a credential

PUT /accounts/{account_id}/core/v1/credentials/{credential_id}

Replaces the entire stored resource with the supplied JSON request body while preserving the key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
credential_id	string	path	True	ID of the credential collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving the key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-credential"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name. When a credential is created for a user, the name will be set to the UUID of that user. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 127

Name	Type	Required	Description
keyType	string	False	<p>JSON string containing an optional user-specified data validation type descriptor for the contents of the keyStore.</p> <p>Extended update constraints:</p> <ul style="list-style-type: none"> • If a keyType does not exist in the resource and is not specified in an update, the keyType must not continue to exist in the updated resource. • If a keyType does not exist in the resource and is specified in an update, the keyType must be added to the resource and validation must be performed. If the validation fails, the update will fail. • If a keyType exists in the resource and is not specified in an update, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified matches the existing keyType, the keyType must be preserved. • If a keyType exists in the resource and is specified in an update, and the keyType specified is different from the existing keyType, the update will fail. <p>Defined values are:</p> <ul style="list-style-type: none"> • "generic" - The credential is a generic collection of data. This is equivalent to not including a keyType.

Name	Type	Required	Description
keyStore	keyStore	True	<p>JSON object containing JSON strings. Each string in the keyStore represents part of the credential. The name of each string represents the credential part, and the corresponding key-value stores the value of that part of the credential in base64 format.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema No limits are placed on the lengths of the strings.
valid	string	False	<p>JSON string describing whether the credential is valid for use. Default value, if omitted, is "true".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The credential is eligible for use. • "false" - The credential must not be used.
validFromTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is valid. These are used for credential rotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

- stored as a hash.
- A "change" string must exist within the keyStore with a value containing a base64-encoded string "true" or "false".
- A credential of type passwordHash can only be deleted if the user ID indicated by179 the name does not

Name	Type	Required	Description
validUntilTimestamp	string	False	<p>JSON string containing a timestamp indicating when the credential is no longer valid. These are used for credential rotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

- "certificate" - The credential is a PEM-

```

{
  "type": "application/astra-credential",
  "version": "1.1",
  "name": "oldCert",
  "keyStore": {
    "privKey": "SGkh",
    "pubKey": "VGhpcyBpcyBhbiBleGFtcGxlLg=="
  }
}

```

- Extended validation is performed as follows:
- A "privkey" string must exist within the keyStore, with a value containing a base64-encoded PEM private

Response

Status: 204, Indicates if the credential resource was updated.

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 406, Not acceptable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/32",
  "title": "Unsupported content type",
  "detail": "The response can't be returned in the requested format.",
  "status": "406"
}
```

keyStore with a value containing a base64-encoded S3 access

Response

Status: 500, Internal server error

string must exist

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Response

Status: 412, Precondition failed

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/38",
  "title": "Precondition not met",
  "detail": "The conditional headers aren't satisfied.",
  "status": "412"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/39",
  "title": "Credential exists",
  "detail": "A credential of this type already exists.",
  "status": "409"
}
```

Response

Status: 502, Bad gateway

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/40",
  "title": "Communication failed",
  "detail": "Communication wasn't made with downstream services.",
  "status": "502"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Error

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example error response

```
{
  "type": "https://astra.netapp.io/problems/7",
  "title": "Invalid JSON payload",
  "detail": "The request body is not valid JSON.",
  "status": "400"
}
```

Definitions

See Definitions

keyStore

JSON object containing JSON strings. Each string in the keyStore represents part of the credential. The name of each string represents the credential part, and the corresponding key-value stores the value of that part of the credential in base64 format.

Defined values are:

- Conforms to the base64 Encoded Data Schema
No limits are placed on the lengths of the strings.

Hash mapping strings to string

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete a credential

DELETE /accounts/{account_id}/core/v1/credentials/{credential_id}

Removes the specified Credential API resource.

Side Effects

- If the credential being deleted is relied on by another resource or API, the deletion might cause unintended side effects within other APIs or the system as a whole.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
credential_id	string	path	True	ID of the credential collection to list

Response

Status: 204, Indicates if the credential resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Entitlement

Entitlement overview

The Entitlement API represents which features or capacities are enabled by the licenses and subscriptions active for an account.

List all entitlements

GET /accounts/{account_id}/core/v1/entitlements

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: product,entitlementType,entitlementValue,allocation
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue> OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: entitlement_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-entitlements",
  "version": "1.0",
  "items": [
    [
      "Astra SDS",
      "capacity",
      "2",
      null
    ],
    [
      "Astra Enterprise",
      "clusters",
      "100",
      "5e9fe8f7-4c54-441c-ac94-fd8451f9ca38"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```


Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

entitlement_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-entitlement"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
allocation	string	False	JSON string containing the ID of the object that the entitlement is allocated to. Only present when the entitlement is allocated. String contents not validated by the schema.
product	string	False	JSON string containing the product string extracted from the license or subscription. String contents not validated by the schema.
productVersion	string	False	JSON string containing the version string extracted from the license or subscription. String contents not validated by the schema.
entitlementType	string	True	JSON string containing the type of the entitlement. This is extracted from the license or subscription. String contents not validated by the schema.
entitlementValue	string	True	JSON string containing the capacity associated with the entitlement. String contents not validated by the schema.
entitlementConsumption	string	False	JSON string containing the amount of the capacity associated with the entitlement that is currently in use. String contents not validated by the schema.

Name	Type	Required	Description
sourceLicense	string	False	JSON string containing the license object ID that the entitlement is sourced from. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceSubscription	string	False	JSON string containing the ID of the subscription object that the entitlement is sourced from. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
validFromTimestamp	string	False	JSON string containing a timestamp indicating when the entitlement becomes valid. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
validUntilTimestamp	string	False	JSON string containing a timestamp indicating when the entitlement is no longer valid. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an entitlement

GET /accounts/{account_id}/core/v1/entitlements/{entitlement_id}

Returns the stored Entitlement API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
entitlement_id	string	path	True	ID of the entitlement collection to list

Response

Status: 200, Returns the stored Entitlement API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-entitlement"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
allocation	string	False	JSON string containing the ID of the object that the entitlement is allocated to. Only present when the entitlement is allocated. String contents not validated by the schema.
product	string	False	JSON string containing the product string extracted from the license or subscription. String contents not validated by the schema.
productVersion	string	False	JSON string containing the version string extracted from the license or subscription. String contents not validated by the schema.
entitlementType	string	True	JSON string containing the type of the entitlement. This is extracted from the license or subscription. String contents not validated by the schema.

Name	Type	Required	Description
entitlementValue	string	True	JSON string containing the capacity associated with the entitlement. String contents not validated by the schema.
entitlementConsumption	string	False	JSON string containing the amount of the capacity associated with the entitlement that is currently in use. String contents not validated by the schema.
sourceLicense	string	False	<p>JSON string containing the license object ID that the entitlement is sourced from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
sourceSubscription	string	False	<p>JSON string containing the ID of the subscription object that the entitlement is sourced from.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
validFromTimestamp	string	False	<p>JSON string containing a timestamp indicating when the entitlement becomes valid.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
validUntilTimestamp	string	False	JSON string containing a timestamp indicating when the entitlement is no longer valid. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-entitlement",
  "version": "1.0",
  "id": "8bdafc19-bde6-5f45-9808-4893c845c9f5",
  "product": "Astra SDS",
  "productVersion": "1.0",
  "entitlementType": "capacity",
  "entitlementValue": "2",
  "entitlementConsumption": "1",
  "sourceLicense": "c8aa757a-5318-489f-8134-a2a1a6956a3e",
  "validFromTimestamp": "2020-08-06T00:00:00.000000Z",
  "validUntilTimestamp": "2021-08-06T00:00:00.000000Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Event

Event overview

The Event API provides access to events occurring in the system.

List all events

GET /accounts/{account_id}/core/v1/events

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,summary
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue> OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: event_1.4_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-events",
  "version": "1.4",
  "items": [
    [
      "4f8273ee-883d-47f0-a512-9e27b6285f20",
      "Discovering Applications in Cluster"
    ],
    [
      "1cdd26dc-5eb0-4cf4-a0c1-39a9b83720e1",
      "Application Discovered"
    ],
    [
      "2064d1c1-4bc6-466e-9c30-b941a11be16a",
      "Application Discovery Failed"
    ],
    [
      "4325f971-ca9c-4a52-bc9a-da6ec62e6bfe",
      "Application Discovered"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

data

JSON object containing additional event-specific information.

Name	Type	Required	Description
ttl	number	False	JSON number indicating the number of seconds (since the eventTime) that the event will be retained. This field is only included when an event is automatically deleted after the specified number of seconds. When deleted, if the event has a notification destination, all associated notifications are also deleted. When deleted, if the event has a banner destination, the banner is also removed. The absence of this field (or a value of "0") means that an event will not be automatically deleted.
isAcknowledgeable	string	False	JSON string indicating whether the banner is dismissible. Defined values are: <ul style="list-style-type: none">• "true" - The banner is dismissible• "false" - The banner is not dismissible

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

event_1.4_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-event"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"• "1.3"• "1.4"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a dot notation (.) hierarchical name for the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 127 • Defined regex is: <code>"^[a-z](\.[a-z])+\$"</code>
sequenceCount	number	True	<p>JSON number containing a sequence count.</p> <p>The number is incremented by the system each time a new event is received.</p>
summary	string	True	<p>JSON string containing the short-form (less than 40 characters) summary of the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 79
eventTime	string	True	<p>JSON string containing a timestamp that indicates when an event occurred.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
source	string	True	<p>JSON string containing the lowercase name of the service generating an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 19 • Defined regex is: <code>"^[a-z]*\$"</code>

Name	Type	Required	Description
resourceID	string	True	<p>JSON string containing the resource ID associated with an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
additionalResourceIDs	array[string]	True	<p>JSON array of JSON strings, each containing a resource ID of an additional resource associated with the event. While the "resourceID" field contains the primary resource associated with this event, this field contains any number of additional resource IDs to be associated with the same events.</p> <p>If no additional resources are associated with the event, the array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
resourceType	string	True	<p>JSON string containing the media type of the resource associated with an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 4 • Maximum length: 79 • Defined regex is: <code>"^application/astra-[a-zA-Z]+\$"</code>

Name	Type	Required	Description
correlationID	string	True	<p>JSON string containing a UUIDv4 correlation ID that allows related events to be grouped together.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
severity	string	True	<p>JSON string containing one of the following values that indicate the severity of an event. Defined values are:</p> <ul style="list-style-type: none"> • "cleared" - Indicates that a previously reported event describing a condition is no longer active. An event with severity "cleared" will use the same summary and correlation ID to allow it to be matched up. • "indeterminate" - Indicates that the severity cannot be determined. • "informational" - Indicates a change in state that is both expected and normal (not defined in X.733). • "warning" - Indicates the detection of a potential or impending service affecting fault before any significant effects have been felt. • "critical" - Indicates that a service affecting condition has occurred and immediate corrective action is required. Definitions for "cleared", "indeterminate", "warning" and "critical" are based on definitions in clause 8.1.2.3 of CCITT X.733.

Name	Type	Required	Description
class	string	True	<p>JSON string containing one of the following values that indicate the class of the event. Defined values are:</p> <ul style="list-style-type: none"> • "system" - The event is related to an internal event or request. • "user" - The event is related to a user-initiated event or request. • "security" - The event is related to a security issue.
description	string	True	<p>JSON string containing a long-form descriptive text about the event. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 1023
descriptionURL	string	False	<p>JSON string containing the URL that enables and links a button in the banner to external documentation. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095

Name	Type	Required	Description
correctiveAction	string	False	<p>JSON string containing a long-form descriptive text about what corrective action must be taken in response to the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 1023
correctiveActionURL	string	False	<p>JSON string containing the URL that links a button in the banner to a page within the UI to fix the issue.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
visibility	array[string]	False	<p>JSON array of JSON strings, each indicating an RBAC role permitted to view the event. Roles are OR-defined together. Optional.</p> <p>If omitted, a user with any RBAC role can view the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
destinations	array[string]	False	<p>JSON array of JSON strings, each indicating an additional destination for the event. These strings allow a service to provide hints about where an event should be routed in addition to the activity log. Optional. Defined values are:</p> <ul style="list-style-type: none"> • "notification" - The event is marked as a notification, and will be accessible through the notifications API endpoint. • "banner" - The event is marked as a banner. • "support" - The event is marked as a support-related event.
resourceURI	string	False	<p>JSON string containing the URI associated with the event. Only included for events related to API operations. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
resourceCollectionURL	array[string]	False	<p>JSON array of JSON strings, each indicating the fully-expanded access URL of the resource associated with the event. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 1023

Name	Type	Required	Description
resourceMethod	string	False	<p>JSON string containing the HTTP method invoked. Only included for events related to API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "options" - OPTIONS API operation • "post" - POST API operation • "get" - GET API operation • "put" - PUT API operation • "delete" - DELETE API operation
resourceMethodResult	string	False	<p>JSON string containing the result of the HTTP method invoked. Only included for events related to the API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[1-5][0-9]{2}\$"</code>
userID	string	False	<p>JSON string containing the user ID associated with an event. Only included for events associated with the user-initiated actions.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
accountID	string	False	JSON string containing the account ID associated with an event. Only included for events associated with an account. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema
data	data	False	JSON object containing additional event-specific information.
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

Retrieve an event

GET /accounts/{account_id}/core/v1/events/{event_id}

Returns the stored Event API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
event_id	string	path	True	ID of the event collection to list

Response

Status: 200, Returns the stored Event API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-event"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1" "1.2" "1.3" "1.4"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a dot notation (.) hierarchical name for the event. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 127 • Defined regex is: <code>"^[a-z](\.[a-z])+\$"</code>
sequenceCount	number	True	JSON number containing a sequence count. The number is incremented by the system each time a new event is received.
summary	string	True	JSON string containing the short-form (less than 40 characters) summary of the event. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 79
eventTime	string	True	JSON string containing a timestamp that indicates when an event occurred. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
source	string	True	<p>JSON string containing the lowercase name of the service generating an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 19 • Defined regex is: <code>"^[a-z-]*\$"</code>
resourceID	string	True	<p>JSON string containing the resource ID associated with an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
additionalResourceIDs	array[string]	True	<p>JSON array of JSON strings, each containing a resource ID of an additional resource associated with the event. While the "resourceID" field contains the primary resource associated with this event, this field contains any number of additional resource IDs to be associated with the same events.</p> <p>If no additional resources are associated with the event, the array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
resourceType	string	True	<p>JSON string containing the media type of the resource associated with an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 4 • Maximum length: 79 • Defined regex is: <code>"^application/astra-([a-zA-Z])+\$"</code>
correlationID	string	True	<p>JSON string containing a UUIDv4 correlation ID that allows related events to be grouped together.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
severity	string	True	<p>JSON string containing one of the following values that indicate the severity of an event. Defined values are:</p> <ul style="list-style-type: none"> • "cleared" - Indicates that a previously reported event describing a condition is no longer active. An event with severity "cleared" will use the same summary and correlation ID to allow it to be matched up. • "indeterminate" - Indicates that the severity cannot be determined. • "informational" - Indicates a change in state that is both expected and normal (not defined in X.733). • "warning" - Indicates the detection of a potential or impending service affecting fault before any significant effects have been felt. • "critical" - Indicates that a service affecting condition has occurred and immediate corrective action is required. Definitions for "cleared", "indeterminate", "warning" and "critical" are based on definitions in clause 8.1.2.3 of CCITT X.733.

Name	Type	Required	Description
class	string	True	<p>JSON string containing one of the following values that indicate the class of the event. Defined values are:</p> <ul style="list-style-type: none"> • "system" - The event is related to an internal event or request. • "user" - The event is related to a user-initiated event or request. • "security" - The event is related to a security issue.
description	string	True	<p>JSON string containing a long-form descriptive text about the event. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 1023
descriptionURL	string	False	<p>JSON string containing the URL that enables and links a button in the banner to external documentation. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
correctiveAction	string	False	<p>JSON string containing a long-form descriptive text about what corrective action must be taken in response to the event. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 1023

Name	Type	Required	Description
correctiveActionURL	string	False	<p>JSON string containing the URL that links a button in the banner to a page within the UI to fix the issue.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
visibility	array[string]	False	<p>JSON array of JSON strings, each indicating an RBAC role permitted to view the event. Roles are OR-defined together. Optional.</p> <p>If omitted, a user with any RBAC role can view the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
destinations	array[string]	False	<p>JSON array of JSON strings, each indicating an additional destination for the event. These strings allow a service to provide hints about where an event should be routed in addition to the activity log. Optional.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "notification" - The event is marked as a notification, and will be accessible through the notifications API endpoint. • "banner" - The event is marked as a banner. • "support" - The event is marked as a support-related event.

Name	Type	Required	Description
resourceURI	string	False	<p>JSON string containing the URI associated with the event. Only included for events related to API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
resourceCollectionURL	array[string]	False	<p>JSON array of JSON strings, each indicating the fully-expanded access URL of the resource associated with the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 1023
resourceMethod	string	False	<p>JSON string containing the HTTP method invoked. Only included for events related to API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "options" - OPTIONS API operation • "post" - POST API operation • "get" - GET API operation • "put" - PUT API operation • "delete" - DELETE API operation

Name	Type	Required	Description
resourceMethodResult	string	False	<p>JSON string containing the result of the HTTP method invoked. Only included for events related to the API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[1-5][0-9]{2}\$"</code>
userID	string	False	<p>JSON string containing the user ID associated with an event. Only included for events associated with the user-initiated actions.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
accountID	string	False	<p>JSON string containing the account ID associated with an event. Only included for events associated with an account.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
data	data	False	<p>JSON object containing additional event-specific information.</p>
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

A large, empty rectangular box with a thin, dashed border, occupying most of the page. It is intended for an example response.


```

{
  "type": "application/astra-event",
  "version": "1.4",
  "id": "c32df10b-8cfb-5a1e-9510-2a262b476009",
  "name": "astra.app.discovery.failed",
  "sequenceCount": 48923,
  "summary": "Application Discovery Failed",
  "eventTime": "2020-08-06T12:24:51.846543Z",
  "source": "composite-compute",
  "resourceID": "f670bf11-8850-44bd-b330-815af6186a06",
  "additionalResourceIDs": [
    "84dfef99-b7b2-46d2-9021-0a1a9a5dfd1d6",
    "abb32003-07b9-49b1-9938-1cf6d2f33566"
  ],
  "resourceType": "application/astra-app",
  "correlationID": "3c603442-cfca-4af9-9f1b-40dde5c7a806",
  "severity": "warning",
  "class": "user",
  "description": "Discovering the application 'mysql' was unsuccessful.
K8s error 442. Application marked in state 'error'.",
  "resourceURI": "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/managedClusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/apps/f670bf11-8850-44bd-b330-815af6186a06",
  "resourceCollectionURL": [
    "https://www.astra.io/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/f8b58091-4b9c-4c64-9b40-
018dbaf7c5de/apps/f670bf11-8850-44bd-b330-815af6186a06",
    "https://www.astra.io/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/923708f8-0435-45b5-8c00-
fbdef3ffaf25/apps/f670bf11-8850-44bd-b330-815af6186a06"
  ],
  "userID": "abda967f-cd2c-4237-908e-99266648c553",
  "accountID": "f126d214-bccf-4558-86b4-2137a41e734f",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

data

JSON object containing additional event-specific information.

Name	Type	Required	Description
ttl	number	False	JSON number indicating the number of seconds (since the eventTime) that the event will be retained. This field is only included when an event is automatically deleted after the specified number of seconds. When deleted, if the event has a notification destination, all associated notifications are also deleted. When deleted, if the event has a banner destination, the banner is also removed. The absence of this field (or a value of "0") means that an event will not be automatically deleted.
isAcknowledgeable	string	False	JSON string indicating whether the banner is dismissible. Defined values are: <ul style="list-style-type: none">• "true" - The banner is dismissible• "false" - The banner is not dismissible

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Execution Hook

Execution Hook overview

The Execution Hook API enables simple management of execution hooks. Execution hooks contain additional configuration and references to a hook source resource.

Create a new execution hook

POST /accounts/{account_id}/core/v1/executionHooks

Indicates the desired values for the Execution Hook API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code>

Request Body

Indicates the desired values for the Execution Hook API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-executionHook"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
name	string	True	JSON string containing a user-specified name for the resource. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63 Name must be unique across all execution hook resources.
hookType	string	True	JSON string defining the hook type. Defined values are: <ul style="list-style-type: none">• "netapp" - NetApp provided execution hook.• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.

Name	Type	Required	Description
matchingCriteria	array[matchingCriteria]	False	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
action	string	True	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"
stage	string	True	<p>JSON string indicating the stage during the action that the hook will be executed. Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".

Name	Type	Required	Description
hookSourceID	string	True	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127
appID	string	True	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	False	<p>JSON string that indicates if the execution hook is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. <p>The default value is "true".</p>

Name	Type	Required	Description
description	string	False	<p>JSON string containing a user-specified description for the hook source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "name": "Payroll",
  "hookType": "custom",
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook"
}
```

Response

Status: 201, Returns the newly created executionHook resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-executionHook"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the resource. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63 Name must be unique across all execution hook resources.

Name	Type	Required	Description
hookType	string	True	<p>JSON string defining the hook type.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "netapp" - NetApp provided execution hook. • "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.
matchingCriteria	array[matchingCriteria]	True	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
matchingContainers	array[matchingContainers]	False	<p>JSON array of JSON objects of each container that matches the configured matching criteria within the defined app.</p>
matchingImages	array[string]	False	<p>JSON array of JSON strings for the matching container images.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 4095 • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
action	string	True	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"
stage	string	True	<p>JSON string indicating the stage during the action that the hook will be executed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".
hookSourceID	string	True	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source. Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127
appID	string	False	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	True	<p>JSON string that indicates if the execution hook is enabled. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. The default value is "true".
description	string	False	<p>JSON string containing a user-specified description for the hook source. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "id": "946e60cb-980b-5374-9e6e-9fe1f6780352",
  "name": "Payroll",
  "hookType": "custom",
  "matchingCriteria": [],
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

matchingCriteria

Name	Type	Required	Description
type	string	False	JSON string identifying the match criteria type.
value	string	False	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

matchingCriteria

Name	Type	Required	Description
type	string	True	JSON string identifying the match criteria type.

Name	Type	Required	Description
value	string	True	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_k8s_label

Name	Type	Required	Description
name	string	True	
value	string	True	

matchingContainers

Name	Type	Required	Description
podName	string	False	JSON string of matching container's pod name.
podLabels	array[type_k8s_label]	False	JSON array of label objects of matching container's pod's labels.
containerImage	string	False	JSON string of matching container's image.
containerName	string	False	JSON string of matching container's name.
namespaceName	string	False	JSON string of matching container's pod's namespace name.

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all execution hooks

GET /accounts/{account_id}/core/v1/executionHooks

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p>
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: executionHook_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-executionHooks",
  "version": "1.2",
  "items": [
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "4c64792c-806b-4457-938d-8e325a37c593",
      "name": "Payroll",
      "hookType": "custom",
      "matchingCriteria": [
        {
          "type": "containerImage",
          "value": "payroll"
        },
        {
          "type": "podName",
          "value": "^payroll-master"
        }
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
      "arguments": [
        "freeze"
      ],
      "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
      "enabled": "true",
      "description": "Payroll production hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
      "name": "Order Processing",
      "hookType": "custom",
      "matchingCriteria": [
        {
```

```

        "type": "containerName",
        "value": "^order-processing$"
    },
    {
        "type": "podLabel",
        "value": "^app=master$|^app=data$"
    }
],
"action": "snapshot",
"stage": "pre",
"hookSourceID": "63f4d6fd-b7f0-4eaa-9890-0b11123604b1",
"arguments": [
    "freeze"
],
"appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
"enabled": "true",
"description": "Order processing hook",
"metadata": {
    "labels": [],
    "creationTimestamp": "2020-08-06T12:24:52.256624Z",
    "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
    "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
}
},
{
    "type": "application/astra-executionHook",
    "version": "1.1",
    "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
    "name": "NetApp Postgres Hook",
    "hookType": "netapp",
    "matchingCriteria": [
        {
            "type": "podName",
            "value": "^postgres"
        },
        {
            "type": "containerImage",
            "value": "3.8"
        }
    ],
    "action": "snapshot",
    "stage": "pre",
    "hookSourceID": "3601ed09-1a74-4156-a1bd-9cb7144bac0e",
    "arguments": [
        "freeze"
    ],

```



```

    "enabled": "true",
    "description": "Order processing hook",
    "metadata": {
      "labels": [],
      "creationTimestamp": "2020-08-06T12:24:52.256624Z",
      "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
      "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
    }
  },
  {
    "type": "application/astra-executionHook",
    "version": "1.1",
    "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
    "name": "Redis Hook",
    "hookType": "custom",
    "matchingCriteria": [
      {
        "type": "containerName",
        "value": "^redis-01$"
      }
    ],
    "action": "snapshot",
    "stage": "pre",
    "hookSourceID": "3601ed09-1a74-4156-a1bd-9cb7144bac0e",
    "arguments": [
      "freeze"
    ],
    "enabled": "true",
    "description": "Order processing hook",
    "metadata": {
      "labels": [],
      "creationTimestamp": "2020-08-06T12:24:52.256624Z",
      "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
      "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
    }
  }
],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

matchingCriteria

Name	Type	Required	Description
type	string	True	JSON string identifying the match criteria type.
value	string	True	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_k8s_label

Name	Type	Required	Description
name	string	True	
value	string	True	

matchingContainers

Name	Type	Required	Description
podName	string	False	JSON string of matching container's pod name.
podLabels	array[type_k8s_label]	False	JSON array of label objects of matching container's pod's labels.
containerImage	string	False	JSON string of matching container's image.
containerName	string	False	JSON string of matching container's name.
namespaceName	string	False	JSON string of matching container's pod's namespace name.

type_astra_label

Name	Type	Required	Description
name	string	True	

Name	Type	Required	Description
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

If not specified on create, a metadata object will be created with no labels.

If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

executionHook_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-executionHook"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-specified name for the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 <p>Name must be unique across all execution hook resources.</p>
hookType	string	True	<p>JSON string defining the hook type.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "netapp" - NetApp provided execution hook. • "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.
matchingCriteria	array[matchingCriteria]	True	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
matchingContainers	array[matchingContainers]	False	<p>JSON array of JSON objects of each container that matches the configured matching criteria within the defined app.</p>

Name	Type	Required	Description
matchingImages	array[string]	False	<p>JSON array of JSON strings for the matching container images.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 4095 • Minimum length: 1 • Maximum length: 255
action	string	True	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"
stage	string	True	<p>JSON string indicating the stage during the action that the hook will be executed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".

Name	Type	Required	Description
hookSourceID	string	True	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127
appID	string	False	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	True	<p>JSON string that indicates if the execution hook is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. <p>The default value is "true".</p>

Name	Type	Required	Description
description	string	False	JSON string containing a user-specified description for the hook source. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an execution hook

GET /accounts/{account_id}/core/v1/executionHooks/{executionHook_id}

Returns the stored Execution Hook API resource in the JSON response body. Also populates matchingContainers and matchingImages based on the current matchingCriteria and the defined app.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
executionHook_id	string	path	True	ID of the executionHook collection to list

Response

Status: 200, Returns the stored Execution Hook API resource in the JSON response body. Also populates matchingContainers and matchingImages based on the current matchingCriteria and the defined app.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-executionHook"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the resource. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 Name must be unique across all execution hook resources.
hookType	string	True	JSON string defining the hook type. Defined values are: <ul style="list-style-type: none"> • "netapp" - NetApp provided execution hook. • "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.

Name	Type	Required	Description
matchingCriteria	array[matchingCriteria]	True	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
matchingContainers	array[matchingContainers]	False	<p>JSON array of JSON objects of each container that matches the configured matching criteria within the defined app.</p>
matchingImages	array[string]	False	<p>JSON array of JSON strings for the matching container images. Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 4095 • Minimum length: 1 • Maximum length: 255
action	string	True	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"

Name	Type	Required	Description
stage	string	True	<p>JSON string indicating the stage during the action that the hook will be executed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".
hookSourceID	string	True	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127

Name	Type	Required	Description
appID	string	False	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	True	<p>JSON string that indicates if the execution hook is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. The default value is "true".
description	string	False	<p>JSON string containing a user-specified description for the hook source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "id": "946e60cb-980b-5374-9e6e-9fe1f6780352",
  "name": "Payroll",
  "hookType": "custom",
  "matchingCriteria": [
    {
      "type": "podLabel",
      "value": "^env=production$"
    },
    {
      "type": "containerName",
      "value": "^payroll-master"
    }
  ],
  "matchingImages": [
    "docker.io/bitnami/payroll:3.7.8",
    "docker.io/bitnami/payroll:4.1.2"
  ],
  "matchingContainers": [
    {
      "namespaceName": "payroll-east",
      "podName": "payroll-release3-7",
      "podLabels": [
        {
          "name": "env",
          "value": "production"
        },
        {
          "name": "app.kubernetes.io/managed-by",
          "value": "Helm"
        }
      ],
      "containerName": "payroll-master-0",
      "containerImage": "docker.io/bitnami/payroll:3.7.8"
    },
    {
      "namespaceName": "payroll-east",
      "podName": "payroll-release3-7",
      "podLabels": [
        {
          "name": "env",
          "value": "production"
        }
      ]
    }
  ]
}
```

```

    },
    {
      "name": "app.kubernetes.io/managed-by",
      "value": "Helm"
    }
  ],
  "containerName": "payroll-master-1",
  "containerImage": "docker.io/bitnami/payroll:3.7.8"
}
],
"action": "snapshot",
"stage": "pre",
"hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
"arguments": [
  "freeze"
],
"appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
"enabled": "true",
"description": "Payroll production hook",
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

matchingCriteria

Name	Type	Required	Description
type	string	True	JSON string identifying the match criteria type.
value	string	True	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_k8s_label

Name	Type	Required	Description
name	string	True	
value	string	True	

matchingContainers

Name	Type	Required	Description
podName	string	False	JSON string of matching container's pod name.
podLabels	array[type_k8s_label]	False	JSON array of label objects of matching container's pod's labels.
containerImage	string	False	JSON string of matching container's image.
containerName	string	False	JSON string of matching container's name.
namespaceName	string	False	JSON string of matching container's pod's namespace name.

type_astra_label

Name	Type	Required	Description
name	string	True	

Name	Type	Required	Description
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify an execution hook

PUT /accounts/{account_id}/core/v1/executionHooks/{executionHook_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Updating an existing execution hook will impact any future actions of applications that use the updated execution hook.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
executionHook_id	string	path	True	ID of the executionHook collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Updating an existing execution hook will impact any future actions of applications that use the updated execution hook.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-executionHook"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1" "1.2"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>JSON string containing a user-specified name for the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 Name must be unique across all execution hook resources.
hookType	string	False	<p>JSON string defining the hook type.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "netapp" - NetApp provided execution hook. • "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.
matchingCriteria	array[matchingCriteria]	False	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
action	string	False	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"

Name	Type	Required	Description
stage	string	False	<p>JSON string indicating the stage during the action that the hook will be executed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".
hookSourceID	string	False	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127

Name	Type	Required	Description
appID	string	False	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	False	<p>JSON string that indicates if the execution hook is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. The default value is "true".
description	string	False	<p>JSON string containing a user-specified description for the hook source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "arguments": [
    "freeze",
    "10"
  ]
}
```

Response

Status: 204, Indicates if the executionHook resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

matchingCriteria

Name	Type	Required	Description
type	string	False	JSON string identifying the match criteria type.
value	string	False	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete an execution hook

DELETE /accounts/{account_id}/core/v1/executionHooks/{executionHook_id}

Removes the specified Execution Hook API resource.

Side Effects

- The deleted execution hook will no longer run as part of future actions.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> • example: <code>{{.Account}}</code>
executionHook_id	string	path	True	ID of the executionHook collection to list

Response

Status: 204, Indicates if the executionHook resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new execution hook for an app

POST /accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks

Indicates the desired values for the Execution Hook API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource

Request Body

Indicates the desired values for the Execution Hook API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-executionHook"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
name	string	True	JSON string containing a user-specified name for the resource. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63 Name must be unique across all execution hook resources.
hookType	string	True	JSON string defining the hook type. Defined values are: <ul style="list-style-type: none">• "netapp" - NetApp provided execution hook.• "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.

Name	Type	Required	Description
matchingCriteria	array[matchingCriteria]	False	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
action	string	True	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"
stage	string	True	<p>JSON string indicating the stage during the action that the hook will be executed. Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".

Name	Type	Required	Description
hookSourceID	string	True	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127
appID	string	True	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	False	<p>JSON string that indicates if the execution hook is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. <p>The default value is "true".</p>

Name	Type	Required	Description
description	string	False	<p>JSON string containing a user-specified description for the hook source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "name": "Payroll",
  "hookType": "custom",
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook"
}
```


Response

Status: 201, Returns the newly created executionHook resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-executionHook"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the resource. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63 Name must be unique across all execution hook resources.

Name	Type	Required	Description
hookType	string	True	<p>JSON string defining the hook type.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "netapp" - NetApp provided execution hook. • "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.
matchingCriteria	array[matchingCriteria]	True	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
matchingContainers	array[matchingContainers]	False	<p>JSON array of JSON objects of each container that matches the configured matching criteria within the defined app.</p>
matchingImages	array[string]	False	<p>JSON array of JSON strings for the matching container images.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 4095 • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
action	string	True	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"
stage	string	True	<p>JSON string indicating the stage during the action that the hook will be executed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".
hookSourceID	string	True	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source. Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127
appID	string	False	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	True	<p>JSON string that indicates if the execution hook is enabled. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. The default value is "true".
description	string	False	<p>JSON string containing a user-specified description for the hook source. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "id": "946e60cb-980b-5374-9e6e-9fe1f6780352",
  "name": "Payroll",
  "hookType": "custom",
  "matchingCriteria": [],
  "action": "snapshot",
  "stage": "pre",
  "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
  "arguments": [
    "freeze"
  ],
  "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
  "enabled": "true",
  "description": "Payroll production hook",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

matchingCriteria

Name	Type	Required	Description
type	string	False	JSON string identifying the match criteria type.
value	string	False	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

matchingCriteria

Name	Type	Required	Description
type	string	True	JSON string identifying the match criteria type.

Name	Type	Required	Description
value	string	True	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_k8s_label

Name	Type	Required	Description
name	string	True	
value	string	True	

matchingContainers

Name	Type	Required	Description
podName	string	False	JSON string of matching container's pod name.
podLabels	array[type_k8s_label]	False	JSON array of label objects of matching container's pod's labels.
containerImage	string	False	JSON string of matching container's image.
containerName	string	False	JSON string of matching container's name.
namespaceName	string	False	JSON string of matching container's pod's namespace name.

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the execution hooks for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id"

Name	Type	In	Required	Description
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%200%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: executionHook_1.2_get_r esponse_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-executionHooks",
  "version": "1.2",
  "items": [
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "4c64792c-806b-4457-938d-8e325a37c593",
      "name": "Payroll",
      "hookType": "custom",
      "matchingCriteria": [
        {
          "type": "containerImage",
          "value": "payroll"
        },
        {
          "type": "podName",
          "value": "^payroll-master"
        }
      ],
      "action": "snapshot",
      "stage": "pre",
      "hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
      "arguments": [
        "freeze"
      ],
      "appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
      "enabled": "true",
      "description": "Payroll production hook",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
      "type": "application/astra-executionHook",
      "version": "1.1",
      "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
      "name": "Order Processing",
      "hookType": "custom",
      "matchingCriteria": [
        {
```

```

        "type": "containerName",
        "value": "^order-processing$"
    },
    {
        "type": "podLabel",
        "value": "^app=master$|^app=data$"
    }
],
"action": "snapshot",
"stage": "pre",
"hookSourceID": "63f4d6fd-b7f0-4eaa-9890-0b11123604b1",
"arguments": [
    "freeze"
],
"appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
"enabled": "true",
"description": "Order processing hook",
"metadata": {
    "labels": [],
    "creationTimestamp": "2020-08-06T12:24:52.256624Z",
    "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
    "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
}
},
{
    "type": "application/astra-executionHook",
    "version": "1.1",
    "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
    "name": "NetApp Postgres Hook",
    "hookType": "netapp",
    "matchingCriteria": [
        {
            "type": "podName",
            "value": "^postgres"
        },
        {
            "type": "containerImage",
            "value": "3.8"
        }
    ],
    "action": "snapshot",
    "stage": "pre",
    "hookSourceID": "3601ed09-1a74-4156-a1bd-9cb7144bac0e",
    "arguments": [
        "freeze"
    ],

```

```

    "enabled": "true",
    "description": "Order processing hook",
    "metadata": {
      "labels": [],
      "creationTimestamp": "2020-08-06T12:24:52.256624Z",
      "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
      "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
    }
  },
  {
    "type": "application/astra-executionHook",
    "version": "1.1",
    "id": "6659892c-c621-44e8-a0bb-8dbdf378a2dd",
    "name": "Redis Hook",
    "hookType": "custom",
    "matchingCriteria": [
      {
        "type": "containerName",
        "value": "^redis-01$"
      }
    ],
    "action": "snapshot",
    "stage": "pre",
    "hookSourceID": "3601ed09-1a74-4156-a1bd-9cb7144bac0e",
    "arguments": [
      "freeze"
    ],
    "enabled": "true",
    "description": "Order processing hook",
    "metadata": {
      "labels": [],
      "creationTimestamp": "2020-08-06T12:24:52.256624Z",
      "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
      "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
    }
  }
],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```


Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

matchingCriteria

Name	Type	Required	Description
type	string	True	JSON string identifying the match criteria type.
value	string	True	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_k8s_label

Name	Type	Required	Description
name	string	True	
value	string	True	

matchingContainers

Name	Type	Required	Description
podName	string	False	JSON string of matching container's pod name.
podLabels	array[type_k8s_label]	False	JSON array of label objects of matching container's pod's labels.
containerImage	string	False	JSON string of matching container's image.
containerName	string	False	JSON string of matching container's name.
namespaceName	string	False	JSON string of matching container's pod's namespace name.

type_astra_label

Name	Type	Required	Description
name	string	True	

Name	Type	Required	Description
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

If not specified on create, a metadata object will be created with no labels.

If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

executionHook_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-executionHook"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-specified name for the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 <p>Name must be unique across all execution hook resources.</p>
hookType	string	True	<p>JSON string defining the hook type.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "netapp" - NetApp provided execution hook. • "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.
matchingCriteria	array[matchingCriteria]	True	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
matchingContainers	array[matchingContainers]	False	<p>JSON array of JSON objects of each container that matches the configured matching criteria within the defined app.</p>

Name	Type	Required	Description
matchingImages	array[string]	False	<p>JSON array of JSON strings for the matching container images.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 4095 • Minimum length: 1 • Maximum length: 255
action	string	True	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"
stage	string	True	<p>JSON string indicating the stage during the action that the hook will be executed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".

Name	Type	Required	Description
hookSourceID	string	True	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127
appID	string	False	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	True	<p>JSON string that indicates if the execution hook is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. <p>The default value is "true".</p>

Name	Type	Required	Description
description	string	False	JSON string containing a user-specified description for the hook source. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an execution hook for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks/{executionHook_id}

Returns the stored Execution Hook API resource in the JSON response body. Also populates matchingContainers and matchingImages based on the current matchingCriteria and the defined app.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
executionHook_id	string	path	True	ID of the executionHook collection to list

Response

Status: 200, Returns the stored Execution Hook API resource in the JSON response body. Also populates matchingContainers and matchingImages based on the current matchingCriteria and the defined app.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-executionHook"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a user-specified name for the resource. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 Name must be unique across all execution hook resources.
hookType	string	True	JSON string defining the hook type. Defined values are: <ul style="list-style-type: none"> • "netapp" - NetApp provided execution hook. • "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.

Name	Type	Required	Description
matchingCriteria	array[matchingCriteria]	True	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria. Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
matchingContainers	array[matchingContainers]	False	<p>JSON array of JSON objects of each container that matches the configured matching criteria within the defined app.</p>
matchingImages	array[string]	False	<p>JSON array of JSON strings for the matching container images. Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 4095 • Minimum length: 1 • Maximum length: 255
action	string	True	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met. Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"

Name	Type	Required	Description
stage	string	True	<p>JSON string indicating the stage during the action that the hook will be executed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".
hookSourceID	string	True	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127

Name	Type	Required	Description
appID	string	False	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	True	<p>JSON string that indicates if the execution hook is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. The default value is "true".
description	string	False	<p>JSON string containing a user-specified description for the hook source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "id": "946e60cb-980b-5374-9e6e-9fe1f6780352",
  "name": "Payroll",
  "hookType": "custom",
  "matchingCriteria": [
    {
      "type": "podLabel",
      "value": "^env=production$"
    },
    {
      "type": "containerName",
      "value": "^payroll-master"
    }
  ],
  "matchingImages": [
    "docker.io/bitnami/payroll:3.7.8",
    "docker.io/bitnami/payroll:4.1.2"
  ],
  "matchingContainers": [
    {
      "namespaceName": "payroll-east",
      "podName": "payroll-release3-7",
      "podLabels": [
        {
          "name": "env",
          "value": "production"
        },
        {
          "name": "app.kubernetes.io/managed-by",
          "value": "Helm"
        }
      ],
      "containerName": "payroll-master-0",
      "containerImage": "docker.io/bitnami/payroll:3.7.8"
    },
    {
      "namespaceName": "payroll-east",
      "podName": "payroll-release3-7",
      "podLabels": [
        {
          "name": "env",
          "value": "production"
        }
      ]
    }
  ]
}
```



```

    },
    {
      "name": "app.kubernetes.io/managed-by",
      "value": "Helm"
    }
  ],
  "containerName": "payroll-master-1",
  "containerImage": "docker.io/bitnami/payroll:3.7.8"
}
],
"action": "snapshot",
"stage": "pre",
"hookSourceID": "50e89023-ba84-435d-bb47-1833f4c250ff",
"arguments": [
  "freeze"
],
"appID": "7be5ae7c-151d-4230-ac39-ac1d0b33c2a9",
"enabled": "true",
"description": "Payroll production hook",
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

matchingCriteria

Name	Type	Required	Description
type	string	True	JSON string identifying the match criteria type.
value	string	True	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_k8s_label

Name	Type	Required	Description
name	string	True	
value	string	True	

matchingContainers

Name	Type	Required	Description
podName	string	False	JSON string of matching container's pod name.
podLabels	array[type_k8s_label]	False	JSON array of label objects of matching container's pod's labels.
containerImage	string	False	JSON string of matching container's image.
containerName	string	False	JSON string of matching container's name.
namespaceName	string	False	JSON string of matching container's pod's namespace name.

type_astra_label

Name	Type	Required	Description
name	string	True	

Name	Type	Required	Description
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify an execution hook for an app

PUT /accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks/{executionHook_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Updating an existing execution hook will impact any future actions of applications that use the updated execution hook.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
executionHook_id	string	path	True	ID of the executionHook collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Updating an existing execution hook will impact any future actions of applications that use the updated execution hook.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-executionHook"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1" • "1.2"
id	string	False	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>JSON string containing a user-specified name for the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 Name must be unique across all execution hook resources.
hookType	string	False	<p>JSON string defining the hook type.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "netapp" - NetApp provided execution hook. • "custom" - Tied to a specific app ID. Execution hook resources with hookType "netapp" are read only.
matchingCriteria	array[matchingCriteria]	False	<p>JSON array of JSON objects describing the match criteria for the execution hook. When multiple matchingCriteria are specified a logical AND is applied to criteria.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 10
action	string	False	<p>JSON string indicating which action the execution hook will run assuming the match criteria are met.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "snapshot" • "backup" • "restore"

Name	Type	Required	Description
stage	string	False	<p>JSON string indicating the stage during the action that the hook will be executed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pre" - The execution hook will be run before the specified action. • "post" - The execution hook will be run after the specified action. Values for action "snapshot" are "pre" and "post". Values for action "backup" are "pre" and "post". Value for action "restore" is "post".
hookSourceID	string	False	<p>JSON string containing the hook source ID that is run through this execution hook.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
arguments	array[string]	False	<p>JSON array of JSON strings for the arguments to the source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0 • Maximum items: 16 • Minimum length: 0 • Maximum length: 127

Name	Type	Required	Description
appID	string	False	<p>JSON string containing the associated ID of the application that this hook is linked to. In essence, other matching criteria, if set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
enabled	string	False	<p>JSON string that indicates if the execution hook is enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will be run as specified. • "false" - The execution hook is disabled and will never run. The default value is "true".
description	string	False	<p>JSON string containing a user-specified description for the hook source.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-executionHook",
  "version": "1.2",
  "arguments": [
    "freeze",
    "10"
  ]
}
```

Response

Status: 204, Indicates if the executionHook resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

matchingCriteria

Name	Type	Required	Description
type	string	False	JSON string identifying the match criteria type.
value	string	False	JSON string containing a regex to match for the given match type. Regex syntax: https://github.com/google/re2/wiki/Syntax

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete an execution hook for an app

DELETE

/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHooks/{executionHook_id}

Removes the specified Execution Hook API resource.

Side Effects

- The deleted execution hook will no longer run as part of future actions.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
executionHook_id	string	path	True	ID of the executionHook collection to list

Response

Status: 204, Indicates if the executionHook resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Execution Hook Override

Execution Hook Override overview

The Execution Hook Override API allows a user to disable the preloaded "netapp" execution hooks for a specific application. **(NOTE BELOW API DEPRECATIONS)**

Create a new execution hook override resource for an app

POST /accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides

Indicates the desired values for the Execution Hook Override API resource to be created.



This operation is deprecated.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
app_id	string	path	True	ID of the containing app resource

Request Body

Indicates the desired values for the Execution Hook Override API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-executionHookOverride"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
executionHookID	string	True	JSON string containing the ID of an execution hook. Defined values are: <ul style="list-style-type: none">Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp".

Name	Type	Required	Description
enabled	string	True	<p>JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are:</p> <ul style="list-style-type: none"> "true" - The execution hook is enabled and will run in a specified order "false" - The execution hook is disabled and cannot run
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-executionHookOverride",
  "version": "1.0",
  "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
  "enabled": "false"
}
```

Response

Status: 201, Returns the newly created executionHookOverride resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-executionHookOverride"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
executionHookID	string	True	JSON string containing the ID of an execution hook. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp".

Name	Type	Required	Description
enabled	string	True	<p>JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are:</p> <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will run in a specified order • "false" - The execution hook is disabled and cannot run
appID	string	True	<p>JSON string containing the associated ID of the application with which the override is linked. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-executionHookOverride",
  "version": "1.0",
  "id": "c11af802-5e53-5897-8cd9-2de730494be3",
  "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
  "enabled": "false",
  "appID": "4b43c2f7-bffa-4f60-b595-d98a05b64bc9",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```


Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the execution hook override resources for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.



This operation is deprecated.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id"
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: executionHookOverride_1 , .0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-executionHookOverrides",
  "version": "1.0",
  "items": [
    {
      "type": "application/astra-executionHookOverride",
      "version": "1.0",
      "id": "36d06222-bd0c-4897-89c2-c16dd9265e12",
      "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
      "enabled": "false",
      "appID": "4b43c2f7-bffa-4f60-b595-d98a05b64bc9",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "863feb92-8619-4298-b222-c48a886024f8"
      }
    },
    {
      "type": "application/astra-executionHookOverride",
      "version": "1.0",
      "id": "f8d1ce66-6c0e-4d3a-96c5-a5e76669442d",
      "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
      "enabled": "false",
      "appID": "36b076ae-b7c4-4e96-a323-ed167ede74ba",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "863feb92-8619-4298-b222-c48a886024f8"
      }
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

executionHookOverride_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-executionHookOverride"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
executionHookID	string	True	JSON string containing the ID of an execution hook. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp".
enabled	string	True	JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are: <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will run in a specified order • "false" - The execution hook is disabled and cannot run
appID	string	True	JSON string containing the associated ID of the application with which the override is linked. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an execution hook override resource

GET

/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides/{executionHookOverride_id}

Returns the stored Execution Hook Override API resource in the JSON response body.



This operation is deprecated.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
executionHookOverride_id	string	path	True	ID of the executionHookOverride collection to list

Response

Status: 200, Returns the stored Execution Hook Override API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-executionHookOverride"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
executionHookID	string	True	JSON string containing the ID of an execution hook. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp".
enabled	string	True	JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are: <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will run in a specified order • "false" - The execution hook is disabled and cannot run
appID	string	True	JSON string containing the associated ID of the application with which the override is linked. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-executionHookOverride",
  "version": "1.0",
  "id": "c11af802-5e53-5897-8cd9-2de730494be3",
  "executionHookID": "eb863cc6-0d9a-454d-8ef7-81b7cac91929",
  "enabled": "false",
  "appID": "4b43c2f7-bffa-4f60-b595-d98a05b64bc9",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify an execution hook override resource

PUT

/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides/{executionHookOverride_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Any execution hook with a hookType value of "netapp" that applies to the specified application will be disabled if the value of enabled is changed from "true" to "false" during the replace operation.
- Any execution hook with a hookType value of "netapp" that applies to the specified application will be enabled if the value of enabled is changed from "false" to "true" during the replace operation.



This operation is deprecated.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
executionHookOverride_id	string	path	True	ID of the executionHookOverride collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Any execution hook with a hookType value of "netapp" that applies to the specified application will be disabled if the value of enabled is changed from "true" to "false" during the replace operation.
- Any execution hook with a hookType value of "netapp" that applies to the specified application will be enabled if the value of enabled is changed from "false" to "true" during the replace operation.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-executionHookOverride"
version	string	True	Version of the resource. Defined values are: • "1.0"

Name	Type	Required	Description
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
executionHookID	string	False	JSON string containing the ID of an execution hook. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema Only allows the executionHookID of an execution hook resource with a hookType value of "netapp".
enabled	string	False	JSON string that indicates whether the execution hook is enabled for the specified application. Defined values are: <ul style="list-style-type: none"> • "true" - The execution hook is enabled and will run in a specified order • "false" - The execution hook is disabled and cannot run
appID	string	False	JSON string containing the associated ID of the application with which the override is linked. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-executionHookOverride",
  "version": "1.0",
  "enabled": "false"
}
```

Response

Status: 204, Indicates if the executionHookOverride resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete an execution hook override resource

DELETE

/accounts/{account_id}/k8s/v1/apps/{app_id}/executionHookOverrides/{executionHookOverride_id}

Removes the specified Execution Hook Override API resource.

Side Effects

- Any execution hook with a hookType value of "netapp" that applies to the specified application will be enabled when a new execution hook override is deleted if it had an enabled value of "false".



This operation is deprecated.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
executionHookOverride_id	string	path	True	ID of the executionHookOverride collection to list

Response

Status: 204, Indicates if the executionHookOverride resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Feature

Feature overview

The Feature API provides read-only access to feature flag resources in order to determine which features are enabled or disabled in the system.

List all features

GET /accounts/{account_id}/core/v1/features

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id"

Name	Type	In	Required	Description
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
count	string	query	False	<p>Indicates if the total number of resources should be returned in the metadata object.</p> <p>URL examples: "count=true"</p> <p>OpenAPI examples: "true"</p>

Name	Type	In	Required	Description
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: feature_1.1_get_response_body, array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-features",
  "version": "1.1",
  "items": [
    {
      "type": "application/astra-feature",
      "version": "1.0",
      "id": "c1d4d2f7-9b30-45a2-9657-8b24f17a4fd1",
      "name": "astra.account.rbac",
      "isEnabled": "true",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2021-02-19T22:10:22.448274Z",
        "modificationTimestamp": "2021-02-19T22:10:22.448274Z",
        "createdBy": "c9550bbb-e70b-4578-8504-07397f875bcb"
      }
    },
    {
      "type": "application/astra-feature",
      "version": "1.0",
      "id": "85c693cd-2f89-4944-982a-e885301162bd",
      "name": "astra.account.smtp",
      "isEnabled": "false",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2021-02-19T22:10:22.448274Z",
        "modificationTimestamp": "2021-02-19T22:10:22.448274Z",
        "createdBy": "c9550bbb-e70b-4578-8504-07397f875bcb"
      }
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

feature_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-feature"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	JSON string containing a name for the feature, in hierarchal dot notation. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
isEnabled	string	True	JSON string containing a value indicating whether the feature flag is turned on or off. Defined values are: <ul style="list-style-type: none"> • "true" - The feature flag is enabled. • "false" - The feature flag is disabled.
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a feature

GET /accounts/{account_id}/core/v1/features/{feature_id}

Returns the stored Feature API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
feature_id	string	path	True	ID of the feature collection to list

Response

Status: 200, Returns the stored Feature API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-feature"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the feature, in hierarchal dot notation. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
isEnabled	string	True	JSON string containing a value indicating whether the feature flag is turned on or off. Defined values are: <ul style="list-style-type: none"> • "true" - The feature flag is enabled. • "false" - The feature flag is disabled.
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-feature",
  "version": "1.1",
  "id": "2d960b50-10be-5a19-a3ef-80bd08c12a89",
  "name": "astra.account.rbac",
  "isEnabled": "true",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Group

Group overview

The Group API provides access to Astra group resources.

Create a new group

POST /accounts/{account_id}/core/v1/groups

Indicates the desired values for the Group API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates the desired values for the Group API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-group"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
name	string	False	The name of the group resource. If not specified on create, the value will be set to <ul style="list-style-type: none">first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID,authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are:<ul style="list-style-type: none">Minimum length: 1Maximum length: 256

Name	Type	Required	Description
authProvider	string	True	The authentication provider for the group resource. Defined values are: <ul style="list-style-type: none"> "ldap"
authID	string	True	The Distinguished Name (DN) for an LDAP group. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 256
metadata	type_astra_metadata_update	False	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-group",
  "version": "1.0",
  "name": "engineering-group",
  "authProvider": "ldap",
  "authID": "CN=Engineering,CN=Groups,DC=example,DC=com"
}
```


Response

Status: 201, Returns the newly created group resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-group"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	The name of the group resource. If not specified on create, the value will be set to <ul style="list-style-type: none">• first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID,• authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are:<ul style="list-style-type: none">• Minimum length: 1• Maximum length: 256

Name	Type	Required	Description
authProvider	string	True	<p>The authentication provider for the group resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "ldap"
authID	string	True	<p>The Distinguished Name (DN) for an LDAP group.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-group",
  "version": "1.0",
  "id": "d8560bb2-7c87-5331-a78d-4e870b22e9a9",
  "name": "engineering-group",
  "authProvider": "ldap",
  "authID": "CN=Engineering,CN=Groups,DC=example,DC=com",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/14",
  "title": "Unauthorized access",
  "detail": "The user isn't enabled.",
  "status": "403"
}
```

Response

Status: 406, Not acceptable

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/32",
  "title": "Unsupported content type",
  "detail": "The response can't be returned in the requested format.",
  "status": "406"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example error response

```
{
  "type": "https://astra.netapp.io/problems/7",
  "title": "Invalid JSON payload",
  "detail": "The request body is not valid JSON.",
  "status": "400"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all groups

GET /accounts/{account_id}/core/v1/groups

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,authProvider, authID
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata=""></continue> OpenAPI examples: <continue token="" from="" collection="" metadata=""></continue></continue>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: group_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-groups",
  "version": "1.0",
  "items": [
    [
      "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa",
      "ldap",
      "CN=Testers,CN=groups,DC=example,DC=com"
    ],
    [
      "e324ec3a-706d-4f57-a95d-1d88c03e7b73",
      "ldap",
      "CN=Admins,CN=groups,DC=example,DC=com"
    ],
    [
      "3070c84d-129b-4017-82a8-2c26a42dd77e",
      "ldap",
      "CN=SREs,CN=groups,DC=example,DC=com"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Name	Type	Required	Description
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

group_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-group"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>The name of the group resource. If not specified on create, the value will be set to</p> <ul style="list-style-type: none"> • first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID, • authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are: • Minimum length: 1 • Maximum length: 256
authProvider	string	True	<p>The authentication provider for the group resource. Defined values are:</p> <ul style="list-style-type: none"> • "Idap"
authID	string	True	<p>The Distinguished Name (DN) for an LDAP group. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a group

GET /accounts/{account_id}/core/v1/groups/{group_id}

Returns the stored Group API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
group_id	string	path	True	ID of the group collection to list

Response

Status: 200, Returns the stored Group API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-group"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>The name of the group resource. If not specified on create, the value will be set to</p> <ul style="list-style-type: none"> • first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID, • authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are: • Minimum length: 1 • Maximum length: 256
authProvider	string	True	<p>The authentication provider for the group resource. Defined values are:</p> <ul style="list-style-type: none"> • "ldap"
authID	string	True	<p>The Distinguished Name (DN) for an LDAP group. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-group",
  "version": "1.0",
  "id": "d8560bb2-7c87-5331-a78d-4e870b22e9a9",
  "name": "engineering-group",
  "authProvider": "ldap",
  "authID": "CN=Engineering,CN=groups,DC=example,DC=com",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/12",
  "title": "Invalid headers",
  "detail": "The request headers are invalid.",
  "status": "400"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a group

PUT /accounts/{account_id}/core/v1/groups/{group_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the group collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-group"
version	string	True	Version of the resource. Defined values are: • "1.0"
id	string	False	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>The name of the group resource. If not specified on create, the value will be set to</p> <ul style="list-style-type: none"> • first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID, • authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are: • Minimum length: 1 • Maximum length: 256
authProvider	string	False	<p>The authentication provider for the group resource. Defined values are:</p> <ul style="list-style-type: none"> • "ldap"
authID	string	False	<p>The Distinguished Name (DN) for an LDAP group. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-group",
  "version": "1.0",
  "name": "my-qa-group",
  "authID": "CN=QA,CN=Groups,DC=example,DC=com"
}
```

Response

Status: 204, Indicates if the group resource was updated.

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/7",
  "title": "Invalid JSON payload",
  "detail": "The request body is not valid JSON.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete a group

DELETE /accounts/{account_id}/core/v1/groups/{group_id}

Removes the specified Group API resource.

Side Effects

- The following resources associated with the group are deleted:

- Role bindings referring to the group

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the group collection to list

Response

Status: 204, Indicates if the group resource was deleted.

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/12",
  "title": "Invalid headers",
  "detail": "The request headers are invalid.",
  "status": "400"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new group for a user

POST /accounts/{account_id}/core/v1/users/{user_id}/groups

Indicates the desired values for the Group API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
user_id	string	path	True	ID of the containing user resource

Request Body

Indicates the desired values for the Group API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-group"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
name	string	False	The name of the group resource. If not specified on create, the value will be set to <ul style="list-style-type: none"> • first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID, • authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256
authProvider	string	True	The authentication provider for the group resource. Defined values are: <ul style="list-style-type: none"> • "ldap"
authID	string	True	The Distinguished Name (DN) for an LDAP group. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-group",
  "version": "1.0",
  "name": "engineering-group",
  "authProvider": "ldap",
  "authID": "CN=Engineering,CN=Groups,DC=example,DC=com"
}
```

Response

Status: 201, Returns the newly created group resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> "application/astra-group"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	The name of the group resource. If not specified on create, the value will be set to <ul style="list-style-type: none"> • first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID, • authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256
authProvider	string	True	The authentication provider for the group resource. Defined values are: <ul style="list-style-type: none"> • "ldap"
authID	string	True	The Distinguished Name (DN) for an LDAP group. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-group",
  "version": "1.0",
  "id": "d8560bb2-7c87-5331-a78d-4e870b22e9a9",
  "name": "engineering-group",
  "authProvider": "ldap",
  "authID": "CN=Engineering,CN=Groups,DC=example,DC=com",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/14",
  "title": "Unauthorized access",
  "detail": "The user isn't enabled.",
  "status": "403"
}
```

Response

Status: 406, Not acceptable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/32",
  "title": "Unsupported content type",
  "detail": "The response can't be returned in the requested format.",
  "status": "406"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example error response

```
{
  "type": "https://astra.netapp.io/problems/7",
  "title": "Invalid JSON payload",
  "detail": "The request body is not valid JSON.",
  "status": "400"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List groups for a user

GET /accounts/{account_id}/core/v1/users/{user_id}/groups

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,authProvider, authID
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata=""></continue> OpenAPI examples: "<continue token="" from="" collection="" metadata=""></continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: group_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-groups",
  "version": "1.0",
  "items": [
    [
      "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa",
      "ldap",
      "CN=Testers,CN=groups,DC=example,DC=com"
    ],
    [
      "e324ec3a-706d-4f57-a95d-1d88c03e7b73",
      "ldap",
      "CN=Admins,CN=groups,DC=example,DC=com"
    ],
    [
      "3070c84d-129b-4017-82a8-2c26a42dd77e",
      "ldap",
      "CN=SREs,CN=groups,DC=example,DC=com"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Name	Type	Required	Description
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

group_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-group"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>The name of the group resource. If not specified on create, the value will be set to</p> <ul style="list-style-type: none"> • first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID, • authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are: • Minimum length: 1 • Maximum length: 256
authProvider	string	True	<p>The authentication provider for the group resource. Defined values are:</p> <ul style="list-style-type: none"> • "Idap"
authID	string	True	<p>The Distinguished Name (DN) for an LDAP group. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a group for a user

GET /accounts/{account_id}/core/v1/users/{user_id}/groups/{group_id}

Returns the stored Group API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
user_id	string	path	True	ID of the containing user resource
group_id	string	path	True	ID of the group collection to list

Response

Status: 200, Returns the stored Group API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-group"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>The name of the group resource. If not specified on create, the value will be set to</p> <ul style="list-style-type: none"> • first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID, • authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256
authProvider	string	True	<p>The authentication provider for the group resource. Defined values are:</p> <ul style="list-style-type: none"> • "ldap"
authID	string	True	<p>The Distinguished Name (DN) for an LDAP group. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-group",
  "version": "1.0",
  "id": "d8560bb2-7c87-5331-a78d-4e870b22e9a9",
  "name": "engineering-group",
  "authProvider": "ldap",
  "authID": "CN=Engineering,CN=groups,DC=example,DC=com",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/12",
  "title": "Invalid headers",
  "detail": "The request headers are invalid.",
  "status": "400"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a group for a user

PUT /accounts/{account_id}/core/v1/users/{user_id}/groups/{group_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
group_id	string	path	True	ID of the group collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-group"
version	string	True	Version of the resource. Defined values are: • "1.0"
id	string	False	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>The name of the group resource. If not specified on create, the value will be set to</p> <ul style="list-style-type: none"> • first Common Name (CN) Relative Distinguished Names (RDN) if found in the authID, • authID, otherwise. If not specified on update, the value will be preserved without modification. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256
authProvider	string	False	<p>The authentication provider for the group resource. Defined values are:</p> <ul style="list-style-type: none"> • "ldap"
authID	string	False	<p>The Distinguished Name (DN) for an LDAP group. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 256

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-group",
  "version": "1.0",
  "name": "my-qa-group",
  "authID": "CN=QA,CN=Groups,DC=example,DC=com"
}
```

Response

Status: 204, Indicates if the group resource was updated.

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/7",
  "title": "Invalid JSON payload",
  "detail": "The request body is not valid JSON.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete a group for a user

DELETE /accounts/{account_id}/core/v1/users/{user_id}/groups/{group_id}

Removes the specified Group API resource.

Side Effects

- The following resources associated with the group are deleted:

- Role bindings referring to the group

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
group_id	string	path	True	ID of the group collection to list

Response

Status: 204, Indicates if the group resource was deleted.

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/12",
  "title": "Invalid headers",
  "detail": "The request headers are invalid.",
  "status": "400"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Hook source

Hook source overview

The Hook Source API enables simple management of hook sources separate from the management of the execution hook resources. For example, a single hook source can be referenced by multiple execution hooks to avoid duplicate hook sources and allow a single API call to update one hook source, even if it is used by multiple execution hook resources.

Create a new hook source

POST /accounts/{account_id}/core/v1/hookSources

Indicates the desired values for the Hook Source API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>

Request Body

Indicates the desired values for the Hook Source API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-hookSource"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
name	string	True	JSON string containing a user-specified name for the resource. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 63 The name is required to be unique within all hook source resources.
sourceType	string	True	JSON string defining the hook source type. Defined values are: <ul style="list-style-type: none"> "script" - Shell script. The plaintext source must not contain binary data or carriage-return characters, otherwise, an error is returned.

Name	Type	Required	Description
source	string	True	<p>JSON string containing the script to be run in base64 format. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 131072 • Conforms to the base64 Encoded Data Schema The maximum size of a source value is 128 KiB when encoded using base64.
description	string	False	<p>JSON string containing a user-specified description of the hook source. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-hookSource",
  "version": "1.0",
  "name": "Payroll script",
  "sourceType": "script",
  "source": "ZWNobyAIVkhKaGJuTWdVbWxuYUhSeklRPT0iIHwgYmFzZTY0IC1k",
  "description": "Pre and post hook script for payroll"
}
```

Response

Status: 201, Returns the newly created hookSource resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-hookSource"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-specified name for the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 <p>The name is required to be unique within all hook source resources.</p>
private	string	True	<p>JSON string indicating whether the source field will be exposed in APIs or be intentionally left blank.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The source value is private and will not be exposed through the API. • "false" - The source value is not private and will be exposed through the API.
preloaded	string	True	<p>JSON string that indicates whether the source was preloaded.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The source was preloaded. • "false" - The source was not preloaded. Preloaded hook source resources are read only.

Name	Type	Required	Description
sourceType	string	True	<p>JSON string defining the hook source type. Defined values are:</p> <ul style="list-style-type: none"> • "script" - Shell script. The plaintext source must not contain binary data or carriage-return characters, otherwise, an error is returned.
source	string	False	<p>JSON string containing the script to be run in base64 format. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 131072 • Conforms to the base64 Encoded Data Schema The maximum size of a source value is 128 KiB when encoded using base64.
sourceMD5Checksum	string	True	<p>JSON string containing the MD5 checksum computed for the value of the "source" key. Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: "^[0-9a-fA-F]{32}\$"
description	string	False	<p>JSON string containing a user-specified description of the hook source. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-hookSource",
  "version": "1.0",
  "id": "fae6dfbb-ecb8-58ff-a116-6357eb7c956a",
  "name": "Payroll script",
  "private": "false",
  "preloaded": "false",
  "sourceType": "script",
  "source": "ZWNobyAIVkhKaGJuTWdVbWxuYUhSeklRPT0iIHwgYmFzZTY0IC1k",
  "sourceMD5Checksum": "b1a4b8b0144c3f6be553b626130ca145",
  "description": "Pre and post hook script for payroll",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all hook sources

GET /accounts/{account_id}/core/v1/hookSources

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id"
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: hookSource_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-hookSources",
  "version": "1.0",
  "items": [
    {
      "type": "application/astra-hookSource",
      "version": "1.0",
      "id": "2d6154dd-6863-4a26-8017-6be092b8b0bd",
      "name": "Payroll script",
      "private": "false",
      "preloaded": "false",
      "sourceType": "script",
      "source": "ZWNobyAIVkhKaGJuTWdVbWxuYUhSeklRPT0iIHwgYmFzZTY0IC1k",
      "sourceMD5Checksum": "b1a4b8b0144c3f6be553b626130ca145",
      "description": "Pre and post hook script for payroll",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
      "type": "application/astra-hookSource",
      "version": "1.0",
      "id": "b71c6793-aa9b-4654-92ef-60663a0aedac",
      "name": "Payroll script",
      "private": "true",
      "preloaded": "false",
      "sourceType": "script",
      "sourceMD5Checksum": "6469094cb279f6d91358bc5062d15baf",
      "description": "Pre and post hook script for payroll",
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-08-08T12:24:52.256624Z",
        "modificationTimestamp": "2020-08-08T12:24:52.256624Z",
        "createdBy": "64182074-ddb6-42eb-b7f4-b6a02cf9ba7c"
      }
    },
    {
      "type": "application/astra-hookSource",
      "version": "1.0",
      "id": "682fe9d2-52d2-4c30-bcec-ecefddde359c",
      "name": "NetApp preloaded ",

```

```

    "private": "true",
    "preloaded": "false",
    "sourceType": "script",
    "sourceMD5Checksum": "7864495443c1087104520a320a2225c9",
    "description": "NetApp Postgres preloaded snapshot pre and post",
    "metadata": {
      "labels": [],
      "creationTimestamp": "2020-07-12T12:24:52.256624Z",
      "modificationTimestamp": "2020-07-12T12:24:52.256624Z",
      "createdBy": "4428cfd4-27fd-4248-9f49-bd3a02043ab8"
    }
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```

{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}

```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

hookSource_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-hookSource"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-specified name for the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 <p>The name is required to be unique within all hook source resources.</p>
private	string	True	<p>JSON string indicating whether the source field will be exposed in APIs or be intentionally left blank.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The source value is private and will not be exposed through the API. • "false" - The source value is not private and will be exposed through the API.
preloaded	string	True	<p>JSON string that indicates whether the source was preloaded.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The source was preloaded. • "false" - The source was not preloaded. Preloaded hook source resources are read only.

Name	Type	Required	Description
sourceType	string	True	<p>JSON string defining the hook source type. Defined values are:</p> <ul style="list-style-type: none"> • "script" - Shell script. The plaintext source must not contain binary data or carriage-return characters, otherwise, an error is returned.
source	string	False	<p>JSON string containing the script to be run in base64 format. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 131072 • Conforms to the base64 Encoded Data Schema The maximum size of a source value is 128 KiB when encoded using base64.
sourceMD5Checksum	string	True	<p>JSON string containing the MD5 checksum computed for the value of the "source" key. Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: "^[0-9a-fA-F]{32}\$"
description	string	False	<p>JSON string containing a user-specified description of the hook source. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a hook source

GET /accounts/{account_id}/core/v1/hookSources/{hookSource_id}

Returns the stored Hook Source API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
hookSource_id	string	path	True	ID of the hookSource collection to list

Response

Status: 200, Returns the stored Hook Source API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-hookSource"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a user-specified name for the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 The name is required to be unique within all hook source resources.
private	string	True	<p>JSON string indicating whether the source field will be exposed in APIs or be intentionally left blank.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The source value is private and will not be exposed through the API. • "false" - The source value is not private and will be exposed through the API.
preloaded	string	True	<p>JSON string that indicates whether the source was preloaded.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The source was preloaded. • "false" - The source was not preloaded. Preloaded hook source resources are read only.

Name	Type	Required	Description
sourceType	string	True	<p>JSON string defining the hook source type. Defined values are:</p> <ul style="list-style-type: none"> "script" - Shell script. The plaintext source must not contain binary data or carriage-return characters, otherwise, an error is returned.
source	string	False	<p>JSON string containing the script to be run in base64 format. Defined values are:</p> <ul style="list-style-type: none"> Minimum length: 0 Maximum length: 131072 Conforms to the base64 Encoded Data Schema The maximum size of a source value is 128 KiB when encoded using base64.
sourceMD5Checksum	string	True	<p>JSON string containing the MD5 checksum computed for the value of the "source" key. Defined values are:</p> <ul style="list-style-type: none"> Defined regex is: "^[0-9a-fA-F]{32}\$"
description	string	False	<p>JSON string containing a user-specified description of the hook source. Defined values are:</p> <ul style="list-style-type: none"> Minimum length: 0 Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-hookSource",
  "version": "1.0",
  "id": "fae6dfbb-ecb8-58ff-a116-6357eb7c956a",
  "name": "Payroll script",
  "private": "false",
  "preloaded": "false",
  "sourceType": "script",
  "source": "ZWNobyAIVkhKaGJuTWdVbWxuYUhSeklRPT0iIHwgYmFzZTY0IC1k",
  "sourceMD5Checksum": "b1a4b8b0144c3f6be553b626130ca145",
  "description": "Pre and post hook script for payroll",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a hook source

PUT /accounts/{account_id}/core/v1/hookSources/{hookSource_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Updating an existing source hook will immediately impact any future snapshots of applications that have matching execution hooks that use the updated source hook resource.

- The MD5 checksum is computed on the value of the "source" field and set as the value of the "sourceMD5Checksum" field.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
hookSource_id	string	path	True	ID of the hookSource collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Updating an existing source hook will immediately impact any future snapshots of applications that have matching execution hooks that use the updated source hook resource.
- The MD5 checksum is computed on the value of the "source" field and set as the value of the "sourceMD5Checksum" field.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-hookSource"
version	string	True	Version of the resource. Defined values are: • "1.0"
id	string	False	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>JSON string containing a user-specified name for the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 The name is required to be unique within all hook source resources.
private	string	False	<p>JSON string indicating whether the source field will be exposed in APIs or be intentionally left blank.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The source value is private and will not be exposed through the API. • "false" - The source value is not private and will be exposed through the API.
preloaded	string	False	<p>JSON string that indicates whether the source was preloaded.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The source was preloaded. • "false" - The source was not preloaded. Preloaded hook source resources are read only.

Name	Type	Required	Description
sourceType	string	False	<p>JSON string defining the hook source type. Defined values are:</p> <ul style="list-style-type: none"> "script" - Shell script. The plaintext source must not contain binary data or carriage-return characters, otherwise, an error is returned.
source	string	False	<p>JSON string containing the script to be run in base64 format. Defined values are:</p> <ul style="list-style-type: none"> Minimum length: 0 Maximum length: 131072 Conforms to the base64 Encoded Data Schema The maximum size of a source value is 128 KiB when encoded using base64.
sourceMD5Checksum	string	False	<p>JSON string containing the MD5 checksum computed for the value of the "source" key. Defined values are:</p> <ul style="list-style-type: none"> Defined regex is: "^[0-9a-fA-F]{32}\$"
description	string	False	<p>JSON string containing a user-specified description of the hook source. Defined values are:</p> <ul style="list-style-type: none"> Minimum length: 0 Maximum length: 511

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-hookSource",
  "version": "1.0",
  "source": "ZWNobyAiVkhKaGJuTWdVbWxuYUhSeklRPT0iIHwgYmFzZTY0IC1k",
  "description": "Pre and post hook script for order processing v2"
}
```

Response

Status: 204, Indicates if the hookSource resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a hook source

DELETE /accounts/{account_id}/core/v1/hookSources/{hookSource_id}

Removes the specified Hook Source API resource.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
hookSource_id	string	path	True	ID of the hookSource collection to list

Response

Status: 204, Indicates if the hookSource resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Kubernetes API Resource

Kubernetes API Resource overview

The Kubernetes API Resource API provides read-only access to Kubernetes API resources to filter the ones supported by Astra on a given cluster.

List the K8s API resources for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/apiResources

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: id,kind,apiVersion
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: apiResource_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-apiResources",
  "version": "1.0",
  "items": [
    [
      "e280ff62-be35-4f31-a31b-a210a1ad1b33",
      "ClusterRole",
      "rbac.authorization.k8s.io/v1"
    ],
    [
      "e8507dad-d33f-44b3-9c15-ec55ba6f6473",
      "ClusterRoleBinding",
      "rbac.authorization.k8s.io/v1"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

apiResource_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-apiResource"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
apiVersion	string	True	<p>JSON string representing the API version of the resource, as set in or by Kubernetes. APIVersion defines the versioned schema for this object representation. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources</p>
kind	string	True	<p>JSON string representing the kind of the resource, as set in or by Kubernetes. The kind field uses camel case and contains a string value representing the REST resource this object represents. Servers might infer this from the endpoint the client submits requests to. It cannot be updated. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds</p>
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a K8s API resource

GET

```
/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/apiResources/{apiResource_id}
```

Returns the specific API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
managedCluster_id	string	path	True	ID of the containing managedCluster resource
apiResource_id	string	path	True	ID of the apiResource collection to list

Response

Status: 200, Returns the specific API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-apiResource"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
apiVersion	string	True	JSON string representing the API version of the resource, as set in or by Kubernetes. APIVersion defines the versioned schema for this object representation. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources

Name	Type	Required	Description
kind	string	True	<p>JSON string representing the kind of the resource, as set in or by Kubernetes.</p> <p>The kind field uses camel case and contains a string value representing the REST resource this object represents. Servers might infer this from the endpoint the client submits requests to. It cannot be updated.</p> <p>More info: https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds</p>
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-apiResource",
  "version": "1.0",
  "id": "e280ff62-be35-4f31-a31b-a210a1ad1b33",
  "kind": "ClusterRole",
  "apiVersion": "rbac.authorization.k8s.io/v1",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

LDAP Group

LDAP Group overview

The LDAP Group API provides read-only access to LDAP groups within the configured LDAP server.

List all LDAP groups

GET /accounts/{account_id}/core/v1/ldapGroups

Returns a JSON array of JSON objects containing the results of the request URL.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,cn,dn
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
continue		query	False	<p>Indicates the token to resume listing from.</p> <p>URL examples: "continue=<continue token="" from="" collection="" metadata=""></continue></p> <p>OpenAPI examples: "<continue token="" from="" collection="" metadata=""></continue>&lt;/continue&gt;"</p>

Response

Status: 200, Returns a JSON array of JSON objects containing the results of the request URL.

Name	Type	Required	Description
items	array[Any of: ldapGroup_1.0_get_response_body, array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-ldapGroups",
  "version": "1.0",
  "items": [
    [
      "4a461f57-70e6-5732-882e-8d5f684f15a1",
      "boulder_sysadmins",
      "cn=boulder_sysadmins,ou=groups,dc=example,dc=com"
    ],
    [
      "da4bbb6f-8f2c-57eb-a9cf-6eefbf9e35d",
      "rtp_sysadmins",
      "cn=rtp_sysadmins,ou=groups,dc=example,dc=com"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Name	Type	Required	Description
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/14",
  "title": "Unauthorized access",
  "detail": "The user isn't enabled.",
  "status": "403"
}
```

Response

Status: 406, Not acceptable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/32",
  "title": "Unsupported content type",
  "detail": "The response can't be returned in the requested format.",
  "status": "406"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

ldapGroup_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-ldapGroup"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
cn	string	False	JSON string representing the LDAP group name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
dn	string	False	JSON string representing the distinguished name of the LDAP group. Defined values are: <ul style="list-style-type: none"> • Conforms to RFC 4514
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

Retrieve an LDAP group

GET /accounts/{account_id}/core/v1/ldapGroups/{ldapGroup_id}

Returns a JSON object representing the stored LDAP resource.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
ldapGroup_id	string	path	True	ID of the ldapGroup collection to list

Response

Status: 200, Returns a JSON object representing the stored LDAP resource.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-ldapGroup"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
cn	string	False	JSON string representing the LDAP group name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
dn	string	False	JSON string representing the distinguished name of the LDAP group. Defined values are: <ul style="list-style-type: none"> • Conforms to RFC 4514
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-ldapGroup",
  "version": "1.0",
  "id": "cb05a289-a7a1-502c-a2bc-7e75dba8fddc",
  "cn": "boulder_sysadmins",
  "dn": "cn=boulder_sysadmins,ou=groups,dc=example,dc=com",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

LDAP User

LDAP User overview

The LDAP User API provides read-only access to LDAP users within the configured LDAP server.

List all LDAP users

GET /accounts/{account_id}/core/v1/ldapUsers

Returns a JSON array of JSON objects containing the results of the request URL.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,cn,dn
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
continue		query	False	<p>Indicates the token to resume listing from.</p> <p>URL examples: "continue=<continue token="" from="" collection="" metadata=""></continue></p> <p>OpenAPI examples: "<continue token="" from="" collection="" metadata=""></continue>&lt;/continue&gt;"</p>

Response

Status: 200, Returns a JSON array of JSON objects containing the results of the request URL.

Name	Type	Required	Description
items	array[Any of: ldapUser_1.0_get_response_body, array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-ldapUsers",
  "version": "1.0",
  "items": [
    [
      "b4bcef18-14ad-5bc1-91ce-3cce15aa8791",
      "John Doe",
      "cn=John Doe,ou=people,dc=example,dc=com"
    ],
    [
      "98b10d6f-8693-555f-b258-70de4cc7301f",
      "Jane Doe",
      "cn=Jane Doe,ou=people,dc=example,dc=com"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/14",
  "title": "Unauthorized access",
  "detail": "The user isn't enabled.",
  "status": "403"
}
```

Response

Status: 406, Not acceptable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/32",
  "title": "Unsupported content type",
  "detail": "The response can't be returned in the requested format.",
  "status": "406"
}
```

Response

Status: 500, Internal server error

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/34",
  "title": "Internal server error",
  "detail": "The server was unable to process this request.",
  "status": "500"
}
```

Error

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example error response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

ldapUser_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-ldapUser"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
email	string	False	JSON string representing the email of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 63
firstName	string	False	JSON string representing the first name of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
lastName	string	False	JSON string representing the last name of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
cn	string	False	JSON string representing the LDAP group name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
dn	string	False	JSON string representing the distinguished name of the LDAP group. Defined values are: <ul style="list-style-type: none"> • Conforms to RFC 4514

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an LDAP user

GET /accounts/{account_id}/core/v1/ldapUsers/{ldapUser_id}

Returns a JSON object representing the stored LDAP resource.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
ldapUser_id	string	path	True	ID of the ldapUser collection to list

Response

Status: 200, Returns a JSON object representing the stored LDAP resource.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-ldapUser"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
email	string	False	JSON string representing the email of the LDAP user. Defined values are: <ul style="list-style-type: none"> Minimum length: 3 Maximum length: 63

Name	Type	Required	Description
firstName	string	False	JSON string representing the first name of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
lastName	string	False	JSON string representing the last name of the LDAP user. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
cn	string	False	JSON string representing the LDAP group name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
dn	string	False	JSON string representing the distinguished name of the LDAP group. Defined values are: <ul style="list-style-type: none"> • Conforms to RFC 4514
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-ldapUser",
  "version": "1.0",
  "id": "2add73ff-89dc-5ff1-be85-39d97549556d",
  "email": "<a href="
mailto:johndoe@example.com">johndoe@example.com</a>",
  "firstName": "John",
  "lastName": "Doe",
  "cn": "John Doe",
  "dn": "cn=John Doe,ou=people,dc=example,dc=com",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```


Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

License

License overview

The License API represents licenses loaded into the account.

Create a new license

POST /accounts/{account_id}/core/v1/licenses

Indicates the desired values for the License API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates the desired values for the License API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-license"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
allocation	string	False	JSON string containing an ID indicating what the license is allocated to. Only present when the license is allocated. For Astra Control Center licenses, this field must be populated with the account ID and must match the account ID specified in the POST URI. Defined values are: <ul style="list-style-type: none">Conforms to the Astra Identifier Schema

Name	Type	Required	Description
deviceCredentialID	string	False	<p>JSON string containing the identifier of the deviceCredential associated with the Credential API. Only present for Astra Data Store licenses.</p> <p>Defined value are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
licenseText	string	True	<p>JSON string containing a base64 encoded representation of the license JSON as obtained from the NetApp license system. This must be provided in the original byte-level order to allow signature verification.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-license",
  "version": "1.0",
  "allocation": "4185d09b-6687-4801-a832-c005a9d94f41",
  "licenseText": "ewogICAic3RhdHVzUmVzcCI6ewogMTYwNzAwIgp9"
}
```

Response

Status: 201, Returns the newly created license resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-license"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
allocation	string	False	<p>JSON string containing an ID indicating what the license is allocated to. Only present when the license is allocated. For Astra Control Center licenses, this field must be populated with the account ID and must match the account ID specified in the POST URI.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
hostID	string	False	<p>JSON string containing a host identifier that a license is bound to. Only present if the license is host-locked.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
deviceCredentialID	string	False	<p>JSON string containing the identifier of the deviceCredential associated with the Credential API. Only present for Astra Data Store licenses.</p> <p>Defined value are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
isEvaluation	string	True	<p>JSON string indicating whether the license is an evaluation license.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" • "false"

Name	Type	Required	Description
licenseProtocol	string	True	<p>JSON string containing the license protocol extracted from the license.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
licenseText	string	True	<p>JSON string containing a base64 encoded representation of the license JSON as obtained from the NetApp license system. This must be provided in the original byte-level order to allow signature verification.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema
validFromTimestamp	string	True	<p>JSON string containing a timestamp indicating when the license becomes valid.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
validUntilTimestamp	string	True	<p>JSON string containing a timestamp indicating when the license is no longer valid.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
product	string	True	<p>JSON string containing the product string extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
productVersion	string	True	<p>JSON string containing the version string extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
productSN	string	True	<p>JSON string containing the serial number string extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
features	string	True	<p>JSON string containing the package value extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
capacity	string	True	<p>JSON string containing the capacity extracted from the license.</p>
capacity2	string	True	<p>JSON string containing the secondary capacity extracted from the license.</p>

Name	Type	Required	Description
addons	array[addons]	False	<p>JSON array of JSON objects containing the list of add-ons from the license.</p> <p>An add-on is a change in license occurring at a potential future date.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-license",
  "version": "1.0",
  "id": "6db53b32-8417-5d3c-8ef0-552fc602c78f",
  "allocation": "4185d09b-6687-4801-a832-c005a9d94f41",
  "hostID": "99132549-e0c2-4203-9d1e-598628b4ff9b",
  "isEvaluation": "false",
  "licenseProtocol": "ASTRASDS-ENT-SUBS",
  "licenseText": "ewogICAic3RhdHVzUmVzcCI6ewogMTYwNzAwIgp9",
  "validFromTimestamp": "2020-08-06T00:00:00.000000Z",
  "validUntilTimestamp": "2021-08-06T00:00:00.000000Z",
  "product": "Astra Control Center",
  "productVersion": "1.0",
  "productSN": "320000046",
  "features": "ASTRA-ENT-STD",
  "capacity": "4000",
  "capacity2": "0",
  "addons": [
    {
      "startDate": "2020-08-06T00:00:00.000000Z",
      "endDate": "2021-08-06T00:00:00.000000Z",
      "capacity": "4000",
      "licenseProtocol": "ASTRA-ENT-STD",
      "features": "p-nfs, dm-storage-policy-based-pvs-for-k8s, dm-spbm-
based-vvols-for-vms, dm-storage-efficiency, dm-data-at-rest-encryption"
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

addons

Name	Type	Required	Description
startDate	string	False	JSON string containing a timestamp indicating when this add-on becomes valid. Defined values are: <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema
endDate	string	False	JSON string containing a timestamp indicating when this add-on is no longer valid. Defined values are: <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
features	string	False	JSON string containing the list of features associated with this add-on. Defined values are: <ul style="list-style-type: none"> • String contents not validated by the schema.
capacity	string	False	JSON string containing the capacity extracted from the add-on. Defined values are: <ul style="list-style-type: none"> • String contents not validated by the schema
licenseProtocol	string	False	JSON string containing the license protocol associated with this add-on. Defined values are: <ul style="list-style-type: none"> • String contents not validated by the schema

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all licenses

GET /accounts/{account_id}/core/v1/licenses

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,product
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: license_1.0_get_response_body, array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-licenses",
  "version": "1.0",
  "items": [
    [
      "c8aa757a-5318-489f-8134-a2a1a6956a3e",
      "Astra SDS"
    ],
    [
      "0f7cc03d-9afc-4192-af7f-b29ab24f8f2a",
      "Astra Enterprise"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

addons

Name	Type	Required	Description
startDate	string	False	JSON string containing a timestamp indicating when this add-on becomes valid. Defined values are: <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema
endDate	string	False	JSON string containing a timestamp indicating when this add-on is no longer valid. Defined values are: <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema
features	string	False	JSON string containing the list of features associated with this add-on. Defined values are: <ul style="list-style-type: none">• String contents not validated by the schema.
capacity	string	False	JSON string containing the capacity extracted from the add-on. Defined values are: <ul style="list-style-type: none">• String contents not validated by the schema

Name	Type	Required	Description
licenseProtocol	string	False	JSON string containing the license protocol associated with this add-on. Defined values are: <ul style="list-style-type: none"> String contents not validated by the schema

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

license_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-license"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
allocation	string	False	JSON string containing an ID indicating what the license is allocated to. Only present when the license is allocated. For Astra Control Center licenses, this field must be populated with the account ID and must match the account ID specified in the POST URI. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
hostID	string	False	JSON string containing a host identifier that a license is bound to. Only present if the license is host-locked. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
deviceCredentialID	string	False	<p>JSON string containing the identifier of the deviceCredential associated with the Credential API. Only present for Astra Data Store licenses.</p> <p>Defined value are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
isEvaluation	string	True	<p>JSON string indicating whether the license is an evaluation license.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" • "false"
licenseProtocol	string	True	<p>JSON string containing the license protocol extracted from the license.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
licenseText	string	True	<p>JSON string containing a base64 encoded representation of the license JSON as obtained from the NetApp license system. This must be provided in the original byte-level order to allow signature verification.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema

Name	Type	Required	Description
validFromTimestamp	string	True	JSON string containing a timestamp indicating when the license becomes valid. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
validUntilTimestamp	string	True	JSON string containing a timestamp indicating when the license is no longer valid. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
product	string	True	JSON string containing the product string extracted from the license. Defined values are: <ul style="list-style-type: none"> • String contents not validated by the schema
productVersion	string	True	JSON string containing the version string extracted from the license. Defined values are: <ul style="list-style-type: none"> • String contents not validated by the schema
productSN	string	True	JSON string containing the serial number string extracted from the license. Defined values are: <ul style="list-style-type: none"> • String contents not validated by the schema

Name	Type	Required	Description
features	string	True	JSON string containing the package value extracted from the license. Defined values are: <ul style="list-style-type: none"> String contents not validated by the schema
capacity	string	True	JSON string containing the capacity extracted from the license.
capacity2	string	True	JSON string containing the secondary capacity extracted from the license.
addons	array[addons]	False	JSON array of JSON objects containing the list of add-ons from the license. An add-on is a change in license occurring at a potential future date.
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a license

GET /accounts/{account_id}/core/v1/licenses/{license_id}

Returns the stored License API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
license_id	string	path	True	ID of the license collection to list

Response

Status: 200, Returns the stored License API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-license"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
allocation	string	False	JSON string containing an ID indicating what the license is allocated to. Only present when the license is allocated. For Astra Control Center licenses, this field must be populated with the account ID and must match the account ID specified in the POST URI. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
hostID	string	False	JSON string containing a host identifier that a license is bound to. Only present if the license is host-locked. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
deviceCredentialID	string	False	<p>JSON string containing the identifier of the deviceCredential associated with the Credential API. Only present for Astra Data Store licenses.</p> <p>Defined value are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
isEvaluation	string	True	<p>JSON string indicating whether the license is an evaluation license.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" • "false"
licenseProtocol	string	True	<p>JSON string containing the license protocol extracted from the license.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
licenseText	string	True	<p>JSON string containing a base64 encoded representation of the license JSON as obtained from the NetApp license system. This must be provided in the original byte-level order to allow signature verification.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema

Name	Type	Required	Description
validFromTimestamp	string	True	<p>JSON string containing a timestamp indicating when the license becomes valid. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
validUntilTimestamp	string	True	<p>JSON string containing a timestamp indicating when the license is no longer valid. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
product	string	True	<p>JSON string containing the product string extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
productVersion	string	True	<p>JSON string containing the version string extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
productSN	string	True	<p>JSON string containing the serial number string extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema

Name	Type	Required	Description
features	string	True	JSON string containing the package value extracted from the license. Defined values are: <ul style="list-style-type: none"> String contents not validated by the schema
capacity	string	True	JSON string containing the capacity extracted from the license.
capacity2	string	True	JSON string containing the secondary capacity extracted from the license.
addons	array[addons]	False	JSON array of JSON objects containing the list of add-ons from the license. An add-on is a change in license occurring at a potential future date.
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-license",
  "version": "1.0",
  "id": "6db53b32-8417-5d3c-8ef0-552fc602c78f",
  "allocation": "4185d09b-6687-4801-a832-c005a9d94f41",
  "hostID": "99132549-e0c2-4203-9d1e-598628b4ff9b",
  "isEvaluation": "false",
  "licenseProtocol": "ASTRASDS-ENT-SUBS",
  "licenseText": "ewogICAic3RhdHVzUmVzcCI6ewogMTYwNzAwIgp9",
  "validFromTimestamp": "2020-08-06T00:00:00.000000Z",
  "validUntilTimestamp": "2021-08-06T00:00:00.000000Z",
  "product": "Astra Control Center",
  "productVersion": "1.0",
  "productSN": "320000046",
  "features": "ASTRA-ENT-STD",
  "capacity": "4000",
  "capacity2": "0",
  "addons": [
    {
      "startDate": "2020-08-06T00:00:00.000000Z",
      "endDate": "2021-08-06T00:00:00.000000Z",
      "capacity": "4000",
      "licenseProtocol": "ASTRA-ENT-STD",
      "features": "p-nfs, dm-storage-policy-based-pvs-for-k8s, dm-spbm-
based-vvols-for-vms, dm-storage-efficiency, dm-data-at-rest-encryption"
    }
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

addons

Name	Type	Required	Description
startDate	string	False	JSON string containing a timestamp indicating when this add-on becomes valid. Defined values are: <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema
endDate	string	False	JSON string containing a timestamp indicating when this add-on is no longer valid. Defined values are: <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema
features	string	False	JSON string containing the list of features associated with this add-on. Defined values are: <ul style="list-style-type: none">• String contents not validated by the schema.
capacity	string	False	JSON string containing the capacity extracted from the add-on. Defined values are: <ul style="list-style-type: none">• String contents not validated by the schema

Name	Type	Required	Description
licenseProtocol	string	False	JSON string containing the license protocol associated with this add-on. Defined values are: <ul style="list-style-type: none"> String contents not validated by the schema

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a license

PUT /accounts/{account_id}/core/v1/licenses/{license_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Entitlements are recalculated to add or merge the license entitlements visible through the Entitlement API.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
license_id	string	path	True	ID of the license collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Entitlements are recalculated to add or merge the license entitlements visible through the Entitlement API.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-license"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"

Name	Type	Required	Description
id	string	False	<p>Globally unique identifier of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
allocation	string	False	<p>JSON string containing an ID indicating what the license is allocated to. Only present when the license is allocated. For Astra Control Center licenses, this field must be populated with the account ID and must match the account ID specified in the POST URI.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
hostID	string	False	<p>JSON string containing a host identifier that a license is bound to. Only present if the license is host-locked.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
deviceCredentialID	string	False	<p>JSON string containing the identifier of the deviceCredential associated with the Credential API. Only present for Astra Data Store licenses.</p> <p>Defined value are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
isEvaluation	string	False	<p>JSON string indicating whether the license is an evaluation license. Defined values are:</p> <ul style="list-style-type: none"> • "true" • "false"
licenseProtocol	string	False	<p>JSON string containing the license protocol extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
licenseText	string	False	<p>JSON string containing a base64 encoded representation of the license JSON as obtained from the NetApp license system. This must be provided in the original byte-level order to allow signature verification. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema
validFromTimestamp	string	False	<p>JSON string containing a timestamp indicating when the license becomes valid. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
validUntilTimestamp	string	False	<p>JSON string containing a timestamp indicating when the license is no longer valid. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
product	string	False	<p>JSON string containing the product string extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
productVersion	string	False	<p>JSON string containing the version string extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
productSN	string	False	<p>JSON string containing the serial number string extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema
features	string	False	<p>JSON string containing the package value extracted from the license. Defined values are:</p> <ul style="list-style-type: none"> • String contents not validated by the schema

Name	Type	Required	Description
capacity	string	False	JSON string containing the capacity extracted from the license.
capacity2	string	False	JSON string containing the secondary capacity extracted from the license.
addons	array[addons]	False	JSON array of JSON objects containing the list of add-ons from the license. An add-on is a change in license occurring at a potential future date.
metadata	type_astra_metadata_update	False	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-license",
  "version": "1.0",
  "allocation": "4185d09b-6687-4801-a832-c005a9d94f41",
  "licenseText": "ewogICAic3RhdHVzUmVzcCI6ewogMTYwNzAwIgp9"
}
```

Response

Status: 204, Indicates if the license resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```


Definitions

See Definitions

addons

Name	Type	Required	Description
startDate	string	False	JSON string containing a timestamp indicating when this add-on becomes valid. Defined values are: <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema
endDate	string	False	JSON string containing a timestamp indicating when this add-on is no longer valid. Defined values are: <ul style="list-style-type: none">• Conforms to the ISO-8601 Date Time Schema
features	string	False	JSON string containing the list of features associated with this add-on. Defined values are: <ul style="list-style-type: none">• String contents not validated by the schema.
capacity	string	False	JSON string containing the capacity extracted from the add-on. Defined values are: <ul style="list-style-type: none">• String contents not validated by the schema

Name	Type	Required	Description
licenseProtocol	string	False	JSON string containing the license protocol associated with this add-on. Defined values are: <ul style="list-style-type: none"> String contents not validated by the schema

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a license

DELETE /accounts/{account_id}/core/v1/licenses/{license_id}

Removes the specified License API resource. The automatically installed evaluation license cannot be deleted.

Side Effects

- Entitlements are recalculated to remove the license entitlements visible through the Entitlement API. If the automatically installed evaluation license was present on this system before deletion, it is reapplied to the system automatically.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
license_id	string	path	True	ID of the license collection to list

Response

Status: 204, Indicates if the license resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Managed cluster

Managed cluster overview

The Managed Cluster API represents managed Kubernetes clusters.

Create a new managed cluster

POST /accounts/{account_id}/topology/v1/managedClusters

Indicates desired values for the Managed Cluster API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>

Request Body

Indicates desired values for the Managed Cluster API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-managedCluster"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
tridentManagedStateDesired	string	False	JSON string containing a value indicating the desired management state for Trident. Defined values are: <ul style="list-style-type: none">• "managed" - Manage Trident on this cluster• "unmanaged" - Do not manage Trident on this cluster
defaultStorageClass	string	False	JSON string containing a storage class ID that corresponds to the default storage class, as set in Kubernetes. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema If not included, it has not yet been discovered.

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-managedCluster",
  "version": "1.2",
  "id": "6f2fa469-cdae-54be-a451-d0e94a47fa62",
  "defaultStorageClass": "e280ff62-be35-4f31-a31b-a210a1ad1b33",
  "tridentManagedStateDesired": "managed"
}
```

Response

Status: 201, Returns the newly created managedCluster resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> "application/astra-managedCluster"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the cluster. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster's state cannot be determined
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the managed cluster's ability to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.

Name	Type	Required	Description
snapshotSupported	string	False	<p>JSON string containing a value indicating the managed cluster's ability to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to the "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in a "running" state, is not under management, and is not eligible for management. The reason or reasons for this ineligibility are provided in the unready key's value • "unmanaged" - The cluster is in a "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in a "running" state and is in the process of being managed • "managed" - The cluster is in a "running", "failed", or "removed" state and is under management

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The cluster's default storage class supports snapshots • "partial" - The cluster has only storage classes that do not support snapshots • "atRisk" - The cluster's default storage class does not support snapshots
protectionStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedTimestamp	string	True	<p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed".
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra

Name	Type	Required	Description
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why "state" transitioned to "managed" or "unmanaged".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"

Name	Type	Required	Description
inUse	string	True	<p>JSON string containing a value indicating whether the cluster has any managed applications and therefore cannot be deleted.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed, or it is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	True	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	True	<p>JSON string containing the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	True	<p>JSON string containing a value indicating the extended versioning information for the cluster environment.</p> <p>For Kubernetes clusters, this is the full Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class, as set in Kubernetes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not included, it has not yet been discovered.

Name	Type	Required	Description
cloudID	string	True	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
location	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
isMultizonal	string	True	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone

Name	Type	Required	Description
privateRouteID	string	False	<p>JSON string containing the locationID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
apiServiceID	string	False	<p>JSON string containing the UUID from the Kubernetes (k8s) api service object. Used to uniquely identify a cluster.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-managedCluster",
  "version": "1.2",
  "id": "6f2fa469-cdae-54be-a451-d0e94a47fa62",
  "name": "GKE-22",
  "state": "running",
  "stateUnready": [],
  "managedState": "managed",
  "managedStateUnready": [],
  "managedTimestamp": "2020-08-06T12:24:52.256624Z",
  "protectionState": "full",
  "protectionStateDetails": [],
  "tridentVersion": "21.07.2",
  "tridentManagedState": "managed",
  "tridentManagedStateDesired": "managed",
  "tridentManagedStateDetails": [],
  "inUse": "false",
  "clusterType": "kubernetes",
  "clusterVersion": "1.91.1",
  "clusterVersionString": "1.19.1",
  "clusterCreationTimestamp": "2020-08-06T12:24:52.256624Z",
  "namespaces": [
    "kube-system",
    "kube-public",
    "my-app-1"
  ],
  "defaultStorageClass": "e280ff62-be35-4f31-a31b-a210a1ad1b33",
  "cloudID": "548bdc1f-f00e-4a23-a062-83265d224d46",
  "credentialID": "055e365a-2215-40de-aecb-a4070a7e6f1e",
  "location": "europe-west4",
  "isMultizonal": "false",
  "apiServiceID": "6bf33af2-872a-4553-a891-26b510c3edbe",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all managed clusters

GET /accounts/{account_id}/topology/v1/managedClusters

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>id,name,managedState</code>

Name	Type	In	Required	Description
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: managedCluster_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-managedClusters",
  "version": "1.2",
  "items": [
    [
      "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
      "GKE-21",
      "managed"
    ],
    [
      "04dc80fa-d1d8-4850-a49f-3b70d0ec1369",
      "GKE-22",
      "unmanaged"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```


Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

managedCluster_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-managedCluster"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the cluster. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster's state cannot be determined
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the managed cluster's ability to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.

Name	Type	Required	Description
snapshotSupported	string	False	<p>JSON string containing a value indicating the managed cluster's ability to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to the "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in a "running" state, is not under management, and is not eligible for management. The reason or reasons for this ineligibility are provided in the unready key's value • "unmanaged" - The cluster is in a "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in a "running" state and is in the process of being managed • "managed" - The cluster is in a "running", "failed", or "removed" state and is under management

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The cluster's default storage class supports snapshots • "partial" - The cluster has only storage classes that do not support snapshots • "atRisk" - The cluster's default storage class does not support snapshots
protectionStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects that lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedTimestamp	string	True	<p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed".
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra

Name	Type	Required	Description
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why "state" transitioned to "managed" or "unmanaged".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"

Name	Type	Required	Description
inUse	string	True	<p>JSON string containing a value indicating whether the cluster has any managed applications and therefore cannot be deleted.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed, or it is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	True	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	True	<p>JSON string containing the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	True	<p>JSON string containing a value indicating the extended versioning information for the cluster environment. For Kubernetes clusters, this is the full Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class, as set in Kubernetes. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not included, it has not yet been discovered.

Name	Type	Required	Description
cloudID	string	True	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
location	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
isMultizonal	string	True	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone

Name	Type	Required	Description
privateRouteID	string	False	JSON string containing the locationID for private clusters. <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
apiServiceID	string	False	JSON string containing the UUID from the Kubernetes (k8s) api service object. Used to uniquely identify a cluster.
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	

Name	Type	Required	Description
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a managed cluster

GET /accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}

Returns the stored Managed Cluster API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
managedCluster_id	string	path	True	ID of the managedCluster collection to list

Response

Status: 200, Returns the stored Managed Cluster API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-managedCluster"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the cluster. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster's state cannot be determined
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the managed cluster's ability to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.

Name	Type	Required	Description
snapshotSupported	string	False	<p>JSON string containing a value indicating the managed cluster's ability to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to the "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in a "running" state, is not under management, and is not eligible for management. The reason or reasons for this ineligibility are provided in the unready key's value • "unmanaged" - The cluster is in a "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in a "running" state and is in the process of being managed • "managed" - The cluster is in a "running", "failed", or "removed" state and is under management

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The cluster's default storage class supports snapshots • "partial" - The cluster has only storage classes that do not support snapshots • "atRisk" - The cluster's default storage class does not support snapshots
protectionStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedTimestamp	string	True	<p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed".
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra

Name	Type	Required	Description
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why "state" transitioned to "managed" or "unmanaged".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"

Name	Type	Required	Description
inUse	string	True	<p>JSON string containing a value indicating whether the cluster has any managed applications and therefore cannot be deleted.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed, or it is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	True	<p>JSON string containing a value indicating the type of cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	True	<p>JSON string containing the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	True	<p>JSON string containing a value indicating the extended versioning information for the cluster environment.</p> <p>For Kubernetes clusters, this is the full Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class, as set in Kubernetes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not included, it has not yet been discovered.

Name	Type	Required	Description
cloudID	string	True	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
location	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
isMultizonal	string	True	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone

Name	Type	Required	Description
privateRouteID	string	False	<p>JSON string containing the locationID for private clusters.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
apiServiceID	string	False	<p>JSON string containing the UUID from the Kubernetes (k8s) api service object. Used to uniquely identify a cluster.</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-managedCluster",
  "version": "1.2",
  "id": "6f2fa469-cdae-54be-a451-d0e94a47fa62",
  "name": "GKE-22",
  "state": "running",
  "stateUnready": [],
  "managedState": "managed",
  "managedStateUnready": [],
  "managedTimestamp": "2020-08-06T12:24:52.256624Z",
  "protectionState": "full",
  "protectionStateDetails": [],
  "tridentVersion": "21.07.2",
  "tridentManagedState": "managed",
  "tridentManagedStateDesired": "managed",
  "tridentManagedStateDetails": [],
  "inUse": "true",
  "clusterType": "kubernetes",
  "clusterVersion": "1.91.1",
  "clusterVersionString": "1.19.1",
  "clusterCreationTimestamp": "2020-08-06T12:24:52.256624Z",
  "namespaces": [
    "kube-system",
    "kube-public",
    "my-app-1"
  ],
  "defaultStorageClass": "e280ff62-be35-4f31-a31b-a210a1ad1b33",
  "cloudID": "548bdc1f-f00e-4a23-a062-83265d224d46",
  "credentialID": "055e365a-2215-40de-aecb-a4070a7e6f1e",
  "location": "europe-west4",
  "isMultizonal": "false",
  "apiServiceID": "6bf33af2-872a-4553-a891-26b510c3edbe",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a managed cluster

PUT /accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- When defaultStorageClass is changed, the Kubernetes default storage class will be updated.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the managedCluster collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- When defaultStorageClass is changed, the Kubernetes default storage class will be updated.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-managedCluster"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1" • "1.2"

Name	Type	Required	Description
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	False	JSON string containing a name for the cluster. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled for discovery • "discovering" - The cluster is in the process of being discovered • "provisioning" - The cluster is in the process of being provisioned • "running" - The cluster is running normally • "failed" - The cluster is in a permanent failure state • "removed" - The cluster is not currently accessible • "unknown" - The cluster's state cannot be determined
restoreTargetSupported	string	False	<p>JSON string containing a value indicating the managed cluster's ability to be a <i>target</i> of application data management operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible target for app data management operations. • "false" - Cluster is <i>not</i> an eligible target for app data management operations.

Name	Type	Required	Description
snapshotSupported	string	False	<p>JSON string containing a value indicating the managed cluster's ability to perform application data management backup-like operations. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Cluster is an eligible to perform app data management operations. • "false" - Cluster is <i>not</i> eligible to perform app data management operations.
stateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why the cluster is unable to transition to "running" state, when there are issues while in "running" state, or why it has transitioned to the "failed" or "removed" state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	False	<p>JSON string containing a value indicating the management state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The cluster is scheduled to be discovered or added • "ineligible" - The cluster is in a "running" state, is not under management, and is not eligible for management. The reason or reasons for this ineligibility are provided in the unready key's value • "unmanaged" - The cluster is in a "running" or "failed" state, is not under management, and is eligible for management • "managing" - The cluster is in a "running" state and is in the process of being managed • "managed" - The cluster is in a "running", "failed", or "removed" state and is under management

Name	Type	Required	Description
protectionState	string	False	<p>JSON string containing a value indicating the protection state of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "full" - The cluster's default storage class supports snapshots • "partial" - The cluster has only storage classes that do not support snapshots • "atRisk" - The cluster's default storage class does not support snapshots
protectionStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about the current protection state, including why the current state was reached.</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum Items: 0
managedStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why the cluster is ineligible to be managed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was brought under management. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This key is only returned when a cluster has a managedState of "managed".
tridentVersion	string	False	<p>JSON string containing the version of Trident installed on the cluster. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Software Version Schema
tridentManagedState	string	False	<p>JSON string containing one of a set of enumerated values indicating the management state of Trident on this cluster. Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Trident instance on the cluster is managed by Astra • "unmanaged" - Trident instance on the cluster is not managed by Astra

Name	Type	Required	Description
tridentManagedStateDesired	string	False	<p>JSON string containing a value indicating the desired management state for Trident.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "managed" - Manage Trident on this cluster • "unmanaged" - Do not manage Trident on this cluster
tridentManagedStateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about why "state" transitioned to "managed" or "unmanaged".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
tridentManagedStateAllowed	array[string]	False	<p>States that can be requested in a given tridentManagedState.</p> <p>The following states can be requested in each defined state:</p> <ul style="list-style-type: none"> • "managed": "managed" • "unmanaged": "unmanaged"

Name	Type	Required	Description
inUse	string	False	<p>JSON string containing a value indicating whether the cluster has any managed applications and therefore cannot be deleted.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "false" - The cluster is not managed, or it is managed but has no managed applications associated with it • "true" - The cluster is managed and has managed applications associated with it
accHost	string	False	<p>JSON string that indicates that this cluster hosts the instance of Astra Control Center that is currently being accessed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - This cluster is hosting the instance of Astra Control Center that is currently being accessed.

Name	Type	Required	Description
clusterType	string	False	<p>JSON string containing a value indicating the type of cluster. Defined values are:</p> <ul style="list-style-type: none"> • "gke" - Kubernetes hosted on Google Kubernetes Engine • "aks" - Kubernetes hosted on Microsoft Azure Kubernetes Service • "eks" - Kubernetes hosted on Amazon Elastic Kubernetes Service • "rke" - The cluster is of type Rancher • "tanzu" -The cluster is of type Tanzu Kubernetes Grid • "openshift" - The cluster is of type OpenShift • "kubernetes" - The cluster is generic Kubernetes
clusterVersion	string	False	<p>JSON string containing the semantic versioning representation of the cluster environment. For Kubernetes clusters, this is the Kubernetes version. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
clusterVersionString	string	False	<p>JSON string containing a value indicating the extended versioning information for the cluster environment.</p> <p>For Kubernetes clusters, this is the full Kubernetes version.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
clusterCreationTimestamp	string	False	<p>JSON string containing the timestamp indicating when the cluster was originally created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
namespaces	array[string]	False	<p>JSON array of JSON strings, each indicating a namespace within the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 253
defaultStorageClass	string	False	<p>JSON string containing a storage class ID that corresponds to the default storage class, as set in Kubernetes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema <p>If not included, it has not yet been discovered.</p>

Name	Type	Required	Description
cloudID	string	False	<p>JSON string containing a value indicating the ID of the cloud the cluster is running on.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
credentialID	string	False	<p>JSON string containing a value indicating the ID of the credential that contains the kubeconfig file for the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
location	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating the cloud-specific location of the cluster.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
isMultizonal	string	False	<p>JSON string containing a value provided by the cloud the cluster is running on, indicating whether the cluster spans two or more availability zones.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The cluster spans two or more availability zones • "false" - The cluster is wholly located within a single availability zone

Name	Type	Required	Description
privateRouteID	string	False	JSON string containing the locationID for private clusters. <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
apiServiceID	string	False	JSON string containing the UUID from the Kubernetes (k8s) api service object. Used to uniquely identify a cluster.
metadata	type_astra_metadata_update	False	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-managedCluster",
  "version": "1.2",
  "defaultStorageClass": "0b146cda-7fc1-4f32-804c-8130a38a7e1c"
}
```

Response

Status: 204, Indicates if the managedCluster resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```


Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a managed cluster

DELETE /accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}

Removes the specified Managed Cluster API resource.

Side Effects

- Internal data structures are cleaned up.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the managedCluster collection to list

Response

Status: 204, Indicates if the managedCluster resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Metrics

Metrics overview

The Metrics API represents metrics associated with a given account.

Retrieve all metrics for an account

GET /accounts/{account_id}/metrics

Returns all metrics for the account

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>

Response

Status: 200, Returns a OpenMetrics text document containing all metrics for the account.

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Namespace

Namespace overview

The Namespace API provides read-only access to namespace resources in order to describe namespaces associated with a given cluster.

List the namespaces for a cloud

GET

/accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}/namespaces

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
cloud_id	string	path	True	ID of the containing cloud resource
cluster_id	string	path	True	ID of the containing cluster resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: id,name,kubernetesLabels
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: namespace_1.1_get_response_body, array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-namespaces",
  "version": "1.1",
  "items": [
    [
      "7d451d2f-196e-4234-ae9-7e2376047e63",
      "kube-system",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ],
    [
      "66b0873b-214f-4ac7-89d8-922432f941eb",
      "jenkins",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

namespace_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-namespace"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.
name	string	True	JSON string containing a value indicating the name of the namespace. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 255

Name	Type	Required	Description
namespaceState	string	True	<p>JSON string containing a value indicating the state of the namespace. Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The namespace has been found in the cluster • "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace
namespaceStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c". If no details are available, this array will be empty. Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0
kubernetesLabels	array[type_astra_label]	False	<p>JSON array of JSON objects, each containing a Kubernetes label associated with the namespace. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Kubernetes Label Array Schema

Name	Type	Required	Description
clusterID	string	True	<p>JSON string containing a globally unique identifier of the cluster that the namespace is contained in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
systemType	string	False	<p>JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only).</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system" • "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring" • "openshift" - An OpenShift system namespace, for example, "openshift-monitoring" • "rke" - A Rancher namespace, for example, "cattle-logging" • "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system"

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a namespace for a cloud

GET

/accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}/namespaces/{namespace_id}

Returns the stored Namespace API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
cloud_id	string	path	True	ID of the containing cloud resource
cluster_id	string	path	True	ID of the containing cluster resource
namespace_id	string	path	True	ID of the namespace collection to list

Response

Status: 200, Returns the stored Namespace API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-namespace"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.

Name	Type	Required	Description
name	string	True	<p>JSON string containing a value indicating the name of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
namespaceState	string	True	<p>JSON string containing a value indicating the state of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The namespace has been found in the cluster • "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace
namespaceStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c".</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0
kubernetesLabels	array[type_astra_label]	False	<p>JSON array of JSON objects, each containing a Kubernetes label associated with the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Kubernetes Label Array Schema

Name	Type	Required	Description
clusterID	string	True	<p>JSON string containing a globally unique identifier of the cluster that the namespace is contained in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
systemType	string	False	<p>JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only).</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system" • "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring" • "openshift" - An OpenShift system namespace, for example, "openshift-monitoring" • "rke" - A Rancher namespace, for example, "cattle-logging" • "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system"

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Metadata Schema

Example response

A large, empty rectangular box with a thin, dashed border, occupying most of the page. It is intended for an example response.


```

{
  "type": "application/astra-namespace",
  "version": "1.1",
  "id": "2de811a6-ce8f-512c-9c3a-9585ca66de22",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/namespaces/7d451d2f-196e-4234-ae9-7e2376047e63",
      "type": "application/vnd.netapp.astra.namespace"
    },
    {
      "rel": "collection",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/e0490197-872e-4de8-9287-b04a938e801f/clusters/0f284377-e5dc-4dcd-bacd-3197f2b8a347/namespaces",
      "type": "application/vnd.netapp.astra.namespaces"
    }
  ],
  "name": "kube-system",
  "namespaceState": "discovered",
  "namespaceStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/9",
      "title": "Namespace Discovered",
      "detail": "The namespace was discovered in the indicated managed cluster"
    }
  ],
  "kubernetesLabels": [
    {
      "name": "app.kubernetes.io/environment",
      "value": "dev"
    }
  ],
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "systemType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the namespaces for a cluster

GET /accounts/{account_id}/topology/v1/clusters/{cluster_id}/namespaces

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code>
cluster_id	string	path	True	ID of the containing cluster resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> • example: id,name,kubernetesLabels
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: namespace_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-namespaces",
  "version": "1.1",
  "items": [
    [
      "7d451d2f-196e-4234-ae9-7e2376047e63",
      "kube-system",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ],
    [
      "66b0873b-214f-4ac7-89d8-922432f941eb",
      "jenkins",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

namespace_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-namespace"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.
name	string	True	JSON string containing a value indicating the name of the namespace. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 255

Name	Type	Required	Description
namespaceState	string	True	<p>JSON string containing a value indicating the state of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The namespace has been found in the cluster • "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace
namespaceStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c".</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0
kubernetesLabels	array[type_astra_label]	False	<p>JSON array of JSON objects, each containing a Kubernetes label associated with the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Kubernetes Label Array Schema

Name	Type	Required	Description
clusterID	string	True	<p>JSON string containing a globally unique identifier of the cluster that the namespace is contained in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
systemType	string	False	<p>JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only).</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system" • "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring" • "openshift" - An OpenShift system namespace, for example, "openshift-monitoring" • "rke" - A Rancher namespace, for example, "cattle-logging" • "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system"

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a namespace for a cluster

GET

```
/accounts/{account_id}/topology/v1/clusters/{cluster_id}/namespaces/{namespace_id}
```

Returns the stored Namespace API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
cluster_id	string	path	True	ID of the containing cluster resource
namespace_id	string	path	True	ID of the namespace collection to list

Response

Status: 200, Returns the stored Namespace API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-namespace"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.

Name	Type	Required	Description
name	string	True	<p>JSON string containing a value indicating the name of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
namespaceState	string	True	<p>JSON string containing a value indicating the state of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The namespace has been found in the cluster • "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace
namespaceStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c".</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0
kubernetesLabels	array[type_astra_label]	False	<p>JSON array of JSON objects, each containing a Kubernetes label associated with the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Kubernetes Label Array Schema

Name	Type	Required	Description
clusterID	string	True	<p>JSON string containing a globally unique identifier of the cluster that the namespace is contained in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
systemType	string	False	<p>JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only).</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system" • "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring" • "openshift" - An OpenShift system namespace, for example, "openshift-monitoring" • "rke" - A Rancher namespace, for example, "cattle-logging" • "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system"

Name	Type	Required	Description
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• Conforms to the Astra Metadata Schema

Example response

A large, empty rectangular box with a thin, dashed border, occupying most of the page. It is intended for an example response.

```

{
  "type": "application/astra-namespace",
  "version": "1.1",
  "id": "2de811a6-ce8f-512c-9c3a-9585ca66de22",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/namespaces/7d451d2f-196e-4234-ae9-7e2376047e63",
      "type": "application/vnd.netapp.astra.namespace"
    },
    {
      "rel": "collection",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/e0490197-872e-4de8-9287-b04a938e801f/clusters/0f284377-e5dc-4dcd-bacd-3197f2b8a347/namespaces",
      "type": "application/vnd.netapp.astra.namespaces"
    }
  ],
  "name": "kube-system",
  "namespaceState": "discovered",
  "namespaceStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/9",
      "title": "Namespace Discovered",
      "detail": "The namespace was discovered in the indicated managed cluster"
    }
  ],
  "kubernetesLabels": [
    {
      "name": "app.kubernetes.io/environment",
      "value": "dev"
    }
  ],
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "systemType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List all namespaces

GET /accounts/{account_id}/topology/v1/namespaces

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code>

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: id,name,kubernetesLabels
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: namespace_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-namespaces",
  "version": "1.1",
  "items": [
    [
      "7d451d2f-196e-4234-ae9-7e2376047e63",
      "kube-system",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ],
    [
      "66b0873b-214f-4ac7-89d8-922432f941eb",
      "jenkins",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```


Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

namespace_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-namespace"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.
name	string	True	JSON string containing a value indicating the name of the namespace. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 255

Name	Type	Required	Description
namespaceState	string	True	<p>JSON string containing a value indicating the state of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The namespace has been found in the cluster • "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace
namespaceStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c".</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0
kubernetesLabels	array[type_astra_label]	False	<p>JSON array of JSON objects, each containing a Kubernetes label associated with the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Kubernetes Label Array Schema

Name	Type	Required	Description
clusterID	string	True	<p>JSON string containing a globally unique identifier of the cluster that the namespace is contained in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
systemType	string	False	<p>JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only).</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system" • "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring" • "openshift" - An OpenShift system namespace, for example, "openshift-monitoring" • "rke" - A Rancher namespace, for example, "cattle-logging" • "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system"

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a namespace

GET /accounts/{account_id}/topology/v1/namespaces/{namespace_id}

Returns the stored Namespace API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
namespace_id	string	path	True	ID of the namespace collection to list

Response

Status: 200, Returns the stored Namespace API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-namespace"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.

Name	Type	Required	Description
name	string	True	<p>JSON string containing a value indicating the name of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
namespaceState	string	True	<p>JSON string containing a value indicating the state of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The namespace has been found in the cluster • "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace
namespaceStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c".</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0
kubernetesLabels	array[type_astra_label]	False	<p>JSON array of JSON objects, each containing a Kubernetes label associated with the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Kubernetes Label Array Schema

Name	Type	Required	Description
clusterID	string	True	<p>JSON string containing a globally unique identifier of the cluster that the namespace is contained in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
systemType	string	False	<p>JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only).</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system" • "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring" • "openshift" - An OpenShift system namespace, for example, "openshift-monitoring" • "rke" - A Rancher namespace, for example, "cattle-logging" • "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system"

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Metadata Schema

Example response

A large, empty rectangular box with a thin, dashed border, occupying most of the page. It is intended for an example response.

```

{
  "type": "application/astra-namespace",
  "version": "1.1",
  "id": "2de811a6-ce8f-512c-9c3a-9585ca66de22",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/namespaces/7d451d2f-196e-4234-ae9-7e2376047e63",
      "type": "application/vnd.netapp.astra.namespace"
    },
    {
      "rel": "collection",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/e0490197-872e-4de8-9287-b04a938e801f/clusters/0f284377-e5dc-4dcd-bacd-3197f2b8a347/namespaces",
      "type": "application/vnd.netapp.astra.namespaces"
    }
  ],
  "name": "kube-system",
  "namespaceState": "discovered",
  "namespaceStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/9",
      "title": "Namespace Discovered",
      "detail": "The namespace was discovered in the indicated managed cluster"
    }
  ],
  "kubernetesLabels": [
    {
      "name": "app.kubernetes.io/environment",
      "value": "dev"
    }
  ],
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "systemType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the namespaces for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/namespaces

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code>
managedCluster_id	string	path	True	ID of the containing managedCluster resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: id,name,kubernetesLabels
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: namespace_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-namespaces",
  "version": "1.1",
  "items": [
    [
      "7d451d2f-196e-4234-ae9-7e2376047e63",
      "kube-system",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ],
    [
      "66b0873b-214f-4ac7-89d8-922432f941eb",
      "jenkins",
      [
        {
          "name": "app.kubernetes.io/environment",
          "value": "dev"
        }
      ]
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

namespace_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-namespace"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.
name	string	True	JSON string containing a value indicating the name of the namespace. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 255

Name	Type	Required	Description
namespaceState	string	True	<p>JSON string containing a value indicating the state of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The namespace has been found in the cluster • "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace
namespaceStateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c".</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0
kubernetesLabels	array[type_astra_label]	False	<p>JSON array of JSON objects, each containing a Kubernetes label associated with the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Kubernetes Label Array Schema

Name	Type	Required	Description
clusterID	string	True	<p>JSON string containing a globally unique identifier of the cluster that the namespace is contained in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
systemType	string	False	<p>JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only).</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system" • "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring" • "openshift" - An OpenShift system namespace, for example, "openshift-monitoring" • "rke" - A Rancher namespace, for example, "cattle-logging" • "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system"

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a namespace for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/namespaces/{namespace_id}

Returns the stored Namespace API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
managedCluster_id	string	path	True	ID of the containing managedCluster resource
namespace_id	string	path	True	ID of the namespace collection to list

Response

Status: 200, Returns the stored Namespace API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-namespace"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
links	array[type_astra_link]	True	Links describing supported operations against the resource.

Name	Type	Required	Description
name	string	True	<p>JSON string containing a value indicating the name of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
namespaceState	string	True	<p>JSON string containing a value indicating the state of the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The namespace has been found in the cluster • "removed" - The namespace has been deleted from the cluster, or the cluster is not managed but there might be resources referring to the namespace
namespaceStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about why "state" transitioned into "state a", "state b", or "state c".</p> <p>If no details are available, this array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum items: 0
kubernetesLabels	array[type_astra_label]	False	<p>JSON array of JSON objects, each containing a Kubernetes label associated with the namespace.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Kubernetes Label Array Schema

Name	Type	Required	Description
clusterID	string	True	<p>JSON string containing a globally unique identifier of the cluster that the namespace is contained in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
systemType	string	False	<p>JSON string that denotes that the namespace is a type of system namespace. This field identifies what type of system namespace, if any, the namespace is (version 1.1 only).</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "kubernetes" - A generic Kubernetes (K8s) system namespace, for example, "kube-system" • "netapp" - A NetApp system namespace, for example, "trident" or "netapp-monitoring" • "openshift" - An OpenShift system namespace, for example, "openshift-monitoring" • "rke" - A Rancher namespace, for example, "cattle-logging" • "other" - Common system namespaces that don't necessarily fit elsewhere, for example, "ingress-nginx", "tekton-system"

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Metadata Schema

Example response

A large, empty rectangular box with a thin, dashed border, occupying most of the page. It is intended for an example response.

```

{
  "type": "application/astra-namespace",
  "version": "1.1",
  "id": "2de811a6-ce8f-512c-9c3a-9585ca66de22",
  "links": [
    {
      "rel": "canonical",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/namespaces/7d451d2f-196e-4234-ae9-7e2376047e63",
      "type": "application/vnd.netapp.astra.namespace"
    },
    {
      "rel": "collection",
      "href": "/accounts/0b311ae7-d89a-4a11-a52c-1349ca090415/topology/v1/clouds/e0490197-872e-4de8-9287-b04a938e801f/clusters/0f284377-e5dc-4dcd-bacd-3197f2b8a347/namespaces",
      "type": "application/vnd.netapp.astra.namespaces"
    }
  ],
  "name": "kube-system",
  "namespaceState": "discovered",
  "namespaceStateDetails": [
    {
      "type": "https://astra.netapp.io/stateDetails/9",
      "title": "Namespace Discovered",
      "detail": "The namespace was discovered in the indicated managed cluster"
    }
  ],
  "kubernetesLabels": [
    {
      "name": "app.kubernetes.io/environment",
      "value": "dev"
    }
  ],
  "clusterID": "0f284377-e5dc-4dcd-bacd-3197f2b8a347",
  "systemType": "kubernetes",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

targetSchema

accept-post

accept-put

hints

Name	Type	Required	Description
status	string	False	
allow	array[string]	False	
accept-post	accept-post	False	
permissions	array[string]	False	
accept-put	accept-put	False	

type_astra_link

Name	Type	Required	Description
rel	string	True	
href	string	True	
type	string	False	
targetSchema	targetSchema	False	
title	string	False	
hints	hints	False	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Notification

Notification overview

The Notification API provides per-user access to events with a notification destination.

List all notifications

GET /accounts/{account_id}/core/v1/notifications

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code>

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> • example: id,summary
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p> <ul style="list-style-type: none"> • example: 4

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	<p>Indicates if the total number of resources should be returned in the metadata object.</p> <p>URL examples: "count=true"</p> <p>OpenAPI examples: "true"</p> <ul style="list-style-type: none"> • example: true
continue		query	False	<p>Indicates the token to resume listing from.</p> <p>URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue></p> <p>OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue>&lt;/continue&gt;"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: notification_1.3_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-notifications",
  "version": "1.3",
  "items": [
    [
      "4f8273ee-883d-47f0-a512-9e27b6285f20",
      "Discovering Applications in Cluster"
    ],
    [
      "1cdd26dc-5eb0-4cf4-a0c1-39a9b83720e1",
      "Application Discovered"
    ],
    [
      "275a8c6f-ebf6-4d10-b671-77d1b8c7c0a6",
      "Application Discovery Failed"
    ],
    [
      "4325f971-ca9c-4a52-bc9a-da6ec62e6bfe",
      "Application Discovered"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

data

JSON object containing additional event-specific information.

Name	Type	Required	Description
ttl	number	False	JSON number indicating the number of seconds (since the eventTime) that the event will be retained. This field is only included when an event is automatically deleted after the specified number of seconds. When deleted, if the event has a notification destination, all associated notifications are also deleted. When deleted, if the event has a banner destination, the banner is also removed. The absence of this field (or a value of "0") means that an event will not be automatically deleted.
isAcknowledgeable	string	False	JSON string indicating whether the banner is dismissible. Defined values are: <ul style="list-style-type: none">• "true" - The banner is dismissible• "false" - The banner is not dismissible

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

notification_1.3_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-notification"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"• "1.3"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a dot notation (.) hierarchical name for the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 127 • Defined regex is: "[a-z](\.[a-z])+\$"
sequenceCount	number	True	<p>JSON number containing a sequence count.</p> <p>The number is incremented by the system each time a new event is received.</p>
summary	string	True	<p>JSON string containing the short-form (less than 40 characters) summary of the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 79
eventTime	string	True	<p>JSON string containing a timestamp that indicates when an event occurred.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
source	string	True	<p>JSON string containing the lowercase name of the service generating an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 19 • Defined regex is: "[a-z]*"

Name	Type	Required	Description
resourceID	string	True	<p>JSON string containing the resource ID associated with an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
additionalResourceIDs	array[string]	True	<p>JSON array of JSON strings, each containing a resource ID of an additional resource associated with the event. Although the "resourceID" field contains the primary resource associated with this event, this field contains any number of additional resource IDs to be associated with the same events.</p> <p>If no additional resources are associated with the event, the array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
resourceType	string	True	<p>JSON string containing the media type of the resource associated with an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 4 • Maximum length: 79 • Defined regex is: <code>"^application/astra-[a-zA-Z]+\$"</code>

Name	Type	Required	Description
correlationID	string	True	<p>JSON string containing a UUIDv4 correlation ID that allows related events to be grouped together.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
severity	string	True	<p>JSON string containing one of the following values that indicate the severity of an event. Defined values are:</p> <ul style="list-style-type: none"> • "cleared" - Indicates that a previously reported event describing a condition is no longer active. An event with severity "cleared" will use the same summary and correlation ID to allow it to be matched up. • "indeterminate" - Indicates that the severity cannot be determined. • "informational" - Indicates a change in state that is both expected and normal (not defined in X.733). • "warning" - Indicates the detection of a potential or impending service affecting fault, before any significant effects have been felt. • "critical" - Indicates that a service affecting condition has occurred and immediate corrective action is required. Definitions for "cleared", "indeterminate", "warning" and "critical" are based on definitions in clause 8.1.2.3 of CCITT X.733.

Name	Type	Required	Description
class	string	True	<p>JSON string containing one of the following values that indicate the class of the event. Defined values are:</p> <ul style="list-style-type: none"> • "system" - The event is related to an internal event or request. • "user" - The event is related to a user-initiated event or request. • "security" - The event is related to a security issue.
description	string	True	<p>JSON string containing a long-form descriptive text about the event. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 1023
descriptionURL	string	False	<p>JSON string containing the URL that enables and links a button in the banner to external documentation. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095

Name	Type	Required	Description
correctiveAction	string	False	<p>JSON string containing a long-form descriptive text about what corrective action should be taken in response to the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 1023
correctiveActionURL	string	False	<p>JSON string containing the URL that links a button in the banner to a page within the UI to fix the issue.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
visibility	array[string]	False	<p>JSON array of JSON strings, each indicating an RBAC role permitted to view the event. Roles are OR-defined together. Optional.</p> <p>If omitted, a user with any RBAC role can view the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
destinations	array[string]	False	<p>JSON array of JSON strings, each indicating an additional destination for the event. These allow a service to provide hints about where an event must be routed in addition to the Activity service's activity log. Optional.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "notification" - The event is marked as a notification, and will be accessible through the notifications API endpoint. • "banner" - The event is marked as a banner. • "support" - The event is marked as a support-related event.
resourceURI	string	False	<p>JSON string containing the URI associated with the event. Only included for events related to API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
resourceCollectionURL	array[string]	False	<p>JSON array of JSON strings, each indicating the fully-expanded access URL of the resource associated with the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 1023

Name	Type	Required	Description
resourceMethod	string	False	<p>JSON string containing the HTTP method invoked. Included only for events related to API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "options" - OPTIONS API operation • "post" - POST API operation • "get" - GET API operation • "put" - PUT API operation • "delete" - DELETE API operation
resourceMethodResult	string	False	<p>JSON string containing the result of the HTTP method invoked. Only included for events related to the API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[1-5][0-9]{2}\$"</code>
userID	string	False	<p>JSON string containing the user ID associated with an event. Only included for events associated with the user-initiated actions.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
accountID	string	False	JSON string containing the account ID associated with an event. Only included for events associated with an account. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema
data	data	False	JSON object containing additional event-specific information.
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

Retrieve a notification

GET /accounts/{account_id}/core/v1/notifications/{notification_id}

Returns the stored Notification API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
notification_id	string	path	True	ID of the notification collection to list

Response

Status: 200, Returns the stored Notification API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-notification"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1" "1.2" "1.3"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a dot notation (.) hierarchical name for the event. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 127 • Defined regex is: <code>"^[a-z](\.[a-z])+\$"</code>
sequenceCount	number	True	JSON number containing a sequence count. The number is incremented by the system each time a new event is received.
summary	string	True	JSON string containing the short-form (less than 40 characters) summary of the event. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 79
eventTime	string	True	JSON string containing a timestamp that indicates when an event occurred. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
source	string	True	<p>JSON string containing the lowercase name of the service generating an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 19 • Defined regex is: <code>"^[a-z-]*\$"</code>
resourceID	string	True	<p>JSON string containing the resource ID associated with an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
additionalResourceIDs	array[string]	True	<p>JSON array of JSON strings, each containing a resource ID of an additional resource associated with the event. Although the "resourceID" field contains the primary resource associated with this event, this field contains any number of additional resource IDs to be associated with the same events.</p> <p>If no additional resources are associated with the event, the array will be empty.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
resourceType	string	True	<p>JSON string containing the media type of the resource associated with an event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 4 • Maximum length: 79 • Defined regex is: <code>"^application/astra-([a-zA-Z])+\$"</code>
correlationID	string	True	<p>JSON string containing a UUIDv4 correlation ID that allows related events to be grouped together.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
severity	string	True	<p>JSON string containing one of the following values that indicate the severity of an event. Defined values are:</p> <ul style="list-style-type: none"> • "cleared" - Indicates that a previously reported event describing a condition is no longer active. An event with severity "cleared" will use the same summary and correlation ID to allow it to be matched up. • "indeterminate" - Indicates that the severity cannot be determined. • "informational" - Indicates a change in state that is both expected and normal (not defined in X.733). • "warning" - Indicates the detection of a potential or impending service affecting fault, before any significant effects have been felt. • "critical" - Indicates that a service affecting condition has occurred and immediate corrective action is required. Definitions for "cleared", "indeterminate", "warning" and "critical" are based on definitions in clause 8.1.2.3 of CCITT X.733.

Name	Type	Required	Description
class	string	True	<p>JSON string containing one of the following values that indicate the class of the event. Defined values are:</p> <ul style="list-style-type: none"> • "system" - The event is related to an internal event or request. • "user" - The event is related to a user-initiated event or request. • "security" - The event is related to a security issue.
description	string	True	<p>JSON string containing a long-form descriptive text about the event. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 1023
descriptionURL	string	False	<p>JSON string containing the URL that enables and links a button in the banner to external documentation. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
correctiveAction	string	False	<p>JSON string containing a long-form descriptive text about what corrective action should be taken in response to the event. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 1023

Name	Type	Required	Description
correctiveActionURL	string	False	<p>JSON string containing the URL that links a button in the banner to a page within the UI to fix the issue.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
visibility	array[string]	False	<p>JSON array of JSON strings, each indicating an RBAC role permitted to view the event. Roles are OR-defined together. Optional.</p> <p>If omitted, a user with any RBAC role can view the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
destinations	array[string]	False	<p>JSON array of JSON strings, each indicating an additional destination for the event. These allow a service to provide hints about where an event must be routed in addition to the Activity service's activity log. Optional.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "notification" - The event is marked as a notification, and will be accessible through the notifications API endpoint. • "banner" - The event is marked as a banner. • "support" - The event is marked as a support-related event.

Name	Type	Required	Description
resourceURI	string	False	<p>JSON string containing the URI associated with the event. Only included for events related to API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
resourceCollectionURL	array[string]	False	<p>JSON array of JSON strings, each indicating the fully-expanded access URL of the resource associated with the event.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 1023
resourceMethod	string	False	<p>JSON string containing the HTTP method invoked. Included only for events related to API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "options" - OPTIONS API operation • "post" - POST API operation • "get" - GET API operation • "put" - PUT API operation • "delete" - DELETE API operation

Name	Type	Required	Description
resourceMethodResult	string	False	<p>JSON string containing the result of the HTTP method invoked. Only included for events related to the API operations.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[1-5][0-9]{2}\$"</code>
userID	string	False	<p>JSON string containing the user ID associated with an event. Only included for events associated with the user-initiated actions.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
accountID	string	False	<p>JSON string containing the account ID associated with an event. Only included for events associated with an account.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
data	data	False	<p>JSON object containing additional event-specific information.</p>
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-notification",
  "version": "1.3",
  "id": "03c645d6-75f0-59b0-95f2-862ae344ea27",
  "name": "astra.app.discovery.failed",
  "sequenceCount": 48923,
  "summary": "Application Discovery Failed",
  "eventTime": "2020-08-06T12:24:51.846543Z",
  "source": "composite-compute",
  "resourceID": "f670bf11-8850-44bd-b330-815af6186a06",
  "additionalResourceIDs": [
    "84dfef99-b7b2-46d2-9021-0a1a9a5df1d6",
    "abb32003-07b9-49b1-9938-1cf6d2f33566"
  ],
  "resourceType": "application/astra-app",
  "correlationID": "3c603442-cfca-4af9-9f1b-40dde5c7a806",
  "severity": "warning",
  "class": "user",
  "description": "Discovering the application 'mysql' was unsuccessful.
K8s error 442. Application marked in state 'error'.",
  "destinations": [
    "notification"
  ],
  "resourceURI": "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/managedClusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/apps/f670bf11-8850-44bd-b330-815af6186a06",
  "resourceCollectionURL": [
    "https://www.astra.io/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/f8b58091-4b9c-4c64-9b40-
018dbaf7c5de/apps/f670bf11-8850-44bd-b330-815af6186a06",
    "https://www.astra.io/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/923708f8-0435-45b5-8c00-
fbdef3ffaf25/apps/f670bf11-8850-44bd-b330-815af6186a06"
  ],
  "userID": "abda967f-cd2c-4237-908e-99266648c553",
  "accountID": "f126d214-bccf-4558-86b4-2137a41e734f",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  }
}
```

```
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

data

JSON object containing additional event-specific information.

Name	Type	Required	Description
ttl	number	False	JSON number indicating the number of seconds (since the eventTime) that the event will be retained. This field is only included when an event is automatically deleted after the specified number of seconds. When deleted, if the event has a notification destination, all associated notifications are also deleted. When deleted, if the event has a banner destination, the banner is also removed. The absence of this field (or a value of "0") means that an event will not be automatically deleted.
isAcknowledgeable	string	False	JSON string indicating whether the banner is dismissible. Defined values are: <ul style="list-style-type: none">• "true" - The banner is dismissible• "false" - The banner is not dismissible

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Package

Package overview

The Package API represents installable software packages.

Create a new package

POST /accounts/{account_id}/core/v1/packages

Indicates desired values for the Package API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: {{.Account}}

Request Body

Indicates desired values for the Package API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-package"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
packageName	string	True	JSON string containing the package name. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 31 Example values are: <ul style="list-style-type: none"> "acc" "acs" "trident"
packageVersion	string	True	JSON string containing the SemVer of the package. Defined values are: <ul style="list-style-type: none"> Conforms to the SemVer Schema
packageType	string	True	JSON string containing the package type, indicating whether this is a full installation package or a patch. Defined values are: <ul style="list-style-type: none"> "install" "patch"
bundleName	array[string]	False	JSON array of JSON strings containing the name of the bundle that the package is contained in.

Name	Type	Required	Description
severityLevel	string	True	<p>JSON string describing the severity level of this patch or installation. Defined values are:</p> <ul style="list-style-type: none"> • "recommended" - Installation is recommended - Default value • "critical" - Installation is strongly recommended to address critical bug fixes and/or security patches
images	array[images]	False	JSON array of JSON objects, each containing a Docker image that is part of the package.
artifacts	array[artifacts]	False	JSON array of JSON objects describing the additional artifacts (binaries and others) associated with this package.
files	array[files]	False	JSON array of JSON objects, each representing a non-image artifact associated with this package.
upgradableVersions	upgradableVersions	False	JSON object containing the minimum and maximum versions that can be upgraded to the package version.
dependencies	array[dependencies]	False	JSON array of JSON objects describing what minimum version of a given dependency is required for this package to be installed

Name	Type	Required	Description
metadata	type_astra_metadata	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example request

```
{
  "type": "application/astra-package",
  "version": "1.0",
  "packageName": "acc",
  "packageVersion": "22.09.1",
  "packageType": "patch",
  "severityLevel": "recommended",
  "images": [
    {
      "imagePath": "/globalcicd/acc",
      "imageName": "storage-provider",
      "imageTag": "1.3.116",
      "imageDigest":
"sha256:2e04d178815537b0ad8c3224e8754e3364456781a161f1be239853dae33deaf
c"
    },
    {
      "imagePath": "/globalcicd/acc",
      "imageName": "storage-backend-metrics",
      "imageTag": "1.3.45",
      "imageDigest":
"sha256:2e04d178815537b0ad8c3224e8754e3364456781a161f1be239853dae33deaf
c"
    },
    {
      "imagePath": "/globalcicd/acc",
      "imageName": "credentials",
      "imageTag": "1.3.45",
      "imageDigest":
"sha256:2e04d178815537b0ad8c322445654e33642da781a161f1be239853dae33deaf
c"
    }
  ],
  "files": [
    {
      "fileName": "astra_control_center_min.yaml",
      "fileIdentifier": "astra_min",
      "fileMediaType": "application/x-yaml",
      "fileContents":
"VGhpcyBpcyBzdXBwb3NlZCB0byBiZSBhIGNvbXBvZXNzZWQgZmlsZSBjb250ZW50"
    }
  ],
  "dependencies": [
    {
```

```

    "componentName": "acc",
    "componentMinVersion": "22.04.29"
  },
  {
    "componentName": "kubernetes",
    "componentMinVersion": "v1.19.7",
    "componentMaxVersion": "v1.22"
  },
  {
    "componentName": "trident",
    "componentMinVersion": "v21.01.1"
  }
]
}

```

Response

Status: 201, Returns the newly created package resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-package"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema

Name	Type	Required	Description
packageName	string	True	<p>JSON string containing the package name. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 Example values are: • "acc" • "acs" • "trident"
packageVersion	string	True	<p>JSON string containing the SemVer of the package. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the SemVer Schema
packageType	string	True	<p>JSON string containing the package type, indicating whether this is a full installation package or a patch. Defined values are:</p> <ul style="list-style-type: none"> • "install" • "patch"
bundleName	array[string]	False	<p>JSON array of JSON strings containing the name of the bundle that the package is contained in.</p>

Name	Type	Required	Description
severityLevel	string	True	<p>JSON string describing the severity level of this patch or installation. Defined values are:</p> <ul style="list-style-type: none"> • "recommended" - Installation is recommended - Default value • "critical" - Installation is strongly recommended to address critical bug fixes and/or security patches
packageState	string	True	<p>JSON string containing a value indicating the operational state of the package. After verification of the package and after import, the state will indicate "complete". Otherwise, the state will indicate "incomplete". Defined values are:</p> <ul style="list-style-type: none"> • "verifying" - The package is in the process of being validated • "corrupt" - The package is corrupt • "incomplete" - The package is missing elements • "available" - All elements associated with the package are available and the package is ready for use

Name	Type	Required	Description
packageStateTransitions	array[type_astra_stateTransition]	True	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state.</p> <p>Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state and the "to" value is an array of permitted destination states.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the State Transition Schema
packageStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current "state".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
images	array[images]	False	<p>JSON array of JSON objects, each containing a Docker image that is part of the package.</p>
artifacts	array[artifacts]	False	<p>JSON array of JSON objects describing the additional artifacts (binaries and others) associated with this package.</p>
files	array[files]	False	<p>JSON array of JSON objects, each representing a non-image artifact associated with this package.</p>

Name	Type	Required	Description
upgradableVersions	upgradableVersions	False	JSON object containing the minimum and maximum versions that can be upgraded to the package version.
dependencies	array[dependencies]	False	JSON array of JSON objects describing what minimum version of a given dependency is required for this package to be installed
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-package",
  "version": "1.0",
  "id": "54edc2b3-18c5-5371-904b-ebcd04d88bdc",
  "packageName": "acc",
  "packageVersion": "22.09.1",
  "packageType": "patch",
  "packageState": "available",
  "packageStateTransitions": [
    {
      "from": "verifying",
      "to": [
        "corrupt",
        "incomplete",
        "available"
      ]
    },
    {
      "from": "corrupt",
      "to": [
        "incomplete",
        "available"
      ]
    },
    {
      "from": "incomplete",
      "to": [
        "corrupt",
        "available"
      ]
    },
    {
      "from": "available",
      "to": [
        "corrupt",
        "available"
      ]
    }
  ],
  "packageStateDetails": [],
  "severityLevel": "recommended",
  "images": [
    {
      "imagePath": "/globalcicd/acc",

```

```

      "imageName": "storage-provider",
      "imageTag": "1.3.116",
      "imageDigest":
"sha256:2e04d178815537b0ad8c3224e8754e33642da781a161f1be239853dae33deaf
c"
    },
    {
      "imagePath": "/globalcid/acc",
      "imageName": "storage-backend-metrics",
      "imageTag": "1.3.45",
      "imageDigest":
"sha256:2e04d178815537b0ad8c3224e8754e33642da781a161f1be239853dae33deaf
c"
    },
    {
      "imagePath": "/globalcid/acc",
      "imageName": "credentials",
      "imageTag": "1.3.45",
      "imageDigest":
"sha256:2e04d178815537b0ad8c3224e8754e33642da781a161f1be239853dae33deaf
c"
    }
  ],
  "files": [
    {
      "fileName": "astra_control_center_min.yaml",
      "fileIdentifier": "astra_min",
      "fileMediaType": "application/x-yaml",
      "fileContents":
"VGhpcyBpcyBzdXBwb3NlZCB0byBiZSBhIGNvbXBvZXRzZXNzZWQgZmlsZSBjb250ZW50"
    }
  ],
  "dependencies": [
    {
      "componentName": "acc",
      "componentMinVersion": "22.04.29"
    },
    {
      "componentName": "kubernetes",
      "componentMinVersion": "v1.19.7",
      "componentMaxVersion": "v1.20"
    },
    {
      "componentName": "trident",
      "componentMinVersion": "v21.01.1"
    }
  ]
}

```

```

    ],
    "metadata": {
      "labels": [],
      "creationTimestamp": "2022-10-06T20:58:16.305662Z",
      "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
      "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
    }
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```

{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}

```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

dependsOnImages

Name	Type	Required	Description
imagePath	string	True	JSON string containing the path to this Docker image. It must not contain the name of the registry, only the absolute path from root to image. Example: /globalcid/acc Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 1023
imageName	string	True	JSON string containing the Docker image name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
imageTag	string	True	JSON string representing the tag/version of this image. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 31

images

Name	Type	Required	Description
imageName	string	True	JSON string containing the Docker image name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63

Name	Type	Required	Description
imagePath	string	True	JSON string containing the path to this Docker image. It must not contain the name of the registry, only the absolute path from root to image. Example: /globalcid/acc Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 1023
imageTag	string	True	JSON string representing the tag/version of this image. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
imageDigest	string	True	JSON string representing the digest of this image. Defined values are: <ul style="list-style-type: none"> • Defined regex is: <code>"^(sha256:)[0-9a-f]{64}\$"</code>
dependsOnImages	array[dependsOnImages]	False	JSON array of JSON objects describing the images required to install or upgrade the current image.

dependsOnComponents

Name	Type	Required	Description
componentName	string	True	JSON string describing the name of the component. Defined values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident" • "kubernetes"
versions	array[string]	True	JSON array of JSON strings defining the component version required to install the current image.

artifacts

Name	Type	Required	Description
artifactName	string	True	JSON string containing the file name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
artifactIdentifier	string	True	JSON string containing an identifier for this file. Between versions of the same package type, the file name might change but the identifier usually stays the same. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511

Name	Type	Required	Description
artifactPath	string	True	JSON string containing the path to this artifact from the root of a known Astra Control Center Data Store/location. Example: /vmware/1.0/ Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 1023
artifactVersion	string	False	JSON string containing the version of that artifact, if provided. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema • Minimum length: 1 • Maximum length: 31
dependsOnComponents	array[dependsOnComponents]	False	JSON array of JSON objects describing the installed components required to install/upgrade the current image.

files

Name	Type	Required	Description
fileName	string	True	JSON string containing the file name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
fileIdentifier	string	True	<p>JSON string containing an identifier of this file. Between versions of the same package type, the file name might change but the identifier usually stays the same.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511
fileMediaType	string	True	<p>JSON string containing the file media-type. Defined values are any media type defined by IANA.</p> <p>In addition, application/x-yaml or application/x-yaml for yaml files is supported.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 211
fileContents	string	True	<p>JSON string containing the file content.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Base64 Schema FIXME - How do we specify that this is compressed? What algorithm ,etc?

upgradableVersions

JSON object containing the minimum and maximum versions that can be upgraded to the package version.

Name	Type	Required	Description
minVersion	string	False	JSON string describing the minimum version that can be upgraded to the package version. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema
maxVersion	string	False	JSON string describing the maximum version that can be upgraded to the package version. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

dependencies

Name	Type	Required	Description
componentName	string	True	JSON string describing the name of the component. Defined values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident" • "kubernetes"
componentMinVersion	string	False	JSON string describing the minimum version required of that component. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

Name	Type	Required	Description
componentMaxVersion	string	False	JSON string describing the maximum version required of that component. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all packages

GET /accounts/{account_id}/core/v1/packages

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: id,packageName ,packageVersion ,softwareType
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: package_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-packages",
  "version": "1.0",
  "items": [
    [
      "e280ff62-be35-4f31-a31b-a210a1ad1b33",
      "acc",
      "22.01.0",
      "install"
    ],
    [
      "e8507dad-d33f-44b3-9c15-ec55ba6f6473",
      "acc",
      "22.01.1",
      "patch"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

dependsOnImages

Name	Type	Required	Description
imagePath	string	True	JSON string containing the path to this Docker image. It must not contain the name of the registry, only the absolute path from root to image. Example: /globalcid/acc Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 1023
imageName	string	True	JSON string containing the Docker image name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
imageTag	string	True	JSON string representing the tag/version of this image. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 31

images

Name	Type	Required	Description
imageName	string	True	JSON string containing the Docker image name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
imagePath	string	True	JSON string containing the path to this Docker image. It must not contain the name of the registry, only the absolute path from root to image. Example: /globalcid/acc Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 1023
imageTag	string	True	JSON string representing the tag/version of this image. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 31
imageDigest	string	True	JSON string representing the digest of this image. Defined values are: <ul style="list-style-type: none">• Defined regex is: <code>"^(sha256:)[0-9a-f]{64}\$"</code>
dependsOnImages	array[dependsOnImages]	False	JSON array of JSON objects describing the images required to install or upgrade the current image.

dependsOnComponents

Name	Type	Required	Description
componentName	string	True	JSON string describing the name of the component. Defined values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident" • "kubernetes"
versions	array[string]	True	JSON array of JSON strings defining the component version required to install the current image.

artifacts

Name	Type	Required	Description
artifactName	string	True	JSON string containing the file name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
artifactIdentifier	string	True	JSON string containing an identifier for this file. Between versions of the same package type, the file name might change but the identifier usually stays the same. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511

Name	Type	Required	Description
artifactPath	string	True	JSON string containing the path to this artifact from the root of a known Astra Control Center Data Store/location. Example: /vmware/1.0/ Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 1023
artifactVersion	string	False	JSON string containing the version of that artifact, if provided. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema • Minimum length: 1 • Maximum length: 31
dependsOnComponents	array[dependsOnComponents]	False	JSON array of JSON objects describing the installed components required to install/upgrade the current image.

files

Name	Type	Required	Description
fileName	string	True	JSON string containing the file name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
fileIdentifier	string	True	<p>JSON string containing an identifier of this file. Between versions of the same package type, the file name might change but the identifier usually stays the same.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511
fileMediaType	string	True	<p>JSON string containing the file media-type. Defined values are any media type defined by IANA.</p> <p>In addition, application/x-yaml or application/x-yaml for yaml files is supported.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 211
fileContents	string	True	<p>JSON string containing the file content.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Base64 Schema FIXME - How do we specify that this is compressed? What algorithm ,etc?

upgradableVersions

JSON object containing the minimum and maximum versions that can be upgraded to the package version.

Name	Type	Required	Description
minVersion	string	False	JSON string describing the minimum version that can be upgraded to the package version. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema
maxVersion	string	False	JSON string describing the maximum version that can be upgraded to the package version. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

dependencies

Name	Type	Required	Description
componentName	string	True	JSON string describing the name of the component. Defined values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident" • "kubernetes"
componentMinVersion	string	False	JSON string describing the minimum version required of that component. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

Name	Type	Required	Description
componentMaxVersion	string	False	JSON string describing the maximum version required of that component. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

package_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-package"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
packageName	string	True	JSON string containing the package name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 Example values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident"
packageVersion	string	True	JSON string containing the SemVer of the package. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema
packageType	string	True	JSON string containing the package type, indicating whether this is a full installation package or a patch. Defined values are: <ul style="list-style-type: none"> • "install" • "patch"
bundleName	array[string]	False	JSON array of JSON strings containing the name of the bundle that the package is contained in.

Name	Type	Required	Description
severityLevel	string	True	<p>JSON string describing the severity level of this patch or installation. Defined values are:</p> <ul style="list-style-type: none"> • "recommended" - Installation is recommended - Default value • "critical" - Installation is strongly recommended to address critical bug fixes and/or security patches
packageState	string	True	<p>JSON string containing a value indicating the operational state of the package. After verification of the package and after import, the state will indicate "complete". Otherwise, the state will indicate "incomplete". Defined values are:</p> <ul style="list-style-type: none"> • "verifying" - The package is in the process of being validated • "corrupt" - The package is corrupt • "incomplete" - The package is missing elements • "available" - All elements associated with the package are available and the package is ready for use

Name	Type	Required	Description
packageStateTransitions	array[type_astra_stateTransition]	True	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state and the "to" value is an array of permitted destination states.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the State Transition Schema
packageStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current "state". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
images	array[images]	False	<p>JSON array of JSON objects, each containing a Docker image that is part of the package.</p>
artifacts	array[artifacts]	False	<p>JSON array of JSON objects describing the additional artifacts (binaries and others) associated with this package.</p>
files	array[files]	False	<p>JSON array of JSON objects, each representing a non-image artifact associated with this package.</p>

Name	Type	Required	Description
upgradableVersions	upgradableVersions	False	JSON object containing the minimum and maximum versions that can be upgraded to the package version.
dependencies	array[dependencies]	False	JSON array of JSON objects describing what minimum version of a given dependency is required for this package to be installed
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

Retrieve a package

GET /accounts/{account_id}/core/v1/packages/{package_id}

Returns the stored Package API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
package_id	string	path	True	ID of the package collection to list

Response

Status: 200, Returns the stored Package API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-package"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
packageName	string	True	JSON string containing the package name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 Example values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident"
packageVersion	string	True	JSON string containing the SemVer of the package. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema
packageType	string	True	JSON string containing the package type, indicating whether this is a full installation package or a patch. Defined values are: <ul style="list-style-type: none"> • "install" • "patch"
bundleName	array[string]	False	JSON array of JSON strings containing the name of the bundle that the package is contained in.

Name	Type	Required	Description
severityLevel	string	True	<p>JSON string describing the severity level of this patch or installation. Defined values are:</p> <ul style="list-style-type: none"> • "recommended" - Installation is recommended - Default value • "critical" - Installation is strongly recommended to address critical bug fixes and/or security patches
packageState	string	True	<p>JSON string containing a value indicating the operational state of the package. After verification of the package and after import, the state will indicate "complete". Otherwise, the state will indicate "incomplete". Defined values are:</p> <ul style="list-style-type: none"> • "verifying" - The package is in the process of being validated • "corrupt" - The package is corrupt • "incomplete" - The package is missing elements • "available" - All elements associated with the package are available and the package is ready for use

Name	Type	Required	Description
packageStateTransitions	array[type_astra_stateTransition]	True	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state.</p> <p>Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state and the "to" value is an array of permitted destination states.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the State Transition Schema
packageStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current "state".</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
images	array[images]	False	<p>JSON array of JSON objects, each containing a Docker image that is part of the package.</p>
artifacts	array[artifacts]	False	<p>JSON array of JSON objects describing the additional artifacts (binaries and others) associated with this package.</p>
files	array[files]	False	<p>JSON array of JSON objects, each representing a non-image artifact associated with this package.</p>

Name	Type	Required	Description
upgradableVersions	upgradableVersions	False	JSON object containing the minimum and maximum versions that can be upgraded to the package version.
dependencies	array[dependencies]	False	JSON array of JSON objects describing what minimum version of a given dependency is required for this package to be installed
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels.

Example response

```
{
  "type": "application/astra-package",
  "version": "1.0",
  "id": "54edc2b3-18c5-5371-904b-ebcd04d88bdc",
  "packageName": "acc",
  "packageVersion": "22.09.1",
  "packageType": "patch",
  "packageState": "available",
  "packageStateTransitions": [
    {
      "from": "verifying",
      "to": [
        "corrupt",
        "incomplete",
        "available"
      ]
    },
    {
      "from": "corrupt",
      "to": [
        "incomplete",
        "available"
      ]
    },
    {
      "from": "incomplete",
      "to": [
        "corrupt",
        "available"
      ]
    },
    {
      "from": "available",
      "to": [
        "corrupt",
        "available"
      ]
    }
  ],
  "packageStateDetails": [],
  "severityLevel": "recommended",
  "images": [
    {
      "imagePath": "/globalcicd/acc",

```

```

    "imageName": "storage-provider",
    "imageTag": "1.3.116",
    "imageDigest":
"sha256:2e04d178815537b0ad8c3224e8754e33642da781a161f1be239853dae33deaf
c"
  },
  {
    "imagePath": "/globalcid/acc",
    "imageName": "storage-backend-metrics",
    "imageTag": "1.3.45",
    "imageDigest":
"sha256:2e04d178815537b0ad8c3224e8754e33642da781a161f1be239853dae33deaf
c"
  },
  {
    "imagePath": "/globalcid/acc",
    "imageName": "credentials",
    "imageTag": "1.3.45",
    "imageDigest":
"sha256:2e04d178815537b0ad8c3224e8754e33642da781a161f1be239853dae33deaf
c"
  }
],
"files": [
  {
    "fileName": "astra_control_center_min.yaml",
    "fileIdentifier": "astra_min",
    "fileMediaType": "application/x-yaml",
    "fileContents":
"VGhpcyBpcyBzdXBwb3NlZCB0byBiZSBhIGNvbXBvZXRzZXNzZWQgZmlsZSBjb250ZW50"
  }
],
"dependencies": [
  {
    "componentName": "acc",
    "componentMinVersion": "22.04.29"
  },
  {
    "componentName": "kubernetes",
    "componentMinVersion": "v1.19.7",
    "componentMaxVersion": "v1.20"
  },
  {
    "componentName": "trident",
    "componentMinVersion": "v21.01.1"
  }
]

```



```

    ],
    "metadata": {
      "labels": [],
      "creationTimestamp": "2022-10-06T20:58:16.305662Z",
      "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
      "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
    }
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```

{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}

```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

dependsOnImages

Name	Type	Required	Description
imagePath	string	True	JSON string containing the path to this Docker image. It must not contain the name of the registry, only the absolute path from root to image. Example: /globalcid/acc Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 1023
imageName	string	True	JSON string containing the Docker image name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
imageTag	string	True	JSON string representing the tag/version of this image. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 31

images

Name	Type	Required	Description
imageName	string	True	JSON string containing the Docker image name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
imagePath	string	True	JSON string containing the path to this Docker image. It must not contain the name of the registry, only the absolute path from root to image. Example: /globalcid/acc Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 1023
imageTag	string	True	JSON string representing the tag/version of this image. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 31
imageDigest	string	True	JSON string representing the digest of this image. Defined values are: <ul style="list-style-type: none">• Defined regex is: <code>"^(sha256:)[0-9a-f]{64}\$"</code>
dependsOnImages	array[dependsOnImages]	False	JSON array of JSON objects describing the images required to install or upgrade the current image.

dependsOnComponents

Name	Type	Required	Description
componentName	string	True	JSON string describing the name of the component. Defined values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident" • "kubernetes"
versions	array[string]	True	JSON array of JSON strings defining the component version required to install the current image.

artifacts

Name	Type	Required	Description
artifactName	string	True	JSON string containing the file name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
artifactIdentifier	string	True	JSON string containing an identifier for this file. Between versions of the same package type, the file name might change but the identifier usually stays the same. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511

Name	Type	Required	Description
artifactPath	string	True	JSON string containing the path to this artifact from the root of a known Astra Control Center Data Store/location. Example: /vmware/1.0/ Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 1023
artifactVersion	string	False	JSON string containing the version of that artifact, if provided. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema • Minimum length: 1 • Maximum length: 31
dependsOnComponents	array[dependsOnComponents]	False	JSON array of JSON objects describing the installed components required to install/upgrade the current image.

files

Name	Type	Required	Description
fileName	string	True	JSON string containing the file name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
fileIdentifier	string	True	<p>JSON string containing an identifier of this file. Between versions of the same package type, the file name might change but the identifier usually stays the same. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511
fileMediaType	string	True	<p>JSON string containing the file media-type. Defined values are any media type defined by IANA. In addition, application/x-yaml or application/x-yaml for yaml files is supported.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 211
fileContents	string	True	<p>JSON string containing the file content. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Base64 Schema FIXME - How do we specify that this is compressed? What algorithm ,etc?

upgradableVersions

JSON object containing the minimum and maximum versions that can be upgraded to the package version.

Name	Type	Required	Description
minVersion	string	False	JSON string describing the minimum version that can be upgraded to the package version. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema
maxVersion	string	False	JSON string describing the maximum version that can be upgraded to the package version. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

dependencies

Name	Type	Required	Description
componentName	string	True	JSON string describing the name of the component. Defined values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident" • "kubernetes"
componentMinVersion	string	False	JSON string describing the minimum version required of that component. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

Name	Type	Required	Description
componentMaxVersion	string	False	JSON string describing the maximum version required of that component. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete a package

DELETE /accounts/{account_id}/core/v1/packages/{package_id}

Removes the specified Package API resource.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
package_id	string	path	True	ID of the package collection to list

Response

Status: 204, Indicates if the package resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Role binding

Role binding overview

The Role Binding API describes the relationships between the user-account pairs, or group-account pairs, along with the sets of permissions they are granted (roles).

Create a new role binding for a group

POST /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings

Indicates desired values for the Role Binding API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
group_id	string	path	True	ID of the containing group resource

Request Body

Indicates desired values for the Role Binding API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
userID	string	False	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	False	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema

Name	Type	Required	Description
role	string	True	JSON string containing one of the four defined roles. Defined values are: <ul style="list-style-type: none">• "viewer"• "member"• "admin"• "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.example.com'"]

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "userID": "00000000-0000-0000-0000-000000000000",
  "groupID": "6f7f5bb3-1320-4861-bd8a-d3a4106d36b1",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ]
}
```

Response

Status: 201, Returns the newly created roleBinding resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> "user" "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	True	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.example.com'"]

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "group",
  "userID": "00000000-0000-0000-0000-000000000000",
  "groupID": "6f7f5bb3-1320-4861-bd8a-d3a4106d36b1",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the role bindings for a group

GET /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: accountID,userI D,role
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue> OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: roleBinding_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-roleBindings",
  "version": "1.1",
  "items": [
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "4c27d25a-9edb-4e85-9438-48dc8e917231",
      "viewer"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "dc40a13f-e9b3-4cf5-900f-58de32174390",
      "owner"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "c38abd8d-7dae-4659-8382-2e74a58738ba",
      "owner"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```


Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

roleBinding_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	True	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
accountID	string	True	JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
role	string	True	JSON string containing one of the four defined roles. Defined values are: <ul style="list-style-type: none">• "viewer"• "member"• "admin"• "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a role binding for a group

GET

/accounts/{account_id}/core/v1/groups/{group_id}/roleBindings/{roleBinding_id}

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
group_id	string	path	True	ID of the containing group resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 200

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	True	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "user",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "groupID": "00000000-0000-0000-0000-000000000000",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a role binding for a group

PUT /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings/{roleBinding_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	False	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
userID	string	False	<p>JSON string containing a user resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	False	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	False	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "role": "member",
  "roleConstraints": [
    "namespaces:id='c832e1dc-d7c3-464e-9c62-47bf91c46ce8'"
  ]
}
```

Response

Status: 204, Indicates if the roleBinding resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a role binding for a group

DELETE

/accounts/{account_id}/core/v1/groups/{group_id}/roleBindings/{roleBinding_id}

Removes the specified Role Binding API resource.

Side Effects

- Deleting the last role-binding associated with a user with authProvider as 'local', or 'cloud-central' (not ldap) triggers the deletion of the user.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
group_id	string	path	True	ID of the containing group resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 204, Indicates if the roleBinding resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new role binding for a user in a group

POST

/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/roleBindings

Indicates desired values for the Role Binding API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource

Request Body

Indicates desired values for the Role Binding API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
userID	string	False	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	False	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
role	string	True	JSON string containing one of the four defined roles. Defined values are: <ul style="list-style-type: none">• "viewer"• "member"• "admin"• "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ]
}
```

Response

Status: 201, Returns the newly created roleBinding resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> "user" "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	True	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "user",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "groupID": "00000000-0000-0000-0000-000000000000",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the role bindings for a user in a group

GET /accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/roleBindings

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: accountID,userI D,role
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue> OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: roleBinding_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-roleBindings",
  "version": "1.1",
  "items": [
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "4c27d25a-9edb-4e85-9438-48dc8e917231",
      "viewer"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "dc40a13f-e9b3-4cf5-900f-58de32174390",
      "owner"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "c38abd8d-7dae-4659-8382-2e74a58738ba",
      "owner"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

roleBinding_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	True	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
accountID	string	True	JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
role	string	True	JSON string containing one of the four defined roles. Defined values are: <ul style="list-style-type: none">• "viewer"• "member"• "admin"• "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a role binding for a user in a group

GET

/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/roleBindings/{roleBinding_id}

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 200

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	True	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "user",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "groupID": "00000000-0000-0000-0000-000000000000",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a role binding for a user in a group

PUT

/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/roleBindings/{roleBinding_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
userID	string	False	<p>JSON string containing a user resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	False	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	False	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.example.com'"]

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "role": "member",
  "roleConstraints": [
    "namespaces:id='c832e1dc-d7c3-464e-9c62-47bf91c46ce8'"
  ]
}
```

Response

Status: 204, Indicates if the roleBinding resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a role binding for a user in a group

DELETE

/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/roleBindings/{roleBinding_id}

Removes the specified Role Binding API resource.

Side Effects

- Deleting the last role-binding associated with a user with authProvider as 'local', or 'cloud-central' (not ldap) triggers the deletion of the user.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 204, Indicates if the roleBinding resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new role binding

POST /accounts/{account_id}/core/v1/roleBindings

Indicates desired values for the Role Binding API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates desired values for the Role Binding API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"

Name	Type	Required	Description
userID	string	False	<p>JSON string containing a user resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	False	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ]
}
```

Response

Status: 201, Returns the newly created roleBinding resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> "user" "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	True	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "user",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "groupID": "00000000-0000-0000-0000-000000000000",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all role bindings

GET /accounts/{account_id}/core/v1/roleBindings

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: accountID,userI D,role
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue> OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: roleBinding_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-roleBindings",
  "version": "1.1",
  "items": [
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "4c27d25a-9edb-4e85-9438-48dc8e917231",
      "viewer"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "dc40a13f-e9b3-4cf5-900f-58de32174390",
      "owner"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "c38abd8d-7dae-4659-8382-2e74a58738ba",
      "owner"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

roleBinding_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	True	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
accountID	string	True	JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
role	string	True	JSON string containing one of the four defined roles. Defined values are: <ul style="list-style-type: none">• "viewer"• "member"• "admin"• "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a role binding

GET /accounts/{account_id}/core/v1/roleBindings/{roleBinding_id}

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 200

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	True	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
accountID	string	True	<p>JSON string containing the ID of an account resource.</p> <p>For create, this must match the account ID in the request URI.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.example.com'"]

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "user",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "groupID": "00000000-0000-0000-0000-000000000000",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a role binding

PUT /accounts/{account_id}/core/v1/roleBindings/{roleBinding_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
userID	string	False	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	False	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	False	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.example.com'"]

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "role": "member",
  "roleConstraints": [
    "namespaces:id='c832e1dc-d7c3-464e-9c62-47bf91c46ce8'"
  ]
}
```

Response

Status: 204, Indicates if the roleBinding resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a role binding

DELETE /accounts/{account_id}/core/v1/roleBindings/{roleBinding_id}

Removes the specified Role Binding API resource.

Side Effects

- Deleting the last role-binding associated with a user with authProvider as 'local', or 'cloud-central' (not ldap) triggers the deletion of the user.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 204, Indicates if the roleBinding resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new role binding for a user

POST /accounts/{account_id}/core/v1/users/{user_id}/roleBindings

Indicates desired values for the Role Binding API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
user_id	string	path	True	ID of the containing user resource

Request Body

Indicates desired values for the Role Binding API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
userID	string	False	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	False	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
role	string	True	JSON string containing one of the four defined roles. Defined values are: <ul style="list-style-type: none">• "viewer"• "member"• "admin"• "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.example.com'"]

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ]
}
```

Response

Status: 201, Returns the newly created roleBinding resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> "user" "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	True	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.example.com'"]

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "user",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "groupID": "00000000-0000-0000-0000-000000000000",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the role bindings for a user

GET /accounts/{account_id}/core/v1/users/{user_id}/roleBindings

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: accountID,userID,role
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue> OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: roleBinding_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-roleBindings",
  "version": "1.1",
  "items": [
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "4c27d25a-9edb-4e85-9438-48dc8e917231",
      "viewer"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "dc40a13f-e9b3-4cf5-900f-58de32174390",
      "owner"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "c38abd8d-7dae-4659-8382-2e74a58738ba",
      "owner"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

roleBinding_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	True	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
accountID	string	True	JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
role	string	True	JSON string containing one of the four defined roles. Defined values are: <ul style="list-style-type: none">• "viewer"• "member"• "admin"• "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a role binding for a user

GET /accounts/{account_id}/core/v1/users/{user_id}/roleBindings/{roleBinding_id}

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 200

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	True	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "user",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "groupID": "00000000-0000-0000-0000-000000000000",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a role binding for a user

PUT /accounts/{account_id}/core/v1/users/{user_id}/roleBindings/{roleBinding_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1"
id	string	False	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
userID	string	False	<p>JSON string containing a user resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	False	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	False	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "role": "member",
  "roleConstraints": [
    "namespaces:id='c832e1dc-d7c3-464e-9c62-47bf91c46ce8'"
  ]
}
```

Response

Status: 204, Indicates if the roleBinding resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a role binding for a user

DELETE

/accounts/{account_id}/core/v1/users/{user_id}/roleBindings/{roleBinding_id}

Removes the specified Role Binding API resource.

Side Effects

- Deleting the last role-binding associated with a user with authProvider as 'local', or 'cloud-central' (not ldap) triggers the deletion of the user.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
user_id	string	path	True	ID of the containing user resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 204, Indicates if the roleBinding resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new role binding for a group associated with a user

POST

/accounts/{account_id}/core/v1/users/{user_id}/groups/{group_id}/roleBindings

Indicates desired values for the Role Binding API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
user_id	string	path	True	ID of the containing user resource
group_id	string	path	True	ID of the containing group resource

Request Body

Indicates desired values for the Role Binding API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
userID	string	False	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	False	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
role	string	True	JSON string containing one of the four defined roles. Defined values are: <ul style="list-style-type: none">• "viewer"• "member"• "admin"• "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "userID": "00000000-0000-0000-0000-000000000000",
  "groupID": "6f7f5bb3-1320-4861-bd8a-d3a4106d36b1",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ]
}
```

Response

Status: 201, Returns the newly created roleBinding resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> "user" "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	True	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.examp

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "group",
  "userID": "00000000-0000-0000-0000-000000000000",
  "groupID": "6f7f5bb3-1320-4861-bd8a-d3a4106d36b1",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the role bindings for a group associated with a user

GET /accounts/{account_id}/core/v1/users/{user_id}/groups/{group_id}/roleBindings

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
group_id	string	path	True	ID of the containing group resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: accountID,userI D,role
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue> OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: roleBinding_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-roleBindings",
  "version": "1.1",
  "items": [
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "4c27d25a-9edb-4e85-9438-48dc8e917231",
      "viewer"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "dc40a13f-e9b3-4cf5-900f-58de32174390",
      "owner"
    ],
    [
      "9fd87309-067f-48c9-a331-527796c14cf3",
      "c38abd8d-7dae-4659-8382-2e74a58738ba",
      "owner"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

roleBinding_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	True	JSON string containing a group resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
accountID	string	True	JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
role	string	True	JSON string containing one of the four defined roles. Defined values are: <ul style="list-style-type: none">• "viewer"• "member"• "admin"• "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*"] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a role binding for a group associated with a user

GET

/accounts/{account_id}/core/v1/users/{user_id}/groups/{group_id}/roleBindings/{roleBinding_id}

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
user_id	string	path	True	ID of the containing user resource
group_id	string	path	True	ID of the containing group resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 200

Returns the stored Role Binding API resource in the JSON response body.

If the request is against /accounts/{account_id}/core/v1/users/{user_id}/roleBindings endpoint, only roleBinding resources where the user ID matches the user ID in the request URL will be permitted to be read.

If the request is against /accounts/{account_id}/core/v1/groups/{group_id}/roleBindings, only roleBinding resources where the group ID matches the group ID in the request URL will be permitted to be read.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
principalType	string	True	JSON string representing the type of the principal this binding is associated with. Defined values are: <ul style="list-style-type: none"> • "user" • "group" For principalType "user", a non-nil user ID is required. For principalType "group", a non-nil group ID is required.
userID	string	True	JSON string containing a user resource ID. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.

Name	Type	Required	Description
groupID	string	True	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	True	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.example.com'"]

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```

{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "id": "a198f052-5cd7-59d3-9f27-9ea32a21fbca",
  "principalType": "user",
  "userID": "4c27d25a-9edb-4e85-9438-48dc8e917231",
  "groupID": "00000000-0000-0000-0000-000000000000",
  "accountID": "9fd87309-067f-48c9-a331-527796c14cf3",
  "role": "viewer",
  "roleConstraints": [
    "*"
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a role binding for a group associated with a user

PUT

/accounts/{account_id}/core/v1/users/{user_id}/groups/{group_id}/roleBindings/{roleBinding_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
group_id	string	path	True	ID of the containing group resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-roleBinding"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
userID	string	False	<p>JSON string containing a user resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
groupID	string	False	<p>JSON string containing a group resource ID. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema If not specified on create, a nil UUID will be used. Only userID or groupID can be specified on create.
accountID	string	False	<p>JSON string containing the ID of an account resource. For create, this must match the account ID in the request URI. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
role	string	True	<p>JSON string containing one of the four defined roles. Defined values are:</p> <ul style="list-style-type: none"> • "viewer" • "member" • "admin" • "owner"

Name	Type	Required	Description
roleConstraints	array[string]	False	<p>JSON array of JSON strings specifying the scope of the role assignment. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to Astra Role Constraints Schema If not specified on create, the value will be set to an array of size 1 containing string "*" representing "full scope". If not specified on update, the value will be preserved without modification. An empty array represents "no scope". Examples: <ul style="list-style-type: none"> • = Allow access to any resource: "roleConstraints": ["*"] • = deny access to all resources: "roleConstraints": [] • = Allow access to a specific namespace resource only: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'"] • = Allow access to a specific namespace and everything under it: "roleConstraints": ["namespaces:id='6fa2f917-f730-41b8-9c15-17f531843b31'.*' "] • = Allow access to all namespaces labelled "dev" in any cluster in any cloud, and everything under them: "roleConstraints": ["namespaces:kubernetesLabels='dev.example.com'"]

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-roleBinding",
  "version": "1.1",
  "role": "member",
  "roleConstraints": [
    "namespaces:id='c832e1dc-d7c3-464e-9c62-47bf91c46ce8'"
  ]
}
```

Response

Status: 204, Indicates if the roleBinding resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a role binding for a group associated with a user

DELETE

/accounts/{account_id}/core/v1/users/{user_id}/groups/{group_id}/roleBindings/{roleBinding_id}

Removes the specified Role Binding API resource.

Side Effects

- Deleting the last role-binding associated with a user with authProvider as 'local', or 'cloud-central' (not ldap) triggers the deletion of the user.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
group_id	string	path	True	ID of the containing group resource
roleBinding_id	string	path	True	ID of the roleBinding collection to list

Response

Status: 204, Indicates if the roleBinding resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Schedule

Schedule overview

The Schedule API allows various scheduled data protection operations to be defined.

Create a new schedule for an app

POST /accounts/{account_id}/k8s/v1/apps/{app_id}/schedules

Indicates desired values for the Schedule API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
app_id	string	path	True	ID of the containing app resource

Request Body

Indicates desired values for the Schedule API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-schedule"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3"
name	string	True	JSON string containing a name of the schedule. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
enabled	string	False	JSON string indicating if a schedule is active. Defined values are: <ul style="list-style-type: none"> • "true" - The schedule is active • "false" - The schedule is not active If not specified, the default value is "true".
granularity	string	True	JSON string indicating the granularity of the schedule. Defined values are: <ul style="list-style-type: none"> • "hourly" • "daily" • "weekly" • "monthly" • "custom"

Name	Type	Required	Description
minute	string	False	<p>JSON string containing a numeric value indicating the minute of the hour (0 - 59) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1-5][0-9]\$" This field is present if granularity is set to "hourly", "daily", "weekly", or "monthly". It will be returned with value "0" for custom schedules.</code>
hour	string	False	<p>JSON string containing a numeric value indicating the hour of the day (0 - 23) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1][0-9][2][0-3]\$" This field is present if granularity is set to "daily", "weekly", or "monthly".</code>
dayOfWeek	string	False	<p>JSON string containing a numeric value indicating the day of the week (0-7) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-7]\$" This field is only present if granularity is set to "weekly".</code>

Name	Type	Required	Description
dayOfMonth	string	False	<p>JSON string containing a numeric value indicating the day of the month (1-31) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[1-9] [1-2][0-9] [3][0-1]\$"</code> This field is only present if granularity is set to "monthly".
recurrenceRule	string	False	<p>JSON string containing an RFC-5545 Section 3.8.5.3. Recurrence Rule. For the DTSTART parameter, only UTC timestamps (denoted by the "Z" suffix) are supported, and only timestamps before the current time are supported.</p> <p>For the RECUR rule parts, "FREQ" and "INTERVAL" are the only rule parts supported.</p> <p>For the FREQ rule part, "MINUTELY" and "HOURLY" are the only values supported.</p> <p>This field is only present if granularity is set to "custom".</p>
snapshotRetention	string	True	<p>JSON string containing a positive numeric value indicating how many snapshots to retain. Zero indicates that snapshots should be deleted after taking a backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^(0 [1-9][0-9]*)\$"</code>

Name	Type	Required	Description
backupRetention	string	True	<p>JSON string containing a positive numeric value indicating how many backups to retain. Zero indicates that no backups should be created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^(0 ([1-9][0-9]*)\$"</code>
bucketID	string	False	<p>JSON string containing an optional bucket ID indicating where the backup must be stored on create. If not specified, a system-selected bucket will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
replicate	string	False	<p>JSON string indicating if the schedule triggers AppMirror replication for each snapshot. Only takes effect if the application has an AppMirror relationship defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The schedule triggers AppMirror replication • "false" - The schedule does not trigger AppMirror replication If not specified, the default value is "false".

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-schedule",
  "version": "1.3",
  "name": "Backup Schedule",
  "enabled": "true",
  "granularity": "monthly",
  "minute": "0",
  "hour": "0",
  "dayOfMonth": "1",
  "snapshotRetention": "12",
  "backupRetention": "12"
}
```

Response

Status: 201, Returns the newly created schedule resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-schedule"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name of the schedule. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
enabled	string	True	JSON string indicating if a schedule is active. Defined values are: <ul style="list-style-type: none"> • "true" - The schedule is active • "false" - The schedule is not active If not specified, the default value is "true".

Name	Type	Required	Description
granularity	string	True	<p>JSON string indicating the granularity of the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "hourly" • "daily" • "weekly" • "monthly" • "custom"
minute	string	True	<p>JSON string containing a numeric value indicating the minute of the hour (0 - 59) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1-5][0-9]\$"</code> This field is present if granularity is set to "hourly", "daily", "weekly", or "monthly". It will be returned with value "0" for custom schedules.
hour	string	False	<p>JSON string containing a numeric value indicating the hour of the day (0 - 23) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1][0-9][2][0-3]\$"</code> This field is present if granularity is set to "daily", "weekly", or "monthly".

Name	Type	Required	Description
dayOfWeek	string	False	<p>JSON string containing a numeric value indicating the day of the week (0-7) to execute the schedule. Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: "[0-7]\$" <p>This field is only present if granularity is set to "weekly".</p>
dayOfMonth	string	False	<p>JSON string containing a numeric value indicating the day of the month (1-31) to execute the schedule. Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: "[1-9] [1-2][0-9] [3][0-1]\$" <p>This field is only present if granularity is set to "monthly".</p>
recurrenceRule	string	False	<p>JSON string containing an RFC-5545 Section 3.8.5.3. Recurrence Rule. For the DTSTART parameter, only UTC timestamps (denoted by the "Z" suffix) are supported, and only timestamps before the current time are supported. For the RECUR rule parts, "FREQ" and "INTERVAL" are the only rule parts supported. For the FREQ rule part, "MINUTELY" and "HOURLY" are the only values supported. This field is only present if granularity is set to "custom".</p>

Name	Type	Required	Description
snapshotRetention	string	True	<p>JSON string containing a positive numeric value indicating how many snapshots to retain. Zero indicates that snapshots should be deleted after taking a backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^(0 ([1-9][0-9]*)\$"</code>
backupRetention	string	True	<p>JSON string containing a positive numeric value indicating how many backups to retain. Zero indicates that no backups should be created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^(0 ([1-9][0-9]*)\$"</code>
bucketID	string	False	<p>JSON string containing an optional bucket ID indicating where the backup must be stored on create. If not specified, a system-selected bucket will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicate	string	False	<p>JSON string indicating if the schedule triggers AppMirror replication for each snapshot. Only takes effect if the application has an AppMirror relationship defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The schedule triggers AppMirror replication • "false" - The schedule does not trigger AppMirror replication <p>If not specified, the default value is "false".</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-schedule",
  "version": "1.3",
  "id": "49cbc480-5f7d-51e2-8f30-52b9a83a03b1",
  "name": "Backup Schedule",
  "enabled": "true",
  "granularity": "monthly",
  "minute": "0",
  "hour": "0",
  "dayOfMonth": "1",
  "snapshotRetention": "12",
  "backupRetention": "12",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the schedules for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/schedules

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name,granularity
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: schedule_1.3_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-schedules",
  "version": "1.3",
  "items": [
    [
      "0d6d20d6-8b7c-498a-b57b-5734210c209a",
      "Backup Schedule",
      "monthly"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

schedule_1.3_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-schedule"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"• "1.3"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name of the schedule. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
enabled	string	True	JSON string indicating if a schedule is active. Defined values are: <ul style="list-style-type: none"> • "true" - The schedule is active • "false" - The schedule is not active If not specified, the default value is "true".
granularity	string	True	JSON string indicating the granularity of the schedule. Defined values are: <ul style="list-style-type: none"> • "hourly" • "daily" • "weekly" • "monthly" • "custom"

Name	Type	Required	Description
minute	string	True	<p>JSON string containing a numeric value indicating the minute of the hour (0 - 59) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1-5][0-9]\$" This field is present if granularity is set to "hourly", "daily", "weekly", or "monthly". It will be returned with value "0" for custom schedules.</code>
hour	string	False	<p>JSON string containing a numeric value indicating the hour of the day (0 - 23) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1][0-9][2][0-3]\$" This field is present if granularity is set to "daily", "weekly", or "monthly".</code>
dayOfWeek	string	False	<p>JSON string containing a numeric value indicating the day of the week (0-7) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-7]\$" This field is only present if granularity is set to "weekly".</code>

Name	Type	Required	Description
dayOfMonth	string	False	<p>JSON string containing a numeric value indicating the day of the month (1-31) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[1-9][1-2][0-9][3][0-1]\$" This field is only present if granularity is set to "monthly".</code>
recurrenceRule	string	False	<p>JSON string containing an RFC-5545 Section 3.8.5.3. Recurrence Rule.</p> <p>For the DTSTART parameter, only UTC timestamps (denoted by the "Z" suffix) are supported, and only timestamps before the current time are supported.</p> <p>For the RECUR rule parts, "FREQ" and "INTERVAL" are the only rule parts supported.</p> <p>For the FREQ rule part, "MINUTELY" and "HOURLY" are the only values supported.</p> <p>This field is only present if granularity is set to "custom".</p>

Name	Type	Required	Description
snapshotRetention	string	True	<p>JSON string containing a positive numeric value indicating how many snapshots to retain. Zero indicates that snapshots should be deleted after taking a backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^(0 ([1-9][0-9]*))\$"</code>
backupRetention	string	True	<p>JSON string containing a positive numeric value indicating how many backups to retain. Zero indicates that no backups should be created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^(0 ([1-9][0-9]*))\$"</code>
bucketID	string	False	<p>JSON string containing an optional bucket ID indicating where the backup must be stored on create. If not specified, a system-selected bucket will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicate	string	False	<p>JSON string indicating if the schedule triggers AppMirror replication for each snapshot. Only takes effect if the application has an AppMirror relationship defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> "true" - The schedule triggers AppMirror replication "false" - The schedule does not trigger AppMirror replication <p>If not specified, the default value is "false".</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a schedule

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/schedules/{schedule_id}

Returns the stored Schedule API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
schedule_id	string	path	True	ID of the schedule collection to list

Response

Status: 200, Returns the stored Schedule API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-schedule"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name of the schedule. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
enabled	string	True	JSON string indicating if a schedule is active. Defined values are: <ul style="list-style-type: none"> • "true" - The schedule is active • "false" - The schedule is not active If not specified, the default value is "true".

Name	Type	Required	Description
granularity	string	True	<p>JSON string indicating the granularity of the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "hourly" • "daily" • "weekly" • "monthly" • "custom"
minute	string	True	<p>JSON string containing a numeric value indicating the minute of the hour (0 - 59) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1-5][0-9]\$"</code> This field is present if granularity is set to "hourly", "daily", "weekly", or "monthly". It will be returned with value "0" for custom schedules.
hour	string	False	<p>JSON string containing a numeric value indicating the hour of the day (0 - 23) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1][0-9][2][0-3]\$"</code> This field is present if granularity is set to "daily", "weekly", or "monthly".

Name	Type	Required	Description
dayOfWeek	string	False	<p>JSON string containing a numeric value indicating the day of the week (0-7) to execute the schedule. Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: "[0-7]" This field is only present if granularity is set to "weekly".
dayOfMonth	string	False	<p>JSON string containing a numeric value indicating the day of the month (1-31) to execute the schedule. Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: "[1-9] [1-2][0-9] [3][0-1]" This field is only present if granularity is set to "monthly".
recurrenceRule	string	False	<p>JSON string containing an RFC-5545 Section 3.8.5.3. Recurrence Rule. For the DTSTART parameter, only UTC timestamps (denoted by the "Z" suffix) are supported, and only timestamps before the current time are supported. For the RECUR rule parts, "FREQ" and "INTERVAL" are the only rule parts supported. For the FREQ rule part, "MINUTELY" and "HOURLY" are the only values supported. This field is only present if granularity is set to "custom".</p>

Name	Type	Required	Description
snapshotRetention	string	True	<p>JSON string containing a positive numeric value indicating how many snapshots to retain. Zero indicates that snapshots should be deleted after taking a backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^(0 ([1-9][0-9]*))\$"</code>
backupRetention	string	True	<p>JSON string containing a positive numeric value indicating how many backups to retain. Zero indicates that no backups should be created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: <code>"^(0 ([1-9][0-9]*))\$"</code>
bucketID	string	False	<p>JSON string containing an optional bucket ID indicating where the backup must be stored on create. If not specified, a system-selected bucket will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
replicate	string	False	<p>JSON string indicating if the schedule triggers AppMirror replication for each snapshot. Only takes effect if the application has an AppMirror relationship defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The schedule triggers AppMirror replication • "false" - The schedule does not trigger AppMirror replication <p>If not specified, the default value is "false".</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-schedule",
  "version": "1.3",
  "id": "49cbc480-5f7d-51e2-8f30-52b9a83a03b1",
  "name": "Backup Schedule",
  "enabled": "true",
  "granularity": "monthly",
  "minute": "0",
  "hour": "0",
  "dayOfMonth": "1",
  "snapshotRetention": "12",
  "backupRetention": "12",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a schedule

PUT /accounts/{account_id}/k8s/v1/apps/{app_id}/schedules/{schedule_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
schedule_id	string	path	True	ID of the schedule collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-schedule"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2""1.3"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>JSON string containing a name of the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
enabled	string	False	<p>JSON string indicating if a schedule is active.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The schedule is active • "false" - The schedule is not active <p>If not specified, the default value is "true".</p>
granularity	string	False	<p>JSON string indicating the granularity of the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "hourly" • "daily" • "weekly" • "monthly" • "custom"
minute	string	False	<p>JSON string containing a numeric value indicating the minute of the hour (0 - 59) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1-5][0-9]\$"</code> <p>This field is present if granularity is set to "hourly", "daily", "weekly", or "monthly". It will be returned with value "0" for custom schedules.</p>

Name	Type	Required	Description
hour	string	False	<p>JSON string containing a numeric value indicating the hour of the day (0 - 23) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-9][1][0-9][2][0-3]\$" This field is present if granularity is set to "daily", "weekly", or "monthly".</code>
dayOfWeek	string	False	<p>JSON string containing a numeric value indicating the day of the week (0-7) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[0-7]\$" This field is only present if granularity is set to "weekly".</code>
dayOfMonth	string	False	<p>JSON string containing a numeric value indicating the day of the month (1-31) to execute the schedule.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Defined regex is: <code>"^[1-9][1-2][0-9][3][0-1]\$" This field is only present if granularity is set to "monthly".</code>

Name	Type	Required	Description
recurrenceRule	string	False	<p>JSON string containing an RFC-5545 Section 3.8.5.3. Recurrence Rule. For the DTSTART parameter, only UTC timestamps (denoted by the "Z" suffix) are supported, and only timestamps before the current time are supported.</p> <p>For the RECUR rule parts, "FREQ" and "INTERVAL" are the only rule parts supported. For the FREQ rule part, "MINUTELY" and "HOURLY" are the only values supported.</p> <p>This field is only present if granularity is set to "custom".</p>
snapshotRetention	string	True	<p>JSON string containing a positive numeric value indicating how many snapshots to retain. Zero indicates that snapshots should be deleted after taking a backup.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: "^(0 ([1-9][0-9]*))\$"
backupRetention	string	True	<p>JSON string containing a positive numeric value indicating how many backups to retain. Zero indicates that no backups should be created.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • Defined regex is: "^(0 ([1-9][0-9]*))\$"

Name	Type	Required	Description
bucketID	string	False	<p>JSON string containing an optional bucket ID indicating where the backup must be stored on create. If not specified, a system-selected bucket will be used.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
replicate	string	False	<p>JSON string indicating if the schedule triggers AppMirror replication for each snapshot. Only takes effect if the application has an AppMirror relationship defined.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The schedule triggers AppMirror replication • "false" - The schedule does not trigger AppMirror replication <p>If not specified, the default value is "false".</p>

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-schedule",
  "version": "1.3",
  "granularity": "daily",
  "minute": "0",
  "hour": "0",
  "snapshotRetention": "12",
  "backupRetention": "12"
}
```

Response

Status: 204, Indicates if the schedule resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a schedule

DELETE /accounts/{account_id}/k8s/v1/apps/{app_id}/schedules/{schedule_id}

Removes the specified Schedule API resource.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
app_id	string	path	True	ID of the containing app resource
schedule_id	string	path	True	ID of the schedule collection to list

Response

Status: 204, Indicates if the schedule resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Setting

Setting overview

An account setting is a collection of key/value pairs that are important for a known feature in an Astra account. The Setting API provides access to important information about an account setting.

List all settings

GET /accounts/{account_id}/core/v1/settings

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id"

Name	Type	In	Required	Description
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
count	string	query	False	<p>Indicates if the total number of resources should be returned in the metadata object.</p> <p>URL examples: "count=true"</p> <p>OpenAPI examples: "true"</p>

Name	Type	In	Required	Description
orderBy	string	query	False	Indicates the sort order of resource when listing a collection. URL examples: "orderBy=name", "orderBy=name%20desc" OpenAPI examples: "name desc"
skip	string	query	False	Indicates the number of resources to skip over when listing a collection. URL examples: "skip=1" OpenAPI examples: "1"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: setting_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-settings",
  "version": "1.1",
  "items": [
    {
      "type": "application/astra-setting",
      "version": "1.0",
      "id": "5da0a2ed-c51d-4d91-8b98-ed3aa8a88cc5",
      "name": "astra.account.smtp",
      "currentConfig": {
        "credential": "",
        "isEnabled": "false",
        "port": 587,
        "relayServer": "smtp.sendgrid.net"
      },
      "configSchema": {
        "$schema": "http://json-schema.org/draft-07/schema#",
        "title": "astra.account.smtp",
        "type": "object",
        "properties": {
          "credential": {
            "type": "string",
            "description": "The credential ID for SMTP authentication."
          },
          "isEnabled": {
            "type": "string",
            "description": "This property determines if this setting is
enabled or not."
          },
          "port": {
            "type": "integer",
            "description": "The SMTP port. For an unencrypted or a TLS
connection, use port 25, 2525, or 587."
          },
          "relayServer": {
            "type": "string",
            "description": "This setting is sometimes referred to as
the external SMTP server or the SMTP relay."
          }
        },
        "additionalProperties": false,
        "required": [
          "relayServer",
          "port",
```

```

        "isEnabled"
      ]
    },
    "state": "valid",
    "stateUnready": [],
    "metadata": {
      "labels": [],
      "creationTimestamp": "2021-06-04T20:14:52Z",
      "modificationTimestamp": "2021-06-04T20:14:52Z",
      "createdBy": "c9550bbb-e70b-4578-8504-07397f875bcb",
      "modifiedBy": "65e1571b-1b46-4f05-95b0-7d7f5a93da6a"
    }
  }
],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_json

JSON object containing keys and values that make up the current configuration for this setting. The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.

type_json

JSON object containing keys and values that make up the requested configuration for this setting. The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration.

properties

type_json_schema

JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7.

If config values are present in the resource, validation against the indicated configSchema is mandatory. As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").

Name	Type	Required	Description
\$schema	string	True	
type	string	True	
properties	properties	True	
additionalProperties	boolean	True	
required	array[string]	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

setting_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-setting"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a name for the setting, in hierarchal dot notation (.).</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. This value is specified by the configmap that is loaded at runtime and cannot be updated by the user.
currentConfig	type_json	True	<p>JSON object containing keys and values that make up the current configuration for this setting.</p> <p>The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.</p>

Name	Type	Required	Description
desiredConfig	type_json	False	<p>JSON object containing keys and values that make up the requested configuration for this setting.</p> <p>The contents of this object must conform to the JSON schema contained in the configSchema field.</p> <p>The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration.</p>
configSchema	type_json_schema	True	<p>JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7.</p> <p>If config values are present in the resource, validation against the indicated configSchema is mandatory.</p> <p>As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").</p>

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> "valid" - The current configuration matches the desired config. "pending" - The desired configuration is being applied. "error" - The desired configuration cannot be applied.
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the setting was not successfully applied.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 127
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

[type_astra_metadata_list](#)

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a setting

GET /accounts/{account_id}/core/v1/settings/{setting_id}

Returns the stored Setting API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
setting_id	string	path	True	ID of the setting collection to list

Response

Status: 200, Returns the stored Setting API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-setting"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a name for the setting, in hierarchal dot notation (.). Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. This value is specified by the configmap that is loaded at runtime and cannot be updated by the user.

Name	Type	Required	Description
currentConfig	type_json	True	<p>JSON object containing keys and values that make up the current configuration for this setting.</p> <p>The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.</p>
desiredConfig	type_json	False	<p>JSON object containing keys and values that make up the requested configuration for this setting.</p> <p>The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration.</p>

Name	Type	Required	Description
configSchema	type_json_schema	True	<p>JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7. If config values are present in the resource, validation against the indicated configSchema is mandatory.</p> <p>As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").</p>
state	string	True	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "valid" - The current configuration matches the desired config. • "pending" - The desired configuration is being applied. • "error" - The desired configuration cannot be applied.
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the setting was not successfully applied.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-setting",
  "version": "1.1",
  "id": "ea510866-47d3-5130-8468-563df4cd6a28",
  "name": "astra.account.smtp",
  "currentConfig": {
    "credential": "",
    "isEnabled": "false",
    "port": 587,
    "relayServer": "smtp.sendgrid.net"
  },
  "configSchema": {
    "$schema": "http://json-schema.org/draft-07/schema#",
    "title": "astra.account.smtp",
    "type": "object",
    "properties": {
      "credential": {
        "type": "string",
        "description": "The credential ID for SMTP authentication."
      },
      "isEnabled": {
        "type": "string",
        "description": "This property determines if this setting is
enabled or not."
      },
      "port": {
        "type": "integer",
        "description": "The SMTP port. For an unencrypted or a TLS
connection, use port 25, 2525, or 587."
      },
      "relayServer": {
        "type": "string",
        "description": "This setting is sometimes referred to as the
external SMTP server or the SMTP relay."
      }
    },
    "additionalProperties": false,
    "required": [
      "relayServer",
      "port",
      "isEnabled"
    ]
  },
  "state": "valid",
}
```

```

"stateUnready": [],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```

{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}

```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_json

JSON object containing keys and values that make up the current configuration for this setting. The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.

type_json

JSON object containing keys and values that make up the requested configuration for this setting. The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration.

properties

type_json_schema

JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7.

If config values are present in the resource, validation against the indicated configSchema is mandatory. As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").

Name	Type	Required	Description
\$schema	string	True	
type	string	True	
properties	properties	True	
additionalProperties	boolean	True	
required	array[string]	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a setting

PUT /accounts/{account_id}/core/v1/settings/{setting_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
setting_id	string	path	True	ID of the setting collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-setting"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	False	JSON string containing a name for the setting, in hierarchal dot notation (.). Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks. This value is specified by the configmap that is loaded at runtime and cannot be updated by the user.

Name	Type	Required	Description
currentConfig	type_json	False	<p>JSON object containing keys and values that make up the current configuration for this setting.</p> <p>The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.</p>
desiredConfig	type_json	False	<p>JSON object containing keys and values that make up the requested configuration for this setting.</p> <p>The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration.</p>

Name	Type	Required	Description
configSchema	type_json_schema	False	<p>JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7. If config values are present in the resource, validation against the indicated configSchema is mandatory.</p> <p>As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").</p>
state	string	False	<p>JSON string containing a value indicating the operational state of the application.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "valid" - The current configuration matches the desired config. • "pending" - The desired configuration is being applied. • "error" - The desired configuration cannot be applied.
stateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why the setting was not successfully applied.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-setting",
  "version": "1.1",
  "desiredConfig": {
    "credential": "e3d2ea77-398e-49be-85fd-ec66d9426a06",
    "port": 587,
    "relayServer": "<a href="
http://smtp.sendgrid.net>smtp.sendgrid.net</a>",
    "isEnabled": "true"
  }
}
```

Response

Status: 204, Indicates if the setting resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Response

Status: 503, Service unavailable

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/41",
  "title": "Service not ready",
  "detail": "Currently, the service can't respond to this request.",
  "status": "503"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_json

JSON object containing keys and values that make up the current configuration for this setting. The contents of this object must conform to the JSON Schema contained in the configSchema field. Default values are supplied by the configmap. After defaults are changed by the user, they will not be overwritten.

type_json

JSON object containing keys and values that make up the requested configuration for this setting. The contents of this object must conform to the JSON schema contained in the configSchema field. The object does not exist until specified. When specified, this triggers the feature service to notify the corresponding service to request that the desired configuration can be applied. The corresponding service can then perform validation and apply the desired configuration to the current configuration.

properties

type_json_schema

JSON object containing the JSON schema for the config property in this resource. Must conform to JSON Schema Draft 7.

If config values are present in the resource, validation against the indicated configSchema is mandatory. As a common convention, configurations are recommended to have an "isEnabled" field, when appropriate. The "isEnabled" field contains a value that indicates whether the setting is turned on ("true") or off ("false").

Name	Type	Required	Description
\$schema	string	True	
type	string	True	
properties	properties	True	
additionalProperties	boolean	True	
required	array[string]	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Storage backend

Storage backend overview

The Storage Backend API provides access to representations of providers of storage services (storage backends) that can be used by managed clusters and applications.

Create a new storage backend

POST /accounts/{account_id}/topology/v1/storageBackends

Indicates desired values for the Storage Backend API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>

Request Body

Indicates desired values for the Storage Backend API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-storageBackend"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1" "1.2" "1.3"
backendName	string	False	JSON string containing a user-specified name for the storage backend. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 63
backendType	string	True	JSON string containing a value indicating the type of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> "ontap" - The storage backend represents a NetApp ONTAP system enum: ["ontap"] example: ontap

Name	Type	Required	Description
backendVersion	string	False	<p>JSON string containing a value indicating the version of the storage backend being represented.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
backendCredentialsName	string	False	<p>JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-storageBackend",
  "version": "1.3",
  "backendName": "st1-45",
  "backendType": "ontap",
  "backendCredentialsName": "st1-45-cred"
}
```

Response

Status: 201, Returns the newly created storageBackend resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-storageBackend"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2""1.3"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
backendName	string	True	<p>JSON string containing a user-specified name for the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
backendType	string	True	<p>JSON string containing a value indicating the type of the storage backend being represented. Defined values are:</p> <ul style="list-style-type: none"> • "ontap" - The storage backend represents a NetApp ONTAP system • enum: ["ontap"] • example: ontap
backendVersion	string	True	<p>JSON string containing a value indicating the version of the storage backend being represented. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
backendCredentialsName	string	True	<p>JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
configVersion	string	False	<p>JSON string containing a value indicating the active configuration to be used by the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
state	string	True	<p>JSON string containing a value indicating the operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The storage backend has been discovered from a managed cluster • "running" - The storage backend is running normally • "unknown" - The state of the storage backend cannot be determined • "failed" - The storage backend is in an unavailable state
stateDesired	string	False	<p>JSON string containing a value indicating the desired operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "running" - The storage backend will be in a normal running state

Name	Type	Required	Description
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a storage backend is unable to transition to "running", why it has transitioned to "failed" or "unknown", and/or why it is at risk of transitioning to "failed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
managedState	string	True	<p>JSON string containing a value indicating the management state of the storage backend.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The storage backend is scheduled to be discovered or added • "unmanaged" - The storage backend is in a "discovered" state, is not under management, and is eligible for management • "managed" - The storage backend is in a "running" or "unknown" state and is under management
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the storage backend is ineligible to be managed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the storage backend.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification
healthStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is not in a normal health state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the storage backend. "unknown" for ONTAP. Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The storage backend has a protection policy defined and is in conformance with that policy • "partial" - The storage backend has a protection policy defined but is out of conformance with that policy • "none" - The storage backend is not protected • "unknown" - The storage backend protection policy conformance cannot be determined • enum: ["protected", "partial", "none", "unknown"] • example: protected
protectionStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a protection policy is out of conformance. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
capabilities	capabilities	True	JSON object containing this Storage Backend capabilities.

Name	Type	Required	Description
ontap	ontap	False	<p>JSON object containing specific information related to ONTAP clusters.</p> <ul style="list-style-type: none"> additionalProperties: false
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-storageBackend",
  "version": "1.3",
  "id": "04ad4237-3c89-5ca5-8a40-282ab5eb6428",
  "backendName": "st1-45",
  "backendType": "ontap",
  "backendVersion": "9.8",
  "backendCredentialsName": "st1-45-cred",
  "state": "running",
  "stateUnready": [],
  "managedState": "managed",
  "managedStateUnready": [],
  "protectionState": "unknown",
  "protectionStateUnready": [
    "Waiting for storage backend discovery"
  ],
  "ontap": {
    "authenticationStyle": "basic",
    "backendManagementIP": "10.193.179.105",
    "managementIPs": [
      "10.193.188.110",
      "10.193.179.105",
      "10.193.179.106"
    ]
  },
  "capabilities": {
    "flexClone": "true",
    "snapMirror": "true",
    "s3": "true"
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

capabilities

JSON object containing this Storage Backend capabilities.

Name	Type	Required	Description
flexClone	string	True	JSON string indicating if this Storage Backend supports FlexClone.
snapMirror	string	True	JSON string indicating if this Storage Backend supports SnapMirror.
s3	string	True	JSON string indicating if this Storage Backend supports s3.

ontap

JSON object containing specific information related to ONTAP clusters.

Name	Type	Required	Description
authenticationStyle	string	True	<p>JSON string indicating whether the ONTAP authentication is performed using a username/password combination or a certificate.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "basic" - Uses username/password • "certificate" - Uses certificate • enum: ["basic", "certificate"] • example: basic
backendManagementIP	string	False	<p>JSON string containing the IP address used to connect to this ONTAP cluster.</p>
managementIPs	array[string]	False	<p>JSON array of JSON strings containing the list of all possible management IPs used to connect to this ONTAP cluster.</p> <p>This is used to correlate backends detected through Trident and storage backends in Astra.</p> <ul style="list-style-type: none"> • uniqueItems: 1

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all storage backends

GET /accounts/{account_id}/topology/v1/storageBackends

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: <code>id,name,state</code>

Name	Type	In	Required	Description
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: storageBackend_1.3_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-storageBackends",
  "version": "1.3",
  "items": [
    [
      "d6ee1e51-d65f-415a-a3d4-6d7fa8b64943",
      "st1-45",
      "running"
    ],
    [
      "a5c508b7-aacd-4d19-9455-53c0d183ab4e",
      "st2-67",
      "discovered"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

capabilities

JSON object containing this Storage Backend capabilities.

Name	Type	Required	Description
flexClone	string	True	JSON string indicating if this Storage Backend supports FlexClone.
snapMirror	string	True	JSON string indicating if this Storage Backend supports SnapMirror.
s3	string	True	JSON string indicating if this Storage Backend supports s3.

ontap

JSON object containing specific information related to ONTAP clusters.

Name	Type	Required	Description
authenticationStyle	string	True	JSON string indicating whether the ONTAP authentication is performed using a username/password combination or a certificate. Defined values are: <ul style="list-style-type: none">• "basic" - Uses username/password• "certificate" - Uses certificate• enum: ["basic", "certificate"]• example: basic
backendManagementIP	string	False	JSON string containing the IP address used to connect to this ONTAP cluster.

Name	Type	Required	Description
managementIPs	array[string]	False	JSON array of JSON strings containing the list of all possible management IPs used to connect to this ONTAP cluster. This is used to correlate backends detected through Trident and storage backends in Astra. <ul style="list-style-type: none"> • uniqueItems: 1

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

storageBackend_1.3_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-storageBackend"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
backendName	string	True	JSON string containing a user-specified name for the storage backend. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
backendType	string	True	JSON string containing a value indicating the type of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> • "ontap" - The storage backend represents a NetApp ONTAP system • enum: ["ontap"] • example: ontap

Name	Type	Required	Description
backendVersion	string	True	<p>JSON string containing a value indicating the version of the storage backend being represented.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
backendCredentialsName	string	True	<p>JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
configVersion	string	False	<p>JSON string containing a value indicating the active configuration to be used by the storage backend.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The storage backend has been discovered from a managed cluster • "running" - The storage backend is running normally • "unknown" - The state of the storage backend cannot be determined • "failed" - The storage backend is in an unavailable state
stateDesired	string	False	<p>JSON string containing a value indicating the desired operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "running" - The storage backend will be in a normal running state
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a storage backend is unable to transition to "running", why it has transitioned to "failed" or "unknown", and/or why it is at risk of transitioning to "failed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	True	<p>JSON string containing a value indicating the management state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The storage backend is scheduled to be discovered or added • "unmanaged" - The storage backend is in a "discovered" state, is not under management, and is eligible for management • "managed" - The storage backend is in a "running" or "unknown" state and is under management
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the storage backend is ineligible to be managed. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification
healthStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is not in a normal health state. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the storage backend. "unknown" for ONTAP. Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The storage backend has a protection policy defined and is in conformance with that policy • "partial" - The storage backend has a protection policy defined but is out of conformance with that policy • "none" - The storage backend is not protected • "unknown" - The storage backend protection policy conformance cannot be determined • enum: ["protected", "partial", "none", "unknown"] • example: protected
protectionStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a protection policy is out of conformance. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
capabilities	capabilities	True	<p>JSON object containing this Storage Backend capabilities.</p>

Name	Type	Required	Description
ontap	ontap	False	JSON object containing specific information related to ONTAP clusters. <ul style="list-style-type: none"> additionalProperties: false
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a storage backend

GET /accounts/{account_id}/topology/v1/storageBackends/{storageBackend_id}

Returns the stored Storage Backend API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
storageBackend_id	string	path	True	ID of the storageBackend collection to list

Response

Status: 200, Returns the stored Storage Backend API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-storageBackend"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
backendName	string	True	JSON string containing a user-specified name for the storage backend. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
backendType	string	True	JSON string containing a value indicating the type of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> • "ontap" - The storage backend represents a NetApp ONTAP system • enum: ["ontap"] • example: ontap
backendVersion	string	True	JSON string containing a value indicating the version of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
backendCredentialsName	string	True	<p>JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
configVersion	string	False	<p>JSON string containing a value indicating the active configuration to be used by the storage backend.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
state	string	True	<p>JSON string containing a value indicating the operational state of the storage backend.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The storage backend has been discovered from a managed cluster • "running" - The storage backend is running normally • "unknown" - The state of the storage backend cannot be determined • "failed" - The storage backend is in an unavailable state

Name	Type	Required	Description
stateDesired	string	False	<p>JSON string containing a value indicating the desired operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "running" - The storage backend will be in a normal running state
stateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a storage backend is unable to transition to "running", why it has transitioned to "failed" or "unknown", and/or why it is at risk of transitioning to "failed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
managedState	string	True	<p>JSON string containing a value indicating the management state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The storage backend is scheduled to be discovered or added • "unmanaged" - The storage backend is in a "discovered" state, is not under management, and is eligible for management • "managed" - The storage backend is in a "running" or "unknown" state and is under management

Name	Type	Required	Description
managedStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why the storage backend is ineligible to be managed.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
healthState	string	False	<p>JSON string containing a value indicating the health state of the storage backend.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is not in a normal health state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
protectionState	string	True	<p>JSON string containing a value indicating the protection state of the storage backend.</p> <p>"unknown" for ONTAP.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The storage backend has a protection policy defined and is in conformance with that policy • "partial" - The storage backend has a protection policy defined but is out of conformance with that policy • "none" - The storage backend is not protected • "unknown" - The storage backend protection policy conformance cannot be determined • enum: ["protected", "partial", "none", "unknown"] • example: protected

Name	Type	Required	Description
protectionStateUnready	array[string]	True	<p>JSON array of JSON strings, each indicating a reason why a protection policy is out of conformance.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127
capabilities	capabilities	True	<p>JSON object containing this Storage Backend capabilities.</p>
ontap	ontap	False	<p>JSON object containing specific information related to ONTAP clusters.</p> <ul style="list-style-type: none"> • additionalProperties: false
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-storageBackend",
  "version": "1.3",
  "id": "04ad4237-3c89-5ca5-8a40-282ab5eb6428",
  "backendName": "st1-45",
  "backendType": "ontap",
  "backendVersion": "9.8",
  "backendCredentialsName": "st1-45-cred",
  "state": "discovered",
  "stateUnready": [],
  "managedState": "unmanaged",
  "managedStateUnready": [],
  "protectionState": "unknown",
  "protectionStateUnready": [
    "Waiting for storage backend discovery"
  ],
  "capabilities": {
    "flexClone": "true",
    "snapMirror": "true",
    "s3": "true"
  },
  "ontap": {
    "authenticationStyle": "basic",
    "backendManagementIP": "10.193.179.105",
    "managementIPs": [
      "10.193.188.110",
      "10.193.179.105",
      "10.193.179.106"
    ]
  },
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

capabilities

JSON object containing this Storage Backend capabilities.

Name	Type	Required	Description
flexClone	string	True	JSON string indicating if this Storage Backend supports FlexClone.
snapMirror	string	True	JSON string indicating if this Storage Backend supports SnapMirror.
s3	string	True	JSON string indicating if this Storage Backend supports s3.

ontap

JSON object containing specific information related to ONTAP clusters.

Name	Type	Required	Description
authenticationStyle	string	True	JSON string indicating whether the ONTAP authentication is performed using a username/password combination or a certificate. Defined values are: <ul style="list-style-type: none">• "basic" - Uses username/password• "certificate" - Uses certificate• enum: ["basic", "certificate"]• example: basic
backendManagementIP	string	False	JSON string containing the IP address used to connect to this ONTAP cluster.

Name	Type	Required	Description
managementIPs	array[string]	False	JSON array of JSON strings containing the list of all possible management IPs used to connect to this ONTAP cluster. This is used to correlate backends detected through Trident and storage backends in Astra. <ul style="list-style-type: none"> • uniqueItems: 1

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter

Name	Type	Required	Description
reason	string	True	Reason why the query parameter is invalid

Modify a storage backend

PUT /accounts/{account_id}/topology/v1/storageBackends/{storageBackend_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Specifying a configuration version results in storage backend type-specific configuration changes being applied, which can include the initial installation of a storage backend.
- Specifying a configuration version might result in storageClass resources being added, modified, or removed.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
storageBackend_id	string	path	True	ID of the storageBackend collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Specifying a configuration version results in storage backend type-specific configuration changes being applied, which can include the initial installation of a storage backend.
- Specifying a configuration version might result in storageClass resources being added, modified, or removed.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-storageBackend"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2" • "1.3"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
backendName	string	False	JSON string containing a user-specified name for the storage backend. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
backendType	string	False	JSON string containing a value indicating the type of the storage backend being represented. Defined values are: <ul style="list-style-type: none"> • "ontap" - The storage backend represents a NetApp ONTAP system • enum: ["ontap"] • example: ontap

Name	Type	Required	Description
backendVersion	string	False	<p>JSON string containing a value indicating the version of the storage backend being represented.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
backendCredentialsName	string	False	<p>JSON string containing a value indicating the name of one or more credential resources used for the storage backend. Allows for credential rotation where multiple credential objects have the same name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
configVersion	string	False	<p>JSON string containing a value indicating the active configuration to be used by the storage backend.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "discovered" - The storage backend has been discovered from a managed cluster • "running" - The storage backend is running normally • "unknown" - The state of the storage backend cannot be determined • "failed" - The storage backend is in an unavailable state
stateDesired	string	False	<p>JSON string containing a value indicating the desired operational state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "running" - The storage backend will be in a normal running state
stateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is unable to transition to "running", why it has transitioned to "failed" or "unknown", and/or why it is at risk of transitioning to "failed". Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
managedState	string	False	<p>JSON string containing a value indicating the management state of the storage backend. Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The storage backend is scheduled to be discovered or added • "unmanaged" - The storage backend is in a "discovered" state, is not under management, and is eligible for management • "managed" - The storage backend is in a "running" or "unknown" state and is under management
managedStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why the storage backend is ineligible to be managed. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the storage backend.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification
healthStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a storage backend is not in a normal health state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
protectionState	string	False	<p>JSON string containing a value indicating the protection state of the storage backend. "unknown" for ONTAP. Defined values are:</p> <ul style="list-style-type: none"> • "protected" - The storage backend has a protection policy defined and is in conformance with that policy • "partial" - The storage backend has a protection policy defined but is out of conformance with that policy • "none" - The storage backend is not protected • "unknown" - The storage backend protection policy conformance cannot be determined • enum: ["protected", "partial", "none", "unknown"] • example: protected
protectionStateUnready	array[string]	False	<p>JSON array of JSON strings, each indicating a reason why a protection policy is out of conformance. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 127

Name	Type	Required	Description
ontap	ontap	False	JSON object containing specific information related to ONTAP clusters. <ul style="list-style-type: none"> additionalProperties: false
metadata	type_astra_metadata_update	False	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-storageBackend",
  "version": "1.3",
  "backendName": "st1-46"
}
```

Response

Status: 204, Indicates if the storageBackend resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

ontap

JSON object containing specific information related to ONTAP clusters.

Name	Type	Required	Description
backendManagementIP	string	False	JSON string containing the IP address used to connect to this ONTAP cluster.
managementIPs	array[string]	False	JSON array of JSON strings containing the list of all possible management IPs used to connect to this ONTAP cluster. This is used to correlate backends detected through Trident and storage backends in Astra. <ul style="list-style-type: none">• uniqueItems: 1

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	

Name	Type	Required	Description
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a storage backend

DELETE /accounts/{account_id}/topology/v1/storageBackends/{storageBackend_id}

Removes the specified Storage Backend API resource.

Side Effects

- All backendConfig resources associated with the storage backend are removed.
- All backendNode resources associated with the storage backend are removed.
- The storage backend might be removed.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> • example: <code>{{.Account}}</code>

Name	Type	In	Required	Description
storageBackend_id	string	path	True	ID of the storageBackend collection to list

Response

Status: 204, Indicates if the storageBackend resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Storage class

Storage class overview

The Storage Class API describes storage classes known to a given cluster.

List the storage classes for a cloud

GET

/accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}/storageClasses

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
cloud_id	string	path	True	ID of the containing cloud resource
cluster_id	string	path	True	ID of the containing cluster resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: <code>id,name</code>
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: storageClass_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-storageClasses",
  "version": "1.1",
  "items": [
    [
      "e280ff62-be35-4f31-a31b-a210a1ad1b33",
      "my-storage-class"
    ],
    [
      "e8507dad-d33f-44b3-9c15-ec55ba6f6473",
      "standard"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

storageClass_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-storageClass"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a value indicating the name of the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
provisioner	string	True	<p>JSON string containing a value indicating the provisioner associated with the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
available	string	True	<p>JSON string indicating whether the storage class is available for the cluster or is eligible to be added to the cluster when under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "available" - The storage class is available for use • "eligible" - The storage class is eligible to be used by the cluster when it is under management • "ineligible" - The storage class is ineligible to be used by the cluster when it is under management

Name	Type	Required	Description
allowVolumeExpansion	string	True	<p>JSON string indicating whether the storage class allows volume expansion.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class allows volume expansion • "false" - The storage class does not allow volume expansion • "unavailable" - It is unknown whether the storage class allows volume expansion
reclaimPolicy	string	True	<p>JSON string containing a cloud-specific value indicating the retention policy of the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
volumeBindingMode	string	True	<p>JSON string containing a cloud-specific value indicating the binding mode for the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
isDefault	string	False	<p>JSON string indicating whether the storage class contains the default annotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class contains the default annotation

Name	Type	Required	Description
maxSnapshotCount	number	False	JSON number indicating how many snapshots are supported. This information is attached to storage classes provided by NetApp.
maxBackupCount	number	False	JSON number indicating how many backups are supported. This information is attached to storage classes provided by NetApp.
price	string	False	JSON string indicating the currency units per unit of time for the storage class. This information is attached to storage classes provided by NetApp. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
currency	string	False	JSON string indicating the ISO 4217 three-letter code for the currency that the price is measured in. This information is attached to storage classes provided by NetApp. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
performance	number	False	JSON number indicating the performance service-level objective (SLO) in MBps. This information is attached to storage classes provided by NetApp.
resilience	string	False	JSON string indicating the resilience configuration for the storage. This information is attached to storage classes provided by NetApp. Defined values are: <ul style="list-style-type: none"> "regional" - The volume will become unavailable if a given region becomes unavailable "multisite" - The volume will continue to be available if a given region becomes unavailable
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a storage class for a cloud

GET

/accounts/{account_id}/topology/v1/clouds/{cloud_id}/clusters/{cluster_id}/storageClasses/{storageClass_id}

Returns the stored Storage Class API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
cloud_id	string	path	True	ID of the containing cloud resource
cluster_id	string	path	True	ID of the containing cluster resource
storageClass_id	string	path	True	ID of the storageClass collection to list

Response

Status: 200, Returns the stored Storage Class API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-storageClass"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a value indicating the name of the storage class. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 255
provisioner	string	True	JSON string containing a value indicating the provisioner associated with the storage class. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 255

Name	Type	Required	Description
available	string	True	<p>JSON string indicating whether the storage class is available for the cluster or is eligible to be added to the cluster when under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "available" - The storage class is available for use • "eligible" - The storage class is eligible to be used by the cluster when it is under management • "ineligible" - The storage class is ineligible to be used by the cluster when it is under management
allowVolumeExpansion	string	True	<p>JSON string indicating whether the storage class allows volume expansion.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class allows volume expansion • "false" - The storage class does not allow volume expansion • "unavailable" - It is unknown whether the storage class allows volume expansion
reclaimPolicy	string	True	<p>JSON string containing a cloud-specific value indicating the retention policy of the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
volumeBindingMode	string	True	<p>JSON string containing a cloud-specific value indicating the binding mode for the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
isDefault	string	False	<p>JSON string indicating whether the storage class contains the default annotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class contains the default annotation
maxSnapshotCount	number	False	<p>JSON number indicating how many snapshots are supported.</p> <p>This information is attached to storage classes provided by NetApp.</p>
maxBackupCount	number	False	<p>JSON number indicating how many backups are supported.</p> <p>This information is attached to storage classes provided by NetApp.</p>
price	string	False	<p>JSON string indicating the currency units per unit of time for the storage class.</p> <p>This information is attached to storage classes provided by NetApp.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
currency	string	False	<p>JSON string indicating the ISO 4217 three-letter code for the currency that the price is measured in. This information is attached to storage classes provided by NetApp.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
performance	number	False	<p>JSON number indicating the performance service-level objective (SLO) in MBps. This information is attached to storage classes provided by NetApp.</p>
resilience	string	False	<p>JSON string indicating the resilience configuration for the storage. This information is attached to storage classes provided by NetApp.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "regional" - The volume will become unavailable if a given region becomes unavailable • "multisite" - The volume will continue to be available if a given region becomes unavailable

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-storageClass",
  "version": "1.1",
  "id": "ad9be22b-53c7-540c-8647-76afe2878952",
  "name": "my-storage-class",
  "provisioner": "csi.trident.netapp.io",
  "available": "eligible",
  "allowVolumeExpansion": "true",
  "reclaimPolicy": "recycle",
  "volumeBindingMode": "immediate",
  "isDefault": "true",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the storage classes for a cluster

GET /accounts/{account_id}/topology/v1/clusters/{cluster_id}/storageClasses

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
cluster_id	string	path	True	ID of the containing cluster resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: id,name
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: storageClass_1.1_get_response_body , array[]]	True	

Name	Type	Required	Description
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-storageClasses",
  "version": "1.1",
  "items": [
    [
      "e280ff62-be35-4f31-a31b-a210a1ad1b33",
      "my-storage-class"
    ],
    [
      "e8507dad-d33f-44b3-9c15-ec55ba6f6473",
      "standard"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

storageClass_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-storageClass"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a value indicating the name of the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
provisioner	string	True	<p>JSON string containing a value indicating the provisioner associated with the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
available	string	True	<p>JSON string indicating whether the storage class is available for the cluster or is eligible to be added to the cluster when under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "available" - The storage class is available for use • "eligible" - The storage class is eligible to be used by the cluster when it is under management • "ineligible" - The storage class is ineligible to be used by the cluster when it is under management

Name	Type	Required	Description
allowVolumeExpansion	string	True	<p>JSON string indicating whether the storage class allows volume expansion.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class allows volume expansion • "false" - The storage class does not allow volume expansion • "unavailable" - It is unknown whether the storage class allows volume expansion
reclaimPolicy	string	True	<p>JSON string containing a cloud-specific value indicating the retention policy of the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
volumeBindingMode	string	True	<p>JSON string containing a cloud-specific value indicating the binding mode for the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
isDefault	string	False	<p>JSON string indicating whether the storage class contains the default annotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class contains the default annotation

Name	Type	Required	Description
maxSnapshotCount	number	False	JSON number indicating how many snapshots are supported. This information is attached to storage classes provided by NetApp.
maxBackupCount	number	False	JSON number indicating how many backups are supported. This information is attached to storage classes provided by NetApp.
price	string	False	JSON string indicating the currency units per unit of time for the storage class. This information is attached to storage classes provided by NetApp. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
currency	string	False	JSON string indicating the ISO 4217 three-letter code for the currency that the price is measured in. This information is attached to storage classes provided by NetApp. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
performance	number	False	JSON number indicating the performance service-level objective (SLO) in MBps. This information is attached to storage classes provided by NetApp.
resilience	string	False	JSON string indicating the resilience configuration for the storage. This information is attached to storage classes provided by NetApp. Defined values are: <ul style="list-style-type: none"> "regional" - The volume will become unavailable if a given region becomes unavailable "multisite" - The volume will continue to be available if a given region becomes unavailable
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a storage class for a cluster

GET

/accounts/{account_id}/topology/v1/clusters/{cluster_id}/storageClasses/{storageClass_id}

Returns the stored Storage Class API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
cluster_id	string	path	True	ID of the containing cluster resource
storageClass_id	string	path	True	ID of the storageClass collection to list

Response

Status: 200, Returns the stored Storage Class API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-storageClass"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a value indicating the name of the storage class. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
provisioner	string	True	JSON string containing a value indicating the provisioner associated with the storage class. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
available	string	True	<p>JSON string indicating whether the storage class is available for the cluster or is eligible to be added to the cluster when under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "available" - The storage class is available for use • "eligible" - The storage class is eligible to be used by the cluster when it is under management • "ineligible" - The storage class is ineligible to be used by the cluster when it is under management
allowVolumeExpansion	string	True	<p>JSON string indicating whether the storage class allows volume expansion.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class allows volume expansion • "false" - The storage class does not allow volume expansion • "unavailable" - It is unknown whether the storage class allows volume expansion
reclaimPolicy	string	True	<p>JSON string containing a cloud-specific value indicating the retention policy of the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
volumeBindingMode	string	True	<p>JSON string containing a cloud-specific value indicating the binding mode for the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
isDefault	string	False	<p>JSON string indicating whether the storage class contains the default annotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class contains the default annotation
maxSnapshotCount	number	False	<p>JSON number indicating how many snapshots are supported.</p> <p>This information is attached to storage classes provided by NetApp.</p>
maxBackupCount	number	False	<p>JSON number indicating how many backups are supported.</p> <p>This information is attached to storage classes provided by NetApp.</p>
price	string	False	<p>JSON string indicating the currency units per unit of time for the storage class.</p> <p>This information is attached to storage classes provided by NetApp.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
currency	string	False	<p>JSON string indicating the ISO 4217 three-letter code for the currency that the price is measured in. This information is attached to storage classes provided by NetApp.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
performance	number	False	<p>JSON number indicating the performance service-level objective (SLO) in MBps. This information is attached to storage classes provided by NetApp.</p>
resilience	string	False	<p>JSON string indicating the resilience configuration for the storage. This information is attached to storage classes provided by NetApp.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "regional" - The volume will become unavailable if a given region becomes unavailable • "multisite" - The volume will continue to be available if a given region becomes unavailable

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-storageClass",
  "version": "1.1",
  "id": "ad9be22b-53c7-540c-8647-76afe2878952",
  "name": "my-storage-class",
  "provisioner": "csi.trident.netapp.io",
  "available": "eligible",
  "allowVolumeExpansion": "true",
  "reclaimPolicy": "recycle",
  "volumeBindingMode": "immediate",
  "isDefault": "true",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the storage classes for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/storageClasses

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: storageClass_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-storageClasses",
  "version": "1.1",
  "items": [
    [
      "e280ff62-be35-4f31-a31b-a210a1ad1b33",
      "my-storage-class"
    ],
    [
      "e8507dad-d33f-44b3-9c15-ec55ba6f6473",
      "standard"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

storageClass_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-storageClass"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	<p>JSON string containing a value indicating the name of the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
provisioner	string	True	<p>JSON string containing a value indicating the provisioner associated with the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
available	string	True	<p>JSON string indicating whether the storage class is available for the cluster or is eligible to be added to the cluster when under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "available" - The storage class is available for use • "eligible" - The storage class is eligible to be used by the cluster when it is under management • "ineligible" - The storage class is ineligible to be used by the cluster when it is under management

Name	Type	Required	Description
allowVolumeExpansion	string	True	<p>JSON string indicating whether the storage class allows volume expansion.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class allows volume expansion • "false" - The storage class does not allow volume expansion • "unavailable" - It is unknown whether the storage class allows volume expansion
reclaimPolicy	string	True	<p>JSON string containing a cloud-specific value indicating the retention policy of the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
volumeBindingMode	string	True	<p>JSON string containing a cloud-specific value indicating the binding mode for the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
isDefault	string	False	<p>JSON string indicating whether the storage class contains the default annotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class contains the default annotation

Name	Type	Required	Description
maxSnapshotCount	number	False	JSON number indicating how many snapshots are supported. This information is attached to storage classes provided by NetApp.
maxBackupCount	number	False	JSON number indicating how many backups are supported. This information is attached to storage classes provided by NetApp.
price	string	False	JSON string indicating the currency units per unit of time for the storage class. This information is attached to storage classes provided by NetApp. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
currency	string	False	JSON string indicating the ISO 4217 three-letter code for the currency that the price is measured in. This information is attached to storage classes provided by NetApp. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
performance	number	False	JSON number indicating the performance service-level objective (SLO) in MBps. This information is attached to storage classes provided by NetApp.
resilience	string	False	JSON string indicating the resilience configuration for the storage. This information is attached to storage classes provided by NetApp. Defined values are: <ul style="list-style-type: none"> "regional" - The volume will become unavailable if a given region becomes unavailable "multisite" - The volume will continue to be available if a given region becomes unavailable
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	

Name	Type	Required	Description
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a storage class for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/storageClasses/{storageClass_id}

Returns the stored Storage Class API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
storageClass_id	string	path	True	ID of the storageClass collection to list

Response

Status: 200, Returns the stored Storage Class API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-storageClass"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a value indicating the name of the storage class. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
provisioner	string	True	JSON string containing a value indicating the provisioner associated with the storage class. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
available	string	True	<p>JSON string indicating whether the storage class is available for the cluster or is eligible to be added to the cluster when under management.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "available" - The storage class is available for use • "eligible" - The storage class is eligible to be used by the cluster when it is under management • "ineligible" - The storage class is ineligible to be used by the cluster when it is under management
allowVolumeExpansion	string	True	<p>JSON string indicating whether the storage class allows volume expansion.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class allows volume expansion • "false" - The storage class does not allow volume expansion • "unavailable" - It is unknown whether the storage class allows volume expansion
reclaimPolicy	string	True	<p>JSON string containing a cloud-specific value indicating the retention policy of the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
volumeBindingMode	string	True	<p>JSON string containing a cloud-specific value indicating the binding mode for the storage class.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
isDefault	string	False	<p>JSON string indicating whether the storage class contains the default annotation.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The storage class contains the default annotation
maxSnapshotCount	number	False	<p>JSON number indicating how many snapshots are supported.</p> <p>This information is attached to storage classes provided by NetApp.</p>
maxBackupCount	number	False	<p>JSON number indicating how many backups are supported.</p> <p>This information is attached to storage classes provided by NetApp.</p>
price	string	False	<p>JSON string indicating the currency units per unit of time for the storage class.</p> <p>This information is attached to storage classes provided by NetApp.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

Name	Type	Required	Description
currency	string	False	<p>JSON string indicating the ISO 4217 three-letter code for the currency that the price is measured in. This information is attached to storage classes provided by NetApp.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
performance	number	False	<p>JSON number indicating the performance service-level objective (SLO) in MBps. This information is attached to storage classes provided by NetApp.</p>
resilience	string	False	<p>JSON string indicating the resilience configuration for the storage. This information is attached to storage classes provided by NetApp.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "regional" - The volume will become unavailable if a given region becomes unavailable • "multisite" - The volume will continue to be available if a given region becomes unavailable

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-storageClass",
  "version": "1.1",
  "id": "ad9be22b-53c7-540c-8647-76afe2878952",
  "name": "my-storage-class",
  "provisioner": "csi.trident.netapp.io",
  "available": "eligible",
  "allowVolumeExpansion": "true",
  "reclaimPolicy": "recycle",
  "volumeBindingMode": "immediate",
  "isDefault": "true",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Subscription

Subscription overview

The Subscription API provides access to subscription resources in order to represent active subscriptions.

Create a new subscription

POST /accounts/{account_id}/core/v1/subscriptions

Indicates desired values for the Subscription API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Request Body

Indicates desired values for the Subscription API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-subscription"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1""1.2"
customerProfileID	string	False	JSON string containing the customer profile ID from Authorize.net , which was invoked by the UI, is not set for the trial term. Returns an empty string during read operation, if not set. Defined values are: <ul style="list-style-type: none">Minimum length: 0Maximum length: 63

Name	Type	Required	Description
paymentFirstName	string	False	<p>JSON string containing a user-specified long-form first name used for payment billing. Specified only when the subscription is being rebilled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
paymentLastName	string	False	<p>JSON string containing a user-specified long-form last name used for payment billing. Specified only when the subscription is being rebilled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
paymentAddress	paymentAddress	False	<p>JSON object containing a collection of JSON strings specifying a billing address. Specified only when the subscription is being rebilled.</p> <p>If this key exists, all six of the contained JSON strings will be present. If nothing was provided by the user, the string will be empty.</p>
paymentProfileID	string	False	<p>JSON string containing the payment profile ID from Authorize.net that was invoked by the UI, not set for trial term.</p> <p>Returns an empty string during read operation if not set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63

Name	Type	Required	Description
paymentExpiry	string	False	<p>JSON string containing a timestamp indicating when the payment method expires. This is obtained from authorize.net(http://authorize.net) and is set by the UI.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This field is not returned for trial terms.</p>
marketplace	string	False	<p>JSON string indicating the marketplace for an account where payments will be recorded.</p> <p>Defined values:</p> <ul style="list-style-type: none"> • "netapp" • "azure" • "aws" • "gcp"
terms	string	True	<p>JSON string indicating the current tier of the account.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "trial" • "paid"

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-subscription",
  "version": "1.2",
  "terms": "trial"
}
```

Response

Status: 201, Returns the newly created subscription resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "application/astra-subscription"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
customerProfileID	string	True	JSON string containing the customer profile ID from Authorize.net , which was invoked by the UI, is not set for the trial term. Returns an empty string during read operation, if not set. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63
paymentProfileID	string	False	JSON string containing the payment profile ID from Authorize.net that was invoked by the UI, not set for trial term. Returns an empty string during read operation if not set. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63

Name	Type	Required	Description
paymentExpiry	string	False	<p>JSON string containing a timestamp indicating when the payment method expires. This is obtained from authorize.net](http://authorize.net) and is set by the UI.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This field is not returned for trial terms.</p>
purchaseOrderNumber	string	False	<p>JSON string containing the purchase order number for the payment method.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
marketplace	string	False	<p>JSON string indicating the marketplace for an account where payments will be recorded.</p> <p>Defined values:</p> <ul style="list-style-type: none"> • "netapp" • "azure" • "aws" • "gcp"
licenseSN	string	False	<p>JSON string containing the license serial number for the payment method.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
terms	string	True	JSON string indicating the current tier of the account. Defined values are: <ul style="list-style-type: none"> • "trial" • "paid"
status	string	True	JSON string indicating the current status of the subscription. Defined values are: <ul style="list-style-type: none"> • "active" • "inactive"
appLimit	number	True	JSON number indicating the application limit for this subscription. Value of -1 indicates no limit.
namespaceLimit	number	True	JSON number indicating the namespace limit for this subscription. Value of -1 indicates no limit.
subscriptionPeriod	number	True	JSON number indicating the subscription period. Value of -1 indicates no limit. Unit: days
gracePeriod	number	True	JSON number indicating the grace period after the trial subscription has expired or a paid subscription is canceled. Unit: days
reminderBeforePeriod	number	True	JSON number indicating the number of days before the end of the trial subscription when the customer notifications will begin. The value is expressed in days with a value of -1 indicating it's not applicable.

Name	Type	Required	Description
onboardStatus	string	True	<p>JSON string indicating the current status of customer onboarding. Valid values are "not started", "in progress", "success", "failed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "not started" • "in progress" • "success" • "failed"
costPerAppUnit	number	True	<p>JSON number indicating the cost per app unit. For a trial version, the value is 0. Unit: US dollars</p>
costPerNamespaceUnit	number	True	<p>JSON number indicating the cost per namespace unit. For a trial version, the value is 0. Unit: US dollars</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-subscription",
  "version": "1.2",
  "id": "40b4106f-b743-5d83-95c7-d539b2b45f63",
  "customerProfileID": "2157047189",
  "paymentProfileID": "E7CEB0A9F1BECA32A02493E1B31D5955",
  "paymentExpiry": "2022-02-01T00:00:00Z",
  "purchaseOrderNumber": "72384632",
  "marketplace": "netapp",
  "licenseSN": "278343",
  "terms": "trial",
  "status": "active",
  "appLimit": 0,
  "namespaceLimit": 10,
  "subscriptionPeriod": 90,
  "gracePeriod": 7,
  "reminderBeforePeriod": 30,
  "onboardStatus": "in progress",
  "costPerAppUnit": 0,
  "costPerNamespaceUnit": 0.005,
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

paymentAddress

JSON object containing a collection of JSON strings specifying a billing address. Specified only when the subscription is being rebilled.

If this key exists, all six of the contained JSON strings will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and more. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all subscriptions

GET /accounts/{account_id}/core/v1/subscriptions

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>

Name	Type	In	Required	Description
continue		query	False	<p>Indicates the token to resume listing from.</p> <p>URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue></p> <p>OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue>&lt;/continue&gt;</p>
count	string	query	False	<p>Indicates if the total number of resources should be returned in the metadata object.</p> <p>URL examples: "count=true"</p> <p>OpenAPI examples: "true"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p>
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
orderBy	string	query	False	Indicates the sort order of resource when listing a collection. URL examples: "orderBy=name", "orderBy=name%20desc" OpenAPI examples: "name desc"
skip	string	query	False	Indicates the number of resources to skip over when listing a collection. URL examples: "skip=1" OpenAPI examples: "1"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: subscription_1.2_get_response_body, array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-subscriptions",
  "version": "1.2",
  "items": [
    {
      "type": "application/astra-subscription",
      "version": "1.1",
      "id": "d4c865c9-64a7-4661-ae4a-3307dffcd3da",
      "customerProfileID": "2157047189",
      "paymentProfileID": "E7CEB0A9F1BECA32A02493E1B31D5955",
      "paymentExpiry": "2022-02-01T00:00:00Z",
      "purchaseOrderNumber": "72384632",
      "marketplace": "netapp",
      "licenseSN": "278343",
      "terms": "trial",
      "status": "inactive",
      "appLimit": 0,
      "namespaceLimit": 10,
      "subscriptionPeriod": 90,
      "gracePeriod": 7,
      "reminderBeforePeriod": 30,
      "onboardStatus": "success",
      "costPerAppUnit": 0,
      "costPerNamespaceUnit": 0.005,
      "metadata": {
        "labels": [],
        "creationTimestamp": "2020-05-06T12:24:52.256624Z",
        "modificationTimestamp": "2020-05-06T12:24:52.256624Z",
        "createdBy": "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa"
      }
    },
    {
      "type": "application/astra-subscription",
      "version": "1.1",
      "id": "4c43ed8b-078f-4fe3-b8c6-5d515f6382e6",
      "customerProfileID": "2157047189",
      "paymentProfileID": "E7CEB0A9F1BECA32A02493E1B31D5955",
      "paymentExpiry": "2022-05-01T00:00:00Z",
      "purchaseOrderNumber": "92374658",
      "marketplace": "netapp",
      "licenseSN": "374623",
      "terms": "paid",
      "status": "active",
      "appLimit": 0,
    }
  ]
}
```

```

"namespaceLimit": -1,
"subscriptionPeriod": -1,
"gracePeriod": -1,
"reminderBeforePeriod": -1,
"onboardStatus": "success",
"costPerAppUnit": 0,
"costPerNamespaceUnit": 0.005,
"metadata": {
  "labels": [],
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
  "createdBy": "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa"
}
],
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

subscription_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-subscription"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"

Name	Type	Required	Description
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
customerProfileID	string	True	JSON string containing the customer profile ID from Authorize.net , which was invoked by the UI, is not set for the trial term. Returns an empty string during read operation, if not set. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63
paymentProfileID	string	False	JSON string containing the payment profile ID from Authorize.net that was invoked by the UI, not set for trial term. Returns an empty string during read operation if not set. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63
paymentExpiry	string	False	JSON string containing a timestamp indicating when the payment method expires. This is obtained from authorize.net (http://authorize.net) and is set by the UI. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema This field is not returned for trial terms.

Name	Type	Required	Description
purchaseOrderNumber	string	False	JSON string containing the purchase order number for the payment method. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
marketplace	string	False	JSON string indicating the marketplace for an account where payments will be recorded. Defined values: <ul style="list-style-type: none"> • "netapp" • "azure" • "aws" • "gcp"
licenseSN	string	False	JSON string containing the license serial number for the payment method. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
terms	string	True	JSON string indicating the current tier of the account. Defined values are: <ul style="list-style-type: none"> • "trial" • "paid"
status	string	True	JSON string indicating the current status of the subscription. Defined values are: <ul style="list-style-type: none"> • "active" • "inactive"

Name	Type	Required	Description
appLimit	number	True	JSON number indicating the application limit for this subscription. Value of -1 indicates no limit.
namespaceLimit	number	True	JSON number indicating the namespace limit for this subscription. Value of -1 indicates no limit.
subscriptionPeriod	number	True	JSON number indicating the subscription period. Value of -1 indicates no limit. Unit: days
gracePeriod	number	True	JSON number indicating the grace period after the trial subscription has expired or a paid subscription is canceled. Unit: days
reminderBeforePeriod	number	True	JSON number indicating the number of days before the end of the trial subscription when the customer notifications will begin. The value is expressed in days with a value of -1 indicating it's not applicable.
onboardStatus	string	True	JSON string indicating the current status of customer onboarding. Valid values are "not started", "in progress", "success", "failed". Defined values are: <ul style="list-style-type: none"> • "not started" • "in progress" • "success" • "failed"

Name	Type	Required	Description
costPerAppUnit	number	True	JSON number indicating the cost per app unit. For a trial version, the value is 0. Unit: US dollars
costPerNamespaceUnit	number	True	JSON number indicating the cost per namespace unit. For a trial version, the value is 0. Unit: US dollars
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a subscription

GET /accounts/{account_id}/core/v1/subscriptions/{subscription_id}

Returns the stored Subscription API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: <code>{{.Account}}</code>
subscription_id	string	path	True	ID of the subscription collection to list

Response

Status: 200, Returns the stored Subscription API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-subscription"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
customerProfileID	string	True	JSON string containing the customer profile ID from Authorize.net , which was invoked by the UI, is not set for the trial term. Returns an empty string during read operation, if not set. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63
paymentProfileID	string	False	JSON string containing the payment profile ID from Authorize.net that was invoked by the UI, not set for trial term. Returns an empty string during read operation if not set. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63

Name	Type	Required	Description
paymentExpiry	string	False	<p>JSON string containing a timestamp indicating when the payment method expires. This is obtained from authorize.net](http://authorize.net) and is set by the UI.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This field is not returned for trial terms.</p>
purchaseOrderNumber	string	False	<p>JSON string containing the purchase order number for the payment method.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
marketplace	string	False	<p>JSON string indicating the marketplace for an account where payments will be recorded.</p> <p>Defined values:</p> <ul style="list-style-type: none"> • "netapp" • "azure" • "aws" • "gcp"
licenseSN	string	False	<p>JSON string containing the license serial number for the payment method.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
terms	string	True	JSON string indicating the current tier of the account. Defined values are: <ul style="list-style-type: none"> • "trial" • "paid"
status	string	True	JSON string indicating the current status of the subscription. Defined values are: <ul style="list-style-type: none"> • "active" • "inactive"
appLimit	number	True	JSON number indicating the application limit for this subscription. Value of -1 indicates no limit.
namespaceLimit	number	True	JSON number indicating the namespace limit for this subscription. Value of -1 indicates no limit.
subscriptionPeriod	number	True	JSON number indicating the subscription period. Value of -1 indicates no limit. Unit: days
gracePeriod	number	True	JSON number indicating the grace period after the trial subscription has expired or a paid subscription is canceled. Unit: days
reminderBeforePeriod	number	True	JSON number indicating the number of days before the end of the trial subscription when the customer notifications will begin. The value is expressed in days with a value of -1 indicating it's not applicable.

Name	Type	Required	Description
onboardStatus	string	True	<p>JSON string indicating the current status of customer onboarding. Valid values are "not started", "in progress", "success", "failed".</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "not started" • "in progress" • "success" • "failed"
costPerAppUnit	number	True	<p>JSON number indicating the cost per app unit. For a trial version, the value is 0. Unit: US dollars</p>
costPerNamespaceUnit	number	True	<p>JSON number indicating the cost per namespace unit. For a trial version, the value is 0. Unit: US dollars</p>
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-subscription",
  "version": "1.2",
  "id": "40b4106f-b743-5d83-95c7-d539b2b45f63",
  "customerProfileID": "2157047189",
  "paymentProfileID": "E7CEB0A9F1BECA32A02493E1B31D5955",
  "paymentExpiry": "2022-02-01T00:00:00Z",
  "purchaseOrderNumber": "72384632",
  "marketplace": "netapp",
  "licenseSN": "278343",
  "terms": "trial",
  "status": "active",
  "onboardStatus": "success",
  "costPerAppUnit": 0,
  "costPerNamespaceUnit": 0.005,
  "appLimit": 0,
  "namespaceLimit": 10,
  "subscriptionPeriod": 90,
  "gracePeriod": 7,
  "reminderBeforePeriod": 30,
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a subscription

PUT /accounts/{account_id}/core/v1/subscriptions/{subscription_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the user cancels the subscription, the PUT endpoint must be called with "status": "inactive".

- When the status is set to "inactive", the pending charges for this subscription are sent to Zuora and the Zuora subscription will be marked as "inactive" in some way.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
subscription_id	string	path	True	ID of the subscription collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- If the user cancels the subscription, the PUT endpoint must be called with "status": "inactive".
- When the status is set to "inactive", the pending charges for this subscription are sent to Zuora and the Zuora subscription will be marked as "inactive" in some way.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-subscription"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1" • "1.2"
id	string	False	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
customerProfileID	string	False	<p>JSON string containing the customer profile ID from Authorize.net, which was invoked by the UI, is not set for the trial term. Returns an empty string during read operation, if not set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63
paymentFirstName	string	False	<p>JSON string containing a user-specified long-form first name used for payment billing. Specified only when the subscription is being rebilled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
paymentLastName	string	False	<p>JSON string containing a user-specified long-form last name used for payment billing. Specified only when the subscription is being rebilled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
paymentAddress	paymentAddress	False	<p>JSON object containing a collection of JSON strings specifying a billing address. Specified only when the subscription is being rebilled.</p> <p>If this key exists, all six of the contained JSON strings will be present. If nothing was provided by the user, the string will be empty.</p>

Name	Type	Required	Description
paymentProfileID	string	False	<p>JSON string containing the payment profile ID from Authorize.net that was invoked by the UI, not set for trial term. Returns an empty string during read operation if not set.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63
paymentExpiry	string	False	<p>JSON string containing a timestamp indicating when the payment method expires. This is obtained from authorize.net (http://authorize.net) and is set by the UI.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema <p>This field is not returned for trial terms.</p>
purchaseOrderNumber	string	False	<p>JSON string containing the purchase order number for the payment method.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
marketplace	string	False	JSON string indicating the marketplace for an account where payments will be recorded. Defined values: <ul style="list-style-type: none">"netapp""azure""aws""gcp"
licenseSN	string	False	JSON string containing the license serial number for the payment method. Defined values are: <ul style="list-style-type: none">Minimum length: 1Maximum length: 31
terms	string	False	JSON string indicating the current tier of the account. Defined values are: <ul style="list-style-type: none">"trial""paid"
status	string	False	JSON string indicating the current status of the subscription. Defined values are: <ul style="list-style-type: none">"active""inactive"
appLimit	number	False	JSON number indicating the application limit for this subscription. Value of -1 indicates no limit.
namespaceLimit	number	False	JSON number indicating the namespace limit for this subscription. Value of -1 indicates no limit.

Name	Type	Required	Description
subscriptionPeriod	number	False	JSON number indicating the subscription period. Value of -1 indicates no limit. Unit: days
gracePeriod	number	False	JSON number indicating the grace period after the trial subscription has expired or a paid subscription is canceled. Unit: days
reminderBeforePeriod	number	False	JSON number indicating the number of days before the end of the trial subscription when the customer notifications will begin. The value is expressed in days with a value of -1 indicating it's not applicable.
onboardStatus	string	False	JSON string indicating the current status of customer onboarding. Valid values are "not started", "in progress", "success", "failed". Defined values are: <ul style="list-style-type: none"> • "not started" • "in progress" • "success" • "failed"
costPerAppUnit	number	False	JSON number indicating the cost per app unit. For a trial version, the value is 0. Unit: US dollars
costPerNamespaceUnit	number	False	JSON number indicating the cost per namespace unit. For a trial version, the value is 0. Unit: US dollars

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-subscription",
  "version": "1.2",
  "customerProfileID": "2157047189",
  "paymentProfileID": "E7CEB0A9F1BECA32A02493E1B31D5955",
  "paymentExpiry": "2022-05-01T00:00:00Z"
}
```

Response

Status: 204, Indicates if the subscription resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

paymentAddress

JSON object containing a collection of JSON strings specifying a billing address. Specified only when the subscription is being rebilled.

If this key exists, all six of the contained JSON strings will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 0• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and more. Defined values are: <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a subscription

DELETE /accounts/{account_id}/core/v1/subscriptions/{subscription_id}

Removes the specified Subscription API resource.

Side Effects

- Subscription is deleted along with all the charges associated with it.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
subscription_id	string	path	True	ID of the subscription collection to list

Response

Status: 204, Indicates if the subscription resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Task

Task overview

The Task App API provides access to managed task resources in order to represent long-running tasks.

List all tasks

GET /accounts/{account_id}/core/v1/tasks

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
include	string	query	False	Indicates which fields should be returned when listing a collection. <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p>
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: task_1.1_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-tasks",
  "version": "1.1",
  "items": [
    {
      "type": "application/astra-task",
      "version": "1.0",
      "id": "ae1e6561-9e22-406c-8a5a-762f4604da00",
      "name": "astra.backup.prep",
      "summary": "Backup preparation",
      "description": "Task to prepare for the application backup",
      "service": "nautilus",
      "parentTaskID": "9cc8c321-6af1-406c-8158-2c6582c247f8",
      "userID": "abda967f-cd2c-4237-908e-99266648c553",
      "resourceID": "626a0978-d55f-4841-8b7c-dc0c0f592c6f",
      "resourceURI": "/accounts/fdaa655c-15ab-4d34-aa61-1e9098e67be0/k8s/v1/apps/7c8bef49-697e-4fb4-810c-675cef4cf6c9/appSnaps/5cb608f9-571b-492e-a520-5bfb900a9b9c",
      "resourceCollectionURI": [
        "/accounts/fdaa655c-15ab-4d34-aa61-1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-c8f7f176cd14/namespaces/f8b58091-4b9c-4c64-9b40-018dbaf7c5de/apps/f670bf11-8850-44bd-b330-815af6186a06/appSnaps/5cb608f9-571b-492e-a520-5bfb900a9b9c",
        "/accounts/fdaa655c-15ab-4d34-aa61-1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-c8f7f176cd14/namespaces/923708f8-0435-45b5-8c00-fbdef3ffaf25/apps/f670bf11-8850-44bd-b330-815af6186a06/appSnaps/5cb608f9-571b-492e-a520-5bfb900a9b9c"
      ],
      "state": "running",
      "stateTransitions": [
        {
          "from": "running",
          "to": [
            "paused",
            "cancelled"
          ]
        },
        {
          "from": "paused",
          "to": [

```

```

        "running",
        "cancelled"
    ]
}
],
"stateDetails": [],
"orderHint": 0,
"percentDone": 20.25,
"startTime": "2020-08-06T12:24:52.256624Z",
"metadata": {
    "labels": [],
    "creationTimestamp": "2020-08-06T12:24:52.256624Z",
    "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
    "createdBy": "00000000-0000-0000-0000-000000000000"
}
},
{
    "type": "application/astra-task",
    "version": "1.0",
    "id": "bc1e6561-9e22-406c-8a5a-762f4604da00",
    "name": "astra.backup",
    "summary": "Backup",
    "description": "Task to take a Backup for an application",
    "service": "nautilus",
    "userID": "abda967f-cd2c-4237-908e-99266648c553",
    "resourceID": "736a0978-d55f-4841-8b7c-dc0c0f592c6f",
    "resourceURI": "/accounts/fdaa655c-15ab-4d34-aa61-1e9098e67be0/k8s/v1/apps/7c8bef49-697e-4fb4-810c-675cef4cf6c9/appBackups/736a0978-d55f-4841-8b7c-dc0c0f592c6f",
    "resourceCollectionURI": [
        "/accounts/fdaa655c-15ab-4d34-aa61-1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-c8f7f176cd14/namespaces/f8b58091-4b9c-4c64-9b40-018dbaf7c5de/apps/f670bf11-8850-44bd-b330-815af6186a06/appBackups/736a0978-d55f-4841-8b7c-dc0c0f592c6f",
        "/accounts/fdaa655c-15ab-4d34-aa61-1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-c8f7f176cd14/namespaces/923708f8-0435-45b5-8c00-fbdef3ffaf25/apps/f670bf11-8850-44bd-b330-815af6186a06/appBackups/736a0978-d55f-4841-8b7c-dc0c0f592c6f"
    ],
    "state": "completed",
    "stateTransitions": [
        {

```



```

    "from": "running",
    "to": [
      "paused",
      "cancelled"
    ]
  },
  {
    "from": "paused",
    "to": [
      "running",
      "cancelled"
    ]
  }
],
"stateDetails": [],
"orderHint": 0,
"percentDone": 100,
"startTime": "2020-08-06T12:24:52.256624Z",
"endTime": "2020-08-06T12:26:52.256624Z",
"metadata": {
  "labels": [],
  "creationTimestamp": "2020-08-06T12:24:52.256624Z",
  "modificationTimestamp": "2020-08-06T12:24:52.256624Z",
  "createdBy": "00000000-0000-0000-0000-000000000000"
}
},
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

task_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-task"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a dot notation (.) hierarchical name for the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 127 • Defined regex is: <code>"^[a-z](\.[a-z])+\$"</code>
summary	string	True	JSON string containing the short-form summary of the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 63
description	string	True	JSON string containing a description of the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511

Name	Type	Required	Description
service	string	False	JSON string containing the name of the service that is managing the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
parentTaskID	string	False	JSON string containing a globally unique identifier of a parent task of the task. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
userID	string	False	JSON string containing the user ID associated with a task. Only included for tasks associated with user-initiated actions. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
resourceID	string	True	JSON string containing a globally unique identifier of the resource associated with the task. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
resourceURI	string	True	JSON string containing the URI associated with the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095

Name	Type	Required	Description
resourceCollectionURI	array[string]	True	<p>JSON array of JSON strings, each indicating the fully-expanded access URL of the resource associated with the task.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
state	string	True	<p>JSON string containing a value indicating the operational state of the task.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "notStarted" - The task has not started executing. • "running" - The task is running. • "completed" - The task has completed. • "pausing" - The task was requested to pause. • "paused" - The task is paused. • "cancelling" - The task was requested to cancel. • "cancelled" - The task is cancelled. • "failed" - The task has failed. • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	True	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state. Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 <p>For example:</p> <pre>"stateTransitions" : [{ "from": "running", "to": ["paused", "cancelled"] }, { "from": "paused", "to": ["running", "cancelled"] },]</pre>
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current "state". This field indicates when there are conditions or errors that prevent the actual state from matching the desired state. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
orderHint	number	False	<p>JSON number representing the order of subtasks. This field can be used by the client to sort subtasks from smallest to largest.</p>

Name	Type	Required	Description
percentDone	number	False	JSON number containing the percentage complete for a running task. When the task is completed, this is set to "100".
startTime	string	False	JSON string containing the timestamp indicating when the task started. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
endTime	string	False	JSON string containing the timestamp indicating when the task ended. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
cancelTime	string	False	JSON string containing the timestamp indicating when the task was cancelled. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

[type_astra_metadata_list](#)

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a task

GET /accounts/{account_id}/core/v1/tasks/{task_id}

Returns the stored Task API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
task_id	string	path	True	ID of the task collection to list

Response

Status: 200, Returns the stored Task API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-task"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a dot notation (.) hierarchical name for the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 127 • Defined regex is: <code>"^[a-z](\.[a-z])+\$"</code>
summary	string	True	JSON string containing the short-form summary of the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 63
description	string	True	JSON string containing a description of the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 511

Name	Type	Required	Description
service	string	False	JSON string containing the name of the service that is managing the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31
parentTaskID	string	False	JSON string containing a globally unique identifier of a parent task of the task. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
userID	string	False	JSON string containing the user ID associated with a task. Only included for tasks associated with user-initiated actions. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
resourceID	string	True	JSON string containing a globally unique identifier of the resource associated with the task. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
resourceURI	string	True	JSON string containing the URI associated with the task. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095

Name	Type	Required	Description
resourceCollectionURI	array[string]	True	<p>JSON array of JSON strings, each indicating the fully-expanded access URL of the resource associated with the task. Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
state	string	True	<p>JSON string containing a value indicating the operational state of the task. Defined values are:</p> <ul style="list-style-type: none"> • "notStarted" - The task has not started executing. • "running" - The task is running. • "completed" - The task has completed. • "pausing" - The task was requested to pause. • "paused" - The task is paused. • "cancelling" - The task was requested to cancel. • "cancelled" - The task is cancelled. • "failed" - The task has failed. • Minimum length: 1 • Maximum length: 31

Name	Type	Required	Description
stateTransitions	array[type_astra_stateTransition]	True	<p>JSON array of JSON objects, each representing the set of permitted state transitions from a given defined state.</p> <p>Each JSON object contains the fields "from" and "to", where the "from" value is the name of a state, and the "to" value is an array of permitted destination states.</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 31 <p>For example:</p> <pre>"stateTransitions" : [{ "from": "running", "to": ["paused", "cancelled"] }, { "from": "paused", "to": ["running", "cancelled"] },]</pre>
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current "state". This field indicates when there are conditions or errors that prevent the actual state from matching the desired state.</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
orderHint	number	False	<p>JSON number representing the order of subtasks.</p> <p>This field can be used by the client to sort subtasks from smallest to largest.</p>

Name	Type	Required	Description
percentDone	number	False	JSON number containing the percentage complete for a running task. When the task is completed, this is set to "100".
startTime	string	False	JSON string containing the timestamp indicating when the task started. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
endTime	string	False	JSON string containing the timestamp indicating when the task ended. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
cancelTime	string	False	JSON string containing the timestamp indicating when the task was cancelled. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-task",
  "version": "1.1",
  "id": "26e8e8ef-5549-5928-98dd-2c3d43a608e8",
  "name": "astra.backup.prep",
  "summary": "Backup preparation",
  "description": "Task to prepare for the application backup",
  "service": "nautilus",
  "userID": "abda967f-cd2c-4237-908e-99266648c553",
  "parentTaskID": "9cc8c321-6af1-406c-8158-2c6582c247f8",
  "resourceID": "626a0978-d55f-4841-8b7c-dc0c0f592c6f",
  "resourceURI": "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/k8s/v1/apps/7c8bef49-697e-4fb4-810c-
675cef4cf6c9/appSnaps/2b6dafc3-2172-4431-a482-6306b2703130",
  "resourceCollectionURI": [
    "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/f8b58091-4b9c-4c64-9b40-
018dbaf7c5de/apps/f670bf11-8850-44bd-b330-
815af6186a06/appSnaps/2b6dafc3-2172-4431-a482-6306b2703130",
    "/accounts/fdaa655c-15ab-4d34-aa61-
1e9098e67be0/topology/v1/clouds/0df3f1a0-7203-4c12-aabf-
a7bee6302671/clusters/dfd9de2d-6f0b-437b-a737-
c8f7f176cd14/namespaces/923708f8-0435-45b5-8c00-
fbdef3ffaf25/apps/f670bf11-8850-44bd-b330-
815af6186a06/appSnaps/2b6dafc3-2172-4431-a482-6306b2703130"
  ],
  "state": "running",
  "stateTransitions": [
    {
      "from": "running",
      "to": [
        "paused",
        "cancelled"
      ]
    },
    {
      "from": "paused",
      "to": [
        "running",
        "cancelled"
      ]
    }
  ]
}
```

```

],
"stateDetails": [],
"orderHint": 0,
"percentDone": 20.25,
"startTime": "2020-08-06T12:24:52.256624Z",
"endTime": "2020-08-06T12:26:52.256624Z",
"metadata": {
  "labels": [],
  "creationTimestamp": "2022-10-06T20:58:16.305662Z",
  "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
  "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
}
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```

{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}

```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateTransition

Name	Type	Required	Description
from	string	True	
to	array[string]	True	

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Token

Token overview

The Token API enables users to create and manage API access tokens.

Create a new token for a user in a group

POST /accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/tokens

Indicates desired values for the Token API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource

Request Body

Indicates desired values for the Token API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-token"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"

Name	Type	Required	Description
name	string	True	<p>JSON string containing a token name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "name": "Snapshot Script"
}
```

Response

Status: 201, Returns the newly created token resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-token"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a token name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
userID	string	True	JSON string containing the UUID for the user that the token is associated with. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
token	string	True	<p>JSON string containing a base64-encoded system-generated API token.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "id": "822fab12-c224-5d1f-8118-5fb5d2def8b9",
  "name": "Snapshot Script",
  "userID": "09f8933c-ad74-4f4e-8ef5-1ffaa0fb8e9b",
  "token": "QSBKV1QgVG9rZW4gd291bGQgZ28gaGVyZS4=",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the tokens for a user in a group

GET /accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/tokens

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: id,name
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata=""></continue> OpenAPI examples: "<continue token="" from="" collection="" metadata=""></continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: token_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-tokens",
  "version": "1.0",
  "items": [
    [
      "4e99da96-152e-4aee-9207-4b6d04d2238d",
      "Snapshot Script"
    ],
    [
      "43ab09af-e558-4b1b-a6d5-49df7c39f22c",
      "Snapshot Taker"
    ],
    [
      "cca48856-9e25-4170-b49a-d32265c5e5f1",
      "Volume Checker"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

token_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-token"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	JSON string containing a token name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
userID	string	True	JSON string containing the UUID for the user that the token is associated with. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	

Name	Type	Required	Description
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a token for a user in a group

GET

```
/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/tokens/{token_id}
```

Returns the stored Token API resource in the JSON response body.

- The "token" key/value will not be returned.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
token_id	string	path	True	ID of the token collection to list

Response

Status: 200

Returns the stored Token API resource in the JSON response body.

- The "token" key/value will not be returned.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-token"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a token name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
userID	string	True	JSON string containing the UUID for the user that the token is associated with. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "id": "822fab12-c224-5d1f-8118-5fb5d2def8b9",
  "name": "Snapshot Script",
  "userID": "09f8933c-ad74-4f4e-8ef5-1ffaa0fb8e9b",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a token for a user in a group

PUT

```
/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/tokens/{token_id}
}
```

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
token_id	string	path	True	ID of the token collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-token"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>JSON string containing a token name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
userID	string	False	<p>JSON string containing the UUID for the user that the token is associated with.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "name": "New Token Name"
}
```

Response

Status: 204, Indicates if the token resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{  
  "type": "https://astra.netapp.io/problems/1",  
  "title": "Resource not found",  
  "detail": "The resource specified in the request URI wasn't found.",  
  "status": "404"  
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a token for a user in a group

DELETE

```
/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/tokens/{token_id}
```

Removes the specified Token API resource.

Side Effects

- The corresponding API token credential is removed from the credential service as a side effect.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: <code>{{.Account}}</code>
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
token_id	string	path	True	ID of the token collection to list

Response

Status: 204, Indicates if the token resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new token for a user

POST /accounts/{account_id}/core/v1/users/{user_id}/tokens

Indicates desired values for the Token API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
user_id	string	path	True	ID of the containing user resource

Request Body

Indicates desired values for the Token API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-token"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0"

Name	Type	Required	Description
name	string	True	<p>JSON string containing a token name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "name": "Snapshot Script"
}
```

Response

Status: 201, Returns the newly created token resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-token"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a token name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
userID	string	True	JSON string containing the UUID for the user that the token is associated with. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
token	string	True	<p>JSON string containing a base64-encoded system-generated API token.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the base64 Encoded Data Schema
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```

{
  "type": "application/astra-token",
  "version": "1.0",
  "id": "822fab12-c224-5d1f-8118-5fb5d2def8b9",
  "name": "Snapshot Script",
  "userID": "09f8933c-ad74-4f4e-8ef5-1ffaa0fb8e9b",
  "token": "QSBKV1QgVG9rZW4gd291bGQgZ28gaGVyZS4=",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the tokens for a user

GET /accounts/{account_id}/core/v1/users/{user_id}/tokens

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata=""></continue> OpenAPI examples: <continue token="" from="" collection="" metadata=""></continue></continue>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: token_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-tokens",
  "version": "1.0",
  "items": [
    [
      "4e99da96-152e-4aee-9207-4b6d04d2238d",
      "Snapshot Script"
    ],
    [
      "43ab09af-e558-4b1b-a6d5-49df7c39f22c",
      "Snapshot Taker"
    ],
    [
      "cca48856-9e25-4170-b49a-d32265c5e5f1",
      "Volume Checker"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

token_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-token"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	JSON string containing a token name. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
userID	string	True	JSON string containing the UUID for the user that the token is associated with. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	

Name	Type	Required	Description
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a token

GET /accounts/{account_id}/core/v1/users/{user_id}/tokens/{token_id}

Returns the stored Token API resource in the JSON response body.

- The "token" key/value will not be returned.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
token_id	string	path	True	ID of the token collection to list

Response

Status: 200

Returns the stored Token API resource in the JSON response body.

- The "token" key/value will not be returned.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-token"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema
name	string	True	JSON string containing a token name. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
userID	string	True	JSON string containing the UUID for the user that the token is associated with. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels.</p> <p>If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "id": "822fab12-c224-5d1f-8118-5fb5d2def8b9",
  "name": "Snapshot Script",
  "userID": "09f8933c-ad74-4f4e-8ef5-1ffaa0fb8e9b",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a token

PUT /accounts/{account_id}/core/v1/users/{user_id}/tokens/{token_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
token_id	string	path	True	ID of the token collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-token"
version	string	True	Version of the resource. Defined values are: • "1.0"
id	string	False	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	False	<p>JSON string containing a token name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.
userID	string	False	<p>JSON string containing the UUID for the user that the token is associated with.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "name": "New Token Name"
}
```

Response

Status: 204, Indicates if the token resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a token

DELETE /accounts/{account_id}/core/v1/users/{user_id}/tokens/{token_id}

Removes the specified Token API resource.

Side Effects

- The corresponding API token credential is removed from the credential service as a side effect.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
token_id	string	path	True	ID of the token collection to list

Response

Status: 204, Indicates if the token resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Unread Notification

Unread Notification overview

The Unread Notification API provides information on notifications that have not been read by a given user and to allow them to be marked as read.

List the unread notifications for a user in a group

GET

/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/unreadNotifications

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: notificationID,sequenceCount
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p> <ul style="list-style-type: none"> example: 2

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p> <ul style="list-style-type: none"> • example: count%20desc

Name	Type	In	Required	Description
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>
count	string	query	False	<p>Indicates if the total number of resources should be returned in the metadata object.</p> <p>URL examples: "count=true"</p> <p>OpenAPI examples: "true"</p> <ul style="list-style-type: none"> • example: true
continue		query	False	<p>Indicates the token to resume listing from.</p> <p>URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue></p> <p>OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue>&lt;/continue&gt;</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: unreadNotification_1.0_get_response_body, array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-unreadNotifications",
  "version": "1.0",
  "items": [
    [
      "4080cf5f-2261-4130-b8fb-8432e2e553e6",
      48923
    ],
    [
      "1b4e89f1-2e70-4a08-a015-e7064b0fb703",
      47345
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```


Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

unreadNotification_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-unreadNotification"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
notificationID	string	True	JSON string containing a notification ID that is to be marked as read by the user creating the mark. Defined values are: <ul style="list-style-type: none"><li data-bbox="1166 394 1393 493">• Conforms to the Astra Identifier Schema
sequenceCount	number	True	JSON number containing a sequence count associated with the notification specified by the notification ID.

Name	Type	Required	Description
severity	string	True	<p>JSON string containing one of the following values that indicate the severity of the event. Defined values are:</p> <ul style="list-style-type: none"> • "cleared" - Indicates that a previously reported event describing a condition is no longer active. An event with severity "cleared" will use the same summary and correlation ID to enable it to be matched up • "indeterminate" - Indicates that the severity cannot be determined • "informational" - Indicates a change in state that is both expected and normal (not defined in X.733) • "warning" - Indicates the detection of a potential or impending service-affecting fault before any significant effects have been felt • "critical" - Indicates that a service-affecting condition has occurred and immediate corrective action is required

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an unread notification for a user in a group

GET

/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/unreadNotifications/{unreadNotification_id}

Returns the stored Unread Notification API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
unreadNotification_id	string	path	True	ID of the unreadNotification collection to list

Response

Status: 200, Returns the stored Unread Notification API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-unreadNotification"
version	string	True	Version of the resource. Defined values are: • "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
notificationID	string	True	JSON string containing a notification ID that is to be marked as read by the user creating the mark. Defined values are: <ul style="list-style-type: none"><li data-bbox="1182 363 1479 426">• Conforms to the Astra Identifier Schema
sequenceCount	number	True	JSON number containing a sequence count associated with the notification specified by the notification ID.

Name	Type	Required	Description
severity	string	True	<p>JSON string containing one of the following values that indicate the severity of the event. Defined values are:</p> <ul style="list-style-type: none"> • "cleared" - Indicates that a previously reported event describing a condition is no longer active. An event with severity "cleared" will use the same summary and correlation ID to enable it to be matched up • "indeterminate" - Indicates that the severity cannot be determined • "informational" - Indicates a change in state that is both expected and normal (not defined in X.733) • "warning" - Indicates the detection of a potential or impending service-affecting fault before any significant effects have been felt • "critical" - Indicates that a service-affecting condition has occurred and immediate corrective action is required
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-unreadNotification",
  "version": "1.0",
  "id": "10df997b-629e-50f8-bc5f-a18b9a4ac5f6",
  "notificationID": "4080cf5f-2261-4130-b8fb-8432e2e553e6",
  "sequenceCount": 48923,
  "severity": "warning",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete an unread notification for a user in a group

DELETE

/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/unreadNotifications/{unreadNotification_id}

Removes the specified Unread Notification API resource.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the containing user resource
unreadNotification_id	string	path	True	ID of the unreadNotification collection to list

Response

Status: 204, Indicates if the unreadNotification resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the unread notifications for a user

GET /accounts/{account_id}/core/v1/users/{user_id}/unreadNotifications

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: <code>{{.Account}}</code>
user_id	string	path	True	ID of the containing user resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: <code>notificationID,sequenceCount</code>

Name	Type	In	Required	Description
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p> <ul style="list-style-type: none"> • example: 2
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Name	Type	In	Required	Description
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p> <ul style="list-style-type: none"> example: count%20desc
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>
count	string	query	False	<p>Indicates if the total number of resources should be returned in the metadata object.</p> <p>URL examples: "count=true"</p> <p>OpenAPI examples: "true"</p> <ul style="list-style-type: none"> example: true

Name	Type	In	Required	Description
continue		query	False	<p>Indicates the token to resume listing from.</p> <p>URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue></p> <p>OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue>&lt;/continue&gt;</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: unreadNotification_1.0_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-unreadNotifications",
  "version": "1.0",
  "items": [
    [
      "4080cf5f-2261-4130-b8fb-8432e2e553e6",
      48923
    ],
    [
      "1b4e89f1-2e70-4a08-a015-e7064b0fb703",
      47345
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

unreadNotification_1.0_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-unreadNotification"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
notificationID	string	True	JSON string containing a notification ID that is to be marked as read by the user creating the mark. Defined values are: <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema
sequenceCount	number	True	JSON number containing a sequence count associated with the notification specified by the notification ID.

Name	Type	Required	Description
severity	string	True	<p>JSON string containing one of the following values that indicate the severity of the event. Defined values are:</p> <ul style="list-style-type: none"> • "cleared" - Indicates that a previously reported event describing a condition is no longer active. An event with severity "cleared" will use the same summary and correlation ID to enable it to be matched up • "indeterminate" - Indicates that the severity cannot be determined • "informational" - Indicates a change in state that is both expected and normal (not defined in X.733) • "warning" - Indicates the detection of a potential or impending service-affecting fault before any significant effects have been felt • "critical" - Indicates that a service-affecting condition has occurred and immediate corrective action is required

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an unread notification

GET

/accounts/{account_id}/core/v1/users/{user_id}/unreadNotifications/{unreadNotification_id}

Returns the stored Unread Notification API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
user_id	string	path	True	ID of the containing user resource
unreadNotification_id	string	path	True	ID of the unreadNotification collection to list

Response

Status: 200, Returns the stored Unread Notification API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-unreadNotification"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
notificationID	string	True	JSON string containing a notification ID that is to be marked as read by the user creating the mark. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Identifier Schema

Name	Type	Required	Description
sequenceCount	number	True	JSON number containing a sequence count associated with the notification specified by the notification ID.
severity	string	True	<p>JSON string containing one of the following values that indicate the severity of the event. Defined values are:</p> <ul style="list-style-type: none"> • "cleared" - Indicates that a previously reported event describing a condition is no longer active. An event with severity "cleared" will use the same summary and correlation ID to enable it to be matched up • "indeterminate" - Indicates that the severity cannot be determined • "informational" - Indicates a change in state that is both expected and normal (not defined in X.733) • "warning" - Indicates the detection of a potential or impending service-affecting fault before any significant effects have been felt • "critical" - Indicates that a service-affecting condition has occurred and immediate corrective action is required

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-unreadNotification",
  "version": "1.0",
  "id": "10df997b-629e-50f8-bc5f-a18b9a4ac5f6",
  "notificationID": "4080cf5f-2261-4130-b8fb-8432e2e553e6",
  "sequenceCount": 48923,
  "severity": "warning",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```


Definitions

See Definitions

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Delete an unread notification

DELETE

/accounts/{account_id}/core/v1/users/{user_id}/unreadNotifications/{unreadNotification_id}

Removes the specified Unread Notification API resource.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the containing user resource
unreadNotification_id	string	path	True	ID of the unreadNotification collection to list

Response

Status: 204, Indicates if the unreadNotification resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Upgrade

Upgrade overview

The Upgrade App API provides access to software components that are eligible for upgrade, and to initiate upgrades. The availability of upgrades is determined based on packages registered with the Packages API.

List all upgrades

GET /accounts/{account_id}/core/v1/upgrades

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: id,componentName,upgradeVersion
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: upgrade_1.1_get_response_body, array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-upgrades",
  "version": "1.1",
  "items": [
    [
      "01982783-b1eb-4dca-a3fe-a385a3186c53",
      "acc",
      "21.07.1"
    ],
    [
      "0a5abab2-39b2-4101-87b9-0d9b8f537ca1",
      "acc",
      "21.07.2"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

upgrade_1.1_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-upgrade"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
componentName	string	True	JSON string containing the name of the type of software that can be upgraded. Defined values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident" • "kubernetes"
componentInstance	string	True	JSON string containing the URI of the component that can be upgraded. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
componentID	string	True	JSON string containing a globally unique identifier of the component that can be upgraded. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
upgradeVersion	string	True	<p>JSON string containing the SemVer of the software image file that can be upgraded to. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the SemVer Schema
currentVersion	string	True	<p>JSON string containing the current SemVer of the entity to be upgraded. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the SemVer Schema
dependencies	array[string]	True	<p>JSON array of JSON strings, each containing the UUID of an upgrade that must be completed before this upgrade can proceed. Used to determine which upgrades will be performed as prerequisites and in which order. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the upgrade.</p> <p>If auto-upgrade is enabled, upgrades will start in the "scheduled" state. Otherwise, upgrades will start in the "proposed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "unavailable" - The upgrade is not available at this time • "proposed" - The upgrade is proposed but will not automatically run until approved • "scheduled" - The upgrade is approved but is not ready to be installed due to dependencies, time windows, or available resources • "running" - The upgrade is in progress • "complete" - The upgrade has completed • "failed" - The upgrade did not complete

Name	Type	Required	Description
stateDesired	string	True	<p>JSON string containing a value indicating the desired state for "state". This field is only included when the user can directly request a change in the state of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "proposed" - The upgrade is not approved and must not be performed • "scheduled" - The upgrade is approved and must be performed in the specified time window • "running" - The upgrade must be performed immediately, regardless of the time window
stateDetails	array[type_astra_stateDe tail]	True	<p>JSON array of JSON objects that lists additional details about the current "state". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve an upgrade

GET /accounts/{account_id}/core/v1/upgrades/{upgrade_id}

Returns the stored Upgrade API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
upgrade_id	string	path	True	ID of the upgrade collection to list

Response

Status: 200, Returns the stored Upgrade API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">"application/astra-upgrade"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">"1.0""1.1"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">Conforms to the UUIDv4 Schema

Name	Type	Required	Description
componentName	string	True	<p>JSON string containing the name of the type of software that can be upgraded.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "acc" • "acs" • "trident" • "kubernetes"
componentInstance	string	True	<p>JSON string containing the URI of the component that can be upgraded.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
componentID	string	True	<p>JSON string containing a globally unique identifier of the component that can be upgraded.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
upgradeVersion	string	True	<p>JSON string containing the SemVer of the software image file that can be upgraded to.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the SemVer Schema
currentVersion	string	True	<p>JSON string containing the current SemVer of the entity to be upgraded.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the SemVer Schema

Name	Type	Required	Description
dependencies	array[string]	True	<p>JSON array of JSON strings, each containing the UUID of an upgrade that must be completed before this upgrade can proceed. Used to determine which upgrades will be performed as prerequisites and in which order.</p> <p>Defined values are:</p> <ul style="list-style-type: none">• Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the upgrade.</p> <p>If auto-upgrade is enabled, upgrades will start in the "scheduled" state. Otherwise, upgrades will start in the "proposed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "unavailable" - The upgrade is not available at this time • "proposed" - The upgrade is proposed but will not automatically run until approved • "scheduled" - The upgrade is approved but is not ready to be installed due to dependencies, time windows, or available resources • "running" - The upgrade is in progress • "complete" - The upgrade has completed • "failed" - The upgrade did not complete

Name	Type	Required	Description
stateDesired	string	True	<p>JSON string containing a value indicating the desired state for "state". This field is only included when the user can directly request a change in the state of the resource. Defined values are:</p> <ul style="list-style-type: none"> • "proposed" - The upgrade is not approved and must not be performed • "scheduled" - The upgrade is approved and must be performed in the specified time window • "running" - The upgrade must be performed immediately, regardless of the time window
stateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current "state". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-upgrade",
  "version": "1.1",
  "id": "aa9a8e88-c012-55b1-b514-7cd94dc79008",
  "componentName": "trident",
  "componentInstance": "https://<dns_name>/accounts/0b311ae7-d89a-4a11-
a52c-1349ca090415/topology/v1/clouds/fdda3ff3-a46a-43a4-902e-
444fde2baeba/storageBackends/72d19c3c-eb43-4bec-b23e-a228c900aded",
  "componentID": "72d19c3c-eb43-4bec-b23e-a228c900aded",
  "upgradeVersion": "21.07.1",
  "currentVersion": "21.04.1",
  "dependencies": [],
  "state": "scheduled",
  "stateDesired": "scheduled",
  "stateDetails": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify an upgrade

PUT /accounts/{account_id}/core/v1/upgrades/{upgrade_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Upgrades are scheduled or run based on desired state.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">• example: {{.Account}}
upgrade_id	string	path	True	ID of the upgrade collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Side Effects

- Upgrades are scheduled or run based on desired state.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-upgrade"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"

Name	Type	Required	Description
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
componentName	string	False	JSON string containing the name of the type of software that can be upgraded. Defined values are: <ul style="list-style-type: none"> • "acc" • "acs" • "trident" • "kubernetes"
componentInstance	string	False	JSON string containing the URI of the component that can be upgraded. Defined values are: <ul style="list-style-type: none"> • Minimum length: 3 • Maximum length: 4095
componentID	string	False	JSON string containing a globally unique identifier of the component that can be upgraded. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
upgradeVersion	string	False	JSON string containing the SemVer of the software image file that can be upgraded to. Defined values are: <ul style="list-style-type: none"> • Conforms to the SemVer Schema

Name	Type	Required	Description
currentVersion	string	False	<p>JSON string containing the current SemVer of the entity to be upgraded. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the SemVer Schema
dependencies	array[string]	False	<p>JSON array of JSON strings, each containing the UUID of an upgrade that must be completed before this upgrade can proceed. Used to determine which upgrades will be performed as prerequisites and in which order. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
state	string	False	<p>JSON string containing a value indicating the operational state of the upgrade.</p> <p>If auto-upgrade is enabled, upgrades will start in the "scheduled" state. Otherwise, upgrades will start in the "proposed" state.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "unavailable" - The upgrade is not available at this time • "proposed" - The upgrade is proposed but will not automatically run until approved • "scheduled" - The upgrade is approved but is not ready to be installed due to dependencies, time windows, or available resources • "running" - The upgrade is in progress • "complete" - The upgrade has completed • "failed" - The upgrade did not complete

Name	Type	Required	Description
stateDesired	string	False	<p>JSON string containing a value indicating the desired state for "state". This field is only included when the user can directly request a change in the state of the resource. Defined values are:</p> <ul style="list-style-type: none"> • "proposed" - The upgrade is not approved and must not be performed • "scheduled" - The upgrade is approved and must be performed in the specified time window • "running" - The upgrade must be performed immediately, regardless of the time window
stateDetails	array[type_astra_stateDetail]	False	<p>JSON array of JSON objects that lists additional details about the current "state". If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-upgrade",
  "version": "1.1",
  "stateDesired": "running"
}
```

Response

Status: 204, Indicates if the upgrade resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	

Name	Type	Required	Description
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{  
  "type": "https://astra.netapp.io/problems/1",  
  "title": "Resource not found",  
  "detail": "The resource specified in the request URI wasn't found.",  
  "status": "404"  
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

User

User overview

The User API represents users who are able to interact with the system.

Create a new user for a group

POST /accounts/{account_id}/core/v1/groups/{group_id}/users

Indicates desired values for the User API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
group_id	string	path	True	ID of the containing group resource

Request Body

Indicates desired values for the User API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-user"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
authID	string	False	JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".
firstName	string	False	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
lastName	string	False	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	<p>JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.</p>
sendWelcomeEmail	string	False	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "firstName": "John",
  "lastName": "Doe",
  "email": "<a href='mailto:jd@exampl.com'>jd@exampl.com</a>"
}
```

Response

Status: 201, Returns the newly created user resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "application/astra-user"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
state	string	True	JSON string containing a value indicating the operational state of the user. Defined values are: <ul style="list-style-type: none"> • "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value). • This state is not valid for a user with "authProvider" as "local" • "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true"). • This is the default value for a user with "authProvider" as "local" • "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).

Name	Type	Required	Description
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The user is allowed to log in; default value on create. • "false" - The user is not allowed to log in.
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider.</p> <p>The contents of this string depend on the specified authProvider.</p> <p>For a user with "authProvider" as "local", "authID" is set to the value of "email".</p> <p>For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".
firstName	string	True	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	<p>JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.</p>
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.)</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example response

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "id": "5bad8e04-e2fd-5c43-98d7-300580993f49",
  "state": "pending",
  "isEnabled": "true",
  "authID": "HteLK3hk28sdbDLKHReB",
  "authProvider": "cloud-central",
  "firstName": "John",
  "lastName": "Doe",
  "email": "<a href='mailto:jdoo@example.com'>jdoo@example.com</a>",
  "sendWelcomeEmail": "true",
  "lastActTimestamp": "2020-08-05T14:24:54.128427Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List the users for a group

GET /accounts/{account_id}/core/v1/groups/{group_id}/users

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> • example: id,email
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue> OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: user_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-users",
  "version": "1.2",
  "items": [
    [
      "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa",
      "<a href='mailto:jdoe@example.com'>jdoe@example.com</a>"
    ],
    [
      "e324ec3a-706d-4f57-a95d-1d88c03e7b73",
      "<a href='mailto:ssmith@example.com'>:ssmith@example.com</a>"
    ],
    [
      "3070c84d-129b-4017-82a8-2c26a42dd77e",
      "<a href='mailto:wjohns@example.com'>wjohns@example.com</a>"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

user_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-user"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the user.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value). • This state is not valid for a user with "authProvider" as "local" • "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true"). • This is the default value for a user with "authProvider" as "local" • "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The user is allowed to log in; default value on create. • "false" - The user is not allowed to log in.

Name	Type	Required	Description
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider.</p> <p>The contents of this string depend on the specified authProvider.</p> <p>For a user with "authProvider" as "local", "authID" is set to the value of "email".</p> <p>For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "ldap" - User authentication comes from an external LDAP server <p>In Astra Control Center, all users are required to have a value of "local", or "ldap". If a value is not specified, a default value of "local" is chosen.</p> <p>In Astra Control Service, "authProvider" as "local", or "ldap" is not supported. If a value is not specified, it will default to "cloud-central".</p>

Name	Type	Required	Description
firstName	string	True	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
lastName	string	True	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
email	string	True	JSON strings containing a user-specified email address.
phone	string	False	JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent. For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".

Name	Type	Required	Description
enableTimestamp	string	False	JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
lastActTimestamp	string	False	JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	

Name	Type	Required	Description
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a user for a group

GET /accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}

Returns the stored User API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the user collection to list

Response

Status: 200, Returns the stored User API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-user"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the user.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value). • This state is not valid for a user with "authProvider" as "local" • "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true"). • This is the default value for a user with "authProvider" as "local" • "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The user is allowed to log in; default value on create. • "false" - The user is not allowed to log in.

Name	Type	Required	Description
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider.</p> <p>The contents of this string depend on the specified authProvider.</p> <p>For a user with "authProvider" as "local", "authID" is set to the value of "email".</p> <p>For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "ldap" - User authentication comes from an external LDAP server <p>In Astra Control Center, all users are required to have a value of "local", or "ldap". If a value is not specified, a default value of "local" is chosen.</p> <p>In Astra Control Service, "authProvider" as "local", or "ldap" is not supported. If a value is not specified, it will default to "cloud-central".</p>

Name	Type	Required	Description
firstName	string	True	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
lastName	string	True	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
email	string	True	JSON strings containing a user-specified email address.
phone	string	False	JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".

Name	Type	Required	Description
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.)</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "id": "5bad8e04-e2fd-5c43-98d7-300580993f49",
  "state": "active",
  "isEnabled": "true",
  "authID": "HteLK3hk28sdbDLKHReB",
  "authProvider": "cloud-central",
  "firstName": "John",
  "lastName": "Doe",
  "companyName": "NetApp, Inc.",
  "email": "<a href='mailto:jd@exampl.com'>jd@exampl.com</a>",
  "phone": "408-555-2222",
  "postalAddress": {
    "addressCountry": "US",
    "addressLocality": "Sunnyvale",
    "addressRegion": "California",
    "postalCode": "94089",
    "streetAddress1": "495 East Java Drive"
  },
  "sendWelcomeEmail": "true",
  "enableTimestamp": "2020-08-05T14:24:54.128427Z",
  "lastActTimestamp": "2020-08-05T14:24:54.128427Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a user for a group

PUT /accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the user collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-user"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	False	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
state	string	False	JSON string containing a value indicating the operational state of the user. Defined values are: <ul style="list-style-type: none"> • "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value). • This state is not valid for a user with "authProvider" as "local" • "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true"). • This is the default value for a user with "authProvider" as "local" • "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).

Name	Type	Required	Description
isEnabled	string	False	<p>JSON string indicating if the user is allowed to log in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The user is allowed to log in; default value on create. • "false" - The user is not allowed to log in.
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider.</p> <p>The contents of this string depend on the specified authProvider.</p> <p>For a user with "authProvider" as "local", "authID" is set to the value of "email".</p> <p>For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "ldap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "ldap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "ldap" is not supported. If a value is not specified, it will default to "cloud-central".
firstName	string	False	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
lastName	string	False	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
email	string	False	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	<p>JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.</p>
sendWelcomeEmail	string	False	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.)</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema <p>If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</p>

Example request

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "firstName": "John",
  "lastName": "Dale",
  "email": "<a href='mailto:jdale@example.com'>jdale@example.com</a>"
}
```

Response

Status: 204, Indicates if the user resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a user for a group

DELETE /accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}

Removes the specified User API resource.

Side Effects

- The following resources associated with the user are deleted: notificationMarks, tokens, and all roleBindings referring to the user.
- For a user with "authProvider" as "local", the linked credential with "keyType" as "passwordHash" will also be deleted.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> • example: <code>{{.Account}}</code>
group_id	string	path	True	ID of the containing group resource
user_id	string	path	True	ID of the user collection to list

Response

Status: 204, Indicates if the user resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Create a new user

POST /accounts/{account_id}/core/v1/users

Indicates desired values for the User API resource to be created.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>

Request Body

Indicates desired values for the User API resource to be created.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-user"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
authID	string	False	JSON string containing the identifier associated with an external identity provider. The contents of this string depend on the specified authProvider. For a user with "authProvider" as "local", "authID" is set to the value of "email". For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".
firstName	string	False	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
lastName	string	False	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	<p>JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.</p>
sendWelcomeEmail	string	False	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".

Name	Type	Required	Description
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "firstName": "John",
  "lastName": "Doe",
  "email": "<a href='mailto:jdoe@example.com'>jdoe@example.com</a>"
}
```

Response

Status: 201, Returns the newly created user resource in the JSON response body.

Name	Type	Required	Description
type	string	True	<p>Media type of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "application/astra-user"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
state	string	True	JSON string containing a value indicating the operational state of the user. Defined values are: <ul style="list-style-type: none"> • "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value). • This state is not valid for a user with "authProvider" as "local" • "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true"). • This is the default value for a user with "authProvider" as "local" • "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).

Name	Type	Required	Description
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The user is allowed to log in; default value on create. • "false" - The user is not allowed to log in.
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider.</p> <p>The contents of this string depend on the specified authProvider.</p> <p>For a user with "authProvider" as "local", "authID" is set to the value of "email".</p> <p>For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "ldap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "ldap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "ldap" is not supported. If a value is not specified, it will default to "cloud-central".
firstName	string	True	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
lastName	string	True	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
email	string	True	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	<p>JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.</p>
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.)</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "id": "5bad8e04-e2fd-5c43-98d7-300580993f49",
  "state": "pending",
  "isEnabled": "true",
  "authID": "HteLK3hk28sdbDLKHReB",
  "authProvider": "cloud-central",
  "firstName": "John",
  "lastName": "Doe",
  "email": "<a href='mailto:jdoo@example.com'>jdoo@example.com</a>",
  "sendWelcomeEmail": "true",
  "lastActTimestamp": "2020-08-05T14:24:54.128427Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

List all users

GET /accounts/{account_id}/core/v1/users

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>

Name	Type	In	Required	Description
include	string	query	False	<p>Indicates which fields should be returned when listing a collection.</p> <p>URL examples: "include=id", "include=id,name"</p> <p>OpenAPI examples: "id"</p> <ul style="list-style-type: none"> example: id,email
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

Name	Type	In	Required	Description
filter	string	query	False	<p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> • eq - Equality • lt/gt - Less than/Greater than • lte/gte - Less than or equals to/Greater than or equals to <p>URL example: "filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples: "field eq 'value'"</p>
orderBy	string	query	False	<p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples: "orderBy=name", "orderBy=name%20desc"</p> <p>OpenAPI examples: "name desc"</p>
skip	string	query	False	<p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples: "skip=1"</p> <p>OpenAPI examples: "1"</p>

Name	Type	In	Required	Description
count	string	query	False	Indicates if the total number of resources should be returned in the metadata object. URL examples: "count=true" OpenAPI examples: "true"
continue		query	False	Indicates the token to resume listing from. URL examples: "continue=<continue token="" from="" collection="" metadata="">"</continue> OpenAPI examples: "<continue token="" from="" collection="" metadata="">"</continue></continue>"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: user_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-users",
  "version": "1.2",
  "items": [
    [
      "11c0cfa1-4f27-4ef7-a21c-cb452fc5c9aa",
      "<a href='mailto:jdoe@example.com'>jdoe@example.com</a>"
    ],
    [
      "e324ec3a-706d-4f57-a95d-1d88c03e7b73",
      "<a href='mailto:ssmith@example.com'>:ssmith@example.com</a>"
    ],
    [
      "3070c84d-129b-4017-82a8-2c26a42dd77e",
      "<a href='mailto:wjohns@example.com'>wjohns@example.com</a>"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	

Name	Type	Required	Description
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

user_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-user"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none">• "1.0"• "1.1"• "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none">• Conforms to the UUIDv4 Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the user.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value). • This state is not valid for a user with "authProvider" as "local" • "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true"). • This is the default value for a user with "authProvider" as "local" • "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The user is allowed to log in; default value on create. • "false" - The user is not allowed to log in.

Name	Type	Required	Description
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider.</p> <p>The contents of this string depend on the specified authProvider.</p> <p>For a user with "authProvider" as "local", "authID" is set to the value of "email".</p> <p>For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "ldap" - User authentication comes from an external LDAP server <p>In Astra Control Center, all users are required to have a value of "local", or "ldap". If a value is not specified, a default value of "local" is chosen.</p> <p>In Astra Control Service, "authProvider" as "local", or "ldap" is not supported. If a value is not specified, it will default to "cloud-central".</p>

Name	Type	Required	Description
firstName	string	True	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
lastName	string	True	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
email	string	True	JSON strings containing a user-specified email address.
phone	string	False	JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center. Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent. For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".

Name	Type	Required	Description
enableTimestamp	string	False	JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled. Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
lastActTimestamp	string	False	JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.) Defined values are: <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	

Name	Type	Required	Description
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a user

GET /accounts/{account_id}/core/v1/users/{user_id}

Returns the stored User API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
user_id	string	path	True	ID of the user collection to list

Response

Status: 200, Returns the stored User API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> • "application/astra-user"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
state	string	True	<p>JSON string containing a value indicating the operational state of the user.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value). • This state is not valid for a user with "authProvider" as "local" • "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true"). • This is the default value for a user with "authProvider" as "local" • "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).
isEnabled	string	True	<p>JSON string indicating if the user is allowed to log in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The user is allowed to log in; default value on create. • "false" - The user is not allowed to log in.

Name	Type	Required	Description
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider.</p> <p>The contents of this string depend on the specified authProvider.</p> <p>For a user with "authProvider" as "local", "authID" is set to the value of "email".</p> <p>For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "ldap" - User authentication comes from an external LDAP server <p>In Astra Control Center, all users are required to have a value of "local", or "ldap". If a value is not specified, a default value of "local" is chosen.</p> <p>In Astra Control Service, "authProvider" as "local", or "ldap" is not supported. If a value is not specified, it will default to "cloud-central".</p>

Name	Type	Required	Description
firstName	string	True	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
lastName	string	True	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
email	string	True	JSON strings containing a user-specified email address.
phone	string	False	JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.
postalAddress	postalAddress	False	JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.
sendWelcomeEmail	string	True	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".

Name	Type	Required	Description
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.)</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example response

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "id": "5bad8e04-e2fd-5c43-98d7-300580993f49",
  "state": "active",
  "isEnabled": "true",
  "authID": "HteLK3hk28sdbDLKHReB",
  "authProvider": "cloud-central",
  "firstName": "John",
  "lastName": "Doe",
  "companyName": "NetApp, Inc.",
  "email": "<a href='mailto:jdoe@example.com'>jdoe@example.com</a>",
  "phone": "408-555-2222",
  "postalAddress": {
    "addressCountry": "US",
    "addressLocality": "Sunnyvale",
    "addressRegion": "California",
    "postalCode": "94089",
    "streetAddress1": "495 East Java Drive"
  },
  "sendWelcomeEmail": "true",
  "enableTimestamp": "2020-08-05T14:24:54.128427Z",
  "lastActTimestamp": "2020-08-05T14:24:54.128427Z",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Modify a user

PUT /accounts/{account_id}/core/v1/users/{user_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
user_id	string	path	True	ID of the user collection to list

Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-user"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1" "1.2"

Name	Type	Required	Description
id	string	False	<p>Globally unique identifier of the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
state	string	False	<p>JSON string containing a value indicating the operational state of the user.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "pending" - The user account is in the process of being created. The user can only read and modify the user resource (default value). • This state is not valid for a user with "authProvider" as "local" • "active" - The user account is operational (The user can log in if the account setting "isEnabled" is "true"). • This is the default value for a user with "authProvider" as "local" • "suspended" - The user account is suspended (The user cannot log in regardless of account "isEnabled" setting).

Name	Type	Required	Description
isEnabled	string	False	<p>JSON string indicating if the user is allowed to log in.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - The user is allowed to log in; default value on create. • "false" - The user is not allowed to log in.
authID	string	False	<p>JSON string containing the identifier associated with an external identity provider.</p> <p>The contents of this string depend on the specified authProvider.</p> <p>For a user with "authProvider" as "local", "authID" is set to the value of "email".</p> <p>For a user with "authProvider" as "ldap", "authID" is set to its Distinguished Name (DN) from the LDAP server.</p>

Name	Type	Required	Description
authProvider	string	False	<p>JSON string indicating the context of the idAuth identifier.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "cloud-central" - User authentication comes from the NetApp Cloud Central service • "local" - User authentication comes from the local user/password store • "Idap" - User authentication comes from an external LDAP server In Astra Control Center, all users are required to have a value of "local", or "Idap". If a value is not specified, a default value of "local" is chosen. In Astra Control Service, "authProvider" as "local", or "Idap" is not supported. If a value is not specified, it will default to "cloud-central".
firstName	string	False	<p>JSON string containing a user-specified long form first name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks

Name	Type	Required	Description
lastName	string	False	<p>JSON string containing a user-specified long-form last name.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 0 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
companyName	string	False	<p>JSON string containing the company name associated with the user. If this key does not exist, it indicates that a company name has not been provided.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63 • This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks
email	string	False	<p>JSON strings containing a user-specified email address.</p>
phone	string	False	<p>JSON string containing the phone number of the user. If this key does not exist, it indicates that a phone number has not been provided.</p>

Name	Type	Required	Description
postalAddress	postalAddress	False	<p>JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided. If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.</p>
sendWelcomeEmail	string	False	<p>JSON string indicating whether a welcome email will be sent after validation. If not specified on create, the value will be set to "true" for ACS and "false" for Astra Control Center.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - A welcome email will be sent; default value on create • "false" - A welcome email will not be sent For a user with "authProvider" as "local" or "ldap", this value is ignored and is set to "false".
enableTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the user was last enabled.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema

Name	Type	Required	Description
lastActTimestamp	string	False	<p>JSON string containing an ISO-8601 formatted timestamp indicating when the identity API was last invoked on behalf of this user. (Note: This is expensive.)</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the ISO-8601 Date Time Schema
metadata	type_astra_metadata_update	False	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Example request

```
{
  "type": "application/astra-user",
  "version": "1.2",
  "firstName": "John",
  "lastName": "Dale",
  "email": "<a href='mailto:jdale@example.com'>jdale@example.com</a>"
}
```

Response

Status: 204, Indicates if the user resource was updated.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 409, Conflict

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidFields	array[invalidFields]	False	List of invalid request body fields

Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

postalAddress

JSON object containing a collection of fields that specifies an address. If this key does not exist, it indicates that an address has not been provided.

If this key exists, all six of the contained fields will be present. If nothing was provided by the user, the string will be empty.

Name	Type	Required	Description
addressCountry	string	True	JSON string containing the country name or country code associated with the postal address, as specified in ISO 3166 Alpha-2. Defined values are: <ul style="list-style-type: none">• Minimum length: 2• Maximum length: 2
addressLocality	string	True	JSON string containing the locality (for example, city) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
addressRegion	string	True	JSON string containing the region (for example, state) associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63
postalCode	string	True	JSON string containing the postal code associated with the postal address. Defined values are: <ul style="list-style-type: none">• Minimum length: 1• Maximum length: 63

Name	Type	Required	Description
streetAddress1	string	True	JSON string containing the street address associated with the postal address. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63
streetAddress2	string	False	JSON string containing optional ancillary street address information, post office box, and so on. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 63

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata_update

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema
If not specified on create, a metadata object will be created with no labels.
If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

Name	Type	Required	Description
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

invalidFields

Name	Type	Required	Description
name	string	True	Name of the invalid request body field
reason	string	True	Reason why the request body field is invalid

Delete a user

DELETE /accounts/{account_id}/core/v1/users/{user_id}

Removes the specified User API resource.

Side Effects

- The following resources associated with the user are deleted: notificationMarks, tokens, and all roleBindings referring to the user.
- For a user with "authProvider" as "local", the linked credential with "keyType" as "passwordHash" will also be deleted.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> • example: <code>{{.Account}}</code>
user_id	string	path	True	ID of the user collection to list

Response

Status: 204, Indicates if the user resource was deleted.

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

Definitions

See Definitions

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Volume

Volume overview

The Volume API provides visibility into Kubernetes volumes associated with applications.

List the volumes for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/volumes

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: id,name
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: volume_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-volumes",
  "version": "1.2",
  "items": [
    [
      "24fe6e79-bf8d-45c9-96af-ef1d11fbd4a0",
      "myVolume"
    ],
    [
      "20a370f4-957f-446a-9126-08853d01933a",
      "secondVol"
    ],
    [
      "48e349a2-5bcd-4c59-896c-12b8240e634b",
      "smallVol"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

volume_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-volume"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing the name of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
state	string	False	JSON string containing a value indicating the operational state of the volume.
size	string	False	JSON string containing the size of the volume.
used	number	False	JSON number containing the number of bytes of quota used by the provisioned volume.
usedPercentage	number	False	JSON number containing the percentage of volume used.
total	number	False	JSON number containing the total bytes of volumes provisioned.

Name	Type	Required	Description
creationToken	string	False	<p>JSON string containing the creation token of the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
snapshotPossible	string	False	<p>JSON string indicating whether the driver can perform a snapshot of the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Driver can take a snapshot of the volume • "false" - Driver cannot take a snapshot of the volume
storageClass	string	False	<p>JSON string containing the storage class for the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
pvcName	string	False	<p>JSON string containing the PersistentVolumeClaim (PVC) name of the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
internalName	string	False	<p>JSON string containing the internal name of the volume on the target storage cluster, if available. This name is obtained from the Kubernetes CSI driver.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
appsUsing	array[string]	True	<p>JSON array of JSON strings, each containing the ID of an application that is using the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
storageBackendID	string	False	<p>JSON string containing the ID of the storage backend that provides the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
orchestrator	string	False	<p>JSON string containing the orchestrator for this volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "trident" - Trident has provisioned this volume • "vasa" - NetApp VASA Provider has provisioned this volume • "other" - The volume has been provisioned manually or the orchestrator is not known
serviceLevel	string	False	<p>JSON string containing the quality of service (QoS) policy defined for this volume at the storage backend level. This will be defined for Astra Data Store volumes.</p>
exportPolicy	string	False	<p>JSON string containing the export policy associated with this volume. This will be defined for Astra Data Store volumes.</p>
nodeId	string	False	<p>JSON string containing the node ID serving the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification
healthStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current health. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a volume for a managed cluster

GET

/accounts/{account_id}/topology/v1/managedClusters/{managedCluster_id}/volumes/{volume_id}

Returns the stored Volume API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
managedCluster_id	string	path	True	ID of the containing managedCluster resource
volume_id	string	path	True	ID of the volume collection to list

Response

Status: 200, Returns the stored Volume API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-volume"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1" "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	JSON string containing the name of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
state	string	False	JSON string containing a value indicating the operational state of the volume.
size	string	False	JSON string containing the size of the volume.
used	number	False	JSON number containing the number of bytes of quota used by the provisioned volume.
usedPercentage	number	False	JSON number containing the percentage of volume used.
total	number	False	JSON number containing the total bytes of volumes provisioned.
creationToken	string	False	JSON string containing the creation token of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
snapshotPossible	string	False	<p>JSON string indicating whether the driver can perform a snapshot of the volume. Defined values are:</p> <ul style="list-style-type: none"> • "true" - Driver can take a snapshot of the volume • "false" - Driver cannot take a snapshot of the volume
storageClass	string	False	<p>JSON string containing the storage class for the volume.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
pvcName	string	False	<p>JSON string containing the PersistentVolumeClaim (PVC) name of the volume.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
internalName	string	False	<p>JSON string containing the internal name of the volume on the target storage cluster, if available. This name is obtained from the Kubernetes CSI driver.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
appsUsing	array[string]	True	<p>JSON array of JSON strings, each containing the ID of an application that is using the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
storageBackendID	string	False	<p>JSON string containing the ID of the storage backend that provides the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
orchestrator	string	False	<p>JSON string containing the orchestrator for this volume. This will be defined for Astra Data Store volumes. Defined values are:</p> <ul style="list-style-type: none"> • "trident" - Trident has provisioned this volume • "vasa" - NetApp VASA Provider has provisioned this volume • "other" - The volume has been provisioned manually or the orchestrator is not known
serviceLevel	string	False	<p>JSON string containing the quality of service (QoS) policy defined for this volume at the storage backend level. This will be defined for Astra Data Store volumes.</p>

Name	Type	Required	Description
exportPolicy	string	False	JSON string containing the export policy associated with this volume. This will be defined for Astra Data Store volumes.
nodeId	string	False	<p>JSON string containing the node ID serving the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
healthState	string	False	<p>JSON string containing a value indicating the health state of the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current health.</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-volume",
  "version": "1.2",
  "id": "ab5c9fb8-ddba-526f-8bd3-8d5b72cf4f7f",
  "name": "myVolume",
  "state": "ready",
  "size": "512 GiB",
  "used": 10000000000,
  "usedPercentage": 10,
  "total": 10000000000,
  "creationToken": "ba7d4e0c-6ae3-4b6e-859d-9463e7ca4b4e",
  "snapshotPossible": "true",
  "storageClass": "gold",
  "pvcName": "myVolume",
  "internalName": "trident_sd234234_23424_897d_876sd65w",
  "appsUsing": [],
  "orchestrator": "trident",
  "serviceLevel": "gold",
  "exportPolicy": "astra-vp-default",
  "nodeId": "94d16dd2-9beb-4edb-ab58-1a00e9a90052",
  "healthState": "normal",
  "healthStateDetails": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the volumes for a storage backend

GET

/accounts/{account_id}/topology/v1/storageBackends/{storageBackend_id}/volumes

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
storageBackend_id	string	path	True	ID of the containing storageBackend resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: volume_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-volumes",
  "version": "1.2",
  "items": [
    [
      "24fe6e79-bf8d-45c9-96af-ef1d11fbd4a0",
      "myVolume"
    ],
    [
      "20a370f4-957f-446a-9126-08853d01933a",
      "secondVol"
    ],
    [
      "48e349a2-5bcd-4c59-896c-12b8240e634b",
      "smallVol"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

volume_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-volume"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing the name of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
state	string	False	JSON string containing a value indicating the operational state of the volume.
size	string	False	JSON string containing the size of the volume.
used	number	False	JSON number containing the number of bytes of quota used by the provisioned volume.
usedPercentage	number	False	JSON number containing the percentage of volume used.
total	number	False	JSON number containing the total bytes of volumes provisioned.

Name	Type	Required	Description
creationToken	string	False	JSON string containing the creation token of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
snapshotPossible	string	False	JSON string indicating whether the driver can perform a snapshot of the volume. Defined values are: <ul style="list-style-type: none"> • "true" - Driver can take a snapshot of the volume • "false" - Driver cannot take a snapshot of the volume
storageClass	string	False	JSON string containing the storage class for the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
pvcName	string	False	JSON string containing the PersistentVolumeClaim (PVC) name of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
internalName	string	False	<p>JSON string containing the internal name of the volume on the target storage cluster, if available. This name is obtained from the Kubernetes CSI driver.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
appsUsing	array[string]	True	<p>JSON array of JSON strings, each containing the ID of an application that is using the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
storageBackendID	string	False	<p>JSON string containing the ID of the storage backend that provides the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
orchestrator	string	False	<p>JSON string containing the orchestrator for this volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "trident" - Trident has provisioned this volume • "vasa" - NetApp VASA Provider has provisioned this volume • "other" - The volume has been provisioned manually or the orchestrator is not known
serviceLevel	string	False	<p>JSON string containing the quality of service (QoS) policy defined for this volume at the storage backend level. This will be defined for Astra Data Store volumes.</p>
exportPolicy	string	False	<p>JSON string containing the export policy associated with this volume. This will be defined for Astra Data Store volumes.</p>
nodeId	string	False	<p>JSON string containing the node ID serving the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification
healthStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current health. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a volume for a storage backend

GET

/accounts/{account_id}/topology/v1/storageBackends/{storageBackend_id}/volumes/{volume_id}

Returns the stored Volume API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
storageBackend_id	string	path	True	ID of the containing storageBackend resource
volume_id	string	path	True	ID of the volume collection to list

Response

Status: 200, Returns the stored Volume API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-volume"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1" "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	JSON string containing the name of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
state	string	False	JSON string containing a value indicating the operational state of the volume.
size	string	False	JSON string containing the size of the volume.
used	number	False	JSON number containing the number of bytes of quota used by the provisioned volume.
usedPercentage	number	False	JSON number containing the percentage of volume used.
total	number	False	JSON number containing the total bytes of volumes provisioned.
creationToken	string	False	JSON string containing the creation token of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
snapshotPossible	string	False	<p>JSON string indicating whether the driver can perform a snapshot of the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Driver can take a snapshot of the volume • "false" - Driver cannot take a snapshot of the volume
storageClass	string	False	<p>JSON string containing the storage class for the volume.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
pvcName	string	False	<p>JSON string containing the PersistentVolumeClaim (PVC) name of the volume.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
internalName	string	False	<p>JSON string containing the internal name of the volume on the target storage cluster, if available. This name is obtained from the Kubernetes CSI driver.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
appsUsing	array[string]	True	<p>JSON array of JSON strings, each containing the ID of an application that is using the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
storageBackendID	string	False	<p>JSON string containing the ID of the storage backend that provides the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
orchestrator	string	False	<p>JSON string containing the orchestrator for this volume. This will be defined for Astra Data Store volumes. Defined values are:</p> <ul style="list-style-type: none"> • "trident" - Trident has provisioned this volume • "vasa" - NetApp VASA Provider has provisioned this volume • "other" - The volume has been provisioned manually or the orchestrator is not known
serviceLevel	string	False	<p>JSON string containing the quality of service (QoS) policy defined for this volume at the storage backend level. This will be defined for Astra Data Store volumes.</p>

Name	Type	Required	Description
exportPolicy	string	False	JSON string containing the export policy associated with this volume. This will be defined for Astra Data Store volumes.
nodeId	string	False	<p>JSON string containing the node ID serving the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
healthState	string	False	<p>JSON string containing a value indicating the health state of the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current health.</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-volume",
  "version": "1.2",
  "id": "ab5c9fb8-ddba-526f-8bd3-8d5b72cf4f7f",
  "name": "myVolume",
  "state": "ready",
  "size": "512 GiB",
  "used": 10000000000,
  "usedPercentage": 10,
  "total": 10000000000,
  "creationToken": "ba7d4e0c-6ae3-4b6e-859d-9463e7ca4b4e",
  "snapshotPossible": "true",
  "storageClass": "gold",
  "pvcName": "myVolume",
  "internalName": "trident_sd234234_23424_897d_876sd65w",
  "appsUsing": [],
  "orchestrator": "trident",
  "serviceLevel": "gold",
  "exportPolicy": "astra-vp-default",
  "nodeId": "94d16dd2-9beb-4edb-ab58-1a00e9a90052",
  "healthState": "normal",
  "healthStateDetails": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```


Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List all volumes

GET /accounts/{account_id}/topology/v1/volumes

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" • example: id,name
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

```
Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.
```

Name	Type	Required	Description
items	array[Any of: volume_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-volumes",
  "version": "1.2",
  "items": [
    [
      "24fe6e79-bf8d-45c9-96af-ef1d11fbd4a0",
      "myVolume"
    ],
    [
      "20a370f4-957f-446a-9126-08853d01933a",
      "secondVol"
    ],
    [
      "48e349a2-5bcd-4c59-896c-12b8240e634b",
      "smallVol"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

volume_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-volume"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing the name of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
state	string	False	JSON string containing a value indicating the operational state of the volume.
size	string	False	JSON string containing the size of the volume.
used	number	False	JSON number containing the number of bytes of quota used by the provisioned volume.
usedPercentage	number	False	JSON number containing the percentage of volume used.
total	number	False	JSON number containing the total bytes of volumes provisioned.

Name	Type	Required	Description
creationToken	string	False	<p>JSON string containing the creation token of the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
snapshotPossible	string	False	<p>JSON string indicating whether the driver can perform a snapshot of the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Driver can take a snapshot of the volume • "false" - Driver cannot take a snapshot of the volume
storageClass	string	False	<p>JSON string containing the storage class for the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
pvcName	string	False	<p>JSON string containing the PersistentVolumeClaim (PVC) name of the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
internalName	string	False	<p>JSON string containing the internal name of the volume on the target storage cluster, if available. This name is obtained from the Kubernetes CSI driver.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
appsUsing	array[string]	True	<p>JSON array of JSON strings, each containing the ID of an application that is using the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
storageBackendID	string	False	<p>JSON string containing the ID of the storage backend that provides the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
orchestrator	string	False	<p>JSON string containing the orchestrator for this volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "trident" - Trident has provisioned this volume • "vasa" - NetApp VASA Provider has provisioned this volume • "other" - The volume has been provisioned manually or the orchestrator is not known
serviceLevel	string	False	<p>JSON string containing the quality of service (QoS) policy defined for this volume at the storage backend level. This will be defined for Astra Data Store volumes.</p>
exportPolicy	string	False	<p>JSON string containing the export policy associated with this volume. This will be defined for Astra Data Store volumes.</p>
nodeId	string	False	<p>JSON string containing the node ID serving the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification
healthStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current health. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a volume

GET /accounts/{account_id}/topology/v1/volumes/{volume_id}

Returns the stored Volume API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> example: <code>{{.Account}}</code>
volume_id	string	path	True	ID of the volume collection to list

Response

Status: 200, Returns the stored Volume API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"> "application/astra-volume"
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> "1.0" "1.1" "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the UUIDv4 Schema
name	string	True	JSON string containing the name of the volume. Defined values are: <ul style="list-style-type: none"> Minimum length: 1 Maximum length: 255

Name	Type	Required	Description
state	string	False	JSON string containing a value indicating the operational state of the volume.
size	string	False	JSON string containing the size of the volume.
used	number	False	JSON number containing the number of bytes of quota used by the provisioned volume.
usedPercentage	number	False	JSON number containing the percentage of volume used.
total	number	False	JSON number containing the total bytes of volumes provisioned.
creationToken	string	False	JSON string containing the creation token of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
snapshotPossible	string	False	JSON string indicating whether the driver can perform a snapshot of the volume. Defined values are: <ul style="list-style-type: none"> • "true" - Driver can take a snapshot of the volume • "false" - Driver cannot take a snapshot of the volume

Name	Type	Required	Description
storageClass	string	False	<p>JSON string containing the storage class for the volume.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
pvcName	string	False	<p>JSON string containing the PersistentVolumeClaim (PVC) name of the volume.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
internalName	string	False	<p>JSON string containing the internal name of the volume on the target storage cluster, if available. This name is obtained from the Kubernetes CSI driver.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
appsUsing	array[string]	True	<p>JSON array of JSON strings, each containing the ID of an application that is using the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
storageBackendID	string	False	<p>JSON string containing the ID of the storage backend that provides the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
orchestrator	string	False	<p>JSON string containing the orchestrator for this volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "trident" - Trident has provisioned this volume • "vasa" - NetApp VASA Provider has provisioned this volume • "other" - The volume has been provisioned manually or the orchestrator is not known
serviceLevel	string	False	<p>JSON string containing the quality of service (QoS) policy defined for this volume at the storage backend level. This will be defined for Astra Data Store volumes.</p>
exportPolicy	string	False	<p>JSON string containing the export policy associated with this volume. This will be defined for Astra Data Store volumes.</p>
nodeId	string	False	<p>JSON string containing the node ID serving the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the volume. This will be defined for Astra Data Store volumes. Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification
healthStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current health. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-volume",
  "version": "1.2",
  "id": "ab5c9fb8-ddba-526f-8bd3-8d5b72cf4f7f",
  "name": "myVolume",
  "state": "ready",
  "size": "512 GiB",
  "used": 1000000000,
  "usedPercentage": 10,
  "total": 1000000000,
  "creationToken": "ba7d4e0c-6ae3-4b6e-859d-9463e7ca4b4e",
  "snapshotPossible": "true",
  "storageClass": "gold",
  "pvcName": "myVolume",
  "internalName": "trident_sd234234_23424_897d_876sd65w",
  "appsUsing": [],
  "orchestrator": "trident",
  "serviceLevel": "gold",
  "exportPolicy": "astra-vp-default",
  "nodeId": "94d16dd2-9beb-4edb-ab58-1a00e9a90052",
  "healthState": "normal",
  "healthStateDetails": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

List the volumes for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/volumes

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the

request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none">example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
include	string	query	False	Indicates which fields should be returned when listing a collection. URL examples: "include=id", "include=id,name" OpenAPI examples: "id" <ul style="list-style-type: none">example: id,name
limit	string	query	False	Indicates the maximum number of resources to return when listing a collection. URL examples: "limit=2" OpenAPI examples: "2"

Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: volume_1.2_get_response_body , array[]]	True	
metadata	type_astra_metadata_list	True	

Example response

```
{
  "type": "application/astra-volumes",
  "version": "1.2",
  "items": [
    [
      "24fe6e79-bf8d-45c9-96af-ef1d11fbd4a0",
      "myVolume"
    ],
    [
      "20a370f4-957f-446a-9126-08853d01933a",
      "secondVol"
    ],
    [
      "48e349a2-5bcd-4c59-896c-12b8240e634b",
      "smallVol"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.

Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

volume_1.2_get_response_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none">• "application/astra-volume"

Name	Type	Required	Description
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"> • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> • Conforms to the UUIDv4 Schema
name	string	True	JSON string containing the name of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
state	string	False	JSON string containing a value indicating the operational state of the volume.
size	string	False	JSON string containing the size of the volume.
used	number	False	JSON number containing the number of bytes of quota used by the provisioned volume.
usedPercentage	number	False	JSON number containing the percentage of volume used.
total	number	False	JSON number containing the total bytes of volumes provisioned.

Name	Type	Required	Description
creationToken	string	False	JSON string containing the creation token of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
snapshotPossible	string	False	JSON string indicating whether the driver can perform a snapshot of the volume. Defined values are: <ul style="list-style-type: none"> • "true" - Driver can take a snapshot of the volume • "false" - Driver cannot take a snapshot of the volume
storageClass	string	False	JSON string containing the storage class for the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
pvcName	string	False	JSON string containing the PersistentVolumeClaim (PVC) name of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
internalName	string	False	<p>JSON string containing the internal name of the volume on the target storage cluster, if available. This name is obtained from the Kubernetes CSI driver.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
appsUsing	array[string]	True	<p>JSON array of JSON strings, each containing the ID of an application that is using the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
storageBackendID	string	False	<p>JSON string containing the ID of the storage backend that provides the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
orchestrator	string	False	<p>JSON string containing the orchestrator for this volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "trident" - Trident has provisioned this volume • "vasa" - NetApp VASA Provider has provisioned this volume • "other" - The volume has been provisioned manually or the orchestrator is not known
serviceLevel	string	False	<p>JSON string containing the quality of service (QoS) policy defined for this volume at the storage backend level. This will be defined for Astra Data Store volumes.</p>
exportPolicy	string	False	<p>JSON string containing the export policy associated with this volume. This will be defined for Astra Data Store volumes.</p>
nodeId	string	False	<p>JSON string containing the node ID serving the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema

Name	Type	Required	Description
healthState	string	False	<p>JSON string containing a value indicating the health state of the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification
healthStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current health. If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0

Name	Type	Required	Description
metadata	type_astra_metadata	True	Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> Conforms to the Astra Metadata Schema

type_astra_metadata_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Retrieve a volume for an app

GET /accounts/{account_id}/k8s/v1/apps/{app_id}/volumes/{volume_id}

Returns the stored Volume API resource in the JSON response body.

Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource • example: {{.Account}}
app_id	string	path	True	ID of the containing app resource
volume_id	string	path	True	ID of the volume collection to list

Response

Status: 200, Returns the stored Volume API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: • "application/astra-volume"
version	string	True	Version of the resource. Defined values are: • "1.0" • "1.1" • "1.2"
id	string	True	Globally unique identifier of the resource. Defined values are: • Conforms to the UUIDv4 Schema

Name	Type	Required	Description
name	string	True	JSON string containing the name of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255
state	string	False	JSON string containing a value indicating the operational state of the volume.
size	string	False	JSON string containing the size of the volume.
used	number	False	JSON number containing the number of bytes of quota used by the provisioned volume.
usedPercentage	number	False	JSON number containing the percentage of volume used.
total	number	False	JSON number containing the total bytes of volumes provisioned.
creationToken	string	False	JSON string containing the creation token of the volume. Defined values are: <ul style="list-style-type: none"> • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
snapshotPossible	string	False	<p>JSON string indicating whether the driver can perform a snapshot of the volume.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "true" - Driver can take a snapshot of the volume • "false" - Driver cannot take a snapshot of the volume
storageClass	string	False	<p>JSON string containing the storage class for the volume.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
pvcName	string	False	<p>JSON string containing the PersistentVolumeClaim (PVC) name of the volume.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255
internalName	string	False	<p>JSON string containing the internal name of the volume on the target storage cluster, if available. This name is obtained from the Kubernetes CSI driver.</p> <ul style="list-style-type: none"> • Defined values are: • Minimum length: 1 • Maximum length: 255

Name	Type	Required	Description
appsUsing	array[string]	True	<p>JSON array of JSON strings, each containing the ID of an application that is using the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
storageBackendID	string	False	<p>JSON string containing the ID of the storage backend that provides the volume. Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
orchestrator	string	False	<p>JSON string containing the orchestrator for this volume. This will be defined for Astra Data Store volumes. Defined values are:</p> <ul style="list-style-type: none"> • "trident" - Trident has provisioned this volume • "vasa" - NetApp VASA Provider has provisioned this volume • "other" - The volume has been provisioned manually or the orchestrator is not known
serviceLevel	string	False	<p>JSON string containing the quality of service (QoS) policy defined for this volume at the storage backend level. This will be defined for Astra Data Store volumes.</p>

Name	Type	Required	Description
exportPolicy	string	False	JSON string containing the export policy associated with this volume. This will be defined for Astra Data Store volumes.
nodeId	string	False	<p>JSON string containing the node ID serving the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Identifier Schema
healthState	string	False	<p>JSON string containing a value indicating the health state of the volume. This will be defined for Astra Data Store volumes.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • "indeterminate" - The health of the resource cannot be determined (for example, due to lack of connectivity) • "normal" - The resource has no known issues and can provide services in accordance with the interface specification • "warning" - The resource has known issues that do not prevent it providing services in accordance with the interface specification • "critical" - The resource has known issues that prevent it from providing services in accordance with the interface specification

Name	Type	Required	Description
healthStateDetails	array[type_astra_stateDetail]	True	<p>JSON array of JSON objects that lists additional details about the current health.</p> <p>If no details are available, this array will be empty.</p> <ul style="list-style-type: none"> • Minimum Items: 0
metadata	type_astra_metadata	True	<p>Client and service-specified metadata associated with the resource.</p> <p>Defined values are:</p> <ul style="list-style-type: none"> • Conforms to the Astra Metadata Schema

Example response

```
{
  "type": "application/astra-volume",
  "version": "1.2",
  "id": "ab5c9fb8-ddba-526f-8bd3-8d5b72cf4f7f",
  "name": "myVolume",
  "state": "ready",
  "size": "512 GiB",
  "used": 10000000000,
  "usedPercentage": 10,
  "total": 10000000000,
  "creationToken": "ba7d4e0c-6ae3-4b6e-859d-9463e7ca4b4e",
  "snapshotPossible": "true",
  "storageClass": "gold",
  "pvcName": "myVolume",
  "internalName": "trident_sd234234_23424_897d_876sd65w",
  "appsUsing": [],
  "orchestrator": "trident",
  "serviceLevel": "gold",
  "exportPolicy": "astra-vp-default",
  "nodeId": "94d16dd2-9beb-4edb-ab58-1a00e9a90052",
  "healthState": "normal",
  "healthStateDetails": [],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	

Name	Type	Required	Description
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

Definitions

See Definitions

type_astra_stateDetail

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

type_astra_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type_astra_metadata

Client and service-specified metadata associated with the resource.
Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

Recursos adicionais

Há recursos adicionais que você pode acessar para obter ajuda e encontrar mais informações sobre os serviços e suporte em nuvem da NetApp, bem como conceitos GERAIS DE REST e nuvem.

Astra

- ["Documentação do Astra Control Center 23,04"](#)

Documentação para a versão 23,04 do software Astra Control Center implantado nas instalações do cliente.

- ["Documentação do Astra Control Service"](#)

Documentação para a versão mais recente do software Astra Control Service disponível na nuvem pública.

- ["Documentação do Astra Trident"](#)

Documentação da versão atual do software Astra Trident, um orquestrador de storage de código aberto mantido pela NetApp.

- ["Documentação da família Astra"](#)

Local central para acessar toda a documentação do Astra para implantações locais e de nuvem pública.

- ["Discórdia"](#)

Suporte comunitário para Astra Control e outros produtos NetApp.

Recursos de nuvem da NetApp

- ["NetApp BlueXP"](#)

Local central para as soluções de nuvem da NetApp.

- ["Console central da nuvem NetApp"](#)

Console de serviço NetApp Cloud Central com login.

- ["Suporte à NetApp"](#)

Acesse ferramentas de solução de problemas, documentação e assistência técnica.

Conceitos DE REST e nuvem

- PhD ["dissertação"](#) por Roy Fielding

Esta publicação introduziu e estabeleceu o modelo de desenvolvimento de aplicações REST.

- "Auth0"

Este é o serviço de plataforma de autenticação e autorização usado pelo serviço Astra para acesso à Web.

- "Editor RFC"

Fonte autorizada para padrões da Web e da Internet mantida como uma coleção de documentos RFC numerados de forma única.

Versões anteriores da documentação do Astra Control Automation

Você pode acessar a documentação de automação de versões anteriores do Astra Control nos links abaixo.

- ["Documentação do Astra Control Automation 22,11"](#)
- ["Documentação do Astra Control Automation 22,08"](#)
- ["Documentação do Astra Control Automation 22,04"](#)
- ["Documentação do Astra Control Automation 21,12"](#)
- ["Documentação do Astra Control Automation 21,08"](#)

Avisos legais

Avisos legais fornecem acesso a declarações de direitos autorais, marcas registradas, patentes e muito mais.

Direitos de autor

["https://www.netapp.com/company/legal/copyright/"](https://www.netapp.com/company/legal/copyright/)

Marcas comerciais

NetApp, o logotipo DA NetApp e as marcas listadas na página de marcas comerciais da NetApp são marcas comerciais da NetApp, Inc. Outros nomes de produtos e empresas podem ser marcas comerciais de seus respectivos proprietários.

["https://www.netapp.com/company/legal/trademarks/"](https://www.netapp.com/company/legal/trademarks/)

Patentes

Uma lista atual de patentes de propriedade da NetApp pode ser encontrada em:

<https://www.netapp.com/pdf.html?item=/media/11887-patentspage.pdf>

Política de privacidade

["https://www.netapp.com/company/legal/privacy-policy/"](https://www.netapp.com/company/legal/privacy-policy/)

Licença de API Astra Control

<https://docs.netapp.com/us-en/astra-automation/media/astra-api-license.pdf>

Informações sobre direitos autorais

Copyright © 2024 NetApp, Inc. Todos os direitos reservados. Impresso nos EUA. Nenhuma parte deste documento protegida por direitos autorais pode ser reproduzida de qualquer forma ou por qualquer meio — gráfico, eletrônico ou mecânico, incluindo fotocópia, gravação, gravação em fita ou storage em um sistema de recuperação eletrônica — sem permissão prévia, por escrito, do proprietário dos direitos autorais.

O software derivado do material da NetApp protegido por direitos autorais está sujeito à seguinte licença e isenção de responsabilidade:

ESTE SOFTWARE É FORNECIDO PELA NETAPP "NO PRESENTE ESTADO" E SEM QUAISQUER GARANTIAS EXPRESSAS OU IMPLÍCITAS, INCLUINDO, SEM LIMITAÇÕES, GARANTIAS IMPLÍCITAS DE COMERCIALIZAÇÃO E ADEQUAÇÃO A UM DETERMINADO PROPÓSITO, CONFORME A ISENÇÃO DE RESPONSABILIDADE DESTES DOCUMENTOS. EM HIPÓTESE ALGUMA A NETAPP SERÁ RESPONSÁVEL POR QUALQUER DANO DIRETO, INDIRETO, INCIDENTAL, ESPECIAL, EXEMPLAR OU CONSEQUENCIAL (INCLUINDO, SEM LIMITAÇÕES, AQUISIÇÃO DE PRODUTOS OU SERVIÇOS SOBRESSALIENTES; PERDA DE USO, DADOS OU LUCROS; OU INTERRUPÇÃO DOS NEGÓCIOS), INDEPENDENTEMENTE DA CAUSA E DO PRINCÍPIO DE RESPONSABILIDADE, SEJA EM CONTRATO, POR RESPONSABILIDADE OBJETIVA OU PREJUÍZO (INCLUINDO NEGLIGÊNCIA OU DE OUTRO MODO), RESULTANTE DO USO DESTES SOFTWARES, MESMO SE ADVERTIDA DA RESPONSABILIDADE DE TAL DANO.

A NetApp reserva-se o direito de alterar quaisquer produtos descritos neste documento, a qualquer momento e sem aviso. A NetApp não assume nenhuma responsabilidade nem obrigação decorrentes do uso dos produtos descritos neste documento, exceto conforme expressamente acordado por escrito pela NetApp. O uso ou a compra deste produto não representam uma licença sob quaisquer direitos de patente, direitos de marca comercial ou quaisquer outros direitos de propriedade intelectual da NetApp.

O produto descrito neste manual pode estar protegido por uma ou mais patentes dos EUA, patentes estrangeiras ou pedidos pendentes.

LEGENDA DE DIREITOS LIMITADOS: o uso, a duplicação ou a divulgação pelo governo estão sujeitos a restrições conforme estabelecido no subparágrafo (b)(3) dos Direitos em Dados Técnicos - Itens Não Comerciais no DFARS 252.227-7013 (fevereiro de 2014) e no FAR 52.227- 19 (dezembro de 2007).

Os dados aqui contidos pertencem a um produto comercial e/ou serviço comercial (conforme definido no FAR 2.101) e são de propriedade da NetApp, Inc. Todos os dados técnicos e software de computador da NetApp fornecidos sob este Contrato são de natureza comercial e desenvolvidos exclusivamente com despesas privadas. O Governo dos EUA tem uma licença mundial limitada, irrevogável, não exclusiva, intransferível e não sublicenciável para usar os Dados que estão relacionados apenas com o suporte e para cumprir os contratos governamentais desse país que determinam o fornecimento de tais Dados. Salvo disposição em contrário no presente documento, não é permitido usar, divulgar, reproduzir, modificar, executar ou exibir os dados sem a aprovação prévia por escrito da NetApp, Inc. Os direitos de licença pertencentes ao governo dos Estados Unidos para o Departamento de Defesa estão limitados aos direitos identificados na cláusula 252.227-7015(b) (fevereiro de 2014) do DFARS.

Informações sobre marcas comerciais

NETAPP, o logotipo NETAPP e as marcas listadas em <http://www.netapp.com/TM> são marcas comerciais da NetApp, Inc. Outros nomes de produtos e empresas podem ser marcas comerciais de seus respectivos proprietários.