



# Kubernetes API Resource

## Astra Automation

NetApp  
March 17, 2024

This PDF was generated from [https://docs.netapp.com/us-en/astra-automation/reference/kubernetes\\_api\\_resource\\_overview.html](https://docs.netapp.com/us-en/astra-automation/reference/kubernetes_api_resource_overview.html) on March 17, 2024. Always check docs.netapp.com for the latest.

# Table of Contents

- Kubernetes API Resource ..... 1
  - Kubernetes API Resource overview..... 1
  - List the K8s API resources for a managed cluster..... 1
  - Retrieve a K8s API resource ..... 9

# Kubernetes API Resource

## Kubernetes API Resource overview

The Kubernetes API Resource API provides read-only access to Kubernetes API resources to filter the ones supported by Astra on a given cluster.

## List the K8s API resources for a managed cluster

GET

/accounts/{account\_id}/topology/v1/managedClusters/{managedCluster\_id}/apiResources

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource  • example: {{.Account}}
managedCluster_id	string	path	True	ID of the containing managedCluster resource
include	string	query	False	Indicates which fields should be returned when listing a collection.  URL examples: "include=id", "include=id,name"  OpenAPI examples: "id"  • example: id,kind,apiVersion

Name	Type	In	Required	Description
limit	string	query	False	<p>Indicates the maximum number of resources to return when listing a collection.</p> <p>URL examples: "limit=2"</p> <p>OpenAPI examples: "2"</p>

## Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

Name	Type	Required	Description
items	array[Any of: <a href="#">apiResource_1.0_get_response_body</a> , array[]]	True	
metadata	<a href="#">type_astra_metadata_list</a>	True	

## Example response

```
{
  "type": "application/astra-apiResources",
  "version": "1.0",
  "items": [
    [
      "e280ff62-be35-4f31-a31b-a210a1ad1b33",
      "ClusterRole",
      "rbac.authorization.k8s.io/v1"
    ],
    [
      "e8507dad-d33f-44b3-9c15-ec55ba6f6473",
      "ClusterRoleBinding",
      "rbac.authorization.k8s.io/v1"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

#### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

#### Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't found.",
  "status": "404"
}
```

**Definitions**



## See Definitions

type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type\_astra\_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

apiResource\_1.0\_get\_response\_body

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-apiResource"</li></ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"><li>• "1.0"</li></ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the UUIDv4 Schema</li></ul>

Name	Type	Required	Description
apiVersion	string	True	<p>JSON string representing the API version of the resource, as set in or by Kubernetes. APIVersion defines the versioned schema for this object representation. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: <a href="https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources">https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources</a></p>
kind	string	True	<p>JSON string representing the kind of the resource, as set in or by Kubernetes. The kind field uses camel case and contains a string value representing the REST resource this object represents. Servers might infer this from the endpoint the client submits requests to. It cannot be updated. More info: <a href="https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds">https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds</a></p>
metadata	<a href="#">type_astra_metadata</a>	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema</li> </ul>

type\_astra\_metadata\_list

Name	Type	Required	Description
continue	string	False	
count	number	False	
labels	array[type_astra_label]	False	
creationTimestamp	string	False	
modificationTimestamp	string	False	
createdBy	string	False	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Retrieve a K8s API resource

GET

/accounts/{account\_id}/topology/v1/managedClusters/{managedCluster\_id}/apiResources/{apiResource\_id}

Returns the specific API resource in the JSON response body.

### Parameters

Name	Type	In	Required	Description
account_id	string	path	True	ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul>
managedCluster_id	string	path	True	ID of the containing managedCluster resource
apiResource_id	string	path	True	ID of the apiResource collection to list

## Response

Status: 200, Returns the specific API resource in the JSON response body.

Name	Type	Required	Description
type	string	True	Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-apiResource"</li></ul>
version	string	True	Version of the resource. Defined values are: <ul style="list-style-type: none"><li>• "1.0"</li></ul>
id	string	True	Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the UUIDv4 Schema</li></ul>
apiVersion	string	True	JSON string representing the API version of the resource, as set in or by Kubernetes. APIVersion defines the versioned schema for this object representation. Servers should convert recognized schemas to the latest internal value, and may reject unrecognized values. More info: <a href="https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources">https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#resources</a>

Name	Type	Required	Description
kind	string	True	JSON string representing the kind of the resource, as set in or by Kubernetes. The kind field uses camel case and contains a string value representing the REST resource this object represents. Servers might infer this from the endpoint the client submits requests to. It cannot be updated. More info: <a href="https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds">https://git.k8s.io/community/contributors/devel/sig-architecture/api-conventions.md#types-kinds</a>
metadata	<a href="#">type_astra_metadata</a>	True	<p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema</li> </ul>

### Example response

```
{
  "type": "application/astra-apiResource",
  "version": "1.0",
  "id": "e280ff62-be35-4f31-a31b-a210a1ad1b33",
  "kind": "ClusterRole",
  "apiVersion": "rbac.authorization.k8s.io/v1",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	
invalidParams	array[invalidParams]	False	List of invalid query parameters

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	
status	string	True	
correlationID	string	False	

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

Name	Type	Required	Description
type	string	True	
title	string	True	
detail	string	True	

Name	Type	Required	Description
status	string	True	
correlationID	string	False	

#### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions



## See Definitions

type\_astra\_label

Name	Type	Required	Description
name	string	True	
value	string	True	

type\_astra\_metadata

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema

Name	Type	Required	Description
labels	array[type_astra_label]	True	
creationTimestamp	string	True	
modificationTimestamp	string	True	
createdBy	string	True	
modifiedBy	string	False	

invalidParams

Name	Type	Required	Description
name	string	True	Name of the invalid query parameter
reason	string	True	Reason why the query parameter is invalid

## Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.