



# Cloud Volumes ONTAP 9.15.1 Release Notes

Cloud Volumes ONTAP release notes

NetApp  
September 09, 2024

# Table of Contents

- Cloud Volumes ONTAP 9.15.1 Release Notes ..... 1
- What's new in Cloud Volumes ONTAP 9.15.1 ..... 2
  - 9.15.1 P1 (3 September 2024) ..... 2
  - 9.15.1 GA (22 August 2024) ..... 2
  - Upgrade notes ..... 3
- Licensing for Cloud Volumes ONTAP ..... 4
- Supported configurations ..... 5
  - Supported configurations in AWS ..... 5
  - Supported configurations in Azure ..... 9
  - Supported configurations in Google Cloud ..... 19
- Storage limits ..... 24
  - Storage limits in AWS ..... 24
  - Storage limits in Azure ..... 31
  - Storage limits in Google Cloud ..... 43
- Known issues ..... 47
- Known limitations ..... 48
  - Limitations in all cloud providers ..... 48
  - Known limitations in AWS ..... 49
  - Known limitations in Azure ..... 50
  - Known limitations in Google Cloud ..... 51
- Cloud provider integrations ..... 52
  - Collaborative support best practices ..... 52
  - Azure maintenance events ..... 52
- Legal notices ..... 53
  - Copyright ..... 53
  - Trademarks ..... 53
  - Patents ..... 53
  - Privacy policy ..... 53
  - Open source ..... 53

# Cloud Volumes ONTAP 9.15.1 Release Notes

# What's new in Cloud Volumes ONTAP 9.15.1

Cloud Volumes ONTAP 9.15.1 includes new enhancements.

Additional features and enhancements are also introduced in the latest versions of BlueXP. See the [BlueXP Release Notes](#) for details.

## 9.15.1 P1 (3 September 2024)

The 9.15.1 P1 patch is now available for Cloud Volumes ONTAP for all cloud providers. BlueXP will prompt you to upgrade your existing systems to this patch release.

[View the list of bugs fixed in the P1 patch](#) (NetApp Support Site login required).

## 9.15.1 GA (22 August 2024)

The Cloud Volumes ONTAP 9.15.1 GA is now available in AWS, Azure, and Google Cloud. The GA version is available for deployment and upgrade.

This release includes the following features and enhancements for Azure. Read on to learn more about the specific configurations supporting these new features.

### Support for Premium SSD v2 Managed Disks on Azure

Premium SSD v2 Managed Disks are now supported in Cloud Volumes ONTAP systems on Azure. These premium disks provide higher performance with lower latency at a lower cost for both single node and high-availability (HA) pairs, as compared to Premium SSD Managed Disks. Like other managed disks, the maximum disk size is 32 TiB. The performance (capacity, throughput, and IOPS) of a Premium SSD v2 Managed Disks can be configured, allowing workloads to be cost effective, while meeting shifting performance needs.

[Learn about Azure storage.](#)

### Deploy HA pairs in single availability zones on Azure

Beginning with Cloud Volumes ONTAP 9.15.1, you can deploy virtual machine (VM) instances in HA mode in single availability zones (AZs) in Azure. Unlike the previous non-zonal deployments, Cloud Volumes ONTAP 9.15.1 uses Microsoft Virtual Machines Scale Sets in Flexible orchestration mode to deploy all resources, including separate fault domains within the same AZ, guaranteeing optimal availability. This deployment mode, by default, uses Premium SSD v2 Managed Disks when the following criteria are met:

- The version of Cloud Volumes ONTAP is 9.15.1 or later.
- The selected region and zone support Premium SSD v2 Managed Disks. For information about the supported regions, refer to [Microsoft Azure website: Products available by region](#). To know how to add them, refer to [Launching a Cloud Volumes ONTAP HA pair in Azure](#).
- The subscription is registered for the Microsoft `Microsoft.Compute/VMOrchestratorZonalMultiFD` feature.

[Learn how to enable VMOrchestratorZonalMultiFD for single availability zones.](#)

If any of these criteria is not fulfilled, the previous non-zonal deployment mode for locally-redundant storage (LRS) becomes effective.

## Support for Virtual Machines Scale Sets to unify all Azure HA types

Cloud Volumes ONTAP 9.15.1 leverages Virtual Machines Scale Sets in Flexible orchestration mode on Azure for deploying virtual machine (VM) instances in single availability zones for high-availability (HA) pairs. It covers all flavors of the HA mode, page blob, LRS, zone-redundant storage (ZRS) or multi-zonal, and LRS zonal (single AZ).

- [Microsoft Azure documentation: Virtual Machine Scale Sets documentation](#)
- [Learn about high-availability pairs in Azure.](#)

## Upgrade notes.

Read through these notes to learn more about upgrading to this release.

### How to upgrade

Upgrades of Cloud Volumes ONTAP must be completed from BlueXP. You should not upgrade Cloud Volumes ONTAP by using System Manager or the CLI. Doing so can impact system stability.

[Learn how to upgrade when BlueXP notifies you.](#)

### Supported upgrade path

You can upgrade to Cloud Volumes ONTAP 9.15.1 from 9.15.0 and 9.14.1 releases. BlueXP will prompt you to upgrade eligible Cloud Volumes ONTAP systems to this release.

### Downtime

- The upgrade of a single node system takes the system offline for up to 25 minutes, during which I/O is interrupted.
- Upgrading an HA pair is nondisruptive and I/O is uninterrupted. During this nondisruptive upgrade process, each node is upgraded in tandem to continue serving I/O to clients.

### c4, m4, and r4 instances no longer supported

In AWS, the c4, m4, and r4 EC2 instance types are no longer supported with Cloud Volumes ONTAP. If you have an existing system that's running on a c4, m4, or r4 instance type, you must change to an instance type in the c5, m5, or r5 instance family. You can't upgrade to this release until you change the instance type.

[Learn how to change the EC2 instance type for Cloud Volumes ONTAP.](#)

Refer to [NetApp Support](#) to learn more about the end of availability and support for these instance types.

# Licensing for Cloud Volumes ONTAP

Cloud Volumes ONTAP offers different licensing options that enable you to choose a consumption model that meets your needs.

The following licensing options are available for new customers.

## Capacity-based licensing packages

Capacity-based licensing enables you to pay for Cloud Volumes ONTAP per TiB of capacity. The license is associated with your NetApp account and enables you to charge multiple systems against the license, as long as enough capacity is available through the license.

Capacity-based licensing is available in the form of a *package*. When you deploy a Cloud Volumes ONTAP system, you can choose from several licensing packages based on your business needs.

## Keystone Flex Subscription

A pay-as-you-grow subscription-based service that delivers a seamless hybrid cloud experience for those preferring OpEx consumption models to upfront CapEx or leasing.

Charging is based on the size of your committed capacity for one or more Cloud Volumes ONTAP HA pairs in your Keystone Flex Subscription.

The previous by-node licensing model remains available for existing customers who have already purchased a license or who have an active marketplace subscription.

[Learn more about these licensing options](#)

# Supported configurations

## Supported configurations in AWS

Several Cloud Volumes ONTAP configurations are supported in AWS.

### Supported number of nodes

Cloud Volumes ONTAP is available in AWS as a single node system and as a high-availability (HA) pair of nodes for fault tolerance and nondisruptive operations.

Upgrading a single node system to an HA pair is not supported. If you want to switch between a single node system and an HA pair, then you need to deploy a new system and replicate data from the existing system to the new system.

### Supported storage

Cloud Volumes ONTAP supports several types of EBS disks, and S3 object storage for data tiering. The maximum storage capacity is determined by the license that you choose.

### Storage support by license

Each license supports a different maximum system capacity. The maximum system capacity includes disk-based storage plus object storage used for data tiering. NetApp doesn't support exceeding this limit.

	Freemium	Capacity-based license	PAYGO Explore	PAYGO Standard	PAYGO Premium	Node-based BYOL
<b>Maximum system capacity (disks + object storage) <sup>1</sup></b>	500 GiB	2 PiB <sup>2</sup>	2 TiB	10 TiB	368 TiB <sup>2</sup>	368 TiB per license <sup>2</sup>
<b>Supported disk types</b>	<ul style="list-style-type: none"><li>• General Purpose SSD (gp3 and gp2) <sup>3,5</sup></li><li>• Provisioned IOPS SSD (io1) <sup>3</sup></li><li>• Throughput Optimized HDD (st1) <sup>4</sup></li></ul>					
<b>Cold data tiering to S3</b>	Supported	Not supported	Supported			

1. For an HA pair, the capacity limit is for the entire HA pair. It's not per node. For example, if you use the Premium license, you can have up to 368 TiB of capacity between both nodes.
2. For some configurations, disk limits prevent you from reaching the capacity limit by using disks alone. In those cases, you can reach the capacity limit by [tiering inactive data to object storage](#). For information about disk limits, refer to [storage limits](#).
3. Enhanced write performance is enabled when using SSDs with all Cloud Volumes ONTAP configurations, except for PAYGO Explore.

4. Tiering data to object storage is not recommended when using Throughput Optimized HDDs (st1).
5. AWS Local Zones only support the General Purpose SSD (gp2) disk type.

### Supported disk sizes

In AWS, an aggregate can contain up to 6 disks that are all the same size. But if you have a configuration that supports the Amazon EBS Elastic Volumes feature, then an aggregate can contain up to 8 disks. [Learn more about support for Elastic Volumes](#)

General Purpose SSDs (gp3 and gp2)	Provisioned IOPS SSDs (io1)	Throughput Optimized HDDs (st1)
<ul style="list-style-type: none"> <li>• 100 GiB</li> <li>• 500 GiB</li> <li>• 1 TiB</li> <li>• 2 TiB</li> <li>• 4 TiB</li> <li>• 6 TiB</li> <li>• 8 TiB</li> <li>• 16 TiB</li> </ul>	<ul style="list-style-type: none"> <li>• 100 GiB</li> <li>• 500 GiB</li> <li>• 1 TiB</li> <li>• 2 TiB</li> <li>• 4 TiB</li> <li>• 6 TiB</li> <li>• 8 TiB</li> <li>• 16 TiB</li> </ul>	<ul style="list-style-type: none"> <li>• 500 GiB</li> <li>• 1 TiB</li> <li>• 2 TiB</li> <li>• 4 TiB</li> <li>• 6 TiB</li> <li>• 8 TiB</li> <li>• 16 TiB</li> </ul>

### Supported EC2 compute

Each Cloud Volumes ONTAP license supports different EC2 instance types. For your convenience, the table below shows the vCPU, RAM, and bandwidth for each supported instance type. [You should refer to AWS for the latest and complete details about EC2 instance types.](#)

Cloud Volumes ONTAP can run on either a Reserved or On-demand EC2 instance. Solutions that use other instance types aren't supported.

The bandwidths shown in the table below match the documented AWS limits for each instance type. These limits don't completely align with what Cloud Volumes ONTAP can provide. For the expected performance, refer to [NetApp Technical Report 4383: Performance Characterization of Cloud Volumes ONTAP in Amazon Web Services with Application Workloads.](#)

License	Supported instance	vCPU	RAM	Flash Cache <sup>1</sup>	Network bandwidth (Gbps)	EBS bandwidth (Mbps)	High write speed <sup>2</sup>
<b>Explore or any other license</b>	m5.xlarge <sup>6</sup>	4	16	Not supported	Up to 10	Up to 4,750	Supported (single node only)



License	Supported instance	vCPU	RAM	Flash Cache <sup>1</sup>	Network bandwidth (Gbps)	EBS bandwidth (Mbps)	High write speed <sup>2</sup>
Standard or any other license	r5.xlarge <sup>6</sup>	4	32	Not supported	Up to 10	Up to 4,750	Supported (single node only)
	m5a.2xlarge	8	32	Not supported	Up to 10	Up to 2,880	Supported
	m5.2xlarge <sup>6</sup>	8	32	Not supported	Up to 10	Up to 4,750	Supported

License	Supported instance	vCPU	RAM	Flash Cache <sup>1</sup>	Network bandwidth (Gbps)	EBS bandwidth (Mbps)	High write speed <sup>2</sup>
Premium or any other license							

License	Supported instance type	vCPU	RAM	Flash Cache	Network bandwidth (Gbps)	EBS bandwidth (Mbps)	High write speed
	r5.12xlarge <sup>3</sup>	48	384	Not supported	10	9,500	Supported
	m5d.xlarge	64 <sup>4</sup>	384	Supported	10	9,500	Supported
	m6id.32xlarge	64 <sup>4</sup>	512	Supported	50	40,000	Supported

- Some instance types include local NVMe storage, which Cloud Volumes ONTAP uses as *Flash Cache*. Flash Cache speeds access to data through real-time intelligent caching of recently read user data and NetApp metadata. It's effective for random read-intensive workloads, including databases, email, and file services. Compression must be disabled on all volumes to take advantage of the Flash Cache performance improvements. [Learn more about Flash Cache](#).
- Cloud Volumes ONTAP supports high write speed with most instance types when using an HA pair. High write speed is supported with all instance types when using a single node system. [Learn more about choosing a write speed](#).
- The r5.12xlarge instance type has a known limitation with supportability. If a node unexpectedly reboots due to a panic, the system might not collect core files used to troubleshoot and root cause the problem. The customer accepts the risks and limited support terms and bears all support responsibility if this condition occurs. This limitation affects newly deployed HA pairs and HA pairs upgraded from 9.8. The limitation does not affect newly deployed single node systems.
- While these EC2 instance types support more than 64 vCPUs, Cloud Volumes ONTAP only supports up to 64 vCPUs.
- When you choose an EC2 instance type, you can specify whether it is a shared instance or a dedicated instance.
- AWS Local Zones are supported in the following EC2 instance type families with sizes xlarge to 4xlarge: M5, C5, C5d, R5, and R5d. [You should refer to AWS for the latest and complete details about supported EC2 instance types in Local Zones](#).

High write speed isn't supported with these instance types in AWS Local Zones.

## Supported regions

For AWS region support, see [Cloud Volumes Global Regions](#).

## Supported configurations in Azure

Several Cloud Volumes ONTAP configurations are supported in Azure.

### Supported configurations by license

Cloud Volumes ONTAP is available in Azure as a single node system and as a high-availability (HA) pair of nodes for fault tolerance and nondisruptive operations.

Upgrading a single node system to an HA pair is not supported. If you want to switch between a single node system and an HA pair, then you need to deploy a new system and replicate data from the existing system to the new system.

Cloud Volumes ONTAP can run on either a Reserved or On-demand VM instance from your cloud provider. Solutions that use other VM instance types aren't supported.

## **Single node systems**

You can choose from the following capacity-based or node-based licensing configurations when deploying Cloud Volumes ONTAP as a single-node system in Azure.

Cloud Volumes ONTAP can run on either a Reserved or On-demand VM instance from your cloud provider. Solutions that use other VM instance types aren't supported.

## Capacity-based licenses

	Freemium	Optimized	Capacity-based license (Essentials and Professional)
<b>Maximum system capacity (disks + object storage)</b>	500 GiB	2 PiB	2 PiB
<b>Supported virtual machine types</b>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS5_v2</li> <li>• DS13_v2</li> <li>• DS14_v2</li> <li>• DS15_v2</li> <li>• E4s_v3</li> <li>• E8s_v3</li> <li>• E32s_v3<sup>3</sup></li> <li>• E48s_v3<sup>3</sup></li> <li>• E64is_v3<sup>3</sup></li> <li>• E4ds_v4</li> <li>• E8ds_v4</li> <li>• E32ds_v4<sup>3</sup></li> <li>• E48ds_v4<sup>3</sup></li> <li>• E80ids_v4<sup>3</sup></li> <li>• E4ds_v5</li> <li>• E8ds_v5</li> <li>• E20ds_v5<sup>3</sup></li> <li>• E32ds_v5<sup>3</sup></li> <li>• E48ds_v5<sup>3</sup></li> <li>• E64ds_v5<sup>3</sup></li> <li>• L8s_v3<sup>2</sup></li> <li>• L16s_v3<sup>2</sup></li> <li>• L32s_v3<sup>2</sup></li> <li>• L48s_v3<sup>2</sup></li> <li>• L64s_v3<sup>2</sup></li> </ul>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS13_v2</li> <li>• E4s_v3</li> <li>• E8s_v3</li> <li>• E4ds_v4<sup>3</sup></li> <li>• E8ds_v4<sup>3</sup></li> <li>• E4ds_v5</li> <li>• E8ds_v5</li> </ul>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS5_v2</li> <li>• DS13_v2</li> <li>• DS14_v2</li> <li>• DS15_v2</li> <li>• E4s_v3</li> <li>• E8s_v3</li> <li>• E32s_v3<sup>3</sup></li> <li>• E48s_v3<sup>3</sup></li> <li>• E64is_v3<sup>3</sup></li> <li>• E4ds_v4<sup>3</sup></li> <li>• E8ds_v4<sup>3</sup></li> <li>• E32ds_v4<sup>3</sup></li> <li>• E48ds_v4<sup>3</sup></li> <li>• E80ids_v4<sup>3</sup></li> <li>• E4ds_v5</li> <li>• E8ds_v5</li> <li>• E20ds_v5<sup>3</sup></li> <li>• E32ds_v5<sup>3</sup></li> <li>• E48ds_v5<sup>3</sup></li> <li>• E64ds_v5<sup>3</sup></li> <li>• L8s_v3<sup>2</sup></li> <li>• L16s_v3<sup>2</sup></li> <li>• L32s_v3<sup>2</sup></li> <li>• L48s_v3<sup>2</sup></li> <li>• L64s_v3<sup>2</sup></li> </ul>
<b>Supported disk types<sup>4</sup></b>	Standard HDD Managed Disks, Standard SSD Managed Disks, Premium SSD Managed Disks, and Premium SSD v2 Managed Disks.		

Notes:

1. Data tiering to Azure Blob storage isn't supported with PAYGO Explore.
2. This VM type includes local NVMe storage, which Cloud Volumes ONTAP uses as *Flash Cache*. Flash Cache speeds access to data through real-time intelligent caching of recently read user data and NetApp metadata. It is effective for random read-intensive workloads, including databases, email, and file services. [Learn more](#).

The minimum ONTAP version required for configuring Flash Cache on Azure is 9.13.1 GA.

3. These VM types use an [Ultra SSD](#) for VNVDRAM, which provides better write performance.

If you choose any of these VM types when you deploy a new Cloud Volumes ONTAP system, you can't change to another VM type that *doesn't* use an Ultra SSD for VNVDRAM. For example, you can't change from E8ds\_v4 to E8s\_v3, but you can change from E8ds\_v4 to E32ds\_v4 because both of those VM types use Ultra SSDs.

Similarly, when you deploy a new Cloud Volumes ONTAP system, you can't change the VM type to one that *doesn't* support Premium SSD v2 Managed Disks. To learn more about the supported configurations for Premium SSD v2 Managed Disks, refer to [HA single availability zone configuration with shared managed disks](#).

Conversely, if you deployed Cloud Volumes ONTAP using any other VM type, you won't be able to change to a VM type that uses an Ultra SSD for VNVDRAM. For example, you can't change from E8s\_v3 to E8ds\_v4.

4. High write speed is supported with all instance types when using a single node system. You can enable high write speed from BlueXP during deployment or any time after. [Learn more about choosing a write speed](#).
5. Enhanced write performance is enabled when using SSDs.

#### Node-based licenses

	PAYGO Explore	PAYGO Standard	PAYGO Premium	Node-based BYOL
<b>Maximum system capacity (disks + object storage)</b>	2 TiB <sup>1</sup>	10 TiB	368 TiB	368 TiB per license

	PAYGO Explore	PAYGO Standard	PAYGO Premium	Node-based BYOL
<b>Supported virtual machine types</b>	<ul style="list-style-type: none"> <li>• E4s_v3</li> <li>• E4ds_v4 <sup>3</sup></li> <li>• E4ds_v5</li> </ul>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS13_v2</li> <li>• E8s_v3</li> <li>• E8ds_v4 <sup>3</sup></li> <li>• E8ds_v5</li> <li>• L8s_v3 <sup>2</sup></li> </ul>	<ul style="list-style-type: none"> <li>• DS5_v2</li> <li>• DS14_v2</li> <li>• DS15_v2</li> <li>• E32s_v3 <sup>3</sup></li> <li>• E48s_v3 <sup>3</sup></li> <li>• E64is_v3 <sup>3</sup></li> <li>• E32ds_v4 <sup>3</sup></li> <li>• E48ds_v4 <sup>3</sup></li> <li>• E80ids_v4 <sup>3</sup></li> <li>• E20ds_v5 <sup>3</sup></li> <li>• E32ds_v5 <sup>3</sup></li> <li>• E48ds_v5 <sup>3</sup></li> <li>• E64ds_v5 <sup>3</sup></li> </ul>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS5_v2</li> <li>• DS13_v2</li> <li>• DS14_v2</li> <li>• DS15_v2</li> <li>• E4s_v3</li> <li>• E8s_v3</li> <li>• E32s_v3 <sup>3</sup></li> <li>• E48s_v3 <sup>3</sup></li> <li>• E64is_v3 <sup>3</sup></li> <li>• E4ds_v4 <sup>3</sup></li> <li>• E8ds_v4 <sup>3</sup></li> <li>• E32ds_v4 <sup>3</sup></li> <li>• E48ds_v4 <sup>3</sup></li> <li>• E80ids_v4 <sup>3</sup></li> <li>• E4ds_v5</li> <li>• E8ds_v5</li> <li>• E20ds_v5 <sup>3</sup></li> <li>• E32ds_v5 <sup>3</sup></li> <li>• E48ds_v5 <sup>3</sup></li> <li>• E64ds_v5 <sup>3</sup></li> <li>• L8s_v3 <sup>2</sup></li> <li>• L16s_v3 <sup>2</sup></li> <li>• L32s_v3 <sup>2</sup></li> <li>• L48s_v3 <sup>2</sup></li> <li>• L64s_v3 <sup>2</sup></li> </ul>
<b>Supported disk types <sup>4</sup></b>	Standard HDD Managed Disks, Standard SSD Managed Disks, and Premium SSD Managed Disks			

Notes:

1. Data tiering to Azure Blob storage isn't supported with PAYGO Explore.
2. This VM type includes local NVMe storage, which Cloud Volumes ONTAP uses as *Flash Cache*. Flash Cache speeds access to data through real-time intelligent caching of recently read user data and NetApp metadata. It is effective for random read-intensive workloads, including databases, email, and file services. [Learn more](#).
3. These VM types use an [Ultra SSD](#) for VNVRAM, which provides better write performance.

If you choose any of these VM types when you deploy a new Cloud Volumes ONTAP system, you can't change to another VM type that *doesn't* use an Ultra SSD for VNVDRAM. For example, you can't change from E8ds\_v4 to E8s\_v3, but you can change from E8ds\_v4 to E32ds\_v4 because both of those VM types use Ultra SSDs.

Conversely, if you deployed Cloud Volumes ONTAP using any other VM type, you won't be able to change to a VM type that uses an Ultra SSD for VNVDRAM. For example, you can't change from E8s\_v3 to E8ds\_v4.

4. High write speed is supported with all instance types when using a single node system. You can enable high write speed from BlueXP during deployment or any time after. [Learn more about choosing a write speed.](#)
5. Enhanced write performance is enabled when using SSDs.

## HA pairs

You can choose from the following configurations when deploying Cloud Volumes ONTAP as an HA pair in Azure.

### HA pairs with page blob



You can use the following configurations with the existing Cloud Volumes ONTAP HA page blob deployments in Azure. Page blobs are not supported for new deployments.



## Capacity-based licenses

	Freemium	Optimized	Capacity-based license (Essentials and Professional)
<b>Maximum system capacity (disks + object storage)</b>	500 GiB	2 PiB	2 PiB
<b>Supported virtual machine types</b>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS5_v2 <sup>1</sup></li> <li>• DS13_v2</li> <li>• DS14_v2 <sup>1</sup></li> <li>• DS15_v2 <sup>1</sup></li> <li>• E8s_v3</li> <li>• E48s_v3 <sup>1</sup></li> <li>• E8ds_v4 <sup>3</sup></li> <li>• E32ds_v4 <sup>1,3</sup></li> <li>• E48ds_v4 <sup>1,3</sup></li> <li>• E80ids_v4 <sup>1,2,3</sup></li> <li>• E8ds_v5</li> <li>• E20ds_v5 <sup>1</sup></li> <li>• E32ds_v5 <sup>1</sup></li> <li>• E48ds_v5 <sup>1</sup></li> <li>• E64ds_v5 <sup>1</sup></li> </ul>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS13_v2</li> <li>• E8s_v3</li> <li>• E8ds_v4 <sup>3</sup></li> <li>• E8ds_v5</li> </ul>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS5_v2 <sup>1</sup></li> <li>• DS13_v2</li> <li>• DS14_v2 <sup>1</sup></li> <li>• DS15_v2 <sup>1</sup></li> <li>• E8s_v3</li> <li>• E48s_v3 <sup>1</sup></li> <li>• E8ds_v4 <sup>3</sup></li> <li>• E32ds_v4 <sup>1,3</sup></li> <li>• E48ds_v4 <sup>1,3</sup></li> <li>• E80ids_v4 <sup>1,2,3</sup></li> <li>• E8ds_v5</li> <li>• E20ds_v5 <sup>1</sup></li> <li>• E32ds_v5 <sup>1</sup></li> <li>• E48ds_v5 <sup>1</sup></li> <li>• E64ds_v5 <sup>1</sup></li> </ul>
<b>Supported disk types</b>	Page blobs		

### Notes:

1. Cloud Volumes ONTAP supports high write speed with these VM types when using an HA pair. You can enable high write speed from BlueXP during deployment or any time after. [Learn more about choosing a write speed.](#)
2. This VM is recommended only when Azure maintenance control is needed. It's not recommended for any other use case due to the higher pricing.
3. These VMs are only supported in deployments of Cloud Volumes ONTAP 9.11.1 or earlier. With these VM types you can upgrade an existing page blob deployment from Cloud Volumes ONTAP 9.11.1 to 9.12.1. You cannot perform new page blob deployments with Cloud Volumes ONTAP 9.12.1 or above.

## Node-based licenses

	PAYGO Standard	PAYGO Premium	Node-based BYOL
<b>Maximum system capacity (disks + object storage)</b>	10 TiB	368 TiB	368 TiB per license

	PAYGO Standard	PAYGO Premium	Node-based BYOL
<b>Supported virtual machine types</b>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS13_v2</li> <li>• E8s_v3</li> <li>• E8ds_v4 <sup>3</sup></li> <li>• E8ds_v5</li> </ul>	<ul style="list-style-type: none"> <li>• DS5_v2 <sup>1</sup></li> <li>• DS14_v2 <sup>1</sup></li> <li>• DS15_v2 <sup>1</sup></li> <li>• E48s_v3 <sup>1</sup></li> <li>• E32ds_v4 <sup>1,3</sup></li> <li>• E48ds_v4 <sup>1,3</sup></li> <li>• E80ids_v4 <sup>1,2,3</sup></li> <li>• E20ds_v5 <sup>1</sup></li> <li>• E32ds_v5 <sup>1</sup></li> <li>• E48ds_v5 <sup>1</sup></li> <li>• E64ds_v5 <sup>1</sup></li> </ul>	<ul style="list-style-type: none"> <li>• DS4_v2</li> <li>• DS5_v2 <sup>1</sup></li> <li>• DS13_v2</li> <li>• DS14_v2 <sup>1</sup></li> <li>• DS15_v2 <sup>1</sup></li> <li>• E8s_v3</li> <li>• E48s_v3 <sup>1</sup></li> <li>• E8ds_v4 <sup>3</sup></li> <li>• E32ds_v4 <sup>1,3</sup></li> <li>• E48ds_v4 <sup>1,3</sup></li> <li>• E80ids_v4 <sup>1,2,3</sup></li> <li>• E4ds_v5</li> <li>• E8ds_v5</li> <li>• E20ds_v5 <sup>1</sup></li> <li>• E32ds_v5 <sup>1</sup></li> <li>• E48ds_v5 <sup>1</sup></li> <li>• E64ds_v5 <sup>1</sup></li> </ul>
<b>Supported disk types</b>	Page blobs		

Notes:

1. Cloud Volumes ONTAP supports high write speed with these VM types when using an HA pair. You can enable high write speed from BlueXP during deployment or any time after. [Learn more about choosing a write speed.](#)
2. This VM is recommended only when Azure maintenance control is needed. It's not recommended for any other use case due to the higher pricing.
3. These VMs are only supported in deployments of Cloud Volumes ONTAP 9.11.1 or earlier. With these VM types you can upgrade an existing page blob deployment from Cloud Volumes ONTAP 9.11.1 to 9.12.1. You cannot perform new page blob deployments with Cloud Volumes ONTAP 9.12.1 or above.

**HA pairs with shared managed disks**

You can choose from the following configurations when deploying Cloud Volumes ONTAP as an HA pair in Azure.

## Capacity-based licenses

	Freemium	Optimized	Capacity-based license (Essentials and Professional)
<b>Maximum system capacity (disks + object storage)</b>	500 GiB	2 PiB	2 PiB
<b>Supported virtual machine types</b>	<ul style="list-style-type: none"> <li>• E8ds_v4</li> <li>• E32ds_v4 <sup>1</sup></li> <li>• E48ds_v4 <sup>1</sup></li> <li>• E80ids_v4 <sup>1,2</sup></li> <li>• E8ds_v5 <sup>4</sup></li> <li>• E20ds_v5 <sup>1,4</sup></li> <li>• E32ds_v5 <sup>1,4</sup></li> <li>• E48ds_v5 <sup>1,4</sup></li> <li>• E64ds_v5 <sup>1,4</sup></li> <li>• L16s_v3 <sup>1,3,5</sup></li> <li>• L32s_v3 <sup>1,3,5</sup></li> <li>• L48s_v3 <sup>1,3,5</sup></li> <li>• L64s_v3 <sup>1,3,5</sup></li> </ul>	<ul style="list-style-type: none"> <li>• E8ds_v4</li> <li>• E8ds_v5 <sup>4</sup></li> </ul>	<ul style="list-style-type: none"> <li>• E8ds_v4</li> <li>• E32ds_v4 <sup>1</sup></li> <li>• E48ds_v4 <sup>1</sup></li> <li>• E80ids_v4 <sup>1,2</sup></li> <li>• E8ds_v5 <sup>4</sup></li> <li>• E20ds_v5 <sup>1,4</sup></li> <li>• E32ds_v5 <sup>1,4</sup></li> <li>• E48ds_v5 <sup>1,4</sup></li> <li>• E64ds_v5 <sup>1,4</sup></li> <li>• L16s_v3 <sup>1,3,5</sup></li> <li>• L32s_v3 <sup>1,3,5</sup></li> <li>• L48s_v3 <sup>1,3,5</sup></li> <li>• L64s_v3 <sup>1,3,5</sup></li> </ul>
<b>Supported disk types</b>	Standard HDD Managed Disks, Standard SSD Managed Disks, Premium SSD Managed Disks, and Premium SSD v2 Managed Disks.		

### Notes:

1. Cloud Volumes ONTAP supports high write speed with these VM types when using an HA pair. You can enable high write speed from BlueXP during deployment or any time after. [Learn more about choosing a write speed.](#)
2. This VM is recommended only when Azure maintenance control is needed. It's not recommended for any other use case due to the higher pricing.
3. Multiple availability zone support starts from ONTAP version 9.13.1.
4. Multiple availability zone support starts from ONTAP version 9.14.1 RC1.
5. This VM type includes local NVMe storage, which Cloud Volumes ONTAP uses as *Flash Cache*. Flash Cache speeds access to data through real-time intelligent caching of recently read user data and NetApp metadata. It is effective for random read-intensive workloads, including databases, email, and file services. [Learn more.](#)

## Node-based licenses

	PAYGO Standard	PAYGO Premium	Node-based BYOL
<b>Maximum system capacity (disks + object storage)</b>	10 TiB	368 TiB	368 TiB per license
<b>Supported virtual machine types</b>	<ul style="list-style-type: none"> <li>• E8ds_v4 <sup>4</sup></li> <li>• E8ds_v5</li> </ul>	<ul style="list-style-type: none"> <li>• E32ds_v4 <sup>1,4</sup></li> <li>• E48ds_v4 <sup>1,4</sup></li> <li>• E80ids_v4 <sup>1,2,4</sup></li> <li>• E20ds_v5 <sup>1</sup></li> <li>• E32ds_v5 <sup>1</sup></li> <li>• E48ds_v5 <sup>1</sup></li> <li>• E64ds_v5 <sup>1</sup></li> <li>• L16s_v3 <sup>1,4,5</sup></li> <li>• L32s_v3 <sup>1,4,5</sup></li> <li>• L48s_v3 <sup>1,4,5</sup></li> <li>• L64s_v3 <sup>1,4,5</sup></li> </ul>	<ul style="list-style-type: none"> <li>• E8ds_v4 <sup>4</sup></li> <li>• E32ds_v4 <sup>1,4</sup></li> <li>• E48ds_v4 <sup>1,4</sup></li> <li>• E80ids_v4 <sup>1,2,4</sup></li> <li>• E4ds_v5</li> <li>• E8ds_v5</li> <li>• E20ds_v5 <sup>1</sup></li> <li>• E32ds_v5 <sup>1</sup></li> <li>• E48ds_v5 <sup>1</sup></li> <li>• E64ds_v5 <sup>1</sup></li> <li>• L16s_v3 <sup>1,4,5</sup></li> <li>• L32s_v3 <sup>1,4,5</sup></li> <li>• L48s_v3 <sup>1,4,5</sup></li> <li>• L64s_v3 <sup>1,4,5</sup></li> </ul>
<b>Supported disk types</b>	Managed disks		

Notes:

1. Cloud Volumes ONTAP supports high write speed with these VM types when using an HA pair. You can enable high write speed from BlueXP during deployment or any time after. [Learn more about choosing a write speed.](#)
2. This VM is recommended only when Azure maintenance control is needed. It's not recommended for any other use case due to the higher pricing.
3. These VM types are only supported for HA pairs in a single availability zone configuration running on shared managed disks.
4. These VM types are supported for HA pairs in single availability zone and multiple availability zone configurations running on shared managed disks. For Ls\_v3 VM types, multiple availability zone support starts from ONTAP version 9.13.1. For Eds\_v5 VM types, multiple availability zone support starts from ONTAP version 9.14.1 RC1.
5. This VM type includes local NVMe storage, which Cloud Volumes ONTAP uses as *Flash Cache*. Flash Cache speeds access to data through real-time intelligent caching of recently read user data and NetApp metadata. It is effective for random read-intensive workloads, including databases, email, and file services. [Learn more.](#)

## Supported disk sizes

In Azure, an aggregate can contain up to 12 disks that are all the same type and size.

## Single node systems

Single node systems use Azure Managed Disks. The following disk sizes are supported:

Premium SSD	Standard SSD	Standard HDD
<ul style="list-style-type: none"><li>• 500 GiB</li><li>• 1 TiB</li><li>• 2 TiB</li><li>• 4 TiB</li><li>• 8 TiB</li><li>• 16 TiB</li><li>• 32 TiB</li></ul>	<ul style="list-style-type: none"><li>• 100 GiB</li><li>• 500 GiB</li><li>• 1 TiB</li><li>• 2 TiB</li><li>• 4 TiB</li><li>• 8 TiB</li><li>• 16 TiB</li><li>• 32 TiB</li></ul>	<ul style="list-style-type: none"><li>• 100 GiB</li><li>• 500 GiB</li><li>• 1 TiB</li><li>• 2 TiB</li><li>• 4 TiB</li><li>• 8 TiB</li><li>• 16 TiB</li><li>• 32 TiB</li></ul>

## HA pairs

HA pairs use Azure Managed Disks. The following disk type and sizes are supported.

(Page blobs are supported with HA pairs deployed before the 9.12.1 release.)

### Premium SSD

- 500 GiB
- 1 TiB
- 2 TiB
- 4 TiB
- 8 TiB
- 16 TiB (managed disks only)
- 32 TiB (managed disks only)

## Supported regions

For Azure region support, see [Cloud Volumes Global Regions](#).

## Supported configurations in Google Cloud

Several Cloud Volumes ONTAP configurations are supported in Google Cloud.

### Supported configurations by license

Cloud Volumes ONTAP is available in Google Cloud as a single node system and as a high-availability (HA) pair of nodes for fault tolerance and nondisruptive operations.

Upgrading a single node system to an HA pair isn't supported. If you want to switch between a single node system and an HA pair, then you need to deploy a new system and replicate data from the existing system to the new system.

Cloud Volumes ONTAP can run on either a Reserved or On-demand VM instance from your cloud provider. Solutions that use other VM instance types aren't supported.

## Capacity-based licenses

	Freemium	Optimized	Capacity-based license (Essentials and Professional)
<b>Maximum system capacity (disks + object storage)</b>	500 GiB	2 PiB	2 PiB
<b>Supported machine types <sup>3</sup></b>	<ul style="list-style-type: none"><li>• n1-standard-8</li><li>• n1-standard-32</li><li>• n2-standard-4</li><li>• n2-standard-8</li><li>• n2-standard-16</li><li>• n2-standard-32</li><li>• n2-standard-48</li><li>• n2-standard-64</li></ul>	<ul style="list-style-type: none"><li>• n2-standard-4</li><li>• n2-standard-8</li></ul>	<ul style="list-style-type: none"><li>• n1-standard-8</li><li>• n1-standard-32</li><li>• n2-standard-4</li><li>• n2-standard-8</li><li>• n2-standard-16</li><li>• n2-standard-32</li><li>• n2-standard-48</li><li>• n2-standard-64</li></ul>
<b>Supported disk types</b>	Balanced persistent disks <sup>4</sup> , Performance (SSD) persistent disks <sup>4</sup> , and Standard (HDD) persistent disks.		

### Notes:

1. Disk limits can prevent you from reaching the maximum system capacity limit by using disks alone. You can reach the capacity limit by [tiering inactive data to object storage](#).

[Learn more about disk limits in Google Cloud.](#)

2. Data tiering to Google Cloud Storage isn't supported with PAYGO Explore.
3. The custom-4-16384 machine type is no longer supported with new Cloud Volumes ONTAP systems.

If you have an existing system running on this machine type, you can keep using it, but we recommend switching to the n2-standard-4 machine type.

4. Enhanced write performance is enabled when using Balanced persistent disks and Performance (SSD) persistent disks.
5. The BlueXP interface shows an additional supported machine type for Standard and BYOL: n1-highmem-4. However, this machine type isn't meant for production environments. We've made it available for a specific lab environment only.
6. Beginning with Cloud Volumes ONTAP 9.13.0, *Flash Cache*, high write speed, and a higher maximum transmission unit (MTU) of 8,896 bytes, are available for the following HA pair deployment instances:
  - n2-standard-16
  - n2-standard-32
  - n2-standard-48
  - n2-standard-64

You can enable *Flash Cache*, and high write speed when deploying an eligible instance type. To

enable the higher maximum transmission unit of 8,896 bytes, you must chose VPC-1, VPC-2, or VPC-3 for the deployment. The higher MTU enables higher network throughput. For more information on launching one of these deployments, see [Launching an HA pair in Google Cloud](#).



*Flash cache*, high write mode, and an MTU of 8,896 are feature-dependent and cannot be disabled individually within a configured instance.

### Node-based licenses

	PAYGO Explore	PAYGO Standard	PAYGO Premium	Node-based BYOL
<b>Maximum system capacity (disks + object storage)</b>	2 TB <sup>2</sup>	10 TiB	368 TiB	368 TiB per license
<b>Supported machine types <sup>3</sup></b>	<ul style="list-style-type: none"> <li>n2-standard-4</li> </ul>	<ul style="list-style-type: none"> <li>n1-standard-8</li> <li>n2-standard-8</li> </ul>	<ul style="list-style-type: none"> <li>n1-standard-32</li> <li>n2-standard-16</li> <li>n2-standard-32</li> <li>n2-standard-48</li> <li>n2-standard-64</li> </ul>	<ul style="list-style-type: none"> <li>n1-standard-8</li> <li>n1-standard-32</li> <li>n2-standard-4</li> <li>n2-standard-8</li> <li>n2-standard-16</li> <li>n2-standard-32</li> <li>n2-standard-48</li> <li>n2-standard-64</li> </ul>
<b>Supported disk types</b>	Balanced persistent disks <sup>4</sup> , Performance (SSD) persistent disks <sup>4</sup> , and Standard (HDD) persistent disks.			

### Notes:

1. Disk limits can prevent you from reaching the maximum system capacity limit by using disks alone. You can reach the capacity limit by [tiering inactive data to object storage](#).

[Learn more about disk limits in Google Cloud](#).

2. Data tiering to Google Cloud Storage isn't supported with PAYGO Explore.
3. The custom-4-16384 machine type is no longer supported with new Cloud Volumes ONTAP systems.

If you have an existing system running on this machine type, you can keep using it, but we recommend switching to the n2-standard-4 machine type.

4. Enhanced write performance is enabled when using Balanced persistent disks and Performance (SSD) persistent disks.
5. The BlueXP interface shows an additional supported machine type for Standard and BYOL: n1-highmem-4. However, this machine type isn't meant for production environments. We've made it available for a specific lab environment only.
6. Starting with Cloud Volumes ONTAP software version 9.13.0, *Flash Cache*, high write speed, and a higher maximum transmission unit (MTU) of 8,896 bytes, are available for the following HA pair deployment instances:



- n2-standard-16
- n2-standard-32
- n2-standard-48
- n2-standard-64

You can enable *Flash Cache*, and high write speed when deploying an eligible instance type. To enable the higher maximum transmission unit of 8,896 bytes, you must chose VPC-1, VPC-2, or VPC-3 for the deployment. The higher MTU enables higher network throughput. For more information on launching one of these deployments, see [Launching an HA pair in Google Cloud](#).



*Flash cache*, high write mode, and an MTU of 8,896 are feature-dependent and cannot be disabled individually within a configured instance.

## Supported disk sizes

In Google Cloud, an aggregate can contain up to 6 disks that are all the same type and size. The following disk sizes are supported:

- 100 GB
- 500 GB
- 1 TB
- 2 TB
- 4 TB
- 8 TB
- 16 TB
- 64 TB

## Supported regions

For Google Cloud region support, see [Cloud Volumes Global Regions](#).

# Storage limits

## Storage limits in AWS

Cloud Volumes ONTAP has storage configuration limits to provide reliable operations. For best performance, do not configure your system at the maximum values.

### Maximum system capacity by license

The maximum system capacity for a Cloud Volumes ONTAP system is determined by its license. The maximum system capacity includes disk-based storage plus object storage used for data tiering.

NetApp doesn't support exceeding the system capacity limit. If you reach the licensed capacity limit, BlueXP displays an action required message and no longer allows you to add additional disks.

For some configurations, disk limits prevent you from reaching the capacity limit by using disks alone. In those cases, you can reach the capacity limit by [tiering inactive data to object storage](#). Refer to capacity and disk limits below for more details.

License	Maximum system capacity (disks + object storage)
Freemium	500 GiB
PAYGO Explore	2 TiB (data tiering is not supported with Explore)
PAYGO Standard	10 TiB
PAYGO Premium	368 TiB
Node-based license	2 PiB (requires multiple licenses)
Capacity-based license	2 PiB

### For HA, is the license capacity limit per node or for the entire HA pair?

The capacity limit is for the entire HA pair. It is not per node. For example, if you use the Premium license, you can have up to 368 TiB of capacity between both nodes.

### For an HA system in AWS, does mirrored data count against the capacity limit?

No, it doesn't. Data in an AWS HA pair is synchronously mirrored between the nodes so that the data is available in the event of failure. For example, if you purchase an 8 TiB disk on node A, BlueXP also allocates an 8 TiB disk on node B that is used for mirrored data. While 16 TiB of capacity was provisioned, only 8 TiB counts against the license limit.

## Aggregate limits

Cloud Volumes ONTAP uses EBS volumes as disks and groups them into *aggregates*. Aggregates provide storage to volumes.

Parameter	Limit
Maximum number of aggregates	Single node: Same as the disk limit HA pairs: 18 in a node <sup>1</sup>
Maximum aggregate size <sup>2</sup>	<ul style="list-style-type: none"> <li>• 96 TiB of raw capacity</li> <li>• 128 TiB of raw capacity with Elastic Volumes <sup>3</sup></li> </ul>
Disks per aggregate <sup>4</sup>	<ul style="list-style-type: none"> <li>• 1-6</li> <li>• 1-8 with Elastic Volumes <sup>3</sup></li> </ul>
Maximum number of RAID groups per aggregate	1

Notes:

1. It's not possible to create 18 aggregates on both nodes in an HA pair because doing so would exceed the data disk limit.
2. The maximum aggregate size is based on the disks that comprise the aggregate. The limit does not include object storage used for data tiering.
3. If you have a configuration that supports the Amazon EBS Elastic Volumes feature, then an aggregate can contain up to 8 disks, which provides up to 128 TiB of capacity. The Amazon EBS Elastic Volumes feature is enabled by default on *new* Cloud Volumes ONTAP 9.11.0 or later systems when using gp3 or io1 disks. [Learn more about support for Elastic Volumes](#)
4. All disks in an aggregate must be the same size.

## Disk and tiering limits by EC2 instance

Capacity limits are different depending on the EC2 instance type family that you use and whether you're using a single node system or an HA pair.

The following notes provide details about the numbers that you'll see in the tables below:

- The disk limits are specific to disks that contain user data.  
The limits do not include the boot disk and root disk.
- A maximum system capacity is listed when using disks alone and when using disks and cold data tiering to object storage.
- Cloud Volumes ONTAP uses EBS volumes as disks, with a maximum disk size of 16 TiB.

### Limits for capacity-based licensing

The following disk limits apply to Cloud Volumes ONTAP systems that use a capacity-based licensing package. [Learn about Cloud Volumes ONTAP licensing options](#)

#### Single node

Instance	Max disks per node	Max system capacity with disks alone	Max system capacity with disks and data tiering
c5, m5, and r5 instances	21	336 TiB	2 PiB
<ul style="list-style-type: none"> <li>m5dn.24xlarge</li> <li>m6id.32xlarge</li> </ul>	19 <sup>1</sup>	304 TiB	2 PiB

1. This instance type has more local NVMe disks than other instance types, which means a smaller number of data disks are supported.

#### HA pairs

Instance	Max disks per node	Max system capacity with disks alone	Max system capacity with disks and data tiering
c5, m5, and r5 instances	18	288 TiB	2 PiB
<ul style="list-style-type: none"> <li>m5dn.24xlarge</li> <li>m6id.32xlarge</li> </ul>	16 <sup>1</sup>	256 TiB	2 PiB

1. This instance type has more local NVMe disks than other instance types, which means a smaller number of data disks are supported.

#### Limits for node-based licensing

The following disk limits apply to Cloud Volumes ONTAP systems that use node-based licensing, which is the previous generation licensing model that enabled you to license Cloud Volumes ONTAP by node. Node-based licensing is still available for existing customers.

You can purchase multiple node-based licenses for a Cloud Volumes ONTAP BYOL single node or HA pair system to allocate more than 368 TiB of capacity, up to the maximum tested and supported system capacity limit of 2 PiB. Be aware that disk limits can prevent you from reaching the capacity limit by using disks alone. You can go beyond the disk limit by [tiering inactive data to object storage](#). [Learn how to add additional system licenses to Cloud Volumes ONTAP](#). Though Cloud Volumes ONTAP supports up to the maximum tested and supported system capacity of 2 PiB, crossing the 2 PiB limit results in an unsupported system configuration.

AWS Secret Cloud and Top Secret Cloud regions support purchases of multiple node-based licenses starting with Cloud Volumes ONTAP 9.12.1.

#### Single node with PAYGO Premium

Instance	Max disks per node	Max system capacity with disks alone	Max system capacity with disks and data tiering
c5, m5, and r5 instances	21 <sup>1</sup>	336 TiB	368 TiB

Instance	Max disks per node	Max system capacity with disks alone	Max system capacity with disks and data tiering
<ul style="list-style-type: none"> <li>• m5dn.24xlarge</li> <li>• m6id.32xlarge</li> </ul>	19 <sup>2</sup>	304 TiB	368 TiB

1. 21 data disks is the limit for *new* deployments of Cloud Volumes ONTAP. If you upgrade a system that was created with version 9.7 or earlier, then the system continues to support 22 disks. One less data disk is supported on new systems that use these instance types because of the addition of a core disk starting with the 9.8 release.
2. This instance type has more local NVMe disks than other instance types, which means a smaller number of data disks are supported.

#### Single node with BYOL

Instance	Max disks per node	Max system capacity with one license		Max system capacity with multiple licenses	
		Disks alone	Disks + data tiering	Disks alone	Disks + data tiering
c5, m5, and r5 instances	21 <sup>1</sup>	336 TiB	368 TiB	336 TiB	2 PiB
<ul style="list-style-type: none"> <li>• m5dn.24xlarge</li> <li>• m6id.32xlarge</li> </ul>	19 <sup>2</sup>	304 TiB	368 TiB	304 TiB	2 PiB

1. 21 data disks is the limit for *new* deployments of Cloud Volumes ONTAP. If you upgrade a system that was created with version 9.7 or earlier, then the system continues to support 22 disks. One less data disk is supported on new systems that use these instance types because of the addition of a core disk starting with the 9.8 release.
2. This instance type has more local NVMe disks than other instance types, which means a smaller number of data disks are supported.

#### HA pairs with PAYGO Premium

Instance	Max disks per node	Max system capacity with disks alone	Max system capacity with disks and data tiering
c5, m5, and r5 instances	18 <sup>1</sup>	288 TiB	368 TiB
<ul style="list-style-type: none"> <li>• m5dn.24xlarge</li> <li>• m6id.32xlarge</li> </ul>	16 <sup>2</sup>	256 TiB	368 TiB

- 18 data disks is the limit for *new* deployments of Cloud Volumes ONTAP. If you upgrade a system that was created with version 9.7 or earlier, then the system continues to support 19 disks. One less data disk is supported on new systems that use these instance types because of the addition of a core disk starting with the 9.8 release.
- This instance type has more local NVMe disks than other instance types, which means a smaller number of data disks are supported.

#### HA pairs with BYOL

Instance	Max disks per node	Max system capacity with one license		Max system capacity with multiple licenses	
		Disks alone	Disks + data tiering	Disks alone	Disks + data tiering
c5, m5, and r5 instances	18 <sup>1</sup>	288 TiB	368 TiB	288 TiB	2 PiB
<ul style="list-style-type: none"> <li>m5dn.24xlarge</li> <li>m6id.32xlarge</li> </ul>	16 <sup>2</sup>	256 TiB	368 TiB	256 TiB	2 PiB

- 18 data disks is the limit for *new* deployments of Cloud Volumes ONTAP. If you upgrade a system that was created with version 9.7 or earlier, then the system continues to support 19 disks. One less data disk is supported on new systems that use these instance types because of the addition of a core disk starting with the 9.8 release.
- This instance type has more local NVMe disks than other instance types, which means a smaller number of data disks are supported.

## Storage VM limits

Some configurations enable you to create additional storage VMs (SVMs) for Cloud Volumes ONTAP.

[Learn how to create additional storage VMs.](#)

License type	Storage VM limit
<b>Freemium</b>	24 storage VMs total <sup>1,2</sup>
<b>Capacity-based PAYGO or BYOL</b> <sup>3</sup>	24 storage VMs total <sup>1,2</sup>
<b>Node-based PAYGO</b>	<ul style="list-style-type: none"> <li>1 storage VM for serving data</li> <li>1 storage VM for disaster recovery</li> </ul>
<b>Node-based BYOL</b> <sup>4</sup>	<ul style="list-style-type: none"> <li>24 storage VMs total <sup>1,2</sup></li> </ul>

- The limit can be lower, depending on the EC2 instance type that you use. The limits per instance are listed in the section below.
- These 24 storage VMs can serve data or be configured for disaster recovery (DR).

- For capacity-based licensing, there are no extra licensing costs for additional storage VMs, but there is a 4 TiB minimum capacity charge per storage VM. For example, if you create two storage VMs and each has 2 TiB of provisioned capacity, you'll be charged a total of 8 TiB.
- For node-based BYOL, an add-on license is required for each additional *data-serving* storage VM beyond the first storage VM that comes with Cloud Volumes ONTAP by default. Contact your account team to obtain a storage VM add-on license.

Storage VMs that you configure for disaster recovery (DR) don't require an add-on license (they are free of charge), but they do count against the storage VM limit. For example, if you have 12 data-serving storage VMs and 12 storage VMs configured for disaster recovery, then you've reached the limit and can't create any additional storage VMs.

### Storage VM limit by EC2 instance type

When you create an additional storage VM, you need to allocate private IP addresses to port e0a. The table below identifies the maximum number of private IPs per interface, as well as the number of IP addresses that are available on port e0a after Cloud Volumes ONTAP has been deployed. The number of available IP addresses directly affects the maximum number of storage VMs for that configuration.

The instances listed below are for the c5, m5, and r5 instance families.

Configuration	Instance type	Max private IPs per interface	IPs remaining after deployment <sup>1</sup>	Max storage VMs without a mgmt LIF <sup>2,3</sup>	Max storage VMs with a mgmt LIF <sup>2,3</sup>
<b>Single node</b>	*.xlarge	15	9	10	5
	*.2xlarge	15	9	10	5
	*.4xlarge	30	24	24	12
	*.8xlarge	30	24	24	12
	*.9xlarge	30	24	24	12
	*.12xlarge	30	24	24	12
	*.16xlarge	50	44	24	12
	*.18xlarge	50	44	24	12
	*.24xlarge	50	44	24	12
<b>HA pair in single AZ</b>	*.xlarge	15	10	11	5
	*.2xlarge	15	10	11	5
	*.4xlarge	30	25	24	12
	*.8xlarge	30	25	24	12
	*.9xlarge	30	25	24	12
	*.12xlarge	30	25	24	12
	*.16xlarge	50	45	24	12
	*.18xlarge	50	45	24	12
	*.24xlarge	50	44	24	12

Configuration	Instance type	Max private IPs per interface	IPs remaining after deployment <sup>1</sup>	Max storage VMs without a mgmt LIF <sup>2,3</sup>	Max storage VMs with a mgmt LIF <sup>2,3</sup>
HA pair in multi AZs	*.xlarge	15	12	13	13
	*.2xlarge	15	12	13	13
	*.4xlarge	30	27	24	24
	*.8xlarge	30	27	24	24
	*.9xlarge	30	27	24	24
	*.12xlarge	30	27	24	24
	*.16xlarge	50	47	24	24
	*.18xlarge	50	47	24	24
	*.24xlarge	50	44	24	12

1. This number indicates how many *remaining* private IP addresses are available on port e0a after Cloud Volumes ONTAP is deployed and set up. For example, a \*.2xlarge system supports a maximum of 15 IP addresses per network interface. When an HA pair is deployed in a single AZ, 5 private IP addresses are allocated to port e0a. As a result, an HA pair that uses a \*.2xlarge instance type has 10 private IP addresses remaining for additional storage VMs.
2. The number listed in these columns includes the initial storage VM that BlueXP creates by default. For example, if 24 is listed in this column, it means that you can create 23 additional storage VMs for a total of 24.
3. A management LIF for the storage VM is optional. A management LIF provides a connection to management tools like SnapCenter.

Because it requires a private IP address, it will limit the number of additional storage VMs that you can create. The only exception is an HA pair in multiple AZs. In that case, the IP address for the management LIF is a *floating* IP address so it doesn't count against the *private* IP limit.

## File and volume limits

Logical storage	Parameter	Limit
Files	Maximum size <sup>2</sup>	128 TB
	Maximum per volume	Volume size dependent, up to 2 billion
FlexClone volumes	Hierarchical clone depth <sup>1</sup>	499
FlexVol volumes	Maximum per node	500
	Minimum size	20 MB
	Maximum size <sup>3</sup>	300 TiB
Qtrees	Maximum per FlexVol volume	4,995
Snapshot copies	Maximum per FlexVol volume	1,023



1. Hierarchical clone depth is the maximum depth of a nested hierarchy of FlexClone volumes that can be created from a single FlexVol volume.
2. Beginning with ONTAP 9.12.1P2, the limit is 128 TB. In ONTAP 9.11.1 and earlier versions, the limit is 16 TB.
3. FlexVol volume creation up to maximum size of 300 TiB is supported using the following tools and minimum versions:
  - System Manager and the ONTAP CLI starting from Cloud Volumes ONTAP 9.12.1 P2 and 9.13.0 P2
  - BlueXP starting from Cloud Volumes ONTAP 9.13.1

## iSCSI storage limits

iSCSI storage	Parameter	Limit
<b>LUNs</b>	Maximum per node	1,024
	Maximum number of LUN maps	1,024
	Maximum size	16 TiB
	Maximum per volume	512
<b>igroups</b>	Maximum per node	256
<b>Initiators</b>	Maximum per node	512
	Maximum per igroup	128
<b>iSCSI sessions</b>	Maximum per node	1,024
<b>LIFs</b>	Maximum per port	32
	Maximum per portset	32
<b>Portsets</b>	Maximum per node	256

## Storage limits in Azure

Cloud Volumes ONTAP has storage configuration limits to provide reliable operations. For best performance, do not configure your system at the maximum values.

### Maximum system capacity by license

The maximum system capacity for a Cloud Volumes ONTAP system is determined by its license. The maximum system capacity includes disk-based storage plus object storage used for data tiering.

NetApp doesn't support exceeding the system capacity limit. If you reach the licensed capacity limit, BlueXP displays an action required message and no longer allows you to add additional disks.

License	Maximum system capacity (disks + object storage)
Freemium	500 GiB
PAYGO Explore	2 TiB (data tiering is not supported with Explore)

License	Maximum system capacity (disks + object storage)
PAYGO Standard	10 TiB
PAYGO Premium	368 TiB
Node-based license	2 PiB (requires multiple licenses)
Capacity-based license	2 PiB

### For HA, is the license capacity limit per node or for the entire HA pair?

The capacity limit is for the entire HA pair. It is not per node. For example, if you use the Premium license, you can have up to 368 TiB of capacity between both nodes.

## Aggregate limits

Cloud Volumes ONTAP uses Azure storage as disks and groups them into *aggregates*. Aggregates provide storage to volumes.

Parameter	Limit
Maximum number of aggregates	Same as the disk limit
Maximum aggregate size <sup>1</sup>	384 TiB of raw capacity for single node <sup>2</sup> 352 TiB of raw capacity for single node with PAYGO 96 TiB of raw capacity for HA pairs with page blob 384 TiB of raw capacity for HA pairs with managed disks
Disks per aggregate	1-12 <sup>3</sup>
Maximum number of RAID groups per aggregate	1

Notes:

1. The aggregate capacity limit is based on the disks that comprise the aggregate. The limit does not include object storage used for data tiering.
2. If using node-based licensing, two BYOL licenses are required to reach 384 TiB.
3. All disks in an aggregate must be the same size.

## Disk and tiering limits by VM size

Capacity limits are different depending on the VM size that you use and whether you're using a single node system or an HA pair.

The following notes provide details about the numbers that you'll see in the tables below:

- The disk limits are specific to disks that contain user data.

The limits do not include the root disk, core disk, and VNVDRAM.

- A maximum system capacity is listed when using disks alone and when using disks and cold data tiering to object storage.
- Single node and HA systems which use managed disks have a maximum of 32 TiB per disk. The number of supported disks varies by VM size.
- HA systems which use page blobs have a maximum of 8 TiB per page blob. The number of supported disks varies by VM size.
- The 896 TiB disk-based limit that's listed for single node systems with certain VM sizes is the *tested* limit.

### Limits for capacity-based licensing

The following disk limits apply to Cloud Volumes ONTAP systems that use a capacity-based licensing package. [Learn about Cloud Volumes ONTAP licensing options](#)

#### Single node

VM size	Max data disks per node	Max system capacity with disks alone	Max system capacity with disks and data tiering
DS4_v2	29	896 TiB	2 PiB
DS5_v2	61	896 TiB	2 PiB
DS13_v2	29	896 TiB	2 PiB
DS14_v2	61	896 TiB	2 PiB
DS15_v2	61	896 TiB	2 PiB
E4s_v3	5	160 TiB	2 PiB
E8s_v3	13	416 TiB	2 PiB
E32s_v3	29	896 TiB	2 PiB
E48s_v3	29	896 TiB	2 PiB
E64is_v3	29	896 TiB	2 PiB
E4ds_v4	5	160 TiB	2 PiB
E8ds_v4	13	416 TiB	2 PiB
E32ds_v4	29	896 TiB	2 PiB
E48ds_v4	29	896 TiB	2 PiB
E80ids_v4	61	896 TiB	2 PiB
E4ds_v5	5	160 TiB	2 PiB
E8ds_v5	13	416 TiB	2 PiB
E20ds_v5	29	896 TiB	2 PiB

<b>VM size</b>	<b>Max data disks per node</b>	<b>Max system capacity with disks alone</b>	<b>Max system capacity with disks and data tiering</b>
E32ds_v5	29	896 TiB	2 PiB
E48ds_v5	29	896 TiB	2 PiB
E64ds_v5	29	896 TiB	2 PiB
L8s_v3	12	384 TiB	2 PiB
L16s_v3	28	896 TiB	2 PiB
L32s_v3	28	896 TiB	2 PiB
L48s_v3	28	896 TiB	2 PiB
L64s_v3	28	896 TiB	2 PiB

**HA pairs in a single availability zone with page blobs**

<b>VM size</b>	<b>Max data disks for an HA pair</b>	<b>Max system capacity with disks alone</b>	<b>Max system capacity with disks and data tiering</b>
DS4_v2	29	232 TiB	2 PiB
DS5_v2	61	488 TiB	2 PiB
DS13_v2	29	232 TiB	2 PiB
DS14_v2	61	488 TiB	2 PiB
DS15_v2	61	488 TiB	2 PiB
E8s_v3	13	104 TiB	2 PiB
E48s_v3	29	232 TiB	2 PiB
E8ds_v4	13	104 TiB	2 PiB
E32ds_v4	29	232 TiB	2 PiB
E48ds_v4	29	232 TiB	2 PiB
E80ids_v4	61	488 TiB	2 PiB

**HA pairs in a single availability zone with shared managed disks**

<b>VM size</b>	<b>Max data disks for an HA pair</b>	<b>Max system capacity with disks alone</b>	<b>Max system capacity with disks and data tiering</b>
E8ds_v4	12	384 TiB	2 PiB

<b>VM size</b>	<b>Max data disks for an HA pair</b>	<b>Max system capacity with disks alone</b>	<b>Max system capacity with disks and data tiering</b>
E32ds_v4	28	896 TiB	2 PiB
E48ds_v4	28	896 TiB	2 PiB
E80ids_v4	28	896 TiB	2 PiB
E8ds_v5	12	384 TiB	2 PiB
E20ds_v5	28	896 TiB	2 PiB
E32ds_v5	28	896 TiB	2 PiB
E48ds_v5	28	896 TiB	2 PiB
E64ds_v5	28	896 TiB	2 PiB
L16s_v3	28	896 TiB	2 PiB
L32s_v3	28	896 TiB	2 PiB
L48s_v3	28	896 TiB	2 PiB
L64s_v3	28	896 TiB	2 PiB

**HA pairs in multiple availability zones with shared managed disks**

<b>VM size</b>	<b>Max data disks for an HA pair</b>	<b>Max system capacity with disks alone</b>	<b>Max system capacity with disks and data tiering</b>
E8ds_v4	12	384 TiB	2 PiB
E32ds_v4	28	896 TiB	2 PiB
E48ds_v4	28	896 TiB	2 PiB
E80ids_v4	28	896 TiB	2 PiB
E8ds_v5	12	384 TiB	2 PiB
E20ds_v5	28	896 TiB	2 PiB
E32ds_v5	28	896 TiB	2 PiB
E48ds_v5	28	896 TiB	2 PiB

VM size	Max data disks for an HA pair	Max system capacity with disks alone	Max system capacity with disks and data tiering
E64ds_v5	28	896 TiB	2 PiB
L16s_v3	28	896 TiB	2 PiB
L32s_v3	28	896 TiB	2 PiB
L48s_v3	28	896 TiB	2 PiB
L64s_v3	28	896 TiB	2 PiB

### Limits for node-based licensing

The following disk limits apply to Cloud Volumes ONTAP systems that use node-based licensing, which is the previous generation licensing model that enabled you to license Cloud Volumes ONTAP by node. Node-based licensing is still available for existing customers.

You can purchase multiple node-based licenses for a Cloud Volumes ONTAP BYOL single node or HA pair system to allocate more than 368 TiB of capacity, up to the maximum tested and supported system capacity limit of 2 PiB. Be aware that disk limits can prevent you from reaching the capacity limit by using disks alone. You can go beyond the disk limit by [tiering inactive data to object storage](#). [Learn how to add additional system licenses to Cloud Volumes ONTAP](#). Though Cloud Volumes ONTAP supports up to the maximum tested and supported system capacity of 2 PiB, crossing the 2 PiB limit results in an unsupported system configuration.

#### Single node

Single node has two node-based licensing options: PAYGO Premium and BYOL.

## Single node with PAYGO Premium

VM size	Max data disks per node	Max system capacity with disks alone	Max system capacity with disks and data tiering
DS5_v2	61	368 TiB	368 TiB
DS14_v2	61	368 TiB	368 TiB
DS15_v2	61	368 TiB	368 TiB
E32s_v3	29	368 TiB	368 TiB
E48s_v3	29	368 TiB	368 TiB
E64is_v3	29	368 TiB	368 TiB
E32ds_v4	29	368 TiB	368 TiB
E48ds_v4	29	368 TiB	368 TiB
E80ids_v4	61	368 TiB	368 TiB
E20ds_v5	29	896 TiB	2 PiB
E32ds_v5	29	896 TiB	2 PiB
E48ds_v5	29	896 TiB	2 PiB
E64ds_v5	29	896 TiB	2 PiB

## Single node with BYOL

VM size	Max data disks per node	Max system capacity with one license		Max system capacity with multiple licenses	
		Disks alone	Disks + data tiering	Disks alone	Disks + data tiering
DS4_v2	29	368 TiB	368 TiB	896 TiB	2 PiB
DS5_v2	61	368 TiB	368 TiB	896 TiB	2 PiB
DS13_v2	29	368 TiB	368 TiB	896 TiB	2 PiB
DS14_v2	61	368 TiB	368 TiB	896 TiB	2 PiB
DS15_v2	61	368 TiB	368 TiB	896 TiB	2 PiB
L8s_v2	13	368 TiB	368 TiB	416 TiB	2 PiB
E4s_v3	5	160 TiB	368 TiB	160 TiB	2 PiB
E8s_v3	13	368 TiB	368 TiB	416 TiB	2 PiB
E32s_v3	29	368 TiB	368 TiB	896 TiB	2 PiB
E48s_v3	29	368 TiB	368 TiB	896 TiB	2 PiB
E64is_v3	29	368 TiB	368 TiB	896 TiB	2 PiB
E4ds_v4	5	160 TiB	368 TiB	160 TiB	2 PiB
E8ds_v4	13	368 TiB	368 TiB	416 TiB	2 PiB
E32ds_v4	29	368 TiB	368 TiB	896 TiB	2 PiB
E48ds_v4	29	368 TiB	368 TiB	896 TiB	2 PiB
E80ids_v4	61	368 TiB	368 TiB	896 TiB	2 PiB
E4ds_v5	5	160 TiB	368 TiB	160 TiB	2 PiB
E8ds_v5	13	368 TiB	368 TiB	416 TiB	2 PiB
E20ds_v5	29	368 TiB	368 TiB	896 TiB	2 PiB
E32ds_v5	29	368 TiB	368 TiB	896 TiB	2 PiB
E48ds_v5	29	368 TiB	368 TiB	896 TiB	2 PiB
E64ds_v5	29	368 TiB	368 TiB	896 TiB	2 PiB

## HA pairs

HA pairs have two configuration types: page blob and multiple availability zone. Each configuration has two



node-based licensing options: PAYGO Premium and BYOL.

**PAYGO Premium: HA pairs in single availability zone with page blobs**

<b>VM size</b>	<b>Max data disks for an HA pair</b>	<b>Max system capacity with disks alone</b>	<b>Max system capacity with disks and data tiering</b>
DS5_v2	61	368 TiB	368 TiB
DS14_v2	61	368 TiB	368 TiB
DS15_v2	61	368 TiB	368 TiB
E8s_v3	13	104 TiB	368 TiB
E48s_v3	29	232 TiB	368 TiB
E32ds_v4	29	232 TiB	368 TiB
E48ds_v4	29	232 TiB	368 TiB
E80ids_v4	61	368 TiB	368 TiB

**PAYGO Premium: HA pairs in a multiple availability zone configuration with shared managed disks**

<b>VM size</b>	<b>Max data disks for an HA pair</b>	<b>Max system capacity with disks alone</b>	<b>Max system capacity with disks and data tiering</b>
E32ds_v4	28	368 TiB	368 TiB
E48ds_v4	28	368 TiB	368 TiB
E80ids_v4	28	368 TiB	368 TiB
E20ds_v5	28	896 TiB	2 PiB
E32ds_v5	28	896 TiB	2 PiB
E48ds_v5	28	896 TiB	2 PiB
E64ds_v5	28	896 TiB	2 PiB

**BYOL: HA pairs in single availability zone with page blobs**

VM size	Max data disks for an HA pair	Max system capacity with one license		Max system capacity with multiple licenses	
		Disks alone	Disks + data tiering	Disks alone	Disks + data tiering
DS4_v2	29	232 TiB	368 TiB	232 TiB	2 PiB
DS5_v2	61	368 TiB	368 TiB	488 TiB	2 PiB
DS13_v2	29	232 TiB	368 TiB	232 TiB	2 PiB
DS14_v2	61	368 TiB	368 TiB	488 TiB	2 PiB
DS15_v2	61	368 TiB	368 TiB	488 TiB	2 PiB
E8s_v3	13	104 TiB	368 TiB	104 TiB	2 PiB
E48s_v3	29	232 TiB	368 TiB	232 TiB	2 PiB
E8ds_v4	13	104 TiB	368 TiB	104 TiB	2 PiB
E32ds_v4	29	232 TiB	368 TiB	232 TiB	2 PiB
E48ds_v4	29	232 TiB	368 TiB	232 TiB	2 PiB
E80ids_v4	61	368 TiB	368 TiB	488 TiB	2 PiB

## BYOL: HA pairs in a multiple availability zone configuration with shared managed disks

VM size	Max data disks for an HA pair	Max system capacity with one license		Max system capacity with multiple licenses	
		Disks alone	Disks + data tiering	Disks alone	Disks + data tiering
E8ds_v4	12	368 TiB	368 TiB	368 TiB	2 PiB
E32ds_v4	28	368 TiB	368 TiB	368 TiB	2 PiB
E48ds_v4	28	368 TiB	368 TiB	368 TiB	2 PiB
E80ids_v4	28	368 TiB	368 TiB	368 TiB	2 PiB
E8ds_v5	12	368 TiB	368 TiB	368 TiB	2 PiB
E20ds_v5	28	368 TiB	368 TiB	368 TiB	2 PiB
E32ds_v5	28	368 TiB	368 TiB	368 TiB	2 PiB
E48ds_v5	28	368 TiB	368 TiB	368 TiB	2 PiB
E64ds_v5	28	368 TiB	368 TiB	368 TiB	2 PiB

## Storage VM limits

Some configurations enable you to create additional storage VMs (SVMs) for Cloud Volumes ONTAP.

These are the tested limits. While it is theoretically possible to configure additional storage VMs, it's not supported.

[Learn how to create additional storage VMs.](#)

License type	Storage VM limit
<b>Freemium</b>	24 storage VMs total <sup>1,2</sup>
<b>Capacity-based PAYGO or BYOL</b> <sup>3</sup>	24 storage VMs total <sup>1,2</sup>
<b>Node-based BYOL</b> <sup>4</sup>	24 storage VMs total <sup>1,2</sup>
<b>Node-based PAYGO</b>	<ul style="list-style-type: none"> <li>• 1 storage VM for serving data</li> <li>• 1 storage VM for disaster recovery</li> </ul>

1. These 24 storage VMs can serve data or be configured for disaster recovery (DR).

- Each storage VM can have up to three LIFs where two are data LIFs and one is an SVM management LIF.
- For capacity-based licensing, there are no extra licensing costs for additional storage VMs, but there is a 4 TiB minimum capacity charge per storage VM. For example, if you create two storage VMs and each has 2 TiB of provisioned capacity, you'll be charged a total of 8 TiB.
- For node-based BYOL, an add-on license is required for each additional *data-serving* storage VM beyond the first storage VM that comes with Cloud Volumes ONTAP by default. Contact your account team to obtain a storage VM add-on license.

Storage VMs that you configure for disaster recovery (DR) don't require an add-on license (they are free of charge), but they do count against the storage VM limit. For example, if you have 12 data-serving storage VMs and 12 storage VMs configured for disaster recovery, then you've reached the limit and can't create any additional storage VMs.

## File and volume limits

Logical storage	Parameter	Limit
<b>Files</b>	Maximum size <sup>2</sup>	128 TB
	Maximum per volume	Volume size dependent, up to 2 billion
<b>FlexClone volumes</b>	Hierarchical clone depth <sup>1</sup>	499
<b>FlexVol volumes</b>	Maximum per node	500
	Minimum size	20 MB
	Maximum size <sup>3</sup>	300 TiB
<b>Qtrees</b>	Maximum per FlexVol volume	4,995
<b>Snapshot copies</b>	Maximum per FlexVol volume	1,023

- Hierarchical clone depth is the maximum depth of a nested hierarchy of FlexClone volumes that can be created from a single FlexVol volume.
- Beginning with ONTAP 9.12.1P2, the limit is 128 TB. In ONTAP 9.11.1 and earlier versions, the limit is 16 TB.
- FlexVol volume creation up to maximum size of 300 TiB is supported using the following tools and minimum versions:
  - System Manager and the ONTAP CLI starting from Cloud Volumes ONTAP 9.12.1 P2 and 9.13.0 P2
  - BlueXP starting from Cloud Volumes ONTAP 9.13.1

## iSCSI storage limits

iSCSI storage	Parameter	Limit
<b>LUNs</b>	Maximum per node	1,024
	Maximum number of LUN maps	1,024
	Maximum size	16 TiB
	Maximum per volume	512
<b>igroups</b>	Maximum per node	256
<b>Initiators</b>	Maximum per node	512
	Maximum per igroup	128
<b>iSCSI sessions</b>	Maximum per node	1,024
<b>LIFs</b>	Maximum per port	32
	Maximum per portset	32
<b>Portsets</b>	Maximum per node	256

## Storage limits in Google Cloud

Cloud Volumes ONTAP has storage configuration limits to provide reliable operations. For best performance, do not configure your system at the maximum values.

### Maximum system capacity by license

The maximum system capacity for a Cloud Volumes ONTAP system is determined by its license. The maximum system capacity includes disk-based storage plus object storage used for data tiering.

NetApp doesn't support exceeding the system capacity limit. If you reach the licensed capacity limit, BlueXP displays an action required message and no longer allows you to add additional disks.

For some configurations, disk limits prevent you from reaching the capacity limit by using disks alone. You can reach the capacity limit by [tiering inactive data to object storage](#). Refer to the disk limits below for more details.

License	Maximum system capacity (disks + object storage)
Freemium	500 GB
PAYGO Explore	2 TB (data tiering is not supported with Explore)
PAYGO Standard	10 TB
PAYGO Premium	368 TB
Node-based license	2 PiB (requires multiple licenses)
Capacity-based license	2 PiB

### For an HA pair, is the licensed capacity limit per node or for the entire HA pair?

The capacity limit is for the entire HA pair. It is not per node. For example, if you use the Premium license, you can have up to 368 TB of capacity between both nodes.

### For an HA pair, does mirrored data count against the licensed capacity limit?

No, it doesn't. Data in an HA pair is synchronously mirrored between the nodes so that the data is available in the event of failure in Google Cloud. For example, if you purchase an 8 TB disk on node A, BlueXP also allocates an 8 TB disk on node B that is used for mirrored data. While 16 TB of capacity was provisioned, only 8 TB counts against the license limit.

## Aggregate limits

Cloud Volumes ONTAP groups Google Cloud Platform disks into *aggregates*. Aggregates provide storage to volumes.

Parameter	Limit
Maximum number of data aggregates <sup>1</sup>	<ul style="list-style-type: none"><li>• 99 for single node</li><li>• 64 for an entire HA pair</li></ul>
Maximum aggregate size	256 TB of raw capacity <sup>2</sup>
Disks per aggregate	1-6 <sup>3</sup>
Maximum number of RAID groups per aggregate	1

Notes:

1. The maximum number of data aggregates doesn't include the root aggregate.
2. The aggregate capacity limit is based on the disks that comprise the aggregate. The limit does not include object storage used for data tiering.
3. All disks in an aggregate must be the same size.

## Disk and tiering limits

The table below shows the maximum system capacity with disks alone, and with disks and cold data tiering to object storage. The disk limits are specific to disks that contain user data. The limits do not include the boot disk, root disk, or NVRAM.

Parameter	Limit
Maximum data disks	<ul style="list-style-type: none"><li>• 124 for single node systems</li><li>• 123 per node for HA pairs</li></ul>
Maximum disk size	64 TB
Maximum system capacity with disks alone	256 TB <sup>1</sup>

Parameter	Limit
Maximum system capacity with disks and cold data tiering to a Google Cloud Storage bucket	Depends on the license. Refer to the maximum system capacity limits above.

<sup>1</sup> This limit is defined by virtual machine limits in Google Cloud Platform.

## Storage VM limits

Some configurations enable you to create additional storage VMs (SVMs) for Cloud Volumes ONTAP.

These are the tested limits. While it is theoretically possible to configure additional storage VMs, it's not supported.

[Learn how to create additional storage VMs.](#)

License type	Storage VM limit
Freemium	24 storage VMs total <sup>1</sup>
Capacity-based PAYGO or BYOL <sup>2</sup>	24 storage VMs total <sup>1</sup>
Node-based BYOL <sup>3</sup>	24 storage VMs total <sup>1</sup>
Node-based PAYGO	<ul style="list-style-type: none"> <li>• 1 storage VM for serving data</li> <li>• 1 storage VM for disaster recovery</li> </ul>

1. These 24 storage VMs can serve data or be configured for disaster recovery (DR).
2. For capacity-based licensing, there are no extra licensing costs for additional storage VMs, but there is a 4 TiB minimum capacity charge per storage VM. For example, if you create two storage VMs and each has 2 TiB of provisioned capacity, you'll be charged a total of 8 TiB.
3. For node-based BYOL, an add-on license is required for each additional *data-serving* storage VM beyond the first storage VM that comes with Cloud Volumes ONTAP by default. Contact your account team to obtain a storage VM add-on license.

Storage VMs that you configure for disaster recovery (DR) don't require an add-on license (they are free of charge), but they do count against the storage VM limit. For example, if you have 12 data-serving storage VMs and 12 storage VMs configured for disaster recovery, then you've reached the limit and can't create any additional storage VMs.

## Logical storage limits

Logical storage	Parameter	Limit
Files	Maximum size <sup>2</sup>	128 TB
	Maximum per volume	Volume size dependent, up to 2 billion
FlexClone volumes	Hierarchical clone depth <sup>12</sup>	499

Logical storage	Parameter	Limit
<b>FlexVol volumes</b>	Maximum per node	500
	Minimum size	20 MB
	Maximum size <sup>3</sup>	300 TiB
<b>Qtrees</b>	Maximum per FlexVol volume	4,995
<b>Snapshot copies</b>	Maximum per FlexVol volume	1,023

1. Hierarchical clone depth is the maximum depth of a nested hierarchy of FlexClone volumes that can be created from a single FlexVol volume.
2. Beginning with ONTAP 9.12.1P2, the limit is 128 TB. In ONTAP 9.11.1 and earlier versions, the limit is 16 TB.
3. FlexVol volume creation up to maximum size of 300 TiB is supported using the following tools and minimum versions:
  - System Manager and the ONTAP CLI starting from Cloud Volumes ONTAP 9.12.1 P2 and 9.13.0 P2
  - BlueXP starting from Cloud Volumes ONTAP 9.13.1

## iSCSI storage limits

iSCSI storage	Parameter	Limit
<b>LUNs</b>	Maximum per node	1,024
	Maximum number of LUN maps	1,024
	Maximum size	16 TB
	Maximum per volume	512
<b>igroups</b>	Maximum per node	256
<b>Initiators</b>	Maximum per node	512
	Maximum per igroup	128
<b>iSCSI sessions</b>	Maximum per node	1,024
<b>LIFs</b>	Maximum per port	1
	Maximum per portset	32
<b>Portsets</b>	Maximum per node	256

## Cloud Volumes ONTAP HA pairs do not support immediate storage giveback

After a node reboots, the partner must sync data before it can return the storage. The time that it takes to resync data depends on the amount of data written by clients while the node was down and the data write speed during the time of giveback.

[Learn how storage works in a Cloud Volumes ONTAP HA pair running in Google Cloud.](#)



# Known issues

Known issues identify problems that might prevent you from using this release of the product successfully.

There are no known issues in this release specific to Cloud Volumes ONTAP.

You can find known issues for ONTAP software in the [ONTAP Release Notes](#).

# Known limitations

## Limitations in all cloud providers

Known limitations identify platforms, devices, or functions that are not supported by this release of the product, or that do not interoperate correctly with it. Review these limitations carefully.

The following limitations apply to Cloud Volumes ONTAP in all cloud providers: AWS, Azure, and Google Cloud.

### Unsupported ONTAP features

The following features are not supported with Cloud Volumes ONTAP:

- Aggregate-level inline deduplication
- Aggregate-level background deduplication
- Disk maintenance center
- Disk sanitization
- FabricPool mirroring
- Fibre Channel (FC)
- Flash Pools
- Infinite Volumes
- Interface groups
- Intranode LIF failover
- MetroCluster
- Multi-admin verification

Enabling multi-admin verification on Cloud Volumes ONTAP will result in an unsupported configuration.

- RAID4, RAID-DP, RAID-TEC (RAID0 is supported)
- Service Processor
- SnapLock Compliance and Enterprise modes (only Cloud WORM is supported)
- SnapMirror Synchronous
- VLANs

### Maximum concurrent replication operations

The maximum number of concurrent SnapMirror or SnapVault transfers for Cloud Volumes ONTAP is 100 per node, regardless of the instance type or machine type.

### Cloud provider snapshots must not be used for your backup and recovery plans

You shouldn't use your cloud provider's snapshots as part of your backup and recovery plan for Cloud Volumes ONTAP data. You should always use ONTAP Snapshot copies or third-party backup solutions to back up and

restore data hosted on Cloud Volumes ONTAP.

[Learn how to use BlueXP backup and recovery to back up and restore ONTAP data.](#)



ONTAP consistency points in the WAFL file system determine data consistency. Only ONTAP can quiesce the WAFL file system to make a crash-consistent backup.

## **Cloud Volumes ONTAP supports only Reserved and On-demand VM instances**

Cloud Volumes ONTAP can run on either a Reserved or On-demand VM instance from your cloud provider. Other types of VM instances aren't supported.

## **Automatic application resource management solutions shouldn't be used**

Automatic application resource management solutions should not manage Cloud Volumes ONTAP systems. Doing so can result in a change to an unsupported configuration. For example, the solution might change Cloud Volumes ONTAP to an unsupported VM instance type.

## **Software updates must be completed by BlueXP**

Upgrades of Cloud Volumes ONTAP must be completed from BlueXP. You should not upgrade Cloud Volumes ONTAP by using System Manager or the CLI. Doing so can impact system stability.

## **Cloud Volumes ONTAP deployment must not be modified from your cloud provider's console**

Changes to a Cloud Volumes ONTAP configuration from your cloud provider's console results in an unsupported configuration. Any changes to the Cloud Volumes ONTAP resources that BlueXP creates and manages can impact system stability and BlueXP's ability to manage the system.



After initial deployment, modification of the Azure Subscription name used for Cloud Volumes ONTAP resources is supported.

## **Disks and aggregates must be managed from BlueXP**

All disks and aggregates must be created and deleted directly from BlueXP. You should not perform these actions from another management tool. Doing so can impact system stability, hamper the ability to add disks in the future, and potentially generate redundant cloud provider fees.

## **SnapManager licensing limitation**

SnapManager per-server licenses are supported with Cloud Volumes ONTAP. Per-storage system (SnapManager suite) licenses are not supported.

## **Limitations with third-party agents and extensions**

Third-party agents and VM extensions are not supported on Cloud Volumes ONTAP virtual machine instances.

## **Known limitations in AWS**

The following known limitations are specific to Cloud Volumes ONTAP in Amazon Web

Services. Be sure to also review [Limitations for Cloud Volumes ONTAP in all cloud providers](#).

## AWS Outpost limitations

If you have an AWS Outpost, you can deploy Cloud Volumes ONTAP in that Outpost by selecting the Outpost VPC in the Working Environment wizard. The experience is the same as any other VPC that resides in AWS. Note that you will need to first deploy a Connector in your AWS Outpost.

There are a few limitations to point out:

- Only single node Cloud Volumes ONTAP systems are supported at this time
- The EC2 instances that you can use with Cloud Volumes ONTAP are limited to what's available in your Outpost
- Only General Purpose SSDs (gp2) are supported at this time

## Flash Cache limitations

C5D and R5D instance types include local NVMe storage, which Cloud Volumes ONTAP uses as *Flash Cache*. Note the following limitations:

- Compression must be disabled on all volumes to take advantage of the Flash Cache performance improvements up to Cloud Volumes ONTAP 9.12.0. When you deploy or upgrade to Cloud Volumes ONTAP 9.12.1, you don't need to disable compression.

You can choose no storage efficiency when creating a volume from BlueXP, or you can create a volume and then [disable data compression by using the CLI](#).

- Cache rewarming after a reboot is not supported with Cloud Volumes ONTAP.

## False alarms reported by Amazon CloudWatch

Cloud Volumes ONTAP does not release CPUs when idle, so [Amazon CloudWatch](#) can report a high CPU warning for the EC2 instance because it sees 100% usage. You can ignore this alarm. The ONTAP statistics command displays the true usage of the CPUs.

## Cloud Volumes ONTAP HA pairs do not support immediate storage giveback

After a node reboots, the partner must sync data before it can return the storage. The time that it takes to resync data depends on the amount of data written by clients while the node was down and the data write speed during the time of giveback.

[Learn how storage works in a Cloud Volumes ONTAP HA pair running in AWS.](#)

## Known limitations in Azure

The following known limitations are specific to Cloud Volumes ONTAP in Microsoft Azure. Be sure to also review [Limitations for Cloud Volumes ONTAP in all cloud providers](#).

## Flash Cache limitations

Cloud Volumes ONTAP uses the local NVMe storage in some VM types as *Flash Cache*. Note this limitation:

- Cache rewarming after a reboot is not supported.

## HA limitations

HA pairs aren't supported in some regions.

[View the list of supported Azure regions.](#)

## Known limitations in Google Cloud

The following known limitations are specific to Cloud Volumes ONTAP in Google Cloud Platform. Be sure to also review [Limitations for Cloud Volumes ONTAP in all cloud providers](#).

### Limitation with packet mirroring

[Packet mirroring](#) must be disabled in the Google Cloud VPC in which you deploy Cloud Volumes ONTAP.

Cloud Volumes ONTAP can't operate properly if packet mirroring is enabled.

### Google Private Service Connect limitations

If you leverage [Google Private Service Connect](#) within the VPC that you are deploying Cloud Volumes ONTAP into, you will need to implement DNS records that forward traffic to the required [BlueXP API Endpoints](#).

Tiering data from Cloud Volumes ONTAP into a Google Cloud Storage bucket is not currently supported with Private Service Connect.

# Cloud provider integrations

This page describes how NetApp works with cloud providers to resolve issues that might arise.

## Collaborative support best practices

NetApp is committed to provide support to Licensee and will use commercially reasonable efforts to resolve technical support issues for Cloud Volumes ONTAP when reported by the Licensee. NetApp and the applicable cloud provider don't have any direct support obligations to each other's licensed software or infrastructure.

NetApp has implemented tools aimed to connect with applicable cloud providers on customer technical issues that may be a result of the applicable cloud provider services. However, the best way to maintain a seamless support flow is for customers to (i) maintain a current support contract with both NetApp and the applicable cloud provider and (ii) coordinate joint escalation meetings with both NetApp and the applicable cloud provider when technical issues arise and the customer needs clarity on which products or services are causing those technical issues.

## Azure maintenance events

Microsoft schedules and programmatically announces maintenance events on its Azure virtual machine (VM) infrastructure that may affect Cloud Volumes ONTAP VMs. These events are announced 15 minutes prior to the maintenance window.

Special handling of the maintenance events is supported for Cloud Volumes ONTAP high availability (HA) pairs. To maintain application health, we perform a preventive takeover to prioritize stability, as any loss of connectivity of more than 15 seconds will disable failover capabilities.

When the maintenance window is announced, the partner node of the targeted node will perform a takeover. When the maintenance is complete, a giveback will be initiated. After the giveback, the HA pair is expected to return to a healthy state. If this doesn't occur, contact NetApp Support for assistance. Note that maintenance events are targeted at one of the VMs in an HA pair at a time, and typically both nodes are targeted in a relatively short period of time.

CIFS/SMB clients that use Cloud Volumes ONTAP non-continuously available CIFS shares will experience a loss of session both when a takeover occurs, and when the aggregate that the session is using is given back to the aggregate's home node. This is a limitation imposed by the CIFS/SMB protocol itself. Customers may wish to use third-party products to avoid issues that may arise from takeover and giveback. For further assistance, contact NetApp Support.

# Legal notices

Legal notices provide access to copyright statements, trademarks, patents, and more.

## Copyright

<https://www.netapp.com/company/legal/copyright/>

## Trademarks

NETAPP, the NETAPP logo, and the marks listed on the NetApp Trademarks page are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.

<https://www.netapp.com/company/legal/trademarks/>

## Patents

A current list of NetApp owned patents can be found at:

<https://www.netapp.com/pdf.html?item=/media/11887-patentspage.pdf>

## Privacy policy

<https://www.netapp.com/company/legal/privacy-policy/>

## Open source

Notice files provide information about third-party copyright and licenses used in NetApp software.

- [Notice for the Cloud Volumes ONTAP 9.15.1](#)
- [Notice for ONTAP](#)

## Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.