



# **Pair volumes**

## Element Software

NetApp  
November 13, 2025

This PDF was generated from [https://docs.netapp.com/us-en/element-software/storage/task\\_replication\\_pair\\_volumes.html](https://docs.netapp.com/us-en/element-software/storage/task_replication_pair_volumes.html) on November 13, 2025. Always check [docs.netapp.com](https://docs.netapp.com) for the latest.

# Table of Contents

Pair volumes . . . . .	1
Pair volumes . . . . .	1
Create a target volume with read or write access . . . . .	1
Pair volumes using a volume ID or pairing key . . . . .	2
Pair volumes using a volume ID . . . . .	2
Pair volumes using a pairing key . . . . .	3
Assign a replication source and target to paired volumes . . . . .	4
Find more information . . . . .	5

# Pair volumes

## Pair volumes

After you have established a connection between clusters in a cluster pair, you can pair a volume on one cluster with a volume on the other cluster in the pair. When a volume pairing relationship is established, you must identify which volume is the replication target.

You can pair two volumes for real-time replication that are stored on different storage clusters in a connected cluster pair. After you pair two clusters, you can configure active volumes on one cluster to be continuously replicated to a second cluster, providing continuous data protection (CDP). You can also assign either volume to be the source or target of the replication.

Volume pairings are always one-to-one. After a volume is part of a pairing with a volume on another cluster, you cannot pair it again with any other volume.

### What you'll need

- You have established a connection between clusters in a cluster pair.
- You have cluster administrator privileges to one or both clusters being paired.

### Steps

1. [Create a target volume with read or write access](#)
2. [Pair volumes using a volume ID or pairing key](#)
3. [Assign a replication source and target to paired volumes](#)

## Create a target volume with read or write access

The replication process involves two endpoints: the source and the target volume. When you create the target volume, the volume is automatically set to read/write mode to accept the data during the replication.

1. Select **Management > Volumes**.
2. Click **Create Volume**.
3. In the Create a New Volume dialog box, enter the **Volume Name**.
4. Enter the total size of the volume, select a block size for the volume, and select the account that should have access to the volume.
5. Click **Create Volume**.
6. In the Active window, click the Actions icon for the volume.
7. Click **Edit**.
8. Change the account access level to **Replication Target**.
9. Click **Save Changes**.

# Pair volumes using a volume ID or pairing key

## Pair volumes using a volume ID

You can pair a volume with another volume on a remote cluster if you have cluster administrator access to both clusters on which volumes are to be paired. This method uses the volume ID of the volume on the remote cluster to initiate a connection.

### What you'll need

- Ensure that the clusters containing the volumes are paired.
- Create a new volume on the remote cluster.



You can assign a replication source and target after the pairing process. A replication source or target can be either volume in a volume pair. You should create a target volume that contains no data and has the exact characteristics of the source volume, such as size, block size setting for the volumes (either 512e or 4k), and QoS configuration. If you assign an existing volume as the replication target, the data on that volume will be overwritten. The target volume can be greater or equal in size to the source volume, but it cannot be smaller.

- Know the target Volume ID.

### Steps

1. Select **Management > Volumes**.
2. Click the **Actions** icon for the volume you want to pair.
3. Click **Pair**.
4. In the **Pair Volume** dialog box, select **Start Pairing**.
5. Select **I Do** to indicate that you have access to the remote cluster.
6. Select a **Replication Mode** from the list:
  - **Real-time (Asynchronous)**: Writes are acknowledged to the client after they are committed on the source cluster.
  - **Real-time (Synchronous)**: Writes are acknowledged to the client after they are committed on both the source and target clusters.
  - **Snapshots Only**: Only snapshots created on the source cluster are replicated. Active writes from the source volume are not replicated.
7. Select a remote cluster from the list.
8. Choose a remote volume ID.
9. Click **Start Pairing**.

The system opens a web browser tab that connects to the Element UI of the remote cluster. You might be required to log on to the remote cluster with cluster administrator credentials.

10. In the Element UI of the remote cluster, select **Complete Pairing**.
11. Confirm the details in **Confirm Volume Pairing**.
12. Click **Complete Pairing**.

After you confirm the pairing, the two clusters begin the process of connecting the volumes for pairing.

During the pairing process, you can see messages in the **Volume Status** column of the **Volume Pairs** window. The volume pair displays `PausedMisconfigured` until the volume pair source and target are assigned.

After you successfully complete the pairing, it is recommended that you refresh the Volumes table to remove the **Pair** option from the **Actions** list for the paired volume. If you do not refresh the table, the **Pair** option remains available for selection. If you select the **Pair** option again, a new tab opens and because the volume is already paired, the system reports a `StartVolumePairing Failed: xVolumeAlreadyPaired` error message in the **Pair Volume** window of the Element UI page.

## Find more information

- [Volume pairing messages](#)
- [Volume pairing warnings](#)
- [Assign a replication source and target to paired volumes](#)

## Pair volumes using a pairing key

If you have cluster administrator access to only the source cluster (you do not have cluster admin credentials for a remote cluster), you can pair a volume with another volume on a remote cluster using a pairing key.

### What you'll need

- Ensure that the clusters containing the volumes are paired.
- Ensure that there is a volume on the remote cluster to use for the pairing.



You can assign a replication source and target after the pairing process. A replication source or target can be either volume in a volume pair. You should create a target volume that contains no data and has the exact characteristics of the source volume, such as size, block size setting for the volumes (either 512e or 4k), and QoS configuration. If you assign an existing volume as the replication target, the data on that volume will be overwritten. The target volume can be greater or equal in size to the source volume, but it cannot be smaller.

### Steps

1. Select **Management > Volumes**.
2. Click **Actions** icon for the volume you want to pair.
3. Click **Pair**.
4. In the **Pair Volume** dialog box, select **Start Pairing**.
5. Select **I Do Not** to indicate that you do not have access to the remote cluster.
6. Select a **Replication Mode** from the list:
  - **Real-time (Asynchronous)**: Writes are acknowledged to the client after they are committed on the source cluster.
  - **Real-time (Synchronous)**: Writes are acknowledged to the client after they are committed on both the source and target clusters.
  - **Snapshots Only**: Only snapshots created on the source cluster are replicated. Active writes from the source volume are not replicated.

## 7. Click **Generate Key**.



This action generates a text key for pairing and creates an unconfigured volume pair on the local cluster. If you do not complete the procedure, you will need to manually delete the volume pair.

8. Copy the pairing key to your computer's clipboard.
9. Make the pairing key accessible to the cluster admin at the remote cluster site.



The volume pairing key should be treated in a secure manner and not used in a way that would allow accidental or unsecured access.



Do not modify any of the characters in the pairing key. The key becomes invalid if it is modified.

10. In the remote cluster Element UI, select **Management > Volumes**.

11. Click the Actions icon for the volume you want to pair.

12. Click **Pair**.

13. In the **Pair Volume** dialog box, select **Complete Pairing**.

14. Paste the pairing key from the other cluster into the **Pairing Key** box.

15. Click **Complete Pairing**.

After you confirm the pairing, the two clusters begin the process of connecting the volumes for pairing. During the pairing process, you can see messages in the **Volume Status** column of the **Volume Pairs** window. The volume pair displays `PausedMisconfigured` until the volume pair source and target are assigned.

After you successfully complete the pairing, it is recommended that you refresh the Volumes table to remove the **Pair** option from the **Actions** list for the paired volume. If you do not refresh the table, the **Pair** option remains available for selection. If you select the **Pair** option again, a new tab opens and because the volume is already paired, the system reports a `StartVolumePairing Failed: xVolumeAlreadyPaired` error message in the **Pair Volume** window of the Element UI page.

### Find more information

- [Volume pairing messages](#)
- [Volume pairing warnings](#)
- [Assign a replication source and target to paired volumes](#)

## Assign a replication source and target to paired volumes

After volumes are paired, you must assign a source volume and its replication target volume. A replication source or target can be either volume in a volume pair. You can also use this procedure to redirect data sent to a source volume to a remote target volume should the source volume become unavailable.

### What you'll need

You have access to the clusters containing the source and target volumes.

## Steps

### 1. Prepare the source volume:

- a. From the cluster that contains the volume you want to assign as source, select **Management > Volumes**.
- b. Click the **Actions** icon for the volume you want to assign as source and click **Edit**.
- c. In the **Access** drop-down list, select **Read/Write**.



If you are reversing source and target assignment, this action will cause the volume pair to display the following message until a new replication target is assigned:  
PausedMisconfigured

Changing access pauses volume replication and causes the transmission of data to cease. Be sure that you have coordinated these changes at both sites.

- d. Click **Save Changes**.

### 2. Prepare the target volume:

- a. From the cluster that contains the volume you want to assign as target, select **Management > Volumes**.
- b. Click the Actions icon for the volume you want to assign as target and click **Edit**.
- c. In the **Access** drop-down list, select **Replication Target**.



If you assign an existing volume as the replication target, the data on that volume will be overwritten. You should use a new target volume that contains no data and has the exact characteristics of the source volume, such as size, 512e setting, and QoS configuration. The target volume can be greater or equal in size to the source volume, but it cannot be smaller.

- d. Click **Save Changes**.

## Find more information

- [Pair volumes using a volume ID](#)
- [Pair volumes using a pairing key](#)

## Copyright information

Copyright © 2025 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—with prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

**LIMITED RIGHTS LEGEND:** Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.