



# Disaster recovery failover

## NetApp Solutions SAP

NetApp  
October 14, 2021

# Table of Contents

- Disaster recovery failover ..... 1
  - Disaster recovery failover ..... 1
  - Prepare the target host ..... 1
  - Break and delete replication peering ..... 4
  - Mount the volumes at the target host ..... 7
  - HANA database recovery ..... 8

# Disaster recovery failover

## Disaster recovery failover


Previous: [HANA database recovery](#).

Depending on whether the log backup replication is part of the disaster recovery setup, the steps for disaster recovery are slightly different. This section describes the disaster recovery failover for data-backup-only replication as well as for data volume replication combined with log backup volume replication.

To execute disaster recovery failover, complete these steps:

1. Prepare the target host.
2. Break and delete the replication relationships.
3. Restore the data volume to the latest application- consistent snapshot backup.
4. Mount the volumes at the target host.
5. Recover the HANA database.
  - Data volume recovery only.
  - Forward recovery using replicated log backups.

The following subsections describe these steps in detail, and the following figure depicts disaster failover testing.



Next: [Prepare the target host](#).

## Prepare the target host

Previous: [Disaster recovery failover](#).

This section describes the preparation steps required at the server that is used for the disaster recovery

failover.

During normal operation, the target host is typically used for other purposes, for example, as a HANA QA or test system. Therefore, most of the described steps must be executed when disaster failover testing is executed. On the other hand, the relevant configuration files, like `/etc/fstab` and `/usr/sap/sapservices`, can be prepared and then put in production by simply copying the configuration file. The disaster recovery failover procedure ensures that the relevant prepared configuration files are configured correctly.

The target host preparation also includes shutting down the HANA QA or test system as well as stopping all services using `systemctl stop sapinit`.

## Target server host name and IP address

The host name of the target server must be identical to the host name of the source system. The IP address can be different.



Proper fencing of the target server must be established so that it cannot communicate with other systems. If proper fencing is not in place, then the cloned production system might exchange data with other production systems, resulting in logically corrupted data.

## Install required software

The SAP host agent software must be installed at the target server. For full information, see the [SAP Host Agent](#) at the SAP help portal.



If the host is used as a HANA QA or test system, the SAP host agent software is already installed.

## Configure users, ports, and SAP services

The required users and groups for the SAP HANA database must be available at the target server. Typically, central user management is used; therefore, no configuration steps are necessary at the target server. The required ports for the HANA database must be configured at the target hosts. The configuration can be copied from the source system by copying the `/etc/services` file to the target server.

The required SAP services entries must be available at the target host. The configuration can be copied from the source system by copying the `/usr/sap/sapservices` file to the target server. The following output shows the required entries for the SAP HANA database used in the lab setup.

```
vm-pr1:~ # cat /usr/sap/sapservices
#!/bin/sh
LD_LIBRARY_PATH=/usr/sap/PR1/HDB01/exe:$LD_LIBRARY_PATH;export
LD_LIBRARY_PATH;/usr/sap/PR1/HDB01/exe/sapstartsrv
pf=/usr/sap/PR1/SYS/profile/PR1_HDB01_vm-pr1 -D -u pr1adm
limit.descriptors=1048576
```

## Prepare HANA log volume

Because the HANA log volume is not part of the replication, an empty log volume must exist at the target host. The log volume must include the same subdirectories as the source HANA system.

```
vm-pr1:~ # ls -al /hana/log/PR1/mnt00001/
total 16
drwxrwxrwx 5 root  root  4096 Feb 19 16:20 .
drwxr-xr-x 3 root  root    22 Feb 18 13:38 ..
drwxr-xr-- 2 prladm sapsys 4096 Feb 22 10:25 hdb00001
drwxr-xr-- 2 prladm sapsys 4096 Feb 22 10:25 hdb00002.00003
drwxr-xr-- 2 prladm sapsys 4096 Feb 22 10:25 hdb00003.00003
vm-pr1:~ #
```

## Prepare log backup volume

Because the source system is configured with a separate volume for the HANA log backups, a log backup volume must also be available at the target host. A volume for the log backups must be configured and mounted at the target host.

If log backup volume replication is part of the disaster recovery setup, the replicated log backup volume is mounted at the target host, and it is not necessary to prepare an additional log backup volume.

## Prepare file system mounts

The following table shows the naming conventions used in the lab setup. The volume names at the disaster recovery site are included in `/etc/fstab`.

HANA PR1 volumes	Volume and subdirectories at disaster recovery site	Mount point at target host
Data volume	PR1-data-mnt00001-sm-dest	/hana/data/PR1/mnt00001
Shared volume	PR1-shared-sm-dest/shared PR1-shared-sm-dest/usr-sap-PR1	/hana/shared /usr/sap/PR1
Log backup volume	hanabackup-sm-dest	/hanabackup



The mount points from this table must be created at the target host.

Here are the required `/etc/fstab` entries.

```
vm-pr1:~ # cat /etc/fstab
# HANA ANF DB Mounts
10.0.2.4:/PR1-data-mnt0001-sm-dest /hana/data/PR1/mnt00001 nfs
rw,vers=4,minorversion=1,hard,timeo=600,rsize=262144,wsiz=262144,intr,noa
time,lock,_netdev,sec=sys 0 0
10.0.2.4:/PR1-log-mnt0001-dr /hana/log/PR1/mnt00001 nfs
rw,vers=4,minorversion=1,hard,timeo=600,rsize=262144,wsiz=262144,intr,noa
time,lock,_netdev,sec=sys 0 0
# HANA ANF Shared Mounts
10.0.2.4:/PR1-shared-sm-dest/hana-shared /hana/shared nfs
rw,vers=4,minorversion=1,hard,timeo=600,rsize=262144,wsiz=262144,intr,noa
time,lock,_netdev,sec=sys 0 0
10.0.2.4:/PR1-shared-sm-dest/usr-sap-PR1 /usr/sap/PR1 nfs
rw,vers=4,minorversion=1,hard,timeo=600,rsize=262144,wsiz=262144,intr,noa
time,lock,_netdev,sec=sys 0 0
# HANA file and log backup destination
10.0.2.4:/hanabackup-sm-dest /hanabackup nfs
rw,vers=3,hard,timeo=600,rsize=262144,wsiz=262144,nconnect=8,bg,noatime,n
olock 0 0
```

[Next: Break and delete replication peering.](#)

## Break and delete replication peering

[Previous: Prepare the target host.](#)

In case of a disaster failover, the target volumes must be broken off so that the target host can mount the volumes for read and write operations.



For the HANA data volume, you must restore the volume to the latest HANA snapshot backup created with AzAcSnap. This volume revert operation is not possible if the latest replication snapshot is marked as busy due to the replication peering. Therefore, you must also delete the replication peering.

The next two screenshots show the break and delete peering operation for the HANA data volume. The same operations must be performed for the log backup and the HANA shared volume as well.

ir-sap-pool-premium/PR1-data-mnt0001-sm-dest

### PR1-data-mnt0001-sm-dest (dr-saponanf/dr-sap-pool-premium/PR1-data-mnt0001-sm-dest)

Volume

Search (Ctrl+/) << Edit Break peering Delete Refresh

Overview  
Activity log  
Access control (IAM)  
Tags

Settings  
Properties  
Locks

Storage service  
Mount instructions  
Export policy  
Snapshots  
Replication

Essentials  
End point type : Destination  
Healthy : Healthy  
Mirror state : Mirrored

Source  
Relationship status  
Replication schedule  
Total progress

Show data for last:  
1 hour 6 hours 12 hours 1 day 7 days

Volume replication lag time

Time	Value
9.72hours	100
8.33hours	90
6.94hours	80
5.56hours	70
	60
	50

Is volume replication transfer

### Break replication peering

Break replication peering

Warning! This action will stop data replication between the volumes and might result in loss of data.

Type 'yes' to proceed

yes

ir-sap-pool-premium/PR1-data-mnt0001-sm-dest

### PR1-data-mnt0001-sm-dest (dr-saponanf/dr-sap-pool-premium/PR1-data-mnt0001-sm-dest)

Volume

Search (Ctrl+/) << Resync Delete Refresh

Overview  
Activity log  
Access control (IAM)  
Tags

Settings  
Properties  
Locks

Storage service  
Mount instructions  
Export policy  
Snapshots  
Replication

Essentials  
End point type : Destination  
Healthy : Healthy  
Mirror state : Broken

Source  
Relationship status  
Replication schedule  
Total progress

Show data for last:  
1 hour 6 hours 12 hours 1 day 7 days

Volume replication lag time

Time	Value
1.67min	100
1.5min	90
1.33min	80
1.17min	70
1min	60
50sec	50

Is volume replication transfer

### Delete replication

Delete replication object

Warning this operation will delete the connection between PR1-data-mnt00001 and PR1-data-mnt0001-sm-dest

This will delete the replication object of PR1-data-mnt00001, type 'yes' to proceed

yes

Since replication peering was deleted, it is possible to revert the volume to the latest HANA snapshot backup. If peering is not deleted, the selection of revert volume is grayed out and is not selectable. The following two screenshots show the volume revert operation.

PR1-data-mnt0001-sm-dest (dr-saponanf/dr-sap-pool-premium/PR1-data-mnt0001-sm-dest) | Snapshots

Search (Ctrl+/) << + Add snapshot Refresh

- Overview
- Activity log
- Access control (IAM)
- Tags
- Settings
  - Properties
  - Locks
- Storage service
  - Mount instructions
  - Export policy
  - Snapshots**
  - Replication
- Monitoring
  - Metrics
- Automation
  - Tasks (preview)
  - Export template
- Support + troubleshooting
  - New support request

Search snapshots

Name	Location	Created	
azacsnap__2021-02-18T120002-2150721Z	West US	02/18/2021, 01:00:05 PM	...
azacsnap__2021-02-18T160002-1442691Z	West US	02/18/2021, 05:00:49 PM	...
azacsnap__2021-02-18T200002-0758687Z	West US	02/18/2021, 09:00:05 PM	...
azacsnap__2021-02-19T000002-0039686Z	West US	02/19/2021, 01:00:05 AM	...
azacsnap__2021-02-19T040001-8773748Z	West US	02/19/2021, 05:00:06 AM	...
azacsnap__2021-02-19T080001-5198653Z	West US	02/19/2021, 09:00:05 AM	...
azacsnap__2021-02-19T120002-1495322Z	West US	02/19/2021, 01:00:06 PM	...
azacsnap__2021-02-19T160002-3698678Z	West US	02/19/2021, 05:00:05 PM	...
azacsnap__2021-02-22T120002-3145398Z	West US	02/22/2021, 01:00:06 PM	...
snapmirror.b1e8e48d-7114-11eb-b147-d039ea...	West US	02/22/2021, 03:32:00 PM	...
azacsnap__2021-02-22T160002-0144647Z	West US	02/22/2021, 05:00:05 PM	...
azacsnap__2021-02-22T200002-0649581Z	West US	02/22/2021, 09:00:05 PM	...
azacsnap__2021-02-23T000002-0311379Z	West US	02/23/2021, 01:00:05 PM	...
snapmirror.b1e8e48d-7114-11eb-b147-d039ea...	West US	02/23/2021, 01:10:00 PM	...

Restore to new volume  
Revert volume  
Delete

PR1-data-mnt0001-sm-dest (dr-saponanf/dr-sap-pool-premium/PR1-data-mnt0001-sm-dest) | Snapshots

Search (Ctrl+/) << + Add snapshot Refresh

- Overview
- Activity log
- Access control (IAM)
- Tags
- Settings
  - Properties
  - Locks
- Storage service
  - Mount instructions
  - Export policy
  - Snapshots**
  - Replication
- Monitoring
  - Metrics
- Automation
  - Tasks (preview)
  - Export template
- Support + troubleshooting
  - New support request

Search snapshots

Name	Location
azacsnap__2021-02-18T120002-2150721Z	West US
azacsnap__2021-02-18T160002-1442691Z	West US
azacsnap__2021-02-18T200002-0758687Z	West US
azacsnap__2021-02-19T000002-0039686Z	West US
azacsnap__2021-02-19T040001-8773748Z	West US
azacsnap__2021-02-19T080001-5198653Z	West US
azacsnap__2021-02-19T120002-1495322Z	West US
azacsnap__2021-02-19T160002-3698678Z	West US
azacsnap__2021-02-22T120002-3145398Z	West US
snapmirror.b1e8e48d-7114-11eb-b147-d039ea...	West US
azacsnap__2021-02-22T160002-0144647Z	West US
azacsnap__2021-02-22T200002-0649581Z	West US
azacsnap__2021-02-23T000002-0311379Z	West US
snapmirror.b1e8e48d-7114-11eb-b147-d039ea...	West US

**Revert volume to snapshot**

Revert volume PR1-data-mnt0001-sm-dest to snapshot azacsnap\_\_2021-02-23T000002-0311379Z?

**Warning:** This action is irreversible and it will delete all the volumes snapshots that are newer than azacsnap\_\_2021-02-23T000002-0311379Z. Please type 'PR1-data-mnt0001-sm-dest' to confirm.

Are you sure you want to revert 'PR1-data-mnt0001-sm-dest' to state of 'azacsnap\_\_2021-02-23T000002-0311379Z'?

PR1-data-mnt0001-sm-dest ✓

After the volume revert operation, the data volume is based on the consistent HANA snapshot backup and can now be used to execute forward recovery operations.





If a capacity pool with a low performance tier has been used, the volumes must now be moved to a capacity pool that can provide the required performance.

Next: [Mount the volumes at the target host.](#)

## Mount the volumes at the target host

Previous: [Break and delete replication peering.](#)

The volumes can now be mounted at the target host, based on the `/etc/fstab` file created before.

```
vm-pr1:~ # mount -a
```

The following output shows the required file systems.

```

vm-pr1:~ # df
Filesystem                1K-blocks    Used
Available Use% Mounted on
devtmpfs                  8201112         0
8201112   0% /dev
tmpfs                     12313116         0
12313116   0% /dev/shm
tmpfs                     8208744         9096
8199648   1% /run
tmpfs                     8208744         0
8208744   0% /sys/fs/cgroup
/dev/sda4                 29866736 2543948
27322788   9% /
/dev/sda3                 1038336       79984
958352    8% /boot
/dev/sda2                 524008        1072
522936   1% /boot/efi
/dev/sdb1                 32894736     49180
31151556   1% /mnt
10.0.2.4:/PR1-log-mnt00001-dr 107374182400   6400
107374176000   1% /hana/log/PR1/mnt00001
tmpfs                   1641748         0
1641748   0% /run/user/0
10.0.2.4:/PR1-shared-sm-dest/hana-shared 107377178368 11317248
107365861120   1% /hana/shared
10.0.2.4:/PR1-shared-sm-dest/usr-sap-PR1 107377178368 11317248
107365861120   1% /usr/sap/PR1
10.0.2.4:/hanabackup-sm-dest 107379678976 35249408
107344429568   1% /hanabackup
10.0.2.4:/PR1-data-mnt0001-sm-dest 107376511232 6696960
107369814272   1% /hana/data/PR1/mnt00001
vm-pr1:~ #

```

Next: [HANA database recovery.](#)

## HANA database recovery

Previous: [Mount the volumes at the target host.](#)

Start the required SAP services.

```
vm-pr1:~ # systemctl start sapinit
```

The following output shows the required processes.

```

vm-pr1:/ # ps -ef | grep sap
root      23101      1  0 11:29 ?          00:00:00
/usr/sap/hostctrl/exe/saphostexec pf=/usr/sap/hostctrl/exe/host_profile
prladm    23191      1  3 11:29 ?          00:00:00
/usr/sap/PR1/HDB01/exe/sapstartsrv
pf=/usr/sap/PR1/SYS/profile/PR1_HDB01_vm-pr1 -D -u prladm
sapadm    23202      1  5 11:29 ?          00:00:00
/usr/sap/hostctrl/exe/sapstartsrv pf=/usr/sap/hostctrl/exe/host_profile -D
root      23292      1  0 11:29 ?          00:00:00
/usr/sap/hostctrl/exe/saposcol -l -w60
pf=/usr/sap/hostctrl/exe/host_profile
root      23359    2597  0 11:29 pts/1      00:00:00 grep --color=auto sap

```

The following subsections describe the recovery process with forward recovery using the replicated log backups. The recovery is executed using the HANA recovery script for the system database and hdbsql commands for the tenant database.

The commands to execute a recovery to the latest data savepoint is described in chapter [Recovery to latest HANA Data Volume Backup Savepoint](#).

## Recovery with forward recovery using log backups

The recovery using all available log backups is executed with the following commands as user pr1adm:

- System database

```

recoverSys.py --command "RECOVER DATABASE UNTIL TIMESTAMP '2021-02-20
00:00:00' CLEAR LOG USING SNAPSHOT"

```

- Tenant database

```

Within hdbsql: RECOVER DATABASE FOR PR1 UNTIL TIMESTAMP '2021-02-20
00:00:00' CLEAR LOG USING SNAPSHOT

```



To recover using all available logs, you can use any time in the future as the timestamp in the recovery statement.

You can also use HANA Studio or Cockpit to execute the recovery of the system and the tenant database.

The following command output show the recovery execution.

### System database recovery

```

pr1adm@vm-pr1:/usr/sap/PR1/HDB01> HDBSettings.sh recoverSys.py --command
"RECOVER DATABASE UNTIL TIMESTAMP '2021-02-24 00:00:00' CLEAR LOG USING
SNAPSHOT"
[139792805873472, 0.008] >> starting recoverSys (at Tue Feb 23 12:05:16
2021)
[139792805873472, 0.008] args: ()
[139792805873472, 0.008] keys: {'command': "RECOVER DATABASE UNTIL
TIMESTAMP '2021-02-24 00:00:00' CLEAR LOG USING SNAPSHOT"}
using logfile /usr/sap/PR1/HDB01/vm-pr1/trace/backup.log
recoverSys started: =====2021-02-23 12:05:16 =====
testing master: vm-pr1
vm-pr1 is master
shutdown database, timeout is 120
stop system
stop system on: vm-pr1
stopping system: 2021-02-23 12:05:17
stopped system: 2021-02-23 12:05:18
creating file recoverInstance.sql
restart database
restart master nameserver: 2021-02-23 12:05:23
start system: vm-pr1
sapcontrol parameter: ['-function', 'Start']
sapcontrol returned successfully:
2021-02-23T12:07:53+00:00 P0012969      177cec93d51 INFO      RECOVERY
RECOVER DATA finished successfully, reached timestamp 2021-02-
23T09:03:11+00:00, reached log position 43123520
recoverSys finished successfully: 2021-02-23 12:07:54
[139792805873472, 157.466] 0
[139792805873472, 157.466] << ending recoverSys, rc = 0 (RC_TEST_OK),
after 157.458 secs
pr1adm@vm-pr1:/usr/sap/PR1/HDB01>

```

## Tenant database recovery

If a user store key has not been created for the pr1adm user at the source system, a key must be created at the target system. The database user configured in the key must have privileges to execute tenant recovery operations.

```

pr1adm@vm-pr1:/usr/sap/PR1/HDB01> hdbuserstore set PR1KEY vm-pr1:30113
<backup-user> <password>

```

```
pr1adm@vm-pr1:/usr/sap/PR1/HDB01> hdbsql -U PR1KEY
Welcome to the SAP HANA Database interactive terminal.
Type:  \h for help with commands
       \q to quit
hdbsql SYSTEMDB=> RECOVER DATABASE FOR PR1 UNTIL TIMESTAMP '2021-02-24
00:00:00' CLEAR LOG USING SNAPSHOT
0 rows affected (overall time 98.740038 sec; server time 98.737788 sec)
hdbsql SYSTEMDB=>
```

## Check consistency of latest log backups

Because log backup volume replication is performed independently of the log backup process executed by the SAP HANA database, there might be open, inconsistent log backup files at the disaster recovery site. Only the latest log backup files might be inconsistent, and those files should be checked before a forward recovery is performed at the disaster recovery site using the `hdbbackupcheck` tool.

```
pr1adm@hana-10: > hdbbackupcheck
/hanabackup/PR1/log/SYSTEMDB/log_backup_0_0_0_0.1589289811148
Loaded library 'libhdbcsaccessor'
Loaded library 'libhdblivercache'
Backup '/mnt/log-backup/SYSTEMDB/log_backup_0_0_0_0.1589289811148'
successfully checked.
```

The check must be executed for the latest log backup files of the System and the tenant database.

If the `hdbbackupcheck` tool reports an error for the latest log backups, the latest set of log backups must be removed or deleted.

[Next: Update history.](#)

## Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.