



# Example Trident Operations

## NetApp Solutions

Kevin Hoke, Michael Oglesby  
May 14, 2021

# Table of Contents

Example Trident Operations ..... 1

# Example Trident Operations

This section includes examples of various operations that you may want to perform with Trident.

## Import an Existing Volume

If there are existing volumes on your NetApp storage system/platform that you want to mount on containers within your Kubernetes cluster, but that are not tied to PVCs in the cluster, then you must import these volumes. You can use the Trident volume import functionality to import these volumes.

The example commands that follow show the importing of the same volume, named `pb_fg_all`, twice, once for each Trident Backend that was created in the example in the section [Example Trident Backends for ONTAP AI Deployments](#), step 1. Importing the same volume twice in this manner enables you to mount the volume (an existing FlexGroup volume) multiple times across different LIFs, as described in the section [Example Trident Backends for ONTAP AI Deployments](#), step 1. For more information about PVCs, see the [official Kubernetes documentation](#). For more information about the volume import functionality, see the [Trident documentation](#).

An `accessModes` value of `ReadOnlyMany` is specified in the example PVC spec files. For more information about the `accessMode` field, see the [official Kubernetes documentation](#).



The Backend names that are specified in the following example import commands correspond to the Backends that were created in the example in the section [Example Trident Backends for ONTAP AI Deployments](#), step 1. The StorageClass names that are specified in the following example PVC definition files correspond to the StorageClasses that were created in the example in the section [Example Kubernetes StorageClasses for ONTAP AI Deployments](#), step 1.

```
$ cat << EOF > ./pvc-import-pb_fg_all-iface1.yaml
kind: PersistentVolumeClaim
apiVersion: v1
metadata:
  name: pb-fg-all-iface1
  namespace: default
spec:
  accessModes:
    - ReadOnlyMany
  storageClassName: ontap-ai-flexgroups-retain-iface1
EOF
$ tridentctl import volume ontap-ai-flexgroups-iface1 pb_fg_all -f ./pvc-
import-pb_fg_all-iface1.yaml -n trident
+-----+-----+
+-----+-----+
+-----+-----+-----+-----+
|           NAME           | SIZE |           STORAGE CLASS           |
| PROTOCOL |      | BACKEND UUID      | STATE |
MANAGED |
+-----+-----+-----+-----+
+-----+-----+-----+-----+
```

```

+-----+-----+-----+
| default-pb-fg-all-iface1-7d9f1 | 10 TiB | ontap-ai-flexgroups-retain-
iface1 | file      | b74cbddb-e0b8-40b7-b263-b6da6dec0bdd | online | true
|
+-----+-----+
+-----+-----+
+-----+-----+
$ cat << EOF > ./pvc-import-pb_fg_all-iface2.yaml
kind: PersistentVolumeClaim
apiVersion: v1
metadata:
  name: pb-fg-all-iface2
  namespace: default
spec:
  accessModes:
    - ReadOnlyMany
  storageClassName: ontap-ai-flexgroups-retain-iface2
EOF
$ tridentctl import volume ontap-ai-flexgroups-iface2 pb_fg_all -f ./pvc-
import-pb_fg_all-iface2.yaml -n trident
+-----+-----+
+-----+-----+
+-----+-----+
|          NAME          | SIZE |          STORAGE CLASS          |
| PROTOCOL |          BACKEND UUID          | STATE |
MANAGED |
+-----+-----+
+-----+-----+
+-----+-----+
| default-pb-fg-all-iface2-85aee | 10 TiB | ontap-ai-flexgroups-retain-
iface2 | file      | 61814d48-c770-436b-9cb4-cf7ee661274d | online | true
|
+-----+-----+
+-----+-----+
+-----+-----+
$ tridentctl get volume -n trident
+-----+-----+
+-----+-----+
+-----+-----+
|          NAME          | SIZE |          STORAGE CLASS          |
| PROTOCOL |          BACKEND UUID          | STATE | MANAGED |
+-----+-----+
+-----+-----+
+-----+-----+
| default-pb-fg-all-iface1-7d9f1 | 10 TiB | ontap-ai-flexgroups-retain-
iface1 | file      | b74cbddb-e0b8-40b7-b263-b6da6dec0bdd | online | true

```

```

|
| default-pb-fg-all-iface2-85aee | 10 TiB | ontap-ai-flexgroups-retain-
iface2 | file | 61814d48-c770-436b-9cb4-cf7ee661274d | online | true
|
+-----+-----+
+-----+-----+
+-----+-----+
$ kubectl get pvc
NAME                                STATUS      VOLUME                                CAPACITY
ACCESS MODES    STORAGECLASS    AGE
pb-fg-all-iface1    Bound         default-pb-fg-all-iface1-7d9f1
10995116277760    ROX          ontap-ai-flexgroups-retain-iface1    25h
pb-fg-all-iface2    Bound         default-pb-fg-all-iface2-85aee
10995116277760    ROX          ontap-ai-flexgroups-retain-iface2    25h

```

## Provision a New Volume

You can use Trident to provision a new volume on your NetApp storage system or platform. The following example commands show the provisioning of a new FlexVol volume. In this example, the volume is provisioned using the StorageClass that was created in the example in the section [Example Kubernetes StorageClasses for ONTAP AI Deployments](#), step 2.

An `accessModes` value of `ReadWriteMany` is specified in the following example PVC definition file. For more information about the `accessMode` field, see the [official Kubernetes documentation](#).

```

$ cat << EOF > ./pvc-tensorflow-results.yaml
kind: PersistentVolumeClaim
apiVersion: v1
metadata:
  name: tensorflow-results
spec:
  accessModes:
    - ReadWriteMany
  resources:
    requests:
      storage: 1Gi
  storageClassName: ontap-ai-flexvols-retain
EOF
$ kubectl create -f ./pvc-tensorflow-results.yaml
persistentvolumeclaim/tensorflow-results created
$ kubectl get pvc
NAME                                STATUS    VOLUME
CAPACITY    ACCESS MODES  STORAGECLASS          AGE
pb-fg-all-iface1  Bound        default-pb-fg-all-iface1-7d9f1
10995116277760  ROX          ontap-ai-flexgroups-retain-iface1  26h
pb-fg-all-iface2  Bound        default-pb-fg-all-iface2-85aee
10995116277760  ROX          ontap-ai-flexgroups-retain-iface2  26h
tensorflow-results  Bound        default-tensorflow-results-
2fd60    1073741824    RWX          ontap-ai-flexvols-retain
25h

```

[Next: Example High-Performance Jobs for ONTAP AI Deployments Overview](#)

## Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.