



# Customizing the transition of 7-Mode configurations

## ONTAP 7-Mode Transition

NetApp  
May 31, 2021

This PDF was generated from [https://docs.netapp.com/us-en/ontap-7mode-transition/copy-free/reference\\_example\\_consolidating\\_nfs\\_export\\_rules\\_for\\_transition.html](https://docs.netapp.com/us-en/ontap-7mode-transition/copy-free/reference_example_consolidating_nfs_export_rules_for_transition.html) on May 31, 2021. Always check docs.netapp.com for the latest.

# Table of Contents

- Customizing the transition of 7-Mode configurations ..... 1
  - Examples of consolidating NFS export rules and Snapshot schedules for transition ..... 1

# Customizing the transition of 7-Mode configurations

When planning the transition of configurations from 7-Mode to ONTAP, you can customize the configuration transition in two ways. You can ignore or skip the transition of one or more configurations. You can consolidate the 7-Mode NFS export rules, and then reuse an existing NFS export policy and Snapshot policy on the target SVM.

The 7-Mode Transition Tool does not perform prechecks for the configuration that is excluded.

By default, all 7-Mode configurations are selected for transition.

It is a best practice to run the prechecks with all configurations first, and then exclude one or more configurations in the subsequent run of the prechecks. This helps you to understand which configurations are excluded from transition and which prechecks are skipped subsequently.

## Steps

1. From the Plan Configuration page, select the following options from the **SVM Configuration** pane:
  - For excluding the transition of configurations, clear the check box for those configurations.
  - For consolidating similar 7-Mode NFS export rules to a single export policy in ONTAP, which can then be applied to the transitioned volume or qtree, select the **Consolidate NFS Export Policies on 7-Mode** check box.
  - For reusing an existing NFS export policy on the SVM that matches the export policy that will be created by the tool, which can then be applied to the transitioned volumes or qtrees, select the **Reuse Export Policies of SVM** check box.
  - For consolidating similar 7-Mode Snapshot schedules to a single Snapshot policy in ONTAP, which can then be applied to the transitioned volume, select the **Consolidate 7-Mode Snapshot Policies** check box.
  - For reusing an existing Snapshot policy on the SVM that matches the Snapshot policy that will be created by the tool, which can then be applied to the transitioned volumes, select the **Reuse Snapshot Policies of SVM** check box.
2. Click **Save and go to Dashboard**.

## Related information

[NFS transition: supported and unsupported configurations, and required manual steps](#)

[Supported and unsupported CIFS configurations for transition to ONTAP](#)

[Data protection transition: supported and unsupported configurations](#)

[Name services transition: supported and unsupported configurations, and required manual steps](#)

## Examples of consolidating NFS export rules and Snapshot schedules for transition

You might want to review examples of how similar 7-Mode export rules and 7-Mode Snapshot schedules are consolidated to a single NFS export policy and a single

Snapshot policy in ONTAP. You might also want to understand how the consolidated policies are assigned to the transitioned volumes or qtrees with or without reusing a matching existing policy on the target SVM.

## Example of consolidating NFS export rules for transition

### NFS export rules in 7-Mode and ONTAP before transition

#### 7-Mode export rules

```
/vol/vol1      -sec=sys,rw,nosuid
/vol/vol2      -sec=sys,rw,nosuid
/vol/vol3      -sec=sys,rw,nosuid
```

### Export policies existing in ONTAP

```
cluster-2::> vserver export-policy show -vserver vs1
Vserver          Policy Name
-----
vs1              default
vs1              export_policy_1
```

The existing export policy `export_policy_1` has the following export rule:

```
cluster-2::> vserver export-policy rule show -vserver vs1 -policyname
export_policy_1
Policy          Rule      Access  Client  RO
Vserver        Name      Index   Protocol Match  Rule
-----
vs1            export_policy_1 1      nfs     0.0.0.0/0  sys
```

### Export policies in ONTAP after transition with consolidation (no reuse)

Volumes `vol1`, `vol2`, and `vol3` have similar export rules in 7-Mode; therefore, a new consolidated export policy, `transition_export_policy_1`, is assigned to these volumes after transition:

```
cluster-2::> vserver export-policy show -vserver vs1
Vserver          Policy Name
-----
vs1              default
vs1              export_policy_1
vs1              transition_export_policy_1
3 entries were displayed.
```

```
cluster-2::> vserver export-policy rule show -vserver vs1 -policyname
transition_export_policy_1
Vserver          Policy          Rule      Access  Client      RO
Name            Index      Protocol Match      Rule
-----
vs1              transition_export_policy_1
                  1          nfs        0.0.0.0/0      sys
```

```
cluster-2::> volume show -vserver vs1 -volume vol1,vol2,vol3 -fields
policy
vserver volume policy
-----
vs1      vol1      transition_export_policy_1
vs1      vol2      transition_export_policy_1
vs1      vol3      transition_export_policy_1
3 entries were displayed.
```

### Export policies in ONTAP after transition with consolidation and reuse

Volumes vol1, vol2, and vol3 have similar export rules in 7-Mode; therefore, a consolidated export policy is assigned to these volumes after transition. The export policy, export\_policy\_1, which matches the 7-Mode export rules, already exists on the SVM. Therefore, the policy is applied to these volumes:

```
cluster-2::> vserver export-policy show -vserver vs1
Vserver          Policy Name
-----
vs1              default
vs1              export_policy_1
2 entries were displayed.
```

```
cluster-2::> vserver export-policy rule show -vserver vs1 -policyname
export_policy_1
      Policy           Rule    Access  Client      RO
Vserver  Name             Index  Protocol Match  Rule
-----
vs1      export_policy_1  1      nfs      0.0.0.0/0    sys
```

```
cluster-2::> volume show -vserver vs1 -volume vol1,vol2,vol3 -fields
policy
vserver volume policy
-----
vs1      vol1      export_policy_1
vs1      vol2      export_policy_1
vs1      vol3      export_policy_1
3 entries were displayed.
```

## Example of consolidating Snapshot policies for transition

### Snapshot schedules in 7-Mode and ONTAP before transition

#### 7-Mode schedule

7-Mode volume	7-Mode Snapshot schedule
vol1	0 2 4@8,12,16,20 (weekly Snapshot copies: 0, daily Snapshot copies: 2, hourly Snapshot copies: 6 at 2, 4, 8, 12, 16, 20 hours)
vol2	0 2 4@8,12,16,20
vol3	0 2 4@8,12,16,20
vol4	1 2 3@8,12,16 (weekly Snapshot copies: 1, daily Snapshot copies: 2, hourly Snapshot copies: 3 at 8,12,16 hours)
vol5	2 2 3@8,12,16 (weekly Snapshot copies: 2, daily Snapshot copies: 2, hourly Snapshot copies: 3 at 8,12,16 hours)

#### Snapshot policies existing in ONTAP

Snapshot policy name	Policy details
ScheduleWeekly	Weekly, count: 1
ScheduleDailyHourly4	<b>Schedule details</b> <ul style="list-style-type: none"> <li>• Schedule1: daily, count1: 2</li> <li>• Schedule2: hourly, count2: 4 every 8, 12, 16, 20 hours</li> </ul>
ScheduleHourly1	Hourly at 8, 12, 16, 20 hours, count: 4

**Snapshot policy in ONTAP after transition with consolidation (no reuse)**

7-Mode volume	7-Mode Snapshot schedule	Snapshot policy in ONTAP
vol1	0 2 4@8,12,16,20 (weekly Snapshot copies: 0, daily Snapshot copies: 2, hourly Snapshot copies: 4 at 8, 12, 16, 20 hours)	<b>Consolidated policy for vol1, vol2, and vol3</b> <ul style="list-style-type: none"> <li>• Name: transition_snapshot_policy_0</li> <li>• Schedule details <ul style="list-style-type: none"> <li>◦ Schedule1: daily, count1: 2</li> <li>◦ Schedule2: hourly, count2: 4 every 8, 12, 16, 20 hours</li> </ul> </li> </ul>
vol2	0 2 4@8,12,16,20	vol3
0 2 4@8,12,16,20	vol4	1 2 3@8,12,16 (weekly Snapshot copies: 1, daily Snapshot copies: 2, hourly Snapshot copies: 3 at 8,12,16 hours)
<ul style="list-style-type: none"> <li>• Name: transition_snapshot_policy_1</li> <li>• Schedule details <ul style="list-style-type: none"> <li>◦ Schedule1: weekly, count1: 1</li> <li>◦ Schedule2: daily, count2: 2</li> <li>◦ Schedule3: hourly, count3: 3 every 8,12,16 hours</li> </ul> </li> </ul>	vol5	2 2 3@8,12,16 (weekly Snapshot copies: 2, daily Snapshot copies: 2, hourly Snapshot copies: 3 at 8,12,16 hours)

**Snapshot policy in ONTAP after transition with consolidation and reuse**

7-Mode volume	7-Mode Snapshot schedule	Snapshot policy in ONTAP
vol1	0 2 4@8,12,16,20 (weekly Snapshot copies: 0, daily Snapshot copies: 2, hourly Snapshot copies: 4 at 2, 4, 8, 12, 16, 20 hours)	Consolidated policy for vol1, vol2, and vol3 for which the existing ONTAP policy is reused  Name: ScheduleDailyHourly4
vol2	0 2 4@8,12,16,20	vol3
0 2 4@8,12,16,20	vol4	1 2 3@8,12,16 (weekly Snapshot copies: 1, daily Snapshot copies: 2, hourly Snapshot copies: 3 at 8,12,16 hours)
<ul style="list-style-type: none"> <li>• Name: transition_snapshot_policy_1</li> <li>• Schedule details <ul style="list-style-type: none"> <li>◦ Schedule1: weekly, count1: 1</li> <li>◦ Schedule2: daily, count2: 2</li> <li>◦ Schedule3: hourly, count3: 3 every 8,12,16 hours</li> </ul> </li> </ul>	vol5	2 2 3@8,12,16 (weekly Snapshot copies: 2, daily Snapshot copies: 2, hourly Snapshot copies: 3 at 8,12,16 hours)



## Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.