



snapmirror policy commands

ONTAP commands

NetApp

February 03, 2026

Table of Contents

- snapmirror policy commands 1
 - snapmirror policy add-rule 1
 - Description 1
 - Parameters 1
 - Examples 2
 - Related Links 3
 - snapmirror policy create 3
 - Description 3
 - Parameters 3
 - Examples 6
 - Related Links 6
 - snapmirror policy delete 6
 - Description 6
 - Parameters 6
 - Examples 7
 - snapmirror policy modify-rule 7
 - Description 7
 - Parameters 7
 - Examples 8
 - Related Links 9
 - snapmirror policy modify 9
 - Description 9
 - Parameters 9
 - Examples 11
 - Related Links 11
 - snapmirror policy remove-rule 11
 - Description 11
 - Parameters 11
 - Examples 12
 - snapmirror policy show 12
 - Description 12
 - Parameters 12
 - Examples 15

snapmirror policy commands

snapmirror policy add-rule

Add a new rule to SnapMirror policy

Availability: This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

Description

The `snapmirror policy add-rule` command adds a rule to a SnapMirror policy. Rules define which snapshots are protected by vault relationships or define the schedule at which snapshots are created on the SnapMirror destination. Rules which do not include a schedule are rules for protecting snapshots. Rules which include a schedule are rules for creating snapshots on the SnapMirror destination. A rule with a schedule can only be added to SnapMirror policies of type *vault* or *mirror-vault*. A rule must not be added to a policy that will be associated with a SnapMirror data protection relationship. A policy that will be associated with a SnapMirror vault relationship must have at least one rule and at most ten rules. A SnapMirror policy with rules must have at least one rule without a schedule.

Parameters

-vserver <vserver name> - Vserver Name

Specifies the Vserver for the SnapMirror policy.

-policy <sm_policy> - SnapMirror Policy Name

Specifies the SnapMirror policy name.

-snapmirror-label <text> - Snapshot Copy Label

This parameter is primarily used for the purpose of snapshot selection for extended data protection (XDP) relationships. Only snapshots that have a SnapMirror label that matches this parameter will be transferred to the SnapMirror destination. However, when this parameter is associated with a rule containing a schedule, snapshots will be created on the SnapMirror destination using this `snapmirror-label` parameter. The label can be 31 or fewer characters in length. SnapMirror policies of type *async-mirror* and *mirror-vault* have a rule added for label `sm_created` at the time of policy creation. This rule cannot be removed or modified by the user. This rule when coupled with `create-snapshot` field set to *true* indicates that the SnapMirror relationship using this policy shall create a new snapshot and transfer it as part of a [snapmirror update](#) operation. SnapMirror policies of type *async-mirror* support one additional rule with SnapMirror label `all_source_snapshots`. This rule along with the rule for SnapMirror label `sm_created` indicates that *all* new snapshots on the primary volume along with the newly created snapshot are transferred as a part of a [snapmirror update](#) or [snapmirror initialize](#) operation. Rules with any other SnapMirror labels cannot be added to SnapMirror policies of type *async-mirror*. The rule for label `sm_created` when added to a `snapmirror policy` of type *vault* indicates that all SnapMirror created snapshots of the primary volume are selected for transfer.

-keep <text> - Snapshot Copy Retention Count

Specifies the maximum number of snapshots that are retained on the SnapMirror destination volume for a rule. The total number of snapshots retained for all the rules in a policy cannot exceed 1019. For all the rules in SnapMirror policies of type *async-mirror*, this parameter must be set to value *1*.

`[-preserve {true|false}]` - Snapshot Copy Preserve Enabled

Specifies the behavior when the snapshot retention count is reached on the SnapMirror vault destination for the rule. The default value is *false*, which means that the oldest snapshot will be deleted to make room for new ones only if the number of snapshots has exceeded the retention count specified in the "keep" parameter. When set to *true*, and when the snapshots have reached the retention count, then an incremental SnapMirror vault update transfer will fail or if the rule has a schedule, snapshots will no longer be created on the SnapMirror destination. For all the rules in SnapMirror policies of type *async-mirror* this parameter must be set to value *false*.

`[-warn <integer>]` - Warning Threshold Count

Specifies the warning threshold count for the rule. The default value is *0*. When set to a value greater than zero, an event is generated after the number of snapshots (for the particular rule) retained on a SnapMirror vault destination reaches the specified warn limit. The preserve parameter for the rule must be *true* to set the warn parameter to a value greater than zero.

`[-schedule <text>]` - Snapshot Copy Creation Schedule

This optional parameter specifies the name of the schedule associated with a rule. This parameter is allowed only for rules associated with SnapMirror policies of type *vault* or *mirror-vault*. When this parameter is specified, snapshots are directly created on the SnapMirror destination. The snapshots created will have the same content as the latest snapshot already present on the SnapMirror destination. snapshots on the source that have a SnapMirror label matching this rule will not be selected for transfer. The default value is *-*.



You define and name a schedule using the [job schedule cron create](#) command.

`[-prefix <text>]` - Snapshot Copy Creation Prefix

This optional parameter specifies the prefix for the snapshot name to be created as per the schedule. If no value is specified, then the *snapmirror-label* will be used as the prefix. The prefix parameter can only be specified for rules which have a schedule.

`[-retention-period {{<integer> seconds|minutes|hours|days|months|years} | infinite}]` - Snapshot Copy Retention Period

This optional parameter specifies the duration for which the snapshots associated with this rule will be locked. The parameter is specified as a number followed by a suffix. The valid suffixes are *seconds*, *minutes*, *hours*, *days*, *months*, and *years*. For example, a value of *6months* represents a retention period of 6 months. It can also be set to a special value of *infinite* for infinite retention. The destination volume must have the *snapshot-locking-enabled* parameter set to true for this field to take effect else it will be ignored.

Examples

The following example adds a rule named *nightly* to the SnapMirror policy named *TieredBackup* on Vserver *vs0.example.com*. The rule will retain a maximum of 5 *nightly* snapshots.

```
vs0.example.com::> snapmirror policy add-rule -vserver vs0.example.com
                    -policy TieredBackup -snapmirror-label nightly -keep 5
```

Related Links

- [snapmirror update](#)
- [snapmirror initialize](#)
- [job schedule cron create](#)

snapmirror policy create

Create a new SnapMirror policy

Availability: This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

Description

The `snapmirror policy create` command creates a SnapMirror policy. When applied to a SnapMirror relationship, the SnapMirror policy controls the behavior of the relationship and specifies the configuration attributes for that relationship. The policies *DPDefault*, *MirrorAllSnapshots*, *MirrorAndVault*, *MirrorLatest*, *Unified7year*, and *XDPDefault* are created by the system for asynchronous replication. The policies *Sync*, *StrictSync*, *AutomatedFailOver*, and *AutomatedFailOverDuplex* are created by the system for synchronous replication.



All SnapMirror policies have a field `create-snapshot`. This field specifies whether SnapMirror creates a new snapshot on the primary volume at the beginning of a [snapmirror update](#) or [snapmirror resync](#) operation. Currently this field cannot be set or modified by the user. It is set to `true` for SnapMirror policies of type *async-mirror* and *mirror-vault* at the time of creation. SnapMirror policies of type *vault* have `create-snapshot` set to `false` at the time of creation.



Use the [snapmirror policy add-rule](#) command to add a rule to a policy.

Parameters

-vserver <vserver name> - Vserver Name

Specifies the Vserver for the SnapMirror policy.

-policy <sm_policy> - SnapMirror Policy Name

This parameter specifies the SnapMirror policy name. A policy name can be made up of the characters A to Z, a to z, 0 to 9, ".", "-", and "_". The name can be up to 256 characters in length.

[-type {vault|async-mirror|mirror-vault|strict-sync-mirror|sync-mirror|automated-failover|automated-failover-duplex|continuous}] - Snapmirror Policy Type

This parameter specifies the SnapMirror policy type. The supported values are *async-mirror*, *vault*, *mirror-vault*, *sync-mirror* and *strict-sync-mirror*. Data protection (DP) relationships support only *async-mirror* policy type, while extended data protection (XDP) relationships support all policy types.

If the type is set to *async-mirror* then the policy is for Disaster Recovery. When the policy type is associated with extended data protection (XDP) relationships, [snapmirror update](#) and [snapmirror resync](#) operations transfer selected snapshots from the primary volume to the secondary volume. The selection of snapshots is governed by the rules in the policy. However [snapmirror initialize](#) and [snapmirror update](#)

operations on data protection (DP) relationships ignore the rules in the policy and transfer *all* snapshots of the primary volume which are newer than the common snapshot on the destination. For both data protection (DP) and extended data protection (XDP) relationships, the snapshots are kept on the secondary volume as long as they exist on the primary volume. Once a protected snapshot is deleted from the primary volume, it is deleted from the secondary volume as part of the next transfer. The policy type supports rules with certain pre-defined label names only. Refer to the man page for the [snapmirror policy add-rule](#) command for the details.

If the type is set to *vault* then the policy is used for Backup and Archive. The rules in this policy type determine which snapshots are protected and how long they are retained on the secondary volume. This policy type is supported by extended data protection (XDP) relationships only.

If the type is set to *mirror-vault* then the policy is used for unified data protection which provides both Disaster Recovery and Backup using the same secondary volume. This policy type is supported by extended data protection (XDP) relationships only.

If the type is set to *sync-mirror* or *strict-sync-mirror* then the policy is used for synchronous Disaster Recovery. These are supported only by extended data protection (XDP) relationships between FlexVol volumes. Once the relationship is initialized with [snapmirror initialize](#), the relationship will be InSync such that all writes to the primary will be replicated to the secondary before the write is acknowledged to the client. Upon a replication failure, relationship falls OutOfSync. Upon an OutOfSync event, the *strict-sync-mirror* variant restricts further client IO on the primary, whereas the *sync-mirror* variant does not. SnapMirror will automatically trigger resync to bring the OutOfSync relationships back InSync as soon as it can, unless the relationship is *Quiesced* or *Broken-off*. Once a relationship is initialized, you normally use the [snapmirror quiesce](#) command to stop synchronous replication and the [snapmirror resume](#) command to resume synchronous replication. These policy types do not support replication of user snapshots.

`[-comment <text>] - Comment`

Specifies a text comment for the SnapMirror policy. If the comment contains spaces, it must be enclosed within quotes.

`[-tries <integer_or_unlimited>] - Tries Limit`

Determines the maximum number of times to attempt each manual or scheduled transfer for a SnapMirror relationship. The value of this parameter must be a positive integer or *unlimited*. The default value is *8*.

`[-transfer-priority {low|normal}] - Transfer Scheduling Priority`

Specifies the priority at which a transfer runs. The supported values are *normal* or *low*. The *normal* transfers are scheduled before the *low* priority transfers. The default is *normal*.

`[-ignore-atime {true|false}] - Ignore File Access Time`

This parameter applies only to extended data protection (XDP) relationships. It specifies whether incremental transfers will ignore files which have only their access time changed. The supported values are *true* or *false*. The default is *false*.

`[-restart {always|never|default}] - Restart Behavior`

This parameter applies only to data protection relationships. It defines the behavior of SnapMirror if an interrupted transfer exists. The supported values are *always*, *never*, or *default*. If the value is set to *always*, an interrupted SnapMirror transfer always restarts provided it has a restart checkpoint and the conditions are the same as they were before the transfer was interrupted. In addition, a new SnapMirror snapshot is created which will then be transferred. If the value is set to *never*, an interrupted SnapMirror transfer will never restart, even if a restart checkpoint exists. A new SnapMirror snapshot will still be created

and transferred. ONTAP version 8.2 will interpret a value of *default* as being the same as *always*. Vault transfers will always resume based on a restart checkpoint, provided the snapshot still exists on the source volume.

`[-is-network-compression-enabled {true|false}] - Is Network Compression Enabled`

Specifies whether network compression is enabled for transfers. The supported values are *true* or *false*. The default is *false*.

`[-rpo <integer>] - Recovery Point Objective (seconds)`

Specifies the time for recovery point objective, in seconds. This parameter is only supported for a policy of type *continuous*.

`[-always-replicate-snapshots {true|false}] - This prioritizes replication of app-consistent snapshots over synchronous replication`

If this parameter is set to *true*, it specifies that SnapMirror Synchronous relationships will lose the zero RPO protection upon failure in replicating application created snapshots. The default value is *false*.

`[-common-snapshot-schedule <text>] - Common Snapshot Copy Creation Schedule for SnapMirror Synchronous (privilege: advanced)`

Specifies the common snapshot creating schedule. This parameter is only supported for SnapMirror Synchronous relationships.

`[-are-data-ops-sequentially-split {true|false}] - Is Sequential Splitting of Data Operations Enabled? (privilege: advanced)`

This parameter specifies whether I/O, such as write, copy-offload and punch-holes, are split sequentially, rather than being run in parallel on the source and destination. Splitting I/O sequentially will make the system more robust, and less prone to I/O errors. Starting 9.11.1, enabling this feature improves the performance when the workload is NAS based and is metadata heavy. However, it will make the IO performance slower for large file workloads like LUNs, databases, virtualization containers, etc. The default value for the parameter `-are-data-ops-sequentially-split` is *false*. The parameter `-are-data-ops-sequentially-split` should only be used if frequent I/O timeout or "OutOfSync" has happened. The parameter `-are-data-ops-sequentially-split` requires an effective cluster version of ONTAP 9.6.0 or later on both the source and destination clusters.

`[-sequential-split-op-timeout-secs <integer>] - Sequential Split Op Timeout in Seconds (privilege: advanced)`

This parameter specifies the op timeout value used when the splitting mode is sequential. This parameter is used only for Sync relationships. Supported values are from 15 to 25 seconds.

`[-disable-fast-resync {true|false}] - Disable Fast Resync (privilege: advanced)`

Specifies whether fast resync for a SnapMirror Synchronous relationship is disabled or not. The default value for this parameter is *false*.

`[-discard-configs <network>, ...] - Configurations Not Replicated During Identity Preserve Vserver DR`

Specifies the configuration to be dropped during replication. The supported values are:

- *network* - Drops network interfaces, routes, and kerberos configuration.

This parameter is supported only for policies of type *async-mirror* and applicable only for identity-preserve Vserver SnapMirror relationships.

[`-transfer-schedule-name <text>`] - Transfer Schedule Name

This optional parameter specifies the schedule which is used to update the SnapMirror relationships.

[`-throttle <throttleType>`] - Throttle (KB/sec)

This optional parameter limits the network bandwidth used for transfers. It configures for the relationships the maximum rate (in Kbytes/sec) at which data can be transferred. If no throttle is configured, by default the SnapMirror relationships fully use the network bandwidth available. You can also configure the relationships to fully use the network bandwidth available by explicitly setting the throttle to *unlimited* or *0*. The minimum effective throttle value is four Kbytes/sec, so if you specify a throttle value between *1* and *4*, it will be treated as *4*. For FlexGroup volume relationships, the throttle value is applied individually to each constituent relationship.

Examples

The following example creates a SnapMirror policy named *TieredBackup* on a Vserver named *vs0.example.com*.

```
vs0.example.com::> snapmirror policy create -vserver vs0.example.com
                    -policy TieredBackup -type vault -tries 10 -restart never
```

Related Links

- [snapmirror update](#)
- [snapmirror resync](#)
- [snapmirror policy add-rule](#)
- [snapmirror initialize](#)
- [snapmirror quiesce](#)
- [snapmirror resume](#)

snapmirror policy delete

Delete a SnapMirror policy

Availability: This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

Description

The `snapmirror policy delete` command deletes a SnapMirror policy. A policy that is to be deleted must not be associated with any SnapMirror relationship. The built-in policies cannot be deleted.

Parameters

`-vserver <vserver name>` - Vserver Name

Specifies the Vserver for the SnapMirror policy.

-policy <sm_policy> - SnapMirror Policy Name

Specifies the SnapMirror policy name.

Examples

The following example deletes a SnapMirror policy named *TieredBackup* on Vserver *vs0.example.com*:

```
vs0.example.com::> snapmirror policy delete -vserver vs0.example.com
-policy TieredBackup
```

snapmirror policy modify-rule

Modify an existing rule in SnapMirror policy

Availability: This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

Description

The `snapmirror policy modify-rule` command can be used to modify the retention count, preserve setting, warning threshold count, schedule, and prefix for a rule in a SnapMirror policy. Reducing the retention count or disabling the preserve setting for a rule in a SnapMirror policy might result in the deletion of snapshots on the vault destination when the next transfer by the [snapmirror update](#) command occurs or when the next scheduled snapshot creation on the destination for the rule occurs. Modifying a rule to add a schedule will enable creation of snapshots on the SnapMirror destination. snapshots on the source that have a SnapMirror label matching this rule will not be selected for transfer. Schedule and prefix can only be modified for rules associated with SnapMirror policies of type *vault* or *mirror-vault*. A SnapMirror policy with rules must have at least one rule without a schedule.



The rules in SnapMirror policies of type *async-mirror* cannot be modified.

Parameters

-vserver <vserver name> - Vserver Name

Specifies the Vserver for the SnapMirror policy.

-policy <sm_policy> - SnapMirror Policy Name

Specifies the SnapMirror policy name.

-snapmirror-label <text> - Snapshot Copy Label

This parameter specifies the rule that is to be modified in a SnapMirror policy.

[-keep <text>] - Snapshot Copy Retention Count

Specifies the maximum number of snapshots that are retained on the SnapMirror destination volume for a rule. The total number of snapshots retained for all the rules in a policy cannot exceed 1019. For all the rules in SnapMirror policies of type *async-mirror*, this parameter must be set to value *1*.

`[-preserve {true|false}] - Snapshot Copy Preserve Enabled`

Specifies the behavior when the snapshot retention count is reached on the SnapMirror vault destination for the rule. The default value is *false*, which means that the oldest snapshot will be deleted to make room for new ones only if the number of snapshots has exceeded the retention count specified in the "keep" parameter. When set to *true*, and when the snapshots have reached the retention count, then an incremental SnapMirror vault update transfer will fail or if the rule has a schedule, snapshots will no longer be created on the SnapMirror destination. For all the rules in SnapMirror policies of type *async-mirror* this parameter must be set to value *false*.

`[-warn <integer>] - Warning Threshold Count`

Specifies the warning threshold count for the rule. The default value is *0*. When set to a value greater than zero, an event is generated after the number of snapshots (for the particular rule) retained on a SnapMirror vault destination reaches the specified warn limit. The preserve parameter for the rule must be *true* to set the warn parameter to a value greater than zero.

`[-schedule <text>] - Snapshot Copy Creation Schedule`

This optional parameter specifies the name of the schedule associated with a rule. This parameter is allowed only for rules associated with SnapMirror policies of type *vault* or *mirror-vault*. When this parameter is specified, snapshots are directly created on the SnapMirror destination. The snapshots created will have the same content as the latest snapshot already present on the SnapMirror destination. snapshots on the source that have a SnapMirror label matching this rule will not be selected for transfer. The default value is *-*.



You define and name a schedule using the [job schedule cron create](#) command.

`[-prefix <text>] - Snapshot Copy Creation Prefix`

This optional parameter specifies the prefix for the snapshot name to be created as per the schedule. If no value is specified, then the *snapmirror-label* will be used as the prefix. The prefix parameter can only be specified for rules which have a schedule.

`[-retention-period {{<integer> seconds|minutes|hours|days|months|years} | infinite}] - Snapshot Copy Retention Period`

This optional parameter specifies the duration for which the snapshots associated with this rule will be locked. The parameter is specified as a number followed by a suffix. The valid suffixes are *seconds*, *minutes*, *hours*, *days*, *months*, and *years*. For example, a value of *6months* represents a retention period of 6 months. It can also be set to a special value of *infinite* for infinite retention. The destination volume must have the *snapshot-locking-enabled* parameter set to true for this field to take effect else it will be ignored.

Examples

The following example changes the retention count for *nightly* snapshots to *6* for a rule named *nightly* on a SnapMirror policy named *TieredBackup* on Vserver *vs0.example.com*:

```
vs0.example.com::> snapmirror policy modify-rule -vserver vs0.example.com
                    -policy TieredBackup -snapmirror-label nightly -keep 6
```

Related Links

- [snapmirror update](#)
- [job schedule cron create](#)

snapmirror policy modify

Modify a SnapMirror policy

Availability: This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

Description

The `snapmirror policy modify` command can be used to modify the policy attributes.



Use the `snapmirror policy modify-rule` command to modify a rule in a SnapMirror policy.

Parameters

-vserver <vserver name> - Vserver Name

Specifies the Vserver for the SnapMirror policy.

-policy <sm_policy> - SnapMirror Policy Name

Specifies the SnapMirror policy name.

[-comment <text>] - Comment

Specifies a text comment for the SnapMirror policy. If the comment contains spaces, it must be enclosed within quotes.

[-tries <integer_or_unlimited>] - Tries Limit

Determines the maximum number of times to attempt each manual or scheduled transfer for a SnapMirror relationship. The value of this parameter must be a positive integer or *unlimited*. The default value is *8*.

[-transfer-priority {low|normal}] - Transfer Scheduling Priority

Specifies the priority at which a transfer runs. The supported values are *normal* or *low*. The *normal* transfers are scheduled before the *low* priority transfers. The default is *normal*.

[-ignore-atime {true|false}] - Ignore File Access Time

This parameter applies only to extended data protection (XDP) relationships. It specifies whether incremental transfers will ignore files which have only their access time changed. The supported values are *true* or *false*. The default is *false*.

[-restart {always|never|default}] - Restart Behavior

This parameter applies only to data protection relationships. It defines the behavior of SnapMirror if an interrupted transfer exists. The supported values are *always*, *never*, or *default*. If the value is set to *always*, an interrupted SnapMirror transfer always restarts provided it has a restart checkpoint and the conditions are the same as they were before the transfer was interrupted. In addition, a new SnapMirror snapshot is created which will then be transferred. If the value is set to *never*, an interrupted SnapMirror transfer will never restart, even if a restart checkpoint exists. A new SnapMirror snapshot will still be created

and transferred. ONTAP version 8.2 will interpret a value of *default* as being the same as *always*. Vault transfers will always resume based on a restart checkpoint, provided the snapshot still exists on the source volume.

`[-is-network-compression-enabled {true|false}] - Is Network Compression Enabled`

Specifies whether network compression is enabled for transfers. The supported values are *true* or *false*. The default is *false*.

`[-rpo <integer>] - Recovery Point Objective (seconds)`

Specifies the time for recovery point objective, in seconds. This parameter is only supported for a policy of type *continuous*.

`[-always-replicate-snapshots {true|false}] - This prioritizes replication of app-consistent snapshots over synchronous replication`

If this parameter is set to *true*, it specifies that SnapMirror Synchronous relationships will lose the zero RPO protection upon failure in replicating application created snapshots. The default value is *false*.

`[-common-snapshot-schedule <text>] - Common Snapshot Copy Creation Schedule for SnapMirror Synchronous (privilege: advanced)`

Specifies the common snapshot creating schedule. This parameter is only supported for SnapMirror Synchronous relationships.

`[-are-data-ops-sequentially-split {true|false}] - Is Sequential Splitting of Data Operations Enabled? (privilege: advanced)`

This parameter specifies whether I/O, such as write, copy-offload and punch-holes, are split sequentially, rather than being run in parallel on the source and destination. Splitting the I/O sequentially will make the system more robust, and less prone to I/O errors. Starting 9.11.1, enabling this feature improves the performance when the workload is NAS based and is metadata heavy. However, it will make the IO performance slower for large file workloads like LUNs, databases, virtualization containers, etc. The default value of parameter `-sequential-split-data-ops` is *false*. The parameter `-are-data-ops-sequentially-split` should only be used if frequent I/O timeout or "OutOfSync" has happened. Changes made by the `snapmirror policy modify -sequential-split-data-ops` command do not take effect until the next resync. Changes do not affect resync or initialize operations that have started and have not finished yet. The parameter `-are-data-ops-sequentially-split` requires an effective cluster version of ONTAP 9.6.0 or later on both the source and destination clusters.

`[-sequential-split-op-timeout-secs <integer>] - Sequential Split Op Timeout in Seconds (privilege: advanced)`

This parameter specifies the op timeout value used when the splitting mode is sequential. This parameter is used only for Sync relationships. Supported values are from 15 to 25 seconds. The default value of the parameter `-sequential-split-op-timeout` is *15 seconds*. Changes made by the `snapmirror policy modify -sequential-split-op-timeout-secs` command do not take effect until the next resync. Changes do not affect resync or initialize operations that have started and have not finished yet.

`[-disable-fast-resync {true|false}] - Disable Fast Resync (privilege: advanced)`

Specifies whether fast resync for a SnapMirror Synchronous relationship is disabled or not. The default value for this parameter when a policy is created is *false*.

`[-discard-configs <network>, ...] - Configurations Not Replicated During Identity Preserve Vserver DR`

Specifies the configuration to be dropped during replication. The supported values are:

- *network* - Drops network interfaces, routes, and kerberos configuration.

This parameter is supported only for policies of type *async-mirror* and applicable only for identity-preserve Vserver SnapMirror relationships.

[-transfer-schedule-name <text>] - Transfer Schedule Name

This optional parameter specifies the schedule which is used to update the SnapMirror relationships.

[-throttle <throttleType>] - Throttle (KB/sec)

This optional parameter limits the network bandwidth used for transfers. It configures for the relationships the maximum rate (in Kbytes/sec) at which data can be transferred. If no throttle is configured, by default the SnapMirror relationships fully use the network bandwidth available. You can also configure the relationships to fully use the network bandwidth available by explicitly setting the throttle to *unlimited* or *0*. The minimum effective throttle value is four Kbytes/sec, so if you specify a throttle value between *1* and *4*, it will be treated as *4*. For FlexGroup volume relationships, the throttle value is applied individually to each constituent relationship.

Examples

The following example changes the "transfer-priority" and the "comment" text of a SnapMirror policy named *TieredBackup* on Vserver *vs0.example.com*:

```
vs0.example.com::> snapmirror policy modify -vserver vs0.example.com
-policy TieredBackup -transfer-priority low -comment "Use for tiered
backups"
```

Related Links

- [snapmirror policy modify-rule](#)

snapmirror policy remove-rule

Remove a rule from SnapMirror policy

Availability: This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

Description

The `snapmirror policy remove-rule` command removes a rule from a SnapMirror policy. On the destination of a SnapMirror relationship with `snapmirror policy` of type *vault* or *mirror-vault*, all snapshots with a SnapMirror label matching the rule being removed are no longer processed by SnapMirror and might need to be deleted manually. A `snapmirror policy` of type *vault* must have at least one rule if that policy is associated with a SnapMirror relationship. A SnapMirror policy with rules must have at least one rule without a schedule.

Parameters

-vserver <vserver name> - Vserver Name

Specifies the Vserver for the SnapMirror policy.

-policy <sm_policy> - SnapMirror Policy Name

Specifies the SnapMirror policy name.

-snapmirror-label <text> - Snapshot Copy Label

This parameter specifies the rule that is removed from the SnapMirror policy.

The rule for SnapMirror label *sm_created* cannot be removed from SnapMirror policies of type *async-mirror* or *mirror-vault*.

Examples

The following example removes a rule named *nightly* from a SnapMirror policy named *TieredBackup* on Vserver *vs0.example.com*:

```
vs0.example.com::> snapmirror policy remove-rule -vserver vs0.example.com  
-policy TieredBackup -snapmirror-label nightly
```

snapmirror policy show

Show SnapMirror policies

Availability: This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

Description

The `snapmirror policy show` command displays the following information about SnapMirror policies:

- Vserver Name
- SnapMirror Policy Name
- SnapMirror Policy Type
- Number of Rules in the policy
- Tries
- Transfer Priority
- Comment for the policy
- Individual Rule Names
- Keep value for the Rule
- Total of Keep values across all Rules in the policy

Parameters

{ [-fields <fieldname>,...]

If you specify the `-fields <fieldname>, ...` parameter, the command output also includes the specified field or fields. You can use `-fields ?` to display the fields to specify.

| [-instance] }

If you specify the `-instance` parameter, the command displays detailed information about all fields.

[-vserver <vserver name>] - Vserver Name

Selects the policies that match this parameter value.

[-policy <sm_policy>] - SnapMirror Policy Name

Selects the policies that match this parameter value.

[-type {vault|async-mirror|mirror-vault|strict-sync-mirror|sync-mirror|automated-failover|automated-failover-duplex|continuous}] - Snapmirror Policy Type

Selects the policies that match this parameter value. A policy can be of type *async-mirror*, *vault* or *mirror-vault*.

[-owner {cluster-admin|vserver-admin}] - Owner of the Policy

Selects the policies that match this parameter value. A policy can be owned by either the *"Cluster Admin"* or a *"Vserver Admin"*.

[-comment <text>] - Comment

Selects the policies that match this parameter value.

[-tries <integer_or_unlimited>] - Tries Limit

Selects the policies that match this parameter value.

[-transfer-priority {low|normal}] - Transfer Scheduling Priority

Selects the policies that match this parameter value.

[-ignore-atime {true|false}] - Ignore File Access Time

Selects the policies that match this parameter value.

[-restart {always|never|default}] - Restart Behavior

Selects the policies that match this parameter value.

[-is-network-compression-enabled {true|false}] - Is Network Compression Enabled

Selects the policies that match this parameter value.

[-create-snapshot {true|false}] - Create a New Snapshot Copy

Selects the policies that match this parameter value.

[-rpo <integer>] - Recovery Point Objective (seconds)

Selects the policies that match this parameter value.

[-always-replicate-snapshots {true|false}] - This prioritizes replication of app-consistent snapshots over synchronous replication

Selects the policies that match this parameter value.

[-snapmirror-label <text>,...] - Snapshot Copy Label

Selects the policies that match this parameter value.

[-keep <text>,...] - Snapshot Copy Retention Count

Selects the policies that match this parameter value.

[-preserve {true|false}] - Snapshot Copy Preserve Enabled

Selects the policies that match this parameter value.

[-warn <integer>,...] - Warning Threshold Count

Selects the policies that match this parameter value.

[-schedule <text>,...] - Snapshot Copy Creation Schedule

Selects the policies that match this parameter value.

[-prefix <text>,...] - Snapshot Copy Creation Prefix

Selects the policies that match this parameter value.

[-retention-period {{<integer> seconds|minutes|hours|days|months|years} | infinite}] - Snapshot Copy Retention Period

This optional parameter specifies the duration for which the snapshots associated with this rule will be locked. The parameter is specified as a number followed by a suffix. The valid suffixes are *seconds* , *minutes* , *hours* , *days* , *months* , and *years* . For example, a value of *6months* represents a retention period of 6 months. It can also be set to a special value of *infinite* for infinite retention. The destination volume must have the *snapshot-locking-enabled* parameter set to true for this field to take effect else it will be ignored.

[-total-rules <integer>] - Total Rules in the Policy

Selects the policies that match this parameter value.

[-total-keep <integer>] - Total Retention Count for All Rules in the Policy

Selects the policies that match this parameter value.

[-common-snapshot-schedule <text>] - Common Snapshot Copy Creation Schedule for SnapMirror Synchronous (privilege: advanced)

Selects the policies that match this parameter value.

[-are-data-ops-sequentially-split {true|false}] - Is Sequential Splitting of Data Operations Enabled? (privilege: advanced)

Selects the policies that match this parameter value.

[-sequential-split-op-timeout-secs <integer>] - Sequential Split Op Timeout in Seconds (privilege: advanced)

Selects the policies that match this parameter value.

[-disable-fast-resync {true|false}] - Disable Fast Resync (privilege: advanced)

Selects the policies that match this parameter value.

[-discard-configs <network>,...] - Configurations Not Replicated During Identity Preserve Vserver DR

Selects the policies that match this parameter value.

[-transfer-schedule-name <text>] - Transfer Schedule Name

Selects the policies that match this parameter value.

[-throttle <throttleType>] - Throttle (KB/sec)

Selects the policies that match this parameter value.

Examples

The following example displays information about all SnapMirror policies:

```
cs::> snapmirror policy show
Vserver Policy          Policy Number      Transfer
Name      Name          Type    Of Rules Tries Priority Comment
-----
cs        DPDefault      async-mirror  2      8  normal  Asynchronous
SnapMirror policy for mirroring all snapshots and the latest active file
system.
  SnapMirror Label: sm_created                      Keep:          1
                    all_source_snapshots            1
                    Total Keep:                      2

cs        MirrorAllSnapshots async-mirror  2      8  normal  Asynchronous
SnapMirror policy for mirroring all snapshots and the latest active file
system.
  SnapMirror Label: sm_created                      Keep:          1
                    all_source_snapshots            1
                    Total Keep:                      2

cs        MirrorAndVault   mirror-vault  3      8  normal  A unified
Asynchronous SnapMirror and SnapVault policy for mirroring the latest
active file system and daily and weekly snapshots.
  SnapMirror Label: sm_created                      Keep:          1
                    daily                            7
                    weekly                          52
                    Total Keep:                     60

cs        MirrorLatest     async-mirror  1      8  normal  Asynchronous
SnapMirror policy for mirroring the latest active file system.
  SnapMirror Label: sm_created                      Keep:          1
                    Total Keep:                     1

vs0.example.com
TieredBackup      vault          0      8  normal  Use for tiered
```

```

backups
  Snapmirror-label: -
                                Keep:      -
                                Total Keep: 0

cs  Unified7year      mirror-vault  4      8  normal  Unified SnapMirror
policy with 7year retention.
  SnapMirror Label: sm_created
                                Keep:      1
                                daily       7
                                weekly     52
                                monthly    84
                                Total Keep: 144

cs      XDPDefault      vault      2      8  normal  Vault policy
with daily and weekly rules.
  SnapMirror Label: daily
                                Keep:      7
                                weekly     52
                                Total Keep: 59

7 entries were displayed.

```

The following example shows all the policies with the following fields - vserver (default), policy (default) and transfer-priority:

```

cs::> snapmirror policy show -fields transfer-priority
vserver      policy      transfer-priority
-----
cs           DPDefault normal
cs           MirrorAllSnapshots
                                normal
cs           MirrorAndVault
                                normal
cs           MirrorLatest
                                normal
vs0.example.com
  TieredBackup
                                normal
cs           Unified7year
                                normal
cs           XDPDefault
                                normal
7 entries were displayed.

```

Copyright information

Copyright © 2026 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.