



## **event notification commands**

### **ONTAP 9.5 commands**

NetApp  
August 29, 2024

# Table of Contents

- event notification commands ..... 1
  - event notification create ..... 1
  - event notification delete ..... 2
  - event notification modify ..... 3
  - event notification show ..... 4
  - event notification destination create ..... 5
  - event notification destination delete ..... 6
  - event notification destination modify ..... 8
  - event notification destination show ..... 10
  - event notification history show ..... 12

# event notification commands

## event notification create

Create an event notification

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

### Description

The `event notification create` command is used to create a new notification of a set of events defined by an event filter to one or more notification destinations.

### Parameters

**-filter-name <text> - Filter Name**

Use this mandatory parameter to specify the name of the event filter. Events that are included in the event filter are forwarded to the destinations specified in the destinations parameter.

The filter name passed to this command must be an existing filter. For more information, see the [event filter create](#) command.

**-destinations <text>, ... - List of Event Notification Destinations**

Use this mandatory parameter to specify the list of destinations to which the notification should be forwarded. Enter multiple destinations separated by a comma.

The destination passed to this command must be an existing destination. For more information, see the [event destination create](#) command.

### Examples

The following example creates an event notification for filter name "filter1" to destinations "email\_dest, snmp-traphost and syslog\_dest":

```

cluster1::> event notification destination show

Name                Type      Hide      Params      Destination
-----
email_dest          email    false     test@example.com
snmp-traphost       snmp     true      10.27.12.1 (from "system snmp
traphost")
syslog_dest         syslog   false     10.23.12.1
3 entries were displayed.

cluster1::> event filter show -filter-name filter1
Filter Name Rule      Rule      Message Name      SNMP Trap Type
Severity
          Position Type
-----
filter1
          1      exclude  callhome.bad.ram   *                *
          2      include  callhome.*         *
ALERT, ERROR
          3      exclude  *                  *                *
3 entries were displayed.

cluster1::> event notification create -filter-name filter1 -destinations
email_dest,syslog_dest,snmp-traphost

cluster1::> event notification show
ID      Filter Name      Destinations
-----
1       filter1           email_dest, syslog_dest, snmp-traphost

```

## Related Links

- [event filter create](#)
- [event destination create](#)

## event notification delete

Delete event notifications

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

### Description

The `event notification delete` command deletes an existing event notification.

## Parameters

### **-ID <integer> - Event Notification ID**

Use this parameter to specify the ID of the notification to be deleted.

## Examples

The following example shows the deletion of event notification with ID 1:

```
cluster1::> event notification show
ID      Filter Name      Destinations
-----
1       filter1           email_dest, syslog_dest, snmp-traphost

cluster1::> event notification delete -ID 1

cluster1::> event notification show
This table is currently empty.
```

## event notification modify

Modify event notifications

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

## Description

The `event notification modify` command is used to modify an existing notification.

## Parameters

### **-ID <integer> - Event Notification ID**

Use this mandatory parameter to specify the ID of the notification to be modified.

### **[-filter-name <text>] - Event Filter Name**

Use this parameter to specify the filter name to be modified.

### **[-destinations <text>,...] - List of Event Notification Destinations**

Use this parameter to specify the destinations to be modified. Enter multiple destinations separated by a comma.

Provide the complete set of destinations to be modified. Individual destination cannot be added or removed.

## Examples

The following example shows the modification of event notification with ID 1:

```

cluster1::> event notification show
ID      Filter Name      Destinations
-----
1       filter1          email_dest, syslog_dest, snmp-traphost

cluster1::> event notification modify -ID 1 -destinations email_dest,
syslog_dest

cluster1::> event notification show
ID      Filter Name      Destinations
-----
1       filter1          email_dest, syslog_dest

```

## event notification show

Display event notifications

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

### Description

The `event notification show` command is used to display the list of existing event notifications.

### Parameters

**{ [-fields <fieldname>,...]**

If you specify the `-fields <fieldname>, ...` parameter, the command output also includes the specified field or fields. You can use `'-fields ?'` to display the fields to specify.

**| [-instance ] }**

If you specify the `-instance` parameter, the command displays detailed information about all fields.

**[-ID <integer>] - Event Notification ID**

Use this parameter to display the detailed information about the notification ID you specify.

**[-filter-name <text>] - Event Filter Name**

Use this parameter to display event notifications that use the filter-name you specify.

**[-destinations <text>,...] - List of Event Notification Destinations**

Use this parameter to display event notifications that use the destinations you specify.

### Examples

The following example displays the event notification:

```
cluster1::> event notification show
ID      Filter Name      Destinations
-----
1       filter1          email_dest, syslog_dest, snmp-traphost
```

## event notification destination create

Create an event notification destination

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

### Description

The `event notification destination create` command creates a new event notification destination of either email or syslog type.

The following system-defined notification destination is configured for your use:

- `snmp-traphost` - This destination reflects the configuration in "system snmp traphost".

### Parameters

#### **-name <text> - Destination Name**

Use this mandatory parameter to specify the name of the notification destination that is to be created. An event notification destination name must be 2 to 64 characters long. Valid characters are the following ASCII characters: A-Z, a-z, 0-9, "\_", and "-". The name must start and end with: A-Z, a-z, or 0-9.

#### **{ -email <mail address> - Email Destination**

Use this parameter to specify the email address to which event notifications will be sent. For events to properly generate email notifications, the event system must also be configured with an address and mail server from which the mail will be sent. See [event config modify](#) command for more information.

#### **| -syslog <text> - Syslog Destination**

Use this parameter to specify syslog server host name or IP address to which syslog entries will be sent.

#### **| -rest-api-url <text> - REST API Server URL**

Use this parameter to specify REST API server URL to which event notifications will be sent. Enter the full URL, which must start either with an `http://` or `https://` prefix. To specify a URL that contains a question mark, press ESC followed by the `"?"`. + If an `https://` URL is specified, then Data ONTAP verifies the identity of the destination host by validating its certificate. If the Online Certificate Status Protocol (OCSP) is enabled for EMS, then Data ONTAP uses that protocol to determine the certificate's revocation status. Use the `security config oscp show -application ems` command to determine if the OCSP-based certificate revocation status check is enabled for EMS.

#### **[-certificate-authority <text>] - Client Certificate Issuing CA**

Use this parameter to specify the name of the certificate authority (CA) that signed the client certificate that will be sent in case mutual authentication with the REST API server is required. + There can be multiple client certificates installed for the admin vserver in the cluster, and this parameter, along with the `certificate-serial` parameter, uniquely identifies which one. + Use the [security certificate show](#)

command to see the list of certificates installed in the cluster.

### **[~~-certificate-serial~~ <text>] - Client Certificate Serial Number }**

Use this parameter to specify the serial number of the client certificate that will be sent in case mutual authentication with the REST API server is required.

## **Examples**

The following example shows the creation of a new event notification destination of type email called "StorageAdminEmail":

```
cluster1::> event notification destination create -name StorageAdminEmail
-email StorageAdmin@example.com

cluster1::> event notification destination show
```

Name	Type	Destination
-----	-----	-----
StorageAdminEmail	email	StorageAdmin@example.com
snmp-traphost	snmp	10.30.40.10 (from "system snmp traphost")

2 entries were displayed.

The following example shows the creation of a new event notification destination of type rest-api called "RestApi":

```
cluster1::> event notification destination create -name RestApi -rest-api
-url https://rest.example.com/rest
-certificate-authority cluster1-root-ca -certificate-serial 052213E60B7088

cluster1::> event notification destination show -name RestApi -instance
Destination Name: RestApi
      Type of Destination: rest-api
      Destination Values: https://rest.example.com/rest
      Client Certificate Issuing CA: cluster1-root-ca
      Client Certificate Serial Number: 052213E60B7088
```

## **Related Links**

- [event config modify](#)
- [security certificate show](#)

## **event notification destination delete**

Delete existing event destinations



**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

## Description

The event notification destination delete command deletes an event notification destination.

The following system-defined notification destination is configured for your use:

- snmp-traphost - This destination reflects the configuration in "system snmp traphost". To remove snmp-traphost addresses, use the system snmp traphost command.

## Parameters

### **-name <text> - Destination Name**

Use this mandatory parameter to specify the name of an event destination to be removed.

## Examples

The following shows the examples of deleting event notification destinations:

```
cluster1::> event notification destination show
Name              Type              Destination
-----
StorageAdminEmail
                  email              StorageAdmin@example.com
StorageAdminSyslog
                  syslog              example.com
snmp-traphost     snmp              10.30.40.10 (from "system snmp traphost")
3 entries were displayed.
cluster1::> event notification destination delete -name StorageAdminEmail

cluster1::> event notification destination show

Name              Type              Destination
-----
StorageAdminSyslog
                  syslog              example.com
snmp-traphost     snmp              10.30.40.10 (from "system snmp traphost")
2 entries were displayed.
cluster1::> event notification destination delete -name Storage*
cluster1::> event notification destination show
Name              Type              Destination
-----
snmp-traphost     snmp              10.30.40.10 (from "system snmp traphost")
1 entries were displayed.
```

# event notification destination modify

Modify an event notification destination

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

## Description

The `event notification destination modify` command modifies event notification destination.

The following system-defined notification destination is configured for your use:

- `snmp-traphost` - This destination reflects the configuration in "system snmp traphost". To modify traphost addresses, use the `system snmp traphost` command.

## Parameters

### **-name <text> - Destination Name**

Use this mandatory parameter to specify the name of an event notification destination to be modified. The name of the destination must already exist.

### **{ [-email <mail address>] - Email Destination**

Use this parameter to specify a new value of email address to replace the current address in the event notification destination. The parameter is specified only when the event notification destination type is already "email". It is not allowed to specify the parameter for a destination that already has another type of destination address.

### **| [-syslog <text>] - Syslog Destination**

Use this parameter to specify a new syslog server host name or IP address to replace the current address of the event notification destination. The parameter is specified only when the event notification destination type is already "syslog". It is not allowed to specify the parameter for a destination that already has another type of destination address.

### **| [-rest-api-url <text>] - REST API Server URL**

Use this parameter to specify a new REST API server URL to replace the current address of the event notification destination. Enter the full URL, which must start either with an `http://` or `https://` prefix. + To specify a URL that contains a question mark, press ESC followed by the `"?"`. + If an `https://` URL is specified, then Data ONTAP verifies the identity of the destination host by validating its certificate. If the Online Certificate Status Protocol (OCSP) is enabled for EMS, then Data ONTAP uses that protocol to determine the certificate's revocation status. Use the `security config oscp show -application ems` command to determine if the OCSP-based certificate revocation status check is enabled for EMS. The parameter is specified only when the event notification destination type is already "rest-api". It is not allowed to specify the parameter for a destination that already has another type of destination address.

### **[-certificate-authority <text>] - Client Certificate Issuing CA**

Use this parameter to specify a new value of the certificate authority (CA) to replace the current value in the event notification destination. There can be multiple client certificates installed for the admin vserver in the cluster, and this parameter, along with the `certificate-serial` parameter, uniquely identifies which one. + Use the [security certificate show](#) command to see the list of certificates installed in the cluster.

### **[-certificate-serial <text>] - Client Certificate Serial Number }**

Use this parameter to specify a new serial number of the client certificate to replace the current value in the event notification destination.

## **Examples**

The following example shows the modification of event notification destinations:

```
cluster1::> event notification destination show
```

Name	Type	Destination
-----	-----	-----
StorageAdminEmail	email	Storage@example.com
StorageAdminSyslog	syslog	example.com
snmp-traphost	snmp	10.30.40.10 (from "system snmp traphost")

3 entries were displayed.

```
cluster1::> event notification destination modify -name StorageAdminEmail  
-email StorageAdmin@example.com
```

```
cluster1::> event notification destination show
```

Name	Type	Destination
-----	-----	-----
StorageAdminEmail	email	StorageAdmin@example.com
StorageAdminSyslog	syslog	example.com
snmp-traphost	snmp	10.30.40.10 (from "system snmp traphost")

3 entries were displayed.

The following example shows how to clear the client certificate configuration when mutual authentication with the REST API server is no longer required:

```

cluster1::> event notification destination show -name RestApi -instance
Destination Name: RestApi
      Type of Destination: rest-api
      Destination Values: https://rest.example.com/rest
      Client Certificate Issuing CA: cluster1-root-ca
Client Certificate Serial Number: 052213E60B7088

cluster-1::> event notification destination modify -name RestApi
-certificate-authority - -certificate-serial -

cluster-1::> event notification destination show -name RestApi -instance
Destination Name: RestApi
      Type of Destination: rest-api
      Destination Values: https://rest.example.com/rest
      Client Certificate Issuing CA: -
Client Certificate Serial Number: -

```

## Related Links

- [security certificate show](#)

# event notification destination show

Display event notification destinations

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

## Description

The `event notification destination show` command displays event notification destinations. Note: In the case of a rest-api destination type, OSCP information is not included. It's available in [security config ocsf show -app ems](#) command.

## Parameters

**{ [-fields <fieldname>,...]**

If you specify the `-fields <fieldname>, ...` parameter, the command output also includes the specified field or fields. You can use `-fields ?` to display the fields to specify.

**| [-instance ] }**

If you specify the `-instance` parameter, the command displays detailed information about all fields.

**[-name <text>] - Destination Name**

Use this optional parameter to display information of an event notification destination that has the specified name.

### **[-type {snmp|email|syslog|rest-api}] - Type of Destination**

Use this optional parameter to display information of event notification destinations that have the specified destination type.

### **[-destination <text>,...] - Destination**

Use this optional parameter to display information of event notification destinations that have the specified destination address. Enter multiple addresses separated by a comma.

### **[-server-ca-present {true|false}] - Server CA Certificates Present?**

Use this optional parameter to display information of event notification destinations that have the specified server-ca-present value. This field indicates whether there are certificates of the server-ca type exist in the system. If not, event messages will not be sent to a rest-api type destination having an HTTPS URL.

### **[-certificate-authority <text>] - Client Certificate Issuing CA**

Use this optional parameter to display information of event notification destinations that have the specified certificate authority name.

### **[-certificate-serial <text>] - Client Certificate Serial Number**

Use this optional parameter to display information of event notification destinations that have the specified certificate serial number.

### **[-certificate-valid {true|false}] - Client Certificate Valid?**

Use this optional parameter to display information of event notification destinations that have the specified certificate-valid value. This field indicates whether the client certificate specified by the certificate-authority and certificate-serial fields is valid. If not, and if the REST API server requires client authentication, event messages will not be sent to the server.

## **Examples**

The following shows examples of "event notification destination show":

```
cluster1::> event notification destination show
```

Name	Type	Destination
-----	-----	-----
StorageAdminEmail	email	StorageAdmin@example.com
StorageAdminSyslog	syslog	example.com
snmp-traphost	snmp	10.30.40.10 (from "system snmp traphost")
RestApi	rest-api	https://rest.example.com/rest

4 entries were displayed.

```
cluster1::> event notification destination show -type snmp -instance
Destination Name: snmp-traphost
Type of Destination: snmp
Destination values: 10.30.40.10 (from "system snmp traphost")
```

## Related Links

- [security config ocsf show](#)

# event notification history show

Display latest events sent to destination

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

## Description

The `event notification history show` command displays a list of event messages that have been sent to a notification destination. Information displayed by the command for each event is identical to that of the `event log show` command. This command displays events sent to a notification destination while the `event log show` command displays all events that have been logged.

## Parameters

**{ [-fields <fieldname>,...]**

If you specify the `-fields <fieldname>, ...` parameter, the command output also includes the specified field or fields. You can use `-fields ?` to display the fields to specify.

**| [-instance ] }**

If you specify the `-instance` parameter, the command displays detailed information about all fields.

**-destination <text> - Destination**

Specifies the destination to which event messages have been sent to be displayed.

**[-node {<nodename>|local}] - Node**

Displays a list of events for the node you specify. Use this parameter with the `-seqnum` parameter to display detailed information.

**[-seqnum <Sequence Number>] - Sequence#**

Selects the events that match this parameter value. Use with the `-node` parameter to display detailed information.

**[-time <MM/DD/YYYY HH:MM:SS>] - Time**

Selects the events that match this parameter value. Use the format: `MM/DD/YYYY HH:MM:SS` [`+/- HH:MM`]. You can specify a time range by using the `".."` operator between two time statements.

**[-severity {EMERGENCY|ALERT|ERROR|NOTICE|INFORMATIONAL|DEBUG}] - Severity**

Selects the events that match this parameter value. Severity levels are as follows:

- EMERGENCY - Disruption.
- ALERT - Single point of failure.
- ERROR - Degradation.
- NOTICE - Information.

- INFORMATIONAL - Information.
- DEBUG - Debug information.

**[`-message-name` <Message Name>] - Message Name**

Selects the events that match this parameter value (string). Message names are descriptive, so filtering output by message name displays messages of a specific type.

**[`-event` <text>] - Event**

Selects the events that match this parameter value. This parameter is useful when entered with wildcards. The "event" field contains the full text of the event, including any parameters. For example, the `waf.vol.offline` event displays the name of the volume that is taken offline.

## Examples

The following example displays all the events which match "important-events" filter and forwarded to the "snmp-traphost" destination:

```
cluster1::> event filter show
```

Filter Name	Rule	Rule	Message Name	SNMP Trap Type
Severity	Position	Type		
-----				
default-trap-events				
	1	include	*	*
EMERGENCY, ALERT				
	2	include	*	Standard, Built-in
				*
	3	exclude	*	*
				*
important-events				
	1	include	*	*
EMERGENCY, ALERT				
	2	include	callhome.*	*
ERROR				
	3	exclude	*	*
				*
no-info-debug-events				
	1	include	*	*
EMERGENCY, ALERT, ERROR, NOTICE				
	2	exclude	*	*
				*

8 entries were displayed.

```
cluster1::> event notification destination show
```

Name	Type	Destination
-----	-----	-----
snmp-traphost	snmp	192.168.10.40 (from "system snmp traphost")

```
cluster1::> event notification show
```

ID	Filter Name	Destinations
-----	-----	-----
1	important-events	snmp-traphost

```
cluster1::>event notification history show -destination snmp-traphost
```

Time	Node	Severity	Event
-----	-----	-----	-----
5/14/2015 03:02:09	node1	EMERGENCY	callhome.clam.node.oog:
Call home for NODE(S) OUT OF CLUSTER QUORUM.			
5/13/2015 12:05:45	node1	ALERT	od.rdb.mbox.read.error:
message="RDB-HA readPSlot: Failed to read blob_type 19, (pslot 16),			
instance 1: 1 (1)."			

2 entries were displayed.



## Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.