



event status commands

ONTAP 9.7 commands

NetApp
December 14, 2022

Table of Contents

- event status commands 1
- event status show 1

event status commands

event status show

Display event status

Availability: This command is available to *cluster* administrators at the *admin* privilege level.

Description

The `event status show` command summarizes information about occurrences of events. For detailed information about specific occurrences of events, use the [event log show](#) command.

Parameters

{ [-fields <fieldname>,...]

If you specify the `-fields <fieldname>, ...` parameter, the command output also includes the specified field or fields. You can use `'-fields ?'` to display the fields to specify.

| [-instance] }

If you specify the `-instance` parameter, the command displays detailed information about all fields.

[-node {<nodename>|local}] - Node

Selects the event records that match this parameter value. Events are tracked on a node-by-node basis, rather than being rolled up cluster-wide.

[-message-name <Message Name>] - Message Name

Selects the event records that match this parameter value. The message name is a short descriptive string. Filtering output by message name displays messages of a specific type.

[-indications <integer>] - Number of Indications

Selects the event records that match this parameter value. This parameter is most useful when used with a range, such as using the range `">20"` to display only events that have been posted more than 20 times.

[-drops <integer>] - Number of Drops

Selects the event records that match this parameter value.

[-last-time-occurred <MM/DD/YYYY HH:MM:SS>] - Last Indication Time

Selects the event records that match this parameter value.

[-last-time-dropped <MM/DD/YYYY HH:MM:SS>] - Last Suppressed Indication Time

Selects the event records that match this parameter value.

[-last-time-processed <MM/DD/YYYY HH:MM:SS>] - Last Processed Indication Time

Selects the event records that match this parameter value.

[-stat-starting-time <MM/DD/YYYY HH:MM:SS>] - Stat Starting Time

Selects the event records that match this parameter value.

[`-last-hour-histogram <integer>,...`] - 60-minute Histogram

Use this parameter with the `-fields` parameter to display the "last hour" histogram for each event type. The last hour histogram records the number of times each event occurred in the last hour. The histogram is divided into sixty buckets, and each bucket collects one minute's events. The buckets display with the most recent event first.

[`-last-day-histogram <integer>,...`] - 24-hour Histogram

Use this parameter with the `-fields` parameter to display the "last day" histogram for each event type. The last day histogram records the number of times each event occurred in the last day. The histogram is divided into 24 buckets, and each bucket collects one hour's events. The buckets display with the most recent event first.

[`-last-week-histogram <integer>,...`] - 7-day Histogram

Use this parameter with the `-fields` parameter to display the "last week" histogram for each event type. The last week histogram records the number of times each event occurred in the last week. The histogram is divided into 7 buckets, and each bucket collects one day's events. The buckets display with the most recent event first.

[`-severity`

{`NODE_FAULT|SVC_FAULT|NODE_ERROR|SVC_ERROR|WARNING|NOTICE|INFO|DEBUG|VAR`}] -

Severity

Selects events that have the event severity you specify. Severity levels sort with the most severe levels first. Severity levels:

- `NODE_FAULT` - The node has detected data corruption, or is unable to provide client service.
- `SVC_FAULT` - The node has detected a temporary loss of service. Typically, this is caused by a transient software fault.
- `NODE_ERROR` - The node has detected a hardware error that is not immediately fatal.
- `SVC_ERROR` - The node has detected a software error that is not immediately fatal.
- `WARNING` - A high-priority message that does not indicate a fault.
- `NOTICE` - A normal-priority message that does not indicate a fault.
- `INFO` - A low-priority message that does not indicate a fault.
- `DEBUG` - A debugging message. These messages are typically suppressed.
- `VAR` - These messages have variable severity. Severity level for these messages is selected at runtime.

The examples below illustrate how to query on severity.

Examples

The following example displays recent event-occurrence status for node1:

```

cluster1::> event status show -node node1
Node           Message                                           Occurs Drops Last Time
-----
node1          raid.spares.media_scrub.start                    6      0    3/11/2010
15:59:00
node1          raid.uninitialized.parity.vol                    3      0    3/11/2010
15:58:28
node1          raid.vol.state.online                           3      0    3/11/2010
15:58:29
node1          reg.defaultCommit.set.timeTaken                 1      0    3/11/2010
15:58:28
node1          scsitgt.ha.state.changed                        2      0    3/11/2010
15:58:28
node1          ses.multipath.notSupported                      2      0    3/11/2010
15:58:43
node1          shelf.config.mpha                               1      0    3/11/2010
15:58:48
node1          sk.hog.runtime                                  1      0    3/11/2010
15:58:28
node1          snmp.agent.msg.access.denied                    1      0    3/11/2010
15:58:28
node1          snmp.link.up                                    6      0    3/11/2010
15:58:28
node1          tar.csum.mismatch                              2      0    3/11/2010
15:58:28
node1          tar.extract.success                             2      0    3/11/2010
15:58:28
node1          vifmgr.lifsuccessfullymoved                     3      0    3/11/2010
15:58:46
node1          vifmgr.portdown                                 1      0    3/11/2010
15:58:48
node1          vifmgr.portup                                   5      0    3/11/2010
15:58:48
node1          vifmgr.startedsuccessfully                       1      0    3/11/2010
15:58:43

```

The following example displays a summary of events which are warnings or more severe:

```

cluster1::> event status show -node node1 -severity <=warning -fields
indications,drops,severity
node      message-name                indications  drops  severity
-----  -
node1     api.output.invalidSchema    5463        840   WARNING
node1     callhome.dsk.config         1           0     WARNING
node1     callhome.sys.config         1           0     SVC_ERROR
node1     cecc_log.dropped            145         0     WARNING
node1     cecc_log.entry              5           0     WARNING
node1     cecc_log.entry_no_syslog    4540        218   WARNING
node1     cecc_log.summary            5           0     WARNING
node1     cf.fm.noPartnerVariable     5469        839   WARNING
node1     cf.fm.notkoverBadMbox       1           0     WARNING
node1     cf.fm.notkoverClusterDisable 1           0     WARNING
node1     cf.fsm.backupMailboxError   1           0     WARNING
node1     cf.takeover.disabled        23          0     WARNING
node1     cmds.sysconf.logErr         1           0     NODE_ERROR
node1     config.noPartnerDisks       1           0     NODE_ERROR
node1     fci.initialization.failed   2           0     NODE_ERROR
node1     fcp.service.adapter         1           0     WARNING
node1     fmb.BlobNotFound            1           0     WARNING
node1     ha.takeoverImpNotDef        1           0     WARNING
node1     httpd.config.mime.missing   2           0     WARNING
node1     mgr.opsmgr.autoreg.norec    1           0     WARNING
node1     monitor.globalStatus.critical 1           0     NODE_ERROR
node1     raid.mirror.vote.versionZero 1           0     SVC_ERROR
node1     ses.multipath.notSupported   2           0     NODE_ERROR
node1     snmp.agent.msg.access.denied 1           0     WARNING
24 entries were displayed.

```

The above example makes use of several features which are common to all `show` commands:

- A query is specified for the severity parameter. A query restricts the output of the show command; only rows matching the query will be displayed. In this case, the query indicates that only events which have a severity of "WARNING" or more severe will be displayed.
- The fields parameter selects the fields to display. Note that the severity field is not displayed in the default output.

Related Links

- [event log show](#)

Copyright information

Copyright © 2022 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.