



# **event catalog commands**

## ONTAP 9.8 commands

NetApp  
September 27, 2022

# Table of Contents

- event catalog commands ..... 1
- event catalog show ..... 1

# event catalog commands

## event catalog show

Display event definitions

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

### Description

The `event catalog show` command displays information about events in the catalog. By default, this command displays the following information:

- Message name of the event
- Severity of the event
- SNMP trap type of the event

To display detailed information about a specific event, run the command with the `-message-name` parameter, and specify the name of the event. The detailed view adds the following information:

- Full description of the event
- Action to be taken to address the event
- Event's deprecation status

You can specify additional parameters to limit output to the information that matches those parameters. For example, to display information only about events with an event name that begins with *raid*, enter the command with the `-message-name`raid*` parameter. The parameter value can either be a specific text string or a wildcard pattern.

Alternatively, an event filter can also be specified to limit the output events.

### Parameters

**{ [-fields <fieldname>,...]**

If you specify the `-fields <fieldname>, ...` parameter, the command output also includes the specified field or fields. You can use `'-fields ?'` to display the fields to specify.

**| [-instance ] }**

If you specify the `-instance` parameter, the command displays detailed information about all fields.

**[-message-name <Message Name>] - Message Name**

Selects the events that match this parameter value.

**[-filter-name <text>] - Filter Name**

Selects the events that match this parameter value. The parameter value indicates an existing filter name that, when applied permits the inclusion of the listed events.

**[`-severity {EMERGENCY|ALERT|ERROR|NOTICE|INFORMATIONAL|DEBUG}`] - Severity**

Selects the events that match this parameter value.

**[`-description <text>`] - Description**

Selects the events that match this parameter value.

**[`-action <text>`] - Corrective Action**

Selects the events that match this parameter value.

**[`-snmp-trap-type {Standard|Built-in|Severity-based}`] - SNMP Trap Type**

Selects the events that match this parameter value. The parameter value describes the type of SNMP trap associated with the event. The value can be one of the following: *Standard* trap type events are those defined in the RFCs. *Built-in* trap types are those that are NetApp Enterprise traps specific to events. The remaining events are considered to have *Severity-based* SNMP trap types.

**[`-deprecated {true|false}`] - Is Deprecated**

Selects the events that match this parameter value. The parameter value indicates whether the event is deprecated or not.



Deprecated events may be removed in a future release of Data ONTAP.

## Examples

The following example displays the event catalog:

```
cluster1::> event filter show -filter-name filter1
Filter Name Rule      Rule      Message Name      SNMP Trap Type
Severity
          Position Type
-----
filter1
          1      include  zapi.*            *              *
          2      exclude  *                  *              *
2 entries were displayed.

cluster1::> event catalog show -filter-name filter1
Message              Severity      SNMP Trap Type
-----
zapi.killed          NOTICE      Severity-based
zapi.method.notfound NOTICE      Severity-based
zapi.sf.up.ready     INFORMATIONAL Severity-based
zapi.snapshot.success NOTICE      Severity-based
zapi.streamout.noMethod NOTICE      Severity-based
5 entries were displayed.

cluster1::> event catalog show -message-name zsm.* -filter-name filter1
```

There are no entries matching your query.

```
cluster1::> event catalog show -message-name zapi.* -filter-name filter1
```

Message	Severity	SNMP Trap Type
-----	-----	-----
zapi.method.notfound	NOTICE	Severity-based
zapi.sf.up.ready	INFORMATIONAL	Severity-based
zapi.snapshot.success	NOTICE	Severity-based
zapi.streamout.noMethod	NOTICE	Severity-based

4 entries were displayed.

```
cluster1::> event catalog show -message-name CR.*
```

Message	Severity	SNMP Trap Type
-----	-----	-----
CR.Corrupt.Redir.Deleted	INFORMATIONAL	Severity-based
CR.Dangling.Redir.Deleted	INFORMATIONAL	Severity-based
CR.Data.File.Inaccessible	NOTICE	Severity-based
CR.Del.Corrupt.Redir.Failed	NOTICE	Severity-based
CR.Del.CrptStreamData.Fail	NOTICE	Severity-based
CR.Del.CrptStreamRedir.Fail	NOTICE	Severity-based
CR.Del.DangStreamData.Fail	NOTICE	Severity-based
CR.Del.DangStreamRedir.Fail	NOTICE	Severity-based
CR.Del.Dangling.Redir.Failed	NOTICE	Severity-based
CR.Fix.Corrupt.Redir.Failed	NOTICE	Severity-based
CR.Fix.Crpt.Data.Dir.Failed	INFORMATIONAL	Severity-based
CR.Fix.Crpt.Data.File.Failed	NOTICE	Severity-based
CR.Fix.CrptStreamRedir.Fail	NOTICE	Severity-based
CR.Fix.Dang.Data.File.Failed	NOTICE	Severity-based
CR.Fix.Nlinks.Failed	NOTICE	Severity-based
CR.Fix.TempFiles.Failed	INFORMATIONAL	Severity-based
CR.Max.Session.Exceed	INFORMATIONAL	Severity-based
CR.RDB.Counters.Not.Updated	INFORMATIONAL	Severity-based
CR.RDB.State.Not.Updated	NOTICE	Severity-based
CR.Redir.File.Inaccessible	NOTICE	Severity-based
CR.Snapshot.Not.Deleted	NOTICE	Severity-based

Message	Severity	SNMP Trap Type
-----	-----	-----
CR.Sync.ACL.Fail	NOTICE	Severity-based

22 entries were displayed.

```
cluster1::> event catalog show -instance
```

...  
...

```
Message Name: Nblade.cifsEncSessAccessDenied  
Severity: ERROR
```

Description: This message occurs when a client not capable of SMB encryption tries to establish a CIFS session that requires SMB encryption.  
Corrective Action: Either ensure that the client is capable of SMB encryption or disable SMB encryption on the Vserver.

SNMP Trap Type: Severity-based

Is Deprecated: false

Message Name: Nblade.cifsEncShrAccessDenied

Severity: ERROR

Description: This message occurs when a client not capable of SMB encryption tries to connect to a CIFS share that requires SMB encryption.  
Corrective Action: Either ensure that the client is capable of SMB encryption or disable SMB encryption on the CIFS share.

SNMP Trap Type: Severity-based

Is Deprecated: false

...

...

## Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.