



# **security certificate commands**

## **ONTAP 9.8 commands**

NetApp  
September 27, 2022

# Table of Contents

- security certificate commands ..... 1
  - security certificate create ..... 1
  - security certificate delete ..... 3
  - security certificate generate-csr ..... 5
  - security certificate install ..... 9
  - security certificate print ..... 12
  - security certificate rename ..... 15
  - security certificate show-generated ..... 16
  - security certificate show-truststore ..... 19
  - security certificate show-user-installed ..... 23
  - security certificate show ..... 26
  - security certificate sign ..... 30
  - security certificate ca-issued revoke ..... 34
  - security certificate ca-issued show ..... 34
  - security certificate config modify ..... 37
  - security certificate config show ..... 38
  - security certificate truststore check ..... 38
  - security certificate truststore clear ..... 39
  - security certificate truststore load ..... 40

# security certificate commands

## security certificate create

Create and Install a Self-Signed Digital Certificate

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

### Description

The `security certificate create` command creates and installs a self-signed digital certificate, which can be used for server authentication, for signing other certificates by acting as a certificate authority (CA), or for Data ONTAP as an SSL client. The certificate function is selected by the `-type` field. Self-signed digital certificates are not as secure as certificates signed by a CA. Therefore, they are not recommended in a production environment.

### Parameters

**-vserver <Vserver Name> - Name of Vserver**

This specifies the name of the Vserver on which the certificate will exist.

**-common-name <FQDN or Custom Common Name> - FQDN or Custom Common Name**

This specifies the desired certificate name as a fully qualified domain name (FQDN) or custom common name or the name of a person. The supported characters, which are a subset of the ASCII character set, are as follows:

- Letters a through z, A through Z
- Numbers 0 through 9
- Asterisk (\*), period (.), underscore (\_) and hyphen (-)

The common name must not start or end with a "-" or ".". The maximum length is 253 characters.

**-type <type of certificate> - Type of Certificate**

This specifies the certificate type. Valid values are the following:

- *server* - creates and installs a self-signed digital certificate and intermediate certificates to be used for server authentication
- *root-ca* - creates and installs a self-signed digital certificate to sign other certificates by acting as a certificate authority (CA)
- *client* - includes a self-signed digital certificate and private key to be used for Data ONTAP as an SSL client

**[-subtype <kmip-cert>] - (DEPRECATED)-Certificate Subtype**



This parameter has been deprecated in ONTAP 9.6 and may be removed in a future release of Data ONTAP.

This specifies a certificate subtype. This optional parameter can have an empty value (the default). The only valid value is as follows:

- *kmip-cert* - this is a Key Management Interoperability Protocol (KMIP) certificate

**[-cert-name <text>] - Unique Certificate Name**

This specifies the system's internal identifier for the certificate. It must be unique within a Vserver. If not provided, it is automatically generated by the system.

**-size <size of requested certificate in bits> - Size of Requested Certificate in Bits**

This specifies the number of bits in the private key. The larger the value, the more secure is the key. The default is 2048. Possible values include *512*, *1024*, *1536*, *2048* and *3072* when the "FIPS Mode" in "security config" is false. When the "FIPS Mode" is true, the possible values are *2048* and *3072*.

**-country <text> - Country Name**

This specifies the country where the Vserver resides. The country name is a two-letter code. The default is US. Here is the list of country codes:

[Country Codes](#)

**-state <text> - State or Province Name**

This specifies the state or province where the Vserver resides.

**-locality <text> - Locality Name**

This specifies the locality where the Vserver resides. For example, the name of a city.

**-organization <text> - Organization Name**

This specifies the organization where the Vserver resides. For example, the name of a company.

**-unit <text> - Organization Unit**

This specifies the unit where the Vserver resides. For example, the name of a section or a department within a company.

**-email-addr <mail address> - Contact Administrator's Email Address**

This specifies the email address of the contact administrator for the Vserver.

**-expire-days <integer> - Number of Days until Expiration**

This specifies the number of days until the certificate expires. The default value is 365 days. Possible values are between *1* and *3652*.

**-protocol <protocol> - Protocol**

This specifies the protocol type. This parameter currently supports only the SSL protocol type. The default is SSL.

**-hash-function <hashing function> - Hashing Function**

This specifies the cryptographic hashing function for signing the certificate. The default is SHA256. Possible values include *SHA1*, *SHA256*, *MD5*, *SHA224*, *SHA384* and *SHA512* when the "FIPS Mode" in "security config" is false. When the "FIPS Mode" is true, the possible values are *SHA224*, *SHA256*, *SHA384* and *SHA512*.

## Examples

This example creates a server type, self-signed digital certificate for a Vserver named vs0 at a company whose custom common name is *www.example.com* and whose Vserver name is vs0.

```
cluster1::> security certificate create -vserver vs0 \-common-  
name``_www.example.com_``-type` server
```

This example creates a root-ca type, self-signed digital certificate with a 2048-bit private key generated by the SHA256 hashing function that will expire in 365 days for a Vserver named vs0 for use by the Software group in IT at a company whose custom common name is *www.example.com*, located in Sunnyvale, California, USA. The email address of the contact administrator who manages the Vserver is *web@example.com*.

```
cluster1::> security certificate create -vserver vs0 \-common-  
name``_www.example.com_``-type` root-ca \-size` 2048 \-country` US \-  
state` California \-locality` Sunnyvale \-organization` IT \-unit`  
Software \-email-addr``_web@example.com_``-expire-days` 365 \-hash-  
function` SHA256
```

This example creates a client type of self-signed digital certificate for a Vserver named vs0 at a company that uses Data ONTAP as an SSL client. The company's custom common name is *www.example.com* and its Vserver name is vs0.

```
cluster1::> security certificate create -vserver vs0 \-common-  
name``_www.example.com_``-type` client \-size` 2048 \-country` US \-  
state` California \-locality` Sunnyvale \-organization` IT \-unit`  
Software \-email-addr``_web@example.com_``-expire-days` 365 \-hash-  
function` SHA256
```

## security certificate delete

Delete an Installed Digital Certificate

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

### Description

This command deletes an installed digital security certificate.

### Parameters

**-vserver <Vserver Name>** - Name of Vserver

This specifies the Vserver that contains the certificate.

### **-common-name <FQDN or Custom Common Name> - FQDN or Custom Common Name**

This specifies the desired certificate name as a fully qualified domain name (FQDN) or custom common name or the name of a person. The supported characters, which are a subset of the ASCII character set, are as follows:

- Letters a through z, A through Z
- Numbers 0 through 9
- Asterisk (\*), period (.), underscore (\_) and hyphen (-)

The common name must not start or end with a "-" or a ".". The maximum length is 253 characters.

### **[-serial <text>] - Serial Number of Certificate**

This specifies the certificate serial number.

### **-ca <text> - Certificate Authority**

This specifies the certificate authority (CA).

### **-type <type of certificate> - Type of Certificate**

This specifies the certificate type. Valid values are the following:

- *server* - includes server certificates and intermediate certificates
- *root-ca* - includes a self-signed digital certificate to sign other certificates by acting as a certificate authority (CA)
- *client-ca* - includes the public key certificate for the root CA of the SSL client. If this *client-ca* certificate is created as part of a *root-ca*, it will be deleted along with the corresponding deletion of the *root-ca*.
- *server-ca* - includes the public key certificate for the root CA of the SSL server to which Data ONTAP is a client. If this *server-ca* certificate is created as part of a *root-ca*, it will be deleted along with the corresponding deletion of the *root-ca*.
- *client* - includes a public key certificate and private key to be used for Data ONTAP as an SSL client

### **[-subtype <kmip-cert>] - (DEPRECATED)-Certificate Subtype**



This parameter has been deprecated in ONTAP 9.6 and may be removed in a future release of Data ONTAP.

This specifies a certificate subtype. This optional parameter can have an empty value (the default). The only valid value is as follows:

- *kmip-cert* - this is a Key Management Interoperability Protocol (KMIP) certificate

### **[-cert-name <text>] - Unique Certificate Name**

This specifies the system's internal identifier for the certificate. It is unique within a Vserver.

## **Examples**

This example deletes a *root-ca* type digital certificate for a Vserver named *vs0* in a company named

`www.example.com` with serial number 4F57D3D1.

```
cluster1::> security certificate delete -vserver vs0 -common-  
name``_www.example.com_``-ca``_www.example.com_``-type` root-ca -  
serial` 4F57D3D1
```

## security certificate generate-csr

### Generate a Digital Certificate Signing Request

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

### Description

This command generates a digital certificate signing request and displays it on the console. A certificate signing request (CSR or certification request) is a message sent to a certificate authority (CA) to apply for a digital identity certificate.

### Parameters

#### **[`-common-name <text>`] - FQDN or Custom Common Name**

This specifies the desired certificate name as a fully qualified domain name (FQDN) or custom common name or the name of a person. The supported characters, which are a subset of the ASCII character set, are as follows:

- Letters a through z, A through Z
- Numbers 0 through 9
- Asterisk (\*), period (.), underscore (\_) and hyphen (-)

The common name must not start or end with a "-" or a ".". The maximum length is 253 characters.

#### **{ [`-size <size of requested certificate in bits>`] - (DEPRECATED)-Size of Requested Certificate in Bits }**

This specifies the number of bits in the private key. A larger size value provides for a more secure key. The default is 2048. Possible values include *512*, *1024*, *1536*, and *2048*.



This parameter has been deprecated in ONTAP 9.8 and may be removed in future releases of Data ONTAP. Use the `security-strength` parameter instead.

#### **[`-security-strength <bits of security strength>`] - Security Strength in Bits }**

Use this parameter to specify the minimum security strength of the certificate in bits. The security bits mapping to RSA and ECDSA key length, in bits, are as follows:

Size	RSA Key Length	Elliptic Curve Key Length
112	2048	224
128	3072	256
192	4096	384

Note: FIPS supported values are restricted to 112 and 128.

**[`-algorithm <Asymmetric key generation algorithm>`] - Asymmetric Encryption Algorithm**

Use this parameter to specify the asymmetric encryption algorithm to use for generating the public/private key for the certificate signing request. Algorithm values can be RSA or EC. Default value is RSA.

**[`-country <text>`] - Country Name**

This specifies the country where the Vserver resides. The country name is a two-letter code. The default is US. Here is the list of country codes:

[Country Codes](#)

**[`-state <text>`] - State or Province Name**

This specifies the state or province where the Vserver resides.

**[`-locality <text>`] - Locality Name**

This specifies the locality where the Vserver resides. For example, the name of a city.

**[`-organization <text>`] - Organization Name**

This specifies the organization where the Vserver resides. For example, the name of a company.

**[`-unit <text>`] - Organization Unit**

This specifies the unit where the Vserver resides. For example, the name of a section or a department within a company.

**[`-email-addr <mail address>`] - Contact Administrator's Email Address**

This specifies the email address of the contact administrator for the Vserver.

**[`-hash-function <hashing function>`] - Hashing Function**

This specifies the cryptographic hashing function for signing the certificate. The default is SHA256. Possible values include *SHA1* , *SHA256* and *MD5* .

**[`-key-usage <Certificate key usage extension>,...`] - Key Usage Extension**

Use this parameter to specify the key usage extension values. The default values are: *digitalSignature* , *keyEncipherment* . Possible values include:

- *digitalSignature*
- *nonRepudiation*
- *keyEncipherment*
- *dataEncipherment*
- *keyAgreement*



- keyCertSigning
- cRLSigning
- encipherOnly
- decipherOnly

**[-extended-key-usage <Certificate extKeyUsage extension>,...] - Extended Key Usage Extension**

Use this parameter to specify the extended key usage extension values. The default values are: *serverAuth*, *clientAuth*. Possible values include:

- serverAuth
- clientAuth
- codeSigning
- emailProtection
- timeStamping
- OCSPSigning

**[-rfc822-name <mail address>,...] - Email Address SAN**

Use this parameter to specify the Subject Alternate Name extension - a list of rfc822-names (email addresses).

**[-uri <text>,...] - URI SAN**

Use this parameter to specify the Subject Alternate Name extension - a list of URIs.

**[-dns-name <text>,...] - DNS Name SAN**

Use this parameter to specify the Subject Alternate Name extension - a list of DNS names.

**[-ipaddr <IP Address>,...] - IP Address SAN**

Use this parameter to specify the Subject Alternate Name extension - a list of IP addresses.

## Examples

This example creates a certificate-signing request with a 2048-bit RSA private key generated by the SHA256 hashing function for use by the Engineering group in IT at a company whose custom common name is *www.example.com*, located in Durham, NC, USA. The email address of the contact administrator who manages the Vserver is *web@example.com*. The request also specifies the subject alternative names, key-usage and extended-key-usage extensions.

```
cluster-1::> security certificate generate-csr -common-
name``_www.example.com_``-algorithm``_RSA_``-hash-
function``_SHA256_``-security-strength``_128_``-key-
usage``_critical,digitalSignature,keyEncipherment_``-extended-key-
usage``_serverAuth,clientAuth_``-country``_US_``-state``_NC_``-
locality``_Durham_``-organization``_IT_``-unit``_Engineering_``-
email-addr``_web@example.com_``-rfc822-name``_example@example.com_``-
dns-name``_shop.example.com_``,``_store.example.com_``
```

Certificate Signing Request :

-----BEGIN CERTIFICATE REQUEST-----

```
MIIEWDCCAsACAQAwwYgXGDAWBgNVBAMTD3d3dy5leGFtcGxlLmNvbTELMaKGA1UE
BhMCMVVMxXcZAJBgNVBAGTAk5DMQ8wDQYDVQQHEwZEdXJoYW0xCzAJBgNVBAoTAKlU
MRQwEgYDVQQLLEwtFbmdpbmVlcm1uZzEeMBwGCSqGSIb3DQEJARYPd2ViQGV4YW1w
bGUuY29tMIIBojANBgkqhkiG9w0BAQEFAAOCAy8AMIIBigKAYEAuo86Jg/szhws
ykYiEXvRaf/j2jJArJMoZby9Z/yINSowe30Xbn5wnfvwiwICUCPwD1e3jhK3TrWH
rNRn/+MqE+jQA7yAdufYxD537cDcT46ihkajISe0Ei93yf6IKmvUAvmJvQ3R7Z4E
QCOWHj56yQ+LXj36bYdwa74S8u8lpCs3Ywx8fgrh/v6H0rnlKDQSQUFR35u7ZZym
tRA7EJMY62f9ALgcFNhQPuP6pjC8aP7Tv7BKXAninryDDcoMdW8UczfTPgzCDh5z
S++eNP3s/7cGfRSQ8aXnDTVQLYpusrdDgVwZXXgu+ZPoZuCF2AYBT+/rdq3VkgWu
QM+mGRMB5300ff4QOi+SVcXSWXq32wzciv1KsW/iB9h2T+kVd/8Z7ESeYLqFhxY+
0nwacskMRGxOuTLgx+XH+/EntjrI4rjF9/ShYCIcy8vqp10xFaPCLU96ebnbiEOu
y6RvCJ2egcM6OerBHWB5fIJ0ZZ3crdjz/d1z4ktBuG7E4cUYkEvvAgMBAAGggYkw
gYYGCSqGSIb3DQEJdJf5MHcwRgYDVR0RAQH/BDwwOoETZXhbbXBsZUBleGFtcGxl
LmNvbYIQC2hvcC5leGFtcGxlLmNvbYIRc3RvcuUuZXhbbXBsZS5jb20wDgYDVR0P
AQH/BAQDAgWgMB0GA1UdJQQWMBQGCCsGAQUFBwMCMCBggrBgEFBQcDATANBgkqhkiG
9w0BAQsFAAOCAyEAh0kOsRy5cCTnFRIWBhBrFFvQhpZIlsoeelNW6Jlke0/ULcAj
JevBx8UibY48D2Wn0nEGle9T3ZeDlgn66xr/OUfsrENm5ORy5Ndvubkkz0t4KF5
Z2SnwPVIcX2b6ID2xhFAny2S58Adwo7uTpLytidqFj026/KcuyVZUEF9HuJcQGE8
+LMfliCkm6rI2h1ncy2sV6vtDo9GlVscTYLghisHp1aTXVPr6Q+1OM81Tot8i71
DmZ7kRyxCDlu20XxxV+p2cm4QQVHXbw0XrKAOL2jCBBiYOSWM/BvwWiliVGD6NLg
WK7ZpyHSFjDH0pUlqJCIs079W6JDhiYvtB2xizqmg8oyABUESMUckHGeymr92mcO
JbSyeTE66Pek+Gwia6ZMG7jcznfSr31+7dShLix9kjGsKUffHTiZVySaYjny/+Aq
Seg3Fpusq25ki9D/NMnbifXraL+LbX/WNLS3nA79rp3+VcOoGBponT4ilfsxn+Bv
5RTT3nhT8BlcTelD
```

-----END CERTIFICATE REQUEST-----

Private Key :

-----BEGIN PRIVATE KEY-----

```
MIIG/AIBADANBgkqhkiG9w0BAQEFAASCBUywggbIAgEAAoIBgQC6jzomD+zOHCzK
RiIRe9Fp/+PamKcSskyhlvL1n/Ig2yjb7fRdufnCd+/CLAgJQI/APV7eOErdOtYes
1Gf/4yoT6NADvIB259jEPnftwNxpjqKGRqMhJ7QSL3fJ/ogqa9QC+Ym9DdHtngRA
I5YePnrJD4tePfpth3BrvhLy7yWkKzdjDHx+CuH+/ofSueUoNBjC4VHfm7tlnKa1
EDsQkxjrZ/0AuBwU2FA+4/qmNzxo/tO/sEpcCeKevIMNygx1bxRzN9M+DMIOhNL
7540/ez/twZ9FJDxpecNNVAtim6yt00BXBldeC75k+hm4J/YBgFP7+t2rdWSBa5A
z6YZEwHnc7R9/hA6L5JVxdJZerfbDNyK/Uqxb+IH2HZP6RV3/xnsRJ5guoXGFj7S
fBpyyQxEbE65MuDH5cf78Se20sjiuMX39KfGihzLy+qnU7EVo8KW73p5uduIQ67L
pG8InZ6Bwzo55FsdYHl8gnRlndyt2PP93XPiS0G4bsThxRiQS+8CAwEAAQKCAyBW
fqtWFFIVaWi2y3dmJcL840AP3PaxTHURXkVund3FkU6TIncngQwqKbHnsSHDaDYX
lvJqc3D7lBx4W+5v7DGJE4rGALKK7olIyzGtUJqUZCwkF0Hw0EijmdBvHYyiJmYg
jvN2bJ7lDTsprZaHJS6mY4eZRSEDgST1PyXn7krEZ6kBSju58G/BWt88KyX80s+Y
pIDiLiDg5pVAI2tPDvQhyI+7sqCKZzQm5GpEgB2JDIS+PgzyUWBlSMplICcPcgx
rarFZQilNe7qrp6FfKvPAO5XLyI0xhgm8fCMJUpxmEb80XY4FeRDzB42a0Z/YL0P
HhpWAI4ZRsDyDd5S7jwLZQ3Hl9WsKvj2/FRU6hWTP+maH/Vel35iLkygfZWUAjNY
F6B0SoBBd9bVeKDODXrD/CwVbuaKZGMAVoEnZbczmFUVSi4HZGyqVRxX6WIxVoD0
```

```
MZXwWUoWZ32C6II3vp/ReAsouhCnKDKhqfrvH58xF82FTMMXBZ/kDy7k5IySylkC
gcEA4tpiVleKzC/ft0sPUNmZB/snHfXC+xohzTygCg4L1Rf8zjDnUT/o9D8SRe1/
crkG7ZcjKvIdPz0tatyjyNMsZ9TDISiAJQJ8Et1+jBP0uy2qG+ab+Ub761BR5TX0
078UcmtEyxaaDZsESWj+qYerG4E7zGZiTscTe2Jma5fPlS1ekyfNzk1GBtya9bIM
r991o/PahSmCz5iPxf4avYM/vQm2p+wIk+o6ZhJIAU1RfRcV8y91YivQjw+tZA+G
bdE7AoHBANKHg0Jb5BLJmN/5/PLkkELhaZG+UNUngtm46dm/84+sqtDtcUHPqdHv
M/skRYDVERmI50QZ2HmzVC8J+zzs9r01VNNA+Tzcoi3eB3FPdDYPTDtLSzRfsC82
kix8d2uVs+rfmvKwT0XucNvMqjUyYDII7IjlnliIjP2XQZaNleggyi65kni+6FrQ
EJ9gVD4PtCkX7rKo8csMITe6n+HZIZfPoY6BX0HU/4VGa+RQHGFgIdfKDOJ5AtyG
RPYVvZ1E3QKBwE520sT7FpsBhBPV9no0iWX1TOZj9wj7RO3EJmbT7OvL3D1FWP0V
afHxTtS5DPgVX3wWZqeYDt2sv2TS5CO2Rwmy4bs6Uvh6H4g27GpvDJshdFEqNpDG
KKR/p5PsUYnI0b2xtJ26N5a1I4pwsoty1CozTQep8h7lZKusoVhdrGMfKjMj9V+C
AtKkw0RwTUsXs4z973tXnFNjPzEKDx21o/oyvebfESh4P7LGZ/lp7o421uU6Y4rN
NNogxiZx6EFbuQKBwGbltJTTmXCHKzZQ6NS6gJOUR9CX/QFLAamHUIfUY3JUU59
RyNZNnvl1luyVWHYKFZgnBSLzkF2yFeDtzmDvmObZAUXh9wpG+Prs5SngqYxSBb3
6Av14XDcY7nnOOTGn6jDcMSqRLsv99nLvlR9ea1U4C+38XvoV3rB/dvG3PpJcxAn
uxbMmWamjEdWYSxAvMcIEZ0Zk5+DF8E/loxQW7fn2pv0HhBmMjLgtRQx7fzaKXJW
Db6UOkp2IbxL11+w3QKBwDl0DgwB7ukGyFHf3Rky3YX0en1WGBesXONf1m2fjwOU
nojccfaGwAUdb6m60JuZfHJ3qZ4ecoloy4GxIKV5krvBg1buow/aqDDkKmVvYNO6
FUuXp+BbTBSxjfftSaog7y5Db5aecLXU5FLE+sVlrbp17s9h8Ur+O04SytSVh9JS
SkzHYv+4GybZqmOeF2U+whib8JXD2bJkSfNI1dZzhKVqoTUQfEAE3VFY0EHkVQwk
rLHmjspSujKc4BKfVRGWJg==
-----END PRIVATE KEY-----
```

Note: Please keep a copy of your certificate request and private key for future reference.

## security certificate install

### Install a Digital Certificate

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

### Description

The `security certificate install` command installs digital security certificates signed by a certificate authority (CA) and the public key certificate of the root CA. Digital security certificates also include the intermediate certificates to construct the chain for server certificates (the `server` type), client-side root CA certificates (the `client-ca` type), or server-side root CA certificates (the `server-ca` type). With FIPS enabled, the following restrictions apply to the certificate getting installed. `server/client/server-ca/client-ca`: Key size  $\geq$  2048, `server/client`: Hash function (No MD-5, No SHA-1), `server-ca/client-ca`: (Intermediate CA), Hash Function (No MD-5, No SHA-1), `server-ca/client-ca`: (Root CA), Hash Function (No MD-5)

### Parameters

### **-vserver <Vserver Name> - Name of Vserver**

This specifies the Vserver that contains the certificate.

### **-type <type of certificate> - Type of Certificate**

This specifies the certificate type. Valid values are the following:

- *server* - includes server certificates and intermediate certificates.
- *client-ca* - includes the public key certificate for the root CA of the SSL client
- *server-ca* - includes the public key certificate for the root CA of the SSL server to which Data ONTAP is a client
- *client* - includes a self-signed or CA-signed digital certificate and private key to be used for Data ONTAP as an SSL client

### **[-subtype <kmip-cert>] - (DEPRECATED)-Certificate Subtype**



This parameter has been deprecated in ONTAP 9.6 and may be removed in a future release of Data ONTAP.

This specifies a certificate subtype. This optional parameter can have an empty value (the default). The only valid value is as follows:

- *kmip-cert* - this is a Key Management Interoperability Protocol (KMIP) certificate

### **[-cert-name <text>] - Unique Certificate Name**

This specifies the system's internal identifier for the certificate. It must be unique within a Vserver. If not provided, it is automatically generated by the system.

## **Examples**

This example installs a CA-signed certificate (along with intermediate certificates) for a Vserver named vs0.

```
cluster1::> security certificate install -vserver vs0 ` -type ` server
Please enter Certificate: Press <Enter> when done
-----BEGIN CERTIFICATE-----
MIIB8TCCAZugAwIBAwIBADANBgkqhkiG9w0BAQQFADBfMRMwEQYDVQQDEwpuZXRh
cHAuY29tMQswCQYDVQQGEwJVUzEJMAcGA1UECBMAMQkwBwYDVQQHEwAxCTAHBgNV
BAoTADBJMAcGA1UECzMAMQ8wDQYJKoZIhvcNAQkBFgAwHhcNMTAwNDI2MTk0OTI4
WhcNMTAwNTI2MTk0OTI4WjBfMRMwEQYDVQQDEwpuZXRhcHAuY29tMQswCQYDVQQG
EwJVUzEJMAcGA1UECBMAMQkwBwYDVQQHEwAxCTAHBgNVBAoTADBJMAcGA1UECzMAMQ8wDQYJKoZIhvcNAQkBFgAwXDANBgkqhkiG9w0BAQEFAANLADBIAkEAyXrK2sry
-----END CERTIFICATE-----
Please enter Private Key: Press <Enter> when done
-----BEGIN RSA PRIVATE KEY-----
MIIBPAIBAAJBAM16ytrK8nQj82UsWeHOeT8gk0BPX+Y5MLycsUdXA7hXhumHNpvF
C61X2G32Sx8VEalth94tx+vOEzq+UaqHlt0CAwEAAQJBAMZjDWlgmlm3qIr/n8VT
PFnnZnbVcXVM70tbUsgPKw+QCCh9dF1jmuQKeDr+wUMWkn1DeGrfhILpzfJGhrLJ
```

```
z7UCIQDr8d3gOG71UyX+BbFmo/N0uAKjS2cvUU+Y8a8pDxGLLwIhANqa99SuS18U
DiPvdaKTj6+EcGuXfCXz+G0rfgTZK8uzAiEArlmnrFYC8KwE9k7A0ylRzBLdUwK9
AvuJDn+/z+H1Bd0CIQDD93P/xpaJETNz53Au49VE5Jba/Jugckrbosd/lSd7nQIg
aEMAzt6qHHT4mndi8Bo8sDGedG2SKx6Qbn2IpuNZ7rc=
-----END RSA PRIVATE KEY-----
```

Do you want to continue entering root and/or intermediate certificates  
{y|n}: y

Please enter Intermediate Certificate: Press <Enter> when done

```
-----BEGIN CERTIFICATE-----
MIIE+zCCBGSgAwIBAgICAQ0wDQYJKoZIhvcNAQEFBQAwbG1DZXJ0IFZhbG1kYXRpb24gTmV0d29yazEXMBUGA1UEChMOVmfSaUNlcnQsIElu
Yy4xNTAzBgNVBAsTTFZhbG1DZXJ0IENsYXNzIDIGUG9saWN5IFZhbG1kYXRpb24gQXV0aG9yaXR5MSEwHwYDVQDEExdHRwOi8vd3d3LnZhbG1jZXJ0LmNvbS8xIDAe
BgkqhkiG9w0BCQEWEluZm9AdmFsaWNlcnQuY29tMB4XDTA0MDYyOTE3MDYyMFoXDTI0MDYyOTE3MDYyMFowYzELMAkGA1UEBhMCVVMxITAfBgNVBAoTGFRoZSBHbyBE
YWRkeSBHcm91cCwgSW5jLjExMC8GA1UECXMOR28gRGFkZHZkgQ2xhc3MgMiBDZXJ0
-----END CERTIFICATE-----
```

Do you want to continue entering root and/or intermediate certificates  
{y|n}: y

Please enter Intermediate Certificate: Press <Enter> when done

```
-----BEGIN CERTIFICATE-----
MIIC5zCCA1ACAQEwDQYJKoZIhvcNAQEFBQAwbG1DZXJ0IFZhbG1kYXRpb24gTmV0d29yazEXMBUGA1UEChMOVmfSaUNlcnQsIEluYy4xNTAz
BgNVBAsTTFZhbG1DZXJ0IENsYXNzIDIGUG9saWN5IFZhbG1kYXRpb24gQXV0aG9yaXR5MSEwHwYDVQDEExdHRwOi8vd3d3LnZhbG1jZXJ0LmNvbS8xIDAeBgkqhkiG
9w0BCQEWEluZm9AdmFsaWNlcnQuY29tMB4XDTk5MDYyNjAwMTk1NFoXDTE5MDYyNjAwMTk1NFowgbsxJDAiBgNVBACtG1ZhbG1DZXJ0IFZhbG1kYXRpb24gTmV0d29y
azEXMBUGA1UEChMOVmfSaUNlcnQsIEluYy4xNTAzBgNVBAsTTFZhbG1DZXJ0IENsYXNzIDIGUG9saWN5IFZhbG1kYXRpb24gQXV0aG9yaXR5MSEwHwYDVQDEExdHRw
-----END CERTIFICATE-----
```

Do you want to continue entering root and/or intermediate certificates  
{y|n}: n

You should keep a copy of the private key and the CA-signed digital certificate for future reference.

This example installs a CA certificate for client authentication for a Vserver named vs0.

```
cluster1::> security certificate install -vserver vs0 ` -type` client-ca

Please enter Certificate: Press <Enter> when done
-----BEGIN CERTIFICATE-----
MIIDNjCCAp+gAwIBAgIQNhIilsXjOKUgodJfTncJVDANBgkqhkiG9w0BAQUFADCB
zjELMAkGA1UEBhMCWkExFTATBgNVBAGTDFdlc3Rlcm4gQ2FwZTESMBAGA1UEBxMJ
Q2FwZSBUb3duMR0wGwYDVQQKEExRUaGF3dGUgQ29uc3VsdGluZyBjYzEoMCYGA1UE
CxMfQ2VydGhmaWNhdGlvbiBTZXJ2aWNlcyBEaXZpc2lvcjEhMB8GA1UEAxMYVGhh
d3RlIFByZW1pdW0gU2VydmVyIENBMSgwJgYJKoZIhvcNAQkBFhlcwVtaXVtLXNl
cnZlc3Rlcm4gU29tMB4XDk2MDgwMTAwMDAwMFOxMDEwMTIzNTk1OVow
gc4xCzAJBgNVBAYTAlpBMRUwEwYDVQQIEWxXZXN0ZXJuIENhcGUxEjAQBgNVBAcT
-----END CERTIFICATE-----
You should keep a copy of the CA-signed digital certificate for future
reference.
```

This example installs a CA certificate for server authentication for a Vserver named vs0. In this case, Data ONTAP acts as an SSL client.

```
cluster1::> security certificate install -vserver vs0 ` -type` server-ca

Please enter Certificate: Press <Enter> when done
-----BEGIN CERTIFICATE-----
MIIDNjCCAp+gAwIBAgIQNhIilsXjOKUgodJfTncJVDANBgkqhkiG9w0BAQUFADCB
zjELMAkGA1UEBhMCWkExFTATBgNVBAGTDFdlc3Rlcm4gQ2FwZTESMBAGA1UEBxMJ
Q2FwZSBUb3duMR0wGwYDVQQKEExRUaGF3dGUgQ29uc3VsdGluZyBjYzEoMCYGA1UE
CxMfQ2VydGhmaWNhdGlvbiBTZXJ2aWNlcyBEaXZpc2lvcjEhMB8GA1UEAxMYVGhh
d3RlIFByZW1pdW0gU2VydmVyIENBMSgwJgYJKoZIhvcNAQkBFhlcwVtaXVtLXNl
cnZlc3Rlcm4gU29tMB4XDk2MDgwMTAwMDAwMFOxMDEwMTIzNTk1OVow
gc4xCzAJBgNVBAYTAlpBMRUwEwYDVQQIEWxXZXN0ZXJuIENhcGUxEjAQBgNVBAcT
-----END CERTIFICATE-----
You should keep a copy of the CA-signed digital certificate for future
reference.
```

## security certificate print

Display the contents of a certificate

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

### Description

This command displays the details of either an installed certificate or by reading a certificate from user input.

## Parameters

### **-vserver <Vserver Name> - Vserver Name**

Use this parameter to specify the Vserver that has the certificate installed.

### **{ [-cert-name <text>] - Installed Certificate Name**

Use this parameter to specify the unique name of the installed certificate to read and display.

### **[ [-cert-uuid <UUID>] - Installed Certificate UUID }**

Use this parameter to specify the unique UUID of the installed certificate to read and display. With no name or UUID specified, the certificate will read and display from user input.

## Examples

The following example reads and prints the details of the certificate.

```
cluster1::> security certificate print -vserver vs0 ` -cert-name `
AAACertificateServices
Certificate details:
Certificate:
  Data:
    Version: 3 (0x2)
    Serial Number: 6271844772424770508 (0x570a119742c4e3cc)
    Signature Algorithm: sha256WithRSAEncryption
    Issuer: C=IT, L=Milan, O=Actalis S.p.A./03358520967, CN=Actalis
Authentication Root CA
  Validity
    Not Before: Sep 22 11:22:02 2011 GMT
    Not After : Sep 22 11:22:02 2030 GMT
    Subject: C=IT, L=Milan, O=Actalis S.p.A./03358520967, CN=Actalis
Authentication Root CA
  Subject Public Key Info:
    Public Key Algorithm: rsaEncryption
    Public-Key: (4096 bit)
    Modulus:
      00:a7:c6:c4:a5:29:a4:2c:ef:e5:18:c5:b0:50:a3:
      6f:51:3b:9f:0a:5a:c9:c2:48:38:0a:c2:1c:a0:18:
      7f:91:b5:87:b9:40:3f:dd:1d:68:1f:08:83:d5:2d:
      1e:88:a0:f8:8f:56:8f:6d:99:02:92:90:16:d5:5f:
      08:6c:89:d7:e1:ac:bc:20:c2:b1:e0:83:51:8a:69:
      4d:00:96:5a:6f:2f:c0:44:7e:a3:0e:e4:91:cd:58:
      ee:dc:fb:c7:1e:45:47:dd:27:b9:08:01:9f:a6:21:
      1d:f5:41:2d:2f:4c:fd:28:ad:e0:8a:ad:22:b4:56:
      65:8e:86:54:8f:93:43:29:de:39:46:78:a3:30:23:
      ba:cd:f0:7d:13:57:c0:5d:d2:83:6b:48:4c:c4:ab:
      9f:80:5a:5b:3a:bd:c9:a7:22:3f:80:27:33:5b:0e:
      b7:8a:0c:5d:07:37:08:cb:6c:d2:7a:47:22:44:35:
```

c5:cc:cc:2e:8e:dd:2a:ed:b7:7d:66:0d:5f:61:51:  
22:55:1b:e3:46:e3:e3:3d:d0:35:62:9a:db:af:14:  
c8:5b:a1:cc:89:1b:e1:30:26:fc:a0:9b:1f:81:a7:  
47:1f:04:eb:a3:39:92:06:9f:99:d3:bf:d3:ea:4f:  
50:9c:19:fe:96:87:1e:3c:65:f6:a3:18:24:83:86:  
10:e7:54:3e:a8:3a:76:24:4f:81:21:c5:e3:0f:02:  
f8:93:94:47:20:bb:fe:d4:0e:d3:68:b9:dd:c4:7a:  
84:82:e3:53:54:79:dd:db:9c:d2:f2:07:9b:2e:b6:  
bc:3e:ed:85:6d:ef:25:11:f2:97:1a:42:61:f7:4a:  
97:e8:8b:b1:10:07:fa:65:81:b2:a2:39:cf:f7:3c:  
ff:18:fb:c6:f1:5a:8b:59:e2:02:ac:7b:92:d0:4e:  
14:4f:59:45:f6:0c:5e:28:5f:b0:e8:3f:45:cf:cf:  
af:9b:6f:fb:84:d3:77:5a:95:6f:ac:94:84:9e:ee:  
bc:c0:4a:8f:4a:93:f8:44:21:e2:31:45:61:50:4e:  
10:d8:e3:35:7c:4c:19:b4:de:05:bf:a3:06:9f:c8:  
b5:cd:e4:1f:d7:17:06:0d:7a:95:74:55:0d:68:1a:  
fc:10:1b:62:64:9d:6d:e0:95:a0:c3:94:07:57:0d:  
14:e6:bd:05:fb:b8:9f:e6:df:8b:e2:c6:e7:7e:96:  
f6:53:c5:80:34:50:28:58:f0:12:50:71:17:30:ba:  
e6:78:63:bc:f4:b2:ad:9b:2b:b2:fe:e1:39:8c:5e:  
ba:0b:20:94:de:7b:83:b8:ff:e3:56:8d:b7:11:e9:  
3b:8c:f2:b1:c1:5d:9d:a4:0b:4c:2b:d9:b2:18:f5:  
b5:9f:4b

Exponent: 65537 (0x10001)

X509v3 extensions:

X509v3 Subject Key Identifier:

52:D8:88:3A:C8:9F:78:66:ED:89:F3:7B:38:70:94:C9:02:02:36:D0

X509v3 Basic Constraints: critical

CA:TRUE

X509v3 Authority Key Identifier:

keyid:52:D8:88:3A:C8:9F:78:66:ED:89:F3:7B:38:70:94:C9:02:02:36:D0

X509v3 Key Usage: critical

Certificate Sign, CRL Sign

Signature Algorithm: sha256WithRSAEncryption

0b:7b:72:87:c0:60:a6:49:4c:88:58:e6:1d:88:f7:14:64:48:  
a6:d8:58:0a:0e:4f:13:35:df:35:1d:d4:ed:06:31:c8:81:3e:  
6a:d5:dd:3b:1a:32:ee:90:3d:11:d2:2e:f4:8e:c3:63:2e:23:  
66:b0:67:be:6f:b6:c0:13:39:60:aa:a2:34:25:93:75:52:de:  
a7:9d:ad:0e:87:89:52:71:6a:16:3c:19:1d:83:f8:9a:29:65:  
be:f4:3f:9a:d9:f0:f3:5a:87:21:71:80:4d:cb:e0:38:9b:3f:  
bb:fa:e0:30:4d:cf:86:d3:65:10:19:18:d1:97:02:b1:2b:72:  
42:68:ac:a0:bd:4e:5a:da:18:bf:6b:98:81:d0:fd:9a:be:5e:  
15:48:cd:11:15:b9:c0:29:5c:b4:e8:88:f7:3e:36:ae:b7:62:  
fd:1e:62:de:70:78:10:1c:48:5b:da:bc:a4:38:ba:67:ed:55:



```
3e:5e:57:df:d4:03:40:4c:81:a4:d2:4f:63:a7:09:42:09:14:
fc:00:a9:c2:80:73:4f:2e:c0:40:d9:11:7b:48:ea:7a:02:c0:
d3:eb:28:01:26:58:74:c1:c0:73:22:6d:93:95:fd:39:7d:bb:
2a:e3:f6:82:e3:2c:97:5f:4e:1f:91:94:fa:fe:2c:a3:d8:76:
1a:b8:4d:b2:38:4f:9b:fa:1d:48:60:79:26:e2:f3:fd:a9:d0:
9a:e8:70:8f:49:7a:d6:e5:bd:0a:0e:db:2d:f3:8d:bf:eb:e3:
a4:7d:cb:c7:95:71:e8:da:a3:7c:c5:c2:f8:74:92:04:1b:86:
ac:a4:22:53:40:b6:ac:fe:4c:76:cf:fb:94:32:c0:35:9f:76:
3f:6e:e5:90:6e:a0:a6:26:a2:b8:2c:be:d1:2b:85:fd:a7:68:
c8:ba:01:2b:b1:6c:74:1d:b8:73:95:e7:ee:b7:c7:25:f0:00:
4c:00:b2:7e:b6:0b:8b:1c:f3:c0:50:9e:25:b9:e0:08:de:36:
66:ff:37:a5:d1:bb:54:64:2c:c9:27:b5:4b:92:7e:65:ff:d3:
2d:e1:b9:4e:bc:7f:a4:41:21:90:41:77:a6:39:1f:ea:9e:e3:
9f:d0:66:6f:05:ec:aa:76:7e:bf:6b:16:a0:eb:b5:c7:fc:92:
54:2f:2b:11:27:25:37:78:4c:51:6a:b0:f3:cc:58:5d:14:f1:
6a:48:15:ff:c2:07:b6:b1:8d:0f:8e:5c:50:46:b3:3d:bf:01:
98:4f:b2:59:54:47:3e:34:7b:78:6d:56:93:2e:73:ea:66:28:
78:cd:1d:14:bf:a0:8f:2f:2e:b8:2e:8e:f2:14:8a:cc:e9:b5:
7c:fb:6c:9d:0c:a5:e1:96
```

## security certificate rename

Rename a certificate

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

### Description

This command allows the user to modify the name of an installed digital certificate. This command does not alter the certificate itself.

### Parameters

**-vserver <Vserver Name> - Vserver Name**

This specifies the name of the Vserver on which the certificate exists.

**-cert-name <text> - Existing Certificate Name**

This specifies the current name of the certificate.

**-new-name <text> - New Certificate Name**

This specifies the desired name of the certificate. It must be unique among certificates in the Vserver.

### Examples

```
cluster1::> security certificate rename -vserver vs0 ` -cert-name `
AAACertificateServices ` -new-name `AAACertServ
```

# security certificate show-generated

Display ONTAP generated certificates

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

## Description

This command displays information about the Data ONTAP generated digital digital certificates. Some details are displayed only when you use the command with the `-instance` parameter.

## Parameters

**{ [-fields <fieldname>,...]**

If you specify the `-fields <fieldname>, ...` parameter, the command output also includes the specified field or fields. You can use `'-fields ?'` to display the fields to specify.

**| [-instance ] }**

If you specify the `-instance` parameter, the command displays detailed information about all fields.

**[-vserver <Vserver Name>] - Name of Vserver**

Selects the Vserver whose digital certificates you want to display.

**[-common-name <FQDN or Custom Common Name>] - FQDN or Custom Common Name**

Selects the certificates that match this parameter value.

**[-serial <text>] - Serial Number of Certificate**

Selects the certificates that match this parameter value.

**[-ca <text>] - Certificate Authority**

Selects the certificates that match this parameter value.

**[-type <type of certificate>] - Type of Certificate**

Selects the certificates that match this parameter value.

**[-subtype <kmip-cert>] - (DEPRECATED)-Certificate Subtype**



This parameter has been deprecated in ONTAP 9.6 and may be removed in a future release of Data ONTAP.

Selects the certificate subtype that matches the specified value. The valid values are as follows:

- `kmip-cert` - this is a Key Management Interoperability Protocol (KMIP) certificate

**[-cert-name <text>] - Unique Certificate Name**

This specifies the system's internal identifier for the certificate. It is unique within a Vserver.

**[-size <size of requested certificate in bits>] - Size of Requested Certificate in Bits**

Selects the certificates that match this parameter value.

**[-start <Date>] - Certificate Start Date**

Selects the certificates that match this parameter value.

**[-expiration <Date>] - Certificate Expiration Date**

Selects the certificates that match this parameter value.

**[-public-cert <certificate>] - Public Key Certificate**

Selects the certificates that match this parameter value.

**[-country <text>] - Country Name**

Selects the certificates that match this parameter value.

**[-state <text>] - State or Province Name**

Selects the certificates that match this parameter value.

**[-locality <text>] - Locality Name**

Selects the certificates that match this parameter value.

**[-organization <text>] - Organization Name**

Selects the certificates that match this parameter value.

**[-unit <text>] - Organization Unit**

Selects the certificates that match this parameter value.

**[-email-addr <mail address>] - Contact Administrator's Email Address**

Selects the certificates that match this parameter value.

**[-protocol <protocol>] - Protocol**

Selects the certificates that match this parameter value.

**[-hash-function <hashing function>] - Hashing Function**

Selects the certificates that match this parameter value.

**[-self-signed {true|false}] - Self-Signed Certificate**

Selects the certificates that match this parameter value.

**[-is-root {true|false}] - Is Root CA Certificate?**

Selects the certificates that match this parameter value.

**[-authority-key-identifier <text>] - Authority Key Identifier**

Selects the certificates that match this parameter value.

**[-subject-key-identifier <text>] - Subject Key Identifier**

Selects the certificates that match this parameter value.

## Examples

The examples below display information about Data ONTAP generated digital certificates.

```
cluster1::> security certificate show-generated
```

Vserver	Serial Number	Certificate Name	Type
vs0	4F4E4D7B	``_www.example.com_``	server
	Certificate Authority:	``_www.example.com_``	
	Expiration Date:	Thu Feb 28 16:08:28 2013	

```

cluster1::> security certificate show-generated -instance
                Vserver: vs0
                Certificate Name: ``_www.example.com_``
                FQDN or Custom Common Name: ``_www.example.com_``
                Serial Number of Certificate: 4F4E4D7B
                Certificate Authority: ``_www.example.com_``
                Type of Certificate: server
                Size of Requested Certificate(bits): 2048
                Certificate Start Date: Fri Apr 30 14:14:46 2010
                Certificate Expiration Date: Sat Apr 30 14:14:46 2011
                Public Key Certificate: -----BEGIN CERTIFICATE-----

MIIDfTCCAmWgAwIBAwIBADANBgkqhkiG9w0BAQsFADBgMRQwEgYDVQQDEwtsYWlu
YWJjLmNvbTELMakGA1UEBhMCMCVVMxCTAHBgNVBAgTADAJMAcGA1UEBxMAMQkwBwYD
VQQKEwAxCTAHBgNVBAStADEPMA0GCSqGSIb3DQEJARYAMB4XDTEwMDQzMDE4MTQ0
BgNVHQ8BAf8EBAMCAQYwHQYDVR0OBBYEFcVG7dYGe51akE14ecaCdL+LOAxUMA0G
CSqGSIb3DQEBCwUAA4IBAQBj1E51pkDY3ZpsSrQeMOoWLteIR+1H0wKZOM1Bhy6Q
+gsE3XEtnN07AE4npjIT0eVP0nI9QIJAbP0uPKaCGAVBSBMoM2mOwbfswI7aJoEh
+XuEoNr0GOz+mltnfhgvl1fT6Ms+xzd3LGZYQTworus2
                -----END CERTIFICATE-----

                Country Name (2 letter code): US
                State or Province Name (full name): California
                Locality Name (e.g. city): Sunnyvale
                Organization Name (e.g. company): example
                Organization Unit (e.g. section): IT
                Email Address (Contact Name): ``_web@example.com_``
                Protocol: SSL
                Hashing Function: SHA256

```

## security certificate show-truststore

Display default truststore certificates

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

### Description

This command displays information about the default CA certificates that come pre-installed with Data ONTAP. Some details are displayed only when you use the command with the *-instance* parameter.

## Parameters

**{ [-fields <fieldname>,...]**

If you specify the `-fields <fieldname>`, ... parameter, the command output also includes the specified field or fields. You can use `'-fields ?'` to display the fields to specify.

**| [-instance ] }**

If you specify the `-instance` parameter, the command displays detailed information about all fields.

**[-vserver <Vserver Name>] - Name of Vserver**

Selects the Vserver whose digital certificates you want to display.

**[-common-name <FQDN or Custom Common Name>] - FQDN or Custom Common Name**

Selects the certificates that match this parameter value.

**[-serial <text>] - Serial Number of Certificate**

Selects the certificates that match this parameter value.

**[-ca <text>] - Certificate Authority**

Selects the certificates that match this parameter value.

**[-type <type of certificate>] - Type of Certificate**

Selects the certificates that match this parameter value.

**[-subtype <kmip-cert>] - (DEPRECATED)-Certificate Subtype**



This parameter has been deprecated in ONTAP 9.6 and may be removed in a future release of Data ONTAP.

Selects the certificate subtype that matches the specified value. The valid values are as follows:

- *kmip-cert* - this is a Key Management Interoperability Protocol (KMIP) certificate

**[-cert-name <text>] - Unique Certificate Name**

This specifies the system's internal identifier for the certificate. It is unique within a Vserver.

**[-size <size of requested certificate in bits>] - Size of Requested Certificate in Bits**

Selects the certificates that match this parameter value.

**[-start <Date>] - Certificate Start Date**

Selects the certificates that match this parameter value.

**[-expiration <Date>] - Certificate Expiration Date**

Selects the certificates that match this parameter value.

**[-public-cert <certificate>] - Public Key Certificate**

Selects the certificates that match this parameter value.

**[-country <text>] - Country Name**

Selects the certificates that match this parameter value.

**[-state <text>] - State or Province Name**

Selects the certificates that match this parameter value.

**[-locality <text>] - Locality Name**

Selects the certificates that match this parameter value.

**[-organization <text>] - Organization Name**

Selects the certificates that match this parameter value.

**[-unit <text>] - Organization Unit**

Selects the certificates that match this parameter value.

**[-email-addr <mail address>] - Contact Administrator's Email Address**

Selects the certificates that match this parameter value.

**[-protocol <protocol>] - Protocol**

Selects the certificates that match this parameter value.

**[-hash-function <hashing function>] - Hashing Function**

Selects the certificates that match this parameter value.

**[-self-signed {true|false}] - Self-Signed Certificate**

Selects the certificates that match this parameter value.

**[-is-root {true|false}] - Is Root CA Certificate?**

Selects the certificates that match this parameter value.

**[-authority-key-identifier <text>] - Authority Key Identifier**

Selects the certificates that match this parameter value.

**[-subject-key-identifier <text>] - Subject Key Identifier**

Selects the certificates that match this parameter value.

## Examples

The examples below display information about the pre-installed truststore digital certificates.

```
cluster1::> security certificate show-truststore
```

Vserver	Serial Number	Certificate Name	Type
vs0	4F4E4D7B	``_www.example.com_``	server-ca

Certificate Authority: ``\_www.example.com\_``  
Expiration Date: Thu Feb 28 16:08:28 2013

```
cluster1::> security certificate show-truststore -instance
```

```
      Vserver: vs0
      Certificate Name: ``_www.example.com_``
      FQDN or Custom Common Name: ``_www.example.com_``
      Serial Number of Certificate: 4F4E4D7B
      Certificate Authority: ``_www.example.com_``
      Type of Certificate: server-ca
      Size of Requested Certificate(bits): 2048
      Certificate Start Date: Fri Apr 30 14:14:46 2010
      Certificate Expiration Date: Sat Apr 30 14:14:46 2011
      Public Key Certificate: -----BEGIN CERTIFICATE-----

MIIDfTCCAmWgAwIBAwIBADANBgkqhkiG9w0BAQsFADBgMRQwEgYDVQQDEwtsYWlu
YWJjLmNvbTEuMCAwLWwvMC4zLWwvMC4zLWwvMC4zLWwvMC4zLWwvMC4zLWwvMC4z
VQOKEwAxCTAHBgNVBAStADEPMA0GCSqGSIb3DQEJARYAMB4XDTEwMDQzMDE4MTQ0
BgNVHQ8BAf8EBAMCAQYwHQYDVR0OBBYEFcVG7dYGe51akE14ecaCdL+LOAxUMA0G
CSqGSIb3DQEBCwUAA4IBAQBj1E51pkDY3ZpsSrQeMOoWLteIR+1H0wKZOM1Bhy6Q
+gsE3XEtnN07AE4npjIT0eVP0nI9QIJAbP0uPKaCGAVBSBMoM2mOwbfswI7aJoEh
+XuEoNr0GOz+mltnfhgvl1fT6Ms+xzd3LGZYQTworus2
      -----END CERTIFICATE-----

      Country Name (2 letter code): US
      State or Province Name (full name): California
      Locality Name (e.g. city): Sunnyvale
      Organization Name (e.g. company): example
      Organization Unit (e.g. section): IT
      Email Address (Contact Name): ``_web@example.com_``
      Protocol: SSL
      Hashing Function: SHA256
```



# security certificate show-user-installed

Display user installed certificates

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

## Description

This command displays information about the user installed digital certificates. Some details are displayed only when you use the command with the `-instance` parameter. In systems upgraded to Data ONTAP 9.4 or later, existing Data ONTAP generated certificates will also be shown as part of this command.

## Parameters

{ [-fields <fieldname>,...]

If you specify the `-fields <fieldname>`, ... parameter, the command output also includes the specified field or fields. You can use `'-fields ?'` to display the fields to specify.

| [-instance ] }

If you specify the `-instance` parameter, the command displays detailed information about all fields.

[-vserver <Vserver Name>] - Name of Vserver

Selects the Vserver whose digital certificates you want to display.

[-common-name <FQDN or Custom Common Name>] - FQDN or Custom Common Name

Selects the certificates that match this parameter value.

[-serial <text>] - Serial Number of Certificate

Selects the certificates that match this parameter value.

[-ca <text>] - Certificate Authority

Selects the certificates that match this parameter value.

[-type <type of certificate>] - Type of Certificate

Selects the certificates that match this parameter value.

[-subtype <kmip-cert>] - (DEPRECATED)-Certificate Subtype



This parameter has been deprecated in ONTAP 9.6 and may be removed in a future release of Data ONTAP.

Selects the certificate subtype that matches the specified value. The valid values are as follows:

- *kmip-cert* - this is a Key Management Interoperability Protocol (KMIP) certificate

[-cert-name <text>] - Unique Certificate Name

This specifies the system's internal identifier for the certificate. It is unique within a Vserver.

**[-size <size of requested certificate in bits>] - Size of Requested Certificate in Bits**

Selects the certificates that match this parameter value.

**[-start <Date>] - Certificate Start Date**

Selects the certificates that match this parameter value.

**[-expiration <Date>] - Certificate Expiration Date**

Selects the certificates that match this parameter value.

**[-public-cert <certificate>] - Public Key Certificate**

Selects the certificates that match this parameter value.

**[-country <text>] - Country Name**

Selects the certificates that match this parameter value.

**[-state <text>] - State or Province Name**

Selects the certificates that match this parameter value.

**[-locality <text>] - Locality Name**

Selects the certificates that match this parameter value.

**[-organization <text>] - Organization Name**

Selects the certificates that match this parameter value.

**[-unit <text>] - Organization Unit**

Selects the certificates that match this parameter value.

**[-email-addr <mail address>] - Contact Administrator's Email Address**

Selects the certificates that match this parameter value.

**[-protocol <protocol>] - Protocol**

Selects the certificates that match this parameter value.

**[-hash-function <hashing function>] - Hashing Function**

Selects the certificates that match this parameter value.

**[-self-signed {true|false}] - Self-Signed Certificate**

Selects the certificates that match this parameter value.

**[-is-root {true|false}] - Is Root CA Certificate?**

Selects the certificates that match this parameter value.

**[-authority-key-identifier <text>] - Authority Key Identifier**

Selects the certificates that match this parameter value.

**[-subject-key-identifier <text>] - Subject Key Identifier**

Selects the certificates that match this parameter value.

## Examples

The examples below display information about user installed digital certificates.

```
cluster1::> security certificate show-user-installed
```

Vserver	Serial Number	Certificate Name	Type
vs0	4F4E4D7B	`_www.example.com_`	server
	Certificate Authority:	`_www.example.com_`	
	Expiration Date:	Thu Feb 28 16:08:28 2013	

```

cluster1::> security certificate show-user-installed -instance
                Vserver: vs0
                Certificate Name: ``_www.example.com_``
                FQDN or Custom Common Name: ``_www.example.com_``
                Serial Number of Certificate: 4F4E4D7B
                Certificate Authority: ``_www.example.com_``
                Type of Certificate: server
                Size of Requested Certificate(bits): 2048
                Certificate Start Date: Fri Apr 30 14:14:46 2010
                Certificate Expiration Date: Sat Apr 30 14:14:46 2011
                Public Key Certificate: -----BEGIN CERTIFICATE-----

MIIDfTCCAmWgAwIBAwIBADANBgkqhkiG9w0BAQsFADBgMRQwEgYDVQQDEwtsYWlu
YWJjLmNvbTEuMCAkGA1UEBhMCVVMxCTAHBgNVBAgTADUuMCAkGA1UEBxMAMQkwBwYD
VQQKEwAxCTAHBgNVBAStADEPMA0GCSqGSIb3DQEJARYAMB4XDTEwMDQzMDE4MTQ0
BgNVHQ8BAf8EBAMCAQYwHQYDVR0OBBYEF7dYGe51akE14ecaCdL+LOAxUMA0G
CSqGSIb3DQEBCwUAA4IBAQBj1E51pkDY3ZpsSrQeMOoWlTeIR+1H0wKZOM1Bhy6Q
+gsE3XEtnN07AE4npjIT0eVP0nI9QIJAbP0uPKaCGAVBSBMom2mOwbfswI7aJoEh
+XuEoNr0GOz+mltnfhgvl1fT6Ms+xzd3LGZYQTworus2
                -----END CERTIFICATE-----

                Country Name (2 letter code): US
                State or Province Name (full name): California
                Locality Name (e.g. city): Sunnyvale
                Organization Name (e.g. company): example
                Organization Unit (e.g. section): IT
                Email Address (Contact Name): ``_web@example.com_``
                Protocol: SSL
                Hashing Function: SHA256

```

## security certificate show

### Display Installed Digital Certificates

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

### Description

This command displays information about the installed digital certificates. Some details are displayed only when you use the command with the *-instance* parameter.

## Parameters

**{ [-fields <fieldname>,...]**

If you specify the `-fields <fieldname>`, ... parameter, the command output also includes the specified field or fields. You can use `'-fields ?'` to display the fields to specify.

**| [-instance ] }**

If you specify the `-instance` parameter, the command displays detailed information about all fields.

**[-vserver <Vserver Name>] - Name of Vserver**

Selects the Vserver whose digital certificates you want to display.

**[-common-name <FQDN or Custom Common Name>] - FQDN or Custom Common Name**

Selects the certificates that match this parameter value.

**[-serial <text>] - Serial Number of Certificate**

Selects the certificates that match this parameter value.

**[-ca <text>] - Certificate Authority**

Selects the certificates that match this parameter value.

**[-type <type of certificate>] - Type of Certificate**

Selects the certificates that match this parameter value.

**[-subtype <kmip-cert>] - (DEPRECATED)-Certificate Subtype**



This parameter has been deprecated in ONTAP 9.6 and may be removed in a future release of Data ONTAP.

Selects the certificate subtype that matches the specified value. The valid values are as follows:

- `kmip-cert` - this is a Key Management Interoperability Protocol (KMIP) certificate

**[-cert-name <text>] - Unique Certificate Name**

This specifies the system's internal identifier for the certificate. It is unique within a Vserver.

**[-size <size of requested certificate in bits>] - Size of Requested Certificate in Bits**

Selects the certificates that match this parameter value.

**[-start <Date>] - Certificate Start Date**

Selects the certificates that match this parameter value.

**[-expiration <Date>] - Certificate Expiration Date**

Selects the certificates that match this parameter value.

**[-public-cert <certificate>] - Public Key Certificate**

Selects the certificates that match this parameter value.

**[-country <text>] - Country Name**

Selects the certificates that match this parameter value.

**[-state <text>] - State or Province Name**

Selects the certificates that match this parameter value.

**[-locality <text>] - Locality Name**

Selects the certificates that match this parameter value.

**[-organization <text>] - Organization Name**

Selects the certificates that match this parameter value.

**[-unit <text>] - Organization Unit**

Selects the certificates that match this parameter value.

**[-email-addr <mail address>] - Contact Administrator's Email Address**

Selects the certificates that match this parameter value.

**[-protocol <protocol>] - Protocol**

Selects the certificates that match this parameter value.

**[-hash-function <hashing function>] - Hashing Function**

Selects the certificates that match this parameter value.

**[-self-signed {true|false}] - Self-Signed Certificate**

Selects the certificates that match this parameter value.

**[-is-root {true|false}] - Is Root CA Certificate?**

Selects the certificates that match this parameter value.

**[-authority-key-identifier <text>] - Authority Key Identifier**

Selects the certificates that match this parameter value.

**[-subject-key-identifier <text>] - Subject Key Identifier**

Selects the certificates that match this parameter value.

## Examples

The examples below display information about digital certificates.

```
cluster1::> security certificate show
```

Vserver	Serial Number	Certificate Name	Type
---------	---------------	------------------	------

-----  
-----

vs0	4F4E4D7B	``_www.example.com_``	
-----	----------	-----------------------	--

server

Certificate Authority: ``\_www.example.com\_``

Expiration Date: Thu Feb 28 16:08:28 2013

```

cluster1::> security certificate show -instance
                Vserver: vs0
                Certificate Name: ``_www.example.com_``
                FQDN or Custom Common Name: ``_www.example.com_``
                Serial Number of Certificate: 4F4E4D7B
                Certificate Authority: ``_www.example.com_``
                Type of Certificate: server
                Size of Requested Certificate(bits): 2048
                Certificate Start Date: Fri Apr 30 14:14:46 2010
                Certificate Expiration Date: Sat Apr 30 14:14:46 2011
                Public Key Certificate: -----BEGIN CERTIFICATE-----

MIIDfTCCAmWgAwIBAwIBADANBgkqhkiG9w0BAQsFADBgMRQwEgYDVQQDEwtsYWlu
YWJjLmNvbTEuMCAkGA1UEBhMCVVMxCTAHBgNVBAgTADAEJMAcGA1UEBxMAMQkwBwYD
VQOKEwAxCTAHBgNVBAStADEPMA0GCSqGSIb3DQEJARYAMB4XDTEwMDQzMDE4MTQ0
BgNVHQ8BAf8EBAMCAQYwHQYDVR0OBBYEF7dYGe51akE14ecaCdL+LOAxUMA0G
CSqGSIb3DQEBCwUAA4IBAQBj1E51pkDY3ZpsSrQeMOoWLteIR+1H0wKZOM1Bhy6Q
+gsE3XEtnN07AE4npjIT0eVP0nI9QIJAbP0uPKaCGAVBSBMoM2mOwbfswI7aJoEh
+XuEoNr0GOz+mltnfhgvl1fT6Ms+xzd3LGZYQTworus2
                -----END CERTIFICATE-----

                Country Name (2 letter code): US
                State or Province Name (full name): California
                Locality Name (e.g. city): Sunnyvale
                Organization Name (e.g. company): example
                Organization Unit (e.g. section): IT
                Email Address (Contact Name): ``_web@example.com_``
                Protocol: SSL
                Hashing Function: SHA256

```

## security certificate sign

### Sign a Digital Certificate using Self-Signed Root CA

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

### Description

This command signs a digital certificate signing request and generates a certificate using a Self-Signed Root CA certificate in either PEM or PKCS12 format. You can use the [security certificate generate-csr](#) command to generate a digital certificate signing request.



## Parameters

### **-vserver <Vserver Name> - Name of Vserver**

This specifies the name of the Vserver on which the signed certificate will exist.

### **-ca <text> - Certificate Authority to Sign**

This specifies the name of the Certificate Authority that will sign the certificate.

### **-ca-serial <text> - Serial Number of CA Certificate**

This specifies the serial number of the Certificate Authority that will sign the certificate.

### **[-expire-days <integer>] - Number of Days until Expiration**

This specifies the number of days until the signed certificate expires. The default value is 365 days. Possible values are between *1* and *3652*.

### **[-format <certificate format>] - Certificate Format**

This specifies the format of signed certificate. The default value is PEM. Possible values include *PEM* and *PKCS12*.

### **[-destination {(ftp|http)://(hostname|IPv4 Address|['IPv6 Address'])...}] - Where to Send File**

This specifies the destination to upload the signed certificate. This option can only be used when the format is PKCS12.

### **[-hash-function <hashing function>] - Hashing Function**

This specifies the cryptographic hashing function for the self-signed certificate. The default value is SHA256. Possible values include *SHA1*, *SHA256* and *MD5*.

## Examples

This example signs a digital certificate for a Vserver named vs0 using a Certificate Authority certificate that has a ca of *www.ca.com* and a ca-serial of 4F4EB629 in PEM format using the SHA256 hashing function.

```
cluster1::> security certificate sign -vserver vs0 -ca ``_www.ca.com_``-
ca-serial` 4F4EB629 ` -expire-days` 36 ` -format` PEM ` -hash-function`
SHA256
```

Please enter Certificate Signing Request (CSR): Press <Enter> when done

```
-----BEGIN CERTIFICATE REQUEST-----
```

```
MIIBGjCBxQIBADBgMRQwEgYDVQQDEwtleGFtcGxlLmNvbTELMakGA1UEBhMCMVVMx
CTAHBgNVBAGTADEJMAcGA1UEBxMAMQkwBwYDVQQKEwAxCTAHBgNVBAsTADEPMA0G
CSqGSIB3DQEJARYAMFwwDQYJKoZIhvcNAQEBBQADSwAwSAJBAPXFanNoJApT1nzS
xOcxixqImRRGZCR7tVmTYyqPSuTvfhVtwDJbmXuj6U3a1woUsb13wfEvQnHVFNCi
2ninsJ8CAwEAAaAAMA0GCSqGSIB3DQEBCwUAA0EA6EagLfso5+4g+ejIRKKTUPQO
UqOUEoKuvxhOvPC2w7b//fNSFsFHvXloqEOhYECn/NX9h8mbphCoM5YZ4OfnKw==
```

```
-----END CERTIFICATE REQUEST-----
```

Signed Certificate: :

```
-----BEGIN CERTIFICATE-----
```

```
MIICwDCCAaigAwIBAgIET1oskDANBgkqhkiG9w0BAQsFADBdMREwDwYDVQQDEwh2
czAuY2VydDELMAkGA1UEBhMCMVVMxCTAHBgNVBAGTADEJMAcGA1UEBxMAMQkwBwYD
VQQKEwAxCTAHBgNVBAsTADEPMA0GCSqGSIB3DQEJARYAMB4XDTEyMDMwOTE2MTUx
M1oXDTEyMDQxNDE2MTUxM1owYDEUMBIGAlUEAxMLZXhhbXBsZS5jb20xCzAJBgNV
BAYTA1VTMQkwBwYDVQQIEwAxCTAHBgNVBACTADEJMAcGA1UEChMAMQkwBwYDVQQL
EwAxDzANBgkqhkiG9w0BCQEWADBCMA0GCSqGSIB3DQEBAQUAA0sAMEgCQQD1xWpz
```

```
-----END CERTIFICATE-----
```

This example signs and exports a digital certificate to destination <ftp://10.98.1.1//u/sam/sign.pfx> for a Vserver named vs0 using a Certificate Authority certificate that expires in 36 days and has a ca value of `www.ca.com` and a ca-serial value of 4F4EB629 in PKCS12 format by the MD5 hashing function.

```
cluster1::> security certificate sign -server vs0 -ca` www.ca.com -ca-serial` 4F4EB629
`-expire-days` 36 -format` PKCS12 -destination`
ftp://10.98.1.1//u/sam/sign.pfx -hash-function` MD5
```

Please enter Certificate Signing Request (CSR): Press <Enter> when done

-----BEGIN CERTIFICATE REQUEST-----

```
MIIBGjCBxQIBADBgMRQwEgYDVQQDEwtleGFTcGxlLmNvbTElMAkGA1UEBhMCVVMx
CTAHBgNVBAGTADEJMAcGA1UEBxMAMQkwBwYDVQQKEwAxCTAHBgNVBAsTADEPMA0G
CSqGSIB3DQEJARYAMFwwDQYJKoZIhvcNAQEBBQADSwAwSAJBAPXFanNoJApTlnzS
xOcxixqImRRGZCR7tVmTYyqPSuTvfhVtwDJbmXuj6U3alwoUsb13wfEvQnHVFNCi
2ninsJ8CAwEAAaAAMA0GCSqGSIB3DQEBcWUAA0EA6EagLfso5+4g+ejiRKKKTUPQO
UqOUEoKuvxhOvPC2w7b//fNSFsFHvXloqEOhYECn/NX9h8mbphCoM5YZ4OfnKw==
```

-----END CERTIFICATE REQUEST-----

Signed Certificate: :

-----BEGIN CERTIFICATE-----

```
MIICwDCCAaigAwIBAgIET1ot8jANBgkqhkiG9w0BAQsFADBdMREwDwYDVQQDEwh2
czAuY2VydDELMAkGA1UEBhMCVVMxCTAHBgNVBAGTADEJMAcGA1UEBxMAMQkwBwYD
VQQKEwAxCTAHBgNVBAsTADEPMA0GCSqGSIB3DQEJARYAMB4XDTEyMDMwOTE2MjEw
Nl0XDTEyMDQxNDE2MjEwNl0wYDEUMBIGA1UEAxMLZXhhbXBsZS5jb20xCzAJBgNV
BAYTA1VTMqkwBwYDVQQIEwAxCTAHBgNVBACTADEJMAcGA1UEChMAMQkwBwYDVQQQL
EwAxDzANBgkqhkiG9w0BCQEWADBCMA0GCSqGSIB3DQEBAAQUAA0sAMEgCQQD1xWpz
oarXHSyDzv3T5QIxBGRJ0ActgdjJuqtuAdmnKvKfLS1o4C90
```

-----END CERTIFICATE-----

Please enter Private Key: Press <Enter> when done

-----BEGIN RSA PRIVATE KEY-----

```
MIIBOwIBAAJBAPXFanNoJApTlnzSxOcxixqImRRGZCR7tVmTYyqPSuTvfhVtwDJb
mXuj6U3alwoUsb13wfEvQnHVFNCi2ninsJ8CAwEAAQJAWt2AO+bW3FKezEuIrQlu
KoMyRYK455wtMk8BrOyJfhYsB20B28eifjJvRwdTOBEav99M7cEzgPv+p5kaZTTM
gQIhAPsp+j1hrUXSRj979LIJJY0sNez397i7ViFXWQScx/ehAiEA+oDbOooWlVvu
xj4aitxVBu6ByVckYU8LbsfeRNsZwD8CIQCbZ1/ENvmlJ/P7N9Exj2NctEYxd0Q5
cwBZ5NfZeMBpwQIhAPk0KWQSLadGfsKO077itF+h9FGFNHbtuNTrVq4vPW3nAiAA
peMBQgEv28y2r8D4dkYzxcXmjzJluUSZSZ9c/ws6fA==
```

-----END RSA PRIVATE KEY-----

Please enter a password for pkcs12 file:

Please enter it again:

Enter User for Destination URI: sam

Enter Password:

## Related Links

- [security certificate generate-csr](#)

# security certificate ca-issued revoke

Revoke a Digital Certificate

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

## Description

This command revokes a digital certificate signed by a Self-Signed Root CA.

## Parameters

**-vserver <Vserver Name> - Name of Vserver**

This specifies the name of the Vserver on which the certificate is stored.

**-serial <text> - Serial Number of Certificate**

This specifies the serial number of the certificate.

**-ca <text> - Certificate Authority**

This specifies the name of the Certificate Authority whose certificate will be revoked.

**-ca-serial <text> - Serial Number of CA Certificate**

This specifies the serial number of Certificate Authority.

**[-common-name <FQDN or Custom Common Name>] - FQDN or Custom Common Name**

This specifies a fully qualified domain name (FQDN) or custom common name or the name of a person. This field is optional if ca-serial is specified.

## Examples

This example revokes a signed digital certificate for a Vserver named vs0 with serial as 4F5A2DF2 for a Certificate Authority certificate that has a ca of *www.ca.com* and a ca-serial of 4F4EB629.

```
cluster1::> security certificate ca-issued revoke -vserver vs0 -serial
4F5A2DF2 -ca ``_www.ca.com_`` -ca-serial 4F4EB629
```

# security certificate ca-issued show

Display CA-Issued Digital Certificates

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *admin* privilege level.

## Description

This command displays the following information about the digital certificates issued by the self-signed root-ca:

- Vserver
- Serial number of certificate

- FQDN or custom common name or the name of a person
- Serial number of CA certificate
- Status (`active`, `revoked`)
- Certificate Authority
- Expiration date
- Revocation date

To display more details, run the command with the `-instance` parameter. This will add the following information:

- Country name
- State or province name
- Locality name
- Organization name
- Organization unit
- Contact administrator's email address

## Parameters

**{ [-fields <fieldname>,...]**

If you specify the `-fields <fieldname>`, ... parameter, the command output also includes the specified field or fields. You can use `'-fields ?'` to display the fields to specify.

**| [-instance ] }**

If you specify the `-instance` parameter, the command displays detailed information about all fields.

**[-vserver <Vserver Name>] - Name of Vserver**

Selects the certificates that match this parameter value.

**[-serial <text>] - Serial Number of Certificate**

Selects the certificates that match this parameter value.

**[-ca <text>] - Certificate Authority**

Selects the certificates that match this parameter value.

**[-ca-serial <text>] - Serial Number of CA Certificate**

Selects the certificates that match this parameter value.

**[-common-name <FQDN or Custom Common Name>] - FQDN or Custom Common Name**

Selects the certificates that match this parameter value.

**[-status <status of certificate>] - Status of Certificate**

Selects the certificates that match this parameter value. Possible values include `active` and `revoked`.

**[-expiration <Date>] - Certificate Expiration Date**

Selects the certificates that match this parameter value.

**[-revocation <Date>] - Certificate Revocation Date**

Selects the certificates that match this parameter value.

**[-country <text>] - Country Name (2 letter code)**

Selects the certificates that match this parameter value.

**[-state <text>] - State or Province Name (full name)**

Selects the certificates that match this parameter value.

**[-locality <text>] - Locality Name (e.g. city)**

Selects the certificates that match this parameter value.

**[-organization <text>] - Organization Name (e.g. company)**

Selects the certificates that match this parameter value.

**[-unit <text>] - Organization Unit (e.g. section)**

Selects the certificates that match this parameter value.

**[-email-addr <mail address>] - Email Address (Contact Name)**

Selects the certificates that match this parameter value.

## Examples

The examples below display information about CA issued digital certificates.

```
cluster1::> security certificate ca-issued show
Serial Number of
Vserver      Serial Number  Common Name          CA's Certificate
Status
-----
-----
vs0          4F5A2C90       ``_example.com_``    4F4EB629
active
    Certificate Authority: vs0.cert
    Expiration Date: Sat Apr 14 16:15:13 2012
    Revocation Date: -

vs0          4F5A2DF2       ``_example.com_``    4F4EB629
revoked
    Certificate Authority: vs0.cert
    Expiration Date: Sat Apr 14 16:21:06 2012
    Revocation Date: Fri Mar 09 17:08:30 2012

2 entries were displayed.
```

```

cluster1::> security certificate ca-issued show -instance
Vserver: vs0
    Serial Number of Certificate: 4F5A2C90
    Certificate Authority: vs0.cert
Serial Number of CA Certificate: 4F4EB629
    FQDN or Custom Common Name: ``_example.com_``
    Status of Certificate: active
    Certificate Expiration Date: Sat Apr 14 16:15:13 2012
    Certificate Revocation Date: -
    Country Name (2 letter code): US
State or Province Name (full name): California
    Locality Name (e.g. city): Sunnyvale
    Organization Name (e.g. company): example
    Organization Unit (e.g. section): IT
    Email Address (Contact Name): ``_web@example.com_``

```

## security certificate config modify

Modify the certificate management configurations

**Availability:** This command is available to *cluster* administrators at the *advanced* privilege level.

### Description

This command modifies the certificate management configuration information for the cluster.

### Parameters

**[-min-security-strength <bits of security strength>] - Minimum Security Strength**

Use this parameter to modify the allowed minimum security strength for certificates. The security bits mapping to RSA and ECDSA key length are as follows:

Length	Security Bits	Asymmetric Key Length	Elliptic Curve Key
	112	2048	224
	128	3072	256
	192	4096	384

FIPS supported values are restricted to 112 and 128.

+  
NOTE: This does not affect root CA certificates.

+

### **[~~-expiration-warn-threshold~~ <integer>] - Minimum Days to EMS for Expiring Certificates**

Use this parameter to modify the number of days prior to certificate expiration the system sends a warning EMS event.

## **Examples**

The following example modifies the minimum security strength allowed for certificates.

```
cluster-1::> security certificate config modify -min-security-strength 192
```

## **security certificate config show**

Displays the certificate management configurations

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

### **Description**

This command displays the certificate management configuration information for the cluster.

"min-security-strength" - If you specify this parameter, the command displays the minimum allowed security strength for certificates.

"expiration-warn-threshold" - If you specify this parameter, the command displays the minimum number of days before expiration date configured for event management system (EMS) notification of expiring certificates.

## **Examples**

The following example lists minimum security strength certificate management configuration.

```
cluster-1::> security certificate config show -fields min-security-  
strength
```

```
Minimum Security Strength  
-----
```

```
112
```

## **security certificate truststore check**

Initiate a TLS connection and identify the root CA certificate

**Availability:** This command is available to *cluster* and *Vserver* administrators at the *advanced* privilege level.



## Description

This command allows the user to check if the node can use the installed set of CA certificates to establish a secure connection with the specified server. If the connection attempt fails, the system reports which expected certificates are missing. If the attempt succeeds, the system displays details of the certificates used.

## Parameters

**-vserver <Vserver Name> - Vserver Name**

Use this parameter to specify the Vserver that needs the connectivity check.

**-server <Hostname and Port> - Server Name**

Use this parameter to specify the server to establish a connection with and look up the required CA certificate.

## Examples

The following example demonstrates a missing CA certificate:

```
cluster1::*> security certificate truststore check -vserver cluster1
-server example.com:443

Error: command failed: Missing certificate with subject name: "CN =
ExampleRoot, C = US"
```

The following example demonstrates the required certificate being present:

```
cluster1::*> security certificate truststore check -server example.com:443

CA certificate with cert-name "ExampleRoot" is already installed in the
truststore. Use "security certificate show -cert-name ExampleRoot" to see
the details of the CA certificate.
```

## security certificate truststore clear

Clear the default root certificates from truststore

**Availability:** This command is available to *cluster* administrators at the *advanced* privilege level.

## Description

The `security certificate truststore clear` command deletes the pre-installed certificates of the type 'server-ca'. If you delete these certificates, some of the applications performing SSL communication can fail.

## Examples

The following example removes the default certificate bundle:

```
cluster1::> security certificate truststore clear
```

## security certificate truststore load

Load the default root certificates to truststore

**Availability:** This command is available to *cluster* administrators at the *advanced* privilege level.

### Description

The `security certificate truststore load` command installs default root certificates in the certificate table of type 'server-ca'. These are the certificates required to validate any incoming server certificate during the SSL handshake process. Note: This command only installs PEM formatted certificates.

### Parameters

**{ [-path <text>] - File to load PEM certificates from**

This specifies the path to the PEM formatted certificate bundle. This optional parameter can have an empty value (the default).

**| [-uri <text>] - URL to download PEM certificates from }**

This specifies the URL from which to download the PEM formatted certificate bundle.

**[-ontap-version <ontap\_version>] - Certificates from specific ONTAP version**

This specifies the ONTAP version in which the certificates were introduced. Only those certificates will be loaded. This optional parameter can have an empty value (the default) which indicates that no filtering on version is done.

## Examples

The following example installs the default certificate bundle:

```
cluster1::> security certificate truststore load
```

## Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.