



## **statistics top commands**

ONTAP 9.8 commands

NetApp  
September 27, 2022

# Table of Contents

- statistics top commands ..... 1
- statistics top client show ..... 1
- statistics top file show ..... 2

# statistics top commands

## statistics top client show

Most active NFS and CIFS clients

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

### Description

This command continuously displays performance data for the top NFS and CIFS clients at a regular interval. The command output displays data in the following columns:

- Client - client name.
- Vserver - vservers name.
- Node - node name.
- Total Ops - total number of operations per second.
- Total (Bps) - total throughput in bytes per second.

### Parameters

**[-node {<nodename>|local}] - Node**

Selects the node for which you want to display performance data.

**[-sort-key <text>] - Column to Sort By**

If this parameter is specified, the command displays statistics sorted by the specified column.

**-interval <integer> - Interval**

Specifies, in seconds, the interval between statistics updates. The default setting is 5 seconds.

**-iterations <integer> - Iterations**

Specifies the number of iterations the command runs before terminating. The default setting is 1. If the number is 0 (zero), the command continues to run until you interrupt it by pressing Ctrl-C.

**-max <integer> - Maximum Number of Instances**

Specifies maximum number of top clients to display. The default setting is 10.

### Examples

The following example displays top client statistics:

```

cluster1::> statistics top client show
cluster-1 : 12/31/1969 16:00:04
*Total Total
      Client      Vserver      Node      Ops (Bps)
-----
 172.17.236.53:938 vserver01 cluster-node2      9      80
172.17.236.160:898 vserver02 cluster-node1      6      50

[...]

```

## statistics top file show

Most actively accessed files

**Availability:** This command is available to *cluster* administrators at the *admin* privilege level.

### Description

This command continuously displays performance data for top files at a regular interval. The command output displays data in the following columns:

- File - file name.
- Volume - volume name.
- Vserver - vserver name.
- Aggregate - aggregate name.
- Node - node name.
- Total Ops - total number of operations per second.
- Total (Bps) - total throughput in bytes per second.

### Parameters

**[-node {<nodename>|local}] - Node**

Selects the node for which you want to display performance data.

**[-sort-key <text>] - Column to Sort By**

If this parameter is specified, the command displays statistics sorted by the specified column.

**-interval <integer> - Interval**

Specifies, in seconds, the interval between statistics updates. The default setting is 5 seconds.

**-iterations <integer> - Iterations**

Specifies the number of iterations the command runs before terminating. The default setting is 1. If the number is 0 (zero), the command continues to run until you interrupt it by pressing Ctrl-C.

**-max <integer> - Maximum Number of Instances**

Specifies maximum number of top files to display. The default setting is 10.

## Examples

The following example displays top files statistics:

```
cluster1::> statistics top file show
cluster-1 : 12/31/1969 16:00:04

Total                                                    *Total
                File  Volume  Vserver Aggregate          Node      Ops
(Bps)
-----
-----
/vol/vol01/clus/cache   vol01  vserver01   aggr1 cluster-node2      9
80
                /vol/vol02  vol02  vserver02   aggr2 cluster-node1      6
50
[...]

```

## Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.