



# Factors that impact the number and size of array LUNs you need

ONTAP FlexArray

NetApp  
September 20, 2021

# Table of Contents

- Factors that impact the number and size of array LUNs you need ..... 1
  - Factors impacting the required number of array LUNs ..... 1
  - Minimum number of array LUNs required per ONTAP system ..... 1
  - Spare array LUN requirement for core dumps ..... 2
  - Minimum and maximum array LUN sizes supported for ONTAP configurations ..... 2
  - Array LUN size required for the root volume ..... 3
  - Elements that reduce the usable space in an array LUN ..... 3
  - Considering checksum type when planning array LUN size and number ..... 3

# Factors that impact the number and size of array LUNs you need

You must consider a number of factors, including usable space in a LUN, when determining how many array LUNs you need and their size.

## Factors impacting the required number of array LUNs

While planning for ONTAP use of array LUNs, you must consider factors such as array LUN size, ONTAP overhead, and checksum type that impact the number of array LUNs required in your ONTAP environment.

You should consider the following when determining the required number of array LUNs:

- The smaller the array LUNs, the more LUNs you require for the storage.

Ideally, creating one large array LUN from a given storage array RAID group is recommended.

- Device limits define the maximum number of disks and array LUNs that can be assigned to an ONTAP system.

The *Hardware Universe* contains information about device limits.

- The more usable space in an array LUN, the fewer array LUNs are required.

The amount of usable space in an array LUN is determined by the space that ONTAP requires, checksum type, and additional factors such as space required for optional Snapshot reserves.

- Different applications generate different loads.

When determining the assignment of array LUNs to ONTAP systems, you must consider what the storage will be used for and the number of requests that are likely to be generated by different applications.

## Minimum number of array LUNs required per ONTAP system

The number of array LUNs that you need per ONTAP system depends on the location of the root volume.

The root volume can be either on a disk or on array LUNs. The location of the root volume then determines the minimum number of array LUNs you need. If the root volume is on a storage array, each stand-alone ONTAP system and each node in an HA pair must own at least one array LUN. If the root volume is on a native disk, the only array LUNs needed are those for data storage.

For a MetroCluster configuration that is using array LUNs, two array LUNs are required (one LUN from each site) if the root volume is on a storage array. The two LUNs are necessary so that the root volume can be mirrored.

# Spare array LUN requirement for core dumps

For both stand-alone ONTAP systems and nodes in HA pairs, you must create a spare array LUN of adequate size to hold core dumps if no spare disk is available.

On a system that uses both disks and array LUNs, a spare array LUN is not required for a core dump if a spare disk is available. If neither a spare array LUN nor a spare disk is available, there is no place for the core to be dumped.

A core dump contains the contents of memory and NVRAM. During a system panic, ONTAP dumps core to a spare array LUN or spare disk, if a spare exists. Upon reboot, the core is read from the spare and saved to a core dump on the root filesystem. Technical support can then use the core dump to help troubleshoot the problem.

The *Hardware Universe* contains the minimum spare core array LUN size for each platform.

## Related information

[NetApp Hardware Universe](#)

# Minimum and maximum array LUN sizes supported for ONTAP configurations

The array LUNs presented from the storage arrays must fall within the minimum and maximum size requirements for an ONTAP configuration with array LUNs. ONTAP issues an error message identifying an array LUN that does not adhere to the minimum or maximum size requirements.

The minimum and maximum array LUN sizes are calculated according to the way that ONTAP defines units of measure. The ONTAP definition of a GB and TB is as follows:

| One... | Equals...                                 |
|--------|---|
| GB     | 1000 x 1024 x 1024 bytes (1000 MB)        |
| TB     | 1000 x 1000 x 1024 x 1024 bytes (1000 GB) |

Different storage array vendors use different formulas for calculating units of measurement. You must use your vendor's units of measure to calculate the array LUN sizes equivalent to the minimum and maximum sizes supported with an ONTAP configuration.

The maximum LUN size that ONTAP supports differs with ONTAP releases. For information about the minimum and maximum array LUN sizes, see the *Hardware Universe*.



The minimum array LUN size for a data (storage) LUN is different from the minimum array LUN size for the root volume.

## Related information

[NetApp Hardware Universe](#)

# Array LUN size required for the root volume

You must set the size of the root volume to be greater than the supported minimum array LUN size, to ensure that there is sufficient space in the root volume for system files, log files, and core files. You must provide these files to technical support if a system issue occurs.

The *Hardware Universe* lists the minimum array LUN size for a root volume.

## Related information

[NetApp Hardware Universe](#)

# Elements that reduce the usable space in an array LUN

Several factors impact the usable space in an array LUN. When planning for the required number and size of the array LUNs, you must consider the usable space in the array LUN according to the checksum type you are using, and the elements you might configure.

When calculating the usable space in an array LUN, you must consider the following factors that reduce the usable space of the LUN:

- Space reserved for use by ONTAP
- Space for core dump
- Volume-level Snapshot reserve
- Aggregate-level Snapshot copy
- Checksum type (you assign one type):
  - Block checksum (BCS)
  - Advanced Zoned checksum (AZCS)

# Considering checksum type when planning array LUN size and number

When planning the number and size of array LUNs that you need for ONTAP, you must consider the impact of the checksum type on the amount of usable space in the array LUN. A checksum type must be specified for each array LUN assigned to an ONTAP system.

When an array LUN on the storage array is mapped to be used by an ONTAP system, ONTAP treats the array LUN as a raw, unformatted disk. When you assign an array LUN to an ONTAP system you specify the checksum type, which tells ONTAP how to format the raw array LUN. The impact of the checksum type on usable space depends on the checksum type you specify for the LUN.

## Characteristics of checksum types that ONTAP supports

ONTAP supports block checksum type (BCS) and advanced zoned checksum type (AZCS) for array LUNs, disks, and aggregates.

The type of checksum assigned to an array LUN in ONTAP can impact performance or the usable space of an array LUN. Therefore, the number and size of array LUNs you need can be impacted depending on the checksum type you assign to array LUNs.

### Block checksum (BCS)

BCS is the default and recommended checksum type for array LUNs. BCS provides better performance for array LUNs than AZCS.

BCS has a greater impact on the usable space in an array LUN than AZCS. BCS uses 12.5 percent of the usable space in an array LUN.

### Advanced zoned checksum (AZCS)

AZCS is an alternative to BCS. The impact of AZCS on usable space in an array LUN is less than with BCS; AZCS uses 1.56 percent of the device capacity. However, you must weigh the need for more usable space against performance. AZCS can sometimes cause performance problems for array LUNs.

AZCS is not recommended for array LUNs for high-performance random workloads. However, you can use AZCS with array LUNs for DR, archive, or similar workloads.

There is no AZCS performance impact on native disks.

The guidelines for checksum types differ according to disk size and type. See *TR3838 Storage Subsystem Configuration Guide* for more information.

### Related information

[NetApp Technical Report 3838: Storage Subsystem Configuration Guide](#)

## Formulas for calculating array LUN size based on checksum type

A number of elements, including checksum type, impact the usable capacity of an array LUN. You can use a formula to calculate how much usable capacity there would be in a given size array LUN, or to calculate how large an array LUN has to be to provide the amount of storage that you want.

A number of elements, including checksum type, impact the size of the array LUN you require for the amount of *usable capacity*. Usable capacity is the amount of space that is available for storage.

The following table shows the ways of calculating the array LUN size you require:

| If you know...                                  | You want to find out...  |
|---|--|
| How large your array LUNs are                   | How much capacity is available for storage (usable capacity). You have to consider the amount of space required for all elements.        |
| How much storage that you want in the array LUN | How large an array LUN you require. You have to take into account your required amount of storage and space required for other elements. |



2 TB in these formulas represents 2 TiB, or 2199023255552 bytes, which is 2097.152 GnaB or 2.097 TnaB according to the way that ONTAP calculates measurements.

### Formula for calculating the usable capacity

When you know how large your array LUNs are, you can use the following formula to determine the usable capacity for storage in an array LUN. This formula takes into account the Snapshot reserve.

- Y is the usable capacity for storage.
- N is the total capacity of the array LUN.

| Checksum type                     | Formula   |
|-----------------------------------|---|
| BCS—array LUNs less than 2 TB     | $N \times \{0.875 \times 0.9 \times 0.99 \times (1 - \text{Snapshot reserve})\} = Y$  |
| BCS—array LUNs greater than 2 TB  | $N \times \{0.875 \times 0.9 \times 0.998 \times (1 - \text{Snapshot reserve})\} = Y$ |
| AZCS—array LUNs less than 2 TB    | $N \times \{0.984 \times 0.9 \times 0.99 \times (1 - \text{Snapshot reserve})\} = Y$  |
| AZCS—array LUNs greater than 2 TB | $N \times \{0.984 \times 0.9 \times 0.998 \times (1 - \text{Snapshot reserve})\} = Y$ |

### Example 1: calculations *with* a Snapshot reserve

In the following example, the total capacity of the array LUN is 4 GB, with a volume Snapshot reserve set at the default for Data ONTAP 8.1.1 (5 percent).

The following examples are for an array LUN less than 2 TB:

| Checksum type                   | Formula  |
|---------------------------------|--|
| BCS (array LUN less than 2 TB)  | $4 \times \{0.875 \times 0.9 \times 0.99 \times 0.95\} = 2.96 \text{ GB usable space for storage}$ |
| AZCS (array LUN less than 2 TB) | $4 \times \{0.984 \times 0.9 \times 0.99 \times 0.95\} = 3.33 \text{ GB usable space for storage}$ |

### Formula for calculating maximum array LUN size needed

When you know the array LUN capacity needed to obtain the storage capacity you want, you can use the following formula to determine the total array LUN size you need, considering elements that require space in the LUN.

- Y is the exact amount of space in the array LUN that you want.
- If you are using Snapshot copies, the Snapshot reserve is taken into account.

The following examples are for an array LUN less than 2 TB:

| Checksum type                   | Formula  |
|---------------------------------|--|
| BCS (array LUN less than 2 TB)  | $Y \div \{0.875 \times 0.9 \times 0.99 \times (1 - \text{Snapshot reserve})\} =$<br>Actual capacity required |
| AZCS (array LUN less than 2 TB) | $Y \div \{0.984 \times 0.9 \times 0.99 \times (1 - \text{Snapshot reserve})\} =$<br>Actual capacity required |

### Example 2: calculations *with* Snapshot reserves

In this example, the volume Snapshot reserve is the default setting for Data ONTAP 8.1.1 (5 percent).

The following examples are for an array LUN less than 2 TB:

| Checksum type                   | Formula   |
|---------------------------------|---|
| BCS (array LUN less than 2 TB)  | $10 \text{ GB} \div \{0.875 \times 0.9 \times 0.99 \times 0.95\} = 13.5 \text{ GB}$ actual capacity required  |
| AZCS (array LUN less than 2 TB) | $10 \text{ GB} \div \{0.984 \times 0.9 \times 0.99 \times 0.95\} = 12.05 \text{ GB}$ actual capacity required |

### Example 3: calculations *without* Snapshot reserves

You want 10 GB of usable capacity for storage. The following example shows calculating actual array LUN size when you are not using Snapshot copies.

The following examples are for an array LUN less than 2 TB:

| Checksum type                   | Formula   |
|---------------------------------|---|
| BCS (array LUN less than 2 TB)  | $10 \text{ GB} \div \{0.875 \times 0.9 \times 0.99\} = 12.8 \text{ GB}$ actual capacity required  |
| AZCS (array LUN less than 2 TB) | $10 \text{ GB} \div \{0.984 \times 0.9 \times 0.99\} = 11.41 \text{ GB}$ actual capacity required |



## Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.