



Manage FlexCache volumes

ONTAP 9.10.1 REST API Documentation

NetApp
April 02, 2024

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-9101/ontap/storage_flexcache_flexcaches_endpoint_overview.html on April 02, 2024. Always check docs.netapp.com for the latest.

Table of Contents

- Manage FlexCache volumes 1
 - Storage flexcache flexcaches endpoint overview 1
 - The response: 2
 - The response: 3
 - The API: 3
 - The call: 4
 - The response: 4
 - The API: 4
 - The call: 4
 - The response: 4
 - The API: 5
 - The call: 5
 - The response: 5
 - the API: 5
 - The call: 5
 - The response: 5
- Retrieve a FlexCache volume in the cluster 6
- Create a FlexCache volume in the cluster 17
- Delete a FlexCache volume 29
- Retrieve attributes of the FlexCache volume in the cluster 33
- Pre-populate a FlexCache volume in the cluster 42

Manage FlexCache volumes

Storage flexcache flexcaches endpoint overview

Overview

FlexCache is a persistent cache of an origin volume. An origin volume can only be a FlexVol while a FlexCache is always a FlexGroup.

The following relationship configurations are supported:

– Intra-Vserver where FlexCache and the corresponding origin volume reside in the same Vserver.

– Cross-Vserver but intra-cluster where FlexCache and the origin volume reside in the same cluster but belong to different Vservers.

– Cross-cluster where FlexCache and the origin volume reside in different clusters.

FlexCache supports fan-out and more than one FlexCache can be created from one origin volume. This API retrieves and manages FlexCache configurations in the cache cluster.

FlexCache APIs

The following APIs can be used to perform operations related with FlexCache:

– GET `/api/storage/flexcache/flexcaches`

– GET `/api/storage/flexcache/flexcaches/{uuid}`

– POST `/api/storage/flexcache/flexcaches`

– DELETE `/api/storage/flexcache/flexcaches/{uuid}`

Examples

Creating a FlexCache

The POST request is used to create a FlexCache.

```

# The API:
/api/storage/flexcache/flexcaches

# The call:
curl -X POST "https://<mgmt-ip>/api/storage/flexcache/flexcaches" -H
"accept: application/json" -H "Content-Type: application/json" -d "{
\"aggregates\": [ { \"name\": \"aggr_1\" } ], \"name\": \"fc_333\",
\"origins\": [ { \"svm\": { \"name\": \"vs_3\" }, \"volume\": {
\"name\": \"vol_o1\" } } ], \"svm\": { \"name\": \"vs_1\" } }"

# The response:
{
"job": {
  "uuid": "e751dd5d-0f3c-11e9-8b2b-0050568e0b79",
  "_links": {
    "self": {
      "href": "/api/cluster/jobs/e751dd5d-0f3c-11e9-8b2b-0050568e0b79"
    }
  }
}
}
}

```

```

curl -X POST "https://<mgmt-ip>/api/storage/flexcache/flexcaches" -H "accept: application/json" -H "Content-
Type: application/json" -d "{ \"aggregates\": [ { \"name\": \"aggr_1\" } ], \"name\": \"fc_333\", \"origins\": [ {
\"svm\": { \"name\": \"vs_3\" }, \"volume\": { \"name\": \"vol_o1\" } } ], \"svm\": { \"name\": \"vs_1\" }, \"path\":
\"/fc_333\", \"prepopulate\": { \"dir_paths\": [ \"/dir1\" ] } }" </mgmt-ip>

```

The response:

```

{ "job": { "uuid": "e751dd5d-0f3c-11e9-8b2b-0050568e0b79", "_links": { "self": { "href":
"/api/cluster/jobs/e751dd5d-0f3c-11e9-8b2b-0050568e0b79" } } } }

```

```

curl -X POST "https://<mgmt-ip>/api/storage/flexcache/flexcaches" -H
"accept: application/json" -H "Content-Type: application/json" -d "{
  \"aggregates\": [ { \"name\": \"aggr_1\" } ], \"name\":
  \"fc_333\", \"origins\": [ { \"svm\": { \"name\": \"vs_3\" },
  \"volume\": { \"name\": \"vol_o1\" } } ], \"svm\": { \"name\": \"vs_1\" },
  \"path\": \"/\
  fc_333\", \"prepopulate\": { \"dir_paths\": [
  \"/dir1\" ], \"exclude_dir_paths\": [ \"/dir1/dir11\" ] } }"

# The response:
{
  \"job\": {
    \"uuid\": \"5afe9ea4-1dcf-11eb-b006-005056ac6a93\",
    \"_links\": {
      \"self\": {
        \"href\": \"/api/cluster/jobs/5afe9ea4-1dcf-11eb-b006-005056ac6a93\"
      }
    }
  }
}

```

```

curl -X POST "https://<mgmt-ip>/api/storage/flexcache/flexcaches" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"aggregates\": [ { \"name\": \"aggr_1\" } ], \"name\": \"fc_333\", \"origins\": [ { \"svm\": { \"name\": \"vs_3\" }, \"volume\": { \"name\": \"vol_o1\" } } ], \"svm\": { \"name\": \"vs_1\" }, \"dr_cache\": true, \"path\": \"/\
fc_333\", \"prepopulate\": { \"dir_paths\": [ \"/dir1\" ] } }" </mgmt-ip>

```

The response:

```

{ \"job\": { \"uuid\": \"e751dd5d-0f3c-11e9-8b2b-0050568e0b79\", \"_links\": { \"self\": { \"href\":
\"/api/cluster/jobs/e751dd5d-0f3c-11e9-8b2b-0050568e0b79\" } } } }

```

Retrieving FlexCache attributes

The GET request is used to retrieve FlexCache attributes. The object includes a large set of fields which can be expensive to retrieve. Most notably, the fields `size`, `guarantee.type`, `aggregates`, `path`, `origins.ip_address`, `origins.size`, and `origins.state` are expensive to retrieve. The recommended method to use this API is to filter and retrieve only the required fields.

The API:

`/api/storage/flexcache/flexcaches`

The call:

```
curl -X GET "https://<mgmt-ip>/api/storage/flexcache/flexcaches?" -H "accept: application/json"</mgmt-ip>
```

The response:

```
{ "records": [ { "uuid": "04d5e07b-0ebe-11e9-8180-0050568e0b79", "name": "fc_322", "_links": { "self": { "href": "/api/storage/flexcache/flexcaches/04d5e07b-0ebe-11e9-8180-0050568e0b79" } } }, { "uuid": "47902654-0ea4-11e9-8180-0050568e0b79", "name": "fc_321", "_links": { "self": { "href": "/api/storage/flexcache/flexcaches/47902654-0ea4-11e9-8180-0050568e0b79" } } }, { "uuid": "77e911ff-0ebe-11e9-8180-0050568e0b79", "name": "fc_323", "_links": { "self": { "href": "/api/storage/flexcache/flexcaches/77e911ff-0ebe-11e9-8180-0050568e0b79" } } }, { "uuid": "ddb42bbc-0e95-11e9-8180-0050568e0b79", "name": "fc_32", "_links": { "self": { "href": "/api/storage/flexcache/flexcaches/ddb42bbc-0e95-11e9-8180-0050568e0b79" } } }, { "uuid": "ec774932-0f3c-11e9-8b2b-0050568e0b79", "name": "fc_333", "_links": { "self": { "href": "/api/storage/flexcache/flexcaches/ec774932-0f3c-11e9-8b2b-0050568e0b79" } } } ], "num_records": 5, "_links": { "self": { "href": "/api/storage/flexcache/flexcaches?" } } }
```

```
### Retrieving the attributes of a FlexCache
```

The GET request is used to retrieve the attributes of a FlexCache. The object includes a large set of fields which can be expensive to retrieve. Most notably, the fields `size`, `guarantee.type`, `aggregates`, `path`, `origins.ip_address`, `origins.size`, and `origins.state` are expensive to retrieve. The recommended method to use this API is to filter and retrieve only the required fields.

The API:

```
/api/storage/flexcache/flexcaches/{uuid}
```

The call:

```
curl -X GET "https://<mgmt-ip>/api/storage/flexcache/flexcaches/ec774932-0f3c-11e9-8b2b-0050568e0b79" -H "accept: application/json"</mgmt-ip>
```

The response:

```
{ "uuid": "ec774932-0f3c-11e9-8b2b-0050568e0b79", "name": "fc_333", "svm": { "name": "vs_1", "uuid": "e708fbe2-0e92-11e9-8180-0050568e0b79" }, "size": 4294967296, "guarantee": { "type": "volume" }, "dr_cache": "true", "aggregates": [ { "name": "aggr_1", "uuid": "26f34b76-88f8-4a47-b5e0-d8e901fb1114" } ], "origins": [ { "ip_address": "10.140.103.175", "size": 20971520, "create_time": "2019-01-03T15:19:55+05:30", "state": "online", "volume": { "name": "vol_o1", "uuid": "2bc957dd-2617-4afb-8d2f-66ac6070d313" }, "svm": { "name": "vs_3", "uuid": "8aa2cd28-0e92-11e9-b391-0050568e4115" }, "cluster": { "name": "node2", "uuid": "50733f81-0e90-11e9-b391-0050568e4115" } } ], "_links": { "self": { "href": "/api/storage/flexcache/flexcaches/ec774932-0f3c-11e9-8b2b-0050568e0b79" } } }
```

```
### Deleting a FlexCache
The DELETE request is used to delete a FlexCache.
```

The API:

/api/storage/flexcache/flexcaches

The call:

```
curl -X DELETE "https://<mgmt-ip>/api/storage/flexcache/flexcaches/ec774932-0f3c-11e9-8b2b-0050568e0b79" -H "accept: application/json"</mgmt-ip>
```

The response:

```
{ "job": { "uuid": "e17994f2-0f3e-11e9-8b2b-0050568e0b79", "_links": { "self": { "href":
"/api/cluster/jobs/e17994f2-0f3e-11e9-8b2b-0050568e0b79" } } } }
```

```
### Modifying a FlexCache volume
Use the PATCH request to update a FlexCache volume.
```

the API:

/api/storage/flexcache/flexcaches/{uuid}

The call:

```
curl -X PATCH "https://<mgmt-ip>/api/storage/flexcache/flexcaches/ec774932-0f3c-11e9-8b2b-0050568e0b79"
-H "accept: application/json" -H "Content-Type: application/json" -d "{ \"prepopulate\": { \"dir_paths\": [ \"/dir1\" ]
} }"</mgmt-ip>
```

The response:

```
{ "job": { "uuid": "e751dd5d-0f3c-11e9-8b2b-0050568e0b79", "_links": { "self": { "href":
"/api/cluster/jobs/e751dd5d-0f3c-11e9-8b2b-0050568e0b79" } } } }
```

```
# The call
curl -X PATCH "https://<mgmt-
ip>/api/storage/flexcache/flexcaches/ec774932-0f3c-11e9-8b2b-0050568e0b79"
-H "accept: application/json" -H "Content-Type: application/json" -d "{
\"prepopulate\": { \"dir_paths\": [ \"/dir1\" ], \"exclude_dir_paths\": [
\"/dir1/dir11\" ] } }"

# The response:
{
  "job": {
    "uuid": "b574c48c-1da7-11eb-b006-005056ac6a93",
    "_links": {
      "self": {
        "href": "/api/cluster/jobs/b574c48c-1da7-11eb-b006-005056ac6a93"
      }
    }
  }
}
}
```

Retrieve a FlexCache volume in the cluster

GET /storage/flexcache/flexcaches

Introduced In: 9.6

Retrieves FlexCache in the cluster.

Expensive properties

There is an added cost to retrieving values for these properties. They are not included by default in GET results and must be explicitly requested using the `fields` query parameter. See [Requesting specific fields](#) to learn more.

- `origins.ip_address` - IP address of origin.
- `origins.size` - Physical size of origin.
- `origins.state` - State of origin.
- `size` - Physical size of FlexCache.
- `guarantee.type` - Space guarantee style of FlexCache.
- `aggregates.name` or `aggregates.uuid` - Name or UUID of aggregate of FlexCache volume.
- `path` - Fully-qualified path of the owning SVM's namespace where the FlexCache is mounted.

Related ONTAP commands

- `volume flexcache show`

Learn more

- [DOC /storage/flexcache/flexcaches](#)

Parameters

| Name | Type | In | Required | Description |
|-----------------------------|---------|-------|----------|--|
| aggregates.uuid | string | query | False | Filter by aggregates.uuid |
| aggregates.name | string | query | False | Filter by aggregates.name |
| global_file_locking_enabled | boolean | query | False | Filter by global_file_locking_enabled <ul style="list-style-type: none">• Introduced in: 9.9 |
| use_tiered_aggregate | boolean | query | False | Filter by use_tiered_aggregate <ul style="list-style-type: none">• Introduced in: 9.8 |
| origins.state | string | query | False | Filter by origins.state |
| origins.svm.uuid | string | query | False | Filter by origins.svm.uuid |
| origins.svm.name | string | query | False | Filter by origins.svm.name |
| origins.size | integer | query | False | Filter by origins.size |
| origins.ip_address | string | query | False | Filter by origins.ip_address |
| origins.create_time | string | query | False | Filter by origins.create_time |
| origins.cluster.name | string | query | False | Filter by origins.cluster.name |
| origins.cluster.uuid | string | query | False | Filter by origins.cluster.uuid |

| Name | Type | In | Required | Description |
|----------------------------|---------|-------|----------|--|
| origins.volume.uuid | string | query | False | Filter by origins.volume.uuid |
| origins.volume.name | string | query | False | Filter by origins.volume.name |
| svm.uuid | string | query | False | Filter by svm.uuid |
| svm.name | string | query | False | Filter by svm.name |
| constituents_per_aggregate | integer | query | False | Filter by constituents_per_aggregate |
| size | integer | query | False | Filter by size |
| name | string | query | False | Filter by name |
| dr_cache | boolean | query | False | Filter by dr_cache • Introduced in: 9.9 |
| guarantee.type | string | query | False | Filter by guarantee.type • Introduced in: 9.7 |
| path | string | query | False | Filter by path |
| uuid | string | query | False | Filter by uuid |

| Name | Type | In | Required | Description |
|--|----------------|---------|----------|---|
| return_timeout | integer | query | False | The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. <ul style="list-style-type: none"> • Default value: 1 • Max value: 120 • Min value: 0 |
| fields | array[string] | query | False | Specify the fields to return. |
| max_records | integer | query | False | Limit the number of records returned. |
| order_by | array[string] | query | False | Order results by specified fields and optional [asc |
| desc] direction. Default direction is 'asc' for ascending. | return_records | boolean | query | False |

Response

Status: 200, Ok

| Name | Type | Description |
|-------------|------------------------------------|-------------------|
| _links | _links | |
| num_records | integer | Number of records |
| records | array[flexcache] | |

Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "aggregates": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "aggr1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "guarantee": {
      "type": "volume"
    },
    "name": "voll",
    "origins": {
      "cluster": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "cluster1",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
      },
      "create_time": "2018-06-04T19:00:00Z",
      "ip_address": "10.10.10.7",
      "size": 0,
      "state": "error",
      "svm": {
        "_links": {
```

```

    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"volume": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "volumel",
  "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
},
"path": "/user/my_fc",
"prepopulate": {
  "dir_paths": {
  },
  "exclude_dir_paths": {
  }
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
}

```

Error

Status: Default, Error

| Name | Type | Description |
|-------|-------|-------------|
| error | error | |

Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| next | href | |
| self | href | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

aggregates

Aggregate

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

guarantee

| Name | Type | Description |
|------|--------|--|
| type | string | The type of space guarantee of this volume in the aggregate. |

cluster

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

svm

| Name | Type | Description |
|------------------------|------------------------|-----------------------------------|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

volume

| Name | Type | Description |
|------------------------|------------------------|--|
| _links | _links | |
| name | string | The name of the volume. |
| uuid | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> • example: 028baa66-41bd-11e9-81d5-00a0986138f7 • Introduced in: 9.6 |

flexcache_relationship

| Name | Type | Description |
|-------------|-------------------------|--|
| cluster | cluster | |
| create_time | string | Creation time of the relationship. |
| ip_address | string | Cluster management IP of the remote cluster. |
| size | integer | Size of the remote volume. |
| state | string | Volume state |
| svm | svm | |
| volume | volume | |

prepopulate

FlexCache prepopulate

| Name | Type | Description |
|-------------------|---------------|--|
| dir_paths | array[string] | |
| exclude_dir_paths | array[string] | |
| recurse | boolean | Specifies whether or not the prepopulate action should search through the <code>dir_paths</code> recursively. If not set, the default value <code>true</code> is used. |

svm

FlexCache SVM

| Name | Type | Description |
|--------|------------------------|-----------------------------------|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

flexcache

Defines the cache endpoint of FlexCache.

| Name | Type | Description |
|-----------------------------|-------------------------------------|---|
| _links | _links | |
| aggregates | array[aggregates] | |
| constituents_per_aggregate | integer | Number of FlexCache constituents per aggregate when the 'aggregates' field is mentioned. |
| dr_cache | boolean | If set to true, a DR cache is created. |
| global_file_locking_enabled | boolean | Specifies whether or not a FlexCache volume has global file locking mode enabled. Global file locking mode is a mode where protocol read locking semantics are enforced across all FlexCaches and origins of a FlexCache volume. When global file locking mode is enabled, the "is_disconnected_mode_off_for_locks" flag is always set to "true". |

| Name | Type | Description |
|----------------------|---|---|
| guarantee | guarantee | |
| name | string | FlexCache name |
| origins | array[flexcache_relationship] | |
| path | string | The fully-qualified path in the owning SVM's namespace at which the FlexCache is mounted. The path is case insensitive and must be unique within a SVM's namespace. Path must begin with '/' and must not end with '/'. Only one FlexCache be mounted at any given junction path. |
| prepopulate | prepopulate | FlexCache prepopulate |
| size | integer | Physical size of the FlexCache. The recommended size for a FlexCache is 10% of the origin volume. The minimum FlexCache constituent size is 1GB. |
| svm | svm | FlexCache SVM |
| use_tiered_aggregate | boolean | Specifies whether or not a Fabricpool-enabled aggregate can be used in FlexCache creation. The use_tiered_aggregate is only used when auto-provisioning a FlexCache volume. |
| uuid | string | FlexCache UUID. Unique identifier for the FlexCache. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|-----------|--|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Create a FlexCache volume in the cluster

POST /storage/flexcache/flexcaches

Introduced In: 9.6

Creates a FlexCache in the cluster.

Required properties

- `name` - Name of FlexCache volume.
- `origins.volume.name` or `origins.volume.uuid` - Name or UUID of origin volume.
- `origins.svm.name` - Name of origin Vserver.
- `svm.name` or `svm.uuid` - Name or UUID of Vserver where FlexCache will be created.

Recommended optional properties

- `path` - Path to mount the FlexCache volume
- `prepopulate.dir_paths` - List of directory-paths to be prepopulated for the FlexCache volume.
- `prepopulate.exclude_dir_paths` - List of directory-paths to be excluded from prepopulation for the FlexCache volume.

Default property values

If not specified in POST, the following default property values are assigned:

- `size` - 10% of origin volume size or 1GB per constituent, whichever is greater.
- `guarantee.type` - none. FlexCache is thin provisioned by default.
- `constituents_per_aggregate` - 4 if `aggregates.name` or `aggregates.uuid` is used.
- `use_tiered_aggregate` - false if `aggr-list` is not used. This property is only used when auto-provisioning a FlexCache volume.
- `is_disconnected_mode_off_for_locks` - false. This property specifies if the origin will honor the cache side locks when doing the lock checks in the disconnected mode.

- `dr_cache` - false if FlexCache is not a DR cache. This property is used to create a DR FlexCache.
- `global_file_locking_enabled` - false. This property specifies whether global file locking is enabled on the FlexCache volume.

Related ONTAP commands

- `volume flexcache create`
- `volume flexcache prepopulate start`

Learn more

- [DOC /storage/flexcache/flexcaches](#)

Parameters

| Name | Type | In | Required | Description |
|-----------------------------|---------|-------|----------|--|
| <code>return_timeout</code> | integer | query | False | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> • Default value: 1 • Max value: 120 • Min value: 0 |

| Name | Type | In | Required | Description |
|----------------|---------|-------|----------|---|
| return_records | boolean | query | False | <p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> • Default value: |

Request Body

| Name | Type | Description |
|-----------------------------|---|---|
| _links | _links | |
| aggregates | array[aggregates] | |
| constituents_per_aggregate | integer | Number of FlexCache constituents per aggregate when the 'aggregates' field is mentioned. |
| dr_cache | boolean | If set to true, a DR cache is created. |
| global_file_locking_enabled | boolean | Specifies whether or not a FlexCache volume has global file locking mode enabled. Global file locking mode is a mode where protocol read locking semantics are enforced across all FlexCaches and origins of a FlexCache volume. When global file locking mode is enabled, the "is_disconnected_mode_off_for_locks" flag is always set to "true". |
| guarantee | guarantee | |
| name | string | FlexCache name |
| origins | array[flexcache_relationship] | |
| path | string | The fully-qualified path in the owning SVM's namespace at which the FlexCache is mounted. The path is case insensitive and must be unique within a SVM's namespace. Path must begin with '/' and must not end with '/'. Only one FlexCache be mounted at any given junction path. |

| Name | Type | Description |
|----------------------|-------------|---|
| prepopulate | prepopulate | FlexCache prepopulate |
| size | integer | Physical size of the FlexCache. The recommended size for a FlexCache is 10% of the origin volume. The minimum FlexCache constituent size is 1GB. |
| svm | svm | FlexCache SVM |
| use_tiered_aggregate | boolean | Specifies whether or not a Fabricpool-enabled aggregate can be used in FlexCache creation. The use_tiered_aggregate is only used when auto-provisioning a FlexCache volume. |
| uuid | string | FlexCache UUID. Unique identifier for the FlexCache. |

Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "aggregates": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "aggr1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "guarantee": {
    "type": "volume"
  },
  "name": "vol1",
  "origins": {
    "cluster": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "cluster1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "create_time": "2018-06-04T19:00:00Z",
    "ip_address": "10.10.10.7",
    "size": 0,
    "state": "error",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "volume": {
      "_links": {
```

```

    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "volume1",
  "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
},
"path": "/user/my_fc",
"prepopulate": {
  "dir_paths": {
  },
  "exclude_dir_paths": {
  }
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}

```

Response

Status: 202, Accepted

| Name | Type | Description |
|------|--------------------------|-------------|
| job | job_link | |

Example response

```
{
  "job": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "uuid": "string"
  }
}
```

Error

Status: Default

ONTAP Error Response Codes

| Error Code | Description |
|------------|--|
| 66846870 | Either the SVM name or origin volume name is missing |
| 66846871 | Constituents per aggregate are specified but aggregate name is missing |
| 66846872 | More than one origin volume is specified |
| 66846873 | The specified SVM UUID is incorrect for the specified SVM name |
| 66846874 | The specified aggregate UUID is incorrect for the specified aggregate name |
| 66846875 | The specified aggregate name does not exist |
| 66846876 | The specified SVM does not exist or is not peered |
| 66846877 | The specified origin SVM name is of zero length |
| 66846878 | The specified SVM UUID is invalid |
| 66846730 | Failed to create a FlexCache volume |
| 66846760 | The specified SVM is not a data Vserver |
| 66846787 | The specified aggregate is a SnapLock aggregate |
| 66846812 | The specified aggregate is a Composite aggregate |
| 66846812 | The specified junction path is under a FlexCache volume |

| Error Code | Description |
|------------|--|
| 66846834 | FlexCache encryption requires a cluster version of 9.6 or higher |
| 66846835 | A volume encryption license is not found |

| Name | Type | Description |
|-------|-------|-------------|
| error | error | |

Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

aggregates

Aggregate

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

guarantee

| Name | Type | Description |
|------|--------|--|
| type | string | The type of space guarantee of this volume in the aggregate. |

cluster

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

svm

| Name | Type | Description |
|--------|------------------------|-----------------------------------|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

volume

| Name | Type | Description |
|---------------------|------------------------|--|
| <code>_links</code> | _links | |
| <code>name</code> | string | The name of the volume. |
| <code>uuid</code> | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> • example: 028baa66-41bd-11e9-81d5-00a0986138f7 • Introduced in: 9.6 |

flexcache_relationship

| Name | Type | Description |
|--------------------------|-------------------------|--|
| <code>cluster</code> | cluster | |
| <code>create_time</code> | string | Creation time of the relationship. |
| <code>ip_address</code> | string | Cluster management IP of the remote cluster. |
| <code>size</code> | integer | Size of the remote volume. |
| <code>state</code> | string | Volume state |
| <code>svm</code> | svm | |
| <code>volume</code> | volume | |

prepopulate

FlexCache prepopulate

| Name | Type | Description |
|--------------------------------|---------------|--|
| <code>dir_paths</code> | array[string] | |
| <code>exclude_dir_paths</code> | array[string] | |
| <code>recurse</code> | boolean | Specifies whether or not the prepopulate action should search through the <code>dir_paths</code> recursively. If not set, the default value <i>true</i> is used. |

svm

FlexCache SVM

| Name | Type | Description |
|--------|------------------------|-----------------------------------|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

flexcache

Defines the cache endpoint of FlexCache.

| Name | Type | Description |
|-----------------------------|---|---|
| _links | _links | |
| aggregates | array[aggregates] | |
| constituents_per_aggregate | integer | Number of FlexCache constituents per aggregate when the 'aggregates' field is mentioned. |
| dr_cache | boolean | If set to true, a DR cache is created. |
| global_file_locking_enabled | boolean | Specifies whether or not a FlexCache volume has global file locking mode enabled. Global file locking mode is a mode where protocol read locking semantics are enforced across all FlexCaches and origins of a FlexCache volume. When global file locking mode is enabled, the "is_disconnected_mode_off_for_locks" flag is always set to "true". |
| guarantee | guarantee | |
| name | string | FlexCache name |
| origins | array[flexcache_relationship] | |

| Name | Type | Description |
|----------------------|-----------------------------|---|
| path | string | The fully-qualified path in the owning SVM's namespace at which the FlexCache is mounted. The path is case insensitive and must be unique within a SVM's namespace. Path must begin with '/' and must not end with '/'. Only one FlexCache be mounted at any given junction path. |
| prepopulate | prepopulate | FlexCache prepopulate |
| size | integer | Physical size of the FlexCache. The recommended size for a FlexCache is 10% of the origin volume. The minimum FlexCache constituent size is 1GB. |
| svm | svm | FlexCache SVM |
| use_tiered_aggregate | boolean | Specifies whether or not a Fabricpool-enabled aggregate can be used in FlexCache creation. The use_tiered_aggregate is only used when auto-provisioning a FlexCache volume. |
| uuid | string | FlexCache UUID. Unique identifier for the FlexCache. |

job_link

| Name | Type | Description |
|------------------------|------------------------|---|
| _links | _links | |
| uuid | string | The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|-----------|--|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Delete a FlexCache volume

```
DELETE /storage/flexcache/flexcaches/{uuid}
```

Introduced In: 9.6

Deletes a FlexCache. If a FlexCache volume is online, it is offlined before deletion.

Related ONTAP commands

- `volume flexcache delete`

Learn more

- [DOC /storage/flexcache/flexcaches](#)

Parameters

| Name | Type | In | Required | Description |
|------|--------|------|----------|-------------------------------------|
| uuid | string | path | True | Unique identifier of the FlexCache. |

| Name | Type | In | Required | Description |
|----------------|---------|-------|----------|--|
| return_timeout | integer | query | False | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> • Default value: 1 • Max value: 120 • Min value: 0 |

Response

Status: 202, Accepted

| Name | Type | Description |
|------|--------------------------|-------------|
| job | job_link | |

Example response

```
{
  "job": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "uuid": "string"
  }
}
```

Error

Status: Default

ONTAP Error Response Codes

| Error Code | Description |
|------------|---|
| 66846879 | The specified volume UUID is not a FlexCache volume |
| 66846731 | Failed to delete the FlexCache volume |
| 524546 | Failed to delete the FlexCache volume because the FlexCache volume is not unmounted |

| Name | Type | Description |
|-------|-------|-------------|
| error | error | |

Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

job_link

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| uuid | string | The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|-----------|--|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Retrieve attributes of the FlexCache volume in the cluster

GET /storage/flexcache/flexcaches/{uuid}

Introduced In: 9.6

Retrieves attributes of the FlexCache in the cluster.

Expensive properties

There is an added cost to retrieving values for these properties. They are included by default in GET. The recommended method to use this API is to filter and retrieve only the required fields. See [Requesting specific fields](#) to learn more.

- `origins.ip_address` - IP address of origin.
- `origins.size` - Physical size of origin.
- `origins.state` - State of origin.
- `size` - Physical size of FlexCache.
- `guarantee.type` - Space guarantee style of FlexCache.
- `aggregates.name` or `aggregates.uuid` - Name or UUID of aggregate of FlexCache volume.
- `path` - Fully-qualified path of the owning SVM's namespace where the FlexCache is mounted.

Related ONTAP commands

- `volume flexcache show`

Learn more

- [DOC /storage/flexcache/flexcaches](#)

Parameters

| Name | Type | In | Required | Description |
|---------------------|---------------|-------|----------|---------------------------------|
| <code>uuid</code> | string | path | True | Unique identifier of FlexCache. |
| <code>fields</code> | array[string] | query | False | Specify the fields to return. |

Response

```
Status: 200, Ok
```

| Name | Type | Description |
|-------------------------|-------------------------------------|-------------|
| <code>_links</code> | _links | |
| <code>aggregates</code> | array[aggregates] | |

| Name | Type | Description |
|-----------------------------|---|---|
| constituents_per_aggregate | integer | Number of FlexCache constituents per aggregate when the 'aggregates' field is mentioned. |
| dr_cache | boolean | If set to true, a DR cache is created. |
| global_file_locking_enabled | boolean | Specifies whether or not a FlexCache volume has global file locking mode enabled. Global file locking mode is a mode where protocol read locking semantics are enforced across all FlexCaches and origins of a FlexCache volume. When global file locking mode is enabled, the "is_disconnected_mode_off_for_locks" flag is always set to "true". |
| guarantee | guarantee | |
| name | string | FlexCache name |
| origins | array[flexcache_relationship] | |
| path | string | The fully-qualified path in the owning SVM's namespace at which the FlexCache is mounted. The path is case insensitive and must be unique within a SVM's namespace. Path must begin with '/' and must not end with '/'. Only one FlexCache be mounted at any given junction path. |
| prepopulate | prepopulate | FlexCache prepopulate |
| size | integer | Physical size of the FlexCache. The recommended size for a FlexCache is 10% of the origin volume. The minimum FlexCache constituent size is 1GB. |
| svm | svm | FlexCache SVM |

| Name | Type | Description |
|----------------------|-------------|---|
| use_tiered_aggregate | boolean | Specifies whether or not a Fabricpool-enabled aggregate can be used in FlexCache creation. The use_tiered_aggregate is only used when auto-provisioning a FlexCache volume. |
| uuid | string | FlexCache UUID. Unique identifier for the FlexCache. |

Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "aggregates": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "aggr1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "guarantee": {
    "type": "volume"
  },
  "name": "vol1",
  "origins": {
    "cluster": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "cluster1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "create_time": "2018-06-04T19:00:00Z",
    "ip_address": "10.10.10.7",
    "size": 0,
    "state": "error",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "volume": {
      "_links": {
```

```

    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "volume1",
  "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
},
"path": "/user/my_fc",
"prepopulate": {
  "dir_paths": {
  },
  "exclude_dir_paths": {
  }
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}

```

Error

Status: Default, Error

| Name | Type | Description |
|-------|-----------------------|-------------|
| error | error | |

Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

aggregates

Aggregate

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

guarantee

| Name | Type | Description |
|------|--------|--|
| type | string | The type of space guarantee of this volume in the aggregate. |

cluster

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

svm

| Name | Type | Description |
|--------|------------------------|-----------------------------------|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

volume

| Name | Type | Description |
|--------|------------------------|--|
| _links | _links | |
| name | string | The name of the volume. |
| uuid | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> • example: 028baa66-41bd-11e9-81d5-00a0986138f7 • Introduced in: 9.6 |

flexcache_relationship

| Name | Type | Description |
|-------------|-------------------------|--|
| cluster | cluster | |
| create_time | string | Creation time of the relationship. |
| ip_address | string | Cluster management IP of the remote cluster. |
| size | integer | Size of the remote volume. |
| state | string | Volume state |
| svm | svm | |
| volume | volume | |

prepopulate

FlexCache prepopulate

| Name | Type | Description |
|-------------------|---------------|--|
| dir_paths | array[string] | |
| exclude_dir_paths | array[string] | |
| recurse | boolean | Specifies whether or not the prepopulate action should search through the <code>dir_paths</code> recursively. If not set, the default value <code>true</code> is used. |

svm

FlexCache SVM

| Name | Type | Description |
|---------------------|------------------------|-----------------------------------|
| <code>_links</code> | _links | |
| <code>name</code> | string | The name of the SVM. |
| <code>uuid</code> | string | The unique identifier of the SVM. |

error_arguments

| Name | Type | Description |
|----------------------|--------|------------------|
| <code>code</code> | string | Argument code |
| <code>message</code> | string | Message argument |

error

| Name | Type | Description |
|------------------------|--|---|
| <code>arguments</code> | array[error_arguments] | Message arguments |
| <code>code</code> | string | Error code |
| <code>message</code> | string | Error message |
| <code>target</code> | string | The target parameter that caused the error. |

Pre-populate a FlexCache volume in the cluster

```
PATCH /storage/flexcache/flexcaches/{uuid}
```

Introduced In: 9.8

Prepopulates a FlexCache volume in the cluster.

Required properties

- `uuid` - FlexCache volume UUID.
- `prepopulate.dir_paths` - List of directory-paths to be prepopulated for the FlexCache volume.

Recommended optional properties

- `prepopulate.exclude_dir_paths` - List of directory-paths to be excluded from prepopulation for the

FlexCache volume.

Default property values

If not specified in PATCH, the following default property value is assigned:

- `prepopulate.recurse` - Default value is "true".

Related ONTAP commands

- `volume flexcache prepopulate start`

Learn more

- [DOC /storage/flexcache/flexcaches](#)

Parameters

| Name | Type | In | Required | Description |
|------|--------|------|----------|--|
| uuid | string | path | True | Unique identifier of the FlexCache volume. |

| Name | Type | In | Required | Description |
|----------------|---------|-------|----------|--|
| return_timeout | integer | query | False | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> • Default value: 1 • Max value: 120 • Min value: 0 |

Request Body

| Name | Type | Description |
|----------------------------|-------------------------------------|--|
| _links | _links | |
| aggregates | array[aggregates] | |
| constituents_per_aggregate | integer | Number of FlexCache constituents per aggregate when the 'aggregates' field is mentioned. |
| dr_cache | boolean | If set to true, a DR cache is created. |

| Name | Type | Description |
|-----------------------------|---|---|
| global_file_locking_enabled | boolean | Specifies whether or not a FlexCache volume has global file locking mode enabled. Global file locking mode is a mode where protocol read locking semantics are enforced across all FlexCaches and origins of a FlexCache volume. When global file locking mode is enabled, the "is_disconnected_mode_off_for_locks" flag is always set to "true". |
| guarantee | guarantee | |
| name | string | FlexCache name |
| origins | array[flexcache_relationship] | |
| path | string | The fully-qualified path in the owning SVM's namespace at which the FlexCache is mounted. The path is case insensitive and must be unique within a SVM's namespace. Path must begin with '/' and must not end with '/'. Only one FlexCache be mounted at any given junction path. |
| prepopulate | prepopulate | FlexCache prepopulate |
| size | integer | Physical size of the FlexCache. The recommended size for a FlexCache is 10% of the origin volume. The minimum FlexCache constituent size is 1GB. |
| svm | svm | FlexCache SVM |
| use_tiered_aggregate | boolean | Specifies whether or not a Fabricpool-enabled aggregate can be used in FlexCache creation. The use_tiered_aggregate is only used when auto-provisioning a FlexCache volume. |
| uuid | string | FlexCache UUID. Unique identifier for the FlexCache. |

Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "aggregates": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "aggr1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "guarantee": {
    "type": "volume"
  },
  "name": "vol1",
  "origins": {
    "cluster": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "cluster1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "create_time": "2018-06-04T19:00:00Z",
    "ip_address": "10.10.10.7",
    "size": 0,
    "state": "error",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "volume": {
      "_links": {
```



```

    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "volume1",
  "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
},
"path": "/user/my_fc",
"prepopulate": {
  "dir_paths": {
  },
  "exclude_dir_paths": {
  }
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}

```

Response

Status: 202, Accepted

| Name | Type | Description |
|------|--------------------------|-------------|
| job | job_link | |

Example response

```
{
  "job": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "uuid": "string"
  }
}
```

Error

Status: Default

ONTAP Error Response Codes

| Error Code | Description |
|------------|---|
| 66846922 | FlexCache volume does not exist in the SVM |
| 66846923 | Failed to prepopulate FlexCache volume because the origin volume is not reachable |
| 66846924 | FlexCache volume is offline |
| 66846925 | FlexCache volume is not mounted or the junction-path is not active |
| 66846926 | The junction-path of FlexCache volume is not active |
| 66846927 | FlexCache volume does not have an origin volume |
| 66846928 | FlexCache volume does not exist |
| 66846929 | Using FlexCache prepopulate requires an effective cluster version of 9.8.0 or later |
| 66846930 | Using FlexCache prepopulate in a MetroCluster configuration requires an effective cluster version of 9.8.0 or later on both the local and remote clusters |
| 66846931 | Internal Error. FlexCache prepopulate job queue failed. Wait a few minutes, and then try the operation again |
| 66846936 | Failed to lookup root file handle for origin of FlexCache volume. Wait a few minutes, and then try the operation again |

| Error Code | Description |
|------------|--|
| 66846937 | Internal error. Failed to initialize thread |
| 66846939 | Internal error. Failed to get the MSID of the origin volume for FlexCache volume |
| 66846943 | Failed to prepopulate because dir_path does not exist |
| 66846944 | Failed to get root constituent for FlexCache volume |
| 66846945 | Origin of FlexCache volume is not mounted or the junction-path is not active |
| 66846946 | The junction-path of origin of FlexCache volume is not active |
| 66846947 | FlexCache prepopulate job for FlexCache volume already exists |
| 66846948 | FlexCache prepopulate job for FlexCache volume could not be queued because the node is offline |

| Name | Type | Description |
|-------|-------|-------------|
| error | error | |

Example error

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

aggregates

Aggregate

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

guarantee

| Name | Type | Description |
|------|--------|--|
| type | string | The type of space guarantee of this volume in the aggregate. |

cluster

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

svm

| Name | Type | Description |
|--------|------------------------|-----------------------------------|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

volume

| Name | Type | Description |
|--------|------------------------|--|
| _links | _links | |
| name | string | The name of the volume. |
| uuid | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> • example: 028baa66-41bd-11e9-81d5-00a0986138f7 • Introduced in: 9.6 |

flexcache_relationship

| Name | Type | Description |
|-------------|-------------------------|--|
| cluster | cluster | |
| create_time | string | Creation time of the relationship. |
| ip_address | string | Cluster management IP of the remote cluster. |
| size | integer | Size of the remote volume. |
| state | string | Volume state |
| svm | svm | |
| volume | volume | |

prepopulate

FlexCache prepopulate

| Name | Type | Description |
|-------------------|---------------|--|
| dir_paths | array[string] | |
| exclude_dir_paths | array[string] | |
| recurse | boolean | Specifies whether or not the prepopulate action should search through the <code>dir_paths</code> recursively. If not set, the default value <code>true</code> is used. |

svm

FlexCache SVM

| Name | Type | Description |
|--------|------------------------|-----------------------------------|
| _links | _links | |
| name | string | The name of the SVM. |
| uuid | string | The unique identifier of the SVM. |

flexcache

Defines the cache endpoint of FlexCache.

| Name | Type | Description |
|-----------------------------|---|---|
| _links | _links | |
| aggregates | array[aggregates] | |
| constituents_per_aggregate | integer | Number of FlexCache constituents per aggregate when the 'aggregates' field is mentioned. |
| dr_cache | boolean | If set to true, a DR cache is created. |
| global_file_locking_enabled | boolean | Specifies whether or not a FlexCache volume has global file locking mode enabled. Global file locking mode is a mode where protocol read locking semantics are enforced across all FlexCaches and origins of a FlexCache volume. When global file locking mode is enabled, the "is_disconnected_mode_off_for_locks" flag is always set to "true". |
| guarantee | guarantee | |
| name | string | FlexCache name |
| origins | array[flexcache_relationship] | |

| Name | Type | Description |
|----------------------|-----------------------------|---|
| path | string | The fully-qualified path in the owning SVM's namespace at which the FlexCache is mounted. The path is case insensitive and must be unique within a SVM's namespace. Path must begin with '/' and must not end with '/'. Only one FlexCache be mounted at any given junction path. |
| prepopulate | prepopulate | FlexCache prepopulate |
| size | integer | Physical size of the FlexCache. The recommended size for a FlexCache is 10% of the origin volume. The minimum FlexCache constituent size is 1GB. |
| svm | svm | FlexCache SVM |
| use_tiered_aggregate | boolean | Specifies whether or not a Fabricpool-enabled aggregate can be used in FlexCache creation. The use_tiered_aggregate is only used when auto-provisioning a FlexCache volume. |
| uuid | string | FlexCache UUID. Unique identifier for the FlexCache. |

job_link

| Name | Type | Description |
|------------------------|------------------------|---|
| _links | _links | |
| uuid | string | The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|-----------|--|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.