



# Manage share-level ACL

ONTAP 9.13.1 REST API reference

NetApp  
August 29, 2024

# Table of Contents

- Manage share-level ACL ..... 1
  - Protocols CIFS shares svm.uuid share acs endpoint overview ..... 1
  - Retrieve a share-level ACL on a CIFS share ..... 5
  - Create a share-level ACL on a CIFS share ..... 11
  - Delete a share-level ACL on a CIFS share ..... 16
  - Retrieve a share-level ACL on a CIFS share for a user or group ..... 19
  - Update a share-level ACL on a CIFS share ..... 23

# Manage share-level ACL

## Protocols CIFS shares svm.uuid share acls endpoint overview

### Overview

Access to files and folders can be secured over a network by configuring share access control lists (ACLs) on CIFS shares. Share-level ACLs can be configured by using either Windows users and groups or UNIX users and groups. A share-level ACL consists of a list of access control entries (ACEs). Each ACE contains a user or group name and a set of permissions that determines user or group access to the share, regardless of the security style of the volume or qtree containing the share.

When an SMB user tries to access a share, ONTAP checks the share-level ACL to determine whether access should be granted. A share-level ACL only restricts access to files in the share; it never grants more access than the file level ACLs.

### Examples

#### Creating a CIFS share ACL

To create a share ACL for a CIFS share, use the following API. Note the *return\_records=true* query parameter used to obtain the newly created entry in the response.

---

```
# The API:
POST /api/protocols/cifs/shares{svm.uuid}/{share}/acls

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-
11e8-a96e-0050568ea3cb/sh1/acls?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{
\"permission\": \"no_access\", \"type\": \"windows\", \"user_or_group\":
\"root\"}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "name": "vs1"
      },
      "user_or_group": "root",
      "type": "windows",
      "permission": "no_access"
    }
  ]
}
```

---

**Retrieving all CIFS shares ACLs for a specific CIFS share for a specific SVM in the cluster**

---

```
# The API:
GET /api/protocols/cifs/shares/{svm.uuid}/{share}/acls

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/sh1/acls?fields=*&return_records=true&return_timeout=15" -H "accept: application/json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1"
      },
      "share": "sh1",
      "user_or_group": "Everyone",
      "type": "windows",
      "permission": "full_control"
    },
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1"
      },
      "share": "sh1",
      "user_or_group": "root",
      "type": "windows",
      "permission": "no_access"
    }
  ],
  "num_records": 2
}
```

---

**Retrieving a CIFS share ACLs for a user or a group of type Windows or type UNIX on a CIFS share for a specific SVM**

---

```

# The API:
GET
/api/protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/sh1/acls/everyone/windows" -H "accept: application/json"

# The response:
{
  "svm": {
    "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
    "name": "vs1"
  },
  "share": "sh1",
  "user_or_group": "everyone",
  "type": "windows",
  "permission": "full_control"
}

```

### Updating a CIFS share ACLs of a user or group on a CIFS share for a specific SVM

The CIFS share ACL being modified is identified by the UUID of its SVM, the CIFS share name, user or group name and the type of the user or group.

```

# The API:
PATCH
/api/protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/sh1/acls/everyone/windows" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"permission\": \"no_access\"}"

```

### Removing a CIFS share ACLs of a user or group on a CIFS Share for a specific SVM

The CIFS share ACL being removed is identified by the UUID of its SVM, the CIFS share name, user or group name and the type of the user or group.

```
# The API:
DELETE
/api/protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/sh1/acls/everyone/windows" -H "accept: application/json"
```

## Retrieve a share-level ACL on a CIFS share

GET /protocols/cifs/shares/{svm.uuid}/{share}/acls

**Introduced In:** 9.6

Retrieves the share-level ACL on a CIFS share.

### Related ONTAP commands

- `vserver cifs share access-control show`

### Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

### Parameters

Name	Type	In	Required	Description
share	string	path	True	CIFS Share Name
permission	string	query	False	Filter by permission
type	string	query	False	Filter by type
svm.name	string	query	False	Filter by svm.name <ul style="list-style-type: none"><li>• Introduced in: 9.9</li></ul>
sid	string	query	False	Filter by sid <ul style="list-style-type: none"><li>• Introduced in: 9.13</li></ul>

Name	Type	In	Required	Description
user_or_group	string	query	False	Filter by user_or_group
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok



Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[cifs_share_acl]	

### Example response

```

{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "num_records": 1,
  "records": [
    {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "permission": "string",
      "share": "string",
      "sid": "S-1-5-21-256008430-3394229847-3930036330-1001",
      "svm": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      },
      "type": "string",
      "user_or_group": "ENGDOMAIN\\ad_user"
    }
  ]
}

```

## Error

Status: Default, Error

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	

Name	Type	Description
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"> <li>• no_access - User does not have CIFS share access</li> <li>• read - User has only read access</li> <li>• change - User has change access</li> <li>• full_control - User has full_control access</li> </ul>
share	string	CIFS share name
sid	string	Specifies the user or group secure identifier (SID).
svm	<a href="#">svm</a>	
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Create a share-level ACL on a CIFS share

POST /protocols/cifs/shares/{svm.uuid}/{share}/acls

**Introduced In:** 9.6

Creates a share-level ACL on a CIFS share.

### Required properties

- `svm.uuid` or `svm.name` - Existing SVM in which to create the share acl.
- `share` - Existing CIFS share in which to create the share acl.
- `user_or_group` - Existing user or group name for which the acl is added on the CIFS share.
- `permission` - Access rights that a user or group has on the defined CIFS share.

### Default property values

- `type` - *windows*

### Related ONTAP commands

- `vserver cifs share access-control create`

### Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

### Parameters

Name	Type	In	Required	Description
share	string	path	True	CIFS Share Name

Name	Type	In	Required	Description
return_records	boolean	query	False	The default is false. If set to true, the records are returned. <ul style="list-style-type: none"> <li>• Default value:</li> </ul>
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Request Body

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"> <li>• no_access - User does not have CIFS share access</li> <li>• read - User has only read access</li> <li>• change - User has change access</li> <li>• full_control - User has full_control access</li> </ul>
share	string	CIFS share name
sid	string	Specifies the user or group secure identifier (SID).
svm	<a href="#">svm</a>	
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>

Name	Type	Description
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

### Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "permission": "string",
  "share": "string",
  "sid": "S-1-5-21-256008430-3394229847-3930036330-1001",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"type": "string",
"user_or_group": "ENGDOMAIN\\ad_user"
}
```

### Response

Status: 201, Created

### Headers

Name	Description	Type
Location	Useful for tracking the resource location	string

### Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
655470	Failed to create share ACL because the share does not exist
655446	Failed to create share ACL because the specified Windows user/group does not exist
4849678	Failed to create share ACL because the specified UNIX user/group does not exist

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions



## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>
share	string	CIFS share name
sid	string	Specifies the user or group secure identifier (SID).

Name	Type	Description
svm	<a href="#">svm</a>	
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Delete a share-level ACL on a CIFS share

```
DELETE /protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}
```

**Introduced In:** 9.6

Deletes a share-level ACL on a CIFS share.

## Related ONTAP commands

- `vserver cifs share access-control delete`

## Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

## Parameters

Name	Type	In	Required	Description
share	string	path	True	Share name
user_or_group	string	path	True	User or group name
type	string	path	True	User or group type
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Response

```
Status: 200, Ok
```

## Error

```
Status: Default, Error
```

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

### See Definitions

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

# Retrieve a share-level ACL on a CIFS share for a user or group

GET /protocols/cifs/shares/{svm.uuid}/{share}/acls/{user\_or\_group}/{type}

Introduced In: 9.6

Retrieves the share-level ACL on CIFS share for a specified user or group.

## Related ONTAP commands

- `vserver cifs share access-control show`

## Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

## Parameters

Name	Type	In	Required	Description
share	string	path	True	Share name
user_or_group	string	path	True	User or group name
type	string	path	True	User or group type
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	

Name	Type	Description
permission	string	<p>Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed:</p> <ul style="list-style-type: none"> <li>• no_access - User does not have CIFS share access</li> <li>• read - User has only read access</li> <li>• change - User has change access</li> <li>• full_control - User has full_control access</li> </ul>
share	string	CIFS share name
sid	string	Specifies the user or group secure identifier (SID).
svm	svm	
type	string	<p>Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed:</p> <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "permission": "string",
  "share": "string",
  "sid": "S-1-5-21-256008430-3394229847-3930036330-1001",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "type": "string",
  "user_or_group": "ENGDOMAIN\\ad_user"
}
```

## Error

Status: Default, Error

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions



## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Update a share-level ACL on a CIFS share

```
PATCH /protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}
```

**Introduced In:** 9.6

Updates a share-level ACL on a CIFS share.

## Related ONTAP commands

- `vserver cifs share access-control modify`

## Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

## Parameters

Name	Type	In	Required	Description
share	string	path	True	Share name
user_or_group	string	path	True	User or group name
type	string	path	True	User or group type
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Request Body

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• <code>no_access</code> - User does not have CIFS share access</li><li>• <code>read</code> - User has only read access</li><li>• <code>change</code> - User has change access</li><li>• <code>full_control</code> - User has full_control access</li></ul>
share	string	CIFS share name

Name	Type	Description
sid	string	Specifies the user or group secure identifier (SID).
svm	<a href="#">svm</a>	
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

### Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "permission": "string",
  "share": "string",
  "sid": "S-1-5-21-256008430-3394229847-3930036330-1001",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"type": "string",
"user_or_group": "ENGDOMAIN\\ad_user"
}
```

## Response

Status: 200, Ok

## Error

Status: Default

### ONTAP Error Response Codes

Error Code	Description
655516	The share ACL does not exist for given user and share

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>
share	string	CIFS share name
sid	string	Specifies the user or group secure identifier (SID).

Name	Type	Description
svm	<a href="#">svm</a>	
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.