

Manage protocols S3 services

ONTAP 9.14.1 REST API reference

NetApp June 13, 2024

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-9141/ontap/protocols_s3_services_endpoint_overview.html on June 13, 2024. Always check docs.netapp.com for the latest.

Table of Contents

/lanage protocols S3 services	1
Protocols S3 services endpoint overview.	1
Retrieve the S3 server configuration for all SVMs	. 10
Create S3 server, users, and buckets configurations.	. 56
Delete the S3 server configuration for an SVM	. 89
Retrieve the S3 server configuration for an SVM	. 94
Update the S3 server configuration for an SVM.	123

Manage protocols S3 services

Protocols S3 services endpoint overview

Overview

An S3 server is an object store server that is compatible with the Amazon S3 protocol. In the initial version, only a subset of the protocol features necessary to support Fabric Pool capacity tier usecases are implemented. S3 server allows you to store objects in ONTAP using Amazon S3 protocol. This feature can be used as a target object store server for ONTAP FabricPools.

Performance monitoring

Performance of the SVM can be monitored by the metric.* and statistics.* properties. These show the performance of the SVM in terms of IOPS, latency and throughput. The metric.* properties denote an average whereas statistics.* properties denote a real-time monotonically increasing value aggregated across all nodes.

Examples

Retrieving all of the S3 configurations

```
# The API:
/api/protocols/s3/services
# The call:
curl -X GET "https://<mgmt-
ip>/api/protocols/s3/services?fields=*&return records=true&return timeout=
15" -H "accept: application/json"
# The response:
{
"records": [
  {
    "svm": {
      "uuid": "cf90b8f2-8071-11e9-8190-0050568eae21",
      "name": "vs2"
    },
    "name": "vs1",
    "comment": "S3 server",
    "enabled": false,
  },
  {
    "svm": {
      "uuid": "d7f1219c-7f8e-11e9-9124-0050568eae21",
      "name": "vs1"
    },
```

```
"name": "Server-1",
  "comment": "S3 server",
  "enabled": true,
  "buckets": [
   {
      "uuid": "e08665af-8114-11e9-8190-0050568eae21",
      "name": "bucket-1",
      "volume": {
        "name": "fg oss 1559026220",
       "uuid": "de146bff-8114-11e9-8190-0050568eae21"
      },
      "size": 209715200,
      "logical used size": 157286400,
      "encryption": {
       "enabled": false
      },
      "comment": "s3 bucket"
    },
    {
      "uuid": "fb1912ef-8114-11e9-8190-0050568eae21",
      "name": "bucket-2",
      "volume": {
        "name": "fg oss 1559026269",
        "uuid": "f9b1cdd0-8114-11e9-8190-0050568eae21"
      },
      "size": 1048576000,
      "logical used size": 78643200,
      "encryption": {
       "enabled": false
      },
      "comment": "s3 bucket"
   }
 ],
  "users": [
   {
      "name": "user-1",
      "comment": "S3 user",
      "access key": "KEOYV21G156K8AB4ZISH"
   },
    {
      "name": "user-2",
      "comment": "",
      "access key": "ANOYV22L156K8AB4ZISB"
   }
 ]
}
```

```
],
"num_records": 2
}
```

Retrieving all S3 configurations for a particular SVM

```
# The API:
/api/protocols/s3/services/{svm.uuid}
# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/s3/services/24c2567a-f269-
11e8-8852-0050568e5298?fields=*" -H "accept: application/json"
# The response:
{
"svm": {
  "uuid": "d7f1219c-7f8e-11e9-9124-0050568eae21",
 "name": "vs1"
},
"name": "Server-1",
"comment": "S3 server",
"enabled": true,
"buckets": [
  {
    "uuid": "e08665af-8114-11e9-8190-0050568eae21",
    "name": "bucket-1",
    "volume": {
      "name": "fg oss 1559026220",
      "uuid": "de146bff-8114-11e9-8190-0050568eae21"
    },
    "size": 209715200,
    "logical used size": 157286400,
    "encryption": {
      "enabled": false
    },
    "comment": "s3 bucket",
    "policy": {
      "statements": [
        {
          "effect": "deny",
          "actions": [
            "*Object"
          ],
          "principals": [
            "mike"
```

```
],
          "resources": [
            "bucket-1/policy-docs/*",
            "bucket-1/confidential-*"
          ],
          "sid": "DenyAccessToGetPutDeleteObjectForMike"
        },
        {
          "effect": "allow",
          "actions": [
           "GetObject"
          ],
          "principals": [
            " * "
          ],
          "resources": [
           "bucket-1/readme"
          ],
          "sid": "AccessToGetObjectForAnonymousUser"
        }
      1
    }
  },
  {
    "uuid": "fb1912ef-8114-11e9-8190-0050568eae21",
    "name": "bucket-2",
    "volume": {
      "name": "fg oss 1559026269",
     "uuid": "f9b1cdd0-8114-11e9-8190-0050568eae21"
    },
    "size": 1677721600,
    "logical used size": 1075838976,
    "encryption": {
      "enabled": false
    },
    "comment": "s3 bucket"
 }
],
"users": [
 {
    "name": "user-1",
    "comment": "s3 user",
    "access key": "KEOYV21G156K8AB4ZISH"
  },
  {
    "name": "user-2",
```

```
"comment": "",
   "access_key": "ANOYV22L156K8AB4ZISB"
}
]
}
```

Creating an S3 server, users, and buckets configurations with required fields specified

```
# The API:
/api/protocols/s3/services
# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/s3/services" -H "accept:
application/hal+json" -H "Content-Type: application/json" -d "{
\"buckets\": [ { \"name\": \"bucket-1\" }, { \"name\": \"bucket-2\" } ],
\"enabled\": true, \"name\": \"Server-1\", \"svm\": { \"uuid\":
\"d49ef663-7f8e-11e9-9b2c-0050568e4594\" }, \"users\": [ { \"name\":
\"user-1\" }, { \"name\": \"user-2\" } ]}"
# The response:
HTTP/1.1 201 Created
Date: Fri, 31 May 2019 08:44:16 GMT
Server: libzapid-httpd
X-Content-Type-Options: nosniff
Cache-Control: no-cache, no-store, must-revalidate
Location: /api/protocols/s3/services/
Content-Length: 623
Content-Type: application/hal+json
{
"num records": 1,
"records": [
  {
    "users": [
      {
        "name": "user-1",
        "access key": "KEOYV21G156K8AB4ZISH",
        "secret key": "fu9PD3gWxrTZWi1Dru TzNZUIncJ Qa01st3NNhA"
      },
      {
        "name": "user-2",
        "access key": "ANOYV22L156K8AB4ZISB",
        "secret key": "YCmjAnPpnqZzyV40VRbbswdX88 96X1qb6453Y"
      }
    ],
    "job": {
```

```
"uuid": "f51675dd-820a-11e9-a762-0050568e4594",
    "_links": {
        "self": {
            "href": "/api/cluster/jobs/f51675dd-820a-11e9-a762-0050568e4594"
        }
    }
    },
    "_links": {
        "self": {
            "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "self": {
             "href": "/api/protocols/s3/services/"
            }
        }
        }
    }
}
```

Creating an S3 server, users, and buckets configurations

```
# The API:
/api/protocols/s3/services
# The call:
curl -X POST "https://<mqmt-ip>/api/protocols/s3/services" -H "accept:
application/hal+json" -H "Content-Type: application/json" -d "{
\"buckets\": [ { \"aggregates\": [ { \"name\": \"aggr1\", \"uuid\":
\"1cd8a442-86d1-11e0-ae1c-123478563412\" } ],
\"constituents per aggregate\": 4, \"name\": \"bucket-1\", \"size\":
\"209715200\", \"policy\": { \"statements\": [ { \"actions\": [ \"*\" ],
\"conditions\": [ { \"operator\": \"ip address\", \"source ips\": [
\"1.1.1.1/23\", \"1.2.2.2/20\" ] } ], \"effect\": \"allow\",
\"resources\": [ \"bucket-1\", \"bucket-1*\" ], \"sid\":
\"fullAccessForAllPrincipalsToBucket\"} ] } }, { \"aggregates\": [ {
\"name\": \"aggr1\", \"uuid\": \"1cd8a442-86d1-11e0-ae1c-123478563412\" },
{ \"name\": \"aggr2\", \"uuid\": \"982fc4d0-d1a2-4da4-9c47-5b433f24757d\"}
], \"constituents per aggregate\": 4, \"name\": \"bucket-2\" } ],
\"enabled\": true, \"name\": \"Server-1\", \"svm\": { \"name\": \"vs1\",
\"uuid\": \"d49ef663-7f8e-11e9-9b2c-0050568e4594\" }, \"users\": [ {
\"name\": \"user-1\" }, { \"name\": \"user-2\" } ]}"
# The response:
HTTP/1.1 201 Created
Date: Fri, 31 May 2019 08:44:16 GMT
Server: libzapid-httpd
X-Content-Type-Options: nosniff
Cache-Control: no-cache, no-store, must-revalidate
```

```
Location: /api/protocols/s3/services/
Content-Length: 623
Content-Type: application/hal+json
{
"num records": 1,
"records": [
 {
    "users": [
     {
        "name": "user-1",
        "access key": "KEOYV21G156K8AB4ZISH",
        "secret key": "YCmjAnPpnqZzyV40VRbbswdX88 96X1qb6453Y"
      },
      {
        "name": "user-2",
        "access key": "M4U4922OTO9QGXM3YR2I",
        "secret key": "fu9PD3gWxrTZWi1Dru TzNZUIncJ Qa01st3NNhA"
      }
    ],
    "job": {
      "uuid": "f51675dd-820a-11e9-a762-0050568e4594",
      " links": {
        "self": {
          "href": "/api/cluster/jobs/f51675dd-820a-11e9-a762-0050568e4594"
        }
      }
    },
    " links": {
      "self": {
        "href": "/api/protocols/s3/services/"
      }
    }
 }
]
}
```

Creating an S3 server configuration

```
# The API:
/api/protocols/s3/services
# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/s3/services" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"comment\":
\"S3 server\", \"enabled\": true, \"name\": \"Server-1\", \"svm\": {
\"name\": \"vs1\", \"uuid\": \"db2ec036-8375-11e9-99e1-0050568e3ed9\" } }"
```

Disable s3 server for the specified SVM

```
# The API:
/api/protocols/s3/services/{svm.uuid}
# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/s3/services/03ce5c36-f269-
11e8-8852-0050568e5298" -H "accept: application/json" -H "Content-Type:
application/json" -d "{ \"enabled\": false }"
```

Deleting the S3 server for a specified SVM

```
# The API:
/api/protocols/s3/services/{svm.uuid}
# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/s3/services/a425f10b-ad3b-
11e9-b559-0050568e8222?delete all=false" -H "accept: application/json"
HTTP/1.1 200 OK
Date: Wed, 14 Aug 2019 07:04:24 GMT
Server: libzapid-httpd
X-Content-Type-Options: nosniff
Cache-Control: no-cache, no-store, must-revalidate
Content-Length: 132
Content-Type: application/json
{
"num records": 1,
"records": [
  {
    "job": {
      "uuid": "bf74ba50-be61-11e9-bea8-0050568e8222"
    }
 }
]
}
```

Deleting all of the S3 server configuration for a specified SVM

```
# The API:
/api/protocols/s3/services/{svm.uuid}
# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/s3/services/03ce5c36-f269-
11e8-8852-0050568e5298?delete all=true" -H "accept: application/json"
# The response:
HTTP/1.1 200 OK
Date: Sat, 01 Jun 2019 15:46:39 GMT
Server: libzapid-httpd
X-Content-Type-Options: nosniff
Cache-Control: no-cache, no-store, must-revalidate
Content-Length: 132
Content-Type: application/hal+json
{
"num records": 1,
"records": [
  {
    "job": {
      "uuid": "71eaaf02-8484-11e9-91f7-0050568ebc5f"
    }
  }
1
}
```

Retrieve the S3 server configuration for all SVMs

GET /protocols/s3/services

Introduced In: 9.7

Retrieves the S3 server configuration for all SVMs. Note that in order to retrieve S3 bucket policy conditions, 'fields' option should be set to '**'.

Expensive properties

There is an added computational cost to retrieving values for these properties. They are not included by default in GET results and must be explicitly requested using the fields query parameter. See Requesting specific fields to learn more.

- statistics.*
- metric.*

Related ONTAP commands

• vserver object-store-server show

Learn more

• DOC /protocols/s3/services

Parameters

Name	Туре	In	Required	Description
certificate.uuid	string	query	False	Filter by certificate.uuid • Introduced in: 9.8
certificate.name	string	query	False	Filter by certificate.name • Introduced in: 9.8
statistics.throughput _raw.total	integer	query	False	Filter by statistics.throughput _raw.total • Introduced in: 9.8
statistics.throughput _raw.write	integer	query	False	Filter by statistics.throughput _raw.write • Introduced in: 9.8
statistics.throughput _raw.read	integer	query	False	Filter by statistics.throughput _raw.read • Introduced in: 9.8
statistics.iops_raw.to tal	integer	query	False	Filter by statistics.iops_raw.to tal • Introduced in: 9.8

Name	Туре	In	Required	Description
statistics.iops_raw.ot her	integer	query	False	Filter by statistics.iops_raw.ot her • Introduced in: 9.8
statistics.iops_raw.w rite	integer	query	False	Filter by statistics.iops_raw.w rite • Introduced in: 9.8
statistics.iops_raw.re ad	integer	query	False	Filter by statistics.iops_raw.r ead • Introduced in: 9.8
statistics.timestamp	string	query	False	Filter by statistics.timestamp • Introduced in: 9.8
statistics.latency_ra w.total	integer	query	False	Filter by statistics.latency_ra w.total • Introduced in: 9.8
statistics.latency_ra w.other	integer	query	False	Filter by statistics.latency_ra w.other • Introduced in: 9.8
statistics.latency_ra w.write	integer	query	False	Filter by statistics.latency_ra w.write • Introduced in: 9.8

Name	Туре	In	Required	Description
statistics.latency_ra w.read	integer	query	False	Filter by statistics.latency_ra w.read • Introduced in: 9.8
statistics.status	string	query	False	Filter by statistics.status • Introduced in: 9.8
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name
enabled	boolean	query	False	Filter by enabled
default_win_user	string	query	False	Filter by default_win_user • Introduced in: 9.12
metric.latency.total	integer	query	False	Filter by metric.latency.total • Introduced in: 9.8
metric.latency.other	integer	query	False	Filter by metric.latency.other • Introduced in: 9.8
metric.latency.write	integer	query	False	Filter by metric.latency.write • Introduced in: 9.8
metric.latency.read	integer	query	False	Filter by metric.latency.read • Introduced in: 9.8

Name	Туре	In	Required	Description
metric.status	string	query	False	Filter by metric.status • Introduced in: 9.8
metric.throughput.tot al	integer	query	False	Filter by metric.throughput.tot al • Introduced in: 9.8
metric.throughput.wri te	integer	query	False	Filter by metric.throughput.wr ite • Introduced in: 9.8
metric.throughput.re ad	integer	query	False	Filter by metric.throughput.re ad • Introduced in: 9.8
metric.iops.total	integer	query	False	Filter by metric.iops.total • Introduced in: 9.8
metric.iops.other	integer	query	False	Filter by metric.iops.other • Introduced in: 9.8
metric.iops.write	integer	query	False	Filter by metric.iops.write • Introduced in: 9.8

Name	Туре	In	Required	Description
metric.iops.read	integer	query	False	Filter by metric.iops.read • Introduced in: 9.8
metric.timestamp	string	query	False	Filter by metric.timestamp • Introduced in: 9.8
metric.duration	string	query	False	Filter by metric.duration • Introduced in: 9.8
default_unix_user	string	query	False	Filter by default_unix_user • Introduced in: 9.12
buckets.role	string	query	False	Filter by buckets.role Introduced in: 9.10
buckets.logical_used _size	integer	query	False	Filter by buckets.logical_use d_size
buckets.comment	string	query	False	Filter by buckets.comment • maxLength: 256 • minLength: 0
buckets.retention.def ault_period	string	query	False	Filter by buckets.retention.de fault_period • Introduced in: 9.14

Name	Туре	In	Required	Description
buckets.retention.mo de	string	query	False	Filter by buckets.retention.m ode • Introduced in: 9.14
buckets.name	string	query	False	Filter by buckets.name • maxLength: 63 • minLength: 3
buckets.versioning_s tate	string	query	False	Filter by buckets.versioning_ state • Introduced in: 9.11
buckets.type	string	query	False	Filter by buckets.type • Introduced in: 9.12
buckets.allowed	boolean	query	False	Filter by buckets.allowed • Introduced in: 9.12
buckets.uuid	string	query	False	Filter by buckets.uuid
buckets.qos_policy.u uid	string	query	False	Filter by buckets.qos_policy. uuid • Introduced in: 9.8

Name	Туре	In	Required	Description
buckets.qos_policy. max_throughput_mb ps	integer	query	False	Filter by buckets.qos_policy. max_throughput_mb ps • Introduced in: 9.8 • Max value: 4194303 • Min value: 0
buckets.qos_policy.n ame	string	query	False	Filter by buckets.qos_policy. name • Introduced in: 9.8
buckets.qos_policy. max_throughput_iop s	integer	query	False	Filter by buckets.qos_policy. max_throughput_iop s • Introduced in: 9.8 • Max value: 2147483647 • Min value: 0
buckets.qos_policy. min_throughput_iops	integer	query	False	Filter by buckets.qos_policy. min_throughput_iop s • Introduced in: 9.8 • Max value: 2147483647 • Min value: 0

Name	Туре	In	Required	Description
buckets.qos_policy. min_throughput_mb ps	integer	query	False	Filter by buckets.qos_policy. min_throughput_mb ps • Introduced in: 9.8 • Max value: 4194303 • Min value: 0
buckets.size	integer	query	False	Filter by buckets.size • Max value: 6267216278323 2000 • Min value: 199229440
buckets.volume.nam e	string	query	False	Filter by buckets.volume.nam e
buckets.volume.uuid	string	query	False	Filter by buckets.volume.uuid
buckets.encryption.e nabled	boolean	query	False	Filter by buckets.encryption.e nabled
buckets.policy.state ments.principals	string	query	False	Filter by buckets.policy.state ments.principals • Introduced in: 9.8
buckets.policy.state ments.conditions.deli miters	string	query	False	Filter by buckets.policy.state ments.conditions.del imiters • Introduced in: 9.8

Name	Туре	In	Required	Description
buckets.policy.state ments.conditions.us ernames	string	query	False	Filter by buckets.policy.state ments.conditions.us ernames • Introduced in: 9.8
buckets.policy.state ments.conditions.ma x_keys	integer	query	False	Filter by buckets.policy.state ments.conditions.ma x_keys • Introduced in: 9.8
buckets.policy.state ments.conditions.so urce_ips	string	query	False	Filter by buckets.policy.state ments.conditions.so urce_ips • Introduced in: 9.8
buckets.policy.state ments.conditions.pre fixes	string	query	False	Filter by buckets.policy.state ments.conditions.pre fixes • Introduced in: 9.8
buckets.policy.state ments.conditions.op erator	string	query	False	Filter by buckets.policy.state ments.conditions.op erator • Introduced in: 9.8
buckets.policy.state ments.actions	string	query	False	Filter by buckets.policy.state ments.actions • Introduced in: 9.8

Name	Туре	In	Required	Description
buckets.policy.state ments.effect	string	query	False	Filter by buckets.policy.state ments.effect • Introduced in: 9.8
buckets.policy.state ments.resources	string	query	False	Filter by buckets.policy.state ments.resources • Introduced in: 9.8
buckets.policy.state ments.sid	string	query	False	Filter by buckets.policy.state ments.sid • Introduced in: 9.8 • maxLength: 256 • minLength: 0
buckets.lifecycle_ma nagement.rules.expir ation.expired_object _delete_marker	boolean	query	False	Filter by buckets.lifecycle_ma nagement.rules.expi ration.expired_objec t_delete_marker • Introduced in: 9.13
buckets.lifecycle_ma nagement.rules.expir ation.object_age_da ys	integer	query	False	Filter by buckets.lifecycle_ma nagement.rules.expi ration.object_age_d ays • Introduced in: 9.13
buckets.lifecycle_ma nagement.rules.expir ation.object_expiry_ date	string	query	False	Filter by buckets.lifecycle_ma nagement.rules.expi ration.object_expiry_ date • Introduced in: 9.13

Name	Туре	In	Required	Description
buckets.lifecycle_ma nagement.rules.svm. uuid	string	query	False	Filter by buckets.lifecycle_ma nagement.rules.svm .uuid • Introduced in: 9.14
buckets.lifecycle_ma nagement.rules.svm. name	string	query	False	Filter by buckets.lifecycle_ma nagement.rules.svm .name • Introduced in: 9.14
buckets.lifecycle_ma nagement.rules.ena bled	boolean	query	False	Filter by buckets.lifecycle_ma nagement.rules.ena bled • Introduced in: 9.13
buckets.lifecycle_ma nagement.rules.buck et_name	string	query	False	Filter by buckets.lifecycle_ma nagement.rules.buc ket_name • Introduced in: 9.14 • maxLength: 63 • minLength: 3
buckets.lifecycle_ma nagement.rules.non _current_version_ex piration.non_current _days	integer	query	False	Filter by buckets.lifecycle_ma nagement.rules.non _current_version_ex piration.non_current _days • Introduced in: _9.13

Name	Туре	In	Required	Description
buckets.lifecycle_ma nagement.rules.non _current_version_ex piration.new_non_cu rrent_versions	integer	query	False	Filter by buckets.lifecycle_ma nagement.rules.non _current_version_ex piration.new_non_cu rrent_versions • Introduced in: 9.13
buckets.lifecycle_ma nagement.rules.nam e	string	query	False	Filter by buckets.lifecycle_ma nagement.rules.nam e • Introduced in: 9.13 • maxLength: 256 • minLength: 0
buckets.lifecycle_ma nagement.rules.obje ct_filter.tags	string	query	False	Filter by buckets.lifecycle_ma nagement.rules.obje ct_filter.tags • Introduced in: 9.13
buckets.lifecycle_ma nagement.rules.obje ct_filter.prefix	string	query	False	Filter by buckets.lifecycle_ma nagement.rules.obje ct_filter.prefix • Introduced in: 9.13
buckets.lifecycle_ma nagement.rules.obje ct_filter.size_greater _than	integer	query	False	Filter by buckets.lifecycle_ma nagement.rules.obje ct_filter.size_greater _than • Introduced in: 9.13

Name	Туре	In	Required	Description
buckets.lifecycle_ma nagement.rules.obje ct_filter.size_less_th an	integer	query	False	Filter by buckets.lifecycle_ma nagement.rules.obje ct_filter.size_less_th an • Introduced in: 9.13
buckets.lifecycle_ma nagement.rules.abor t_incomplete_multip art_upload.after_initi ation_days	integer	query	False	Filter by buckets.lifecycle_ma nagement.rules.abor t_incomplete_multip art_upload.after_initi ation_days • Introduced in: 9.13
buckets.lifecycle_ma nagement.rules.uuid	string	query	False	Filter by buckets.lifecycle_ma nagement.rules.uuid • Introduced in: 9.14
buckets.audit_event _selector.access	string	query	False	Filter by buckets.audit_event _selector.access • Introduced in: 9.10
buckets.audit_event _selector.permission	string	query	False	Filter by buckets.audit_event _selector.permission • Introduced in: 9.10
buckets.nas_path	string	query	False	Filter by buckets.nas_path • Introduced in: 9.12
buckets.svm.uuid	string	query	False	Filter by buckets.svm.uuid

Name	Туре	In	Required	Description
buckets.svm.name	string	query	False	Filter by buckets.svm.name
buckets.protection_s tatus.is_protected	boolean	query	False	Filter by buckets.protection_s tatus.is_protected • Introduced in: 9.10
buckets.protection_s tatus.destination.is_ external_cloud	boolean	query	False	Filter by buckets.protection_s tatus.destination.is_ external_cloud • Introduced in: 9.12
buckets.protection_s tatus.destination.is_ ontap	boolean	query	False	Filter by buckets.protection_s tatus.destination.is_ ontap • Introduced in: 9.10
buckets.protection_s tatus.destination.is_c loud	boolean	query	False	Filter by buckets.protection_s tatus.destination.is_ cloud • Introduced in: 9.10
port	integer	query	False	Filter by port Introduced in: 9.8 Max value: 65535 Min value: 1
name	string	query	False	Filter by name maxLength: 253 minLength: 3

Name	Туре	In	Required	Description
is_http_enabled	boolean	query	False	Filter by is_http_enabled • Introduced in: 9.8
comment	string	query	False	Filter by comment maxLength: 256 minLength: 0
secure_port	integer	query	False	 Filter by secure_port Introduced in: 9.8 Max value: 65535 Min value: 1
is_https_enabled	boolean	query	False	Filter by is_https_enabled • Introduced in: 9.8
users.comment	string	query	False	Filter by users.comment • maxLength: 256 • minLength: 0
users.key_expiry_ti me	string	query	False	Filter by users.key_expiry_ti me • Introduced in: 9.14
users.svm.uuid	string	query	False	Filter by users.svm.uuid
users.svm.name	string	query	False	Filter by users.svm.name

Name	Туре	In	Required	Description
users.key_time_to_li ve	string	query	False	Filter by users.key_time_to_li ve • Introduced in: 9.14
users.access_key	string	query	False	Filter by users.access_key
users.name	string	query	False	Filter by users.name • maxLength: 64 • minLength: 1
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned. • Default value: 1
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. • Max value: 120 • Min value: 0 • Default value: 1

Name	Туре	In	Required	Description
order_by	array[string]	query	False	Order results by specified fields and optional [asc

Response

Status: 200, Ok

Name	Туре	Description
_links	collection_links	
num_records	integer	Number of records
records	array[s3_service]	

Example response

{

```
" links": {
  "next": {
   "href": "/api/resourcelink"
 },
 "self": {
  "href": "/api/resourcelink"
 }
},
"num records": 1,
"records": [
  {
    " links": {
     "self": {
       "href": "/api/resourcelink"
      }
    },
    "buckets": [
     {
        "aggregates": [
          {
            " links": {
              "self": {
               "href": "/api/resourcelink"
              }
            },
            "name": "aggr1",
            "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
          }
        ],
        "audit event selector": {
         "access": "string",
         "permission": "string"
        },
        "comment": "S3 bucket.",
        "constituents_per_aggregate": 4,
        "lifecycle management": {
          "rules": [
            {
              " links": {
               "self": {
                 "href": "/api/resourcelink"
                }
              },
```

```
"abort incomplete multipart upload": {
  " links": {
   "self": {
     "href": "/api/resourcelink"
   }
 }
},
"bucket name": "bucket1",
"expiration": {
 " links": {
    "self": {
     "href": "/api/resourcelink"
   }
 },
 "object expiry date": "string"
},
"name": "string",
"non current version expiration": {
 " links": {
   "self": {
     "href": "/api/resourcelink"
    }
  }
},
"object filter": {
 " links": {
   "self": {
     "href": "/api/resourcelink"
   }
  },
 "prefix": "/logs",
 "size greater than": 10240,
  "size less than": 10485760,
  "tags": [
   "project1=projA",
   "project2=projB"
 ]
},
"svm": {
  " links": {
    "self": {
    "href": "/api/resourcelink"
   }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
```

```
},
      "uuid": "414b29a1-3b26-11e9-bd58-0050568ea055"
   }
 ]
},
"logical used size": 0,
"name": "bucket1",
"nas path": "/",
"policy": {
  "statements": [
   {
      "actions": [
       "GetObject",
        "PutObject",
        "DeleteObject",
        "ListBucket"
      ],
      "conditions": [
        {
          "delimiters": [
           "/"
          ],
          "max keys": [
           1000
          ],
          "operator": "ip_address",
          "prefixes": [
           "pref"
          ],
          "source_ips": [
           "1.1.1.1",
          "1.2.2.0/24"
          ],
          "usernames": [
          "user1"
          1
        }
      ],
      "effect": "allow",
      "principals": [
        "user1",
       "group/grp1",
        "nasgroup/group1"
      ],
      "resources": [
        "bucket1",
```

```
"bucket1/*"
      ],
      "sid": "FullAccessToUser1"
    }
  1
},
"qos policy": {
  " links": {
    "self": {
     "href": "/api/resourcelink"
   }
  },
  "max throughput iops": 10000,
  "max throughput mbps": 500,
  "min throughput iops": 2000,
  "min throughput mbps": 500,
  "name": "performance",
 "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"retention": {
  "default period": "P10Y",
 "mode": "governance"
},
"role": "string",
"size": 1677721600,
"storage service level": "value",
"svm": {
  " links": {
   "self": {
      "href": "/api/resourcelink"
   }
  },
  "name": "svm1",
 "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"type": "s3",
"uuid": "414b29a1-3b26-11e9-bd58-0050568ea055",
"versioning state": "enabled",
"volume": {
  " links": {
    "self": {
     "href": "/api/resourcelink"
    }
  },
  "name": "volume1",
  "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
```

```
}
  }
],
"certificate": {
 " links": {
   "self": {
     "href": "/api/resourcelink"
   }
 },
 "name": "string",
 "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"comment": "S3 server",
"default unix user": "string",
"default win user": "string",
"metric": {
 " links": {
   "self": {
     "href": "/api/resourcelink"
   }
 },
  "duration": "PT15S",
  "iops": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "latency": {
   "read": 200,
   "total": 1000,
   "write": 100
 },
 "status": "ok",
 "throughput": {
   "read": 200,
   "total": 1000,
   "write": 100
 },
 "timestamp": "2017-01-25 06:20:13 -0500"
},
"name": "Server-1",
"port": 80,
"secure port": 443,
"statistics": {
  "iops raw": {
   "read": 200,
```

```
"total": 1000,
          "write": 100
        },
        "latency raw": {
         "read": 200,
         "total": 1000,
         "write": 100
        },
        "status": "ok",
        "throughput raw": {
         "read": 200,
         "total": 1000,
         "write": 100
        },
        "timestamp": "2017-01-25 06:20:13 -0500"
      },
      "svm": {
       " links": {
         "self": {
           "href": "/api/resourcelink"
         }
       },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      },
      "users": [
        {
         "access key": "HJAKU28M3SXTE2UXUACV",
          "comment": "S3 user",
          "key expiry time": "2023-12-31 19:00:00 -0500",
          "key time to live": "PT6H3M",
          "name": "user-1",
          "svm": {
            " links": {
             "self": {
               "href": "/api/resourcelink"
             }
            },
            "name": "svm1",
           "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
          }
        }
      1
   }
 ]
}
```

Error

Status: Default, Error

Name	Туре	Description
error	returned_error	

Example error

```
{
    "error": {
        "arguments": [
            {
            "code": "string",
            "message": "string"
            }
        ],
        "code": "4",
        "message": "entry doesn't exist",
        "target": "uuid"
     }
}
```

Definitions
See Definitions

href

Name	Туре	Description
href	string	

collection_links

Name	Туре	Description
next	href	
self	href	

self_link

Name	Туре	Description
self	href	

_links

Name	Туре	Description
self	href	

aggregates

Aggregate

Name	Туре	Description
_links	_links	
name	string	
uuid	string	

audit_event_selector

Audit event selector allows you to specify access and permission types to audit.

Name	Туре	Description
access	string	Specifies read and write access types.
permission	string	Specifies allow and deny permission types.

encryption

Name	Туре	Description
enabled	boolean	Specifies whether encryption is enabled on the bucket. By default, encryption is disabled on a bucket. This field cannot be specified in a POST method.

abort_incomplete_multipart_upload

Specifies a way to perform abort_incomplete_multipart_upload action on filtered objects within a bucket. It cannot be specified with tags.

Name	Туре	Description
_links	_links	
after_initiation_days	integer	Number of days of initiation after which uploads can be aborted.

expiration

Specifies a way to perform expiration action on filtered objects within a bucket.

Name	Туре	Description
_links	_links	
expired_object_delete_marker	boolean	Cleanup object delete markers.
object_age_days	integer	Number of days since creation after which objects can be deleted. This cannot be used along with object_expiry_date.
object_expiry_date	string	Specific date from when objects can expire. This cannot be used with object_age_days.

non_current_version_expiration

Specifies a way to perform non_current_version_expiration action on filtered objects within a bucket.

Name	Туре	Description
_links	_links	
new_non_current_versions	integer	Number of latest non-current versions to be retained.

Name	Туре	Description
non_current_days	integer	Number of days after which non- current versions can be deleted.

object_filter

Specifies a way to filter objects within a bucket.

Name	Туре	Description
_links	_links	
prefix	string	A prefix that is matched against object-names within a bucket.
size_greater_than	integer	Size of the object greater than specified for which the corresponding lifecycle rule is to be applied.
size_less_than	integer	Size of the object smaller than specified for which the corresponding lifecycle rule is to be applied.
tags	array[string]	An array of key-value paired tags of the form <tag>or <tag=value>.</tag>

svm

Specifies the name of the SVM where this bucket exists.

Name	Туре	Description
_links	_links	
name	string	The name of the SVM. This field cannot be specified in a PATCH method.
uuid	string	The unique identifier of the SVM. This field cannot be specified in a PATCH method.

rules

Information about the lifecycle management rule of a bucket.

Name	Туре	Description
_links	_links	
abort_incomplete_multipart_uploa d	abort_incomplete_multipart_uploa d	Specifies a way to perform abort_incomplete_multipart_uplo ad action on filtered objects within a bucket. It cannot be specified with tags.
bucket_name	string	Specifies the name of the bucket. Bucket name is a string that can only contain the following combination of ASCII-range alphanumeric characters 0-9, a-z, ".", and "-".
enabled	boolean	Specifies whether or not the associated rule is enabled.
expiration	expiration	Specifies a way to perform expiration action on filtered objects within a bucket.
name	string	Bucket lifecycle management rule identifier. The length of the name can range from 0 to 256 characters.
non_current_version_expiration	non_current_version_expiration	Specifies a way to perform non_current_version_expiration action on filtered objects within a bucket.
object_filter	object_filter	Specifies a way to filter objects within a bucket.
svm	svm	Specifies the name of the SVM where this bucket exists.
uuid	string	Specifies the unique identifier of the bucket.

lifecycle_management

Lifecycle management is implemented as an object associated with a bucket. It defines rules to be applied against objects within a bucket. These rules are applied in the background and can delete objects.

Name	Туре	Description
rules	array[rules]	Specifies an object store lifecycle management policy.

s3_bucket_policy_condition

Information about policy conditions based on various condition operators and condition keys.

Name	Туре	Description
delimiters	array[string]	An array of delimiters that are compared with the delimiter value specified at the time of execution of an S3-based command, using the condition operator specified.
max_keys	array[integer]	An array of maximum keys that are allowed or denied to be retrieved using an S3 list operation, based on the condition operator specified.
operator	string	Condition operator that is applied to the specified condition key.
prefixes	array[string]	An array of prefixes that are compared with the input prefix value specified at the time of execution of an S3-based command, using the condition operator specified.
source_ips	array[string]	An array of IP address ranges that are compared with the IP address of a source command at the time of execution of an S3- based command, using the condition operator specified.
usernames	array[string]	An array of usernames that a current user in the context is evaluated against using the condition operators.

s3_bucket_policy_statement

Specifies information about a single access permission.

Name	Туре	Description
actions	array[string]	
conditions	array[s3_bucket_policy_condition]	Specifies bucket policy conditions.
effect	string	Specifies whether access is allowed or denied when a user requests the specific action. If access (to allow) is not granted explicitly to a resource, access is implicitly denied. Access can also be denied explicitly to a resource, in order to make sure that a user cannot access it, even if a different policy grants access.
principals	array[string]	
resources	array[string]	
sid	string	Specifies the statement identifier used to differentiate between statements. The sid length can range from 1 to 256 characters and can only contain the following combination of characters 0-9, A- Z, and a-z. Special characters are not valid.

policy

A policy is an object associated with a bucket. It defines resource (bucket, folder, or object) permissions. These policies get evaluated when an S3 user makes a request by executing a specific command. The user must be part of the principal (user or group) specified in the policy. Permissions in the policies determine whether the request is allowed or denied.

Name	Туре	Description
statements	array[s3_bucket_policy_statemen t]	Specifies bucket access policy statement.

destination

Name	Туре	Description
is_cloud	boolean	Specifies whether a bucket is protected within the Cloud. This field cannot be specified using a POST method.

Name	Туре	Description
is_external_cloud	boolean	Specifies whether a bucket is protected on external Cloud providers. This field cannot be specified using a POST method.
is_ontap	boolean	Specifies whether a bucket is protected within ONTAP. This field cannot be specified using a POST method.
		Default value: 1
		• readOnly: 1
		Introduced in: 9.10
		• x-nullable: true

protection_status

Specifies attributes of bucket protection.

Name	Туре	Description
destination	destination	
is_protected	boolean	 Specifies whether a bucket is a source and if it is protected within ONTAP and/or an external cloud. This field cannot be specified using a POST method. Default value: 1 readOnly: 1 Introduced in: 9.10 x-nullable: true

qos_policy

Specifes "qos_policy.max_throughput_iops" and/or "qos_policy.max_throughput_mbps" or "qos_policy.min_throughput_iops" and/or "qos_policy.min_throughput_mbps". Specifying "min_throughput_iops" or "min_throughput_mbps" is only supported on volumes hosted on a node that is flash optimized. A pre-created QoS policy can also be used by specifying "qos_policy.name" or "qos_policy.uuid" properties. Setting or assigning a QoS policy to a bucket is not supported if its containing volume or SVM already has a QoS policy attached.

Name	Туре	Description
_links	_links	

Name	Туре	Description
max_throughput_iops	integer	Specifies the maximum throughput in IOPS, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.
max_throughput_mbps	integer	Specifies the maximum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.
min_throughput_iops	integer	Specifies the minimum throughput in IOPS, 0 means none. Setting "min_throughput" is supported on AFF platforms only, unless FabricPool tiering policies are set. This is mutually exclusive with name and UUID during POST and PATCH.
min_throughput_mbps	integer	Specifies the minimum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.
name	string	The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH.
uuid	string	The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH.

retention

Specifies the retention mode and default retention period configured on the bucket.

Name	Туре	Description
default_period	string	Specifies the default retention period that is applied to objects while committing them to the WORM state without an associated retention period. The retention period can be in years, or days. The retention period value represents a duration and must be specified in the ISO- 8601 duration format. A period specified for years and days is represented in the ISO-8601 format as "P <num>Y" and "P<num>D" respectively, for example "P10Y" represents a duration of 10 years. The period string must contain only a single time element that is, either years, or days. A duration which combines different periods is not supported, for example "P1Y10D" is not supported.</num></num>
mode	string	The lock mode of the bucket. compliance ‐ A SnapLock Compliance (SLC) bucket provides the highest level of WORM protection and an administrator cannot destroy a compliance bucket if it contains unexpired WORM objects. governance ‐ An administrator can delete a Governance bucket. no_lock ‐ Indicates the bucket does not support object locking.

svm

SVM, applies only to SVM-scoped objects.

Name	Туре	Description
_links	_links	
name	string	The name of the SVM. This field cannot be specified in a PATCH method.

Name	Туре	Description
uuid	string	The unique identifier of the SVM. This field cannot be specified in a PATCH method.

volume

Specifies the FlexGroup volume name and UUID where the bucket is hosted.

Name	Туре	Description
_links	_links	
name	string	The name of the volume. This field cannot be specified in a POST or PATCH method.
uuid	string	 Unique identifier for the volume. This corresponds to the instance- uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. example: 028baa66-41bd- 11e9-81d5-00a0986138f7 Introduced in: 9.6 x-nullable: true

s3_bucket

A bucket is a container of objects. Each bucket defines an object namespace. S3 requests specify objects using a bucket-name and object-name pair. An object resides within a bucket.

Name	Туре	Description
aggregates	array[aggregates]	A list of aggregates for FlexGroup volume constituents where the bucket is hosted. If this option is not specified, the bucket is auto- provisioned as a FlexGroup volume.
allowed	boolean	If this is set to true, an SVM administrator can manage the S3 service. If it is false, only the cluster administrator can manage the service. This field cannot be specified in a POST method.

Name	Туре	Description
audit_event_selector	audit_event_selector	Audit event selector allows you to specify access and permission types to audit.
comment	string	Can contain any additional information about the bucket being created or modified.
constituents_per_aggregate	integer	Specifies the number of constituents or FlexVol volumes per aggregate. A FlexGroup volume consisting of all such constituents across all specified aggregates is created. This option is used along with the aggregates option and cannot be used independently.
encryption	encryption	
lifecycle_management	lifecycle_management	Lifecycle management is implemented as an object associated with a bucket. It defines rules to be applied against objects within a bucket. These rules are applied in the background and can delete objects.
logical_used_size	integer	Specifies the bucket logical used size up to this point. This field cannot be specified using a POST or PATCH method.
name	string	Specifies the name of the bucket. Bucket name is a string that can only contain the following combination of ASCII-range alphanumeric characters 0-9, a-z, ".", and "-".
nas_path	string	Specifies the NAS path to which the nas bucket corresponds to.

Name	Туре	Description
policy	policy	A policy is an object associated with a bucket. It defines resource (bucket, folder, or object) permissions. These policies get evaluated when an S3 user makes a request by executing a specific command. The user must be part of the principal (user or group) specified in the policy. Permissions in the policies determine whether the request is allowed or denied.
protection_status	protection_status	Specifies attributes of bucket protection.
qos_policy	<pre>qos_policy</pre>	Specifes "qos_policy.max_throughput_iops " and/or "qos_policy.max_throughput_mb ps" or "qos_policy.min_throughput_iops" and/or "qos_policy.min_throughput_mbp s". Specifying "min_throughput_iops" or "min_throughput_mbps" is only supported on volumes hosted on a node that is flash optimized. A pre-created QoS policy can also be used by specifying "qos_policy.name" or "qos_policy.uuid" properties. Setting or assigning a QoS policy to a bucket is not supported if its containing volume or SVM already has a QoS policy attached.
retention	retention	Specifies the retention mode and default retention period configured on the bucket.
role	string	Specifies the role of the bucket. This field cannot be specified using a POST method.
size	integer	Specifies the bucket size in bytes; ranges from 190MB to 62PB.

Name	Туре	Description
storage_service_level	string	Specifies the storage service level of the FlexGroup volume on which the bucket should be created. Valid values are "value", "performance" or "extreme".
svm	svm	SVM, applies only to SVM- scoped objects.
type	string	Specifies the bucket type. Valid values are "s3"and "nas".
use_mirrored_aggregates	boolean	Specifies whether mirrored aggregates are selected when provisioning a FlexGroup. Only mirrored aggregates are used if this parameter is set to "true" and only unmirrored aggregates are used if this parameter is set to "false". The default value is "true" for a MetroCluster configuration and is "false" for a non- MetroCluster configuration.
uuid	string	Specifies the unique identifier of the bucket.
versioning_state	string	Specifies the versioning state of the bucket. Valid values are "disabled", "enabled" or "suspended". Note that the versioning state cannot be modified to 'disabled' from any other state.
volume	volume	Specifies the FlexGroup volume name and UUID where the bucket is hosted.

certificate

Specifies the certificate that will be used for creating HTTPS connections to the S3 server.

Name	Туре	Description
_links	_links	
name	string	Certificate name

Name	Туре	Description
uuid	string	Certificate UUID

iops

The rate of I/O operations observed at the storage object.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

latency

The round trip latency in microseconds observed at the storage object.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

throughput

The rate of throughput bytes per second observed at the storage object.

Name	Туре	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

metric

Performance numbers, such as IOPS latency and throughput, for SVM protocols.

Name	Туре	Description
_links	_links	
duration	string	The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
iops	iops	The rate of I/O operations observed at the storage object.
latency	latency	The round trip latency in microseconds observed at the storage object.

Name	Туре	Description
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_ delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput	throughput	The rate of throughput bytes per second observed at the storage object.
timestamp	string	The timestamp of the performance data.

iops_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.

Name	Туре	Description
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

latency_raw

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

throughput_raw

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

Name	Туре	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

statistics

These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.

Name	Туре	Description
iops_raw	iops_raw	The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.
latency_raw	latency_raw	The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput_raw	throughput_raw	Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.
timestamp	string	The timestamp of the performance data.

s3_user

This is a container of S3 users.

Name	Туре	Description
access_key	string	Specifies the access key for the user.
comment	string	Can contain any additional information about the user being created or modified.
key_expiry_time	string	Specifies the date and time after which keys expire and are no longer valid.
key_time_to_live	string	 Indicates the time period from when this parameter is specified: when creating or modifying a user or when the user keys were last regenerated, after which the user keys expire and are no longer valid. Valid format is: 'PnDTnHnMnS PnW'. For example, P2DT6H3M10S specifies a time period of 2 days, 6 hours, 3 minutes, and 10 seconds. If the value specified is '0' seconds, then the keys won't expire.
name	string	Specifies the name of the user. A user name length can range from 1 to 64 characters and can only contain the following combination of characters 0-9, A-Z, a-z, "_", "+", "=", ",", ".","@", and "-".
svm	svm	SVM, applies only to SVM- scoped objects.

s3_service

Specifies the S3 server configuration.

Name	Туре	Description
_links	self_link	
buckets	array[s3_bucket]	This field cannot be specified in a PATCH method.
certificate	certificate	Specifies the certificate that will be used for creating HTTPS connections to the S3 server.
comment	string	Can contain any additional information about the server being created or modified.
default_unix_user	string	Specifies the default UNIX user for NAS Access.
default_win_user	string	Specifies the default Windows user for NAS Access.
enabled	boolean	Specifies whether the S3 server being created or modified should be up or down.
is_http_enabled	boolean	Specifies whether HTTP is enabled on the S3 server being created or modified. By default, HTTP is disabled on the S3 server.
is_https_enabled	boolean	Specifies whether HTTPS is enabled on the S3 server being created or modified. By default, HTTPS is enabled on the S3 server.
metric	metric	Performance numbers, such as IOPS latency and throughput, for SVM protocols.
name	string	Specifies the name of the S3 server. A server name can contain 3 to 253 characters using only the following combination of characters':' 0-9, A-Z, a-z, ".", and "-".

Name	Туре	Description
port	integer	Specifies the HTTP listener port for the S3 server. By default, HTTP is enabled on port 80. Valid values range from 1 to 65535.
secure_port	integer	Specifies the HTTPS listener port for the S3 server. By default, HTTPS is enabled on port 443. Valid values range from 1 to 65535.
statistics	statistics	These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.
svm	svm	SVM, applies only to SVM- scoped objects.
users	array[s3_user]	This field cannot be specified in a PATCH method.

error_arguments

Name	Туре	Description
code	string	Argument code
message	string	Message argument

returned_error

Name	Туре	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

Create S3 server, users, and buckets configurations

POST /protocols/s3/services

Introduced In: 9.7

Creates an S3 server, users, and buckets configurations.

Important notes

- Each SVM can have one S3 server configuration.
- One or more buckets and users can also be created using this end-point.
- If creating a user configuration fails, buckets are not created either and already created users are not saved.
- If creating a bucket configuration fails, all buckets already created are saved with no new buckets created.

Required properties

• svm.uuid - Existing SVM in which to create an S3 server configuration.

Recommended optional properties

- enabled Specifies the state of the server created.
- comment Any information related to the server created.

Default property values

- comment ""
- enabled true

Related ONTAP commands

- vserver object-store-server create
- vserver object-store-server bucket create
- vserver object-store-server bucket policy statement create
- vserver object-store-server bucket policy-statement-condition create
- vserver object-store-server user create

Learn more

DOC /protocols/s3/services

Parameters

return_records boolean query False The default is false	Name	Туре	In	Required	Description
Set to true, the records are returned. • Default value	return_records	boolean	query	False	The default is false. If set to true, the records are returned. • Default value:

Request Body

Name	Туре	Description
_links	self_link	
buckets	array[s3_bucket]	This field cannot be specified in a PATCH method.
certificate	certificate	Specifies the certificate that will be used for creating HTTPS connections to the S3 server.
comment	string	Can contain any additional information about the server being created or modified.
default_unix_user	string	Specifies the default UNIX user for NAS Access.
default_win_user	string	Specifies the default Windows user for NAS Access.
enabled	boolean	Specifies whether the S3 server being created or modified should be up or down.
is_http_enabled	boolean	Specifies whether HTTP is enabled on the S3 server being created or modified. By default, HTTP is disabled on the S3 server.
is_https_enabled	boolean	Specifies whether HTTPS is enabled on the S3 server being created or modified. By default, HTTPS is enabled on the S3 server.

Name	Туре	Description
metric	metric	Performance numbers, such as IOPS latency and throughput, for SVM protocols.
name	string	Specifies the name of the S3 server. A server name can contain 3 to 253 characters using only the following combination of characters':' 0-9, A-Z, a-z, ".", and "-".
port	integer	Specifies the HTTP listener port for the S3 server. By default, HTTP is enabled on port 80. Valid values range from 1 to 65535.
secure_port	integer	Specifies the HTTPS listener port for the S3 server. By default, HTTPS is enabled on port 443. Valid values range from 1 to 65535.
statistics	statistics	These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.
svm	svm	SVM, applies only to SVM-scoped objects.
users	array[s3_user]	This field cannot be specified in a PATCH method.

Example request

```
{
 " links": {
   "self": {
     "href": "/api/resourcelink"
   }
 },
 "buckets": [
   {
     "aggregates": [
       {
         " links": {
            "self": {
             "href": "/api/resourcelink"
           }
          },
         "name": "aggr1",
         "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
       }
     ],
     "audit event selector": {
       "access": "string",
       "permission": "string"
     },
     "comment": "S3 bucket.",
     "constituents per aggregate": 4,
     "lifecycle management": {
       "rules": [
          {
            " links": {
              "self": {
              "href": "/api/resourcelink"
              }
            },
            "abort incomplete multipart upload": {
             " links": {
               "self": {
                 "href": "/api/resourcelink"
               }
              }
            },
            "bucket_name": "bucket1",
            "expiration": {
              " links": {
                "self": {
```

```
"href": "/api/resourcelink"
         }
        },
        "object expiry date": "string"
      },
      "name": "string",
      "non current version expiration": {
        " links": {
          "self": {
           "href": "/api/resourcelink"
          }
        }
      },
      "object filter": {
        " links": {
          "self": {
           "href": "/api/resourcelink"
         }
        },
        "prefix": "/logs",
        "size greater than": 10240,
        "size less than": 10485760,
        "tags": [
         "project1=projA",
         "project2=projB"
        ]
      },
      "svm": {
       " links": {
          "self": {
           "href": "/api/resourcelink"
         }
        },
        "name": "svm1",
       "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      },
     "uuid": "414b29a1-3b26-11e9-bd58-0050568ea055"
   }
 1
},
"logical used size": 0,
"name": "bucket1",
"nas path": "/",
"policy": {
  "statements": [
   {
```

```
"actions": [
       "GetObject",
       "PutObject",
       "DeleteObject",
       "ListBucket"
      ],
      "conditions": [
       {
          "delimiters": [
          "/"
          ],
          "max keys": [
          1000
         ],
          "operator": "ip_address",
          "prefixes": [
          "pref"
          ],
          "source_ips": [
          "1.1.1.1",
           "1.2.2.0/24"
          ],
         "usernames": [
          "user1"
          ]
       }
      ],
      "effect": "allow",
     "principals": [
      "user1",
       "group/grp1",
       "nasgroup/group1"
      ],
      "resources": [
       "bucket1",
       "bucket1/*"
     ],
     "sid": "FullAccessToUser1"
    }
 ]
},
"qos policy": {
 " links": {
   "self": {
     "href": "/api/resourcelink"
    }
```

```
},
      "max throughput iops": 10000,
      "max throughput mbps": 500,
      "min throughput iops": 2000,
      "min throughput mbps": 500,
      "name": "performance",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "retention": {
     "default period": "P10Y",
      "mode": "governance"
    },
    "role": "string",
    "size": 1677721600,
    "storage service level": "value",
    "svm": {
     " links": {
        "self": {
         "href": "/api/resourcelink"
       }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "type": "s3",
    "uuid": "414b29a1-3b26-11e9-bd58-0050568ea055",
    "versioning state": "enabled",
    "volume": {
      " links": {
        "self": {
          "href": "/api/resourcelink"
       }
      },
      "name": "volume1",
     "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
    }
  }
],
"certificate": {
  " links": {
    "self": {
     "href": "/api/resourcelink"
   }
  },
  "name": "string",
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
```

```
},
"comment": "S3 server",
"default unix user": "string",
"default win user": "string",
"metric": {
 " links": {
    "self": {
     "href": "/api/resourcelink"
   }
  },
  "duration": "PT15S",
  "iops": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "latency": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "status": "ok",
  "throughput": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
 "timestamp": "2017-01-25 06:20:13 -0500"
},
"name": "Server-1",
"port": 80,
"secure port": 443,
"statistics": {
  "iops raw": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "latency raw": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "status": "ok",
  "throughput raw": {
   "read": 200,
```

```
"total": 1000,
     "write": 100
   },
   "timestamp": "2017-01-25 06:20:13 -0500"
  },
 "svm": {
   " links": {
     "self": {
       "href": "/api/resourcelink"
     }
    },
   "name": "svm1",
   "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
 },
 "users": [
   {
      "access key": "HJAKU28M3SXTE2UXUACV",
      "comment": "S3 user",
     "key expiry time": "2023-12-31 19:00:00 -0500",
      "key time to live": "PT6H3M",
     "name": "user-1",
      "svm": {
        " links": {
         "self": {
           "href": "/api/resourcelink"
         }
        },
        "name": "svm1",
       "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      }
   }
 ]
}
```

Response

```
Status: 201, Created
```

Name	Туре	Description
num_records	integer	Number of Records
records	array[records]	

Example response

```
{
 "num records": 1,
 "records": [
    {
      " links": {
       "next": {
         "href": "/api/resourcelink"
       },
        "self": {
         "href": "/api/resourcelink"
       }
      },
      "job": {
       " links": {
         "self": {
          "href": "/api/resourcelink"
         }
       },
       "uuid": "string"
      },
      "users": [
        {
          " links": {
           "next": {
             "href": "/api/resourcelink"
            },
           "self": {
             "href": "/api/resourcelink"
           }
          },
          "access key": "HJAKU28M3SXTE2UXUACV",
          "name": "user-1",
          "secret key": "BcA HX6If458llhnx3n1TCO3mg4roCXG0ddYf cJ"
        }
      1
    }
 ]
}
```

Headers

Name	Description	Туре
Location	Useful for tracking the resource location	string

Error

Status: Default

ONTAP Error Response Codes

| Error Code | Description | | ------ | ------ |

| 2621706 | The specified \"{svm.uuid}\" and \"{svm.name}\" refer to different SVMs. | 92405789 | The specified object server name contains invalid characters or not a fully qualified domain name. Valid characters for an object store server name are 0-9, A-Z, a-z, ".", and "-". | 92405790 | Object store server names must have between 3 and 253 characters. | 92405839 | Creating an object store server requires an effective cluster version of data ONTAP 9.7.0 or later. Upgrade all the nodes to 9.7.0 or later and try the operation again. | 92405853 | Failed to create the object store server because Cloud Volumes ONTAP does not support object store servers. |

92405863	An error occurs when creating an S3 user or bucket. The reason for failure is detailed in the error message. Follow the error codes specified for the user or bucket endpoints to see details for the failure.
92405863	Failed to create bucket \"{bucket name}\". Reason: "Failed to create bucket \"{bucket name}\" for SVM \"{svm.name}\". Reason: Bucket name \"{bucket name}\" contains invalid characters. Valid characters for a bucket name are 0-9, a-z, ".", and "-". ". Resolve all the issues and retry the operation.
92405863	Failed to create bucket \"{bucket name}\". Reason: "Failed to create bucket \"{bucket name}\" for SVM \"{svm.name}\". Reason: Invalid QoS policy group specified \"{qos policy}\". The specified QoS policy group has a min-throughput value set, and the workload being assigned resides on a platform that does not support min-throughput or the cluster is in a mixed version state and the effective cluster version of ONTAP does not support min-throughput on this platform. Resolve all the issues and retry the operation.
92405863	Failed to create bucket \"{bucket name}\". Reason: "User(s) "{user name(s)}\" specified in the principal list do not exist for SVM \"{svm.name}\". Use the "object- store-server user create" command to create a user.". Resolve all the issues and retry the operation.

92405863	Failed to create user \"{user name}\". Reason: "SVM "Cluster" is not a data SVM. Specify a data SVM.". Resolve all the issues and retry the operation.
92405884	An object store server can only be created on a data SVM. An object store server can also be created on a system SVM on a mixed platform cluster.
92405903	Failed to configure HTTPS on an object store server for SVM \"{svm.name}\". Reason: {Reason of failure}.
92405900	Certificate not found for SVM \"{svm.name}\".
92406044	Failed to set default UNIX user for SVM \"{svm.name}\". Reason: UNIX user can only be created on a Data SVM.

Name	Туре	Description
error	returned_error	

Example error

```
{
   "error": {
      "arguments": [
        {
            "code": "string",
            "message": "string"
        }
      ],
      "code": "4",
      "message": "entry doesn't exist",
      "target": "uuid"
    }
}
```

Definitions

See Definitions

href

Name	Туре	Description
href	string	

self_link

Name	Туре	Description
self	href	

_links

Name	Туре	Description
self	href	

aggregates

Aggregate

Name	Туре	Description
_links	_links	
name	string	
uuid	string	

audit_event_selector

Audit event selector allows you to specify access and permission types to audit.

Name	Туре	Description
access	string	Specifies read and write access types.
permission	string	Specifies allow and deny permission types.

encryption

Name	Туре	Description
enabled	boolean	Specifies whether encryption is enabled on the bucket. By default, encryption is disabled on a bucket. This field cannot be specified in a POST method.

Specifies a way to perform abort_incomplete_multipart_upload action on filtered objects within a bucket. It cannot be specified with tags.

Name	Туре	Description
_links	_links	
after_initiation_days	integer	Number of days of initiation after which uploads can be aborted.

expiration

Specifies a way to perform expiration action on filtered objects within a bucket.

Name	Туре	Description
_links	_links	
expired_object_delete_marker	boolean	Cleanup object delete markers.
object_age_days	integer	Number of days since creation after which objects can be deleted. This cannot be used along with object_expiry_date.
object_expiry_date	string	Specific date from when objects can expire. This cannot be used with object_age_days.

non_current_version_expiration

Specifies a way to perform non_current_version_expiration action on filtered objects within a bucket.

Name	Туре	Description
_links	_links	
new_non_current_versions	integer	Number of latest non-current versions to be retained.
non_current_days	integer	Number of days after which non- current versions can be deleted.

object_filter

Specifies a way to filter objects within a bucket.

Name	Туре	Description
_links	_links	

Name	Туре	Description
prefix	string	A prefix that is matched against object-names within a bucket.
size_greater_than	integer	Size of the object greater than specified for which the corresponding lifecycle rule is to be applied.
size_less_than	integer	Size of the object smaller than specified for which the corresponding lifecycle rule is to be applied.
tags	array[string]	An array of key-value paired tags of the form <tag>or <tag=value>.</tag>

svm

Specifies the name of the SVM where this bucket exists.

Name	Туре	Description
_links	_links	
name	string	The name of the SVM. This field cannot be specified in a PATCH method.
uuid	string	The unique identifier of the SVM. This field cannot be specified in a PATCH method.

rules

Information about the lifecycle management rule of a bucket.

Name	Туре	Description
_links	_links	
abort_incomplete_multipart_uploa d	abort_incomplete_multipart_uploa d	Specifies a way to perform abort_incomplete_multipart_uplo ad action on filtered objects within a bucket. It cannot be specified with tags.
Name	Туре	Description
--------------------------------	--------------------------------	---
bucket_name	string	Specifies the name of the bucket. Bucket name is a string that can only contain the following combination of ASCII-range alphanumeric characters 0-9, a-z, ".", and "-".
enabled	boolean	Specifies whether or not the associated rule is enabled.
expiration	expiration	Specifies a way to perform expiration action on filtered objects within a bucket.
name	string	Bucket lifecycle management rule identifier. The length of the name can range from 0 to 256 characters.
non_current_version_expiration	non_current_version_expiration	Specifies a way to perform non_current_version_expiration action on filtered objects within a bucket.
object_filter	object_filter	Specifies a way to filter objects within a bucket.
svm	svm	Specifies the name of the SVM where this bucket exists.
uuid	string	Specifies the unique identifier of the bucket.

lifecycle_management

Lifecycle management is implemented as an object associated with a bucket. It defines rules to be applied against objects within a bucket. These rules are applied in the background and can delete objects.

Name	Туре	Description
rules	array[rules]	Specifies an object store lifecycle management policy.

s3_bucket_policy_condition

Information about policy conditions based on various condition operators and condition keys.

Name	Туре	Description
delimiters	array[string]	An array of delimiters that are compared with the delimiter value specified at the time of execution of an S3-based command, using the condition operator specified.
max_keys	array[integer]	An array of maximum keys that are allowed or denied to be retrieved using an S3 list operation, based on the condition operator specified.
operator	string	Condition operator that is applied to the specified condition key.
prefixes	array[string]	An array of prefixes that are compared with the input prefix value specified at the time of execution of an S3-based command, using the condition operator specified.
source_ips	array[string]	An array of IP address ranges that are compared with the IP address of a source command at the time of execution of an S3- based command, using the condition operator specified.
usernames	array[string]	An array of usernames that a current user in the context is evaluated against using the condition operators.

s3_bucket_policy_statement

Specifies information about a single access permission.

Name	Туре	Description
actions	array[string]	
conditions	array[s3_bucket_policy_condition]	Specifies bucket policy conditions.

Name	Туре	Description
effect	string	Specifies whether access is allowed or denied when a user requests the specific action. If access (to allow) is not granted explicitly to a resource, access is implicitly denied. Access can also be denied explicitly to a resource, in order to make sure that a user cannot access it, even if a different policy grants access.
principals	array[string]	
resources	array[string]	
sid	string	Specifies the statement identifier used to differentiate between statements. The sid length can range from 1 to 256 characters and can only contain the following combination of characters 0-9, A- Z, and a-z. Special characters are not valid.

policy

A policy is an object associated with a bucket. It defines resource (bucket, folder, or object) permissions. These policies get evaluated when an S3 user makes a request by executing a specific command. The user must be part of the principal (user or group) specified in the policy. Permissions in the policies determine whether the request is allowed or denied.

Name	Туре	Description
statements	array[s3_bucket_policy_statemen t]	Specifies bucket access policy statement.

destination

Name	Туре	Description
is_cloud	boolean	Specifies whether a bucket is protected within the Cloud. This field cannot be specified using a POST method.
is_external_cloud	boolean	Specifies whether a bucket is protected on external Cloud providers. This field cannot be specified using a POST method.

Name	Туре	Description
is_ontap	boolean	Specifies whether a bucket is protected within ONTAP. This field cannot be specified using a POST method.
		Default value: 1
		• readOnly: 1
		 Introduced in: 9.10
		• x-nullable: true

protection_status

Specifies attributes of bucket protection.

Name	Туре	Description
destination	destination	
is_protected	boolean	 Specifies whether a bucket is a source and if it is protected within ONTAP and/or an external cloud. This field cannot be specified using a POST method. Default value: 1 readOnly: 1 Introduced in: 9.10 x-nullable: true

qos_policy

Specifes "qos_policy.max_throughput_iops" and/or "qos_policy.max_throughput_mbps" or "qos_policy.min_throughput_iops" and/or "qos_policy.min_throughput_mbps". Specifying "min_throughput_iops" or "min_throughput_mbps" is only supported on volumes hosted on a node that is flash optimized. A pre-created QoS policy can also be used by specifying "qos_policy.name" or "qos_policy.uuid" properties. Setting or assigning a QoS policy to a bucket is not supported if its containing volume or SVM already has a QoS policy attached.

Name	Туре	Description
_links	_links	
max_throughput_iops	integer	Specifies the maximum throughput in IOPS, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.

Name	Туре	Description
max_throughput_mbps	integer	Specifies the maximum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.
min_throughput_iops	integer	Specifies the minimum throughput in IOPS, 0 means none. Setting "min_throughput" is supported on AFF platforms only, unless FabricPool tiering policies are set. This is mutually exclusive with name and UUID during POST and PATCH.
min_throughput_mbps	integer	Specifies the minimum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.
name	string	The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH.
uuid	string	The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH.

retention

Specifies the retention mode and default retention period configured on the bucket.

Name	Туре	Description
default_period	string	Specifies the default retention period that is applied to objects while committing them to the WORM state without an associated retention period. The retention period can be in years, or days. The retention period value represents a duration and must be specified in the ISO- 8601 duration format. A period specified for years and days is represented in the ISO-8601 format as "P <num>Y" and "P<num>D" respectively, for example "P10Y" represents a duration of 10 years. The period string must contain only a single time element that is, either years, or days. A duration which combines different periods is not supported, for example "P1Y10D" is not supported.</num></num>
mode	string	The lock mode of the bucket. compliance ‐ A SnapLock Compliance (SLC) bucket provides the highest level of WORM protection and an administrator cannot destroy a compliance bucket if it contains unexpired WORM objects. governance ‐ An administrator can delete a Governance bucket. no_lock ‐ Indicates the bucket does not support object locking.

svm

SVM, applies only to SVM-scoped objects.

Name	Туре	Description
_links	_links	
name	string	The name of the SVM. This field cannot be specified in a PATCH method.

Name	Туре	Description
uuid	string	The unique identifier of the SVM. This field cannot be specified in a PATCH method.

volume

Specifies the FlexGroup volume name and UUID where the bucket is hosted.

Name	Туре	Description
_links	_links	
name	string	The name of the volume. This field cannot be specified in a POST or PATCH method.
uuid	string	 Unique identifier for the volume. This corresponds to the instance- uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. example: 028baa66-41bd- 11e9-81d5-00a0986138f7 Introduced in: 9.6 x-nullable: true

s3_bucket

A bucket is a container of objects. Each bucket defines an object namespace. S3 requests specify objects using a bucket-name and object-name pair. An object resides within a bucket.

Name	Туре	Description
aggregates	array[aggregates]	A list of aggregates for FlexGroup volume constituents where the bucket is hosted. If this option is not specified, the bucket is auto- provisioned as a FlexGroup volume.
allowed	boolean	If this is set to true, an SVM administrator can manage the S3 service. If it is false, only the cluster administrator can manage the service. This field cannot be specified in a POST method.

Name	Туре	Description
audit_event_selector	audit_event_selector	Audit event selector allows you to specify access and permission types to audit.
comment	string	Can contain any additional information about the bucket being created or modified.
constituents_per_aggregate	integer	Specifies the number of constituents or FlexVol volumes per aggregate. A FlexGroup volume consisting of all such constituents across all specified aggregates is created. This option is used along with the aggregates option and cannot be used independently.
encryption	encryption	
lifecycle_management	lifecycle_management	Lifecycle management is implemented as an object associated with a bucket. It defines rules to be applied against objects within a bucket. These rules are applied in the background and can delete objects.
logical_used_size	integer	Specifies the bucket logical used size up to this point. This field cannot be specified using a POST or PATCH method.
name	string	Specifies the name of the bucket. Bucket name is a string that can only contain the following combination of ASCII-range alphanumeric characters 0-9, a-z, ".", and "-".
nas_path	string	Specifies the NAS path to which the nas bucket corresponds to.

Name	Туре	Description
policy	policy	A policy is an object associated with a bucket. It defines resource (bucket, folder, or object) permissions. These policies get evaluated when an S3 user makes a request by executing a specific command. The user must be part of the principal (user or group) specified in the policy. Permissions in the policies determine whether the request is allowed or denied.
protection_status	protection_status	Specifies attributes of bucket protection.
qos_policy	qos_policy	Specifes "qos_policy.max_throughput_iops " and/or "qos_policy.max_throughput_mb ps" or "qos_policy.min_throughput_iops" and/or "qos_policy.min_throughput_mbp s". Specifying "min_throughput_iops" or "min_throughput_mbps" is only supported on volumes hosted on a node that is flash optimized. A pre-created QoS policy can also be used by specifying "qos_policy.name" or "qos_policy.uuid" properties. Setting or assigning a QoS policy to a bucket is not supported if its containing volume or SVM already has a QoS policy attached.
retention	retention	Specifies the retention mode and default retention period configured on the bucket.
role	string	Specifies the role of the bucket. This field cannot be specified using a POST method.
size	integer	Specifies the bucket size in bytes; ranges from 190MB to 62PB.

Name	Туре	Description
storage_service_level	string	Specifies the storage service level of the FlexGroup volume on which the bucket should be created. Valid values are "value", "performance" or "extreme".
svm	svm	SVM, applies only to SVM- scoped objects.
type	string	Specifies the bucket type. Valid values are "s3"and "nas".
use_mirrored_aggregates	boolean	Specifies whether mirrored aggregates are selected when provisioning a FlexGroup. Only mirrored aggregates are used if this parameter is set to "true" and only unmirrored aggregates are used if this parameter is set to "false". The default value is "true" for a MetroCluster configuration and is "false" for a non- MetroCluster configuration.
uuid	string	Specifies the unique identifier of the bucket.
versioning_state	string	Specifies the versioning state of the bucket. Valid values are "disabled", "enabled" or "suspended". Note that the versioning state cannot be modified to 'disabled' from any other state.
volume	volume	Specifies the FlexGroup volume name and UUID where the bucket is hosted.

certificate

Specifies the certificate that will be used for creating HTTPS connections to the S3 server.

Name	Туре	Description
_links	_links	
name	string	Certificate name

Name	Туре	Description
uuid	string	Certificate UUID

iops

The rate of I/O operations observed at the storage object.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

latency

The round trip latency in microseconds observed at the storage object.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

throughput

The rate of throughput bytes per second observed at the storage object.

Name	Туре	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

metric

Performance numbers, such as IOPS latency and throughput, for SVM protocols.

Name	Туре	Description
_links	_links	
duration	string	The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
iops	iops	The rate of I/O operations observed at the storage object.
latency	latency	The round trip latency in microseconds observed at the storage object.

Name	Туре	Description
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_ delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput	throughput	The rate of throughput bytes per second observed at the storage object.
timestamp	string	The timestamp of the performance data.

iops_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.

Name	Туре	Description
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

latency_raw

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

throughput_raw

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

Name	Туре	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

statistics

These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.

Name	Туре	Description
iops_raw	iops_raw	The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.
latency_raw	latency_raw	The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput_raw	throughput_raw	Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.
timestamp	string	The timestamp of the performance data.

s3_user

This is a container of S3 users.

Name	Туре	Description
access_key	string	Specifies the access key for the user.
comment	string	Can contain any additional information about the user being created or modified.
key_expiry_time	string	Specifies the date and time after which keys expire and are no longer valid.
key_time_to_live	string	 Indicates the time period from when this parameter is specified: when creating or modifying a user or when the user keys were last regenerated, after which the user keys expire and are no longer valid. Valid format is: 'PnDTnHnMnS PnW'. For example, P2DT6H3M10S specifies a time period of 2 days, 6 hours, 3 minutes, and 10 seconds. If the value specified is '0' seconds, then the keys won't expire.
name	string	Specifies the name of the user. A user name length can range from 1 to 64 characters and can only contain the following combination of characters 0-9, A-Z, a-z, "_", "+", "=", ",", ".","@", and "-".
svm	svm	SVM, applies only to SVM- scoped objects.

s3_service

Specifies the S3 server configuration.

Name	Туре	Description
_links	self_link	
buckets	array[s3_bucket]	This field cannot be specified in a PATCH method.
certificate	certificate	Specifies the certificate that will be used for creating HTTPS connections to the S3 server.
comment	string	Can contain any additional information about the server being created or modified.
default_unix_user	string	Specifies the default UNIX user for NAS Access.
default_win_user	string	Specifies the default Windows user for NAS Access.
enabled	boolean	Specifies whether the S3 server being created or modified should be up or down.
is_http_enabled	boolean	Specifies whether HTTP is enabled on the S3 server being created or modified. By default, HTTP is disabled on the S3 server.
is_https_enabled	boolean	Specifies whether HTTPS is enabled on the S3 server being created or modified. By default, HTTPS is enabled on the S3 server.
metric	metric	Performance numbers, such as IOPS latency and throughput, for SVM protocols.
name	string	Specifies the name of the S3 server. A server name can contain 3 to 253 characters using only the following combination of characters':' 0-9, A-Z, a-z, ".", and "-".

Name	Туре	Description
port	integer	Specifies the HTTP listener port for the S3 server. By default, HTTP is enabled on port 80. Valid values range from 1 to 65535.
secure_port	integer	Specifies the HTTPS listener port for the S3 server. By default, HTTPS is enabled on port 443. Valid values range from 1 to 65535.
statistics	statistics	These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.
svm	svm	SVM, applies only to SVM- scoped objects.
users	array[s3_user]	This field cannot be specified in a PATCH method.

collection_links

Name	Туре	Description
next	href	
self	href	

job_link

Name	Туре	Description
_links	_links	
uuid	string	The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation.

s3_service_user_post_response

Name	Туре	Description
_links	collection_links	

Name	Туре	Description
access_key	string	Specifies the access key for the user.
name	string	The name of the user.
secret_key	string	Specifies the secret key for the user.

records

Name	Туре	Description
_links	collection_links	
job	job_link	
users	array[s3_service_user_post_resp onse]	

error_arguments

Name	Туре	Description
code	string	Argument code
message	string	Message argument

returned_error

Name	Туре	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

Delete the S3 server configuration for an SVM

DELETE /protocols/s3/services/{svm.uuid}

Introduced In: 9.7

Deletes the S3 server configuration of an SVM. If the 'delete_all' parameter is set to false, only the S3 server is

deleted. Otherwise S3 users and buckets present on the SVM are also deleted. Note that only empty buckets can be deleted. This endpoint returns the S3 server delete job-uuid in response. To monitor the job status follow /api/cluster/jobs/<job-uuid>.</job-uuid>

Related ONTAP commands

• vserver object-store-server delete

Learn more

DOC /protocols/s3/services

Parameters

Name	Туре	In	Required	Description
delete_all	boolean	query	False	Delete S3 server and associated users and empty buckets. • Default value: 1
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

Response

Status: 200, Ok

Name	Туре	Description
num_records	integer	Number of Records
records	array[records]	

Example response

Error

Status: Default

ONTAP Error Response Codes

Error Code	Description
92405864	An error occurs when deleting an S3 user or bucket. The reason for failure is detailed in the error message. Follow the error codes specified for the user or bucket endpoints to see details for the failure.

Name	Туре	Description
error	returned_error	

Example error

```
{
    "error": {
        "arguments": [
            {
            "code": "string",
            "message": "string"
            }
        ],
        "code": "4",
        "message": "entry doesn't exist",
        "target": "uuid"
     }
}
```

Definitions

See Definitions

href

Name	Туре	Description
href	string	

_links

Name	Туре	Description
self	href	

job_link

Name	Туре	Description
_links	_links	
uuid	string	The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation.

records

Name	Туре	Description
job	job_link	

error_arguments

Name	Туре	Description
code	string	Argument code
message	string	Message argument

returned_error

Name	Туре	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

Retrieve the S3 server configuration for an SVM

GET /protocols/s3/services/{svm.uuid}

Introduced In: 9.7

Retrieves the S3 Server configuration of an SVM. Note that in order to retrieve S3 bucket policy conditions, the 'fields' option should be set to '**'.

Related ONTAP commands

• vserver object-store-server show

Learn more

DOC /protocols/s3/services

Parameters

Name	Туре	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

Response

```
Status: 200, Ok
```

Name	Туре	Description
_links	self_link	
buckets	array[s3_bucket]	This field cannot be specified in a PATCH method.
certificate	certificate	Specifies the certificate that will be used for creating HTTPS connections to the S3 server.
comment	string	Can contain any additional information about the server being created or modified.

Name	Туре	Description
default_unix_user	string	Specifies the default UNIX user for NAS Access.
default_win_user	string	Specifies the default Windows user for NAS Access.
enabled	boolean	Specifies whether the S3 server being created or modified should be up or down.
is_http_enabled	boolean	Specifies whether HTTP is enabled on the S3 server being created or modified. By default, HTTP is disabled on the S3 server.
is_https_enabled	boolean	Specifies whether HTTPS is enabled on the S3 server being created or modified. By default, HTTPS is enabled on the S3 server.
metric	metric	Performance numbers, such as IOPS latency and throughput, for SVM protocols.
name	string	Specifies the name of the S3 server. A server name can contain 3 to 253 characters using only the following combination of characters':' 0-9, A-Z, a-z, ".", and "-".
port	integer	Specifies the HTTP listener port for the S3 server. By default, HTTP is enabled on port 80. Valid values range from 1 to 65535.
secure_port	integer	Specifies the HTTPS listener port for the S3 server. By default, HTTPS is enabled on port 443. Valid values range from 1 to 65535.

Name	Туре	Description
statistics	statistics	These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.
svm	svm	SVM, applies only to SVM-scoped objects.
users	array[s3_user]	This field cannot be specified in a PATCH method.

Example response

```
{
 " links": {
   "self": {
     "href": "/api/resourcelink"
   }
 },
 "buckets": [
   {
     "aggregates": [
       {
         " links": {
            "self": {
             "href": "/api/resourcelink"
           }
          },
         "name": "aggr1",
         "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
       }
     ],
     "audit event selector": {
       "access": "string",
       "permission": "string"
     },
     "comment": "S3 bucket.",
     "constituents per aggregate": 4,
     "lifecycle management": {
       "rules": [
          {
            " links": {
              "self": {
              "href": "/api/resourcelink"
              }
            },
            "abort incomplete multipart upload": {
             " links": {
               "self": {
                 "href": "/api/resourcelink"
               }
              }
            },
            "bucket_name": "bucket1",
            "expiration": {
              " links": {
                "self": {
```

```
"href": "/api/resourcelink"
         }
        },
        "object expiry date": "string"
      },
      "name": "string",
      "non current version expiration": {
        " links": {
          "self": {
           "href": "/api/resourcelink"
          }
        }
      },
      "object filter": {
        " links": {
          "self": {
           "href": "/api/resourcelink"
         }
        },
        "prefix": "/logs",
        "size greater than": 10240,
        "size less than": 10485760,
        "tags": [
         "project1=projA",
         "project2=projB"
        ]
      },
      "svm": {
       " links": {
          "self": {
           "href": "/api/resourcelink"
         }
        },
        "name": "svm1",
       "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      },
     "uuid": "414b29a1-3b26-11e9-bd58-0050568ea055"
   }
 1
},
"logical used size": 0,
"name": "bucket1",
"nas path": "/",
"policy": {
  "statements": [
   {
```

```
"actions": [
       "GetObject",
       "PutObject",
       "DeleteObject",
       "ListBucket"
      ],
      "conditions": [
       {
          "delimiters": [
          "/"
          ],
          "max keys": [
          1000
         ],
          "operator": "ip_address",
          "prefixes": [
          "pref"
          ],
          "source_ips": [
          "1.1.1.1",
           "1.2.2.0/24"
          ],
         "usernames": [
          "user1"
          ]
       }
      ],
      "effect": "allow",
     "principals": [
      "user1",
       "group/grp1",
       "nasgroup/group1"
      ],
      "resources": [
      "bucket1",
       "bucket1/*"
     ],
     "sid": "FullAccessToUser1"
    }
 ]
},
"qos policy": {
 " links": {
   "self": {
     "href": "/api/resourcelink"
    }
```

```
},
      "max throughput iops": 10000,
      "max throughput mbps": 500,
      "min throughput iops": 2000,
      "min throughput mbps": 500,
      "name": "performance",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "retention": {
     "default period": "P10Y",
      "mode": "governance"
    },
    "role": "string",
    "size": 1677721600,
    "storage service level": "value",
    "svm": {
     " links": {
        "self": {
         "href": "/api/resourcelink"
       }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "type": "s3",
    "uuid": "414b29a1-3b26-11e9-bd58-0050568ea055",
    "versioning state": "enabled",
    "volume": {
      " links": {
        "self": {
          "href": "/api/resourcelink"
       }
      },
      "name": "volume1",
     "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
    }
  }
],
"certificate": {
  " links": {
    "self": {
     "href": "/api/resourcelink"
   }
  },
  "name": "string",
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
```

```
},
"comment": "S3 server",
"default unix user": "string",
"default win user": "string",
"metric": {
 " links": {
    "self": {
     "href": "/api/resourcelink"
   }
  },
  "duration": "PT15S",
  "iops": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "latency": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "status": "ok",
  "throughput": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
 "timestamp": "2017-01-25 06:20:13 -0500"
},
"name": "Server-1",
"port": 80,
"secure port": 443,
"statistics": {
  "iops raw": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "latency raw": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "status": "ok",
  "throughput raw": {
   "read": 200,
```

```
"total": 1000,
     "write": 100
   },
   "timestamp": "2017-01-25 06:20:13 -0500"
  },
 "svm": {
   " links": {
     "self": {
       "href": "/api/resourcelink"
     }
    },
   "name": "svm1",
   "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
 },
 "users": [
   {
      "access key": "HJAKU28M3SXTE2UXUACV",
      "comment": "S3 user",
      "key expiry time": "2023-12-31 19:00:00 -0500",
      "key time to live": "PT6H3M",
     "name": "user-1",
      "svm": {
        " links": {
         "self": {
           "href": "/api/resourcelink"
         }
        },
        "name": "svm1",
       "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      }
   }
 ]
}
```

Error

error

```
Status: Default, Error
                                                            Description
Name
                              Туре
                              returned_error
```

Example error

```
{
    "error": {
        "arguments": [
            {
            "code": "string",
            "message": "string"
            }
        ],
        "code": "4",
        "message": "entry doesn't exist",
        "target": "uuid"
      }
}
```

Definitions

See Definitions

href

Name	Туре	Description
href	string	

self_link

Name	Туре	Description
self	href	

_links

Name	Туре	Description
self	href	

aggregates

Aggregate

Name	Туре	Description
_links	_links	
name	string	
uuid	string	

audit_event_selector

Audit event selector allows you to specify access and permission types to audit.

Name	Туре	Description
access	string	Specifies read and write access types.
permission	string	Specifies allow and deny permission types.

encryption

Name	Туре	Description
enabled	boolean	Specifies whether encryption is enabled on the bucket. By default, encryption is disabled on a bucket. This field cannot be specified in a POST method.

Specifies a way to perform abort_incomplete_multipart_upload action on filtered objects within a bucket. It cannot be specified with tags.

Name	Туре	Description
_links	_links	
after_initiation_days	integer	Number of days of initiation after which uploads can be aborted.

expiration

Specifies a way to perform expiration action on filtered objects within a bucket.

Name	Туре	Description
_links	_links	
expired_object_delete_marker	boolean	Cleanup object delete markers.
object_age_days	integer	Number of days since creation after which objects can be deleted. This cannot be used along with object_expiry_date.
object_expiry_date	string	Specific date from when objects can expire. This cannot be used with object_age_days.

non_current_version_expiration

Specifies a way to perform non_current_version_expiration action on filtered objects within a bucket.

Name	Туре	Description
_links	_links	
new_non_current_versions	integer	Number of latest non-current versions to be retained.
non_current_days	integer	Number of days after which non- current versions can be deleted.

object_filter

Specifies a way to filter objects within a bucket.

Name	Туре	Description
_links	_links	

Name	Туре	Description
prefix	string	A prefix that is matched against object-names within a bucket.
size_greater_than	integer	Size of the object greater than specified for which the corresponding lifecycle rule is to be applied.
size_less_than	integer	Size of the object smaller than specified for which the corresponding lifecycle rule is to be applied.
tags	array[string]	An array of key-value paired tags of the form <tag>or <tag=value>.</tag>

svm

Specifies the name of the SVM where this bucket exists.

Name	Туре	Description
_links	_links	
name	string	The name of the SVM. This field cannot be specified in a PATCH method.
uuid	string	The unique identifier of the SVM. This field cannot be specified in a PATCH method.

rules

Information about the lifecycle management rule of a bucket.

Name	Туре	Description
_links	_links	
abort_incomplete_multipart_uploa d	abort_incomplete_multipart_uploa d	Specifies a way to perform abort_incomplete_multipart_uplo ad action on filtered objects within a bucket. It cannot be specified with tags.
Name	Туре	Description
--------------------------------	--------------------------------	---
bucket_name	string	Specifies the name of the bucket. Bucket name is a string that can only contain the following combination of ASCII-range alphanumeric characters 0-9, a-z, ".", and "-".
enabled	boolean	Specifies whether or not the associated rule is enabled.
expiration	expiration	Specifies a way to perform expiration action on filtered objects within a bucket.
name	string	Bucket lifecycle management rule identifier. The length of the name can range from 0 to 256 characters.
non_current_version_expiration	non_current_version_expiration	Specifies a way to perform non_current_version_expiration action on filtered objects within a bucket.
object_filter	object_filter	Specifies a way to filter objects within a bucket.
svm	svm	Specifies the name of the SVM where this bucket exists.
uuid	string	Specifies the unique identifier of the bucket.

lifecycle_management

Lifecycle management is implemented as an object associated with a bucket. It defines rules to be applied against objects within a bucket. These rules are applied in the background and can delete objects.

Name	Туре	Description
rules	array[rules]	Specifies an object store lifecycle management policy.

s3_bucket_policy_condition

Information about policy conditions based on various condition operators and condition keys.

Name	Туре	Description
delimiters	array[string]	An array of delimiters that are compared with the delimiter value specified at the time of execution of an S3-based command, using the condition operator specified.
max_keys	array[integer]	An array of maximum keys that are allowed or denied to be retrieved using an S3 list operation, based on the condition operator specified.
operator	string	Condition operator that is applied to the specified condition key.
prefixes	array[string]	An array of prefixes that are compared with the input prefix value specified at the time of execution of an S3-based command, using the condition operator specified.
source_ips	array[string]	An array of IP address ranges that are compared with the IP address of a source command at the time of execution of an S3- based command, using the condition operator specified.
usernames	array[string]	An array of usernames that a current user in the context is evaluated against using the condition operators.

s3_bucket_policy_statement

Specifies information about a single access permission.

Name	Туре	Description
actions	array[string]	
conditions	array[s3_bucket_policy_condition]	Specifies bucket policy conditions.

Name	Туре	Description
effect	string	Specifies whether access is allowed or denied when a user requests the specific action. If access (to allow) is not granted explicitly to a resource, access is implicitly denied. Access can also be denied explicitly to a resource, in order to make sure that a user cannot access it, even if a different policy grants access.
principals	array[string]	
resources	array[string]	
sid	string	Specifies the statement identifier used to differentiate between statements. The sid length can range from 1 to 256 characters and can only contain the following combination of characters 0-9, A- Z, and a-z. Special characters are not valid.

policy

A policy is an object associated with a bucket. It defines resource (bucket, folder, or object) permissions. These policies get evaluated when an S3 user makes a request by executing a specific command. The user must be part of the principal (user or group) specified in the policy. Permissions in the policies determine whether the request is allowed or denied.

Name	Туре	Description
statements	array[s3_bucket_policy_statemen t]	Specifies bucket access policy statement.

destination

Name	Туре	Description
is_cloud	boolean	Specifies whether a bucket is protected within the Cloud. This field cannot be specified using a POST method.
is_external_cloud	boolean	Specifies whether a bucket is protected on external Cloud providers. This field cannot be specified using a POST method.

Name	Туре	Description
is_ontap	boolean	Specifies whether a bucket is protected within ONTAP. This field cannot be specified using a POST method.
		Default value: 1
		• readOnly: 1
		 Introduced in: 9.10
		• x-nullable: true

protection_status

Specifies attributes of bucket protection.

Name	Туре	Description
destination	destination	
is_protected	boolean	 Specifies whether a bucket is a source and if it is protected within ONTAP and/or an external cloud. This field cannot be specified using a POST method. Default value: 1 readOnly: 1 Introduced in: 9.10 x-nullable: true

qos_policy

Specifes "qos_policy.max_throughput_iops" and/or "qos_policy.max_throughput_mbps" or "qos_policy.min_throughput_iops" and/or "qos_policy.min_throughput_mbps". Specifying "min_throughput_iops" or "min_throughput_mbps" is only supported on volumes hosted on a node that is flash optimized. A pre-created QoS policy can also be used by specifying "qos_policy.name" or "qos_policy.uuid" properties. Setting or assigning a QoS policy to a bucket is not supported if its containing volume or SVM already has a QoS policy attached.

Name	Туре	Description
_links	_links	
max_throughput_iops	integer	Specifies the maximum throughput in IOPS, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.

Name	Туре	Description
max_throughput_mbps	integer	Specifies the maximum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.
min_throughput_iops	integer	Specifies the minimum throughput in IOPS, 0 means none. Setting "min_throughput" is supported on AFF platforms only, unless FabricPool tiering policies are set. This is mutually exclusive with name and UUID during POST and PATCH.
min_throughput_mbps	integer	Specifies the minimum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.
name	string	The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH.
uuid	string	The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH.

retention

Specifies the retention mode and default retention period configured on the bucket.

Name	Туре	Description
default_period	string	Specifies the default retention period that is applied to objects while committing them to the WORM state without an associated retention period. The retention period can be in years, or days. The retention period value represents a duration and must be specified in the ISO- 8601 duration format. A period specified for years and days is represented in the ISO-8601 format as "P <num>Y" and "P<num>D" respectively, for example "P10Y" represents a duration of 10 years. The period string must contain only a single time element that is, either years, or days. A duration which combines different periods is not supported, for example "P1Y10D" is not supported.</num></num>
mode	string	The lock mode of the bucket. compliance ‐ A SnapLock Compliance (SLC) bucket provides the highest level of WORM protection and an administrator cannot destroy a compliance bucket if it contains unexpired WORM objects. governance ‐ An administrator can delete a Governance bucket. no_lock ‐ Indicates the bucket does not support object locking.

svm

SVM, applies only to SVM-scoped objects.

Name	Туре	Description
_links	_links	
name	string	The name of the SVM. This field cannot be specified in a PATCH method.

Name	Туре	Description
uuid	string	The unique identifier of the SVM. This field cannot be specified in a PATCH method.

volume

Specifies the FlexGroup volume name and UUID where the bucket is hosted.

Name	Туре	Description
_links	_links	
name	string	The name of the volume. This field cannot be specified in a POST or PATCH method.
uuid	string	 Unique identifier for the volume. This corresponds to the instance- uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. example: 028baa66-41bd- 11e9-81d5-00a0986138f7 Introduced in: 9.6 x-nullable: true

s3_bucket

A bucket is a container of objects. Each bucket defines an object namespace. S3 requests specify objects using a bucket-name and object-name pair. An object resides within a bucket.

Name	Туре	Description
aggregates	array[aggregates]	A list of aggregates for FlexGroup volume constituents where the bucket is hosted. If this option is not specified, the bucket is auto- provisioned as a FlexGroup volume.
allowed	boolean	If this is set to true, an SVM administrator can manage the S3 service. If it is false, only the cluster administrator can manage the service. This field cannot be specified in a POST method.

Name	Туре	Description
audit_event_selector	audit_event_selector	Audit event selector allows you to specify access and permission types to audit.
comment	string	Can contain any additional information about the bucket being created or modified.
constituents_per_aggregate	integer	Specifies the number of constituents or FlexVol volumes per aggregate. A FlexGroup volume consisting of all such constituents across all specified aggregates is created. This option is used along with the aggregates option and cannot be used independently.
encryption	encryption	
lifecycle_management	lifecycle_management	Lifecycle management is implemented as an object associated with a bucket. It defines rules to be applied against objects within a bucket. These rules are applied in the background and can delete objects.
logical_used_size	integer	Specifies the bucket logical used size up to this point. This field cannot be specified using a POST or PATCH method.
name	string	Specifies the name of the bucket. Bucket name is a string that can only contain the following combination of ASCII-range alphanumeric characters 0-9, a-z, ".", and "-".
nas_path	string	Specifies the NAS path to which the nas bucket corresponds to.

Name	Туре	Description
policy	policy	A policy is an object associated with a bucket. It defines resource (bucket, folder, or object) permissions. These policies get evaluated when an S3 user makes a request by executing a specific command. The user must be part of the principal (user or group) specified in the policy. Permissions in the policies determine whether the request is allowed or denied.
protection_status	protection_status	Specifies attributes of bucket protection.
qos_policy	qos_policy	Specifes "qos_policy.max_throughput_iops " and/or "qos_policy.max_throughput_mb ps" or "qos_policy.min_throughput_iops" and/or "qos_policy.min_throughput_mbp s". Specifying "min_throughput_iops" or "min_throughput_mbps" is only supported on volumes hosted on a node that is flash optimized. A pre-created QoS policy can also be used by specifying "qos_policy.name" or "qos_policy.uuid" properties. Setting or assigning a QoS policy to a bucket is not supported if its containing volume or SVM already has a QoS policy attached.
retention	retention	Specifies the retention mode and default retention period configured on the bucket.
role	string	Specifies the role of the bucket. This field cannot be specified using a POST method.
size	integer	Specifies the bucket size in bytes; ranges from 190MB to 62PB.

Name	Туре	Description
storage_service_level	string	Specifies the storage service level of the FlexGroup volume on which the bucket should be created. Valid values are "value", "performance" or "extreme".
svm	svm	SVM, applies only to SVM- scoped objects.
type	string	Specifies the bucket type. Valid values are "s3"and "nas".
use_mirrored_aggregates	boolean	Specifies whether mirrored aggregates are selected when provisioning a FlexGroup. Only mirrored aggregates are used if this parameter is set to "true" and only unmirrored aggregates are used if this parameter is set to "false". The default value is "true" for a MetroCluster configuration and is "false" for a non- MetroCluster configuration.
uuid	string	Specifies the unique identifier of the bucket.
versioning_state	string	Specifies the versioning state of the bucket. Valid values are "disabled", "enabled" or "suspended". Note that the versioning state cannot be modified to 'disabled' from any other state.
volume	volume	Specifies the FlexGroup volume name and UUID where the bucket is hosted.

certificate

Specifies the certificate that will be used for creating HTTPS connections to the S3 server.

Name	Туре	Description
_links	_links	
name	string	Certificate name

Name	Туре	Description
uuid	string	Certificate UUID

iops

The rate of I/O operations observed at the storage object.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

latency

The round trip latency in microseconds observed at the storage object.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

throughput

The rate of throughput bytes per second observed at the storage object.

Name	Туре	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

metric

Performance numbers, such as IOPS latency and throughput, for SVM protocols.

Name	Туре	Description
_links	_links	
duration	string	The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
iops	iops	The rate of I/O operations observed at the storage object.
latency	latency	The round trip latency in microseconds observed at the storage object.

Name	Туре	Description
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_ delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput	throughput	The rate of throughput bytes per second observed at the storage object.
timestamp	string	The timestamp of the performance data.

iops_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.

Name	Туре	Description
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

latency_raw

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Type Description	
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

throughput_raw

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

Name	Type Description	
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

statistics

These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.

Name	Туре	Description
iops_raw	iops_raw	The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.
latency_raw	latency_raw	The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput_raw	throughput_raw	Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.
timestamp	string	The timestamp of the performance data.

s3_user

This is a container of S3 users.

Name	Туре	Description
access_key	string	Specifies the access key for the user.
comment	string	Can contain any additional information about the user being created or modified.
key_expiry_time	string	Specifies the date and time after which keys expire and are no longer valid.
key_time_to_live	string	 Indicates the time period from when this parameter is specified: when creating or modifying a user or when the user keys were last regenerated, after which the user keys expire and are no longer valid. Valid format is: 'PnDTnHnMnS PnW'. For example, P2DT6H3M10S specifies a time period of 2 days, 6 hours, 3 minutes, and 10 seconds. If the value specified is '0' seconds, then the keys won't expire.
name	string	Specifies the name of the user. A user name length can range from 1 to 64 characters and can only contain the following combination of characters 0-9, A-Z, a-z, "_", "+", "=", ",",",",",",",",",",",",",",",",
svm	svm	SVM, applies only to SVM- scoped objects.

error_arguments

Name	Туре	Description
code	string	Argument code

Name	Туре	Description
message	string	Message argument

returned_error

Name	Туре	Description	
arguments	array[error_arguments]	Message arguments	
code	string Error code		
message	string	Error message	
target	string	The target parameter that caused the error.	

Update the S3 server configuration for an SVM

PATCH /protocols/s3/services/{svm.uuid}

Introduced In: 9.7

Updates the S3 Server configuration of an SVM.

Related ONTAP commands

• vserver object-store-server modify

Learn more

DOC /protocols/s3/services

Parameters

Name	Туре	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

Request Body

Name	Туре	Description
_links	self_link	

Name	Туре	Description
buckets	array[s3_bucket]	This field cannot be specified in a PATCH method.
certificate	certificate	Specifies the certificate that will be used for creating HTTPS connections to the S3 server.
comment	string	Can contain any additional information about the server being created or modified.
default_unix_user	string	Specifies the default UNIX user for NAS Access.
default_win_user	string	Specifies the default Windows user for NAS Access.
enabled	boolean	Specifies whether the S3 server being created or modified should be up or down.
is_http_enabled	boolean	Specifies whether HTTP is enabled on the S3 server being created or modified. By default, HTTP is disabled on the S3 server.
is_https_enabled	boolean	Specifies whether HTTPS is enabled on the S3 server being created or modified. By default, HTTPS is enabled on the S3 server.
metric	metric	Performance numbers, such as IOPS latency and throughput, for SVM protocols.
name	string	Specifies the name of the S3 server. A server name can contain 3 to 253 characters using only the following combination of characters':' 0-9, A-Z, a-z, ".", and "-".
port	integer	Specifies the HTTP listener port for the S3 server. By default, HTTP is enabled on port 80. Valid values range from 1 to 65535.

Name	Туре	Description
secure_port	integer	Specifies the HTTPS listener port for the S3 server. By default, HTTPS is enabled on port 443. Valid values range from 1 to 65535.
statistics	statistics	These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.
svm	svm	SVM, applies only to SVM-scoped objects.
users	array[s3_user]	This field cannot be specified in a PATCH method.

Example request

```
{
 " links": {
   "self": {
     "href": "/api/resourcelink"
   }
 },
 "buckets": [
   {
     "aggregates": [
       {
         " links": {
           "self": {
             "href": "/api/resourcelink"
           }
         },
         "name": "aggr1",
         "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
       }
     ],
     "audit event selector": {
       "access": "string",
       "permission": "string"
     },
     "comment": "S3 bucket.",
     "constituents per aggregate": 4,
     "lifecycle management": {
       "rules": [
         {
            " links": {
             "self": {
              "href": "/api/resourcelink"
              }
            },
            "abort incomplete multipart upload": {
             " links": {
               "self": {
                 "href": "/api/resourcelink"
               }
              }
            },
            "bucket_name": "bucket1",
            "expiration": {
             " links": {
                "self": {
```

```
"href": "/api/resourcelink"
         }
        },
        "object expiry date": "string"
      },
      "name": "string",
      "non current version expiration": {
        " links": {
          "self": {
           "href": "/api/resourcelink"
          }
        }
      },
      "object filter": {
        " links": {
          "self": {
           "href": "/api/resourcelink"
         }
        },
        "prefix": "/logs",
        "size greater than": 10240,
        "size less than": 10485760,
        "tags": [
         "project1=projA",
         "project2=projB"
       ]
      },
      "svm": {
       " links": {
          "self": {
           "href": "/api/resourcelink"
         }
        },
        "name": "svm1",
       "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      },
      "uuid": "414b29a1-3b26-11e9-bd58-0050568ea055"
   }
 1
},
"logical used size": 0,
"name": "bucket1",
"nas path": "/",
"policy": {
  "statements": [
   {
```

```
"actions": [
       "GetObject",
       "PutObject",
       "DeleteObject",
       "ListBucket"
      ],
      "conditions": [
       {
          "delimiters": [
          "/"
          ],
          "max keys": [
          1000
         ],
          "operator": "ip_address",
          "prefixes": [
          "pref"
          ],
          "source_ips": [
          "1.1.1.1",
          "1.2.2.0/24"
          ],
         "usernames": [
          "user1"
         ]
       }
     ],
      "effect": "allow",
     "principals": [
      "user1",
       "group/grp1",
       "nasgroup/group1"
      ],
      "resources": [
      "bucket1",
      "bucket1/*"
     ],
     "sid": "FullAccessToUser1"
    }
 ]
},
"qos policy": {
 " links": {
   "self": {
     "href": "/api/resourcelink"
   }
```

```
},
      "max throughput iops": 10000,
      "max throughput mbps": 500,
      "min throughput iops": 2000,
      "min throughput mbps": 500,
      "name": "performance",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "retention": {
      "default period": "P10Y",
      "mode": "governance"
    },
    "role": "string",
    "size": 1677721600,
    "storage service level": "value",
    "svm": {
     " links": {
        "self": {
         "href": "/api/resourcelink"
       }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "type": "s3",
    "uuid": "414b29a1-3b26-11e9-bd58-0050568ea055",
    "versioning state": "enabled",
    "volume": {
      " links": {
        "self": {
          "href": "/api/resourcelink"
       }
      },
      "name": "volume1",
     "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
    }
 }
],
"certificate": {
  " links": {
    "self": {
     "href": "/api/resourcelink"
   }
  },
  "name": "string",
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
```

```
},
"comment": "S3 server",
"default unix user": "string",
"default win user": "string",
"metric": {
 " links": {
    "self": {
     "href": "/api/resourcelink"
   }
  },
  "duration": "PT15S",
  "iops": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "latency": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "status": "ok",
  "throughput": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
 "timestamp": "2017-01-25 06:20:13 -0500"
},
"name": "Server-1",
"port": 80,
"secure port": 443,
"statistics": {
  "iops raw": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "latency raw": {
   "read": 200,
   "total": 1000,
   "write": 100
  },
  "status": "ok",
  "throughput raw": {
   "read": 200,
```

```
"total": 1000,
     "write": 100
   },
   "timestamp": "2017-01-25 06:20:13 -0500"
  },
 "svm": {
    " links": {
     "self": {
       "href": "/api/resourcelink"
     }
    },
   "name": "svm1",
   "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
 },
 "users": [
   {
      "access key": "HJAKU28M3SXTE2UXUACV",
      "comment": "S3 user",
      "key_expiry_time": "2023-12-31 19:00:00 -0500",
      "key time to live": "PT6H3M",
     "name": "user-1",
      "svm": {
        " links": {
         "self": {
           "href": "/api/resourcelink"
         }
        },
        "name": "svm1",
       "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      }
   }
 ]
}
```

Response

Status: 200, Ok

Error

Status: Default

ONTAP Error Response Codes

Error Code	Description
92405789	The name \"{object server name}\" is not valid. A valid object server name must be a fully qualified domain name.
92405790	Object store server name is not valid. Object store server names must have between 3 and 253 characters.
92406151	Set the enabled field of the server to "down" before modifying following fields: {field name}

Name	Туре	Description
error	returned_error	

Example error

```
{
    "error": {
        "arguments": [
            {
            "code": "string",
            "message": "string"
            }
        ],
        "code": "4",
        "message": "entry doesn't exist",
        "target": "uuid"
     }
}
```

Definitions

See Definitions

href

Name	Туре	Description
href	string	

self_link

Name	Туре	Description
self	href	

_links

Name	Туре	Description
self	href	

aggregates

Aggregate

Name	Туре	Description
_links	_links	
name	string	
uuid	string	

audit_event_selector

Audit event selector allows you to specify access and permission types to audit.

Name	Туре	Description
access	string	Specifies read and write access types.
permission	string	Specifies allow and deny permission types.

encryption

Name	Туре	Description
enabled	boolean	Specifies whether encryption is enabled on the bucket. By default, encryption is disabled on a bucket. This field cannot be specified in a POST method.

Specifies a way to perform abort_incomplete_multipart_upload action on filtered objects within a bucket. It cannot be specified with tags.

Name	Туре	Description
_links	_links	
after_initiation_days	integer	Number of days of initiation after which uploads can be aborted.

expiration

Specifies a way to perform expiration action on filtered objects within a bucket.

Name	Туре	Description
_links	_links	
expired_object_delete_marker	boolean	Cleanup object delete markers.
object_age_days	integer	Number of days since creation after which objects can be deleted. This cannot be used along with object_expiry_date.
object_expiry_date	string	Specific date from when objects can expire. This cannot be used with object_age_days.

non_current_version_expiration

Specifies a way to perform non_current_version_expiration action on filtered objects within a bucket.

Name	Туре	Description
_links	_links	
new_non_current_versions	integer	Number of latest non-current versions to be retained.
non_current_days	integer	Number of days after which non- current versions can be deleted.

object_filter

Specifies a way to filter objects within a bucket.

Name	Туре	Description
_links	_links	

Name	Туре	Description
prefix	string	A prefix that is matched against object-names within a bucket.
size_greater_than	integer	Size of the object greater than specified for which the corresponding lifecycle rule is to be applied.
size_less_than	integer	Size of the object smaller than specified for which the corresponding lifecycle rule is to be applied.
tags	array[string]	An array of key-value paired tags of the form <tag>or <tag=value>.</tag>

svm

Specifies the name of the SVM where this bucket exists.

Name	Туре	Description
_links	_links	
name	string	The name of the SVM. This field cannot be specified in a PATCH method.
uuid	string	The unique identifier of the SVM. This field cannot be specified in a PATCH method.

rules

Information about the lifecycle management rule of a bucket.

Name	Туре	Description
_links	_links	
abort_incomplete_multipart_uploa d	abort_incomplete_multipart_uploa d	Specifies a way to perform abort_incomplete_multipart_uplo ad action on filtered objects within a bucket. It cannot be specified with tags.

Name	Туре	Description
bucket_name	string	Specifies the name of the bucket. Bucket name is a string that can only contain the following combination of ASCII-range alphanumeric characters 0-9, a-z, ".", and "-".
enabled	boolean	Specifies whether or not the associated rule is enabled.
expiration	expiration	Specifies a way to perform expiration action on filtered objects within a bucket.
name	string	Bucket lifecycle management rule identifier. The length of the name can range from 0 to 256 characters.
non_current_version_expiration	non_current_version_expiration	Specifies a way to perform non_current_version_expiration action on filtered objects within a bucket.
object_filter	object_filter	Specifies a way to filter objects within a bucket.
svm	svm	Specifies the name of the SVM where this bucket exists.
uuid	string	Specifies the unique identifier of the bucket.

lifecycle_management

Lifecycle management is implemented as an object associated with a bucket. It defines rules to be applied against objects within a bucket. These rules are applied in the background and can delete objects.

Name	Туре	Description
rules	array[rules]	Specifies an object store lifecycle management policy.

s3_bucket_policy_condition

Information about policy conditions based on various condition operators and condition keys.

Name	Туре	Description
delimiters	array[string]	An array of delimiters that are compared with the delimiter value specified at the time of execution of an S3-based command, using the condition operator specified.
max_keys	array[integer]	An array of maximum keys that are allowed or denied to be retrieved using an S3 list operation, based on the condition operator specified.
operator	string	Condition operator that is applied to the specified condition key.
prefixes	array[string]	An array of prefixes that are compared with the input prefix value specified at the time of execution of an S3-based command, using the condition operator specified.
source_ips	array[string]	An array of IP address ranges that are compared with the IP address of a source command at the time of execution of an S3- based command, using the condition operator specified.
usernames	array[string]	An array of usernames that a current user in the context is evaluated against using the condition operators.

s3_bucket_policy_statement

Specifies information about a single access permission.

Name	Туре	Description
actions	array[string]	
conditions	array[s3_bucket_policy_condition]	Specifies bucket policy conditions.

Name	Туре	Description
effect	string	Specifies whether access is allowed or denied when a user requests the specific action. If access (to allow) is not granted explicitly to a resource, access is implicitly denied. Access can also be denied explicitly to a resource, in order to make sure that a user cannot access it, even if a different policy grants access.
principals	array[string]	
resources	array[string]	
sid	string	Specifies the statement identifier used to differentiate between statements. The sid length can range from 1 to 256 characters and can only contain the following combination of characters 0-9, A- Z, and a-z. Special characters are not valid.

policy

A policy is an object associated with a bucket. It defines resource (bucket, folder, or object) permissions. These policies get evaluated when an S3 user makes a request by executing a specific command. The user must be part of the principal (user or group) specified in the policy. Permissions in the policies determine whether the request is allowed or denied.

Name	Туре	Description
statements	array[s3_bucket_policy_statemen t]	Specifies bucket access policy statement.

destination

Name	Туре	Description
is_cloud	boolean	Specifies whether a bucket is protected within the Cloud. This field cannot be specified using a POST method.
is_external_cloud	boolean	Specifies whether a bucket is protected on external Cloud providers. This field cannot be specified using a POST method.

Name	Туре	Description
is_ontap	boolean	Specifies whether a bucket is protected within ONTAP. This field cannot be specified using a POST method.
		Default value: 1
		 readOnly: 1
		Introduced in: 9.10
		• x-nullable: true

protection_status

Specifies attributes of bucket protection.

Name Ty	ӯре	Description
destination de	estination	
is_protected bo	oolean	Specifies whether a bucket is a source and if it is protected within ONTAP and/or an external cloud. This field cannot be specified using a POST method. • Default value: 1 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true

qos_policy

Specifes "qos_policy.max_throughput_iops" and/or "qos_policy.max_throughput_mbps" or "qos_policy.min_throughput_iops" and/or "qos_policy.min_throughput_mbps". Specifying "min_throughput_iops" or "min_throughput_mbps" is only supported on volumes hosted on a node that is flash optimized. A pre-created QoS policy can also be used by specifying "qos_policy.name" or "qos_policy.uuid" properties. Setting or assigning a QoS policy to a bucket is not supported if its containing volume or SVM already has a QoS policy attached.

Name	Туре	Description
_links	_links	
max_throughput_iops	integer	Specifies the maximum throughput in IOPS, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.

Name	Туре	Description
max_throughput_mbps	integer	Specifies the maximum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.
min_throughput_iops	integer	Specifies the minimum throughput in IOPS, 0 means none. Setting "min_throughput" is supported on AFF platforms only, unless FabricPool tiering policies are set. This is mutually exclusive with name and UUID during POST and PATCH.
min_throughput_mbps	integer	Specifies the minimum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH.
name	string	The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH.
uuid	string	The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH.

retention

Specifies the retention mode and default retention period configured on the bucket.

Name	Туре	Description
default_period	string	Specifies the default retention period that is applied to objects while committing them to the WORM state without an associated retention period. The retention period can be in years, or days. The retention period value represents a duration and must be specified in the ISO- 8601 duration format. A period specified for years and days is represented in the ISO-8601 format as "P <num>Y" and "P<num>D" respectively, for example "P10Y" represents a duration of 10 years. The period string must contain only a single time element that is, either years, or days. A duration which combines different periods is not supported, for example "P1Y10D" is not supported.</num></num>
mode	string	The lock mode of the bucket. compliance ‐ A SnapLock Compliance (SLC) bucket provides the highest level of WORM protection and an administrator cannot destroy a compliance bucket if it contains unexpired WORM objects. governance ‐ An administrator can delete a Governance bucket. no_lock ‐ Indicates the bucket does not support object locking.

svm

SVM, applies only to SVM-scoped objects.

Name	Туре	Description
_links	_links	
name	string	The name of the SVM. This field cannot be specified in a PATCH method.

Name	Туре	Description
uuid	string	The unique identifier of the SVM. This field cannot be specified in a PATCH method.

volume

Specifies the FlexGroup volume name and UUID where the bucket is hosted.

Name	Туре	Description
_links	_links	
name	string	The name of the volume. This field cannot be specified in a POST or PATCH method.
uuid	string	 Unique identifier for the volume. This corresponds to the instance- uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. example: 028baa66-41bd- 11e9-81d5-00a0986138f7 Introduced in: 9.6 x-nullable: true

s3_bucket

A bucket is a container of objects. Each bucket defines an object namespace. S3 requests specify objects using a bucket-name and object-name pair. An object resides within a bucket.

Name	Туре	Description
aggregates	array[aggregates]	A list of aggregates for FlexGroup volume constituents where the bucket is hosted. If this option is not specified, the bucket is auto- provisioned as a FlexGroup volume.
allowed	boolean	If this is set to true, an SVM administrator can manage the S3 service. If it is false, only the cluster administrator can manage the service. This field cannot be specified in a POST method.
Name	Туре	Description
----------------------------	----------------------	--
audit_event_selector	audit_event_selector	Audit event selector allows you to specify access and permission types to audit.
comment	string	Can contain any additional information about the bucket being created or modified.
constituents_per_aggregate	integer	Specifies the number of constituents or FlexVol volumes per aggregate. A FlexGroup volume consisting of all such constituents across all specified aggregates is created. This option is used along with the aggregates option and cannot be used independently.
encryption	encryption	
lifecycle_management	lifecycle_management	Lifecycle management is implemented as an object associated with a bucket. It defines rules to be applied against objects within a bucket. These rules are applied in the background and can delete objects.
logical_used_size	integer	Specifies the bucket logical used size up to this point. This field cannot be specified using a POST or PATCH method.
name	string	Specifies the name of the bucket. Bucket name is a string that can only contain the following combination of ASCII-range alphanumeric characters 0-9, a-z, ".", and "-".
nas_path	string	Specifies the NAS path to which the nas bucket corresponds to.

Name	Туре	Description
policy	policy	A policy is an object associated with a bucket. It defines resource (bucket, folder, or object) permissions. These policies get evaluated when an S3 user makes a request by executing a specific command. The user must be part of the principal (user or group) specified in the policy. Permissions in the policies determine whether the request is allowed or denied.
protection_status	protection_status	Specifies attributes of bucket protection.
qos_policy	qos_policy	Specifes "qos_policy.max_throughput_iops " and/or "qos_policy.max_throughput_mb ps" or "qos_policy.min_throughput_iops" and/or "qos_policy.min_throughput_mbp s". Specifying "min_throughput_iops" or "min_throughput_mbps" is only supported on volumes hosted on a node that is flash optimized. A pre-created QoS policy can also be used by specifying "qos_policy.name" or "qos_policy.uuid" properties. Setting or assigning a QoS policy to a bucket is not supported if its containing volume or SVM already has a QoS policy attached.
retention	retention	Specifies the retention mode and default retention period configured on the bucket.
role	string	Specifies the role of the bucket. This field cannot be specified using a POST method.
size	integer	Specifies the bucket size in bytes; ranges from 190MB to 62PB.

Name	Туре	Description
storage_service_level	string	Specifies the storage service level of the FlexGroup volume on which the bucket should be created. Valid values are "value", "performance" or "extreme".
svm	svm	SVM, applies only to SVM- scoped objects.
type	string	Specifies the bucket type. Valid values are "s3"and "nas".
use_mirrored_aggregates	boolean	Specifies whether mirrored aggregates are selected when provisioning a FlexGroup. Only mirrored aggregates are used if this parameter is set to "true" and only unmirrored aggregates are used if this parameter is set to "false". The default value is "true" for a MetroCluster configuration and is "false" for a non- MetroCluster configuration.
uuid	string	Specifies the unique identifier of the bucket.
versioning_state	string	Specifies the versioning state of the bucket. Valid values are "disabled", "enabled" or "suspended". Note that the versioning state cannot be modified to 'disabled' from any other state.
volume	volume	Specifies the FlexGroup volume name and UUID where the bucket is hosted.

certificate

Specifies the certificate that will be used for creating HTTPS connections to the S3 server.

Name	Туре	Description
_links	_links	
name	string	Certificate name

Name	Туре	Description
uuid	string	Certificate UUID

iops

The rate of I/O operations observed at the storage object.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

latency

The round trip latency in microseconds observed at the storage object.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

throughput

The rate of throughput bytes per second observed at the storage object.

Name	Туре	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

metric

Performance numbers, such as IOPS latency and throughput, for SVM protocols.

Name	Туре	Description
_links	_links	
duration	string	The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
iops	iops	The rate of I/O operations observed at the storage object.
latency	latency	The round trip latency in microseconds observed at the storage object.

Name	Туре	Description
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_ delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput	throughput	The rate of throughput bytes per second observed at the storage object.
timestamp	string	The timestamp of the performance data.

iops_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.

Name	Туре	Description
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

latency_raw

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Туре	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

throughput_raw

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

Name	Туре	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Peformance metric for write I/O operations.

statistics

These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.

Name	Туре	Description
iops_raw	iops_raw	The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.
latency_raw	latency_raw	The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput_raw	throughput_raw	Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.
timestamp	string	The timestamp of the performance data.

s3_user

This is a container of S3 users.

Name	Туре	Description
access_key	string	Specifies the access key for the user.
comment	string	Can contain any additional information about the user being created or modified.
key_expiry_time	string	Specifies the date and time after which keys expire and are no longer valid.
key_time_to_live	string	 Indicates the time period from when this parameter is specified: when creating or modifying a user or when the user keys were last regenerated, after which the user keys expire and are no longer valid. Valid format is: 'PnDTnHnMnS PnW'. For example, P2DT6H3M10S specifies a time period of 2 days, 6 hours, 3 minutes, and 10 seconds. If the value specified is '0' seconds, then the keys won't expire.
name	string	Specifies the name of the user. A user name length can range from 1 to 64 characters and can only contain the following combination of characters 0-9, A-Z, a-z, "_", "+", "=", ",", ".","@", and "-".
svm	svm	SVM, applies only to SVM- scoped objects.

s3_service

Specifies the S3 server configuration.

Name	Туре	Description
_links	self_link	
buckets	array[s3_bucket]	This field cannot be specified in a PATCH method.
certificate	certificate	Specifies the certificate that will be used for creating HTTPS connections to the S3 server.
comment	string	Can contain any additional information about the server being created or modified.
default_unix_user	string	Specifies the default UNIX user for NAS Access.
default_win_user	string	Specifies the default Windows user for NAS Access.
enabled	boolean	Specifies whether the S3 server being created or modified should be up or down.
is_http_enabled	boolean	Specifies whether HTTP is enabled on the S3 server being created or modified. By default, HTTP is disabled on the S3 server.
is_https_enabled	boolean	Specifies whether HTTPS is enabled on the S3 server being created or modified. By default, HTTPS is enabled on the S3 server.
metric	metric	Performance numbers, such as IOPS latency and throughput, for SVM protocols.
name	string	Specifies the name of the S3 server. A server name can contain 3 to 253 characters using only the following combination of characters':' 0-9, A-Z, a-z, ".", and "-".

Name	Туре	Description
port	integer	Specifies the HTTP listener port for the S3 server. By default, HTTP is enabled on port 80. Valid values range from 1 to 65535.
secure_port	integer	Specifies the HTTPS listener port for the S3 server. By default, HTTPS is enabled on port 443. Valid values range from 1 to 65535.
statistics	statistics	These are raw performance numbers, such as IOPS latency and throughput for SVM protocols. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.
svm	svm	SVM, applies only to SVM- scoped objects.
users	array[s3_user]	This field cannot be specified in a PATCH method.

error_arguments

Name	Туре	Description
code	string	Argument code
message	string	Message argument

returned_error

Name	Туре	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.