



# SnapLock

ONTAP 9.14.1 REST API reference

NetApp

May 23, 2024

# Table of Contents

|  |     |
|--|-----|
| SnapLock .....                                     | 1   |
| SnapLock overview .....                            | 1   |
| Manage SnapLock audit logs .....                   | 2   |
| Manage the SnapLock ComplianceClock .....          | 41  |
| Manage event based retention operations .....      | 54  |
| Manage event based retention policies .....        | 81  |
| View key information about files and volumes ..... | 108 |
| Manage SnapLock file retention time .....          | 129 |
| Manage SnapLock storage litigations .....          | 146 |
| View litigation ID files .....                     | 169 |
| Manage legal-hold operations .....                 | 174 |

# SnapLock

## SnapLock overview

SnapLock is an alternative to the traditional optical "write once, read many" (WORM) data. SnapLock is used for the storage of read-only WORM data. SnapLock is a license-based, disk-based, open-protocol feature that works with application software to administer non-rewritable storage of data. The primary objective of this feature is to provide storage-enforced WORM and retention functionality. SnapLock can be deployed for protecting data in strict regulatory environments in such a way that even the storage administrator is considered an untrusted party. SnapLock provides special purpose volumes in which files can be stored and committed to a non-erasable, non-rewritable state either forever or for a designated retention period. SnapLock allows this retention to be performed at the granularity of individual files. These APIs allow you to manage the following endpoints:

- SnapLock log
- SnapLock compliance-clock
- SnapLock event-retention
- SnapLock file retention
- SnapLock privileged-delete
- SnapLock file fingerprint
- SnapLock legal-hold

## APIs

### SnapLock log

These APIs are used to create and initialize the SnapLock log configuration for an SVM, modify attributes associated with the SnapLock log configuration, and delete the auditlog configuration.

### SnapLock compliance-clock

This API manages the ComplianceClock of the system. ComplianceClock determines the expiry time of the SnapLock objects in the system. ComplianceClock can be initialized only once by the user and once it is set, it cannot be changed or altered by the user.

### SnapLock event-retention

This API is used to create Event Based Retention (EBR) policies for an SVM. A policy consists of a policy-name and a retention-period. Only a user with security login role vsadmin-snaplock is allowed to perform this operation.

### SnapLock file retention

This API is used to set the retention time of a file. Retention time expects the date in ISO 8601 format or "infinite".

### SnapLock privileged-delete

This API is used to perform a privileged-delete operation on unexpired WORM files on a SnapLock Enterprise volume. The only built-in role that has access to the command is "vsadmin-snaplock".

## SnapLock file fingerprint

This API is used to start the fingerprint computation on a file.

## SnapLock legal-hold

This API is used to retain Compliance-mode WORM files for the duration of a litigation. A file under a Legal-Hold behaves like a WORM file with an indefinite retention period. Only a user with security login role vsadmin-snaplock is allowed to perform the operation.

# Manage SnapLock audit logs

## Storage SnapLock audit-logs endpoint overview

The SnapLock log volume can be a SnapLock Compliance volume or SnapLock Enterprise volume. The SnapLock log infrastructure creates directories and files in this volume to store the SnapLock log records. The directory named "snaplock\_log" is created under the root. There are three subdirectories created under the "snaplock\_log" directory. They are "privileged\_delete\_logs", "system\_logs" and "legal\_hold\_logs". The log files are created and populated under these subdirectories when respective SnapLock operations are initiated. The maximum log size specifies the maximum size of a log file that stores SnapLock log records. When the file reaches this size, the log infrastructure archives it and creates a new log file. An active log file has the suffix "-present" in the name. When a file is archived, it is renamed such that the suffix is replaced with the date of archival. The default retention period is the length of time the log file is retained, if the SnapLock log records that are stored in the file do not carry any retention period.

### Examples

1. Verifies that the audit log is configured for the specified SVM:

```
GET "/api/storage/snaplock/audit-logs/?svm.name=VS0"
```

1. Verifies that the specified volume is an audit log volume:

```
GET "/api/storage/snaplock/audit-logs/?log_volume.volume.name=VS0 ALOG"
```

### Examples

1. Creates a SnapLock log configuration by providing SVM name:

```
POST "/api/storage/snaplock/audit-logs" '{"svm": {"name": "VS3"},  
"log_volume": { "volume": { "name": "VS3 ALOG" }, "max_log_size": "20971520",  
"retention_period": "P30Y" } }'
```

1. Creates a SnapLock log configuration by providing SVM UUID:

```
POST "/api/storage/snaplock/audit-logs" '{"svm": {"uuid": "bc744cc7-296d-11e9-a26f-0050568e5b05"}, "log_volume": { "volume": { "name": "VS3 ALOG" }, "max_log_size": "20971520", "retention_period": "P30Y" }}'
```

- Creates a SnapLock log configuration without specifying a retention period:

```
POST "/api/storage/snaplock/audit-logs" '{"svm": {"name": "VS3"}, "log_volume": {"volume": {"name": "VS3 ALOG"} } }'
```

## Examples

- Updates the audit log volume:

```
PATCH "/api/storage/snaplock/audit-logs/bc744cc7-296d-11e9-a26f-0050568e5b05" '{"log_volume": {"volume": {"name": "VS4 ALOG_NEW"} } }'
```

- Updates the maximum size of the log file and the retention period:

```
PATCH "/api/storage/snaplock/audit-logs/420cac7a-296a-11e9-a26f-0050568e5b05" '{"log_volume": {"max_log_size": "20971520", "retention_period": "P1Y"} }'
```

- Archives all of the audit log files:

```
PATCH "/api/storage/snaplock/audit-logs/c7e4fa7d-2968-11e9-a26f-0050568e5b05" '{"log_archive": {"archive": "true"} }'
```

- Archives the specified audit log file:

```
PATCH "/api/storage/snaplock/audit-logs/c7e4fa7d-2968-11e9-a26f-0050568e5b05" '{"log_archive": {"archive": "true", "base_name": "privileged_delete"} }'
```

## Retrieve SVMs configured with audit log volumes

GET /storage/snaplock/audit-logs

**Introduced In:** 9.7

Retrieves a list of SVMs configured with audit log volumes.

## Related ONTAP commands

- `snaplock log show`

## Learn more

- [DOC /storage/snaplock/audit-logs](#)

## Parameters

| Name                        | Type          | In    | Required | Description                           |
|-----------------------------|---------------|-------|----------|---------------------------------------|
| svm.uuid                    | string        | query | False    | Filter by svm.uuid                    |
| svm.name                    | string        | query | False    | Filter by svm.name                    |
| log_files.path              | string        | query | False    | Filter by log_files.path              |
| log_files.size              | integer       | query | False    | Filter by log_files.size              |
| log_files.base_name         | string        | query | False    | Filter by log_files.base_name         |
| log_files.expiry_time       | string        | query | False    | Filter by log_files.expiry_time       |
| log_volume.retention_period | string        | query | False    | Filter by log_volume.retention_period |
| log_volume.max_log_size     | integer       | query | False    | Filter by log_volume.max_log_size     |
| log_volume.volume.name      | string        | query | False    | Filter by log_volume.volume.name      |
| log_volume.volume.uuid      | string        | query | False    | Filter by log_volume.volume.uuid      |
| fields                      | array[string] | query | False    | Specify the fields to return.         |
| max_records                 | integer       | query | False    | Limit the number of records returned. |

| Name           | Type          | In    | Required | Description  |
|----------------|---------------|-------|----------|--|
| return_timeout | integer       | query | False    | <p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul> |
| return_records | boolean       | query | False    | <p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>  |
| order_by       | array[string] | query | False    | Order results by specified fields and optional [asc]   |

## Response

```
Status: 200, Ok
```

| Name        | Type                                  | Description       |
|-------------|---------------------------------------|-------------------|
| _links      | <a href="#">_links</a>                |                   |
| num_records | integer                               | Number of records |
| records     | array[ <a href="#">snaplock_log</a> ] |                   |

## Example response

```
{  
    "_links": {  
        "next": {  
            "href": "/api/resourcelink"  
        },  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "num_records": 1,  
    "records": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "log_archive": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "base_name": "legal_hold"  
        },  
        "log_files": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "base_name": "legal_hold",  
            "expiry_time": "2058-06-04 15:00:00 -0400",  
            "path": "/snaplock_log/system_logs/20180822_005947_GMT-present",  
            "size": 20000  
        },  
        "log_volume": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "max_log_size": 20971520,  
            "retention_period": "P30M",  
            "volume": {  
                "log_files": {  
                    "base_name": "legal_hold",  
                    "expiry_time": "2058-06-04 15:00:00 -0400",  
                    "path": "/snaplock_log/system_logs/20180822_005947_GMT-present",  
                    "size": 20000  
                },  
                "log_archive": {  
                    "base_name": "legal_hold",  
                    "expiry_time": "2058-06-04 15:00:00 -0400",  
                    "path": "/snaplock_log/system_logs/20180822_005947_GMT-present",  
                    "size": 20000  
                }  
            }  
        }  
    }  
}
```

```

    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
},
"svm": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
}

```

## Error

Status: Default, Error

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{
    "error": {
        "arguments": {
            "code": "string",
            "message": "string"
        },
        "code": "4",
        "message": "entry doesn't exist",
        "target": "uuid"
    }
}
```

## **Definitions**

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| next | href |             |
| self | href |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

log\_archive

| Name      | Type    | Description   |
|-----------|---------|---|
| _links    | _links  |   |
| archive   | boolean | Archive the specified SnapLock log file for the given base_name, and create a new log file. If base_name is not mentioned, archive all log files. |
| base_name | string  | Base name of log archive  |

snaplock\_log\_file

| Name        | Type   | Description   |
|-------------|--------|---|
| _links      | _links |   |
| base_name   | string | Base name of log file   |
| expiry_time | string | Expiry time of the log file in date-time format. Value '9999-12-31T00:00:00Z' indicates infinite expiry time. |
| path        | string | Absolute path of the log file in the volume   |

| Name | Type    | Description                   |
|------|---------|-------------------------------|
| size | integer | Size of the log file in bytes |

volume

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string                 | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> <li>example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>Introduced in: 9.6</li> <li>x-nullability: true</li> </ul> |

snaplock\_log\_volume

| Name         | Type                   | Description                       |
|--------------|------------------------|-----------------------------------|
| _links       | <a href="#">_links</a> |                                   |
| max_log_size | integer                | Maximum size of log file in bytes |

| Name             | Type                   | Description   |
|------------------|------------------------|---|
| retention_period | string                 | Specifies the default log record retention period. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours, minutes and seconds. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. A duration in hours, minutes and seconds is represented by "PT<num>H", "PT<num>M", and "PT<num>S" respectively. The period string must contain only a single time element i.e. either years, months, days, hours, minutes or seconds. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the string "infinite".</num></num></num></num></num> |
| volume           | <a href="#">volume</a> |   |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

[snaplock\\_log](#)

| Name        | Type                                       | Description                              |
|-------------|--|--|
| _links      | <a href="#">_links</a>                     |  |
| log_archive | <a href="#">log_archive</a>                |  |
| log_files   | array[ <a href="#">snaplock_log_file</a> ] |  |
| log_volume  | <a href="#">snaplock_log_volume</a>        |  |
| svm         | <a href="#">svm</a>                        | SVM, applies only to SVM-scoped objects. |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                                     | Description                                 |
|-----------|--|---|
| arguments | array[ <a href="#">error_arguments</a> ] | Message arguments                           |
| code      | string                                   | Error code                                  |
| message   | string                                   | Error message                               |
| target    | string                                   | The target parameter that caused the error. |

## Create a SnapLock log configuration for an SVM

POST /storage/snaplock/audit-logs

**Introduced In:** 9.7

Creates a SnapLock log configuration for an SVM. A SnapLock log configuration consists of a volume to store the log, the maximum size of the log file, and the default period of time for which the log file should be retained. The volume must be a Read-Write SnapLock volume of type Enterprise or Compliance. The input parameter retention\_period expects the duration in ISO 8601 format.

### Required properties

- `svm.uuid` or `svm.name` - Name or UUID of the SVM.
- `log_volume.volume.name` or `log_volume.volume.uuid` - Name or UUID of audit log volume.

## **Recommended optional properties**

- `log_volume.max_log_size` - Max log file size.
- `log_volume.volume.retention_period` - Retention period of log file.

## **Default property values**

If not specified in POST, the following default property values are assigned:

- `log_volume.retention_period` - *P6M*
- `log_volume.max_log_size` - *10MB*

## **Related ONTAP commands**

- `snaplock log create`

## **Learn more**

- [DOC /storage/snaplock/audit-logs](#)

## **Parameters**

| Name           | Type    | In    | Required | Description  |
|----------------|---------|-------|----------|--|
| return_timeout | integer | query | False    | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul> |
| return_records | boolean | query | False    | <p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> <li>• Default value:</li> </ul>  |

## Request Body

| Name        | Type                                       | Description |
|-------------|--|-------------|
| _links      | <a href="#">_links</a>                     |             |
| log_archive | <a href="#">log_archive</a>                |             |
| log_files   | array[ <a href="#">snaplock_log_file</a> ] |             |
| log_volume  | <a href="#">snaplock_log_volume</a>        |             |

| Name | Type                | Description                              |
|------|---------------------|--|
| svm  | <a href="#">svm</a> | SVM, applies only to SVM-scoped objects. |

## Example request

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "log_archive": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "base_name": "legal_hold"  
    },  
    "log_files": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "base_name": "legal_hold",  
        "expiry_time": "2058-06-04 15:00:00 -0400",  
        "path": "/snaplock_log/system_logs/20180822_005947_GMT-present",  
        "size": 20000  
    },  
    "log_volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "max_log_size": 20971520,  
        "retention_period": "P30M",  
        "volume": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "name": "volume1",  
            "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
        }  
    },  
    "svm": {
```

```

    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svml",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}

```

## Response

Status: 202, Accepted

| Name | Type     | Description |
|------|----------|-------------|
| job  | job_link |             |

## Example response

```
{
  "job": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "uuid": "string"
  }
}
```

## Headers

| Name     | Description                               | Type   |
|----------|---|--------|
| Location | Useful for tracking the resource location | string |

## Response

Status: 201, Created

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 918236     | The specified volume name and UUID refer to different volumes                      |
| 918253     | Incorrect format for the retention period, duration must be in the ISO-8601 format |
| 13763161   | Audit logging is already configured for the SVM                                    |
| 14090340   | {field} is a required field  |
| 14090343   | Invalid Field  |
| 14090346   | Internal Error. Wait a few minutes, then try the command again                     |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

log\_archive

| Name      | Type    | Description   |
|-----------|---------|---|
| _links    | _links  |   |
| archive   | boolean | Archive the specified SnapLock log file for the given base_name, and create a new log file. If base_name is not mentioned, archive all log files. |
| base_name | string  | Base name of log archive  |

snaplock\_log\_file

| Name        | Type    | Description   |
|-------------|---------|---|
| _links      | _links  |   |
| base_name   | string  | Base name of log file   |
| expiry_time | string  | Expiry time of the log file in date-time format. Value '9999-12-31T00:00:00Z' indicates infinite expiry time. |
| path        | string  | Absolute path of the log file in the volume   |
| size        | integer | Size of the log file in bytes   |

volume

| Name   | Type   | Description |
|--------|--------|-------------|
| _links | _links |             |

| Name | Type   | Description   |
|------|--------|---|
| name | string | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid | string | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"> <li>example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>Introduced in: 9.6</li> <li>x-nullable: true</li> </ul> |

#### snaplock\_log\_volume

| Name         | Type                   | Description                       |
|--------------|------------------------|-----------------------------------|
| _links       | <a href="#">_links</a> |                                   |
| max_log_size | integer                | Maximum size of log file in bytes |

| Name             | Type                   | Description   |
|------------------|------------------------|---|
| retention_period | string                 | Specifies the default log record retention period. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours, minutes and seconds. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. A duration in hours, minutes and seconds is represented by "PT<num>H", "PT<num>M", and "PT<num>S" respectively. The period string must contain only a single time element i.e. either years, months, days, hours, minutes or seconds. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the string "infinite".</num></num></num></num></num> |
| volume           | <a href="#">volume</a> |   |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

[snaplock\\_log](#)

| Name        | Type                                       | Description                              |
|-------------|--|--|
| _links      | <a href="#">_links</a>                     |  |
| log_archive | <a href="#">log_archive</a>                |  |
| log_files   | array[ <a href="#">snaplock_log_file</a> ] |  |
| log_volume  | <a href="#">snaplock_log_volume</a>        |  |
| svm         | <a href="#">svm</a>                        | SVM, applies only to SVM-scoped objects. |

#### job\_link

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| uuid   | string                 | The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation. |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                                     | Description                                 |
|-----------|--|---|
| arguments | array[ <a href="#">error_arguments</a> ] | Message arguments                           |
| code      | string                                   | Error code                                  |
| message   | string                                   | Error message                               |
| target    | string                                   | The target parameter that caused the error. |

## Disassociate SnapLock audit logs

`DELETE /storage/snaplock/audit-logs/{svm.uuid}`

**Introduced In:** 9.7

Disassociates a SnapLock volume as the audit log volume for an SVM. This API closes all the active log files in the log volume and marks the volume as disabled for SnapLock logging.

## Related ONTAP commands

- `snaplock log delete`

## Learn more

- [DOC /storage/snaplock/audit-logs](#)

## Parameters

| Name           | Type    | In    | Required | Description  |
|----------------|---------|-------|----------|--|
| svm.uuid       | string  | path  | True     | SVM UUID   |
| return_timeout | integer | query | False    | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"><li>• Default value: 1</li><li>• Max value: 120</li><li>• Min value: 0</li></ul> |

## Response

Status: 200, Ok

| Name | Type                     | Description |
|------|--------------------------|-------------|
| job  | <a href="#">job_link</a> |             |

## Example response

```
{  
  "job": {  
    "_links": {  
      "self": {  
        "href": "/api/resourcelink"  
      }  
    },  
    "uuid": "string"  
  }  
}
```

## Response

Status: 202, Accepted

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 14090346   | Internal Error. Wait a few minutes, then try the command again |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

job\_link

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| uuid   | string | The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation. |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Retrieve SnapLock audit logs

GET /storage/snaplock/audit-logs/{svm.uuid}

## Introduced In: 9.7

Retrieves SnapLock logs for the specified SVM.

### Related ONTAP commands

- `snaplock log show`

### Learn more

- [DOC /storage/snaplock/audit-logs](#)

### Parameters

| Name     | Type          | In    | Required | Description                   |
|----------|---------------|-------|----------|-------------------------------|
| svm.uuid | string        | path  | True     | SVM UUID                      |
| fields   | array[string] | query | False    | Specify the fields to return. |

### Response

```
Status: 200, Ok
```

| Name        | Type                     | Description                              |
|-------------|--------------------------|--|
| _links      | _links                   |  |
| log_archive | log_archive              |  |
| log_files   | array[snaplock_log_file] |  |
| log_volume  | snaplock_log_volume      |  |
| svm         | svm                      | SVM, applies only to SVM-scoped objects. |

## Example response

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "log_archive": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "base_name": "legal_hold"  
    },  
    "log_files": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "base_name": "legal_hold",  
        "expiry_time": "2058-06-04 15:00:00 -0400",  
        "path": "/snaplock_log/system_logs/20180822_005947_GMT-present",  
        "size": 20000  
    },  
    "log_volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "max_log_size": 20971520,  
        "retention_period": "P30M",  
        "volume": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "name": "volume1",  
            "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
        }  
    },  
    "svm": {
```

```

    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}

```

## Error

Status: Default, Error

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

log\_archive

| Name      | Type    | Description   |
|-----------|---------|---|
| _links    | _links  |   |
| archive   | boolean | Archive the specified SnapLock log file for the given base_name, and create a new log file. If base_name is not mentioned, archive all log files. |
| base_name | string  | Base name of log archive  |

snaplock\_log\_file

| Name        | Type    | Description   |
|-------------|---------|---|
| _links      | _links  |   |
| base_name   | string  | Base name of log file   |
| expiry_time | string  | Expiry time of the log file in date-time format. Value '9999-12-31T00:00:00Z' indicates infinite expiry time. |
| path        | string  | Absolute path of the log file in the volume   |
| size        | integer | Size of the log file in bytes   |

volume

| Name   | Type   | Description |
|--------|--------|-------------|
| _links | _links |             |

| Name | Type   | Description   |
|------|--------|---|
| name | string | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid | string | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"> <li>example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>Introduced in: 9.6</li> <li>x-nullable: true</li> </ul> |

### snaplock\_log\_volume

| Name         | Type                   | Description                       |
|--------------|------------------------|-----------------------------------|
| _links       | <a href="#">_links</a> |                                   |
| max_log_size | integer                | Maximum size of log file in bytes |

| Name             | Type                   | Description   |
|------------------|------------------------|---|
| retention_period | string                 | Specifies the default log record retention period. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours, minutes and seconds. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. A duration in hours, minutes and seconds is represented by "PT<num>H", "PT<num>M", and "PT<num>S" respectively. The period string must contain only a single time element i.e. either years, months, days, hours, minutes or seconds. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the string "infinite".</num></num></num></num></num> |
| volume           | <a href="#">volume</a> |   |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Update SnapLock audit logs

PATCH /storage/snaplock/audit-logs/{svm.uuid}

**Introduced In:** 9.7

Updates one of the following:

- the audit log volume,
- the attributes of the audit log volume present, or
- archive the current audit log files

### Related ONTAP commands

- snaplock log modify

### Learn more

- [DOC /storage/snaplock/audit-logs](#)

### Parameters

| Name     | Type   | In   | Required | Description |
|----------|--------|------|----------|-------------|
| svm.uuid | string | path | True     | SVM UUID    |

| Name           | Type    | In    | Required | Description  |
|----------------|---------|-------|----------|--|
| return_timeout | integer | query | False    | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul> |

## Request Body

| Name        | Type                                       | Description                              |
|-------------|--|--|
| _links      | <a href="#">_links</a>                     |  |
| log_archive | <a href="#">log_archive</a>                |  |
| log_files   | array[ <a href="#">snaplock_log_file</a> ] |  |
| log_volume  | <a href="#">snaplock_log_volume</a>        |  |
| svm         | <a href="#">svm</a>                        | SVM, applies only to SVM-scoped objects. |

## Example request

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "log_archive": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "base_name": "legal_hold"  
    },  
    "log_files": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "base_name": "legal_hold",  
        "expiry_time": "2058-06-04 15:00:00 -0400",  
        "path": "/snaplock_log/system_logs/20180822_005947_GMT-present",  
        "size": 20000  
    },  
    "log_volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "max_log_size": 20971520,  
        "retention_period": "P30M",  
        "volume": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "name": "volume1",  
            "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
        }  
    },  
    "svm": {
```

```
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
}
```

## Response

Status: 200, Ok

| Name | Type                     | Description |
|------|--------------------------|-------------|
| job  | <a href="#">job_link</a> |             |

## Example response

```
{
    "job": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "uuid": "string"
    }
}
```

## Response

Status: 202, Accepted

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 14090344   | If log_volume is specified, then log_archive must not be specified                     |
| 14090345   | If log_archive.base_name is specified, then log_archive.archive must also be specified |
| 14090346   | Internal Error. Wait a few minutes, then try the command again                         |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

log\_archive

| Name      | Type    | Description   |
|-----------|---------|---|
| _links    | _links  |   |
| archive   | boolean | Archive the specified SnapLock log file for the given base_name, and create a new log file. If base_name is not mentioned, archive all log files. |
| base_name | string  | Base name of log archive  |

snaplock\_log\_file

| Name        | Type    | Description   |
|-------------|---------|---|
| _links      | _links  |   |
| base_name   | string  | Base name of log file   |
| expiry_time | string  | Expiry time of the log file in date-time format. Value '9999-12-31T00:00:00Z' indicates infinite expiry time. |
| path        | string  | Absolute path of the log file in the volume   |
| size        | integer | Size of the log file in bytes   |

volume

| Name   | Type   | Description |
|--------|--------|-------------|
| _links | _links |             |

| Name | Type   | Description   |
|------|--------|---|
| name | string | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid | string | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"> <li>example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>Introduced in: 9.6</li> <li>x-nullable: true</li> </ul> |

### snaplock\_log\_volume

| Name         | Type                   | Description                       |
|--------------|------------------------|-----------------------------------|
| _links       | <a href="#">_links</a> |                                   |
| max_log_size | integer                | Maximum size of log file in bytes |

| Name             | Type                   | Description   |
|------------------|------------------------|---|
| retention_period | string                 | Specifies the default log record retention period. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours, minutes and seconds. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. A duration in hours, minutes and seconds is represented by "PT<num>H", "PT<num>M", and "PT<num>S" respectively. The period string must contain only a single time element i.e. either years, months, days, hours, minutes or seconds. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the string "infinite".</num></num></num></num></num> |
| volume           | <a href="#">volume</a> |   |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

[snaplock\\_log](#)

| Name        | Type                                       | Description                              |
|-------------|--|--|
| _links      | <a href="#">_links</a>                     |  |
| log_archive | <a href="#">log_archive</a>                |  |
| log_files   | array[ <a href="#">snaplock_log_file</a> ] |  |
| log_volume  | <a href="#">snaplock_log_volume</a>        |  |
| svm         | <a href="#">svm</a>                        | SVM, applies only to SVM-scoped objects. |

#### job\_link

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| uuid   | string                 | The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation. |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                                     | Description                                 |
|-----------|--|---|
| arguments | array[ <a href="#">error_arguments</a> ] | Message arguments                           |
| code      | string                                   | Error code                                  |
| message   | string                                   | Error message                               |
| target    | string                                   | The target parameter that caused the error. |

## Manage the SnapLock ComplianceClock

### Storage SnapLock compliance-clocks endpoint overview

This API manages the ComplianceClock of the system. ComplianceClock determines the expiry time of the

SnapLock objects in the system. The user can initialize the ComplianceClock. The ComplianceClock can be re-initialized if all nodes in the cluster are healthy, all volumes are in online state, no volumes are present in the volume recovery queue and there are no SnapLock volumes or volumes with "snapshot-locking-enabled" set to true or S3 buckets with object locking enabled.

## Retrieve the SnapLock ComplianceClock for nodes in a cluster

GET /storage/snaplock/compliance-clocks

**Introduced In:** 9.7

Retrieves the SnapLock ComplianceClock for all of the nodes in the cluster.

### Related ONTAP commands

- snaplock compliance-clock show

### Learn more

- [DOC /storage/snaplock/compliance-clocks](#)

### Parameters

| Name           | Type          | In    | Required | Description  |
|----------------|---------------|-------|----------|--|
| fields         | array[string] | query | False    | Specify the fields to return.  |
| max_records    | integer       | query | False    | Limit the number of records returned.  |
| return_timeout | integer       | query | False    | <p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"><li>• Default value: 1</li><li>• Max value: 120</li><li>• Min value: 0</li></ul> |

| Name           | Type          | In    | Required | Description   |
|----------------|---------------|-------|----------|---|
| return_records | boolean       | query | False    | <p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul> |
| order_by       | array[string] | query | False    | Order results by specified fields and optional [asc]  |

## Response

Status: 200, Ok

| Name        | Type   | Description       |
|-------------|--|-------------------|
| _links      | <a href="#">_links</a>                             |                   |
| num_records | integer  | Number of records |
| records     | array[ <a href="#">snaplock_compliance_clock</a> ] |                   |

## Example response

```
{  
  "_links": {  
    "next": {  
      "href": "/api/resourcelink"  
    },  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "num_records": 1,  
  "records": {  
    "_links": {  
      "self": {  
        "href": "/api/resourcelink"  
      }  
    },  
    "node": {  
      "_links": {  
        "self": {  
          "href": "/api/resourcelink"  
        }  
      },  
      "name": "node1",  
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"  
    },  
    "time": "2018-06-04 15:00:00 -0400"  
  }  
}
```

## Error

Status: Default, Error

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| next | href |             |
| self | href |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

node

| Name   | Type   | Description |
|--------|--------|-------------|
| _links | _links |             |
| name   | string |             |
| uuid   | string |             |

snaplock\_compliance\_clock

| Name   | Type   | Description           |
|--------|--------|-----------------------|
| _links | _links |                       |
| node   | node   |                       |
| time   | string | Compliance clock time |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Initialize a SnapLock ComplianceClock

POST /storage/snaplock/compliance-clocks

**Introduced In:** 9.10

Initializes the SnapLock ComplianceClock.

### Required properties

- node.name or node.uuid - Name or UUID of the node.

### Related ONTAP commands

- snaplock compliance-clock initialize

### Learn more

- [DOC /storage/snaplock/compliance-clocks](#)

### Parameters

| Name           | Type    | In    | Required | Description   |
|----------------|---------|-------|----------|---|
| return_records | boolean | query | False    | <p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> <li>Default value:</li> </ul> |

### Request Body

| Name   | Type   | Description |
|--------|--------|-------------|
| _links | _links |             |
| node   | node   |             |

| Name | Type   | Description           |
|------|--------|-----------------------|
| time | string | Compliance clock time |

### Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "node": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "node1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "time": "2018-06-04 15:00:00 -0400"
}
```

### Response

Status: 201, Created

### Headers

| Name     | Description                               | Type   |
|----------|---|--------|
| Location | Useful for tracking the resource location | string |

### Error

Status: Default

### ONTAP Error Response codes

| Error code | Description                          |
|------------|--------------------------------------|
| 13763062   | Compliance Clock already initialized |

| Error code | Description   |
|------------|---|
| 13763084   | ComplianceClock re-initialization failed as it requires that all nodes in the cluster are healthy, all volumes are in online state, no volumes are present in the volume recovery queue and there are no SnapLock volumes or volumes with "snapshot-locking-enabled" set to true or S3 buckets with object locking enabled. |
| 13763085   | ComplianceClock re-initialization supported on effective cluster version of ONTAP 9.14.1 or later.  |
| 14090240   | Node with the specified UUID does not exist   |
| 14090241   | The specified node name and node UUID refer to different nodes  |
| 14090343   | Invalid field   |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

node

| Name   | Type   | Description |
|--------|--------|-------------|
| _links | _links |             |
| name   | string |             |
| uuid   | string |             |

snaplock\_compliance\_clock

| Name   | Type   | Description           |
|--------|--------|-----------------------|
| _links | _links |                       |
| node   | node   |                       |
| time   | string | Compliance clock time |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description       |
|-----------|------------------------|-------------------|
| arguments | array[error_arguments] | Message arguments |
| code      | string                 | Error code        |
| message   | string                 | Error message     |

| Name   | Type   | Description                                 |
|--------|--------|---|
| target | string | The target parameter that caused the error. |

## Retrieve a SnapLock ComplianceClock for a node

GET /storage/snaplock/compliance-clocks/{node.uuid}

**Introduced In:** 9.7

Retrieves the SnapLock ComplianceClock for a specific node.

### Related ONTAP commands

- snaplock compliance-clock show

### Learn more

- [DOC /storage/snaplock/compliance-clocks](#)

### Parameters

| Name      | Type          | In    | Required | Description                   |
|-----------|---------------|-------|----------|-------------------------------|
| node.uuid | string        | path  | True     | Node UUID                     |
| fields    | array[string] | query | False    | Specify the fields to return. |

### Response

Status: 200, Ok

| Name   | Type                   | Description           |
|--------|------------------------|-----------------------|
| _links | <a href="#">_links</a> |                       |
| node   | <a href="#">node</a>   |                       |
| time   | string                 | Compliance clock time |

## Example response

```
{  
  "_links": {  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "node": {  
    "_links": {  
      "self": {  
        "href": "/api/resourcelink"  
      }  
    },  
    "name": "node1",  
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"  
  },  
  "time": "2018-06-04 15:00:00 -0400"  
}
```

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description                                   |
|------------|---|
| 14090240   | A node with the specified UUID does not exist |
| 14090446   | Invalid session ID                            |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

node

| Name   | Type   | Description |
|--------|--------|-------------|
| _links | _links |             |
| name   | string |             |
| uuid   | string |             |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Manage event based retention operations

## Storage SnapLock event-retention operations endpoint overview

Use this API to display all Event Based Retention (EBR) operations and to apply an EBR policy on a specified volume or path within the volume. Only a user with security login role vsadmin-snaplock can perform the operation.

### Examples

1. Displays all of the EBR operations:

```
GET "/api/storage/snaplock/event-retention/operations"
```

1. Displays all completed EBR operations:

```
GET "/api/storage/snaplock/event-retention/operations?state=completed"
```

1. Displays all completed EBR operations with filter set as volume.uuid:

```
GET "/api/storage/snaplock/event-retention/operations?volume.uuid=b96f976e-404b-11e9-bff2-0050568e4dbe"
```

1. Displays all of the EBR operations with filter set as volume.name:

```
GET "/api/storage/snaplock/event-retention/operations?volume.name=SLCVOL"
```

### Examples

1. Applies an EBR policy on a specific path:

```
POST "/api/storage/snaplock/event-retention/operations"  
'{"volume.name":"SLCVOL", "policy.name":"p1day", "path":"/dir1/file.txt"}'
```

1. Applies an EBR policy on the complete volume:

```
POST "/api/storage/snaplock/event-retention/operations"  
'{"volume.name":"SLCVOL", "policy.name":"p1day", "path":"/"}'
```

### Example

```
DELETE "/api/storage/snaplock/event-retention/operations/16842999"
```

## Retrieve EBR operations

GET /storage/snaplock/event-retention/operations

**Introduced In:** 9.7

Retrieves a list of all EBR operations.

### Related ONTAP commands

- snaplock event-retention show

### Learn more

- [DOC /storage/snaplock/event-retention/operations](#)

### Parameters

| Name           | Type          | In    | Required | Description  |
|----------------|---------------|-------|----------|--|
| volume.uuid    | string        | query | False    | Volume UUID  |
| fields         | array[string] | query | False    | Specify the fields to return.  |
| max_records    | integer       | query | False    | Limit the number of records returned.  |
| return_timeout | integer       | query | False    | <p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"><li>• Default value: 1</li><li>• Max value: 120</li><li>• Min value: 0</li></ul> |

| Name           | Type          | In    | Required | Description   |
|----------------|---------------|-------|----------|---|
| return_records | boolean       | query | False    | <p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul> |
| order_by       | array[string] | query | False    | Order results by specified fields and optional [asc]  |

## Response

```
Status: 200, Ok
```

| Name        | Type                   | Description       |
|-------------|------------------------|-------------------|
| _links      | <a href="#">_links</a> |                   |
| num_records | integer                | Number of records |
| records     | array[ebr_operation]   |                   |

## Example response

```
{  
    "_links": {  
        "next": {  
            "href": "/api/resourcelink"  
        },  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "num_records": 1,  
    "records": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "id": 16842759,  
        "num_files_failed": 0,  
        "num_files_processed": 50,  
        "num_files_skipped": 2,  
        "num_inodes_ignored": 2,  
        "path": "/dir1/file",  
        "policy": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "retention_period": "P30M"  
        },  
        "state": "completed",  
        "svm": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "name": "svm1",  
            "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
        },  
        "volume": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            }  
        }  
    }  
}
```

```

        }
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
}
}
```

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 14090242   | Only a user with the security login role "vsadmin-snaplock" is allowed to perform this operation. |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| next | <a href="#">href</a> |             |
| self | <a href="#">href</a> |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| self | <a href="#">href</a> |             |

policy

| Name   | Type                   | Description                   |
|--------|------------------------|-------------------------------|
| _links | <a href="#">_links</a> |                               |
| name   | string                 | Specifies the EBR policy name |

| Name             | Type   | Description  |
|------------------|--------|--|
| retention_period | string | Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT<num>H", "PT<num>M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".</num></num></num></num> |

## svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

## volume

| Name   | Type                   | Description  |
|--------|------------------------|--|
| _links | <a href="#">_links</a> |  |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.  |
| uuid   | string                 | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"> <li>example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>Introduced in: 9.6</li> <li>x-nullability: true</li> </ul> |

## ebr\_operation

| Name                | Type                   | Description  |
|---------------------|------------------------|--|
| _links              | <a href="#">_links</a> |  |
| id                  | integer                | Operation ID   |
| num_files_failed    | integer                | Specifies the number of files on which the application of EBR policy failed.   |
| num_files_processed | integer                | Specifies the number of files on which EBR policy was applied successfully.  |
| num_files_skipped   | integer                | Specifies the number of files on which the application of EBR policy was skipped.  |
| num_inodes_ignored  | integer                | Specifies the number of inodes on which the application of EBR policy was not attempted because they were not regular files.                               |
| path                | string                 | The path for the EBR operation. Specifies the path relative to the output volume root, of the form "/path". The path can be path to a file or a directory. |

| Name   | Type   | Description   |
|--------|--------|---|
| policy | policy |   |
| state  | string | Specifies the operation status of an EBR operation. |
| svm    | svm    | SVM, applies only to SVM-scoped objects.            |
| volume | volume |   |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Create an EBR policy

POST /storage/snaplock/event-retention/operations

**Introduced In:** 9.7

Start an EBR operation. This operation applies an EBR policy to a specific volume or to a path within the volume.

### Required properties

- path - Path of the file.
- policy.name - Name of the EBR policy. Either volume.name or volume.uuid must be specified when applying EBR policy to the volume or a path within the volume.
- volume.name - Volume name.

- volume.uuid - Volume uuid.

## Related ONTAP commands

- snaplock event-retention apply

## Learn more

- [DOC /storage/snaplock/event-retention/operations](#)

## Parameters

| Name           | Type    | In    | Required | Description   |
|----------------|---------|-------|----------|---|
| return_records | boolean | query | False    | <p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> <li>• Default value:</li> </ul> |

## Request Body

| Name                | Type                   | Description  |
|---------------------|------------------------|--|
| _links              | <a href="#">_links</a> |  |
| id                  | integer                | Operation ID   |
| num_files_failed    | integer                | Specifies the number of files on which the application of EBR policy failed.   |
| num_files_processed | integer                | Specifies the number of files on which EBR policy was applied successfully.  |
| num_files_skipped   | integer                | Specifies the number of files on which the application of EBR policy was skipped.  |
| num_inodes_ignored  | integer                | Specifies the number of inodes on which the application of EBR policy was not attempted because they were not regular files. |

| Name   | Type                   | Description  |
|--------|------------------------|--|
| path   | string                 | The path for the EBR operation. Specifies the path relative to the output volume root, of the form "/path". The path can be path to a file or a directory. |
| policy | <a href="#">policy</a> |  |
| state  | string                 | Specifies the operation status of an EBR operation.  |
| svm    | <a href="#">svm</a>    | SVM, applies only to SVM-scoped objects.   |
| volume | <a href="#">volume</a> |  |

## Example request

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "id": 16842759,  
    "num_files_failed": 0,  
    "num_files_processed": 50,  
    "num_files_skipped": 2,  
    "num_inodes_ignored": 2,  
    "path": "/dir1/file",  
    "policy": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "retention_period": "P30M"  
    },  
    "state": "completed",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svm1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "volume1",  
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
    }  
}
```

## Response

Status: 201, Created

| Name                | Type                   | Description  |
|---------------------|------------------------|--|
| _links              | <a href="#">_links</a> |  |
| id                  | integer                | Operation ID   |
| num_files_failed    | integer                | Specifies the number of files on which the application of EBR policy failed.   |
| num_files_processed | integer                | Specifies the number of files on which EBR policy was applied successfully.  |
| num_files_skipped   | integer                | Specifies the number of files on which the application of EBR policy was skipped.  |
| num_inodes_ignored  | integer                | Specifies the number of inodes on which the application of EBR policy was not attempted because they were not regular files.                               |
| path                | string                 | The path for the EBR operation. Specifies the path relative to the output volume root, of the form "/path". The path can be path to a file or a directory. |
| policy              | <a href="#">policy</a> |  |
| state               | string                 | Specifies the operation status of an EBR operation.  |
| svm                 | <a href="#">svm</a>    | SVM, applies only to SVM-scoped objects.   |
| volume              | <a href="#">volume</a> |  |

## Example response

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "id": 16842759,  
    "num_files_failed": 0,  
    "num_files_processed": 50,  
    "num_files_skipped": 2,  
    "num_inodes_ignored": 2,  
    "path": "/dir1/file",  
    "policy": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "retention_period": "P30M"  
    },  
    "state": "completed",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svm1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "volume1",  
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
    }  
}
```

## Headers

| Name     | Description                               | Type   |
|----------|---|--------|
| Location | Useful for tracking the resource location | string |

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 918236     | The specified volume uuid and volume name refer to different volumes.                             |
| 13763372   | Path should be given in the format "\<dir path>".   |
| 14090242   | Only a user with the security login role "vsadmin-snaplock" is allowed to perform this operation. |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

policy

| Name             | Type   | Description   |
|------------------|--------|---|
| _links           | _links |   |
| name             | string | Specifies the EBR policy name   |
| retention_period | string | Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT<num>H", "PT<num>M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".</num></num></nu m></num></num> |

## svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

## volume

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string                 | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"><li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li><li>• Introduced in: 9.6</li><li>• x-nullable: true</li></ul> |

## ebr\_operation

| Name             | Type                   | Description  |
|------------------|------------------------|--|
| _links           | <a href="#">_links</a> |  |
| id               | integer                | Operation ID   |
| num_files_failed | integer                | Specifies the number of files on which the application of EBR policy failed. |

| Name                | Type                   | Description  |
|---------------------|------------------------|--|
| num_files_processed | integer                | Specifies the number of files on which EBR policy was applied successfully.  |
| num_files_skipped   | integer                | Specifies the number of files on which the application of EBR policy was skipped.  |
| num_inodes_ignored  | integer                | Specifies the number of inodes on which the application of EBR policy was not attempted because they were not regular files.                               |
| path                | string                 | The path for the EBR operation. Specifies the path relative to the output volume root, of the form "/path". The path can be path to a file or a directory. |
| policy              | <a href="#">policy</a> |  |
| state               | string                 | Specifies the operation status of an EBR operation.  |
| svm                 | <a href="#">svm</a>    | SVM, applies only to SVM-scoped objects.   |
| volume              | <a href="#">volume</a> |  |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                   | Description       |
|-----------|------------------------|-------------------|
| arguments | array[error_arguments] | Message arguments |
| code      | string                 | Error code        |
| message   | string                 | Error message     |

| Name   | Type   | Description                                 |
|--------|--------|---|
| target | string | The target parameter that caused the error. |

## Cancel an ongoing EBR operation

DELETE /storage/snaplock/event-retention/operations/{id}

**Introduced In:** 9.7

Aborts an ongoing EBR operation.

### Related ONTAP commands

- snaplock event-retention abort

### Learn more

- [DOC /storage/snaplock/event-retention/operations](#)

### Parameters

| Name | Type   | In   | Required | Description                           |
|------|--------|------|----------|---------------------------------------|
| id   | string | path | True     | Unique identifier of an EBR operation |

### Response

Status: 200, Ok

### Error

Status: Default

### ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 14090541   | A completed or failed operation cannot be aborted   |
| 14090242   | Only a user with the security login role "vsadmin-snaplock" is allowed to perform this operation. |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

### See Definitions

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Retrieve attributes for an EBR operation

GET /storage/snaplock/event-retention/operations/{id}

**Introduced In:** 9.7

Retrieves a list of attributes for an EBR operation.

### Related ONTAP commands

- snaplock event-retention show

### Learn more

- [DOC /storage/snaplock/event-retention/operations](#)

### Parameters

| Name   | Type          | In    | Required | Description                           |
|--------|---------------|-------|----------|---------------------------------------|
| id     | string        | path  | True     | Unique identifier of an EBR operation |
| fields | array[string] | query | False    | Specify the fields to return.         |

### Response

Status: 200, Ok

| Name                | Type                   | Description   |
|---------------------|------------------------|---|
| _links              | <a href="#">_links</a> |   |
| id                  | integer                | Operation ID  |
| num_files_failed    | integer                | Specifies the number of files on which the application of EBR policy failed.      |
| num_files_processed | integer                | Specifies the number of files on which EBR policy was applied successfully.       |
| num_files_skipped   | integer                | Specifies the number of files on which the application of EBR policy was skipped. |

| Name               | Type                   | Description  |
|--------------------|------------------------|--|
| num_inodes_ignored | integer                | Specifies the number of inodes on which the application of EBR policy was not attempted because they were not regular files.                               |
| path               | string                 | The path for the EBR operation. Specifies the path relative to the output volume root, of the form "/path". The path can be path to a file or a directory. |
| policy             | <a href="#">policy</a> |  |
| state              | string                 | Specifies the operation status of an EBR operation.  |
| svm                | <a href="#">svm</a>    | SVM, applies only to SVM-scoped objects.   |
| volume             | <a href="#">volume</a> |  |

## Example response

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "id": 16842759,  
    "num_files_failed": 0,  
    "num_files_processed": 50,  
    "num_files_skipped": 2,  
    "num_inodes_ignored": 2,  
    "path": "/dir1/file",  
    "policy": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "retention_period": "P30M"  
    },  
    "state": "completed",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svm1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "volume1",  
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
    }  
}
```

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 14090242   | Only a user with the security login role "vsadmin-snaplock" is allowed to perform this operation. |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

### Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

policy

| Name             | Type   | Description  |
|------------------|--------|--|
| _links           | _links |  |
| name             | string | Specifies the EBR policy name  |
| retention_period | string | Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT<num>H", "PT<num>M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".</num></num></num></num> |

## svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

## volume

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string                 | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"><li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li><li>• Introduced in: 9.6</li><li>• x-nullable: true</li></ul> |

## error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

## returned\_error

| Name      | Type                   | Description       |
|-----------|------------------------|-------------------|
| arguments | array[error_arguments] | Message arguments |

| Name    | Type   | Description                                 |
|---------|--------|---|
| code    | string | Error code                                  |
| message | string | Error message                               |
| target  | string | The target parameter that caused the error. |

## Manage event based retention policies

### Storage SnapLock event-retention policies endpoint overview

An event retention policy consists of a policy-name and a retention-period. The policy can be applied to a single file or files in a directory. Only a user with the security login role vsadmin-snaplock can perform the operation. EBR policies cannot be applied to files under a Legal-Hold.

#### Examples

- Creates an EBR policy policy\_name with a retention period of "10 years":

```
POST "/api/storage/snaplock/event-retention/policies/" '{"name": "policy_name", "retention_period": "P10Y"}'
```

- Creates an EBR policy policy\_name1 with a retention period of "infinite":

```
POST "/api/storage/snaplock/event-retention/policies/" {"name": "policy_name1", "retention_period": "infinite"}
```

## Retrieve event retention policies for an SVM

GET /storage/snaplock/event-retention/policies

**Introduced In:** 9.7

Retrieves all event retention policies for an SVM.

### Related ONTAP commands

- snaplock event-retention policy show

### Learn more

- [DOC /storage/snaplock/event-retention/policies](#)

## Parameters

| Name           | Type          | In    | Required | Description  |
|----------------|---------------|-------|----------|--|
| fields         | array[string] | query | False    | Specify the fields to return.  |
| max_records    | integer       | query | False    | Limit the number of records returned.  |
| return_timeout | integer       | query | False    | <p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul> |
| return_records | boolean       | query | False    | <p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>  |
| order_by       | array[string] | query | False    | Order results by specified fields and optional [asc  |

## Response

```
Status: 200, Ok
```

| Name        | Type                   | Description       |
|-------------|------------------------|-------------------|
| _links      | <a href="#">_links</a> |                   |
| num_records | integer                | Number of records |

| Name    | Type                             | Description |
|---------|----------------------------------|-------------|
| records | array[snaplock_retention_policy] |             |

### Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "num_records": 1,
  "records": [
    {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "retention_period": "P30M",
      "svm": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      }
    }
  }
}
```

### Error

Status: Default

### ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 918253     | Incorrect format for the retention period, duration must be in the ISO-8601 format or infinite or unspecified. |
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation.                  |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| next | href |             |
| self | href |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| name   | string | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

snaplock\_retention\_policy

| Name   | Type   | Description                   |
|--------|--------|-------------------------------|
| _links | _links |                               |
| name   | string | Specifies the EBR policy name |

| Name             | Type   | Description   |
|------------------|--------|---|
| retention_period | string | Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT<num>H", "PT<num>M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".</num></num></nu m></num></num> |
| svm              | svm    | SVM, applies only to SVM-scoped objects.  |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                   | Description       |
|-----------|------------------------|-------------------|
| arguments | array[error_arguments] | Message arguments |

| Name    | Type   | Description                                 |
|---------|--------|---|
| code    | string | Error code                                  |
| message | string | Error message                               |
| target  | string | The target parameter that caused the error. |

## Create an EBR policy for an SVM

POST /storage/snaplock/event-retention/policies

**Introduced In:** 9.7

Creates an Event Based Retention (EBR) policy for an SVM. The input parameter retention\_period expects the duration in ISO 8601 format or infinite.

### Required properties

- name - Event retention policy name.
- retention\_period - Retention period of the EBR policy.

### Related ONTAP commands

- snaplock event-retention policy create

### Learn more

- [DOC /storage/snaplock/event-retention/policies](#)

### Parameters

| Name           | Type    | In    | Required | Description   |
|----------------|---------|-------|----------|---|
| return_records | boolean | query | False    | <p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> <li>Default value:</li> </ul> |

### Request Body

| Name   | Type                   | Description                   |
|--------|------------------------|-------------------------------|
| _links | <a href="#">_links</a> |                               |
| name   | string                 | Specifies the EBR policy name |

| Name             | Type   | Description   |
|------------------|--------|---|
| retention_period | string | <p>Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P&lt;num&gt;Y", "P&lt;num&gt;M", "P&lt;num&gt;D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT&lt;num&gt;H", "PT&lt;num&gt;M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".&lt;/num&gt;&lt;/num&gt;&lt;/num&gt;&gt;&lt;/num&gt;&lt;/num&gt;</p> |
| svm              | svm    | SVM, applies only to SVM-scoped objects.  |

## Example request

```
{  
  "_links": {  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "retention_period": "P30M",  
  "svm": {  
    "_links": {  
      "self": {  
        "href": "/api/resourcelink"  
      }  
    },  
    "name": "svm1",  
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
  }  
}
```

## Response

Status: 201, Created

| Name   | Type   | Description                   |
|--------|--------|-------------------------------|
| _links | _links |                               |
| name   | string | Specifies the EBR policy name |

| Name             | Type   | Description   |
|------------------|--------|---|
| retention_period | string | <p>Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P&lt;num&gt;Y", "P&lt;num&gt;M", "P&lt;num&gt;D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT&lt;num&gt;H", "PT&lt;num&gt;M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".&lt;/num&gt;&lt;/num&gt;&lt;/num&gt;&gt;&lt;/num&gt;&lt;/num&gt;</p> |
| svm              | svm    | SVM, applies only to SVM-scoped objects.  |

## Example response

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "retention_period": "P30M",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svm1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    }  
}
```

## Headers

| Name     | Description                               | Type   |
|----------|---|--------|
| Location | Useful for tracking the resource location | string |

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 918253     | Incorrect format for the retention period, duration must be in the ISO-8601 format or infinite or unspecified. |
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation.                  |
| 13763402   | Policy name already exists.  |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| name   | string | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

snaplock\_retention\_policy

| Name   | Type   | Description                   |
|--------|--------|-------------------------------|
| _links | _links |                               |
| name   | string | Specifies the EBR policy name |

| Name             | Type   | Description   |
|------------------|--------|---|
| retention_period | string | Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT<num>H", "PT<num>M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".</num></num></nu m></num></num> |
| svm              | svm    | SVM, applies only to SVM-scoped objects.  |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                   | Description       |
|-----------|------------------------|-------------------|
| arguments | array[error_arguments] | Message arguments |

| Name    | Type   | Description                                 |
|---------|--------|---|
| code    | string | Error code                                  |
| message | string | Error message                               |
| target  | string | The target parameter that caused the error. |

## Delete an EBR policy

DELETE /storage/snaplock/event-retention/policies/{policy.name}

**Introduced In:** 9.7

Deletes the specified Event Based Retention (EBR) policy.

### Related ONTAP commands

- snaplock event-retention policy delete

### Example

Delete the specified Event Based Retention policy "policy\_name":

```
DELETE "/api/storage/snaplock/event-retention/policies/{policy.name}"
```

### Learn more

- [DOC /storage/snaplock/event-retention/policies](#)

### Parameters

| Name        | Type   | In   | Required | Description                  |
|-------------|--------|------|----------|------------------------------|
| policy.name | string | path | True     | Name of the retention policy |

### Response

```
Status: 200, Ok
```

### Error

```
Status: Default
```

## ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation. |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

### Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

### Definitions

## See Definitions

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Retrieve attributes of an EBR policy

GET /storage/snaplock/event-retention/policies/{policy.name}

**Introduced In:** 9.7

Retrieves a list of attributes of the specified Event Based Retention (EBR) policy.

### Related ONTAP commands

- snaplock event-retention policy show

### Learn more

- [DOC /storage/snaplock/event-retention/policies](#)

### Parameters

| Name        | Type          | In    | Required | Description                   |
|-------------|---------------|-------|----------|-------------------------------|
| policy.name | string        | path  | True     | Name of the retention policy  |
| fields      | array[string] | query | False    | Specify the fields to return. |

## Response

Status: 200, Ok

| Name             | Type                   | Description   |
|------------------|------------------------|---|
| _links           | <a href="#">_links</a> |   |
| name             | string                 | Specifies the EBR policy name   |
| retention_period | string                 | Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT<num>H", "PT<num>M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".</num></num></num>></num></num> |
| svm              | <a href="#">svm</a>    | SVM, applies only to SVM-scoped objects.  |

## Example response

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "retention_period": "P30M",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svm1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    }  
}
```

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation. |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| name   | string | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Update the retention period of an EBR policy

PATCH /storage/snaplock/event-retention/policies/{policy.name}

**Introduced In:** 9.7

Updates the retention period of an Event Based Retention (EBR) policy.

### Related ONTAP commands

- snaplock event-retention policy modify

### Example

Updates the retention period of an EBR policy "policy\_name":

```
PATCH "/api/storage/snaplock/event-retention/policies/{policy.name}"
'{"retention_period": "P20Y"}'
```

### Learn more

- [DOC /storage/snaplock/event-retention/policies](#)

### Parameters

| Name        | Type   | In   | Required | Description                  |
|-------------|--------|------|----------|------------------------------|
| policy.name | string | path | True     | Name of the retention policy |

### Request Body

| Name   | Type                   | Description                   |
|--------|------------------------|-------------------------------|
| _links | <a href="#">_links</a> |                               |
| name   | string                 | Specifies the EBR policy name |

| Name             | Type   | Description   |
|------------------|--------|---|
| retention_period | string | <p>Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P&lt;num&gt;Y", "P&lt;num&gt;M", "P&lt;num&gt;D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT&lt;num&gt;H", "PT&lt;num&gt;M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".&lt;/num&gt;&lt;/num&gt;&lt;/num&gt;&gt;&lt;/num&gt;&lt;/num&gt;</p> |
| svm              | svm    | SVM, applies only to SVM-scoped objects.  |

## Example request

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "retention_period": "P30M",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svm1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    }  
}
```

## Response

Status: 200, Ok

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 918253     | Incorrect format for the retention period, duration must be in the ISO-8601 format or infinite or unspecified. |
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation.                  |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| name   | string | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

snaplock\_retention\_policy

| Name   | Type   | Description                   |
|--------|--------|-------------------------------|
| _links | _links |                               |
| name   | string | Specifies the EBR policy name |

| Name             | Type   | Description  |
|------------------|--------|--|
| retention_period | string | Specifies the retention period of an event based retention policy. The retention period value represents a duration and must be specified in the ISO-8601 duration format. The retention period can be in years, months, days, hours or minutes. A period specified for years, months and days is represented in the ISO-8601 format as "P<num>Y", "P<num>M", "P<num>D" respectively. For example "P10Y" represents a duration of 10 years. Similarly, a duration in hours, minutes is represented by "PT<num>H", "PT<num>M" respectively. The period string must contain only a single time element i.e. either years, months, days, hours or minutes. A duration which combines different periods is not supported, example "P1Y10M" is not supported. Apart from the duration specified in the ISO-8601 format, the retention period field also accepts the strings "infinite" and "unspecified".</num></num></num></num> |
| svm              | svm    | SVM, applies only to SVM-scoped objects.   |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                   | Description       |
|-----------|------------------------|-------------------|
| arguments | array[error_arguments] | Message arguments |

| Name    | Type   | Description                                 |
|---------|--------|---|
| code    | string | Error code                                  |
| message | string | Error message                               |
| target  | string | The target parameter that caused the error. |

## View key information about files and volumes

### Storage SnapLock file-fingerprints endpoint overview

Use this API to view key information about files and volumes, including the file type (regular, WORM, or WORM appendable), the volume expiration date, and so on.

### Retrieve fingerprint operations of an SVM and volume

GET /storage/snaplock/file-fingerprints

**Introduced In:** 9.7

Retrieves a list of all the fingerprint operations of the specified SVM and volume.

#### Related ONTAP commands

- volume file fingerprint show

#### Example

```
GET "/api/storage/snaplock/file-fingerprints/?svm.uuid=23940494-3f3a-11e9-8675-0050568e8f89&volume.uuid=36cdb58c-3f3a-11e9-8675-0050568e8f89"
```

#### Learn more

- [DOC /storage/snaplock/file-fingerprints](#)

#### Parameters

| Name        | Type   | In    | Required | Description |
|-------------|--------|-------|----------|-------------|
| svm.uuid    | string | query | True     | SVM UUID    |
| volume.uuid | string | query | True     | Volume UUID |

| Name           | Type          | In    | Required | Description  |
|----------------|---------------|-------|----------|--|
| fields         | array[string] | query | False    | Specify the fields to return.  |
| max_records    | integer       | query | False    | Limit the number of records returned.  |
| return_timeout | integer       | query | False    | <p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul> |
| return_records | boolean       | query | False    | <p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>  |
| order_by       | array[string] | query | False    | Order results by specified fields and optional [asc]   |

## Response

Status: 200, Ok

| Name        | Type   | Description        |
|-------------|--|--------------------|
| _links      | <a href="#">_links</a>                             |                    |
| num_records | integer  | Number of Records. |
| records     | array[ <a href="#">snaplock_file_fingerprint</a> ] |                    |

## Example response

```
{  
    "_links": {  
        "next": {  
            "href": "/api/resourcelink"  
        },  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "num_records": 1,  
    "records": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "algorithm": "sha256",  
        "data_fingerprint": "MOFJVevxNSJm3C/4Bn5oEEYH51CrudOzZYK4r5Cfy1g=",  
        "file_size": 1048576,  
        "file_type": "worm",  
        "id": 17039367,  
        "metadata_fingerprint":  
            "8iMjqJXiNcqgXT5XuRhLiEwIrJEihDmwS0hrexnjgmc=",  
        "path": "/homedir/dirl",  
        "scope": "data_only",  
        "state": "completed",  
        "svm": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "name": "svml",  
            "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
        },  
        "volume": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "name": "volume1",  
            "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
        }  
    }  
}
```

```
    }
}
```

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 14090442   | Invalid Vserver UUID                                     |
| 14090445   | Invalid key values. Provide Vserver UUID and Volume UUID |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| next | href |             |
| self | href |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| name   | string | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| name   | string | The name of the volume. This field cannot be specified in a POST or PATCH method. |

| Name | Type   | Description  |
|------|--------|--|
| uuid | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> <li>example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>Introduced in: 9.6</li> <li>x-nullable: true</li> </ul> |

### snaplock\_file\_fingerprint

| Name                 | Type                   | Description  |
|----------------------|------------------------|--|
| _links               | <a href="#">_links</a> |  |
| algorithm            | string                 | The digest algorithm which is used for the fingerprint computation   |
| data_fingerprint     | string                 | The digest value of data of the file. The fingerprint is base64 encoded. This field is not included if the scope is metadata-only.   |
| file_size            | integer                | The size of the file in bytes.   |
| file_type            | string                 | The type of the file.  |
| id                   | integer                | A unique identifier for the fingerprint operation  |
| metadata_fingerprint | string                 | The digest value of metadata of the file. The metadata fingerprint is calculated for file size, file ctime, file mtime, file crttime, file retention time, file uid, file gid, and file type. The fingerprint is base64 encoded. This field is not included if the scope is data-only. |

| Name   | Type   | Description  |
|--------|--------|--|
| path   | string | Specifies the path on which file fingerprint operation is running or has completed. Specifies the path relative to the output volume root, of the form "/path". The path can be path to a file or a directory. |
| scope  | string | The scope of the file which is used for the fingerprint computation  |
| state  | string | Specifies the status of fingerprint operation.   |
| svm    | svm    | SVM, applies only to SVM-scoped objects.   |
| volume | volume |  |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Create a fingerprint computation session

POST /storage/snaplock/file-fingerprints

Introduced In: 9.7

Creates a fingerprint computation session on the file and returns a session-id. This session-id is a unique identifier that you can use to retrieve the progress of an ongoing fingerprint operation. When the operation is complete, you can use the session-id to retrieve the complete fingerprint output for the file .

## Required properties

- `svm.uuid` or `svm.name` - Name or UUID of the SVM.
- `volume.name` or `volume.uuid` - Name or UUID of the volume.
- `path` - Path of the file.

## Default property values

If not specified in POST, the follow default property values are assigned:

- `algorithm` - `sha256`

## Related ONTAP commands

- `volume file fingerprint start`

## Example

```
POST "/api/storage/snaplock/file-fingerprints" '{"svm": {"uuid": "23940494-3f3a-11e9-8675-0050568e8f89"}, "volume": {"uuid": "26cdb58c-3f3a-11e9-8675-0050568e8f89"}, "path": "/vol/a1.txt", "algorithm": "md5"}'
```

## Learn more

- [DOC /storage/snaplock/file-fingerprints](#)

## Parameters

| Name           | Type    | In    | Required | Description   |
|----------------|---------|-------|----------|---|
| return_records | boolean | query | False    | <p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"><li>• Default value:</li></ul> |

## Request Body

| Name      | Type   | Description  |
|-----------|--------|--|
| _links    | _links |  |
| algorithm | string | The digest algorithm which is used for the fingerprint computation |

| Name                 | Type    | Description   |
|----------------------|---------|---|
| data_fingerprint     | string  | The digest value of data of the file. The fingerprint is base64 encoded. This field is not included if the scope is metadata-only.  |
| file_size            | integer | The size of the file in bytes.  |
| file_type            | string  | The type of the file.   |
| id                   | integer | A unique identifier for the fingerprint operation   |
| metadata_fingerprint | string  | The digest value of metadata of the file. The metadata fingerprint is calculated for file size, file ctime, file mtime, file crtime, file retention time, file uid, file gid, and file type. The fingerprint is base64 encoded. This field is not included if the scope is data-only. |
| path                 | string  | Specifies the path on which file fingerprint operation is running or has completed. Specifies the path relative to the output volume root, of the form "/path". The path can be path to a file or a directory.  |
| scope                | string  | The scope of the file which is used for the fingerprint computation   |
| state                | string  | Specifies the status of fingerprint operation.  |
| svm                  | svm     | SVM, applies only to SVM-scoped objects.  |
| volume               | volume  |   |

## Example request

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "algorithm": "sha256",  
    "data_fingerprint": "MOFJVevxNSJm3C/4Bn5oEEYH51CrudOzZYK4r5Cfy1g=",  
    "file_size": 1048576,  
    "file_type": "worm",  
    "id": 17039367,  
    "metadata_fingerprint":  
        "8iMjqJXiNcqgXT5XuRhLiEwIrJEihDmwS0hrexnjgmc=",  
    "path": "/omedir/dir1",  
    "scope": "data_only",  
    "state": "completed",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svml",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "volumel",  
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
    }  
}
```

## Response

Status: 201, Created

## Headers

| Name     | Description                               | Type   |
|----------|---|--------|
| Location | Useful for tracking the resource location | string |

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 2          | An invalid value was entered for one of the fields   |
| 2621519    | Invalid SVM name format  |
| 14090347   | Invalid path format  |
| 14090443   | Invalid volume name  |
| 14090444   | Invalid Vserver name   |
| 14090447   | Invalid volume UUID  |
| 14090448   | Invalid key values. Provide valid Vserver name and volume name or Vserver UUID and volume UUID |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## **Definitions**

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| self | <a href="#">href</a> |             |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string                 | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"><li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li><li>• Introduced in: 9.6</li><li>• x-nullable: true</li></ul> |

snaplock\_file\_fingerprint

| Name                 | Type                   | Description   |
|----------------------|------------------------|---|
| _links               | <a href="#">_links</a> |   |
| algorithm            | string                 | The digest algorithm which is used for the fingerprint computation  |
| data_fingerprint     | string                 | The digest value of data of the file. The fingerprint is base64 encoded. This field is not included if the scope is metadata-only.  |
| file_size            | integer                | The size of the file in bytes.  |
| file_type            | string                 | The type of the file.   |
| id                   | integer                | A unique identifier for the fingerprint operation   |
| metadata_fingerprint | string                 | The digest value of metadata of the file. The metadata fingerprint is calculated for file size, file ctime, file mtime, file crtime, file retention time, file uid, file gid, and file type. The fingerprint is base64 encoded. This field is not included if the scope is data-only. |
| path                 | string                 | Specifies the path on which file fingerprint operation is running or has completed. Specifies the path relative to the output volume root, of the form "/path". The path can be path to a file or a directory.  |
| scope                | string                 | The scope of the file which is used for the fingerprint computation   |
| state                | string                 | Specifies the status of fingerprint operation.  |
| svm                  | <a href="#">svm</a>    | SVM, applies only to SVM-scoped objects.  |
| volume               | <a href="#">volume</a> |   |
| error_arguments      |                        |   |

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Cancel a fingerprint operation

DELETE /storage/snaplock/file-fingerprints/{id}

**Introduced In:** 9.7

Aborts an in-progress fingerprint operation. This API takes session-id as input and aborts the fingerprint operation that is associated with the specified session-id.

### Related ONTAP commands

- volume file fingerprint abort

### Learn more

- [DOC /storage/snaplock/file-fingerprints](#)

### Parameters

| Name | Type   | In   | Required | Description                        |
|------|--------|------|----------|------------------------------------|
| id   | string | path | True     | Unique identifier of the operation |

### Response

Status: 200, Ok

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description                              |
|------------|--|
| 14090440   | File fingerprint operation has completed |
| 14090446   | Invalid session ID                       |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Retrieve the file fingerprint information for a specific session ID

GET /storage/snaplock/file-fingerprints/{id}

**Introduced In:** 9.7

Retrieves the file fingerprint information for a specific session ID.

### Related ONTAP commands

- volume file fingerprint dump

### Learn more

- [DOC /storage/snaplock/file-fingerprints](#)

### Parameters

| Name   | Type          | In    | Required | Description                        |
|--------|---------------|-------|----------|------------------------------------|
| id     | string        | path  | True     | Unique identifier of the operation |
| fields | array[string] | query | False    | Specify the fields to return.      |

## Response

Status: 200, Ok

| Name                 | Type                   | Description   |
|----------------------|------------------------|---|
| _links               | <a href="#">_links</a> |   |
| algorithm            | string                 | The digest algorithm which is used for the fingerprint computation  |
| data_fingerprint     | string                 | The digest value of data of the file. The fingerprint is base64 encoded. This field is not included if the scope is metadata-only.  |
| file_size            | integer                | The size of the file in bytes.  |
| file_type            | string                 | The type of the file.   |
| id                   | integer                | A unique identifier for the fingerprint operation   |
| metadata_fingerprint | string                 | The digest value of metadata of the file. The metadata fingerprint is calculated for file size, file ctime, file mtime, file crtime, file retention time, file uid, file gid, and file type. The fingerprint is base64 encoded. This field is not included if the scope is data-only. |
| path                 | string                 | Specifies the path on which file fingerprint operation is running or has completed. Specifies the path relative to the output volume root, of the form "/path". The path can be path to a file or a directory.  |
| scope                | string                 | The scope of the file which is used for the fingerprint computation   |
| state                | string                 | Specifies the status of fingerprint operation.  |
| svm                  | <a href="#">svm</a>    | SVM, applies only to SVM-scoped objects.  |
| volume               | <a href="#">volume</a> |   |

## Example response

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "algorithm": "sha256",  
    "data_fingerprint": "MOFJVevxNSJm3C/4Bn5oEEYH51CrudOzZYK4r5Cfy1g=",  
    "file_size": 1048576,  
    "file_type": "worm",  
    "id": 17039367,  
    "metadata_fingerprint":  
        "8iMjqJXiNcqgXT5XuRhLiEwIrJEihDmwS0hrexnjgmc=",  
    "path": "/homedir/dir1",  
    "scope": "data_only",  
    "state": "completed",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svml",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "volumel",  
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
    }  
}
```

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 14090441   | Invalid key values. Provide session ID or Vserver UUID and volume UUID |
| 14090449   | File fingerprint operation has not completed                           |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| self | <a href="#">href</a> |             |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string                 | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"><li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li><li>• Introduced in: 9.6</li><li>• x-nullable: true</li></ul> |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Manage SnapLock file retention time

### Storage SnapLock file volume.uuid path endpoint overview

This API manages the SnapLock retention time of a file. You can perform a privileged-delete operation by executing this API.

#### Examples

1. Sets the SnapLock retention time of a file:

```
PATCH "/api/storage/snaplock/file/000dc5fd-4175-11e9-b937-
0050568e3f82/%2Ffile2.txt" '{"expiry_time": "2030-02-14T18:30:00+5:30"}'
```

2. Extends the retention time of a WORM file:

```
PATCH "/api/storage/snaplock/file/000dc5fd-4175-11e9-b937-
0050568e3f82/%2Ffile2.txt" '{"expiry_time": "infinite"}'
```

3. Extends the retention time of a WORM file:

```
PATCH "/api/storage/snaplock/file/000dc5fd-4175-11e9-b937-
0050568e3f82/%2Ffile2.txt" '{"retention_period": "P1M"}'
```

4. Extends the retention time of a WORM file:

```
PATCH "/api/storage/snaplock/file/000dc5fd-4175-11e9-b937-0050568e3f82/%2Ffile2.txt" '{"retention_period": "infinite"}'
```

## Delete unexpired WORM files of a SnapLock enterprise volume

DELETE /storage/snaplock/file/{volume.uuid}/{path}

**Introduced In:** 9.7

Deletes unexpired WORM files of a SnapLock Enterprise volume. This is a privileged-delete operation. The only built-in role that has access to the command is vsadmin-snaplock.

### Related ONTAP commands

- `volume file privileged-delete`

### Learn more

- [DOC /storage/snaplock/file/{volume.uuid}/{path}](#)

### Parameters

| Name        | Type   | In   | Required | Description   |
|-------------|--------|------|----------|---|
| volume.uuid | string | path | True     | Volume UUID   |
| path        | string | path | True     | Path of the file in the form<br>"/<filepath>/<filename>"<br>"/<filename><filepath>" |

| Name           | Type    | In    | Required | Description  |
|----------------|---------|-------|----------|--|
| return_timeout | integer | query | False    | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul> |

## Response

```
Status: 200, Ok
```

| Name | Type                     | Description |
|------|--------------------------|-------------|
| job  | <a href="#">job_link</a> |             |

## Example response

```
{  
  "job": {  
    "_links": {  
      "self": {  
        "href": "/api/resourcelink"  
      }  
    },  
    "uuid": "string"  
  }  
}
```

## Response

Status: 202, Accepted

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 262179     | Unexpected argument "<file_name>\</file_name>"   |
| 6691623    | User is not authorized   |
| 13763162   | SnapLock audit log volume is not configured for the SVM  |
| 13763280   | Only a user with the security login role "vsadmin-snaplock" is allowed to perform this operation |
| 14090347   | File path must be in the format "\<dir>\<file path>"   |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

job\_link

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| uuid   | string | The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation. |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Retrieve SnapLock retention details of a file

GET /storage/snaplock/file/{volume.uuid}/{path}

## Introduced In: 9.7

Retrieves the SnapLock retention details of the specified file. An indefinite expiry time indicates the file is under a Legal-Hold.

### Related ONTAP commands

- volume file retention show

### Learn more

- [DOC /storage/snaplock/file/{volume.uuid}/{path}](#)

### Parameters

| Name        | Type          | In    | Required | Description  |
|-------------|---------------|-------|----------|--|
| volume.uuid | string        | path  | True     | Volume UUID  |
| path        | string        | path  | True     | Path of the file in the form<br>"/<filepath>/<filename>"<br></filename></filepath> |
| fields      | array[string] | query | False    | Specify the fields to return.  |

### Response

Status: 200, Ok

| Name        | Type                   | Description  |
|-------------|------------------------|--|
| _links      | <a href="#">_links</a> |  |
| expiry_time | string                 | Expiry time of the file in date-time format, "infinite", "indefinite", or "unspecified". An "infinite" retention time indicates that the file will be retained forever. An "unspecified" retention time indicates that the file will be retained forever; however, the retention time of the file can be changed to an absolute value. An "indefinite" retention time indicates that the file is under Legal-Hold. |

| Name                 | Type                   | Description   |
|----------------------|------------------------|---|
| file_path            | string                 | Specifies the volume relative path of the file  |
| is_expired           | boolean                | This indicates if the file is under active retention or if the file is past its expiry time.  |
| retention_period     | string                 | Duration of retention time file to be locked with, An "infinite" retention period indicates that the file will be retained forever. |
| seconds_until_expiry | integer                | Specifies the number of seconds until the expiration time of the file.  |
| svm                  | <a href="#">svm</a>    | SVM, applies only to SVM-scoped objects.  |
| volume               | <a href="#">volume</a> |   |

## Example response

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "expiry_time": "2058-06-04 15:00:00 -0400",  
    "file_path": "/dir1/file",  
    "is_expired": 1,  
    "retention_period": "P2M",  
    "seconds_until_expiry": 168,  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svm1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "volume1",  
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
    }  
}
```

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description                                      |
|------------|--|
| 262179     | Unexpected argument "<file_name>\\"</file_name>" |
| 917864     | Operation not supported                          |

| Error code | Description  |
|------------|--|
| 6691623    | User is not authorized                               |
| 13762592   | Operation not supported on non-SnapLock volume       |
| 14090347   | File path must be in the format "\<dir>\<file path>" |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| self | <a href="#">href</a> |             |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string                 | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"><li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li><li>• Introduced in: 9.6</li><li>• x-nullable: true</li></ul> |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Update the SnapLock retention time of a file

PATCH /storage/snaplock/file/{volume.uuid}/{path}

**Introduced In:** 9.7

Updates the SnapLock retention time of a file or extends the retention time of a WORM file. Input parameters "expiry\_time" or "retention\_period" can be used to set or extend the retention time of file. Both "expiry\_time" and "retention\_period" parameters expect the date in ISO 8601 format. Additionally, the "expiry\_time" parameter can also be set to "infinite" or "unspecified" and the "retention\_period" parameter can also be set to "infinite". The input parameters are mutually exclusive.

### Related ONTAP commands

- volume file retention set

### Learn more

- [DOC /storage/snaplock/file/{volume.uuid}/{path}](#)

### Parameters

| Name        | Type   | In   | Required | Description |
|-------------|--------|------|----------|-------------|
| volume.uuid | string | path | True     | Volume UUID |

| Name | Type   | In   | Required | Description  |
|------|--------|------|----------|--|
| path | string | path | True     | Path of the file in the form<br>"/<filepath>/<filename>"<br></filename></filepath> |

## Request Body

| Name                 | Type    | Description  |
|----------------------|---------|--|
| _links               | _links  |  |
| expiry_time          | string  | Expiry time of the file in date-time format, "infinite", "indefinite", or "unspecified". An "infinite" retention time indicates that the file will be retained forever. An "unspecified" retention time indicates that the file will be retained forever; however, the retention time of the file can be changed to an absolute value. An "indefinite" retention time indicates that the file is under Legal-Hold. |
| file_path            | string  | Specifies the volume relative path of the file   |
| is_expired           | boolean | This indicates if the file is under active retention or if the file is past its expiry time.   |
| retention_period     | string  | Duration of retention time file to be locked with, An "infinite" retention period indicates that the file will be retained forever.  |
| seconds_until_expiry | integer | Specifies the number of seconds until the expiration time of the file.   |
| svm                  | svm     | SVM, applies only to SVM-scoped objects.   |
| volume               | volume  |  |

## Example request

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "expiry_time": "2058-06-04 15:00:00 -0400",  
    "file_path": "/dir1/file",  
    "is_expired": 1,  
    "retention_period": "P2M",  
    "seconds_until_expiry": 168,  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svm1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "volume1",  
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
    }  
}
```

## Response

```
Status: 200, Ok
```

## Error

```
Status: Default
```

## ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 262179     | Unexpected argument "<file_name>"</file_name>   |
| 262186     | Field "expiry_time" cannot be used with field "retention_period"  |
| 6691623    | User is not authorized  |
| 13763279   | The resulting expiry time due to the specified retention period is earlier than the current expiry time |
| 14090348   | Invalid Expiry time   |
| 14090347   | File path must be in the format "\<dir>\<file path>"  |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| name   | string | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

| Name   | Type   | Description   |
|--------|--------|---|
| _links | _links |   |
| name   | string | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"><li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li><li>• Introduced in: 9.6</li><li>• x-nullable: true</li></ul> |

snaplock\_file\_retention

| Name                 | Type                   | Description  |
|----------------------|------------------------|--|
| _links               | <a href="#">_links</a> |  |
| expiry_time          | string                 | Expiry time of the file in date-time format, "infinite", "indefinite", or "unspecified". An "infinite" retention time indicates that the file will be retained forever. An "unspecified" retention time indicates that the file will be retained forever; however, the retention time of the file can be changed to an absolute value. An "indefinite" retention time indicates that the file is under Legal-Hold. |
| file_path            | string                 | Specifies the volume relative path of the file   |
| is_expired           | boolean                | This indicates if the file is under active retention or if the file is past its expiry time.   |
| retention_period     | string                 | Duration of retention time file to be locked with, An "infinite" retention period indicates that the file will be retained forever.  |
| seconds_until_expiry | integer                | Specifies the number of seconds until the expiration time of the file.   |
| svm                  | <a href="#">svm</a>    | SVM, applies only to SVM-scoped objects.   |
| volume               | <a href="#">volume</a> |  |

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Manage SnapLock storage litigations

### Storage SnapLock litigations endpoint overview

Use this API to retain Compliance-mode WORM files for the duration of a litigation. A file under a legal-hold behaves as a WORM file with an indefinite retention period. Litigation ID is a combination of volume UUID and litigation name in the format <volume UUID>:<litigation name>. Only a user with the security login role vsadmin-snaplock can perform the operation.

#### Retrieve litigations under an SVM

GET /storage/snaplock/litigations

**Introduced In:** 9.7

Retrieves the list of litigations under an SVM.

#### Related ONTAP commands

- snaplock legal-hold show

#### Learn more

- [DOC /storage/snaplock/litigations](#)

#### Parameters

| Name        | Type          | In    | Required | Description                           |
|-------------|---------------|-------|----------|---------------------------------------|
| fields      | array[string] | query | False    | Specify the fields to return.         |
| max_records | integer       | query | False    | Limit the number of records returned. |

| Name           | Type          | In    | Required | Description  |
|----------------|---------------|-------|----------|--|
| return_timeout | integer       | query | False    | <p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul> |
| return_records | boolean       | query | False    | <p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>  |
| order_by       | array[string] | query | False    | Order results by specified fields and optional [asc]   |

## Response

```
Status: 200, Ok
```

| Name        | Type   | Description       |
|-------------|--|-------------------|
| _links      | <a href="#">_links</a>                       |                   |
| num_records | integer                                      | Number of Records |
| records     | array[ <a href="#">snaplock_litigation</a> ] |                   |

## Example response

```
{  
    "_links": {  
        "next": {  
            "href": "/api/resourcelink"  
        },  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "num_records": 1,  
    "records": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "id": "string",  
        "name": "liti1",  
        "operations": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "id": 16842759,  
            "num_files_failed": 0,  
            "num_files_processed": 30,  
            "num_files_skipped": 10,  
            "num_inodes_ignored": 10,  
            "path": "/dir1",  
            "state": "completed",  
            "type": "begin"  
        },  
        "path": "/dir1",  
        "svm": {  
            "_links": {  
                "self": {  
                    "href": "/api/resourcelink"  
                }  
            },  
            "name": "svml1",  
            "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
        },  
        "volume": {  
    }
```

```

    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
}
}

```

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation. |
| 14090346   | Internal Error. Wait a few minutes, then try the command again                                |
| 14090343   | Invalid field   |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

### Example error

```

{
    "error": {
        "arguments": {
            "code": "string",
            "message": "string"
        },
        "code": "4",
        "message": "entry doesn't exist",
        "target": "uuid"
    }
}

```

## **Definitions**

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| next | href |             |
| self | href |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

snaplock\_legal\_hold\_operation

| Name                | Type    | Description  |
|---------------------|---------|--|
| _links              | _links  |  |
| id                  | integer | Operation ID.  |
| num_files_failed    | string  | Specifies the number of files on which legal-hold operation failed.  |
| num_files_processed | string  | Specifies the number of files on which legal-hold operation was successful.  |
| num_files_skipped   | string  | Specifies the number of files on which legal-hold begin operation was skipped. The legal-hold begin operation is skipped on a file if it is already under hold for a given litigation. |
| num_inodes_ignored  | string  | Specifies the number of inodes on which the legal-hold operation was not attempted because they were not regular files.  |
| path                | string  | Specifies the path on which legal-hold operation is applied.   |

| Name  | Type   | Description                                   |
|-------|--------|---|
| state | string | Specifies the status of legal-hold operation. |
| type  | string | Specifies the type of legal-hold operation.   |

## svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

## volume

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string                 | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"> <li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>• Introduced in: 9.6</li> <li>• x-nullable: true</li> </ul> |

## snaplock\_litigation

| Name   | Type                   | Description |
|--------|------------------------|-------------|
| _links | <a href="#">_links</a> |             |

| Name       | Type                                 | Description   |
|------------|--------------------------------------|---|
| id         | string                               | Specifies the litigation ID.  |
| name       | string                               | Specifies the legal-hold litigation name.                           |
| operations | array[snaplock_legal_hold_operation] |   |
| path       | string                               | Specifies the path on which legal-hold operation has to be applied. |
| svm        | svm                                  | SVM, applies only to SVM-scoped objects.                            |
| volume     | volume                               |   |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Start a legal-hold operation

POST /storage/snaplock/litigations

**Introduced In:** 9.7

Starts a Legal-Hold.

## Required properties

- path - Path of the file.
- name - Litigation name.
- volume.name or volume.uuid - Name or UUID of the volume.

## Related ONTAP commands

- snaplock legal-hold begin

## Example

```
POST "/api/storage/snaplock/litigations"
'{"volume.name":"SLC1","name":"l3","path":"/b.txt"}'
```

## Learn more

- [DOC /storage/snaplock/litigations](#)

## Parameters

| Name           | Type    | In    | Required | Description   |
|----------------|---------|-------|----------|---|
| return_records | boolean | query | False    | <p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"><li>• Default value:</li></ul> |

## Request Body

| Name       | Type   | Description   |
|------------|--|---|
| _links     | <a href="#">_links</a>                                 |   |
| id         | string   | Specifies the litigation ID.  |
| name       | string   | Specifies the legal-hold litigation name.                           |
| operations | array[ <a href="#">snaplock_legal_hold_operation</a> ] |   |
| path       | string   | Specifies the path on which legal-hold operation has to be applied. |
| svm        | <a href="#">svm</a>                                    | SVM, applies only to SVM-scoped objects.                            |

| Name   | Type   | Description |
|--------|--------|-------------|
| volume | volume |             |

## Example request

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "id": "string",  
    "name": "lit1",  
    "operations": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "id": 16842759,  
        "num_files_failed": 0,  
        "num_files_processed": 30,  
        "num_files_skipped": 10,  
        "num_inodes_ignored": 10,  
        "path": "/dir1",  
        "state": "completed",  
        "type": "begin"  
    },  
    "path": "/dir1",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svml1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "volumel1",  
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
    }  
}
```

## Response

Status: 201, Created

## Headers

| Name     | Description                               | Type   |
|----------|---|--------|
| Location | Useful for tracking the resource location | string |

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 13762586   | Volume is not a SnapLock Compliance volume  |
| 13763162   | Audit logging is not configured for the SVM   |
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation. |
| 14090346   | Internal Error. Wait a few minutes, then try the command again                                |
| 14090340   | {field} is a required field   |
| 14090343   | Invalid Field   |
| 14090641   | The specified volume.name and volume.uuid refer to different volumes                          |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

snaplock\_legal\_hold\_operation

| Name                | Type    | Description  |
|---------------------|---------|--|
| _links              | _links  |  |
| id                  | integer | Operation ID.  |
| num_files_failed    | string  | Specifies the number of files on which legal-hold operation failed.  |
| num_files_processed | string  | Specifies the number of files on which legal-hold operation was successful.  |
| num_files_skipped   | string  | Specifies the number of files on which legal-hold begin operation was skipped. The legal-hold begin operation is skipped on a file if it is already under hold for a given litigation. |
| num_inodes_ignored  | string  | Specifies the number of inodes on which the legal-hold operation was not attempted because they were not regular files.  |
| path                | string  | Specifies the path on which legal-hold operation is applied.   |
| state               | string  | Specifies the status of legal-hold operation.  |
| type                | string  | Specifies the type of legal-hold operation.  |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

#### volume

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string                 | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"> <li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>• Introduced in: 9.6</li> <li>• x-nullable: true</li> </ul> |

#### snaplock\_litigation

| Name       | Type                                 | Description   |
|------------|--------------------------------------|---|
| _links     | <a href="#">_links</a>               |   |
| id         | string                               | Specifies the litigation ID.  |
| name       | string                               | Specifies the legal-hold litigation name.                           |
| operations | array[snaplock_legal_hold_operation] |   |
| path       | string                               | Specifies the path on which legal-hold operation has to be applied. |

| Name   | Type   | Description                              |
|--------|--------|--|
| svm    | svm    | SVM, applies only to SVM-scoped objects. |
| volume | volume |  |

### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

### returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Create a legal-hold end on all of the files for a litigation ID

DELETE /storage/snaplock/litigations/{id}

**Introduced In:** 9.7

Creates a legal-hold end on all of the files for the specified litigation ID. This is only allowed when an operation is no longer in progress.

### Related ONTAP commands

- snaplock legal-hold end

### Example

```
DELETE "/api/storage/snaplock/litigations/fd72e138-4bc3-11e9-a85f-0050568eb48f%3A13"
```

## Learn more

- [DOC /storage/snaplock/litigations](#)

## Parameters

| Name | Type   | In   | Required | Description   |
|------|--------|------|----------|---------------|
| id   | string | path | True     | Litigation ID |

## Response

Status: 200, Ok

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description  |
|------------|--|
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation.                                      |
| 14090343   | Invalid Field  |
| 14090346   | Internal Error. Wait a few minutes, then try the command again   |
| 14090642   | Legal-Hold operation is in progress. Legal-Hold end cannot be performed. Wait for the operation to complete or abort the operation |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

### See Definitions

#### error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

#### returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Retrieve ongoing operations for a litigation ID

GET /storage/snaplock/litigations/{id}

Introduced In: 9.7

Retrieves the list of ongoing operations for the specified litigation ID.

## Related ONTAP commands

- snaplock legal-hold show

## Learn more

- [DOC /storage/snaplock/litigations](#)

## Parameters

| Name   | Type          | In    | Required | Description                   |
|--------|---------------|-------|----------|-------------------------------|
| id     | string        | path  | True     | Litigation ID                 |
| fields | array[string] | query | False    | Specify the fields to return. |

## Response

Status: 200, Ok

| Name       | Type   | Description   |
|------------|--|---|
| _links     | <a href="#">_links</a>                                 |   |
| id         | string   | Specifies the litigation ID.  |
| name       | string   | Specifies the legal-hold litigation name.                           |
| operations | array[ <a href="#">snaplock_legal_hold_operation</a> ] |   |
| path       | string   | Specifies the path on which legal-hold operation has to be applied. |
| svm        | <a href="#">svm</a>                                    | SVM, applies only to SVM-scoped objects.                            |
| volume     | <a href="#">volume</a>                                 |   |

## Example response

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "id": "string",  
    "name": "lit1",  
    "operations": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "id": 16842759,  
        "num_files_failed": 0,  
        "num_files_processed": 30,  
        "num_files_skipped": 10,  
        "num_inodes_ignored": 10,  
        "path": "/dir1",  
        "state": "completed",  
        "type": "begin"  
    },  
    "path": "/dir1",  
    "svm": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "svml1",  
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "volume": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        },  
        "name": "volumel1",  
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"  
    }  
}
```

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation. |
| 14090346   | Internal Error. Wait a few minutes, then try the command again                                |
| 14090343   | Invalid Field   |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

snaplock\_legal\_hold\_operation

| Name                | Type    | Description  |
|---------------------|---------|--|
| _links              | _links  |  |
| id                  | integer | Operation ID.  |
| num_files_failed    | string  | Specifies the number of files on which legal-hold operation failed.  |
| num_files_processed | string  | Specifies the number of files on which legal-hold operation was successful.  |
| num_files_skipped   | string  | Specifies the number of files on which legal-hold begin operation was skipped. The legal-hold begin operation is skipped on a file if it is already under hold for a given litigation. |
| num_inodes_ignored  | string  | Specifies the number of inodes on which the legal-hold operation was not attempted because they were not regular files.  |
| path                | string  | Specifies the path on which legal-hold operation is applied.   |
| state               | string  | Specifies the status of legal-hold operation.  |
| type                | string  | Specifies the type of legal-hold operation.  |

svm

SVM, applies only to SVM-scoped objects.

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the SVM. This field cannot be specified in a PATCH method.              |
| uuid   | string                 | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

| Name   | Type                   | Description   |
|--------|------------------------|---|
| _links | <a href="#">_links</a> |   |
| name   | string                 | The name of the volume. This field cannot be specified in a POST or PATCH method.   |
| uuid   | string                 | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> <li>example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>Introduced in: 9.6</li> <li>x-nullables: true</li> </ul> |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description       |
|-----------|------------------------|-------------------|
| arguments | array[error_arguments] | Message arguments |

| Name    | Type   | Description                                 |
|---------|--------|---|
| code    | string | Error code                                  |
| message | string | Error message                               |
| target  | string | The target parameter that caused the error. |

## View litigation ID files

### Storage SnapLock litigations litigation.id files endpoint overview

Displays the list of files under the specified litigation ID.

#### Display files for a litigation ID

GET /storage/snaplock/litigations/{litigation.id}/files

**Introduced In:** 9.7

Displays the list of files for the specified litigation ID.

#### Parameters

| Name           | Type          | In    | Required | Description  |
|----------------|---------------|-------|----------|--|
| litigation.id  | string        | path  | True     | Litigation ID  |
| fields         | array[string] | query | False    | Specify the fields to return.  |
| max_records    | integer       | query | False    | Limit the number of records returned.  |
| return_records | boolean       | query | False    | The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none"> <li>Default value: 1</li> </ul> |

| Name           | Type          | In    | Required | Description  |
|----------------|---------------|-------|----------|--|
| return_timeout | integer       | query | False    | <p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul> |
| order_by       | array[string] | query | False    | Order results by specified fields and optional [asc]   |

## Response

Status: 200, Ok

| Name        | Type                             | Description                                   |
|-------------|----------------------------------|---|
| _links      | <a href="#">_links</a>           |   |
| num_records | integer                          | Number of records                             |
| records     | array[ <a href="#">records</a> ] | List of Files under the specified litigation. |

## Example response

```
{  
  "_links": {  
    "next": {  
      "href": "/api/resourcelink"  
    },  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "num_records": 1,  
  "records": {  
    "file": {  
    }  
  }  
}
```

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation. |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type                 | Description |
|------|----------------------|-------------|
| next | <a href="#">href</a> |             |
| self | <a href="#">href</a> |             |

records

| Name           | Type          | Description  |
|----------------|---------------|--|
| file           | array[string] | Name of the file including the path from the root. |
| sequence_index | integer       | Sequence index of files path list.                 |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

# Manage legal-hold operations

## Storage SnapLock litigations litigation.id operations endpoint overview

Manages the legal-hold operations for the specified litigation ID.

### Examples

1. Adds a Legal-Hold.

```
POST "/api/storage/snaplock/litigations/f8a67b60-4461-11e9-b327-0050568ebef5:11/operations" '{"type" : "begin", "path" : "/a.txt"}'
```

1. Removes a Legal-Hold.

```
POST "/api/storage/snaplock/litigations/f8a67b60-4461-11e9-b327-0050568ebef5:11/operations" '{"type" : "end", "path" : "/a.txt"}'
```

## Create or remove litigations for a path

POST /storage/snaplock/litigations/{litigation.id}/operations

**Introduced In:** 9.7

Creates or removes litigations for the specified path.

### Required properties

- type - Legal-Hold operation type.
- path - Litigation path.

### Related ONTAP commands

- snaplock legal-hold begin
- snaplock legal-hold end

### Learn more

- [DOC /storage/snaplock/litigations/{litigation.id}/operations](#)

### Parameters

| Name          | Type   | In   | Required | Description   |
|---------------|--------|------|----------|---------------|
| litigation.id | string | path | True     | Litigation ID |

| Name           | Type    | In    | Required | Description   |
|----------------|---------|-------|----------|---|
| return_records | boolean | query | False    | <p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> <li>• Default value:</li> </ul> |

## Request Body

| Name                | Type                   | Description  |
|---------------------|------------------------|--|
| _links              | <a href="#">_links</a> |  |
| id                  | integer                | Operation ID.  |
| num_files_failed    | string                 | Specifies the number of files on which legal-hold operation failed.  |
| num_files_processed | string                 | Specifies the number of files on which legal-hold operation was successful.  |
| num_files_skipped   | string                 | Specifies the number of files on which legal-hold begin operation was skipped. The legal-hold begin operation is skipped on a file if it is already under hold for a given litigation. |
| num_inodes_ignored  | string                 | Specifies the number of inodes on which the legal-hold operation was not attempted because they were not regular files.  |
| path                | string                 | Specifies the path on which legal-hold operation is applied.   |
| state               | string                 | Specifies the status of legal-hold operation.  |
| type                | string                 | Specifies the type of legal-hold operation.  |

## Example request

```
{  
  "_links": {  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "id": 16842759,  
  "num_files_failed": 0,  
  "num_files_processed": 30,  
  "num_files_skipped": 10,  
  "num_inodes_ignored": 10,  
  "path": "/dir1",  
  "state": "completed",  
  "type": "begin"  
}
```

## Response

Status: 201, Created

| Name                | Type    | Description  |
|---------------------|---------|--|
| _links              | _links  |  |
| id                  | integer | Operation ID.  |
| num_files_failed    | string  | Specifies the number of files on which legal-hold operation failed.  |
| num_files_processed | string  | Specifies the number of files on which legal-hold operation was successful.  |
| num_files_skipped   | string  | Specifies the number of files on which legal-hold begin operation was skipped. The legal-hold begin operation is skipped on a file if it is already under hold for a given litigation. |

| Name               | Type   | Description   |
|--------------------|--------|---|
| num_inodes_ignored | string | Specifies the number of inodes on which the legal-hold operation was not attempted because they were not regular files. |
| path               | string | Specifies the path on which legal-hold operation is applied.  |
| state              | string | Specifies the status of legal-hold operation.   |
| type               | string | Specifies the type of legal-hold operation.   |

### Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "id": 16842759,
  "num_files_failed": 0,
  "num_files_processed": 30,
  "num_files_skipped": 10,
  "num_inodes_ignored": 10,
  "path": "/dir1",
  "state": "completed",
  "type": "begin"
}
```

### Headers

| Name     | Description                               | Type   |
|----------|---|--------|
| Location | Useful for tracking the resource location | string |

### Error

Status: Default

## ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation. |
| 14090343   | Invalid Field   |
| 14090346   | Internal Error. Wait a few minutes, then try the command again                                |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

### Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

### Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

snaplock\_legal\_hold\_operation

| Name                | Type    | Description  |
|---------------------|---------|--|
| _links              | _links  |  |
| id                  | integer | Operation ID.  |
| num_files_failed    | string  | Specifies the number of files on which legal-hold operation failed.  |
| num_files_processed | string  | Specifies the number of files on which legal-hold operation was successful.  |
| num_files_skipped   | string  | Specifies the number of files on which legal-hold begin operation was skipped. The legal-hold begin operation is skipped on a file if it is already under hold for a given litigation. |
| num_inodes_ignored  | string  | Specifies the number of inodes on which the legal-hold operation was not attempted because they were not regular files.  |
| path                | string  | Specifies the path on which legal-hold operation is applied.   |
| state               | string  | Specifies the status of legal-hold operation.  |
| type                | string  | Specifies the type of legal-hold operation.  |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Cancel the ongoing legal-hold operation

DELETE /storage/snaplock/litigations/{litigation.id}/operations/{id}

**Introduced In:** 9.7

Aborts the ongoing legal-hold operation. An abort does not rollback any changes already made. You must re-run begin or end for cleanup.

### Related ONTAP commands

- snaplock legal-hold abort

### Example

```
DELETE "/api/storage/snaplock/litigations/f8a67b60-4461-11e9-b327-0050568ebef5:11/operations/16908292"
```

### Learn more

- [DOC /storage/snaplock/litigations/{litigation.id}/operations](#)

### Parameters

| Name          | Type   | In   | Required | Description   |
|---------------|--------|------|----------|---------------|
| litigation.id | string | path | True     | Litigation ID |

| Name | Type   | In   | Required | Description   |
|------|--------|------|----------|---------------|
| id   | string | path | True     | Operation ID. |

## Response

Status: 200, Ok

## Error

Status: Default

## ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation. |
| 13763378   | SnapLock legal-hold operation for this operation ID does not exist                            |
| 14090346   | Internal Error. Wait a few minutes, then try the command again                                |
| 14090541   | A completed or failed operation cannot be aborted   |

| Name  | Type                           | Description |
|-------|--------------------------------|-------------|
| error | <a href="#">returned_error</a> |             |

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

### See Definitions

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## Retrieve the status of legal-hold for an operation ID

GET /storage/snaplock/litigations/{litigation.id}/operations/{id}

**Introduced In:** 9.7

Retrieves the status of legal-hold for the specified operation ID.

### Related ONTAP commands

- snaplock legal-hold show

### Learn more

- [DOC /storage/snaplock/litigations/{litigation.id}/operations](#)

### Parameters

| Name          | Type   | In   | Required | Description   |
|---------------|--------|------|----------|---------------|
| litigation.id | string | path | True     | Litigation ID |
| id            | string | path | True     | Operation ID. |

| Name   | Type          | In    | Required | Description                   |
|--------|---------------|-------|----------|-------------------------------|
| fields | array[string] | query | False    | Specify the fields to return. |

## Response

Status: 200, Ok

| Name                | Type                   | Description  |
|---------------------|------------------------|--|
| _links              | <a href="#">_links</a> |  |
| id                  | integer                | Operation ID.  |
| num_files_failed    | string                 | Specifies the number of files on which legal-hold operation failed.  |
| num_files_processed | string                 | Specifies the number of files on which legal-hold operation was successful.  |
| num_files_skipped   | string                 | Specifies the number of files on which legal-hold begin operation was skipped. The legal-hold begin operation is skipped on a file if it is already under hold for a given litigation. |
| num_inodes_ignored  | string                 | Specifies the number of inodes on which the legal-hold operation was not attempted because they were not regular files.  |
| path                | string                 | Specifies the path on which legal-hold operation is applied.   |
| state               | string                 | Specifies the status of legal-hold operation.  |
| type                | string                 | Specifies the type of legal-hold operation.  |

## Example response

```
{  
    "_links": {  
        "self": {  
            "href": "/api/resourcelink"  
        }  
    },  
    "id": 16842759,  
    "num_files_failed": 0,  
    "num_files_processed": 30,  
    "num_files_skipped": 10,  
    "num_inodes_ignored": 10,  
    "path": "/dir1",  
    "state": "completed",  
    "type": "begin"  
}
```

## Error

Status: Default

### ONTAP Error Response codes

| Error code | Description   |
|------------|---|
| 13763280   | Only a user with security login role "vsadmin-snaplock" is allowed to perform this operation. |
| 14090343   | Invalid Field   |
| 14090346   | Internal Error. Wait a few minutes, then try the command again                                |

| Name  | Type           | Description |
|-------|----------------|-------------|
| error | returned_error |             |

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

| Name | Type   | Description |
|------|--------|-------------|
| href | string |             |

\_links

| Name | Type | Description |
|------|------|-------------|
| self | href |             |

error\_arguments

| Name    | Type   | Description      |
|---------|--------|------------------|
| code    | string | Argument code    |
| message | string | Message argument |

returned\_error

| Name      | Type                   | Description                                 |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments                           |
| code      | string                 | Error code                                  |
| message   | string                 | Error message                               |
| target    | string                 | The target parameter that caused the error. |

## **Copyright information**

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—with prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## **Trademark information**

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.