



View and update shadow copy information

ONTAP 9.14.1 REST API reference

NetApp
May 23, 2024

Table of Contents

- View and update shadow copy information 1
 - Protocols CIFS shadow-copies endpoint overview 1
 - Retrieve shadow copies 6
 - Retrieve a shadow copy 14
 - Update a shadow copy 19
 - Retrieve shadow copy sets 27
 - Retrieve a shadow copy set 32
 - Update a shadow copy set 36

View and update shadow copy information

Protocols CIFS shadow-copies endpoint overview

Microsoft Remote Volume Shadow Copy Services (VSS) is an extension of the existing Microsoft VSS infrastructure. Previously, VSS could be used for backup services only for data stored on the local disk. This limited the use of VSS to applications that stored data either on a local disk or on SAN-based storage. With Remote VSS, Microsoft has extended the VSS infrastructure to support the shadow copying of SMB shares. Server applications, such as, Hyper-V are now storing VHD files on SMB file shares. With these new extensions, it is possible to take application consistent shadow copies for virtual machines that store data and configuration files on shares.

Retrieving Shadow copy sets for all SVMs

```
# The API:
GET /api/protocols/cifs/shadowcopy-sets

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/shadowcopy-sets?fields=*&return_records=true&return_timeout=15" -H "accept: application/json" -H "authorization: Basic YWRtaW46bmV0YXBwMSE="

# The Response:
{
  "records": [
    {
      "uuid": "27ed1b79-97f6-11ec-8ad1-0050568e57be",
      "svm": {
        "uuid": "dfb8e00d-9498-11ec-9f9d-0050568e57be",
        "name": "vs1"
      },
      "keep_snapshots": true
    },
    {
      "uuid": "388be551-97f6-11ec-8ad1-0050568e57be",
      "svm": {
        "uuid": "dfb8e00d-9498-11ec-9f9d-0050568e57be",
        "name": "vs1"
      },
      "keep_snapshots": false
    },
    {
      "uuid": "525104ef-9f96-11ec-82fd-0050568e57be",
      "svm": {
        "uuid": "fdb5bd8b-9498-11ec-9f9d-0050568e57be",
```

```
    "name": "vs2"
  },
  "keep_snapshots": false
},
{
  "uuid": "66f8f723-9f96-11ec-82fd-0050568e57be",
  "svm": {
    "uuid": "fdb5bd8b-9498-11ec-9f9d-0050568e57be",
    "name": "vs2"
  },
  "keep_snapshots": true
}
],
"num_records": 4
}
```

Retrieving information for a specific shadow copy set

```
# The API:
GET /api/protocols/cifs/shadowcopy-sets/{uuid}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/shadowcopy-sets/525104ef-9f96-11ec-82fd-0050568e57be?fields=*" -H "accept: application/json"

# The Response:
{
  "uuid": "525104ef-9f96-11ec-82fd-0050568e57be",
  "svm": {
    "uuid": "fdb5bd8b-9498-11ec-9f9d-0050568e57be",
    "name": "vs2"
  },
  "keep_snapshots": false
}
```

Updating the keep-snapshot property of a specific shadow copy set

```
# The API:
GET /api/protocols/cifs/shadowcopy-sets/{uuid}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/shadowcopy-sets/525104ef-9f96-11ec-82fd-0050568e57be" -H "accept: application/json" -H "Content-Type: application/json" -d '{"keep_snapshots": true}'
```

Retrieving shadow copy information for all SVMs

```
# The API:
GET /api/protocols/cifs/shadow-copies

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/shadow-copies?fields=*&return_records=true&return_timeout=15" -H "accept: application/json"

# The Response:
{
  "records": [
    {
      "svm": {
        "uuid": "dfb8e00d-9498-11ec-9f9d-0050568e57be",
        "name": "vs1"
      },
      "shadowcopy_set": {
        "uuid": "9169cd4a-a421-11ec-b82e-0050568e57be"
      },
      "uuid": "919fbc80-a421-11ec-b82e-0050568e57be",
      "share": {
        "name": "sh1"
      },
      "client_uuid": "918536b7-a421-11ec-b82e-0050568e57be",
      "volume": {
        "uuid": "e117c8f6-9498-11ec-9f9d-0050568e57be",
        "name": "vol1"
      }
    },
    {
      "svm": {
```

```

    "uuid": "dfb8e00d-9498-11ec-9f9d-0050568e57be",
    "name": "vs1"
  },
  "shadowcopy_set": {
    "uuid": "9169cd4a-a421-11ec-b82e-0050568e57be"
  },
  "uuid": "91ac5a5f-a421-11ec-b82e-0050568e57be",
  "share": {
    "name": "sh2"
  },
  "client_uuid": "91a9252b-a421-11ec-b82e-0050568e57be",
  "volume": {
    "uuid": "e117c8f6-9498-11ec-9f9d-0050568e57be",
    "name": "vol1"
  }
},
{
  "svm": {
    "uuid": "dfb8e00d-9498-11ec-9f9d-0050568e57be",
    "name": "vs1"
  },
  "shadowcopy_set": {
    "uuid": "9169cd4a-a421-11ec-b82e-0050568e57be"
  },
  "uuid": "91b14098-a421-11ec-b82e-0050568e57be",
  "share": {
    "name": "sh3"
  },
  "client_uuid": "91adfc85-a421-11ec-b82e-0050568e57be",
  "volume": {
    "uuid": "e117c8f6-9498-11ec-9f9d-0050568e57be",
    "name": "vol1"
  }
},
{
  "svm": {
    "uuid": "dfb8e00d-9498-11ec-9f9d-0050568e57be",
    "name": "vs1"
  },
  "shadowcopy_set": {
    "uuid": "9169cd4a-a421-11ec-b82e-0050568e57be"
  },
  "uuid": "91b63309-a421-11ec-b82e-0050568e57be",
  "share": {
    "name": "sh4"
  }
},

```

```
    "client_uuid": "91b2f817-a421-11ec-b82e-0050568e57be",
    "volume": {
      "uuid": "e117c8f6-9498-11ec-9f9d-0050568e57be",
      "name": "vol1"
    }
  },
  "num_records": 4
}
```

Retrieving information for a specific shadow copy

```
# The API:
GET /api/protocols/cifs/shadow-copies/{client_uuid}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/shadow-copies/91adfc85-
a421-11ec-b82e-0050568e57be?fields=*" -H "accept: application/json"

# The Response:
{
  "svm": {
    "uuid": "dfb8e00d-9498-11ec-9f9d-0050568e57be",
    "name": "vs1"
  },
  "shadowcopy_set": {
    "uuid": "9169cd4a-a421-11ec-b82e-0050568e57be"
  },
  "uuid": "91b14098-a421-11ec-b82e-0050568e57be",
  "share": {
    "name": "sh3"
  },
  "client_uuid": "91adfc85-a421-11ec-b82e-0050568e57be",
  "volume": {
    "uuid": "e117c8f6-9498-11ec-9f9d-0050568e57be",
    "name": "vol1"
  }
}
```

Updating the list of files to be shadowcopied in a particular share

Use this endpoint to update the list of files to be shadow copied in a particular share. Set "restore" field as false to perform this operation.

```
# The API:
PATCH /protocols/cifs/shadow-copies/{client_uuid}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/shadow-copies/91adfc85-a421-11ec-b82e-0050568e57be?restore=false" -H "accept: application/json" -d "{ \"files\": [ \"/vhd1\", \"/vhd2\" ]}"
```

Requesting the storage system to restore a directory

You set restore field to true to perform this operation. Only users with the security login role "vsadmin" can perform the operation.

```
# The API:
PATCH /protocols/cifs/shadow-copies?restore=true

# The call:
PATCH "api/protocols/cifs/shadow-copies?restore=true" -d "{ \"destination_dir\": \"/dir2\", \"source_dir\": \"/src_dir\", \"volume\": { \"name\": \"test_vol\" }, \"with_content\": false}"
```

Retrieve shadow copies

GET /protocols/cifs/shadow-copies

Introduced In: 9.11

Retrieves Shadowcopies

Related ONTAP commands

- vserver cifs shadowcopy show-shares

Learn more

- [DOC /protocols/cifs/shadow-copies](#)

Parameters

| Name | Type | In | Required | Description |
|---|----------------|---------------|----------|---|
| files | string | query | False | Filter by files |
| client_uuid | string | query | False | Filter by client_uuid |
| svm.uuid | string | query | False | Filter by svm.uuid |
| svm.name | string | query | False | Filter by svm.name |
| share.name | string | query | False | Filter by share.name |
| uuid | string | query | False | Filter by uuid |
| shadowcopy_set.uuid | string | query | False | Filter by shadowcopy_set.uuid |
| order_by | array[string] | query | False | Order results by specified fields and optional [asc |
| desc] direction. Default direction is 'asc' for ascending. | fields | array[string] | query | False |
| Specify the fields to return. | max_records | integer | query | False |
| Limit the number of records returned. | return_records | boolean | query | False |
| The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none">• Default value: 1 | return_timeout | integer | query | False |

Response

Status: 200, Ok

| Name | Type | Description |
|-------------|-------------------------------------|-------------------|
| _links | _links | |
| num_records | integer | Number of records |
| records | array[shadowcopy] | |

Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "num_records": 1,
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "client_uuid": "abc13450-1f19-40ba-9b82-ebf277517e7e",
    "destination_dir": "/dir2",
    "files": [
      "/vhd1",
      "/vhd2"
    ],
    "shadowcopy_set": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "uuid": "5f4e19f3-5e2d-11ec-8766-005056a7c134"
    },
    "share": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "sh1"
    },
    "source_dir": "/dir1",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      }
    }
  }
}
```

```

    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "uuid": "fef32805-1f19-40ba-9b82-ebf277517e7e",
  "volume": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}

```

Error

Status: Default, Error

| Name | Type | Description |
|-------|--------------------------------|-------------|
| error | returned_error | |

Example error

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| next | href | |
| self | href | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

self_link

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

shadowcopy_set

| Name | Type | Description |
|--------|---------------------------|-------------|
| _links | self_link | |
| uuid | string | |

share

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | Share name |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

The name of the volume where the source and destination directories reside.

| Name | Type | Description |
|--------|------------------------|--|
| _links | _links | |
| name | string | The name of the volume. This field cannot be specified in a POST or PATCH method. |
| uuid | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> • example: 028baa66-41bd-11e9-81d5-00a0986138f7 • Introduced in: 9.6 • x-nullable: true |

shadowcopy

| Name | Type | Description |
|-----------------|------------------------|---|
| _links | _links | |
| client_uuid | string | The universally-unique identifier of the client's shadow copy. |
| destination_dir | string | The path of the destination directory. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the volume. |

| Name | Type | Description |
|----------------|--------------------------------|--|
| files | array[string] | The list of files to shadow copy in the share. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the share. |
| shadowcopy_set | shadowcopy_set | |
| share | share | |
| source_dir | string | The path of the source directory. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the volume. |
| svm | svm | SVM, applies only to SVM-scoped objects. |
| uuid | string | The universally-unique identifier of the storage's shadow copy. |
| volume | volume | The name of the volume where the source and destination directories reside. |
| with_content | boolean | Specifies what needs to be restored. False specifies the directory only. True indicates the directory and its content. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|--|-------------------|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |

| Name | Type | Description |
|---------|--------|---|
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Retrieve a shadow copy

GET /protocols/cifs/shadow-copies/{client_uuid}

Introduced In: 9.11

Retrieves a Shadowcopy

Related ONTAP commands

- `vserver cifs shadowcopy show-shares`

Learn more

- [DOC /protocols/cifs/shadow-copies](#)

Parameters

| Name | Type | In | Required | Description |
|--------|---------------|-------|----------|-------------------------------|
| fields | array[string] | query | False | Specify the fields to return. |

Response

Status: 200, Ok

| Name | Type | Description |
|------------------------|------------------------|---|
| _links | _links | |
| client_uuid | string | The universally-unique identifier of the client's shadow copy. |
| destination_dir | string | The path of the destination directory. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the volume. |

| Name | Type | Description |
|----------------|--------------------------------|--|
| files | array[string] | The list of files to shadow copy in the share. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the share. |
| shadowcopy_set | shadowcopy_set | |
| share | share | |
| source_dir | string | The path of the source directory. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the volume. |
| svm | svm | SVM, applies only to SVM-scoped objects. |
| uuid | string | The universally-unique identifier of the storage's shadow copy. |
| volume | volume | The name of the volume where the source and destination directories reside. |
| with_content | boolean | Specifies what needs to be restored. False specifies the directory only. True indicates the directory and its content. |

Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "client_uuid": "abc13450-1f19-40ba-9b82-ebf277517e7e",
  "destination_dir": "/dir2",
  "files": [
    "/vhd1",
    "/vhd2"
  ],
  "shadowcopy_set": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "uuid": "5f4e19f3-5e2d-11ec-8766-005056a7c134"
},
"share": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "sh1"
},
"source_dir": "/dir1",
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"uuid": "fef32805-1f19-40ba-9b82-ebf277517e7e",
"volume": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  }
}
```

```
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}
```

Error

Status: Default, Error

| Name | Type | Description |
|-------|--------------------------------|-------------|
| error | returned_error | |

Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

self_link

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

shadowcopy_set

| Name | Type | Description |
|--------|---------------------------|-------------|
| _links | self_link | |
| uuid | string | |

share

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | Share name |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

The name of the volume where the source and destination directories reside.

| Name | Type | Description |
|------------------------|------------------------|---|
| _links | _links | |
| name | string | The name of the volume. This field cannot be specified in a POST or PATCH method. |
| uuid | string | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none">• example: 028baa66-41bd-11e9-81d5-00a0986138f7• Introduced in: 9.6• x-nullable: true |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|--|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Update a shadow copy

PATCH /protocols/cifs/shadow-copies/{client_uuid}

Introduced In: 9.11

Specify list Files to be added as a part of Shadowcopy creation

Learn more

- [DOC /protocols/cifs/shadow-copies](#)

Parameters

| Name | Type | In | Required | Description |
|---------|---------|-------|----------|--|
| restore | boolean | query | False | Indicates whether to restore a directory |

Request Body

| Name | Type | Description |
|-----------------|--------------------------------|--|
| _links | _links | |
| client_uuid | string | The universally-unique identifier of the client's shadow copy. |
| destination_dir | string | The path of the destination directory. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the volume. |
| files | array[string] | The list of files to shadow copy in the share. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the share. |
| shadowcopy_set | shadowcopy_set | |
| share | share | |
| source_dir | string | The path of the source directory. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the volume. |
| svm | svm | SVM, applies only to SVM-scoped objects. |
| uuid | string | The universally-unique identifier of the storage's shadow copy. |

| Name | Type | Description |
|--------------|-------------|--|
| volume | volume | The name of the volume where the source and destination directories reside. |
| with_content | boolean | Specifies what needs to be restored. False specifies the directory only. True indicates the directory and its content. |

Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "client_uuid": "abc13450-1f19-40ba-9b82-ebf277517e7e",
  "destination_dir": "/dir2",
  "files": [
    "/vhd1",
    "/vhd2"
  ],
  "shadowcopy_set": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "uuid": "5f4e19f3-5e2d-11ec-8766-005056a7c134"
},
"share": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "sh1"
},
"source_dir": "/dir1",
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"uuid": "fef32805-1f19-40ba-9b82-ebf277517e7e",
"volume": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  }
}
```



```
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}
```

Response

Status: 200, Ok

| Name | Type | Description |
|-----------------------------|--------|---|
| storage_shadowcopy_set_uuid | string | The universally-unique identifier of the storage's shadow copy set. |
| storage_shadowcopy_uuid | string | The universally-unique identifier of the storage's shadow copy. |

Example response

```
{
  "storage_shadowcopy_set_uuid": "f8328660-00e6-11e6-80d9-005056bd65a9",
  "storage_shadowcopy_uuid": "fef32805-1f19-40ba-9b82-ebf277517e7e"
}
```

Error

Status: Default, Error

| Name | Type | Description |
|-------|--------------------------------|-------------|
| error | returned_error | |

Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

self_link

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

shadowcopy_set

| Name | Type | Description |
|--------|---------------------------|-------------|
| _links | self_link | |
| uuid | string | |

share

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | Share name |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

The name of the volume where the source and destination directories reside.

| Name | Type | Description |
|------------------------|------------------------|---|
| _links | _links | |
| name | string | The name of the volume. This field cannot be specified in a POST or PATCH method. |
| uuid | string | Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none">• example: 028baa66-41bd-11e9-81d5-00a0986138f7• Introduced in: 9.6• x-nullable: true |

shadowcopy

| Name | Type | Description |
|------------------------|--------------------------------|--|
| _links | _links | |
| client_uuid | string | The universally-unique identifier of the client's shadow copy. |
| destination_dir | string | The path of the destination directory. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the volume. |
| files | array[string] | The list of files to shadow copy in the share. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the share. |
| shadowcopy_set | shadowcopy_set | |
| share | share | |
| source_dir | string | The path of the source directory. The path is in UTF8 and uses forward slash as a directory separator. The path is relative to the root of the volume. |

| Name | Type | Description |
|--------------|------------------------|--|
| svm | svm | SVM, applies only to SVM-scoped objects. |
| uuid | string | The universally-unique identifier of the storage's shadow copy. |
| volume | volume | The name of the volume where the source and destination directories reside. |
| with_content | boolean | Specifies what needs to be restored. False specifies the directory only. True indicates the directory and its content. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|--|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Retrieve shadow copy sets

GET /protocols/cifs/shadowcopy-sets

Introduced In: 9.11

Retrieves Shadowcopy Sets.

Related ONTAP commands

- `vserver cifs shadowcopy show-sets`

Learn more

- [DOC /protocols/cifs/shadow-copies](#)

Parameters

| Name | Type | In | Required | Description |
|---|----------------|---------------|----------|---|
| svm.uuid | string | query | False | Filter by svm.uuid |
| svm.name | string | query | False | Filter by svm.name |
| uuid | string | query | False | Filter by uuid |
| keep_snapshots | boolean | query | False | Filter by keep_snapshots |
| order_by | array[string] | query | False | Order results by specified fields and optional [asc |
| desc] direction. Default direction is 'asc' for ascending. | fields | array[string] | query | False |
| Specify the fields to return. | max_records | integer | query | False |
| Limit the number of records returned. | return_records | boolean | query | False |
| The default is true for GET calls. When set to false, only the number of records is returned. • Default value: 1 | return_timeout | integer | query | False |

Response

Status: 200, Ok

| Name | Type | Description |
|-------------|---|-------------------|
| _links | _links | |
| num_records | integer | Number of records |
| records | array[shadowcopy_set] | |

Example response

```

{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "num_records": 1,
  "records": {
    "keep_snapshots": "",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "uuid": "f8328660-00e6-11e6-80d9-005056bd65a9"
  }
}

```

Error

Status: Default, Error

| Name | Type | Description |
|-------|--------------------------------|-------------|
| error | returned_error | |

Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| next | href | |
| self | href | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

shadowcopy_set

| Name | Type | Description |
|----------------|---------------------|---|
| keep_snapshots | boolean | Request the storage system to keep the snapshot copies taken as a part of the shadow copy set creation. |
| svm | svm | SVM, applies only to SVM-scoped objects. |
| uuid | string | The universally-unique identifier of the storage's shadow copy set. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|--|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Retrieve a shadow copy set

GET /protocols/cifs/shadowcopy-sets/{uuid}

Introduced In: 9.11

Retrieves a Shadowcopy set

Related ONTAP commands

- `vserver cifs shadowcopy show-sets`

Learn more

- [DOC /protocols/cifs/shadow-copies](#)

Parameters

| Name | Type | In | Required | Description |
|--------|---------------|-------|----------|-------------------------------|
| fields | array[string] | query | False | Specify the fields to return. |

Response

Status: 200, Ok

| Name | Type | Description |
|----------------|---------|---|
| keep_snapshots | boolean | Request the storage system to keep the snapshot copies taken as a part of the shadow copy set creation. |
| svm | svm | SVM, applies only to SVM-scoped objects. |
| uuid | string | The universally-unique identifier of the storage's shadow copy set. |

Example response

```
{
  "keep_snapshots": "",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "uuid": "f8328660-00e6-11e6-80d9-005056bd65a9"
}
```

Error

Status: Default, Error

| Name | Type | Description |
|-------|----------------|-------------|
| error | returned_error | |

Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|--|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Update a shadow copy set

PATCH /protocols/cifs/shadowcopy-sets/{uuid}

Introduced In: 9.11

Updates a Shadowcopy set

Learn more

- [DOC /protocols/cifs/shadowcopy](#)

Request Body

| Name | Type | Description |
|----------------|---------------------|---|
| keep_snapshots | boolean | Request the storage system to keep the snapshot copies taken as a part of the shadow copy set creation. |
| svm | svm | SVM, applies only to SVM-scoped objects. |
| uuid | string | The universally-unique identifier of the storage's shadow copy set. |

Example request

```
{
  "keep_snapshots": "",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "uuid": "f8328660-00e6-11e6-80d9-005056bd65a9"
}
```

Response

Status: 200, Ok

Error

Status: Default, Error

| Name | Type | Description |
|-------|--------------------------------|-------------|
| error | returned_error | |

Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

shadowcopy_set

| Name | Type | Description |
|----------------|---------------------|---|
| keep_snapshots | boolean | Request the storage system to keep the snapshot copies taken as a part of the shadow copy set creation. |
| svm | svm | SVM, applies only to SVM-scoped objects. |
| uuid | string | The universally-unique identifier of the storage's shadow copy set. |

error_arguments

| Name | Type | Description |
|------|--------|---------------|
| code | string | Argument code |

| Name | Type | Description |
|---------|--------|------------------|
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|--|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.