



Manage application consistency groups

REST API reference

NetApp
September 09, 2025

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-9161/application_consistency-groups_endpoint_overview.html on September 09, 2025. Always check docs.netapp.com for the latest.

Table of Contents

| | |
|---|-----|
| Manage application consistency groups | 1 |
| Application consistency-groups endpoint overview | 1 |
| Overview | 1 |
| Consistency group APIs | 1 |
| Examples | 1 |
| Retrieve details of a collection or consistency group | 23 |
| Notes | 24 |
| Expensive properties | 24 |
| Parameters | 24 |
| Response | 69 |
| Error | 85 |
| Definitions | 86 |
| Create a consistency group | 142 |
| Required properties | 143 |
| Naming Conventions | 143 |
| Consistency groups | 143 |
| Volume | 143 |
| LUN | 143 |
| NVMe Namespace | 143 |
| Related ONTAP commands | 143 |
| Parameters | 143 |
| Request Body | 144 |
| Response | 159 |
| Response | 160 |
| Error | 160 |
| Definitions | 161 |
| Delete a consistency group | 230 |
| Related ONTAP commands | 230 |
| Parameters | 230 |
| Response | 231 |
| Response | 231 |
| Error | 231 |
| Definitions | 232 |
| Retrieve a consistency group | 233 |
| Expensive properties | 233 |
| Related ONTAP commands | 233 |
| Parameters | 234 |
| Response | 278 |
| Error | 297 |
| Definitions | 298 |
| Update a consistency group | 346 |
| Related ONTAP commands | 346 |
| Parameters | 346 |

| | |
|--------------------|-----|
| Request Body | 347 |
| Response | 359 |
| Response | 359 |
| Error | 360 |
| Definitions | 361 |

Manage application consistency groups

Application consistency-groups endpoint overview

Overview

A consistency group is a group of volumes that supports capabilities such as creating a snapshot of all of its member volumes at the same point-in-time with a write-fence, thus ensuring a consistent image of the volumes at that time.

Applications with datasets scoped to a single volume can have its contents saved to a snapshot, replicated, or cloned in a crash-consistent manner implicitly with corresponding native ONTAP volume-granular operations. Applications with datasets spanning a group of multiple volumes must have such operations performed on the group. Typically, by first fencing writes to all the volumes in the group, flushing any writes pending in queues, executing the intended operation, that is, take snapshot of every volume in the group and when that is complete, unfence and resume writes. A consistency group is the conventional mechanism for providing such group semantics.

Consistency group APIs

The following APIs are used to perform operations related to consistency groups:

– GET /api/application/consistency-groups

– POST /api/application/consistency-groups

– GET /api/application/consistency-groups/{uuid}

– PATCH /api/application/consistency-groups/{uuid}

– DELETE /api/application/consistency-groups/{uuid}

Examples

Retrieving all consistency groups of an SVM

```
# The API:  
/api/application/consistency-groups  
  
# The call:  
curl -X GET "https://<mgmt-ip>/api/application/consistency-  
groups?svm.name=vs1" -H "accept: application/hal+json"  
  
# The response:  
{  
  "records": [  
    {  
      "uuid": "6f48d798-0a7f-11ec-a449-005056bbcf9f",  
      "name": "vol1",  
      "svm": {  
        "name": "vs1",  
        "svm_type": "filestore"  
      }  
    }  
  ]  
}
```

```

    "_links": {
        "self": {
            "href": "/api/application/consistency-groups/6f48d798-0a7f-11ec-
a449-005056bbcf9f"
        }
    }
},
{
    "uuid": "c1b22c85-0a82-11ec-a449-005056bbcf9f",
    "name": "parent_cg",
    "_links": {
        "self": {
            "href": "/api/application/consistency-groups/c1b22c85-0a82-11ec-
a449-005056bbcf9f"
        }
    }
},
{
    "uuid": "c1b270b1-0a82-11ec-a449-005056bbcf9f",
    "name": "child_1",
    "_links": {
        "self": {
            "href": "/api/application/consistency-groups/c1b270b1-0a82-11ec-
a449-005056bbcf9f"
        }
    }
},
{
    "uuid": "c1b270c3-0a82-11ec-a449-005056bbcf9f",
    "name": "child_2",
    "_links": {
        "self": {
            "href": "/api/application/consistency-groups/c1b270c3-0a82-11ec-
a449-005056bbcf9f"
        }
    }
},
],
"num_records": 4,
"_links": {
    "self": {
        "href": "/api/application/consistency-groups"
    }
}
}

```

Retrieving details of all consistency groups of an SVM

Retrieving details of the consistency groups for a specified SVM. These details are considered to be performant and will return within 1 second when 40 records or less are requested.

```
curl -X GET "https://<mgmt-ip>/api/application/consistency-groups?svm.name=vs1&fields=&max_records=40"

#### Response:
{
"records": [
{
"uuid": "6f48d798-0a7f-11ec-a449-005056bbcf9f",
"name": "vol1",
"svm": {
"uuid": "4853f97a-0a63-11ec-a449-005056bbcf9f",
"name": "vs1",
"_links": {
"self": {
"href": "/api/svm/svms/4853f97a-0a63-11ec-a449-005056bbcf9f"
}
}
},
"space": {
"size": 108003328,
"available": 107704320,
"used": 299008
},
"replicated": false,
"_links": {
"self": {
"href": "/api/application/consistency-groups/6f48d798-0a7f-11ec-a449-005056bbcf9f"
}
}
},
{
"uuid": "c1b22c85-0a82-11ec-a449-005056bbcf9f",
"name": "parent_cg",
"svm": {
"uuid": "4853f97a-0a63-11ec-a449-005056bbcf9f",
"name": "vs1",
"_links": {
"self": {
"href": "/api/svm/svms/4853f97a-0a63-11ec-a449-005056bbcf9f"
}
}
}
}
]
```

```

} ,
"snapshot_policy": {
  "name": "default-1weekly",
  "uuid": "a30bd0fe-067d-11ec-a449-005056bbcf9f",
  "_links": {
    "self": {
      "href": "/api/storage/snapshot-policies/a30bd0fe-067d-11ec-a449-005056bbcf9f"
    }
  }
},
"consistency_groups": [
{
  "uuid": "c1b270b1-0a82-11ec-a449-005056bbcf9f",
  "name": "child_1",
  "space": {
    "size": 41943040,
    "available": 39346176,
    "used": 499712
  },
  "_links": {
    "self": {
      "href": "/api/application/consistency-groups/c1b270b1-0a82-11ec-a449-005056bbcf9f"
    }
  }
},
{
  "uuid": "c1b270c3-0a82-11ec-a449-005056bbcf9f",
  "name": "child_2",
  "space": {
    "size": 41943040,
    "available": 39350272,
    "used": 495616
  },
  "_links": {
    "self": {
      "href": "/api/application/consistency-groups/c1b270c3-0a82-11ec-a449-005056bbcf9f"
    }
  }
},
],
"space": {
  "size": 83886080,
  "available": 78696448,

```

```

    "used": 995328
  },
  "replicated": false,
  "_links": {
    "self": {
      "href": "/api/application/consistency-groups/c1b22c85-0a82-11ec-a449-005056bbcf9f"
    }
  }
},
{
  "uuid": "c1b270b1-0a82-11ec-a449-005056bbcf9f",
  "name": "child_1",
  "parent_consistency_group": {
    "uuid": "c1b22c85-0a82-11ec-a449-005056bbcf9f",
    "name": "parent_cg",
    "_links": {
      "self": {
        "href": "/api/application/consistency-groups/c1b22c85-0a82-11ec-a449-005056bbcf9f"
      }
    }
  },
  "svm": {
    "uuid": "4853f97a-0a63-11ec-a449-005056bbcf9f",
    "name": "vs1",
    "_links": {
      "self": {
        "href": "/api/svm/svms/4853f97a-0a63-11ec-a449-005056bbcf9f"
      }
    }
  },
  "snapshot_policy": {
    "name": "default",
    "uuid": "a30b60a4-067d-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/storage/snapshot-policies/a30b60a4-067d-11ec-a449-005056bbcf9f"
      }
    }
  },
  "space": {
    "size": 41943040,
    "available": 39346176,
    "used": 499712
  }
}

```

```

} ,
"_links": {
  "self": {
    "href": "/api/application/consistency-groups/c1b270b1-0a82-11ec-
a449-005056bbcf9f"
  }
}
},
{
  "uuid": "c1b270c3-0a82-11ec-a449-005056bbcf9f",
  "name": "child_2",
  "parent_consistency_group": {
    "uuid": "c1b22c85-0a82-11ec-a449-005056bbcf9f",
    "name": "parent_cg",
    "_links": {
      "self": {
        "href": "/api/application/consistency-groups/c1b22c85-0a82-11ec-
a449-005056bbcf9f"
      }
    }
  },
  "svm": {
    "uuid": "4853f97a-0a63-11ec-a449-005056bbcf9f",
    "name": "vs1",
    "_links": {
      "self": {
        "href": "/api/svm/svms/4853f97a-0a63-11ec-a449-005056bbcf9f"
      }
    }
  },
  "snapshot_policy": {
    "name": "default",
    "uuid": "a30b60a4-067d-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/storage/snapshot-policies/a30b60a4-067d-11ec-a449-
005056bbcf9f"
      }
    }
  },
  "space": {
    "size": 41943040,
    "available": 39350272,
    "used": 495616
  },
  "_links": {

```

```
        "self": {
            "href": "/api/application/consistency-groups/c1b270c3-0a82-11ec-
a449-005056bbcf9f"
        }
    }
}
],
"num_records": 4,
"_links": {
    "self": {
        "href": "/api/application/consistency-
groups?svm.name=vs1&fields=*&max_records=40"
    }
}
}
```

Retrieving details of non-nested consistency groups

Retrieves details of the consistency groups without nested consistency groups, or only the parent consistency group for a number of consistency groups of a specified SVM.

```

curl -X GET "https://<mgmt-ip>/api/application/consistency-
groups?svm.name=vs1&parent_consistency_group.uuid=null"

#### Response:
{
"records": [
{
"uuid": "6f48d798-0a7f-11ec-a449-005056bbcf9f",
"name": "vol1",
"svm": {
"name": "vs1"
},
"_links": {
"self": {
"href": "/api/application/consistency-groups/6f48d798-0a7f-11ec-
a449-005056bbcf9f"
}
}
},
{
"uuid": "c1b22c85-0a82-11ec-a449-005056bbcf9f",
"name": "parent_cg",
"svm": {
"name": "vs1"
},
"_links": {
"self": {
"href": "/api/application/consistency-groups/c1b22c85-0a82-11ec-
a449-005056bbcf9f"
}
}
}
],
"num_records": 2,
"_links": {
"self": {
"href": "/api/application/consistency-
groups?svm.name=vs1&parent_consistency_group.uuid=null"
}
}
}

```

Creating a single consistency group with a new SAN volume

Provisions an application with one consistency group, each with one new SAN volumes, with one LUN, an

igroup and no explicit snapshot policy, FabricPool tiering policy, storage service, and QoS policy specification. The igroup to map a LUN to is specified at LUN-granularity.

```
curl -X POST https://<mgmt-ip>/api/application/consistency-groups?return_records=true -d '{ "svm": { "name": "vs1" }, "luns": [ { "name": "/vol/voll/lun1", "space": { "size": "100mb" }, "os_type": "linux", "lun_maps": [ { "igroup": { "name": "igroup1", "initiators": [ { "name": "example_name" } ] } } ] } }'
```

Response:

```
{  
  "num_records": 1,  
  "records": [  
    {  
      "uuid": "6f48d798-0a7f-11ec-a449-005056bbcf9f",  
      "name": "voll",  
      "svm": {  
        "uuid": "4853f97a-0a63-11ec-a449-005056bbcf9f",  
        "name": "vs1",  
        "_links": {  
          "self": {  
            "href": "/api/svm/svms/4853f97a-0a63-11ec-a449-005056bbcf9f"  
          }  
        }  
      },  
      "luns": [  
        {  
          "lun_maps": [  
            {  
              "igroup": {  
                "name": "igroup1",  
                "initiators": [  
                  {  
                    "name": "example_name"  
                  }  
                ]  
              }  
            }  
          ]  
        },  
        {  
          "name": "/vol/voll/lun1",  
          "os_type": "linux",  
          "space": {  
            "size": 104857600  
          }  
        }  
      ]  
    }  
  ]  
}
```

```

    }
  ],
  "job": {
    "uuid": "6f4907ae-0a7f-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/cluster/jobs/6f4907ae-0a7f-11ec-a449-005056bbcf9f"
      }
    }
  }
}

```

Creating an Application with two consistency groups with existing SAN volumes

Provisions an application with two consistency groups, each with two existing SAN volumes, a snapshot policy at application-granularity, and a distinct consistency group granular snapshot policy.

```

curl -X POST https://<mgmt-ip>/api/application/consistency-
groups?return_records=true -d '{
  "svm": { "name": "vs1" }, "name": "parent_cg",
  "snapshot_policy": { "name": "default-1weekly" },
  "consistency_groups": [ { "name": "child_1", "snapshot_policy": { "name": "default" },
    "volumes": [ { "name": "existing_vol1",
      "provisioning_options": { "action": "add" } }, { "name": "existing_vol2",
      "provisioning_options": { "action": "add" } } ] }, { "name": "child_2",
    "snapshot_policy": { "name": "default" }, "volumes": [ { "name": "existing_vol3",
      "provisioning_options": { "action": "add" } }, { "name": "existing_vol4",
      "provisioning_options": { "action": "add" } } ] } ] }'

#### Response:
{
  "num_records": 1,
  "records": [
    {
      "uuid": "c1b22c85-0a82-11ec-a449-005056bbcf9f",
      "name": "parent_cg",
      "svm": {
        "uuid": "4853f97a-0a63-11ec-a449-005056bbcf9f",
        "name": "vs1",
        "_links": {
          "self": {
            "href": "/api/svm/svms/4853f97a-0a63-11ec-a449-005056bbcf9f"
          }
        }
      },
      "snapshot_policy": {
        "name": "default-1weekly"
      }
    }
  ]
}

```

```

} ,
"consistency_groups": [
{
  "uuid": "c1b270b1-0a82-11ec-a449-005056bbcf9f",
  "name": "child_1",
  "snapshot_policy": {
    "name": "default"
  },
  "volumes": [
    {
      "name": "existing_vol1"
    },
    {
      "name": "existing_vol2"
    }
  ]
},
{
  "uuid": "c1b270c3-0a82-11ec-a449-005056bbcf9f",
  "name": "child_2",
  "snapshot_policy": {
    "name": "default"
  },
  "volumes": [
    {
      "name": "existing_vol3"
    },
    {
      "name": "existing_vol4"
    }
  ]
}
]
},
"job": {
  "uuid": "c1b272b9-0a82-11ec-a449-005056bbcf9f",
  "_links": {
    "self": {
      "href": "/api/cluster/jobs/c1b272b9-0a82-11ec-a449-005056bbcf9f"
    }
  }
}
}

```

Retrieving specific details of an existing consistency group

Retrieves the details of an existing consistency group.

```
curl -X GET https://<mgmt-ip>/api/application/consistency-groups/6f48d798-0a7f-11ec-a449-005056bbcf9f

#### Response:
{
  "uuid": "6f48d798-0a7f-11ec-a449-005056bbcf9f",
  "name": "vol1",
  "svm": {
    "uuid": "4853f97a-0a63-11ec-a449-005056bbcf9f",
    "name": "vs1",
    "_links": {
      "self": {
        "href": "/api/svm/svms/4853f97a-0a63-11ec-a449-005056bbcf9f"
      }
    }
  },
  "space": {
    "size": 108003328,
    "available": 107724800,
    "used": 278528
  },
  "replicated": false,
  "_links": {
    "self": {
      "href": "/api/application/consistency-groups/6f48d798-0a7f-11ec-a449-005056bbcf9f"
    }
  }
}
```

Retrieving all details of an existing consistency group

Retrieves all details of an existing consistency group. These details are not considered to be performant and are not guaranteed to return within one second.

```
curl -X GET https://<mgmt-ip>/api/application/consistency-groups/6f48d798-0a7f-11ec-a449-005056bbcf9f?fields=**

#### Response:
{
  "uuid": "6f48d798-0a7f-11ec-a449-005056bbcf9f",
  "name": "vol1",
```

```

"svm": {
  "uuid": "4853f97a-0a63-11ec-a449-005056bbcf9f",
  "name": "vs1",
  "_links": {
    "self": {
      "href": "/api/svm/svms/4853f97a-0a63-11ec-a449-005056bbcf9f"
    }
  }
},
"qos": {
  "policy": {
    "uuid": "b7189398-e572-48ab-8f69-82cd46580812",
    "name": "extreme-fixed",
    "_links": {
      "self": {
        "href": "/api/storage/qos/policies/b7189398-e572-48ab-8f69-82cd46580812"
      }
    }
  }
},
"tiering": {
  "policy": "none"
},
"create_time": "2021-08-31T13:18:24-04:00",
"volumes": [
  {
    "uuid": "6f516c6c-0a7f-11ec-a449-005056bbcf9f",
    "qos": {
      "policy": {
        "uuid": "b7189398-e572-48ab-8f69-82cd46580812",
        "name": "extreme-fixed",
        "_links": {
          "self": {
            "href": "/api/storage/qos/policies/b7189398-e572-48ab-8f69-82cd46580812"
          }
        }
      }
    }
  },
  "tiering": {
    "policy": "none"
  },
  "comment": "",
  "create_time": "2021-08-31T13:18:22-04:00",
  "name": "vol1",

```

```

"snapshot_policy": {
    "name": "default",
    "uuid": "a30b60a4-067d-11ec-a449-005056bbcf9f"
},
"space": {
    "size": 108003328,
    "available": 107569152,
    "used": 434176,
    "snapshot": {
        "used": 151552,
        "reserve_percent": 0,
        "autodelete_enabled": false
    }
},
"_links": {
    "self": {
        "href": "/api/storage/volumes/6f516c6c-0a7f-11ec-a449-005056bbcf9f"
    }
}
},
"luns": [
{
    "uuid": "6f51748a-0a7f-11ec-a449-005056bbcf9f",
    "location": {
        "logical_unit": "lun1",
        "node": {
            "name": "example_node_name",
            "uuid": "6eb682f2-067d-11ec-a449-005056bbcf9f",
            "_links": {
                "self": {
                    "href": "/api/cluster/nodes/6eb682f2-067d-11ec-a449-005056bbcf9f"
                }
            }
        }
    },
    "volume": {
        "uuid": "6f516c6c-0a7f-11ec-a449-005056bbcf9f",
        "name": "vol1",
        "_links": {
            "self": {
                "href": "/api/storage/volumes/6f516c6c-0a7f-11ec-a449-005056bbcf9f"
            }
        }
    }
}
]

```

```

        }
    },
    "lun_maps": [
        {
            "igroup": {
                "uuid": "6f4a4b86-0a7f-11ec-a449-005056bbcf9f",
                "name": "igroup1",
                "os_type": "linux",
                "protocol": "mixed",
                "initiators": [
                    {
                        "name": "example_name"
                    }
                ],
                "_links": {
                    "self": {
                        "href": "/api/protocols/san/igroups/6f4a4b86-0a7f-11ec-a449-005056bbcf9f"
                    }
                }
            },
            "logical_unit_number": 0
        }
    ],
    "name": "/vol/vol1/lun1",
    "auto_delete": false,
    "class": "regular",
    "create_time": "2021-08-31T13:18:24-04:00",
    "os_type": "linux",
    "serial_number": "wIqM6]RfQK3t",
    "space": {
        "size": 104857600,
        "used": 0,
        "guarantee": {
            "requested": false,
            "reserved": false
        }
    },
    "status": {
        "container_state": "online",
        "mapped": true,
        "read_only": false,
        "state": "online"
    },
    "_links": {
        "self": {

```

```

        "href": "/api/storage/luns/6f51748a-0a7f-11ec-a449-005056bbcf9f"
    }
}
]
,
"space": {
    "size": 108003328,
    "available": 107569152,
    "used": 434176
},
"replicated": false,
"_links": {
    "self": {
        "href": "/api/application/consistency-groups/6f48d798-0a7f-11ec-a449-005056bbcf9f?fields=**"
    }
}
}

```

Adding LUNs to an existing volume in an existing consistency group

Adds two NVMe namespaces to an existing volume in an existing consistency group, creates a new subsystem, and binds the new namespaces to it.

```

curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-
groups/6f48d798-0a7f-11ec-a449-005056bbcf9f' -d '{ "luns": [ { "name": 
"/vol/vol1/new_luns", "provisioning_options": { "count": 2, "action": 
"create" }, "space": { "size": "100mb" }, "os_type": "linux", "lun_maps": 
[ { "igroup": { "name": "igroup2", "initiators": [ { "name": 
"01:02:03:04:05:06:07:01" } ] } ] } ] }'

#### Response:
{
"job": {
    "uuid": "5306ea44-0a87-11ec-a449-005056bbcf9f",
    "_links": {
        "self": {
            "href": "/api/cluster/jobs/5306ea44-0a87-11ec-a449-005056bbcf9f"
        }
    }
}
}

```

Restoring a consistency group to the contents of an existing snapshot

Restores an existing consistency group to the contents of an existing snapshot of the consistency group.

```
curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-
groups/6f51748a-0a7f-11ec-a449-005056bbcf9f' -d '{ "restore_to": {
"snapshot": { "uuid": "92c6c770-17a1-11eb-b141-005056acd498" } } }' -H
"Accept: Application/hal+json"

#### Response:
{
"job": {
"uuid": "8907bd9e-1463-11eb-a719-005056ac70af",
"_links": {
"self": {
"href": "/api/cluster/jobs/8907bd9e-1463-11eb-a719-005056ac70af"
}
}
}
}
```

Deleting a consistency group

Deletes a consistency group, where all storage originally associated with that consistency group remains in place.

```
curl -X DELETE 'https://<mgmt-ip>/api/application/consistency-
groups/6f48d798-0a7f-11ec-a449-005056bbcf9f'

#### Response:
{}
```

Cloning an existing consistency group

The following example clones an existing consistency group with the current contents:

```

curl -X POST 'https://<mgmt-ip>/api/application/consistency-groups' -d '{
  "name": "clone01_of_cg01", "svm": { "name": "vs_0"}, "clone": { "volume": {
    "prefix": "my_clone_pfx", "suffix": "my_clone_sfx"}, "split_initiated": true, "parent_consistency_group": { "name": "cg01", "uuid": "ca5e76fb-98c0-11ec-855a-005056a7693b"}, "guarantee": { "type": "none"} } }' -H "accept: application/hal+json"

#### Response:
{
  "job": {
    "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
      }
    }
  }
}

```

Cloning a consistency group from an existing snapshot

The following example clones an existing consistency group with contents from an existing snapshot:

```

curl -X POST 'https://<mgmt-ip>/api/application/consistency-groups' -d '{
  "name": "clone01_of_cg01", "svm": { "name": "vs_0"}, "clone": { "volume": {
    "prefix": "my_clone_pfx", "suffix": "my_clone_sfx"}, "split_initiated": true, "parent_snapshot": { "name": "snap01_of_cg01"}, "parent_consistency_group": { "name": "cg01", "uuid": "ca5e76fb-98c0-11ec-855a-005056a7693b"}, "guarantee": { "type": "none"} } }' -H "accept: application/hal+json"

#### Response:
{
  "job": {
    "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
      }
    }
  }
}

```

Adding namespaces to an existing volume in an existing consistency group

To add two NVMe Namespaces to an existing volume in an existing consistency group, create a new subsystem and bind the new namespaces to it.

```
curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-groups/6f51748a-0a7f-11ec-a449-005056bbcf9f' -d '{ "namespaces": [ { "name": "/vol/voll/new_namespace", "space": { "size": "10M" }, "os_type": "windows", "provisioning_options": { "count": 2 }, "subsystem_map": { "subsystem": { "name": "mySubsystem", "hosts": [ { "nqn": "nqn.1992-08.com.netapp:sn.d04594ef915b4c73b642169e72e4c0b1:subsystem.host1" }, { "nqn": "nqn.1992-08.com.netapp:sn.d04594ef915b4c73b642169e72e4c0b1:subsystem.host2" } ] } } } ] }'

#### Response:
{
  "job": {
    "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
      }
    }
  }
}
```

Add a new volume in an existing consistency group

The following example adds two new volumes to an existing consistency group.

```

curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-
groups/6f51748a-0a7f-11ec-a449-005056bbcf9f' -d '{ "volumes" : [ { "name": 
"new_vol_", "provisioning_options": { "count" : "2"}, "space": { "size": 
"1gb"} } ] }'

#### Response:
{
"job": {
  "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
  "_links": {
    "self": {
      "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
    }
  }
}
}

```

Adding an existing volume to an existing consistency group

The following example adds an existing volume to an existing consistency group.

```

curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-
groups/6f51748a-0a7f-11ec-a449-005056bbcf9f' -d '{ "volumes" : [ { "name": 
"existing_vol", "provisioning_options": { "action" : "add"} } ] }'

#### Response:
{
"job": {
  "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
  "_links": {
    "self": {
      "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
    }
  }
}
}

```

Promoting a single consistency group to a nested consistency group

The following example promotes a single consistency group to a nested consistency group with a new child consistency group.

```

curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-
groups/6f51748a-0a7f-11ec-a449-005056bbcf9f' -d '{ "provisioning_options": 
{ "action":"promote" }, "consistency_groups": [ { "name":"cg_child", 
"provisioning_options": { "action":"create" } } ] }'

#### Response:
{
"job": {
  "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
  "_links": {
    "self": {
      "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
    }
  }
}
}

```

Demoting a nested consistency group to a single consistency group

The following example demotes (flattens) a nested consistency group to a single consistency group.

```

curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-
groups/6f51748a-0a7f-11ec-a449-005056bbcf9f' -d '{ "provisioning_options": 
{ "action":"demote" } }'

#### Response:
{
"job": {
  "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
  "_links": {
    "self": {
      "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
    }
  }
}
}

```

Adding a new child consistency group to nested consistency group

The following example adds a new child consistency group to an existing nested consistency group, creating a new volume.

```

curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-
groups/6f51748a-0a7f-11ec-a449-005056bbcf9f' -d '{
  "consistency_groups": [
    {
      "name": "cg_child5",
      "provisioning_options": {
        "action": "create"
      },
      "volumes": [
        {
          "name": "child5_vol_1",
          "space": {
            "size": "100mb"
          }
        }
      ]
    }
  ]
}'

#### Response:
{
  "job": {
    "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
      }
    }
  }
}

```

Removing a child consistency group from nested consistency group

The following example removes a child consistency group from a nested consistency, changing it to a single consistency group with a new consistency group name.

```

curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-
groups/6f51748a-0a7f-11ec-a449-005056bbcf9f' -d '{
  "consistency_groups": [
    {
      "name": "cg_child5",
      "provisioning_options": {
        "action": "remove"
      },
      "name": "new_single_cg"
    }
  ]
}'

#### Response:
{
  "job": {
    "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
      }
    }
  }
}

```

Create a new parent consistency group with an existing consistency group

The following example creates a new nested consistency group with an existing consistency group as child consistency group.

```

curl -X POST 'https://<mgmt-ip>/api/application/consistency-groups' -d '{
  "svm": { "name": "vs1" }, "name": "cg_parent2", "consistency_groups": [ {
    "name": "cg_large", "provisioning_options":{ "action": "add" } }, {
    "name": "cg_standalone2", "provisioning_options":{ "action": "add" } } ]
}'

#### Response:
{
  "job": {
    "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
      }
    }
  }
}

```

Reassign a volume to another child consistency group.

The following example reassigns a volume from a child consistency group to another child consistency group with the same parent consistency group.

```

curl -X PATCH 'https://<mgmt-ip>/api/application/consistency-
groups/6f51748a-0a7f-11ec-a449-005056bbcf9f' -d '{ "consistency_groups": [
  { "name": "cg_child1", "volumes": [ { "name": "child2_vol_1",
    "provisioning_options": { "action": "reassign" } } ] }, { "name": "cg_child2" } ] }'

#### Response:
{
  "job": {
    "uuid": "8c9cabf3-0a88-11ec-a449-005056bbcf9f",
    "_links": {
      "self": {
        "href": "/api/cluster/jobs/8c9cabf3-0a88-11ec-a449-005056bbcf9f"
      }
    }
  }
}

```

Retrieve details of a collection or consistency group

GET /application/consistency-groups

Introduced In: 9.10

Retrieve details of a collection or a specific consistency group.

Notes

When volume granular properties, such as, the storage SLC, Fabric Pool tiering are not the same for all the existing volumes of a consistency group, the corresponding property is not reported at consistency group granularity. It is only reported if all the volumes of the consistency group have the same value for that property.

If this consistency group instance has 1 or more replication relationships, the "replicated" parameter is true. If there are no associated replication relationships, it is false. This parameter is only included in the output for Single-CG and Parent-CG, not for Child-CG. If this consistency group instance has 1 or more replication relationships, the "replication_relationships" parameter is included in the output for Single-CG and Parent-CG instances. If there are no associated replication relationships, this parameter is not included in the output. Note that this parameter is an array and as such it has as many elements as the number of replication relationships associated with this consistency group. Each element of the array describes properties of one replication relationship associated with this consistency group. The "uuid" parameter identifies a specific replication relationship and the "href" parameter is a link to the corresponding SnapMirror relationship. The "is_source" parameter is true if this consistency group is the source in that relationship, otherwise it is false.

Expensive properties

There is an added computational cost to retrieving values for these properties. They are not included by default in GET results and must be explicitly requested using the `fields` query parameter. See [DOC Requesting specific fields](#) to learn more.

- volumes
- luns
- namespaces

Parameters

| Name | Type | In | Required | Description |
|-----------------------------|---------|-------|----------|---|
| namespaces.uuid | string | query | False | Filter by namespaces.uuid <ul style="list-style-type: none">• Introduced in: 9.12 |
| namespaces.status.read_only | boolean | query | False | Filter by namespaces.status.read_only <ul style="list-style-type: none">• Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| namespaces.status.mapped | boolean | query | False | Filter by namespaces.status.mapped <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.status.container_state | string | query | False | Filter by namespaces.status.container_state <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.status.state | string | query | False | Filter by namespaces.status.state <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.auto_delete | boolean | query | False | Filter by namespaces.auto_delete <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.subsystem_map.nsid | string | query | False | Filter by namespaces.subsystem_map.nsid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.subsystem_map.subsystem.name | string | query | False | Filter by namespaces.subsystem_map.subsystem.name <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 64 • minLength: 1 |

| Name | Type | In | Required | Description |
|---|--------|-------|----------|--|
| namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.group_size | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.group_size</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |
| namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.mode | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.mode</p> <ul style="list-style-type: none"> • Introduced in: 9.16 |
| namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.hash_function | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.hash_function</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |
| namespaces.subsystem_map.subsystem.hosts.nqn | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.hosts.nqn</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.subsystem_map.subsystem.hosts.priority | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.hosts.priority</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |
| namespaces.subsystem_map.subsystem.hosts.tls.key_type | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.hosts.tls.key_type</p> <ul style="list-style-type: none"> • Introduced in: 9.16 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| namespaces.subsystem_map.subsystem.uuid | string | query | False | Filter by namespaces.subsystem_map.subsystem.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.subsystem_map.subsystem.os_type | string | query | False | Filter by namespaces.subsystem_map.subsystem.os_type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.subsystem_map.subsystem.comment | string | query | False | Filter by namespaces.subsystem_map.subsystem.comment <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 255 • minLength: 0 |
| namespaces.subsystem_map.anagrpid | string | query | False | Filter by namespaces.subsystem_map.anagrpid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.os_type | string | query | False | Filter by namespaces.os_type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.space.block_size | integer | query | False | Filter by namespaces.space.block_size <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--------------------------------------|---------|-------|----------|---|
| namespaces.space.guarantee.requested | boolean | query | False | <p>Filter by namespaces.space.guarantee.requested</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.space.guarantee.reserved | boolean | query | False | <p>Filter by namespaces.space.guarantee.reserved</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.space.size | integer | query | False | <p>Filter by namespaces.space.size</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • Max value: 140737488355328 • Min value: 4096 |
| namespaces.space.used | integer | query | False | <p>Filter by namespaces.space.used</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.create_time | string | query | False | <p>Filter by namespaces.create_time</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.enabled | boolean | query | False | <p>Filter by namespaces.enabled</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|------------------------------|---------|-------|----------|--|
| namespaces.comment | string | query | False | Filter by namespaces.comment <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 254 • minLength: 0 |
| namespaces.name | string | query | False | Filter by namespaces.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| statistics.timestamp | string | query | False | Filter by statistics.timestamp <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.latency_raw.write | integer | query | False | Filter by statistics.latency_raw.write <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.latency_raw.total | integer | query | False | Filter by statistics.latency_raw.total <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.latency_raw.read | integer | query | False | Filter by statistics.latency_raw.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.latency_raw.other | integer | query | False | Filter by statistics.latency_raw.other <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|----------------------------|---------|-------|----------|--|
| statistics.status | string | query | False | Filter by statistics.status <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.iops_raw.write | integer | query | False | Filter by statistics.iops_raw.write <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.iops_raw.to tal | integer | query | False | Filter by statistics.iops_raw.to tal <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.iops_raw.read | integer | query | False | Filter by statistics.iops_raw.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.iops_raw.other | integer | query | False | Filter by statistics.iops_raw.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.size | integer | query | False | Filter by statistics.size <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.used_space | integer | query | False | Filter by statistics.used_space <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|---------------------------------|---------|-------|----------|---|
| statistics.throughput_raw.write | integer | query | False | Filter by statistics.throughput_raw.write <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.throughput_raw.total | integer | query | False | Filter by statistics.throughput_raw.total <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.throughput_raw.read | integer | query | False | Filter by statistics.throughput_raw.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.throughput_raw.other | integer | query | False | Filter by statistics.throughput_raw.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.available_space | integer | query | False | Filter by statistics.available_space <ul style="list-style-type: none"> • Introduced in: 9.13 |
| tiering.policy | string | query | False | Filter by tiering.policy |
| uuid | string | query | False | Filter by uuid |
| qos.policy.uuid | string | query | False | Filter by qos.policy.uuid |
| qos.policy.name | string | query | False | Filter by qos.policy.name |
| space.available | integer | query | False | Filter by space.available |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| space.size | integer | query | False | Filter by space.size |
| space.used | integer | query | False | Filter by space.used |
| replicated | boolean | query | False | Filter by replicated |
| replication_relations hips.is_source | boolean | query | False | Filter by replication_relations hips.is_source <ul style="list-style-type: none"> • Introduced in: 9.13 |
| replication_relations hips.is_protected_by _svm_dr | boolean | query | False | Filter by replication_relations hips.is_protected_by _svm_dr <ul style="list-style-type: none"> • Introduced in: 9.14 |
| replication_relations hips.uuid | string | query | False | Filter by replication_relations hips.uuid <ul style="list-style-type: none"> • Introduced in: 9.13 |
| _tags | string | query | False | Filter by _tags <ul style="list-style-type: none"> • Introduced in: 9.15 |
| application.component_type | string | query | False | Filter by application.component_type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| application.type | string | query | False | Filter by application.type <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|-------------------------------------|---------|-------|----------|---|
| snapshot_policy.uuid | string | query | False | Filter by snapshot_policy.uuid |
| snapshot_policy.name | string | query | False | Filter by snapshot_policy.name |
| clone.parent_svm.name | string | query | False | Filter by clone.parent_svm.name <ul style="list-style-type: none"> • Introduced in: 9.15 |
| clone.parent_svm.uid | string | query | False | Filter by clone.parent_svm.uid <ul style="list-style-type: none"> • Introduced in: 9.15 |
| clone.split_complete_percent | integer | query | False | Filter by clone.split_complete_percent <ul style="list-style-type: none"> • Introduced in: 9.15 |
| clone.parent_consistency_group.name | string | query | False | Filter by clone.parent_consistency_group.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.parent_consistency_group.uuid | string | query | False | Filter by clone.parent_consistency_group.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.parent_snapshot.uuid | string | query | False | Filter by clone.parent_snapshot.uuid <ul style="list-style-type: none"> • Introduced in: 9.15 |

| Name | Type | In | Required | Description |
|------------------------------|---------|-------|----------|--|
| clone.parent_snapshot.name | string | query | False | Filter by clone.parent_snapshot.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.volume.suffix | string | query | False | Filter by clone.volume.suffix <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.volume.prefix | string | query | False | Filter by clone.volume.prefix <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.split_estimate | integer | query | False | Filter by clone.split_estimate <ul style="list-style-type: none"> • Introduced in: 9.15 |
| clone.is_flexclone | boolean | query | False | Filter by clone.is_flexclone <ul style="list-style-type: none"> • Introduced in: 9.15 |
| clone.guarantee.type | string | query | False | Filter by clone.guarantee.type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.split_initiated | boolean | query | False | Filter by clone.split_initiated <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.snapshot_policy.uuid | string | query | False | Filter by volumes.snapshot_policy.uuid |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| volumes.snapshot_policy.name | string | query | False | Filter by volumes.snapshot_policy.name |
| volumes.tiering.policy | string | query | False | Filter by volumes.tiering.policy |
| volumes.uuid | string | query | False | Filter by volumes.uuid |
| volumes.qos.policy.uuid | string | query | False | Filter by volumes.qos.policy.uuid |
| volumes.qos.policy.name | string | query | False | Filter by volumes.qos.policy.name |
| volumes.space.used | integer | query | False | Filter by volumes.space.used |
| volumes.space.size | integer | query | False | Filter by volumes.space.size |
| volumes.space.available | integer | query | False | Filter by volumes.space.available |
| volumes.nas.export_policy.id | integer | query | False | Filter by volumes.nas.export_policy.id <ul style="list-style-type: none"> • Introduced in: 9.14 |
| volumes.nas.export_policy.rules.superuser | string | query | False | Filter by volumes.nas.export_policy.rules.superuser <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| volumes.nas.export_policy.rules.index | integer | query | False | Filter by volumes.nas.export_policy.rules.index <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.allow_device_creation | boolean | query | False | Filter by volumes.nas.export_policy.rules.allow_device_creation <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.allow_su_id | boolean | query | False | Filter by volumes.nas.export_policy.rules.allow_su_id <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.rw_rule | string | query | False | Filter by volumes.nas.export_policy.rules.rw_rule <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.clients.match | string | query | False | Filter by volumes.nas.export_policy.rules.clients.match <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.chown_mode | string | query | False | Filter by volumes.nas.export_policy.rules.chown_mode <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|--|
| volumes.nas.export_policy.rules.anonymous_user | string | query | False | Filter by volumes.nas.export_policy.rules.anonymous_user <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.ntfs_unix_security | string | query | False | Filter by volumes.nas.export_policy.rules.ntfs_unix_security <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.ro_rule | string | query | False | Filter by volumes.nas.export_policy.rules.ro_rule <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.protocols | string | query | False | Filter by volumes.nas.export_policy.rules.protocols <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.name | string | query | False | Filter by volumes.nas.export_policy.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.junction_parent.name | string | query | False | Filter by volumes.nas.junction_parent.name <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| volumes.nas.junction _parent.uuid | string | query | False | Filter by volumes.nas.junction_parent.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.path | string | query | False | Filter by volumes.nas.path <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.unix_symlink | string | query | False | Filter by volumes.nas.cifs.shares.unix_symlink <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.show_snapshot | boolean | query | False | Filter by volumes.nas.cifs.shares.show_snapshot <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.vscan_profile | string | query | False | Filter by volumes.nas.cifs.shares.vscan_profile <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.comment | string | query | False | Filter by volumes.nas.cifs.shares.comment <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 256 • minLength: 1 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| volumes.nas.cifs.shares.continuously_available | boolean | query | False | <p>Filter by volumes.nas.cifs.shares.continuously_available</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.encryption | boolean | query | False | <p>Filter by volumes.nas.cifs.shares.encryption</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.file_umask | integer | query | False | <p>Filter by volumes.nas.cifs.shares.file_umask</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.home_directory | boolean | query | False | <p>Filter by volumes.nas.cifs.shares.home_directory</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.namespace_caching | boolean | query | False | <p>Filter by volumes.nas.cifs.shares.namespace_caching</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.oplocks | boolean | query | False | <p>Filter by volumes.nas.cifs.shares.oplocks</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| volumes.nas.cifs.sha res.offline_files | string | query | False | Filter by volumes.nas.cifs.shares.offline_files <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.access_based_enumeration | boolean | query | False | Filter by volumes.nas.cifs.shares.access_based_enumeration <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.name | string | query | False | Filter by volumes.nas.cifs.shares.name <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 80 • minLength: 1 |
| volumes.nas.cifs.sha res.acls.user_or_group | string | query | False | Filter by volumes.nas.cifs.shares.acls.user_or_group <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.acls.type | string | query | False | Filter by volumes.nas.cifs.shares.acls.type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.acls.permission | string | query | False | Filter by volumes.nas.cifs.shares.acls.permission <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| volumes.nas.cifs.shares.acls.win_sid_unix_id | string | query | False | Filter by volumes.nas.cifs.shares.acls.win_sid_unix_id <ul style="list-style-type: none"> • Introduced in: 9.16 |
| volumes.nas.cifs.shares.dir_umask | integer | query | False | Filter by volumes.nas.cifs.shares.dir_umask <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.allow_unencrypted_access | boolean | query | False | Filter by volumes.nas.cifs.shares.allow_unencrypted_access <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.change_notify | boolean | query | False | Filter by volumes.nas.cifs.shares.change_notify <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.no_strict_security | boolean | query | False | Filter by volumes.nas.cifs.shares.no_strict_security <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.security_style | string | query | False | Filter by volumes.nas.security_style <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|------------------------------------|---------|-------|----------|---|
| volumes.nas.unix_permissions | integer | query | False | Filter by volumes.nas.unix_permissions <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.uid | integer | query | False | Filter by volumes.nas.uid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.gid | integer | query | False | Filter by volumes.nas.gid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.name | string | query | False | Filter by volumes.name <ul style="list-style-type: none"> • maxLength: 203 • minLength: 1 |
| volumes.comment | string | query | False | Filter by volumes.comment <ul style="list-style-type: none"> • maxLength: 1023 • minLength: 0 |
| consistency_groups.tiering.policy | string | query | False | Filter by consistency_groups.tiering.policy |
| consistency_groups.namespaces.uuid | string | query | False | Filter by consistency_groups.namespaces.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| consistency_groups.namespaces.status.read_only | boolean | query | False | Filter by consistency_groups.namespaces.status.read_only <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.status.mapped | boolean | query | False | Filter by consistency_groups.namespaces.status.mapped <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.status.container_state | string | query | False | Filter by consistency_groups.namespaces.status.container_state <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.status.state | string | query | False | Filter by consistency_groups.namespaces.status.state <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.auto_delete | boolean | query | False | Filter by consistency_groups.namespaces.auto_delete <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.subsystem_map.nsid | string | query | False | Filter by consistency_groups.namespaces.subsystem_map.nsid <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|--------|-------|----------|--|
| consistency_groups.namespaces.subsystem_map.subsystem.name | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.name</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 64 • minLength: 1 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_cha.p.group_size | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_cha.p.group_size</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_cha.p.mode | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_cha.p.mode</p> <ul style="list-style-type: none"> • Introduced in: 9.16 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_cha.p.hash_function | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_cha.p.hash_function</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.nqn | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.nqn</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|--|
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.priority | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.priority</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.tls.key_type | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.tls.key_type</p> <ul style="list-style-type: none"> • Introduced in: 9.16 |
| consistency_groups.namespaces.subsystem_map.subsystem.uuid | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.uuid</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.subsystem_map.subsystem.os_type | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.os_type</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.subsystem_map.subsystem.comment | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.comment</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 255 • minLength: 0 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| consistency_groups.namespaces.subsystem_map.anagrpid | string | query | False | Filter by consistency_groups.namespaces.subsystem_map.anagrpid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.os_type | string | query | False | Filter by consistency_groups.namespaces.os_type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.space.block_size | integer | query | False | Filter by consistency_groups.namespaces.space.block_size <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.space.guarantee.requested | boolean | query | False | Filter by consistency_groups.namespaces.space.guarantee.requested <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.space.guarantee.reserved | boolean | query | False | Filter by consistency_groups.namespaces.space.guarantee.reserved <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| consistency_groups.namespaces.space.size | integer | query | False | <p>Filter by consistency_groups.namespaces.space.size</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • Max value: 140737488355328 • Min value: 4096 |
| consistency_groups.namespaces.space.used | integer | query | False | <p>Filter by consistency_groups.namespaces.space.used</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.create_time | string | query | False | <p>Filter by consistency_groups.namespaces.create_time</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.enabled | boolean | query | False | <p>Filter by consistency_groups.namespaces.enabled</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.comment | string | query | False | <p>Filter by consistency_groups.namespaces.comment</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 254 • minLength: 0 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| consistency_groups.namespaces.name | string | query | False | Filter by consistency_groups.namespaces.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.space.available | integer | query | False | Filter by consistency_groups.space.available |
| consistency_groups.space.size | integer | query | False | Filter by consistency_groups.space.size |
| consistency_groups.space.used | integer | query | False | Filter by consistency_groups.space.used |
| consistency_groups.qos.policy.uuid | string | query | False | Filter by consistency_groups.qos.policy.uuid |
| consistency_groups.qos.policy.name | string | query | False | Filter by consistency_groups.qos.policy.name |
| consistency_groups.uuid | string | query | False | Filter by consistency_groups.uuid |
| consistency_groups.application.type | string | query | False | Filter by consistency_groups.application.type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.application.component_type | string | query | False | Filter by consistency_groups.application.component_type <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| consistency_groups._tags | string | query | False | Filter by consistency_groups._tags <ul style="list-style-type: none"> • Introduced in: 9.15 |
| consistency_groups.volumes.snapshot_policy.uuid | string | query | False | Filter by consistency_groups.volumes.snapshot_policy.uuid |
| consistency_groups.volumes.snapshot_policy.name | string | query | False | Filter by consistency_groups.volumes.snapshot_policy.name |
| consistency_groups.volumes.tiering.policy | string | query | False | Filter by consistency_groups.volumes.tiering.policy |
| consistency_groups.volumes.uuid | string | query | False | Filter by consistency_groups.volumes.uuid |
| consistency_groups.volumes.qos.policy.uuid | string | query | False | Filter by consistency_groups.volumes.qos.policy.uuid |
| consistency_groups.volumes.qos.policy.name | string | query | False | Filter by consistency_groups.volumes.qos.policy.name |
| consistency_groups.volumes.space.used | integer | query | False | Filter by consistency_groups.volumes.space.used |
| consistency_groups.volumes.space.size | integer | query | False | Filter by consistency_groups.volumes.space.size |
| consistency_groups.volumes.space.available | integer | query | False | Filter by consistency_groups.volumes.space.available |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| consistency_groups.volumes.nas.export_policy.id | integer | query | False | Filter by consistency_groups.volumes.nas.export_policy.id <ul style="list-style-type: none"> • Introduced in: 9.14 |
| consistency_groups.volumes.nas.export_policy.rules.superuser | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.superuser <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.index | integer | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.index <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.allow_device_creation | boolean | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.allow_device_creation <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.allow_suid | boolean | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.allow_suid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.rw_rule | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.rw_rule <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|--------|-------|----------|---|
| consistency_groups.volumes.nas.export_policy.rules.clients.match | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.clients.match <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.chown_mode | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.chown_mode <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.anonymous_user | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.anonymous_user <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.ntfs_unix_security | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.ntfs_unix_security <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.ro_rule | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.ro_rule <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|--|
| consistency_groups.volumes.nas.export_policy.rules.protocols | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.protocols <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.name | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.junction_parent.name | string | query | False | Filter by consistency_groups.volumes.nas.junction_parent.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.junction_parent.uuid | string | query | False | Filter by consistency_groups.volumes.nas.junction_parent.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.path | string | query | False | Filter by consistency_groups.volumes.nas.path <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.unix_symlink | string | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.unix_symlink <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| consistency_groups.volumes.nas.cifs.shares.show_snapshot | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.show_snapshot <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.vscan_profile | string | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.vscan_profile <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.comment | string | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.comment <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 256 • minLength: 1 |
| consistency_groups.volumes.nas.cifs.shares.continuously_available | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.continuously_available <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.encryption | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.encryption <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| consistency_groups.volumes.nas.cifs.shares.file_umask | integer | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.file_umask <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.home_directory | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.home_directory <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.namespace_caching | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.namespace_caching <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.oplocks | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.oplocks <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.offline_files | string | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.offline_files <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.access_basedEnumeration | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.access_basedEnumeration <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|--------|-------|----------|---|
| consistency_groups.volumes.nas.cifs.shares.name | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.name</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 80 • minLength: 1 |
| consistency_groups.volumes.nas.cifs.shares.acls.user_or_group | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.acls.user_or_group</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.acls.type | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.acls.type</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.acls.permission | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.acls.permission</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.acls.win_sid_unix_id | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.acls.win_sid_unix_id</p> <ul style="list-style-type: none"> • Introduced in: 9.16 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| consistency_groups.volumes.nas.cifs.shares.dir_umask | integer | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.dir_umask</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.allow_unencrypted_access | boolean | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.allow_unencrypted_access</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.change_notify | boolean | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.change_notify</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.no_strict_security | boolean | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.no_strict_security</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.security_style | string | query | False | <p>Filter by consistency_groups.volumes.nas.security_style</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.unix_permissions | integer | query | False | <p>Filter by consistency_groups.volumes.nas.unix_permissions</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| consistency_groups.volumes.nas.uid | integer | query | False | Filter by consistency_groups.volumes.nas.uid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.gid | integer | query | False | Filter by consistency_groups.volumes.nas.gid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.name | string | query | False | Filter by consistency_groups.volumes.name <ul style="list-style-type: none"> • maxLength: 203 • minLength: 1 |
| consistency_groups.volumes.comment | string | query | False | Filter by consistency_groups.volumes.comment <ul style="list-style-type: none"> • maxLength: 1023 • minLength: 0 |
| consistency_groups.snapshot_policy.uuid | string | query | False | Filter by consistency_groups.snapshot_policy.uuid |
| consistency_groups.snapshot_policy.name | string | query | False | Filter by consistency_groups.snapshot_policy.name |
| consistency_groups.name | string | query | False | Filter by consistency_groups.name |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|---|
| consistency_groups.luns.serial_number | string | query | False | Filter by consistency_groups.luns.serial_number <ul style="list-style-type: none"> • maxLength: 12 • minLength: 12 |
| consistency_groups.luns.name | string | query | False | Filter by consistency_groups.luns.name |
| consistency_groups.luns.lun_maps.igroup.initiators.comment | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.initiators.comment <ul style="list-style-type: none"> • maxLength: 254 • minLength: 0 |
| consistency_groups.luns.lun_maps.igroup.initiators.name | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.initiators.name |
| consistency_groups.luns.lun_maps.igroup.comment | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.comment <ul style="list-style-type: none"> • Introduced in: 9.11 • maxLength: 254 • minLength: 0 |
| consistency_groups.luns.lun_maps.igroup.os_type | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.os_type |
| consistency_groups.luns.lun_maps.igroup.uuid | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.uuid |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| consistency_groups.luns.lun_maps.igroups.name | string | query | False | Filter by consistency_groups.luns.lun_maps.igroups.name <ul style="list-style-type: none"> • maxLength: 96 • minLength: 1 |
| consistency_groups.luns.lun_maps.igroups.uuid | string | query | False | Filter by consistency_groups.luns.lun_maps.igroups.uuid |
| consistency_groups.luns.lun_maps.igroup.protocol | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.protocol |
| consistency_groups.luns.lun_maps.igroup.name | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.name <ul style="list-style-type: none"> • maxLength: 96 • minLength: 1 |
| consistency_groups.luns.lun_maps.logical_unit_number | integer | query | False | Filter by consistency_groups.luns.lun_maps.logical_unit_number |
| consistency_groups.luns.comment | string | query | False | Filter by consistency_groups.luns.comment <ul style="list-style-type: none"> • maxLength: 254 • minLength: 0 |
| consistency_groups.luns.create_time | string | query | False | Filter by consistency_groups.luns.create_time |
| consistency_groups.luns.enabled | boolean | query | False | Filter by consistency_groups.luns.enabled |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| consistency_groups.luns.os_type | string | query | False | Filter by consistency_groups.luns.os_type |
| consistency_groups.luns.qos.policy.min_throughput_mbps | integer | query | False | Filter by consistency_groups.luns.qos.policy.min_throughput_mbps <ul style="list-style-type: none"> • Max value: 4194303 • Min value: 0 |
| consistency_groups.luns.qos.policy.max_throughput_mbps | integer | query | False | Filter by consistency_groups.luns.qos.policy.max_throughput_mbps <ul style="list-style-type: none"> • Max value: 4194303 • Min value: 0 |
| consistency_groups.luns.qos.policy.uuid | string | query | False | Filter by consistency_groups.luns.qos.policy.uuid |
| consistency_groups.luns.qos.policy.min_throughput_iops | integer | query | False | Filter by consistency_groups.luns.qos.policy.min_throughput_iops <ul style="list-style-type: none"> • Max value: 2147483647 • Min value: 0 |
| consistency_groups.luns.qos.policy.name | string | query | False | Filter by consistency_groups.luns.qos.policy.name |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| consistency_groups.luns.qos.policy.max_throughput_iops | integer | query | False | <p>Filter by consistency_groups.luns.qos.policy.max_throughput_iops</p> <ul style="list-style-type: none"> • Max value: 2147483647 • Min value: 0 |
| consistency_groups.luns.uuid | string | query | False | Filter by consistency_groups.luns.uuid |
| consistency_groups.luns.space.size | integer | query | False | <p>Filter by consistency_groups.luns.space.size</p> <ul style="list-style-type: none"> • Max value: 140737488355328 • Min value: 4096 |
| consistency_groups.luns.space.used | integer | query | False | Filter by consistency_groups.luns.space.used |
| consistency_groups.luns.space.guarantee.requested | boolean | query | False | <p>Filter by consistency_groups.luns.space.guarantee.requested</p> <ul style="list-style-type: none"> • Introduced in: 9.11 |
| consistency_groups.luns.space.guarantee.reserved | boolean | query | False | <p>Filter by consistency_groups.luns.space.guarantee.reserved</p> <ul style="list-style-type: none"> • Introduced in: 9.11 |
| consistency_groups.svm.name | string | query | False | Filter by consistency_groups.svm.name |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|--|
| consistency_groups.svm.uuid | string | query | False | Filter by consistency_groups.svm.uuid |
| consistency_groups.parent_consistency_group.uuid | string | query | False | Filter by consistency_groups.parent_consistency_group.uuid |
| consistency_groups.parent_consistency_group.name | string | query | False | Filter by consistency_groups.parent_consistency_group.name |
| luns.serial_number | string | query | False | Filter by luns.serial_number <ul style="list-style-type: none"> • maxLength: 12 • minLength: 12 |
| luns.name | string | query | False | Filter by luns.name |
| luns.lun_maps.igroup.initiators.comment | string | query | False | Filter by luns.lun_maps.igroup.initiators.comment <ul style="list-style-type: none"> • maxLength: 254 • minLength: 0 |
| luns.lun_maps.igroup.initiators.name | string | query | False | Filter by luns.lun_maps.igroup.initiators.name |
| luns.lun_maps.igroup.comment | string | query | False | Filter by luns.lun_maps.igroup.comment <ul style="list-style-type: none"> • Introduced in: 9.11 • maxLength: 254 • minLength: 0 |
| luns.lun_maps.igroup.os_type | string | query | False | Filter by luns.lun_maps.igroup.os_type |

| Name | Type | In | Required | Description |
|-----------------------------------|---------|-------|----------|---|
| luns.lun_maps.igroup.uuid | string | query | False | Filter by luns.lun_maps.igroup.uuid |
| luns.lun_maps.igroup.igroups.name | string | query | False | Filter by luns.lun_maps.igroup.igroups.name <ul style="list-style-type: none"> • maxLength: 96 • minLength: 1 |
| luns.lun_maps.igroup.igroups.uuid | string | query | False | Filter by luns.lun_maps.igroup.igroups.uuid |
| luns.lun_maps.igroup.protocol | string | query | False | Filter by luns.lun_maps.igroup.protocol |
| luns.lun_maps.igroup.name | string | query | False | Filter by luns.lun_maps.igroup.name <ul style="list-style-type: none"> • maxLength: 96 • minLength: 1 |
| luns.lun_maps.logical_unit_number | integer | query | False | Filter by luns.lun_maps.logical_unit_number |
| luns.comment | string | query | False | Filter by luns.comment <ul style="list-style-type: none"> • maxLength: 254 • minLength: 0 |
| luns.create_time | string | query | False | Filter by luns.create_time |
| luns.enabled | boolean | query | False | Filter by luns.enabled |
| luns.os_type | string | query | False | Filter by luns.os_type |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| luns.qos.policy.min_t hroughput_mbps | integer | query | False | Filter by luns.qos.policy.min_throughput_mbps <ul style="list-style-type: none"> • Max value: 4194303 • Min value: 0 |
| luns.qos.policy.max_ throughput_mbps | integer | query | False | Filter by luns.qos.policy.max_throughput_mbps <ul style="list-style-type: none"> • Max value: 4194303 • Min value: 0 |
| luns.qos.policy.uuid | string | query | False | Filter by luns.qos.policy.uuid |
| luns.qos.policy.min_t hroughput_iops | integer | query | False | Filter by luns.qos.policy.min_throughput_iops <ul style="list-style-type: none"> • Max value: 2147483647 • Min value: 0 |
| luns.qos.policy.name | string | query | False | Filter by luns.qos.policy.name |
| luns.qos.policy.max_ throughput_iops | integer | query | False | Filter by luns.qos.policy.max_throughput_iops <ul style="list-style-type: none"> • Max value: 2147483647 • Min value: 0 |
| luns.uuid | string | query | False | Filter by luns.uuid |

| Name | Type | In | Required | Description |
|---------------------------------|---------|-------|----------|--|
| luns.space.size | integer | query | False | Filter by luns.space.size <ul style="list-style-type: none"> • Max value: 1407374883553 28 • Min value: 4096 |
| luns.space.used | integer | query | False | Filter by luns.space.used |
| luns.space.guarante.e.requested | boolean | query | False | Filter by luns.space.guarante.e.requested <ul style="list-style-type: none"> • Introduced in: 9.11 |
| luns.space.guarante.e.reserved | boolean | query | False | Filter by luns.space.guarante.e.reserved <ul style="list-style-type: none"> • Introduced in: 9.11 |
| svm.name | string | query | False | Filter by svm.name |
| svm.uuid | string | query | False | Filter by svm.uuid |
| metric.duration | string | query | False | Filter by metric.duration <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.used_space | integer | query | False | Filter by metric.used_space <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.latency.write | integer | query | False | Filter by metric.latency.write <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|-------------------------|---------|-------|----------|---|
| metric.latency.total | integer | query | False | Filter by metric.latency.total <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.latency.read | integer | query | False | Filter by metric.latency.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.latency.other | integer | query | False | Filter by metric.latency.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.available_space | integer | query | False | Filter by metric.available_space <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.size | integer | query | False | Filter by metric.size <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.throughput.write | integer | query | False | Filter by metric.throughput.write <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.throughput.total | integer | query | False | Filter by metric.throughput.total <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|-------------------------|---------|-------|----------|---|
| metric.throughput.read | integer | query | False | Filter by metric.throughput.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.throughput.other | integer | query | False | Filter by metric.throughput.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.timestamp | string | query | False | Filter by metric.timestamp <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.iops.write | integer | query | False | Filter by metric.iops.write <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.iops.total | integer | query | False | Filter by metric.iops.total <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.iops.read | integer | query | False | Filter by metric.iops.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.iops.other | integer | query | False | Filter by metric.iops.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.status | string | query | False | Filter by metric.status <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|-------------------------------|---------------|-------|----------|--|
| name | string | query | False | Filter by name |
| replication_source | boolean | query | False | Filter by replication_source |
| parent_consistency_group.uuid | string | query | False | Filter by parent_consistency_group.uuid |
| parent_consistency_group.name | string | query | False | Filter by parent_consistency_group.name |
| fields | array[string] | query | False | Specify the fields to return. |
| max_records | integer | query | False | Limit the number of records returned. |
| return_records | boolean | query | False | <p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> Default value: 1 |
| return_timeout | integer | query | False | <p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> Max value: 120 Min value: 0 Default value: 1 |

| Name | Type | In | Required | Description |
|----------|---------------|-------|----------|--|
| order_by | array[string] | query | False | Order results by specified fields and optional [asc] |

Response

Status: 200, Ok

| Name | Type | Description |
|-------------|----------------------------------|--------------------|
| _links | collection_links | |
| num_records | integer | Number of records. |
| records | array[records] | |

Example response

```
{  
  "_links": {  
    "next": {  
      "href": "/api/resourcelink"  
    },  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "num_records": 1,  
  "records": [  
    {  
      "_links": {  
        "self": {  
          "href": "/api/resourcelink"  
        }  
      },  
      "_tags": [  
        "team:csi",  
        "environment:test"  
      ],  
      "application": {  
        "component_type": "string",  
        "type": "string"  
      },  
      "clone": {  
        "guarantee": {  
          "type": "string"  
        },  
        "parent_consistency_group": {  
          "_links": {  
            "self": {  
              "href": "/api/resourcelink"  
            }  
          },  
          "name": "string",  
          "uuid": "string"  
        },  
        "parent_snapshot": {  
          "_links": {  
            "self": {  
              "href": "/api/resourcelink"  
            }  
          },  
          "name": "string",  
          "uuid": "string"  
        }  
      }  
    }  
  ]  
}
```

```

  "name": "this_snapshot",
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"parent_svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"split_complete_percent": 0,
"split_estimate": 0,
"volume": {
  "prefix": "string",
  "suffix": "string"
}
},
"consistency_groups": [
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "_tags": [
    "team:csi",
    "environment:test"
  ],
  "application": {
    "component_type": "string",
    "type": "string"
  },
  "luns": [
    {
      "comment": "string",
      "create_time": "2018-06-04 15:00:00 -0400",
      "lun_maps": [
        {
          "igroup": {
            "comment": "string",
            "igroups": [
              {
                "_links": {
                  "self": {
                    "href": "/api/resourcelink"
                  }
                }
              }
            ]
          }
        }
      ]
    }
  ]
}
]
}

```

```

                "href": "/api/resourcelink"
            }
        },
        "name": "igroup1",
        "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
    }
],
"initiators": [
{
    "comment": "my comment",
    "name": "iqn.1998-01.com.corp.iscsi:namel"
}
],
"name": "igroup1",
"os_type": "string",
"protocol": "string",
"uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
}
}
],
"name": "/vol/volume1/lun1",
"os_type": "string",
"qos": {
    "policy": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "max_throughput_iops": 10000,
        "max_throughput_mbps": 500,
        "min_throughput_iops": 2000,
        "min_throughput_mbps": 500,
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"serial_number": "string",
"space": {
    "size": 1073741824,
    "used": 0
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
],
"name": "string",

```

```

"namespaces": [
  {
    "comment": "string",
    "create_time": "2018-06-04 15:00:00 -0400",
    "name": "/vol/volume1/qtree1/namespace1",
    "os_type": "string",
    "space": {
      "block_size": 512,
      "size": 1073741824,
      "used": 0
    },
    "status": {
      "container_state": "string",
      "state": "online"
    },
    "subsystem_map": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "anagrpid": "00103050h",
      "nsid": "00000001h",
      "subsystem": {
        "comment": "string",
        "hosts": [
          {
            "dh_hmac_chap": {
              "group_size": "string",
              "hash_function": "string",
              "mode": "bidirectional"
            },
            "nqn": "nqn.1992-01.example.com:string",
            "priority": "string",
            "tls": {
              "key_type": "configured"
            }
          }
        ],
        "name": "subsystem1",
        "os_type": "string",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
      }
    },
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  }
]

```

```

] ,
  "parent_consistency_group": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "my_consistency_group",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "qos": {
    "policy": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "performance",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
  },
  "restore_to": {
    "snapshot": {
      "name": "string",
      "uuid": "string"
    }
  },
  "snapshot_policy": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "space": {
    "available": 5737418,
    "size": 1073741824,
    "used": 5737418
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  }
}

```

```

},
"name": "svml1",
"uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"tiering": {
  "object_stores": [
    {}
  ],
  "policy": "string"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412",
"volumes": [
  {
    "comment": "string",
    "name": "vol_cs_dept",
    "nas": {
      "cifs": {
        "shares": [
          {
            "_links": {
              "self": {
                "href": "/api/resourcelink"
              }
            },
            "acls": [
              {
                "_links": {
                  "self": {
                    "href": "/api/resourcelink"
                  }
                },
                "permission": "string",
                "type": "string",
                "user_or_group": "ENGDOMAIN\\ad_user",
                "win_sid_unix_id": "string"
              }
            ],
            "comment": "HR Department Share",
            "dir_umask": 18,
            "file_umask": 18,
            "name": "HR_SHARE",
            "offline_files": "string",
            "unix_symlink": "string",
            "vscan_profile": "string"
          }
        ]
      }
    }
  }
]

```

```
},
"export_policy": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "id": 0,
  "name": "string",
  "rules": [
    {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "anonymous_user": "string",
      "chown_mode": "string",
      "clients": [
        {
          "match": "0.0.0.0/0"
        }
      ],
      "ntfs_unix_security": "string",
      "protocols": [
        "string"
      ],
      "ro_rule": [
        "string"
      ],
      "rw_rule": [
        "string"
      ],
      "superuser": [
        "string"
      ]
    }
  ]
},
"junction_parent": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "vs1_root",
```

```

        "uuid": "75c9cfb0-3eb4-11eb-9fb4-005056bb088a"
    },
    "path": "/user/my_volume",
    "security_style": "string",
    "unix_permissions": 493
},
"qos": {
    "policy": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"snapshot_policy": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"space": {
    "available": 0,
    "used": 0
},
"tiering": {
    "object_stores": [
        {}
    ],
    "policy": "string"
},
"uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
]
}
],
"luns": [
{
    "comment": "string",
    "create_time": "2018-06-04 15:00:00 -0400",
    "lun_maps": [

```

```
{
  "igroup": {
    "comment": "string",
    "igroups": [
      {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "igroup1",
        "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
      }
    ],
    "initiators": [
      {
        "comment": "my comment",
        "name": "iqn.1998-01.com.corp.iscsi:namel"
      }
    ],
    "name": "igroup1",
    "os_type": "string",
    "protocol": "string",
    "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
  }
},
  "name": "/vol/volumel/lun1",
  "os_type": "string",
  "qos": {
    "policy": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "max_throughput_iops": 10000,
      "max_throughput_mbps": 500,
      "min_throughput_iops": 2000,
      "min_throughput_mbps": 500,
      "name": "performance",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
  },
  "serial_number": "string",
  "space": {

```

```
        "size": 1073741824,
        "used": 0
    },
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
],
"metric": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "available_space": 4096,
    "duration": "PT15S",
    "iops": {
        "read": 200,
        "total": 1000,
        "write": 100
    },
    "latency": {
        "read": 200,
        "total": 1000,
        "write": 100
    },
    "size": 4096,
    "status": "ok",
    "throughput": {
        "read": 200,
        "total": 1000,
        "write": 100
    },
    "timestamp": "2017-01-25 06:20:13 -0500",
    "used_space": 4096
},
"name": "string",
"namespaces": [
    {
        "comment": "string",
        "create_time": "2018-06-04 15:00:00 -0400",
        "name": "/vol/volume1/qtree1/namespacel",
        "os_type": "string",
        "space": {
            "block_size": 512,
            "size": 1073741824,
            "used": 0
        }
    },
    {
        "comment": "string",
        "create_time": "2018-06-04 15:00:00 -0400",
        "name": "/vol/volume1/qtree1/namespacetwo",
        "os_type": "string",
        "space": {
            "block_size": 512,
            "size": 1073741824,
            "used": 0
        }
    }
]
```

```

"status": {
    "container_state": "string",
    "state": "online"
},
"subsystem_map": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "anagrpid": "00103050h",
    "nsid": "00000001h",
    "subsystem": {
        "comment": "string",
        "hosts": [
            {
                "dh_hmac_chap": {
                    "group_size": "string",
                    "hash_function": "string",
                    "mode": "bidirectional"
                },
                "nqn": "nqn.1992-01.example.com:string",
                "priority": "string",
                "tls": {
                    "key_type": "configured"
                }
            }
        ],
        "name": "subsystem1",
        "os_type": "string",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"parent_consistency_group": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "my_consistency_group",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"qos": {

```

```

"policy": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "performance",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
},
"replication_relationships": [
    {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
],
"restore_to": {
    "snapshot": {
        "name": "string",
        "uuid": "string"
    }
},
"snapshot_policy": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"space": {
    "available": 5737418,
    "size": 1073741824,
    "used": 5737418
},
"statistics": {
    "available_space": 4096,
    "iops_raw": {
        "read": 200,
        "total": 1000,
        "write": 100
}
}

```

```

        },
        "latency_raw": {
            "read": 200,
            "total": 1000,
            "write": 100
        },
        "size": 4096,
        "status": "ok",
        "throughput_raw": {
            "read": 200,
            "total": 1000,
            "write": 100
        },
        "timestamp": "2017-01-25 06:20:13 -0500",
        "used_space": 4096
    },
    "svm": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "tiering": {
        "object_stores": [
            {}
        ],
        "policy": "string"
    },
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412",
    "volumes": [
        {
            "comment": "string",
            "name": "vol_cs_dept",
            "nas": {
                "cifs": {
                    "shares": [
                        {
                            "_links": {
                                "self": {
                                    "href": "/api/resourcelink"
                                }
                            },
                            "acls": [

```

```

    {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "permission": "string",
      "type": "string",
      "user_or_group": "ENGDOMAIN\\ad_user",
      "win_sid_unix_id": "string"
    }
  ],
  "comment": "HR Department Share",
  "dir_umask": 18,
  "file_umask": 18,
  "name": "HR_SHARE",
  "offline_files": "string",
  "unix_symlink": "string",
  "vscan_profile": "string"
}
]
},
"export_policy": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "id": 0,
  "name": "string",
  "rules": [
    {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "anonymous_user": "string",
      "chown_mode": "string",
      "clients": [
        {
          "match": "0.0.0.0/0"
        }
      ],
      "ntfs_unix_security": "string",
      "protocols": [
        {
          "name": "string"
        }
      ],
      "share": "string"
    }
  ]
}
]
}

```

```
        "string"
    ],
    "ro_rule": [
        "string"
    ],
    "rw_rule": [
        "string"
    ],
    "superuser": [
        "string"
    ]
}
]
},
"junction_parent": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "vs1_root",
    "uuid": "75c9cfb0-3eb4-11eb-9fb4-005056bb088a"
},
"path": "/user/my_volume",
"security_style": "string",
"unix_permissions": 493
},
"qos": {
    "policy": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"snapshot_policy": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
```

```

} ,
"space": {
  "available": 0,
  "used": 0
},
"tiering": {
  "object_stores": [
    {}
  ],
  "policy": "string"
},
"uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
]
}
}
}

```

Error

Status: Default, Error

| Name | Type | Description |
|-------|----------------|-------------|
| error | returned_error | |

Example error

```

{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

collection_links

| Name | Type | Description |
|------|----------------------|-------------|
| next | href | |
| self | href | |

self_link

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

application

| Name | Type | Description |
|----------------|--------|----------------------------------|
| component_type | string | Nested consistency group tag. |
| type | string | Top level consistency group tag. |

guarantee

| Name | Type | Description |
|------|--------|--|
| type | string | The type of space guarantee of this volume in the aggregate. |

parent_consistency_group

Consistency group that is to be cloned.

| Name | Type | Description |
|--------|---------------------------|---|
| _links | self_link | |
| name | string | The name of the consistency group. |
| uuid | string | The unique identifier of the consistency group. |

_links

| Name | Type | Description |
|------|----------------------|-------------|
| self | href | |

parent_snapshot

Consistency group that is to be cloned.

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

parent_svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

Volume name suffix/prefix for the cloned volumes.

| Name | Type | Description |
|--------|--------|--|
| prefix | string | Volume name prefix for cloned volumes. |
| suffix | string | Volume name suffix for cloned volumes. |

clone

Creates a clone of an existing consistency group from the current contents or an existing snapshot.

| Name | Type | Description |
|-----------|---------------------------|-------------|
| guarantee | guarantee | |

| Name | Type | Description |
|--------------------------|--------------------------|--|
| is_flexclone | boolean | Specifies if this consistency group is a FlexClone of a consistency group. |
| parent_consistency_group | parent_consistency_group | Consistency group that is to be cloned. |
| parent_snapshot | parent_snapshot | Consistency group that is to be cloned. |
| parent_svm | parent_svm | SVM, applies only to SVM-scoped objects. |
| split_complete_percent | integer | Percentage of FlexClone blocks split from its parent consistency group. |
| split_estimate | integer | Space required to split the FlexClone consistency group. |
| split_initiated | boolean | Splits volumes after cloning. Defaults to false during POST. Only accepts true during a PATCH. |
| volume | volume | Volume name suffix/prefix for the cloned volumes. |

source

The source LUN for a LUN clone operation. This can be specified using property `clone.source.uuid` or `clone.source.name`. If both properties are supplied, they must refer to the same LUN.

Valid in POST to create a new LUN as a clone of the source.

Valid in PATCH to overwrite an existing LUN's data as a clone of another.

clone

This sub-object is used in POST to create a new LUN as a clone of an existing LUN, or PATCH to overwrite an existing LUN as a clone of another. Setting a property in this sub-object indicates that a LUN clone is desired. Consider the following other properties when cloning a LUN: `auto_delete`, `qos_policy`, `space.guarantee.requested` and `space.scsi_thin_provisioning_support_enabled`.

When used in a PATCH, the patched LUN's data is over-written as a clone of the source and the following properties are preserved from the patched LUN unless otherwise specified as part of the PATCH: `class`, `auto_delete`, `lun_maps`, `serial_number`, `status.state`, and `uuid`.

Persistent reservations for the patched LUN are also preserved.

igroups

| Name | Type | Description |
|--------|---------------------------|---|
| _links | self_link | |
| name | string | The name of the initiator group. |
| uuid | string | The unique identifier of the initiator group. |

initiators

The initiators that are members of the initiator group.

| Name | Type | Description |
|---------|--------|--|
| comment | string | A comment available for use by the administrator. |
| name | string | Name of initiator that is a member of the initiator group. |

igroup

The initiator group that directly owns the initiator, which is where modification of the initiator is supported. This property will only be populated when the initiator is a member of a nested initiator group.

| Name | Type | Description |
|---------|--------|--|
| comment | string | A comment available for use by the administrator. Valid in POST and PATCH. |

| Name | Type | Description |
|------------|-------------------------------------|---|
| igroups | array[igroups] | <p>The existing initiator groups that are members of the group. Optional in POST.</p> <p>This property is mutually exclusive with the <i>initiators</i> property during POST.</p> <p>This array contains only the direct children of the initiator group. If the member initiator groups have further nested initiator groups, those are reported in the <i>igroups</i> property of the child initiator group.</p> <p>Zero or more nested initiator groups can be supplied when the initiator group is created. The initiator group will act as if it contains the aggregation of all initiators in any nested initiator groups.</p> <p>After creation, nested initiator groups can be added or removed from the initiator group using the <code>/protocols/san/igroups/{group.uuid}/igroups</code> endpoint. See DELETE /protocols/san/igroups/{group.uuid}/igroups/{uuid} for more details.</p> |
| initiators | array[initiators] | The initiators that are members of the group. |
| name | string | The name of the initiator group. Required in POST; optional in PATCH. |
| os_type | string | The host operating system of the initiator group. All initiators in the group should be hosts of the same operating system. Required in POST; optional in PATCH. |

| Name | Type | Description |
|----------|--------|---|
| protocol | string | <p>The protocols supported by the initiator group. This restricts the type of initiators that can be added to the initiator group. Optional in POST; if not supplied, this defaults to <i>mixed</i>.</p> <p>The protocol of an initiator group cannot be changed after creation of the group.</p> |
| uuid | string | The unique identifier of the initiator group. |

lun_maps

A LUN map is an association between a LUN and an initiator group.

When a LUN is mapped to an initiator group, the initiator group's initiators are granted access to the LUN. The relationship between a LUN and an initiator group is many LUNs to many initiator groups.

| Name | Type | Description |
|---------------------|------------------------|--|
| igroup | igroup | <p>The initiator group that directly owns the initiator, which is where modification of the initiator is supported. This property will only be populated when the initiator is a member of a nested initiator group.</p> |
| logical_unit_number | integer | <p>The logical unit number assigned to the LUN when mapped to the specified initiator group. The number is used to identify the LUN to initiators in the initiator group when communicating through the Fibre Channel Protocol or iSCSI. Optional in POST; if no value is provided, ONTAP assigns the lowest available value. This property is not supported when the <i>provisioning_options.count</i> property is 2 or more.</p> <ul style="list-style-type: none"> • Introduced in: 9.6 • readCreate: 1 • x-nullable: true |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|--------|---------|---|
| action | string | Operation to perform |
| count | integer | Number of elements to perform the operation on. |

policy

The QoS policy

| Name | Type | Description |
|---------------------|---------------------------|---|
| _links | self_link | |
| max_throughput_iops | integer | Specifies the maximum throughput in IOPS, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| max_throughput_mbps | integer | Specifies the maximum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| min_throughput_iops | integer | Specifies the minimum throughput in IOPS, 0 means none. Setting "min_throughput" is supported on AFF platforms only, unless FabricPool tiering policies are set. This is mutually exclusive with name and UUID during POST and PATCH. |
| min_throughput_mbps | integer | Specifies the minimum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| name | string | The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH. |

| Name | Type | Description |
|------|--------|---|
| uuid | string | The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH. |

qos

| Name | Type | Description |
|--------|--------|----------------|
| policy | policy | The QoS policy |

guarantee

Properties that request and report the space guarantee for the LUN.

| Name | Type | Description |
|-----------|---------|--|
| requested | boolean | The requested space reservation policy for the LUN. If <i>true</i> , a space reservation is requested for the LUN; if <i>false</i> , the LUN is thin provisioned. Guaranteeing a space reservation request for a LUN requires that the volume in which the LUN resides is also space reserved and that the fractional reserve for the volume is 100%. Valid in POST and PATCH. |
| reserved | boolean | Reports if the LUN is space guaranteed. If <i>true</i> , a space guarantee is requested and the containing volume and aggregate support the request. If <i>false</i> , a space guarantee is not requested or a space guarantee is requested and either the containing volume or aggregate do not support the request. |

space

The storage space related properties of the LUN.

| Name | Type | Description |
|-----------|-----------|---|
| guarantee | guarantee | Properties that request and report the space guarantee for the LUN. |
| size | integer | <p>The total provisioned size of the LUN. The LUN size can be increased but not reduced using the REST interface. The maximum and minimum sizes listed here are the absolute maximum and absolute minimum sizes, in bytes. The actual minimum and maximum sizes vary depending on the ONTAP version, ONTAP platform, and the available space in the containing volume and aggregate. For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • example: 1073741824 • format: int64 • Max value: 140737488355328 • Min value: 4096 • Introduced in: 9.6 • x-nullable: true |

| Name | Type | Description |
|------|---------|---|
| used | integer | <p>The amount of space consumed by the main data stream of the LUN.</p> <p>This value is the total space consumed in the volume by the LUN, including filesystem overhead, but excluding prefix and suffix streams. Due to internal filesystem overhead and the many ways SAN filesystems and applications utilize blocks within a LUN, this value does not necessarily reflect actual consumption/availability from the perspective of the filesystem or application. Without specific knowledge of how the LUN blocks are utilized outside of ONTAP, this property should not be used as an indicator for an out-of-space condition.</p> <p>For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • format: int64 • readOnly: 1 • Introduced in: 9.6 • x-nullable: true |

luns

A LUN is the logical representation of storage in a storage area network (SAN).

A LUN must be mapped to an initiator group to grant access to the initiator group's initiators (client hosts). Initiators can then access the LUN and perform I/O over a Fibre Channel (FC) fabric using the FC Protocol or a TCP/IP network using iSCSI.

See the LUN object model to learn more about each of the properties supported by the LUN REST API.

A LUN is located within a volume. Optionally, it can be located within a qtree in a volume.

LUN names are paths of the form "/vol/<volume>[/<qtree>]/<lun>" where the qtree name is optional.

A LUN can be created to a specified size using thin or thick provisioning. A LUN can then be renamed, resized, cloned, moved to a different volume and copied. LUNs support the assignment of a QoS policy for performance management or a QoS policy can be assigned to a volume containing one or more LUNs.

```
</lun></qtree></volume>
```

| Name | Type | Description |
|-------------|-----------------|--|
| comment | string | A configurable comment available for use by the administrator. Valid in POST and PATCH. |
| create_time | string | The time the LUN was created. |
| enabled | boolean | The enabled state of the LUN. LUNs can be disabled to prevent access to the LUN. Certain error conditions also cause the LUN to become disabled. If the LUN is disabled, you can consult the state property to determine if the LUN is administratively disabled (<i>offline</i>) or has become disabled as a result of an error. A LUN in an error condition can be brought online by setting the enabled property to <i>true</i> or brought administratively offline by setting the enabled property to <i>false</i> . Upon creation, a LUN is enabled by default. Valid in PATCH. |
| lun_maps | array[lun_maps] | An array of LUN maps. A LUN map is an association between a LUN and an initiator group. When a LUN is mapped to an initiator group, the initiator group's initiators are granted access to the LUN. The relationship between a LUN and an initiator group is many LUNs to many initiator groups. |
| name | string | The fully qualified path name of the LUN composed of the "/vol" prefix, the volume name, the qtree name (optional), and the base name of the LUN. Valid in POST and PATCH. |

| Name | Type | Description |
|---------------|-----------------------|--|
| os_type | string | <p>The operating system type of the LUN.</p> <p>Required in POST when creating a LUN that is not a clone of another. Disallowed in POST when creating a LUN clone.</p> |
| qos | qos | |
| serial_number | string | <p>The LUN serial number. The serial number is generated by ONTAP when the LUN is created.</p> <ul style="list-style-type: none"> • maxLength: 12 • minLength: 12 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |
| space | space | The storage space related properties of the LUN. |
| uuid | string | <p>The unique identifier of the LUN. The UUID is generated by ONTAP when the LUN is created.</p> <ul style="list-style-type: none"> • example: 1cd8a442-86d1-11e0-ae1c-123478563412 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |

guarantee

Properties that request and report the space guarantee for the NVMe namespace.

| Name | Type | Description |
|-----------|---------|--|
| requested | boolean | <p>The requested space reservation policy for the NVMe namespace. If <i>true</i>, a space reservation is requested for the namespace; if <i>false</i>, the namespace is thin provisioned. Guaranteeing a space reservation request for a namespace requires that the volume in which the namespace resides also be space reserved and that the fractional reserve for the volume be 100%.</p> <p>The space reservation policy for an NVMe namespace is determined by ONTAP.</p> <ul style="list-style-type: none"> • Introduced in: 9.6 • x-nullable: true |
| reserved | boolean | <p>Reports if the NVMe namespace is space guaranteed.</p> <p>This property is <i>true</i> if a space guarantee is requested and the containing volume and aggregate support the request. This property is <i>false</i> if a space guarantee is not requested or if a space guarantee is requested and either the containing volume and aggregate do not support the request.</p> |

space

The storage space related properties of the NVMe namespace.

| Name | Type | Description |
|------------|---------|---|
| block_size | integer | <p>The size of blocks in the namespace, in bytes.</p> <p>Valid in POST when creating an NVMe namespace that is not a clone of another. Disallowed in POST when creating a namespace clone. Valid in POST.</p> |

| Name | Type | Description |
|-----------|-----------|--|
| guarantee | guarantee | Properties that request and report the space guarantee for the NVMe namespace. |
| size | integer | <p>The total provisioned size of the NVMe namespace. Valid in POST and PATCH. The NVMe namespace size can be increased but not reduced using the REST interface.</p> <p>The maximum and minimum sizes listed here are the absolute maximum and absolute minimum sizes, in bytes. The maximum size is variable with respect to large NVMe namespace support in ONTAP. If large namespaces are supported, the maximum size is 128 TB (140737488355328 bytes) and if not supported, the maximum size is just under 16 TB (17557557870592 bytes). The minimum size supported is always 4096 bytes.</p> <p>For more information, see Size properties in the docs section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • example: 1073741824 • format: int64 • Max value: 140737488355328 • Min value: 4096 • Introduced in: 9.6 • x-nullable: true |

| Name | Type | Description |
|------|---------|--|
| used | integer | <p>The amount of space consumed by the main data stream of the NVMe namespace.</p> <p>This value is the total space consumed in the volume by the NVMe namespace, including filesystem overhead, but excluding prefix and suffix streams. Due to internal filesystem overhead and the many ways NVMe filesystems and applications utilize blocks within a namespace, this value does not necessarily reflect actual consumption/availability from the perspective of the filesystem or application. Without specific knowledge of how the namespace blocks are utilized outside of ONTAP, this property should not be used as an indicator for an out-of-space condition.</p> <p>For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • format: int64 • readOnly: 1 • Introduced in: 9.6 • x-nullable: true |

status

Status information about the NVMe namespace.

| Name | Type | Description |
|-----------------|--------|---|
| container_state | string | The state of the volume and aggregate that contain the NVMe namespace. Namespaces are only available when their containers are available. |

| Name | Type | Description |
|-----------|---------|---|
| mapped | boolean | <p>Reports if the NVMe namespace is mapped to an NVMe subsystem.</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for either a collection GET or an instance GET unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| read_only | boolean | Reports if the NVMe namespace allows only read access. |
| state | string | The state of the NVMe namespace. Normal states for a namespace are <i>online</i> and <i>offline</i> . Other states indicate errors. |

consistency_group_nvme_host_dh_hmac_chap

A container for the configuration of NVMe in-band authentication using the DH-HMAC-CHAP protocol for a host.

| Name | Type | Description |
|---------------|--------|--|
| group_size | string | <p>The Diffie-Hellman group size for NVMe in-band authentication. When property <code>host_secret_key</code> is provided, this property defaults to <code>2048_bit</code>. When supplied, the property <code>host_secret_key</code> must also be supplied. Optional in POST.</p> |
| hash_function | string | <p>The hash function for NVMe in-band authentication. When property <code>host_secret_key</code> is provided, this property defaults to <code>sha_256</code>. When supplied, the property <code>host_secret_key</code> must also be supplied. Optional in POST.</p> |

| Name | Type | Description |
|------|--------|---|
| mode | string | <p>The expected NVMe in-band authentication mode for the host. This property is an indication of which secrets are configured for the host. When set to:</p> <ul style="list-style-type: none"> • none: The host has neither the host nor controller secret configured, and no authentication is performed. • unidirectional: The host has a host secret configured. The controller will authenticate the host. • bidirectional: The host has both a host and controller secret configured. The controller will authenticate the host and the host will authenticate the controller. |

tls

A container for the configuration for NVMe/TCP-TLS transport session for the host.

| Name | Type | Description |
|----------|--------|--|
| key_type | string | <p>The method by which the TLS pre-shared key (PSK) is configured for the host. Optional in POST.</p> <p>The values for property <code>key_type</code> and property <code>configured_psk</code> must logically agree.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • <code>none</code> - TLS is not configured for the host connection. No value is allowed for property <code>configured_psk</code>. • <code>configured</code> - A user supplied PSK is configured for the NVMe/TCP-TLS transport connection between the host and the NVMe subsystem. A valid value for property <code>configured_psk</code> is required. <p>This property defaults to <code>none</code> unless a value is supplied for <code>configured_psk</code> in which case it defaults to <code>configured</code>.</p> |

consistency_group_nvme_host

The NVMe host provisioned to access NVMe namespaces mapped to a subsystem.

| Name | Type | Description |
|--------------|--|--|
| dh_hmac_chap | consistency_group_nvme_host_dh_hmac_chap | A container for the configuration of NVMe in-band authentication using the DH-HMAC-CHAP protocol for a host. |
| nqn | string | The NVMe qualified name (NQN) used to identify the NVMe storage target. |

| Name | Type | Description |
|----------|---------------------|---|
| priority | string | The host priority setting allocates appropriate NVMe I/O queues (count and depth) for the host to submit I/O commands. Absence of this property in GET implies io_queue count and I/O queue depth are being used. |
| tls | tls | A container for the configuration for NVMe/TCP-TLS transport session for the host. |

consistency_group_nvme_subsystem

An NVMe subsystem maintains configuration state and namespace access control for a set of NVMe-connected hosts.

| Name | Type | Description |
|---------|--|--|
| comment | string | A configurable comment for the NVMe subsystem. Optional in POST and PATCH. |
| hosts | array[consistency_group_nvme_host] | The NVMe hosts configured for access to the NVMe subsystem. Optional in POST. |
| name | string | The name of the NVMe subsystem. Once created, an NVMe subsystem cannot be renamed. Required in POST. |
| os_type | string | The host operating system of the NVMe subsystem's hosts. Required in POST. |
| uuid | string | The unique identifier of the NVMe subsystem. |

subsystem_map

The NVMe subsystem with which the NVMe namespace is associated. A namespace can be mapped to zero (0) or one (1) subsystems.

There is an added computational cost to retrieving property values for `subsystem_map`. They are not populated for either a collection GET or an instance GET unless explicitly requested using the `fields` query parameter.

| Name | Type | Description |
|-----------|--|---|
| _links | self_link | |
| anagrpid | string | <p>The Asymmetric Namespace Access Group ID (ANAGRPID) of the NVMe namespace.</p> <p>The format for an ANAGRPID is 8 hexadecimal digits (zero-filled) followed by a lower case "h".</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for a GET request unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| nsid | string | <p>The NVMe namespace identifier. This is an identifier used by an NVMe controller to provide access to the NVMe namespace.</p> <p>The format for an NVMe namespace identifier is 8 hexadecimal digits (zero-filled) followed by a lower case "h".</p> |
| subsystem | consistency_group_nvme_subsystem | An NVMe subsystem maintains configuration state and namespace access control for a set of NVMe-connected hosts. |

namespaces

An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the storage virtual machine using the NVMe over Fabrics protocol.

An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.

See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API. An NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.

NVMe namespace names are paths of the form "/vol/<volume>[/<qtree>]/<namespace>" where the qtree name is optional.

An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. An NVMe namespace can then be resized or cloned. An NVMe namespace cannot be renamed, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing

the namespace.

```
</namespace></qtree></volume>
```

| Name | Type | Description |
|-------------|---------|---|
| auto_delete | boolean | <p>This property marks the NVMe namespace for auto deletion when the volume containing the namespace runs out of space. This is most commonly set on namespace clones.</p> <p>When set to <i>true</i>, the NVMe namespace becomes eligible for automatic deletion when the volume runs out of space. Auto deletion only occurs when the volume containing the namespace is also configured for auto deletion and free space in the volume decreases below a particular threshold.</p> <p>This property is optional in POST and PATCH. The default value for a new NVMe namespace is <i>false</i>.</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for a GET request unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| comment | string | A configurable comment available for use by the administrator. Valid in POST and PATCH. |
| create_time | string | The time the NVMe namespace was created. |
| enabled | boolean | The enabled state of the NVMe namespace. Certain error conditions cause the namespace to become disabled. If the namespace is disabled, check the <code>status.state</code> property to determine what error disabled the namespace. An NVMe namespace is enabled automatically when it is created. |

| Name | Type | Description |
|---------------|---------------|--|
| name | string | <p>The name of the NVMe namespace. An NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>NVMe namespace names are paths of the form "/vol/<volume>[/<qtree>]/<namespace>" where the qtree name is optional.</p> <p>Renaming an NVMe namespace is not supported. Valid in POST.</p> |
| os_type | string | <p>The operating system type of the NVMe namespace.</p> <p>Required in POST when creating an NVMe namespace that is not a clone of another. Disallowed in POST when creating a namespace clone.</p> |
| space | space | <p>The storage space related properties of the NVMe namespace.</p> |
| status | status | <p>Status information about the NVMe namespace.</p> |
| subsystem_map | subsystem_map | <p>The NVMe subsystem with which the NVMe namespace is associated. A namespace can be mapped to zero (0) or one (1) subsystems.</p> <p>There is an added computational cost to retrieving property values for <code>subsystem_map</code>. They are not populated for either a collection GET or an instance GET unless explicitly requested using the <code>fields</code> query parameter.</p> |
| uuid | string | <p>The unique identifier of the NVMe namespace.</p> |

parent_consistency_group

The parent consistency group.

| Name | Type | Description |
|--------|---------------------------|---|
| _links | self_link | |
| name | string | The name of the consistency group. |
| uuid | string | The unique identifier of the consistency group. |

storage_service

Determines the placement of any storage object created during this operation.

| Name | Type | Description |
|------|--------|--|
| name | string | Storage service name. If not specified, the default value is the most performant for the platform. |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|-----------------|---------------------------------|---|
| action | string | Operation to perform |
| name | string | New name for consistency group. Required to resolve naming collisions. |
| storage_service | storage_service | Determines the placement of any storage object created during this operation. |

policy

The QoS policy

| Name | Type | Description |
|--------|---------------------------|-------------|
| _links | self_link | |

| Name | Type | Description |
|------|--------|---|
| name | string | The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH. |
| uuid | string | The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH. |

snapshot

A consistency group's snapshot

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the consistency group's snapshot to restore to. |
| uuid | string | The UUID of the consistency group's snapshot to restore to. |

restore_to

Use to restore a consistency group to a previous snapshot

| Name | Type | Description |
|----------|--------------------------|--------------------------------|
| snapshot | snapshot | A consistency group's snapshot |

snapshot_policy_reference

This is a reference to the snapshot policy.

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

space

Space information for the consistency group.

| Name | Type | Description |
|-----------|---------|---|
| available | integer | The amount of space available in the consistency group, in bytes. |
| size | integer | The total provisioned size of the consistency group, in bytes. |
| used | integer | The amount of space consumed in the consistency group, in bytes. |

svm

The Storage Virtual Machine (SVM) in which the consistency group is located.

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

object_stores

tiering

The tiering placement and policy definitions for volumes in this consistency group.

| Name | Type | Description |
|---------------|--|---|
| object_stores | array[object_stores] | Object stores to use. Used for placement. |

| Name | Type | Description |
|--------|--------|---|
| policy | string | <p>Policy that determines whether the user data blocks of a volume in a FabricPool will be tiered to the cloud store when they become cold.</p> <p>FabricPool combines flash (performance tier) with a cloud store into a single aggregate. Temperature of a volume block increases if it is accessed frequently and decreases when it is not. Valid in POST or PATCH.</p> <p>all &dash; Allows tiering of both snapshots and active file system user data to the cloud store as soon as possible by ignoring the temperature on the volume blocks.</p> <p>auto &dash; Allows tiering of both snapshot and active file system user data to the cloud store</p> <p>none &dash; Volume blocks are not be tiered to the cloud store.</p> <p>snapshot_only &dash; Allows tiering of only the volume snapshots not associated with the active file system.</p> <p>The default tiering policy is "snapshot-only" for a FlexVol volume and "none" for a FlexGroup volume. The default minimum cooling period for the "snapshot-only" tiering policy is 2 days and for the "auto" tiering policy it is 31 days.</p> |

acls

The permissions that users and groups have on a CIFS share.

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |

| Name | Type | Description |
|-----------------|--------|---|
| permission | string | <p>Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed:</p> <ul style="list-style-type: none"> • no_access - User does not have CIFS share access • read - User has only read access • change - User has change access • full_control - User has full_control access |
| type | string | <p>Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed:</p> <ul style="list-style-type: none"> • windows - Windows user or group • unix_user - UNIX user • unix_group - UNIX group |
| user_or_group | string | Specifies the user or group name to add to the access control list of a CIFS share. |
| win_sid_unix_id | string | Windows SID/UNIX ID depending on access-control type. |

consistency_group_cifs_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |

| Name | Type | Description |
|--------------------------|---------------------|--|
| access_based_enumeration | boolean | Specifies whether all folders inside this share are visible to a user based on that individual user's access right; prevents the display of folders or other shared resources that the user does not have access to. |
| acls | array <acls></acls> | |
| allow_unencrypted_access | boolean | Specifies whether or not the SMB2 clients are allowed to access the encrypted share. |
| change_notify | boolean | Specifies whether CIFS clients can request for change notifications for directories on this share. |
| comment | string | Specify the CIFS share descriptions. |
| continuously_available | boolean | Specifies whether or not the clients connecting to this share can open files in a persistent manner. Files opened in this way are protected from disruptive events, such as, failover and giveback. |
| dir_umask | integer | Directory mode creation mask to be viewed as an octal number. |
| encryption | boolean | Specifies whether SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share. |
| file_umask | integer | File mode creation mask to be viewed as an octal number. |

| Name | Type | Description |
|-------------------|---------|--|
| home_directory | boolean | <p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> • Default value: true • Introduced in: 9.12 • readCreate: 1 • x-nullable: true |
| name | string | Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically. |
| namespace_caching | boolean | Specifies whether or not the SMB clients connecting to this share can cache the directory enumeration results returned by the CIFS servers. |

| Name | Type | Description |
|--------------------|---------|--|
| no_strict_security | boolean | Specifies whether or not CIFS clients can follow Unix symlinks outside the share boundaries. |
| offline_files | string | <p>Offline Files The supported values are:</p> <ul style="list-style-type: none"> • none - Clients are not permitted to cache files for offline access. • manual - Clients may cache files that are explicitly selected by the user for offline access. • documents - Clients may automatically cache files that are used by the user for offline access. • programs - Clients may automatically cache files that are used by the user for offline access and may use those files in an offline mode even if the share is available. |
| oplocks | boolean | Specifies whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations. |
| show_snapshot | boolean | Specifies whether or not the snapshots can be viewed and traversed by clients. |
| unix_symlink | string | <p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> • local - Enables only local symbolic links which is within the same CIFS share. • widelink - Enables both local symlinks and widelinks. • disable - Disables local symlinks and widelinks. |

| Name | Type | Description |
|---------------|--------|---|
| vscan_profile | string | <p>Vscan File-Operations Profile The supported values are:</p> <ul style="list-style-type: none"> • no_scan - Virus scans are never triggered for accesses to this share. • standard - Virus scans can be triggered by open, close, and rename operations. • strict - Virus scans can be triggered by open, read, close, and rename operations. • writes_only - Virus scans can be triggered only when a file that has been modified is closed. |

cifs

| Name | Type | Description |
|--------|--|-------------|
| shares | array[consistency_group_cifs_shares] | |

export_clients

| Name | Type | Description |
|-------|--------|--|
| match | string | <p>Client Match Hostname, IP Address, Netgroup, or Domain. You can specify the match as a string value in any of the following formats:</p> <ul style="list-style-type: none"> • As a hostname; for instance, host1 • As an IPv4 address; for instance, 10.1.12.24 • As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1 • As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24 • As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64 • As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0 • As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng • As a domain name preceded by the . character; for instance, .example.com |

export_rules

| Name | Type | Description |
|-----------------------|------------------------|--|
| _links | _links | |
| allow_device_creation | boolean | Specifies whether or not device creation is allowed. |
| allow_suid | boolean | Specifies whether or not SetUID bits in SETATTR Op is to be honored. |
| anonymous_user | string | User ID To Which Anonymous Users Are Mapped. |

| Name | Type | Description |
|--------------------|---|---|
| chown_mode | string | Specifies who is authorized to change the ownership mode of a file. |
| clients | array[export_clients] | Array of client matches |
| index | integer | Index of the rule within the export policy. |
| ntfs_unix_security | string | NTFS export UNIX security options. |
| protocols | array[string] | |
| ro_rule | array[string] | Authentication flavors that the read-only access rule governs |
| rw_rule | array[string] | Authentication flavors that the read/write access rule governs |
| superuser | array[string] | Authentication flavors that the superuser security type governs |

export_policy

The policy associated with volumes to export them for protocol access.

| Name | Type | Description |
|--------|---------------------------------------|---|
| _links | self_link | |
| id | integer | Identifier for the export policy. |
| name | string | Name of the export policy. |
| rules | array[export_rules] | The set of rules that govern the export policy. |

junction_parent

| Name | Type | Description |
|--------|---------------------------|-------------|
| _links | self_link | |

| Name | Type | Description |
|------|--------|--|
| name | string | The name of the parent volume that contains the junction inode of this volume. The junction parent volume must belong to the same SVM that owns this volume. |
| uuid | string | Unique identifier for the parent volume. |

nas

The CIFS share policy and/or export policies for this volume.

| Name | Type | Description |
|-----------------|---------------------------------|---|
| cifs | cifs | |
| export_policy | export_policy | The policy associated with volumes to export them for protocol access. |
| gid | integer | The UNIX group ID of the volume. Valid in POST or PATCH. |
| junction_parent | junction_parent | |
| path | string | The fully-qualified path in the owning SVM's namespace at which the volume is mounted. The path is case insensitive and must be unique within an SVM's namespace. Path must begin with '/' and must not end with '/'. Only one volume can be mounted at any given junction path. An empty path in POST creates an unmounted volume. An empty path in PATCH deactivates and unmounts the volume. Taking a volume offline or restricted state removes its junction path. This attribute is reported in GET only when the volume is mounted. |

| Name | Type | Description |
|------------------|---------|---|
| security_style | string | Security style associated with the volume. Valid in POST or PATCH. mixed ‐ Mixed-style security ntfs ‐ NTFS/WIndows-style security unified ‐ Unified-style security, unified UNIX, NFS and CIFS permissions unix ‐ UNIX-style security. |
| uid | integer | The UNIX user ID of the volume. Valid in POST or PATCH. |
| unix_permissions | integer | UNIX permissions to be viewed as an octal number, consisting of 4 digits derived by adding up bits 4 (read), 2 (write), and 1 (execute). First digit selects the set user ID (4), set group ID (2), and sticky (1) attributes. Second digit selects permission for the owner of the file. Third selects permissions for other users in the same group while the fourth selects permissions for other users not in the group. Valid in POST or PATCH. For security style "mixed" or "unix", the default setting is 0755 in octal (493 in decimal) and for security style "ntfs", the default setting is 0000. In cases where only owner, group, and other permissions are given (as in 755, representing the second, third and fourth digit), the first digit is assumed to be zero. |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|--------|---------|---|
| action | string | Operation to perform |
| count | integer | Number of elements to perform the operation on. |

| Name | Type | Description |
|-----------------|-----------------|---|
| storage_service | storage_service | Determines the placement of any storage object created during this operation. |

qos

The QoS policy for this volume.

| Name | Type | Description |
|--------|--------|----------------|
| policy | policy | The QoS policy |

space

| Name | Type | Description |
|-----------|---------|--|
| available | integer | The available space, in bytes. |
| size | integer | Total provisioned size, in bytes. |
| used | integer | The virtual space used (includes volume reserves) before storage efficiency, in bytes. |

tiering

The tiering placement and policy definitions for this volume.

| Name | Type | Description |
|---------------|----------------------|---|
| object_stores | array[object_stores] | Object stores to use. Used for placement. |

| Name | Type | Description |
|--------|--------|---|
| policy | string | <p>Policy that determines whether the user data blocks of a volume in a FabricPool will be tiered to the cloud store when they become cold.</p> <p>FabricPool combines flash (performance tier) with a cloud store into a single aggregate. Temperature of a volume block increases if it is accessed frequently and decreases when it is not. Valid in POST or PATCH.</p> <p>all &dash; Allows tiering of both snapshots and active file system user data to the cloud store as soon as possible by ignoring the temperature on the volume blocks.</p> <p>auto &dash; Allows tiering of both snapshot and active file system user data to the cloud store</p> <p>none &dash; Volume blocks are not be tiered to the cloud store.</p> <p>snapshot_only &dash; Allows tiering of only the volume snapshots not associated with the active file system.</p> <p>The default tiering policy is "snapshot-only" for a FlexVol volume and "none" for a FlexGroup volume. The default minimum cooling period for the "snapshot-only" tiering policy is 2 days and for the "auto" tiering policy it is 31 days.</p> |

volumes

| Name | Type | Description |
|---------|--------|---|
| comment | string | A comment for the volume. Valid in POST or PATCH. |

| Name | Type | Description |
|-----------------|---|---|
| name | string | Volume name. The name of volume must start with an alphabetic character (a to z or A to Z) or an underscore (_). The name must be 197 or fewer characters in length for FlexGroup volumes, and 203 or fewer characters in length for all other types of volumes. Volume names must be unique within an SVM. Required on POST. |
| nas | nas | The CIFS share policy and/or export policies for this volume. |
| qos | qos | The QoS policy for this volume. |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| space | space | |
| tiering | tiering | The tiering placement and policy definitions for this volume. |
| uuid | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> • example: 028baa66-41bd-11e9-81d5-00a0986138f7 • readOnly: 1 • Introduced in: 9.8 • x-nullable: true |

consistency_groups

| Name | Type | Description |
|--------|---------------------------|--|
| _links | self_link | |
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |

| Name | Type | Description |
|-------------|-------------|---|
| application | application | |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |
| name | string | Name of the consistency group. The consistency group name must be unique within an SVM. |

| Name | Type | Description |
|--------------------------|--|--|
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| qos | qos | |
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |

| Name | Type | Description |
|-----------------|---|--|
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| space | space | Space information for the consistency group. |
| svm | svm | The Storage Virtual Machine (SVM) in which the consistency group is located. |
| tiering | tiering | The tiering placement and policy definitions for volumes in this consistency group. |
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> • example: 1cd8a442-86d1-11e0-ae1c-123478563412 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

iops

The rate of I/O operations observed at the storage object.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

latency

The round trip latency observed at the storage object, in microseconds.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

throughput

The rate of throughput bytes per second observed at the storage object.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |

| Name | Type | Description |
|-------|---------|---|
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

metric

Performance and capacity numbers, such as, IOPS, latency, throughput, used space, and available space.

| Name | Type | Description |
|-----------------|-------------------------|--|
| _links | _links | |
| available_space | integer | The total space available in the consistency group, in bytes. |
| duration | string | The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations: |
| iops | iops | The rate of I/O operations observed at the storage object. |
| latency | latency | The round trip latency observed at the storage object, in microseconds. |
| size | integer | The total size of the consistency group, in bytes. |

| Name | Type | Description |
|------------|------------|---|
| status | string | Errors associated with the sample. For example, if the aggregation of data over multiple nodes fails, then any partial errors might return "ok" on success or "error" on an internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data. |
| throughput | throughput | The rate of throughput bytes per second observed at the storage object. |
| timestamp | string | The timestamp of the performance and capacity data. |
| used_space | integer | The total space used in the consistency group, in bytes. |

replication_relationships

| Name | Type | Description |
|------------------------|---------------------------|--|
| _links | self_link | |
| is_protected_by_svm_dr | boolean | Indicates whether or not this consistency group is protected by SVM DR. |
| is_source | boolean | Indicates whether or not this consistency group is the source for replication. |

| Name | Type | Description |
|------|--------|---|
| uuid | string | The unique identifier of the SnapMirror relationship. |

iops_raw

The number of I/O operations observed at the storage object. This can be used along with delta time to calculate the rate of I/O operations per unit of time.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

latency_raw

The raw latency observed at the storage object, in microseconds. This can be divided by the raw IOPS value to calculate the average latency per I/O operation.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

throughput_raw

Throughput bytes observed at the storage object. This can be used along with delta time to calculate the rate of throughput bytes per unit of time.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

statistics

These are raw performance and space numbers, such as, IOPS, latency, throughput, used space, and available space. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.

| Name | Type | Description |
|-----------------|-------------|--|
| available_space | integer | The total space available in the consistency group, in bytes. |
| iops_raw | iops_raw | The number of I/O operations observed at the storage object. This can be used along with delta time to calculate the rate of I/O operations per unit of time. |
| latency_raw | latency_raw | The raw latency observed at the storage object, in microseconds. This can be divided by the raw IOPS value to calculate the average latency per I/O operation. |
| size | integer | The total size of the consistency group, in bytes. |

| Name | Type | Description |
|----------------|--------------------------------|---|
| status | string | Errors associated with the sample. For example, if the aggregation of data over multiple nodes fails, then any partial errors might return "ok" on success or "error" on an internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data. |
| throughput_raw | throughput_raw | Throughput bytes observed at the storage object. This can be used along with delta time to calculate the rate of throughput bytes per unit of time. |
| timestamp | string | The timestamp of the performance data. |
| used_space | integer | The total used space in the consistency group, in bytes. |

consistency_group_cifs_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

| Name | Type | Description |
|------------------------|------------------------|-------------|
| _links | _links | |

| Name | Type | Description |
|-------------------------|---------------------|--|
| access_basedEnumeration | boolean | Specifies whether all folders inside this share are visible to a user based on that individual user's access right; prevents the display of folders or other shared resources that the user does not have access to. |
| acls | array <acls></acls> | |
| allowUnencryptedAccess | boolean | Specifies whether or not the SMB2 clients are allowed to access the encrypted share. |
| changeNotify | boolean | Specifies whether CIFS clients can request for change notifications for directories on this share. |
| comment | string | Specify the CIFS share descriptions. |
| continuouslyAvailable | boolean | Specifies whether or not the clients connecting to this share can open files in a persistent manner. Files opened in this way are protected from disruptive events, such as, failover and giveback. |
| dirUmask | integer | Directory mode creation mask to be viewed as an octal number. |
| encryption | boolean | Specifies whether SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share. |
| fileUmask | integer | File mode creation mask to be viewed as an octal number. |

| Name | Type | Description |
|-------------------|---------|---|
| home_directory | boolean | <p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> • Default value: 1 • Introduced in: 9.12 • readCreate: 1 • x-nullable: true |
| name | string | Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically. |
| namespace_caching | boolean | Specifies whether or not the SMB clients connecting to this share can cache the directory enumeration results returned by the CIFS servers. |

| Name | Type | Description |
|--------------------|---------|--|
| no_strict_security | boolean | Specifies whether or not CIFS clients can follow Unix symlinks outside the share boundaries. |
| offline_files | string | <p>Offline Files The supported values are:</p> <ul style="list-style-type: none"> • none - Clients are not permitted to cache files for offline access. • manual - Clients may cache files that are explicitly selected by the user for offline access. • documents - Clients may automatically cache files that are used by the user for offline access. • programs - Clients may automatically cache files that are used by the user for offline access and may use those files in an offline mode even if the share is available. |
| oplocks | boolean | Specifies whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations. |
| show_snapshot | boolean | Specifies whether or not the snapshots can be viewed and traversed by clients. |
| unix_symlink | string | <p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> • local - Enables only local symbolic links which is within the same CIFS share. • widelink - Enables both local symlinks and widelinks. • disable - Disables local symlinks and widelinks. |

| Name | Type | Description |
|---------------|--------|---|
| vscan_profile | string | <p>Vscan File-Operations Profile The supported values are:</p> <ul style="list-style-type: none"> • no_scan - Virus scans are never triggered for accesses to this share. • standard - Virus scans can be triggered by open, close, and rename operations. • strict - Virus scans can be triggered by open, read, close, and rename operations. • writes_only - Virus scans can be triggered only when a file that has been modified is closed. |

export_clients

| Name | Type | Description |
|-------|--------|--|
| match | string | <p>Client Match Hostname, IP Address, Netgroup, or Domain. You can specify the match as a string value in any of the following formats:</p> <ul style="list-style-type: none"> • As a hostname; for instance, host1 • As an IPv4 address; for instance, 10.1.12.24 • As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1 • As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24 • As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64 • As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0 • As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng • As a domain name preceded by the . character; for instance, .example.com |

records

| Name | Type | Description |
|-------------|-----------------------------|--|
| _links | self_link | |
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |
| application | application | |

| Name | Type | Description |
|--------------------|---|---|
| clone | clone | Creates a clone of an existing consistency group from the current contents or an existing snapshot. |
| consistency_groups | array[consistency_groups] | A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A consistency group can only be associated with one direct parent consistency group. |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |
| metric | metric | Performance and capacity numbers, such as, IOPS, latency, throughput, used space, and available space. |
| name | string | Name of the consistency group. The consistency group name must be unique within an SVM. |

| Name | Type | Description |
|--------------------------|--|--|
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| qos | qos | |
| replicated | boolean | Indicates whether or not replication has been enabled on this consistency group. |

| Name | Type | Description |
|---------------------------|----------------------------------|---|
| replication_relationships | array[replication_relationships] | Indicates the SnapMirror relationship of this consistency group. |
| replication_source | boolean | Since support for this field is to be removed in the next release, use replication_relationships.is_source instead. |
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| space | space | Space information for the consistency group. |
| statistics | statistics | These are raw performance and space numbers, such as, IOPS, latency, throughput, used space, and available space. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster. |
| svm | svm | The Storage Virtual Machine (SVM) in which the consistency group is located. |
| tiering | tiering | The tiering placement and policy definitions for volumes in this consistency group. |
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> example: 1cd8a442-86d1-11e0-ae1c-123478563412 readOnly: 1 Introduced in: 9.6 x-nullable: true |

| Name | Type | Description |
|---------|----------------|--|
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Create a consistency group

POST /application/consistency-groups

Introduced In: 9.10

Creates a consistency group with one or more consistency groups having:

- new SAN volumes,
- existing SAN, NVMe or NAS FlexVol volumes in a new or existing consistency group

Required properties

- `svm.uuid` or `svm.name` - Existing SVM in which to create the group.
- `volumes`, `luns` or `namespaces`

Naming Conventions

Consistency groups

- `name` or `consistency_groups[]`.`name`, if specified
- derived from `volumes[0].name`, if only one volume is specified, same as volume name

Volume

- `volumes[]`.`name`, if specified
- derived from volume prefix in `luns[]`.`name`
- derived from `cg[]`.`name`, suffixed by `_#` where `#` is a system generated unique number
- suffixed by `_#` where `#` is a system generated unique number, if `provisioning_options.count` is provided

LUN

- `luns[]`.`name`, if specified
- derived from `volumes[]`.`name`, suffixed by `_#` where `#` is a system generated unique number
- suffixed by `_#` where `#` is a system generated unique number, if `provisioning_options.count` is provided

NVMe Namespace

- `namespaces[]`.`name`, if specified
- derived from `volumes[]`.`name`, suffixed by `_#` where `#` is a system generated unique number
- suffixed by `_#` where `#` is a system generated unique number, if `provisioning_options.count` is provided

Related ONTAP commands

There are no ONTAP commands for managing consistency group.

Parameters

| Name | Type | In | Required | Description |
|----------------|---------|-------|----------|--|
| return_timeout | integer | query | False | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> • Default value: 1 • Max value: 120 • Min value: 0 |
| return_records | boolean | query | False | <p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> • Default value: |

Request Body

| Name | Type | Description |
|-------|---------------|--|
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |

| Name | Type | Description |
|--------------------|---|---|
| application | application | |
| clone | clone | Creates a clone of an existing consistency group from the current contents or an existing snapshot. |
| consistency_groups | array[consistency_groups] | A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A consistency group can only be associated with one direct parent consistency group. |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |
| name | string | Name of the consistency group. The consistency group name must be unique within an SVM. |

| Name | Type | Description |
|--------------------------|--|--|
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | |
| replicated | boolean | Indicates whether or not replication has been enabled on this consistency group. |

| Name | Type | Description |
|---------------------------|--|--|
| replication_relationships | array[replication_relationships] | Indicates the SnapMirror relationship of this consistency group. |
| replication_source | boolean | Since support for this field is to be removed in the next release, use replication_relationships.is_source instead. |
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| svm | svm | The Storage Virtual Machine (SVM) in which the consistency group is located. |
| tiering | tiering | The tiering placement and policy definitions for volumes in this consistency group. |
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> example: 1cd8a442-86d1-11e0-ae1c-123478563412 readOnly: 1 Introduced in: 9.10 x-nullable: true |
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

Example request

```
{  
  "_tags": [  
    "team:csi",  
    "environment:test"  
,  
  "application": {  
    "component_type": "string",  
    "type": "string"  
,  
  "clone": {  
    "guarantee": {  
      "type": "string"  
,  
    "parent_consistency_group": {  
      "name": "string",  
      "uuid": "string"  
,  
    "parent_snapshot": {  
      "name": "this_snapshot",  
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"  
,  
    "parent_svm": {  
      "name": "svm1",  
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
,  
    "split_complete_percent": 0,  
    "split_estimate": 0,  
    "volume": {  
      "prefix": "string",  
      "suffix": "string"  
,  
    },  
  },  
  "consistency_groups": [  
    {  
      "_tags": [  
        "team:csi",  
        "environment:test"  
,  
      "application": {  
        "component_type": "string",  
        "type": "string"  
,  
      "luns": [  
        {  

```

```

"clone": {
    "source": {
        "name": "/vol/volume1/lun1",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"comment": "string",
"create_time": "2018-06-04 15:00:00 -0400",
"lun_maps": [
    {
        "igroup": {
            "comment": "string",
            "igroups": [
                {
                    "name": "igroup1",
                    "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
                }
            ],
            "initiators": [
                {
                    "comment": "my comment",
                    "name": "iqn.1998-01.com.corp.iscsi:name1"
                }
            ],
            "name": "igroup1",
            "os_type": "string",
            "protocol": "string",
            "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
        }
    }
],
"name": "/vol/volume1/lun1",
"os_type": "string",
"provisioning_options": {
    "action": "string"
},
"qos": {
    "policy": {
        "max_throughput_iops": 10000,
        "max_throughput_mbps": 500,
        "min_throughput_iops": 2000,
        "min_throughput_mbps": 500,
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
}
},

```

```

    "serial_number": "string",
    "space": {
        "size": 1073741824,
        "used": 0
    },
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
],
"name": "string",
"namespaces": [
{
    "comment": "string",
    "create_time": "2018-06-04 15:00:00 -0400",
    "name": "/vol/volume1/qtree1/namespacel",
    "os_type": "string",
    "provisioning_options": {
        "action": "string"
    },
    "space": {
        "block_size": 512,
        "size": 1073741824,
        "used": 0
    },
    "subsystem_map": {
        "anagrpid": "00103050h",
        "nsid": "00000001h",
        "subsystem": {
            "comment": "string",
            "hosts": [
{
                "dh_hmac_chap": {
                    "controller_secret_key": "DHHC-1:00:ia6zGodOr4SEG0Zzaw398rpY0wqipUWj4jWjUh4HWUz6aQ2n:",
                    "group_size": "string",
                    "hash_function": "string",
                    "host_secret_key": "DHHC-1:00:ia6zGodOr4SEG0Zzaw398rpY0wqipUWj4jWjUh4HWUz6aQ2n:",
                    "mode": "bidirectional"
                },
                "nqn": "nqn.1992-01.example.com:string",
                "priority": "string",
                "tls": {
                    "configured_psk": "NVMeTLSkey-1:01:VRLbtnN9AQb2WXW3c9+wEf/DRLz0QuLdbYvEhwtdWwNf9LrZ:",
                    "key_type": "configured"
                }
            }
        }
    }
}
]
}

```

```

        }
    ],
    "name": "subsystem1",
    "os_type": "string",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
],
"parent_consistency_group": {
    "name": "my_consistency_group",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"provisioning_options": {
    "action": "string",
    "name": "string",
    "storage_service": {
        "name": "string"
    }
},
"qos": {
    "policy": {
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"restore_to": {
    "snapshot": {
        "name": "string",
        "uuid": "string"
    }
},
"snapshot_policy": {
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"svm": {
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"tiering": {
    "control": "string",
    "object_stores": [
        {
            "name": "string"
        }
    ]
}
}

```

```
        }
    ],
    "policy": "string"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412",
"volumes": [
{
    "comment": "string",
    "name": "vol_cs_dept",
    "nas": {
        "cifs": {
            "shares": [
{
                "acls": [
{
                    "permission": "string",
                    "type": "string",
                    "user_or_group": "ENGDOMAIN\\ad_user"
                }
            ],
            "comment": "HR Department Share",
            "dir_umask": 18,
            "file_umask": 18,
            "name": "HR_SHARE",
            "offline_files": "string",
            "unix_symlink": "string",
            "vscan_profile": "string"
}
        }
    ]
},
"export_policy": {
    "id": 0,
    "name": "string",
    "rules": [
{
    "anonymous_user": "string",
    "chown_mode": "string",
    "clients": [
{
        "match": "0.0.0.0/0"
}
],
    "ntfs_unix_security": "string",
    "protocols": [
        "string"
]
}
]
```

```

        "ro_rule": [
            "string"
        ],
        "rw_rule": [
            "string"
        ],
        "superuser": [
            "string"
        ]
    }
},
"junction_parent": {
    "name": "vs1_root",
    "uuid": "75c9cfb0-3eb4-11eb-9fb4-005056bb088a"
},
"path": "/user/my_volume",
"security_style": "string",
"unix_permissions": 493
},
"provisioning_options": {
    "action": "string",
    "storage_service": {
        "name": "string"
    }
},
"qos": {
    "policy": {
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"snapshot_policy": {
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"space": {
    "available": 0,
    "used": 0
},
"tiering": {
    "control": "string",
    "object_stores": [
        {
            "name": "string"
        }
    ]
}

```

```
        ],
        "policy": "string"
    },
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
],
}
],
"luns": [
{
    "clone": {
        "source": {
            "name": "/vol/volumel/lun1",
            "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
        }
    },
    "comment": "string",
    "create_time": "2018-06-04 15:00:00 -0400",
    "lun_maps": [
        {
            "igroup": {
                "comment": "string",
                "igroups": [
                    {
                        "name": "igroup1",
                        "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
                    }
                ],
                "initiators": [
                    {
                        "comment": "my comment",
                        "name": "iqn.1998-01.com.corp.iscsi:name1"
                    }
                ],
                "name": "igroup1",
                "os_type": "string",
                "protocol": "string",
                "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
            }
        }
    ],
    "name": "/vol/volumel/lun1",
    "os_type": "string",
    "provisioning_options": {
        "action": "string"
    }
},
```

```

    "qos": {
        "policy": {
            "max_throughput_iops": 10000,
            "max_throughput_mbps": 500,
            "min_throughput_iops": 2000,
            "min_throughput_mbps": 500,
            "name": "performance",
            "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
        }
    },
    "serial_number": "string",
    "space": {
        "size": 1073741824,
        "used": 0
    },
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
],
"name": "string",
"namespaces": [
{
    "comment": "string",
    "create_time": "2018-06-04 15:00:00 -0400",
    "name": "/vol/volumel/qtree1/namespacel",
    "os_type": "string",
    "provisioning_options": {
        "action": "string"
    },
    "space": {
        "block_size": 512,
        "size": 1073741824,
        "used": 0
    },
    "subsystem_map": {
        "anagrpid": "00103050h",
        "nsid": "00000001h",
        "subsystem": {
            "comment": "string",
            "hosts": [
{
                "dh_hmac_chap": {
                    "controller_secret_key": "DHHC-1:00:ia6zGodOr4SEG0Zzaw398rpY0wqipUWj4jWjUh4HWUz6aQ2n:",
                    "group_size": "string",
                    "hash_function": "string",
                    "host_secret_key": "DHHC-"
                }
            ]
        }
    }
}
]

```

```
1:00:ia6zGodOr4SEG0Zzaw398rpY0wqipUWj4jwjUh4HWUz6aQ2n:",
    "mode": "bidirectional"
},
"nqn": "nqn.1992-01.example.com:string",
"priority": "string",
"tls": {
    "configured_psk": "NVMeTLSkey-
1:01:VRLbtnN9AQb2WXW3c9+wEf/DRLz0QuLdbYvEhwtdWwNf9LrZ:",
        "key_type": "configured"
    }
},
],
"name": "subsystem1",
"os_type": "string",
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
],
"parent_consistency_group": {
    "name": "my_consistency_group",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"provisioning_options": {
    "action": "string",
    "name": "string",
    "storage_service": {
        "name": "string"
    }
},
"qos": {
    "policy": {
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
],
"replication_relationships": [
{
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
],
"restore_to": {
    "snapshot": {
        "name": "string",
        "uuid": "string"
    }
}
```

```

        }
    },
    "snapshot_policy": {
        "name": "default",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "svm": {
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "tiering": {
        "control": "string",
        "object_stores": [
            {
                "name": "string"
            }
        ],
        "policy": "string"
    },
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412",
    "volumes": [
        {
            "comment": "string",
            "name": "vol_cs_dept",
            "nas": {
                "cifs": {
                    "shares": [
                        {
                            "acl": [
                                {
                                    "permission": "string",
                                    "type": "string",
                                    "user_or_group": "ENGDOMAIN\\ad_user"
                                }
                            ],
                            "comment": "HR Department Share",
                            "dir_umask": 18,
                            "file_umask": 18,
                            "name": "HR_SHARE",
                            "offline_files": "string",
                            "unix_symlink": "string",
                            "vscan_profile": "string"
                        }
                    ]
                }
            }
        },
        "export_policy": {

```

```
"id": 0,
"name": "string",
"rules": [
  {
    "anonymous_user": "string",
    "chown_mode": "string",
    "clients": [
      {
        "match": "0.0.0.0/0"
      }
    ],
    "ntfs_unix_security": "string",
    "protocols": [
      "string"
    ],
    "ro_rule": [
      "string"
    ],
    "rw_rule": [
      "string"
    ],
    "superuser": [
      "string"
    ]
  }
],
"junction_parent": {
  "name": "vs1_root",
  "uuid": "75c9cfb0-3eb4-11eb-9fb4-005056bb088a"
},
"path": "/user/my_volume",
"security_style": "string",
"unix_permissions": 493
},
"provisioning_options": {
  "action": "string",
  "storage_service": {
    "name": "string"
  }
},
"qos": {
  "policy": {
    "name": "performance",
    "uuid": "1cd8a442-86d1-11e0-aelc-123478563412"
  }
}
```

```

    },
    "snapshot_policy": {
        "name": "default",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "space": {
        "available": 0,
        "used": 0
    },
    "tiering": {
        "control": "string",
        "object_stores": [
            {
                "name": "string"
            }
        ],
        "policy": "string"
    },
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
]
}

```

Response

Status: 202, Accepted

| Name | Type | Description |
|------|----------|-------------|
| job | job_link | |

Example response

```
{
    "job": {
        "uuid": "string"
    }
}
```

Headers

| Name | Description | Type |
|----------|---|--------|
| Location | Useful for tracking the resource location | string |

Response

Status: 201, Created

Error

Status: Default

ONTAP Error Response Codes

| Error Code | Description |
|------------|--|
| 5374127 | The specified LUN name is invalid. |
| 5440501 | The specified storage unit size is insufficient. |
| 5440509 | No suitable storage can be found for the specified requirements. |
| 53411842 | Consistency group does not exist. |
| 53411843 | A consistency group with specified UUID was not found. |
| 53411844 | Specified consistency group was not found in the specified SVM. |
| 53411845 | The specified UUID and name refer to different consistency groups. |
| 53411846 | Either name or UUID must be provided. |
| 53411853 | Fields provided in the request conflict with each other. |
| 53411856 | Field provided is only supported when provisioning new objects. |
| 53411857 | LUNs that are not members of the application are not supported by this API. LUNs can be added to an application by adding the volume containing the LUNs to the application. |
| 53411860 | An object with the same identifier in the same scope exists. |
| 53411861 | Volume specified does not exist in provided volume array. |
| 53411862 | Modifying existing igroups is not supported using this API. |

| Error Code | Description |
|------------|--|
| 53411864 | Request content insufficient to add an existing volume to an application. |
| 53411865 | Volumes contained in one consistency group can not be added to a different consistency group. |
| 53411866 | LUNs are not supported on FlexGroups volumes. |
| 53411867 | LUN name is too long after appending a unique suffix. |
| 53411869 | Volume name is too long after appending a unique suffix. |
| 53411870 | When using the "round_robin" layout, the volume count must not be greater than the LUN count. |
| 53411959 | Volumes with snapshot locking enabled cannot be added to a consistency group. |
| 53412040 | Splitting a non-snaplock clone from a Snaplock consistency group during clone creation is not supported. |

Also see the table of common errors in the [Response body](#) overview section of this documentation.

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

self_link

application

| Name | Type | Description |
|----------------|--------|----------------------------------|
| component_type | string | Nested consistency group tag. |
| type | string | Top level consistency group tag. |

guarantee

| Name | Type | Description |
|------|--------|--|
| type | string | The type of space guarantee of this volume in the aggregate. |

parent_consistency_group

Consistency group that is to be cloned.

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the consistency group. |
| uuid | string | The unique identifier of the consistency group. |

_links

parent_snapshot

Consistency group that is to be cloned.

| Name | Type | Description |
|------|--------|-------------|
| name | string | |
| uuid | string | |

parent_svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

Volume name suffix/prefix for the cloned volumes.

| Name | Type | Description |
|--------|--------|--|
| prefix | string | Volume name prefix for cloned volumes. |
| suffix | string | Volume name suffix for cloned volumes. |

clone

Creates a clone of an existing consistency group from the current contents or an existing snapshot.

| Name | Type | Description |
|--------------------------|--|--|
| guarantee | guarantee | |
| is_flexclone | boolean | Specifies if this consistency group is a FlexClone of a consistency group. |
| parent_consistency_group | parent_consistency_group | Consistency group that is to be cloned. |
| parent_snapshot | parent_snapshot | Consistency group that is to be cloned. |
| parent_svm | parent_svm | SVM, applies only to SVM-scoped objects. |
| split_complete_percent | integer | Percentage of FlexClone blocks split from its parent consistency group. |
| split_estimate | integer | Space required to split the FlexClone consistency group. |

| Name | Type | Description |
|-----------------|---------|--|
| split_initiated | boolean | Splits volumes after cloning. Defaults to false during POST. Only accepts true during a PATCH. |
| volume | volume | Volume name suffix/prefix for the cloned volumes. |

source

The source LUN for a LUN clone operation. This can be specified using property `clone.source.uuid` or `clone.source.name`. If both properties are supplied, they must refer to the same LUN.

Valid in POST to create a new LUN as a clone of the source.

Valid in PATCH to overwrite an existing LUN's data as a clone of another.

| Name | Type | Description |
|------|--------|--|
| name | string | <p>The name of the clone source LUN. A LUN is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>LUN names are paths of the form "/vol/<volume>[/<qtree>]/<name>" where the qtree name is optional.</p> <p>Valid in POST and PATCH.</p> |
| uuid | string | The unique identifier of the clone source LUN. Valid in POST and PATCH. |

clone

This sub-object is used in POST to create a new LUN as a clone of an existing LUN, or PATCH to overwrite an existing LUN as a clone of another. Setting a property in this sub-object indicates that a LUN clone is desired. Consider the following other properties when cloning a LUN: `auto_delete`, `qos_policy`, `space.guarantee.requested` and `space.scsi_thin_provisioning_support_enabled`.

When used in a PATCH, the patched LUN's data is over-written as a clone of the source and the following properties are preserved from the patched LUN unless otherwise specified as part of the PATCH: `class`, `auto_delete`, `lun_maps`, `serial_number`, `status.state`, and `uuid`.

Persistent reservations for the patched LUN are also preserved.

| Name | Type | Description |
|--------|--------|---|
| source | source | <p>The source LUN for a LUN clone operation. This can be specified using property <code>clone.source.uuid</code> or <code>clone.source.name</code>. If both properties are supplied, they must refer to the same LUN.</p> <p>Valid in POST to create a new LUN as a clone of the source.</p> <p>Valid in PATCH to overwrite an existing LUN's data as a clone of another.</p> |

igroups

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the initiator group. |
| uuid | string | The unique identifier of the initiator group. |

initiators

The initiators that are members of the initiator group.

| Name | Type | Description |
|---------|--------|--|
| comment | string | A comment available for use by the administrator. |
| name | string | Name of initiator that is a member of the initiator group. |

igroup

The initiator group that directly owns the initiator, which is where modification of the initiator is supported. This property will only be populated when the initiator is a member of a nested initiator group.

| Name | Type | Description |
|---------|--------|--|
| comment | string | A comment available for use by the administrator. Valid in POST and PATCH. |

| Name | Type | Description |
|------------|-------------------------------------|---|
| igroups | array[igroups] | <p>The existing initiator groups that are members of the group. Optional in POST.</p> <p>This property is mutually exclusive with the <i>initiators</i> property during POST.</p> <p>This array contains only the direct children of the initiator group. If the member initiator groups have further nested initiator groups, those are reported in the <i>igroups</i> property of the child initiator group.</p> <p>Zero or more nested initiator groups can be supplied when the initiator group is created. The initiator group will act as if it contains the aggregation of all initiators in any nested initiator groups.</p> <p>After creation, nested initiator groups can be added or removed from the initiator group using the <code>/protocols/san/igroups/{igroup.uuid}/igroups</code> endpoint. See DELETE /protocols/san/igroups/{igroup.uuid}/igroups/{uuid} for more details.</p> |
| initiators | array[initiators] | The initiators that are members of the group. |
| name | string | The name of the initiator group. Required in POST; optional in PATCH. |
| os_type | string | The host operating system of the initiator group. All initiators in the group should be hosts of the same operating system. Required in POST; optional in PATCH. |

| Name | Type | Description |
|----------|--------|---|
| protocol | string | <p>The protocols supported by the initiator group. This restricts the type of initiators that can be added to the initiator group. Optional in POST; if not supplied, this defaults to <i>mixed</i>.</p> <p>The protocol of an initiator group cannot be changed after creation of the group.</p> |
| uuid | string | The unique identifier of the initiator group. |

lun_maps

A LUN map is an association between a LUN and an initiator group.

When a LUN is mapped to an initiator group, the initiator group's initiators are granted access to the LUN. The relationship between a LUN and an initiator group is many LUNs to many initiator groups.

| Name | Type | Description |
|---------------------|---------|--|
| igroup | igroup | <p>The initiator group that directly owns the initiator, which is where modification of the initiator is supported. This property will only be populated when the initiator is a member of a nested initiator group.</p> |
| logical_unit_number | integer | <p>The logical unit number assigned to the LUN when mapped to the specified initiator group. The number is used to identify the LUN to initiators in the initiator group when communicating through the Fibre Channel Protocol or iSCSI. Optional in POST; if no value is provided, ONTAP assigns the lowest available value. This property is not supported when the <i>provisioning_options.count</i> property is 2 or more.</p> <ul style="list-style-type: none"> • Introduced in: 9.6 • readCreate: 1 • x-nullable: true |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|--------|---------|---|
| action | string | Operation to perform |
| count | integer | Number of elements to perform the operation on. |

policy

The QoS policy

| Name | Type | Description |
|---------------------|---------|---|
| max_throughput_iops | integer | Specifies the maximum throughput in IOPS, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| max_throughput_mbps | integer | Specifies the maximum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| min_throughput_iops | integer | Specifies the minimum throughput in IOPS, 0 means none. Setting "min_throughput" is supported on AFF platforms only, unless FabricPool tiering policies are set. This is mutually exclusive with name and UUID during POST and PATCH. |
| min_throughput_mbps | integer | Specifies the minimum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| name | string | The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH. |

| Name | Type | Description |
|------|--------|---|
| uuid | string | The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH. |

qos

| Name | Type | Description |
|--------|--------|----------------|
| policy | policy | The QoS policy |

guarantee

Properties that request and report the space guarantee for the LUN.

| Name | Type | Description |
|-----------|---------|--|
| requested | boolean | The requested space reservation policy for the LUN. If <i>true</i> , a space reservation is requested for the LUN; if <i>false</i> , the LUN is thin provisioned. Guaranteeing a space reservation request for a LUN requires that the volume in which the LUN resides is also space reserved and that the fractional reserve for the volume is 100%. Valid in POST and PATCH. |
| reserved | boolean | Reports if the LUN is space guaranteed. If <i>true</i> , a space guarantee is requested and the containing volume and aggregate support the request. If <i>false</i> , a space guarantee is not requested or a space guarantee is requested and either the containing volume or aggregate do not support the request. |

space

The storage space related properties of the LUN.

| Name | Type | Description |
|-----------|-----------|---|
| guarantee | guarantee | Properties that request and report the space guarantee for the LUN. |
| size | integer | <p>The total provisioned size of the LUN. The LUN size can be increased but not reduced using the REST interface. The maximum and minimum sizes listed here are the absolute maximum and absolute minimum sizes, in bytes. The actual minimum and maximum sizes vary depending on the ONTAP version, ONTAP platform, and the available space in the containing volume and aggregate. For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • example: 1073741824 • format: int64 • Max value: 140737488355328 • Min value: 4096 • Introduced in: 9.6 • x-nullable: true |

| Name | Type | Description |
|------|---------|---|
| used | integer | <p>The amount of space consumed by the main data stream of the LUN.</p> <p>This value is the total space consumed in the volume by the LUN, including filesystem overhead, but excluding prefix and suffix streams. Due to internal filesystem overhead and the many ways SAN filesystems and applications utilize blocks within a LUN, this value does not necessarily reflect actual consumption/availability from the perspective of the filesystem or application. Without specific knowledge of how the LUN blocks are utilized outside of ONTAP, this property should not be used as an indicator for an out-of-space condition.</p> <p>For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • format: int64 • readOnly: 1 • Introduced in: 9.6 • x-nullable: true |

luns

A LUN is the logical representation of storage in a storage area network (SAN).

A LUN must be mapped to an initiator group to grant access to the initiator group's initiators (client hosts). Initiators can then access the LUN and perform I/O over a Fibre Channel (FC) fabric using the FC Protocol or a TCP/IP network using iSCSI.

See the LUN object model to learn more about each of the properties supported by the LUN REST API.

A LUN is located within a volume. Optionally, it can be located within a qtree in a volume.

LUN names are paths of the form "/vol/<volume>[/<qtree>]/<lun>" where the qtree name is optional.

A LUN can be created to a specified size using thin or thick provisioning. A LUN can then be renamed, resized, cloned, moved to a different volume and copied. LUNs support the assignment of a QoS policy for performance management or a QoS policy can be assigned to a volume containing one or more LUNs.

```
</lun></qtree></volume>
```

| Name | Type | Description |
|-------------|--------|---|
| clone | clone | <p>This sub-object is used in POST to create a new LUN as a clone of an existing LUN, or PATCH to overwrite an existing LUN as a clone of another. Setting a property in this sub-object indicates that a LUN clone is desired. Consider the following other properties when cloning a LUN: <code>auto_delete</code>, <code>qos_policy</code>, <code>space.guarantee.requested</code> and <code>space.scsi_thin_provisioning_support_enabled</code>.</p> <p>When used in a PATCH, the patched LUN's data is overwritten as a clone of the source and the following properties are preserved from the patched LUN unless otherwise specified as part of the PATCH: <code>class</code>, <code>auto_delete</code>, <code>lun_maps</code>, <code>serial_number</code>, <code>status.state</code>, and <code>uuid</code>.</p> <p>Persistent reservations for the patched LUN are also preserved.</p> |
| comment | string | A configurable comment available for use by the administrator. Valid in POST and PATCH. |
| create_time | string | The time the LUN was created. |

| Name | Type | Description |
|----------------------|--------------------------------------|--|
| enabled | boolean | The enabled state of the LUN. LUNs can be disabled to prevent access to the LUN. Certain error conditions also cause the LUN to become disabled. If the LUN is disabled, you can consult the state property to determine if the LUN is administratively disabled (<i>offline</i>) or has become disabled as a result of an error. A LUN in an error condition can be brought online by setting the enabled property to <i>true</i> or brought administratively offline by setting the enabled property to <i>false</i> . Upon creation, a LUN is enabled by default. Valid in PATCH. |
| lun_maps | array[lun_maps] | An array of LUN maps. A LUN map is an association between a LUN and an initiator group. When a LUN is mapped to an initiator group, the initiator group's initiators are granted access to the LUN. The relationship between a LUN and an initiator group is many LUNs to many initiator groups. |
| name | string | The fully qualified path name of the LUN composed of the "/vol" prefix, the volume name, the qtree name (optional), and the base name of the LUN. Valid in POST and PATCH. |
| os_type | string | The operating system type of the LUN. Required in POST when creating a LUN that is not a clone of another. Disallowed in POST when creating a LUN clone. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | |

| Name | Type | Description |
|---------------|-----------------------|--|
| serial_number | string | <p>The LUN serial number. The serial number is generated by ONTAP when the LUN is created.</p> <ul style="list-style-type: none"> • maxLength: 12 • minLength: 12 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |
| space | space | The storage space related properties of the LUN. |
| uuid | string | <p>The unique identifier of the LUN. The UUID is generated by ONTAP when the LUN is created.</p> <ul style="list-style-type: none"> • example: 1cd8a442-86d1-11e0-ae1c-123478563412 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |

guarantee

Properties that request and report the space guarantee for the NVMe namespace.

| Name | Type | Description |
|-----------|---------|--|
| requested | boolean | <p>The requested space reservation policy for the NVMe namespace. If <i>true</i>, a space reservation is requested for the namespace; if <i>false</i>, the namespace is thin provisioned. Guaranteeing a space reservation request for a namespace requires that the volume in which the namespace resides also be space reserved and that the fractional reserve for the volume be 100%.</p> <p>The space reservation policy for an NVMe namespace is determined by ONTAP.</p> <ul style="list-style-type: none"> • Introduced in: 9.6 • x-nullable: true |
| reserved | boolean | <p>Reports if the NVMe namespace is space guaranteed.</p> <p>This property is <i>true</i> if a space guarantee is requested and the containing volume and aggregate support the request. This property is <i>false</i> if a space guarantee is not requested or if a space guarantee is requested and either the containing volume and aggregate do not support the request.</p> |

space

The storage space related properties of the NVMe namespace.

| Name | Type | Description |
|------------|---------|---|
| block_size | integer | <p>The size of blocks in the namespace, in bytes.</p> <p>Valid in POST when creating an NVMe namespace that is not a clone of another. Disallowed in POST when creating a namespace clone. Valid in POST.</p> |

| Name | Type | Description |
|-----------|-----------|--|
| guarantee | guarantee | Properties that request and report the space guarantee for the NVMe namespace. |
| size | integer | <p>The total provisioned size of the NVMe namespace. Valid in POST and PATCH. The NVMe namespace size can be increased but not reduced using the REST interface.</p> <p>The maximum and minimum sizes listed here are the absolute maximum and absolute minimum sizes, in bytes. The maximum size is variable with respect to large NVMe namespace support in ONTAP. If large namespaces are supported, the maximum size is 128 TB (140737488355328 bytes) and if not supported, the maximum size is just under 16 TB (17557557870592 bytes). The minimum size supported is always 4096 bytes.</p> <p>For more information, see Size properties in the docs section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • example: 1073741824 • format: int64 • Max value: 140737488355328 • Min value: 4096 • Introduced in: 9.6 • x-nullable: true |

| Name | Type | Description |
|------|---------|--|
| used | integer | <p>The amount of space consumed by the main data stream of the NVMe namespace.</p> <p>This value is the total space consumed in the volume by the NVMe namespace, including filesystem overhead, but excluding prefix and suffix streams. Due to internal filesystem overhead and the many ways NVMe filesystems and applications utilize blocks within a namespace, this value does not necessarily reflect actual consumption/availability from the perspective of the filesystem or application. Without specific knowledge of how the namespace blocks are utilized outside of ONTAP, this property should not be used as an indicator for an out-of-space condition.</p> <p>For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • format: int64 • readOnly: 1 • Introduced in: 9.6 • x-nullable: true |

status

Status information about the NVMe namespace.

| Name | Type | Description |
|-----------------|--------|---|
| container_state | string | The state of the volume and aggregate that contain the NVMe namespace. Namespaces are only available when their containers are available. |

| Name | Type | Description |
|-----------|---------|---|
| mapped | boolean | <p>Reports if the NVMe namespace is mapped to an NVMe subsystem.</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for either a collection GET or an instance GET unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| read_only | boolean | Reports if the NVMe namespace allows only read access. |
| state | string | The state of the NVMe namespace. Normal states for a namespace are <i>online</i> and <i>offline</i> . Other states indicate errors. |

consistency_group_nvme_host_dh_hmac_chap

A container for the configuration of NVMe in-band authentication using the DH-HMAC-CHAP protocol for a host.

| Name | Type | Description |
|-----------------------|--------|---|
| controller_secret_key | string | <p>The controller secret for NVMe in-band authentication. The value of this property is used by the NVMe host to authenticate the NVMe controller while establishing a connection. If unset, the controller is not authenticated. When supplied, the property <code>host_secret_key</code> must also be supplied. Optional in POST.</p> <p>This property is write-only. The <code>mode</code> property can be used to identify if a controller secret has been set for the host, but the controller secret value cannot be read. To change the value, the host must be deleted from the subsystem and re-added.</p> |

| Name | Type | Description |
|-----------------|--------|---|
| group_size | string | <p>The Diffie-Hellman group size for NVMe in-band authentication. When property <code>host_secret_key</code> is provided, this property defaults to <code>2048_bit</code>. When supplied, the property <code>host_secret_key</code> must also be supplied. Optional in POST.</p> |
| hash_function | string | <p>The hash function for NVMe in-band authentication. When property <code>host_secret_key</code> is provided, this property defaults to <code>sha_256</code>. When supplied, the property <code>host_secret_key</code> must also be supplied. Optional in POST.</p> |
| host_secret_key | string | <p>The host secret for NVMe in-band authentication. The value of this property is used by the NVMe controller to authenticate the NVMe host while establishing a connection. If unset, no authentication is performed by the host or controller. This property must be supplied if any other NVMe in-band authentication properties are supplied. Optional in POST.</p> <p>This property is write-only. The <code>mode</code> property can be used to identify if a host secret has been set for the host, but the host secret value cannot be read. To change the value, the host must be deleted from the subsystem and re-added.</p> |

| Name | Type | Description |
|------|--------|---|
| mode | string | <p>The expected NVMe in-band authentication mode for the host. This property is an indication of which secrets are configured for the host. When set to:</p> <ul style="list-style-type: none"> • none: The host has neither the host nor controller secret configured, and no authentication is performed. • unidirectional: The host has a host secret configured. The controller will authenticate the host. • bidirectional: The host has both a host and controller secret configured. The controller will authenticate the host and the host will authenticate the controller. |

tls

A container for the configuration for NVMe/TCP-TLS transport session for the host.

| Name | Type | Description |
|----------------|--------|--|
| configured_psk | string | <p>A user supplied pre-shared key (PSK) value in PSK Interchange Format. Optional in POST.</p> <p>The values for property <code>key_type</code> and property <code>configured_psk</code> must logically agree. This property is only allowed when <code>key_type</code> is configured. If <code>configured_psk</code> is supplied and <code>key_type</code> is unset, <code>key_type</code> defaults to configured.</p> <p>This property is write-only. The <code>key_type</code> property can be used to identify if a configured PSK has been set for the host, but the PSK value cannot be read. To change the value, the host must be deleted from the subsystem and re-added.</p> |

| Name | Type | Description |
|----------|--------|--|
| key_type | string | <p>The method by which the TLS pre-shared key (PSK) is configured for the host. Optional in POST.</p> <p>The values for property <code>key_type</code> and property <code>configured_psk</code> must logically agree.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • <code>none</code> - TLS is not configured for the host connection. No value is allowed for property <code>configured_psk</code>. • <code>configured</code> - A user supplied PSK is configured for the NVMe/TCP-TLS transport connection between the host and the NVMe subsystem. A valid value for property <code>configured_psk</code> is required. <p>This property defaults to <code>none</code> unless a value is supplied for <code>configured_psk</code> in which case it defaults to <code>configured</code>.</p> |

consistency_group_nvme_host

The NVMe host provisioned to access NVMe namespaces mapped to a subsystem.

| Name | Type | Description |
|--------------|--|--|
| dh_hmac_chap | consistency_group_nvme_host_dh_hmac_chap | A container for the configuration of NVMe in-band authentication using the DH-HMAC-CHAP protocol for a host. |
| nqn | string | The NVMe qualified name (NQN) used to identify the NVMe storage target. |

| Name | Type | Description |
|----------|---------------------|---|
| priority | string | The host priority setting allocates appropriate NVMe I/O queues (count and depth) for the host to submit I/O commands. Absence of this property in GET implies io_queue count and I/O queue depth are being used. |
| tls | tls | A container for the configuration for NVMe/TCP-TLS transport session for the host. |

consistency_group_nvme_subsystem

An NVMe subsystem maintains configuration state and namespace access control for a set of NVMe-connected hosts.

| Name | Type | Description |
|---------|--|--|
| comment | string | A configurable comment for the NVMe subsystem. Optional in POST and PATCH. |
| hosts | array[consistency_group_nvme_host] | The NVMe hosts configured for access to the NVMe subsystem. Optional in POST. |
| name | string | The name of the NVMe subsystem. Once created, an NVMe subsystem cannot be renamed. Required in POST. |
| os_type | string | The host operating system of the NVMe subsystem's hosts. Required in POST. |
| uuid | string | The unique identifier of the NVMe subsystem. |

subsystem_map

The NVMe subsystem with which the NVMe namespace is associated. A namespace can be mapped to zero (0) or one (1) subsystems.

There is an added computational cost to retrieving property values for `subsystem_map`. They are not populated for either a collection GET or an instance GET unless explicitly requested using the `fields` query parameter.

| Name | Type | Description |
|-----------|--|--|
| anagrpid | string | <p>The Asymmetric Namespace Access Group ID (ANAGRPID) of the NVMe namespace.</p> <p>The format for an ANAGRPIID is 8 hexadecimal digits (zero-filled) followed by a lower case "h".</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for a GET request unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| nsid | string | <p>The NVMe namespace identifier. This is an identifier used by an NVMe controller to provide access to the NVMe namespace.</p> <p>The format for an NVMe namespace identifier is 8 hexadecimal digits (zero-filled) followed by a lower case "h".</p> |
| subsystem | consistency_group_nvme_subsystem | An NVMe subsystem maintains configuration state and namespace access control for a set of NVMe-connected hosts. |

namespaces

An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the storage virtual machine using the NVMe over Fabrics protocol.

An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.

See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API. An NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.

NVMe namespace names are paths of the form "/vol/<volume>[/<qtree>]/<namespace>" where the qtree name is optional.

An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. An NVMe namespace can then be resized or cloned. An NVMe namespace cannot be renamed, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace.

```
</namespace></qtree></volume>
```

| Name | Type | Description |
|-------------|---------|---|
| auto_delete | boolean | <p>This property marks the NVMe namespace for auto deletion when the volume containing the namespace runs out of space. This is most commonly set on namespace clones.</p> <p>When set to <i>true</i>, the NVMe namespace becomes eligible for automatic deletion when the volume runs out of space. Auto deletion only occurs when the volume containing the namespace is also configured for auto deletion and free space in the volume decreases below a particular threshold.</p> <p>This property is optional in POST and PATCH. The default value for a new NVMe namespace is <i>false</i>.</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for a GET request unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| comment | string | A configurable comment available for use by the administrator. Valid in POST and PATCH. |
| create_time | string | The time the NVMe namespace was created. |
| enabled | boolean | The enabled state of the NVMe namespace. Certain error conditions cause the namespace to become disabled. If the namespace is disabled, check the <code>status.state</code> property to determine what error disabled the namespace. An NVMe namespace is enabled automatically when it is created. |

| Name | Type | Description |
|----------------------|--------------------------------------|--|
| name | string | <p>The name of the NVMe namespace. An NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>NVMe namespace names are paths of the form "/vol/<volume>[/<qtree>]/<namespace>" where the qtree name is optional.</p> <p>Renaming an NVMe namespace is not supported. Valid in POST.</p> |
| os_type | string | <p>The operating system type of the NVMe namespace.</p> <p>Required in POST when creating an NVMe namespace that is not a clone of another. Disallowed in POST when creating a namespace clone.</p> |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| space | space | The storage space related properties of the NVMe namespace. |
| subsystem_map | subsystem_map | <p>The NVMe subsystem with which the NVMe namespace is associated. A namespace can be mapped to zero (0) or one (1) subsystems.</p> <p>There is an added computational cost to retrieving property values for <code>subsystem_map</code>. They are not populated for either a collection GET or an instance GET unless explicitly requested using the <code>fields</code> query parameter.</p> |
| uuid | string | The unique identifier of the NVMe namespace. |

parent_consistency_group

The parent consistency group.

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the consistency group. |
| uuid | string | The unique identifier of the consistency group. |

storage_service

Determines the placement of any storage object created during this operation.

| Name | Type | Description |
|------|--------|--|
| name | string | Storage service name. If not specified, the default value is the most performant for the platform. |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|-----------------|-----------------|---|
| action | string | Operation to perform |
| name | string | New name for consistency group. Required to resolve naming collisions. |
| storage_service | storage_service | Determines the placement of any storage object created during this operation. |

policy

The QoS policy

| Name | Type | Description |
|------|--------|---|
| name | string | The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH. |

| Name | Type | Description |
|------|--------|---|
| uuid | string | The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH. |

snapshot

A consistency group's snapshot

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the consistency group's snapshot to restore to. |
| uuid | string | The UUID of the consistency group's snapshot to restore to. |

restore_to

Use to restore a consistency group to a previous snapshot

| Name | Type | Description |
|----------|----------|--------------------------------|
| snapshot | snapshot | A consistency group's snapshot |

snapshot_policy_reference

This is a reference to the snapshot policy.

| Name | Type | Description |
|------|--------|-------------|
| name | string | |
| uuid | string | |

space

Space information for the consistency group.

| Name | Type | Description |
|-----------|---------|---|
| available | integer | The amount of space available in the consistency group, in bytes. |
| size | integer | The total provisioned size of the consistency group, in bytes. |

| Name | Type | Description |
|------|---------|--|
| used | integer | The amount of space consumed in the consistency group, in bytes. |

svm

The Storage Virtual Machine (SVM) in which the consistency group is located.

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

object_stores

| Name | Type | Description |
|------|--------|--|
| name | string | The name of the object store to use. Used for placement. |

tiering

The tiering placement and policy definitions for volumes in this consistency group.

| Name | Type | Description |
|---------------|--|---|
| control | string | Storage tiering placement rules for the object. |
| object_stores | array[object_stores] | Object stores to use. Used for placement. |

| Name | Type | Description |
|--------|--------|---|
| policy | string | <p>Policy that determines whether the user data blocks of a volume in a FabricPool will be tiered to the cloud store when they become cold.</p> <p>FabricPool combines flash (performance tier) with a cloud store into a single aggregate. Temperature of a volume block increases if it is accessed frequently and decreases when it is not. Valid in POST or PATCH.</p> <p>all &dash; Allows tiering of both snapshots and active file system user data to the cloud store as soon as possible by ignoring the temperature on the volume blocks.</p> <p>auto &dash; Allows tiering of both snapshot and active file system user data to the cloud store</p> <p>none &dash; Volume blocks are not be tiered to the cloud store.</p> <p>snapshot_only &dash; Allows tiering of only the volume snapshots not associated with the active file system.</p> <p>The default tiering policy is "snapshot-only" for a FlexVol volume and "none" for a FlexGroup volume. The default minimum cooling period for the "snapshot-only" tiering policy is 2 days and for the "auto" tiering policy it is 31 days.</p> |

acls

The permissions that users and groups have on a CIFS share.

| Name | Type | Description |
|---------------|--------|---|
| permission | string | <p>Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed:</p> <ul style="list-style-type: none"> • no_access - User does not have CIFS share access • read - User has only read access • change - User has change access • full_control - User has full_control access |
| type | string | <p>Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed:</p> <ul style="list-style-type: none"> • windows - Windows user or group • unix_user - UNIX user • unix_group - UNIX group |
| user_or_group | string | Specifies the user or group name to add to the access control list of a CIFS share. |

consistency_group_cifs_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

| Name | Type | Description |
|--------------------------|------------------------------|--|
| access_based_enumeration | boolean | Specifies whether all folders inside this share are visible to a user based on that individual user's access right; prevents the display of folders or other shared resources that the user does not have access to. |
| acls | array [acls] | |

| Name | Type | Description |
|--------------------------|---------|---|
| allow_unencrypted_access | boolean | Specifies whether or not the SMB2 clients are allowed to access the encrypted share. |
| change_notify | boolean | Specifies whether CIFS clients can request for change notifications for directories on this share. |
| comment | string | Specify the CIFS share descriptions. |
| continuously_available | boolean | Specifies whether or not the clients connecting to this share can open files in a persistent manner. Files opened in this way are protected from disruptive events, such as, failover and giveback. |
| dir_umask | integer | Directory mode creation mask to be viewed as an octal number. |
| encryption | boolean | Specifies whether SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share. |
| file_umask | integer | File mode creation mask to be viewed as an octal number. |

| Name | Type | Description |
|-------------------|---------|---|
| home_directory | boolean | <p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> • Default value: 1 • Introduced in: 9.12 • readCreate: 1 • x-nullable: true |
| name | string | Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically. |
| namespace_caching | boolean | Specifies whether or not the SMB clients connecting to this share can cache the directory enumeration results returned by the CIFS servers. |

| Name | Type | Description |
|--------------------|---------|--|
| no_strict_security | boolean | Specifies whether or not CIFS clients can follow Unix symlinks outside the share boundaries. |
| offline_files | string | <p>Offline Files The supported values are:</p> <ul style="list-style-type: none"> • none - Clients are not permitted to cache files for offline access. • manual - Clients may cache files that are explicitly selected by the user for offline access. • documents - Clients may automatically cache files that are used by the user for offline access. • programs - Clients may automatically cache files that are used by the user for offline access and may use those files in an offline mode even if the share is available. |
| oplocks | boolean | Specifies whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations. |
| show_snapshot | boolean | Specifies whether or not the snapshots can be viewed and traversed by clients. |
| unix_symlink | string | <p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> • local - Enables only local symbolic links which is within the same CIFS share. • widelink - Enables both local symlinks and widelinks. • disable - Disables local symlinks and widelinks. |

| Name | Type | Description |
|---------------|--------|---|
| vscan_profile | string | <p>Vscan File-Operations Profile The supported values are:</p> <ul style="list-style-type: none"> • no_scan - Virus scans are never triggered for accesses to this share. • standard - Virus scans can be triggered by open, close, and rename operations. • strict - Virus scans can be triggered by open, read, close, and rename operations. • writes_only - Virus scans can be triggered only when a file that has been modified is closed. |

cifs

| Name | Type | Description |
|--------|--|-------------|
| shares | array[consistency_group_cifs_shares] | |

export_clients

| Name | Type | Description |
|-------|--------|--|
| match | string | <p>Client Match Hostname, IP Address, Netgroup, or Domain. You can specify the match as a string value in any of the following formats:</p> <ul style="list-style-type: none"> • As a hostname; for instance, host1 • As an IPv4 address; for instance, 10.1.12.24 • As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1 • As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24 • As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64 • As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0 • As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng • As a domain name preceded by the . character; for instance, .example.com |

export_rules

| Name | Type | Description |
|-----------------------|---------|--|
| allow_device_creation | boolean | Specifies whether or not device creation is allowed. |
| allow_suid | boolean | Specifies whether or not SetUID bits in SETATTR Op is to be honored. |
| anonymous_user | string | User ID To Which Anonymous Users Are Mapped. |

| Name | Type | Description |
|--------------------|---|---|
| chown_mode | string | Specifies who is authorized to change the ownership mode of a file. |
| clients | array[export_clients] | Array of client matches |
| index | integer | Index of the rule within the export policy. |
| ntfs_unix_security | string | NTFS export UNIX security options. |
| protocols | array[string] | |
| ro_rule | array[string] | Authentication flavors that the read-only access rule governs |
| rw_rule | array[string] | Authentication flavors that the read/write access rule governs |
| superuser | array[string] | Authentication flavors that the superuser security type governs |

export_policy

The policy associated with volumes to export them for protocol access.

| Name | Type | Description |
|-------|---------------------------------------|---|
| id | integer | Identifier for the export policy. |
| name | string | Name of the export policy. |
| rules | array[export_rules] | The set of rules that govern the export policy. |

junction_parent

| Name | Type | Description |
|------|--------|--|
| name | string | The name of the parent volume that contains the junction inode of this volume. The junction parent volume must belong to the same SVM that owns this volume. |

| Name | Type | Description |
|------|--------|--|
| uuid | string | Unique identifier for the parent volume. |

nas

The CIFS share policy and/or export policies for this volume.

| Name | Type | Description |
|-----------------|-----------------|---|
| cifs | cifs | |
| export_policy | export_policy | The policy associated with volumes to export them for protocol access. |
| gid | integer | The UNIX group ID of the volume. Valid in POST or PATCH. |
| junction_parent | junction_parent | |
| path | string | The fully-qualified path in the owning SVM's namespace at which the volume is mounted. The path is case insensitive and must be unique within an SVM's namespace. Path must begin with '/' and must not end with '/'. Only one volume can be mounted at any given junction path. An empty path in POST creates an unmounted volume. An empty path in PATCH deactivates and unmounts the volume. Taking a volume offline or restricted state removes its junction path. This attribute is reported in GET only when the volume is mounted. |
| security_style | string | Security style associated with the volume. Valid in POST or PATCH. mixed – Mixed-style security ntfs – NTFS/Windows-style security unified – Unified-style security, unified UNIX, NFS and CIFS permissions unix – UNIX-style security. |
| uid | integer | The UNIX user ID of the volume. Valid in POST or PATCH. |

| Name | Type | Description |
|------------------|---------|---|
| unix_permissions | integer | UNIX permissions to be viewed as an octal number, consisting of 4 digits derived by adding up bits 4 (read), 2 (write), and 1 (execute). First digit selects the set user ID (4), set group ID (2), and sticky (1) attributes. Second digit selects permission for the owner of the file. Third selects permissions for other users in the same group while the fourth selects permissions for other users not in the group. Valid in POST or PATCH. For security style "mixed" or "unix", the default setting is 0755 in octal (493 in decimal) and for security style "ntfs", the default setting is 0000. In cases where only owner, group, and other permissions are given (as in 755, representing the second, third and fourth digit), the first digit is assumed to be zero. |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|-----------------|---------------------------------|---|
| action | string | Operation to perform |
| count | integer | Number of elements to perform the operation on. |
| storage_service | storage_service | Determines the placement of any storage object created during this operation. |

qos

The QoS policy for this volume.

| Name | Type | Description |
|--------|------------------------|----------------|
| policy | policy | The QoS policy |

space

| Name | Type | Description |
|-----------|---------|--|
| available | integer | The available space, in bytes. |
| size | integer | Total provisioned size, in bytes. |
| used | integer | The virtual space used (includes volume reserves) before storage efficiency, in bytes. |

tiering

The tiering placement and policy definitions for this volume.

| Name | Type | Description |
|---------------|--|---|
| control | string | Storage tiering placement rules for the object. |
| object_stores | array[object_stores] | Object stores to use. Used for placement. |

| Name | Type | Description |
|--------|--------|---|
| policy | string | <p>Policy that determines whether the user data blocks of a volume in a FabricPool will be tiered to the cloud store when they become cold.</p> <p>FabricPool combines flash (performance tier) with a cloud store into a single aggregate. Temperature of a volume block increases if it is accessed frequently and decreases when it is not. Valid in POST or PATCH.</p> <p>all &dash; Allows tiering of both snapshots and active file system user data to the cloud store as soon as possible by ignoring the temperature on the volume blocks.</p> <p>auto &dash; Allows tiering of both snapshot and active file system user data to the cloud store</p> <p>none &dash; Volume blocks are not be tiered to the cloud store.</p> <p>snapshot_only &dash; Allows tiering of only the volume snapshots not associated with the active file system.</p> <p>The default tiering policy is "snapshot-only" for a FlexVol volume and "none" for a FlexGroup volume. The default minimum cooling period for the "snapshot-only" tiering policy is 2 days and for the "auto" tiering policy it is 31 days.</p> |

volumes

| Name | Type | Description |
|---------|--------|---|
| comment | string | A comment for the volume. Valid in POST or PATCH. |

| Name | Type | Description |
|----------------------|---|---|
| name | string | Volume name. The name of volume must start with an alphabetic character (a to z or A to Z) or an underscore (_). The name must be 197 or fewer characters in length for FlexGroup volumes, and 203 or fewer characters in length for all other types of volumes. Volume names must be unique within an SVM. Required on POST. |
| nas | nas | The CIFS share policy and/or export policies for this volume. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | The QoS policy for this volume. |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| space | space | |
| tiering | tiering | The tiering placement and policy definitions for this volume. |
| uuid | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> example: 028baa66-41bd-11e9-81d5-00a0986138f7 readOnly: 1 Introduced in: 9.8 x-nullable: true |

consistency_groups

| Name | Type | Description |
|-------------|-----------------------------|---|
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |
| application | application | |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |
| name | string | Name of the consistency group. The consistency group name must be unique within an SVM. |

| Name | Type | Description |
|--------------------------|--|--|
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | |

| Name | Type | Description |
|-----------------|---|--|
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| svm | svm | The Storage Virtual Machine (SVM) in which the consistency group is located. |
| tiering | tiering | The tiering placement and policy definitions for volumes in this consistency group. |
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> • example: 1cd8a442-86d1-11e0-ae1c-123478563412 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

iops

The rate of I/O operations observed at the storage object.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

latency

The round trip latency observed at the storage object, in microseconds.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

throughput

The rate of throughput bytes per second observed at the storage object.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |

| Name | Type | Description |
|-------|---------|---|
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

metric

Performance and capacity numbers, such as, IOPS, latency, throughput, used space, and available space.

| Name | Type | Description |
|-----------------|---------|--|
| available_space | integer | The total space available in the consistency group, in bytes. |
| duration | string | The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations: |
| iops | iops | The rate of I/O operations observed at the storage object. |
| latency | latency | The round trip latency observed at the storage object, in microseconds. |
| size | integer | The total size of the consistency group, in bytes. |

| Name | Type | Description |
|------------|------------|---|
| status | string | Errors associated with the sample. For example, if the aggregation of data over multiple nodes fails, then any partial errors might return "ok" on success or "error" on an internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data. |
| throughput | throughput | The rate of throughput bytes per second observed at the storage object. |
| timestamp | string | The timestamp of the performance and capacity data. |
| used_space | integer | The total space used in the consistency group, in bytes. |

replication_relationships

| Name | Type | Description |
|------------------------|---------|--|
| is_protected_by_svm_dr | boolean | Indicates whether or not this consistency group is protected by SVM DR. |
| is_source | boolean | Indicates whether or not this consistency group is the source for replication. |
| uuid | string | The unique identifier of the SnapMirror relationship. |

iops_raw

The number of I/O operations observed at the storage object. This can be used along with delta time to calculate the rate of I/O operations per unit of time.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

latency_raw

The raw latency observed at the storage object, in microseconds. This can be divided by the raw IOPS value to calculate the average latency per I/O operation.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

throughput_raw

Throughput bytes observed at the storage object. This can be used along with delta time to calculate the rate of throughput bytes per unit of time.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

statistics

These are raw performance and space numbers, such as, IOPS, latency, throughput, used space, and available space. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.

| Name | Type | Description |
|-----------------|-----------------------------|--|
| available_space | integer | The total space available in the consistency group, in bytes. |
| iops_raw | iops_raw | The number of I/O operations observed at the storage object. This can be used along with delta time to calculate the rate of I/O operations per unit of time. |
| latency_raw | latency_raw | The raw latency observed at the storage object, in microseconds. This can be divided by the raw IOPS value to calculate the average latency per I/O operation. |
| size | integer | The total size of the consistency group, in bytes. |

| Name | Type | Description |
|----------------|--------------------------------|---|
| status | string | Errors associated with the sample. For example, if the aggregation of data over multiple nodes fails, then any partial errors might return "ok" on success or "error" on an internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data. |
| throughput_raw | throughput_raw | Throughput bytes observed at the storage object. This can be used along with delta time to calculate the rate of throughput bytes per unit of time. |
| timestamp | string | The timestamp of the performance data. |
| used_space | integer | The total used space in the consistency group, in bytes. |

consistency_group_cifs_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

| Name | Type | Description |
|--------------------------|---------------------|--|
| access_based_enumeration | boolean | Specifies whether all folders inside this share are visible to a user based on that individual user's access right; prevents the display of folders or other shared resources that the user does not have access to. |
| acls | array <acls></acls> | |
| allow_unencrypted_access | boolean | Specifies whether or not the SMB2 clients are allowed to access the encrypted share. |
| change_notify | boolean | Specifies whether CIFS clients can request for change notifications for directories on this share. |
| comment | string | Specify the CIFS share descriptions. |
| continuously_available | boolean | Specifies whether or not the clients connecting to this share can open files in a persistent manner. Files opened in this way are protected from disruptive events, such as, failover and giveback. |
| dir_umask | integer | Directory mode creation mask to be viewed as an octal number. |
| encryption | boolean | Specifies whether SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share. |
| file_umask | integer | File mode creation mask to be viewed as an octal number. |

| Name | Type | Description |
|-------------------|---------|---|
| home_directory | boolean | <p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> • Default value: 1 • Introduced in: 9.12 • readCreate: 1 • x-nullable: true |
| name | string | Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically. |
| namespace_caching | boolean | Specifies whether or not the SMB clients connecting to this share can cache the directory enumeration results returned by the CIFS servers. |

| Name | Type | Description |
|--------------------|---------|--|
| no_strict_security | boolean | Specifies whether or not CIFS clients can follow Unix symlinks outside the share boundaries. |
| offline_files | string | <p>Offline Files The supported values are:</p> <ul style="list-style-type: none"> • none - Clients are not permitted to cache files for offline access. • manual - Clients may cache files that are explicitly selected by the user for offline access. • documents - Clients may automatically cache files that are used by the user for offline access. • programs - Clients may automatically cache files that are used by the user for offline access and may use those files in an offline mode even if the share is available. |
| oplocks | boolean | Specifies whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations. |
| show_snapshot | boolean | Specifies whether or not the snapshots can be viewed and traversed by clients. |
| unix_symlink | string | <p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> • local - Enables only local symbolic links which is within the same CIFS share. • widelink - Enables both local symlinks and widelinks. • disable - Disables local symlinks and widelinks. |

| Name | Type | Description |
|---------------|--------|---|
| vscan_profile | string | <p>Vscan File-Operations Profile The supported values are:</p> <ul style="list-style-type: none"> • no_scan - Virus scans are never triggered for accesses to this share. • standard - Virus scans can be triggered by open, close, and rename operations. • strict - Virus scans can be triggered by open, read, close, and rename operations. • writes_only - Virus scans can be triggered only when a file that has been modified is closed. |

export_clients

| Name | Type | Description |
|-------|--------|--|
| match | string | <p>Client Match Hostname, IP Address, Netgroup, or Domain. You can specify the match as a string value in any of the following formats:</p> <ul style="list-style-type: none"> • As a hostname; for instance, host1 • As an IPv4 address; for instance, 10.1.12.24 • As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1 • As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24 • As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64 • As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0 • As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng • As a domain name preceded by the . character; for instance, .example.com |

consistency_group

| Name | Type | Description |
|-------------|---------------|--|
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |
| application | application | |
| clone | clone | Creates a clone of an existing consistency group from the current contents or an existing snapshot. |

| Name | Type | Description |
|--------------------|---|---|
| consistency_groups | array[consistency_groups] | A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A consistency group can only be associated with one direct parent consistency group. |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |
| name | string | Name of the consistency group. The consistency group name must be unique within an SVM. |

| Name | Type | Description |
|--------------------------|--|--|
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | |

| Name | Type | Description |
|---------------------------|--|--|
| replicated | boolean | Indicates whether or not replication has been enabled on this consistency group. |
| replication_relationships | array[replication_relationships] | Indicates the SnapMirror relationship of this consistency group. |
| replication_source | boolean | Since support for this field is to be removed in the next release, use replication_relationships.is_source instead. |
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| svm | svm | The Storage Virtual Machine (SVM) in which the consistency group is located. |
| tiering | tiering | The tiering placement and policy definitions for volumes in this consistency group. |
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> example: 1cd8a442-86d1-11e0-ae1c-123478563412 readOnly: 1 Introduced in: 9.10 x-nullable: true |

| Name | Type | Description |
|---------|----------------|--|
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

consistency_group_cifs_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

| Name | Type | Description |
|--------------------------|-------------|--|
| access_based_enumeration | boolean | Specifies whether all folders inside this share are visible to a user based on that individual user's access right; prevents the display of folders or other shared resources that the user does not have access to. |
| acls | array[acls] | |
| allow_unencrypted_access | boolean | Specifies whether or not the SMB2 clients are allowed to access the encrypted share. |
| change_notify | boolean | Specifies whether CIFS clients can request for change notifications for directories on this share. |
| comment | string | Specify the CIFS share descriptions. |

| Name | Type | Description |
|------------------------|---------|---|
| continuously_available | boolean | Specifies whether or not the clients connecting to this share can open files in a persistent manner. Files opened in this way are protected from disruptive events, such as, failover and giveback. |
| dir_umask | integer | Directory mode creation mask to be viewed as an octal number. |
| encryption | boolean | Specifies whether SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share. |
| file_umask | integer | File mode creation mask to be viewed as an octal number. |

| Name | Type | Description |
|-------------------|---------|---|
| home_directory | boolean | <p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> • Default value: 1 • Introduced in: 9.12 • readCreate: 1 • x-nullable: true |
| name | string | Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically. |
| namespace_caching | boolean | Specifies whether or not the SMB clients connecting to this share can cache the directory enumeration results returned by the CIFS servers. |

| Name | Type | Description |
|--------------------|---------|--|
| no_strict_security | boolean | Specifies whether or not CIFS clients can follow Unix symlinks outside the share boundaries. |
| offline_files | string | <p>Offline Files The supported values are:</p> <ul style="list-style-type: none"> • none - Clients are not permitted to cache files for offline access. • manual - Clients may cache files that are explicitly selected by the user for offline access. • documents - Clients may automatically cache files that are used by the user for offline access. • programs - Clients may automatically cache files that are used by the user for offline access and may use those files in an offline mode even if the share is available. |
| oplocks | boolean | Specifies whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations. |
| show_snapshot | boolean | Specifies whether or not the snapshots can be viewed and traversed by clients. |
| unix_symlink | string | <p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> • local - Enables only local symbolic links which is within the same CIFS share. • widelink - Enables both local symlinks and widelinks. • disable - Disables local symlinks and widelinks. |

| Name | Type | Description |
|---------------|--------|---|
| vscan_profile | string | <p>Vscan File-Operations Profile The supported values are:</p> <ul style="list-style-type: none"> • no_scan - Virus scans are never triggered for accesses to this share. • standard - Virus scans can be triggered by open, close, and rename operations. • strict - Virus scans can be triggered by open, read, close, and rename operations. • writes_only - Virus scans can be triggered only when a file that has been modified is closed. |

export_clients

| Name | Type | Description |
|-------|--------|--|
| match | string | <p>Client Match Hostname, IP Address, Netgroup, or Domain. You can specify the match as a string value in any of the following formats:</p> <ul style="list-style-type: none"> • As a hostname; for instance, host1 • As an IPv4 address; for instance, 10.1.12.24 • As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1 • As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24 • As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64 • As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0 • As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng • As a domain name preceded by the . character; for instance, .example.com |

consistency_group_cifs_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

| Name | Type | Description |
|-------------------------|---------------------|--|
| access_basedEnumeration | boolean | Specifies whether all folders inside this share are visible to a user based on that individual user's access right; prevents the display of folders or other shared resources that the user does not have access to. |
| acls | array <acls></acls> | |
| allowUnencryptedAccess | boolean | Specifies whether or not the SMB2 clients are allowed to access the encrypted share. |
| changeNotify | boolean | Specifies whether CIFS clients can request for change notifications for directories on this share. |
| comment | string | Specify the CIFS share descriptions. |
| continuouslyAvailable | boolean | Specifies whether or not the clients connecting to this share can open files in a persistent manner. Files opened in this way are protected from disruptive events, such as, failover and giveback. |
| dirUmask | integer | Directory mode creation mask to be viewed as an octal number. |
| encryption | boolean | Specifies whether SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share. |
| fileUmask | integer | File mode creation mask to be viewed as an octal number. |

| Name | Type | Description |
|-------------------|---------|---|
| home_directory | boolean | <p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> • Default value: 1 • Introduced in: 9.12 • readCreate: 1 • x-nullable: true |
| name | string | Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically. |
| namespace_caching | boolean | Specifies whether or not the SMB clients connecting to this share can cache the directory enumeration results returned by the CIFS servers. |

| Name | Type | Description |
|--------------------|---------|--|
| no_strict_security | boolean | Specifies whether or not CIFS clients can follow Unix symlinks outside the share boundaries. |
| offline_files | string | <p>Offline Files The supported values are:</p> <ul style="list-style-type: none"> • none - Clients are not permitted to cache files for offline access. • manual - Clients may cache files that are explicitly selected by the user for offline access. • documents - Clients may automatically cache files that are used by the user for offline access. • programs - Clients may automatically cache files that are used by the user for offline access and may use those files in an offline mode even if the share is available. |
| oplocks | boolean | Specifies whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations. |
| show_snapshot | boolean | Specifies whether or not the snapshots can be viewed and traversed by clients. |
| unix_symlink | string | <p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> • local - Enables only local symbolic links which is within the same CIFS share. • widelink - Enables both local symlinks and widelinks. • disable - Disables local symlinks and widelinks. |

| Name | Type | Description |
|---------------|--------|---|
| vscan_profile | string | <p>Vscan File-Operations Profile The supported values are:</p> <ul style="list-style-type: none"> • no_scan - Virus scans are never triggered for accesses to this share. • standard - Virus scans can be triggered by open, close, and rename operations. • strict - Virus scans can be triggered by open, read, close, and rename operations. • writes_only - Virus scans can be triggered only when a file that has been modified is closed. |

job_link

| Name | Type | Description |
|------|--------|---|
| uuid | string | The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Delete a consistency group

DELETE /application/consistency-groups/{uuid}

Introduced In: 9.10

Deletes a consistency group.



this will not delete any associated volumes or LUNs. To delete those elements, use the appropriate object endpoint.

Related ONTAP commands

There are no ONTAP commands for managing consistency groups.

Parameters

| Name | Type | In | Required | Description |
|------|--------|------|----------|---|
| uuid | string | path | True | The unique identifier of the consistency group to delete. |

| Name | Type | In | Required | Description |
|----------------|---------|-------|----------|--|
| return_timeout | integer | query | False | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> • Default value: 1 • Max value: 120 • Min value: 0 |

Response

Status: 200, Ok

Response

Status: 202, Accepted

Error

Status: Default

ONTAP Error Response Codes

| Error Code | Description |
|------------|---|
| 53411842 | Consistency group does not exist. |
| 53411843 | A consistency group with specified UUID was not found. |
| 53411844 | Specified consistency group was not found in the specified SVM. |
| 53411845 | The specified UUID and name refer to different consistency groups. |
| 53411846 | Either name or UUID must be provided. |
| 53412041 | Cannot delete a consistency group because it contains one or more storage units that are part of replication relationships. |

Also see the table of common errors in the [Response body](#) overview section of this documentation.

| Name | Type | Description |
|-------|--------------------------------|-------------|
| error | returned_error | |

Example error

```
{  
  "error": {  
    "arguments": [  
      {  
        "code": "string",  
        "message": "string"  
      }  
    ],  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

Definitions

See Definitions

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Retrieve a consistency group

GET /application/consistency-groups/{uuid}

Introduced In: 9.10

Retrieves a single consistency group.

Expensive properties

There is an added computational cost to retrieving values for these properties. They are not included by default in GET results and must be explicitly requested using the `fields` query parameter. See [DOC Requesting specific fields](#) to learn more.

- volumes
- luns
- namespaces

Related ONTAP commands

There are no ONTAP commands for managing consistency groups.

Parameters

| Name | Type | In | Required | Description |
|-----------------------------------|---------|-------|----------|---|
| uuid | string | path | True | The unique identifier of the group to retrieve. |
| namespaces.uuid | string | query | False | Filter by namespaces.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.status.read_only | boolean | query | False | Filter by namespaces.status.read_only <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.status.mapped | boolean | query | False | Filter by namespaces.status.mapped <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.status.container_state | string | query | False | Filter by namespaces.status.container_state <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.status.state | string | query | False | Filter by namespaces.status.state <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.auto_delete | boolean | query | False | Filter by namespaces.auto_delete <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|--------|-------|----------|---|
| namespaces.subsystem_map.nsid | string | query | False | <p>Filter by namespaces.subsystem_map.nsid</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.subsystem_map.subsystem.name | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.name</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 64 • minLength: 1 |
| namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.group_size | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.group_size</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |
| namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.mode | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.mode</p> <ul style="list-style-type: none"> • Introduced in: 9.16 |
| namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.hash_function | string | query | False | <p>Filter by namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.hash_function</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |

| Name | Type | In | Required | Description |
|---|--------|-------|----------|--|
| namespaces.subsystem_map.subsystem.hosts.nqn | string | query | False | Filter by namespaces.subsystem_map.subsystem.hosts.nqn <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.subsystem_map.subsystem.hosts.priority | string | query | False | Filter by namespaces.subsystem_map.subsystem.hosts.priority <ul style="list-style-type: none"> • Introduced in: 9.14 |
| namespaces.subsystem_map.subsystem.hosts.tls.key_type | string | query | False | Filter by namespaces.subsystem_map.subsystem.hosts.tls.key_type <ul style="list-style-type: none"> • Introduced in: 9.16 |
| namespaces.subsystem_map.subsystem.uuid | string | query | False | Filter by namespaces.subsystem_map.subsystem.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.subsystem_map.subsystem.os_type | string | query | False | Filter by namespaces.subsystem_map.subsystem.os_type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.subsystem_map.subsystem.comment | string | query | False | Filter by namespaces.subsystem_map.subsystem.comment <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 255 • minLength: 0 |

| Name | Type | In | Required | Description |
|--------------------------------------|---------|-------|----------|--|
| namespaces.subsystem_map.anagrpid | string | query | False | Filter by namespaces.subsystem_map.anagrpid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.os_type | string | query | False | Filter by namespaces.os_type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.space.block_size | integer | query | False | Filter by namespaces.space.block_size <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.space.guarantee.requested | boolean | query | False | Filter by namespaces.space.guarantee.requested <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.space.guarantee.reserved | boolean | query | False | Filter by namespaces.space.guarantee.reserved <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.space.size | integer | query | False | Filter by namespaces.space.size <ul style="list-style-type: none"> • Introduced in: 9.12 • Max value: 140737488355328 • Min value: 4096 |

| Name | Type | In | Required | Description |
|------------------------------|---------|-------|----------|--|
| namespaces.space.used | integer | query | False | Filter by namespaces.space.used <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.create_time | string | query | False | Filter by namespaces.create_time <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.enabled | boolean | query | False | Filter by namespaces.enabled <ul style="list-style-type: none"> • Introduced in: 9.12 |
| namespaces.comment | string | query | False | Filter by namespaces.comment <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 254 • minLength: 0 |
| namespaces.name | string | query | False | Filter by namespaces.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| statistics.timestamp | string | query | False | Filter by statistics.timestamp <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.latency_raw.write | integer | query | False | Filter by statistics.latency_raw.write <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|-----------------------------|---------|-------|----------|---|
| statistics.latency_rw.total | integer | query | False | Filter by statistics.latency_rw.total <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.latency_rw.read | integer | query | False | Filter by statistics.latency_rw.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.latency_rw.other | integer | query | False | Filter by statistics.latency_rw.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.status | string | query | False | Filter by statistics.status <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.iops_raw.write | integer | query | False | Filter by statistics.iops_raw.write <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.iops_raw.total | integer | query | False | Filter by statistics.iops_raw.total <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.iops_raw.read | integer | query | False | Filter by statistics.iops_raw.read <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|---------------------------------|---------|-------|----------|---|
| statistics.iops_raw.other | integer | query | False | Filter by statistics.iops_raw.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.size | integer | query | False | Filter by statistics.size <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.used_space | integer | query | False | Filter by statistics.used_space <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.throughput_raw.write | integer | query | False | Filter by statistics.throughput_raw.write <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.throughput_raw.total | integer | query | False | Filter by statistics.throughput_raw.total <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.throughput_raw.read | integer | query | False | Filter by statistics.throughput_raw.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| statistics.throughput_raw.other | integer | query | False | Filter by statistics.throughput_raw.other <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| statistics.available_space | integer | query | False | Filter by statistics.available_space <ul style="list-style-type: none"> • Introduced in: 9.13 |
| tiering.policy | string | query | False | Filter by tiering.policy |
| qos.policy.uuid | string | query | False | Filter by qos.policy.uuid |
| qos.policy.name | string | query | False | Filter by qos.policy.name |
| space.available | integer | query | False | Filter by space.available |
| space.size | integer | query | False | Filter by space.size |
| space.used | integer | query | False | Filter by space.used |
| replicated | boolean | query | False | Filter by replicated |
| replication_relations_hips.is_source | boolean | query | False | Filter by replication_relations_hips.is_source <ul style="list-style-type: none"> • Introduced in: 9.13 |
| replication_relations_hips.is_protected_by_svm_dr | boolean | query | False | Filter by replication_relations_hips.is_protected_by_svm_dr <ul style="list-style-type: none"> • Introduced in: 9.14 |
| replication_relations_hips.uuid | string | query | False | Filter by replication_relations_hips.uuid <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|------------------------------|---------|-------|----------|--|
| _tags | string | query | False | Filter by _tags <ul style="list-style-type: none"> • Introduced in: 9.15 |
| application.component_type | string | query | False | Filter by application.component_type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| application.type | string | query | False | Filter by application.type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| snapshot_policy.uuid | string | query | False | Filter by snapshot_policy.uuid |
| snapshot_policy.name | string | query | False | Filter by snapshot_policy.name |
| clone.parent_svm.name | string | query | False | Filter by clone.parent_svm.name <ul style="list-style-type: none"> • Introduced in: 9.15 |
| clone.parent_svm.uid | string | query | False | Filter by clone.parent_svm.uid <ul style="list-style-type: none"> • Introduced in: 9.15 |
| clone.split_complete_percent | integer | query | False | Filter by clone.split_complete_percent <ul style="list-style-type: none"> • Introduced in: 9.15 |

| Name | Type | In | Required | Description |
|-------------------------------------|---------|-------|----------|---|
| clone.parent_consistency_group.name | string | query | False | Filter by clone.parent_consistency_group.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.parent_consistency_group.uuid | string | query | False | Filter by clone.parent_consistency_group.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.parent_snapshot.uuid | string | query | False | Filter by clone.parent_snapshot.uuid <ul style="list-style-type: none"> • Introduced in: 9.15 |
| clone.parent_snapshot.name | string | query | False | Filter by clone.parent_snapshot.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.volume.suffix | string | query | False | Filter by clone.volume.suffix <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.volume.prefix | string | query | False | Filter by clone.volume.prefix <ul style="list-style-type: none"> • Introduced in: 9.12 |
| clone.split_estimate | integer | query | False | Filter by clone.split_estimate <ul style="list-style-type: none"> • Introduced in: 9.15 |

| Name | Type | In | Required | Description |
|------------------------------|---------|-------|----------|--|
| clone.is_flexclone | boolean | query | False | Filter by clone.is_flexclone • Introduced in: 9.15 |
| clone.guarantee.type | string | query | False | Filter by clone.guarantee.type • Introduced in: 9.12 |
| clone.split_initiated | boolean | query | False | Filter by clone.split_initiated • Introduced in: 9.12 |
| volumes.snapshot_policy.uuid | string | query | False | Filter by volumes.snapshot_policy.uuid |
| volumes.snapshot_policy.name | string | query | False | Filter by volumes.snapshot_policy.name |
| volumes.tiering.policy | string | query | False | Filter by volumes.tiering.policy |
| volumes.uuid | string | query | False | Filter by volumes.uuid |
| volumes.qos.policy.uuid | string | query | False | Filter by volumes.qos.policy.uuid |
| volumes.qos.policy.name | string | query | False | Filter by volumes.qos.policy.name |
| volumes.space.used | integer | query | False | Filter by volumes.space.used |
| volumes.space.size | integer | query | False | Filter by volumes.space.size |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| volumes.space.available | integer | query | False | Filter by volumes.space.available |
| volumes.nas.export_policy.id | integer | query | False | Filter by volumes.nas.export_policy.id <ul style="list-style-type: none"> • Introduced in: 9.14 |
| volumes.nas.export_policy.rules.superuser | string | query | False | Filter by volumes.nas.export_policy.rules.superuser <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.index | integer | query | False | Filter by volumes.nas.export_policy.rules.index <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.allow_device_creation | boolean | query | False | Filter by volumes.nas.export_policy.rules.allow_device_creation <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.allow_su_id | boolean | query | False | Filter by volumes.nas.export_policy.rules.allow_su_id <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.rw_rule | string | query | False | Filter by volumes.nas.export_policy.rules.rw_rule <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|--|
| volumes.nas.export_policy.rules.clients.match | string | query | False | Filter by volumes.nas.export_policy.rules.clients.match <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.chown_mode | string | query | False | Filter by volumes.nas.export_policy.rules.chown_mode <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.anonymous_user | string | query | False | Filter by volumes.nas.export_policy.rules.anonymous_user <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.ntfs_unix_security | string | query | False | Filter by volumes.nas.export_policy.rules.ntfs_unix_security <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.ro_rule | string | query | False | Filter by volumes.nas.export_policy.rules.ro_rule <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.export_policy.rules.protocols | string | query | False | Filter by volumes.nas.export_policy.rules.protocols <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---------------------------------------|---------|-------|----------|---|
| volumes.nas.export_policy.name | string | query | False | Filter by volumes.nas.export_policy.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.junction_parent.name | string | query | False | Filter by volumes.nas.junction_parent.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.junction_parent.uuid | string | query | False | Filter by volumes.nas.junction_parent.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.path | string | query | False | Filter by volumes.nas.path <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.unix_symlink | string | query | False | Filter by volumes.nas.cifs.shares.unix_symlink <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.show_snapshot | boolean | query | False | Filter by volumes.nas.cifs.shares.show_snapshot <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.vscan_profile | string | query | False | Filter by volumes.nas.cifs.shares.vscan_profile <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| volumes.nas.cifs.sha res.comment | string | query | False | <p>Filter by volumes.nas.cifs.shares.comment</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 256 • minLength: 1 |
| volumes.nas.cifs.sha res.continuously_available | boolean | query | False | <p>Filter by volumes.nas.cifs.shares.continuously_available</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.encryption | boolean | query | False | <p>Filter by volumes.nas.cifs.shares.encryption</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.file_umask | integer | query | False | <p>Filter by volumes.nas.cifs.shares.file_umask</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.home_directory | boolean | query | False | <p>Filter by volumes.nas.cifs.shares.home_directory</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.namespace_caching | boolean | query | False | <p>Filter by volumes.nas.cifs.shares.namespace_caching</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| volumes.nas.cifs.sha res.oplocks | boolean | query | False | Filter by volumes.nas.cifs.shares.oplocks <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.offline_files | string | query | False | Filter by volumes.nas.cifs.shares.offline_files <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.access_based_enumeration | boolean | query | False | Filter by volumes.nas.cifs.shares.access_based_enumeration <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.name | string | query | False | Filter by volumes.nas.cifs.shares.name <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 80 • minLength: 1 |
| volumes.nas.cifs.sha res.acls.user_or_group | string | query | False | Filter by volumes.nas.cifs.shares.acls.user_or_group <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.sha res.acls.type | string | query | False | Filter by volumes.nas.cifs.shares.acls.type <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| volumes.nas.cifs.shares.acls.permission | string | query | False | Filter by volumes.nas.cifs.shares.acls.permission <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.acls.win_sid_unix_id | string | query | False | Filter by volumes.nas.cifs.shares.acls.win_sid_unix_id <ul style="list-style-type: none"> • Introduced in: 9.16 |
| volumes.nas.cifs.shares.dir_umask | integer | query | False | Filter by volumes.nas.cifs.shares.dir_umask <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.allow_unencrypted_access | boolean | query | False | Filter by volumes.nas.cifs.shares.allow_unencrypted_access <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.change_notify | boolean | query | False | Filter by volumes.nas.cifs.shares.change_notify <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.cifs.shares.no_strict_security | boolean | query | False | Filter by volumes.nas.cifs.shares.no_strict_security <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|-----------------------------------|---------|-------|----------|---|
| volumes.nas.security_style | string | query | False | Filter by volumes.nas.security_style <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.unix_permissions | integer | query | False | Filter by volumes.nas.unix_permissions <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.uid | integer | query | False | Filter by volumes.nas.uid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.nas.gid | integer | query | False | Filter by volumes.nas.gid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| volumes.name | string | query | False | Filter by volumes.name <ul style="list-style-type: none"> • maxLength: 203 • minLength: 1 |
| volumes.comment | string | query | False | Filter by volumes.comment <ul style="list-style-type: none"> • maxLength: 1023 • minLength: 0 |
| consistency_groups.tiering.policy | string | query | False | Filter by consistency_groups.tiering.policy |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| consistency_groups.namespaces.uuid | string | query | False | Filter by consistency_groups.namespaces.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.status.read_only | boolean | query | False | Filter by consistency_groups.namespaces.status.read_only <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.status.mapped | boolean | query | False | Filter by consistency_groups.namespaces.status.mapped <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.status.container_state | string | query | False | Filter by consistency_groups.namespaces.status.container_state <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.status.state | string | query | False | Filter by consistency_groups.namespaces.status.state <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.auto_delete | boolean | query | False | Filter by consistency_groups.namespaces.auto_delete <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|--|
| consistency_groups.namespaces.subsystem_map.nsid | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.nsid</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.subsystem_map.subsystem.name | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.name</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 64 • minLength: 1 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.group_size | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.group_size</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.mode | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.mode</p> <ul style="list-style-type: none"> • Introduced in: 9.16 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.hash_function | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.dh_hmac_chap.hash_function</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|---|
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.nqn | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.nqn</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.priority | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.priority</p> <ul style="list-style-type: none"> • Introduced in: 9.14 |
| consistency_groups.namespaces.subsystem_map.subsystem.hosts.tls.key_type | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.hosts.tls.key_type</p> <ul style="list-style-type: none"> • Introduced in: 9.16 |
| consistency_groups.namespaces.subsystem_map.subsystem.uuid | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.uuid</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.subsystem_map.subsystem.os_type | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.os_type</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| consistency_groups.namespaces.subsystem_map.subsystem.comment | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.subsystem.comment</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 255 • minLength: 0 |
| consistency_groups.namespaces.subsystem_map.anagrpid | string | query | False | <p>Filter by consistency_groups.namespaces.subsystem_map.anagrpid</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.os_type | string | query | False | <p>Filter by consistency_groups.namespaces.os_type</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.space.block_size | integer | query | False | <p>Filter by consistency_groups.namespaces.space.block_size</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.namespaces.space.guarantee.requested | boolean | query | False | <p>Filter by consistency_groups.namespaces.space.guarantee.requested</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| consistency_groups.namespaces.space.guarantee.reserved | boolean | query | False | Filter by consistency_groups.namespaces.space.guarantee.reserved <ul style="list-style-type: none"> Introduced in: 9.12 |
| consistency_groups.namespaces.space.size | integer | query | False | Filter by consistency_groups.namespaces.space.size <ul style="list-style-type: none"> Introduced in: 9.12 Max value: 140737488355328 Min value: 4096 |
| consistency_groups.namespaces.space.used | integer | query | False | Filter by consistency_groups.namespaces.space.used <ul style="list-style-type: none"> Introduced in: 9.12 |
| consistency_groups.namespaces.create_time | string | query | False | Filter by consistency_groups.namespaces.create_time <ul style="list-style-type: none"> Introduced in: 9.12 |
| consistency_groups.namespaces.enabled | boolean | query | False | Filter by consistency_groups.namespaces.enabled <ul style="list-style-type: none"> Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---------------------------------------|---------|-------|----------|--|
| consistency_groups.namespaces.comment | string | query | False | <p>Filter by consistency_groups.namespaces.comment</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 254 • minLength: 0 |
| consistency_groups.namespaces.name | string | query | False | <p>Filter by consistency_groups.namespaces.name</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.space.available | integer | query | False | Filter by consistency_groups.space.available |
| consistency_groups.space.size | integer | query | False | Filter by consistency_groups.space.size |
| consistency_groups.space.used | integer | query | False | Filter by consistency_groups.space.used |
| consistency_groups.qos.policy.uuid | string | query | False | Filter by consistency_groups.qos.policy.uuid |
| consistency_groups.qos.policy.name | string | query | False | Filter by consistency_groups.qos.policy.name |
| consistency_groups.uuid | string | query | False | Filter by consistency_groups.uuid |
| consistency_groups.application.type | string | query | False | <p>Filter by consistency_groups.application.type</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| consistency_groups.application.component_type | string | query | False | Filter by consistency_groups.application.component_type <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups._tags | string | query | False | Filter by consistency_groups._tags <ul style="list-style-type: none"> • Introduced in: 9.15 |
| consistency_groups.volumes.snapshot_policy.uuid | string | query | False | Filter by consistency_groups.volumes.snapshot_policy.uuid |
| consistency_groups.volumes.snapshot_policy.name | string | query | False | Filter by consistency_groups.volumes.snapshot_policy.name |
| consistency_groups.volumes.tiering.policy | string | query | False | Filter by consistency_groups.volumes.tiering.policy |
| consistency_groups.volumes.uuid | string | query | False | Filter by consistency_groups.volumes.uuid |
| consistency_groups.volumes.qos.policy.uuid | string | query | False | Filter by consistency_groups.volumes.qos.policy.uuid |
| consistency_groups.volumes.qos.policy.name | string | query | False | Filter by consistency_groups.volumes.qos.policy.name |
| consistency_groups.volumes.space.used | integer | query | False | Filter by consistency_groups.volumes.space.used |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| consistency_groups.volumes.space.size | integer | query | False | Filter by consistency_groups.volumes.space.size |
| consistency_groups.volumes.space.available | integer | query | False | Filter by consistency_groups.volumes.space.available |
| consistency_groups.volumes.nas.export_policy.id | integer | query | False | Filter by consistency_groups.volumes.nas.export_policy.id <ul style="list-style-type: none"> • Introduced in: 9.14 |
| consistency_groups.volumes.nas.export_policy.rules.superuser | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.superuser <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.index | integer | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.index <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.allow_device_creation | boolean | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.allow_device_creation <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| consistency_groups.volumes.nas.export_policy.rules.allow_suid | boolean | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.allow_suid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.rw_rule | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.rw_rule <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.clients.match | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.clients.match <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.chown_mode | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.chown_mode <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.anonymous_user | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.anonymous_user <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|--------|-------|----------|---|
| consistency_groups.volumes.nas.export_policy.rules.ntfs_unix_security | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.ntfs_unix_security <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.ro_rule | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.ro_rule <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.rules.protocols | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.rules.protocols <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.export_policy.name | string | query | False | Filter by consistency_groups.volumes.nas.export_policy.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.junction_parent.name | string | query | False | Filter by consistency_groups.volumes.nas.junction_parent.name <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.junction_parent.uuid | string | query | False | Filter by consistency_groups.volumes.nas.junction_parent.uuid <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| consistency_groups.volumes.nas.path | string | query | False | Filter by consistency_groups.volumes.nas.path <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.unix_symlink | string | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.unix_symlink <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.show_snapshot | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.show_snapshot <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.vscan_profile | string | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.vscan_profile <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.comment | string | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.comment <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 256 • minLength: 1 |
| consistency_groups.volumes.nas.cifs.shares.continuously_available | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.continuously_available <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| consistency_groups.volumes.nas.cifs.shares.encryption | boolean | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.encryption</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.file_umask | integer | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.file_umask</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.home_directory | boolean | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.home_directory</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.namespace_caching | boolean | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.namespace_caching</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.oplocks | boolean | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.oplocks</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.offline_files | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.offline_files</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| consistency_groups.volumes.nas.cifs.shares.access_basedEnumeration | boolean | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.access_basedEnumeration</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.name | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.name</p> <ul style="list-style-type: none"> • Introduced in: 9.12 • maxLength: 80 • minLength: 1 |
| consistency_groups.volumes.nas.cifs.shares.acls.user_or_group | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.acls.user_or_group</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.acls.type | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.acls.type</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.acls.permission | string | query | False | <p>Filter by consistency_groups.volumes.nas.cifs.shares.acls.permission</p> <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|---|
| consistency_groups.volumes.nas.cifs.shares.acls.win_sid_unix_id | string | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.acls.win_sid_unix_id <ul style="list-style-type: none"> • Introduced in: 9.16 |
| consistency_groups.volumes.nas.cifs.shares.dir_umask | integer | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.dir_umask <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.allow_unencrypted_access | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.allow_unencrypted_access <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.change_notify | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.change_notify <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.cifs.shares.no_strict_security | boolean | query | False | Filter by consistency_groups.volumes.nas.cifs.shares.no_strict_security <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.security_style | string | query | False | Filter by consistency_groups.volumes.nas.security_style <ul style="list-style-type: none"> • Introduced in: 9.12 |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| consistency_groups.volumes.nas.unix_permissions | integer | query | False | Filter by consistency_groups.volumes.nas.unix_permissions <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.uid | integer | query | False | Filter by consistency_groups.volumes.nas.uid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.nas.gid | integer | query | False | Filter by consistency_groups.volumes.nas.gid <ul style="list-style-type: none"> • Introduced in: 9.12 |
| consistency_groups.volumes.name | string | query | False | Filter by consistency_groups.volumes.name <ul style="list-style-type: none"> • maxLength: 203 • minLength: 1 |
| consistency_groups.volumes.comment | string | query | False | Filter by consistency_groups.volumes.comment <ul style="list-style-type: none"> • maxLength: 1023 • minLength: 0 |
| consistency_groups.snapshot_policy.uuid | string | query | False | Filter by consistency_groups.snapshot_policy.uuid |
| consistency_groups.snapshot_policy.name | string | query | False | Filter by consistency_groups.snapshot_policy.name |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|---|
| consistency_groups.name | string | query | False | Filter by consistency_groups.name |
| consistency_groups.luns.serial_number | string | query | False | Filter by consistency_groups.luns.serial_number <ul style="list-style-type: none"> • maxLength: 12 • minLength: 12 |
| consistency_groups.luns.name | string | query | False | Filter by consistency_groups.luns.name |
| consistency_groups.luns.lun_maps.igroup.initiators.comment | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.initiators.comment <ul style="list-style-type: none"> • maxLength: 254 • minLength: 0 |
| consistency_groups.luns.lun_maps.igroup.initiators.name | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.initiators.name |
| consistency_groups.luns.lun_maps.igroup.comment | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.comment <ul style="list-style-type: none"> • Introduced in: 9.11 • maxLength: 254 • minLength: 0 |
| consistency_groups.luns.lun_maps.igroup.os_type | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.os_type |
| consistency_groups.luns.lun_maps.igroup.uuid | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.uuid |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|---|
| consistency_groups.luns.lun_maps.igroups.name | string | query | False | Filter by consistency_groups.luns.lun_maps.igroups.name <ul style="list-style-type: none"> • maxLength: 96 • minLength: 1 |
| consistency_groups.luns.lun_maps.igroups.uuid | string | query | False | Filter by consistency_groups.luns.lun_maps.igroups.uuid |
| consistency_groups.luns.lun_maps.igroup.protocol | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.protocol |
| consistency_groups.luns.lun_maps.igroup.name | string | query | False | Filter by consistency_groups.luns.lun_maps.igroup.name <ul style="list-style-type: none"> • maxLength: 96 • minLength: 1 |
| consistency_groups.luns.lun_maps.logical_unit_number | integer | query | False | Filter by consistency_groups.luns.lun_maps.logical_unit_number |
| consistency_groups.luns.comment | string | query | False | Filter by consistency_groups.luns.comment <ul style="list-style-type: none"> • maxLength: 254 • minLength: 0 |
| consistency_groups.luns.create_time | string | query | False | Filter by consistency_groups.luns.create_time |
| consistency_groups.luns.enabled | boolean | query | False | Filter by consistency_groups.luns.enabled |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| consistency_groups.luns.os_type | string | query | False | Filter by consistency_groups.luns.os_type |
| consistency_groups.luns.qos.policy.min_throughput_mbps | integer | query | False | Filter by consistency_groups.luns.qos.policy.min_throughput_mbps <ul style="list-style-type: none"> • Max value: 4194303 • Min value: 0 |
| consistency_groups.luns.qos.policy.max_throughput_mbps | integer | query | False | Filter by consistency_groups.luns.qos.policy.max_throughput_mbps <ul style="list-style-type: none"> • Max value: 4194303 • Min value: 0 |
| consistency_groups.luns.qos.policy.uuid | string | query | False | Filter by consistency_groups.luns.qos.policy.uuid |
| consistency_groups.luns.qos.policy.min_throughput_iops | integer | query | False | Filter by consistency_groups.luns.qos.policy.min_throughput_iops <ul style="list-style-type: none"> • Max value: 2147483647 • Min value: 0 |
| consistency_groups.luns.qos.policy.name | string | query | False | Filter by consistency_groups.luns.qos.policy.name |

| Name | Type | In | Required | Description |
|--|---------|-------|----------|--|
| consistency_groups.luns.qos.policy.max_throughput_iops | integer | query | False | Filter by consistency_groups.luns.qos.policy.max_throughput_iops <ul style="list-style-type: none"> • Max value: 2147483647 • Min value: 0 |
| consistency_groups.luns.uuid | string | query | False | Filter by consistency_groups.luns.uuid |
| consistency_groups.luns.space.size | integer | query | False | Filter by consistency_groups.luns.space.size <ul style="list-style-type: none"> • Max value: 140737488355328 • Min value: 4096 |
| consistency_groups.luns.space.used | integer | query | False | Filter by consistency_groups.luns.space.used |
| consistency_groups.luns.space.guarantee.requested | boolean | query | False | Filter by consistency_groups.luns.space.guarantee.requested <ul style="list-style-type: none"> • Introduced in: 9.11 |
| consistency_groups.luns.space.guarantee.reserved | boolean | query | False | Filter by consistency_groups.luns.space.guarantee.reserved <ul style="list-style-type: none"> • Introduced in: 9.11 |
| consistency_groups.svm.name | string | query | False | Filter by consistency_groups.svm.name |

| Name | Type | In | Required | Description |
|--|--------|-------|----------|--|
| consistency_groups.svm.uuid | string | query | False | Filter by consistency_groups.svm.uuid |
| consistency_groups.parent_consistency_group.uuid | string | query | False | Filter by consistency_groups.parent_consistency_group.uuid |
| consistency_groups.parent_consistency_group.name | string | query | False | Filter by consistency_groups.parent_consistency_group.name |
| luns.serial_number | string | query | False | Filter by luns.serial_number <ul style="list-style-type: none"> • maxLength: 12 • minLength: 12 |
| luns.name | string | query | False | Filter by luns.name |
| luns.lun_maps.igroup.initiators.comment | string | query | False | Filter by luns.lun_maps.igroup.initiators.comment <ul style="list-style-type: none"> • maxLength: 254 • minLength: 0 |
| luns.lun_maps.igroup.initiators.name | string | query | False | Filter by luns.lun_maps.igroup.initiators.name |
| luns.lun_maps.igroup.comment | string | query | False | Filter by luns.lun_maps.igroup.comment <ul style="list-style-type: none"> • Introduced in: 9.11 • maxLength: 254 • minLength: 0 |
| luns.lun_maps.igroup.os_type | string | query | False | Filter by luns.lun_maps.igroup.os_type |

| Name | Type | In | Required | Description |
|-----------------------------------|---------|-------|----------|---|
| luns.lun_maps.igroup.uuid | string | query | False | Filter by luns.lun_maps.igroup.uuid |
| luns.lun_maps.igroup.igroups.name | string | query | False | Filter by luns.lun_maps.igroup.igroups.name <ul style="list-style-type: none"> • maxLength: 96 • minLength: 1 |
| luns.lun_maps.igroup.igroups.uuid | string | query | False | Filter by luns.lun_maps.igroup.igroups.uuid |
| luns.lun_maps.igroup.protocol | string | query | False | Filter by luns.lun_maps.igroup.protocol |
| luns.lun_maps.igroup.name | string | query | False | Filter by luns.lun_maps.igroup.name <ul style="list-style-type: none"> • maxLength: 96 • minLength: 1 |
| luns.lun_maps.logical_unit_number | integer | query | False | Filter by luns.lun_maps.logical_unit_number |
| luns.comment | string | query | False | Filter by luns.comment <ul style="list-style-type: none"> • maxLength: 254 • minLength: 0 |
| luns.create_time | string | query | False | Filter by luns.create_time |
| luns.enabled | boolean | query | False | Filter by luns.enabled |
| luns.os_type | string | query | False | Filter by luns.os_type |

| Name | Type | In | Required | Description |
|---|---------|-------|----------|--|
| luns.qos.policy.min_t hroughput_mbps | integer | query | False | Filter by luns.qos.policy.min_ throughput_mbps <ul style="list-style-type: none"> • Max value: 4194303 • Min value: 0 |
| luns.qos.policy.max_ throughput_mbps | integer | query | False | Filter by luns.qos.policy.max _throughput_mbps <ul style="list-style-type: none"> • Max value: 4194303 • Min value: 0 |
| luns.qos.policy.uuid | string | query | False | Filter by luns.qos.policy.uuid |
| luns.qos.policy.min_t hroughput_iops | integer | query | False | Filter by luns.qos.policy.min_ throughput_iops <ul style="list-style-type: none"> • Max value: 2147483647 • Min value: 0 |
| luns.qos.policy.name | string | query | False | Filter by luns.qos.policy.name |
| luns.qos.policy.max_ throughput_iops | integer | query | False | Filter by luns.qos.policy.max _throughput_iops <ul style="list-style-type: none"> • Max value: 2147483647 • Min value: 0 |
| luns.uuid | string | query | False | Filter by luns.uuid |

| Name | Type | In | Required | Description |
|---------------------------------|---------|-------|----------|--|
| luns.space.size | integer | query | False | Filter by luns.space.size <ul style="list-style-type: none"> • Max value: 1407374883553 28 • Min value: 4096 |
| luns.space.used | integer | query | False | Filter by luns.space.used |
| luns.space.guarante.e.requested | boolean | query | False | Filter by luns.space.guarante.e.requested <ul style="list-style-type: none"> • Introduced in: 9.11 |
| luns.space.guarante.e.reserved | boolean | query | False | Filter by luns.space.guarante.e.reserved <ul style="list-style-type: none"> • Introduced in: 9.11 |
| svm.name | string | query | False | Filter by svm.name |
| svm.uuid | string | query | False | Filter by svm.uuid |
| metric.duration | string | query | False | Filter by metric.duration <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.used_space | integer | query | False | Filter by metric.used_space <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.latency.write | integer | query | False | Filter by metric.latency.write <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|-------------------------|---------|-------|----------|---|
| metric.latency.total | integer | query | False | Filter by metric.latency.total <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.latency.read | integer | query | False | Filter by metric.latency.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.latency.other | integer | query | False | Filter by metric.latency.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.available_space | integer | query | False | Filter by metric.available_space <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.size | integer | query | False | Filter by metric.size <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.throughput.write | integer | query | False | Filter by metric.throughput.write <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.throughput.total | integer | query | False | Filter by metric.throughput.total <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|-------------------------|---------|-------|----------|---|
| metric.throughput.read | integer | query | False | Filter by metric.throughput.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.throughput.other | integer | query | False | Filter by metric.throughput.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.timestamp | string | query | False | Filter by metric.timestamp <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.iops.write | integer | query | False | Filter by metric.iops.write <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.iops.total | integer | query | False | Filter by metric.iops.total <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.iops.read | integer | query | False | Filter by metric.iops.read <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.iops.other | integer | query | False | Filter by metric.iops.other <ul style="list-style-type: none"> • Introduced in: 9.13 |
| metric.status | string | query | False | Filter by metric.status <ul style="list-style-type: none"> • Introduced in: 9.13 |

| Name | Type | In | Required | Description |
|-------------------------------|---------------|-------|----------|--|
| name | string | query | False | Filter by name |
| replication_source | boolean | query | False | Filter by replication_source |
| parent_consistency_group.uuid | string | query | False | Filter by parent_consistency_group.uuid |
| parent_consistency_group.name | string | query | False | Filter by parent_consistency_group.name |
| fields | array[string] | query | False | Specify the fields to return. |
| max_records | integer | query | False | Limit the number of records returned. |
| return_records | boolean | query | False | <p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> Default value: 1 |
| return_timeout | integer | query | False | <p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> Max value: 120 Min value: 0 Default value: 1 |

| Name | Type | In | Required | Description |
|----------|---------------|-------|----------|--|
| order_by | array[string] | query | False | Order results by specified fields and optional [asc] |

Response

Status: 200, Ok

| Name | Type | Description |
|--------------------|---|---|
| _links | self_link | |
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |
| application | application | |
| clone | clone | Creates a clone of an existing consistency group from the current contents or an existing snapshot. |
| consistency_groups | array[consistency_groups] | A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A consistency group can only be associated with one direct parent consistency group. |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |
| metric | metric | Performance and capacity numbers, such as, IOPS, latency, throughput, used space, and available space. |

| Name | Type | Description |
|--------------------------|--|--|
| name | string | Name of the consistency group. The consistency group name must be unique within an SVM. |
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| qos | qos | |

| Name | Type | Description |
|---------------------------|--|---|
| replicated | boolean | Indicates whether or not replication has been enabled on this consistency group. |
| replication_relationships | array[replication_relationships] | Indicates the SnapMirror relationship of this consistency group. |
| replication_source | boolean | Since support for this field is to be removed in the next release, use replication_relationships.is_source instead. |
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| space | space | Space information for the consistency group. |
| statistics | statistics | These are raw performance and space numbers, such as, IOPS, latency, throughput, used space, and available space. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster. |
| svm | svm | The Storage Virtual Machine (SVM) in which the consistency group is located. |
| tiering | tiering | The tiering placement and policy definitions for volumes in this consistency group. |

| Name | Type | Description |
|---------|----------------------------------|--|
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> • example: 1cd8a442-86d1-11e0-ae1c-123478563412 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

Example response

```
{  
  "_links": {  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "_tags": [  
    "team:csi",  
    "environment:test"  
  ],  
  "application": {  
    "component_type": "string",  
    "type": "string"  
  },  
  "clone": {  
    "guarantee": {  
      "type": "string"  
    },  
    "parent_consistency_group": {  
      "_links": {  
        "self": {  
          "href": "/api/resourcelink"  
        }  
      },  
      "name": "string",  
      "uuid": "string"  
    },  
    "parent_snapshot": {  
      "_links": {  
        "self": {  
          "href": "/api/resourcelink"  
        }  
      },  
      "name": "this_snapshot",  
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"  
    },  
    "parent_svm": {  
      "_links": {  
        "self": {  
          "href": "/api/resourcelink"  
        }  
      },  
      "name": "svm1",  
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    }  
}
```

```

} ,
"split_complete_percent": 0,
"split_estimate": 0,
"volume": {
  "prefix": "string",
  "suffix": "string"
}
},
"consistency_groups": [
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "_tags": [
    "team:csi",
    "environment:test"
  ],
  "application": {
    "component_type": "string",
    "type": "string"
  },
  "luns": [
    {
      "comment": "string",
      "create_time": "2018-06-04 15:00:00 -0400",
      "lun_maps": [
        {
          "igroup": {
            "comment": "string",
            "igroups": [
              {
                "_links": {
                  "self": {
                    "href": "/api/resourcelink"
                  }
                },
                "name": "igroup1",
                "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
              }
            ],
            "initiators": [
              {
                "comment": "my comment",
                "name": "iqn.1998-01.com.corp.iscsi:name1"
              }
            ]
          }
        }
      ]
    }
  }
}

```

```
        },
        "name": "igroup1",
        "os_type": "string",
        "protocol": "string",
        "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
    },
},
],
"name": "/vol/volume1/lun1",
"os_type": "string",
"qos": {
    "policy": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "max_throughput_iops": 10000,
        "max_throughput_mbps": 500,
        "min_throughput_iops": 2000,
        "min_throughput_mbps": 500,
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"serial_number": "string",
"space": {
    "size": 1073741824,
    "used": 0
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
],
"name": "string",
"namespaces": [
{
    "comment": "string",
    "create_time": "2018-06-04 15:00:00 -0400",
    "name": "/vol/volume1/qtree1/namespac1",
    "os_type": "string",
    "space": {
        "block_size": 512,
        "size": 1073741824,
        "used": 0
    }
},
```

```

"status": {
    "container_state": "string",
    "state": "online"
},
"subsystem_map": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "anagrpid": "00103050h",
    "nsid": "00000001h",
    "subsystem": {
        "comment": "string",
        "hosts": [
            {
                "dh_hmac_chap": {
                    "group_size": "string",
                    "hash_function": "string",
                    "mode": "bidirectional"
                },
                "nqn": "nqn.1992-01.example.com:string",
                "priority": "string",
                "tls": {
                    "key_type": "configured"
                }
            }
        ],
        "name": "subsystem1",
        "os_type": "string",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"parent_consistency_group": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "my_consistency_group",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"qos": {

```

```
  "policy": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "performance",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  }
},
"restore_to": {
  "snapshot": {
    "name": "string",
    "uuid": "string"
  }
},
"snapshot_policy": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "default",
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"space": {
  "available": 5737418,
  "size": 1073741824,
  "used": 5737418
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svml1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"tiering": {
  "object_stores": [
    {}
  ],
  "policy": "string"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412",
```

```

"volumes": [
  {
    "comment": "string",
    "name": "vol_cs_dept",
    "nas": {
      "cifs": {
        "shares": [
          {
            "_links": {
              "self": {
                "href": "/api/resourcelink"
              }
            },
            "acls": [
              {
                "_links": {
                  "self": {
                    "href": "/api/resourcelink"
                  }
                },
                "permission": "string",
                "type": "string",
                "user_or_group": "ENGDOMAIN\\ad_user",
                "win_sid_unix_id": "string"
              }
            ],
            "comment": "HR Department Share",
            "dir_umask": 18,
            "file_umask": 18,
            "name": "HR_SHARE",
            "offline_files": "string",
            "unix_symlink": "string",
            "vscan_profile": "string"
          }
        ]
      },
      "export_policy": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "id": 0,
        "name": "string",
        "rules": [
          {

```

```

        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "anonymous_user": "string",
        "chown_mode": "string",
        "clients": [
            {
                "match": "0.0.0.0/0"
            }
        ],
        "ntfs_unix_security": "string",
        "protocols": [
            "string"
        ],
        "ro_rule": [
            "string"
        ],
        "rw_rule": [
            "string"
        ],
        "superuser": [
            "string"
        ]
    }
},
"junction_parent": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "vs1_root",
    "uuid": "75c9cfb0-3eb4-11eb-9fb4-005056bb088a"
},
"path": "/user/my_volume",
"security_style": "string",
"unix_permissions": 493
},
"qos": {
    "policy": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        }
    }
}

```



```

        "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
    }
],
"initiators": [
{
    "comment": "my comment",
    "name": "iqn.1998-01.com.corp.iscsi:namel"
}
],
"name": "igroup1",
"os_type": "string",
"protocol": "string",
"uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
}
}
],
"name": "/vol/volumel/lun1",
"os_type": "string",
"qos": {
    "policy": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "max_throughput_iops": 10000,
        "max_throughput_mbps": 500,
        "min_throughput_iops": 2000,
        "min_throughput_mbps": 500,
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"serial_number": "string",
"space": {
    "size": 1073741824,
    "used": 0
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
],
"metric": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    }
}
]

```

```
},
"available_space": 4096,
"duration": "PT15S",
"iops": {
  "read": 200,
  "total": 1000,
  "write": 100
},
"latency": {
  "read": 200,
  "total": 1000,
  "write": 100
},
"size": 4096,
"status": "ok",
"throughput": {
  "read": 200,
  "total": 1000,
  "write": 100
},
"timestamp": "2017-01-25 06:20:13 -0500",
"used_space": 4096
},
"name": "string",
"namespaces": [
{
  "comment": "string",
  "create_time": "2018-06-04 15:00:00 -0400",
  "name": "/vol/volume1/qtree1/namespace1",
  "os_type": "string",
  "space": {
    "block_size": 512,
    "size": 1073741824,
    "used": 0
  },
  "status": {
    "container_state": "string",
    "state": "online"
  },
  "subsystem_map": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "anagrpid": "00103050h",
    "id": "string"
  }
}
]
```

```

    "nsid": "00000001h",
    "subsystem": {
        "comment": "string",
        "hosts": [
            {
                "dh_hmac_chap": {
                    "group_size": "string",
                    "hash_function": "string",
                    "mode": "bidirectional"
                },
                "nqn": "nqn.1992-01.example.com:string",
                "priority": "string",
                "tls": {
                    "key_type": "configured"
                }
            }
        ],
        "name": "subsystem1",
        "os_type": "string",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
],
"parent_consistency_group": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "my_consistency_group",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"qos": {
    "policy": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"replication_relationships": [

```

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
],
"restore_to": {
  "snapshot": {
    "name": "string",
    "uuid": "string"
  }
},
"snapshot_policy": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "default",
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"space": {
  "available": 5737418,
  "size": 1073741824,
  "used": 5737418
},
"statistics": {
  "available_space": 4096,
  "iops_raw": {
    "read": 200,
    "total": 1000,
    "write": 100
  },
  "latency_raw": {
    "read": 200,
    "total": 1000,
    "write": 100
  },
  "size": 4096,
  "status": "ok",
  "throughput_raw": {
    "read": 200,
    "total": 1000,
    "write": 100
  }
}
```

```
        "write": 100
    },
    "timestamp": "2017-01-25 06:20:13 -0500",
    "used_space": 4096
},
"svm": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"tiering": {
    "object_stores": [
        {}
    ],
    "policy": "string"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412",
"volumes": [
    {
        "comment": "string",
        "name": "vol_cs_dept",
        "nas": {
            "cifs": {
                "shares": [
                    {
                        "_links": {
                            "self": {
                                "href": "/api/resourcelink"
                            }
                        },
                        "acls": [
                            {
                                "_links": {
                                    "self": {
                                        "href": "/api/resourcelink"
                                    }
                                },
                                "permission": "string",
                                "type": "string",
                                "user_or_group": "ENGDOMAIN\\ad_user",
                                "win_sid_unix_id": "string"
                            }
                        ]
                    }
                ]
            }
        }
    }
]
```

```
        ],
        "comment": "HR Department Share",
        "dir_umask": 18,
        "file_umask": 18,
        "name": "HR_SHARE",
        "offline_files": "string",
        "unix_symlink": "string",
        "vscan_profile": "string"
    }
]
},
"export_policy": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "id": 0,
    "name": "string",
    "rules": [
        {
            "_links": {
                "self": {
                    "href": "/api/resourcelink"
                }
            },
            "anonymous_user": "string",
            "chown_mode": "string",
            "clients": [
                {
                    "match": "0.0.0.0/0"
                }
            ],
            "ntfs_unix_security": "string",
            "protocols": [
                "string"
            ],
            "ro_rule": [
                "string"
            ],
            "rw_rule": [
                "string"
            ],
            "superuser": [
                "string"
            ]
        }
    ]
}
```

```
        }
    ],
},
"junction_parent": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "vs1_root",
    "uuid": "75c9cfb0-3eb4-11eb-9fb4-005056bb088a"
},
"path": "/user/my_volume",
"security_style": "string",
"unix_permissions": 493
},
"qos": {
    "policy": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"snapshot_policy": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"space": {
    "available": 0,
    "used": 0
},
"tiering": {
    "object_stores": [
        {}
    ],
    "policy": "string"
},
```

```
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
    }
]
}
```

Error

Status: Default

ONTAP Error Response Codes

| Error Code | Description |
|------------|--|
| 53411842 | Consistency group does not exist. |
| 53411843 | A consistency group with specified UUID was not found. |
| 53411844 | Specified consistency group was not found in the specified SVM. |
| 53411845 | The specified UUID and name refer to different consistency groups. |
| 53411846 | Either name or UUID must be provided. |

Also see the table of common errors in the [Response body](#) overview section of this documentation.

| Name | Type | Description |
|-------|--------------------------------|-------------|
| error | returned_error | |

Example error

```
{  
  "error": {  
    "arguments": [  
      {  
        "code": "string",  
        "message": "string"  
      }  
    ],  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

self_link

| Name | Type | Description |
|------|------|-------------|
| self | href | |

application

| Name | Type | Description |
|----------------|--------|----------------------------------|
| component_type | string | Nested consistency group tag. |
| type | string | Top level consistency group tag. |

guarantee

| Name | Type | Description |
|------|--------|--|
| type | string | The type of space guarantee of this volume in the aggregate. |

parent_consistency_group

Consistency group that is to be cloned.

| Name | Type | Description |
|--------|-----------|---|
| _links | self_link | |
| name | string | The name of the consistency group. |
| uuid | string | The unique identifier of the consistency group. |

_links

| Name | Type | Description |
|------|------|-------------|
| self | href | |

parent_snapshot

Consistency group that is to be cloned.

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

parent_svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

Volume name suffix/prefix for the cloned volumes.

| Name | Type | Description |
|--------|--------|--|
| prefix | string | Volume name prefix for cloned volumes. |
| suffix | string | Volume name suffix for cloned volumes. |

clone

Creates a clone of an existing consistency group from the current contents or an existing snapshot.

| Name | Type | Description |
|--------------------------|--|--|
| guarantee | guarantee | |
| is_flexclone | boolean | Specifies if this consistency group is a FlexClone of a consistency group. |
| parent_consistency_group | parent_consistency_group | Consistency group that is to be cloned. |

| Name | Type | Description |
|------------------------|---------------------------------|--|
| parent_snapshot | parent_snapshot | Consistency group that is to be cloned. |
| parent_svm | parent_svm | SVM, applies only to SVM-scoped objects. |
| split_complete_percent | integer | Percentage of FlexClone blocks split from its parent consistency group. |
| split_estimate | integer | Space required to split the FlexClone consistency group. |
| split_initiated | boolean | Splits volumes after cloning. Defaults to false during POST. Only accepts true during a PATCH. |
| volume | volume | Volume name suffix/prefix for the cloned volumes. |

source

The source LUN for a LUN clone operation. This can be specified using property `clone.source.uuid` or `clone.source.name`. If both properties are supplied, they must refer to the same LUN.

Valid in POST to create a new LUN as a clone of the source.

Valid in PATCH to overwrite an existing LUN's data as a clone of another.

clone

This sub-object is used in POST to create a new LUN as a clone of an existing LUN, or PATCH to overwrite an existing LUN as a clone of another. Setting a property in this sub-object indicates that a LUN clone is desired. Consider the following other properties when cloning a LUN: `auto_delete`, `qos_policy`, `space.guarantee.requested` and `space.scsi_thin_provisioning_enabled`.

When used in a PATCH, the patched LUN's data is over-written as a clone of the source and the following properties are preserved from the patched LUN unless otherwise specified as part of the PATCH: `class`, `auto_delete`, `lun_maps`, `serial_number`, `status.state`, and `uuid`.

Persistent reservations for the patched LUN are also preserved.

igroups

| Name | Type | Description |
|---------------------|---------------------------|-------------|
| <code>_links</code> | self_link | |

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the initiator group. |
| uuid | string | The unique identifier of the initiator group. |

initiators

The initiators that are members of the initiator group.

| Name | Type | Description |
|---------|--------|--|
| comment | string | A comment available for use by the administrator. |
| name | string | Name of initiator that is a member of the initiator group. |

igroup

The initiator group that directly owns the initiator, which is where modification of the initiator is supported. This property will only be populated when the initiator is a member of a nested initiator group.

| Name | Type | Description |
|---------|--------|--|
| comment | string | A comment available for use by the administrator. Valid in POST and PATCH. |

| Name | Type | Description |
|------------|-------------------------------------|---|
| igroups | array[igroups] | <p>The existing initiator groups that are members of the group. Optional in POST.</p> <p>This property is mutually exclusive with the <i>initiators</i> property during POST.</p> <p>This array contains only the direct children of the initiator group. If the member initiator groups have further nested initiator groups, those are reported in the <i>igroups</i> property of the child initiator group.</p> <p>Zero or more nested initiator groups can be supplied when the initiator group is created. The initiator group will act as if it contains the aggregation of all initiators in any nested initiator groups.</p> <p>After creation, nested initiator groups can be added or removed from the initiator group using the <code>/protocols/san/igroups/{igroup.uuid}/igroups</code> endpoint. See DELETE /protocols/san/igroups/{igroup.uuid}/igroups/{uuid} for more details.</p> |
| initiators | array[initiators] | The initiators that are members of the group. |
| name | string | The name of the initiator group. Required in POST; optional in PATCH. |
| os_type | string | The host operating system of the initiator group. All initiators in the group should be hosts of the same operating system. Required in POST; optional in PATCH. |

| Name | Type | Description |
|----------|--------|---|
| protocol | string | <p>The protocols supported by the initiator group. This restricts the type of initiators that can be added to the initiator group. Optional in POST; if not supplied, this defaults to <i>mixed</i>.</p> <p>The protocol of an initiator group cannot be changed after creation of the group.</p> |
| uuid | string | The unique identifier of the initiator group. |

lun_maps

A LUN map is an association between a LUN and an initiator group.

When a LUN is mapped to an initiator group, the initiator group's initiators are granted access to the LUN. The relationship between a LUN and an initiator group is many LUNs to many initiator groups.

| Name | Type | Description |
|---------------------|------------------------|--|
| igroup | igroup | <p>The initiator group that directly owns the initiator, which is where modification of the initiator is supported. This property will only be populated when the initiator is a member of a nested initiator group.</p> |
| logical_unit_number | integer | <p>The logical unit number assigned to the LUN when mapped to the specified initiator group. The number is used to identify the LUN to initiators in the initiator group when communicating through the Fibre Channel Protocol or iSCSI. Optional in POST; if no value is provided, ONTAP assigns the lowest available value. This property is not supported when the <i>provisioning_options.count</i> property is 2 or more.</p> <ul style="list-style-type: none"> • Introduced in: 9.6 • readCreate: 1 • x-nullable: true |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|--------|---------|---|
| action | string | Operation to perform |
| count | integer | Number of elements to perform the operation on. |

policy

The QoS policy

| Name | Type | Description |
|---------------------|---------------------------|---|
| _links | self_link | |
| max_throughput_iops | integer | Specifies the maximum throughput in IOPS, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| max_throughput_mbps | integer | Specifies the maximum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| min_throughput_iops | integer | Specifies the minimum throughput in IOPS, 0 means none. Setting "min_throughput" is supported on AFF platforms only, unless FabricPool tiering policies are set. This is mutually exclusive with name and UUID during POST and PATCH. |
| min_throughput_mbps | integer | Specifies the minimum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| name | string | The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH. |

| Name | Type | Description |
|------|--------|---|
| uuid | string | The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH. |

qos

| Name | Type | Description |
|--------|--------|----------------|
| policy | policy | The QoS policy |

guarantee

Properties that request and report the space guarantee for the LUN.

| Name | Type | Description |
|-----------|---------|--|
| requested | boolean | The requested space reservation policy for the LUN. If <i>true</i> , a space reservation is requested for the LUN; if <i>false</i> , the LUN is thin provisioned. Guaranteeing a space reservation request for a LUN requires that the volume in which the LUN resides is also space reserved and that the fractional reserve for the volume is 100%. Valid in POST and PATCH. |
| reserved | boolean | Reports if the LUN is space guaranteed. If <i>true</i> , a space guarantee is requested and the containing volume and aggregate support the request. If <i>false</i> , a space guarantee is not requested or a space guarantee is requested and either the containing volume or aggregate do not support the request. |

space

The storage space related properties of the LUN.

| Name | Type | Description |
|-----------|-----------|---|
| guarantee | guarantee | Properties that request and report the space guarantee for the LUN. |
| size | integer | <p>The total provisioned size of the LUN. The LUN size can be increased but not reduced using the REST interface. The maximum and minimum sizes listed here are the absolute maximum and absolute minimum sizes, in bytes. The actual minimum and maximum sizes vary depending on the ONTAP version, ONTAP platform, and the available space in the containing volume and aggregate. For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • example: 1073741824 • format: int64 • Max value: 140737488355328 • Min value: 4096 • Introduced in: 9.6 • x-nullable: true |

| Name | Type | Description |
|------|---------|---|
| used | integer | <p>The amount of space consumed by the main data stream of the LUN.</p> <p>This value is the total space consumed in the volume by the LUN, including filesystem overhead, but excluding prefix and suffix streams. Due to internal filesystem overhead and the many ways SAN filesystems and applications utilize blocks within a LUN, this value does not necessarily reflect actual consumption/availability from the perspective of the filesystem or application. Without specific knowledge of how the LUN blocks are utilized outside of ONTAP, this property should not be used as an indicator for an out-of-space condition.</p> <p>For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • format: int64 • readOnly: 1 • Introduced in: 9.6 • x-nullable: true |

luns

A LUN is the logical representation of storage in a storage area network (SAN).

A LUN must be mapped to an initiator group to grant access to the initiator group's initiators (client hosts). Initiators can then access the LUN and perform I/O over a Fibre Channel (FC) fabric using the FC Protocol or a TCP/IP network using iSCSI.

See the LUN object model to learn more about each of the properties supported by the LUN REST API.

A LUN is located within a volume. Optionally, it can be located within a qtree in a volume.

LUN names are paths of the form "/vol/<volume>[/<qtree>]/<lun>" where the qtree name is optional.

A LUN can be created to a specified size using thin or thick provisioning. A LUN can then be renamed, resized, cloned, moved to a different volume and copied. LUNs support the assignment of a QoS policy for performance management or a QoS policy can be assigned to a volume containing one or more LUNs.

```
</lun></qtree></volume>
```

| Name | Type | Description |
|-------------|-----------------|--|
| comment | string | A configurable comment available for use by the administrator. Valid in POST and PATCH. |
| create_time | string | The time the LUN was created. |
| enabled | boolean | The enabled state of the LUN. LUNs can be disabled to prevent access to the LUN. Certain error conditions also cause the LUN to become disabled. If the LUN is disabled, you can consult the state property to determine if the LUN is administratively disabled (<i>offline</i>) or has become disabled as a result of an error. A LUN in an error condition can be brought online by setting the enabled property to <i>true</i> or brought administratively offline by setting the enabled property to <i>false</i> . Upon creation, a LUN is enabled by default. Valid in PATCH. |
| lun_maps | array[lun_maps] | An array of LUN maps. A LUN map is an association between a LUN and an initiator group. When a LUN is mapped to an initiator group, the initiator group's initiators are granted access to the LUN. The relationship between a LUN and an initiator group is many LUNs to many initiator groups. |
| name | string | The fully qualified path name of the LUN composed of the "/vol" prefix, the volume name, the qtree name (optional), and the base name of the LUN. Valid in POST and PATCH. |

| Name | Type | Description |
|---------------|-----------------------|--|
| os_type | string | <p>The operating system type of the LUN.</p> <p>Required in POST when creating a LUN that is not a clone of another. Disallowed in POST when creating a LUN clone.</p> |
| qos | qos | |
| serial_number | string | <p>The LUN serial number. The serial number is generated by ONTAP when the LUN is created.</p> <ul style="list-style-type: none"> • maxLength: 12 • minLength: 12 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |
| space | space | The storage space related properties of the LUN. |
| uuid | string | <p>The unique identifier of the LUN. The UUID is generated by ONTAP when the LUN is created.</p> <ul style="list-style-type: none"> • example: 1cd8a442-86d1-11e0-ae1c-123478563412 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |

guarantee

Properties that request and report the space guarantee for the NVMe namespace.

| Name | Type | Description |
|-----------|---------|--|
| requested | boolean | <p>The requested space reservation policy for the NVMe namespace. If <i>true</i>, a space reservation is requested for the namespace; if <i>false</i>, the namespace is thin provisioned. Guaranteeing a space reservation request for a namespace requires that the volume in which the namespace resides also be space reserved and that the fractional reserve for the volume be 100%.</p> <p>The space reservation policy for an NVMe namespace is determined by ONTAP.</p> <ul style="list-style-type: none"> • Introduced in: 9.6 • x-nullable: true |
| reserved | boolean | <p>Reports if the NVMe namespace is space guaranteed.</p> <p>This property is <i>true</i> if a space guarantee is requested and the containing volume and aggregate support the request. This property is <i>false</i> if a space guarantee is not requested or if a space guarantee is requested and either the containing volume and aggregate do not support the request.</p> |

space

The storage space related properties of the NVMe namespace.

| Name | Type | Description |
|------------|---------|---|
| block_size | integer | <p>The size of blocks in the namespace, in bytes.</p> <p>Valid in POST when creating an NVMe namespace that is not a clone of another. Disallowed in POST when creating a namespace clone. Valid in POST.</p> |

| Name | Type | Description |
|-----------|-----------|--|
| guarantee | guarantee | Properties that request and report the space guarantee for the NVMe namespace. |
| size | integer | <p>The total provisioned size of the NVMe namespace. Valid in POST and PATCH. The NVMe namespace size can be increased but not reduced using the REST interface.</p> <p>The maximum and minimum sizes listed here are the absolute maximum and absolute minimum sizes, in bytes. The maximum size is variable with respect to large NVMe namespace support in ONTAP. If large namespaces are supported, the maximum size is 128 TB (140737488355328 bytes) and if not supported, the maximum size is just under 16 TB (17557557870592 bytes). The minimum size supported is always 4096 bytes.</p> <p>For more information, see Size properties in the docs section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • example: 1073741824 • format: int64 • Max value: 140737488355328 • Min value: 4096 • Introduced in: 9.6 • x-nullable: true |

| Name | Type | Description |
|------|---------|--|
| used | integer | <p>The amount of space consumed by the main data stream of the NVMe namespace.</p> <p>This value is the total space consumed in the volume by the NVMe namespace, including filesystem overhead, but excluding prefix and suffix streams. Due to internal filesystem overhead and the many ways NVMe filesystems and applications utilize blocks within a namespace, this value does not necessarily reflect actual consumption/availability from the perspective of the filesystem or application. Without specific knowledge of how the namespace blocks are utilized outside of ONTAP, this property should not be used as an indicator for an out-of-space condition.</p> <p>For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • format: int64 • readOnly: 1 • Introduced in: 9.6 • x-nullable: true |

status

Status information about the NVMe namespace.

| Name | Type | Description |
|-----------------|--------|---|
| container_state | string | The state of the volume and aggregate that contain the NVMe namespace. Namespaces are only available when their containers are available. |

| Name | Type | Description |
|-----------|---------|---|
| mapped | boolean | <p>Reports if the NVMe namespace is mapped to an NVMe subsystem.</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for either a collection GET or an instance GET unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| read_only | boolean | Reports if the NVMe namespace allows only read access. |
| state | string | The state of the NVMe namespace. Normal states for a namespace are <i>online</i> and <i>offline</i> . Other states indicate errors. |

consistency_group_nvme_host_dh_hmac_chap

A container for the configuration of NVMe in-band authentication using the DH-HMAC-CHAP protocol for a host.

| Name | Type | Description |
|---------------|--------|--|
| group_size | string | <p>The Diffie-Hellman group size for NVMe in-band authentication. When property <code>host_secret_key</code> is provided, this property defaults to <code>2048_bit</code>. When supplied, the property <code>host_secret_key</code> must also be supplied. Optional in POST.</p> |
| hash_function | string | <p>The hash function for NVMe in-band authentication. When property <code>host_secret_key</code> is provided, this property defaults to <code>sha_256</code>. When supplied, the property <code>host_secret_key</code> must also be supplied. Optional in POST.</p> |

| Name | Type | Description |
|------|--------|---|
| mode | string | <p>The expected NVMe in-band authentication mode for the host. This property is an indication of which secrets are configured for the host. When set to:</p> <ul style="list-style-type: none"> • none: The host has neither the host nor controller secret configured, and no authentication is performed. • unidirectional: The host has a host secret configured. The controller will authenticate the host. • bidirectional: The host has both a host and controller secret configured. The controller will authenticate the host and the host will authenticate the controller. |

tls

A container for the configuration for NVMe/TCP-TLS transport session for the host.

| Name | Type | Description |
|----------|--------|--|
| key_type | string | <p>The method by which the TLS pre-shared key (PSK) is configured for the host. Optional in POST.</p> <p>The values for property <code>key_type</code> and property <code>configured_psk</code> must logically agree.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • <code>none</code> - TLS is not configured for the host connection. No value is allowed for property <code>configured_psk</code>. • <code>configured</code> - A user supplied PSK is configured for the NVMe/TCP-TLS transport connection between the host and the NVMe subsystem. A valid value for property <code>configured_psk</code> is required. <p>This property defaults to <code>none</code> unless a value is supplied for <code>configured_psk</code> in which case it defaults to <code>configured</code>.</p> |

consistency_group_nvme_host

The NVMe host provisioned to access NVMe namespaces mapped to a subsystem.

| Name | Type | Description |
|--------------|--|--|
| dh_hmac_chap | consistency_group_nvme_host_dh_hmac_chap | A container for the configuration of NVMe in-band authentication using the DH-HMAC-CHAP protocol for a host. |
| nqn | string | The NVMe qualified name (NQN) used to identify the NVMe storage target. |

| Name | Type | Description |
|----------|---------------------|---|
| priority | string | The host priority setting allocates appropriate NVMe I/O queues (count and depth) for the host to submit I/O commands. Absence of this property in GET implies io_queue count and I/O queue depth are being used. |
| tls | tls | A container for the configuration for NVMe/TCP-TLS transport session for the host. |

consistency_group_nvme_subsystem

An NVMe subsystem maintains configuration state and namespace access control for a set of NVMe-connected hosts.

| Name | Type | Description |
|---------|--|--|
| comment | string | A configurable comment for the NVMe subsystem. Optional in POST and PATCH. |
| hosts | array[consistency_group_nvme_host] | The NVMe hosts configured for access to the NVMe subsystem. Optional in POST. |
| name | string | The name of the NVMe subsystem. Once created, an NVMe subsystem cannot be renamed. Required in POST. |
| os_type | string | The host operating system of the NVMe subsystem's hosts. Required in POST. |
| uuid | string | The unique identifier of the NVMe subsystem. |

subsystem_map

The NVMe subsystem with which the NVMe namespace is associated. A namespace can be mapped to zero (0) or one (1) subsystems.

There is an added computational cost to retrieving property values for `subsystem_map`. They are not populated for either a collection GET or an instance GET unless explicitly requested using the `fields` query parameter.

| Name | Type | Description |
|-----------|--|---|
| _links | self_link | |
| anagrpid | string | <p>The Asymmetric Namespace Access Group ID (ANAGRPID) of the NVMe namespace.</p> <p>The format for an ANAGRPID is 8 hexadecimal digits (zero-filled) followed by a lower case "h".</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for a GET request unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| nsid | string | <p>The NVMe namespace identifier. This is an identifier used by an NVMe controller to provide access to the NVMe namespace.</p> <p>The format for an NVMe namespace identifier is 8 hexadecimal digits (zero-filled) followed by a lower case "h".</p> |
| subsystem | consistency_group_nvme_subsystem | An NVMe subsystem maintains configuration state and namespace access control for a set of NVMe-connected hosts. |

namespaces

An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the storage virtual machine using the NVMe over Fabrics protocol.

An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.

See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API. An NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.

NVMe namespace names are paths of the form "/vol/<volume>[/<qtree>]/<namespace>" where the qtree name is optional.

An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. An NVMe namespace can then be resized or cloned. An NVMe namespace cannot be renamed, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing

the namespace.

```
</namespace></qtree></volume>
```

| Name | Type | Description |
|-------------|---------|---|
| auto_delete | boolean | <p>This property marks the NVMe namespace for auto deletion when the volume containing the namespace runs out of space. This is most commonly set on namespace clones.</p> <p>When set to <i>true</i>, the NVMe namespace becomes eligible for automatic deletion when the volume runs out of space. Auto deletion only occurs when the volume containing the namespace is also configured for auto deletion and free space in the volume decreases below a particular threshold.</p> <p>This property is optional in POST and PATCH. The default value for a new NVMe namespace is <i>false</i>.</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for a GET request unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| comment | string | A configurable comment available for use by the administrator. Valid in POST and PATCH. |
| create_time | string | The time the NVMe namespace was created. |
| enabled | boolean | The enabled state of the NVMe namespace. Certain error conditions cause the namespace to become disabled. If the namespace is disabled, check the <code>status.state</code> property to determine what error disabled the namespace. An NVMe namespace is enabled automatically when it is created. |

| Name | Type | Description |
|---------------|---------------|--|
| name | string | <p>The name of the NVMe namespace. An NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>NVMe namespace names are paths of the form "/vol/<volume>[/<qtree>]/<namespace>" where the qtree name is optional.</p> <p>Renaming an NVMe namespace is not supported. Valid in POST.</p> |
| os_type | string | <p>The operating system type of the NVMe namespace.</p> <p>Required in POST when creating an NVMe namespace that is not a clone of another. Disallowed in POST when creating a namespace clone.</p> |
| space | space | <p>The storage space related properties of the NVMe namespace.</p> |
| status | status | <p>Status information about the NVMe namespace.</p> |
| subsystem_map | subsystem_map | <p>The NVMe subsystem with which the NVMe namespace is associated. A namespace can be mapped to zero (0) or one (1) subsystems.</p> <p>There is an added computational cost to retrieving property values for <code>subsystem_map</code>. They are not populated for either a collection GET or an instance GET unless explicitly requested using the <code>fields</code> query parameter.</p> |
| uuid | string | <p>The unique identifier of the NVMe namespace.</p> |

parent_consistency_group

The parent consistency group.

| Name | Type | Description |
|--------|---------------------------|---|
| _links | self_link | |
| name | string | The name of the consistency group. |
| uuid | string | The unique identifier of the consistency group. |

storage_service

Determines the placement of any storage object created during this operation.

| Name | Type | Description |
|------|--------|--|
| name | string | Storage service name. If not specified, the default value is the most performant for the platform. |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|-----------------|---------------------------------|---|
| action | string | Operation to perform |
| name | string | New name for consistency group. Required to resolve naming collisions. |
| storage_service | storage_service | Determines the placement of any storage object created during this operation. |

policy

The QoS policy

| Name | Type | Description |
|--------|---------------------------|-------------|
| _links | self_link | |

| Name | Type | Description |
|------|--------|---|
| name | string | The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH. |
| uuid | string | The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH. |

snapshot

A consistency group's snapshot

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the consistency group's snapshot to restore to. |
| uuid | string | The UUID of the consistency group's snapshot to restore to. |

restore_to

Use to restore a consistency group to a previous snapshot

| Name | Type | Description |
|----------|--------------------------|--------------------------------|
| snapshot | snapshot | A consistency group's snapshot |

snapshot_policy_reference

This is a reference to the snapshot policy.

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |
| name | string | |
| uuid | string | |

space

Space information for the consistency group.

| Name | Type | Description |
|-----------|---------|---|
| available | integer | The amount of space available in the consistency group, in bytes. |
| size | integer | The total provisioned size of the consistency group, in bytes. |
| used | integer | The amount of space consumed in the consistency group, in bytes. |

svm

The Storage Virtual Machine (SVM) in which the consistency group is located.

| Name | Type | Description |
|--------|------------------------|---|
| _links | _links | |
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

object_stores

tiering

The tiering placement and policy definitions for volumes in this consistency group.

| Name | Type | Description |
|---------------|--|---|
| object_stores | array[object_stores] | Object stores to use. Used for placement. |

| Name | Type | Description |
|--------|--------|---|
| policy | string | <p>Policy that determines whether the user data blocks of a volume in a FabricPool will be tiered to the cloud store when they become cold.</p> <p>FabricPool combines flash (performance tier) with a cloud store into a single aggregate. Temperature of a volume block increases if it is accessed frequently and decreases when it is not. Valid in POST or PATCH.</p> <p>all &dash; Allows tiering of both snapshots and active file system user data to the cloud store as soon as possible by ignoring the temperature on the volume blocks.</p> <p>auto &dash; Allows tiering of both snapshot and active file system user data to the cloud store</p> <p>none &dash; Volume blocks are not be tiered to the cloud store.</p> <p>snapshot_only &dash; Allows tiering of only the volume snapshots not associated with the active file system.</p> <p>The default tiering policy is "snapshot-only" for a FlexVol volume and "none" for a FlexGroup volume. The default minimum cooling period for the "snapshot-only" tiering policy is 2 days and for the "auto" tiering policy it is 31 days.</p> |

acls

The permissions that users and groups have on a CIFS share.

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |

| Name | Type | Description |
|-----------------|--------|---|
| permission | string | <p>Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed:</p> <ul style="list-style-type: none"> • no_access - User does not have CIFS share access • read - User has only read access • change - User has change access • full_control - User has full_control access |
| type | string | <p>Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed:</p> <ul style="list-style-type: none"> • windows - Windows user or group • unix_user - UNIX user • unix_group - UNIX group |
| user_or_group | string | Specifies the user or group name to add to the access control list of a CIFS share. |
| win_sid_unix_id | string | Windows SID/UNIX ID depending on access-control type. |

consistency_group_cifs_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

| Name | Type | Description |
|--------|------------------------|-------------|
| _links | _links | |

| Name | Type | Description |
|--------------------------|---------------------|--|
| access_based_enumeration | boolean | Specifies whether all folders inside this share are visible to a user based on that individual user's access right; prevents the display of folders or other shared resources that the user does not have access to. |
| acls | array <acls></acls> | |
| allow_unencrypted_access | boolean | Specifies whether or not the SMB2 clients are allowed to access the encrypted share. |
| change_notify | boolean | Specifies whether CIFS clients can request for change notifications for directories on this share. |
| comment | string | Specify the CIFS share descriptions. |
| continuously_available | boolean | Specifies whether or not the clients connecting to this share can open files in a persistent manner. Files opened in this way are protected from disruptive events, such as, failover and giveback. |
| dir_umask | integer | Directory mode creation mask to be viewed as an octal number. |
| encryption | boolean | Specifies whether SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share. |
| file_umask | integer | File mode creation mask to be viewed as an octal number. |

| Name | Type | Description |
|-------------------|---------|---|
| home_directory | boolean | <p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> • Default value: 1 • Introduced in: 9.12 • readCreate: 1 • x-nullable: true |
| name | string | Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically. |
| namespace_caching | boolean | Specifies whether or not the SMB clients connecting to this share can cache the directory enumeration results returned by the CIFS servers. |

| Name | Type | Description |
|--------------------|---------|--|
| no_strict_security | boolean | Specifies whether or not CIFS clients can follow Unix symlinks outside the share boundaries. |
| offline_files | string | <p>Offline Files The supported values are:</p> <ul style="list-style-type: none"> • none - Clients are not permitted to cache files for offline access. • manual - Clients may cache files that are explicitly selected by the user for offline access. • documents - Clients may automatically cache files that are used by the user for offline access. • programs - Clients may automatically cache files that are used by the user for offline access and may use those files in an offline mode even if the share is available. |
| oplocks | boolean | Specifies whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations. |
| show_snapshot | boolean | Specifies whether or not the snapshots can be viewed and traversed by clients. |
| unix_symlink | string | <p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> • local - Enables only local symbolic links which is within the same CIFS share. • widelink - Enables both local symlinks and widelinks. • disable - Disables local symlinks and widelinks. |

| Name | Type | Description |
|---------------|--------|---|
| vscan_profile | string | <p>Vscan File-Operations Profile The supported values are:</p> <ul style="list-style-type: none"> • no_scan - Virus scans are never triggered for accesses to this share. • standard - Virus scans can be triggered by open, close, and rename operations. • strict - Virus scans can be triggered by open, read, close, and rename operations. • writes_only - Virus scans can be triggered only when a file that has been modified is closed. |

cifs

| Name | Type | Description |
|--------|--|-------------|
| shares | array[consistency_group_cifs_shares] | |

export_clients

| Name | Type | Description |
|-------|--------|--|
| match | string | <p>Client Match Hostname, IP Address, Netgroup, or Domain. You can specify the match as a string value in any of the following formats:</p> <ul style="list-style-type: none"> • As a hostname; for instance, host1 • As an IPv4 address; for instance, 10.1.12.24 • As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1 • As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24 • As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64 • As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0 • As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng • As a domain name preceded by the . character; for instance, .example.com |

export_rules

| Name | Type | Description |
|-----------------------|------------------------|--|
| _links | _links | |
| allow_device_creation | boolean | Specifies whether or not device creation is allowed. |
| allow_suid | boolean | Specifies whether or not SetUID bits in SETATTR Op is to be honored. |
| anonymous_user | string | User ID To Which Anonymous Users Are Mapped. |

| Name | Type | Description |
|--------------------|---|---|
| chown_mode | string | Specifies who is authorized to change the ownership mode of a file. |
| clients | array[export_clients] | Array of client matches |
| index | integer | Index of the rule within the export policy. |
| ntfs_unix_security | string | NTFS export UNIX security options. |
| protocols | array[string] | |
| ro_rule | array[string] | Authentication flavors that the read-only access rule governs |
| rw_rule | array[string] | Authentication flavors that the read/write access rule governs |
| superuser | array[string] | Authentication flavors that the superuser security type governs |

export_policy

The policy associated with volumes to export them for protocol access.

| Name | Type | Description |
|--------|---------------------------------------|---|
| _links | self_link | |
| id | integer | Identifier for the export policy. |
| name | string | Name of the export policy. |
| rules | array[export_rules] | The set of rules that govern the export policy. |

junction_parent

| Name | Type | Description |
|--------|---------------------------|-------------|
| _links | self_link | |

| Name | Type | Description |
|------|--------|--|
| name | string | The name of the parent volume that contains the junction inode of this volume. The junction parent volume must belong to the same SVM that owns this volume. |
| uuid | string | Unique identifier for the parent volume. |

nas

The CIFS share policy and/or export policies for this volume.

| Name | Type | Description |
|-----------------|---------------------------------|---|
| cifs | cifs | |
| export_policy | export_policy | The policy associated with volumes to export them for protocol access. |
| gid | integer | The UNIX group ID of the volume. Valid in POST or PATCH. |
| junction_parent | junction_parent | |
| path | string | The fully-qualified path in the owning SVM's namespace at which the volume is mounted. The path is case insensitive and must be unique within an SVM's namespace. Path must begin with '/' and must not end with '/'. Only one volume can be mounted at any given junction path. An empty path in POST creates an unmounted volume. An empty path in PATCH deactivates and unmounts the volume. Taking a volume offline or restricted state removes its junction path. This attribute is reported in GET only when the volume is mounted. |

| Name | Type | Description |
|------------------|---------|---|
| security_style | string | Security style associated with the volume. Valid in POST or PATCH. mixed ‐ Mixed-style security ntfs ‐ NTFS/WIndows-style security unified ‐ Unified-style security, unified UNIX, NFS and CIFS permissions unix ‐ UNIX-style security. |
| uid | integer | The UNIX user ID of the volume. Valid in POST or PATCH. |
| unix_permissions | integer | UNIX permissions to be viewed as an octal number, consisting of 4 digits derived by adding up bits 4 (read), 2 (write), and 1 (execute). First digit selects the set user ID (4), set group ID (2), and sticky (1) attributes. Second digit selects permission for the owner of the file. Third selects permissions for other users in the same group while the fourth selects permissions for other users not in the group. Valid in POST or PATCH. For security style "mixed" or "unix", the default setting is 0755 in octal (493 in decimal) and for security style "ntfs", the default setting is 0000. In cases where only owner, group, and other permissions are given (as in 755, representing the second, third and fourth digit), the first digit is assumed to be zero. |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|--------|---------|---|
| action | string | Operation to perform |
| count | integer | Number of elements to perform the operation on. |

| Name | Type | Description |
|-----------------|-----------------|---|
| storage_service | storage_service | Determines the placement of any storage object created during this operation. |

qos

The QoS policy for this volume.

| Name | Type | Description |
|--------|--------|----------------|
| policy | policy | The QoS policy |

space

| Name | Type | Description |
|-----------|---------|--|
| available | integer | The available space, in bytes. |
| size | integer | Total provisioned size, in bytes. |
| used | integer | The virtual space used (includes volume reserves) before storage efficiency, in bytes. |

tiering

The tiering placement and policy definitions for this volume.

| Name | Type | Description |
|---------------|----------------------|---|
| object_stores | array[object_stores] | Object stores to use. Used for placement. |

| Name | Type | Description |
|--------|--------|---|
| policy | string | <p>Policy that determines whether the user data blocks of a volume in a FabricPool will be tiered to the cloud store when they become cold.</p> <p>FabricPool combines flash (performance tier) with a cloud store into a single aggregate. Temperature of a volume block increases if it is accessed frequently and decreases when it is not. Valid in POST or PATCH.</p> <p>all &dash; Allows tiering of both snapshots and active file system user data to the cloud store as soon as possible by ignoring the temperature on the volume blocks.</p> <p>auto &dash; Allows tiering of both snapshot and active file system user data to the cloud store</p> <p>none &dash; Volume blocks are not be tiered to the cloud store.</p> <p>snapshot_only &dash; Allows tiering of only the volume snapshots not associated with the active file system.</p> <p>The default tiering policy is "snapshot-only" for a FlexVol volume and "none" for a FlexGroup volume. The default minimum cooling period for the "snapshot-only" tiering policy is 2 days and for the "auto" tiering policy it is 31 days.</p> |

volumes

| Name | Type | Description |
|---------|--------|---|
| comment | string | A comment for the volume. Valid in POST or PATCH. |

| Name | Type | Description |
|-----------------|---|---|
| name | string | Volume name. The name of volume must start with an alphabetic character (a to z or A to Z) or an underscore (_). The name must be 197 or fewer characters in length for FlexGroup volumes, and 203 or fewer characters in length for all other types of volumes. Volume names must be unique within an SVM. Required on POST. |
| nas | nas | The CIFS share policy and/or export policies for this volume. |
| qos | qos | The QoS policy for this volume. |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| space | space | |
| tiering | tiering | The tiering placement and policy definitions for this volume. |
| uuid | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> • example: 028baa66-41bd-11e9-81d5-00a0986138f7 • readOnly: 1 • Introduced in: 9.8 • x-nullable: true |

consistency_groups

| Name | Type | Description |
|--------|---------------------------|--|
| _links | self_link | |
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |

| Name | Type | Description |
|-------------|-------------|---|
| application | application | |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |
| name | string | Name of the consistency group. The consistency group name must be unique within an SVM. |

| Name | Type | Description |
|--------------------------|--|--|
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| qos | qos | |
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |

| Name | Type | Description |
|-----------------|---|--|
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| space | space | Space information for the consistency group. |
| svm | svm | The Storage Virtual Machine (SVM) in which the consistency group is located. |
| tiering | tiering | The tiering placement and policy definitions for volumes in this consistency group. |
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> • example: 1cd8a442-86d1-11e0-ae1c-123478563412 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

iops

The rate of I/O operations observed at the storage object.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

latency

The round trip latency observed at the storage object, in microseconds.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

throughput

The rate of throughput bytes per second observed at the storage object.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |

| Name | Type | Description |
|-------|---------|---|
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

metric

Performance and capacity numbers, such as, IOPS, latency, throughput, used space, and available space.

| Name | Type | Description |
|-----------------|-------------------------|--|
| _links | _links | |
| available_space | integer | The total space available in the consistency group, in bytes. |
| duration | string | The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations: |
| iops | iops | The rate of I/O operations observed at the storage object. |
| latency | latency | The round trip latency observed at the storage object, in microseconds. |
| size | integer | The total size of the consistency group, in bytes. |

| Name | Type | Description |
|------------|------------|---|
| status | string | Errors associated with the sample. For example, if the aggregation of data over multiple nodes fails, then any partial errors might return "ok" on success or "error" on an internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data. |
| throughput | throughput | The rate of throughput bytes per second observed at the storage object. |
| timestamp | string | The timestamp of the performance and capacity data. |
| used_space | integer | The total space used in the consistency group, in bytes. |

replication_relationships

| Name | Type | Description |
|------------------------|---------------------------|--|
| _links | self_link | |
| is_protected_by_svm_dr | boolean | Indicates whether or not this consistency group is protected by SVM DR. |
| is_source | boolean | Indicates whether or not this consistency group is the source for replication. |

| Name | Type | Description |
|------|--------|---|
| uuid | string | The unique identifier of the SnapMirror relationship. |

iops_raw

The number of I/O operations observed at the storage object. This can be used along with delta time to calculate the rate of I/O operations per unit of time.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

latency_raw

The raw latency observed at the storage object, in microseconds. This can be divided by the raw IOPS value to calculate the average latency per I/O operation.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

throughput_raw

Throughput bytes observed at the storage object. This can be used along with delta time to calculate the rate of throughput bytes per unit of time.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

statistics

These are raw performance and space numbers, such as, IOPS, latency, throughput, used space, and available space. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.

| Name | Type | Description |
|-----------------|-------------|--|
| available_space | integer | The total space available in the consistency group, in bytes. |
| iops_raw | iops_raw | The number of I/O operations observed at the storage object. This can be used along with delta time to calculate the rate of I/O operations per unit of time. |
| latency_raw | latency_raw | The raw latency observed at the storage object, in microseconds. This can be divided by the raw IOPS value to calculate the average latency per I/O operation. |
| size | integer | The total size of the consistency group, in bytes. |

| Name | Type | Description |
|----------------|--------------------------------|---|
| status | string | Errors associated with the sample. For example, if the aggregation of data over multiple nodes fails, then any partial errors might return "ok" on success or "error" on an internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data. |
| throughput_raw | throughput_raw | Throughput bytes observed at the storage object. This can be used along with delta time to calculate the rate of throughput bytes per unit of time. |
| timestamp | string | The timestamp of the performance data. |
| used_space | integer | The total used space in the consistency group, in bytes. |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Update a consistency group

PATCH /application/consistency-groups/{uuid}

Introduced In: 9.10

Updates a consistency group.



that this operation will never delete storage elements. You can specify only elements that should be added to the consistency group regardless of existing storage objects.

Related ONTAP commands

- vserver consistency-group modify

Parameters

| Name | Type | In | Required | Description |
|------|--------|------|----------|---|
| uuid | string | path | True | The unique identifier of the consistency group to modify. |

| Name | Type | In | Required | Description |
|----------------|---------|-------|----------|--|
| return_timeout | integer | query | False | <p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> • Default value: 1 • Max value: 120 • Min value: 0 |

Request Body

| Name | Type | Description |
|-------------|---------------|--|
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |
| application | application | |
| clone | clone | Creates a clone of an existing consistency group from the current contents or an existing snapshot. |

| Name | Type | Description |
|--------------------|---|---|
| consistency_groups | array[consistency_groups] | A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A consistency group can only be associated with one direct parent consistency group. |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |

| Name | Type | Description |
|--------------------------|--|--|
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | |
| replicated | boolean | Indicates whether or not replication has been enabled on this consistency group. |

| Name | Type | Description |
|---------------------------|--|--|
| replication_relationships | array[replication_relationships] | Indicates the SnapMirror relationship of this consistency group. |
| replication_source | boolean | Since support for this field is to be removed in the next release, use replication_relationships.is_source instead. |
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> example: 1cd8a442-86d1-11e0-ae1c-123478563412 readOnly: 1 Introduced in: 9.10 x-nullable: true |
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

Example request

```
{  
  "_tags": [  
    "team:csi",  
    "environment:test"  
,  
  "application": {  
    "component_type": "string",  
    "type": "string"  
,  
  "clone": {  
    "parent_svm": {  
      "name": "svm1",  
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
,  
      "split_complete_percent": 0,  
      "split_estimate": 0  
,  
    "consistency_groups": [  
      {  
        "_tags": [  
          "team:csi",  
          "environment:test"  
,  
        "application": {  
          "component_type": "string",  
          "type": "string"  
,  
        "luns": [  
          {  
            "clone": {  
              "source": {  
                "name": "/vol/volumel/lun1",  
                "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"  
,  
              },  
              "comment": "string",  
              "create_time": "2018-06-04 15:00:00 -0400",  
              "lun_maps": [  
                {  
                  "igroup": {  
                    "comment": "string",  
                    "igroups": [  
                      {  
                        "name": "igroup1",  
                      }  
                    ]  
                  }  
                ]  
              }  
            }  
          ]  
        ]  
      ]  
    ]  
  ]  
}
```

```
        "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
    }
],
"initiators": [
{
    "comment": "my comment",
    "name": "iqn.1998-01.com.corp.iscsi:name1"
},
],
"name": "igroup1",
"os_type": "string",
"uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
},
},
],
"provisioning_options": {
    "action": "string"
},
"qos": {
    "policy": {
        "max_throughput_iops": 10000,
        "max_throughput_mbps": 500,
        "min_throughput_iops": 2000,
        "min_throughput_mbps": 500,
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"serial_number": "string",
"space": {
    "size": 1073741824,
    "used": 0
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
],
"namespaces": [
{
    "comment": "string",
    "create_time": "2018-06-04 15:00:00 -0400",
    "name": "/vol/volume1/qtree1/namespace1",
    "provisioning_options": {
        "action": "string"
    },
    "space": {
        "size": 1073741824,
        "used": 0
    }
}
]
```

```

        "used": 0
    },
    "subsystem_map": {
        "anagrpid": "00103050h",
        "nsid": "00000001h",
        "subsystem": {
            "comment": "string",
            "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
        }
    },
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
],
"parent_consistency_group": {
    "name": "my_consistency_group",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"provisioning_options": {
    "action": "string",
    "name": "string",
    "storage_service": {
        "name": "string"
    }
},
"qos": {
    "policy": {
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"restore_to": {
    "snapshot": {
        "name": "string",
        "uuid": "string"
    }
},
"snapshot_policy": {
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412",
"volumes": [
{
    "comment": "string",
    "name": "vol_cs_dept",
    "nas": {

```

```

"cifs": {
    "shares": [
        {
            "comment": "HR Department Share",
            "dir_umask": 18,
            "file_umask": 18,
            "home_directory": true,
            "offline_files": "string",
            "unix_symlink": "string",
            "vscan_profile": "string"
        }
    ]
},
"export_policy": {
    "id": 0,
    "name": "string",
    "rules": [
        {
            "anonymous_user": "string",
            "chown_mode": "string",
            "clients": [
                {
                    "match": "0.0.0.0/0"
                }
            ],
            "ntfs_unix_security": "string",
            "protocols": [
                "string"
            ],
            "ro_rule": [
                "string"
            ],
            "rw_rule": [
                "string"
            ],
            "superuser": [
                "string"
            ]
        }
    ]
},
"provisioning_options": {
    "action": "string",
    "storage_service": {
        "name": "string"
    }
}
}

```

```

        }
    },
    "qos": {
        "policy": {
            "name": "performance",
            "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
        }
    },
    "snapshot_policy": {
        "name": "default",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "space": {
        "available": 0,
        "used": 0
    },
    "tiering": {
        "control": "string",
        "object_stores": [
            {
                "name": "string"
            }
        ],
        "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
    }
}
],
}
],
],
"luns": [
{
    "clone": {
        "source": {
            "name": "/vol/volume1/lun1",
            "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
        }
    },
    "comment": "string",
    "create_time": "2018-06-04 15:00:00 -0400",
    "lun_maps": [
    {
        "igroup": {
            "comment": "string",
            "igroups": [
            {
                "name": "igroup1",

```

```
        "uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
    }
],
"initiators": [
{
    "comment": "my comment",
    "name": "iqn.1998-01.com.corp.iscsi:namel"
}
],
"name": "igroup1",
"os_type": "string",
"uuid": "4ea7a442-86d1-11e0-ae1c-123478563412"
}
},
"provisioning_options": {
    "action": "string"
},
"qos": {
    "policy": {
        "max_throughput_iops": 10000,
        "max_throughput_mbps": 500,
        "min_throughput_iops": 2000,
        "min_throughput_mbps": 500,
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"serial_number": "string",
"space": {
    "size": 1073741824,
    "used": 0
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
}
],
"namespaces": [
{
    "comment": "string",
    "create_time": "2018-06-04 15:00:00 -0400",
    "name": "/vol/volume1/qtree1/namespacel",
    "provisioning_options": {
        "action": "string"
    },
    "space": {
        "size": 1073741824,
```

```
        "used": 0
    },
    "subsystem_map": {
        "anagrpid": "00103050h",
        "nsid": "00000001h",
        "subsystem": {
            "comment": "string",
            "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
        }
    },
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
],
"parent_consistency_group": {
    "name": "my_consistency_group",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"provisioning_options": {
    "action": "string",
    "name": "string",
    "storage_service": {
        "name": "string"
    }
},
"qos": {
    "policy": {
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"replication_relationships": [
{
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
],
"restore_to": {
    "snapshot": {
        "name": "string",
        "uuid": "string"
    }
},
"snapshot_policy": {
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"uuid": "1cd8a442-86d1-11e0-ae1c-123478563412",
```

```

"volumes": [
  {
    "comment": "string",
    "name": "vol_cs_dept",
    "nas": {
      "cifs": {
        "shares": [
          {
            "comment": "HR Department Share",
            "dir_umask": 18,
            "file_umask": 18,
            "home_directory": true,
            "offline_files": "string",
            "unix_symlink": "string",
            "vscan_profile": "string"
          }
        ]
      },
      "export_policy": {
        "id": 0,
        "name": "string",
        "rules": [
          {
            "anonymous_user": "string",
            "chown_mode": "string",
            "clients": [
              {
                "match": "0.0.0.0/0"
              }
            ],
            "ntfs_unix_security": "string",
            "protocols": [
              "string"
            ],
            "ro_rule": [
              "string"
            ],
            "rw_rule": [
              "string"
            ],
            "superuser": [
              "string"
            ]
          }
        ]
      }
    }
  }
]

```

```

} ,
"provisioning_options": {
    "action": "string",
    "storage_service": {
        "name": "string"
    }
},
"qos": {
    "policy": {
        "name": "performance",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    }
},
"snapshot_policy": {
    "name": "default",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"space": {
    "available": 0,
    "used": 0
},
"tiering": {
    "control": "string",
    "object_stores": [
        {
            "name": "string"
        }
    ]
},
"uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
}
]
}
}

```

Response

Status: 200, Ok

Response

Status: 202, Accepted

Error

Status: Default

ONTAP Error Response Codes

| Error Code | Description |
|------------|--|
| 262285 | Consistency group does not support removing elements using a PATCH request. |
| 2621761 | Consistency groups with DP volumes are not supported on storage-limit enabled SVM. |
| 53411842 | Consistency group does not exist. |
| 53411843 | A consistency group with specified UUID was not found. |
| 53411844 | Specified consistency group was not found in the specified SVM. |
| 53411845 | The specified UUID and name refer to different consistency groups. |
| 53411846 | Either name or UUID must be provided. |
| 53411852 | A consistency group with the same identifier in the same scope exists. |
| 53411853 | Fields provided in the request conflict with each other. |
| 53411856 | Field provided is only supported when provisioning new objects. |
| 53411857 | LUNs that are not members of the application are not supported by this API. LUNs can be added to an application by adding the volume containing the LUNs to the application. |
| 53411860 | An object with the same identifier in the same scope exists. |
| 53411861 | Volume specified does not exist in provided volume array. |
| 53411862 | Modifying existing igroups is not supported using this API. |
| 53411864 | Request content insufficient to add an existing volume to an application. |
| 53411865 | Volumes contained in one consistency group cannot be added to a different consistency group. |
| 53411866 | LUNs are not supported on FlexGroup volumes. |
| 53411867 | LUN name is too long after appending a unique suffix. |

| Error Code | Description |
|------------|--|
| 53411869 | Volume name is too long after appending a unique suffix. |
| 53411870 | When using the "round_robin" layout, the volume count must not be greater than the LUN count. |
| 53411942 | The application or component type of a consistency group that has an associated SnapMirror relationship cannot be changed. |
| 53411959 | Volumes with snapshot locking enabled cannot be added to a consistency group. |
| 53412027 | Failed to update the snapshot policy because the snapshot policies are not supported on the destination consistency group of SnapMirror active sync relationships. |
| 53412056 | The consistency group is not a FlexClone. |
| 53412057 | Consistency group split operation failed. |

Also see the table of common errors in the [Response body](#) overview section of this documentation.

Definitions

See Definitions

href

| Name | Type | Description |
|------|--------|-------------|
| href | string | |

self_link

application

| Name | Type | Description |
|----------------|--------|----------------------------------|
| component_type | string | Nested consistency group tag. |
| type | string | Top level consistency group tag. |

guarantee

| Name | Type | Description |
|------|--------|--|
| type | string | The type of space guarantee of this volume in the aggregate. |

parent_consistency_group

Consistency group that is to be cloned.

_links

parent_snapshot

Consistency group that is to be cloned.

| Name | Type | Description |
|------|--------|-------------|
| name | string | |
| uuid | string | |

parent_svm

SVM, applies only to SVM-scoped objects.

| Name | Type | Description |
|------|--------|--|
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |

| Name | Type | Description |
|------|--------|---|
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

volume

Volume name suffix/prefix for the cloned volumes.

| Name | Type | Description |
|--------|--------|--|
| prefix | string | Volume name prefix for cloned volumes. |
| suffix | string | Volume name suffix for cloned volumes. |

clone

Creates a clone of an existing consistency group from the current contents or an existing snapshot.

| Name | Type | Description |
|------------------------|----------------------------|--|
| is_flexclone | boolean | Specifies if this consistency group is a FlexClone of a consistency group. |
| parent_svm | parent_svm | SVM, applies only to SVM-scoped objects. |
| split_complete_percent | integer | Percentage of FlexClone blocks split from its parent consistency group. |
| split_estimate | integer | Space required to split the FlexClone consistency group. |
| split_initiated | boolean | Splits volumes after cloning. Defaults to false during POST. Only accepts true during a PATCH. |

source

The source LUN for a LUN clone operation. This can be specified using property `clone.source.uuid` or `clone.source.name`. If both properties are supplied, they must refer to the same LUN.

Valid in POST to create a new LUN as a clone of the source.

Valid in PATCH to overwrite an existing LUN's data as a clone of another.

| Name | Type | Description |
|------|--------|---|
| name | string | <p>The name of the clone source LUN. A LUN is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>LUN names are paths of the form "/vol/<volume>[/<qtree>]<name>" where the qtree name is optional.</p> <p>Valid in POST and PATCH.</p> |
| uuid | string | <p>The unique identifier of the clone source LUN. Valid in POST and PATCH.</p> |

clone

This sub-object is used in POST to create a new LUN as a clone of an existing LUN, or PATCH to overwrite an existing LUN as a clone of another. Setting a property in this sub-object indicates that a LUN clone is desired. Consider the following other properties when cloning a LUN: `auto_delete`, `qos_policy`, `space.guarantee.requested` and `space.scsi_thin_provisioning_support_enabled`.

When used in a PATCH, the patched LUN's data is over-written as a clone of the source and the following properties are preserved from the patched LUN unless otherwise specified as part of the PATCH: `class`, `auto_delete`, `lun_maps`, `serial_number`, `status.state`, and `uuid`.

Persistent reservations for the patched LUN are also preserved.

| Name | Type | Description |
|--------|--------|---|
| source | source | <p>The source LUN for a LUN clone operation. This can be specified using property <code>clone.source.uuid</code> or <code>clone.source.name</code>. If both properties are supplied, they must refer to the same LUN.</p> <p>Valid in POST to create a new LUN as a clone of the source.</p> <p>Valid in PATCH to overwrite an existing LUN's data as a clone of another.</p> |

igroups

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the initiator group. |
| uuid | string | The unique identifier of the initiator group. |

initiators

The initiators that are members of the initiator group.

| Name | Type | Description |
|---------|--------|--|
| comment | string | A comment available for use by the administrator. |
| name | string | Name of initiator that is a member of the initiator group. |

igroup

The initiator group that directly owns the initiator, which is where modification of the initiator is supported. This property will only be populated when the initiator is a member of a nested initiator group.

| Name | Type | Description |
|---------|--------|--|
| comment | string | A comment available for use by the administrator. Valid in POST and PATCH. |

| Name | Type | Description |
|------------|-------------------------------------|---|
| igroups | array[igroups] | <p>The existing initiator groups that are members of the group. Optional in POST.</p> <p>This property is mutually exclusive with the <i>initiators</i> property during POST.</p> <p>This array contains only the direct children of the initiator group. If the member initiator groups have further nested initiator groups, those are reported in the <i>igroups</i> property of the child initiator group.</p> <p>Zero or more nested initiator groups can be supplied when the initiator group is created. The initiator group will act as if it contains the aggregation of all initiators in any nested initiator groups.</p> <p>After creation, nested initiator groups can be added or removed from the initiator group using the <code>/protocols/san/igroups/{igroup.uuid}/igroups</code> endpoint. See DELETE /protocols/san/igroups/{igroup.uuid}/igroups/{uuid} for more details.</p> |
| initiators | array[initiators] | The initiators that are members of the group. |
| name | string | The name of the initiator group. Required in POST; optional in PATCH. |
| os_type | string | The host operating system of the initiator group. All initiators in the group should be hosts of the same operating system. Required in POST; optional in PATCH. |
| uuid | string | The unique identifier of the initiator group. |

lun_maps

A LUN map is an association between a LUN and an initiator group.

When a LUN is mapped to an initiator group, the initiator group's initiators are granted access to the LUN. The relationship between a LUN and an initiator group is many LUNs to many initiator groups.

| Name | Type | Description |
|--------|--------|---|
| igroup | igroup | The initiator group that directly owns the initiator, which is where modification of the initiator is supported. This property will only be populated when the initiator is a member of a nested initiator group. |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|--------|---------|---|
| action | string | Operation to perform |
| count | integer | Number of elements to perform the operation on. |

policy

The QoS policy

| Name | Type | Description |
|---------------------|---------|---|
| max_throughput_iops | integer | Specifies the maximum throughput in IOPS, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| max_throughput_mbps | integer | Specifies the maximum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |

| Name | Type | Description |
|---------------------|---------|---|
| min_throughput_iops | integer | Specifies the minimum throughput in IOPS, 0 means none. Setting "min_throughput" is supported on AFF platforms only, unless FabricPool tiering policies are set. This is mutually exclusive with name and UUID during POST and PATCH. |
| min_throughput_mbps | integer | Specifies the minimum throughput in Megabytes per sec, 0 means none. This is mutually exclusive with name and UUID during POST and PATCH. |
| name | string | The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH. |
| uuid | string | The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH. |

qos

| Name | Type | Description |
|--------|--------|----------------|
| policy | policy | The QoS policy |

guarantee

Properties that request and report the space guarantee for the LUN.

| Name | Type | Description |
|-----------|---------|--|
| requested | boolean | The requested space reservation policy for the LUN. If <i>true</i> , a space reservation is requested for the LUN; if <i>false</i> , the LUN is thin provisioned. Guaranteeing a space reservation request for a LUN requires that the volume in which the LUN resides is also space reserved and that the fractional reserve for the volume is 100%. Valid in POST and PATCH. |

| Name | Type | Description |
|----------|---------|---|
| reserved | boolean | <p>Reports if the LUN is space guaranteed.</p> <p>If <i>true</i>, a space guarantee is requested and the containing volume and aggregate support the request. If <i>false</i>, a space guarantee is not requested or a space guarantee is requested and either the containing volume or aggregate do not support the request.</p> |

space

The storage space related properties of the LUN.

| Name | Type | Description |
|-----------|-----------|---|
| guarantee | guarantee | Properties that request and report the space guarantee for the LUN. |
| size | integer | <p>The total provisioned size of the LUN. The LUN size can be increased but not reduced using the REST interface. The maximum and minimum sizes listed here are the absolute maximum and absolute minimum sizes, in bytes. The actual minimum and maximum sizes vary depending on the ONTAP version, ONTAP platform, and the available space in the containing volume and aggregate. For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> example: 1073741824 format: int64 Max value: 140737488355328 Min value: 4096 Introduced in: 9.6 x-nullable: true |

| Name | Type | Description |
|------|---------|---|
| used | integer | <p>The amount of space consumed by the main data stream of the LUN.</p> <p>This value is the total space consumed in the volume by the LUN, including filesystem overhead, but excluding prefix and suffix streams. Due to internal filesystem overhead and the many ways SAN filesystems and applications utilize blocks within a LUN, this value does not necessarily reflect actual consumption/availability from the perspective of the filesystem or application. Without specific knowledge of how the LUN blocks are utilized outside of ONTAP, this property should not be used as an indicator for an out-of-space condition.</p> <p>For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • format: int64 • readOnly: 1 • Introduced in: 9.6 • x-nullable: true |

luns

A LUN is the logical representation of storage in a storage area network (SAN).

A LUN must be mapped to an initiator group to grant access to the initiator group's initiators (client hosts). Initiators can then access the LUN and perform I/O over a Fibre Channel (FC) fabric using the FC Protocol or a TCP/IP network using iSCSI.

See the LUN object model to learn more about each of the properties supported by the LUN REST API.

A LUN is located within a volume. Optionally, it can be located within a qtree in a volume.

LUN names are paths of the form "/vol/<volume>[/<qtree>]/<lun>" where the qtree name is optional.

A LUN can be created to a specified size using thin or thick provisioning. A LUN can then be renamed, resized, cloned, moved to a different volume and copied. LUNs support the assignment of a QoS policy for performance management or a QoS policy can be assigned to a volume containing one or more LUNs.

</lun></qtree></volume>

| Name | Type | Description |
|-------------|--------|---|
| clone | clone | <p>This sub-object is used in POST to create a new LUN as a clone of an existing LUN, or PATCH to overwrite an existing LUN as a clone of another. Setting a property in this sub-object indicates that a LUN clone is desired. Consider the following other properties when cloning a LUN: <code>auto_delete</code>, <code>qos_policy</code>, <code>space.guarantee.requested</code> and <code>space.scsi_thin_provisioning_support_enabled</code>.</p> <p>When used in a PATCH, the patched LUN's data is overwritten as a clone of the source and the following properties are preserved from the patched LUN unless otherwise specified as part of the PATCH: <code>class</code>, <code>auto_delete</code>, <code>lun_maps</code>, <code>serial_number</code>, <code>status.state</code>, and <code>uuid</code>.</p> <p>Persistent reservations for the patched LUN are also preserved.</p> |
| comment | string | A configurable comment available for use by the administrator. Valid in POST and PATCH. |
| create_time | string | The time the LUN was created. |

| Name | Type | Description |
|----------------------|----------------------|--|
| enabled | boolean | The enabled state of the LUN. LUNs can be disabled to prevent access to the LUN. Certain error conditions also cause the LUN to become disabled. If the LUN is disabled, you can consult the state property to determine if the LUN is administratively disabled (<i>offline</i>) or has become disabled as a result of an error. A LUN in an error condition can be brought online by setting the enabled property to <i>true</i> or brought administratively offline by setting the enabled property to <i>false</i> . Upon creation, a LUN is enabled by default. Valid in PATCH. |
| lun_maps | array[lun_maps] | An array of LUN maps. A LUN map is an association between a LUN and an initiator group. When a LUN is mapped to an initiator group, the initiator group's initiators are granted access to the LUN. The relationship between a LUN and an initiator group is many LUNs to many initiator groups. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | |
| serial_number | string | The LUN serial number. The serial number is generated by ONTAP when the LUN is created. <ul style="list-style-type: none"> • maxLength: 12 • minLength: 12 • readOnly: 1 • Introduced in: 9.10 • x-nullable: true |
| space | space | The storage space related properties of the LUN. |

| Name | Type | Description |
|------|--------|--|
| uuid | string | <p>The unique identifier of the LUN. The UUID is generated by ONTAP when the LUN is created.</p> <ul style="list-style-type: none"> example: 1cd8a442-86d1-11e0-ae1c-123478563412 readOnly: 1 Introduced in: 9.10 x-nullable: true |

guarantee

Properties that request and report the space guarantee for the NVMe namespace.

| Name | Type | Description |
|-----------|---------|--|
| requested | boolean | <p>The requested space reservation policy for the NVMe namespace. If <i>true</i>, a space reservation is requested for the namespace; if <i>false</i>, the namespace is thin provisioned. Guaranteeing a space reservation request for a namespace requires that the volume in which the namespace resides also be space reserved and that the fractional reserve for the volume be 100%.</p> <p>The space reservation policy for an NVMe namespace is determined by ONTAP.</p> <ul style="list-style-type: none"> Introduced in: 9.6 x-nullable: true |
| reserved | boolean | <p>Reports if the NVMe namespace is space guaranteed.</p> <p>This property is <i>true</i> if a space guarantee is requested and the containing volume and aggregate support the request. This property is <i>false</i> if a space guarantee is not requested or if a space guarantee is requested and either the containing volume and aggregate do not support the request.</p> |

space

The storage space related properties of the NVMe namespace.

| Name | Type | Description |
|-----------|---------------------------|---|
| guarantee | guarantee | Properties that request and report the space guarantee for the NVMe namespace. |
| size | integer | <p>The total provisioned size of the NVMe namespace. Valid in POST and PATCH. The NVMe namespace size can be increased but not reduced using the REST interface.</p> <p>The maximum and minimum sizes listed here are the absolute maximum and absolute minimum sizes, in bytes. The maximum size is variable with respect to large NVMe namespace support in ONTAP. If large namespaces are supported, the maximum size is 128 TB (140737488355328 bytes) and if not supported, the maximum size is just under 16 TB (17557557870592 bytes). The minimum size supported is always 4096 bytes.</p> <p>For more information, see Size properties in the docs section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none">• example: 1073741824• format: int64• Max value: 140737488355328• Min value: 4096• Introduced in: 9.6• x-nullable: true |

| Name | Type | Description |
|------|---------|--|
| used | integer | <p>The amount of space consumed by the main data stream of the NVMe namespace.</p> <p>This value is the total space consumed in the volume by the NVMe namespace, including filesystem overhead, but excluding prefix and suffix streams. Due to internal filesystem overhead and the many ways NVMe filesystems and applications utilize blocks within a namespace, this value does not necessarily reflect actual consumption/availability from the perspective of the filesystem or application. Without specific knowledge of how the namespace blocks are utilized outside of ONTAP, this property should not be used as an indicator for an out-of-space condition.</p> <p>For more information, see <i>Size properties</i> in the <i>docs</i> section of the ONTAP REST API documentation.</p> <ul style="list-style-type: none"> • format: int64 • readOnly: 1 • Introduced in: 9.6 • x-nullable: true |

status

Status information about the NVMe namespace.

| Name | Type | Description |
|-----------------|--------|---|
| container_state | string | The state of the volume and aggregate that contain the NVMe namespace. Namespaces are only available when their containers are available. |

| Name | Type | Description |
|-----------|---------|---|
| mapped | boolean | <p>Reports if the NVMe namespace is mapped to an NVMe subsystem.</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for either a collection GET or an instance GET unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| read_only | boolean | Reports if the NVMe namespace allows only read access. |
| state | string | The state of the NVMe namespace. Normal states for a namespace are <i>online</i> and <i>offline</i> . Other states indicate errors. |

consistency_group_nvme_host_dh_hmac_chap

A container for the configuration of NVMe in-band authentication using the DH-HMAC-CHAP protocol for a host.

| Name | Type | Description |
|------|--------|--|
| mode | string | <p>The expected NVMe in-band authentication mode for the host. This property is an indication of which secrets are configured for the host. When set to:</p> <ul style="list-style-type: none"> • none: The host has neither the host nor controller secret configured, and no authentication is performed. • unidirectional: The host has a host secret configured. The controller will authenticate the host. • bidirectional: The host has both a host and controller secret configured. The controller will authenticate the host and the host will authenticate the controller. |

tls

A container for the configuration for NVMe/TCP-TLS transport session for the host.

consistency_group_nvme_host

The NVMe host provisioned to access NVMe namespaces mapped to a subsystem.

consistency_group_nvme_subsystem

An NVMe subsystem maintains configuration state and namespace access control for a set of NVMe-connected hosts.

| Name | Type | Description |
|---------|--------|--|
| comment | string | A configurable comment for the NVMe subsystem. Optional in POST and PATCH. |
| uuid | string | The unique identifier of the NVMe subsystem. |

subsystem_map

The NVMe subsystem with which the NVMe namespace is associated. A namespace can be mapped to zero (0) or one (1) subsystems.

There is an added computational cost to retrieving property values for `subsystem_map`. They are not populated for either a collection GET or an instance GET unless explicitly requested using the `fields` query parameter.

| Name | Type | Description |
|----------|--------|---|
| anagrpid | string | <p>The Asymmetric Namespace Access Group ID (ANAGRPID) of the NVMe namespace.</p> <p>The format for an ANAGRPID is 8 hexadecimal digits (zero-filled) followed by a lower case "h".</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for a GET request unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |

| Name | Type | Description |
|-----------|--|--|
| nsid | string | <p>The NVMe namespace identifier. This is an identifier used by an NVMe controller to provide access to the NVMe namespace.</p> <p>The format for an NVMe namespace identifier is 8 hexadecimal digits (zero-filled) followed by a lower case "h".</p> |
| subsystem | consistency_group_nvme_subsystem | An NVMe subsystem maintains configuration state and namespace access control for a set of NVMe-connected hosts. |

namespaces

An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the storage virtual machine using the NVMe over Fabrics protocol.

An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.

See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API. An NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.

NVMe namespace names are paths of the form "/vol/<volume>[/<qtree>]/<namespace>" where the qtree name is optional.

An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. An NVMe namespace can then be resized or cloned. An NVMe namespace cannot be renamed, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace.

</namespace></qtree></volume>

| Name | Type | Description |
|-------------|---------|---|
| auto_delete | boolean | <p>This property marks the NVMe namespace for auto deletion when the volume containing the namespace runs out of space. This is most commonly set on namespace clones.</p> <p>When set to <i>true</i>, the NVMe namespace becomes eligible for automatic deletion when the volume runs out of space. Auto deletion only occurs when the volume containing the namespace is also configured for auto deletion and free space in the volume decreases below a particular threshold.</p> <p>This property is optional in POST and PATCH. The default value for a new NVMe namespace is <i>false</i>.</p> <p>There is an added computational cost to retrieving this property's value. It is not populated for a GET request unless it is explicitly requested using the <code>fields</code> query parameter. See Requesting specific fields to learn more.</p> |
| comment | string | A configurable comment available for use by the administrator. Valid in POST and PATCH. |
| create_time | string | The time the NVMe namespace was created. |
| enabled | boolean | The enabled state of the NVMe namespace. Certain error conditions cause the namespace to become disabled. If the namespace is disabled, check the <code>status.state</code> property to determine what error disabled the namespace. An NVMe namespace is enabled automatically when it is created. |

| Name | Type | Description |
|----------------------|--------------------------------------|--|
| name | string | <p>The name of the NVMe namespace. An NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>NVMe namespace names are paths of the form "/vol/<volume>[/<qtree>]/<namespace>" where the qtree name is optional.</p> <p>Renaming an NVMe namespace is not supported. Valid in POST.</p> |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| space | space | The storage space related properties of the NVMe namespace. |
| subsystem_map | subsystem_map | <p>The NVMe subsystem with which the NVMe namespace is associated. A namespace can be mapped to zero (0) or one (1) subsystems.</p> <p>There is an added computational cost to retrieving property values for <code>subsystem_map</code>. They are not populated for either a collection GET or an instance GET unless explicitly requested using the <code>fields</code> query parameter.</p> |
| uuid | string | The unique identifier of the NVMe namespace. |

parent_consistency_group

The parent consistency group.

| Name | Type | Description |
|------|--------|------------------------------------|
| name | string | The name of the consistency group. |

| Name | Type | Description |
|------|--------|---|
| uuid | string | The unique identifier of the consistency group. |

storage_service

Determines the placement of any storage object created during this operation.

| Name | Type | Description |
|------|--------|--|
| name | string | Storage service name. If not specified, the default value is the most performant for the platform. |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|-----------------|-----------------|---|
| action | string | Operation to perform |
| name | string | New name for consistency group. Required to resolve naming collisions. |
| storage_service | storage_service | Determines the placement of any storage object created during this operation. |

policy

The QoS policy

| Name | Type | Description |
|------|--------|---|
| name | string | The QoS policy group name. This is mutually exclusive with UUID and other QoS attributes during POST and PATCH. |
| uuid | string | The QoS policy group UUID. This is mutually exclusive with name and other QoS attributes during POST and PATCH. |

snapshot

A consistency group's snapshot

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the consistency group's snapshot to restore to. |
| uuid | string | The UUID of the consistency group's snapshot to restore to. |

restore_to

Use to restore a consistency group to a previous snapshot

| Name | Type | Description |
|----------|----------|--------------------------------|
| snapshot | snapshot | A consistency group's snapshot |

snapshot_policy_reference

This is a reference to the snapshot policy.

| Name | Type | Description |
|------|--------|-------------|
| name | string | |
| uuid | string | |

space

Space information for the consistency group.

| Name | Type | Description |
|-----------|---------|---|
| available | integer | The amount of space available in the consistency group, in bytes. |
| size | integer | The total provisioned size of the consistency group, in bytes. |
| used | integer | The amount of space consumed in the consistency group, in bytes. |

svm

The Storage Virtual Machine (SVM) in which the consistency group is located.

| Name | Type | Description |
|------|--------|---|
| name | string | The name of the SVM. This field cannot be specified in a PATCH method. |
| uuid | string | The unique identifier of the SVM. This field cannot be specified in a PATCH method. |

object_stores

| Name | Type | Description |
|------|--------|--|
| name | string | The name of the object store to use. Used for placement. |

tiering

The tiering placement and policy definitions for volumes in this consistency group.

| Name | Type | Description |
|---------------|----------------------|---|
| control | string | Storage tiering placement rules for the object. |
| object_stores | array[object_stores] | Object stores to use. Used for placement. |

acls

The permissions that users and groups have on a CIFS share.

| Name | Type | Description |
|------------|--------|---|
| permission | string | <p>Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed:</p> <ul style="list-style-type: none"> • no_access - User does not have CIFS share access • read - User has only read access • change - User has change access • full_control - User has full_control access |

consistency_group_cifs_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

| Name | Type | Description |
|--------------------------|---------|--|
| access_based_enumeration | boolean | Specifies whether all folders inside this share are visible to a user based on that individual user's access right; prevents the display of folders or other shared resources that the user does not have access to. |
| allow_unencrypted_access | boolean | Specifies whether or not the SMB2 clients are allowed to access the encrypted share. |
| change_notify | boolean | Specifies whether CIFS clients can request for change notifications for directories on this share. |
| comment | string | Specify the CIFS share descriptions. |
| continuously_available | boolean | Specifies whether or not the clients connecting to this share can open files in a persistent manner. Files opened in this way are protected from disruptive events, such as, failover and giveback. |
| dir_umask | integer | Directory mode creation mask to be viewed as an octal number. |
| encryption | boolean | Specifies whether SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share. |
| file_umask | integer | File mode creation mask to be viewed as an octal number. |

| Name | Type | Description |
|--------------------|---------|--|
| namespace_caching | boolean | Specifies whether or not the SMB clients connecting to this share can cache the directory enumeration results returned by the CIFS servers. |
| no_strict_security | boolean | Specifies whether or not CIFS clients can follow Unix symlinks outside the share boundaries. |
| offline_files | string | <p>Offline Files The supported values are:</p> <ul style="list-style-type: none"> • none - Clients are not permitted to cache files for offline access. • manual - Clients may cache files that are explicitly selected by the user for offline access. • documents - Clients may automatically cache files that are used by the user for offline access. • programs - Clients may automatically cache files that are used by the user for offline access and may use those files in an offline mode even if the share is available. |
| oplocks | boolean | Specifies whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations. |
| show_snapshot | boolean | Specifies whether or not the snapshots can be viewed and traversed by clients. |

| Name | Type | Description |
|---------------|--------|---|
| unix_symlink | string | <p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> • local - Enables only local symbolic links which is within the same CIFS share. • widelink - Enables both local symlinks and widelinks. • disable - Disables local symlinks and widelinks. |
| vscan_profile | string | <p>Vscan File-Operations Profile The supported values are:</p> <ul style="list-style-type: none"> • no_scan - Virus scans are never triggered for accesses to this share. • standard - Virus scans can be triggered by open, close, and rename operations. • strict - Virus scans can be triggered by open, read, close, and rename operations. • writes_only - Virus scans can be triggered only when a file that has been modified is closed. |

cifs

| Name | Type | Description |
|--------|-------------------------------------|-------------|
| shares | array[consistency_group_cifs_share] | |

export_clients

| Name | Type | Description |
|-------|--------|--|
| match | string | <p>Client Match Hostname, IP Address, Netgroup, or Domain. You can specify the match as a string value in any of the following formats:</p> <ul style="list-style-type: none"> • As a hostname; for instance, host1 • As an IPv4 address; for instance, 10.1.12.24 • As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1 • As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24 • As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64 • As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0 • As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng • As a domain name preceded by the . character; for instance, .example.com |

export_rules

| Name | Type | Description |
|-----------------------|---------|--|
| allow_device_creation | boolean | Specifies whether or not device creation is allowed. |
| allow_suid | boolean | Specifies whether or not SetUID bits in SETATTR Op is to be honored. |
| anonymous_user | string | User ID To Which Anonymous Users Are Mapped. |

| Name | Type | Description |
|--------------------|---|---|
| chown_mode | string | Specifies who is authorized to change the ownership mode of a file. |
| clients | array[export_clients] | Array of client matches |
| index | integer | Index of the rule within the export policy. |
| ntfs_unix_security | string | NTFS export UNIX security options. |
| protocols | array[string] | |
| ro_rule | array[string] | Authentication flavors that the read-only access rule governs |
| rw_rule | array[string] | Authentication flavors that the read/write access rule governs |
| superuser | array[string] | Authentication flavors that the superuser security type governs |

export_policy

The policy associated with volumes to export them for protocol access.

| Name | Type | Description |
|-------|---------------------------------------|---|
| id | integer | Identifier for the export policy. |
| name | string | Name of the export policy. |
| rules | array[export_rules] | The set of rules that govern the export policy. |

junction_parent

| Name | Type | Description |
|------|--------|--|
| name | string | The name of the parent volume that contains the junction inode of this volume. The junction parent volume must belong to the same SVM that owns this volume. |

| Name | Type | Description |
|------|--------|--|
| uuid | string | Unique identifier for the parent volume. |

nas

The CIFS share policy and/or export policies for this volume.

| Name | Type | Description |
|---------------|---------------|--|
| cifs | cifs | |
| export_policy | export_policy | The policy associated with volumes to export them for protocol access. |

provisioning_options

Options that are applied to the operation.

| Name | Type | Description |
|-----------------|-----------------|---|
| action | string | Operation to perform |
| count | integer | Number of elements to perform the operation on. |
| storage_service | storage_service | Determines the placement of any storage object created during this operation. |

qos

The QoS policy for this volume.

| Name | Type | Description |
|--------|--------|----------------|
| policy | policy | The QoS policy |

space

| Name | Type | Description |
|-----------|---------|-----------------------------------|
| available | integer | The available space, in bytes. |
| size | integer | Total provisioned size, in bytes. |

| Name | Type | Description |
|------|---------|--|
| used | integer | The virtual space used (includes volume reserves) before storage efficiency, in bytes. |

tiering

The tiering placement and policy definitions for this volume.

| Name | Type | Description |
|---------------|----------------------|---|
| control | string | Storage tiering placement rules for the object. |
| object_stores | array[object_stores] | Object stores to use. Used for placement. |

volumes

| Name | Type | Description |
|----------------------|---------------------------|---|
| comment | string | A comment for the volume. Valid in POST or PATCH. |
| name | string | Volume name. The name of volume must start with an alphabetic character (a to z or A to Z) or an underscore (_). The name must be 197 or fewer characters in length for FlexGroup volumes, and 203 or fewer characters in length for all other types of volumes. Volume names must be unique within an SVM. Required on POST. |
| nas | nas | The CIFS share policy and/or export policies for this volume. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | The QoS policy for this volume. |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| space | space | |

| Name | Type | Description |
|---------|-------------------------|---|
| tiering | tiering | The tiering placement and policy definitions for this volume. |
| uuid | string | <p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> • example: 028baa66-41bd-11e9-81d5-00a0986138f7 • readOnly: 1 • Introduced in: 9.8 • x-nullable: true |

consistency_groups

| Name | Type | Description |
|-------------|-------------------------------|---|
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |
| application | application | |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |

| Name | Type | Description |
|--------------------------|--|--|
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | |

| Name | Type | Description |
|-----------------|---|--|
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> example: 1cd8a442-86d1-11e0-ae1c-123478563412 readOnly: 1 Introduced in: 9.10 x-nullable: true |
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

iops

The rate of I/O operations observed at the storage object.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |

| Name | Type | Description |
|-------|---------|--|
| write | integer | Performance metric for write I/O operations. |

latency

The round trip latency observed at the storage object, in microseconds.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

throughput

The rate of throughput bytes per second observed at the storage object.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

metric

Performance and capacity numbers, such as, IOPS, latency, throughput, used space, and available

space.

| Name | Type | Description |
|-----------------|---------|---|
| available_space | integer | The total space available in the consistency group, in bytes. |
| duration | string | The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations: |
| iops | iops | The rate of I/O operations observed at the storage object. |
| latency | latency | The round trip latency observed at the storage object, in microseconds. |
| size | integer | The total size of the consistency group, in bytes. |
| status | string | Errors associated with the sample. For example, if the aggregation of data over multiple nodes fails, then any partial errors might return "ok" on success or "error" on an internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data. |

| Name | Type | Description |
|------------|------------|---|
| throughput | throughput | The rate of throughput bytes per second observed at the storage object. |
| timestamp | string | The timestamp of the performance and capacity data. |
| used_space | integer | The total space used in the consistency group, in bytes. |

replication_relationships

| Name | Type | Description |
|------------------------|---------|--|
| is_protected_by_svm_dr | boolean | Indicates whether or not this consistency group is protected by SVM DR. |
| is_source | boolean | Indicates whether or not this consistency group is the source for replication. |
| uuid | string | The unique identifier of the SnapMirror relationship. |

iops_raw

The number of I/O operations observed at the storage object. This can be used along with delta time to calculate the rate of I/O operations per unit of time.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

latency_raw

The raw latency observed at the storage object, in microseconds. This can be divided by the raw IOPS value to calculate the average latency per I/O operation.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

throughput_raw

Throughput bytes observed at the storage object. This can be used along with delta time to calculate the rate of throughput bytes per unit of time.

| Name | Type | Description |
|-------|---------|--|
| other | integer | Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on. |
| read | integer | Performance metric for read I/O operations. |
| total | integer | Performance metric aggregated over all types of I/O operations. |
| write | integer | Performance metric for write I/O operations. |

statistics

These are raw performance and space numbers, such as, IOPS, latency, throughput, used space, and available space. These numbers are aggregated across all nodes in the cluster and increase with the uptime of the cluster.

| Name | Type | Description |
|-----------------|--------------------------------|---|
| available_space | integer | The total space available in the consistency group, in bytes. |
| iops_raw | iops_raw | The number of I/O operations observed at the storage object. This can be used along with delta time to calculate the rate of I/O operations per unit of time. |
| latency_raw | latency_raw | The raw latency observed at the storage object, in microseconds. This can be divided by the raw IOPS value to calculate the average latency per I/O operation. |
| size | integer | The total size of the consistency group, in bytes. |
| status | string | Errors associated with the sample. For example, if the aggregation of data over multiple nodes fails, then any partial errors might return "ok" on success or "error" on an internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data. |
| throughput_raw | throughput_raw | Throughput bytes observed at the storage object. This can be used along with delta time to calculate the rate of throughput bytes per unit of time. |

| Name | Type | Description |
|------------|---------|--|
| timestamp | string | The timestamp of the performance data. |
| used_space | integer | The total used space in the consistency group, in bytes. |

consistency_group

| Name | Type | Description |
|--------------------|---------------------------|---|
| _tags | array[string] | Tags are an optional way to track the uses of a resource. Tag values must be formatted as key:value strings. |
| application | application | |
| clone | clone | Creates a clone of an existing consistency group from the current contents or an existing snapshot. |
| consistency_groups | array[consistency_groups] | A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A consistency group can only be associated with one direct parent consistency group. |
| luns | array[luns] | The LUNs array can be used to create or modify LUNs in a consistency group on a new or existing volume that is a member of the consistency group. LUNs are considered members of a consistency group if they are located on a volume that is a member of the consistency group. |

| Name | Type | Description |
|--------------------------|--|--|
| namespaces | array[namespaces] | <p>An NVMe namespace is a collection of addressable logical blocks presented to hosts connected to the SVM using the NVMe over Fabrics protocol. In ONTAP, an NVMe namespace is located within a volume. Optionally, it can be located within a qtree in a volume.</p> <p>An NVMe namespace is created to a specified size using thin or thick provisioning as determined by the volume on which it is created. NVMe namespaces support being cloned. An NVMe namespace cannot be renamed, resized, or moved to a different volume. NVMe namespaces do not support the assignment of a QoS policy for performance management, but a QoS policy can be assigned to the volume containing the namespace. See the NVMe namespace object model to learn more about each of the properties supported by the NVMe namespace REST API.</p> <p>An NVMe namespace must be mapped to an NVMe subsystem to grant access to the subsystem's hosts. Hosts can then access the NVMe namespace and perform I/O using the NVMe over Fabrics protocol.</p> <ul style="list-style-type: none"> • minItems: 0 • uniqueItems: 1 • Introduced in: 9.10 |
| parent_consistency_group | parent_consistency_group | The parent consistency group. |
| provisioning_options | provisioning_options | Options that are applied to the operation. |
| qos | qos | |

| Name | Type | Description |
|---------------------------|--|--|
| replicated | boolean | Indicates whether or not replication has been enabled on this consistency group. |
| replication_relationships | array[replication_relationships] | Indicates the SnapMirror relationship of this consistency group. |
| replication_source | boolean | Since support for this field is to be removed in the next release, use replication_relationships.is_source instead. |
| restore_to | restore_to | Use to restore a consistency group to a previous snapshot |
| snapshot_policy | snapshot_policy_reference | This is a reference to the snapshot policy. |
| uuid | string | <p>The unique identifier of the consistency group. The UUID is generated by ONTAP when the consistency group is created.</p> <ul style="list-style-type: none"> example: 1cd8a442-86d1-11e0-ae1c-123478563412 readOnly: 1 Introduced in: 9.10 x-nullable: true |
| volumes | array[volumes] | <p>A consistency group is a mutually exclusive aggregation of volumes or other consistency groups. A volume can only be associated with one direct parent consistency group.</p> <p>The total number of volumes across all child consistency groups contained in a consistency group is constrained by the same limit.</p> |

error_arguments

| Name | Type | Description |
|---------|--------|------------------|
| code | string | Argument code |
| message | string | Message argument |

returned_error

| Name | Type | Description |
|-----------|------------------------|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

Copyright information

Copyright © 2025 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.