



# Manage name mappings for SVMs

ONTAP 9.7 REST API reference

NetApp  
August 29, 2024

# Table of Contents

- Manage name mappings for SVMs ..... 1
  - Name-services name-mappings endpoint overview ..... 1
  - Retrieve hostname mapping for all SVMs ..... 6
  - Create the hostname mappings for an SVM ..... 12
  - Delete the name mapping configuration ..... 20
  - Retrieve the name mapping configuration for an SVM ..... 23
  - Update the name mapping configuration for an SVM ..... 27

# Manage name mappings for SVMs

## Name-services name-mappings endpoint overview

### Overview

Name mapping is used to map CIFS identities to UNIX identities, Kerberos identities to UNIX identities, and UNIX identities to CIFS identities. It needs this information to obtain user credentials and provide proper file access regardless of whether they are connecting from an NFS client or a CIFS client.

The system keeps a set of conversion rules for each Storage Virtual Machine (SVM). Each rule consists of two pieces: a pattern and a replacement. Conversions start at the beginning of the appropriate list and perform a substitution based on the first matching rule. The pattern is a UNIX-style regular expression. The replacement is a string containing escape sequences representing subexpressions from the pattern, as in the UNIX `sed` program.

Name mappings are applied in the order in which they occur in the priority list; for example, a name mapping that occurs at position 2 in the priority list is applied before a name mapping that occurs at position 3. Each mapping direction (Kerberos-to-UNIX, Windows-to-UNIX, and UNIX-to-Windows) has its own priority list. You are prevented from creating two name mappings with the same pattern.

### Examples

#### Creating a name-mapping with `client_match` as the ip-address

Use the following API to create a name-mapping. Note the `return_records=true` query parameter is used to obtain the newly created entry in the response.

```

# The API:
POST /api//name-services/name-mappings

# The call:
curl -X POST "https://<mgmt-ip>/api/name-services/name-
mappings?return_records=true" -H "accept: application/json" -H "Content-
Type: application/json" -d "{ \"client_match\": \"10.254.101.111/28\",
\"direction\": \"win_unix\", \"index\": 1, \"pattern\":
\"ENGCIIFS_AD_USER\", \"replacement\": \"unix_user1\", \"svm\": { \"name\":
\"vs1\", \"uuid\": \"f71d3640-0226-11e9-8526-000c290a8c4b\" }}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "uuid": "f71d3640-0226-11e9-8526-000c290a8c4b",
        "name": "vs1"
      },
      "direction": "win_unix",
      "index": 1,
      "pattern": "ENGCIIFS_AD_USER",
      "replacement": "unix_user1",
      "client_match": "10.254.101.111/28"
    }
  ]
}

```

### Creating a name-mapping with `client_match` as the hostname

Use the following API to create a name-mapping. Note the `return_records=true` query parameter is used to obtain the newly created entry in the response.

```

# The API:
POST /api//name-services/name-mappings

# The call:
curl -X POST "https://<mgmt-ip>/api/name-services/name-
mappings?return_records=true" -H "accept: application/json" -H "Content-
Type: applicatio/json" -d "{ \"client_match\": \"google.com\",
\"direction\": \"win_unix\", \"index\": 2, \"pattern\":
\"ENGCIIFS_AD_USER\", \"replacement\": \"unix_user1\", \"svm\": { \"name\":
\"vs1\", \"uuid\": \"f71d3640-0226-11e9-8526-000c290a8c4b\" }}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "uuid": "f71d3640-0226-11e9-8526-000c290a8c4b",
        "name": "vs1"
      },
      "direction": "win_unix",
      "index": 2,
      "pattern": "ENGCIIFS_AD_USER",
      "replacement": "unix_user1",
      "client_match": "google.com"
    }
  ]
}

```

### Retrieving all name-mapping configurations for all SVMs in the cluster

```
# The API:
GET /api/name-services/name-mappings

# The call:
curl -X GET "https://<mgmt-ip>/api/name-services/name-
mappings?fields=*&return_records=true&return_timeout=15" -H "accept:
application/json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "f71d3640-0226-11e9-8526-000c290a8c4b",
        "name": "vs1"
      },
      "direction": "win_unix",
      "index": 1,
      "pattern": "ENGCIIFS_AD_USER",
      "replacement": "unix_user1",
      "client_match": "10.254.101.111/28"
    },
    {
      "svm": {
        "uuid": "f71d3640-0226-11e9-8526-000c290a8c4b",
        "name": "vs1"
      },
      "direction": "win_unix",
      "index": 2,
      "pattern": "ENGCIIFS_AD_USER",
      "replacement": "unix_user1",
      "client_match": "google.com"
    }
  ],
  "num_records": 2
}
```

**Retrieving a name-mapping configuration for a specific SVM, and for the specified direction and index**

```
# The API:
GET /api/name-services/name-mappings/{svm.uuid}/{direction}/{index}

# The call:
curl -X GET "https://<mgmt-ip>/api/name-services/name-mappings/f71d3640-0226-11e9-8526-000c290a8c4b/win_unix/1" -H "accept: application/json"

# The response:
{
  "svm": {
    "uuid": "f71d3640-0226-11e9-8526-000c290a8c4b",
    "name": "vs1"
  },
  "direction": "win_unix",
  "index": 1,
  "pattern": "ENGCIFS_AD_USER",
  "replacement": "unix_user1",
  "client_match": "10.254.101.111/28"
}
```

---

## Updating a specific name-mapping configuration

---

```
# The API:
PATCH /api//name-services/name-mappings/{svm.uuid}/{direction}/{index}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/name-services/name-mappings/f71d3640-0226-11e9-8526-000c290a8c4b/win_unix/1" -H "accept: application/json" -H "Content-Type: application/json" -d '{"client_match": "10.254.101.222/28", "pattern": "ENGCIFS_LOCAL_USER", "replacement": "pcuser"}'

# swapping a specified namemapping entry by index
curl -X PATCH "https://<mgmt-ip>/api/name-services/name-mappings/f71d3640-0226-11e9-8526-000c290a8c4b/win-unix/3?new_index=1" -H "accept: application/json" -H "Content-Type: application/json" -d '{"pattern": "ENGCIFS_AD_USER", "replacement": "unix_user1"}'
```

## Removing a specific name-mapping configuration

```
# The API:
DELETE /api/name-services/name-mappings/{svm.uuid}/{direction}/{index}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/name-services/name-mappings/f71d3640-0226-11e9-8526-000c290a8c4b/win_unix/1" -H "accept: application/json"
```

## Retrieve hostname mapping for all SVMs

GET /name-services/name-mappings

Retrieves the name mapping configuration for all SVMs.

### Related ONTAP commands

- `vserver name-mapping show`

### Learn more

- [DOC /name-services/name-mappings](#)

### Parameters

Name	Type	In	Required	Description
pattern	string	query	False	Filter by pattern
client_match	string	query	False	Filter by client_match
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name
replacement	string	query	False	Filter by replacement
direction	string	query	False	Filter by direction
index	integer	query	False	Filter by index



Name	Type	In	Required	Description
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned.
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">name_mapping</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": [
    {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "client_match": "10.254.101.111/28",
      "direction": "win_unix",
      "index": 1,
      "pattern": "ENGCIIFS_AD_USER",
      "replacement": "unix_user1",
      "svm": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      }
    }
  ]
}
```

## Error

Status: Default, Error

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

name\_mapping

Name mapping is used to map CIFS identities to UNIX identities, Kerberos identities to UNIX identities, and UNIX identities to CIFS identities. It needs this information to obtain user credentials and provide proper file access regardless of whether they are connecting from an NFS client or a CIFS client.

Name	Type	Description
_links	<a href="#">_links</a>	

Name	Type	Description
client_match	string	<p>Client workstation IP Address which is matched when searching for the pattern. You can specify the value in any of the following formats:</p> <ul style="list-style-type: none"> <li>• As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24</li> <li>• As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64</li> <li>• As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0</li> <li>• As a hostname</li> </ul>
direction	string	<p>Direction in which the name mapping is applied. The possible values are:</p> <ul style="list-style-type: none"> <li>• krb_unix - Kerberos principal name to UNIX user name</li> <li>• win_unix - Windows user name to UNIX user name</li> <li>• unix_win - UNIX user name to Windows user name mapping</li> </ul>
index	integer	Position in the list of name mappings.
pattern	string	<p>Pattern used to match the name while searching for a name that can be used as a replacement. The pattern is a UNIX-style regular expression. Regular expressions are case-insensitive when mapping from Windows to UNIX, and they are case-sensitive for mappings from Kerberos to UNIX and UNIX to Windows.</p>

Name	Type	Description
replacement	string	The name that is used as a replacement, if the pattern associated with this entry matches.
svm	<a href="#">svm</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Create the hostname mappings for an SVM

POST /name-services/name-mappings

Creates name mappings for an SVM.

### Required properties

- `svm.uuid` or `svm.name` - Existing SVM in which to create the name mapping.
- `index` - Name mapping's position in the priority list.
- `direction` - Direction of the name mapping.
- `pattern` - Pattern to match to. Maximum length is 256 characters.
- `replacement` - Replacement pattern to match to. Maximum length is 256 characters.

## Recommended optional properties

- `client_match` - Hostname or IP address added to match the pattern to the client's workstation IP address.

## Related ONTAP commands

- `vserver name-mapping create`
- `vserver name-mapping insert`

## Learn more

- [DOC /name-services/name-mappings](#)

## Parameters

Name	Type	In	Required	Description
<code>return_records</code>	boolean	query	False	The default is false. If set to true, the records are returned.

## Request Body

Name	Type	Description
<code>_links</code>	<a href="#">_links</a>	
<code>client_match</code>	string	<p>Client workstation IP Address which is matched when searching for the pattern. You can specify the value in any of the following formats:</p> <ul style="list-style-type: none"><li>• As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24</li><li>• As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64</li><li>• As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0</li><li>• As a hostname</li></ul>

Name	Type	Description
direction	string	Direction in which the name mapping is applied. The possible values are: <ul style="list-style-type: none"> <li>• krb_unix - Kerberos principal name to UNIX user name</li> <li>• win_unix - Windows user name to UNIX user name</li> <li>• unix_win - UNIX user name to Windows user name mapping</li> </ul>
index	integer	Position in the list of name mappings.
pattern	string	Pattern used to match the name while searching for a name that can be used as a replacement. The pattern is a UNIX-style regular expression. Regular expressions are case-insensitive when mapping from Windows to UNIX, and they are case-sensitive for mappings from Kerberos to UNIX and UNIX to Windows.
replacement	string	The name that is used as a replacement, if the pattern associated with this entry matches.
svm	svm	



## Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "client_match": "10.254.101.111/28",
  "direction": "win_unix",
  "index": 1,
  "pattern": "ENGCIFS_AD_USER",
  "replacement": "unix_user1",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

## Response

Status: 201, Created

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	<a href="#">array[name_mapping]</a>	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": [
    {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "client_match": "10.254.101.111/28",
      "direction": "win_unix",
      "index": 1,
      "pattern": "ENGCIIFS_AD_USER",
      "replacement": "unix_user1",
      "svm": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      }
    }
  ]
}
```

## Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
65798185	Failed to resolve the specified hostname
65798149	Invalid index for the name mapping entry
2621706	The specified svm.uuid and svm.name refer to different SVMs

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

name\_mapping

Name mapping is used to map CIFS identities to UNIX identities, Kerberos identities to UNIX identities, and UNIX identities to CIFS identities. It needs this information to obtain user credentials and provide proper file access regardless of whether they are connecting from an NFS client or a CIFS client.

Name	Type	Description
_links	<a href="#">_links</a>	

Name	Type	Description
client_match	string	<p>Client workstation IP Address which is matched when searching for the pattern. You can specify the value in any of the following formats:</p> <ul style="list-style-type: none"> <li>• As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24</li> <li>• As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64</li> <li>• As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0</li> <li>• As a hostname</li> </ul>
direction	string	<p>Direction in which the name mapping is applied. The possible values are:</p> <ul style="list-style-type: none"> <li>• krb_unix - Kerberos principal name to UNIX user name</li> <li>• win_unix - Windows user name to UNIX user name</li> <li>• unix_win - UNIX user name to Windows user name mapping</li> </ul>
index	integer	Position in the list of name mappings.
pattern	string	<p>Pattern used to match the name while searching for a name that can be used as a replacement. The pattern is a UNIX-style regular expression. Regular expressions are case-insensitive when mapping from Windows to UNIX, and they are case-sensitive for mappings from Kerberos to UNIX and UNIX to Windows.</p>

Name	Type	Description
replacement	string	The name that is used as a replacement, if the pattern associated with this entry matches.
svm	<a href="#">svm</a>	

#### \_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Delete the name mapping configuration

```
DELETE /name-services/name-mappings/{svm.uuid}/{direction}/{index}
```

Deletes the name mapping configuration.

### Related ONTAP commands

- `vserver name-mapping delete`

## Learn more

- [DOC /name-services/name-mappings](#)

## Parameters

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
direction	string	path	True	Direction
index	integer	path	True	Position of the entry in the list

## Response

Status: 200, Ok

## Error

Status: Default, Error

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

### See Definitions

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.



# Retrieve the name mapping configuration for an SVM

GET /name-services/name-mappings/{svm.uuid}/{direction}/{index}

Retrieves the name mapping configuration of an SVM.

## Related ONTAP commands

- `vserver name-mapping show`

## Learn more

- [DOC /name-services/name-mappings](#)

## Parameters

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
direction	string	path	True	Direction
index	integer	path	True	Position of the entry in the list
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	

Name	Type	Description
client_match	string	<p>Client workstation IP Address which is matched when searching for the pattern. You can specify the value in any of the following formats:</p> <ul style="list-style-type: none"> <li>• As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24</li> <li>• As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64</li> <li>• As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0</li> <li>• As a hostname</li> </ul>
direction	string	<p>Direction in which the name mapping is applied. The possible values are:</p> <ul style="list-style-type: none"> <li>• krb_unix - Kerberos principal name to UNIX user name</li> <li>• win_unix - Windows user name to UNIX user name</li> <li>• unix_win - UNIX user name to Windows user name mapping</li> </ul>
index	integer	Position in the list of name mappings.
pattern	string	<p>Pattern used to match the name while searching for a name that can be used as a replacement. The pattern is a UNIX-style regular expression. Regular expressions are case-insensitive when mapping from Windows to UNIX, and they are case-sensitive for mappings from Kerberos to UNIX and UNIX to Windows.</p>
replacement	string	The name that is used as a replacement, if the pattern associated with this entry matches.

Name	Type	Description
svm	svm	

### Example response

```

{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "client_match": "10.254.101.111/28",
  "direction": "win_unix",
  "index": 1,
  "pattern": "ENGCIFS_AD_USER",
  "replacement": "unix_user1",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}

```

### Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Update the name mapping configuration for an SVM

PATCH /name-services/name-mappings/{svm.uuid}/{direction}/{index}

Updates the name mapping configuration of an SVM. The positions can be swapped by providing the `new_index` property. Swapping is not allowed for entries that have `client_match` property configured.

## Related ONTAP commands

- `vserver name-mapping insert`
- `vserver name-mapping modify`
- `vserver name-mapping swap`

## Learn more

- [DOC /name-services/name-mappings](#)

## Parameters

Name	Type	In	Required	Description
<code>svm.uuid</code>	string	path	True	UUID of the SVM to which this object belongs.
<code>direction</code>	string	path	True	Direction
<code>index</code>	integer	path	True	Position of the entry in the list
<code>new_index</code>	integer	query	False	New position of the Index after a swap is completed.

## Request Body

Name	Type	Description
<code>_links</code>	<a href="#">_links</a>	

Name	Type	Description
client_match	string	<p>Client workstation IP Address which is matched when searching for the pattern. You can specify the value in any of the following formats:</p> <ul style="list-style-type: none"> <li>• As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24</li> <li>• As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64</li> <li>• As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0</li> <li>• As a hostname</li> </ul>
direction	string	<p>Direction in which the name mapping is applied. The possible values are:</p> <ul style="list-style-type: none"> <li>• krb_unix - Kerberos principal name to UNIX user name</li> <li>• win_unix - Windows user name to UNIX user name</li> <li>• unix_win - UNIX user name to Windows user name mapping</li> </ul>
index	integer	Position in the list of name mappings.
pattern	string	<p>Pattern used to match the name while searching for a name that can be used as a replacement. The pattern is a UNIX-style regular expression. Regular expressions are case-insensitive when mapping from Windows to UNIX, and they are case-sensitive for mappings from Kerberos to UNIX and UNIX to Windows.</p>
replacement	string	The name that is used as a replacement, if the pattern associated with this entry matches.

Name	Type	Description
svm	svm	

### Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "client_match": "10.254.101.111/28",
  "direction": "win_unix",
  "index": 1,
  "pattern": "ENGCIFS_AD_USER",
  "replacement": "unix_user1",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

### Response

Status: 200, Ok

### Error

Status: Default

### ONTAP Error Response Codes

Error Code	Description
65798185	Failed to resolve the specified hostname
65798179	Cannot swap entries because one or both entries have hostname or address configured.



Error Code	Description
	Delete and recreate the new entry at the specified position.

schema: \$ref: "#/definitions/error\_response"

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

name\_mapping

Name mapping is used to map CIFS identities to UNIX identities, Kerberos identities to UNIX identities, and UNIX identities to CIFS identities. It needs this information to obtain user credentials and provide proper file access regardless of whether they are connecting from an NFS client or a CIFS client.

Name	Type	Description
_links	<a href="#">_links</a>	

Name	Type	Description
client_match	string	<p>Client workstation IP Address which is matched when searching for the pattern. You can specify the value in any of the following formats:</p> <ul style="list-style-type: none"> <li>• As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24</li> <li>• As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64</li> <li>• As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0</li> <li>• As a hostname</li> </ul>
direction	string	<p>Direction in which the name mapping is applied. The possible values are:</p> <ul style="list-style-type: none"> <li>• krb_unix - Kerberos principal name to UNIX user name</li> <li>• win_unix - Windows user name to UNIX user name</li> <li>• unix_win - UNIX user name to Windows user name mapping</li> </ul>
index	integer	Position in the list of name mappings.
pattern	string	<p>Pattern used to match the name while searching for a name that can be used as a replacement. The pattern is a UNIX-style regular expression. Regular expressions are case-insensitive when mapping from Windows to UNIX, and they are case-sensitive for mappings from Kerberos to UNIX and UNIX to Windows.</p>

Name	Type	Description
replacement	string	The name that is used as a replacement, if the pattern associated with this entry matches.
svm	svm	

## Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.