



# Manage SVM FPolicy configuration

## ONTAP 9.8 REST API reference

NetApp  
April 02, 2024

# Table of Contents

Manage SVM FPolicy configuration .....	1
Protocols fpolicy svm.uuid policies endpoint overview .....	1
Retrieve the FPolicy configuration for an SVM .....	13
Create the FPolicy configuration for an SVM .....	21
Delete an FPolicy configuration for an SVM .....	30
Retrieve an FPolicy configuration for an SVM .....	32
Update an FPolicy configuration for an SVM .....	37

# Manage SVM FPolicy configuration

## Protocols fpolicy svm.uuid policies endpoint overview

### Overview

The FPolicy policy acts as a container for different constituents of the FPolicy such as FPolicy events and the FPolicy engine. It also provides a platform for policy management functions, such as policy enabling and disabling. As part of FPolicy policy configuration, you can specify the name of policy, the SVM to which it belongs, the FPolicy events to monitor, the FPolicy engine to which the generated notifications are sent and the policy priority. FPolicy policy configuration also allows to you to configure the file access behaviour when the primary and secondary servers are down. Under such circumstances, if the "mandatory" field is set to true, file access is denied.

Each FPolicy policy is associated with a scope which allows you to restrain the scope of the policy to specified storage objects such as volume, shares and export or to a set of file extensions such as .txt, .jpeg. An FPolicy policy can be configured to send notifications, to the FPolicy server or for native file blocking which uses the file extension specified in the policy scope. An SVM can have multiple FPolicy policies which can be enabled or disabled independently of each other.

### Examples

#### Creating an FPolicy policy

Use the following API to create an FPolicy policy configuration. Note that the *return\_records=true* query parameter used to obtain the newly created entry in the response.

```
# The API:  
POST /protocols/fpolicy/{svm.uuid}/policies  
  
# The call:  
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-  
b64a-0050568eeb34/policies?return_records=true" -H "accept:  
application/json" -H "Content-Type: application/json" -d "{ \"engine\": {  
\"name\": \"engine1\" }, \"events\": [ { \"name\": \"cifs\" }, { \"name\":  
\"nfs\" } ], \"mandatory\": true, \"name\": \"FPolicy_policy_0\",  
\"scope\": { \"exclude_export_policies\": [ \"export_pol1\" ],  
\"exclude_extension\": [ \"txt\", \"png\" ], \"exclude_shares\": [ \"sh1\" ],  
\"exclude_volumes\": [ \"vol0\" ], \"include_export_policies\": [  
\"export_pol10\" ], \"include_extension\": [ \"pdf\" ],  
\"include_shares\": [ \"sh2\", \"sh3\" ], \"include_volumes\": [ \"vol1\",  
\"vol2\" ] } }"  
  
# The response:  
{  
"num_records": 1,
```

```
"records": [
  {
    "name": "FPolicy_policy_0",
    "events": [
      {
        "name": "cifs"
      },
      {
        "name": "nfs"
      }
    ],
    "engine": {
      "name": "engine1"
    },
    "scope": {
      "include_shares": [
        "sh2",
        "sh3"
      ],
      "exclude_shares": [
        "sh1"
      ],
      "include_volumes": [
        "vol1",
        "vol2"
      ],
      "exclude_volumes": [
        "vol0"
      ],
      "include_export_policies": [
        "export_pol10"
      ],
      "exclude_export_policies": [
        "export_pol1"
      ],
      "include_extension": [
        "pdf"
      ],
      "exclude_extension": [
        "txt",
        "png"
      ]
    },
    "mandatory": true
  }
]
```

```
}
```

## Creating and enable an FPolicy policy

```
# The API:  
POST /protocols/fpolicy/{svm.uuid}/policies  
  
# The call:  
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-b64a-0050568eeb34/policies?return_records=true" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"priority\": 1, \"engine\": { \"name\": \"engine1\" }, \"events\": [ { \"name\": \"cifs\" }, { \"name\": \"nfs\" } ], \"mandatory\": true, \"name\": \"FPolicy_policy_on\", \"scope\": { \"exclude_export_policies\": [ \"export_pol1\" ], \"exclude_extension\": [ \"txt\", \"png\" ], \"exclude_shares\": [ \"sh1\" ], \"exclude_volumes\": [ \"vol0\" ], \"include_export_policies\": [ \"export_pol10\" ], \"include_extension\": [ \"pdf\" ], \"include_shares\": [ \"sh2\", \"sh3\" ], \"include_volumes\": [ \"vol1\", \"vol2\" ] } }"  
  
# The response:  
{  
  "num_records": 1,  
  "records": [  
    {  
      "name": "FPolicy_policy_0",  
      "priority": 1,  
      "events": [  
        {  
          "name": "cifs"  
        },  
        {  
          "name": "nfs"  
        }  
      ],  
      "engine": {  
        "name": "engine1"  
      },  
      "scope": {  
        "include_shares": [  
          "sh2",  
          "sh3"  
        ]  
      }  
    }  
  ]  
}
```

```
],
  "exclude_shares": [
    "sh1"
  ],
  "include_volumes": [
    "vol1",
    "vol2"
  ],
  "exclude_volumes": [
    "vol0"
  ],
  "include_export_policies": [
    "export_pol10"
  ],
  "exclude_export_policies": [
    "export_pol1"
  ],
  "include_extension": [
    "pdf"
  ],
  "exclude_extension": [
    "txt",
    "png"
  ]
},
"mandatory": true
}
]
}
```

---

## Creating an FPolicy policy with the minimum required fields and a native engine

---

```

# The API:
POST /protocols/fpolicy/{svm.uuid}/policies

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"events\": [
{ \"name\": \"cifs\" }, { \"name\": \"nfs\" } ], \"name\":
\"pol_minimum_fields\", \"scope\": { \"include_volumes\": [ \"vol1\",
\"vol2\" ] }}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "name": "pol_minimum_fields",
      "events": [
        {
          "name": "cifs"
        },
        {
          "name": "nfs"
        }
      ],
      "scope": {
        "include_volumes": [
          "vol1",
          "vol2"
        ]
      }
    }
  ]
}

```

## Retrieving all the FPolicy policy configurations for an SVM

```

# The API:
GET /protocols/fpolicy/{svm.uuid}/policies

# The call:

```

```

curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies?fields=*&return_records=true&return_timeout=15"
-H "accept: application/json"

# The response:
{
"records": [
{
"svm": {
"uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34",
},
"name": "pol0",
"enabled": false,
"events": [
{
"name": "cifs"
},
{
"name": "nfs"
}
],
"engine": {
"name": "engine1"
},
"scope": {
"include_shares": [
"sh2",
"sh3"
],
"exclude_shares": [
"sh1"
],
"include_volumes": [
"vol1",
"vol2"
],
"exclude_volumes": [
"vol0"
],
"include_export_policies": [
"export_pol10"
],
"exclude_export_policies": [
"export_pol1"
],
"include_extension": [
]
}
}
]
}

```

```
        "pdf"
    ],
    "exclude_extension": [
        "txt",
        "png"
    ]
},
"mandatory": true
},
{
    "svm": {
        "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
    },
    "name": "FPolicy_policy_on",
    "enabled": true,
    "priority": 1,
    "events": [
        {
            "name": "cifs"
        },
        {
            "name": "nfs"
        }
    ],
    "engine": {
        "name": "engine1"
    },
    "scope": {
        "include_shares": [
            "sh2",
            "sh3"
        ],
        "exclude_shares": [
            "sh1"
        ],
        "include_volumes": [
            "vol1",
            "vol2"
        ],
        "exclude_volumes": [
            "vol0"
        ],
        "include_export_policies": [
            "export_pol10"
        ],
        "exclude_export_policies": [

```

```

    "export_pol1"
],
"include_extension": [
    "pdf"
],
"exclude_extension": [
    "txt",
    "png"
]
},
"mandatory": true
},
{
"svm": {
    "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
},
"name": "cluster_pol",
"enabled": false,
"events": [
    {
        "name": "cluster"
    }
],
"engine": {
    "name": "native"
},
"mandatory": true
},
{
"svm": {
    "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
},
"name": "pol_minimum_fields",
"enabled": false,
"events": [
    {
        "name": "cifs"
    },
    {
        "name": "nfs"
    }
],
"engine": {
    "name": "native"
},
"scope": {

```

```

    "include_volumes": [
        "vol1",
        "vol2"
    ],
},
"mandatory": true
},
],
"num_records": 4
}

```

## Retrieving all of the FPolicy policy configurations for the FPolicy engine "engine1" for an SVM

```

# The API:
GET /protocols/fpolicy/{svm.uuid}/policies/{name}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-
0050568eeb34/policies?engine.name=engine1&fields=&return_records=true&ret
urn_timeout=15" -H "accept: application/json"

# The response:
{
"records": [
{
    "svm": {
        "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
    },
    "name": "pol0",
    "enabled": false,
    "events": [
        {
            "name": "cifs"
        },
        {
            "name": "nfs"
        }
    ],
    "engine": {
        "name": "engine1"
    },

```

```

"scope": {
    "include_export_policies": [
        "export_pol10"
    ],
    "exclude_export_policies": [
        "export_pol1"
    ],
    "include_extension": [
        "pdf"
    ],
    "exclude_extension": [
        "txt",
        "png"
    ]
},
"mandatory": true
},
{
    "svm": {
        "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
    },
    "name": "FPolicy_policy_on",
    "enabled": true,
    "priority": 1,
    "events": [
        {
            "name": "cifs"
        },
        {
            "name": "nfs"
        }
    ],
    "engine": {
        "name": "engine1"
    },
    "scope": {
        "include_shares": [
            "sh2",
            "sh3"
        ],
        "exclude_shares": [
            "sh1"
        ],
        "include_volumes": [
            "vol1",
            "vol2"
        ]
    }
}

```

```

        ],
        "exclude_volumes": [
            "vol0"
        ],
        "include_export_policies": [
            "export_pol10"
        ],
        "exclude_export_policies": [
            "export_pol1"
        ],
        "include_extension": [
            "pdf"
        ],
        "exclude_extension": [
            "txt",
            "png"
        ]
    },
    "mandatory": true
}
],
"num_records": 2
}

```

## Retrieving a particular FPolicy policy configuration for an SVM

```

# The API:
GET /protocols/fpolicy/{svm.uuid}/policies/{name}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies/pol0" -H "accept: application/json"

# The response:
{
  "svm": {
    "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
  },
  "name": "pol0",
  "enabled": false,
  "events": [
    {

```

```

        "name": "cifs"
    },
{
    "name": "nfs"
}
],
"engine": {
    "name": "engine1"
},
"scope": {
    "include_shares": [
        "sh2",
        "sh3"
    ],
    "exclude_shares": [
        "sh1"
    ],
    "include_volumes": [
        "vol1",
        "vol2"
    ],
    "exclude_volumes": [
        "vol0"
    ],
    "include_export_policies": [
        "export_pol10"
    ],
    "exclude_export_policies": [
        "export_pol1"
    ],
    "include_extension": [
        "pdf"
    ],
    "exclude_extension": [
        "txt",
        "png"
    ]
},
"mandatory": true
}

```

## Updating a particular FPolicy policy

```
# The API:
PATCH /protocols/fpolicy/{svm.uuid}/policies/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies/pol0" -H "accept: application/json" -H
"Content-Type: application/json" -d "{ \"engine\": { \"name\": \"native\",
\"events\": [ { \"name\": \"cifs\" } ], \"mandatory\": false,
\"scope\": { \"include_volumes\": [ \"*\" ] } } }
```

## Enabling a particular FPolicy policy

```
# The API:
PATCH /protocols/fpolicy/{svm.uuid}/policies/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies/pol0" -H "accept: application/json" -H
"Content-Type: application/json" -d "{ \"enabled\": true, \"priority\": 3 }
```

## Disabling a particular FPolicy policy

```
# The API:
PATCH /protocols/fpolicy/{svm.uuid}/policies/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies/pol0" -H "accept: application/json" -H
"Content-Type: application/json" -d "{ \"enabled\": false }
```

# Retrieve the FPolicy configuration for an SVM

GET /protocols/fpolicy/{svm.uuid}/policies

## Introduced In: 9.6

Retrieves the FPolicy policy configuration of an SVM. ONTAP allows the creation of a cluster level FPolicy policy that acts as a template for all the data SVMs belonging to the cluster. This cluster level FPolicy policy is also retrieved for the specified SVM.

## Related ONTAP commands

- `fpolicy policy show`
- `fpolicy policy scope show`

## Learn more

- [DOC /protocols/fpolicy/{svm.uuid}/policies](#)

## Parameters

Name	Type	In	Required	Description
priority	integer	query	False	Filter by priority
engine.name	string	query	False	Filter by engine.name
events.name	string	query	False	Filter by events.name
scope.include_shares	string	query	False	Filter by scope.include_shares
scope.include_extension	string	query	False	Filter by scope.include_extension
scope.include_volumes	string	query	False	Filter by scope.include_volumes
scope.include_export_policies	string	query	False	Filter by scope.include_export_policies
scope.exclude_export_policies	string	query	False	Filter by scope.exclude_export_policies

Name	Type	In	Required	Description
scope.exclude_shares	string	query	False	Filter by scope.exclude_shares
scope.exclude_volumes	string	query	False	Filter by scope.exclude_volumes
scope.exclude_extension	string	query	False	Filter by scope.exclude_extension
name	string	query	False	Filter by name
enabled	boolean	query	False	Filter by enabled
mandatory	boolean	query	False	Filter by mandatory
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	<p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc]

## Response

```
Status: 200, Ok
```

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of Records
records	array[fpolicy_policy]	

## Example response

```
{  
  "_links": {  
    "next": {  
      "href": "/api/resourcelink"  
    },  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "records": {  
    "engine": {  
      "_links": {  
        "self": {  
          "href": "/api/resourcelink"  
        }  
      },  
      "events": [  
        "event_nfs_close",  
        "event_open"  
      ],  
      "name": "fp_policy_1",  
      "scope": {  
        "exclude_export_policies": {  
        },  
        "exclude_extension": {  
        },  
        "exclude_shares": {  
        },  
        "exclude_volumes": [  
          "vol1",  
          "vol_svml",  
          "*"  
        ],  
        "include_export_policies": {  
        },  
        "include_extension": {  
        },  
        "include_shares": [  
          "sh1",  
          "share_cifs"  
        ],  
        "include_volumes": [  
          "vol1",  
          "vol_svml",  
          "*"  
        ]  
      }  
    }  
  }  
}
```

```
        "vol_svm1"
    ]
}
}
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	href	
self	href	

\_links

Name	Type	Description
self	href	

fpolicy\_engine\_reference

FPolicy external engine

Name	Type	Description
_links	_links	
name	string	The name of the FPolicy external engine.

fpolicy\_event\_reference

FPolicy events

Name	Type	Description
_links	_links	
name	string	

scope

Name	Type	Description
exclude_export_policies	array[string]	
exclude_extension	array[string]	
exclude_shares	array[string]	
exclude_volumes	array[string]	
include_export_policies	array[string]	

Name	Type	Description
include_extension	array[string]	
include_shares	array[string]	
include_volumes	array[string]	

### fpolicy\_policy

Name	Type	Description
enabled	boolean	Specifies if the policy is enabled on the SVM or not. If no value is mentioned for this field but priority is set, then this policy will be enabled.
engine	<a href="#">fpolicy_engine_reference</a>	FPolicy external engine
events	array[fpolicy_event_reference]	
mandatory	boolean	Specifies what action to take on a file access event in a case when all primary and secondary servers are down or no response is received from the FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.
name	string	Specifies the name of the policy.
priority	integer	Specifies the priority that is assigned to this policy.
scope	<a href="#">scope</a>	

### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

### error

Name	Type	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Create the FPolicy configuration for an SVM

POST /protocols/fpolicy/{svm.uuid}/policies

**Introduced In:** 9.6

Creates an FPolicy policy configuration for the specified SVM. To create an FPolicy policy, you must specify the policy scope and the FPolicy events to be monitored.

Important notes:

- A single policy can monitor multiple events.
- An FPolicy engine is an optional field whose default value is set to native. A native engine can be used to simply block the file access based on the file extensions specified in the policy scope.
- To enable a policy, the policy priority must be specified. If the priority is not specified, the policy is created but it is not enabled.
- The "mandatory" field, if set to true, blocks the file access when the primary or secondary FPolicy servers are down.

### Required properties

- `svm.uuid` - Existing SVM in which to create the FPolicy policy.
- `events` - Name of the events to monitor.
- `name` - Name of the FPolicy policy.
- `scope` - Scope of the policy. Can be limited to exports, volumes, shares or file extensions.
- `priority` - Priority of the policy (ranging from 1 to 10).

### Default property values

- `mandatory` - `true`
- `engine` - `native`

## Related ONTAP commands

- `fpolicy policy scope create`
- `fpolicy policy create`
- `fpolicy enable`

## Learn more

- [DOC /protocols/fpolicy/{svm.uuid}/policies](#)

## Parameters

Name	Type	In	Required	Description
return_records	boolean	query	False	The default is false. If set to true, the records are returned. <ul style="list-style-type: none"><li>• Default value:</li></ul>
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Request Body

Name	Type	Description
enabled	boolean	Specifies if the policy is enabled on the SVM or not. If no value is mentioned for this field but priority is set, then this policy will be enabled.
engine	<a href="#">fpolicy_engine_reference</a>	FPolicy external engine
events	array[ <a href="#">fpolicy_event_reference</a> ]	
mandatory	boolean	Specifies what action to take on a file access event in a case when all primary and secondary servers are down or no response is received from the FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.

Name	Type	Description
name	string	Specifies the name of the policy.
priority	integer	Specifies the priority that is assigned to this policy.
scope	scope	

## Example request

```
{  
    "engine": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        }  
    },  
    "events": [  
        "event_nfs_close",  
        "event_open"  
    ],  
    "name": "fp_policy_1",  
    "scope": {  
        "exclude_export_policies": {  
        },  
        "exclude_extension": {  
        },  
        "exclude_shares": {  
        },  
        "exclude_volumes": [  
            "vol1",  
            "vol_svm1",  
            "*"  
        ],  
        "include_export_policies": {  
        },  
        "include_extension": {  
        },  
        "include_shares": [  
            "sh1",  
            "share_cifs"  
        ],  
        "include_volumes": [  
            "vol1",  
            "vol_svm1"  
        ]  
    }  
}
```

## Response

Status: 201, Created

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of Records
records	array[ <a href="#">fpolicy_policy</a> ]	

## Example response

```
{  
  "_links": {  
    "next": {  
      "href": "/api/resourcelink"  
    },  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "records": {  
    "engine": {  
      "_links": {  
        "self": {  
          "href": "/api/resourcelink"  
        }  
      },  
      "events": [  
        "event_nfs_close",  
        "event_open"  
      ],  
      "name": "fp_policy_1",  
      "scope": {  
        "exclude_export_policies": {  
        },  
        "exclude_extension": {  
        },  
        "exclude_shares": {  
        },  
        "exclude_volumes": [  
          "vol1",  
          "vol_svml",  
          "*"  
        ],  
        "include_export_policies": {  
        },  
        "include_extension": {  
        },  
        "include_shares": [  
          "sh1",  
          "share_cifs"  
        ],  
        "include_volumes": [  
          "vol1",  
          "vol2"  
        ]  
      }  
    }  
  }  
}
```

```

        "vol_svm1"
    ]
}
}
}
```

## Error

Status: Default

### ONTAP Error Response Codes

Error Code	Description
9765027	FPolicy creation is successful but it cannot be enabled as the priority is already in use by another policy
9764898	An FPolicy policy cannot be created without defining its scope

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	href	

fpolicy\_engine\_reference

FPolicy external engine

Name	Type	Description
_links	_links	
name	string	The name of the FPolicy external engine.

fpolicy\_event\_reference

FPolicy events

Name	Type	Description
_links	_links	
name	string	

scope

Name	Type	Description
exclude_export_policies	array[string]	
exclude_extension	array[string]	
exclude_shares	array[string]	
exclude_volumes	array[string]	
include_export_policies	array[string]	
include_extension	array[string]	
include_shares	array[string]	
include_volumes	array[string]	

fpolicy\_policy

Name	Type	Description
enabled	boolean	Specifies if the policy is enabled on the SVM or not. If no value is mentioned for this field but priority is set, then this policy will be enabled.
engine	fpolicy_engine_reference	FPolicy external engine
events	array[fpolicy_event_reference]	
mandatory	boolean	Specifies what action to take on a file access event in a case when all primary and secondary servers are down or no response is received from the FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.
name	string	Specifies the name of the policy.
priority	integer	Specifies the priority that is assigned to this policy.
scope	scope	

## \_links

Name	Type	Description
next	href	
self	href	

## error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

## error

Name	Type	Description
arguments	array[error_arguments]	Message arguments

Name	Type	Description
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Delete an FPolicy configuration for an SVM

DELETE /protocols/fpolicy/{svm.uuid}/policies/{name}

**Introduced In:** 9.6

Deletes a particular FPolicy policy configuration for a specified SVM. To delete a policy, you must first disable the policy.

### Related ONTAP commands

- `fpolicy policy scope delete`
- `fpolicy policy delete`

### Learn more

- [DOC /protocols/fpolicy/{svm.uuid}/policies](#)

### Parameters

Name	Type	In	Required	Description
name	string	path	True	
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

### Response

Status: 200, Ok

### Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
9764900	Deletion of a cluster level FPolicy policy is not supported
9764941	Cannot delete an enabled FPolicy policy

Name	Type	Description
error	error	

### Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve an FPolicy configuration for an SVM

GET /protocols/fpolicy/{svm.uuid}/policies/{name}

**Introduced In:** 9.6

Retrieves a particular FPolicy policy configuration for a specified SVM. Cluster-level FPolicy policy configuration details cannot be retrieved for a data SVM.

## Related ONTAP commands

- `fpolicy policy show`
- `fpolicy policy scope show`
- `fpolicy show`

## Learn more

- [DOC /protocols/fpolicy/{svm.uuid}/policies](#)

## Parameters

Name	Type	In	Required	Description
name	string	path	True	

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
enabled	boolean	Specifies if the policy is enabled on the SVM or not. If no value is mentioned for this field but priority is set, then this policy will be enabled.
engine	fpolicy_engine_reference	FPolicy external engine
events	array[fpolicy_event_reference]	
mandatory	boolean	Specifies what action to take on a file access event in a case when all primary and secondary servers are down or no response is received from the FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.
name	string	Specifies the name of the policy.
priority	integer	Specifies the priority that is assigned to this policy.
scope	scope	

## Example response

```
{  
    "engine": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        }  
    },  
    "events": [  
        "event_nfs_close",  
        "event_open"  
    ],  
    "name": "fp_policy_1",  
    "scope": {  
        "exclude_export_policies": {  
        },  
        "exclude_extension": {  
        },  
        "exclude_shares": {  
        },  
        "exclude_volumes": [  
            "vol1",  
            "vol_svm1",  
            "*"  
        ],  
        "include_export_policies": {  
        },  
        "include_extension": {  
        },  
        "include_shares": [  
            "sh1",  
            "share_cifs"  
        ],  
        "include_volumes": [  
            "vol1",  
            "vol_svm1"  
        ]  
    }  
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	href	

fpolicy\_engine\_reference

FPolicy external engine

Name	Type	Description
_links	_links	
name	string	The name of the FPolicy external engine.

fpolicy\_event\_reference

FPolicy events

Name	Type	Description
_links	_links	
name	string	

scope

Name	Type	Description
exclude_export_policies	array[string]	
exclude_extension	array[string]	
exclude_shares	array[string]	
exclude_volumes	array[string]	
include_export_policies	array[string]	
include_extension	array[string]	
include_shares	array[string]	
include_volumes	array[string]	

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Update an FPolicy configuration for an SVM

PATCH /protocols/fpolicy/{svm.uuid}/policies/{name}

**Introduced In:** 9.6

Updates a particular FPolicy policy configuration for a specified SVM. PATCH can be used to enable or disable the policy. When enabling a policy, you must specify the policy priority. The policy priority of the policy is not required when disabling the policy. If the policy is enabled, the FPolicy policy engine cannot be modified.

### Related ONTAP commands

- [fpolicy policy modify](#)
- [fpolicy policy scope modify](#)
- [fpolicy enable](#)
- [fpolicy disable](#)

### Learn more

- [DOC /protocols/fpolicy/{svm.uuid}/policies](#)

### Parameters

Name	Type	In	Required	Description
name	string	path	True	

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Request Body

Name	Type	Description
enabled	boolean	Specifies if the policy is enabled on the SVM or not. If no value is mentioned for this field but priority is set, then this policy will be enabled.
engine	<a href="#">fpolicy_engine_reference</a>	FPolicy external engine
events	array[ <a href="#">fpolicy_event_reference</a> ]	
mandatory	boolean	Specifies what action to take on a file access event in a case when all primary and secondary servers are down or no response is received from the FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.
name	string	Specifies the name of the policy.
priority	integer	Specifies the priority that is assigned to this policy.
scope	<a href="#">scope</a>	

## Example request

```
{  
    "engine": {  
        "_links": {  
            "self": {  
                "href": "/api/resourcelink"  
            }  
        }  
    },  
    "events": [  
        "event_nfs_close",  
        "event_open"  
    ],  
    "name": "fp_policy_1",  
    "scope": {  
        "exclude_export_policies": {  
        },  
        "exclude_extension": {  
        },  
        "exclude_shares": {  
        },  
        "exclude_volumes": [  
            "vol1",  
            "vol_svm1",  
            "*"  
        ],  
        "include_export_policies": {  
        },  
        "include_extension": {  
        },  
        "include_shares": [  
            "sh1",  
            "share_cifs"  
        ],  
        "include_volumes": [  
            "vol1",  
            "vol_svm1"  
        ]  
    }  
}
```

## Response

```
Status: 200, Ok
```

## Error

```
Status: Default
```

### ONTAP Error Response Codes

Error Code	Description
9765026	The priority must be specified when enabling the FPolicy policy
9765025	Cannot disable an FPolicy policy when the priority is specified
9764899	Cannot modify an FPolicy engine when the policy is enabled
9764899	Deletion of a cluster policy is not supported
9764908	An FPolicy policy is already enabled
9764907	An FPolicy policy is already disabled
9765029	An FPolicy was modified but disable/enable failed as the policy is already disabled/enabled

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## **Definitions**

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	href	

fpolicy\_engine\_reference

FPolicy external engine

Name	Type	Description
_links	_links	
name	string	The name of the FPolicy external engine.

fpolicy\_event\_reference

FPolicy events

Name	Type	Description
_links	_links	
name	string	

scope

Name	Type	Description
exclude_export_policies	array[string]	
exclude_extension	array[string]	
exclude_shares	array[string]	
exclude_volumes	array[string]	
include_export_policies	array[string]	
include_extension	array[string]	
include_shares	array[string]	
include_volumes	array[string]	

fpolicy\_policy

Name	Type	Description
enabled	boolean	Specifies if the policy is enabled on the SVM or not. If no value is mentioned for this field but priority is set, then this policy will be enabled.
engine	fpolicy_engine_reference	FPolicy external engine
events	array[fpolicy_event_reference]	
mandatory	boolean	Specifies what action to take on a file access event in a case when all primary and secondary servers are down or no response is received from the FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.
name	string	Specifies the name of the policy.
priority	integer	Specifies the priority that is assigned to this policy.
scope	scope	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message

Name	Type	Description
target	string	The target parameter that caused the error.

## **Copyright information**

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—with prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## **Trademark information**

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.