



Manage security roles

REST API reference

NetApp
September 12, 2025

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-98/security_roles_endpoint_overview.html on September 12, 2025. Always check docs.netapp.com for the latest.

Table of Contents

Manage security roles	1
Security roles endpoint overview	1
Overview	1
Examples	2
Retrieve a list of roles configured in the cluster	6
Related ONTAP commands	6
Learn more	6
Parameters	6
Response	8
Error	10
Definitions	10
Create a new cluster-scoped or SVM-scoped role	12
Required parameters	13
Optional parameters	13
Related ONTAP commands	13
Learn more	13
Parameters	13
Request Body	13
Response	14
Error	14
Definitions	15

Manage security roles

Security roles endpoint overview

Overview

ONTAP supports Role Based Access Control (RBAC) wherein a user account must be associated with a role and the role defines the privileges and rights for that user account. A privilege defines the access level of the API as either "none", "readonly", or "all". This specifies whether the user account can perform only a GET operation or POST, PATCH, and DELETE operations as well. A role can comprise of multiple tuples and each tuple consists of the REST API and its access level. For example, "role1" might be a role that has a tuple `{"access":"all","path":"/api/storage/volume"}`, which means that a user account with "role1" can perform all GET, POST, PATCH, and DELETE requests on the `api/storage/volume` API or derived APIs which have `api/storage/volume` as the prefix.

In cases where a role has tuples with multiple APIs having the same prefix, the highest match wins out. For example, if "role1" has the following tuples: `{"access":"readonly","path":"/api/cluster"}` and `{"access":"all","path":"/api/cluster/schedules"}`, then only a GET request is allowed on APIs with `api/cluster` as the prefix; while POST, PATCH and DELETE requests are possible on the `api/cluster/schedules` API.

Predefined (built-in) roles

Related REST APIs are used to form predefined cluster-scoped and SVM-scoped roles, such as: "admin", "backup", "readonly" for cluster and "vsadmin", "vsadmin-backup", "vsadmin-protocol" for SVMs. These can be retrieved by calling a GET request on `/api/security/roles` API and can be assigned to user accounts. See the examples for `api/security/accounts`.

These predefined roles cannot be modified or deleted.

Mapped roles

Before REST APIs, the RBAC roles (legacy roles) were defined to contain the CLI commands and their access levels. Now, almost all REST APIs map to one or more CLI commands. When a role is created using a POST request on `/api/security/roles`, a mapped legacy role is created. This legacy role has the same access level (as that of the REST API) for the mapped CLI commands. However, if a legacy role with the same name already exists, the POST operation fails and you need to choose a unique name for the role. The legacy roles cannot be managed using the REST endpoint `/api/security/roles` or its derivatives. Legacy roles are managed using the CLI commands `"security login role <create | modify | delete> -role <rolename>"</rolename>`

Note that the mapped legacy role (for the REST API role created) cannot be manipulated using the CLI.

The reverse case is not true; the creation of a legacy role will not create a mapped role with equivalent REST APIs.

API restrictions

Numerous APIs are scoped for the cluster level only. This results in an access error if assigned to an SVM-scoped role. For example, `api/cluster/nodes` does not work when added as a tuple entry for an SVM-scoped role.

A number of APIs allowed for an SVM-scoped role might have restrictions on the access level. For example, `/api/network/ethernet/ports` cannot have an access level of "all" for an SVM-scoped role; this results in an

access error when a POST or PATCH request is made.

Roles created with a REST API path prefix which is common to many APIs might have restrictions based on the scope of the role; cluster or SVM. For example, `{"access":"all","path":"/api/security"}` might be a tuple entry for an SVM role. Any GET, POST, PATCH, or DELETE operation fails on API `/api/security/accounts` while the same on `/api/security/login/messages` succeeds. However, a role with exactly the same tuple when created at the cluster-scope level allows the operations.

Numerous APIs have restrictions on the objects that can be operated on based on the context of the SVM or cluster. For example, a POST request on `/api/security/authentication/password` API changes the password for a user account. If executed in the context of an SVM (POST request on an SVM interface), only the password of the user executing the POST can be modified, and attempts to modify the password of any other user results in an access error. However, if a POST request is performed by a cluster administrator account, the password for any user account (cluster or SVM) can be modified.

Examples

Creating a cluster-scoped custom role

Specify the role name and the tuples (of REST APIs and their access level) in the body of the POST request. The owner.uuid or owner.name are not required to be specified for a cluster-scoped role.

```
# The API:  
POST "/api/security/roles"  
  
# The call:  
curl -X POST "https://<mgmt-ip>/api/security/roles" -d  
'{"name":"cluster_role", "privileges" :  
[{"access":"readonly","path":"/api/cluster/jobs"}, {"access":"all","path":"/api/application/applications"}, {"access":"readonly","path":"/api/application/templates"}]}'
```

Creating an SVM-scoped custom role

For an SVM-scoped role, specify either owner.name or owner.uuid in the request body along with other parameters for the role. These correspond to the name or UUID of the SVM for which the role is being created and can be obtained from the response body of the GET request performed on the `/api/svm/svms` API.

```
# The API:  
POST "/api/security/roles"  
  
# The call:  
curl -X POST "https://<mgmt-ip>/api/security/roles" -d '{"owner": {"uuid" : "9f93e553-4b02-11e9-a3f9-005056bb7acd"}, "name": "svm_role", "privileges" :  
[{"access":"readonly","path":"/api/cluster/jobs"}, {"access":"all","path":"/api/application/applications"}, {"access":"readonly","path":"/api/application/templates"}]}'
```

Retrieving the configured roles

All of the roles or a filtered list of roles (for example by name, predefined, and so on) can be retrieved.

```
# The API:  
GET "/api/security/roles"  
  
# The call to retrieve all the roles configured in the cluster:  
curl -X GET "https://<mgmt-ip>/api/security/roles"  
  
# The response:  
{  
  "records": [  
    {  
      "owner": {  
        "uuid": "2903de6f-4bd2-11e9-b238-0050568e2e25",  
        "name": "cluster1",  
        "_links": {  
          "self": {  
            "href": "/api/svm/svms/2903de6f-4bd2-11e9-b238-0050568e2e25"  
          }  
        }  
      },  
      "name": "admin",  
      "privileges": [  
        {  
          "path": "/api",  
          "access": "all",  
          "_links": {  
            "self": {  
              "href": "/api/security/roles/2903de6f-4bd2-11e9-b238-  
0050568e2e25/admin/privileges/%2Fapi"  
            }  
          }  
        }  
      ],  
      "builtin": true,  
      "scope": "cluster",  
      "_links": {  
        "self": {  
          "href": "/api/security/roles/2903de6f-4bd2-11e9-b238-  
0050568e2e25/admin"  
        }  
      }  
    },  
    {
```

```

"owner": {
    "uuid": "aaef7c38-4bd3-11e9-b238-0050568e2e25",
    "name": "svm1",
    "_links": {
        "self": {
            "href": "/api/svm/svms/aaef7c38-4bd3-11e9-b238-0050568e2e25"
        }
    }
},
"name": "vsadmin",
"privileges": [
{
    "path": "/api/application/applications",
    "access": "all",
    "_links": {
        "self": {
            "href": "/api/security/roles/aaef7c38-4bd3-11e9-b238-0050568e2e25/vsadmin/privileges/%2Fapi%2Fapplication%2Fapplications"
        }
    }
},
{
    "path": "/api/application/templates",
    "access": "readonly",
    "_links": {
        "self": {
            "href": "/api/security/roles/aaef7c38-4bd3-11e9-b238-0050568e2e25/vsadmin/privileges/%2Fapi%2Fapplication%2Ftemplates"
        }
    }
},
{
    "path": "/api/cluster",
    "access": "readonly",
    "_links": {
        "self": {
            "href": "/api/security/roles/aaef7c38-4bd3-11e9-b238-0050568e2e25/vsadmin/privileges/%2Fapi%2Fcluster"
        }
    }
},
{
    "path": "/api/svm/svms",
    "access": "readonly",
    "_links": {
        "self": {
            "href": "/api/security/roles/aaef7c38-4bd3-11e9-b238-0050568e2e25/vsadmin/privileges/%2Fapi%2Fsvm%2Fsvms"
        }
    }
}
]
}

```

```

        "href": "/api/security/roles/aaef7c38-4bd3-11e9-b238-
0050568e2e25/vsadmin/privileges/%2Fapi%2Fsvm%2Fsvms"
    }
}
},
{
    "path": "/api/svms",
    "access": "readonly",
    "_links": {
        "self": {
            "href": "/api/security/roles/aaef7c38-4bd3-11e9-b238-
0050568e2e25/vsadmin/privileges/%2Fapi%2Fsvm"
        }
    }
}
],
"builtin": true,
"scope": "svm",
"_links": {
    "self": {
        "href": "/api/security/roles/aaef7c38-4bd3-11e9-b238-
0050568e2e25/vsadmin"
    }
}
}
],
"num_records": 2,
"_links": {
    "self": {
        "href": "/api/security/roles"
    }
}
}

```

Using a scoped call to retrieve the configured roles

```

# Scoped call to retrieve all the roles for a particular SVM using
owner.uuid:
curl -X GET "https://<mgmt-ip>/api/security/roles/?owner.uuid=aaef7c38-
4bd3-11e9-b238-0050568e2e25"

# Scoped call to retrieve all the roles for a particular SVM using
owner.name:
curl -X GET "https://<mgmt-ip>/api/security/roles/?owner.name=svm1"

# Scoped call to retrieve the roles having vsadmin as the prefix in the
role name:
curl -X GET "https://<mgmt-ip>/api/security/roles/?name=vsadmin*"

# Scoped call to retrieve the predefined roles:
curl -X GET "https://<mgmt-ip>/api/security/roles/?builtin=true"

# Scoped call to retrieve the custom roles:
curl -X GET "https://<mgmt-ip>/api/security/roles/?builtin=false"

```

Retrieve a list of roles configured in the cluster

GET /security/roles

Introduced In: 9.6

Retrieves a list of roles configured in the cluster.

Related ONTAP commands

- security login rest-role show

Learn more

- [DOC /security/roles](#)

Parameters

Name	Type	In	Required	Description
privileges.path	string	query	False	<p>Filter by privileges.path</p> <ul style="list-style-type: none"> • Introduced in: 9.7

Name	Type	In	Required	Description
privileges.access	string	query	False	Filter by privileges.access <ul style="list-style-type: none"> • Introduced in: 9.7
scope	string	query	False	Filter by scope <ul style="list-style-type: none"> • Introduced in: 9.7
owner.uuid	string	query	False	Filter by owner.uuid <ul style="list-style-type: none"> • Introduced in: 9.7
owner.name	string	query	False	Filter by owner.name <ul style="list-style-type: none"> • Introduced in: 9.7
name	string	query	False	Filter by name <ul style="list-style-type: none"> • Introduced in: 9.7
builtin	boolean	query	False	Filter by builtin <ul style="list-style-type: none"> • Introduced in: 9.7
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none"> • Default value: 1

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> • Default value: 1 • Max value: 120 • Min value: 0
order_by	array[string]	query	False	Order results by specified fields and optional [asc]

Response

Status: 200, Ok

Name	Type	Description
_links	_links	
num_records	integer	Number of records
records	array[role]	

Example response

```
{  
  "_links": {  
    "next": {  
      "href": "/api/resourcelink"  
    },  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "records": [  
    {  
      "_links": {  
        "self": {  
          "href": "/api/resourcelink"  
        }  
      },  
      "name": "admin",  
      "owner": {  
        "_links": {  
          "self": {  
            "href": "/api/resourcelink"  
          }  
        }  
      },  
      "name": "svml",  
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"  
    },  
    "privileges": [  
      {  
        "_links": {  
          "self": {  
            "href": "/api/resourcelink"  
          }  
        }  
      },  
      "access": "readonly",  
      "path": "/api/storage/volumes"  
    }  
  ],  
  "scope": "string"  
}  
]
```

Error

Status: Default, Error

Name	Type	Description
error	error	

Example error

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

Definitions

See Definitions

href

Name	Type	Description
href	string	

_links

Name	Type	Description
next	href	
self	href	

_links

Name	Type	Description
self	href	

owner

Owner name and UUID that uniquely identifies the role.

Name	Type	Description
_links	_links	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

role_privilege

A tuple containing the REST endpoint and the access level assigned to that endpoint.

Name	Type	Description
_links	_links	
access	string	Access level for the REST endpoint.
path	string	REST URI/endpoint

role

A named set of privileges that defines the rights an account has when it is assigned the role.

Name	Type	Description
_links	_links	
builtin	boolean	Indicates if this is a built-in (pre-defined) role which cannot be modified or deleted.
name	string	Role name
owner	owner	Owner name and UUID that uniquely identifies the role.
privileges	array[role_privilege]	The list of privileges that this role has been granted.
scope	string	Scope of the entity. Set to "cluster" for cluster owned objects and to "svm" for SVM owned objects.

error_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

Create a new cluster-scoped or SVM-scoped role

POST /security/roles

Introduced In: 9.6

Creates a new cluster-scoped role or an SVM-scoped role. For an SVM-scoped role, specify either the SVM name as the owner.name or SVM UUID as the owner.uuid in the request body along with other parameters for the role. The owner.uuid or owner.name are not required to be specified for a cluster-scoped role.

Required parameters

- name - Name of the role to be created.
- privileges - Array of privilege tuples. Each tuple consists of a REST API path and its desired access level.

Optional parameters

- owner.name or owner.uuid - Name or UUID of the SVM for an SVM-scoped role.

Related ONTAP commands

- `security login rest-role create`

Learn more

- [DOC /security/roles](#)

Parameters

Name	Type	In	Required	Description
return_records	boolean	query	False	<p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none">• Default value:

Request Body

Name	Type	Description
builtin	boolean	Indicates if this is a built-in (pre-defined) role which cannot be modified or deleted.
name	string	Role name
owner	owner	Owner name and UUID that uniquely identifies the role.
privileges	array[role_privilege]	The list of privileges that this role has been granted.

Name	Type	Description
scope	string	Scope of the entity. Set to "cluster" for cluster owned objects and to "svm" for SVM owned objects.

Example request

```
{
  "name": "admin",
  "owner": {
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "privileges": [
    {
      "access": "readonly",
      "path": "/api/storage/volumes"
    }
  ],
  "scope": "string"
}
```

Response

Status: 201, Created

Error

Status: Default

ONTAP Error Response Codes

Error Code	Description
2621462	The supplied SVM does not exist.
5636129	Role with given name has not been defined.
5636143	Vserver admin cannot use the API with this access level.
5636144	Invalid value specified for access level.
5636169	Invalid character in URI.

Error Code	Description
5636170	URI does not exist.
5636171	Role already exists in legacy role table.
13434890	Vserver-ID failed for Vserver roles.
13434891	UUID lookup failed for Vserver roles.
13434892	Roles is a required field.

Definitions

See Definitions

href

Name	Type	Description
href	string	

_links

owner

Owner name and UUID that uniquely identifies the role.

Name	Type	Description
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

role_privilege

A tuple containing the REST endpoint and the access level assigned to that endpoint.

Name	Type	Description
access	string	Access level for the REST endpoint.
path	string	REST URI/endpoint

role

A named set of privileges that defines the rights an account has when it is assigned the role.

Name	Type	Description
builtin	boolean	Indicates if this is a built-in (pre-defined) role which cannot be modified or deleted.
name	string	Role name
owner	owner	Owner name and UUID that uniquely identifies the role.
privileges	array[role_privilege]	The list of privileges that this role has been granted.

Name	Type	Description
scope	string	Scope of the entity. Set to "cluster" for cluster owned objects and to "svm" for SVM owned objects.

error_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[error_arguments]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

Copyright information

Copyright © 2025 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—with prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.