



# NAS

## ONTAP 9.8 REST API reference

NetApp  
April 02, 2024

# Table of Contents

- NAS ..... 1
  - NAS overview ..... 1
  - Private protocols audit audit-log-redirect ..... 1
  - Manage NAS audit configurations ..... 18
  - Manage home directory search paths ..... 67
  - Manage CIFS services ..... 88
  - View CIFS active sessions ..... 176
  - Manage CIFS shares ..... 196
  - Manage share-level ACL ..... 245
  - Manage CIFS UNIX symlink mapping ..... 269
  - Retrieve trace results for denied or allowed events ..... 300
  - Delete trace results ..... 310
  - Retrieve trace results ..... 312
  - Retrieve security trace filter entry information ..... 319
  - Create security trace filter entries ..... 326
  - Update security trace filter entries ..... 333
  - Retrieve security trace filter entry information ..... 339
  - Update security trace filter entries ..... 343
  - View file security permissions ..... 348

# NAS

## NAS overview

### Overview

These APIs allow you to complete various tasks, including:

- Creating an NFS server for an SVM
- Managing an NFS configuration of an SVM
- Viewing and updating the NFS configuration of an SVM
- Configuring export policies and rules for an SVM
- Managing export policies and rules for an SVM

### APIs

#### NFS

The NFS APIs enable you to create and configure NFS settings for an SVM. You can delete or update NFS configurations, and you can also disable or enable different NFS features as needed.

#### Exports

The export APIs allow you to create and manage export policies for an SVM that enable an administrator to restrict access to volumes for clients that match specific IP addresses and specific authentication types. Export APIs are also used to create export rules for an export policy. The APIs allow each rule to specify the number of mask bits in the client IP address that must be matched for that rule to apply to a particular client request. The APIs also allow each export rule to specify the authentication types that are required for both read-only and read-write operations.

#### Kerberos

Kerberos is a protocol designed to provide strong authentication for users and hosts within a client/server environment. The basis of the protocol is a shared, secret-key cryptology system. (Kerberos uses shared-key encryption to ensure the confidentiality of the data. It also uses hashing techniques to ensure the integrity of the data (so that no one can modify the data unless allowed to do so). With the NetApp multiprotocol storage platform, through which clients based on UNIX or Windows can access data using CIFS or NFS, it is crucial to provide the ability to use standard network services for authentication and for identity storage.

To configure an ONTAP system to use Kerberos for NFS, Kerberos must be enabled on a data LIF in the SVM that owns the NFS server. A Kerberos realm needs to be created before enabling Kerberos on a data LIF. (The Kerberos realm is needed so that the cluster knows how to format Kerberos ticket requests.) The Kerberos APIs allow you to define, create, modify, and delete realms for the SVM. The APIs also allow you to enable/disable Kerberos on a data LIF and update the Kerberos interface configuration for a particular data LIF in the SVM.

## Private protocols audit audit-log-redirect

## Private protocols audit audit-log-redirect endpoint overview

### Overview

Use this API to specify a dedicated SVM for all NAS auditing events log to reside in.

### Examples

---

#### Creating an Audit Log Redirect configuration.

To create an Audit Log Redirect configuration.

---

```
# The API:
POST /api/private/protocols/audit/audit-log-redirect/

# The call:
curl -X POST "https://<mgmt-ip>/api/private/protocols/audit/audit-log-redirect?return_timeout=5&return_records=false" -H "accept: application/json" -H "authorization: Basic YWRtaW46bmV0YXBwMSE=" -H "Content-Type: application/json" -d "{ \"svm\": { \"uuid\": \"02c9e252-41be-11e9-81d5-00a0986138f7\" } }"

# The response:
{ }
```

#### Retrieving an Audit Log Redirect configuration in the cluster.

To retrieve an Audit Log Redirect configuration.

---

```
# The API:
GET /api/private/protocols/audit/audit-log-redirect/

# The call:
curl -X GET "https://<mgmt-ip>/api/private/protocols/audit/audit-log-redirect?return_records=true" -H "accept: application/json" -H "authorization: Basic YWRtaW46bmV0YXBwMSE="

# The response:
{
  "svm": {
    "uuid": "24870c49-8a73-11ea-ad05-005056827898",
    "name": "vs2"
  }
}
```

---

#### Updating Audit Log Redirect configuration in the cluster.

To modify an existing Audit Log Redirect configuration.

```
# The API:
PATCH /api/private/protocols/audit/audit-log-redirect/

# The call:
curl -X PATCH "https://<mgmt-ip>/api/private/protocols/audit/audit-log-redirect?return_records=true" -H "accept: application/json" -H "authorization: Basic YWRtaW46bmV0YXBwMSE=" -H "Content-Type: application/json" -d "{ \"svm\": { \"name\": \"svm1\", \"uuid\": \"02c9e252-41be-11e9-81d5-00a0986138f7\" } }"
```

---

#### Deleting an Audit Log Redirect configuration in the cluster.

To delete an existing Audit Log Redirect configuration.

```
# The API:
DELETE /api/private/protocols/audit/audit-log-redirect/

# The call:
curl -X DELETE "https://<mgmt-ip>/api/private/protocols/audit/audit-log-redirect" -H "accept: application/json" -H "authorization: Basic YWRtaW46bmV0YXBwMSE="
```

## Deletes an audit log redirect configuration

### related ontap commands

- `vserver audit audit-log-redirect delete` [# learn more](#)
- `[doc /private/protocols/audit/audit-log-redirect](#docs-nas-private_protocols_audit_audit-log-redirect)`

```
DELETE /private/protocols/audit/audit-log-redirect
```

### Introduced In: 9.8

Deletes an Audit Log Redirect configuration.

### Related ONTAP commands

- `vserver audit audit-log-redirect delete`

### Learn more

- [DOC /private/protocols/audit/audit-log-redirect](#)

### Response

```
Status: 200, Ok
```

### Error

```
Status: Default
```

### ONTAP Error Response Codes

Error Code	Description
9699482	Failed to delete Audit Log Redirect configuration.
9699484	Failed to delete Audit Log Redirect configuration because all SVMs audit configuration must be deleted first.

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

#### See Definitions

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieves audit log redirect configuration

### related ontap commands

- `vserver audit audit-log-redirect show` [# learn more](#)
- [\[doc /private/protocols/audit/audit-log-redirect\]\(#docs-nas-private\\_protocols\\_audit\\_audit-log-redirect\)](#)

GET /private/protocols/audit/audit-log-redirect

### Introduced In: 9.8

Retrieves Audit Log Redirect configuration.

### Related ONTAP commands

- `vserver audit audit-log-redirect show`

### Learn more

- [DOC /private/protocols/audit/audit-log-redirect](#)

### Response

Status: 200, Ok

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
<a href="#">svm</a>	<a href="#">svm</a>	



## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

### See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Updates an audit log redirect configuration

### required properties

- `svmuuid` or `svmname` - existing svm to which nas audit events logs will be redirected to <#> related ontap commands
- `vserver audit audit-log-redirect modify` <#> learn more
- `[doc /private/protocols/audit/audit-log-redirect](#docs-nas-private_protocols_audit_audit-log-redirect)`

PATCH `/private/protocols/audit/audit-log-redirect`

### Introduced In: 9.8

Updates an Audit Log Redirect configuration.

### Required properties

- `svm.uuid` or `svm.name` - Existing SVM to which NAS audit events logs will be redirected to.

### Related ONTAP commands

- `vserver audit audit-log-redirect modify`

### Learn more

- [DOC /private/protocols/audit/audit-log-redirect](#)

### Parameters

Name	Type	In	Required	Description
<code>return_records</code>	boolean	query	False	The default is false. If set to true, the records are returned.  • Default value:

### Request Body

Name	Type	Description
<code>_links</code>	<a href="#">_links</a>	
<code>svm</code>	<a href="#">svm</a>	

## Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

## Response

Status: 200, Ok

## Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
9699478	Audit Log Redirect configuration already exists.
9699480	Failed to modify Audit Log Redirect configuration.
9699481	Failed to modify Audit Log Redirect configuration because it does not exist.
9699483	Audit Log Redirect configuration not available.
9699484	Failed to modify Audit Log Redirect configuration because all SVMs audit configuration must be deleted first.
9699486	Audit Log Redirect feature is not available in maintenance mode.

Error Code	Description
9699487	Node is not part of a cluster.
9699488	SVM does not exist.
9699489	Audit Log Redirect configuration only supported on Data SVM.

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

audit\_log\_redirect

Name	Type	Description
_links	<a href="#">_links</a>	
svm	<a href="#">svm</a>	

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message

Name	Type	Description
target	string	The target parameter that caused the error.

## Creates an audit log redirect configuration

### required properties

- `svmuuid` or `svmname` - existing svm to which nas audit events logs will be redirected to **#** related ontap commands
- `vserver audit audit-log-redirect create #` [learn more](#)
- `[doc /private/protocols/audit/audit-log-redirect](#docs-nas-private_protocols_audit_audit-log-redirect)`

POST /private/protocols/audit/audit-log-redirect

**Introduced In:** 9.8

Creates an Audit Log Redirect configuration.

### Required properties

- `svm.uuid` or `svm.name` - Existing SVM to which NAS audit events logs will be redirected to.

### Related ONTAP commands

- `vserver audit audit-log-redirect create`

### Learn more

- [DOC /private/protocols/audit/audit-log-redirect](#)

### Parameters

Name	Type	In	Required	Description
return_records	boolean	query	False	The default is false. If set to true, the records are returned.  • Default value:

### Request Body

Name	Type	Description
_links	<a href="#">_links</a>	

Name	Type	Description
svm	svm	

### Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

### Response

Status: 201, Created

Name	Type	Description
_links	_links	
svm	svm	



## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

## Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
9699478	Audit Log Redirect configuration already exists.
9699479	Failed to create Audit Log Redirect configuration.
9699483	Audit Log Redirect configuration not available.
9699484	Failed to modify Audit Log Redirect configuration because all SVMs audit configuration must be deleted first.
9699486	Audit Log Redirect feature is not available in maintenance mode.
9699487	Node is not part of a cluster.
9699488	SVM does not exist.
9699489	Audit Log Redirect configuration only supported on Data SVM.

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

audit\_log\_redirect

Name	Type	Description
_links	<a href="#">_links</a>	
svm	<a href="#">svm</a>	

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message

Name	Type	Description
target	string	The target parameter that caused the error.

## Manage NAS audit configurations

### Protocols audit endpoint overview

#### Overview

Auditing for NAS events is a security measure that enables you to track and log certain CIFS and NFS events on storage virtual machines (SVMs). This helps you track potential security problems and provides evidence of any security breaches.

#### Examples

##### Creating an audit entry with log rotation size and log retention count

To create an audit entry with log rotation size and log retention count, use the following API. Note the *return\_records=true* query parameter is used to obtain the newly created entry in the response.

```
# The API:
POST /api/protocols/audit/

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/audit" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"enabled\":
true, \"events\": { \"authorization_policy\": false, \"cap_staging\":
false, \"cifs_logon_logoff\": true, \"file_operations\": true,
\"file_share\": false, \"security_group\": false, \"user_account\": false
}, \"log\": { \"format\": \"evtX\", \"retention\": { \"count\": 10 },
\"rotation\": { \"size\": 2048000 }}, \"log_path\": \"/\", \"svm\": {
\"name\": \"vs1\", \"uuid\": \"ec650e97-156e-11e9-abcb-005056bbd0bf\" }}"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "ec650e97-156e-11e9-abcb-005056bbd0bf",
        "name": "vs1"
      }
    },
  ],
}
```

```

    "enabled": true,
    "events": {
      "authorization_policy": false,
      "cap_staging": false,
      "cifs_logon_logoff": true,
      "file_operations": true,
      "file_share": false,
      "security_group": false,
      "user_account": false
    },
    "log": {
      "format": "evtx",
      "rotation": {
        "size": 2048000
      },
      "retention": {
        "count": 10,
        "duration": "0s"
      }
    },
    "log_path": "/"
  }
],
"num_records": 1
}

```

### Creating an audit entry with log rotation schedule and log retention duration

To create an audit entry with log rotation schedule and log retention duration, use the following API. Note that the *return\_records=true* query parameter is used to obtain the newly created entry in the response.

```

# The API:
POST /api/protocols/audit/

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/audit" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"enabled\":
false, \"events\": { \"authorization_policy\": false, \"cap_staging\":
false, \"cifs_logon_logoff\": true, \"file_operations\": true,
\"file_share\": false, \"security_group\": false, \"user_account\": false
}, \"log\": { \"format\": \"xml\", \"retention\": { \"duration\":
\"P4DT12H30M5S\" }, \"rotation\": { \"schedule\": { \"days\": [1, 5, 10,
15], \"hours\": [0, 1, 6, 12, 18, 23], \"minutes\": [10, 15, 30, 45, 59],

```

```
\\"months\\": [0], \\"weekdays\\": [0, 2, 5] } } }, \\"log_path\\": \"/\\",  
\\"svm\\": { \\"name\\": \\"vs3\\", \\"uuid\\": \\"a8d64674-13fc-11e9-87b1-  
005056a7ae7e\\" } }"
```

# The response:

```
{  
  "records": [  
    {  
      "svm": {  
        "uuid": "a8d64674-13fc-11e9-87b1-005056a7ae7e",  
        "name": "vs3"  
      },  
      "enabled": true,  
      "events": {  
        "authorization_policy": false,  
        "cap_staging": false,  
        "cifs_logon_logoff": true,  
        "file_operations": true,  
        "file_share": false,  
        "security_group": false,  
        "user_account": false  
      },  
      "log": {  
        "format": "xml",  
        "rotation": {  
          "schedule": {  
            "minutes": [  
              10,  
              15,  
              30,  
              45,  
              59  
            ],  
            "hours": [  
              0,  
              1,  
              6,  
              12,  
              18,  
              23  
            ],  
            "weekdays": [  
              0,  
              2,  
              5  
            ],  
          }  
        }  
      }  
    ]  
  }  
}
```

```

        "days": [
            1,
            5,
            10,
            15
        ],
        "months": [
            0
        ]
    },
    "retention": {
        "count": 0,
        "duration": "P4DT12H30M5S"
    }
},
"log_path": "/"
}
],
"num_records": 1
}

```

---

### Retrieving an audit configuration for all SVMs in the cluster

---

```

# The API:
GET /api/protocols/audit/

# The call:
curl -X GET "https://<mgmt-
ip>/api/protocols/audit?fields=*&return_records=true&return_timeout=15" -H
"accept: application/json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "ec650e97-156e-11e9-abcb-005056bbd0bf",
        "name": "vs1"
      },
      "enabled": true,
      "events": {

```

```

    "authorization_policy": false,
    "cap_staging": false,
    "cifs_logon_logoff": true,
    "file_operations": true,
    "file_share": false,
    "security_group": false,
    "user_account": false
  },
  "log": {
    "format": "evtx",
    "rotation": {
      "size": 2048000
    },
    "retention": {
      "count": 10,
      "duration": "0s"
    }
  },
  "log_path": "/"
},
{
  "svm": {
    "uuid": "a8d64674-13fc-11e9-87b1-005056a7ae7e",
    "name": "vs3"
  },
  "enabled": true,
  "events": {
    "authorization_policy": false,
    "cap_staging": false,
    "cifs_logon_logoff": true,
    "file_operations": true,
    "file_share": false,
    "security_group": false,
    "user_account": false
  },
  "log": {
    "format": "xml",
    "rotation": {
      "schedule": {
        "minutes": [
          10,
          15,
          30,
          45,
          59
        ]
      }
    }
  },

```



```
    "hours": [
      0,
      1,
      6,
      12,
      18,
      23
    ],
    "weekdays": [
      0,
      2,
      5
    ],
    "days": [
      1,
      5,
      10,
      15
    ],
    "months": [
      0
    ]
  }
},
"retention": {
  "count": 0,
  "duration": "P4DT12H30M5S"
}
},
"log_path": "/"
}
],
"num_records": 2
}
```

---

#### Retrieving specific entries with event list as cifs-logon-logoff, file-ops = true for an SVM

The configuration returned is identified by the events in the list of audit configurations for an SVM.

---

```
# The API:
GET /api/protocols/audit/

# The call:
curl -X GET "https://<mgmt-
ip>/api/protocols/audit?events.file_operations=true&events.cifs_logon_logoff=true&return_records=true&return_timeout=15" -H "accept:
application/json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "ec650e97-156e-11e9-abcb-005056bbd0bf",
        "name": "vs1"
      },
      "events": {
        "cifs_logon_logoff": true,
        "file_operations": true
      }
    },
    {
      "svm": {
        "uuid": "a8d64674-13fc-11e9-87b1-005056a7ae7e",
        "name": "vs3"
      },
      "events": {
        "cifs_logon_logoff": true,
        "file_operations": true
      }
    }
  ],
  "num_records": 2
}
```

---

### Retrieving a specific audit configuration for an SVM

The configuration returned is identified by the UUID of its SVM.

---

```
# The API:
GET /api/protocols/audit/{svm.uuid}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/audit/ec650e97-156e-11e9-
abcb-005056bbd0bf" -H "accept: application/json"

# The response:
{
  "svm": {
    "uuid": "ec650e97-156e-11e9-abcb-005056bbd0bf",
    "name": "vs1"
  },
  "enabled": true,
  "events": {
    "authorization_policy": false,
    "cap_staging": false,
    "cifs_logon_logoff": true,
    "file_operations": true,
    "file_share" : false,
    "security_group": false,
    "user_account": false
  },
  "log": {
    "format": "evtx",
    "rotation": {
      "size": 2048000
    },
    "retention": {
      "count": 10,
      "duration": "0s"
    }
  },
  "log_path": "/"
}
```

---

### Updating a specific audit configuration of an SVM

The configuration is identified by the UUID of its SVM and the provided information is updated.

---

```
# The API:
PATCH /api/protocols/audit/{svm.uuid}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/audit/ec650e97-156e-11e9-
abcb-005056bbd0bf" -H "accept: application/json" -H "Content-Type:
application/json" -d "{\"enabled\": false}"
```

### Deleting a specific audit configuration for an SVM

The entry to be deleted is identified by the UUID of its SVM.

```
# The API:
DELETE /api/protocols/audit/{svm.uuid}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/audit/ec650e97-156e-11e9-
abcb-005056bbd0bf" -H "accept: application/json"
```

## Retrieve audit configurations

GET /protocols/audit

**Introduced In:** 9.6

Retrieves audit configurations.

### Related ONTAP commands

- `vserver audit show`

### Learn more

- [DOC /protocols/audit](#)

### Parameters

Name	Type	In	Required	Description
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name

Name	Type	In	Required	Description
events.file_operations	boolean	query	False	Filter by events.file_operations
events.security_group	boolean	query	False	Filter by events.security_group
events.cifs_logon_logoff	boolean	query	False	Filter by events.cifs_logon_logoff
events.authorization_policy	boolean	query	False	Filter by events.authorization_policy
events.user_account	boolean	query	False	Filter by events.user_account
events.file_share	boolean	query	False	Filter by events.file_share
events.cap_staging	boolean	query	False	Filter by events.cap_staging
log_path	string	query	False	Filter by log_path
log.retention.duration	string	query	False	Filter by log.retention.duration
log.retention.count	integer	query	False	Filter by log.retention.count
log.format	string	query	False	Filter by log.format
log.rotation.schedule.months	integer	query	False	Filter by log.rotation.schedule.months
log.rotation.schedule.days	integer	query	False	Filter by log.rotation.schedule.days

Name	Type	In	Required	Description
log.rotation.schedule.minutes	integer	query	False	Filter by log.rotation.schedule.minutes
log.rotation.schedule.hours	integer	query	False	Filter by log.rotation.schedule.hours
log.rotation.schedule.weekdays	integer	query	False	Filter by log.rotation.schedule.weekdays
log.rotation.size	integer	query	False	Filter by log.rotation.size
enabled	boolean	query	False	Filter by enabled
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	<p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">audit</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "log": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "format": "xml",
      "retention": {
        "duration": "P4DT12H30M5S"
      },
      "rotation": {
        "schedule": {
          "days": {
          },
          "hours": {
          },
          "minutes": {
          },
          "months": {
          },
          "weekdays": {
          }
        }
      }
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  }
}
```



```
}  
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

events

Name	Type	Description
authorization_policy	boolean	Authorization policy change events
cap_staging	boolean	Central access policy staging events
cifs_logon_logoff	boolean	CIFS logon and logoff events
file_operations	boolean	File operation events
file_share	boolean	File share category events
security_group	boolean	Local security group management events
user_account	boolean	Local user account management events

\_links

Name	Type	Description
self	<a href="#">href</a>	

retention

Name	Type	Description
count	integer	Determines how many audit log files to retain before rotating the oldest log file out. This is mutually exclusive with duration.
duration	string	Specifies an ISO-8601 format date and time to retain the audit log file. The audit log files are deleted once they reach the specified date/time. This is mutually exclusive with count.

#### audit\_schedule

Rotates the audit logs based on a schedule by using the time-based rotation parameters in any combination. The rotation schedule is calculated by using all the time-related values.

Name	Type	Description
days	array[integer]	Specifies the day of the month schedule to rotate audit log. Leave empty for all.
hours	array[integer]	Specifies the hourly schedule to rotate audit log. Leave empty for all.
minutes	array[integer]	Specifies the minutes schedule to rotate the audit log.
months	array[integer]	Specifies the months schedule to rotate audit log. Leave empty for all.
weekdays	array[integer]	Specifies the weekdays schedule to rotate audit log. Leave empty for all.

#### rotation

Audit event log files are rotated when they reach a configured threshold log size or are on a configured schedule. When an event log file is rotated, the scheduled consolidation task first renames the active converted file to a time-stamped archive file, and then creates a new active converted event log file.

Name	Type	Description
now	boolean	Manually rotates the audit logs. Optional in PATCH only. Not available in POST.
schedule	<a href="#">audit_schedule</a>	Rotates the audit logs based on a schedule by using the time-based rotation parameters in any combination. The rotation schedule is calculated by using all the time-related values.
size	integer	Rotates logs based on log size in bytes.

#### log

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
format	string	<p>The format in which the logs are generated by consolidation process. Possible values are:</p> <ul style="list-style-type: none"> <li>• xml - Data ONTAP-specific XML log format</li> <li>• evtX - Microsoft Windows EVT X log format <ul style="list-style-type: none"> <li>◦ Default value: 1</li> <li>◦ enum: ["xml", "evtX"]</li> <li>◦ Introduced in: 9.6</li> </ul> </li> </ul>
retention	<a href="#">retention</a>	
rotation	<a href="#">rotation</a>	Audit event log files are rotated when they reach a configured threshold log size or are on a configured schedule. When an event log file is rotated, the scheduled consolidation task first renames the active converted file to a time-stamped archive file, and then creates a new active converted event log file.

#### svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

#### audit

Auditing for NAS events is a security measure that enables you to track and log certain CIFS and NFS events on SVMs.

Name	Type	Description
enabled	boolean	Specifies whether or not auditing is enabled on the SVM.
events	<a href="#">events</a>	
log	<a href="#">log</a>	
log_path	string	The audit log destination path where consolidated audit logs are stored.
svm	<a href="#">svm</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Create an audit configuration

POST /protocols/audit

**Introduced In:** 9.6

Creates an audit configuration.

### Required properties

- `svm.uuid` or `svm.name` - Existing SVM to which audit configuration is to be created.
- `log_path` - Path in the owning SVM namespace that is used to store audit logs.

### Default property values

If not specified in POST, the following default property values are assigned:

- `enabled` - *true*
- `events.authorization_policy` - *false*
- `events.cap_staging` - *false*
- `events.file_share` - *false*
- `events.security_group` - *false*
- `events.user_account` - *false*
- `events.cifs_logon_logoff` - *true*
- `events.file_operations` - *true*
- `log.format` - *evtx*
- `log.retention.count` - *0*
- `log.retention.duration` - *PT0S*
- `log.rotation.size` - *100MB*
- `log.rotation.now` - *false*

### Related ONTAP commands

- `vserver audit create`
- `vserver audit enable`

### Learn more

- [DOC /protocols/audit](#)

### Parameters

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
return_records	boolean	query	False	<p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> <li>• Default value:</li> </ul>

### Request Body

Name	Type	Description
enabled	boolean	Specifies whether or not auditing is enabled on the SVM.
events	<a href="#">events</a>	
log	<a href="#">log</a>	

Name	Type	Description
log_path	string	The audit log destination path where consolidated audit logs are stored.
svm	svm	



## Example request

```
{
  "log": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "format": "xml",
    "retention": {
      "duration": "P4DT12H30M5S"
    },
    "rotation": {
      "schedule": {
        "days": {
        },
        "hours": {
        },
        "minutes": {
        },
        "months": {
        },
        "weekdays": {
        }
      }
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

## Response

Status: 202, Accepted

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">audit</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "log": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "format": "xml",
      "retention": {
        "duration": "P4DT12H30M5S"
      },
      "rotation": {
        "schedule": {
          "days": {
          },
          "hours": {
          },
          "minutes": {
          },
          "months": {
          },
          "weekdays": {
          }
        }
      }
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  }
}
```

```
}  
}
```

## Error

Status: Default

### ONTAP Error Response Codes

Error Code	Description
262196	Log_rotation_now is not an allowed operation
2621462	The specified SVM does not exist
9699330	An audit configuration already exists
9699337	Audit system internal update is in progress, audit configuration create failed
9699340	SVM UUID lookup failed
9699358	Audit configuration is absent for enabling
9699359	Audit configuration is already enabled
9699360	Final consolidation is in progress, audit enable failed
9699365	Enabling of audit configuration failed
9699370	Auditing was successfully configured, however audit configuration could not be enabled
9699384	The specified log_path does not exist
9699385	The log_path must be a directory
9699386	The log_path must be a canonical path in the SVMs namespace
9699387	The log_path cannot be empty
9699388	Rotate size must be greater than or equal to 1024 KB
9699389	The log_path must not contain a symbolic link
9699398	The log_path exceeds a maximum supported length of characters
9699399	The log_path contains an unsupported read-only (DP/LS) volume
9699400	The specified log_path is not a valid destination for SVM
9699402	The log_path contains an unsupported snaplock volume
9699403	The log_path cannot be accessed for validation

Error Code	Description
9699406	The log_path validation failed
9699409	Failed to enable multiproto.audit.evtxlog.support support capability
9699428	All nodes need to run ONTAP 8.3.0 release to audit CIFS logon-logoff events
9699429	Failed to enable multiproto.audit.cifslogonlogoff.support support capability
9699431	All nodes need to run ONTAP 8.3.0 release to audit CAP staging events
9699432	Failed to enable multiproto.audit.capstaging.support support capability

Name	Type	Description
error	<a href="#">error</a>	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

### events

Name	Type	Description
authorization_policy	boolean	Authorization policy change events
cap_staging	boolean	Central access policy staging events
cifs_logon_logoff	boolean	CIFS logon and logoff events
file_operations	boolean	File operation events
file_share	boolean	File share category events
security_group	boolean	Local security group management events
user_account	boolean	Local user account management events

### href

Name	Type	Description
href	string	

### \_links

Name	Type	Description
self	<a href="#">href</a>	

### retention

Name	Type	Description
count	integer	Determines how many audit log files to retain before rotating the oldest log file out. This is mutually exclusive with duration.

Name	Type	Description
duration	string	Specifies an ISO-8601 format date and time to retain the audit log file. The audit log files are deleted once they reach the specified date/time. This is mutually exclusive with count.

#### audit\_schedule

Rotates the audit logs based on a schedule by using the time-based rotation parameters in any combination. The rotation schedule is calculated by using all the time-related values.

Name	Type	Description
days	array[integer]	Specifies the day of the month schedule to rotate audit log. Leave empty for all.
hours	array[integer]	Specifies the hourly schedule to rotate audit log. Leave empty for all.
minutes	array[integer]	Specifies the minutes schedule to rotate the audit log.
months	array[integer]	Specifies the months schedule to rotate audit log. Leave empty for all.
weekdays	array[integer]	Specifies the weekdays schedule to rotate audit log. Leave empty for all.

#### rotation

Audit event log files are rotated when they reach a configured threshold log size or are on a configured schedule. When an event log file is rotated, the scheduled consolidation task first renames the active converted file to a time-stamped archive file, and then creates a new active converted event log file.

Name	Type	Description
now	boolean	Manually rotates the audit logs. Optional in PATCH only. Not available in POST.

Name	Type	Description
schedule	<a href="#">audit_schedule</a>	Rotates the audit logs based on a schedule by using the time-based rotation parameters in any combination. The rotation schedule is calculated by using all the time-related values.
size	integer	Rotates logs based on log size in bytes.

#### log

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
format	string	The format in which the logs are generated by consolidation process. Possible values are: <ul style="list-style-type: none"> <li>• xml - Data ONTAP-specific XML log format</li> <li>• evtX - Microsoft Windows EVT X log format <ul style="list-style-type: none"> <li>◦ Default value: 1</li> <li>◦ enum: ["xml", "evtX"]</li> <li>◦ Introduced in: 9.6</li> </ul> </li> </ul>
retention	<a href="#">retention</a>	
rotation	<a href="#">rotation</a>	Audit event log files are rotated when they reach a configured threshold log size or are on a configured schedule. When an event log file is rotated, the scheduled consolidation task first renames the active converted file to a time-stamped archive file, and then creates a new active converted event log file.

#### svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.



Name	Type	Description
uuid	string	The unique identifier of the SVM.

#### audit

Auditing for NAS events is a security measure that enables you to track and log certain CIFS and NFS events on SVMs.

Name	Type	Description
enabled	boolean	Specifies whether or not auditing is enabled on the SVM.
events	<a href="#">events</a>	
log	<a href="#">log</a>	
log_path	string	The audit log destination path where consolidated audit logs are stored.
svm	<a href="#">svm</a>	

#### \_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message

Name	Type	Description
target	string	The target parameter that caused the error.

## Delete an audit configuration

```
DELETE /protocols/audit/{svm.uuid}
```

**Introduced In:** 9.6

Deletes an audit configuration.

### Related ONTAP commands

- `vserver audit disable`
- `vserver audit delete`

### Learn more

- [DOC /protocols/audit](#)

### Parameters

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
svm.uuid	string	path	True	<p>UUID of the SVM to which this object belongs.</p>

## Response

```
Status: 202, Accepted
```

## Error

```
Status: Default
```

## ONTAP Error Response Codes

Error Code	Description
9699349	Auditing should be disabled before deleting the audit configuration
9699350	Audit configuration cannot be deleted, final consolidation is in progress
9699410	Failed to disable multiproto.audit.evtxlog.support support capability
9699430	Failed to disable multiproto.audit.cifslogonlogoff.support support capability
9699433	Failed to disable multiproto.audit.capstaging.support support capability

Name	Type	Description
error	error	

### Example error

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

### Definitions

## See Definitions

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve an audit configuration for an SVM

```
GET /protocols/audit/{svm.uuid}
```

**Introduced In:** 9.6

Retrieves an audit configuration for an SVM.

### Related ONTAP commands

- `vserver audit show`

### Learn more

- [DOC /protocols/audit](#)

### Parameters

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

Name	Type	In	Required	Description
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
enabled	boolean	Specifies whether or not auditing is enabled on the SVM.
events	<a href="#">events</a>	
log	<a href="#">log</a>	
log_path	string	The audit log destination path where consolidated audit logs are stored.
svm	<a href="#">svm</a>	

## Example response

```
{
  "log": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "format": "xml",
    "retention": {
      "duration": "P4DT12H30M5S"
    },
    "rotation": {
      "schedule": {
        "days": {
        },
        "hours": {
        },
        "minutes": {
        },
        "months": {
        },
        "weekdays": {
        }
      }
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions



## See Definitions

### events

Name	Type	Description
authorization_policy	boolean	Authorization policy change events
cap_staging	boolean	Central access policy staging events
cifs_logon_logoff	boolean	CIFS logon and logoff events
file_operations	boolean	File operation events
file_share	boolean	File share category events
security_group	boolean	Local security group management events
user_account	boolean	Local user account management events

### href

Name	Type	Description
href	string	

### \_links

Name	Type	Description
self	<a href="#">href</a>	

### retention

Name	Type	Description
count	integer	Determines how many audit log files to retain before rotating the oldest log file out. This is mutually exclusive with duration.

Name	Type	Description
duration	string	Specifies an ISO-8601 format date and time to retain the audit log file. The audit log files are deleted once they reach the specified date/time. This is mutually exclusive with count.

#### audit\_schedule

Rotates the audit logs based on a schedule by using the time-based rotation parameters in any combination. The rotation schedule is calculated by using all the time-related values.

Name	Type	Description
days	array[integer]	Specifies the day of the month schedule to rotate audit log. Leave empty for all.
hours	array[integer]	Specifies the hourly schedule to rotate audit log. Leave empty for all.
minutes	array[integer]	Specifies the minutes schedule to rotate the audit log.
months	array[integer]	Specifies the months schedule to rotate audit log. Leave empty for all.
weekdays	array[integer]	Specifies the weekdays schedule to rotate audit log. Leave empty for all.

#### rotation

Audit event log files are rotated when they reach a configured threshold log size or are on a configured schedule. When an event log file is rotated, the scheduled consolidation task first renames the active converted file to a time-stamped archive file, and then creates a new active converted event log file.

Name	Type	Description
now	boolean	Manually rotates the audit logs. Optional in PATCH only. Not available in POST.

Name	Type	Description
schedule	<a href="#">audit_schedule</a>	Rotates the audit logs based on a schedule by using the time-based rotation parameters in any combination. The rotation schedule is calculated by using all the time-related values.
size	integer	Rotates logs based on log size in bytes.

#### log

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
format	string	<p>The format in which the logs are generated by consolidation process. Possible values are:</p> <ul style="list-style-type: none"> <li>• xml - Data ONTAP-specific XML log format</li> <li>• evtX - Microsoft Windows EVT X log format <ul style="list-style-type: none"> <li>◦ Default value: 1</li> <li>◦ enum: ["xml", "evtX"]</li> <li>◦ Introduced in: 9.6</li> </ul> </li> </ul>
retention	<a href="#">retention</a>	
rotation	<a href="#">rotation</a>	Audit event log files are rotated when they reach a configured threshold log size or are on a configured schedule. When an event log file is rotated, the scheduled consolidation task first renames the active converted file to a time-stamped archive file, and then creates a new active converted event log file.

#### svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.

Name	Type	Description
uuid	string	The unique identifier of the SVM.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Update an audit configuration for an SVM

```
PATCH /protocols/audit/{svm.uuid}
```

**Introduced In:** 9.6

Updates an audit configuration for an SVM.

### Related ONTAP commands

- `vserver audit modify`

### Learn more

- [DOC /protocols/audit](#)

### Parameters

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

### Request Body

Name	Type	Description
enabled	boolean	Specifies whether or not auditing is enabled on the SVM.
events	<a href="#">events</a>	
log	<a href="#">log</a>	

Name	Type	Description
log_path	string	The audit log destination path where consolidated audit logs are stored.
svm	svm	

## Example request

```
{
  "log": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "format": "xml",
    "retention": {
      "duration": "P4DT12H30M5S"
    },
    "rotation": {
      "schedule": {
        "days": {
        },
        "hours": {
        },
        "minutes": {
        },
        "months": {
        },
        "weekdays": {
        }
      }
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

## Response

Status: 202, Accepted

## Error

Status: Default

### ONTAP Error Response Codes

Error Code	Description
9699340	SVM UUID lookup failed
9699343	Audit configuration is absent for modification
9699358	Audit configuration is absent for enabling
9699359	Audit configuration is already enabled
9699360	Final consolidation is in progress, audit enable failed
9699365	Enabling of audit configuration failed
9699373	Audit configuration is absent for disabling
9699374	Audit configuration is already disabled
9699375	Disabling of audit configuration failed
9699384	The specified log_path does not exist
9699385	The log_path must be a directory
9699386	The log_path must be a canonical path in the SVMs namespace
9699387	The log_path cannot be empty
9699388	Rotate size must be greater than or equal to 1024 KB
9699389	The log_path must not contain a symbolic link
9699398	The log_path exceeds a maximum supported length of characters
9699399	The log_path contains an unsupported read-only (DP/LS) volume
9699400	The specified log_path is not a valid destination for SVM
9699402	The log_path contains an unsupported snaplock volume
9699403	The log_path cannot be accessed for validation
9699406	The log_path validation failed
9699407	Additional fields are provided
9699409	Failed to enable multiproto.audit.evtxlog.support support capability
9699410	Failed to disable multiproto.audit.evtxlog.support support capability



Error Code	Description
9699418	Audit configuration is absent for rotate
9699419	Failed to rotate audit log
9699420	Cannot rotate audit log, auditing is not enabled for this SVM
9699428	All nodes need to run ONTAP 8.3.0 release to audit CIFS logon-logoff events
9699429	Failed to enable multiproto.audit.cifslogonlogoff.support support capability
9699430	Failed to disable multiproto.audit.cifslogonlogoff.support support capability
9699431	All nodes need to run ONTAP 8.3.0 release to audit CAP staging events
9699432	Failed to enable multiproto.audit.capstaging.support support capability
9699433	Failed to disable multiproto.audit.capstaging.support support capability

Name	Type	Description
error	error	

### Example error

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

### Definitions

## See Definitions

### events

Name	Type	Description
authorization_policy	boolean	Authorization policy change events
cap_staging	boolean	Central access policy staging events
cifs_logon_logoff	boolean	CIFS logon and logoff events
file_operations	boolean	File operation events
file_share	boolean	File share category events
security_group	boolean	Local security group management events
user_account	boolean	Local user account management events

### href

Name	Type	Description
href	string	

### \_links

Name	Type	Description
self	<a href="#">href</a>	

### retention

Name	Type	Description
count	integer	Determines how many audit log files to retain before rotating the oldest log file out. This is mutually exclusive with duration.

Name	Type	Description
duration	string	Specifies an ISO-8601 format date and time to retain the audit log file. The audit log files are deleted once they reach the specified date/time. This is mutually exclusive with count.

#### audit\_schedule

Rotates the audit logs based on a schedule by using the time-based rotation parameters in any combination. The rotation schedule is calculated by using all the time-related values.

Name	Type	Description
days	array[integer]	Specifies the day of the month schedule to rotate audit log. Leave empty for all.
hours	array[integer]	Specifies the hourly schedule to rotate audit log. Leave empty for all.
minutes	array[integer]	Specifies the minutes schedule to rotate the audit log.
months	array[integer]	Specifies the months schedule to rotate audit log. Leave empty for all.
weekdays	array[integer]	Specifies the weekdays schedule to rotate audit log. Leave empty for all.

#### rotation

Audit event log files are rotated when they reach a configured threshold log size or are on a configured schedule. When an event log file is rotated, the scheduled consolidation task first renames the active converted file to a time-stamped archive file, and then creates a new active converted event log file.

Name	Type	Description
now	boolean	Manually rotates the audit logs. Optional in PATCH only. Not available in POST.

Name	Type	Description
schedule	<a href="#">audit_schedule</a>	Rotates the audit logs based on a schedule by using the time-based rotation parameters in any combination. The rotation schedule is calculated by using all the time-related values.
size	integer	Rotates logs based on log size in bytes.

#### log

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
format	string	<p>The format in which the logs are generated by consolidation process. Possible values are:</p> <ul style="list-style-type: none"> <li>• xml - Data ONTAP-specific XML log format</li> <li>• evtX - Microsoft Windows EVT X log format <ul style="list-style-type: none"> <li>◦ Default value: 1</li> <li>◦ enum: ["xml", "evtX"]</li> <li>◦ Introduced in: 9.6</li> </ul> </li> </ul>
retention	<a href="#">retention</a>	
rotation	<a href="#">rotation</a>	Audit event log files are rotated when they reach a configured threshold log size or are on a configured schedule. When an event log file is rotated, the scheduled consolidation task first renames the active converted file to a time-stamped archive file, and then creates a new active converted event log file.

#### svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.

Name	Type	Description
uuid	string	The unique identifier of the SVM.

#### audit

Auditing for NAS events is a security measure that enables you to track and log certain CIFS and NFS events on SVMs.

Name	Type	Description
enabled	boolean	Specifies whether or not auditing is enabled on the SVM.
events	<a href="#">events</a>	
log	<a href="#">log</a>	
log_path	string	The audit log destination path where consolidated audit logs are stored.
svm	<a href="#">svm</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Manage home directory search paths

## Protocols CIFS home-directory search-paths endpoint overview

### Overview

ONTAP home directory functionality can be used to create home directories for SMB users on the CIFS server and automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user.

The home directory search path is a set of absolute paths from the root of an SVM that directs ONTAP to search for home directories. If there are multiple search paths, ONTAP tries them in the order specified until it finds a valid path. To use the CIFS home directories feature, at least one home directory search path must be added for an SVM.

### Examples

#### Creating a home directory search path

To create a home directory search path, use the following API. Note the *return\_records=true* query parameter used to obtain the newly created entry in the response.

```
# The API:
POST /api/protocols/cifs/home-directory/search-paths

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/cifs/home-directory/search-paths?return_records=true" -H "accept: applicaion/json" -H "Content-Type: application/json" -d "{ \"path\": \"/\", \"svm\": { \"name\": \"vs1\", \"uuid\": \"a41fd873-ecf8-11e8-899d-0050568e9333\" }}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "uuid": "a41fd873-ecf8-11e8-899d-0050568e9333",
        "name": "vs1"
      },
      "path": "/"
    }
  ]
}
```

#### Retrieving the CIFS home directory search paths configuration for all SVMs in the cluster

```
# The API:
```

```
GET /protocols/cifs/home-directory/search-paths
```

```
# The call:
```

```
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/home-directory/search-paths?fields=*&return_records=true&return_timeout=15" -H "accept: application/json"
```

```
# The response:
```

```
{
  "records": [
    {
      "svm": {
        "uuid": "2d96f9aa-f4ce-11e8-b075-0050568e278e",
        "name": "vs1"
      },
      "index": 1,
      "path": "/"
    },
    {
      "svm": {
        "uuid": "2d96f9aa-f4ce-11e8-b075-0050568e278e",
        "name": "vs1"
      },
      "index": 2,
      "path": "/a"
    },
    {
      "svm": {
        "uuid": "4f23449b-f4ce-11e8-b075-0050568e278e",
        "name": "vs2"
      },
      "index": 1,
      "path": "/"
    },
    {
      "svm": {
        "uuid": "4f23449b-f4ce-11e8-b075-0050568e278e",
        "name": "vs2"
      },
      "index": 2,
      "path": "/1"
    }
  ],
  "num_records": 4
}
```

### Retrieving a specific home directory searchpath configuration for an SVM

The configuration returned is identified by the UUID of its SVM and the index (position) in the list of search paths that is searched to find a home directory of a user.

```
# The API:
GET /api/protocols/home-directory/search-paths/{svm.uuid}/{index}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/home-directory/search-paths/2d96f9aa-f4ce-11e8-b075-0050568e278e/2" -H "accept: application/json"

# The response:
{
  "svm": {
    "uuid": "2d96f9aa-f4ce-11e8-b075-0050568e278e",
    "name": "vs1"
  },
  "index": 2,
  "path": "/a"
}
```

### Reordering a specific home directory search path in the list

An entry in the home directory search path list can be reordered to a new position by specifying the 'new\_index' field. The reordered configuration is identified by the UUID of its SVM and the index.

```
# The API:
PATCH /api/protocols/cifs/home-directory/search-paths/{svm.uuid}/{index}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/home-directory/search-paths/2d96f9aa-f4ce-11e8-b075-0050568e278e/2?new_index=1" -H "accept: application/json"
```

### Removing a specific home directory search path for an SVM

The entry being removed is identified by the UUID of its SVM and the index.



```
# The API:
DELETE /api/protocols/cifs/home-directory/search-paths/{svm.uuid}/{index}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/cifs/home-
directory/search-paths/2d96f9aa-f4ce-11e8-b075-0050568e278e/2" -H "accept:
application/json"
```

## Retrieve CIFS home directory search paths

GET /protocols/cifs/home-directory/search-paths

**Introduced In:** 9.6

Retrieves CIFS home directory search paths.

### Related ONTAP commands

- `cifs server home-directory search-path show`

### Learn more

- [DOC /protocols/cifs/home-directory/search-paths](#)

### Parameters

Name	Type	In	Required	Description
index	integer	query	False	Filter by index
path	string	query	False	Filter by path
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.

Name	Type	In	Required	Description
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">cifs_search_path</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "index": 0,
    "path": "/HomeDirectory/EngDomain",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

cifs\_search\_path

This is a list of CIFS home directory search paths. When a CIFS client connects to a home directory share, these paths are searched in the order indicated by the position field to find the home directory of the connected CIFS client.

Name	Type	Description
index	integer	The position in the list of paths that is searched to find the home directory of the CIFS client. Not available in POST.
path	string	The file system path that is searched to find the home directory of the CIFS client.
svm	<a href="#">svm</a>	

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Create a home directory search path

POST `/protocols/cifs/home-directory/search-paths`

**Introduced In:** 9.6

Creates a home directory search path.

### Required properties

- `svm.uuid` or `svm.name` - Existing SVM in which to create the home directory search path.
- `path` - Path in the owning SVM namespace that is used to search for home directories.

### Related ONTAP commands

- `cifs server home-directory search-path add`

### Learn more

- [DOC /protocols/cifs/home-directory/search-paths](#)

### Parameters

Name	Type	In	Required	Description
return_records	boolean	query	False	<p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> <li>• Default value:</li> </ul>

### Request Body

Name	Type	Description
index	integer	The position in the list of paths that is searched to find the home directory of the CIFS client. Not available in POST.
path	string	The file system path that is searched to find the home directory of the CIFS client.
svm	<a href="#">svm</a>	

### Example request

```
{
  "index": 0,
  "path": "/HomeDirectory/EngDomain",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
```

### Response

Status: 201, Created

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">cifs_search_path</a> ]	

### Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "index": 0,
    "path": "/HomeDirectory/EngDomain",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  }
}
```

### Error

Status: Default

### ONTAP Error Response Codes

Error Code	Description
655551	Invalid home-directory search-path path
655462	The specified path is an invalid file-type



Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

cifs\_search\_path

This is a list of CIFS home directory search paths. When a CIFS client connects to a home directory share, these paths are searched in the order indicated by the position field to find the home directory of the connected CIFS client.

Name	Type	Description
index	integer	The position in the list of paths that is searched to find the home directory of the CIFS client. Not available in POST.
path	string	The file system path that is searched to find the home directory of the CIFS client.
svm	<a href="#">svm</a>	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Delete a CIFS home directory search path

```
DELETE /protocols/cifs/home-directory/search-paths/{svm.uuid}/{index}
```

**Introduced In:** 9.6

Deletes a CIFS home directory search path.

### Related ONTAP commands

- `cifs server home-directory search-path remove`

### Learn more

- [DOC /protocols/cifs/home-directory/search-paths](#)

### Parameters

Name	Type	In	Required	Description
index	integer	path	True	Home directory search path index
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Response

Status: 200, Ok

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve a CIFS home directory search path for an SVM

GET /protocols/cifs/home-directory/search-paths/{svm.uuid}/{index}

**Introduced In:** 9.6

Retrieves a CIFS home directory search path of an SVM.

### Related ONTAP commands

- `cifs server home-directory search-path show`

### Learn more

- [DOC /protocols/cifs/home-directory/search-paths](#)

### Parameters

Name	Type	In	Required	Description
index	integer	path	True	Home directory search path index

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
index	integer	The position in the list of paths that is searched to find the home directory of the CIFS client. Not available in POST.
path	string	The file system path that is searched to find the home directory of the CIFS client.
svm	<a href="#">svm</a>	

## Example response

```
{
  "index": 0,
  "path": "/HomeDirectory/EngDomain",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Re-order a CIFS home directory search path

```
PATCH /protocols/cifs/home-directory/search-paths/{svm.uuid}/{index}
```



## Introduced In: 9.6

Reorders a CIFS home directory search path.

### Related ONTAP commands

- `cifs server home-directory search-path reorder`

### Learn more

- [DOC /protocols/cifs/home-directory/search-paths](#)

### Parameters

Name	Type	In	Required	Description
index	integer	path	True	Home directory search path index
new_index	integer	query	False	New position for the home directory search path
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

### Response

```
Status: 200, Ok
```

### Error

```
Status: Default
```

### ONTAP Error Response Codes

Error Code	Description
655463	Failed to reorder the search-path because the new-index is invalid. It cannot be '0' and it cannot go beyond the current entries

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

### See Definitions

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

# Manage CIFS services

## Protocols CIFS services endpoint overview

## Overview

A CIFS server is necessary to provide SMB clients with access to the Storage Virtual Machine (SVM). Before you begin, the following prerequisites must be in place:

- At least one SVM LIF must exist on the SVM.
- The LIFs must be able to connect to the DNS servers configured on the SVM and to an Active Directory domain controller of the domain to which you want to join the CIFS server.
- The DNS servers must contain the service location records that are needed to locate the Active Directory domain services.
- The cluster time must be synchronized to within five minutes of the Active Directory domain controller.

## Performance monitoring

Performance of the SVM can be monitored by the `metric.*` and `statistics.*` properties. These show the performance of the SVM in terms of IOPS, latency and throughput. The `metric.*` properties denote an average whereas `statistics.*` properties denote a real-time monotonically increasing value aggregated across all nodes.

## Information on the CIFS server

You must keep the following in mind when creating the CIFS server:

- The CIFS server name might or might not be the same as the SVM name.
- The CIFS server name can be up to 15 characters in length.
- The following characters are not allowed: @ # \* ( ) = + [ ] \ | ; : " , < > \ / ?
- You must use the FQDN when specifying the domain.
- The default is to add the CIFS server machine account to the Active Directory "CN=Computer" object.
- You can choose to add the CIFS server to a different organizational unit (OU) by specifying the "organizational\_unit" parameter. When specifying the OU, do not specify the domain portion of the distinguished name; only specify the OU or CN portion of the distinguished name. ONTAP appends the value provided for the required "-domain" parameter onto the value provided for the "-ou" parameter to create the Active Directory distinguished name, which is used when joining the Active Directory domain.
- You can optionally choose to add a text comment of up to 48 characters about the CIFS server. If there is a space in the comment text, you must enclose the entire string in quotation marks.
- You can optionally choose to add a comma-delimited list of one or more NetBIOS aliases for the CIFS server.
- The initial administrative status of the CIFS server is "up".
- The `<i>large-mtu</i>` and `<em>multichannel</em>` features are enabled for the new CIFS server.
- If LDAP is configured with the `use_start_tls` and `session_security` features, the new CIFS server will also have this property set.

## Examples

### Creating a CIFS server

To create a CIFS server, use the following API. Note the `return_records=true` query parameter used to obtain the newly created entry in the response.

```

# The API:
POST /api/protocols/cifs/services

# The call:
curl -X POST "https://<mgmt-
ip>/api/protocols/cifs/services?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"ad_domain\":
{ \"fqdn\": \"CIFS-2008R2-AD.GDL.ENGLAB.NETAPP.COM\",
\"organizational_unit\": \"CN=Computers\", \"password\": \"cifs*123\",
\"user\": \"administrator\" }, \"comment\": \"This CIFS Server Belongs to
CS Department\", \"default_unix_user\": \"string\", \"enabled\": true,
\"name\": \"CIFS-DOC\", \"netbios\": { \"aliases\": [ \"ALIAS_1\",
\"ALIAS_2\", \"ALIAS_3\" ], \"enabled\": false, \"wins_servers\": [
\"10.224.65.20\", \"10.224.65.21\" ] }, \"security\": {
\"kdc_encryption\": false, \"encrypt_dc_connection\": false,
\"restrict_anonymous\": \"no_enumeration\", \"smb_encryption\": false,
\"smb_signing\": false }, \"svm\": { \"name\": \"vs1\", \"uuid\":
\"ef087155-f9e2-11e8-ac52-0050568ea248\" }}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "uuid": "9f5ab4cb-f703-11e8-91cc-0050568eca13",
        "name": "vs1"
      },
      "name": "CIFS-DOC",
      "ad_domain": {
        "fqdn": "CIFS-2008R2-AD.GDL.ENGLAB.NETAPP.COM",
        "user": "administrator",
        "password": "cifs*123",
        "organizational_unit": "CN=Computers"
      },
      "enabled": true,
      "comment": "This CIFS Server Belongs to CS Department",
      "security": {
        "restrict_anonymous": "no_enumeration",
        "smb_signing": false,
        "smb_encryption": false,
        "encrypt_dc_connection": false,
        "kdc_encryption": false
      },
      "netbios": {

```

```

    "aliases": [
      "ALIAS_1",
      "ALIAS_2",
      "ALIAS_3"
    ],
    "wins_servers": [
      "10.224.65.20",
      "10.224.65.21"
    ],
    "enabled": false
  },
  "default_unix_user": "string"
}
],
"job": {
  "uuid": "f232b6da-00a4-11e9-a8c1-0050568eca13",
  "_links": {
    "self": {
      "href": "/api/cluster/jobs/f232b6da-00a4-11e9-a8c1-0050568eca13"
    }
  }
}
}
}

```

---

### Retrieving the full CIFS server configuration for all SVMs in the cluster

---

```

# The API:
GET /api/protocols/cifs/services

# The call:
curl -X GET "https://<mgmt-
ip>/api/protocols/cifs/services?fields=*&return_records=true&return_timeou
t=15" -H "accept: application/json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "9f5ab4cb-f703-11e8-91cc-0050568eca13",
        "name": "vs1"
      }
    },
  ],
}

```

```
"name": "CIFS-DOC",
"ad_domain": {
  "fqdn": "CIFS-2008R2-AD.GDL.ENGLAB.NETAPP.COM",
  "organizational_unit": "CN=Computers"
},
"enabled": true,
"comment": "This CIFS Server Belongs to CS Department",
"security": {
  "restrict_anonymous": "no_enumeration",
  "smb_signing": false,
  "smb_encryption": false,
  "encrypt_dc_connection": false,
  "kdc_encryption": false,
  "lm_compatibility_level": "lm_ntlm_ntlmv2_krb"
},
"netbios": {
  "aliases": [
    "ALIAS_1",
    "ALIAS_2",
    "ALIAS_3"
  ],
  "wins_servers": [
    "10.224.65.20",
    "10.224.65.21"
  ],
  "enabled": false
},
"default_unix_user": "string"
}
],
"num_records": 1
}
```

---

### Retrieving CIFS server configuration details for a specific SVM

---

```
# The API:
GET /api/protocols/cifs/services/{svm.uuid}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/services/9f5ab4cb-f703-11e8-91cc-0050568eca13" -H "accept: application/json"

# The response:
{
  "svm": {
    "uuid": "9f5ab4cb-f703-11e8-91cc-0050568eca13",
    "name": "vs1"
  },
  "name": "CIFS-DOC",
  "ad_domain": {
    "fqdn": "CIFS-2008R2-AD.GDL.ENGLAB.NETAPP.COM",
    "organizational_unit": "CN=Computers"
  },
  "enabled": true,
  "comment": "This CIFS Server Belongs to CS Department",
  "security": {
    "restrict_anonymous": "no_enumeration",
    "smb_signing": false,
    "smb_encryption": false,
    "encrypt_dc_connection": false,
    "kdc_encryption": false,
    "lm_compatibility_level": "lm_ntlm_ntlmv2_krb"
  },
  "netbios": {
    "aliases": [
      "ALIAS_1",
      "ALIAS_2",
      "ALIAS_3"
    ],
    "wins_servers": [
      "10.224.65.20",
      "10.224.65.21"
    ],
    "enabled": false
  },
  "default_unix_user": "string"
}
```

## Updating CIFS server properties for the specified SVM

```
# The API:
PATCH /api/protocols/cifs/services/{svm.uuid}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/services/9f5ab4cb-f703-11e8-91cc-0050568eca13" -H "accept: application/json" -H "Content-Type: application/json" -d '{"comment": "CIFS SERVER MODIFICATION"}'
```

## Removing a CIFS server for a specific SVM

To delete a CIFS server, use the following API. This will delete the CIFS server along with other CIFS configurations such as CIFS share, share ACLs, homedir search-path, and so on.

```
# The API:
DELETE /api/protocols/cifs/services/{svm.uuid}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/cifs/services/9f5ab4cb-f703-11e8-91cc-0050568eca13" -H "accept: application/json" -H "Content-Type: application/json" -d '{"ad_domain": {"password": "cifs*123", "user": "administrator"} }'
```

## Retrieve CIFS servers

```
GET /protocols/cifs/services
```

**Introduced In:** 9.6

Retrieves CIFS servers.

### Expensive properties

There is an added cost to retrieving values for these properties. They are not included by default in GET results and must be explicitly requested using the `fields` query parameter. See [Requesting specific fields](#) to learn more.

- `statistics.*`
- `metric.*`



## Related ONTAP commands

- `vserver cifs server show`
- `vserver cifs server options show`
- `vserver cifs server security show`

## Learn more

- [DOC /protocols/cifs/services](#)

## Parameters

Name	Type	In	Required	Description
<code>metric.throughput.write</code>	integer	query	False	Filter by <code>metric.throughput.write</code> <ul style="list-style-type: none"><li>• Introduced in: 9.7</li></ul>
<code>metric.throughput.read</code>	integer	query	False	Filter by <code>metric.throughput.read</code> <ul style="list-style-type: none"><li>• Introduced in: 9.7</li></ul>
<code>metric.throughput.total</code>	integer	query	False	Filter by <code>metric.throughput.total</code> <ul style="list-style-type: none"><li>• Introduced in: 9.7</li></ul>
<code>metric.duration</code>	string	query	False	Filter by <code>metric.duration</code> <ul style="list-style-type: none"><li>• Introduced in: 9.7</li></ul>
<code>metric.timestamp</code>	string	query	False	Filter by <code>metric.timestamp</code> <ul style="list-style-type: none"><li>• Introduced in: 9.7</li></ul>

Name	Type	In	Required	Description
metric.status	string	query	False	Filter by metric.status  • Introduced in: 9.7
metric.iops.total	integer	query	False	Filter by metric.iops.total  • Introduced in: 9.7
metric.iops.read	integer	query	False	Filter by metric.iops.read  • Introduced in: 9.7
metric.iops.other	integer	query	False	Filter by metric.iops.other  • Introduced in: 9.7
metric.iops.write	integer	query	False	Filter by metric.iops.write  • Introduced in: 9.7
metric.latency.total	integer	query	False	Filter by metric.latency.total  • Introduced in: 9.7
metric.latency.read	integer	query	False	Filter by metric.latency.read  • Introduced in: 9.7
metric.latency.other	integer	query	False	Filter by metric.latency.other  • Introduced in: 9.7

Name	Type	In	Required	Description
metric.latency.write	integer	query	False	Filter by metric.latency.write  • Introduced in: 9.7
comment	string	query	False	Filter by comment
name	string	query	False	Filter by name
default_unix_user	string	query	False	Filter by default_unix_user
ad_domain.user	string	query	False	Filter by ad_domain.user
ad_domain.fqdn	string	query	False	Filter by ad_domain.fqdn
ad_domain.organizational_unit	string	query	False	Filter by ad_domain.organizational_unit
enabled	boolean	query	False	Filter by enabled
security.encrypt_dc_connection	boolean	query	False	Filter by security.encrypt_dc_connection  • Introduced in: 9.8
security.lm_compatibility_level	string	query	False	Filter by security.lm_compatibility_level  • Introduced in: 9.8
security.smb_encryption	boolean	query	False	Filter by security.smb_encryption
security.kdc_encryption	boolean	query	False	Filter by security.kdc_encryption

Name	Type	In	Required	Description
security.smb_signing	boolean	query	False	Filter by security.smb_signing
security.restrict_anonymous	string	query	False	Filter by security.restrict_anonymous
netbios.enabled	boolean	query	False	Filter by netbios.enabled
netbios.wins_servers	string	query	False	Filter by netbios.wins_servers
netbios.aliaes	string	query	False	Filter by netbios.aliaes
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name
statistics.latency_raw.total	integer	query	False	Filter by statistics.latency_raw.total  • Introduced in: 9.7
statistics.latency_raw.read	integer	query	False	Filter by statistics.latency_raw.read  • Introduced in: 9.7
statistics.latency_raw.other	integer	query	False	Filter by statistics.latency_raw.other  • Introduced in: 9.7

Name	Type	In	Required	Description
statistics.latency_raw.write	integer	query	False	Filter by statistics.latency_raw.write  • Introduced in: 9.7
statistics.timestamp	string	query	False	Filter by statistics.timestamp  • Introduced in: 9.7
statistics.iops_raw.total	integer	query	False	Filter by statistics.iops_raw.total  • Introduced in: 9.7
statistics.iops_raw.read	integer	query	False	Filter by statistics.iops_raw.read  • Introduced in: 9.7
statistics.iops_raw.other	integer	query	False	Filter by statistics.iops_raw.other  • Introduced in: 9.7
statistics.iops_raw.write	integer	query	False	Filter by statistics.iops_raw.write  • Introduced in: 9.7
statistics.throughput_raw.write	integer	query	False	Filter by statistics.throughput_raw.write  • Introduced in: 9.7

Name	Type	In	Required	Description
statistics.throughput_raw.read	integer	query	False	Filter by statistics.throughput_raw.read  • Introduced in: 9.7
statistics.throughput_raw.total	integer	query	False	Filter by statistics.throughput_raw.total  • Introduced in: 9.7
statistics.status	string	query	False	Filter by statistics.status  • Introduced in: 9.7
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned.  • Default value: 1

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">cifs_service</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "ad_domain": {
      "fqdn": "example.com"
    },
    "comment": "This CIFS Server Belongs to CS Department",
    "metric": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "duration": "PT15S",
      "iops": {
        "read": "200",
        "total": "1000",
        "write": "100"
      },
      "latency": {
        "read": "200",
        "total": "1000",
        "write": "100"
      },
      "status": "ok",
      "throughput": {
        "read": "200",
        "total": "1000",
        "write": "100"
      },
      "timestamp": "2017-01-25T11:20:13Z"
    }
  },
}
```



```

"name": "CIFS1",
"netbios": {
  "aliases": [
    "ALIAS_1",
    "ALIAS_2",
    "ALIAS_3"
  ],
  "wins_servers": [
    "10.224.65.20",
    "10.224.65.21"
  ]
},
"security": {
  "lm_compatibility_level": "lm_ntlm_ntlmv2_krb",
  "restrict_anonymous": "no_restriction"
},
"statistics": {
  "iops_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
}

```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

ad\_domain

Name	Type	Description
fqdn	string	The fully qualified domain name of the Windows Active Directory to which this CIFS server belongs. A CIFS server appears as a member of Windows server object in the Active Directory store. POST and PATCH only.
organizational_unit	string	Specifies the organizational unit within the Active Directory domain to associate with the CIFS server. POST and PATCH only.
password	string	The account password used to add this CIFS server to the Active Directory. This is not audited.
user	string	The user account used to add this CIFS server to the Active Directory. POST and DELETE only.

iops

The rate of I/O operations observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### latency

The round trip latency in microseconds observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### throughput

The rate of throughput bytes per second observed at the storage object.

Name	Type	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.

Name	Type	Description
write	integer	Performance metric for write I/O operations.

metric

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
duration	string	The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
iops	<a href="#">iops</a>	The rate of I/O operations observed at the storage object.
latency	<a href="#">latency</a>	The round trip latency in microseconds observed at the storage object.
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.

Name	Type	Description
throughput	throughput	The rate of throughput bytes per second observed at the storage object.
timestamp	string	The timestamp of the performance data.

#### cifs\_netbios

Name	Type	Description
aliases	array[string]	
enabled	boolean	Specifies whether NetBios name service (NBNS) is enabled for the CIFS. If this service is enabled, the CIFS server will start sending the broadcast for name registration.
wins_servers	array[string]	

#### cifs\_service\_security

Name	Type	Description
encrypt_dc_connection	boolean	Specifies whether encryption is required for domain controller connections.

Name	Type	Description
kdc_encryption	boolean	<p>Specifies whether AES-128 and AES-256 encryption is enabled for all Kerberos-based communication with the Active Directory KDC. To take advantage of the strongest security with Kerberos-based communication, AES-256 and AES-128 encryption can be enabled on the CIFS server. Kerberos-related communication for CIFS is used during CIFS server creation on the SVM, as well as during the SMB session setup phase. The CIFS server supports the following encryption types for Kerberos communication:</p> <ul style="list-style-type: none"> <li>• RC4-HMAC</li> <li>• DES</li> <li>• AES When the CIFS server is created, the domain controller creates a computer machine account in Active Directory. After a newly created machine account authenticates, the KDC and the CIFS server negotiates encryption types. At this time, the KDC becomes aware of the encryption capabilities of the particular machine account and uses those capabilities in subsequent communication with the CIFS server. In addition to negotiating encryption types during CIFS server creation, the encryption types are renegotiated when a machine account password is reset.</li> </ul>

Name	Type	Description
lm_compatibility_level	string	<p>It is CIFS server minimum security level, also known as the LMCompatibilityLevel. The minimum security level is the minimum level of the security tokens that the CIFS server accepts from SMB clients. The available values are:</p> <ul style="list-style-type: none"> <li>• lm_ntlm_ntlmv2_krb Accepts LM, NTLM, NTLMv2 and Kerberos</li> <li>• ntlm_ntlmv2_krb Accepts NTLM, NTLMv2 and Kerberos</li> <li>• ntlmv2_krb Accepts NTLMv2 and Kerberos</li> <li>• krb Accepts Kerberos only</li> </ul>
restrict_anonymous	string	<p>Specifies what level of access an anonymous user is granted. An anonymous user (also known as a "null user") can list or enumerate certain types of system information from Windows hosts on the network, including user names and details, account policies, and share names. Access for the anonymous user can be controlled by specifying one of three access restriction settings. The available values are:</p> <ul style="list-style-type: none"> <li>• no_restriction - No access restriction for an anonymous user.</li> <li>• no_enumeration - Enumeration is restricted for an anonymous user.</li> <li>• no_access - All access is restricted for an anonymous user.</li> </ul>
smb_encryption	boolean	Specifies whether encryption is required for incoming CIFS traffic.



Name	Type	Description
smb_signing	boolean	Specifies whether signing is required for incoming CIFS traffic. SMB signing helps to ensure that network traffic between the CIFS server and the client is not compromised.

#### iops\_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### latency\_raw

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.

Name	Type	Description
write	integer	Performance metric for write I/O operations.

#### throughput\_raw

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

Name	Type	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### statistics

Name	Type	Description
iops_raw	<a href="#">iops_raw</a>	The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.
latency_raw	<a href="#">latency_raw</a>	The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Type	Description
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput_raw	<a href="#">throughput_raw</a>	Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.
timestamp	string	The timestamp of the performance data.

#### svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

#### cifs\_service

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	

Name	Type	Description
ad_domain	<a href="#">ad_domain</a>	
comment	string	A descriptive text comment for the CIFS server. SMB clients can see the CIFS server comment when browsing servers on the network. If there is a space in the comment, you must enclose the entire string in quotation marks.
default_unix_user	string	Specifies the UNIX user to which any authenticated CIFS user is mapped to, if the normal user mapping rules fails.
enabled	boolean	Specifies if the CIFS service is administratively enabled.
metric	<a href="#">metric</a>	
name	string	The name of the CIFS server.
netbios	<a href="#">cifs_netbios</a>	
security	<a href="#">cifs_service_security</a>	
statistics	<a href="#">statistics</a>	
svm	<a href="#">svm</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message

Name	Type	Description
target	string	The target parameter that caused the error.

## Create a CIFS server

POST /protocols/cifs/services

**Introduced In:** 9.6

Creates a CIFS server. Each SVM can have one CIFS server.

### Important notes

- The CIFS server name might or might not be the same as the SVM name.
- The CIFS server name can contain up to 15 characters.
- The CIFS server name does not support the following characters: @ # \* ( ) = + [ ] \ | ; : " , < > / ?

### Required properties

- `svm.uuid` or `svm.name` - Existing SVM in which to create the CIFS server.
- `name` - Name of the CIFS server.
- `ad_domain.fqdn` - Fully qualified domain name of the Windows Active Directory to which this CIFS server belongs.
- `ad_domain.user` - User account with the access to add the CIFS server to the Active Directory.
- `ad_domain.password` - Account password used to add this CIFS server to the Active Directory.

### Recommended optional properties

- `comment` - Add a text comment of up to 48 characters about the CIFS server.
- `netbios.aliases` - Add a comma-delimited list of one or more NetBIOS aliases for the CIFS server.
- `netbios.wins_servers` - Add a list of Windows Internet Name Server (WINS) addresses that manage and map the NetBIOS name of the CIFS server to their network IP addresses. The IP addresses must be IPv4 addresses.

### Default property values

If not specified in POST, the following default property values are assigned:

- `ad_domain.organizational_unit` - *CN=Computers*
- `enabled` - *true*
- `restrict_anonymous` - *no\_enumeration*
- `smb_signing` - *false*
- `smb_encryption` - *false*

- `encrypt_dc_connection` - *false*
- `kdc_encryption` - *false*
- `default_unix_user` - *pcuser*
- `netbios_enabled` - *false* However, if either "netbios.wins-server" or "netbios.aliases" is set during POST and if `netbios_enabled` is not specified then `netbios_enabled` is set to true.

### Related ONTAP commands

- `vserver cifs server create`
- `vserver cifs server options modify`
- `vserver cifs security modify`
- `vserver cifs server add-netbios-aliases`

### Learn more

- [DOC /protocols/cifs/services](#)

### Parameters

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
return_records	boolean	query	False	<p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> <li>• Default value:</li> </ul>

### Request Body

Name	Type	Description
_links	<a href="#">_links</a>	
ad_domain	<a href="#">ad_domain</a>	

Name	Type	Description
comment	string	A descriptive text comment for the CIFS server. SMB clients can see the CIFS server comment when browsing servers on the network. If there is a space in the comment, you must enclose the entire string in quotation marks.
default_unix_user	string	Specifies the UNIX user to which any authenticated CIFS user is mapped to, if the normal user mapping rules fails.
enabled	boolean	Specifies if the CIFS service is administratively enabled.
metric	<a href="#">metric</a>	
name	string	The name of the CIFS server.
netbios	<a href="#">cifs_netbios</a>	
security	<a href="#">cifs_service_security</a>	
statistics	<a href="#">statistics</a>	
svm	<a href="#">svm</a>	



## Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "ad_domain": {
    "fqdn": "example.com"
  },
  "comment": "This CIFS Server Belongs to CS Department",
  "metric": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"name": "CIFS1",
"netbios": {
  "aliases": [
    "ALIAS_1",
    "ALIAS_2",
    "ALIAS_3"
  ],
  "wins_servers": [
    "10.224.65.20",
```

```

    "10.224.65.21"
  ]
},
"security": {
  "lm_compatibility_level": "lm_ntlm_ntlmv2_krb",
  "restrict_anonymous": "no_restriction"
},
"statistics": {
  "iops_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}

```

## Response

Status: 202, Accepted

Name	Type	Description
job	<a href="#">job_link</a>	

## Example response

```
{
  "job": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "uuid": "string"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

ad\_domain

Name	Type	Description
fqdn	string	The fully qualified domain name of the Windows Active Directory to which this CIFS server belongs. A CIFS server appears as a member of Windows server object in the Active Directory store. POST and PATCH only.
organizational_unit	string	Specifies the organizational unit within the Active Directory domain to associate with the CIFS server. POST and PATCH only.
password	string	The account password used to add this CIFS server to the Active Directory. This is not audited.
user	string	The user account used to add this CIFS server to the Active Directory. POST and DELETE only.

iops

The rate of I/O operations observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### latency

The round trip latency in microseconds observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### throughput

The rate of throughput bytes per second observed at the storage object.

Name	Type	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.

Name	Type	Description
write	integer	Performance metric for write I/O operations.

metric

Name	Type	Description
_links	<a href="#">_links</a>	
duration	string	The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
iops	<a href="#">iops</a>	The rate of I/O operations observed at the storage object.
latency	<a href="#">latency</a>	The round trip latency in microseconds observed at the storage object.
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.

Name	Type	Description
throughput	<a href="#">throughput</a>	The rate of throughput bytes per second observed at the storage object.
timestamp	string	The timestamp of the performance data.

#### cifs\_netbios

Name	Type	Description
aliases	array[string]	
enabled	boolean	Specifies whether NetBios name service (NBNS) is enabled for the CIFS. If this service is enabled, the CIFS server will start sending the broadcast for name registration.
wins_servers	array[string]	

#### cifs\_service\_security

Name	Type	Description
encrypt_dc_connection	boolean	Specifies whether encryption is required for domain controller connections.

Name	Type	Description
kdc_encryption	boolean	<p>Specifies whether AES-128 and AES-256 encryption is enabled for all Kerberos-based communication with the Active Directory KDC. To take advantage of the strongest security with Kerberos-based communication, AES-256 and AES-128 encryption can be enabled on the CIFS server. Kerberos-related communication for CIFS is used during CIFS server creation on the SVM, as well as during the SMB session setup phase. The CIFS server supports the following encryption types for Kerberos communication:</p> <ul style="list-style-type: none"> <li>• RC4-HMAC</li> <li>• DES</li> <li>• AES When the CIFS server is created, the domain controller creates a computer machine account in Active Directory. After a newly created machine account authenticates, the KDC and the CIFS server negotiates encryption types. At this time, the KDC becomes aware of the encryption capabilities of the particular machine account and uses those capabilities in subsequent communication with the CIFS server. In addition to negotiating encryption types during CIFS server creation, the encryption types are renegotiated when a machine account password is reset.</li> </ul>



Name	Type	Description
lm_compatibility_level	string	<p>It is CIFS server minimum security level, also known as the LMCompatibilityLevel. The minimum security level is the minimum level of the security tokens that the CIFS server accepts from SMB clients. The available values are:</p> <ul style="list-style-type: none"> <li>• lm_ntlm_ntlmv2_krb Accepts LM, NTLM, NTLMv2 and Kerberos</li> <li>• ntlm_ntlmv2_krb Accepts NTLM, NTLMv2 and Kerberos</li> <li>• ntlmv2_krb Accepts NTLMv2 and Kerberos</li> <li>• krb Accepts Kerberos only</li> </ul>
restrict_anonymous	string	<p>Specifies what level of access an anonymous user is granted. An anonymous user (also known as a "null user") can list or enumerate certain types of system information from Windows hosts on the network, including user names and details, account policies, and share names. Access for the anonymous user can be controlled by specifying one of three access restriction settings. The available values are:</p> <ul style="list-style-type: none"> <li>• no_restriction - No access restriction for an anonymous user.</li> <li>• no_enumeration - Enumeration is restricted for an anonymous user.</li> <li>• no_access - All access is restricted for an anonymous user.</li> </ul>
smb_encryption	boolean	<p>Specifies whether encryption is required for incoming CIFS traffic.</p>

Name	Type	Description
smb_signing	boolean	Specifies whether signing is required for incoming CIFS traffic. SMB signing helps to ensure that network traffic between the CIFS server and the client is not compromised.

#### iops\_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### latency\_raw

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.

Name	Type	Description
write	integer	Performance metric for write I/O operations.

#### throughput\_raw

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

Name	Type	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### statistics

Name	Type	Description
iops_raw	<a href="#">iops_raw</a>	The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.
latency_raw	<a href="#">latency_raw</a>	The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Type	Description
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput_raw	<a href="#">throughput_raw</a>	Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.
timestamp	string	The timestamp of the performance data.

#### svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

#### cifs\_service

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	

Name	Type	Description
ad_domain	<a href="#">ad_domain</a>	
comment	string	A descriptive text comment for the CIFS server. SMB clients can see the CIFS server comment when browsing servers on the network. If there is a space in the comment, you must enclose the entire string in quotation marks.
default_unix_user	string	Specifies the UNIX user to which any authenticated CIFS user is mapped to, if the normal user mapping rules fails.
enabled	boolean	Specifies if the CIFS service is administratively enabled.
metric	<a href="#">metric</a>	
name	string	The name of the CIFS server.
netbios	<a href="#">cifs_netbios</a>	
security	<a href="#">cifs_service_security</a>	
statistics	<a href="#">statistics</a>	
svm	<a href="#">svm</a>	

#### job\_link

Name	Type	Description
_links	<a href="#">_links</a>	
uuid	string	The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Delete a CIFS server and related configurations

```
DELETE /protocols/cifs/services/{svm.uuid}
```

**Introduced In:** 9.6

Deletes a CIFS server and related CIFS configurations.

### Related ONTAP commands

- `vserver cifs server delete`
- `vserver cifs remove-netbios-aliases`

### Learn more

- [DOC /protocols/cifs/services](#)

### Parameters

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

### Request Body

Name	Type	Description
ad_domain	<a href="#">ad_domain</a>	

## Example request

```
{
  "ad_domain": {
    "fqdn": "example.com"
  }
}
```

## Response

Status: 202, Accepted

Name	Type	Description
job	job_link	

## Example response

```
{
  "job": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "uuid": "string"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	



## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

ad\_domain

Name	Type	Description
fqdn	string	The fully qualified domain name of the Windows Active Directory to which this CIFS server belongs. A CIFS server appears as a member of Windows server object in the Active Directory store. POST and PATCH only.
organizational_unit	string	Specifies the organizational unit within the Active Directory domain to associate with the CIFS server. POST and PATCH only.
password	string	The account password used to add this CIFS server to the Active Directory. This is not audited.
user	string	The user account used to add this CIFS server to the Active Directory. POST and DELETE only.

cifs\_service\_delete

Name	Type	Description
ad_domain	<a href="#">ad_domain</a>	

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

job\_link

Name	Type	Description
_links	<a href="#">_links</a>	

Name	Type	Description
uuid	string	The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve a CIFS server

GET /protocols/cifs/services/{svm.uuid}

**Introduced In:** 9.6

Retrieves a CIFS server.

### Related ONTAP commands

- `vserver cifs server show`
- `vserver cifs server options show`
- `vserver cifs server security show`

### Learn more

- [DOC /protocols/cifs/services](#)

## Parameters

Name	Type	In	Required	Description
svm.uuid	string	path	True	
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
ad_domain	<a href="#">ad_domain</a>	
comment	string	A descriptive text comment for the CIFS server. SMB clients can see the CIFS server comment when browsing servers on the network. If there is a space in the comment, you must enclose the entire string in quotation marks.
default_unix_user	string	Specifies the UNIX user to which any authenticated CIFS user is mapped to, if the normal user mapping rules fails.
enabled	boolean	Specifies if the CIFS service is administratively enabled.
metric	<a href="#">metric</a>	
name	string	The name of the CIFS server.
netbios	<a href="#">cifs_netbios</a>	
security	<a href="#">cifs_service_security</a>	
statistics	<a href="#">statistics</a>	
svm	<a href="#">svm</a>	

## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "ad_domain": {
    "fqdn": "example.com"
  },
  "comment": "This CIFS Server Belongs to CS Department",
  "metric": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"name": "CIFS1",
"netbios": {
  "aliases": [
    "ALIAS_1",
    "ALIAS_2",
    "ALIAS_3"
  ],
  "wins_servers": [
    "10.224.65.20",
```

```

    "10.224.65.21"
  ]
},
"security": {
  "lm_compatibility_level": "lm_ntlm_ntlmv2_krb",
  "restrict_anonymous": "no_restriction"
},
"statistics": {
  "iops_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}

```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

ad\_domain

Name	Type	Description
fqdn	string	The fully qualified domain name of the Windows Active Directory to which this CIFS server belongs. A CIFS server appears as a member of Windows server object in the Active Directory store. POST and PATCH only.
organizational_unit	string	Specifies the organizational unit within the Active Directory domain to associate with the CIFS server. POST and PATCH only.
password	string	The account password used to add this CIFS server to the Active Directory. This is not audited.
user	string	The user account used to add this CIFS server to the Active Directory. POST and DELETE only.

iops

The rate of I/O operations observed at the storage object.



Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### latency

The round trip latency in microseconds observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### throughput

The rate of throughput bytes per second observed at the storage object.

Name	Type	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.

Name	Type	Description
write	integer	Performance metric for write I/O operations.

metric

Name	Type	Description
_links	<a href="#">_links</a>	
duration	string	The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
iops	<a href="#">iops</a>	The rate of I/O operations observed at the storage object.
latency	<a href="#">latency</a>	The round trip latency in microseconds observed at the storage object.
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.

Name	Type	Description
throughput	<a href="#">throughput</a>	The rate of throughput bytes per second observed at the storage object.
timestamp	string	The timestamp of the performance data.

#### cifs\_netbios

Name	Type	Description
aliases	array[string]	
enabled	boolean	Specifies whether NetBios name service (NBNS) is enabled for the CIFS. If this service is enabled, the CIFS server will start sending the broadcast for name registration.
wins_servers	array[string]	

#### cifs\_service\_security

Name	Type	Description
encrypt_dc_connection	boolean	Specifies whether encryption is required for domain controller connections.

Name	Type	Description
kdc_encryption	boolean	<p>Specifies whether AES-128 and AES-256 encryption is enabled for all Kerberos-based communication with the Active Directory KDC. To take advantage of the strongest security with Kerberos-based communication, AES-256 and AES-128 encryption can be enabled on the CIFS server. Kerberos-related communication for CIFS is used during CIFS server creation on the SVM, as well as during the SMB session setup phase. The CIFS server supports the following encryption types for Kerberos communication:</p> <ul style="list-style-type: none"> <li>• RC4-HMAC</li> <li>• DES</li> <li>• AES When the CIFS server is created, the domain controller creates a computer machine account in Active Directory. After a newly created machine account authenticates, the KDC and the CIFS server negotiates encryption types. At this time, the KDC becomes aware of the encryption capabilities of the particular machine account and uses those capabilities in subsequent communication with the CIFS server. In addition to negotiating encryption types during CIFS server creation, the encryption types are renegotiated when a machine account password is reset.</li> </ul>

Name	Type	Description
lm_compatibility_level	string	<p>It is CIFS server minimum security level, also known as the LMCompatibilityLevel. The minimum security level is the minimum level of the security tokens that the CIFS server accepts from SMB clients. The available values are:</p> <ul style="list-style-type: none"> <li>• lm_ntlm_ntlmv2_krb Accepts LM, NTLM, NTLMv2 and Kerberos</li> <li>• ntlm_ntlmv2_krb Accepts NTLM, NTLMv2 and Kerberos</li> <li>• ntlmv2_krb Accepts NTLMv2 and Kerberos</li> <li>• krb Accepts Kerberos only</li> </ul>
restrict_anonymous	string	<p>Specifies what level of access an anonymous user is granted. An anonymous user (also known as a "null user") can list or enumerate certain types of system information from Windows hosts on the network, including user names and details, account policies, and share names. Access for the anonymous user can be controlled by specifying one of three access restriction settings. The available values are:</p> <ul style="list-style-type: none"> <li>• no_restriction - No access restriction for an anonymous user.</li> <li>• no_enumeration - Enumeration is restricted for an anonymous user.</li> <li>• no_access - All access is restricted for an anonymous user.</li> </ul>
smb_encryption	boolean	<p>Specifies whether encryption is required for incoming CIFS traffic.</p>

Name	Type	Description
smb_signing	boolean	Specifies whether signing is required for incoming CIFS traffic. SMB signing helps to ensure that network traffic between the CIFS server and the client is not compromised.

#### iops\_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### latency\_raw

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.

Name	Type	Description
write	integer	Performance metric for write I/O operations.

#### throughput\_raw

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

Name	Type	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### statistics

Name	Type	Description
iops_raw	<a href="#">iops_raw</a>	The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.
latency_raw	<a href="#">latency_raw</a>	The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Type	Description
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput_raw	<a href="#">throughput_raw</a>	Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.
timestamp	string	The timestamp of the performance data.

#### svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

#### error\_arguments



Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Update CIFS mandatory and optional parameters

PATCH /protocols/cifs/services/{svm.uuid}

**Introduced In:** 9.6

Updates both the mandatory and optional parameters of the CIFS configuration. Ensure the CIFS server is administratively disabled when renaming the CIFS server or modifying the *ad\_domain* properties.

### Related ONTAP commands

- `vserver cifs server modify`
- `vserver cifs server options modify`
- `vserver cifs security modify`
- `vserver cifs server add-netbios-aliases`
- `vserver cifs server remove-netbios-aliases`

### Learn more

- [DOC /protocols/cifs/services](#)

### Parameters

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When doing a POST, PATCH, or DELETE operation on a single record, the default is 0 seconds. This means that if an asynchronous operation is started, the server immediately returns HTTP code 202 (Accepted) along with a link to the job. If a non-zero value is specified for POST, PATCH, or DELETE operations, ONTAP waits that length of time to see if the job completes so it can return something other than 202.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

### Request Body

Name	Type	Description
_links	<a href="#">_links</a>	
ad_domain	<a href="#">ad_domain</a>	

Name	Type	Description
comment	string	A descriptive text comment for the CIFS server. SMB clients can see the CIFS server comment when browsing servers on the network. If there is a space in the comment, you must enclose the entire string in quotation marks.
default_unix_user	string	Specifies the UNIX user to which any authenticated CIFS user is mapped to, if the normal user mapping rules fails.
enabled	boolean	Specifies if the CIFS service is administratively enabled.
metric	<a href="#">metric</a>	
name	string	The name of the CIFS server.
netbios	<a href="#">cifs_netbios</a>	
security	<a href="#">cifs_service_security</a>	
statistics	<a href="#">statistics</a>	
svm	<a href="#">svm</a>	

## Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "ad_domain": {
    "fqdn": "example.com"
  },
  "comment": "This CIFS Server Belongs to CS Department",
  "metric": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"name": "CIFS1",
"netbios": {
  "aliases": [
    "ALIAS_1",
    "ALIAS_2",
    "ALIAS_3"
  ],
  "wins_servers": [
    "10.224.65.20",
```

```

    "10.224.65.21"
  ]
},
"security": {
  "lm_compatibility_level": "lm_ntlm_ntlmv2_krb",
  "restrict_anonymous": "no_restriction"
},
"statistics": {
  "iops_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}

```

## Response

Status: 202, Accepted

Name	Type	Description
job	<a href="#">job_link</a>	

## Example response

```
{
  "job": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "uuid": "string"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

ad\_domain

Name	Type	Description
fqdn	string	The fully qualified domain name of the Windows Active Directory to which this CIFS server belongs. A CIFS server appears as a member of Windows server object in the Active Directory store. POST and PATCH only.
organizational_unit	string	Specifies the organizational unit within the Active Directory domain to associate with the CIFS server. POST and PATCH only.
password	string	The account password used to add this CIFS server to the Active Directory. This is not audited.
user	string	The user account used to add this CIFS server to the Active Directory. POST and DELETE only.

iops

The rate of I/O operations observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

### latency

The round trip latency in microseconds observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

### throughput

The rate of throughput bytes per second observed at the storage object.

Name	Type	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.



Name	Type	Description
write	integer	Performance metric for write I/O operations.

metric

Name	Type	Description
_links	<a href="#">_links</a>	
duration	string	The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
iops	<a href="#">iops</a>	The rate of I/O operations observed at the storage object.
latency	<a href="#">latency</a>	The round trip latency in microseconds observed at the storage object.
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.

Name	Type	Description
throughput	throughput	The rate of throughput bytes per second observed at the storage object.
timestamp	string	The timestamp of the performance data.

#### cifs\_netbios

Name	Type	Description
aliases	array[string]	
enabled	boolean	Specifies whether NetBios name service (NBNS) is enabled for the CIFS. If this service is enabled, the CIFS server will start sending the broadcast for name registration.
wins_servers	array[string]	

#### cifs\_service\_security

Name	Type	Description
encrypt_dc_connection	boolean	Specifies whether encryption is required for domain controller connections.

Name	Type	Description
kdc_encryption	boolean	<p>Specifies whether AES-128 and AES-256 encryption is enabled for all Kerberos-based communication with the Active Directory KDC. To take advantage of the strongest security with Kerberos-based communication, AES-256 and AES-128 encryption can be enabled on the CIFS server. Kerberos-related communication for CIFS is used during CIFS server creation on the SVM, as well as during the SMB session setup phase. The CIFS server supports the following encryption types for Kerberos communication:</p> <ul style="list-style-type: none"> <li>• RC4-HMAC</li> <li>• DES</li> <li>• AES When the CIFS server is created, the domain controller creates a computer machine account in Active Directory. After a newly created machine account authenticates, the KDC and the CIFS server negotiates encryption types. At this time, the KDC becomes aware of the encryption capabilities of the particular machine account and uses those capabilities in subsequent communication with the CIFS server. In addition to negotiating encryption types during CIFS server creation, the encryption types are renegotiated when a machine account password is reset.</li> </ul>

Name	Type	Description
lm_compatibility_level	string	<p>It is CIFS server minimum security level, also known as the LMCompatibilityLevel. The minimum security level is the minimum level of the security tokens that the CIFS server accepts from SMB clients. The available values are:</p> <ul style="list-style-type: none"> <li>• lm_ntlm_ntlmv2_krb Accepts LM, NTLM, NTLMv2 and Kerberos</li> <li>• ntlm_ntlmv2_krb Accepts NTLM, NTLMv2 and Kerberos</li> <li>• ntlmv2_krb Accepts NTLMv2 and Kerberos</li> <li>• krb Accepts Kerberos only</li> </ul>
restrict_anonymous	string	<p>Specifies what level of access an anonymous user is granted. An anonymous user (also known as a "null user") can list or enumerate certain types of system information from Windows hosts on the network, including user names and details, account policies, and share names. Access for the anonymous user can be controlled by specifying one of three access restriction settings. The available values are:</p> <ul style="list-style-type: none"> <li>• no_restriction - No access restriction for an anonymous user.</li> <li>• no_enumeration - Enumeration is restricted for an anonymous user.</li> <li>• no_access - All access is restricted for an anonymous user.</li> </ul>
smb_encryption	boolean	<p>Specifies whether encryption is required for incoming CIFS traffic.</p>

Name	Type	Description
smb_signing	boolean	Specifies whether signing is required for incoming CIFS traffic. SMB signing helps to ensure that network traffic between the CIFS server and the client is not compromised.

#### iops\_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### latency\_raw

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.

Name	Type	Description
write	integer	Performance metric for write I/O operations.

#### throughput\_raw

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

Name	Type	Description
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

#### statistics

Name	Type	Description
iops_raw	<a href="#">iops_raw</a>	The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.
latency_raw	<a href="#">latency_raw</a>	The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

Name	Type	Description
status	string	Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput_raw	<a href="#">throughput_raw</a>	Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.
timestamp	string	The timestamp of the performance data.

#### svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

#### cifs\_service

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	

Name	Type	Description
ad_domain	<a href="#">ad_domain</a>	
comment	string	A descriptive text comment for the CIFS server. SMB clients can see the CIFS server comment when browsing servers on the network. If there is a space in the comment, you must enclose the entire string in quotation marks.
default_unix_user	string	Specifies the UNIX user to which any authenticated CIFS user is mapped to, if the normal user mapping rules fails.
enabled	boolean	Specifies if the CIFS service is administratively enabled.
metric	<a href="#">metric</a>	
name	string	The name of the CIFS server.
netbios	<a href="#">cifs_netbios</a>	
security	<a href="#">cifs_service_security</a>	
statistics	<a href="#">statistics</a>	
svm	<a href="#">svm</a>	

#### job\_link

Name	Type	Description
_links	<a href="#">_links</a>	
uuid	string	The UUID of the asynchronous job that is triggered by a POST, PATCH, or DELETE operation.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error



Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve CIFS protocol historical performance metrics for an SVM

GET /protocols/cifs/services/{svm.uuid}/metrics

**Introduced In:** 9.7

Retrieves historical performance metrics for the CIFS protocol of an SVM.

### Parameters

Name	Type	In	Required	Description
throughput.total	integer	query	False	Filter by throughput.total
throughput.read	integer	query	False	Filter by throughput.read
throughput.other	integer	query	False	Filter by throughput.other
throughput.write	integer	query	False	Filter by throughput.write
timestamp	string	query	False	Filter by timestamp
duration	string	query	False	Filter by duration
status	string	query	False	Filter by status
iops.total	integer	query	False	Filter by iops.total
iops.read	integer	query	False	Filter by iops.read
iops.other	integer	query	False	Filter by iops.other

<b>Name</b>	<b>Type</b>	<b>In</b>	<b>Required</b>	<b>Description</b>
iops.write	integer	query	False	Filter by iops.write
latency.total	integer	query	False	Filter by latency.total
latency.read	integer	query	False	Filter by latency.read
latency.other	integer	query	False	Filter by latency.other
latency.write	integer	query	False	Filter by latency.write
svm.uuid	string	path	True	Unique identifier of the SVM.

Name	Type	In	Required	Description
interval	string	query	False	<p>The time range for the data. Examples can be 1h, 1d, 1m, 1w, 1y. The period for each time range is as follows:</p> <ul style="list-style-type: none"> <li>• 1h: Metrics over the most recent hour sampled over 15 seconds.</li> <li>• 1d: Metrics over the most recent day sampled over 5 minutes.</li> <li>• 1w: Metrics over the most recent week sampled over 30 minutes.</li> <li>• 1m: Metrics over the most recent month sampled over 2 hours.</li> <li>• 1y: Metrics over the most recent year sampled over a day.</li> <li>• Default value: 1</li> <li>• enum: ["1h", "1d", "1w", "1m", "1y"]</li> </ul>

Name	Type	In	Required	Description
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
order_by	array[string]	query	False	Order results by specified fields and optional [asc
desc] direction. Default direction is 'asc' for ascending.	return_records	boolean	query	False

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">records</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "duration": "PT15S",
    "iops": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "status": "ok",
    "throughput": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

iops

The rate of I/O operations observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

latency

The round trip latency in microseconds observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

### throughput

The rate of throughput bytes per second observed at the storage object.

Name	Type	Description
other	integer	Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
read	integer	Performance metric for read I/O operations.
total	integer	Performance metric aggregated over all types of I/O operations.
write	integer	Performance metric for write I/O operations.

### records

Performance numbers, such as IOPS latency and throughput.

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	



Name	Type	Description
duration	string	The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
iops	iops	The rate of I/O operations observed at the storage object.
latency	latency	The round trip latency in microseconds observed at the storage object.
status	string	Errors associated with the sample. For example, if the aggregation of data over multiple nodes fails, then any partial errors might return "ok" on success or "error" on an internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
throughput	throughput	The rate of throughput bytes per second observed at the storage object.
timestamp	string	The timestamp of the performance data.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## View CIFS active sessions

### Protocols CIFS sessions endpoint overview

#### Overview

ONTAP CIFS sessions `show` functionality is used to provide a list of currently established CIFS sessions.

The following lists the fields retrieved using the CIFS sessions GET API:

**node.name:** Node name hosting this record; basically the node hosting the "server\_ip". **node.uuid:** Node UUID hosting this record; basically the node hosting the "server\_ip". **svm.name:** Svm name to which the "server\_ip" belongs to. **svm.uuid:** Svm uuid to which the "server\_ip" belongs to. **server\_ip:** All clients connected to this interface are displayed in rows. **client\_ip:** IP address of the client connected to the interface. **identifier:** Unique identifier used to represent each SMB session. **connection\_id:** Unique identifier used to represent each SMB Connection. **authentication:** Type of authentication supported by the server when a client accesses a SMB share. **user:** Username for the Windows client. **mapped\_unix\_user:** Mapped UNIX user name. **open\_shares:** Number of shares opened by the client on a specific SVM. **open\_files:** Number of files opened by the client on a specific SVM. **open\_others:** Number of other files opened by the client on a specific SVM. **connected\_duration:** Time elapsed since the first request was sent by the client for this SMB session. **idle\_duration:** Time elapsed since the last request was sent by the client for this SMB session. **protocol:** SMB protocol dialects over which the client accesses the SMB share. **availability:** Level of continuous availability of protection provided to the files from the SMB share **smb\_signing:** Specifies whether SMB signing is enabled. **smb\_encryption:** Specifies the SMB session encryption status. **large\_mtu:** Specifies whether the SMB session's large MTU is enabled. **connection\_count:** Counter used to track requests that are sent to the volumes to the node. **volumes.name:** Name of the active volumes the client is accessing. **volumes.uuid:** UUID of the active volumes the client is accessing.

## Example

### Retrieves established sessions information

```
# The API:
GET /protocols/cifs/sessions

# The call:
curl -X GET "https://<cluster-mgmt-
ip>/api/protocols/cifs/sessions?return_timeout=15&return_records=true" -H
"accept: application/json"

# The response:
{
  "records": [
    {
      "node": {
        "uuid": "85d46998-4e5d-11ea-afb1-0050568ec4e4",
        "name": "bkalyan-vsim1"
      },
      "svm": {
        "uuid": "fc824aa8-4e60-11ea-afb1-0050568ec4e4",
        "name": "vs1"
      },
      "identifier": 625718873227788300,
      "connection_id": 91842,
      "lif_address": "10.140.70.197",
      "address": "10.74.7.182",
      "auth_mechanism": "ntlmv2",
      "windows_user": "NBCIFSQA2\\administrator",
      "unix_user": "root",
      "shares": 1,
      "files": 2,
      "other": 0,
      "connected_time": "PT16H54M47S",
      "idle_time": "PT3S",
      "protocol_version": "smb3_1",
      "continuously_available": "no",
      "is_session_signed": false,
      "smb_encryption_status": "unencrypted",
      "connection_count": 1,
      "is_large_mtu_enabled": true,
      "vol_names": [
        "voll2",
        "origin",
        "fg",
```

```

    "voll1"
  ],
  "vol_uuids": [
    "954d697f-4e62-11ea-afb1-0050568ec4e4",
    "0f909e06-4e6e-11ea-afb1-0050568ec4e4",
    "08c27b7d-4e61-11ea-afb1-0050568ec4e4",
    "02f0a240-4e61-11ea-afb1-0050568ec4e4"
  ]
},
{
  "node": {
    "uuid": "85d46998-4e5d-11ea-afb1-0050568ec4e4",
    "name": "bkalyan-vs1m1"
  },
  "svm": {
    "uuid": "fc824aa8-4e60-11ea-afb1-0050568ec4e4",
    "name": "vs1"
  },
  "identifier": 625718873227788500,
  "connection_id": 92080,
  "lif_address": "10.140.70.197",
  "address": "10.140.133.97",
  "auth_mechanism": "ntlmv2",
  "windows_user": "NBCIFSQA2\\administrator",
  "unix_user": "root",
  "shares": 1,
  "files": 1,
  "other": 0,
  "connected_time": "PT1M19S",
  "idle_time": "PT1M1S",
  "protocol_version": "smb3",
  "continuously_available": "no",
  "is_session_signed": false,
  "smb_encryption_status": "unencrypted",
  "connection_count": 1,
  "is_large_mtu_enabled": true,
  "vol_names": [
    "origin",
    "fg",
    "voll1"
  ],
  "vol_uuids": [
    "0f909e06-4e6e-11ea-afb1-0050568ec4e4",
    "08c27b7d-4e61-11ea-afb1-0050568ec4e4",
    "02f0a240-4e61-11ea-afb1-0050568ec4e4"
  ]
}

```

```

    }
  ],
  "num_records": 2
}

```

## Retrieve CIFS session information for all SVMs

GET /protocols/cifs/sessions

**Introduced In:** 9.8

Retrieves the CIFS sessions information for all SVMs.

### Related ONTAP commands

- `vserver cifs session show -active-volumes`

### Parameters

Name	Type	In	Required	Description
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name
large_mtu	boolean	query	False	Filter by large_mtu
authentication	string	query	False	Filter by authentication
user	string	query	False	Filter by user
open_other	integer	query	False	Filter by open_other
client_ip	string	query	False	Filter by client_ip
smb_encryption	string	query	False	Filter by smb_encryption
continuous_availability	string	query	False	Filter by continuous_availability
connected_duration	string	query	False	Filter by connected_duration

Name	Type	In	Required	Description
mapped_unix_user	string	query	False	Filter by mapped_unix_user
idle_duration	string	query	False	Filter by idle_duration
volumes.uuid	string	query	False	Filter by volumes.uuid
volumes.name	string	query	False	Filter by volumes.name
open_shares	integer	query	False	Filter by open_shares
server_ip	string	query	False	Filter by server_ip
node.name	string	query	False	Filter by node.name
node.uuid	string	query	False	Filter by node.uuid
connection_id	integer	query	False	Filter by connection_id
smb_signing	boolean	query	False	Filter by smb_signing
open_files	integer	query	False	Filter by open_files
identifier	integer	query	False	Filter by identifier
protocol	string	query	False	Filter by protocol
connection_count	integer	query	False	Filter by connection_count
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
return_records	boolean	query	False	<p>The default is true for GET calls. When set to false, only the number of records is returned.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>
order_by	array[string]	query	False	<p>Order results by specified fields and optional [asc</p>

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">cifs_session</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "authentication": "ntlmv2",
    "client_ip": "10.74.7.182",
    "connected_duration": "P4DT84H30M5S",
    "connection_count": "0",
    "connection_id": "22802",
    "continuous_availability": "no",
    "identifier": "4622663542519103507",
    "idle_duration": "P4DT84H30M5S",
    "large_mtu": 1,
    "mapped_unix_user": "root",
    "node": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "node1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "open_files": 0,
    "open_other": 0,
    "open_shares": 0,
    "protocol": "smb3.1",
    "server_ip": "10.140.78.248",
    "smb_encryption": "unencrypted",
    "smb_signing": "",
    "svm": {
      "_links": {
        "self": {
```



```

        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "user": "NBCIFSQA2\\administrator",
  "volumes": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}

```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

**Definitions**

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

node

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	
uuid	string	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

volumes

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the volume.

Name	Type	Description
uuid	string	<p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> <li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> </ul>

cifs\_session

Name	Type	Description
_links	<a href="#">_links</a>	
authentication	string	<p>SMB authentication over which the client accesses the share. The following values are supported:</p> <ul style="list-style-type: none"> <li>• none - No authentication</li> <li>• ntlmv1 - Ntlm version 1 mechanism</li> <li>• ntlmv2 - Ntlm version 2 mechanism</li> <li>• kerberos - Kerberos authentication</li> <li>• anonymous - Anonymous mechanism</li> </ul>
client_ip	string	Specifies IP address of the client.
connected_duration	string	Specifies an ISO-8601 format of date and time used to retrieve the connected time duration in hours, minutes, and seconds format.
connection_count	integer	A counter used to track requests that are sent to the volumes to the node.
connection_id	integer	A unique identifier used to represent each SMB connection.

Name	Type	Description
continuous_availability	string	<p>The level of continuous availability protection provided to the SMB sessions and/or files.</p> <ul style="list-style-type: none"> <li>• no - Open file is not continuously available. For sessions, it contains one or more open files but none of them are continuously available.</li> <li>• yes - open file is continuously available. For sessions, it contains one or more open files and all of them are continuously available.</li> <li>• partial - Sessions only. Contains at least one continuously available open file with other files open but not continuously available.</li> </ul>
identifier	integer	A unique identifier used to represent each SMB session.
idle_duration	string	Specifies an ISO-8601 format of date and time used to retrieve the idle time duration in hours, minutes, and seconds format.
large_mtu	boolean	Specifies whether or not a large MTU is enabled for an SMB session.
mapped_unix_user	string	Indicated that a mapped UNIX user has logged in.
node	<a href="#">node</a>	
open_files	integer	Number of files the SMB session has opened.
open_other	integer	Number of other files the SMB session has opened.
open_shares	integer	Number of shares the SMB session has opened.

Name	Type	Description
protocol	string	The SMB protocol version over which the client accesses the volumes. The following values are supported: <ul style="list-style-type: none"> <li>• smb1 - SMB version 1</li> <li>• smb2 - SMB version 2</li> <li>• smb2.1 - SMB version 2 minor version 1</li> <li>• smb3 - SMB version 3</li> <li>• smb3.1 - SMB version 3 minor version 1</li> </ul>
server_ip	string	Specifies the IP address of the SVM.
smb_encryption	string	Indicates an SMB encryption state. The following values are supported: <ul style="list-style-type: none"> <li>• unencrypted - SMB session is not encrypted</li> <li>• encrypted - SMB session is fully encrypted. SVM level encryption is enabled and encryption occurs for the entire session.</li> <li>• partially_encrypted - SMB session is partially encrypted. Share level encryption is enabled and encryption is initiated when the tree-connect occurs.</li> </ul>
smb_signing	boolean	Specifies whether or not SMB signing is enabled.
svm	<a href="#">svm</a>	
user	string	Indicates that a Windows user has logged in.
volumes	array[ <a href="#">volumes</a> ]	A group of volumes, the client is accessing.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve an SMB session information for an SMB connection in a SVM node

GET /protocols/cifs/sessions/{node.uuid}/{svm.uuid}/{identifier}/{connection\_id}

**Introduced In:** 9.8

Retrieves SMB session information for a specific SMB connection of a SVM in a node.

### Learn more

- [DOC /protocols/cifs/sessions](#)

### Parameters

Name	Type	In	Required	Description
node.uuid	string	path	True	Node UUID.
identifier	integer	path	True	Unique identifier for the SMB session.
connection_id	integer	path	True	Unique identifier for the SMB connection.
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

Name	Type	In	Required	Description
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
authentication	string	<p>SMB authentication over which the client accesses the share. The following values are supported:</p> <ul style="list-style-type: none"> <li>• none - No authentication</li> <li>• ntlmv1 - Ntlm version 1 mechanism</li> <li>• ntlmv2 - Ntlm version 2 mechanism</li> <li>• kerberos - Kerberos authentication</li> <li>• anonymous - Anonymous mechanism</li> </ul>
client_ip	string	Specifies IP address of the client.
connected_duration	string	Specifies an ISO-8601 format of date and time used to retrieve the connected time duration in hours, minutes, and seconds format.
connection_count	integer	A counter used to track requests that are sent to the volumes to the node.
connection_id	integer	A unique identifier used to represent each SMB connection.



Name	Type	Description
continuous_availability	string	<p>The level of continuous availability protection provided to the SMB sessions and/or files.</p> <ul style="list-style-type: none"> <li>• no - Open file is not continuously available. For sessions, it contains one or more open files but none of them are continuously available.</li> <li>• yes - open file is continuously available. For sessions, it contains one or more open files and all of them are continuously available.</li> <li>• partial - Sessions only. Contains at least one continuously available open file with other files open but not continuously available.</li> </ul>
identifier	integer	A unique identifier used to represent each SMB session.
idle_duration	string	Specifies an ISO-8601 format of date and time used to retrieve the idle time duration in hours, minutes, and seconds format.
large_mtu	boolean	Specifies whether or not a large MTU is enabled for an SMB session.
mapped_unix_user	string	Indicated that a mapped UNIX user has logged in.
node	<a href="#">node</a>	
open_files	integer	Number of files the SMB session has opened.
open_other	integer	Number of other files the SMB session has opened.
open_shares	integer	Number of shares the SMB session has opened.

Name	Type	Description
protocol	string	<p>The SMB protocol version over which the client accesses the volumes. The following values are supported:</p> <ul style="list-style-type: none"> <li>• smb1 - SMB version 1</li> <li>• smb2 - SMB version 2</li> <li>• smb2.1 - SMB version 2 minor version 1</li> <li>• smb3 - SMB version 3</li> <li>• smb3.1 - SMB version 3 minor version 1</li> </ul>
server_ip	string	Specifies the IP address of the SVM.
smb_encryption	string	<p>Indicates an SMB encryption state. The following values are supported:</p> <ul style="list-style-type: none"> <li>• unencrypted - SMB session is not encrypted</li> <li>• encrypted - SMB session is fully encrypted. SVM level encryption is enabled and encryption occurs for the entire session.</li> <li>• partially_encrypted - SMB session is partially encrypted. Share level encryption is enabled and encryption is initiated when the tree-connect occurs.</li> </ul>
smb_signing	boolean	Specifies whether or not SMB signing is enabled.
svm	<a href="#">svm</a>	
user	string	Indicates that a Windows user has logged in.
volumes	array[ <a href="#">volumes</a> ]	A group of volumes, the client is accessing.

## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "authentication": "ntlmv2",
  "client_ip": "10.74.7.182",
  "connected_duration": "P4DT84H30M5S",
  "connection_count": "0",
  "connection_id": "22802",
  "continuous_availability": "no",
  "identifier": "4622663542519103507",
  "idle_duration": "P4DT84H30M5S",
  "large_mtu": 1,
  "mapped_unix_user": "root",
  "node": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "name": "node1",
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"open_files": 0,
"open_other": 0,
"open_shares": 0,
"protocol": "smb3.1",
"server_ip": "10.140.78.248",
"smb_encryption": "unencrypted",
"smb_signing": "",
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  }
},
"name": "svm1",
"uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
},
"user": "NBCIFSQA2\\administrator",
"volumes": {
  "_links": {
```

```
    "self": {
      "href": "/api/resourcelink"
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

node

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	
uuid	string	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

volumes

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the volume.
uuid	string	Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"><li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li></ul>

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Manage CIFS shares

### Protocols CIFS shares endpoint overview

#### Overview

Before any users or applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permissions. CIFS share is a named access point in a volume which is tied to the CIFS server on the SVM. Before creating a CIFS share make sure that the path is valid within the scope of the SVM and that it is reachable.

Permissions can be assigned to this newly created share by specifying the 'acls' field. When a CIFS share is created, ONTAP creates a default ACL for this share with 'Full-Control' permissions for an 'Everyone' user.

#### Examples

##### Creating a CIFS share

To create a CIFS share for a CIFS server, use the following API. Note the *return\_records=true* query parameter used to obtain the newly created entry in the response.

```

# The API:
POST /api/protocols/cifs/shares

# The call:
curl -X POST "https://<mgmt-
ip>/api/protocols/cifs/shares?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{
  \"access_based_enumeration\": false, \"acls\": [ { \"permission\":
  \"no_access\", \"type\": \"unix_user\", \"user_or_group\": \"root\" } ],
  \"change_notify\": true, \"comment\": \"HR Department Share\",
  \"encryption\": false, \"home_directory\": false, \"name\": \"TEST\",
  \"oplocks\": true, \"path\": \"/\", \"svm\": { \"name\": \"vs1\",
  \"uuid\": \"000c5cd2-ebdf-11e8-a96e-0050568ea3cb\" }, \"unix_symlink\":
  \"local\"}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1"
      },
      "name": "TEST",
      "path": "/",
      "comment": "HR Department Share",
      "home_directory": false,
      "oplocks": true,
      "access_based_enumeration": false,
      "change_notify": true,
      "encryption": false,
      "unix_symlink": "local",
      "acls": [
        {
          "user_or_group": "root",
          "type": "unix_user",
          "permission": "no_access",
          "winsid_unixId": "0"
        }
      ]
    }
  ]
}

```

```
# The API:
GET /api/protocols/cifs/shares

# The call:
curl -X GET "https://<mgmt-
ip>/api/protocols/cifs/shares?fields=*&return_records=true&return_timeout=
15" -H "accept application/hal+json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1",
        "_links": {
          "self": {
            "href": "/api/svm/svms/000c5cd2-ebdf-11e8-a96e-0050568ea3cb"
          }
        }
      },
      "name": "admin$",
      "path": "/",
      "home_directory": false,
      "oplocks": false,
      "access_based_enumeration": false,
      "change_notify": false,
      "encryption": false,
      "volume": {
        "name": "vol1",
        "uuid": "4e06f1bc-1ddc-42e2-abb2-f221c6a2ab2a"
      },
      "_links": {
        "self": {
          "href": "/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-
0050568ea3cb/admin%24"
        }
      }
    },
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1",
```



```

    "_links": {
      "self": {
        "href": "/api/svm/svms/000c5cd2-ebdf-11e8-a96e-0050568ea3cb"
      }
    }
  },
  "name": "c$",
  "path": "/",
  "home_directory": false,
  "oplocks": true,
  "access_based_enumeration": false,
  "change_notify": true,
  "encryption": false,
  "unix_symlink": "local",
  "acls": [
    {
      "user_or_group": "BUILTIN\\Administrators",
      "type": "windows",
      "permission": "full_control"
    }
  ],
  "volume": {
    "name": "vol1",
    "uuid": "4e06f1bc-1ddc-42e2-abb2-f221c6a2ab2a"
  },
  "_links": {
    "self": {
      "href": "/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/c%24"
    }
  }
},
{
  "svm": {
    "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
    "name": "vs1",
    "_links": {
      "self": {
        "href": "/api/svm/svms/000c5cd2-ebdf-11e8-a96e-0050568ea3cb"
      }
    }
  },
  "name": "ipc$",
  "path": "/",
  "home_directory": false,
  "oplocks": false,

```

```

"access_based_enumeration": false,
"change_notify": false,
"encryption": false,
"volume": {
  "name": "voll",
  "uuid": "4e06f1bc-1ddc-42e2-abb2-f221c6a2ab2a"
},
"_links": {
  "self": {
    "href": "/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/ipc%24"
  }
}
},
{
  "svm": {
    "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
    "name": "vs1",
    "_links": {
      "self": {
        "href": "/api/svm/svms/000c5cd2-ebdf-11e8-a96e-0050568ea3cb"
      }
    }
  },
  "name": "TEST",
  "path": "/",
  "comment": "HR Department Share",
  "home_directory": false,
  "oplocks": true,
  "access_based_enumeration": false,
  "change_notify": true,
  "encryption": false,
  "unix_symlink": "local",
  "acls": [
    {
      "user_or_group": "Everyone",
      "type": "windows",
      "permission": "full_control"
    },
    {
      "user_or_group": "root",
      "type": "unix_user",
      "permission": "no_access"
    }
  ],
  "volume": {

```

```
    "name": "vol1",
    "uuid": "4e06f1bc-1ddc-42e2-abb2-f221c6a2ab2a"
  },
  "_links": {
    "self": {
      "href": "/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/TEST"
    }
  }
},
"num_records": 4,
"_links": {
  "self": {
    "href":
"/api/protocols/cifs/shares?fields=*&return_records=true&return_timeout=15"
  }
}
}
```

**Retrieving all CIFS Shares for all SVMs in the cluster for which the acls are configured for a "root" user**

---

```

# The API:
GET /api/protocols/cifs/shares

# The call:
curl -X GET "https://<mgmt-
ip>/api/protocols/cifs/shares?acls.user_or_group=root&fields=*&return_reco
rds=true&return_timeout=15" -H "accept: application/json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1"
      },
      "name": "TEST",
      "path": "/",
      "comment": "HR Department Share",
      "home_directory": false,
      "oplocks": true,
      "access_based_enumeration": false,
      "change_notify": true,
      "encryption": false,
      "unix_symlink": "local",
      "acls": [
        {
          "user_or_group": "Everyone",
          "type": "windows",
          "permission": "full_control"
        },
        {
          "user_or_group": "root",
          "type": "unix_user",
          "permission": "no_access"
        }
      ],
      "volume": {
        "name": "vol1",
        "uuid": "4e06f1bc-1ddc-42e2-abb2-f221c6a2ab2a"
      }
    }
  ],
  "num_records": 1
}

```

## Retrieving a specific CIFS share configuration for an SVM

The configuration being returned is identified by the UUID of its SVM and the name of the share.

```
# The API:
GET /api/protocols/cifs/shares/{svm.uuid}/{name}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/TEST" -H "accept: application/json"

# The response:
{
  "svm": {
    "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
    "name": "vs1"
  },
  "name": "TEST",
  "path": "/",
  "comment": "HR Department Share",
  "home_directory": false,
  "oplocks": true,
  "access_based_enumeration": false,
  "change_notify": true,
  "encryption": false,
  "unix_symlink": "local",
  "acls": [
    {
      "user_or_group": "Everyone",
      "type": "windows",
      "permission": "full_control"
    },
    {
      "user_or_group": "root",
      "type": "unix_user",
      "permission": "no_access"
    }
  ],
  "volume": {
    "name": "vol1",
    "uuid": "4e06f1bc-1ddc-42e2-abb2-f221c6a2ab2a"
  }
}
```

## Updating a specific CIFS share for an SVM

The CIFS share being modified is identified by the UUID of its SVM and the CIFS share name. The CIFS share ACLs cannot be modified with this API.

```
# The API:
PATCH /api/protocols/cifs/shares/{svm.uuid}/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/TEST" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"access_based_enumeration\": true, \"change_notify\": true, \"comment\": \"HR Department Share\", \"encryption\": false, \"oplocks\": true, \"path\": \"/\", \"unix_symlink\": \"widelink\"}"
```

## Removing a specific CIFS share for an SVM

The CIFS share being removed is identified by the UUID of its SVM and the CIFS share name.

```
# The API:
DELETE /api/protocols/cifs/shares/{svm.uuid}/{name}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/test" -H "accept: application/json"
```

---

## Retrieve CIFS shares

```
GET /protocols/cifs/shares
```

**Introduced In:** 9.6

Retrieves CIFS shares.

### Related ONTAP commands

- `vserver cifs share show`
- `vserver cifs share properties show`

### Learn more

- [DOC /protocols/cifs/shares](#)

## Parameters

Name	Type	In	Required	Description
volume.uuid	string	query	False	Filter by volume.uuid
volume.name	string	query	False	Filter by volume.name
path	string	query	False	Filter by path
change_notify	boolean	query	False	Filter by change_notify
home_directory	boolean	query	False	Filter by home_directory
access_based_enumeration	boolean	query	False	Filter by access_based_enumeration
name	string	query	False	Filter by name
comment	string	query	False	Filter by comment
acls.permission	string	query	False	Filter by acls.permission
acls.user_or_group	string	query	False	Filter by acls.user_or_group
acls.type	string	query	False	Filter by acls.type
unix_symlink	string	query	False	Filter by unix_symlink
oplocks	boolean	query	False	Filter by oplocks
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name
encryption	boolean	query	False	Filter by encryption
fields	array[string]	query	False	Specify the fields to return.

Name	Type	In	Required	Description
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">cifs_share</a> ]	



## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "acls": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "permission": "no_access",
      "type": "windows",
      "user_or_group": "ENGDOMAIN\\ad_user"
    },
    "comment": "HR Department Share",
    "name": "HR_SHARE",
    "path": "/volume_1/eng_vol/",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "unix_symlink": "local",
    "volume": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      }
    }
  },
}
```

```
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>

Name	Type	Description
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

#### svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

#### volume

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the volume.
uuid	string	Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"> <li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>• Introduced in: 9.6</li> </ul>

#### cifs\_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

Name	Type	Description
_links	<a href="#">_links</a>	
access_based_enumeration	boolean	If enabled, all folders inside this share are visible to a user based on that individual user access right; prevents the display of folders or other shared resources that the user does not have access to.
acls	array[ <a href="#">cifs_share_acl</a> ]	
change_notify	boolean	Specifies whether CIFS clients can request for change notifications for directories on this share.
comment	string	Specify the CIFS share descriptions.
encryption	boolean	Specifies that SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share.

Name	Type	Description
home_directory	boolean	<p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> <li>• Default value:</li> <li>• Introduced in: 9.6</li> <li>• readCreate: 1</li> </ul>
name	string	<p>Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically.</p>
oplocks	boolean	<p>Specify whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations.</p>

Name	Type	Description
path	string	<p>The fully-qualified pathname in the owning SVM namespace that is shared through this share. If this is a home directory share then the path should be dynamic by specifying the pattern %w (Windows user name), %u (UNIX user name), or %d (domain name) variables in any combination. ONTAP generates the path dynamically for the connected user and this path is appended to each search path to find the full Home Directory path.</p> <ul style="list-style-type: none"> <li>• example: /volume_1/eng_vol/</li> <li>• maxLength: 256</li> <li>• minLength: 1</li> <li>• Introduced in: 9.6</li> </ul>
svm	<a href="#">svm</a>	
unix_symlink	string	<p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> <li>• local - Enables only local symbolic links which is within the same CIFS share.</li> <li>• widelink - Enables both local symlinks and widelinks.</li> <li>• disable - Disables local symlinks and widelinks.</li> </ul>
volume	<a href="#">volume</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Create a CIFS share

POST /protocols/cifs/shares

**Introduced In:** 9.6

Creates a CIFS share.

### Required properties

- `svm.uuid` or `svm.name` - Existing SVM in which to create the CIFS share.
- `name` - Name of the CIFS share.
- `path` - Path in the owning SVM namespace that is shared through this share.

### Recommended optional properties

- `comment` - Optionally choose to add a text comment of up to 256 characters about the CIFS share.
- `acls` - Optionally choose to add share permissions that users and groups have on the CIFS share.

### Default property values

If not specified in POST, the following default property values are assigned:

- `home_directory` - *false*
- `oplocks` - *true*
- `access_based_enumeration` - *false*
- `change_notify` - *true*
- `encryption` - *false*
- `unix_symlink` - *local*

### Related ONTAP commands

- `vserver cifs share create`
- `vserver cifs share properties add`



- `vserver cifs share access-control create`

## Learn more

- [DOC /protocols/cifs/shares](#)

## Parameters

Name	Type	In	Required	Description
return_records	boolean	query	False	<p>The default is false. If set to true, the records are returned.</p> <ul style="list-style-type: none"> <li>• Default value:</li> </ul>

## Request Body

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
access_based_enumeration	boolean	If enabled, all folders inside this share are visible to a user based on that individual user access right; prevents the display of folders or other shared resources that the user does not have access to.
acls	array[ <a href="#">cifs_share_acl</a> ]	
change_notify	boolean	Specifies whether CIFS clients can request for change notifications for directories on this share.
comment	string	Specify the CIFS share descriptions.
encryption	boolean	Specifies that SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share.

Name	Type	Description
home_directory	boolean	<p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Introduced in: 9.6</li> <li>• readCreate: 1</li> </ul>
name	string	<p>Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically.</p>
oplocks	boolean	<p>Specify whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations.</p>

Name	Type	Description
path	string	<p>The fully-qualified pathname in the owning SVM namespace that is shared through this share. If this is a home directory share then the path should be dynamic by specifying the pattern %w (Windows user name), %u (UNIX user name), or %d (domain name) variables in any combination. ONTAP generates the path dynamically for the connected user and this path is appended to each search path to find the full Home Directory path.</p> <ul style="list-style-type: none"> <li>• example: /volume_1/eng_vol/</li> <li>• maxLength: 256</li> <li>• minLength: 1</li> <li>• Introduced in: 9.6</li> </ul>
svm	svm	
unix_symlink	string	<p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> <li>• local - Enables only local symbolic links which is within the same CIFS share.</li> <li>• widelink - Enables both local symlinks and widelinks.</li> <li>• disable - Disables local symlinks and widelinks.</li> </ul>
volume	volume	

## Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "acls": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "permission": "no_access",
    "type": "windows",
    "user_or_group": "ENGDOMAIN\\ad_user"
  },
  "comment": "HR Department Share",
  "name": "HR_SHARE",
  "path": "/volume_1/eng_vol/",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "unix_symlink": "local",
  "volume": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "volumel",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}
```

## Response

Status: 201, Created

## Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
655628	CIFS Share Creation with property 'SMB_ENCRYPTION' failed because the CIFS server does not support SMB3.0
655551	CIFS Share Creation failed because the specified path does not exist
655577	The CIFS share name cannot be more than 80 characters long
655399	Failed to create CIFS share. The CIFS server does not exist for specified SVM
656422	Failed to create the home directory share because the directory shares must specify a path relative to one or more home directory search paths
656423	Failed to create CIFS share. The Shares must define an absolute share path
656424	Failed to create CIFS the administrator share 'c\$' because you are not permitted to created any admin shares
655625	Failed to create CIFS share. The Shares path is not a valid file-type for CIFS share
656426	CIFS Share Creation failed because the share name is invalid

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"><li>• windows - Windows user or group</li><li>• unix_user - UNIX user</li><li>• unix_group - UNIX group</li></ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

#### volume

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the volume.
uuid	string	<p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> <li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>• Introduced in: 9.6</li> </ul>

#### cifs\_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
access_based_enumeration	boolean	If enabled, all folders inside this share are visible to a user based on that individual user access right; prevents the display of folders or other shared resources that the user does not have access to.
acls	array[ <a href="#">cifs_share_acl</a> ]	
change_notify	boolean	Specifies whether CIFS clients can request for change notifications for directories on this share.



Name	Type	Description
comment	string	Specify the CIFS share descriptions.
encryption	boolean	Specifies that SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share.
home_directory	boolean	<p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Introduced in: 9.6</li> <li>• readCreate: 1</li> </ul>
name	string	Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically.

Name	Type	Description
oplocks	boolean	Specify whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations.
path	string	<p>The fully-qualified pathname in the owning SVM namespace that is shared through this share. If this is a home directory share then the path should be dynamic by specifying the pattern %w (Windows user name), %u (UNIX user name), or %d (domain name) variables in any combination. ONTAP generates the path dynamically for the connected user and this path is appended to each search path to find the full Home Directory path.</p> <ul style="list-style-type: none"> <li>• example: /volume_1/eng_vol/</li> <li>• maxLength: 256</li> <li>• minLength: 1</li> <li>• Introduced in: 9.6</li> </ul>
svm	<a href="#">svm</a>	
unix_symlink	string	<p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> <li>• local - Enables only local symbolic links which is within the same CIFS share.</li> <li>• widelink - Enables both local symlinks and widelinks.</li> <li>• disable - Disables local symlinks and widelinks.</li> </ul>
volume	<a href="#">volume</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code

Name	Type	Description
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Delete a CIFS share

```
DELETE /protocols/cifs/shares/{svm.uuid}/{name}
```

**Introduced In:** 9.6

Deletes a CIFS share.

### Related ONTAP commands

- `vserver cifs share delete`

### Learn more

- [DOC /protocols/cifs/shares](#)

### Parameters

Name	Type	In	Required	Description
name	string	path	True	Share Name
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

### Response

```
Status: 200, Ok
```

## Error

Status: Default

### ONTAP Error Response Codes

Error Code	Description
655393	Standard admin shares cannot be removed

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve a CIFS share

GET /protocols/cifs/shares/{svm.uuid}/{name}

**Introduced In:** 9.6

Retrieves a CIFS share.

### Related ONTAP commands

- `vserver cifs share show`
- `vserver cifs share properties show`

### Learn more

- [DOC /protocols/cifs/shares](#)

### Parameters

Name	Type	In	Required	Description
name	string	path	True	Share Name

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
access_based_enumeration	boolean	If enabled, all folders inside this share are visible to a user based on that individual user access right; prevents the display of folders or other shared resources that the user does not have access to.
acls	array[ <a href="#">cifs_share_acl</a> ]	
change_notify	boolean	Specifies whether CIFS clients can request for change notifications for directories on this share.
comment	string	Specify the CIFS share descriptions.
encryption	boolean	Specifies that SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share.

Name	Type	Description
home_directory	boolean	<p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Introduced in: 9.6</li> <li>• readCreate: 1</li> </ul>
name	string	<p>Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically.</p>
oplocks	boolean	<p>Specify whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations.</p>

Name	Type	Description
path	string	<p>The fully-qualified pathname in the owning SVM namespace that is shared through this share. If this is a home directory share then the path should be dynamic by specifying the pattern %w (Windows user name), %u (UNIX user name), or %d (domain name) variables in any combination. ONTAP generates the path dynamically for the connected user and this path is appended to each search path to find the full Home Directory path.</p> <ul style="list-style-type: none"> <li>• example: /volume_1/eng_vol/</li> <li>• maxLength: 256</li> <li>• minLength: 1</li> <li>• Introduced in: 9.6</li> </ul>
svm	svm	
unix_symlink	string	<p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> <li>• local - Enables only local symbolic links which is within the same CIFS share.</li> <li>• widelink - Enables both local symlinks and widelinks.</li> <li>• disable - Disables local symlinks and widelinks.</li> </ul>
volume	volume	



## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "acls": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "permission": "no_access",
    "type": "windows",
    "user_or_group": "ENGDOMAIN\\ad_user"
  },
  "comment": "HR Department Share",
  "name": "HR_SHARE",
  "path": "/volume_1/eng_vol/",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "unix_symlink": "local",
  "volume": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "volumel",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"><li>• windows - Windows user or group</li><li>• unix_user - UNIX user</li><li>• unix_group - UNIX group</li></ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

#### volume

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the volume.
uuid	string	<p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> <li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>• Introduced in: 9.6</li> </ul>

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Update a CIFS share

PATCH /protocols/cifs/shares/{svm.uuid}/{name}

**Introduced In:** 9.6

Updates a CIFS share.

### Related ONTAP commands

- `vserver cifs share modify`
- `vserver cifs share properties add`
- `vserver cifs share properties remove`

### Learn more

- [DOC /protocols/cifs/shares](#)

### Parameters

Name	Type	In	Required	Description
name	string	path	True	Share Name
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

### Request Body

Name	Type	Description
<code>_links</code>	<a href="#">_links</a>	
<code>access_based_enumeration</code>	boolean	If enabled, all folders inside this share are visible to a user based on that individual user access right; prevents the display of folders or other shared resources that the user does not have access to.
<code>acls</code>	array[ <a href="#">cifs_share_acl</a> ]	
<code>change_notify</code>	boolean	Specifies whether CIFS clients can request for change notifications for directories on this share.
<code>comment</code>	string	Specify the CIFS share descriptions.

Name	Type	Description
encryption	boolean	Specifies that SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share.
home_directory	boolean	<p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Introduced in: 9.6</li> <li>• readCreate: 1</li> </ul>
name	string	Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically.

Name	Type	Description
oplocks	boolean	Specify whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations.
path	string	<p>The fully-qualified pathname in the owning SVM namespace that is shared through this share. If this is a home directory share then the path should be dynamic by specifying the pattern %w (Windows user name), %u (UNIX user name), or %d (domain name) variables in any combination. ONTAP generates the path dynamically for the connected user and this path is appended to each search path to find the full Home Directory path.</p> <ul style="list-style-type: none"> <li>• example: /volume_1/eng_vol/</li> <li>• maxLength: 256</li> <li>• minLength: 1</li> <li>• Introduced in: 9.6</li> </ul>
svm	svm	
unix_symlink	string	<p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> <li>• local - Enables only local symbolic links which is within the same CIFS share.</li> <li>• widelink - Enables both local symlinks and widelinks.</li> <li>• disable - Disables local symlinks and widelinks.</li> </ul>
volume	volume	

## Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "acls": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "permission": "no_access",
    "type": "windows",
    "user_or_group": "ENGDOMAIN\\ad_user"
  },
  "comment": "HR Department Share",
  "name": "HR_SHARE",
  "path": "/volume_1/eng_vol/",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "unix_symlink": "local",
  "volume": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "volumel",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}
```



## Response

Status: 200, Ok

## Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
655628	'SMB_ENCRYPTION' property cannot be set on CIFS share because the CIFS server does not support SMB3.0
655551	CIFS Share modification failed because the specified path does not exist
655620	Cannot set symlink properties for admin shares
656420	Cannot modify the standard share ipc\$
656421	Cannot modify the standard share admin\$
656422	Failed to modify the home directory share because the directory shares must specify a path relative to one or more home directory search paths
656423	Failed to modify CIFS share. The Shares must define an absolute share path
656425	Failed to modify the CIFS share because the path for an administrative share cannot be modified

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"><li>• windows - Windows user or group</li><li>• unix_user - UNIX user</li><li>• unix_group - UNIX group</li></ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

svm

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

#### volume

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the volume.
uuid	string	<p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> <li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>• Introduced in: 9.6</li> </ul>

#### cifs\_share

CIFS share is a named access point in a volume. Before users and applications can access data on the CIFS server over SMB, a CIFS share must be created with sufficient share permission. CIFS shares are tied to the CIFS server on the SVM. When a CIFS share is created, ONTAP creates a default ACL for the share with Full Control permissions for Everyone.

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
access_based_enumeration	boolean	If enabled, all folders inside this share are visible to a user based on that individual user access right; prevents the display of folders or other shared resources that the user does not have access to.
acls	array[ <a href="#">cifs_share_acl</a> ]	
change_notify	boolean	Specifies whether CIFS clients can request for change notifications for directories on this share.

Name	Type	Description
comment	string	Specify the CIFS share descriptions.
encryption	boolean	Specifies that SMB encryption must be used when accessing this share. Clients that do not support encryption are not able to access this share.
home_directory	boolean	<p>Specifies whether or not the share is a home directory share, where the share and path names are dynamic. ONTAP home directory functionality automatically offer each user a dynamic share to their home directory without creating an individual SMB share for each user. The ONTAP CIFS home directory feature enable us to configure a share that maps to different directories based on the user that connects to it. Instead of creating a separate shares for each user, a single share with a home directory parameters can be created. In a home directory share, ONTAP dynamically generates the share-name and share-path by substituting %w, %u, and %d variables with the corresponding Windows user name, UNIX user name, and domain name, respectively.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Introduced in: 9.6</li> <li>• readCreate: 1</li> </ul>
name	string	Specifies the name of the CIFS share that you want to create. If this is a home directory share then the share name includes the pattern as %w (Windows user name), %u (UNIX user name) and %d (Windows domain name) variables in any combination with this parameter to generate shares dynamically.

Name	Type	Description
oplocks	boolean	Specify whether opportunistic locks are enabled on this share. "Oplocks" allow clients to lock files and cache content locally, which can increase performance for file operations.
path	string	<p>The fully-qualified pathname in the owning SVM namespace that is shared through this share. If this is a home directory share then the path should be dynamic by specifying the pattern %w (Windows user name), %u (UNIX user name), or %d (domain name) variables in any combination. ONTAP generates the path dynamically for the connected user and this path is appended to each search path to find the full Home Directory path.</p> <ul style="list-style-type: none"> <li>• example: /volume_1/eng_vol/</li> <li>• maxLength: 256</li> <li>• minLength: 1</li> <li>• Introduced in: 9.6</li> </ul>
svm	<a href="#">svm</a>	
unix_symlink	string	<p>Controls the access of UNIX symbolic links to CIFS clients. The supported values are:</p> <ul style="list-style-type: none"> <li>• local - Enables only local symbolic links which is within the same CIFS share.</li> <li>• widelink - Enables both local symlinks and widelinks.</li> <li>• disable - Disables local symlinks and widelinks.</li> </ul>
volume	<a href="#">volume</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code

Name	Type	Description
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Manage share-level ACL

### Protocols CIFS shares svm.uuid share acs endpoint overview

#### Overview

Access to files and folders can be secured over a network by configuring share access control lists (ACLs) on CIFS shares. Share-level ACLs can be configured by using either Windows users and groups or UNIX users and groups. A share-level ACL consists of a list of access control entries (ACEs). Each ACE contains a user or group name and a set of permissions that determines user or group access to the share, regardless of the security style of the volume or qtree containing the share.

When an SMB user tries to access a share, ONTAP checks the share-level ACL to determine whether access should be granted. A share-level ACL only restricts access to files in the share; it never grants more access than the file level ACLs.

#### Examples

##### Creating a CIFS share ACL

To create a share ACL for a CIFS share, use the following API. Note the *return\_records=true* query parameter used to obtain the newly created entry in the response.

```
# The API:
POST /api/protocols/cifs/shares{svm.uuid}/{share}/acls

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-
11e8-a96e-0050568ea3cb/sh1/acls?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{
\"permission\": \"no_access\", \"type\": \"windows\", \"user_or_group\":
\"root\"}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "name": "vs1"
      },
      "user_or_group": "root",
      "type": "windows",
      "permission": "no_access"
    }
  ]
}
```

---

**Retrieving all CIFS shares ACLs for a specific CIFS share for a specific SVM in the cluster**

---



```

# The API:
GET /api/protocols/cifs/shares/{svm.uuid}/{share}/acls

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/sh1/acls?fields=*&return_records=true&return_timeout=15" -H "accept: application/json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1"
      },
      "share": "sh1",
      "user_or_group": "Everyone",
      "type": "windows",
      "permission": "full_control"
    },
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1"
      },
      "share": "sh1",
      "user_or_group": "root",
      "type": "windows",
      "permission": "no_access"
    }
  ],
  "num_records": 2
}

```

---

**Retrieving a CIFS share ACLs for a user or a group of type Windows or type UNIX on a CIFS share for a specific SVM**

---

```

# The API:
GET
/api/protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/sh1/acls/everyone/windows" -H "accept: application/json"

# The response:
{
  "svm": {
    "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
    "name": "vs1"
  },
  "share": "sh1",
  "user_or_group": "everyone",
  "type": "windows",
  "permission": "full_control"
}

```

#### Updating a CIFS share ACLs of a user or group on a CIFS share for a specific SVM

The CIFS share ACL being modified is identified by the UUID of its SVM, the CIFS share name, user or group name and the type of the user or group.

```

# The API:
PATCH
/api/protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/sh1/acls/everyone/windows" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"permission\": \"no_access\"}"

```

#### Removing a CIFS share ACLs of a user or group on a CIFS Share for a specific SVM

The CIFS share ACL being removed is identified by the UUID of its SVM, the CIFS share name, user or group name and the type of the user or group.

```
# The API:
DELETE
/api/protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/cifs/shares/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/sh1/acls/everyone/windows" -H "accept: application/json"
```

## Retrieve a share-level ACL on a CIFS share

GET /protocols/cifs/shares/{svm.uuid}/{share}/acls

**Introduced In:** 9.6

Retrieves the share-level ACL on a CIFS share.

### Related ONTAP commands

- `vserver cifs share access-control show`

### Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

### Parameters

Name	Type	In	Required	Description
share	string	path	True	CIFS Share Name
permission	string	query	False	Filter by permission
user_or_group	string	query	False	Filter by user_or_group
type	string	query	False	Filter by type
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

Name	Type	In	Required	Description
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">cifs_share_acl</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "permission": "no_access",
    "type": "windows",
    "user_or_group": "ENGDOMAIN\\ad_user"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>

Name	Type	Description
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Create a share-level ACL on a CIFS share

POST /protocols/cifs/shares/{svm.uuid}/{share}/acls

**Introduced In:** 9.6

Creates a share-level ACL on a CIFS share.



## Required properties

- `svm.uuid` or `svm.name` - Existing SVM in which to create the share acl.
- `share` - Existing CIFS share in which to create the share acl.
- `user_or_group` - Existing user or group name for which the acl is added on the CIFS share.
- `permission` - Access rights that a user or group has on the defined CIFS share.

## Default property values

- `type` - *windows*

## Related ONTAP commands

- `vserver cifs share access-control create`

## Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

## Parameters

Name	Type	In	Required	Description
share	string	path	True	CIFS Share Name
return_records	boolean	query	False	The default is false. If set to true, the records are returned. <ul style="list-style-type: none"><li>• Default value:</li></ul>
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Request Body

Name	Type	Description
<code>_links</code>	<code><a href="#">_links</a></code>	

Name	Type	Description
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"> <li>• no_access - User does not have CIFS share access</li> <li>• read - User has only read access</li> <li>• change - User has change access</li> <li>• full_control - User has full_control access</li> </ul>
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

### Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "permission": "no_access",
  "type": "windows",
  "user_or_group": "ENGDOMAIN\\ad_user"
}
```

## Response

Status: 201, Created

## Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
655470	Failed to create share ACL because the share does not exist
655446	Failed to create share ACL because the specified Windows user/group does not exist
4849678	Failed to create share ACL because the specified UNIX user/group does not exist

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"><li>• windows - Windows user or group</li><li>• unix_user - UNIX user</li><li>• unix_group - UNIX group</li></ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Delete a share-level ACL on a CIFS share

```
DELETE /protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}
```

**Introduced In:** 9.6

Deletes a share-level ACL on a CIFS share.

### Related ONTAP commands

- `vserver cifs share access-control delete`

### Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

### Parameters

Name	Type	In	Required	Description
share	string	path	True	Share name
user_or_group	string	path	True	User or group name
type	string	path	True	User or group type

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Response

Status: 200, Ok

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve a share-level ACL on a CIFS share for a user or group

```
GET /protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}
```

**Introduced In:** 9.6

Retrieves the share-level ACL on CIFS share for a specified user or group.

### Related ONTAP commands

- `vserver cifs share access-control show`

### Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

### Parameters

Name	Type	In	Required	Description
share	string	path	True	Share name
user_or_group	string	path	True	User or group name
type	string	path	True	User or group type

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
permission	string	<p>Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed:</p> <ul style="list-style-type: none"> <li>• no_access - User does not have CIFS share access</li> <li>• read - User has only read access</li> <li>• change - User has change access</li> <li>• full_control - User has full_control access</li> </ul>
type	string	<p>Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed:</p> <ul style="list-style-type: none"> <li>• windows - Windows user or group</li> <li>• unix_user - UNIX user</li> <li>• unix_group - UNIX group</li> </ul>
user_or_group	string	<p>Specifies the user or group name to add to the access control list of a CIFS share.</p>



## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "permission": "no_access",
  "type": "windows",
  "user_or_group": "ENGDOMAIN\\ad_user"
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Update a share-level ACL on a CIFS share

```
PATCH /protocols/cifs/shares/{svm.uuid}/{share}/acls/{user_or_group}/{type}
```

**Introduced In:** 9.6

Updates a share-level ACL on a CIFS share.

### Related ONTAP commands

- `vserver cifs share access-control modify`

## Learn more

- [DOC /protocols/cifs/shares/{svm.uuid}/{share}/acls](#)

## Parameters

Name	Type	In	Required	Description
share	string	path	True	Share name
user_or_group	string	path	True	User or group name
type	string	path	True	User or group type
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Request Body

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
permission	string	<p>Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed:</p> <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>
type	string	<p>Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed:</p> <ul style="list-style-type: none"><li>• windows - Windows user or group</li><li>• unix_user - UNIX user</li><li>• unix_group - UNIX group</li></ul>

Name	Type	Description
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

### Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "permission": "no_access",
  "type": "windows",
  "user_or_group": "ENGDOMAIN\\ad_user"
}
```

### Response

Status: 200, Ok

### Error

Status: Default

### ONTAP Error Response Codes

Error Code	Description
655516	The share ACL does not exist for given user and share

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

cifs\_share\_acl

The permissions that users and groups have on a CIFS share.

Name	Type	Description
_links	<a href="#">_links</a>	
permission	string	Specifies the access rights that a user or group has on the defined CIFS Share. The following values are allowed: <ul style="list-style-type: none"><li>• no_access - User does not have CIFS share access</li><li>• read - User has only read access</li><li>• change - User has change access</li><li>• full_control - User has full_control access</li></ul>
type	string	Specifies the type of the user or group to add to the access control list of a CIFS share. The following values are allowed: <ul style="list-style-type: none"><li>• windows - Windows user or group</li><li>• unix_user - UNIX user</li><li>• unix_group - UNIX group</li></ul>
user_or_group	string	Specifies the user or group name to add to the access control list of a CIFS share.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Manage CIFS UNIX symlink mapping

### Protocols CIFS unix-symlink-mapping endpoint overview

#### Overview

ONTAP allows both CIFS and NFS to access the same datastore. This datastore can contain symbolic links which are files, created by UNIX clients. It contains a reference to another file or directory. If an SMB client accesses a symbolic link, it is redirected to the target file or directory that the symbolic link refers to. The symbolic links can point to files within the volume that contain the share, or to files that are contained in other volumes on the Storage Virtual Machine (SVM), or even to volumes contained on other SVMs.

There are two types of symbolic links:

**Relative** A relative symbolic link contains a reference to the file or directory relative to its parent directory. Therefore, the path of the file it is referring to should not begin with a backslash (*/*). If you enable symbolic links on a share, relative symbolic links work without UNIX symlink mapping.

**Absolute** An absolute symbolic link contains a reference to a file or directory in the form of an absolute path. Therefore, the path of the file it is referring to should begin with a backslash (*/*). An absolute symbolic link can refer to a file or directory within or outside of the file system of the symbolic link. If the target is not in the same local file system, the symbolic link is called a "widelink". If the symbolic link is enabled on a share and absolute symbolic links do not work right away, the mapping between the UNIX path of the symbolic link to the destination CIFS path must be created. When creating absolute symbolic link mappings, locality could be either "local" or "widelink" and it must be specified. If UNIX symlink mapping is created for a file or directory which is outside of the local share but the locality is set to "local", ONTAP does not allow access to the target.

A UNIX symbolic link support could be added to SMB shares by specifying the *unix\_symlink* property during the creation of SMB shares or at any time by modifying the existing SMB *unix\_symlink* property. UNIX symbolic link support is enabled by default.

## Examples

### Creating a UNIX symlink mapping for CIFS shares

To create UNIX symlink mappings for SMB shares, use the following API. Note the *return\_records=true* query parameter used to obtain the newly created entry in the response.

```
# The API:
POST /api/protocols/cifs/unix-symlink-mapping

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/cifs/unix-symlink-
mapping?return_records=true" -H "accept: application/json" -H "Content-
Type: application/json" -d "{ \"svm\": { \"name\": \"vs1\", \"uuid\":
\"000c5cd2-ebdf-11e8-a96e-0050568ea3cb\" }, \"target\": {
\"home_directory\": false, \"locality\": \"local\", \"path\":
\"/dir1/dir2/\", \"server\": \"cifs123\", \"share\": \"sh1\" },
\"unix_path\": \"/mnt/eng_volume/\"}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1"
      },
      "unix_path": "/mnt/eng_volume/",
      "target": {
        "share": "sh1",
        "path": "/dir1/dir2/",
        "server": "cifs123",
        "locality": "local",
        "home_directory": false
      }
    }
  ]
}
```



## Retrieving UNIX symlink mappings for all SVMs in the cluster

```
# The API:
GET /api/protocols/cifs/unix-symlink-mapping

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/unix-symlink-
mapping?fields=*&return_records=true&return_timeout=15" -H "accept:
application/hal+json"

# The response:
{
  "records": [
    {
      "svm": {
        "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs1",
        "_links": {
          "self": {
            "href": "/api/svm/svms/000c5cd2-ebdf-11e8-a96e-0050568ea3cb"
          }
        }
      },
      "unix_path": "/mnt/eng_volume/",
      "target": {
        "share": "sh1",
        "path": "/dir1/dir2/",
        "server": "CIFS123",
        "locality": "local",
        "home_directory": false
      },
      "_links": {
        "self": {
          "href": "/api/protocols/cifs/unix-symlink-mapping/000c5cd2-ebdf-
11e8-a96e-0050568ea3cb/%2Fmnt%2Feng_volume%2F"
        }
      }
    },
    {
      "svm": {
        "uuid": "1d30d1b1-ebdf-11e8-a96e-0050568ea3cb",
        "name": "vs2",
        "_links": {
          "self": {
            "href": "/api/svm/svms/1d30d1b1-ebdf-11e8-a96e-0050568ea3cb"
          }
        }
      }
    }
  ]
}
```

```

    }
  },
  "unix_path": "/mnt/eng_volume/",
  "target": {
    "share": "ENG_SHARE",
    "path": "/dir1/dir2/",
    "server": "ENG_CIFS",
    "locality": "widelink",
    "home_directory": false
  },
  "_links": {
    "self": {
      "href": "/api/protocols/cifs/unix-symlink-mapping/1d30d1b1-ebdf-11e8-a96e-0050568ea3cb/%2Fmnt%2Feng_volume%2F"
    }
  }
},
],
"num_records": 2,
"_links": {
  "self": {
    "href": "/api/protocols/cifs/unix-symlink-mapping?fields=*&return_records=true&return_timeout=15"
  }
}
}

```

### Retrieving a specific UNIX symlink mapping for an SVM

The mapping being returned is identified by the UUID of its SVM and the unix-path.

```

# The API:
GET /api/protocols/cifs/unix-symlink-mapping/{svm.uuid}/{unix_path}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/cifs/unix-symlink-
mapping/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/%2Fmnt%2Feng_volume%2F" -H
"accept: application/json"

# The response:
{
  "svm": {
    "uuid": "000c5cd2-ebdf-11e8-a96e-0050568ea3cb",
    "name": "vs1"
  },
  "unix_path": "/mnt/eng_volume/",
  "target": {
    "share": "sh1",
    "path": "/dir1/dir2/",
    "server": "CIFS123",
    "locality": "local",
    "home_directory": false
  }
}

```

### Updating a specific UNIX symlink mapping for an SVM

The mapping being modified is identified by the UUID of its SVM and the unix-path.

```

# The API:
PATCH /api/protocols/cifs/unix-symlink-mapping/{svm.uuid}/{unix_path}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/cifs/unix-symlink-
mapping/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/%2Fmnt%2Feng_volume%2F" -H
"accept: application/json" -H "Content-Type: application/json" -d "{
  \"target\": { \"home_directory\": true, \"locality\": \"widelink\",
  \"path\": \"/new_path/\", \"server\": \"HR_SERVER\", \"share\": \"sh2\"
  } }"

```

### Removing a specific UNIX symlink mapping for an SVM

The mapping being removed is identified by the UUID of its SVM and the unix-path.

```
# The API:
DELETE /api/protocols/cifs/unix-symlink-mapping/{svm.uuid}/{unix_path}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/cifs/unix-symlink-
mapping/000c5cd2-ebdf-11e8-a96e-0050568ea3cb/%2Fmnt%2Feng_volume%2F" -H
"accept: application/json"
```

## Retrieve UNIX symbolic link mappings for CIFS clients

GET /protocols/cifs/unix-symlink-mapping

**Introduced In:** 9.6

Retrieves UNIX symbolic link mappings for CIFS clients.

### Related ONTAP commands

- `vserver cifs symlink show`

### Learn more

- [DOC /protocols/cifs/unix-symlink-mapping](#)

### Parameters

Name	Type	In	Required	Description
unix_path	string	query	False	Filter by unix_path
target.share	string	query	False	Filter by target.share
target.home_directory	boolean	query	False	Filter by target.home_directory
target.server	string	query	False	Filter by target.server
target.path	string	query	False	Filter by target.path
target.locality	string	query	False	Filter by target.locality
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name

Name	Type	In	Required	Description
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">cifs_symlink_mapping</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "target": {
      "locality": "local",
      "path": "/dir1/dir2/",
      "server": "ENG_CIFS",
      "share": "ENG_SHARE"
    },
    "unix_path": "/mnt/eng_volume/"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

cifs\_target

Name	Type	Description
home_directory	boolean	Specify if the destination share is a home directory.
locality	string	Specifies whether the CIFS symbolic link is a local link or wide link. The following values are supported: <ul style="list-style-type: none"><li>• local - Local symbolic link maps only to the same CIFS share.</li><li>• widelink - Wide symbolic link maps to any CIFS share on the network.</li></ul>



Name	Type	Description
path	string	Specifies the CIFS path on the destination to which the symbolic link maps. The final path is generated by concatenating the CIFS server name, the share name, the cifs-path and the remaining path in the symbolic link left after the prefix match. This value is specified by using a UNIX-style path name. The trailing forward slash is required for the full path name to be properly interpreted.
server	string	Specifies the destination CIFS server where the UNIX symbolic link is pointing. This field is mandatory if the locality of the symbolic link is 'widelink'. You can specify the value in any of the following formats: <ul style="list-style-type: none"> <li>• DNS name of the CIFS server.</li> <li>• IP address of the CIFS server.</li> <li>• NetBIOS name of the CIFS server.</li> </ul>
share	string	Specifies the CIFS share name on the destination CIFS server to which the UNIX symbolic link is pointing.

#### cifs\_symlink\_mapping

ONTAP allows for both CIFS and NFS access to the same datastore. This datastore can contain symbolic links created by UNIX clients which can point anywhere from the perspective of the UNIX client. To Access such UNIX symlink from CIFS share, we need to create a CIFS symbolic link path mapping from a UNIX symlink and target it as a CIFS path.

Name	Type	Description
_links	<a href="#">_links</a>	
svm	<a href="#">svm</a>	
target	<a href="#">cifs_target</a>	

Name	Type	Description
unix_path	string	Specifies the UNIX path prefix to be matched for the mapping.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Create a UNIX symbolic link mapping for a CIFS client

POST /protocols/cifs/unix-symlink-mapping

**Introduced In:** 9.6

Creates a UNIX symbolic link mapping for a CIFS client.

### Required properties

- `svm.uuid` or `svm.name` - Existing SVM in which to create the CIFS unix-symlink-mapping.
- `unix_path` - UNIX path to which the CIFS symlink mapping to be created.
- `target.share` - CIFS share name on the destination CIFS server to which the UNIX symbolic link is pointing.
- `target.path` - CIFS path on the destination to which the symbolic link maps.

### Default property values

- `target.server` - *Local\_NetBIOS\_Server\_Name*
- `locality` - *local*

- `home_directory` - *false*

### Related ONTAP commands

- `vserver cifs symlink create`

### Learn more

- [DOC /protocols/cifs/unix-symlink-mapping](#)

### Parameters

Name	Type	In	Required	Description
return_records	boolean	query	False	The default is false. If set to true, the records are returned. <ul style="list-style-type: none"> <li>• Default value:</li> </ul>

### Request Body

Name	Type	Description
_links	<a href="#">_links</a>	
svm	<a href="#">svm</a>	
target	<a href="#">cifs_target</a>	
unix_path	string	Specifies the UNIX path prefix to be matched for the mapping.

## Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "target": {
    "locality": "local",
    "path": "/dir1/dir2/",
    "server": "ENGCIFS",
    "share": "ENG_SHARE"
  },
  "unix_path": "/mnt/eng_volume/"
}
```

## Response

Status: 201, Created

Name	Type	Description
<code>_links</code>	<code>_links</code>	
<code>num_records</code>	integer	Number of records
<code>records</code>	array[cifs_symlink_mapping]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "target": {
      "locality": "local",
      "path": "/dir1/dir2/",
      "server": "ENG_CIFS",
      "share": "ENG_SHARE"
    },
    "unix_path": "/mnt/eng_volume/"
  }
}
```

## Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
655654	Must specify the target CIFS share while creating path mapping entries with localities "local" or "widelink"
655572	The target path contains illegal characters or is too long
655574	The target server contains illegal characters or is too long
655436	If the locality is "local", the target server must be blank or must match the CIFS NetBIOS name for given SVM
655439	The Specified target server is local CIFS server for given SVM but the locality is specified as "widelink"
655546	Failed to create symlink mapping because administrative share cannot be used as target share
655437	Failed to create the symlink mapping with locality "local" because the target share does not exist for specified SVM
655429	UNIX path must begin and end with a "/"
655430	Target path must begin and end with a "/"
655399	Failed to get the CIFS server for specified SVM

Name	Type	Description
error	error	

### Example error

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

### Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

cifs\_target

Name	Type	Description
home_directory	boolean	Specify if the destination share is a home directory.
locality	string	Specifies whether the CIFS symbolic link is a local link or wide link. The following values are supported: <ul style="list-style-type: none"><li>• local - Local symbolic link maps only to the same CIFS share.</li><li>• widelink - Wide symbolic link maps to any CIFS share on the network.</li></ul>

Name	Type	Description
path	string	Specifies the CIFS path on the destination to which the symbolic link maps. The final path is generated by concatenating the CIFS server name, the share name, the cifs-path and the remaining path in the symbolic link left after the prefix match. This value is specified by using a UNIX-style path name. The trailing forward slash is required for the full path name to be properly interpreted.
server	string	Specifies the destination CIFS server where the UNIX symbolic link is pointing. This field is mandatory if the locality of the symbolic link is 'widelink'. You can specify the value in any of the following formats: <ul style="list-style-type: none"> <li>• DNS name of the CIFS server.</li> <li>• IP address of the CIFS server.</li> <li>• NetBIOS name of the CIFS server.</li> </ul>
share	string	Specifies the CIFS share name on the destination CIFS server to which the UNIX symbolic link is pointing.

#### cifs\_symlink\_mapping

ONTAP allows for both CIFS and NFS access to the same datastore. This datastore can contain symbolic links created by UNIX clients which can point anywhere from the perspective of the UNIX client. To Access such UNIX symlink from CIFS share, we need to create a CIFS symbolic link path mapping from a UNIX symlink and target it as a CIFS path.

Name	Type	Description
_links	<a href="#">_links</a>	
svm	<a href="#">svm</a>	
target	<a href="#">cifs_target</a>	



Name	Type	Description
unix_path	string	Specifies the UNIX path prefix to be matched for the mapping.

\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Delete the UNIX symbolic link mapping for CIFS clients

```
DELETE /protocols/cifs/unix-symlink-mapping/{svm.uuid}/{unix_path}
```

**Introduced In:** 9.6

Deletes the UNIX symbolic link mapping for CIFS clients.

### Related ONTAP commands

- `vserver cifs symlink delete`

### Learn more

- [DOC /protocols/cifs/unix-symlink-mapping](#)

## Parameters

Name	Type	In	Required	Description
unix_path	string	path	True	UNIX symbolic link path
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Response

Status: 200, Ok

## Error

Status: Default, Error

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve the UNIX symbolic link mapping for CIFS clients

```
GET /protocols/cifs/unix-symlink-mapping/{svm.uuid}/{unix_path}
```

**Introduced In:** 9.6

Retrieves a UNIX symbolic link mapping for CIFS clients.

### Related ONTAP commands

- `vserver cifs symlink show`

### Learn more

- [DOC /protocols/cifs/unix-symlink-mapping](#)

### Parameters

Name	Type	In	Required	Description
unix_path	string	path	True	UNIX symbolic link path

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">_links</a>	
svm	<a href="#">svm</a>	
target	<a href="#">cifs_target</a>	
unix_path	string	Specifies the UNIX path prefix to be matched for the mapping.

## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "target": {
    "locality": "local",
    "path": "/dir1/dir2/",
    "server": "ENGCIFS",
    "share": "ENG_SHARE"
  },
  "unix_path": "/mnt/eng_volume/"
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

cifs\_target

Name	Type	Description
home_directory	boolean	Specify if the destination share is a home directory.
locality	string	Specifies whether the CIFS symbolic link is a local link or wide link. The following values are supported: <ul style="list-style-type: none"><li>• local - Local symbolic link maps only to the same CIFS share.</li><li>• widelink - Wide symbolic link maps to any CIFS share on the network.</li></ul>

Name	Type	Description
path	string	Specifies the CIFS path on the destination to which the symbolic link maps. The final path is generated by concatenating the CIFS server name, the share name, the cifs-path and the remaining path in the symbolic link left after the prefix match. This value is specified by using a UNIX-style path name. The trailing forward slash is required for the full path name to be properly interpreted.
server	string	Specifies the destination CIFS server where the UNIX symbolic link is pointing. This field is mandatory if the locality of the symbolic link is 'widelink'. You can specify the value in any of the following formats: <ul style="list-style-type: none"> <li>• DNS name of the CIFS server.</li> <li>• IP address of the CIFS server.</li> <li>• NetBIOS name of the CIFS server.</li> </ul>
share	string	Specifies the CIFS share name on the destination CIFS server to which the UNIX symbolic link is pointing.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments



Name	Type	Description
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Update the UNIX symbolic link mapping for CIFS clients

PATCH /protocols/cifs/unix-symlink-mapping/{svm.uuid}/{unix\_path}

**Introduced In:** 9.6

Updates the UNIX symbolic link mapping for CIFS clients.

### Related ONTAP commands

- `vserver cifs symlink modify`

### Learn more

- [DOC /protocols/cifs/unix-symlink-mapping](#)

### Parameters

Name	Type	In	Required	Description
unix_path	string	path	True	UNIX symbolic link path
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

### Request Body

Name	Type	Description
_links	<a href="#">_links</a>	
svm	<a href="#">svm</a>	
target	<a href="#">cifs_target</a>	
unix_path	string	Specifies the UNIX path prefix to be matched for the mapping.

## Example request

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "target": {
    "locality": "local",
    "path": "/dir1/dir2/",
    "server": "ENG_CIFS",
    "share": "ENG_SHARE"
  },
  "unix_path": "/mnt/eng_volume/"
}
```

## Response

Status: 200, Ok

## Error

Status: Default

## ONTAP Error Response Codes

Error Code	Description
655573	Failed to modify the symlink mapping to target path because it contains illegal characters or is too long
655575	Failed to modify the symlink mapping to target server because it contains illegal characters or is too long

Error Code	Description
655547	Failed to modify symlink mapping because administrative share cannot be used as target share

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

### Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

cifs\_target

Name	Type	Description
home_directory	boolean	Specify if the destination share is a home directory.
locality	string	Specifies whether the CIFS symbolic link is a local link or wide link. The following values are supported: <ul style="list-style-type: none"><li>• local - Local symbolic link maps only to the same CIFS share.</li><li>• widelink - Wide symbolic link maps to any CIFS share on the network.</li></ul>

Name	Type	Description
path	string	Specifies the CIFS path on the destination to which the symbolic link maps. The final path is generated by concatenating the CIFS server name, the share name, the cifs-path and the remaining path in the symbolic link left after the prefix match. This value is specified by using a UNIX-style path name. The trailing forward slash is required for the full path name to be properly interpreted.
server	string	Specifies the destination CIFS server where the UNIX symbolic link is pointing. This field is mandatory if the locality of the symbolic link is 'widelink'. You can specify the value in any of the following formats: <ul style="list-style-type: none"> <li>• DNS name of the CIFS server.</li> <li>• IP address of the CIFS server.</li> <li>• NetBIOS name of the CIFS server.</li> </ul>
share	string	Specifies the CIFS share name on the destination CIFS server to which the UNIX symbolic link is pointing.

#### cifs\_symlink\_mapping

ONTAP allows for both CIFS and NFS access to the same datastore. This datastore can contain symbolic links created by UNIX clients which can point anywhere from the perspective of the UNIX client. To Access such UNIX symlink from CIFS share, we need to create a CIFS symbolic link path mapping from a UNIX symlink and target it as a CIFS path.

Name	Type	Description
_links	<a href="#">_links</a>	
svm	<a href="#">svm</a>	
target	<a href="#">cifs_target</a>	

Name	Type	Description
unix_path	string	Specifies the UNIX path prefix to be matched for the mapping.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve trace results for denied or allowed events

GET /protocols/file-access-tracing/events

**Introduced In:** 9.8

Retrieves the trace results for access allowed or denied events.

### Related ONTAP commands

- `vserver security trace trace-result show`

### Parameters

Name	Type	In	Required	Description
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name

<b>Name</b>	<b>Type</b>	<b>In</b>	<b>Required</b>	<b>Description</b>
reason.message	string	query	False	Filter by reason.message
node.name	string	query	False	Filter by node.name
node.uuid	string	query	False	Filter by node.uuid
index	integer	query	False	Filter by index
session_id	integer	query	False	Filter by session_id
filter.trace_allowed_ops	boolean	query	False	Filter by filter.trace_allowed_ops
filter.unix_user	string	query	False	Filter by filter.unix_user
filter.index	integer	query	False	Filter by filter.index
filter.client_ip	string	query	False	Filter by filter.client_ip
filter.svm.uuid	string	query	False	Filter by filter.svm.uuid
filter.svm.name	string	query	False	Filter by filter.svm.name
filter.enabled	boolean	query	False	Filter by filter.enabled
filter.windows_user	string	query	False	Filter by filter.windows_user
filter.path	string	query	False	Filter by filter.path
filter.protocol	string	query	False	Filter by filter.protocol
share.name	string	query	False	Filter by share.name
create_time	string	query	False	Filter by create_time
volume.uuid	string	query	False	Filter by volume.uuid

Name	Type	In	Required	Description
volume.name	string	query	False	Filter by volume.name
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none"> <li>• Default value: 1</li> </ul>
return_timeout	integer	query	False	The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached. <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">collection_links</a>	



Name	Type	Description
num_records	integer	Number of records
records	array[ <a href="#">file_access_event</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "create_time": "2018-06-04T19:00:00Z",
    "filter": {
      "client_ip": "10.140.68.143",
      "index": "1",
      "path": "/dir1/dir2",
      "protocol": "cifs",
      "svm": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "svm1",
        "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
      },
      "unix_user": "root",
      "windows_user": "cifs1/administrator"
    },
    "index": "1",
    "node": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "node1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "reason": {
```

```

    "message": "Access is allowed because the operation is trusted
and no security is configured."
  },
  "session_id": "2628976282477527056",
  "share": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "sh1"
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "volume": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}
}

```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

collection\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm\_reference

SVM, applies only to SVM-scoped objects.

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

file\_access\_filter

ONTAP allows creation of filters for file access tracing for both CIFS and NFS. These filters have protocols, path, username and client IP based on which file access operations are logged.

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.

Name	Type	Description
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.

#### node

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	
uuid	string	

#### reason

Displays the allowed or denied reason for the file access tracing events that are generated.

Name	Type	Description
message	string	The error message.

## share

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	Share name

## volume

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the volume.
uuid	string	Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move. <ul style="list-style-type: none"><li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li><li>• Introduced in: 9.6</li></ul>

## file\_access\_event

ONTAP generates the list of file access tracing records stored on the cluster. These records are generated in response to security trace filters applied. The list of trace events recorded depends on the parameters configured for the filter.

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
create_time	string	Specifies the time at which the trace event entry was generated.
filter	<a href="#">file_access_filter</a>	ONTAP allows creation of filters for file access tracing for both CIFS and NFS. These filters have protocols, path, username and client IP based on which file access operations are logged. <ul style="list-style-type: none"><li>• Introduced in: 9.8</li></ul>
index	integer	Specifies the sequence number of the security trace event.
node	<a href="#">node</a>	

Name	Type	Description
reason	<a href="#">reason</a>	Displays the allowed or denied reason for the file access tracing events that are generated.
session_id	integer	Specifies the CIFS session ID for the file access trace event, this is generated only for CIFS file accesses.
share	<a href="#">share</a>	
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
volume	<a href="#">volume</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Delete trace results

```
DELETE /protocols/file-access-tracing/events/{node.uuid}/{svm.uuid}/{index}
```

**Introduced In:** 9.8

Deletes trace results.



## Related ONTAP commands

- `vserver security trace result delete`

## Parameters

Name	Type	In	Required	Description
node.uuid	string	path	True	Node UUID.
index	integer	path	True	Sequence number of traced event.
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Response

Status: 200, Ok

## Error

Status: Default, Error

Name	Type	Description
error	<a href="#">error</a>	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

### See Definitions

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve trace results

GET /protocols/file-access-tracing/events/{node.uuid}/{svm.uuid}/{index}

**Introduced In:** 9.8

Retrieves trace results for the specified sequence number.

### Related ONTAP commands

- `vserver security trace trace-result show`

### Parameters

Name	Type	In	Required	Description
node.uuid	string	path	True	Node UUID.
index	integer	path	True	Sequence number of traced event.

Name	Type	In	Required	Description
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
create_time	string	Specifies the time at which the trace event entry was generated.
filter	<a href="#">file_access_filter</a>	<p>ONTAP allows creation of filters for file access tracing for both CIFS and NFS. These filters have protocols, path, username and client IP based on which file access operations are logged.</p> <ul style="list-style-type: none"> <li>Introduced in: 9.8</li> </ul>
index	integer	Specifies the sequence number of the security trace event.
node	<a href="#">node</a>	
reason	<a href="#">reason</a>	Displays the allowed or denied reason for the file access tracing events that are generated.
session_id	integer	Specifies the CIFS session ID for the file access trace event, this is generated only for CIFS file accesses.
share	<a href="#">share</a>	
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
volume	<a href="#">volume</a>	

## Example response

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "create_time": "2018-06-04T19:00:00Z",
  "filter": {
    "client_ip": "10.140.68.143",
    "index": "1",
    "path": "/dir1/dir2",
    "protocol": "cifs",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "unix_user": "root",
    "windows_user": "cifs1/administrator"
  },
  "index": "1",
  "node": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "node1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "reason": {
    "message": "Access is allowed because the operation is trusted and no security is configured."
  },
  "session_id": "2628976282477527056",
  "share": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  }
}
```

```
    },
    "name": "sh1"
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "volume": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "volume1",
    "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm\_reference

SVM, applies only to SVM-scoped objects.

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

file\_access\_filter

ONTAP allows creation of filters for file access tracing for both CIFS and NFS. These filters have protocols, path, username and client IP based on which file access operations are logged.

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.

Name	Type	Description
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.

#### node

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	
uuid	string	

#### reason

Displays the allowed or denied reason for the file access tracing events that are generated.

Name	Type	Description
message	string	The error message.

#### share

Name	Type	Description
_links	<a href="#">_links</a>	



Name	Type	Description
name	string	Share name

volume

Name	Type	Description
<a href="#">_links</a>	<a href="#">_links</a>	
name	string	The name of the volume.
uuid	string	<p>Unique identifier for the volume. This corresponds to the instance-uuid that is exposed in the CLI and ONTAPI. It does not change due to a volume move.</p> <ul style="list-style-type: none"> <li>• example: 028baa66-41bd-11e9-81d5-00a0986138f7</li> <li>• Introduced in: 9.6</li> </ul>

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Retrieve security trace filter entry information

GET /protocols/file-access-tracing/filters

## Introduced In: 9.8

Retrieves information about security trace filter entries.

## Related ONTAP commands

- `vserver security trace filter show`

## Parameters

Name	Type	In	Required	Description
trace_allowed_ops	boolean	query	False	Filter by trace_allowed_ops
unix_user	string	query	False	Filter by unix_user
index	integer	query	False	Filter by index
client_ip	string	query	False	Filter by client_ip
svm.uuid	string	query	False	Filter by svm.uuid
svm.name	string	query	False	Filter by svm.name
enabled	boolean	query	False	Filter by enabled
windows_user	string	query	False	Filter by windows_user
path	string	query	False	Filter by path
protocol	string	query	False	Filter by protocol
fields	array[string]	query	False	Specify the fields to return.
max_records	integer	query	False	Limit the number of records returned.
return_records	boolean	query	False	The default is true for GET calls. When set to false, only the number of records is returned. <ul style="list-style-type: none"><li>• Default value: 1</li></ul>

Name	Type	In	Required	Description
return_timeout	integer	query	False	<p>The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.</p> <ul style="list-style-type: none"> <li>• Default value: 1</li> <li>• Max value: 120</li> <li>• Min value: 0</li> </ul>
order_by	array[string]	query	False	Order results by specified fields and optional [asc

## Response

Status: 200, Ok

Name	Type	Description
_links	<a href="#">collection_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">file_access_filter</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "client_ip": "10.140.68.143",
    "index": "1",
    "path": "/dir1/dir2",
    "protocol": "cifs",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "unix_user": "root",
    "windows_user": "cifs1/administrator"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

collection\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm\_reference

SVM, applies only to SVM-scoped objects.

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

file\_access\_filter

ONTAP allows creation of filters for file access tracing for both CIFS and NFS. These filters have protocols, path, username and client IP based on which file access operations are logged.

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.

Name	Type	Description
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code

Name	Type	Description
message	string	Error message
target	string	The target parameter that caused the error.

## Create security trace filter entries

POST /protocols/file-access-tracing/filters

Introduced In: 9.8

Creates security trace filter entries.

### Related ONTAP commands

- `vserver security trace filter create`

### Parameters

Name	Type	In	Required	Description
return_records	boolean	query	False	The default is false. If set to true, the records are returned.  • Default value:

### Request Body

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.



Name	Type	Description
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.

## Example request

```
{
  "client_ip": "10.140.68.143",
  "index": "1",
  "path": "/dir1/dir2",
  "protocol": "cifs",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resource/link"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "unix_user": "root",
  "windows_user": "cifs1/administrator"
}
```

## Response

Status: 201, Created

Name	Type	Description
_links	<a href="#">collection_links</a>	
num_records	integer	Number of records
records	array[ <a href="#">file_access_filter</a> ]	

## Example response

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "client_ip": "10.140.68.143",
    "index": "1",
    "path": "/dir1/dir2",
    "protocol": "cifs",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "unix_user": "root",
    "windows_user": "cifs1/administrator"
  }
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm\_reference

SVM, applies only to SVM-scoped objects.

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

file\_access\_filter

ONTAP allows creation of filters for file access tracing for both CIFS and NFS. These filters have protocols, path, username and client IP based on which file access operations are logged.

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.

Name	Type	Description
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.

#### collection\_links

Name	Type	Description
next	<a href="#">href</a>	
self	<a href="#">href</a>	

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments

Name	Type	Description
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

## Update security trace filter entries

PATCH /protocols/file-access-tracing/filters/{svm.uuid}/{index}

**Introduced In:** 9.8

Updates security trace filter entries.

### Related ONTAP commands

- `vserver security trace filter modify`

### Parameters

Name	Type	In	Required	Description
index	integer	path	True	Filter index.
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

### Request Body

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.

Name	Type	Description
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.



## Example request

```
{
  "client_ip": "10.140.68.143",
  "index": "1",
  "path": "/dir1/dir2",
  "protocol": "cifs",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "unix_user": "root",
  "windows_user": "cifs1/administrator"
}
```

## Response

Status: 200, Ok

## Error

Status: Default, Error

Name	Type	Description
error	error	

## Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm\_reference

SVM, applies only to SVM-scoped objects.

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

file\_access\_filter

ONTAP allows creation of filters for file access tracing for both CIFS and NFS. These filters have protocols, path, username and client IP based on which file access operations are logged.

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.

Name	Type	Description
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

# Retrieve security trace filter entry information

GET /protocols/file-access-tracing/filters/{svm.uuid}/{index}

Introduced In: 9.8

Retrieves information about security trace filter entries.

## Related ONTAP commands

- `vserver security trace filter show`

## Parameters

Name	Type	In	Required	Description
index	integer	path	True	
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.
fields	array[string]	query	False	Specify the fields to return.

## Response

Status: 200, Ok

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.

Name	Type	Description
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.

### Example response

```
{
  "client_ip": "10.140.68.143",
  "index": "1",
  "path": "/dir1/dir2",
  "protocol": "cifs",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resource/link"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "unix_user": "root",
  "windows_user": "cifs1/administrator"
}
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm\_reference

SVM, applies only to SVM-scoped objects.

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.



# Update security trace filter entries

PATCH /protocols/file-access-tracing/filters/{svm.uuid}/{index}

Introduced In: 9.8

Updates security trace filter entries.

## Related ONTAP commands

- `vserver security trace filter modify`

## Parameters

Name	Type	In	Required	Description
index	integer	path	True	Filter index.
svm.uuid	string	path	True	UUID of the SVM to which this object belongs.

## Request Body

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.

Name	Type	Description
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.

### Example request

```
{
  "client_ip": "10.140.68.143",
  "index": "1",
  "path": "/dir1/dir2",
  "protocol": "cifs",
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "unix_user": "root",
  "windows_user": "cifs1/administrator"
}
```

### Response

```
Status: 200, Ok
```

## Error

Status: Default, Error

Name	Type	Description
error	error	

### Example error

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

## See Definitions

href

Name	Type	Description
href	string	

\_links

Name	Type	Description
self	<a href="#">href</a>	

svm\_reference

SVM, applies only to SVM-scoped objects.

Name	Type	Description
_links	<a href="#">_links</a>	
name	string	The name of the SVM.
uuid	string	The unique identifier of the SVM.

file\_access\_filter

ONTAP allows creation of filters for file access tracing for both CIFS and NFS. These filters have protocols, path, username and client IP based on which file access operations are logged.

Name	Type	Description
client_ip	string	Specifies the IP address from which the client accesses the file or directory.
enabled	boolean	Specifies whether to enable or disable the filter. Filters are enabled by default and are deleted after 60 mins.
index	integer	Position of the file access tracing filter.
path	string	Specifies the path for which permission tracing can be applied. The value can be complete path from root of CIFS share or root of volume for NFS.

Name	Type	Description
protocol	string	Specifies the protocol for which permission trace is required.
svm	<a href="#">svm_reference</a>	SVM, applies only to SVM-scoped objects.
trace_allowed_ops	boolean	Specifies if the filter can trace file access denied and allowed events. The value of trace-allow is false by default, and it traces access denied events. The value is set to true for tracing access allowed events.
unix_user	string	Specifies the UNIX username whose access requests you want to trace. The filter would match only if the request is received with this user.
windows_user	string	Specifies the Windows username whose access requests you want to trace. The filter would match only if the request is received with this user.

#### error\_arguments

Name	Type	Description
code	string	Argument code
message	string	Message argument

#### error

Name	Type	Description
arguments	array[ <a href="#">error_arguments</a> ]	Message arguments
code	string	Error code
message	string	Error message
target	string	The target parameter that caused the error.

# View file security permissions

## Protocols file-security effective-permissions svm.uuid path endpoint overview

### Overview

This API displays the effective permission granted to a Windows or UNIX user on the specified file or folder path.

### Examples

Retrieving the effective permission for the specified Windows user on the specified path of an SVM.

= The API:

```
curl -X GET "https://10.63.26.252/api/protocols/file-security/effective-permissions/cf5f271a-1beb-11ea-8fad-005056bb645e/administrator/windows/%2F?share.name=sh1&return_records=true" -H "accept: application/json" -H "authorization: Basic YWRtaW46bmV0YXBwMSE="
```

= The response:

```
{
  "svm": {
    "uuid": "cf5f271a-1beb-11ea-8fad-005056bb645e",
    "name": "vs1"
  },
  "user": "administrator",
  "type": "windows",
  "path": "/",
  "share": {
    "path": "/"
  },
  "file_permission": [
    "read",
    "write",
    "append",
    "read_ea",
    "write_ea",
    "execute",
    "delete_child",
    "read_attributes",
    "write_attributes",
    "delete",
    "read_control",
    "write_dac",
```

```

    "write_owner",
    "synchronize",
    "system_security"
  ],
  "share_permission": [
    "read",
    "read_ea",
    "execute",
    "read_attributes",
    "read_control",
    "synchronize"
  ]
}

```

```

[[ID64b7077825058ba43fdf1ab01dacf8ef]]
= Retrieve effective security permissions on a file

```

```

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/file-security/effective-permissions/{svm.uuid}/{path}`#

```

\*Introduced In:\* 9.8

Retrieves effective security permissions on a file.

== Related ONTAP commands

\* `vserver security file-directory show-effective-permissions`

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```

|Name
|Type
|In
|Required
|Description

```

```

|path
|string
|path

```

```
|True
a|File Path

|user
|string
|query
|True
a|User_Name

|share.name
|string
|query
|False
a|Share Name

|type
|string
|query
|False
a|User Type

|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
```



```
|Name
|Type
|Description

|file_permissions
|array[string]
a|Specifies the effective permission granted to a user on the specified
file or folder path.

|path
|string
a|Specifies the path of the file or the folder for which you want to
display effective permissions.
The path is relative to the SVM root volume. If "-share-name" is specified
then path will be relative to the share path.

|share
|link:#share[share]
a|

|share_permissions
|array[string]
a|Specifies the effective permission granted to a user on the specified
file or folder path.

|svm
|link:#svm_reference[svm_reference]
a|SVM, applies only to SVM-scoped objects.

|type
|string
a|Specifies the user type. The following values are allowed:

* windows - Windows user
* unix    - UNIX user

|user
|string
a|Specifies the user for which effective permission needs to be displayed
for the specified path.
```

```

|===

.Example response
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "file_permissions": {
  },
  "path": "/dir1/dir2",
  "share_permissions": {
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  },
  "type": "windows",
  "user": "cifsl/administrator"
}
=====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]

```

```

=====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====

```

```

[#share]
[.api-collapsible-fifth-title]
share

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|name
|string
a|Displays the file or directory effective permission for the mentioned
user, only for files and directories contained where the
specified path is relative to the root of the specified share. If this
parameter is not specified, the SVM root volume is
taken as the default. If this parameter is specified, the effective share
permission of the user is also displayed.
Wildcard query characters are not supported.

```

```

|path
|string
a|Displays the CIFS share path.

```

```

|===

[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#svm_reference]
[.api-collapsible-fifth-title]
svm_reference

SVM, applies only to SVM-scoped objects.

[cols=3*,options=header]
|===

```

```
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

:leveloffset: -1

= Manage FPolicy configuration

:leveloffset: +1

[[ID5228e9e7e677ccb4975d462619a25506]]
= Protocols fpolicy endpoint overview

```

## == Overview

FPolicy is an infrastructure component of ONTAP that enables partner applications to connect to ONTAP in order to monitor and set file access permissions. Every time a client accesses a file from a storage system, based on the configuration of FPolicy, the partner application is notified about file access. This enables partners to set restrictions on files that are created or accessed on the storage system. FPolicy also allows you to create file policies that specify file operation permissions according to file type. For example, you can restrict certain file types, such as .jpeg and .mp3 files, from being stored on the storage system. FPolicy can monitor file access from CIFS and NFS clients.

As part of FPolicy configuration, you can specify an FPolicy engine which defines the external FPolicy server, FPolicy events, which defines the protocol and file operations to monitor and the FPolicy policy that acts as a container for the FPolicy engine and FPolicy events. It provides a way for policy management functions, such as policy enabling and disabling.

## == Examples

### === Creating an FPolicy configuration

To create an FPolicy for an SVM use the following API. Note that the `_return_records=true_` query parameter is used to obtain the newly created entry in the response.

----

# The API:

```
POST /protocols/fpolicy/
```

#The call:

```
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy?return_records=true"
-H "accept: application/json" -H "Content-Type: application/json" -d "{
  \"engines\": [ { \"name\": \"engine1\", \"port\": 9876,
  \"primary_servers\": [ \"10.132.145.22\", \"10.140.101.109\" ],
  \"secondary_servers\": [ \"10.132.145.20\", \"10.132.145.21\" ], \"type\":
  \"synchronous\" } ], \"events\": [ { \"file_operations\": { \"read\":
  true, \"write\": true }, \"filters\": { \"monitor_ads\": true }, \"name\":
  \"event_cifs\", \"protocol\": \"cifs\", \"volume_monitoring\": true } ],
  \"policies\": [ { \"engine\": { \"name\": \"engine1\" }, \"events\": [ {
  \"name\": \"event_cifs\" } ], \"mandatory\": true, \"name\": \"pol0\",
  \"priority\": 1, \"scope\": { \"include_volumes\": [ \"vol1\" ] } } ],
```

```
\\"svm\\": { \\"name\\": \\"vs1\\", \\"uuid\\": \\"b34f5e3d-01d0-11e9-8f63-0050568ea311\\" } }"
```

```
# The response:
```

```
{  
  "num_records": 1,  
  "records": [  
    {  
      "svm": {  
        "uuid": "b34f5e3d-01d0-11e9-8f63-0050568ea311",  
        "name": "vs1"  
      },  
      "engines": [  
        {  
          "name": "engine1",  
          "primary_servers": [  
            "10.132.145.22",  
            "10.140.101.109"  
          ],  
          "secondary_servers": [  
            "10.132.145.20",  
            "10.132.145.21"  
          ],  
          "type": "synchronous",  
          "port": 9876  
        }  
      ],  
      "events": [  
        {  
          "name": "event_cifs",  
          "protocol": "cifs",  
          "volume_monitoring": true,  
          "file_operations": {  
            "read": true,  
            "write": true  
          },  
          "filters": {  
            "monitor_ads": true  
          }  
        }  
      ],  
      "policies": [  
        {  
          "name": "pol0",  
          "priority": 1,  
          "events": [  

```



```

        {
            "name": "event_cifs"
        }
    ],
    "engine": {
        "name": "engine1"
    },
    "scope": {
        "include_volumes": [
            "voll"
        ]
    },
    "mandatory": true
}
]
}
]
}
----

'''

=== Retrieving the FPolicy configuration for all the SVMs in the cluster

'''

----

# The API:
GET /protocols/fpolicy

# The call:
curl -X GET "https://<mgmt-
ip>/api/protocols/fpolicy?fields=*&return_records=true&return_timeout=15"
-H "accept: application/json"

# The response:
{
"records": [
    {
        "svm": {
            "uuid": "b34f5e3d-01d0-11e9-8f63-0050568ea311",
            "name": "vs1"
        },
        "engines": [
            {

```

```

    "name": "engine1",
    "primary_servers": [
      "10.132.145.22",
      "10.140.101.109"
    ],
    "secondary_servers": [
      "10.132.145.20",
      "10.132.145.21"
    ],
    "type": "synchronous",
    "port": 9876
  }
],
"events": [
  {
    "name": "event_cifs",
    "protocol": "cifs",
    "volume_monitoring": true,
    "file_operations": {
      "close": false,
      "create": false,
      "create_dir": false,
      "delete": false,
      "delete_dir": false,
      "getattr": false,
      "link": false,
      "lookup": false,
      "open": false,
      "read": true,
      "write": true,
      "rename": false,
      "rename_dir": false,
      "setattr": false,
      "symlink": false
    },
  },
  "filters": {
    "monitor_ads": true,
    "close_with_modification": false,
    "close_without_modification": false,
    "close_with_read": false,
    "first_read": false,
    "first_write": false,
    "offline_bit": false,
    "open_with_delete_intent": false,
    "open_with_write_intent": false,
    "write_with_size_change": false,
  }
]

```

```

    "setattr_with_owner_change": false,
    "setattr_with_group_change": false,
    "setattr_with_sacl_change": false,
    "setattr_with_dacl_change": false,
    "setattr_with_modify_time_change": false,
    "setattr_with_access_time_change": false,
    "setattr_with_creation_time_change": false,
    "setattr_with_mode_change": false,
    "setattr_with_size_change": false,
    "setattr_with_allocation_size_change": false,
    "exclude_directory": false
  }
}
],
"policies": [
  {
    "name": "pol0",
    "enabled": true,
    "priority": 1,
    "events": [
      {
        "name": "event_cifs"
      }
    ],
    "engine": {
      "name": "engine1"
    },
    "scope": {
      "include_volumes": [
        "vol1"
      ]
    },
    "mandatory": true
  }
]
}
],
"num_records": 1
}
----

'''

=== Retrieving an FPolicy configuration for a particular SVM

'''

```

----

# The API:

```
GET /protocols/fpolicy/{svm.uuid}
```

# The call:

```
curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/b34f5e3d-01d0-11e9-8f63-0050568ea311?fields=*&return_records=true&return_timeout=15" -H "accept: application/json"
```

# The response:

```
{
  "svm": {
    "uuid": "b34f5e3d-01d0-11e9-8f63-0050568ea311",
    "name": "vs1"
  },
  "engines": [
    {
      "name": "engine1",
      "primary_servers": [
        "10.132.145.22",
        "10.140.101.109"
      ],
      "secondary_servers": [
        "10.132.145.20",
        "10.132.145.21"
      ],
      "type": "synchronous",
      "port": 9876
    }
  ],
  "events": [
    {
      "name": "event_cifs",
      "protocol": "cifs",
      "volume_monitoring": true,
      "file_operations": {
        "close": false,
        "create": false,
        "create_dir": false,
        "delete": false,
        "delete_dir": false,
        "getattr": false,
        "link": false,
        "lookup": false,

```

```

    "open": false,
    "read": true,
    "write": true,
    "rename": false,
    "rename_dir": false,
    "setattr": false,
    "symlink": false
  },
  "filters": {
    "monitor_ads": true,
    "close_with_modification": false,
    "close_without_modification": false,
    "close_with_read": false,
    "first_read": false,
    "first_write": false,
    "offline_bit": false,
    "open_with_delete_intent": false,
    "open_with_write_intent": false,
    "write_with_size_change": false,
    "setattr_with_owner_change": false,
    "setattr_with_group_change": false,
    "setattr_with_sacl_change": false,
    "setattr_with_dacl_change": false,
    "setattr_with_modify_time_change": false,
    "setattr_with_access_time_change": false,
    "setattr_with_creation_time_change": false,
    "setattr_with_mode_change": false,
    "setattr_with_size_change": false,
    "setattr_with_allocation_size_change": false,
    "exclude_directory": false
  }
}
],
"policies": [
  {
    "name": "pol0",
    "enabled": true,
    "priority": 1,
    "events": [
      {
        "name": "event_cifs"
      }
    ],
    "engine": {
      "name": "engine1"
    }
  },

```

```

    "scope": {
      "include_volumes": [
        "vol1"
      ]
    },
    "mandatory": true
  }
]
}
-----

'''

=== Deleting an FPolicy configuration for a particular SVM

'''

-----

# The API:
DELETE /protocols/fpolicy/{svm.uuid}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/fpolicy/b34f5e3d-01d0-
11e9-8f63-0050568ea311" -H "accept: application/json"
-----

'''

[[ID29c612fe57d9aa37fe92f467ac25b914]]
= Retrieve an FPolicy configuration

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/fpolicy`#

*Introduced In:* 9.6

Retrieves an FPolicy configuration.

== Related ONTAP commands

* `fpolicy show`
* `fpolicy policy show`

```

```
* `fpolicy policy scope show`  
* `fpolicy policy event show`  
* `fpolicy policy external-engine show`
```

== Learn more

```
* xref:{relative_path}protocols_fpolicy_endpoint_overview.html [DOC  
/protocols/fpolicy]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|engines.secondary_servers
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by engines.secondary_servers
```

```
|engines.port
```

```
|integer
```

```
|query
```

```
|False
```

```
a|Filter by engines.port
```

```
|engines.type
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by engines.type
```

```
|engines.name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by engines.name
```

```
|engines.primary_servers
|string
|query
|False
a|Filter by engines.primary_servers
```

```
|policies.priority
|integer
|query
|False
a|Filter by policies.priority
```

```
|policies.engine.name
|string
|query
|False
a|Filter by policies.engine.name
```

```
|policies.events.name
|string
|query
|False
a|Filter by policies.events.name
```

```
|policies.scope.include_shares
|string
|query
|False
a|Filter by policies.scope.include_shares
```

```
|policies.scope.include_extension
|string
|query
|False
a|Filter by policies.scope.include_extension
```

```
|policies.scope.include_volumes
|string
|query
```



```
|False
a|Filter by policies.scope.include_volumes

|policies.scope.include_export_policies
|string
|query
|False
a|Filter by policies.scope.include_export_policies

|policies.scope.exclude_export_policies
|string
|query
|False
a|Filter by policies.scope.exclude_export_policies

|policies.scope.exclude_shares
|string
|query
|False
a|Filter by policies.scope.exclude_shares

|policies.scope.exclude_volumes
|string
|query
|False
a|Filter by policies.scope.exclude_volumes

|policies.scope.exclude_extension
|string
|query
|False
a|Filter by policies.scope.exclude_extension

|policies.name
|string
|query
|False
a|Filter by policies.name

|policies.enabled
```

```
|boolean  
|query  
|False  
a|Filter by policies.enabled
```

```
|policies.mandatory  
|boolean  
|query  
|False  
a|Filter by policies.mandatory
```

```
|events.protocol  
|string  
|query  
|False  
a|Filter by events.protocol
```

```
|events.name  
|string  
|query  
|False  
a|Filter by events.name
```

```
|events.filters.close_with_modification  
|boolean  
|query  
|False  
a|Filter by events.filters.close_with_modification
```

```
|events.filters.close_without_modification  
|boolean  
|query  
|False  
a|Filter by events.filters.close_without_modification
```

```
|events.filters.offline_bit  
|boolean  
|query  
|False  
a|Filter by events.filters.offline_bit
```

```
|events.filters.write_with_size_change
|boolean
|query
|False
a|Filter by events.filters.write_with_size_change
```

```
|events.filters.setattr_with_creation_time_change
|boolean
|query
|False
a|Filter by events.filters.setattr_with_creation_time_change
```

```
|events.filters.setattr_with_size_change
|boolean
|query
|False
a|Filter by events.filters.setattr_with_size_change
```

```
|events.filters.open_with_delete_intent
|boolean
|query
|False
a|Filter by events.filters.open_with_delete_intent
```

```
|events.filters.setattr_with_owner_change
|boolean
|query
|False
a|Filter by events.filters.setattr_with_owner_change
```

```
|events.filters.setattr_with_access_time_change
|boolean
|query
|False
a|Filter by events.filters.setattr_with_access_time_change
```

```
|events.filters.setattr_with_group_change
|boolean
|query
|False
```

```
a|Filter by events.filters.setattr_with_group_change
```

```
|events.filters.setattr_with_dacl_change
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by events.filters.setattr_with_dacl_change
```

```
|events.filters.setattr_with_allocation_size_change
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by events.filters.setattr_with_allocation_size_change
```

```
|events.filters.exclude_directory
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by events.filters.exclude_directory
```

```
|events.filters.open_with_write_intent
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by events.filters.open_with_write_intent
```

```
|events.filters.monitor_ads
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by events.filters.monitor_ads
```

```
|events.filters.setattr_with_mode_change
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by events.filters.setattr_with_mode_change
```

```
|events.filters.setattr_with_sacl_change
```

```
|boolean
```

```
|query
|False
a|Filter by events.filters.setattr_with_sacl_change

|events.filters.setattr_with_modify_time_change
|boolean
|query
|False
a|Filter by events.filters.setattr_with_modify_time_change

|events.filters.first_read
|boolean
|query
|False
a|Filter by events.filters.first_read

|events.filters.close_with_read
|boolean
|query
|False
a|Filter by events.filters.close_with_read

|events.filters.first_write
|boolean
|query
|False
a|Filter by events.filters.first_write

|events.volume_monitoring
|boolean
|query
|False
a|Filter by events.volume_monitoring

|events.file_operations.close
|boolean
|query
|False
a|Filter by events.file_operations.close
```

```
|events.file_operations.lookup
|boolean
|query
|False
a|Filter by events.file_operations.lookup

|events.file_operations.delete_dir
|boolean
|query
|False
a|Filter by events.file_operations.delete_dir

|events.file_operations.create_dir
|boolean
|query
|False
a|Filter by events.file_operations.create_dir

|events.file_operations.create
|boolean
|query
|False
a|Filter by events.file_operations.create

|events.file_operations.setattr
|boolean
|query
|False
a|Filter by events.file_operations.setattr

|events.file_operations.getattr
|boolean
|query
|False
a|Filter by events.file_operations.getattr

|events.file_operations.delete
|boolean
|query
|False
a|Filter by events.file_operations.delete
```

```
|events.file_operations.symlink
|boolean
|query
|False
a|Filter by events.file_operations.symlink
```

```
|events.file_operations.rename
|boolean
|query
|False
a|Filter by events.file_operations.rename
```

```
|events.file_operations.open
|boolean
|query
|False
a|Filter by events.file_operations.open
```

```
|events.file_operations.read
|boolean
|query
|False
a|Filter by events.file_operations.read
```

```
|events.file_operations.rename_dir
|boolean
|query
|False
a|Filter by events.file_operations.rename_dir
```

```
|events.file_operations.link
|boolean
|query
|False
a|Filter by events.file_operations.link
```

```
|events.file_operations.write
|boolean
|query
```

```
|False
a|Filter by events.file_operations.write

|svm.uuid
|string
|query
|False
a|Filter by svm.uuid

|svm.name
|string
|query
|False
a|Filter by svm.name

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|max_records
|integer
|query
|False
a|Limit the number of records returned.

|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.

* Default value: 1

|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
```



When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.

- \* Default value: 1
- \* Max value: 120
- \* Min value: 0

```
|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.
```

```
|===
```

```
== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#fpolicy[fpolicy]]
a|

|===
```

.Example response  
[%collapsible%closed]

```

====
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "engines": {
      "name": "fp_ex_eng",
      "port": "9876",
      "primary_servers": [
        "10.132.145.20",
        "10.140.101.109"
      ],
      "secondary_servers": [
        "10.132.145.20",
        "10.132.145.21"
      ],
      "type": "synchronous"
    },
    "events": {
      "name": "event_nfs_close",
      "protocol": "cifs"
    },
    "policies": {
      "engine": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        }
      }
    },
    "events": [
      "event_nfs_close",
      "event_open"
    ],

```

```

"name": "fp_policy_1",
"scope": {
  "exclude_export_policies": {
  },
  "exclude_extension": {
  },
  "exclude_shares": {
  },
  "exclude_volumes": [
    "voll",
    "vol_svm1",
    "*"
  ],
  "include_export_policies": {
  },
  "include_extension": {
  },
  "include_shares": [
    "sh1",
    "share_cifs"
  ],
  "include_volumes": [
    "voll",
    "vol_svm1"
  ]
}
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
}
====

== Error

```

Status: Default, Error

[cols=3\*,options=header]

```

|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:href[href]
a|

|===

[#fpolicy_engine]
[.api-collapsible-fifth-title]

```

## fpolicy\_engine

The engine defines how ONTAP makes and manages connections to external FPolicy servers.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|name
```

```
|string
```

```
a|Specifies the name to assign to the external server configuration.
```

```
|port
```

```
|integer
```

```
a|Port number of the FPolicy server application.
```

```
|primary_servers
```

```
|array[string]
```

```
a|
```

```
|secondary_servers
```

```
|array[string]
```

```
a|
```

```
|type
```

```
|string
```

```
a|The notification mode determines what ONTAP does after sending notifications to FPolicy servers.
```

```
The possible values are:
```

```
***** synchronous - After sending a notification, wait for a response from the FPolicy server.
```

```
***** asynchronous - After sending a notification, file request processing continues.
```

```
* Default value: 1
```

```
* enum: ["synchronous", "asynchronous"]
```

```
* Introduced in: 9.6
```

```
|===
```

```
[#file_operations]  
[.api-collapsible-fifth-title]  
file_operations
```

Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.  
The event will check the operations specified from all client requests using the protocol.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|close  
|boolean  
a|File close operations
```

```
|create  
|boolean  
a|File create operations
```

```
|create_dir  
|boolean  
a|Directory create operations
```

```
|delete  
|boolean  
a|File delete operations
```

```
|delete_dir  
|boolean  
a|Directory delete operations
```

```
|getattr  
|boolean  
a|Get attribute operations
```

|link  
|boolean  
a|Link operations

|lookup  
|boolean  
a|Lookup operations

|open  
|boolean  
a|File open operations

|read  
|boolean  
a|File read operations

|rename  
|boolean  
a|File rename operations

|rename\_dir  
|boolean  
a|Directory rename operations

|setattr  
|boolean  
a|Set attribute operations

|symlink  
|boolean  
a|Symbolic link operations

|write  
|boolean  
a|File write operations



```
|===
```

```
[#filters]  
[.api-collapsible-fifth-title]  
filters
```

Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|close_with_modification
```

```
|boolean
```

```
a|Filter the client request for close with modification.
```

```
|close_with_read
```

```
|boolean
```

```
a|Filter the client request for close with read.
```

```
|close_without_modification
```

```
|boolean
```

```
a|Filter the client request for close without modification.
```

```
|exclude_directory
```

```
|boolean
```

```
a|Filter the client requests for directory operations. When this filter is specified directory operations are not monitored.
```

```
|first_read
```

```
|boolean
```

```
a|Filter the client requests for the first-read.
```

```
|first_write
```

```
|boolean
```

a|Filter the client requests for the first-write.

|monitor\_ads

|boolean

a|Filter the client request for alternate data stream.

|offline\_bit

|boolean

a|Filter the client request for offline bit set. FPolicy server receives notification only when offline files are accessed.

|open\_with\_delete\_intent

|boolean

a|Filter the client request for open with delete intent.

|open\_with\_write\_intent

|boolean

a|Filter the client request for open with write intent.

|setattr\_with\_access\_time\_change

|boolean

a|Filter the client setattr requests for changing the access time of a file or directory.

|setattr\_with\_allocation\_size\_change

|boolean

a|Filter the client setattr requests for changing the allocation size of a file.

|setattr\_with\_creation\_time\_change

|boolean

a|Filter the client setattr requests for changing the creation time of a file or directory.

|setattr\_with\_dacl\_change

|boolean

a|Filter the client setattr requests for changing dacl on a file or directory.

```
|setattr_with_group_change
|boolean
a|Filter the client setattr requests for changing group of a file or
directory.
```

```
|setattr_with_mode_change
|boolean
a|Filter the client setattr requests for changing the mode bits on a file
or directory.
```

```
|setattr_with_modify_time_change
|boolean
a|Filter the client setattr requests for changing the modification time of
a file or directory.
```

```
|setattr_with_owner_change
|boolean
a|Filter the client setattr requests for changing owner of a file or
directory.
```

```
|setattr_with_sacl_change
|boolean
a|Filter the client setattr requests for changing sacl on a file or
directory.
```

```
|setattr_with_size_change
|boolean
a|Filter the client setattr requests for changing the size of a file.
```

```
|write_with_size_change
|boolean
a|Filter the client request for write with size change.
```

```
|===
```

```
[#fpolicy_event]
[.api-collapsible-fifth-title]
fpolicy_event
```

The information that a FPolicy process needs to determine what file access operations to monitor and for which of the monitored events notifications should be sent to the external FPolicy server.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|file_operations
```

```
|link:#file_operations[file_operations]
```

a|Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.

The event will check the operations specified from all client requests using the protocol.

```
|filters
```

```
|link:#filters[filters]
```

a|Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

```
|name
```

```
|string
```

a|Specifies the name of the FPolicy event.

```
|protocol
```

```
|string
```

a|Protocol for which event is created. If you specify protocol, then you must also specify a valid value for the file operation parameters.

The value of this parameter must be one of the following:

```
***** cifs - for the CIFS protocol.
```

```
***** nfsv3 - for the NFSv3 protocol.
```

```
***** nfsv4 - for the NFSv4 protocol.
```

```
|volume_monitoring
```

```
|boolean  
a|Specifies whether volume operation monitoring is required.
```

```
|===
```

```
[#fpolicy_engine_reference]  
[.api-collapsible-fifth-title]  
fpolicy_engine_reference
```

FPolicy external engine

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|The name of the FPolicy external engine.
```

```
|===
```

```
[#fpolicy_event_reference]  
[.api-collapsible-fifth-title]  
fpolicy_event_reference
```

FPolicy events

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```

a|

|name
|string
a|

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_export_policies
|array[string]
a|

|exclude_extension
|array[string]
a|

|exclude_shares
|array[string]
a|

|exclude_volumes
|array[string]
a|

|include_export_policies
|array[string]
a|

|include_extension
|array[string]
a|

|include_shares
|array[string]
a|

```

```

|include_volumes
|array[string]
a|

|===

[#fpolicy_policy]
[.api-collapsible-fifth-title]
fpolicy_policy

[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Specifies if the policy is enabled on the SVM or not. If no value is
mentioned for this field but priority is set, then this policy will be
enabled.

|engine
|link:#fpolicy_engine_reference[fpolicy_engine_reference]
a|FPolicy external engine

|events
|array[link:#fpolicy_event_reference[fpolicy_event_reference]]
a|

|mandatory
|boolean
a|Specifies what action to take on a file access event in a case when all
primary and secondary servers are down or no response is received from the
FPolicy servers within a given timeout period. When this parameter is set
to true, file access events will be denied under these circumstances.

|name
|string
a|Specifies the name of the policy.

|priority

```

```
|integer
a|Specifies the priority that is assigned to this policy.
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

```
[#svm]
[.api-collapsible-fifth-title]
svm
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|name
|string
a|The name of the SVM.
```

```
|uuid
|string
a|The unique identifier of the SVM.
```

```
|===
```

```
[#fpolicy]
[.api-collapsible-fifth-title]
fpolicy
```

FPolicy is an infrastructure component of ONTAP that enables partner applications connected to your storage systems to monitor and set file access permissions. Every time a client accesses a file from a storage system, based on the configuration of FPolicy, the partner application is notified about file access.



```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|engines
|array[link:#fpolicy_engine[fpolicy_engine]]
a|

|events
|array[link:#fpolicy_event[fpolicy_event]]
a|

|policies
|array[link:#fpolicy_policy[fpolicy_policy]]
a|

|svm
|link:#svm[svm]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message

```

```

|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDf0a80616ae12512d2d8c1ceec057c587]]
= Create an FPolicy configuration

```

```
[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-block]#\protocols/fpolicy`#
```

\*Introduced In:\* 9.6

Creates an FPolicy configuration.

== Required properties

\* `svm.uuid` or `svm.name` - Existing SVM in which to create the FPolicy configuration.

== Recommended optional properties

\* `engines` - External server to which the notifications will be sent.

\* `events` - File operations to monitor.

\* `policies` - Policy configuration which acts as a container for FPolicy event and FPolicy engine.

\* `scope` - Scope of the policy. Can be limited to exports, volumes, shares or file extensions.

== Default property values

If not specified in POST, the following default property values are assigned:

\* `engines.type` - `__synchronous__`

\* `policies.engine` - `__native__`

\* `policies.mandatory` - `__true__`

\* `events.volume\_monitoring` - `__false__`

\* `events.file\_operations.+++` - `__false__`

\* `events.filters.+++` - `__false__`

== Related ONTAP commands

\* `fpolicy policy event create`

\* `fpolicy policy external-engine create`

\* `fpolicy policy create`

\* `fpolicy policy scope create`

\* `fpolicy enable`

== Learn more

\* xref:{relative\_path}protocols\_fpolicy\_endpoint\_overview.html[DOC /protocols/fpolicy]

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|return_records
```

```
|boolean
```

```
|query
```

```
|False
```

a|The default is false. If set to true, the records are returned.

\* Default value:

```
|===
```

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
 |_links
```

```
 |link:#_links[_links]
```

a|

```
 |engines
```

```
 |array[link:#fpolicy_engine[fpolicy_engine]]
```

a|

```
 |events
```

```
 |array[link:#fpolicy_event[fpolicy_event]]
```

a|

```
 |policies
```

```
 |array[link:#fpolicy_policy[fpolicy_policy]]
```

a|

```

|svm
|link:#svm[svm]
a|

|===

.Example request
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "engines": {
    "name": "fp_ex_eng",
    "port": "9876",
    "primary_servers": [
      "10.132.145.20",
      "10.140.101.109"
    ],
    "secondary_servers": [
      "10.132.145.20",
      "10.132.145.21"
    ],
    "type": "synchronous"
  },
  "events": {
    "name": "event_nfs_close",
    "protocol": "cifs"
  },
  "policies": {
    "engine": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      }
    }
  },
  "events": [
    "event_nfs_close",
    "event_open"
  ]
}

```

```

],
"name": "fp_policy_1",
"scope": {
  "exclude_export_policies": {
  },
  "exclude_extension": {
  },
  "exclude_shares": {
  },
  "exclude_volumes": [
    "vol1",
    "vol_svm1",
    "*"
  ],
  "include_export_policies": {
  },
  "include_extension": {
  },
  "include_shares": [
    "sh1",
    "share_cifs"
  ],
  "include_volumes": [
    "vol1",
    "vol_svm1"
  ]
}
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
====

```

== Response

Status: 201, Created

[cols=3\*,options=header]

```

|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#fpolicy[fpolicy]]
a|

|===

.Example response
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "engines": {
      "name": "fp_ex_eng",
      "port": "9876",
      "primary_servers": [
        "10.132.145.20",
        "10.140.101.109"
      ]
    }
  }
}

```

```

    ],
    "secondary_servers": [
        "10.132.145.20",
        "10.132.145.21"
    ],
    "type": "synchronous"
},
"events": {
    "name": "event_nfs_close",
    "protocol": "cifs"
},
"policies": {
    "engine": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        }
    },
    "events": [
        "event_nfs_close",
        "event_open"
    ],
    "name": "fp_policy_1",
    "scope": {
        "exclude_export_policies": {
        },
        "exclude_extension": {
        },
        "exclude_shares": {
        },
        "exclude_volumes": [
            "voll",
            "vol_svm1",
            "*"
        ],
        "include_export_policies": {
        },
        "include_extension": {
        },
        "include_shares": [
            "sh1",
            "share_cifs"
        ],
        "include_volumes": [
            "voll",

```



```

        "vol_svm1"
    ]
}
},
"svm": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
}
====

```

== Error

#### Status: Default

##### ONTAP Error Response Codes

```

|===
| Error Code | Description

| 9765032
| The FPolicy engine, FPolicy event or FPolicy policy specified already
exists

| 9765031
| If any of the FPolicy engine, FPolicy event, or FPolicy policy creation
fails due to a systematic error or hardware failure, the cause of the
failure is detailed in the error message

| 2621706
| The SVM UUID specified belongs to different SVM

| 2621462
| The SVM name specified does not exist
|===

```

[cols=3\*,options=header]

|===

```

|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href

```

```
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|self
|link:#href[href]
a|
```

```
|===
```

```
[#fpolicy_engine]
[.api-collapsible-fifth-title]
fpolicy_engine
```

The engine defines how ONTAP makes and manages connections to external FPolicy servers.

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|name
|string
a|Specifies the name to assign to the external server configuration.
```

```
|port
|integer
a|Port number of the FPolicy server application.
```

```

|primary_servers
|array[string]
a|

|secondary_servers
|array[string]
a|

|type
|string
a|The notification mode determines what ONTAP does after sending
notifications to FPolicy servers.
The possible values are:

***** synchronous - After sending a notification, wait for a response
from the FPolicy server.

***** asynchronous - After sending a notification, file request processing
continues.

* Default value: 1
* enum: ["synchronous", "asynchronous"]
* Introduced in: 9.6

|===

[#file_operations]
[.api-collapsible-fifth-title]
file_operations

Specifies the file operations for the FPolicy event. You must specify a
valid protocol in the protocol parameter.
The event will check the operations specified from all client requests
using the protocol.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|close
|boolean
a|File close operations

```

|create  
|boolean  
a|File create operations

|create\_dir  
|boolean  
a|Directory create operations

|delete  
|boolean  
a|File delete operations

|delete\_dir  
|boolean  
a|Directory delete operations

|getattr  
|boolean  
a|Get attribute operations

|link  
|boolean  
a|Link operations

|lookup  
|boolean  
a|Lookup operations

|open  
|boolean  
a|File open operations

|read  
|boolean  
a|File read operations

```
|rename
|boolean
a|File rename operations
```

```
|rename_dir
|boolean
a|Directory rename operations
```

```
|setattr
|boolean
a|Set attribute operations
```

```
|symlink
|boolean
a|Symbolic link operations
```

```
|write
|boolean
a|File write operations
```

```
|===
```

```
[#filters]
[.api-collapsible-fifth-title]
filters
```

Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|close_with_modification
|boolean
```

```
a|Filter the client request for close with modification.
```

|close\_with\_read

|boolean

a|Filter the client request for close with read.

|close\_without\_modification

|boolean

a|Filter the client request for close without modification.

|exclude\_directory

|boolean

a|Filter the client requests for directory operations. When this filter is specified directory operations are not monitored.

|first\_read

|boolean

a|Filter the client requests for the first-read.

|first\_write

|boolean

a|Filter the client requests for the first-write.

|monitor\_ads

|boolean

a|Filter the client request for alternate data stream.

|offline\_bit

|boolean

a|Filter the client request for offline bit set. FPolicy server receives notification only when offline files are accessed.

|open\_with\_delete\_intent

|boolean

a|Filter the client request for open with delete intent.

|open\_with\_write\_intent

|boolean

a|Filter the client request for open with write intent.

|setattr\_with\_access\_time\_change

|boolean

a|Filter the client setattr requests for changing the access time of a file or directory.

|setattr\_with\_allocation\_size\_change

|boolean

a|Filter the client setattr requests for changing the allocation size of a file.

|setattr\_with\_creation\_time\_change

|boolean

a|Filter the client setattr requests for changing the creation time of a file or directory.

|setattr\_with\_dacl\_change

|boolean

a|Filter the client setattr requests for changing dacl on a file or directory.

|setattr\_with\_group\_change

|boolean

a|Filter the client setattr requests for changing group of a file or directory.

|setattr\_with\_mode\_change

|boolean

a|Filter the client setattr requests for changing the mode bits on a file or directory.

|setattr\_with\_modify\_time\_change

|boolean

a|Filter the client setattr requests for changing the modification time of a file or directory.

|setattr\_with\_owner\_change

|boolean

a|Filter the client setattr requests for changing owner of a file or



directory.

|setattr\_with\_sacl\_change

|boolean

a|Filter the client setattr requests for changing sacl on a file or directory.

|setattr\_with\_size\_change

|boolean

a|Filter the client setattr requests for changing the size of a file.

|write\_with\_size\_change

|boolean

a|Filter the client request for write with size change.

|===

[#fpolicy\_event]

[.api-collapsible-fifth-title]

fpolicy\_event

The information that a FPolicy process needs to determine what file access operations to monitor and for which of the monitored events notifications should be sent to the external FPolicy server.

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|file\_operations

|link:#file\_operations[file\_operations]

a|Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.

The event will check the operations specified from all client requests using the protocol.

|filters

|link:#filters[filters]

a|Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

|name

|string

a|Specifies the name of the FPolicy event.

|protocol

|string

a|Protocol for which event is created. If you specify protocol, then you must also specify a valid value for the file operation parameters.

The value of this parameter must be one of the following:

\*\*\*\*\* cifs - for the CIFS protocol.

\*\*\*\*\* nfsv3 - for the NFSv3 protocol.

\*\*\*\*\* nfsv4 - for the NFSv4 protocol.

|volume\_monitoring

|boolean

a|Specifies whether volume operation monitoring is required.

|===

[#fpolicy\_engine\_reference]

[.api-collapsible-fifth-title]

fpolicy\_engine\_reference

FPolicy external engine

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|\_links

|link:#\_links[\_links]

```
a|  
  
|name  
|string  
a|The name of the FPolicy external engine.
```

```
|===
```

```
[#fpolicy_event_reference]  
[.api-collapsible-fifth-title]  
fpolicy_event_reference
```

FPolicy events

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name  
|string
```

```
a|
```

```
|===
```

```
[#scope]  
[.api-collapsible-fifth-title]  
scope
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|exclude_export_policies  
|array[string]
```

```
a|
```

```
|exclude_extension  
|array[string]  
a|
```

```
|exclude_shares  
|array[string]  
a|
```

```
|exclude_volumes  
|array[string]  
a|
```

```
|include_export_policies  
|array[string]  
a|
```

```
|include_extension  
|array[string]  
a|
```

```
|include_shares  
|array[string]  
a|
```

```
|include_volumes  
|array[string]  
a|
```

```
|===
```

```
[#fpolicy_policy]  
[.api-collapsible-fifth-title]  
fpolicy_policy
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|enabled
```

```
|boolean
```

```
a|Specifies if the policy is enabled on the SVM or not. If no value is mentioned for this field but priority is set, then this policy will be enabled.
```

```
|engine
|link:#fpolicy_engine_reference[fpolicy_engine_reference]
a|FPolicy external engine
```

```
|events
|array[link:#fpolicy_event_reference[fpolicy_event_reference]]
a|
```

```
|mandatory
|boolean
a|Specifies what action to take on a file access event in a case when all primary and secondary servers are down or no response is received from the FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.
```

```
|name
|string
a|Specifies the name of the policy.
```

```
|priority
|integer
a|Specifies the priority that is assigned to this policy.
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

```
[#svm]
[.api-collapsible-fifth-title]
svm
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|The name of the SVM.
```

```
|uuid
```

```
|string
```

```
a|The unique identifier of the SVM.
```

```
|===
```

```
[#fpolicy]
```

```
[.api-collapsible-fifth-title]
```

```
fpolicy
```

FPolicy is an infrastructure component of ONTAP that enables partner applications connected to your storage systems to monitor and set file access permissions. Every time a client accesses a file from a storage system, based on the configuration of FPolicy, the partner application is notified about file access.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|engines
```

```
|array[link:#fpolicy_engine[fpolicy_engine]]
```

```
a|
```

```
|events
```

```
|array[link:#fpolicy_event[fpolicy_event]]
```

```
a|
```

```
|policies
```

```
|array[link:#fpolicy_policy[fpolicy_policy]]
```

```

a|

|svm
|link:#svm[svm]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string

```

```

a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDc9cd82da2444ff28d45712500d5e41f0]]
= Delete the FPolicy configuration for an SVM

```



```
[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-block]#`/protocols/fpolicy/{svm.uuid}`#
```

\*Introduced In:\* 9.6

Deletes the FPolicy configuration for the specified SVM. Before deleting the FPolicy configuration, ensure that all policies belonging to the SVM are disabled.

== Related ONTAP commands

- \* `fpolicy delete`
- \* `fpolicy policy scope delete`
- \* `fpolicy policy delete`
- \* `fpolicy policy event delete`
- \* `fpolicy policy external-engine delete`

== Learn more

\* xref:{relative\_path}protocols\_fpolicy\_endpoint\_overview.html[DOC /protocols/fpolicy]

== Parameters

[cols=5\*,options=header]

|===

Name
Type
In
Required
Description

svm.uuid
string
path
True
a UUID of the SVM to which this object belongs.

|===

== Response

Status: 200, Ok

```
== Error
```

## Status: Default

### ONTAP Error Response Codes

```
|===
```

```
| Error Code | Description
```

```
| 9765030
```

```
| Cannot delete an FPolicy configuration if any of the policy is enabled
```

```
| 9765031
```

```
| If any of the FPolicy engine, FPolicy event or FPolicy policy deletion fails due to a systemic error or hardware failure, the cause of the failure is detailed in the error message.
```

```
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",
```

```

    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]

```

```
a|Message arguments
```

```
|code
```

```
|string
```

```
a|Error code
```

```
|message
```

```
|string
```

```
a|Error message
```

```
|target
```

```
|string
```

```
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
```

```
====
```

```
[[ID03ac946848545f865503754536c8ec7e]]
```

```
= Retrieve the FPolicy configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-  
block]#`/protocols/fpolicy/{svm.uuid}`#
```

```
*Introduced In:* 9.6
```

```
Retrieves an FPolicy configuration of an SVM.
```

```
== Related ONTAP commands
```

```
* `fpolicy show`
```

```
* `fpolicy policy show`
```

```
* `fpolicy policy scope show`
```

```
* `fpolicy policy event show`
```

```
* `fpolicy policy external-engine show`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_fpolicy_endpoint_overview.html[DOC
```

```
/protocols/fpolicy]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|fields
```

```
|array[string]
```

```
|query
```

```
|False
```

```
a|Specify the fields to return.
```

```
|===
```

```
== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|engines
```

```
|array[link:#fpolicy_engine[fpolicy_engine]]
```

```
a|
```

```

|events
|array[link:#fpolicy_event[fpolicy_event]]
a|

|policies
|array[link:#fpolicy_policy[fpolicy_policy]]
a|

|svm
|link:#svm[svm]
a|

|===

```

.Example response

[%collapsible%closed]

====

```

[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "engines": {
    "name": "fp_ex_eng",
    "port": "9876",
    "primary_servers": [
      "10.132.145.20",
      "10.140.101.109"
    ],
    "secondary_servers": [
      "10.132.145.20",
      "10.132.145.21"
    ],
    "type": "synchronous"
  },
  "events": {
    "name": "event_nfs_close",
    "protocol": "cifs"
  },
  "policies": {
    "engine": {
      "_links": {

```

```

    "self": {
      "href": "/api/resourcelink"
    }
  },
  "events": [
    "event_nfs_close",
    "event_open"
  ],
  "name": "fp_policy_1",
  "scope": {
    "exclude_export_policies": {
    },
    "exclude_extension": {
    },
    "exclude_shares": {
    },
    "exclude_volumes": [
      "vol1",
      "vol_svm1",
      "*"
    ],
    "include_export_policies": {
    },
    "include_extension": {
    },
    "include_shares": [
      "sh1",
      "share_cifs"
    ],
    "include_volumes": [
      "vol1",
      "vol_svm1"
    ]
  }
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}

```

```
====
```

```
== Error
```

Status: Default, Error

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href
```



```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|href
```

```
|string
```

```
a|
```

```
|===
```

```
[#_links]
```

```
[.api-collapsible-fifth-title]
```

```
_links
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|self
```

```
|link:href[href]
```

```
a|
```

```
|===
```

```
[#fpolicy_engine]
```

```
[.api-collapsible-fifth-title]
```

```
fpolicy_engine
```

The engine defines how ONTAP makes and manages connections to external FPolicy servers.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|name
```

```
|string
```

a|Specifies the name to assign to the external server configuration.

|port

|integer

a|Port number of the FPolicy server application.

|primary\_servers

|array[string]

a|

|secondary\_servers

|array[string]

a|

|type

|string

a|The notification mode determines what ONTAP does after sending notifications to FPolicy servers.

The possible values are:

\*\*\*\*\* synchronous - After sending a notification, wait for a response from the FPolicy server.

\*\*\*\*\* asynchronous - After sending a notification, file request processing continues.

\* Default value: 1

\* enum: ["synchronous", "asynchronous"]

\* Introduced in: 9.6

|===

[#file\_operations]

[.api-collapsible-fifth-title]

file\_operations

Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.

The event will check the operations specified from all client requests using the protocol.

[cols=3\*,options=header]

```
|===  
|Name  
|Type  
|Description  
  
|close  
|boolean  
a|File close operations  
  
|create  
|boolean  
a|File create operations  
  
|create_dir  
|boolean  
a|Directory create operations  
  
|delete  
|boolean  
a|File delete operations  
  
|delete_dir  
|boolean  
a|Directory delete operations  
  
|getattr  
|boolean  
a|Get attribute operations  
  
|link  
|boolean  
a|Link operations  
  
|lookup  
|boolean  
a|Lookup operations  
  
|open  
|boolean
```

a|File open operations

|read

|boolean

a|File read operations

|rename

|boolean

a|File rename operations

|rename\_dir

|boolean

a|Directory rename operations

|setattr

|boolean

a|Set attribute operations

|symlink

|boolean

a|Symbolic link operations

|write

|boolean

a|File write operations

|===

[#filters]

[.api-collapsible-fifth-title]

filters

Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

[cols=3\*,options=header]

```
|===  
|Name  
|Type  
|Description  
  
|close_with_modification  
|boolean  
a|Filter the client request for close with modification.  
  
|close_with_read  
|boolean  
a|Filter the client request for close with read.  
  
|close_without_modification  
|boolean  
a|Filter the client request for close without modification.  
  
|exclude_directory  
|boolean  
a|Filter the client requests for directory operations. When this filter is  
specified directory operations are not monitored.  
  
|first_read  
|boolean  
a|Filter the client requests for the first-read.  
  
|first_write  
|boolean  
a|Filter the client requests for the first-write.  
  
|monitor_ads  
|boolean  
a|Filter the client request for alternate data stream.  
  
|offline_bit  
|boolean  
a|Filter the client request for offline bit set. FPolicy server receives  
notification only when offline files are accessed.
```

|open\_with\_delete\_intent

|boolean

a|Filter the client request for open with delete intent.

|open\_with\_write\_intent

|boolean

a|Filter the client request for open with write intent.

|setattr\_with\_access\_time\_change

|boolean

a|Filter the client setattr requests for changing the access time of a file or directory.

|setattr\_with\_allocation\_size\_change

|boolean

a|Filter the client setattr requests for changing the allocation size of a file.

|setattr\_with\_creation\_time\_change

|boolean

a|Filter the client setattr requests for changing the creation time of a file or directory.

|setattr\_with\_dacl\_change

|boolean

a|Filter the client setattr requests for changing dacl on a file or directory.

|setattr\_with\_group\_change

|boolean

a|Filter the client setattr requests for changing group of a file or directory.

|setattr\_with\_mode\_change

|boolean

a|Filter the client setattr requests for changing the mode bits on a file or directory.

|setattr\_with\_modify\_time\_change

```

|boolean
a|Filter the client setattr requests for changing the modification time of
a file or directory.

|setattr_with_owner_change
|boolean
a|Filter the client setattr requests for changing owner of a file or
directory.

|setattr_with_sacl_change
|boolean
a|Filter the client setattr requests for changing sacl on a file or
directory.

|setattr_with_size_change
|boolean
a|Filter the client setattr requests for changing the size of a file.

|write_with_size_change
|boolean
a|Filter the client request for write with size change.

|===

[#fpolicy_event]
[.api-collapsible-fifth-title]
fpolicy_event

The information that a FPolicy process needs to determine what file access
operations to monitor and for which of the monitored events notifications
should be sent to the external FPolicy server.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|file_operations
|link:#file_operations[file_operations]

```

a|Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.

The event will check the operations specified from all client requests using the protocol.

|filters

|link:#filters[filters]

a|Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

|name

|string

a|Specifies the name of the FPolicy event.

|protocol

|string

a|Protocol for which event is created. If you specify protocol, then you must also specify a valid value for the file operation parameters.

The value of this parameter must be one of the following:

\*\*\*\*\* cifs - for the CIFS protocol.

\*\*\*\*\* nfsv3 - for the NFSv3 protocol.

\*\*\*\*\* nfsv4 - for the NFSv4 protocol.

|volume\_monitoring

|boolean

a|Specifies whether volume operation monitoring is required.

|===

[#fpolicy\_engine\_reference]

[.api-collapsible-fifth-title]

fpolicy\_engine\_reference

FPolicy external engine



```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the FPolicy external engine.
```

```
|===
```

```
[#fpolicy_event_reference]
[.api-collapsible-fifth-title]
fpolicy_event_reference
```

FPolicy events

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|name
|string
a|
```

```
|===
```

```
[#scope]
[.api-collapsible-fifth-title]
scope
```

```
[cols=3*,options=header]
```

```

|===
|Name
|Type
|Description

|exclude_export_policies
|array[string]
a|

|exclude_extension
|array[string]
a|

|exclude_shares
|array[string]
a|

|exclude_volumes
|array[string]
a|

|include_export_policies
|array[string]
a|

|include_extension
|array[string]
a|

|include_shares
|array[string]
a|

|include_volumes
|array[string]
a|

|===

[#fpolicy_policy]
[.api-collapsible-fifth-title]
fpolicy_policy

[cols=3*,options=header]
|===
|Name

```

```

|Type
|Description

|enabled
|boolean
a|Specifies if the policy is enabled on the SVM or not. If no value is
mentioned for this field but priority is set, then this policy will be
enabled.

|engine
|link:#fpolicy_engine_reference[fpolicy_engine_reference]
a|FPolicy external engine

|events
|array[link:#fpolicy_event_reference[fpolicy_event_reference]]
a|

|mandatory
|boolean
a|Specifies what action to take on a file access event in a case when all
primary and secondary servers are down or no response is received from the
FPolicy servers within a given timeout period. When this parameter is set
to true, file access events will be denied under these circumstances.

|name
|string
a|Specifies the name of the policy.

|priority
|integer
a|Specifies the priority that is assigned to this policy.

|scope
|link:#scope[scope]
a|

|===

[#svm]
[.api-collapsible-fifth-title]
svm

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

```

```

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

:leveloffset: -1

= Manage FPolicy engine configuration

:leveloffset: +1

[[ID38fa779062104bc903d542d230c63b65]]

```

```
= Protocols fpolicy svm.uuid engines endpoint overview
```

```
== Overview
```

The FPolicy engine allows you to configure the external servers to which the file access notifications are sent. As part of FPolicy engine configuration, you can configure the server(s) to which the notification is sent, an optional set of secondary server(s) to which the notification is sent in the case of the primary server(s) failure, the port number for FPolicy application and the type of the engine, synchronous or asynchronous.

For the synchronous engine, ONTAP will wait for a response from the FPolicy application before it allows the operation. With an asynchronous engine, ONTAP proceeds with the operation processing after sending the notification to the FPolicy application. An engine can belong to multiple FPolicy policies.

```
== Examples
```

```
=== Creating an FPolicy engine
```

```
'''
```

```
----
```

```
# The API:
```

```
POST /protocols/fpolicy/{svm.uuid}/engines
```

```
#The call:
```

```
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/engines/" -H "accept: application/json" -H "Content-Type: application/json" -d '{"name": "engine0", "port": 9876, "primary_servers": [ "10.132.145.22", "10.140.101.109" ], "secondary_servers": [ "10.132.145.20", "10.132.145.21" ], "type": "synchronous"}'
```

```
# The response:
```

```
{
  "num_records": 1,
  "records": [
    {
      "name": "engine0",
      "primary_servers": [
        "10.132.145.22",
```

```

    "10.140.101.109"
  ],
  "secondary_servers": [
    "10.132.145.20",
    "10.132.145.21"
  ],
  "port": 9876,
  "type": "synchronous"
}
]
}
-----

'''

=== Creating an FPolicy engine with the minimum required fields

'''

-----

# The API:
POST /protocols/fpolicy/{svm.uuid}/engines

#The call:
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/engines/" -H "accept: application/json" -H "Content-Type: application/json" -d '{"name": "engine0", "port": 9876, "primary_servers": [ "10.132.145.22", "10.140.101.109" ], "type": "synchronous"}'

# The response:
{
  "num_records": 1,
  "records": [
    {
      "name": "engine0",
      "primary_servers": [
        "10.132.145.22",
        "10.140.101.109"
      ],
      "port": 9876,
      "type": "synchronous"
    }
  ]
}
}

```

```

-----

'''

=== Retrieving an FPolicy engine configuration for a particular SVM

'''

-----

# The API:
GET /protocols/fpolicy/{svm.uuid}/engines

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/engines/?fields=*&return_records=true&return_timeout=15"
-H "accept: application/json"

# The response:
{
"records": [
  {
    "svm": {
      "uuid": "4f643fb4-fd21-11e8-ae49-0050568e2c1e"
    },
    "name": "cifs",
    "primary_servers": [
      "10.20.20.10"
    ],
    "port": 9876,
    "type": "synchronous"
  },
  {
    "svm": {
      "uuid": "4f643fb4-fd21-11e8-ae49-0050568e2c1e"
    },
    "name": "nfs",
    "primary_servers": [
      "10.23.140.64",
      "10.140.101.109"
    ],
    "secondary_servers": [
      "10.132.145.20",
      "10.132.145.22"
    ],
    "port": 9876,

```



```

    "type": "synchronous"
  }
],
"num_records": 2
}
----

'''

=== Retrieving a specific FPolicy engine configuration for an SVM

'''

----

# The Api:
GET /protocols/fpolicy/{svm.uuid}/engines/{name}

#The call:
curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/engines/cifs?fields=*" -H "accept: application/json"

# The response:
{
"svm": {
  "uuid": "4f643fb4-fd21-11e8-ae49-0050568e2c1e"
},
"name": "cifs",
"primary_servers": [
  "10.20.20.10"
],
"port": 9876,
"type": "synchronous"
}
----

'''

=== Updating an FPolicy engine for an SVM

'''

----

# The API:
PATCH /protocols/fpolicy/{svm.uuid}/engines/{name}

```

```

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/engines/cifs" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"port\": 6666, \"secondary_servers\": [ \"10.132.145.20\", \"10.132.145.21\" ], \"type\": \"synchronous\"}"
-----

'''

=== Updating all the attributes of a specific FPolicy engine for an SVM

'''

-----

# The API:
PATCH /protocols/fpolicy/{svm.uuid}/engines/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/engines/cifs" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"port\": 9876, \"primary_servers\": [ \"10.132.145.20\", \"10.140.101.109\" ], \"secondary_servers\": [ \"10.132.145.23\", \"10.132.145.21\" ], \"type\": \"synchronous\"}"
-----

'''

=== Deleting a specific FPolicy engine for an SVM

'''

-----

# The API:
DELETE /protocols/fpolicy/{svm.uuid}/engines/{name}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/events/cifs" -H "accept: application/json"
-----

'''

```

```
[[ID5b772288a491477602039582c63ad4ae]]
```

```
= Retrieve the FPolicy engine configuration for all engines of an SVM
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/fpolicy/{svm.uuid}/engines`#
```

```
*Introduced In:* 9.6
```

Retrieves FPolicy engine configurations of all the engines for a specified SVM. ONTAP allows creation of cluster-level FPolicy engines that act as a template for all the SVMs belonging to the cluster. These cluster-level FPolicy engines are also retrieved for the specified SVM.

```
== Related ONTAP commands
```

```
* `fpolicy policy external-engine show`
```

```
== Learn more
```

```
*
```

```
xref:{relative_path}protocols_fpolicy_svm.uuid_engines_endpoint_overview.html[DOC /protocols/fpolicy/{svm.uuid}/engines]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|secondary_servers
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by secondary_servers
```

```
|port
```

```
|integer
```

```
|query
```

```
|False
```

```
a|Filter by port
```

```
|type
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by type
```

```
|name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by name
```

```
|primary_servers
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by primary_servers
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|fields
```

```
|array[string]
```

```
|query
```

```
|False
```

```
a|Specify the fields to return.
```

```
|max_records
```

```
|integer
```

```
|query
```

```
|False
```

```
a|Limit the number of records returned.
```

```
|return_records
```

```
|boolean
```

```
|query
|False
a|The default is true for GET calls.  When set to false, only the number
of records is returned.

* Default value: 1

|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds.  ONTAP
returns earlier if either max records or the end of the collection is
reached.

* Default value: 1
* Max value: 120
* Min value: 0

|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
```

```
|integer
a|Number of records

|records
|array[link:#fpolicy_engine[fpolicy_engine]]
a|
```

|===

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "name": "fp_ex_eng",
    "port": "9876",
    "primary_servers": [
      "10.132.145.20",
      "10.140.101.109"
    ],
    "secondary_servers": [
      "10.132.145.20",
      "10.132.145.21"
    ],
    "type": "synchronous"
  }
}
```

====

== Error

Status: Default,

[cols=3\*,options=header]

|===

```

|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href

```

```

|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

[#fpolicy_engine]
[.api-collapsible-fifth-title]
fpolicy_engine

The engine defines how ONTAP makes and manages connections to external
FPolicy servers.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|name
|string
a|Specifies the name to assign to the external server configuration.

|port

```



```

|integer
a|Port number of the FPolicy server application.

|primary_servers
|array[string]
a|

|secondary_servers
|array[string]
a|

|type
|string
a|The notification mode determines what ONTAP does after sending
notifications to FPolicy servers.
The possible values are:

***** synchronous - After sending a notification, wait for a response
from the FPolicy server.

***** asynchronous - After sending a notification, file request processing
continues.

* Default value: 1
* enum: ["synchronous", "asynchronous"]
* Introduced in: 9.6

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

```

```

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[ID4303dc8453ec1c3b40e47a0f9da41f15]]

```

= Create an FPolicy engine configuration for an SVM

```
[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-  
block]#`/protocols/fpolicy/{svm.uuid}/engines`#
```

\*Introduced In:\* 9.6

Creates an FPolicy engine configuration for a specified SVM. FPolicy engine creation is allowed only on data SVMs.

== Required properties

- \* `svm.uuid` - Existing SVM in which to create the FPolicy engine.
- \* `name` - Name of external engine.
- \* `port` - Port number of the FPolicy server application.
- \* `primary\_servers` - List of primary FPolicy servers to which the node will send notifications.

== Recommended optional properties

- \* `secondary\_servers` - It is recommended to configure secondary FPolicy server to which the node will send notifications when the primary server is down.

== Default property values

- \* `type` - `_synchronous_`

== Related ONTAP commands

- \* `fpolicy policy external-engine create``

== Learn more

- \*  
`xref:{relative_path}protocols_fpolicy_svm.uuid_engines_endpoint_overview.html[DOC /protocols/fpolicy/{svm.uuid}/engines]`

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
|Description

|return_records
|boolean
|query
|False
a|The default is false. If set to true, the records are returned.
```

\* Default value:

```
|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.
```

|===

== Request Body

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|name
|string
a|Specifies the name to assign to the external server configuration.
```

```
|port
|integer
a|Port number of the FPolicy server application.
```

```
|primary_servers
|array[string]
a|
```

```
|secondary_servers
|array[string]
a|
```

```
|type
|string
a|The notification mode determines what ONTAP does after sending
notifications to FPolicy servers.
The possible values are:

***** synchronous - After sending a notification, wait for a response
from the FPolicy server.

***** asynchronous - After sending a notification, file request processing
continues.

* Default value: 1
* enum: ["synchronous", "asynchronous"]
* Introduced in: 9.6
```

```
|===
```

```
.Example request
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "name": "fp_ex_eng",
  "port": "9876",
  "primary_servers": [
    "10.132.145.20",
    "10.140.101.109"
  ],
  "secondary_servers": [
    "10.132.145.20",
    "10.132.145.21"
  ],
  "type": "synchronous"
}
====
```

```
== Response
```

Status: 201, Created

```
[cols=3*,options=header]
|===
```

```

|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#fpolicy_engine[fpolicy_engine]]
a|

|===

```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```

{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "name": "fp_ex_eng",
    "port": "9876",
    "primary_servers": [
      "10.132.145.20",
      "10.140.101.109"
    ],
    "secondary_servers": [
      "10.132.145.20",
      "10.132.145.21"
    ],
    "type": "synchronous"
  }
}

```

```
}  
====  
  
== Error
```

## Status: Default

### ONTAP Error Response Codes

```
|===  
| Error Code | Description  
  
| 9764885  
| The primary secondary server has a redundant IP address  
  
| 9764953  
| The name of the FPolicy engine is "native" which is reserved by the  
system  
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|error  
|link:#error[error]  
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",
```

```
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====
```

== Definitions

```
[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
```

```
[#fpolicy_engine]
[.api-collapsible-fifth-title]
fpolicy_engine
```

The engine defines how ONTAP makes and manages connections to external FPolicy servers.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|name
```

```
|string
```

```
a|Specifies the name to assign to the external server configuration.
```

```
|port
```

```
|integer
```

```
a|Port number of the FPolicy server application.
```

```
|primary_servers
```

```
|array[string]
```

```
a|
```

```
|secondary_servers
```

```
|array[string]
```

```
a|
```

```
|type
```

```
|string
```



a|The notification mode determines what ONTAP does after sending notifications to FPolicy servers.

The possible values are:

\*\*\*\*\* synchronous - After sending a notification, wait for a response from the FPolicy server.

\*\*\*\*\* asynchronous - After sending a notification, file request processing continues.

\* Default value: 1

\* enum: ["synchronous", "asynchronous"]

\* Introduced in: 9.6

|===

[#href]

[.api-collapsible-fifth-title]

href

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|href

|string

a|

|===

[#\_links]

[.api-collapsible-fifth-title]

\_links

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|next

|link:#href[href]

```

a|

|self
|link:#href[href]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

```

```

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

[[IDfbec3f05d5bd172441d5a461e012d42d]]
= Delete an FPolicy external engine configuration

[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-
block]#`/protocols/fpolicy/{svm.uuid}/engines/{name}`#

*Introduced In:* 9.6

Deletes the FPolicy external engine configuration. Deletion of an FPolicy
engine that is attached to one or more FPolicy policies is not allowed.

== Related ONTAP commands

* `fpolicy policy external-engine modify`

== Learn more

*
xref:{relative_path}protocols_fpolicy_svm.uuid_engines_endpoint_overview.h
tml[DOC /protocols/fpolicy/{svm.uuid}/engines]

== Parameters

```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|name
```

```
|string
```

```
|path
```

```
|True
```

```
a|
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```

```
== Response
```

Status: 200, Ok

```
== Error
```

Status: Default

```
ONTAP Error Response Codes
```

```
|===
```

```
| Error Code | Description
```

```
| 9764940
```

```
| At least one FPolicy policy is using the FPolicy engine
```

```
| 9764887
```

```
| The FPolicy engine is a cluster level FPolicy engine
```

```
|===
```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block

```

====

[[ID3cab0d13082b63223c39bef95911800f]]

= Retrieve a particular FPolicy engine configuration for an SVM

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/fpolicy/{svm.uuid}/engines/{name}`#

\*Introduced In:\* 9.6

Retrieves a particular FPolicy engine configuration of a specified SVM. A cluster-level FPolicy engine configuration cannot be retrieved for a data SVM.

== Related ONTAP commands

\* `fpolicy policy external-engine show`

== Learn more

\*

xref:{relative\_path}protocols\_fpolicy\_svm.uuid\_engines\_endpoint\_overview.html[DOC /protocols/fpolicy/{svm.uuid}/engines]

== Parameters

[cols=5\*,options=header]

|====

|Name

|Type

|In

|Required

|Description

|name

|string

|path

|True

a|

|svm.uuid

|string

|path

```
|True
a|UUID of the SVM to which this object belongs.

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|name
|string
a|Specifies the name to assign to the external server configuration.

|port
|integer
a|Port number of the FPolicy server application.

|primary_servers
|array[string]
a|

|secondary_servers
|array[string]
a|

|type
|string
a|The notification mode determines what ONTAP does after sending
notifications to FPolicy servers.
The possible values are:
```



```
***** synchronous - After sending a notification, wait for a response
from the FPolicy server.
```

```
***** asynchronous - After sending a notification, file request processing
continues.
```

```
* Default value: 1
```

```
* enum: ["synchronous", "asynchronous"]
```

```
* Introduced in: 9.6
```

```
|===
```

```
.Example response
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "name": "fp_ex_eng",
  "port": "9876",
  "primary_servers": [
    "10.132.145.20",
    "10.140.101.109"
  ],
  "secondary_servers": [
    "10.132.145.20",
    "10.132.145.21"
  ],
  "type": "synchronous"
}
```

```
====
```

```
== Error
```

Status: Default, Error

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```

|===

.Example error
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====

```

```

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

```

```

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

|code
|string
a|Argument code

```

```

|message
|string
a|Message argument

```

```

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDfa27c9dea0b6c9c1347236b7c0671557]]
= Update a specific FPolicy engine configuration for an SVM

[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/fpolicy/{svm.uuid}/engines/{name}`#

```

\*Introduced In:\* 9.6

Updates a specific FPolicy engine configuration of an SVM. Modification of an FPolicy engine that is attached to one or more enabled FPolicy policies is not allowed.

== Related ONTAP commands

\* `fpolicy policy external-engine modify`

== Learn more

\*

xref:{relative\_path}protocols\_fpolicy\_svm.uuid\_engines\_endpoint\_overview.html[DOC /protocols/fpolicy/{svm.uuid}/engines]

== Parameters

[cols=5\*,options=header]

|===

|Name

|Type

|In

|Required

|Description

|name

|string

|path

|True

a|

|svm.uuid

|string

|path

|True

a|UUID of the SVM to which this object belongs.

|===

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|name
```

```
|string
```

```
a|Specifies the name to assign to the external server configuration.
```

```
|port
```

```
|integer
```

```
a|Port number of the FPolicy server application.
```

```
|primary_servers
```

```
|array[string]
```

```
a|
```

```
|secondary_servers
```

```
|array[string]
```

```
a|
```

```
|type
```

```
|string
```

```
a|The notification mode determines what ONTAP does after sending notifications to FPolicy servers.
```

```
The possible values are:
```

```
***** synchronous - After sending a notification, wait for a response from the FPolicy server.
```

```
***** asynchronous - After sending a notification, file request processing continues.
```

```
* Default value: 1
```

```
* enum: ["synchronous", "asynchronous"]
```

```
* Introduced in: 9.6
```

```
|===
```

```
.Example request
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```
{  
  "name": "fp_ex_eng",  
  "port": "9876",  
  "primary_servers": [  
    "10.132.145.20",  
    "10.140.101.109"  
  ],  
  "secondary_servers": [  
    "10.132.145.20",  
    "10.132.145.21"  
  ],  
  "type": "synchronous"  
}
```

```
====  
  
== Response
```

Status: 200, Ok

```
== Error
```

Status: Default

```
ONTAP Error Response Codes
```

```
|===  
| Error Code | Description  
  
| 9764922  
| The primary and secondary server has a redundant IP address  
  
| 9764942  
| At least one FPolicy policy is using the FPolicy engine  
  
| 9764886  
| FPolicy engine is a cluster-level FPolicy engine  
|===
```

```
[cols=3*,options=header]
```

```
|===  
|Name  
|Type
```

```

|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#fpolicy_engine]
[.api-collapsible-fifth-title]
fpolicy_engine

The engine defines how ONTAP makes and manages connections to external
FPolicy servers.

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|name
|string
a|Specifies the name to assign to the external server configuration.

|port
|integer
a|Port number of the FPolicy server application.

|primary_servers
|array[string]
a|

|secondary_servers
|array[string]
a|

|type
|string
a|The notification mode determines what ONTAP does after sending
notifications to FPolicy servers.
The possible values are:

***** synchronous - After sending a notification, wait for a response
from the FPolicy server.

***** asynchronous - After sending a notification, file request processing
continues.

* Default value: 1
* enum: ["synchronous", "asynchronous"]
* Introduced in: 9.6

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

```



```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```

//end collapsible .Definitions block
====

:leveloffset: -1

= Manage FPolicy event configuration

:leveloffset: +1

[[IDd0cb909f6ac0e47daa073e3256e5f077]]
= Protocols fpolicy svm.uuid events endpoint overview

== Overview

FPolicy events configurations allow you to specify which file access is
monitored. As part of an FPolicy event, you can configure the SVM for
which the events are generated, the name of the event configuration, the
protocol (cifs, nfsv3/nfsv4) for which the events are generated, the file
operations which are monitored, and filters that can be used to filter the
unwanted notification generation for a specified protocol and file
operation.

Each protocol has a set of supported file operations and filters. An SVM
can have multiple events. A single FPolicy policy can have multiple
FPolicy events.

== Examples

=== Creating an FPolicy event for a CIFS protocol with all the supported
file operations and filters

'''

----

# The API:
POST /protocols/fpolicy/{svm.uuid}/events

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-
ae49-0050568e2c1e/events?return_records=true" -H "accept:

```

```
application/json" -H "Content-Type: application/json" -d "{
  \"file_operations\": { \"close\": true, \"create\": true, \"create_dir\":
true, \"delete\": true, \"delete_dir\": true, \"getattr\": true, \"open\":
true, \"read\": true, \"rename\": true, \"rename_dir\": true, \"setattr\":
true, \"write\": true }, \"filters\": { \"close_with_modification\": true,
\"close_with_read\": true, \"close_without_modification\": true,
\"first_read\": true, \"first_write\": true, \"monitor_ads\": true,
\"offline_bit\": true, \"open_with_delete_intent\": true,
\"open_with_write_intent\": true, \"write_with_size_change\": true },
\"name\": \"event_cifs\", \"protocol\": \"cifs\", \"volume_monitoring\":
true}"
```

# The response:

```
{
  "num_records": 1,
  "records": [
    {
      "name": "event_cifs",
      "protocol": "cifs",
      "volume_monitoring": true,
      "file_operations": {
        "close": true,
        "create": true,
        "create_dir": true,
        "delete": true,
        "delete_dir": true,
        "getattr": true,
        "open": true,
        "read": true,
        "write": true,
        "rename": true,
        "rename_dir": true,
        "setattr": true
      },
      "filters": {
        "monitor_ads": true,
        "close_with_modification": true,
        "close_without_modification": true,
        "close_with_read": true,
        "first_read": true,
        "first_write": true,
        "offline_bit": true,
        "open_with_delete_intent": true,
        "open_with_write_intent": true,
        "write_with_size_change": true
      }
    }
  ]
}
```

```

    }
  ]
}
----

'''

=== Creating an FPolicy event for an NFS protocol with all the supported
file operations and filters

'''

----

# The API:
post /protocols/fpolicy/{svm.uuid}/events

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-
ae49-0050568e2c1e/events?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{
\"file_operations\": { \"create\": true, \"create_dir\": true, \"delete\":
true, \"delete_dir\": true, \"link\": true, \"lookup\": true, \"read\":
true, \"rename\": true, \"rename_dir\": true, \"setattr\": true,
\"symlink\": true, \"write\": true }, \"filters\": { \"offline_bit\":
true, \"write_with_size_change\": true }, \"name\": \"event_nfsv3\",
\"protocol\": \"nfsv3\", \"volume_monitoring\": false}"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "name": "event_nfsv3",
      "protocol": "nfsv3",
      "volume_monitoring": false,
      "file_operations": {
        "create": true,
        "create_dir": true,
        "delete": true,
        "delete_dir": true,
        "link": true,
        "lookup": true,
        "read": true,
        "write": true,
        "rename": true,

```

```

    "rename_dir": true,
    "setattr": true,
    "symlink": true
  },
  "filters": {
    "offline_bit": true,
    "write_with_size_change": true
  }
}
]
}
-----
'''

```

=== Retrieving all of the FPolicy event configurations for a specified SVM

```
'''
```

```
-----
```

# The API:

```
GET /protocols/fpolicy/{svm.uuid}/events
```

# The call:

```
curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/events/?fields=*&return_records=true&return_timeout=15"
-H "accept: application/json"
```

# The response:

```

{
  "records": [
    {
      "svm": {
        "uuid": "4f643fb4-fd21-11e8-ae49-0050568e2c1e"
      },
      "name": "cluster",
      "protocol": "cifs",
      "volume_monitoring": false,
      "file_operations": {
        "close": true,
        "create": false,
        "create_dir": false,
        "delete": false,
        "delete_dir": false,
        "getattr": false,

```

```

    "link": false,
    "lookup": false,
    "open": false,
    "read": false,
    "write": false,
    "rename": false,
    "rename_dir": false,
    "setattr": false,
    "symlink": false
  },
  "filters": {
    "monitor_ads": false,
    "close_with_modification": false,
    "close_without_modification": false,
    "close_with_read": true,
    "first_read": false,
    "first_write": false,
    "offline_bit": false,
    "open_with_delete_intent": false,
    "open_with_write_intent": false,
    "write_with_size_change": false,
    "setattr_with_owner_change": false,
    "setattr_with_group_change": false,
    "setattr_with_sacl_change": false,
    "setattr_with_dacl_change": false,
    "setattr_with_modify_time_change": false,
    "setattr_with_access_time_change": false,
    "setattr_with_creation_time_change": false,
    "setattr_with_mode_change": false,
    "setattr_with_size_change": false,
    "setattr_with_allocation_size_change": false,
    "exclude_directory": false
  }
},
{
  "svm": {
    "uuid": "4f643fb4-fd21-11e8-ae49-0050568e2c1e"
  },
  "name": "event_cifs",
  "protocol": "cifs",
  "volume_monitoring": true,
  "file_operations": {
    "close": true,
    "create": true,
    "create_dir": true,
    "delete": true,

```

```

    "delete_dir": true,
    "getattr": true,
    "link": false,
    "lookup": false,
    "open": true,
    "read": true,
    "write": true,
    "rename": true,
    "rename_dir": true,
    "setattr": true,
    "symlink": false
  },
  "filters": {
    "monitor_ads": true,
    "close_with_modification": true,
    "close_without_modification": true,
    "close_with_read": true,
    "first_read": true,
    "first_write": true,
    "offline_bit": true,
    "open_with_delete_intent": true,
    "open_with_write_intent": true,
    "write_with_size_change": true,
    "setattr_with_owner_change": false,
    "setattr_with_group_change": false,
    "setattr_with_sacl_change": false,
    "setattr_with_dacl_change": false,
    "setattr_with_modify_time_change": false,
    "setattr_with_access_time_change": false,
    "setattr_with_creation_time_change": false,
    "setattr_with_mode_change": false,
    "setattr_with_size_change": false,
    "setattr_with_allocation_size_change": false,
    "exclude_directory": false
  }
},
"num_records": 2
}
----

'''

=== Retrieving a specific FPolicy event configuration for an SVM

'''

```

----

# The API:

```
GET /protocols/fpolicy/{svm.uuid}/events/{name}
```

# The call:

```
curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/events/event_cifs?fields=*&return_records=true&return_timeout=15" -H "accept: application/json"
```

# The response:

```
{
  "svm": {
    "uuid": "4f643fb4-fd21-11e8-ae49-0050568e2c1e"
  },
  "name": "event_cifs",
  "protocol": "cifs",
  "volume_monitoring": true,
  "file_operations": {
    "close": true,
    "create": true,
    "create_dir": true,
    "delete": true,
    "delete_dir": true,
    "getattr": true,
    "link": false,
    "lookup": false,
    "open": true,
    "read": true,
    "write": true,
    "rename": true,
    "rename_dir": true,
    "setattr": true,
    "symlink": false
  },
  "filters": {
    "monitor_ads": true,
    "close_with_modification": true,
    "close_without_modification": true,
    "close_with_read": true,
    "first_read": true,
    "first_write": true,
    "offline_bit": true,
    "open_with_delete_intent": true,
  }
}
```



```

"open_with_write_intent": true,
"write_with_size_change": true,
"setattr_with_owner_change": false,
"setattr_with_group_change": false,
"setattr_with_sacl_change": false,
"setattr_with_dacl_change": false,
"setattr_with_modify_time_change": false,
"setattr_with_access_time_change": false,
"setattr_with_creation_time_change": false,
"setattr_with_mode_change": false,
"setattr_with_size_change": false,
"setattr_with_allocation_size_change": false,
"exclude_directory": false
}
}
----

'''

=== Updating a specific FPolicy event configuration for a specified SVM

'''

----

# The API:
PATCH /protocols/fpolicy/{svm.uuid}/events/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/events/event_cifs" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"file_operations\": { \"close\": false, \"create\": false, \"read\": true }, \"filters\": { \"close_with_modification\": false, \"close_with_read\": false, \"close_without_modification\": false }, \"protocol\": \"cifs\", \"volume_monitoring\": false}"
----

'''

=== Deleting a specific FPolicy event configuration for a specific SVM

'''

----

# The API:

```

```
DELETE /protocols/fpolicy/{svm.uuid}/events/{name}
```

```
# The call:
```

```
curl -X DELETE "https://<mgmt-ip>/api/protocols/fpolicy/4f643fb4-fd21-11e8-ae49-0050568e2c1e/events/event_cifs" -H "accept: application/json"
----
```

```
'''
```

```
[[ID6fca7cf4c76d02252a148955806a12e4]]
```

```
= Retrieve the FPolicy event configuration for all events for an SVM
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/fpolicy/{svm.uuid}/events`#
```

```
*Introduced In:* 9.6
```

Retrieves FPolicy event configurations for all events for a specified SVM. ONTAP allows the creation of cluster-level FPolicy events that act as a template for all the data SVMs belonging to the cluster. These cluster-level FPolicy events are also retrieved for the specified SVM.

```
== Related ONTAP commands
```

```
* `fpolicy policy event show`
```

```
== Learn more
```

```
*
```

```
xref:{relative_path}protocols_fpolicy_svm.uuid_events_endpoint_overview.html[DOC /protocols/fpolicy/{svm.uuid}/events]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|protocol
|string
|query
|False
a|Filter by protocol
```

```
|name
|string
|query
|False
a|Filter by name
```

```
|filters.close_with_modification
|boolean
|query
|False
a|Filter by filters.close_with_modification
```

```
|filters.close_without_modification
|boolean
|query
|False
a|Filter by filters.close_without_modification
```

```
|filters.offline_bit
|boolean
|query
|False
a|Filter by filters.offline_bit
```

```
|filters.write_with_size_change
|boolean
|query
|False
a|Filter by filters.write_with_size_change
```

```
|filters.setattr_with_creation_time_change
|boolean
|query
|False
```

```
a|Filter by filters.setattr_with_creation_time_change
```

```
|filters.setattr_with_size_change
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by filters.setattr_with_size_change
```

```
|filters.open_with_delete_intent
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by filters.open_with_delete_intent
```

```
|filters.setattr_with_owner_change
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by filters.setattr_with_owner_change
```

```
|filters.setattr_with_access_time_change
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by filters.setattr_with_access_time_change
```

```
|filters.setattr_with_group_change
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by filters.setattr_with_group_change
```

```
|filters.setattr_with_dacl_change
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by filters.setattr_with_dacl_change
```

```
|filters.setattr_with_allocation_size_change
```

```
|boolean
```

```
|query
|False
a|Filter by filters.setattr_with_allocation_size_change
```

```
|filters.exclude_directory
|boolean
|query
|False
a|Filter by filters.exclude_directory
```

```
|filters.open_with_write_intent
|boolean
|query
|False
a|Filter by filters.open_with_write_intent
```

```
|filters.monitor_ads
|boolean
|query
|False
a|Filter by filters.monitor_ads
```

```
|filters.setattr_with_mode_change
|boolean
|query
|False
a|Filter by filters.setattr_with_mode_change
```

```
|filters.setattr_with_sacl_change
|boolean
|query
|False
a|Filter by filters.setattr_with_sacl_change
```

```
|filters.setattr_with_modify_time_change
|boolean
|query
|False
a|Filter by filters.setattr_with_modify_time_change
```

```
|filters.first_read
|boolean
|query
|False
a|Filter by filters.first_read
```

```
|filters.close_with_read
|boolean
|query
|False
a|Filter by filters.close_with_read
```

```
|filters.first_write
|boolean
|query
|False
a|Filter by filters.first_write
```

```
|volume_monitoring
|boolean
|query
|False
a|Filter by volume_monitoring
```

```
|file_operations.close
|boolean
|query
|False
a|Filter by file_operations.close
```

```
|file_operations.lookup
|boolean
|query
|False
a|Filter by file_operations.lookup
```

```
|file_operations.delete_dir
|boolean
|query
|False
a|Filter by file_operations.delete_dir
```

```
|file_operations.create_dir  
|boolean  
|query  
|False  
a|Filter by file_operations.create_dir
```

```
|file_operations.create  
|boolean  
|query  
|False  
a|Filter by file_operations.create
```

```
|file_operations.setattr  
|boolean  
|query  
|False  
a|Filter by file_operations.setattr
```

```
|file_operations.getattr  
|boolean  
|query  
|False  
a|Filter by file_operations.getattr
```

```
|file_operations.delete  
|boolean  
|query  
|False  
a|Filter by file_operations.delete
```

```
|file_operations.symlink  
|boolean  
|query  
|False  
a|Filter by file_operations.symlink
```

```
|file_operations.rename  
|boolean  
|query
```

```
|False
a|Filter by file_operations.rename

|file_operations.open
|boolean
|query
|False
a|Filter by file_operations.open

|file_operations.read
|boolean
|query
|False
a|Filter by file_operations.read

|file_operations.rename_dir
|boolean
|query
|False
a|Filter by file_operations.rename_dir

|file_operations.link
|boolean
|query
|False
a|Filter by file_operations.link

|file_operations.write
|boolean
|query
|False
a|Filter by file_operations.write

|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.

|fields
```



```
|array[string]
|query
|False
a|Specify the fields to return.

|max_records
|integer
|query
|False
a|Limit the number of records returned.

|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.

* Default value: 1

|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds. ONTAP
returns earlier if either max records or the end of the collection is
reached.

* Default value: 1
* Max value: 120
* Min value: 0

|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#fpolicy_event[fpolicy_event]]
a|

|===
```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "name": "event_nfs_close",
    "protocol": "cifs"
  }
}
```

====

== Error

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
```

```

|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|next
|link:href[href]
a|

```

```

|self
|link:href[href]
a|

```

```

|===

```

```

[#file_operations]
[.api-collapsible-fifth-title]
file_operations

```

Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.

The event will check the operations specified from all client requests using the protocol.

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

|close  
|boolean  
a|File close operations

|create  
|boolean  
a|File create operations

|create\_dir  
|boolean  
a|Directory create operations

|delete  
|boolean  
a|File delete operations

|delete\_dir  
|boolean  
a|Directory delete operations

|getattr  
|boolean  
a|Get attribute operations

|link  
|boolean  
a|Link operations

|lookup  
|boolean  
a|Lookup operations

|open  
|boolean  
a|File open operations

|read  
|boolean

a|File read operations

|rename

|boolean

a|File rename operations

|rename\_dir

|boolean

a|Directory rename operations

|setattr

|boolean

a|Set attribute operations

|symlink

|boolean

a|Symbolic link operations

|write

|boolean

a|File write operations

|===

[#filters]

[.api-collapsible-fifth-title]

filters

Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

[cols=3\*,options=header]

|===

|Name

|Type

|Description

```
|close_with_modification
|boolean
a|Filter the client request for close with modification.

|close_with_read
|boolean
a|Filter the client request for close with read.

|close_without_modification
|boolean
a|Filter the client request for close without modification.

|exclude_directory
|boolean
a|Filter the client requests for directory operations. When this filter is
specified directory operations are not monitored.

|first_read
|boolean
a|Filter the client requests for the first-read.

|first_write
|boolean
a|Filter the client requests for the first-write.

|monitor_ads
|boolean
a|Filter the client request for alternate data stream.

|offline_bit
|boolean
a|Filter the client request for offline bit set. FPolicy server receives
notification only when offline files are accessed.

|open_with_delete_intent
|boolean
a|Filter the client request for open with delete intent.
```

|open\_with\_write\_intent

|boolean

a|Filter the client request for open with write intent.

|setattr\_with\_access\_time\_change

|boolean

a|Filter the client setattr requests for changing the access time of a file or directory.

|setattr\_with\_allocation\_size\_change

|boolean

a|Filter the client setattr requests for changing the allocation size of a file.

|setattr\_with\_creation\_time\_change

|boolean

a|Filter the client setattr requests for changing the creation time of a file or directory.

|setattr\_with\_dacl\_change

|boolean

a|Filter the client setattr requests for changing dacl on a file or directory.

|setattr\_with\_group\_change

|boolean

a|Filter the client setattr requests for changing group of a file or directory.

|setattr\_with\_mode\_change

|boolean

a|Filter the client setattr requests for changing the mode bits on a file or directory.

|setattr\_with\_modify\_time\_change

|boolean

a|Filter the client setattr requests for changing the modification time of a file or directory.



```
|setattr_with_owner_change
|boolean
a|Filter the client setattr requests for changing owner of a file or
directory.
```

```
|setattr_with_sacl_change
|boolean
a|Filter the client setattr requests for changing sacl on a file or
directory.
```

```
|setattr_with_size_change
|boolean
a|Filter the client setattr requests for changing the size of a file.
```

```
|write_with_size_change
|boolean
a|Filter the client request for write with size change.
```

```
|===
```

```
[#fpolicy_event]
[.api-collapsible-fifth-title]
fpolicy_event
```

The information that a FPolicy process needs to determine what file access operations to monitor and for which of the monitored events notifications should be sent to the external FPolicy server.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|file_operations
|link:#file_operations[file_operations]
a|Specifies the file operations for the FPolicy event. You must specify a
valid protocol in the protocol parameter.
The event will check the operations specified from all client requests
using the protocol.
```

|filters  
|link:#filters[filters]  
a|Specifies the list of filters for a given file operation for the specified protocol.  
When you specify the filters, you must specify the valid protocols and a valid file operations.

|name  
|string  
a|Specifies the name of the FPolicy event.

|protocol  
|string  
a|Protocol for which event is created. If you specify protocol, then you must also specify a valid value for the file operation parameters.  
The value of this parameter must be one of the following:

\*\*\*\*\* cifs - for the CIFS protocol.

\*\*\*\*\* nfsv3 - for the NFSv3 protocol.

\*\*\*\*\* nfsv4 - for the NFSv4 protocol.

|volume\_monitoring  
|boolean  
a|Specifies whether volume operation monitoring is required.

|===

[#error\_arguments]  
[.api-collapsible-fifth-title]  
error\_arguments

[cols=3\*,options=header]

|===

|Name  
|Type  
|Description

|code  
|string

```

a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

```

[[IDfe33292b1e3aedd6a330837b8d599fc8]]

= Create the FPolicy event configuration for an SVM

[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-block]#`/protocols/fpolicy/{svm.uuid}/events`#

\*Introduced In:\* 9.6

Creates an FPolicy event configuration for a specified SVM. FPolicy event creation is allowed only on data SVMs. When a protocol is specified, you must specify a file operation or a file operation and filters.

== Required properties

- \* `svm.uuid` - Existing SVM in which to create the FPolicy event.
- \* `name` - Name of the FPolicy event.

== Recommended optional properties

- \* `file-operations` - List of file operations to monitor.
- \* `protocol` - Protocol for which the file operations should be monitored.
- \* `filters` - List of filters for the specified file operations.

== Default property values

If not specified in POST, the following default property values are assigned:

- \* `file\_operations.+++` - `_false_`
- \* `filters.+++` - `_false_`
- \* `volume-monitoring` - `_false_`

== Related ONTAP commands

- \* `fpolicy policy event create`

== Learn more

\*

xref:{relative\_path}protocols\_fpolicy\_svm.uuid\_events\_endpoint\_overview.html[DOC /protocols/fpolicy/{svm.uuid}/events]

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|return_records
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|The default is false. If set to true, the records are returned.
```

```
* Default value:
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```

```
== Request Body
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|file_operations
```

```
|link:#file_operations[file_operations]
```

```
a|Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.
```

```
The event will check the operations specified from all client requests using the protocol.
```

```
|filters
```

```
|link:#filters[filters]
```

```
a|Specifies the list of filters for a given file operation for the
```

specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

```
|name
|string
a|Specifies the name of the FPolicy event.
```

```
|protocol
|string
a|Protocol for which event is created. If you specify protocol, then you
must also specify a valid value for the file operation parameters.
The value of this parameter must be one of the following:
```

```
***** cifs - for the CIFS protocol.
```

```
***** nfsv3 - for the NFSv3 protocol.
```

```
***** nfsv4 - for the NFSv4 protocol.
```

```
|volume_monitoring
|boolean
a|Specifies whether volume operation monitoring is required.
```

```
|===
```

.Example request

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "name": "event_nfs_close",
  "protocol": "cifs"
}
```

```
====
```

```
== Response
```

Status: 201, Created

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#fpolicy_event[fpolicy_event]]
a|

|===

.Example response
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "name": "event_nfs_close",
    "protocol": "cifs"
  }
}
=====

== Error

```

Status: Default

```

|===
| Error Code | Description

| 9764929
| The file operation is not supported by the protocol

| 9764955
| The filter is not supported by the protocol

| 9764930
| The filter is not supported by any of the file operations

| 9764946
| The protocol is specified without a file operation or a file operation
and filter pair
|===

```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```



```

}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#file_operations]
[.api-collapsible-fifth-title]
file_operations

```

Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter. The event will check the operations specified from all client requests using the protocol.

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|close
|boolean
a|File close operations

|create
|boolean
a|File create operations

|create_dir
|boolean
a|Directory create operations

|delete
|boolean
a|File delete operations

|delete_dir

```

|boolean  
a|Directory delete operations

|getattr  
|boolean  
a|Get attribute operations

|link  
|boolean  
a|Link operations

|lookup  
|boolean  
a|Lookup operations

|open  
|boolean  
a|File open operations

|read  
|boolean  
a|File read operations

|rename  
|boolean  
a|File rename operations

|rename\_dir  
|boolean  
a|Directory rename operations

|setattr  
|boolean  
a|Set attribute operations

|symlink  
|boolean  
a|Symbolic link operations

```
|write
|boolean
a|File write operations
```

```
|===
```

```
[#filters]
[.api-collapsible-fifth-title]
filters
```

Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|close_with_modification
|boolean
a|Filter the client request for close with modification.
```

```
|close_with_read
|boolean
a|Filter the client request for close with read.
```

```
|close_without_modification
|boolean
a|Filter the client request for close without modification.
```

```
|exclude_directory
|boolean
a|Filter the client requests for directory operations. When this filter is specified directory operations are not monitored.
```

```
|first_read
|boolean
a|Filter the client requests for the first-read.
```

```
|first_write
|boolean
a|Filter the client requests for the first-write.
```

```
|monitor_ads
|boolean
a|Filter the client request for alternate data stream.
```

```
|offline_bit
|boolean
a|Filter the client request for offline bit set. FPolicy server receives notification only when offline files are accessed.
```

```
|open_with_delete_intent
|boolean
a|Filter the client request for open with delete intent.
```

```
|open_with_write_intent
|boolean
a|Filter the client request for open with write intent.
```

```
|setattr_with_access_time_change
|boolean
a|Filter the client setattr requests for changing the access time of a file or directory.
```

```
|setattr_with_allocation_size_change
|boolean
a|Filter the client setattr requests for changing the allocation size of a file.
```

```
|setattr_with_creation_time_change
|boolean
a|Filter the client setattr requests for changing the creation time of a file or directory.
```

```
|setattr_with_dacl_change
|boolean
a|Filter the client setattr requests for changing dacl on a file or
directory.
```

```
|setattr_with_group_change
|boolean
a|Filter the client setattr requests for changing group of a file or
directory.
```

```
|setattr_with_mode_change
|boolean
a|Filter the client setattr requests for changing the mode bits on a file
or directory.
```

```
|setattr_with_modify_time_change
|boolean
a|Filter the client setattr requests for changing the modification time of
a file or directory.
```

```
|setattr_with_owner_change
|boolean
a|Filter the client setattr requests for changing owner of a file or
directory.
```

```
|setattr_with_sacl_change
|boolean
a|Filter the client setattr requests for changing sacl on a file or
directory.
```

```
|setattr_with_size_change
|boolean
a|Filter the client setattr requests for changing the size of a file.
```

```
|write_with_size_change
|boolean
a|Filter the client request for write with size change.
```

```
|===
```

```
[#fpolicy_event]  
[.api-collapsible-fifth-title]  
fpolicy_event
```

The information that a FPolicy process needs to determine what file access operations to monitor and for which of the monitored events notifications should be sent to the external FPolicy server.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|file_operations
```

```
|link:#file_operations[file_operations]
```

a|Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.

The event will check the operations specified from all client requests using the protocol.

```
|filters
```

```
|link:#filters[filters]
```

a|Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

```
|name
```

```
|string
```

a|Specifies the name of the FPolicy event.

```
|protocol
```

```
|string
```

a|Protocol for which event is created. If you specify protocol, then you must also specify a valid value for the file operation parameters.

The value of this parameter must be one of the following:

```
***** cifs - for the CIFS protocol.
```

\*\*\*\*\* nfsv3 - for the NFSv3 protocol.

\*\*\*\*\* nfsv4 - for the NFSv4 protocol.

|volume\_monitoring

|boolean

a|Specifies whether volume operation monitoring is required.

|===

[#href]

[.api-collapsible-fifth-title]

href

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|href

|string

a|

|===

[#\_links]

[.api-collapsible-fifth-title]

\_links

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|next

|link:href[href]

a|

|self

|link:href[href]

```

a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

```



```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[IDf24a0936c21f74a0575f06b5394b9e22]]
= Delete a specific FPolicy event configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-
block]#`/protocols/fpolicy/{svm.uuid}/events/{name}`#
```

```
*Introduced In:* 9.6
```

Deletes a specific FPolicy event configuration for an SVM. A cluster-level FPolicy event configuration cannot be modified for a data SVM through REST. An FPolicy event that is attached to an FPolicy policy cannot be deleted.

```
== Related ONTAP commands
```

```
* `fpolicy policy event delete`
```

```
== Learn more
```

```
*
xref:{relative_path}protocols_fpolicy_svm.uuid_events_endpoint_overview.ht
ml[DOC /protocols/fpolicy/{svm.uuid}/events]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```

|Name
|Type
|In
|Required
|Description

|name
|string
|path
|True
a|

|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.

|===

== Response

```

Status: 200, Ok

```

== Error

```

Status: Default

```

|===
| Error Code | Description

| 9764874
| The FPolicy event is a cluster event

| 9764947
| The FPolicy event is attached to an FPolicy policy
|===

[cols=3*,options=header]
|===
|Name
|Type

```

```

|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

```

```

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

```

```
[[ID5cf26c95f095c31db6a2912d88bd9b00]]
```

= Retrieve a specific FPolicy event configuration for an SVM

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/fpolicy/{svm.uuid}/events/{name}`#
```

\*Introduced In:\* 9.6

Retrieves a specific FPolicy event configuration for an SVM. A cluster-level FPolicy event configuration cannot be retrieved for a data SVM through a REST API.

== Related ONTAP commands

\* `fpolicy policy event show`

== Learn more

\*

xref:{relative\_path}protocols\_fpolicy\_svm.uuid\_events\_endpoint\_overview.html[DOC /protocols/fpolicy/{svm.uuid}/events]

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name  
|Type  
|In  
|Required  
|Description
```

```
|name  
|string  
|path  
|True  
a|
```

```
|svm.uuid  
|string  
|path  
|True  
a|UUID of the SVM to which this object belongs.
```

```
|fields
|array[string]
|query
|False
a|Specify the fields to return.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|file_operations
|link:#file_operations[file_operations]
a|Specifies the file operations for the FPolicy event. You must specify a
valid protocol in the protocol parameter.
The event will check the operations specified from all client requests
using the protocol.

|filters
|link:#filters[filters]
a|Specifies the list of filters for a given file operation for the
specified protocol.
When you specify the filters, you must specify the valid protocols and a
valid file operations.

|name
|string
a|Specifies the name of the FPolicy event.

|protocol
|string
a|Protocol for which event is created. If you specify protocol, then you
must also specify a valid value for the file operation parameters.
The value of this parameter must be one of the following:

***** cifs - for the CIFS protocol.
```

```

***** nfsv3 - for the NFSv3 protocol.

***** nfsv4 - for the NFSv4 protocol.

|volume_monitoring
|boolean
a|Specifies whether volume operation monitoring is required.

|===

.Example response
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "name": "event_nfs_close",
  "protocol": "cifs"
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{

```

```

"error": {
  "arguments": {
    "code": "string",
    "message": "string"
  },
  "code": "4",
  "message": "entry doesn't exist",
  "target": "uuid"
}
}

```

====

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block

```

====

```

[#file_operations]
[.api-collapsible-fifth-title]
file_operations

```

Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.

The event will check the operations specified from all client requests using the protocol.

```

[cols=3*,options=header]

```

```

|===

```

```

|Name
|Type
|Description

```

```

|close
|boolean
a|File close operations

```

```

|create
|boolean
a|File create operations

```

```

|create_dir
|boolean

```



a|Directory create operations

|delete

|boolean

a|File delete operations

|delete\_dir

|boolean

a|Directory delete operations

|getattr

|boolean

a|Get attribute operations

|link

|boolean

a|Link operations

|lookup

|boolean

a|Lookup operations

|open

|boolean

a|File open operations

|read

|boolean

a|File read operations

|rename

|boolean

a|File rename operations

|rename\_dir

|boolean

a|Directory rename operations

```
|setattr
|boolean
a|Set attribute operations
```

```
|symlink
|boolean
a|Symbolic link operations
```

```
|write
|boolean
a|File write operations
```

```
|===
```

```
[#filters]
[.api-collapsible-fifth-title]
filters
```

Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|close_with_modification
|boolean
a|Filter the client request for close with modification.
```

```
|close_with_read
|boolean
a|Filter the client request for close with read.
```

```
|close_without_modification
|boolean
```

a|Filter the client request for close without modification.

|exclude\_directory

|boolean

a|Filter the client requests for directory operations. When this filter is specified directory operations are not monitored.

|first\_read

|boolean

a|Filter the client requests for the first-read.

|first\_write

|boolean

a|Filter the client requests for the first-write.

|monitor\_ads

|boolean

a|Filter the client request for alternate data stream.

|offline\_bit

|boolean

a|Filter the client request for offline bit set. FPolicy server receives notification only when offline files are accessed.

|open\_with\_delete\_intent

|boolean

a|Filter the client request for open with delete intent.

|open\_with\_write\_intent

|boolean

a|Filter the client request for open with write intent.

|setattr\_with\_access\_time\_change

|boolean

a|Filter the client setattr requests for changing the access time of a file or directory.

|setattr\_with\_allocation\_size\_change

|boolean

a|Filter the client setattr requests for changing the allocation size of a file.

|setattr\_with\_creation\_time\_change

|boolean

a|Filter the client setattr requests for changing the creation time of a file or directory.

|setattr\_with\_dacl\_change

|boolean

a|Filter the client setattr requests for changing dacl on a file or directory.

|setattr\_with\_group\_change

|boolean

a|Filter the client setattr requests for changing group of a file or directory.

|setattr\_with\_mode\_change

|boolean

a|Filter the client setattr requests for changing the mode bits on a file or directory.

|setattr\_with\_modify\_time\_change

|boolean

a|Filter the client setattr requests for changing the modification time of a file or directory.

|setattr\_with\_owner\_change

|boolean

a|Filter the client setattr requests for changing owner of a file or directory.

|setattr\_with\_sacl\_change

|boolean

a|Filter the client setattr requests for changing sacl on a file or directory.

```
|setattr_with_size_change
|boolean
a|Filter the client setattr requests for changing the size of a file.
```

```
|write_with_size_change
|boolean
a|Filter the client request for write with size change.
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|arguments
```

```
|array[link:#error_arguments[error_arguments]]
```

```
a|Message arguments
```

```
|code
```

```
|string
```

```
a|Error code
```

```
|message
```

```
|string
```

```
a|Error message
```

```
|target
```

```
|string
```

```
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
```

```
====
```

```
[[ID1a4746a035d22d5b9efd726e7122ea3e]]
```

```
= Update a specific FPolicy event configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-  
block]#`/protocols/fpolicy/{svm.uuid}/events/{name}`#
```

```
*Introduced In:* 9.6
```

Updates a specific FPolicy event configuration for an SVM. A cluster-level FPolicy event configuration cannot be modified for a data SVM through REST. When the file operations and filters fields are modified, the previous values are retained and new values are added to the list of previous values. To remove a particular file operation or filter, set its value to false in the request.

```
== Related ONTAP commands
```

```
* `fpolicy policy event modify`
```

```
== Learn more
```

```
*
xref:{relative_path}protocols_fpolicy_svm.uuid_events_endpoint_overview.ht
ml[DOC /protocols/fpolicy/{svm.uuid}/events]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
|Type
|In
|Required
|Description
```

```
|name
|string
|path
|True
a|
```

```
|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.
```

```
|===
```

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|file_operations
|link:#file_operations[file_operations]
a|Specifies the file operations for the FPolicy event. You must specify a
valid protocol in the protocol parameter.
The event will check the operations specified from all client requests
using the protocol.
```

```
|filters
|link:#filters[filters]
a|Specifies the list of filters for a given file operation for the
specified protocol.
When you specify the filters, you must specify the valid protocols and a
valid file operations.
```

```
|name
|string
a|Specifies the name of the FPolicy event.
```

```
|protocol
|string
a|Protocol for which event is created. If you specify protocol, then you
must also specify a valid value for the file operation parameters.
The value of this parameter must be one of the following:
```

```
***** cifs - for the CIFS protocol.
```

```
***** nfsv3 - for the NFSv3 protocol.
```

```
***** nfsv4 - for the NFSv4 protocol.
```

```
|volume_monitoring
|boolean
a|Specifies whether volume operation monitoring is required.
```

```
|===
```

```
.Example request
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```
{
  "name": "event_nfs_close",
  "protocol": "cifs"
}
```

```
=====
```

```
== Response
```



Status: 200, Ok

== Error

Status: Default

```
|===  
| Error Code | Description  
  
| 9764873  
| The event is a cluster event  
  
| 9764929  
| The file operation is not supported by the protocol  
  
| 9764955  
| The filter is not supported by the protocol  
  
| 9764930  
| The filter is not supported by any of the file operations  
  
| 9764946  
| The protocol is specified without file operation or a file operation and  
filter pair  
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====

```

```

[#file_operations]
[.api-collapsible-fifth-title]
file_operations

```

Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter. The event will check the operations specified from all client requests using the protocol.

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|close
|boolean
a|File close operations

```

```

|create
|boolean
a|File create operations

```

```

|create_dir

```

|boolean  
a|Directory create operations

|delete  
|boolean  
a|File delete operations

|delete\_dir  
|boolean  
a|Directory delete operations

|getattr  
|boolean  
a|Get attribute operations

|link  
|boolean  
a|Link operations

|lookup  
|boolean  
a|Lookup operations

|open  
|boolean  
a|File open operations

|read  
|boolean  
a|File read operations

|rename  
|boolean  
a|File rename operations

|rename\_dir  
|boolean  
a|Directory rename operations

```
|setattr
|boolean
a|Set attribute operations
```

```
|symlink
|boolean
a|Symbolic link operations
```

```
|write
|boolean
a|File write operations
```

```
|===
```

```
[#filters]
[.api-collapsible-fifth-title]
filters
```

Specifies the list of filters for a given file operation for the specified protocol.

When you specify the filters, you must specify the valid protocols and a valid file operations.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|close_with_modification
|boolean
a|Filter the client request for close with modification.
```

```
|close_with_read
|boolean
a|Filter the client request for close with read.
```

```
|close_without_modification
```

|boolean

a|Filter the client request for close without modification.

|exclude\_directory

|boolean

a|Filter the client requests for directory operations. When this filter is specified directory operations are not monitored.

|first\_read

|boolean

a|Filter the client requests for the first-read.

|first\_write

|boolean

a|Filter the client requests for the first-write.

|monitor\_ads

|boolean

a|Filter the client request for alternate data stream.

|offline\_bit

|boolean

a|Filter the client request for offline bit set. FPolicy server receives notification only when offline files are accessed.

|open\_with\_delete\_intent

|boolean

a|Filter the client request for open with delete intent.

|open\_with\_write\_intent

|boolean

a|Filter the client request for open with write intent.

|setattr\_with\_access\_time\_change

|boolean

a|Filter the client setattr requests for changing the access time of a file or directory.

|setattr\_with\_allocation\_size\_change

|boolean

a|Filter the client setattr requests for changing the allocation size of a file.

|setattr\_with\_creation\_time\_change

|boolean

a|Filter the client setattr requests for changing the creation time of a file or directory.

|setattr\_with\_dacl\_change

|boolean

a|Filter the client setattr requests for changing dacl on a file or directory.

|setattr\_with\_group\_change

|boolean

a|Filter the client setattr requests for changing group of a file or directory.

|setattr\_with\_mode\_change

|boolean

a|Filter the client setattr requests for changing the mode bits on a file or directory.

|setattr\_with\_modify\_time\_change

|boolean

a|Filter the client setattr requests for changing the modification time of a file or directory.

|setattr\_with\_owner\_change

|boolean

a|Filter the client setattr requests for changing owner of a file or directory.

|setattr\_with\_sacl\_change

|boolean

a|Filter the client setattr requests for changing sacl on a file or directory.

```
|setattr_with_size_change
|boolean
a|Filter the client setattr requests for changing the size of a file.
```

```
|write_with_size_change
|boolean
a|Filter the client request for write with size change.
```

```
|===
```

```
[#fpolicy_event]
[.api-collapsible-fifth-title]
fpolicy_event
```

The information that a FPolicy process needs to determine what file access operations to monitor and for which of the monitored events notifications should be sent to the external FPolicy server.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|file_operations
|link:#file_operations[file_operations]
a|Specifies the file operations for the FPolicy event. You must specify a valid protocol in the protocol parameter.
The event will check the operations specified from all client requests using the protocol.
```

```
|filters
|link:#filters[filters]
a|Specifies the list of filters for a given file operation for the specified protocol.
When you specify the filters, you must specify the valid protocols and a valid file operations.
```

```
|name
|string
```

a|Specifies the name of the FPolicy event.

|protocol

|string

a|Protocol for which event is created. If you specify protocol, then you must also specify a valid value for the file operation parameters.

The value of this parameter must be one of the following:

\*\*\*\*\* cifs - for the CIFS protocol.

\*\*\*\*\* nfsv3 - for the NFSv3 protocol.

\*\*\*\*\* nfsv4 - for the NFSv4 protocol.

|volume\_monitoring

|boolean

a|Specifies whether volume operation monitoring is required.

|===

[#error\_arguments]

[.api-collapsible-fifth-title]

error\_arguments

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|code

|string

a|Argument code

|message

|string

a|Message argument

|===



```

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

:leveloffset: -1

= Manage SVM FPolicy configuration

:leveloffset: +1

[[ID05dd375a3d19922016289fc5aed51631]]

```

```
= Protocols fpolicy svm.uuid policies endpoint overview
```

```
== Overview
```

The FPolicy policy acts as a container for different constituents of the FPolicy such as FPolicy events and the FPolicy engine. It also provides a platform for policy management functions, such as policy enabling and disabling. As part of FPolicy policy configuration, you can specify the name of policy, the SVM to which it belongs, the FPolicy events to monitor, the FPolicy engine to which the generated notifications are sent and the policy priority. FPolicy policy configuration also allows you to configure the file access behaviour when the primary and secondary servers are down. Under such circumstances, if the "mandatory" field is set to true, file access is denied.

Each FPolicy policy is associated with a scope which allows you to restrain the scope of the policy to specified storage objects such as volume, shares and export or to a set of file extensions such as .txt, .jpeg. An FPolicy policy can be configured to send notifications, to the FPolicy server or for native file blocking which uses the file extension specified in the policy scope. An SVM can have multiple FPolicy policies which can be enabled or disabled independently of each other.

```
== Examples
```

```
=== Creating an FPolicy policy
```

Use the following API to create an FPolicy policy configuration. Note that the `_return_records=true_query` parameter used to obtain the newly created entry in the response.

```
'''
```

```
----
```

```
# The API:
```

```
POST /protocols/fpolicy/{svm.uuid}/policies
```

```
# The call:
```

```
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-b64a-0050568eeb34/policies?return_records=true" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"engine\": { \"name\": \"engine1\" }, \"events\": [ { \"name\": \"cifs\" }, { \"name\": \"nfs\" } ], \"mandatory\": true, \"name\": \"FPolicy_policy_0\", \"scope\": { \"exclude_export_policies\": [ \"export_poll\" ],
```

```
\\"exclude_extension\\": [ \\"txt\\", \\"png\\" ], \\"exclude_shares\\": [ \\"sh1\\" ], \\"exclude_volumes\\": [ \\"vol0\\" ], \\"include_export_policies\\": [ \\"export_pol10\\" ], \\"include_extension\\": [ \\"pdf\\" ], \\"include_shares\\": [ \\"sh2\\", \\"sh3\\" ], \\"include_volumes\\": [ \\"vol1\\", \\"vol2\\" ] } }"
```

# The response:

```
{  
  "num_records": 1,  
  "records": [  
    {  
      "name": "FPolicy_policy_0",  
      "events": [  
        {  
          "name": "cifs"  
        },  
        {  
          "name": "nfs"  
        }  
      ],  
      "engine": {  
        "name": "engine1"  
      },  
      "scope": {  
        "include_shares": [  
          "sh2",  
          "sh3"  
        ],  
        "exclude_shares": [  
          "sh1"  
        ],  
        "include_volumes": [  
          "vol1",  
          "vol2"  
        ],  
        "exclude_volumes": [  
          "vol0"  
        ],  
        "include_export_policies": [  
          "export_pol10"  
        ],  
        "exclude_export_policies": [  
          "export_pol1"  
        ],  
        "include_extension": [  
          "pdf"  
        ]  
      }  
    }  
  ]  
}
```

```

    ],
    "exclude_extension": [
        "txt",
        "png"
    ]
},
"mandatory": true
}
]
}
----

'''

=== Creating and enable an FPolicy policy

'''

----

# The API:
POST /protocols/fpolicy/{svm.uuid}/policies

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"priority\":
1, \"engine\": { \"name\": \"engine1\" }, \"events\": [ { \"name\":
\"cifs\" }, { \"name\": \"nfs\" } ], \"mandatory\": true, \"name\":
\"FPolicy_policy_on\", \"scope\": { \"exclude_export_policies\": [
\"export_pol1\" ], \"exclude_extension\": [ \"txt\", \"png\" ],
\"exclude_shares\": [ \"sh1\" ], \"exclude_volumes\": [ \"vol0\" ],
\"include_export_policies\": [ \"export_pol10\" ], \"include_extension\":
[ \"pdf\" ], \"include_shares\": [ \"sh2\", \"sh3\" ],
\"include_volumes\": [ \"vol1\", \"vol2\" ] } }"

# The response:
{
"num_records": 1,
"records": [
{
"name": "FPolicy_policy_0",
"priority": 1,
"events": [
{
"name": "cifs"

```

```

    },
    {
        "name": "nfs"
    }
],
"engine": {
    "name": "engine1"
},
"scope": {
    "include_shares": [
        "sh2",
        "sh3"
    ],
    "exclude_shares": [
        "sh1"
    ],
    "include_volumes": [
        "vol1",
        "vol2"
    ],
    "exclude_volumes": [
        "vol0"
    ],
    "include_export_policies": [
        "export_pol10"
    ],
    "exclude_export_policies": [
        "export_pol1"
    ],
    "include_extension": [
        "pdf"
    ],
    "exclude_extension": [
        "txt",
        "png"
    ]
},
"mandatory": true
}
]
}
-----

'''

```

=== Creating an FPolicy policy with the minimum required fields and a

```

native engine

'''

-----

# The API:
POST /protocols/fpolicy/{svm.uuid}/policies

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"events\": [
{ \"name\": \"cifs\" }, { \"name\": \"nfs\" } ], \"name\":
\"pol_minimum_fields\", \"scope\": { \"include_volumes\": [ \"vol1\",
\"vol2\" ] } }"

# The response:
{
  "num_records": 1,
  "records": [
    {
      "name": "pol_minimum_fields",
      "events": [
        {
          "name": "cifs"
        },
        {
          "name": "nfs"
        }
      ],
      "scope": {
        "include_volumes": [
          "vol1",
          "vol2"
        ]
      }
    }
  ]
}

-----

'''

=== Retrieving all the FPolicy policy configurations for an SVM

```

```

'''
----

# The API:
GET /protocols/fpolicy/{svm.uuid}/policies

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies?fields=*&return_records=true&return_timeout=15"
-H "accept: application/json"

# The response:
{
"records": [
  {
    "svm": {
      "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
    },
    "name": "pol0",
    "enabled": false,
    "events": [
      {
        "name": "cifs"
      },
      {
        "name": "nfs"
      }
    ],
    "engine": {
      "name": "engine1"
    },
    "scope": {
      "include_shares": [
        "sh2",
        "sh3"
      ],
      "exclude_shares": [
        "sh1"
      ],
      "include_volumes": [
        "vol1",
        "vol2"
      ],
      "exclude_volumes": [
        "vol0"
      ]
    }
  }
]
}

```

```

    ],
    "include_export_policies": [
        "export_poll0"
    ],
    "exclude_export_policies": [
        "export_poll1"
    ],
    "include_extension": [
        "pdf"
    ],
    "exclude_extension": [
        "txt",
        "png"
    ]
},
"mandatory": true
},
{
    "svm": {
        "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
    },
    "name": "FPolicy_policy_on",
    "enabled": true,
    "priority": 1,
    "events": [
        {
            "name": "cifs"
        },
        {
            "name": "nfs"
        }
    ],
    "engine": {
        "name": "engine1"
    },
    "scope": {
        "include_shares": [
            "sh2",
            "sh3"
        ],
        "exclude_shares": [
            "sh1"
        ],
        "include_volumes": [
            "vol1",
            "vol2"
        ]
    }
}

```



```

    ],
    "exclude_volumes": [
        "vol0"
    ],
    "include_export_policies": [
        "export_pol10"
    ],
    "exclude_export_policies": [
        "export_pol1"
    ],
    "include_extension": [
        "pdf"
    ],
    "exclude_extension": [
        "txt",
        "png"
    ]
    ],
    "mandatory": true
},
{
    "svm": {
        "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
    },
    "name": "cluster_pol",
    "enabled": false,
    "events": [
        {
            "name": "cluster"
        }
    ],
    "engine": {
        "name": "native"
    },
    "mandatory": true
},
{
    "svm": {
        "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
    },
    "name": "pol_minimum_fields",
    "enabled": false,
    "events": [
        {
            "name": "cifs"
        }
    ],

```

```

    {
      "name": "nfs"
    }
  ],
  "engine": {
    "name": "native"
  },
  "scope": {
    "include_volumes": [
      "vol1",
      "vol2"
    ]
  },
  "mandatory": true
}
],
"num_records": 4
}

```

----

'''

=== Retrieving all of the FPolicy policy configurations for the FPolicy engine "engine1" for an SVM

'''

----

# The API:

GET /protocols/fpolicy/{svm.uuid}/policies/{name}

# The call:

```

curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-b64a-0050568eeb34/policies?engine.name=engine1&fields=*&return_records=true&return_timeout=15" -H "accept: application/json"

```

# The response:

```

{
  "records": [
    {
      "svm": {
        "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
      },
      "name": "pol10",

```

```
"enabled": false,
"events": [
  {
    "name": "cifs"
  },
  {
    "name": "nfs"
  }
],
"engine": {
  "name": "engine1"
},
"scope": {
  "include_export_policies": [
    "export_poll0"
  ],
  "exclude_export_policies": [
    "export_poll1"
  ],
  "include_extension": [
    "pdf"
  ],
  "exclude_extension": [
    "txt",
    "png"
  ]
},
"mandatory": true
},
{
  "svm": {
    "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
  },
  "name": "FPolicy_policy_on",
  "enabled": true,
  "priority": 1,
  "events": [
    {
      "name": "cifs"
    },
    {
      "name": "nfs"
    }
  ],
  "engine": {
    "name": "engine1"
  }
}
```

```

    },
    "scope": {
      "include_shares": [
        "sh2",
        "sh3"
      ],
      "exclude_shares": [
        "sh1"
      ],
      "include_volumes": [
        "vol1",
        "vol2"
      ],
      "exclude_volumes": [
        "vol0"
      ],
      "include_export_policies": [
        "export_pol10"
      ],
      "exclude_export_policies": [
        "export_pol1"
      ],
      "include_extension": [
        "pdf"
      ],
      "exclude_extension": [
        "txt",
        "png"
      ]
    ],
    "mandatory": true
  }
],
"num_records": 2
}
----

'''

=== Retrieving a particular FPolicy policy configuration for an SVM

'''

----

# The API:

```

```
GET /protocols/fpolicy/{svm.uuid}/policies/{name}
```

```
# The call:
```

```
curl -X GET "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-b64a-0050568eeb34/policies/pol0" -H "accept: application/json"
```

```
# The response:
```

```
{
  "svm": {
    "uuid": "a00fac5d-0164-11e9-b64a-0050568eeb34"
  },
  "name": "pol0",
  "enabled": false,
  "events": [
    {
      "name": "cifs"
    },
    {
      "name": "nfs"
    }
  ],
  "engine": {
    "name": "engine1"
  },
  "scope": {
    "include_shares": [
      "sh2",
      "sh3"
    ],
    "exclude_shares": [
      "sh1"
    ],
    "include_volumes": [
      "vol1",
      "vol2"
    ],
    "exclude_volumes": [
      "vol0"
    ],
    "include_export_policies": [
      "export_pol10"
    ],
    "exclude_export_policies": [
      "export_pol1"
    ],
    "include_extension": [
```

```

    "pdf"
  ],
  "exclude_extension": [
    "txt",
    "png"
  ]
},
"mandatory": true
}
-----

'''

=== Updating a particular FPolicy policy

'''

-----

# The API:
PATCH /protocols/fpolicy/{svm.uuid}/policies/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies/pol0" -H "accept: application/json" -H
"Content-Type: application/json" -d "{ \"engine\": { \"name\": \"native\"
}, \"events\": [ { \"name\": \"cifs\" } ], \"mandatory\": false,
\"scope\": { \"include_volumes\": [ \"*\"] } }"
-----

'''

=== Enabling a particular FPolicy policy

'''

-----

# The API:
PATCH /protocols/fpolicy/{svm.uuid}/policies/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-
b64a-0050568eeb34/policies/pol0" -H "accept: application/json" -H
"Content-Type: application/json" -d "{ \"enabled\": true, \"priority\":
3}"
-----

```

'''

=== Disabling a particular FPolicy policy

'''

----

# The API:

```
PATCH /protocols/fpolicy/{svm.uuid}/policies/{name}
```

# The call:

```
curl -X PATCH "https://<mgmt-ip>/api/protocols/fpolicy/a00fac5d-0164-11e9-  
b64a-0050568eeb34/policies/pol0" -H "accept: application/json" -H  
"Content-Type: application/json" -d "{ \"enabled\": true }"
```

----

'''

[[IDa93cbd2ead6360937f4e4926a2c3fd1e]]

= Retrieve the FPolicy configuration for an SVM

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-  
block]#`/protocols/fpolicy/{svm.uuid}/policies`#

\*Introduced In:\* 9.6

Retrieves the FPolicy policy configuration of an SVM. ONTAP allows the creation of a cluster level FPolicy policy that acts as a template for all the data SVMs belonging to the cluster. This cluster level FPolicy policy is also retrieved for the specified SVM.

== Related ONTAP commands

- \* `fpolicy policy show`
- \* `fpolicy policy scope show`

== Learn more

\*

xref:{relative\_path}protocols\_fpolicy\_svm.uuid\_policies\_endpoint\_overview.  
html[DOC /protocols/fpolicy/{svm.uuid}/policies]

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|priority
```

```
|integer
```

```
|query
```

```
|False
```

```
a|Filter by priority
```

```
|engine.name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by engine.name
```

```
|events.name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by events.name
```

```
|scope.include_shares
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by scope.include_shares
```

```
|scope.include_extension
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by scope.include_extension
```



```
|scope.include_volumes
|string
|query
|False
a|Filter by scope.include_volumes
```

```
|scope.include_export_policies
|string
|query
|False
a|Filter by scope.include_export_policies
```

```
|scope.exclude_export_policies
|string
|query
|False
a|Filter by scope.exclude_export_policies
```

```
|scope.exclude_shares
|string
|query
|False
a|Filter by scope.exclude_shares
```

```
|scope.exclude_volumes
|string
|query
|False
a|Filter by scope.exclude_volumes
```

```
|scope.exclude_extension
|string
|query
|False
a|Filter by scope.exclude_extension
```

```
|name
|string
|query
|False
```

a|Filter by name

|enabled

|boolean

|query

|False

a|Filter by enabled

|mandatory

|boolean

|query

|False

a|Filter by mandatory

|svm.uuid

|string

|path

|True

a|UUID of the SVM to which this object belongs.

|fields

|array[string]

|query

|False

a|Specify the fields to return.

|max\_records

|integer

|query

|False

a|Limit the number of records returned.

|return\_records

|boolean

|query

|False

a|The default is true for GET calls. When set to false, only the number of records is returned.

\* Default value: 1

```

|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds. ONTAP
returns earlier if either max records or the end of the collection is
reached.

* Default value: 1
* Max value: 120
* Min value: 0

|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.

|===

== Response

```

Status: 200, Ok

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of Records

|records
|array[link:#fpolicy_policy[fpolicy_policy]]
a|

```

|===

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "engine": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      }
    },
    "events": [
      "event_nfs_close",
      "event_open"
    ],
    "name": "fp_policy_1",
    "scope": {
      "exclude_export_policies": {
      },
      "exclude_extension": {
      },
      "exclude_shares": {
      },
      "exclude_volumes": [
        "vol1",
        "vol_svm1",
        "*"
      ],
      "include_export_policies": {
      },
      "include_extension": {
      },

```

```

    "include_shares": [
      "sh1",
      "share_cifs"
    ],
    "include_volumes": [
      "vol1",
      "vol_svm1"
    ]
  }
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

```

====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#fpolicy_engine_reference]
[.api-collapsible-fifth-title]
fpolicy_engine_reference

FPolicy external engine

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the FPolicy external engine.

|===

[#fpolicy_event_reference]
[.api-collapsible-fifth-title]
fpolicy_event_reference

FPolicy events

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_export_policies
|array[string]
a|

|exclude_extension
|array[string]
a|

|exclude_shares
|array[string]
a|

|exclude_volumes
|array[string]
a|

|include_export_policies
|array[string]

```



```

a|

|include_extension
|array[string]
a|

|include_shares
|array[string]
a|

|include_volumes
|array[string]
a|

|===

[#fpolicy_policy]
[.api-collapsible-fifth-title]
fpolicy_policy

[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Specifies if the policy is enabled on the SVM or not. If no value is
mentioned for this field but priority is set, then this policy will be
enabled.

|engine
|link:#fpolicy_engine_reference[fpolicy_engine_reference]
a|FPolicy external engine

|events
|array[link:#fpolicy_event_reference[fpolicy_event_reference]]
a|

|mandatory
|boolean
a|Specifies what action to take on a file access event in a case when all
primary and secondary servers are down or no response is received from the

```

FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.

|name  
|string  
a|Specifies the name of the policy.

|priority  
|integer  
a|Specifies the priority that is assigned to this policy.

|scope  
|link:#scope[scope]  
a|

|===

[#error\_arguments]  
[.api-collapsible-fifth-title]  
error\_arguments

[cols=3\*,options=header]

|===  
|Name  
|Type  
|Description

|code  
|string  
a|Argument code

|message  
|string  
a|Message argument

|===

[#error]  
[.api-collapsible-fifth-title]  
error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[ID72c5496dbedce10c7f5d026555cece7c]]
= Create the FPolicy configuration for an SVM

[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-
block]#`/protocols/fpolicy/{svm.uuid}/policies`#

*Introduced In:* 9.6

Creates an FPolicy policy configuration for the specified SVM. To create
an FPolicy policy, you must specify the policy scope and the FPolicy
events to be monitored.

```

## Important notes:

- \* A single policy can monitor multiple events.
- \* An FPolicy engine is an optional field whose default value is set to native. A native engine can be used to simply block the file access based on the file extensions specified in the policy scope.
- \* To enable a policy, the policy priority must be specified. If the priority is not specified, the policy is created but it is not enabled.
- \* The "mandatory" field, if set to true, blocks the file access when the primary or secondary FPolicy servers are down.

### == Required properties

- \* ``svm.uuid`` - Existing SVM in which to create the FPolicy policy.
- \* ``events`` - Name of the events to monitor.
- \* ``name`` - Name of the FPolicy policy.
- \* ``scope`` - Scope of the policy. Can be limited to exports, volumes, shares or file extensions.
- \* ``priority`` - Priority of the policy (ranging from 1 to 10).

### == Default property values

- \* ``mandatory`` - `_true_`
- \* ``engine`` - `_native_`

### == Related ONTAP commands

- \* ``fpolicy policy scope create``
- \* ``fpolicy policy create``
- \* ``fpolicy enable``

### == Learn more

\*  
`xref:{relative_path}protocols_fpolicy_svm.uuid_policies_endpoint_overview.html[DOC /protocols/fpolicy/{svm.uuid}/policies]`

### == Parameters

`[cols=5*,options=header]`

|===

|Name

|Type

|In

|Required

```

|Description

|return_records
|boolean
|query
|False
a|The default is false. If set to true, the records are returned.

* Default value:

|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.

|===

== Request Body

[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Specifies if the policy is enabled on the SVM or not. If no value is
mentioned for this field but priority is set, then this policy will be
enabled.

|engine
|link:#fpolicy_engine_reference[fpolicy_engine_reference]
a|FPolicy external engine

|events
|array[link:#fpolicy_event_reference[fpolicy_event_reference]]
a|

|mandatory
|boolean

```

a|Specifies what action to take on a file access event in a case when all primary and secondary servers are down or no response is received from the FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.

|name

|string

a|Specifies the name of the policy.

|priority

|integer

a|Specifies the priority that is assigned to this policy.

|scope

|link:#scope[scope]

a|

|===

.Example request

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "engine": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "events": [
    "event_nfs_close",
    "event_open"
  ],
  "name": "fp_policy_1",
  "scope": {
    "exclude_export_policies": {
    },
    "exclude_extension": {
    },
    "exclude_shares": {
    },
  },
}
```

```

"exclude_volumes": [
  "vol1",
  "vol_svm1",
  "*"
],
"include_export_policies": {
},
"include_extension": {
},
"include_shares": [
  "sh1",
  "share_cifs"
],
"include_volumes": [
  "vol1",
  "vol_svm1"
]
}
}
====

== Response

```

Status: 201, Created

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of Records

|records
|array[link:#fpolicy_policy[fpolicy_policy]]
a|

|===

```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "engine": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      }
    }
  },
  "events": [
    "event_nfs_close",
    "event_open"
  ],
  "name": "fp_policy_1",
  "scope": {
    "exclude_export_policies": {
    },
    "exclude_extension": {
    },
    "exclude_shares": {
    },
    "exclude_volumes": [
      "vol1",
      "vol_svm1",
      "*"
    ],
    "include_export_policies": {
    },
    "include_extension": {
    },
    "include_shares": [
      "sh1",
      "share_cifs"
    ]
  }
}
```



```

    ],
    "include_volumes": [
        "vol1",
        "vol_svm1"
    ]
}
}
}
}
====

== Error

```

## Status: Default

### ONTAP Error Response Codes

```

|====
| Error Code | Description
|
| 9765027
| FPolicy creation is successful but it cannot be enabled as the priority
| is already in use by another policy
|
| 9764898
| An FPolicy policy cannot be created without defining its scope
|====

```

```
[cols=3*,options=header]
```

```
|====
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|====
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====

```

```

[#href]
[.api-collapsible-fifth-title]
href

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|href
|string
a|

```

```

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|self
|link:#href[href]
a|

|===

[#fpolicy_engine_reference]
[.api-collapsible-fifth-title]
fpolicy_engine_reference

FPolicy external engine

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the FPolicy external engine.

|===

[#fpolicy_event_reference]
[.api-collapsible-fifth-title]
fpolicy_event_reference

FPolicy events

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]

```

```

a|

|name
|string
a|

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_export_policies
|array[string]
a|

|exclude_extension
|array[string]
a|

|exclude_shares
|array[string]
a|

|exclude_volumes
|array[string]
a|

|include_export_policies
|array[string]
a|

|include_extension
|array[string]
a|

|include_shares
|array[string]
a|

```

```

|include_volumes
|array[string]
a|

|===

[#fpolicy_policy]
[.api-collapsible-fifth-title]
fpolicy_policy

[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Specifies if the policy is enabled on the SVM or not. If no value is
mentioned for this field but priority is set, then this policy will be
enabled.

|engine
|link:#fpolicy_engine_reference[fpolicy_engine_reference]
a|FPolicy external engine

|events
|array[link:#fpolicy_event_reference[fpolicy_event_reference]]
a|

|mandatory
|boolean
a|Specifies what action to take on a file access event in a case when all
primary and secondary servers are down or no response is received from the
FPolicy servers within a given timeout period. When this parameter is set
to true, file access events will be denied under these circumstances.

|name
|string
a|Specifies the name of the policy.

|priority

```

```

|integer
a|Specifies the priority that is assigned to this policy.

|scope
|link:#scope[scope]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

```

```
|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====
```

```
[[ID3bae3cdb74a90e04c7513e837f66b4fd]]
```

= Delete an FPolicy configuration for an SVM

```
[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-block]#\protocols/fpolicy/{svm.uuid}/policies/{name}`#
```

\*Introduced In:\* 9.6

Deletes a particular FPolicy policy configuration for a specified SVM. To delete a policy, you must first disable the policy.

== Related ONTAP commands

\* `fpolicy policy scope delete`

\* `fpolicy policy delete`

== Learn more

\*

xref:{relative\_path}protocols\_fpolicy\_svm.uuid\_policies\_endpoint\_overview.html[DOC /protocols/fpolicy/{svm.uuid}/policies]

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|name
```

```
|string
```

```
|path
```

```
|True
```

```
a|
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```



```
== Response
```

Status: 200, Ok

```
== Error
```

Status: Default

```
ONTAP Error Response Codes
```

```
|===
```

```
| Error Code | Description
```

```
| 9764900
```

```
| Deletion of a cluster level FPolicy policy is not supported
```

```
| 9764941
```

```
| Cannot delete an enabled FPolicy policy
```

```
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
```

```
  "error": {
```

```
    "arguments": {
```

```
      "code": "string",
```

```
      "message": "string"
```

```
    },
```

```
"code": "4",
"message": "entry doesn't exist",
"target": "uuid"
}
}
====
```

== Definitions

```
[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|code
```

```
|string
```

```
a|Argument code
```

```
|message
```

```
|string
```

```
a|Message argument
```

```
|===
```

```
[#error]
```

```
[.api-collapsible-fifth-title]
```

```
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[ID895b78db0185ca0ae5f281967a8ed666]]
= Retrieve an FPolicy configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/fpolicy/{svm.uuid}/policies/{name}`#
```

**\*Introduced In:\* 9.6**

Retrieves a particular FPolicy policy configuration for a specified SVM. Cluster-level FPolicy policy configuration details cannot be retrieved for a data SVM.

== Related ONTAP commands

```
* `fpolicy policy show`
* `fpolicy policy scope show`
* `fpolicy show`
```

== Learn more

```
*
xref:{relative_path}protocols_fpolicy_svm.uuid_policies_endpoint_overview.
html[DOC /protocols/fpolicy/{svm.uuid}/policies]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|name
```

```
|string
```

```
|path
```

```
|True
```

```
a|
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|fields
```

```
|array[string]
```

```
|query
```

```
|False
```

```
a|Specify the fields to return.
```

```
|===
```

== Response

Status: 200, Ok

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

|Description

|enabled

|boolean

a|Specifies if the policy is enabled on the SVM or not. If no value is mentioned for this field but priority is set, then this policy will be enabled.

|engine

|link:#fpolicy\_engine\_reference[fpolicy\_engine\_reference]

a|FPolicy external engine

|events

|array[link:#fpolicy\_event\_reference[fpolicy\_event\_reference]]

a|

|mandatory

|boolean

a|Specifies what action to take on a file access event in a case when all primary and secondary servers are down or no response is received from the FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.

|name

|string

a|Specifies the name of the policy.

|priority

|integer

a|Specifies the priority that is assigned to this policy.

|scope

|link:#scope[scope]

a|

|===

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "engine": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "events": [
    "event_nfs_close",
    "event_open"
  ],
  "name": "fp_policy_1",
  "scope": {
    "exclude_export_policies": {
    },
    "exclude_extension": {
    },
    "exclude_shares": {
    },
    "exclude_volumes": [
      "vol1",
      "vol_svm1",
      "*"
    ],
    "include_export_policies": {
    },
    "include_extension": {
    },
    "include_shares": [
      "sh1",
      "share_cifs"
    ],
    "include_volumes": [
      "vol1",
      "vol_svm1"
    ]
  }
}
====

== Error
```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#fpolicy_engine_reference]
[.api-collapsible-fifth-title]
fpolicy_engine_reference

FPolicy external engine

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the FPolicy external engine.

|===

```



```
[#fpolicy_event_reference]
[.api-collapsible-fifth-title]
fpolicy_event_reference
```

FPolicy events

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|
```

```
|===
```

```
[#scope]
```

```
[.api-collapsible-fifth-title]
```

```
scope
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|exclude_export_policies
```

```
|array[string]
```

```
a|
```

```
|exclude_extension
```

```
|array[string]
```

```
a|
```

```
|exclude_shares
```

```
|array[string]
```

```
a|
```

```

|exclude_volumes
|array[string]
a|

|include_export_policies
|array[string]
a|

|include_extension
|array[string]
a|

|include_shares
|array[string]
a|

|include_volumes
|array[string]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

```

```

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[ID3804de0035097ad303606455c72cebb3]]
= Update an FPolicy configuration for an SVM

[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/fpolicy/{svm.uuid}/policies/{name}`#

*Introduced In:* 9.6

Updates a particular FPolicy policy configuration for a specified SVM.

```

PATCH can be used to enable or disable the policy. When enabling a policy, you must specify the policy priority. The policy priority of the policy is not required when disabling the policy. If the policy is enabled, the FPolicy policy engine cannot be modified.

== Related ONTAP commands

- \* `fpolicy policy modify`
- \* `fpolicy policy scope modify`
- \* `fpolicy enable`
- \* `fpolicy disable`

== Learn more

\*  
xref:{relative\_path}protocols\_fpolicy\_svm.uuid\_policies\_endpoint\_overview.html[DOC /protocols/fpolicy/{svm.uuid}/policies]

== Parameters

[cols=5\*,options=header]

|===

Name
Type
In
Required
Description

name
string

path
------

True
------

a
---

svm.uuid
----------

string
--------

path
------

True
------

a UUID of the SVM to which this object belongs.
---

|===

== Request Body

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Specifies if the policy is enabled on the SVM or not. If no value is
mentioned for this field but priority is set, then this policy will be
enabled.

|engine
|link:#fpolicy_engine_reference[fpolicy_engine_reference]
a|FPolicy external engine

|events
|array[link:#fpolicy_event_reference[fpolicy_event_reference]]
a|

|mandatory
|boolean
a|Specifies what action to take on a file access event in a case when all
primary and secondary servers are down or no response is received from the
FPolicy servers within a given timeout period. When this parameter is set
to true, file access events will be denied under these circumstances.

|name
|string
a|Specifies the name of the policy.

|priority
|integer
a|Specifies the priority that is assigned to this policy.

|scope
|link:#scope[scope]
a|

|===

```

```

.Example request
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "engine": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "events": [
    "event_nfs_close",
    "event_open"
  ],
  "name": "fp_policy_1",
  "scope": {
    "exclude_export_policies": {
    },
    "exclude_extension": {
    },
    "exclude_shares": {
    },
    "exclude_volumes": [
      "voll",
      "vol_svm1",
      "*"
    ],
    "include_export_policies": {
    },
    "include_extension": {
    },
    "include_shares": [
      "sh1",
      "share_cifs"
    ],
    "include_volumes": [
      "voll",
      "vol_svm1"
    ]
  }
}
====

```

```
== Response
```

Status: 200, Ok

```
== Error
```

Status: Default

```
ONTAP Error Response Codes
```

```
|===  
| Error Code | Description  
  
| 9765026  
| The priority must be specified when enabling the FPolicy policy  
  
| 9765025  
| Cannot disable an FPolicy policy when the priority is specified  
  
| 9764899  
| Cannot modify an FPolicy engine when the policy is enabled  
  
| 9764899  
| Deletion of a cluster policy is not supported  
  
| 9764908  
| An FPolicy policy is already enabled  
  
| 9764907  
| An FPolicy policy is already disabled  
  
| 9765029  
| An FPolicy was modified but disable/enable failed as the policy is  
already disabled/enabled  
|===
```

```
[cols=3*,options=header]
```

```
|===  
|Name  
|Type  
|Description
```

```
|error
```

```

|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

```



```

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#fpolicy_engine_reference]
[.api-collapsible-fifth-title]
fpolicy_engine_reference

FPolicy external engine

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the FPolicy external engine.

|===

[#fpolicy_event_reference]
[.api-collapsible-fifth-title]
fpolicy_event_reference

FPolicy events

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_export_policies
|array[string]
a|

|exclude_extension
|array[string]
a|

|exclude_shares
|array[string]
a|

|exclude_volumes
|array[string]
a|

|include_export_policies
|array[string]

```

```

a|

|include_extension
|array[string]
a|

|include_shares
|array[string]
a|

|include_volumes
|array[string]
a|

|===

[#fpolicy_policy]
[.api-collapsible-fifth-title]
fpolicy_policy

[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Specifies if the policy is enabled on the SVM or not. If no value is
mentioned for this field but priority is set, then this policy will be
enabled.

|engine
|link:#fpolicy_engine_reference[fpolicy_engine_reference]
a|FPolicy external engine

|events
|array[link:#fpolicy_event_reference[fpolicy_event_reference]]
a|

|mandatory
|boolean
a|Specifies what action to take on a file access event in a case when all
primary and secondary servers are down or no response is received from the

```

FPolicy servers within a given timeout period. When this parameter is set to true, file access events will be denied under these circumstances.

|name  
|string  
a|Specifies the name of the policy.

|priority  
|integer  
a|Specifies the priority that is assigned to this policy.

|scope  
|link:#scope[scope]  
a|

|===

[#error\_arguments]  
[.api-collapsible-fifth-title]  
error\_arguments

[cols=3\*,options=header]

|===  
|Name  
|Type  
|Description

|code  
|string  
a|Argument code

|message  
|string  
a|Message argument

|===

[#error]  
[.api-collapsible-fifth-title]  
error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

:leveloffset: -1

= View NFS connected clients

:leveloffset: +1

[[ID6e1d4dc41f181cdaae059581b53d90a3]]
= Protocols NFS connected-clients endpoint overview

```

## == Overview

ONTAP connected clients show functionality is mainly used to provide a list of currently connected NFS clients. It also provides a potential list of other NFS clients that can be connected but are currently idle.

The following are details of the fields retrieved for the Connected Clients GET API:

node.name: The node name hosting this record; basically the node hosting the "server\_ip".

node.uuid: The node UUID hosting this record; basically the node hosting the "server\_ip".

svm.name: The svm name to which the "server\_ip" belongs to.

svm.uuid: The svm uuid to which the "server\_ip" belongs to.

server\_ip: All clients that are connected to this interface are displayed in rows.

client\_ip: The IP address of the client that is connected to the interface.

volume.name: The name of the volume the client is accessing.

volume.uuid: The UUID of the volume the client is accessing.

protocol: The NFS protocol version over which client is accessing the volume.

idle\_duration: The time elapsed since the last request was sent by the client for this volume.

local\_request\_count: A counter that tracks requests that are sent to the volume with fast-path to local node.

remote\_request\_count: A counter that tracks requests that are sent to the volume with slow-path to remote node.

## == Example

=== Retrieves connected client information

----

# The API:

```
GET /protocols/nfs/connected-clients
```

# The call:

```
curl -X GET "https://<cluster-mgmt-ip>/api/protocols/nfs/connected-clients?return_timeout=15&return_records=true" -H "accept: application/json"
```

# The response:

```

{
"records": [
{
  "svm": {
    "uuid": "c642db55-b8d0-11e9-9ad1-0050568e8480",
    "name": "vs1"
  },
  "node": {
    "uuid": "cc282893-b82f-11e9-a3ad-0050568e8480",
    "name": "vsim1"
  },
  "server_ip": "10.140.72.214",
  "client_ip": "10.140.137.57",
  "volume": {
    "name": "rvol1",
    "uuid": "c6bbc6f2-b8d0-11e9-9ad1-0050568e8480"
  },
  "protocol": "nfs4"
},
{
  "svm": {
    "uuid": "c642db55-b8d0-11e9-9ad1-0050568e8480",
    "name": "vs1"
  },
  "node": {
    "uuid": "cc282893-b82f-11e9-a3ad-0050568e8480",
    "name": "vsim1"
  },
  "server_ip": "10.140.72.214",
  "client_ip": "10.140.137.57",
  "volume": {
    "name": "vol1",
    "uuid": "d28d1999-b8d0-11e9-9ad1-0050568e8480"
  },
  "protocol": "nfs3"
},
{
  "svm": {
    "uuid": "c642db55-b8d0-11e9-9ad1-0050568e8480",
    "name": "vs1"
  },
  "node": {
    "uuid": "cc282893-b82f-11e9-a3ad-0050568e8480",
    "name": "vsim1"
  },
  "server_ip": "10.140.72.214",

```

```

    "client_ip": "10.140.137.57",
    "volume": {
      "name": "vol1",
      "uuid": "d28d1999-b8d0-11e9-9ad1-0050568e8480"
    },
    "protocol": "nfs4"
  }],
  "num_records": 3
}
-----

```

```

[[ID6d7084347587ff5918e48747d2d3a529]]
= Retrieve the NFS configuration for an SVM

```

```

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/connected-clients`#

```

\*Introduced In:\* 9.7

Retrieves the NFS configuration of SVMs.

== Parameters

```

[cols=5*,options=header]
|===

```

```

|Name
|Type
|In
|Required
|Description

```

```

|local_request_count
|integer
|query
|False
a|Filter by local_request_count

```

```

|client_ip
|string
|query

```



```
|False
a|Filter by client_ip

|remote_request_count
|integer
|query
|False
a|Filter by remote_request_count

|svm.uuid
|string
|query
|False
a|Filter by svm.uuid

|svm.name
|string
|query
|False
a|Filter by svm.name

|node.name
|string
|query
|False
a|Filter by node.name

|node.uuid
|string
|query
|False
a|Filter by node.uuid

|server_ip
|string
|query
|False
a|Filter by server_ip

|volume.uuid
```

```
|string
|query
|False
a|Filter by volume.uuid
```

```
|volume.name
|string
|query
|False
a|Filter by volume.name
```

```
|idle_duration
|string
|query
|False
a|Filter by idle_duration
```

```
|protocol
|string
|query
|False
a|Filter by protocol
```

```
|fields
|array[string]
|query
|False
a|Specify the fields to return.
```

```
|max_records
|integer
|query
|False
a|Limit the number of records returned.
```

```
|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds. ONTAP
```

returns earlier if either max records or the end of the collection is reached.

\* Default value: 1

\* Max value: 120

\* Min value: 0

|return\_records

|boolean

|query

|False

a|The default is true for GET calls. When set to false, only the number of records is returned.

\* Default value: 1

|order\_by

|array[string]

|query

|False

a|Order results by specified fields and optional [asc|desc] direction. Default direction is 'asc' for ascending.

|===

== Response

Status: 200, Ok

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|\_links

|link:#\_links[\_links]

a|

|num\_records

|integer

a|Number of records

```

|records
|array[link:#nfs_clients[nfs_clients]]
a|

|===

.Example response
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "idle_duration": "P4DT84H30M5S",
    "node": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "node1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "protocol": "nfs3",
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
  },
}

```

```

    "volume": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "volume1",
      "uuid": "028baa66-41bd-11e9-81d5-00a0986138f7"
    }
  }
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

```

====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====

[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#node]
[.api-collapsible-fifth-title]
node

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|

|uuid
|string
a|

|===

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

|===

[#volume]
[.api-collapsible-fifth-title]
volume

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the volume.

|uuid
|string
a|Unique identifier for the volume. This corresponds to the instance-uuid
that is exposed in the CLI and ONTAPI. It does not change due to a volume
move.

```



```
* example: 028baa66-41bd-11e9-81d5-00a0986138f7
* Introduced in: 9.6
```

```
|===
```

```
[#nfs_clients]
[.api-collapsible-fifth-title]
nfs_clients
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|client_ip
|string
a|Specifies IP address of the client.
```

```
|idle_duration
|string
a|Specifies an ISO-8601 format of date and time to retrieve the idle time
duration in hours, minutes, and seconds format.
```

```
|local_request_count
|integer
a|A counter that tracks requests that are sent to the volume with fast-
path to local node.
```

```
|node
|link:#node[node]
a|
```

```
|protocol
|string
a|The NFS protocol version over which client is accessing the volume. The
following values are supported:
```

```
* nfs - All NFS versions are considered
* nfs3 - NFS version 3 protocol
* nfs4 - NFS version 4 protocol
* nfs4.1 - NFS version 4 minor version 1 protocol
```

```
|remote_request_count
|integer
```

```
a|A counter that tracks requests that are sent to the volume with slow-
path to remote node.
```

```
|server_ip
|string
```

```
a|Specifies the IP address of the server.
```

```
|svm
|link:#svm[svm]
```

```
a|
```

```
|volume
|link:#volume[volume]
```

```
a|
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

:leveloffset: -1

= Manage NFS export policies

```

```

:leveloffset: +1

[[IDa6dc453e1a130f315b1ec2d4d320ad6e]]
= Protocols NFS export-policies endpoint overview

== Export Policies

=== 1) Retrieve the export policy details

'''
-----

# The API:
GET /api/protocols/nfs/export-policies

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/nfs/export-policies"
-----

'''

=== 2) Create an export policy for an SVM

'''
-----

# The API:
POST /api/protocols/nfs/export-policies

# The call:
curl -d "@test_post_policy_single_rule.txt" -X POST "https://<mgmt-
ip>/api/protocols/nfs/export-policies"
test_post_policy_single_rule.txt (body):
{
"name": "P1",
"rules": [
  {
    "clients": [
      {
        "match": "host1"
      }
    ]
  }
],

```

```

    "ro_rule": [
      "krb5"
    ],
    "rw_rule": [
      "ntlm"
    ],
    "anonymous_user": "anon1"
  },
  {
    "clients": [
      {
        "match": "host2"
      }
    ],
    "ro_rule": [
      "sys"
    ],
    "rw_rule": [
      "ntlm"
    ],
    "superuser": [
      "any"
    ]
  }
]
}
-----

'''

=== 3) Update an export policy for an SVM

'''

-----

# The API:
PATCH /api/protocols/nfs/export-policies/{policy.id}

# The call:
curl -d "@test_patch_policy.txt" -X PATCH "https://<mgmt-
ip>/api/protocols/nfs/export-policies/8589934594"
test_patch_policy.txt (body):
{
  "name": "S1",
  "rules": [

```

```

{
  "clients": [
    {
      "match": "host4"
    }
  ],
  "ro_rule": [
    "krb5"
  ],
  "rw_rule": [
    "ntlm"
  ]
}
]
}
-----

'''

=== 4) Delete an export policy for an SVM

'''

-----

# The API:
DELETE /api/protocols/nfs/export-policies/{policy.id}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/nfs/export-
policies/8589934594"
-----

'''

== Export Rules

=== 1) Retrieve the export policy rule details for an export policy

'''

-----

# The API:
GET /api/protocols/nfs/export-policies/{policy.id}/rules

# The call:

```

```
curl -X GET "https://<mgmt-ip>/api/protocols/nfs/export-
policies/8589934595/rules"
```

```
----
```

```
'''
```

```
=== 2) Create an export policy rule for an export policy
```

```
'''
```

```
----
```

```
# The API:
```

```
POST /api/protocols/nfs/export-policies/{policy.id}/rules
```

```
# The call:
```

```
curl -d "@test_patch_export_rule.txt" -X POST "https://<mgmt-
ip>/api/protocols/nfs/export-policies/8589934595/rules"
```

```
test_patch_export_rule.txt (body):
```

```
{
"clients": [
  {
    "match": "host2"
  }
],
"ro_rule": [
  "sys"
],
"rw_rule": [
  "ntlm"
]
}
```

```
----
```

```
'''
```

```
=== 3) Update an export policy rule for an export policy
```

```
'''
```

```
----
```

```
# The API:
```

```
PATCH /api/protocols/nfs/export-policies/{policy.id}/rules/{index}
```

```
# The call:
```

```
curl -d "@test_patch_export_rule.txt" -X PATCH "https://<mgmt-
```

```

ip>/api/protocols/nfs/export-policies/8589934595/rules/5?new_index=10"
test_patch_export_rule.txt (body) :
{
"clients": [
  {
    "match": "host4"
  }
],
"ro_rule": [
  "sys"
],
"rw_rule": [
  "krb5"
]
}
-----

'''

=== 4) Delete an export policy rule for an export policy

'''

-----

# The API:
DELETE /api/protocols/nfs/export-policies/{policy.id}/rules/{index}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/nfs/export-
policies/8589934595/rules/15"
-----

'''

== Export Clients

=== 1) Retrieve the export client matches of an export policy rule

'''

-----

# The API:
GET /api/protocols/nfs/export-policies/{policy.id}/rules/{index}/clients

# The call:

```



```
curl -X GET "https://<mgmt-ip>/api/protocols/nfs/export-
policies/8589934593/rules/2/clients"
```

```
----
```

```
'''
```

```
=== 2) Add an export client match to an export policy rule
```

```
'''
```

```
----
```

```
# The API:
```

```
POST /api/protocols/nfs/export-policies/{policy.id}/rules/{index}/clients
```

```
# The call:
```

```
curl -d "@add_client_match.txt" -X POST "https://<mgmt-
ip>/api/protocols/nfs/export-policies/8589934593/rules/1/clients"
```

```
add_client_match.txt (body):
```

```
{
```

```
"match" : "host4"
```

```
}
```

```
----
```

```
'''
```

```
=== 3) Delete an export client match from an export policy rule
```

```
'''
```

```
----
```

```
# The API:
```

```
DELETE /api/protocols/nfs/export-
policies/{policy.id}/rules/{index}/clients/{match}
```

```
# The call:
```

```
curl -X DELETE "https://<mgmt-ip>/api/protocols/nfs/export-
policies/8589934593/rules/1/clients/host1,host2"
```

```
----
```

```
'''
```

```
[[ID2098b5e07040ad2dc620a4437adb697b]]
```

```
= Retrieve export policies
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/nfs/export-policies`#
```

```
*Introduced In:* 9.6
```

```
Retrieves export policies.
```

```
== Related ONTAP commands
```

```
* `vserver export-policy show`
```

```
* `vserver export-policy rule show`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_nfs_export-policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|id
```

```
|integer
```

```
|query
```

```
|False
```

```
a|Filter by id
```

```
|name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by name
```

```
|rules.anonymous_user
```

```
|string
|query
|False
a|Filter by rules.anonymous_user
```

```
|rules.index
|integer
|query
|False
a|Filter by rules.index
```

```
|rules.clients.match
|string
|query
|False
a|Filter by rules.clients.match
```

```
|rules.rw_rule
|string
|query
|False
a|Filter by rules.rw_rule
```

```
|rules.protocols
|string
|query
|False
a|Filter by rules.protocols
```

```
|rules.superuser
|string
|query
|False
a|Filter by rules.superuser
```

```
|rules.ro_rule
|string
|query
|False
a|Filter by rules.ro_rule
```

```
|svm.uuid  
|string  
|query  
|False  
a|Filter by svm.uuid
```

```
|svm.name  
|string  
|query  
|False  
a|Filter by svm.name
```

```
|fields  
|array[string]  
|query  
|False  
a|Specify the fields to return.
```

```
|max_records  
|integer  
|query  
|False  
a|Limit the number of records returned.
```

```
|return_records  
|boolean  
|query  
|False  
a|The default is true for GET calls. When set to false, only the number  
of records is returned.
```

\* Default value: 1

```
|return_timeout  
|integer  
|query  
|False  
a|The number of seconds to allow the call to execute before returning.  
When iterating over a collection, the default is 15 seconds. ONTAP  
returns earlier if either max records or the end of the collection is  
reached.
```

```
* Default value: 1
* Max value: 120
* Min value: 0
```

```
|order_by
|array[string]
|query
|False
```

a|Order results by specified fields and optional [asc|desc] direction.  
Default direction is 'asc' for ascending.

```
|===
```

```
== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
 |_links
|link:#_links[_links]
a|
```

```
 |num_records
|integer
a|The number of export policy records
```

```
 |records
|array[link:#export_policy[export_policy]]
a|
```

```
|===
```

```
.Example response
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```
{
```

```

"_links": {
  "next": {
    "href": "/api/resourcelink"
  },
  "self": {
    "href": "/api/resourcelink"
  }
},
"records": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "id": 0,
  "rules": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "clients": {
      "match": "0.0.0.0/0"
    },
    "index": 0,
    "protocols": {
    },
    "ro_rule": {
    },
    "rw_rule": {
    },
    "superuser": {
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
}
=====

```

```
== Error
```

Status: Default, Error

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href
```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:href[href]
a|

```



```
|===
```

```
[#export_client]  
[.api-collapsible-fifth-title]  
export_client
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|match
```

```
|string
```

a|Client Match Hostname, IP Address, Netgroup, or Domain.  
You can specify the match as a string value in any of the  
following formats:

- \* As a hostname; for instance, host1
- \* As an IPv4 address; for instance, 10.1.12.24
- \* As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1
- \* As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24
- \* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64
- \* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0
- \* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng
- \* As a domain name preceded by the . character; for instance, .example.com

```
|===
```

```
[#export_rule]  
[.api-collapsible-fifth-title]  
export_rule
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```

|_links
|link:#_links[_links]
a|

|anonymous_user
|string
a|User ID To Which Anonymous Users Are Mapped.

|clients
|array[link:#export_client[export_client]]
a|Array of client matches

|index
|integer
a|Index of the rule within the export policy.

|protocols
|array[string]
a|

|ro_rule
|array[string]
a|Authentication flavors that the read-only access rule governs

|rw_rule
|array[string]
a|Authentication flavors that the read/write access rule governs

|superuser
|array[string]
a|Authentication flavors that the superuser security type governs

|===

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===

```

```

|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

|===

[#export_policy]
[.api-collapsible-fifth-title]
export_policy

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|id
|integer
a|Export Policy ID

|name
|string
a|Export Policy Name

|rules
|array[link:#export_rule[export_rule]]

```

a|Rules of the Export Policy.

|svm

|link:#svm[svm]

a|

|===

[#error\_arguments]

[.api-collapsible-fifth-title]

error\_arguments

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|code

|string

a|Argument code

|message

|string

a|Message argument

|===

[#error]

[.api-collapsible-fifth-title]

error

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|arguments

|array[link:#error\_arguments[error\_arguments]]

a|Message arguments

```
|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[ID7772d3e5378c11e52dc4651491e9f578]]
= Create an export policy
```

```
[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-
block]#`/protocols/nfs/export-policies`#
```

```
*Introduced In:* 9.6
```

Creates an export policy. An SVM can have any number of export policies to define rules for which clients can access data exported by the SVM. A policy with no rules prohibits access.

```
== Required properties
```

```
* `svm.uuid` or `svm.name` - Existing SVM in which to create an export
policy.
* `name` - Name of the export policy.
```

```
== Recommended optional properties
```

```
* `rules` - Rule(s) of an export policy. Used to create the export rule
and populate the export policy with export rules in a single request.
```

== Related ONTAP commands

```
* `vserver export-policy create`  
* `vserver export-policy rule create`
```

== Learn more

```
* xref:{relative_path}protocols_nfs_export-  
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name  
|Type  
|In  
|Required  
|Description
```

```
|return_records
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|The default is false. If set to true, the records are returned.
```

```
* Default value:
```

```
|===
```

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|id
```

```
|integer
a|Export Policy ID

|name
|string
a|Export Policy Name

|rules
|array[link:#export_rule[export_rule]]
a|Rules of the Export Policy.

|svm
|link:#svm[svm]
a|

|===
```

.Example request

[%collapsible%closed]

====

```
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "id": 0,
  "rules": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "clients": {
      "match": "0.0.0.0/0"
    },
    "index": 0,
    "protocols": {
    },
    "ro_rule": {
    },
  },
}
```

```

    "rw_rule": {
      },
      "superuser": {
      }
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  }
}
====

== Response

```

Status: 201, Created

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|The number of export policy records

|records
|array[link:#export_policy[export_policy]]
a|

|===

.Example response
[%collapsible%closed]
====

```



```
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "id": 0,
    "rules": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "clients": {
        "match": "0.0.0.0/0"
      },
      "index": 0,
      "protocols": {
      },
      "ro_rule": {
      },
      "rw_rule": {
      },
      "superuser": {
      }
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    }
  }
}
```

```
}  
====  
  
== Error
```

## Status: Default

### ONTAP Error Response Codes

```
|===  
| Error Code | Description  
  
| 1703952  
| Invalid ruleset name provided. No spaces allowed in a ruleset name  
  
| 1703954  
| Export policy does not exist  
  
| 1704049  
| Invalid clientmatch: clientmatch lists require an effective cluster  
version of Data ONTAP 9.0 or later. Upgrade all nodes to Data ONTAP 9.0 or  
above to use features that operate on lists of clientmatch strings in  
export-policy rules  
  
| 1704055  
| Export policies are only supported for data Vservers  
  
| 3277000  
| Upgrade all nodes to Data ONTAP 9.0.0 or above to use krb5p as a  
security flavor in export-policy rules  
  
| 3277083  
| User ID is not valid. Enter a value for User ID from 0 to 4294967295  
|===
```

```
[cols=3*,options=header]
```

```
|===  
|Name  
|Type  
|Description  
  
|error  
|link:#error[error]  
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

```
=====
```

```
== Definitions
```

```
[.api-def-first-level]
```

```
.See Definitions
```

```
[%collapsible%closed]
```

```
//Start collapsible Definitions block
```

```
=====
```

```
[#href]
```

```
[.api-collapsible-fifth-title]
```

```
href
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|href
```

```
|string
```

```
a|
```

```
|===
```

```
[#_links]
```

```
[.api-collapsible-fifth-title]
```

```
_links
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|self
```

```
|link:href[href]
```

```
a|
```

```
|===
```

```
[#export_client]
```

```
[.api-collapsible-fifth-title]
```

```
export_client
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|match
```

```
|string
```

```
a|Client Match Hostname, IP Address, Netgroup, or Domain.
```

```
You can specify the match as a string value in any of the  
following formats:
```

```
* As a hostname; for instance, host1
```

```
* As an IPv4 address; for instance, 10.1.12.24
```

```
* As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1
```

```
* As an IPv4 address with a subnet mask expressed as a number of bits; for  
instance, 10.1.12.0/24
```

```
* As an IPv6 address with a subnet mask expressed as a number of bits; for  
instance, fd20:8b1e:b255:4071::/64
```

```
* As an IPv4 address with a network mask; for instance,  
10.1.16.0/255.255.255.0
```

```
* As a netgroup, with the netgroup name preceded by the @ character; for  
instance, @eng
```

```
* As a domain name preceded by the . character; for instance, .example.com
```

```
|===
```

```

[#export_rule]
[.api-collapsible-fifth-title]
export_rule

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|anonymous_user
|string
a|User ID To Which Anonymous Users Are Mapped.

|clients
|array[link:#export_client[export_client]]
a|Array of client matches

|index
|integer
a|Index of the rule within the export policy.

|protocols
|array[string]
a|

|ro_rule
|array[string]
a|Authentication flavors that the read-only access rule governs

|rw_rule
|array[string]
a|Authentication flavors that the read/write access rule governs

|superuser
|array[string]

```

```
a|Authentication flavors that the superuser security type governs
```

```
|===
```

```
[#svm]
```

```
[.api-collapsible-fifth-title]
```

```
svm
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|The name of the SVM.
```

```
|uuid
```

```
|string
```

```
a|The unique identifier of the SVM.
```

```
|===
```

```
[#export_policy]
```

```
[.api-collapsible-fifth-title]
```

```
export_policy
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```

|id
|integer
a|Export Policy ID

|name
|string
a|Export Policy Name

|rules
|array[link:#export_rule[export_rule]]
a|Rules of the Export Policy.

|svm
|link:#svm[svm]
a|

|===

[#export_client]
[.api-collapsible-fifth-title]
export_client

[cols=3*,options=header]
|===
|Name
|Type
|Description

|match
|string
a|Client Match Hostname, IP Address, Netgroup, or Domain.
You can specify the match as a string value in any of the
    following formats:

* As a hostname; for instance, host1
* As an IPv4 address; for instance, 10.1.12.24
* As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1
* As an IPv4 address with a subnet mask expressed as a number of bits; for
instance, 10.1.12.0/24
* As an IPv6 address with a subnet mask expressed as a number of bits; for
instance, fd20:8b1e:b255:4071::/64
* As an IPv4 address with a network mask; for instance,
10.1.16.0/255.255.255.0

```

\* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng

\* As a domain name preceded by the . character; for instance, .example.com

|===

[#\_links]

[.api-collapsible-fifth-title]

\_links

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|next

|link:#href[href]

a|

|self

|link:#href[href]

a|

|===

[#export\_client]

[.api-collapsible-fifth-title]

export\_client

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|match

|string

a|Client Match Hostname, IP Address, Netgroup, or Domain.  
You can specify the match as a string value in any of the  
following formats:

\* As a hostname; for instance, host1

\* As an IPv4 address; for instance, 10.1.12.24



```
* As an IPv6 address; for instance, fd20:8ble:b255:4071::100:1
* As an IPv4 address with a subnet mask expressed as a number of bits; for
instance, 10.1.12.0/24
* As an IPv6 address with a subnet mask expressed as a number of bits; for
instance, fd20:8ble:b255:4071::/64
* As an IPv4 address with a network mask; for instance,
10.1.16.0/255.255.255.0
* As a netgroup, with the netgroup name preceded by the @ character; for
instance, @eng
* As a domain name preceded by the . character; for instance, .example.com
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[ID3cbdb054e0f315838192bec585154193]]
= Delete an export policy
```

```
[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{id}`#
```

```
*Introduced In:* 9.6
```

```
Deletes an export policy.
```

```
== Related ONTAP commands
```

```
* `vserver export-policy delete`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_nfs_export-
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|id
```

```
|integer
```

```
|path
```

```
|True
```

```
a|Export Policy ID
```

```
|===
```

== Response

Status: 200, Ok

== Error

Status: Default

ONTAP Error Response Codes

```
|===
```

```
| Error Code | Description
```

```
| 1703944
```

```
| Failed to delete rule
```

```
| 1703945
```

```
| Ruleset is in use by a volume. It cannot be deleted until all volumes  
that refer to it are first deleted
```

```
| 1703946
```

```
| Cannot determine if the ruleset is in use by a volume. It cannot be  
deleted until all volumes that refer to it are first deleted
```

```
| 1703947
| Cannot delete default ruleset. This ruleset will be deleted when the
| owning Vserver is deleted

| 1703952
| Invalid ruleset name provided. No spaces are allowed in a ruleset name

| 1703953
| This ruleset is in use by a qtree export policy. It cannot be deleted
| until all qtree policies that refer to it are first deleted
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

```
====
```

```
== Definitions
```

```
[.api-def-first-level]
```

```

.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

```

```

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

[[ID047973129684c94cb25c16f8f6b24204]]
= Retrieve an export policy

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{id}`#

*Introduced In:* 9.6

Retrieves an export policy.

== Related ONTAP commands

* `vserver export-policy show`
* `vserver export-policy rule show`

== Learn more

* xref:{relative_path}protocols_nfs_export-
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]

== Parameters

[cols=5*,options=header]
|===

|Name
|Type
|In

```

```
|Required
|Description

|id
|integer
|path
|True
a|Export Policy ID

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|id
|integer
a|Export Policy ID

|name
|string
a|Export Policy Name

|rules
|array[link:#export_rule[export_rule]]
a|Rules of the Export Policy.
```

```

|svm
|link:#svm[svm]
a|

|===

.Example response
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "id": 0,
  "rules": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "clients": {
      "match": "0.0.0.0/0"
    },
    "index": 0,
    "protocols": {
    },
    "ro_rule": {
    },
    "rw_rule": {
    },
    "superuser": {
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}

```



```
}  
}  
====  
  
== Error
```

Status: Default, Error

```
[cols=3*,options=header]  
|===  
|Name  
|Type  
|Description  
  
|error  
|link:#error[error]  
a|  
  
|===  
  
.Example error  
[%collapsible%closed]  
====  
[source,json,subs=+macros]  
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}  
====  
  
== Definitions  
  
[.api-def-first-level]  
.See Definitions  
[%collapsible%closed]  
//Start collapsible Definitions block  
====  
[#href]
```

```

[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#export_client]
[.api-collapsible-fifth-title]
export_client

[cols=3*,options=header]
|===
|Name
|Type
|Description

|match
|string
a|Client Match Hostname, IP Address, Netgroup, or Domain.
You can specify the match as a string value in any of the

```

following formats:

- \* As a hostname; for instance, host1
- \* As an IPv4 address; for instance, 10.1.12.24
- \* As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1
- \* As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24
- \* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64
- \* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0
- \* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng
- \* As a domain name preceded by the . character; for instance, .example.com

|===

```
[#export_rule]
[.api-collapsible-fifth-title]
export_rule
```

```
[cols=3*,options=header]
```

|===

```
|Name
|Type
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|anonymous_user
```

```
|string
```

```
a|User ID To Which Anonymous Users Are Mapped.
```

```
|clients
```

```
|array[link:#export_client[export_client]]
```

```
a|Array of client matches
```

```
|index
```

```
|integer
```

```
a|Index of the rule within the export policy.
```

```

|protocols
|array[string]
a|

|ro_rule
|array[string]
a|Authentication flavors that the read-only access rule governs

|rw_rule
|array[string]
a|Authentication flavors that the read/write access rule governs

|superuser
|array[string]
a|Authentication flavors that the superuser security type governs

|===

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

```

```

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message

```

```
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[IDa64097244af2a55d259b1e889bfe7fb2]]
= Update export policy properties
```

```
[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{id}`#
```

```
*Introduced In:* 9.6
```

Updates the properties of an export policy to change an export policy name or replace all export policy rules.

```
== Related ONTAP commands
```

```
* `vserver export-policy rename`
* `vserver export-policy rule delete`
* `vserver export-policy rule create`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_nfs_export-
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]
```

```
== Parameters
```

```
[cols=5*,options=header]
|===
```

```
|Name
|Type
```

```
|In
|Required
|Description

|id
|integer
|path
|True
a|Export Policy ID
```

```
|===
```

```
== Request Body
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
 |_links
|link:#_links[_links]
a|
```

```
|id
|integer
a|Export Policy ID
```

```
|name
|string
a|Export Policy Name
```

```
|rules
|array[link:#export_rule[export_rule]]
a|Rules of the Export Policy.
```

```
|svm
|link:#svm[svm]
a|
```

```
|===
```

```
.Example request
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "id": 0,
  "rules": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "clients": {
      "match": "0.0.0.0/0"
    },
    "index": 0,
    "protocols": {
    },
    "ro_rule": {
    },
    "rw_rule": {
    },
    "superuser": {
    }
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
====

== Response
```

Status: 200, Ok



```
== Error
```

## Status: Default

### ONTAP Error Response Codes

```
|===
```

```
| Error Code | Description
```

```
| 1703950
```

```
| Failed to rename ruleset
```

```
| 1703952
```

```
| Invalid ruleset name provided. No spaces are allowed in a ruleset name
```

```
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

```

}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#export_client]
[.api-collapsible-fifth-title]
export_client

```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|match
```

```
|string
```

a|Client Match Hostname, IP Address, Netgroup, or Domain.

You can specify the match as a string value in any of the following formats:

\* As a hostname; for instance, host1

\* As an IPv4 address; for instance, 10.1.12.24

\* As an IPv6 address; for instance, fd20:8ble:b255:4071::100:1

\* As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24

\* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8ble:b255:4071::/64

\* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0

\* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng

\* As a domain name preceded by the . character; for instance, .example.com

```
|===
```

```
[#export_rule]
```

```
[.api-collapsible-fifth-title]
```

```
export_rule
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|anonymous_user
```

```
|string
```

a|User ID To Which Anonymous Users Are Mapped.

|clients

|array[link:#export\_client[export\_client]]

a|Array of client matches

|index

|integer

a|Index of the rule within the export policy.

|protocols

|array[string]

a|

|ro\_rule

|array[string]

a|Authentication flavors that the read-only access rule governs

|rw\_rule

|array[string]

a|Authentication flavors that the read/write access rule governs

|superuser

|array[string]

a|Authentication flavors that the superuser security type governs

|===

[#svm]

[.api-collapsible-fifth-title]

svm

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|\_links

|link:#\_links[\_links]

```

a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

|===

[#export_policy]
[.api-collapsible-fifth-title]
export_policy

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|id
|integer
a|Export Policy ID

|name
|string
a|Export Policy Name

|rules
|array[link:#export_rule[export_rule]]
a|Rules of the Export Policy.

|svm
|link:#svm[svm]
a|

```

```
|===
```

```
[#error_arguments]  
[.api-collapsible-fifth-title]  
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|code  
|string  
a|Argument code
```

```
|message  
|string  
a|Message argument
```

```
|===
```

```
[#error]  
[.api-collapsible-fifth-title]  
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|arguments  
|array[link:#error_arguments[error_arguments]]  
a|Message arguments
```

```
|code  
|string  
a|Error code
```

```

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

[[IDf39b76d056fc35f8c76fbbb5c50752b9]]
= Retrieve export policy rules

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{policy.id}/rules`#

*Introduced In:* 9.6

Retrieves export policy rules.

== Related ONTAP commands

* `vserver export-policy rule show`

== Learn more

* xref:{relative_path}protocols_nfs_export-
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]

== Parameters

[cols=5*,options=header]
|===

|Name
|Type
|In
|Required

```

```
|Description

|policy.id
|integer
|path
|True
a|Export Policy ID

|anonymous_user
|string
|query
|False
a|Filter by anonymous_user

|index
|integer
|query
|False
a|Filter by index

|clients.match
|string
|query
|False
a|Filter by clients.match

|rw_rule
|string
|query
|False
a|Filter by rw_rule

|protocols
|string
|query
|False
a|Filter by protocols

|superuser
|string
|query
```



```
|False  
a|Filter by superuser
```

```
|ro_rule  
|string  
|query  
|False  
a|Filter by ro_rule
```

```
|fields  
|array[string]  
|query  
|False  
a|Specify the fields to return.
```

```
|max_records  
|integer  
|query  
|False  
a|Limit the number of records returned.
```

```
|return_records  
|boolean  
|query  
|False  
a|The default is true for GET calls. When set to false, only the number  
of records is returned.
```

\* Default value: 1

```
|return_timeout  
|integer  
|query  
|False  
a|The number of seconds to allow the call to execute before returning.  
When iterating over a collection, the default is 15 seconds. ONTAP  
returns earlier if either max records or the end of the collection is  
reached.
```

\* Default value: 1

\* Max value: 120

\* Min value: 0

```
|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of Export Rule records

|records
|array[link:#export_rule[export_rule]]
a|

|===

.Example response
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
```

```

    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "clients": {
      "match": "0.0.0.0/0"
    },
    "index": 0,
    "protocols": {
    },
    "ro_rule": {
    },
    "rw_rule": {
    },
    "superuser": {
    }
  }
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]

```

```

====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```

====

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block

```

====

```

[#href]
[.api-collapsible-fifth-title]
href

```

```

[cols=3*,options=header]

```

|===

```

|Name
|Type
|Description

```

```

|href
|string
a|

```

|===

```

[#_links]
[.api-collapsible-fifth-title]
_links

```

```

[cols=3*,options=header]

```

|===

```

|Name

```

```

|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#export_client]
[.api-collapsible-fifth-title]
export_client

[cols=3*,options=header]
|===
|Name
|Type
|Description

|match
|string
a|Client Match Hostname, IP Address, Netgroup, or Domain.
You can specify the match as a string value in any of the
following formats:

```

- \* As a hostname; for instance, host1
- \* As an IPv4 address; for instance, 10.1.12.24
- \* As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1
- \* As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24
- \* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64
- \* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0
- \* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng
- \* As a domain name preceded by the . character; for instance, .example.com

|===

```
[#export_rule]
[.api-collapsible-fifth-title]
export_rule
```

```
[cols=3*,options=header]
```

|===

```
|Name
|Type
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|anonymous_user
```

```
|string
```

```
a|User ID To Which Anonymous Users Are Mapped.
```

```
|clients
```

```
|array[link:#export_client[export_client]]
```

```
a|Array of client matches
```

```
|index
```

```
|integer
```

```
a|Index of the rule within the export policy.
```

```
|protocols
```

```

|array[string]
a|

|ro_rule
|array[string]
a|Authentication flavors that the read-only access rule governs

|rw_rule
|array[string]
a|Authentication flavors that the read/write access rule governs

|superuser
|array[string]
a|Authentication flavors that the superuser security type governs

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[ID91026b510f9869d554d07693b8670398]]
= Create an export policy rule

[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{policy.id}/rules`#

*Introduced In:* 9.6

Creates an export policy rule.

== Required properties

```



\* ``policy.id`` - Existing export policy for which to create an export rule.  
\* ``clients.match`` - List of clients (hostnames, ipaddresses, netgroups, domains) to which the export rule applies.  
\* ``ro_rule`` - Used to specify the security type for read-only access to volumes that use the export rule.  
\* ``rw_rule`` - Used to specify the security type for read-write access to volumes that use the export rule.

== Default property values

If not specified in POST, the following default property values are assigned:

\* ``protocols`` - `_any_`  
\* ``anonymous_user`` - `_none_`  
\* ``superuser`` - `_any_`

== Related ONTAP commands

\* ``vserver export-policy rule create``

== Learn more

\* `xref:{relative_path}protocols_nfs_export-policies_endpoint_overview.html` [DOC /protocols/nfs/export-policies]

== Parameters

[cols=5\*,options=header]

|===

|Name

|Type

|In

|Required

|Description

|`policy.id`

|integer

|path

|True

a|Export Policy ID

|return\_records

```
|boolean
|query
|False
a|The default is false. If set to true, the records are returned.
```

\* Default value:

```
|===
```

```
== Request Body
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|anonymous_user
```

```
|string
```

```
a|User ID To Which Anonymous Users Are Mapped.
```

```
|clients
```

```
|array[link:#export_client[export_client]]
```

```
a|Array of client matches
```

```
|index
```

```
|integer
```

```
a|Index of the rule within the export policy.
```

```
|protocols
```

```
|array[string]
```

```
a|
```

```
|ro_rule
```

```
|array[string]
```

```
a|Authentication flavors that the read-only access rule governs
```

```
|rw_rule
|array[string]
a|Authentication flavors that the read/write access rule governs
```

```
|superuser
|array[string]
a|Authentication flavors that the superuser security type governs
```

```
|===
```

.Example request

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "clients": {
    "match": "0.0.0.0/0"
  },
  "index": 0,
  "protocols": {
  },
  "ro_rule": {
  },
  "rw_rule": {
  },
  "superuser": {
  }
}
=====
```

```
== Response
```

Status: 201, Created

```
[cols=3*,options=header]
|===
|Name
|Type
```

```

|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of Export Rule records

|records
|array[link:#export_rule[export_rule]]
a|

|===

```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```

{
  "_links": {
    "next": {
      "href": "/api/resource/link"
    },
    "self": {
      "href": "/api/resource/link"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resource/link"
      }
    },
    "clients": {
      "match": "0.0.0.0/0"
    },
    "index": 0,
    "protocols": {
    },
    "ro_rule": {
    },
    "rw_rule": {

```

```
    },  
    "superuser": {  
    }  
  }  
}  
====  
== Error
```

## Status: Default

### ONTAP Error Response Codes

```
|===  
| Error Code | Description  
  
| 1703954  
| Export policy does not exist  
  
| 1704036  
| Invalid clientmatch: missing domain name  
  
| 1704037  
| Invalid clientmatch: missing network name  
  
| 1704038  
| Invalid clientmatch: missing netgroup name  
  
| 1704039  
| Invalid clientmatch  
  
| 1704040  
| Invalid clientmatch: address bytes masked out by netmask are non-zero  
  
| 1704041  
| Invalid clientmatch: address bytes masked to zero by netmask  
  
| 1704042  
| Invalid clientmatch: too many bits in netmask  
  
| 1704043  
| Invalid clientmatch: invalid netmask  
  
| 1704044  
| Invalid clientmatch: invalid characters in host name
```

```

| 1704045
| Invalid clientmatch: invalid characters in domain name

| 1704050
| Invalid clientmatch: clientmatch list contains a duplicate string.
Duplicate strings in a clientmatch list are not supported

| 1704051
| Warning: Not adding any new strings to the clientmatch field for
ruleindex. All of the match strings are already in the clientmatch list

| 1704064
| Clientmatch host name too long

| 1704065
| Clientmatch domain name too long

| 3277000
| Upgrade all nodes to Data ONTAP 9.0.0 or above to use krb5p as a
security flavor in export-policy rules

| 3277083
| User ID is not valid. Enter a value for User ID from 0 to 4294967295
|===

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {

```

```

    "code": "string",
    "message": "string"
  },
  "code": "4",
  "message": "entry doesn't exist",
  "target": "uuid"
}
}
====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====

```

```

[#href]
[.api-collapsible-fifth-title]
href

```

```

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

```

```

|href
|string
a|

```

```

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

```

```

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

```

```

|self
|link:#href[href]

```

```
a|
```

```
|===
```

```
[#export_client]  
[.api-collapsible-fifth-title]  
export_client
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|match
```

```
|string
```

a|Client Match Hostname, IP Address, Netgroup, or Domain.  
You can specify the match as a string value in any of the following formats:

- \* As a hostname; for instance, host1
- \* As an IPv4 address; for instance, 10.1.12.24
- \* As an IPv6 address; for instance, fd20:8ble:b255:4071::100:1
- \* As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24
- \* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8ble:b255:4071::/64
- \* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0
- \* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng
- \* As a domain name preceded by the . character; for instance, .example.com

```
|===
```

```
[#export_rule]  
[.api-collapsible-fifth-title]  
export_rule
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```



```

|_links
|link:#_links[_links]
a|

|anonymous_user
|string
a|User ID To Which Anonymous Users Are Mapped.

|clients
|array[link:#export_client[export_client]]
a|Array of client matches

|index
|integer
a|Index of the rule within the export policy.

|protocols
|array[string]
a|

|ro_rule
|array[string]
a|Authentication flavors that the read-only access rule governs

|rw_rule
|array[string]
a|Authentication flavors that the read/write access rule governs

|superuser
|array[string]
a|Authentication flavors that the superuser security type governs

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type

```

```

|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDc3471319e5b2919014809d50629b4dfe]]
= Delete an export policy rule

[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{policy.id}/rules/{index}`#

*Introduced In:* 9.6

Deletes an export policy rule.

== Related ONTAP commands

* `vserver export-policy rule delete`

== Learn more

* xref:{relative_path}protocols_nfs_export-

```

```
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|policy.id
```

```
|integer
```

```
|path
```

```
|True
```

```
a|Export Policy ID
```

```
|index
```

```
|integer
```

```
|path
```

```
|True
```

```
a|Export Rule Index
```

```
|===
```

```
== Response
```

Status: 200, Ok

```
== Error
```

Status: Default

```
ONTAP Error Response Codes
```

```
|===
```

```
| Error Code | Description
```

```
| 1703945
```

```
| Ruleset is in use by a volume. It cannot be deleted until all volumes  
that refer to it are first deleted
```

```
| 1703946
| Cannot determine if the ruleset is in use by a volume.  It cannot be
deleted until all volumes that refer to it are first deleted
```

```
| 1703954
| Export policy does not exist
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

```
====
```

```
== Definitions
```

```
[.api-def-first-level]
```

```
.See Definitions
```

```
[%collapsible%closed]
```

```
//Start collapsible Definitions block
```

```

====
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

```

```

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

[[ID74e500a6aea4e9a27e66635638a90bf7]]
= Retrieve an export policy rule

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{policy.id}/rules/{index}`#

*Introduced In:* 9.6

Retrieves an export policy rule

== Related ONTAP commands

* `vserver export-policy rule show`

== Learn more

* xref:{relative_path}protocols_nfs_export-
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]

== Parameters

[cols=5*,options=header]
|===

|Name
|Type
|In
|Required
|Description

|policy.id

```

```
|integer
|path
|True
a|Export Policy ID

|index
|integer
|path
|True
a|Export Rule Index

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|anonymous_user
|string
a|User ID To Which Anonymous Users Are Mapped.

|clients
|array[link:#export_client[export_client]]
a|Array of client matches

|index
```



```
|integer
a|Index of the rule within the export policy.

|protocols
|array[string]
a|

|ro_rule
|array[string]
a|Authentication flavors that the read-only access rule governs

|rw_rule
|array[string]
a|Authentication flavors that the read/write access rule governs

|superuser
|array[string]
a|Authentication flavors that the superuser security type governs

|===
```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "clients": {
    "match": "0.0.0.0/0"
  },
  "index": 0,
  "protocols": {
  },
  "ro_rule": {
  },
  "rw_rule": {
  },
  "superuser": {
```

```
}  
}  
====  
  
== Error
```

Status: Default, Error

```
[cols=3*,options=header]  
|===  
|Name  
|Type  
|Description  
  
|error  
|link:#error[error]  
a|  
  
|===  
  
.Example error  
[%collapsible%closed]  
====  
[source,json,subs=+macros]  
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}  
====  
  
== Definitions  
  
[.api-def-first-level]  
.See Definitions  
[%collapsible%closed]  
//Start collapsible Definitions block  
====  
[#href]
```

```

[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#export_client]
[.api-collapsible-fifth-title]
export_client

[cols=3*,options=header]
|===
|Name
|Type
|Description

|match
|string
a|Client Match Hostname, IP Address, Netgroup, or Domain.
You can specify the match as a string value in any of the

```

following formats:

- \* As a hostname; for instance, host1
- \* As an IPv4 address; for instance, 10.1.12.24
- \* As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1
- \* As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24
- \* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64
- \* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0
- \* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng
- \* As a domain name preceded by the . character; for instance, .example.com

|===

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

|===

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```

|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

[[IDd768b9068c1f01adf8009eb75fa1b83b]]
= Update the properties of an export policy rule

[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{policy.id}/rules/{index}`#

*Introduced In:* 9.6

Updates the properties of an export policy rule to change an export policy
rule's index or fields.

== Related ONTAP commands

* `vserver export-policy rule modify`

```

```
* `vserver export-policy rule setindex`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_nfs_export-  
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|policy.id
```

```
|integer
```

```
|path
```

```
|True
```

```
a|Export Policy ID
```

```
|index
```

```
|integer
```

```
|path
```

```
|True
```

```
a|Export Rule Index
```

```
|new_index
```

```
|integer
```

```
|query
```

```
|False
```

```
a|New Export Rule Index
```

```
|===
```

```
== Request Body
```

```
[cols=3*,options=header]
```

```
|===
```

```

|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|anonymous_user
|string
a|User ID To Which Anonymous Users Are Mapped.

|clients
|array[link:#export_client[export_client]]
a|Array of client matches

|index
|integer
a|Index of the rule within the export policy.

|protocols
|array[string]
a|

|ro_rule
|array[string]
a|Authentication flavors that the read-only access rule governs

|rw_rule
|array[string]
a|Authentication flavors that the read/write access rule governs

|superuser
|array[string]
a|Authentication flavors that the superuser security type governs

|===

.Example request
[%collapsible%closed]

```

```
====  
[source,json,subs=+macros]  
{  
  "_links": {  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "clients": {  
    "match": "0.0.0.0/0"  
  },  
  "index": 0,  
  "protocols": {  
  },  
  "ro_rule": {  
  },  
  "rw_rule": {  
  },  
  "superuser": {  
  }  
}  
====
```

== Response

Status: 200, Ok

== Error

Status: Default

ONTAP Error Response Codes

```
|====  
| Error Code | Description  
  
| 1703954  
| Export policy does not exist  
  
| 1704036  
| Invalid clientmatch: missing domain name  
  
| 1704037  
| Invalid clientmatch: missing network name
```



```
| 1704038
| Invalid clientmatch: missing netgroup name

| 1704039
| Invalid clientmatch

| 1704040
| Invalid clientmatch: address bytes masked out by netmask are non-zero

| 1704041
| Invalid clientmatch: address bytes masked to zero by netmask

| 1704042
| Invalid clientmatch: too many bits in netmask

| 1704043
| Invalid clientmatch: invalid netmask

| 1704044
| Invalid clientmatch: invalid characters in host name

| 1704045
| Invalid clientmatch: invalid characters in domain name

| 1704050
| Invalid clientmatch: clientmatch list contains a duplicate string.
Duplicate strings in a clientmatch list are not supported

| 1704051
| Warning: Not adding any new strings to the clientmatch field for
ruleindex. All of the match strings are already in the clientmatch list

| 1704064
| Clientmatch host name too long

| 1704065
| Clientmatch domain name too long

| 3277000
| Upgrade all nodes to Data ONTAP 9.0.0 or above to use krb5p as a
security flavor in export-policy rules

| 3277083
| User ID is not valid. Enter a value for User ID from 0 to 4294967295
|===
```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type

```

```
|Description
```

```
|href
```

```
|string
```

```
a|
```

```
|===
```

```
[#_links]
```

```
[.api-collapsible-fifth-title]
```

```
_links
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|self
```

```
|link:#href[href]
```

```
a|
```

```
|===
```

```
[#export_client]
```

```
[.api-collapsible-fifth-title]
```

```
export_client
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|match
```

```
|string
```

```
a|Client Match Hostname, IP Address, Netgroup, or Domain.  
You can specify the match as a string value in any of the  
following formats:
```

```
* As a hostname; for instance, host1
```

```
* As an IPv4 address; for instance, 10.1.12.24
```

```
* As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1
```

```
* As an IPv4 address with a subnet mask expressed as a number of bits; for  
instance, 10.1.12.0/24
```

- \* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64
- \* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0
- \* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng
- \* As a domain name preceded by the . character; for instance, .example.com

|===

```
[#export_rule]
[.api-collapsible-fifth-title]
export_rule
```

```
[cols=3*,options=header]
```

|===

```
|Name
|Type
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|anonymous_user
```

```
|string
```

```
a|User ID To Which Anonymous Users Are Mapped.
```

```
|clients
```

```
|array[link:#export_client[export_client]]
```

```
a|Array of client matches
```

```
|index
```

```
|integer
```

```
a|Index of the rule within the export policy.
```

```
|protocols
```

```
|array[string]
```

```
a|
```

```
|ro_rule
```

```
|array[string]
```

```
a|Authentication flavors that the read-only access rule governs
```

```
|rw_rule
```

```
|array[string]
```

```
a|Authentication flavors that the read/write access rule governs
```

```
|superuser
```

```
|array[string]
```

```
a|Authentication flavors that the superuser security type governs
```

```
|===
```

```
[#error_arguments]
```

```
[.api-collapsible-fifth-title]
```

```
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|code
```

```
|string
```

```
a|Argument code
```

```
|message
```

```
|string
```

```
a|Message argument
```

```
|===
```

```
[#error]
```

```
[.api-collapsible-fifth-title]
```

```
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```

|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDb88d9fe21a1404d089b760d457e9af65]]
= Retrieve export policy rule clients

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{policy.id}/rules/{index}/clients`#

*Introduced In:* 9.6

Retrieves export policy rule clients.

== Learn more

* xref:{relative_path}protocols_nfs_export-
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]

== Parameters

```

```

[cols=5*,options=header]
|===

|Name
|Type
|In
|Required
|Description

|policy.id
|integer
|path
|True
a|Export Policy ID

|index
|integer
|path
|True
a|Export Rule Index

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|max_records
|integer
|query
|False
a|Limit the number of records returned.

|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.

* Default value: 1

```

```
|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds. ONTAP
returns earlier if either max records or the end of the collection is
reached.

* Default value: 1
* Max value: 120
* Min value: 0

|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.

|===

== Response
```

Status: 200, Ok



```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of export rule client records

|records
|array[link:#export_client[export_client]]
a|

|===

```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```

{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "match": "0.0.0.0/0"
  }
}

```

====

== Error

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#export_client]
[.api-collapsible-fifth-title]
export_client

[cols=3*,options=header]
|===
|Name
|Type
|Description

|match
|string
a|Client Match Hostname, IP Address, Netgroup, or Domain.
You can specify the match as a string value in any of the
following formats:

* As a hostname; for instance, host1
* As an IPv4 address; for instance, 10.1.12.24
* As an IPv6 address; for instance, fd20:8b1e:b255:4071::100:1

```

\* As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24  
\* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8b1e:b255:4071::/64  
\* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0  
\* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng  
\* As a domain name preceded by the . character; for instance, .example.com

|===

```
[#error_arguments]  
[.api-collapsible-fifth-title]  
error_arguments
```

```
[cols=3*,options=header]
```

|===

```
|Name  
|Type  
|Description
```

```
|code  
|string  
a|Argument code
```

```
|message  
|string  
a|Message argument
```

|===

```
[#error]  
[.api-collapsible-fifth-title]  
error
```

```
[cols=3*,options=header]
```

|===

```
|Name  
|Type  
|Description
```

```

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[ID75f7f3f4b5e4d0a0abb168880a6223a3]]
= Create an export policy rule client

[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-
block]#`/protocols/nfs/export-policies/{policy.id}/rules/{index}/clients`#

*Introduced In:* 9.6

Creates an export policy rule client

== Required properties

* `policy.id` - Existing export policy that contains export policy rules
for the client being added.
* `index` - Existing export policy rule for which to create an export
client.
* `match` - Base name for the export policy client.

== Related ONTAP commands

```

```
* `vserver export-policy rule add-clientmatches`
```

== Learn more

```
* xref:{relative_path}protocols_nfs_export-  
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name  
|Type  
|In  
|Required  
|Description
```

```
|policy.id  
|integer  
|path  
|True  
a|Export Policy ID
```

```
|index  
|integer  
|path  
|True  
a|Export Rule Index
```

```
|return_records  
|boolean  
|query  
|False  
a|The default is false. If set to true, the records are returned.
```

```
* Default value:
```

```
|===
```

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|match
```

```
|string
```

a|Client Match Hostname, IP Address, Netgroup, or Domain.

You can specify the match as a string value in any of the following formats:

- \* As a hostname; for instance, host1

- \* As an IPv4 address; for instance, 10.1.12.24

- \* As an IPv6 address; for instance, fd20:8ble:b255:4071::100:1

- \* As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24

- \* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8ble:b255:4071::/64

- \* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0

- \* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng

- \* As a domain name preceded by the . character; for instance, .example.com

```
|===
```

.Example request

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
```

```
  "match": "0.0.0.0/0"
```

```
}
```

```
====
```

```
== Response
```

Status: 201, Created

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of export rule client records

|records
|array[link:#export_client[export_client]]
a|

|===

```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```

{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "match": "0.0.0.0/0"
  }
}

```

====

== Error

Status: Default



## ONTAP Error Response Codes

```
|===  
| Error Code | Description  
  
| 1703954  
| Export policy does not exist  
  
| 1704036  
| Invalid clientmatch: missing domain name  
  
| 1704037  
| Invalid clientmatch: missing network name  
  
| 1704038  
| Invalid clientmatch: missing netgroup name  
  
| 1704039  
| Invalid clientmatch  
  
| 1704040  
| Invalid clientmatch: address bytes masked out by netmask are non-zero  
  
| 1704041  
| Invalid clientmatch: address bytes masked to zero by netmask  
  
| 1704042  
| Invalid clientmatch: too many bits in netmask  
  
| 1704043  
| Invalid clientmatch: invalid netmask  
  
| 1704044  
| Invalid clientmatch: invalid characters in host name  
  
| 1704045  
| Invalid clientmatch: invalid characters in domain name  
  
| 1704050  
| Invalid clientmatch: the clientmatch list contains a duplicate string.  
Duplicate strings in a clientmatch list are not supported  
  
| 1704051  
| Warning: Not adding any new strings to the clientmatch field for  
ruleindex. All of the match strings are already in the clientmatch list  
  
| 1704064
```

```
| Clientmatch host name too long  
  
| 1704065  
| Clientmatch domain name too long  
|===
```

```
[cols=3*,options=header]
```

```
|===  
|Name  
|Type  
|Description
```

```
|error  
|link:#error[error]  
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}
```

```
====
```

```
== Definitions
```

```
[.api-def-first-level]
```

```
.See Definitions
```

```
[%collapsible%closed]
```

```
//Start collapsible Definitions block
```

```
====
```

```
[#export_client]
```

```
[.api-collapsible-fifth-title]
```

```
export_client
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|match
```

```
|string
```

```
a|Client Match Hostname, IP Address, Netgroup, or Domain.
```

```
You can specify the match as a string value in any of the following formats:
```

```
* As a hostname; for instance, host1
```

```
* As an IPv4 address; for instance, 10.1.12.24
```

```
* As an IPv6 address; for instance, fd20:8ble:b255:4071::100:1
```

```
* As an IPv4 address with a subnet mask expressed as a number of bits; for instance, 10.1.12.0/24
```

```
* As an IPv6 address with a subnet mask expressed as a number of bits; for instance, fd20:8ble:b255:4071::/64
```

```
* As an IPv4 address with a network mask; for instance, 10.1.16.0/255.255.255.0
```

```
* As a netgroup, with the netgroup name preceded by the @ character; for instance, @eng
```

```
* As a domain name preceded by the . character; for instance, .example.com
```

```
|===
```

```
[#href]
```

```
[.api-collapsible-fifth-title]
```

```
href
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|href
```

```
|string
```

```
a|
```

```
|===
```

```

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]

```

```

error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[ID1093e5afa35b89cc19a817a0fa9b1823]]
= Delete an export policy client

[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-
block]#`/protocols/nfs/export-
policies/{policy.id}/rules/{index}/clients/{match}`#

*Introduced In:* 9.6

Deletes an export policy client

```

== Related ONTAP commands

```
* `vserver export-policy rule remove-clientmatches`
```

== Learn more

```
* xref:{relative_path}protocols_nfs_export-  
policies_endpoint_overview.html[DOC /protocols/nfs/export-policies]
```

== Parameters

[cols=5\*,options=header]

|===

|Name

|Type

|In

|Required

|Description

|policy.id

|integer

|path

|True

a|Export Policy ID

|index

|integer

|path

|True

a|Export Rule Index

|match

|string

|path

|True

a|Export Client Match

|===

== Response

Status: 200, Ok

== Error

## Status: Default

### ONTAP Error Response Codes

```
|===  
| Error Code | Description  
  
| 1703954  
| Export policy does not exist  
  
| 1704036  
| Invalid clientmatch: missing domain name  
  
| 1704037  
| Invalid clientmatch: missing network name  
  
| 1704038  
| Invalid clientmatch: missing netgroup name  
  
| 1704039  
| Invalid clientmatch  
  
| 1704040  
| Invalid clientmatch: address bytes masked out by netmask are non-zero  
  
| 1704041  
| Invalid clientmatch: address bytes masked to zero by netmask  
  
| 1704042  
| Invalid clientmatch: too many bits in netmask  
  
| 1704043  
| Invalid clientmatch: invalid netmask  
  
| 1704044  
| Invalid clientmatch: invalid characters in host name  
  
| 1704045  
| Invalid clientmatch: invalid characters in domain name  
  
| 1704050  
| Invalid clientmatch: the clientmatch list contains a duplicate string.  
Duplicate strings in a clientmatch list are not supported
```

```
| 1704052
| Warning: Not removing any strings from the clientmatch field for
ruleindex. None of the match strings were found in the clientmatch list
```

```
| 1704064
| Clientmatch host name too long
```

```
| 1704065
| Clientmatch domain name too long
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====
```

```
== Definitions
```

```
[.api-def-first-level]
```



```

.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

```

```

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

:leveloffset: -1

= View and update Kerberos interfaces

:leveloffset: +1

[[IDf3905e3fb14bd734c53695a417f6365e]]
= Protocols NFS Kerberos interfaces endpoint overview

== Examples

=== Retrieving the Kerberos interface configuration details

----

# The API:
GET /api/protocols/nfs/kerberos/interfaces

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/nfs/kerberos/interfaces"
----

=== Updating the Kerberos interface configuration

----

```

```

# The API:
PATCH /api/protocols/nfs/kerberos/interfaces/{interface.uuid}

# The call:
curl -d "@test_patch_kerb_interface.txt" -X PATCH "https://<mgmt-
ip>/api/protocols/nfs/kerberos/interfaces/e62936de-7342-11e8-9eb4-
0050568be2b7"
test_patch_kerb_interface.txt (body) :
{
  "enabled" : "true",
  "spn": "nfs/datalif1-vs3im3-d1.sim.netapp.com@NFS-NSR-W01.RTP.NETAPP.COM",
  "user" : "administrator",
  "password" : "Hello123!"
}
-----

[[IDdca64a9637c41903ec803ffd2d422e82]]
= Retrieve Kerberos interfaces

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/kerberos/interfaces`#

*Introduced In:* 9.6

Retrieves Kerberos interfaces.

== Related ONTAP commands

* `vserver nfs kerberos interface show`

== Learn more

*
xref:{relative_path}protocols_nfs_kerberos_interfaces_endpoint_overview.ht
ml[DOC /protocols/nfs/kerberos/interfaces]

== Parameters

[cols=5*,options=header]
|===

```

```
|Name  
|Type  
|In  
|Required  
|Description
```

```
|svm.uuid  
|string  
|query  
|False  
a|Filter by svm.uuid
```

```
|svm.name  
|string  
|query  
|False  
a|Filter by svm.name
```

```
|encryption_types  
|string  
|query  
|False  
a|Filter by encryption_types
```

```
|spn  
|string  
|query  
|False  
a|Filter by spn
```

```
|enabled  
|boolean  
|query  
|False  
a|Filter by enabled
```

```
|interface.name  
|string  
|query  
|False  
a|Filter by interface.name
```

```
|interface.uuid
|string
|query
|False
a|Filter by interface.uuid
```

```
|interface.ip.address
|string
|query
|False
a|Filter by interface.ip.address
```

```
|fields
|array[string]
|query
|False
a|Specify the fields to return.
```

```
|max_records
|integer
|query
|False
a|Limit the number of records returned.
```

```
|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.
```

\* Default value: 1

```
|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds. ONTAP
returns earlier if either max records or the end of the collection is
reached.
```

```
* Default value: 1
* Max value: 120
* Min value: 0
```

```
|order_by
|array[string]
|query
|False
```

a|Order results by specified fields and optional [asc|desc] direction.  
Default direction is 'asc' for ascending.

```
|===
```

```
== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
 |_links
|link:#_links[_links]
a|
```

```
 |num_records
|integer
a|Number of records
```

```
 |records
|array[link:#kerberos_interface[kerberos_interface]]
a|
```

```
|===
```

```
.Example response
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```
{
```

```
"_links": {
  "next": {
    "href": "/api/resourcelink"
  },
  "self": {
    "href": "/api/resourcelink"
  }
},
"records": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "encryption_types": {
  },
  "interface": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "ip": {
      "address": "10.10.10.7"
    },
    "name": "lif1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
}
====

== Error
```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

```



```

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:href[href]
a|

|===

[#ip]
[.api-collapsible-fifth-title]

```

ip

IP information

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|address

|string

a|IPv4 or IPv6 address

|===

[#interface]

[.api-collapsible-fifth-title]

interface

Network interface

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|\_links

|link:#\_links[\_links]

a|

|ip

|link:#ip[ip]

a|IP information

|name

|string

a|The name of the interface.

|uuid

```
|string  
a|The UUID that uniquely identifies the interface.
```

```
|===
```

```
[#svm]  
[.api-collapsible-fifth-title]  
svm
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|_links  
|link:#_links[_links]  
a|
```

```
|name  
|string  
a|The name of the SVM.
```

```
|uuid  
|string  
a|The unique identifier of the SVM.
```

```
|===
```

```
[#kerberos_interface]  
[.api-collapsible-fifth-title]  
kerberos_interface
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|_links  
|link:#_links[_links]  
a|
```

```
|enabled
|boolean
a|Specifies if Kerberos is enabled.
```

```
|encryption_types
|array[string]
a|
```

```
|interface
|link:#interface[interface]
a|Network interface
```

```
|keytab_uri
|string
a|Load keytab from URI
```

```
|organizational_unit
|string
a|Organizational unit
```

```
|password
|string
a|Account creation password
```

```
|spn
|string
a|Service principal name. Valid in PATCH.
```

```
|svm
|link:#svm[svm]
a|
```

```
|user
|string
a|Account creation user name
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[IDe891f69682adfb38e5ealc5ad3dd9014]]
= Retrieve a Kerberos interface
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/kerberos/interfaces/{interface.uuid}`#
```

```
*Introduced In:* 9.6
```

```
Retrieves a Kerberos interface.
```

```
== Related ONTAP commands
```

```
* `vserver nfs kerberos interface show`
```

```
== Learn more
```

```
*
```

```
xref:{relative_path}protocols_nfs_kerberos_interfaces_endpoint_overview.ht
ml[DOC /protocols/nfs/kerberos/interfaces]
```

```
== Parameters
```

```
[cols=5*,options=header]
|===
```

```
|Name
|Type
|In
|Required
|Description
```

```
|interface.uuid
```

```
|string
|path
|True
a|Network interface UUID

* Introduced in: 9.7

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|enabled
|boolean
a|Specifies if Kerberos is enabled.

|encryption_types
|array[string]
a|

|interface
|link:#interface[interface]
a|Network interface

|keytab_uri
|string
```

```
a|Load keytab from URI
```

```
|organizational_unit
```

```
|string
```

```
a|Organizational unit
```

```
|password
```

```
|string
```

```
a|Account creation password
```

```
|spn
```

```
|string
```

```
a|Service principal name. Valid in PATCH.
```

```
|svm
```

```
|link:#svm[svm]
```

```
a|
```

```
|user
```

```
|string
```

```
a|Account creation user name
```

```
|===
```

```
.Example response
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{  
  "_links": {  
    "self": {  
      "href": "/api/resourcelink"  
    }  
  },  
  "encryption_types": {  
  },  
  "interface": {  
    "_links": {  
      "self": {  
        "href": "/api/resourcelink"  
      }  
    }  
  }  
}
```



```

    },
    "ip": {
      "address": "10.10.10.7"
    },
    "name": "lif1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    }
  }
}

```

```

    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====

```

```

[#href]
[.api-collapsible-fifth-title]
href

```

```

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

```

```

|href
|string
a|

```

```

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

```

```

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

```

```

|self
|link:#href[href]
a|

```

```

|===

```

```
[#ip]
[.api-collapsible-fifth-title]
ip
```

IP information

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|address
|string
a|IPv4 or IPv6 address
```

```
|===
```

```
[#interface]
[.api-collapsible-fifth-title]
interface
```

Network interface

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
 |_links
|link:#_links[_links]
a|
```

```
|ip
|link:#ip[ip]
a|IP information
```

```
|name
|string
```

```
a|The name of the interface.  
  
|uuid  
|string  
a|The UUID that uniquely identifies the interface.
```

```
|===
```

```
[#svm]  
[.api-collapsible-fifth-title]  
svm
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|_links  
|link:#_links[_links]  
a|
```

```
|name  
|string  
a|The name of the SVM.
```

```
|uuid  
|string  
a|The unique identifier of the SVM.
```

```
|===
```

```
[#error_arguments]  
[.api-collapsible-fifth-title]  
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
```

```
====
```

```
[[IDc066f05084bbec5bfe48d0780449dd67]]
```

```
= Update Kerberos interface properties
```

```
[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-  
block]#`/protocols/nfs/kerberos/interfaces/{interface.uuid}`#
```

```
*Introduced In:* 9.6
```

Updates the properties of a Kerberos interface.

```
== Related ONTAP commands
```

```
* `vserver nfs kerberos interface modify`  
* `vserver nfs kerberos interface enable`  
* `vserver nfs kerberos interface disable`
```

```
== Learn more
```

```
*
```

```
xref:{relative_path}protocols_nfs_kerberos_interfaces_endpoint_overview.ht  
ml[DOC /protocols/nfs/kerberos/interfaces]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|interface.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|Network interface UUID
```

```
* Introduced in: 9.7
```

```
|===
```

```
== Request Body
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
 |_links
```

```
 |link:#_links[_links]
```

```
 a|
```

```
 |enabled
```

```
 |boolean
```

```
 a|Specifies if Kerberos is enabled.
```

```
 |encryption_types
```

```
 |array[string]
```

```
 a|
```

```
 |interface
```

```
 |link:#interface[interface]
```

```
 a|Network interface
```

```
 |keytab_uri
```

```
 |string
```

```
 a|Load keytab from URI
```

```
 |organizational_unit
```

```
 |string
```

```
 a|Organizational unit
```

```
 |password
```

```
 |string
```

```
 a|Account creation password
```

```
 |spn
```

```
 |string
```

a|Service principal name. Valid in PATCH.

|svm  
|link:#svm[svm]  
a|

|user  
|string  
a|Account creation user name

|===

.Example request

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "encryption_types": {
  },
  "interface": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "ip": {
      "address": "10.10.10.7"
    },
    "name": "lif1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
```



```
"uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
====
```

== Response

Status: 200, Ok

```
== Error
```

Status: Default

ONTAP Error Response codes

```
|====
| Error codes | Description

| 1966082
| LIF could not be found in database. Contact technical support for
assistance.

| 3276801
| Failed to bind service principal name on LIF.

| 3276809
| Failed to disable NFS Kerberos on LIF.

| 3276832
| Failed to insert Kerberos attributes to database.

| 3276842
| Internal error. Failed to import Kerberos keytab file into the
management databases. Contact technical support for assistance.

| 3276861
| Kerberos is already enabled/disabled on this LIF.

| 3276862
| Kerberos service principal name is required.

| 3276889
| Failed to enable NFS Kerberos on LIF.

| 3276937
```

```

| Failed to lookup the Vserver for the virtual interface.

| 3276941
| Kerberos is a required field.

| 3276942
| Service principal name is invalid. It must of the format:"nfs/+++<LIF-
FQDN>+++@REALM"+++</LIF-FQDN>+++

| 3276944
| Internal error. Reason: Failed to initialize the Kerberos context

| 3276945
| Internal error. Reason: Failed to parse the service principal name

| 3276951
| Warning: Skipping unsupported encryption type for service principal name

| 3276952
| "organizational_unit" option cannot be used for "Other" vendor.

| 3276965
| Account sharing across Vservers is not allowed. Use a different service
principal name unique within the first 15 characters.

| 3277019
| Cannot specify -force when enabling Kerberos.

| 3277020
| Modifying the NFS Kerberos configuration for a LIF that is not
configured for NFS is not supported.

| 3277043
| Keytab import failed due to missing keys. Keys for encryption types are
required for Vserver but found no matching keys for service principal
name. Generate the keytab file with all required keys and try again.
|===

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error

```

```

|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#ip]
[.api-collapsible-fifth-title]
ip

IP information

[cols=3*,options=header]
|===
|Name
|Type
|Description

|address
|string
a|IPv4 or IPv6 address

|===

[#interface]
[.api-collapsible-fifth-title]
interface

Network interface

[cols=3*,options=header]
|===

```

```

|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|ip
|link:#ip[ip]
a|IP information

|name
|string
a|The name of the interface.

|uuid
|string
a|The UUID that uniquely identifies the interface.

|===

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string

```

a|The unique identifier of the SVM.

|===

```
[#kerberos_interface]
[.api-collapsible-fifth-title]
kerberos_interface
```

```
[cols=3*,options=header]
```

|===

```
|Name
|Type
|Description
```

```
 |_links
```

```
|link:#_links[_links]
```

a|

```
|enabled
```

```
|boolean
```

a|Specifies if Kerberos is enabled.

```
|encryption_types
```

```
|array[string]
```

a|

```
|interface
```

```
|link:#interface[interface]
```

a|Network interface

```
|keytab_uri
```

```
|string
```

a|Load keytab from URI

```
|organizational_unit
```

```
|string
```

a|Organizational unit

```
|password
```

```
|string
```

a|Account creation password

```
|spn
|string
a|Service principal name. Valid in PATCH.
```

```
|svm
|link:#svm[svm]
a|
```

```
|user
|string
a|Account creation user name
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```

|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

:leveloffset: -1

= Manage Kerberos realms

:leveloffset: +1

[[ID5a879d8e1f8368d4b3f2db3591f37489]]
= Protocols NFS Kerberos realms endpoint overview

== Examples

```



```
=== Retrieving the Kerberos realm details
```

```
----
```

```
# The API:
```

```
GET /api/protocols/nfs/kerberos/realms
```

```
# The call:
```

```
curl -X GET "https://<mgmt-ip>/api/protocols/nfs/kerberos/realms"
```

```
----
```

```
=== Creating the Kerberos realm for an SVM
```

```
----
```

```
# The API:
```

```
POST /api/protocols/nfs/kerberos/realms
```

```
# The call:
```

```
curl -d "@test_post_kerb_realm.txt" -X POST "https://<mgmt-ip>/api/protocols/nfs/kerberos/realms"
```

```
test_post_kerb_realm.txt (body):
```

```
{
```

```
"svm.uuid": "05c90dc2-7343-11e8-9eb4-0050568be2b7",
```

```
"name": "NFS-NSR-W02.RTP.NETAPP.COM",
```

```
  "kdc": {
```

```
    "vendor": "microsoft",
```

```
    "ip": "10.225.185.112",
```

```
    "port": 88
```

```
  },
```

```
  "comment": "realm",
```

```
  "ad_server": {
```

```
    "name": "nfs-nsr-w02.rtp.netapp.com",
```

```
    "address": "10.225.185.112"
```

```
  }
```

```
}
```

```
----
```

```
=== Updating the Kerberos realm for an SVM
```

```
----
```

```
# The API:
```

```
PATCH /api/protocols/nfs/kerberos/realms/{svm.uuid}/{name}
```

```
# The call:
```

```

curl -d "@test_patch_kerb_realm.txt" -X PATCH "https://<mgmt-
ip>/api/protocols/nfs/kerberos/realms/05c90dc2-7343-11e8-9eb4-
0050568be2b7/NFS-NSR-W02.RTP.NETAPP.COM"
test_patch_kerb_realm.txt(body):
{
  "kdc": {
    "vendor": "Microsoft",
    "ip": "100.225.185.112",
    "port": 88
  },
  "comment": "realm modify",
  "ad_server": {
    "name": "nfs.netapp.com",
    "address": "192.2.18.112"
  }
}
}
-----

=== Deleting the Kerberos realm for an SVM

-----

# The API:
DELETE /api/protocols/nfs/kerberos/realms/{svm.uuid}/{name}

# The call:
curl -X DELETE "https://<mgmt-
ip>/api/protocols/nfs/kerberos/realms/05c90dc2-7343-11e8-9eb4-
0050568be2b7/NFS-NSR-W02.RTP.NETAPP.COM"
-----

'''

[[ID8b1a8b95867bfd2dca53b310cffec3f5]]
= Retrieve Kerberos realms

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/kerberos/realms`#

*Introduced In:* 9.6

Retrieves Kerberos realms.

```

== Related ONTAP commands

\* ``vserver nfs kerberos realm show``

== Learn more

\*

xref:{relative\_path}protocols\_nfs\_kerberos\_realms\_endpoint\_overview.html[DOC /protocols/nfs/kerberos/realms]

== Parameters

[cols=5\*,options=header]

|===

|Name

|Type

|In

|Required

|Description

|ad\_server.address

|string

|query

|False

a|Filter by ad\_server.address

|ad\_server.name

|string

|query

|False

a|Filter by ad\_server.name

|svm.uuid

|string

|query

|False

a|Filter by svm.uuid

|svm.name

|string

|query

|False

```
a|Filter by svm.name
```

```
|kdc.vendor
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by kdc.vendor
```

```
|kdc.port
```

```
|integer
```

```
|query
```

```
|False
```

```
a|Filter by kdc.port
```

```
|kdc.ip
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by kdc.ip
```

```
|encryption_types
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by encryption_types
```

```
|name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by name
```

```
|comment
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by comment
```

```
|fields
```

```
|array[string]
```

```
|query
|False
a|Specify the fields to return.

|max_records
|integer
|query
|False
a|Limit the number of records returned.

|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.

* Default value: 1

|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds. ONTAP
returns earlier if either max records or the end of the collection is
reached.

* Default value: 1
* Max value: 120
* Min value: 0

|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.

|===

== Response
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#kerberos_realm[kerberos_realm]]
a|

|===
```

.Example response

[%collapsible%closed]

====

```
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "ad_server": {
      "address": "1.2.3.4"
    }
  },
}
```

```

"comment": "string",
"encryption_types": {
},
"kdc": {
  "ip": "1.2.3.4",
  "port": "88",
  "vendor": "microsoft"
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {

```

```

    "code": "string",
    "message": "string"
  },
  "code": "4",
  "message": "entry doesn't exist",
  "target": "uuid"
}
}
====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====

```

```

[#href]
[.api-collapsible-fifth-title]
href

```

```

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

```

```

|href
|string
a|

```

```

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

```

```

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

```

```

|next
|link:#href[href]

```



```

a|

|self
|link:#href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#ad_server]
[.api-collapsible-fifth-title]
ad_server

[cols=3*,options=header]
|===
|Name
|Type
|Description

|address
|string
a|Active Directory server IP address

|name
|string
a|Active Directory server name

|===

```

```

[#kdc]
[.api-collapsible-fifth-title]
kdc

[cols=3*,options=header]
|===
|Name
|Type
|Description

|ip
|string
a|KDC IP address

|port
|integer
a|KDC port

|vendor
|string
a|Key Distribution Center (KDC) vendor. Following values are supported:

* microsoft - Microsoft Active Directory KDC
* other - MIT Kerberos KDC or other KDC

|===

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

```

```
|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.
```

```
|===
```

```
[#kerberos_realm]
[.api-collapsible-fifth-title]
kerberos_realm
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|ad_server
|link:#ad_server[ad_server]
a|
```

```
|comment
|string
a|Comment
```

```
|encryption_types
|array[string]
a|
```

```
|kdc
|link:#kdc[kdc]
a|
```

```
|name
|string
a|Kerberos realm
```

```

|svm
|link:#svm[svm]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

```

```

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

[[IDb53a0c56a9e4c676b65cfd4781c6d6cf]]
= Create a Kerberos realm

[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-
block]#`/protocols/nfs/kerberos/realms`#

*Introduced In:* 9.6

Creates a Kerberos realm.

== Required properties

* `svm.uuid` or `svm.name` - Existing SVM on which to create the Kerberos
realm.
* `name` - Base name for the Kerberos realm.
* `kdc.vendor` - Vendor of the Key Distribution Center (KDC) server for
this Kerberos realm. If the configuration uses a Microsoft Active
Directory domain for authentication, this field must be `microsoft`.
* `kdc.ip` - IP address of the KDC server for this Kerberos realm.

== Recommended optional properties

* `ad_server.name` - Host name of the Active Directory Domain Controller
(DC). This is a mandatory parameter if the kdc-vendor is `microsoft`.

```

\* `ad\_server.address` - IP address of the Active Directory Domain Controller (DC). This is a mandatory parameter if the kdc-vendor is `microsoft`.

== Default property values

If not specified in POST, the following default property value is assigned:

\* `kdc.port` - `_88_`

== Related ONTAP commands

\* `vserver nfs kerberos realm create`

== Learn more

\*

xref:{relative\_path}protocols\_nfs\_kerberos\_realms\_endpoint\_overview.html[DOC /protocols/nfs/kerberos/realms]

== Parameters

[cols=5\*,options=header]

|===

|Name

|Type

|In

|Required

|Description

|return\_records

|boolean

|query

|False

a|The default is false. If set to true, the records are returned.

\* Default value:

|===

== Request Body

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|ad_server
|link:#ad_server[ad_server]
a|

|comment
|string
a|Comment

|encryption_types
|array[string]
a|

|kdc
|link:#kdc[kdc]
a|

|name
|string
a|Kerberos realm

|svm
|link:#svm[svm]
a|

|===

.Example request
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  }
}

```

```
    }
  },
  "ad_server": {
    "address": "1.2.3.4"
  },
  "comment": "string",
  "encryption_types": {
  },
  "kdc": {
    "ip": "1.2.3.4",
    "port": "88",
    "vendor": "microsoft"
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
====
```

== Response

Status: 201, Created

```
== Error
```

Status: Default

ONTAP Error Response codes

```
|===
| Error codes | Description
| 2949121
| Active Directory server name required.
| 2949122
| Active Directory server address required
| 2949123
```



```
| Failed to create Kerberos realm.

| 2949124
| Failed to create hosts file entry.

| 3276949
| Kerberos realm creation failed. Reason: The parameters "ad_server.name"
and "ad_server.address" are only valid when "kdc.vendor" is Microsoft

| 3276976
| "realm" is a required input

| 3276998
| Only the data Vservers can own NFS Kerberos realms.
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

```
====
```

```

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#ad_server]
[.api-collapsible-fifth-title]
ad_server

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

|address
|string
a|Active Directory server IP address

|name
|string
a|Active Directory server name

|===

[#kdc]
[.api-collapsible-fifth-title]
kdc

[cols=3*,options=header]
|===
|Name
|Type
|Description

|ip
|string
a|KDC IP address

|port
|integer
a|KDC port

|vendor
|string
a|Key Distribution Center (KDC) vendor. Following values are supported:

* microsoft - Microsoft Active Directory KDC
* other - MIT Kerberos KDC or other KDC

|===

```

```

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

|===

[#kerberos_realm]
[.api-collapsible-fifth-title]
kerberos_realm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|ad_server
|link:#ad_server[ad_server]
a|

```

```
|comment
|string
a|Comment
```

```
|encryption_types
|array[string]
a|
```

```
|kdc
|link:#kdc[kdc]
a|
```

```
|name
|string
a|Kerberos realm
```

```
|svm
|link:#svm[svm]
a|
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDed1392fe1563a7636d50702840487b4c]]
= Delete a Kerberos realm

[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-
block]#`/protocols/nfs/kerberos/realms/{svm.uuid}/{name}`#

*Introduced In:* 9.6

```

Deletes a Kerberos realm.

```
* `vserver nfs kerberos realm delete`
```

== Learn more

\*

xref:{relative\_path}protocols\_nfs\_kerberos\_realms\_endpoint\_overview.html[DOC /protocols/nfs/kerberos/realms]

== Parameters

[cols=5\*,options=header]

|===

|Name

|Type

|In

|Required

|Description

|svm.uuid

|string

|path

|True

a|SVM UUID

|name

|string

|path

|True

a|Kerberos realm

|===

== Response

Status: 200, Ok

== Error

Status: Default

## ONTAP Error Response codes

|===

| Error codes | Description

| 1966125

| Failed to remove hosts entry.

| 1966126

| Failed to lookup hosts entry.

| 2949141

| Failed to lookup Kerberos realm.

| 2949142

| Failed to remove Kerberos realm.

| 3276942

| Service principal name is invalid. It must of the format:"nfs/+++<LIF-FQDN>+++@REALM\\\\"+++</LIF-FQDN>+++

| 3276976

| "realm" is a required input

| 3276998

| Only the data Vservers can own NFS Kerberos realms.

|===

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|error

|link:#error[error]

a|

|===

.Example error

[%collapsible%closed]

====

[source,json,subs=+macros]



```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====

```

```

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|code
|string
a|Argument code

```

```

|message
|string
a|Message argument

```

```

|===

```

```

[#error]
[.api-collapsible-fifth-title]
error

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[ID60c8f218cf96038baca583767ab859a3]]
= Retrieve a Kerberos realm

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/kerberos/realms/{svm.uuid}/{name}`#

*Introduced In:* 9.6

Retrieves a Kerberos realm.

* `vserver nfs kerberos realm show`

== Learn more

```

```
*
xref:{relative_path}protocols_nfs_kerberos_realms_endpoint_overview.html[DOC /protocols/nfs/kerberos/realms]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|SVM UUID
```

```
|name
```

```
|string
```

```
|path
```

```
|True
```

```
a|Kerberos realm
```

```
|fields
```

```
|array[string]
```

```
|query
```

```
|False
```

```
a|Specify the fields to return.
```

```
|===
```

== Response

Status: 200, Ok

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```

|Type
|Description

|_links
|link:#_links[_links]
a|

|ad_server
|link:#ad_server[ad_server]
a|

|comment
|string
a|Comment

|encryption_types
|array[string]
a|

|kdc
|link:#kdc[kdc]
a|

|name
|string
a|Kerberos realm

|svm
|link:#svm[svm]
a|

|===

.Example response
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "ad_server": {

```

```

    "address": "1.2.3.4"
  },
  "comment": "string",
  "encryption_types": {
  },
  "kdc": {
    "ip": "1.2.3.4",
    "port": "88",
    "vendor": "microsoft"
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {

```

```

    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====

```

```

[#href]
[.api-collapsible-fifth-title]
href

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|href
|string
a|

```

```

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|self

```

```

|link:#href[href]
a|

|===

[#ad_server]
[.api-collapsible-fifth-title]
ad_server

[cols=3*,options=header]
|===
|Name
|Type
|Description

|address
|string
a|Active Directory server IP address

|name
|string
a|Active Directory server name

|===

[#kdc]
[.api-collapsible-fifth-title]
kdc

[cols=3*,options=header]
|===
|Name
|Type
|Description

|ip
|string
a|KDC IP address

|port
|integer
a|KDC port

```

```
|vendor
|string
a|Key Distribution Center (KDC) vendor. Following values are supported:
```

- \* microsoft - Microsoft Active Directory KDC
- \* other - MIT Kerberos KDC or other KDC

```
|===
```

```
[#svm]
[.api-collapsible-fifth-title]
svm
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|name
|string
a|The name of the SVM.
```

```
|uuid
|string
a|The unique identifier of the SVM.
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```



```
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```

//end collapsible .Definitions block
====

[[IDabc7a80f0fa77302bd0d7b7f9469fc0a]]
= Update Kerberos realm properties

[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/nfs/kerberos/realms/{svm.uuid}/{name}`#

*Introduced In:* 9.6

Updates the properties of a Kerberos realm.

* `vserver nfs kerberos realm modify`

== Learn more

*
xref:{relative_path}protocols_nfs_kerberos_realms_endpoint_overview.html[D
OC /protocols/nfs/kerberos/realms]

== Parameters

[cols=5*,options=header]
|===
|Name
|Type
|In
|Required
|Description

|svm.uuid
|string
|path
|True
a|SVM UUID

|name
|string
|path

```

```

|True
a|Kerberos realm

|===

== Request Body

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|ad_server
|link:#ad_server[ad_server]
a|

|comment
|string
a|Comment

|encryption_types
|array[string]
a|

|kdc
|link:#kdc[kdc]
a|

|name
|string
a|Kerberos realm

|svm
|link:#svm[svm]
a|

|===

```

```
.Example request
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "ad_server": {
    "address": "1.2.3.4"
  },
  "comment": "string",
  "encryption_types": {
  },
  "kdc": {
    "ip": "1.2.3.4",
    "port": "88",
    "vendor": "microsoft"
  },
  "svm": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
  }
}
====
```

== Response

Status: 200, Ok

```
== Error
```

Status: Default

```
ONTAP Error Response codes
```

```
|===
```

Error codes	Description
1966125	Failed to remove hosts entry.
1966126	Failed to lookup hosts entry.
1966131	Failed to create hosts entry.
1966132	Failed to modify hosts entry.
2949121	Active Directory server name required.
2949122	Active Directory server address required
2949123	Failed to create Kerberos realm.
2949124	Failed to create hosts file entry.
2949141	Failed to lookup Kerberos realm.
2949148	Failed to modify Kerberos realm.
3276976	"realm" is a required input
3276998	Only the data Vservers can own NFS Kerberos realms.

|===

[cols=3\*,options=header]

|===

|Name

|Type

|Description

```

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#ad_server]
[.api-collapsible-fifth-title]
ad_server

[cols=3*,options=header]
|===
|Name
|Type
|Description

|address
|string
a|Active Directory server IP address

|name
|string
a|Active Directory server name

|===

[#kdc]
[.api-collapsible-fifth-title]
kdc

[cols=3*,options=header]
|===

```

```

|Name
|Type
|Description

|ip
|string
a|KDC IP address

|port
|integer
a|KDC port

|vendor
|string
a|Key Distribution Center (KDC) vendor. Following values are supported:

* microsoft - Microsoft Active Directory KDC
* other - MIT Kerberos KDC or other KDC

|===

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

```



```
|===  
  
[#kerberos_realm]  
[.api-collapsible-fifth-title]  
kerberos_realm  
  
[cols=3*,options=header]  
|===  
|Name  
|Type  
|Description  
  
|_links  
|link:#_links[_links]  
a|  
  
|ad_server  
|link:#ad_server[ad_server]  
a|  
  
|comment  
|string  
a|Comment  
  
|encryption_types  
|array[string]  
a|  
  
|kdc  
|link:#kdc[kdc]  
a|  
  
|name  
|string  
a|Kerberos realm  
  
|svm  
|link:#svm[svm]  
a|  
  
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|code
```

```
|string
```

```
a|Argument code
```

```
|message
```

```
|string
```

```
a|Message argument
```

```
|===
```

```
[#error]
```

```
[.api-collapsible-fifth-title]
```

```
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|arguments
```

```
|array[link:#error_arguments[error_arguments]]
```

```
a|Message arguments
```

```
|code
```

```
|string
```

```
a|Error code
```

```
|message
```

```
|string
```

```
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
:leveloffset: -1
```

```
= Manage NFS services
```

```
:leveloffset: +1
```

```
[[ID644e592b298f8e43332ecc1ca26d8a30]]
= Protocols NFS services endpoint overview
```

```
=== Retrieving an NFS configuration
```

```
----
```

```
# The API:
```

```
GET /api/protocols/nfs/services
```

```
# The call:
```

```
curl -X GET "https://<mgmt-ip>/api/protocols/nfs/services"
```

```
----
```

```
=== Creating an NFS configuration for an SVM
```

```
----
```

```
# The API:
```

```
POST /api/protocols/nfs/services
```

```
# The call:
```

```

curl -d "@test_nfs_post.txt" -X POST "https://<mgmt-
ip>/api/protocols/nfs/services"
test_nfs_post.txt (body):
{
"svm": {
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"protocol": {
  "v4_id_domain": "nfs-nsr-w01.rtp.netapp.com"
},
"vstorage_enabled": "true"
}
----

=== Updating an NFS configuration for an SVM

----

# The API:
PATCH /api/protocols/nfs/services/{svm.uuid}

# The call:
curl -d "@test_nfs_patch.txt" -X PATCH "https://<mgmt-
ip>/api/protocols/nfs/services/4a415601-548c-11e8-a21d-0050568bcb9"
test_nfs_patch.txt (body):
{
"protocol": {
  "v4_id_domain": "nfs-nsr-w01.rtp.netapp.com"
},
"vstorage_enabled": "false"
}
----

=== Deleting an NFS configuration for an SVM

----

# The API:
DELETE /api/protocols/nfs/services/{svm.uuid}

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/nfs/services/4a415601-
548c-11e8-a21d-0050568bcb9"
----

== Performance monitoring

```

Performance of the SVM can be monitored by the ``metric.+++`` and ``statistics.+++`` properties. These show the performance of the SVM in terms of IOPS, latency and throughput. The ``metric.+++`` properties denote an average whereas ``statistics.+++`` properties denote a real-time monotonically increasing value aggregated across all nodes.

[[ID195c510963b714a7751670278ae6c370]]  
= Retrieve the NFS configuration for SVMs

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/nfs/services`#

\*Introduced In:\* 9.6

Retrieves the NFS configuration of SVMs.

== Expensive properties

There is an added cost to retrieving values for these properties. They are not included by default in GET results and must be explicitly requested using the ``fields`` query parameter. See [xref:{relative\\_path}getting\\_started\\_with\\_the\\_ontap\\_rest\\_api.html#Requesting\\_specific\\_fields\[Requesting specific fields\]](#) to learn more.

\* ``statistics.+++``  
\* ``metric.+++``

== Related ONTAP commands

\* ``vserver nfs show``  
\* ``vserver nfs status``

== Learn more

\* [xref:{relative\\_path}protocols\\_nfs\\_services\\_endpoint\\_overview.html\[DOC /protocols/nfs/services\]](#)

== Parameters

[cols=5\*,options=header]  
|===

```
|Name
|Type
|In
|Required
|Description

|enabled
|boolean
|query
|False
a|Filter by enabled

|transport.udp_enabled
|boolean
|query
|False
a|Filter by transport.udp_enabled

|transport.tcp_enabled
|boolean
|query
|False
a|Filter by transport.tcp_enabled

|extended_groups_limit
|integer
|query
|False
a|Filter by extended_groups_limit

* Introduced in: 9.8

|positive_cached_credential_ttl
|integer
|query
|False
a|Filter by positive_cached_credential_ttl

* Introduced in: 9.8

|metric.v3.throughput.write
|integer
```

```
|query
|False
a|Filter by metric.v3.throughput.write
```

\* Introduced in: 9.7

```
|metric.v3.throughput.read
|integer
|query
|False
a|Filter by metric.v3.throughput.read
```

\* Introduced in: 9.7

```
|metric.v3.throughput.total
|integer
|query
|False
a|Filter by metric.v3.throughput.total
```

\* Introduced in: 9.7

```
|metric.v3.duration
|string
|query
|False
a|Filter by metric.v3.duration
```

\* Introduced in: 9.7

```
|metric.v3.timestamp
|string
|query
|False
a|Filter by metric.v3.timestamp
```

\* Introduced in: 9.7

```
|metric.v3.status
|string
|query
|False
```

```
a|Filter by metric.v3.status

* Introduced in: 9.7

|metric.v3.iops.total
|integer
|query
|False
a|Filter by metric.v3.iops.total

* Introduced in: 9.7

|metric.v3.iops.read
|integer
|query
|False
a|Filter by metric.v3.iops.read

* Introduced in: 9.7

|metric.v3.iops.other
|integer
|query
|False
a|Filter by metric.v3.iops.other

* Introduced in: 9.7

|metric.v3.iops.write
|integer
|query
|False
a|Filter by metric.v3.iops.write

* Introduced in: 9.7

|metric.v3.latency.total
|integer
|query
|False
a|Filter by metric.v3.latency.total
```



\* Introduced in: 9.7

```
|metric.v3.latency.read  
|integer  
|query  
|False  
a|Filter by metric.v3.latency.read
```

\* Introduced in: 9.7

```
|metric.v3.latency.other  
|integer  
|query  
|False  
a|Filter by metric.v3.latency.other
```

\* Introduced in: 9.7

```
|metric.v3.latency.write  
|integer  
|query  
|False  
a|Filter by metric.v3.latency.write
```

\* Introduced in: 9.7

```
|metric.v41.throughput.write  
|integer  
|query  
|False  
a|Filter by metric.v41.throughput.write
```

\* Introduced in: 9.8

```
|metric.v41.throughput.read  
|integer  
|query  
|False  
a|Filter by metric.v41.throughput.read
```

\* Introduced in: 9.8

```
|metric.v41.throughput.total
|integer
|query
|False
a|Filter by metric.v41.throughput.total
```

\* Introduced in: 9.8

```
|metric.v41.duration
|string
|query
|False
a|Filter by metric.v41.duration
```

\* Introduced in: 9.8

```
|metric.v41.timestamp
|string
|query
|False
a|Filter by metric.v41.timestamp
```

\* Introduced in: 9.8

```
|metric.v41.status
|string
|query
|False
a|Filter by metric.v41.status
```

\* Introduced in: 9.8

```
|metric.v41.iops.total
|integer
|query
|False
a|Filter by metric.v41.iops.total
```

\* Introduced in: 9.8

```
|metric.v41.iops.read
```

```
|integer
|query
|False
a|Filter by metric.v41.iops.read
```

\* Introduced in: 9.8

```
|metric.v41.iops.other
|integer
|query
|False
a|Filter by metric.v41.iops.other
```

\* Introduced in: 9.8

```
|metric.v41.iops.write
|integer
|query
|False
a|Filter by metric.v41.iops.write
```

\* Introduced in: 9.8

```
|metric.v41.latency.total
|integer
|query
|False
a|Filter by metric.v41.latency.total
```

\* Introduced in: 9.8

```
|metric.v41.latency.read
|integer
|query
|False
a|Filter by metric.v41.latency.read
```

\* Introduced in: 9.8

```
|metric.v41.latency.other
|integer
|query
```

```
|False
a|Filter by metric.v41.latency.other

* Introduced in: 9.8

|metric.v41.latency.write
|integer
|query
|False
a|Filter by metric.v41.latency.write

* Introduced in: 9.8

|metric.v4.throughput.write
|integer
|query
|False
a|Filter by metric.v4.throughput.write

* Introduced in: 9.8

|metric.v4.throughput.read
|integer
|query
|False
a|Filter by metric.v4.throughput.read

* Introduced in: 9.8

|metric.v4.throughput.total
|integer
|query
|False
a|Filter by metric.v4.throughput.total

* Introduced in: 9.8

|metric.v4.duration
|string
|query
|False
a|Filter by metric.v4.duration
```

\* Introduced in: 9.8

```
|metric.v4.timestamp  
|string  
|query  
|False  
a|Filter by metric.v4.timestamp
```

\* Introduced in: 9.8

```
|metric.v4.status  
|string  
|query  
|False  
a|Filter by metric.v4.status
```

\* Introduced in: 9.8

```
|metric.v4.iops.total  
|integer  
|query  
|False  
a|Filter by metric.v4.iops.total
```

\* Introduced in: 9.8

```
|metric.v4.iops.read  
|integer  
|query  
|False  
a|Filter by metric.v4.iops.read
```

\* Introduced in: 9.8

```
|metric.v4.iops.other  
|integer  
|query  
|False  
a|Filter by metric.v4.iops.other
```

\* Introduced in: 9.8

```
|metric.v4.iops.write
|integer
|query
|False
a|Filter by metric.v4.iops.write
```

\* Introduced in: 9.8

```
|metric.v4.latency.total
|integer
|query
|False
a|Filter by metric.v4.latency.total
```

\* Introduced in: 9.8

```
|metric.v4.latency.read
|integer
|query
|False
a|Filter by metric.v4.latency.read
```

\* Introduced in: 9.8

```
|metric.v4.latency.other
|integer
|query
|False
a|Filter by metric.v4.latency.other
```

\* Introduced in: 9.8

```
|metric.v4.latency.write
|integer
|query
|False
a|Filter by metric.v4.latency.write
```

\* Introduced in: 9.8

```
|protocol.v41_enabled  
|boolean  
|query  
|False  
a|Filter by protocol.v41_enabled
```

```
|protocol.v3_enabled  
|boolean  
|query  
|False  
a|Filter by protocol.v3_enabled
```

```
|protocol.v41_features.pnfs_enabled  
|boolean  
|query  
|False  
a|Filter by protocol.v41_features.pnfs_enabled
```

```
|protocol.v41_features.write_delegation_enabled  
|boolean  
|query  
|False  
a|Filter by protocol.v41_features.write_delegation_enabled
```

```
|protocol.v41_features.acl_enabled  
|boolean  
|query  
|False  
a|Filter by protocol.v41_features.acl_enabled
```

```
|protocol.v41_features.read_delegation_enabled  
|boolean  
|query  
|False  
a|Filter by protocol.v41_features.read_delegation_enabled
```

```
|protocol.v40_features.read_delegation_enabled  
|boolean  
|query  
|False  
a|Filter by protocol.v40_features.read_delegation_enabled
```

```
|protocol.v40_features.write_delegation_enabled
|boolean
|query
|False
a|Filter by protocol.v40_features.write_delegation_enabled
```

```
|protocol.v40_features.acl_enabled
|boolean
|query
|False
a|Filter by protocol.v40_features.acl_enabled
```

```
|protocol.v4_64bit_identifiers_enabled
|boolean
|query
|False
a|Filter by protocol.v4_64bit_identifiers_enabled
```

\* Introduced in: 9.8

```
|protocol.v3_64bit_identifiers_enabled
|boolean
|query
|False
a|Filter by protocol.v3_64bit_identifiers_enabled
```

\* Introduced in: 9.8

```
|protocol.v40_enabled
|boolean
|query
|False
a|Filter by protocol.v40_enabled
```

```
|protocol.v4_id_domain
|string
|query
|False
a|Filter by protocol.v4_id_domain
```



```
|statistics.v41.latency_raw.total
|integer
|query
|False
a|Filter by statistics.v41.latency_raw.total
```

\* Introduced in: 9.8

```
|statistics.v41.latency_raw.read
|integer
|query
|False
a|Filter by statistics.v41.latency_raw.read
```

\* Introduced in: 9.8

```
|statistics.v41.latency_raw.other
|integer
|query
|False
a|Filter by statistics.v41.latency_raw.other
```

\* Introduced in: 9.8

```
|statistics.v41.latency_raw.write
|integer
|query
|False
a|Filter by statistics.v41.latency_raw.write
```

\* Introduced in: 9.8

```
|statistics.v41.timestamp
|string
|query
|False
a|Filter by statistics.v41.timestamp
```

\* Introduced in: 9.8

```
|statistics.v41.iops_raw.total
```

```
|integer
|query
|False
a|Filter by statistics.v41.iops_raw.total
```

\* Introduced in: 9.8

```
|statistics.v41.iops_raw.read
|integer
|query
|False
a|Filter by statistics.v41.iops_raw.read
```

\* Introduced in: 9.8

```
|statistics.v41.iops_raw.other
|integer
|query
|False
a|Filter by statistics.v41.iops_raw.other
```

\* Introduced in: 9.8

```
|statistics.v41.iops_raw.write
|integer
|query
|False
a|Filter by statistics.v41.iops_raw.write
```

\* Introduced in: 9.8

```
|statistics.v41.throughput_raw.write
|integer
|query
|False
a|Filter by statistics.v41.throughput_raw.write
```

\* Introduced in: 9.8

```
|statistics.v41.throughput_raw.read
|integer
|query
```

```
|False
a|Filter by statistics.v41.throughput_raw.read

* Introduced in: 9.8

|statistics.v41.throughput_raw.total
|integer
|query
|False
a|Filter by statistics.v41.throughput_raw.total

* Introduced in: 9.8

|statistics.v41.status
|string
|query
|False
a|Filter by statistics.v41.status

* Introduced in: 9.8

|statistics.v3.latency_raw.total
|integer
|query
|False
a|Filter by statistics.v3.latency_raw.total

* Introduced in: 9.7

|statistics.v3.latency_raw.read
|integer
|query
|False
a|Filter by statistics.v3.latency_raw.read

* Introduced in: 9.7

|statistics.v3.latency_raw.other
|integer
|query
|False
a|Filter by statistics.v3.latency_raw.other
```

\* Introduced in: 9.7

```
|statistics.v3.latency_raw.write  
|integer  
|query  
|False  
a|Filter by statistics.v3.latency_raw.write
```

\* Introduced in: 9.7

```
|statistics.v3.timestamp  
|string  
|query  
|False  
a|Filter by statistics.v3.timestamp
```

\* Introduced in: 9.7

```
|statistics.v3.iops_raw.total  
|integer  
|query  
|False  
a|Filter by statistics.v3.iops_raw.total
```

\* Introduced in: 9.7

```
|statistics.v3.iops_raw.read  
|integer  
|query  
|False  
a|Filter by statistics.v3.iops_raw.read
```

\* Introduced in: 9.7

```
|statistics.v3.iops_raw.other  
|integer  
|query  
|False  
a|Filter by statistics.v3.iops_raw.other
```

\* Introduced in: 9.7

```
|statistics.v3.iops_raw.write
|integer
|query
|False
a|Filter by statistics.v3.iops_raw.write

* Introduced in: 9.7

|statistics.v3.throughput_raw.write
|integer
|query
|False
a|Filter by statistics.v3.throughput_raw.write

* Introduced in: 9.7

|statistics.v3.throughput_raw.read
|integer
|query
|False
a|Filter by statistics.v3.throughput_raw.read

* Introduced in: 9.7

|statistics.v3.throughput_raw.total
|integer
|query
|False
a|Filter by statistics.v3.throughput_raw.total

* Introduced in: 9.7

|statistics.v3.status
|string
|query
|False
a|Filter by statistics.v3.status

* Introduced in: 9.7
```

```
|statistics.v4.latency_raw.total
|integer
|query
|False
a|Filter by statistics.v4.latency_raw.total
```

\* Introduced in: 9.8

```
|statistics.v4.latency_raw.read
|integer
|query
|False
a|Filter by statistics.v4.latency_raw.read
```

\* Introduced in: 9.8

```
|statistics.v4.latency_raw.other
|integer
|query
|False
a|Filter by statistics.v4.latency_raw.other
```

\* Introduced in: 9.8

```
|statistics.v4.latency_raw.write
|integer
|query
|False
a|Filter by statistics.v4.latency_raw.write
```

\* Introduced in: 9.8

```
|statistics.v4.timestamp
|string
|query
|False
a|Filter by statistics.v4.timestamp
```

\* Introduced in: 9.8

```
|statistics.v4.iops_raw.total
|integer
```

```
|query
|False
a|Filter by statistics.v4.iops_raw.total

* Introduced in: 9.8

|statistics.v4.iops_raw.read
|integer
|query
|False
a|Filter by statistics.v4.iops_raw.read

* Introduced in: 9.8

|statistics.v4.iops_raw.other
|integer
|query
|False
a|Filter by statistics.v4.iops_raw.other

* Introduced in: 9.8

|statistics.v4.iops_raw.write
|integer
|query
|False
a|Filter by statistics.v4.iops_raw.write

* Introduced in: 9.8

|statistics.v4.throughput_raw.write
|integer
|query
|False
a|Filter by statistics.v4.throughput_raw.write

* Introduced in: 9.8

|statistics.v4.throughput_raw.read
|integer
|query
|False
```

a|Filter by statistics.v4.throughput\_raw.read

\* Introduced in: 9.8

|statistics.v4.throughput\_raw.total

|integer

|query

|False

a|Filter by statistics.v4.throughput\_raw.total

\* Introduced in: 9.8

|statistics.v4.status

|string

|query

|False

a|Filter by statistics.v4.status

\* Introduced in: 9.8

|state

|string

|query

|False

a|Filter by state

|auth\_sys\_extended\_groups\_enabled

|boolean

|query

|False

a|Filter by auth\_sys\_extended\_groups\_enabled

\* Introduced in: 9.8

|svm.uuid

|string

|query

|False

a|Filter by svm.uuid

|svm.name



```
|string  
|query  
|False  
a|Filter by svm.name
```

```
|rquota_enabled  
|boolean  
|query  
|False  
a|Filter by rquota_enabled
```

\* Introduced in: 9.8

```
|showmount_enabled  
|boolean  
|query  
|False  
a|Filter by showmount_enabled
```

\* Introduced in: 9.8

```
|vstorage_enabled  
|boolean  
|query  
|False  
a|Filter by vstorage_enabled
```

```
|fields  
|array[string]  
|query  
|False  
a|Specify the fields to return.
```

```
|max_records  
|integer  
|query  
|False  
a|Limit the number of records returned.
```

```
|return_timeout  
|integer
```

```
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds. ONTAP
returns earlier if either max records or the end of the collection is
reached.

* Default value: 1
* Max value: 120
* Min value: 0

|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.

* Default value: 1

|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
```

```
|integer
a|Number of NFS Server Records

|records
|array[link:#nfs_service[nfs_service]]
a|

|===
```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "extended_groups_limit": "32",
    "metric": {
      "v3": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "duration": "PT15S",
        "iops": {
          "read": "200",
          "total": "1000",
          "write": "100"
        },
        "latency": {
          "read": "200",
```

```

    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"v4": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"v41": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",

```

```
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
}
},
"positive_cached_credential_ttl": "7200000",
"state": "online",
"statistics": {
  "v3": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
  },
  "v4": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency_raw": {
      "read": "200",
```

```

        "total": "1000",
        "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
        "read": "200",
        "total": "1000",
        "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
},
"v41": {
    "iops_raw": {
        "read": "200",
        "total": "1000",
        "write": "100"
    },
    "latency_raw": {
        "read": "200",
        "total": "1000",
        "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
        "read": "200",
        "total": "1000",
        "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
}
},
"svm": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
}
====

== Error

```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
```

```

|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:href[href]
a|

|===

```



```
[#iops]
[.api-collapsible-fifth-title]
iops
```

The rate of I/O operations observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|other
```

```
|integer
```

a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.

```
|read
```

```
|integer
```

a|Performance metric for read I/O operations.

```
|total
```

```
|integer
```

a|Performance metric aggregated over all types of I/O operations.

```
|write
```

```
|integer
```

a|Performance metric for write I/O operations.

```
|===
```

```
[#latency]
```

```
[.api-collapsible-fifth-title]
```

```
latency
```

The round trip latency in microseconds observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```

|Name
|Type
|Description

|other
|integer
a|Performance metric for other I/O operations. Other I/O operations can be
metadata operations, such as directory lookups and so on.

|read
|integer
a|Performance metric for read I/O operations.

|total
|integer
a|Performance metric aggregated over all types of I/O operations.

|write
|integer
a|Performance metric for write I/O operations.

|===

[#throughput]
[.api-collapsible-fifth-title]
throughput

The rate of throughput bytes per second observed at the storage object.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|read
|integer
a|Performance metric for read I/O operations.

|total

```

```

|integer
a|Performance metric aggregated over all types of I/O operations.

|write
|integer
a|Peformance metric for write I/O operations.

|===

[#v3]
[.api-collapsible-fifth-title]
v3

The NFSv3 operations

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|duration
|string
a|The duration over which this sample is calculated. The time durations
are represented in the ISO-8601 standard format. Samples can be calculated
over the following durations:

|iops
|link:#iops[iops]
a|The rate of I/O operations observed at the storage object.

|latency
|link:#latency[latency]
a|The round trip latency in microseconds observed at the storage object.

|status

```

```
|string
a|Any errors associated with the sample. For example, if the aggregation
of data over multiple nodes fails then any of the partial errors might be
returned, "ok" on success, or "error" on any internal uncategorized
failure. Whenever a sample collection is missed but done at a later time,
it is back filled to the previous 15 second timestamp and tagged with
"backfilled_data". "Inconsistent_delta_time" is encountered when the time
between two collections is not the same for all nodes. Therefore, the
aggregated value might be over or under inflated. "Negative_delta" is
returned when an expected monotonically increasing value has decreased in
value. "Inconsistent_old_data" is returned when one or more nodes do not
have the latest data.
```

```
|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#v4]
[.api-collapsible-fifth-title]
v4
```

The NFSv4 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|duration
|string
a|The duration over which this sample is calculated. The time durations
```

are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:

|iops

|link:#iops[iops]

a|The rate of I/O operations observed at the storage object.

|latency

|link:#latency[latency]

a|The round trip latency in microseconds observed at the storage object.

|status

|string

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

|throughput

|link:#throughput[throughput]

a|The rate of throughput bytes per second observed at the storage object.

|timestamp

|string

a|The timestamp of the performance data.

|===

[#v41]

[.api-collapsible-fifth-title]

v41

The NFSv4.1 operations

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|duration
|string
a|The duration over which this sample is calculated. The time durations
are represented in the ISO-8601 standard format. Samples can be calculated
over the following durations:

|iops
|link:#iops[iops]
a|The rate of I/O operations observed at the storage object.

|latency
|link:#latency[latency]
a|The round trip latency in microseconds observed at the storage object.

|status
|string
a|Any errors associated with the sample. For example, if the aggregation
of data over multiple nodes fails then any of the partial errors might be
returned, "ok" on success, or "error" on any internal uncategorized
failure. Whenever a sample collection is missed but done at a later time,
it is back filled to the previous 15 second timestamp and tagged with
"backfilled_data". "Inconsistent_delta_time" is encountered when the time
between two collections is not the same for all nodes. Therefore, the
aggregated value might be over or under inflated. "Negative_delta" is
returned when an expected monotonically increasing value has decreased in
value. "Inconsistent_old_data" is returned when one or more nodes do not
have the latest data.

|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.

```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#metric]
[.api-collapsible-fifth-title]
metric
```

Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|v3
```

```
|link:#v3[v3]
a|The NFSv3 operations
```

```
|v4
```

```
|link:#v4[v4]
a|The NFSv4 operations
```

```
|v41
```

```
|link:#v41[v41]
a|The NFSv4.1 operations
```

```
|===
```

```
[#v40_features]
[.api-collapsible-fifth-title]
v40_features
```

```
[cols=3*,options=header]
```

```

|===
|Name
|Type
|Description

|acl_enabled
|boolean
a|Specifies whether NFSv4.0 ACLs is enabled.

|read_delegation_enabled
|boolean
a|Specifies whether NFSv4.0 Read Delegation is enabled.

|write_delegation_enabled
|boolean
a|Specifies whether NFSv4.0 Write Delegation is enabled.

|===

[#v41_features]
[.api-collapsible-fifth-title]
v41_features

[cols=3*,options=header]
|===
|Name
|Type
|Description

|acl_enabled
|boolean
a|Specifies whether NFSv4.1 or later ACLs is enabled.

|pnfs_enabled
|boolean
a|Specifies whether NFSv4.1 or later Parallel NFS is enabled.

|read_delegation_enabled
|boolean
a|Specifies whether NFSv4.1 or later Read Delegation is enabled.

```



```
|write_delegation_enabled
|boolean
a|Specifies whether NFSv4.1 or later Write Delegation is enabled.
```

```
|===
```

```
[#protocol]
[.api-collapsible-fifth-title]
protocol
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|v3_64bit_identifiers_enabled
|boolean
a|Specifies whether 64-bit support for NFSv3 FSIDs and file IDs is
enabled.
```

```
|v3_enabled
|boolean
a|Specifies whether NFSv3 protocol is enabled.
```

```
|v40_enabled
|boolean
a|Specifies whether NFSv4.0 protocol is enabled.
```

```
|v40_features
|link:#v40_features[v40_features]
a|
```

```
|v41_enabled
|boolean
a|Specifies whether NFSv4.1 or later protocol is enabled.
```

```
|v41_features
|link:#v41_features[v41_features]
a|
```

|v4\_64bit\_identifiers\_enabled  
|boolean  
a|Specifies whether 64-bit support for NFSv4.x FSIDs and file IDs is enabled.

|v4\_id\_domain  
|string  
a|Specifies the domain portion of the string form of user and group names as defined by the NFSv4 protocol.

|===

[#iops\_raw]  
[.api-collapsible-fifth-title]  
iops\_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

[cols=3\*,options=header]

|===

|Name  
|Type  
|Description

|other

|integer

a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.

|read

|integer

a|Performance metric for read I/O operations.

|total

|integer

a|Performance metric aggregated over all types of I/O operations.

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#latency_raw]
[.api-collapsible-fifth-title]
latency_raw
```

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|other
|integer
a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#throughput_raw]
[.api-collapsible-fifth-title]
throughput_raw
```

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|read
```

```
|integer
```

```
a|Performance metric for read I/O operations.
```

```
|total
```

```
|integer
```

```
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
```

```
|integer
```

```
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#v3]
```

```
[.api-collapsible-fifth-title]
```

```
v3
```

The NFSv3 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|iops_raw
```

|link:#iops\_raw[iops\_raw]

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

|latency\_raw

|link:#latency\_raw[latency\_raw]

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

|status

|string

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

|throughput\_raw

|link:#throughput\_raw[throughput\_raw]

a|Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

|timestamp

|string

a|The timestamp of the performance data.

|===

[#v4]

[.api-collapsible-fifth-title]

v4

## The NFSv4 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|iops_raw
```

```
|link:#iops_raw[iops_raw]
```

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

```
|latency_raw
```

```
|link:#latency_raw[latency_raw]
```

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

```
|status
```

```
|string
```

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

```
|throughput_raw
```

```
|link:#throughput_raw[throughput_raw]
```

a|Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

```
|timestamp
```

```
|string
```

a|The timestamp of the performance data.

|===

[#v41]

[.api-collapsible-fifth-title]

v41

The NFSv4.1 operations

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|iops\_raw

|link:#iops\_raw[iops\_raw]

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

|latency\_raw

|link:#latency\_raw[latency\_raw]

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

|status

|string

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

```
|throughput_raw
|link:#throughput_raw[throughput_raw]
a|Throughput bytes observed at the storage object. This should be used
along with delta time to calculate the rate of throughput bytes per unit
of time.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#statistics]
[.api-collapsible-fifth-title]
statistics
```

Realtime performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|v3
|link:#v3[v3]
a|The NFSv3 operations
```

```
|v4
|link:#v4[v4]
a|The NFSv4 operations
```

```
|v41
|link:#v41[v41]
a|The NFSv4.1 operations
```

```
|===
```



```

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

|===

[#transport]
[.api-collapsible-fifth-title]
transport

[cols=3*,options=header]
|===
|Name
|Type
|Description

|tcp_enabled
|boolean
a|Specifies whether TCP transports are enabled on the server.

|udp_enabled
|boolean
a|Specifies whether UDP transports are enabled on the server.

```

```
|===
```

```
[#nfs_service]
```

```
[.api-collapsible-fifth-title]
```

```
nfs_service
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|auth_sys_extended_groups_enabled
```

```
|boolean
```

```
a|Specifies whether or not extended groups support over AUTH_SYS is enabled.
```

```
|enabled
```

```
|boolean
```

```
a|Specifies if the NFS service is administratively enabled.
```

```
|extended_groups_limit
```

```
|integer
```

```
a|Specifies the maximum auxillary groups supported over AUTH_SYS and RPCSEC_GSS.
```

```
|metric
```

```
|link:#metric[metric]
```

```
a|Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.
```

```
|positive_cached_credential_ttl
```

```
|integer
```

```
a|Specifies the time to live value (in msec) of a positive cached credential
```

```
|protocol
|link:#protocol[protocol]
a|

|rquota_enabled
|boolean
a|Specifies whether or not the remote quota feature is enabled.

|showmount_enabled
|boolean
a|Specifies whether or not the showmount feature is enabled.

|state
|string
a|Specifies the state of the NFS service on the SVM. The following values
are supported:
    * online - NFS server is ready to accept client requests.
    * offline - NFS server is not ready to accept client requests.

|statistics
|link:#statistics[statistics]
a|Realtime performance numbers, such as IOPS latency and throughput, for
SVM-NFS protocol.

|svm
|link:#svm[svm]
a|

|transport
|link:#transport[transport]
a|

|vstorage_enabled
|boolean
a|Specifies whether or not the VMware vstorage feature is enabled.

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|code
```

```
|string
```

```
a|Argument code
```

```
|message
```

```
|string
```

```
a|Message argument
```

```
|===
```

```
[#error]
```

```
[.api-collapsible-fifth-title]
```

```
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|arguments
```

```
|array[link:#error_arguments[error_arguments]]
```

```
a|Message arguments
```

```
|code
```

```
|string
```

```
a|Error code
```

```
|message
```

```
|string
```

```
a|Error message
```

```
|target
```

```
|string
```

a|The target parameter that caused the error.

|===

//end collapsible .Definitions block

====

[[ID300aff25cef5f002584e8f8a08d19928]]  
= Create an NFS configuration for an SVM

[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-block]#`/protocols/nfs/services`#

\*Introduced In:\* 9.6

Creates an NFS configuration for an SVM.

== Required properties

\* `svm.uuid` or `svm.name` - Existing SVM for which to create the NFS configuration.

== Default property values

If not specified in POST, the following default property values are assigned:

\* `enabled` - `_true_`  
\* `state` - `online`  
\* `transport.udp\_enabled` - `_true_`  
\* `transport.tcp\_enabled` - `_true_`  
\* `protocol.v3\_enabled` - `_true_`  
\* `protocol.v3\_64bit\_identifiers\_enabled` - `_false_`  
\* `protocol.v4\_id\_domain` - `defaultv4iddomain.com`  
\* `protocol.v4\_64bit\_identifiers\_enabled` - `_true_`  
\* `protocol.v4\_enabled` - `_false_`  
\* `protocol.v41\_enabled` - `_false_`  
\* `protocol.v40\_features.acl\_enabled` - `_false_`  
\* `protocol.v40\_features.read\_delegation\_enabled` - `_false_`  
\* `protocol.v40\_features.write\_delegation\_enabled` - `_false_`  
\* `protocol.v41\_features.acl\_enabled` - `_false_`  
\* `protocol.v41\_features.read\_delegation\_enabled` - `_false_`  
\* `protocol.v41\_features.write\_delegation\_enabled` - `_false_`

```
* `protocol.v41_features.pnfs_enabled` - _false_
* `vstorage_enabled` - _false_
* `rquota_enabled` - _false_
* `showmount_enabled` - _true_
* `auth_sys_extended_groups_enabled` - _false_
* `extended_groups_limit` - _32_
* `positive_cached_credential_ttl` - _7200000_
```

== Related ONTAP commands

```
* `vserver nfs create`
```

== Learn more

```
* xref:{relative_path}protocols_nfs_services_endpoint_overview.html[DOC
/protocols/nfs/services]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|return_records
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|The default is false. If set to true, the records are returned.
```

```
* Default value:
```

```
|===
```

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

|Description

|\_links

|link:#\_links[\_links]

a|

|auth\_sys\_extended\_groups\_enabled

|boolean

a|Specifies whether or not extended groups support over AUTH\_SYS is enabled.

|enabled

|boolean

a|Specifies if the NFS service is administratively enabled.

|extended\_groups\_limit

|integer

a|Specifies the maximum auxillary groups supported over AUTH\_SYS and RPCSEC\_GSS.

|metric

|link:#metric[metric]

a|Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

|positive\_cached\_credential\_ttl

|integer

a|Specifies the time to live value (in msec) of a positive cached credential

|protocol

|link:#protocol[protocol]

a|

|quota\_enabled

|boolean

a|Specifies whether or not the remote quota feature is enabled.

|showmount\_enabled

|boolean

a|Specifies whether or not the showmount feature is enabled.

```
|state
|string
a|Specifies the state of the NFS service on the SVM. The following values
are supported:
    * online - NFS server is ready to accept client requests.
    * offline - NFS server is not ready to accept client requests.
```

```
|statistics
|link:#statistics[statistics]
a|Realtime performance numbers, such as IOPS latency and throughput, for
SVM-NFS protocol.
```

```
|svm
|link:#svm[svm]
a|
```

```
|transport
|link:#transport[transport]
a|
```

```
|vstorage_enabled
|boolean
a|Specifies whether or not the VMware vstorage feature is enabled.
```

```
|===
```

```
.Example request
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "extended_groups_limit": "32",
  "metric": {
    "v3": {
      "_links": {
        "self": {
```



```
    "href": "/api/resourcelink"
  }
},
"duration": "PT15S",
"iops": {
  "read": "200",
  "total": "1000",
  "write": "100"
},
"latency": {
  "read": "200",
  "total": "1000",
  "write": "100"
},
"status": "ok",
"throughput": {
  "read": "200",
  "total": "1000",
  "write": "100"
},
"timestamp": "2017-01-25T11:20:13Z"
},
"v4": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
```

```

},
"v41": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
}
},
"positive_cached_credential_ttl": "7200000",
"state": "online",
"statistics": {
  "v3": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    }
  }
}

```

```

    },
    "timestamp": "2017-01-25T11:20:13Z"
  },
  "v4": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
  },
  "v41": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
  }
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  }
}

```

```

    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
====

== Response

```

Status: 201, Created

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of NFS Server Records

|records
|array[link:#nfs_service[nfs_service]]
a|

|===

.Example response
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  }
}

```

```

},
"records": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
},
"extended_groups_limit": "32",
"metric": {
  "v3": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    },
    "duration": "PT15S",
    "iops": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    },
    "status": "ok",
    "throughput": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    },
    "timestamp": "2017-01-25T11:20:13Z"
  },
  "v4": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  },

```

```
"latency": {
  "read": "200",
  "total": "1000",
  "write": "100"
},
"status": "ok",
"throughput": {
  "read": "200",
  "total": "1000",
  "write": "100"
},
"timestamp": "2017-01-25T11:20:13Z"
},
"v41": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
}
},
"positive_cached_credential_ttl": "7200000",
"state": "online",
"statistics": {
  "v3": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
```

```
    "write": "100"
  },
  "latency_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"v4": {
  "iops_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"v41": {
  "iops_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
```

```

    "throughput_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
  }
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
}
====

== Error

```

## Status: Default

### ONTAP Error Response Codes

```

|====
| Error Code | Description
|
| 3276916
| Vserver is not running
|
| 3276994
| Kerberos must be disabled on all LIFs on Vserver before adding or
removing AES encryption. Disable Kerberos on the LIF and try again
|
| 3277038
| Cannot enable \"showmount\" feature because it requires an effective
cluster version of Data ONTAP 8.3.0 or later
|
| 3277049
| Cannot enable \"showmount\" feature on ID-Discard Vserver. Ensure that
the Vserver is initialized and retry the command
|
| 3277052

```



```
| NFSv4.x access to transitioned volumes in this Vserver could trigger
conversion of non-Unicode directories to Unicode, which might impact data-
serving performance. Before enabling NFSv4.x for this Vserver, refer to
the Data and Configuration Transition Guide
```

```
| 3277069
```

```
| Cannot disable TCP because the SnapDiff RPC server is in the \"on\"
state
```

```
| 3277089
```

```
| Attempting to create an NFS server using 64-bits for NFSv3 FSIDs and
File IDs on Vserver. Older client software might not work with 64-bit
identifiers
```

```
| 3277099
```

```
| Domain name contains invalid characters or it is too short. Allowed
characters are: alphabetical characters (A-Za-z), numeric characters (0-
9), minus sign (-), and the period (.). The first character must be
alphabetical or numeric, last character must not be a minus sign or a
period. Minimum supported length: 2 characters, maximum of 256 characters
```

```
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
```

```
  "error": {
```

```
    "arguments": {
```

```
      "code": "string",
```

```
      "message": "string"
```

```
    },
```

```
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

====

== Definitions

```
[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
```

====

```
[#href]
[.api-collapsible-fifth-title]
href
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|href
|string
a|
```

```
|===
```

```
[#_links]
[.api-collapsible-fifth-title]
_links
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|self
|link:#href[href]
a|
```

```
|===
```

```
[#iops]
[.api-collapsible-fifth-title]
iops
```

The rate of I/O operations observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|other
```

```
|integer
```

a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.

```
|read
```

```
|integer
```

a|Performance metric for read I/O operations.

```
|total
```

```
|integer
```

a|Performance metric aggregated over all types of I/O operations.

```
|write
```

```
|integer
```

a|Performance metric for write I/O operations.

```
|===
```

```
[#latency]
```

```
[.api-collapsible-fifth-title]
```

```
latency
```

The round trip latency in microseconds observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```

|Name
|Type
|Description

|other
|integer
a|Performance metric for other I/O operations. Other I/O operations can be
metadata operations, such as directory lookups and so on.

|read
|integer
a|Performance metric for read I/O operations.

|total
|integer
a|Performance metric aggregated over all types of I/O operations.

|write
|integer
a|Performance metric for write I/O operations.

|===

[#throughput]
[.api-collapsible-fifth-title]
throughput

The rate of throughput bytes per second observed at the storage object.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|read
|integer
a|Performance metric for read I/O operations.

|total

```

```

|integer
a|Performance metric aggregated over all types of I/O operations.

|write
|integer
a|Performance metric for write I/O operations.

|===

[#v3]
[.api-collapsible-fifth-title]
v3

The NFSv3 operations

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|duration
|string
a|The duration over which this sample is calculated. The time durations
are represented in the ISO-8601 standard format. Samples can be calculated
over the following durations:

|iops
|link:#iops[iops]
a|The rate of I/O operations observed at the storage object.

|latency
|link:#latency[latency]
a|The round trip latency in microseconds observed at the storage object.

|status

```

```
|string
a|Any errors associated with the sample. For example, if the aggregation
of data over multiple nodes fails then any of the partial errors might be
returned, "ok" on success, or "error" on any internal uncategorized
failure. Whenever a sample collection is missed but done at a later time,
it is back filled to the previous 15 second timestamp and tagged with
"backfilled_data". "Inconsistent_delta_time" is encountered when the time
between two collections is not the same for all nodes. Therefore, the
aggregated value might be over or under inflated. "Negative_delta" is
returned when an expected monotonically increasing value has decreased in
value. "Inconsistent_old_data" is returned when one or more nodes do not
have the latest data.
```

```
|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#v4]
[.api-collapsible-fifth-title]
v4
```

The NFSv4 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|duration
|string
a|The duration over which this sample is calculated. The time durations
```

are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:

|iops

|link:#iops[iops]

a|The rate of I/O operations observed at the storage object.

|latency

|link:#latency[latency]

a|The round trip latency in microseconds observed at the storage object.

|status

|string

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

|throughput

|link:#throughput[throughput]

a|The rate of throughput bytes per second observed at the storage object.

|timestamp

|string

a|The timestamp of the performance data.

|===

[#v41]

[.api-collapsible-fifth-title]

v41

The NFSv4.1 operations

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|duration
|string
a|The duration over which this sample is calculated. The time durations
are represented in the ISO-8601 standard format. Samples can be calculated
over the following durations:

|iops
|link:#iops[iops]
a|The rate of I/O operations observed at the storage object.

|latency
|link:#latency[latency]
a|The round trip latency in microseconds observed at the storage object.

|status
|string
a|Any errors associated with the sample. For example, if the aggregation
of data over multiple nodes fails then any of the partial errors might be
returned, "ok" on success, or "error" on any internal uncategorized
failure. Whenever a sample collection is missed but done at a later time,
it is back filled to the previous 15 second timestamp and tagged with
"backfilled_data". "Inconsistent_delta_time" is encountered when the time
between two collections is not the same for all nodes. Therefore, the
aggregated value might be over or under inflated. "Negative_delta" is
returned when an expected monotonically increasing value has decreased in
value. "Inconsistent_old_data" is returned when one or more nodes do not
have the latest data.

|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.

```



```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#metric]
[.api-collapsible-fifth-title]
metric
```

Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|v3
```

```
|link:#v3[v3]
```

```
a|The NFSv3 operations
```

```
|v4
```

```
|link:#v4[v4]
```

```
a|The NFSv4 operations
```

```
|v41
```

```
|link:#v41[v41]
```

```
a|The NFSv4.1 operations
```

```
|===
```

```
[#v40_features]
[.api-collapsible-fifth-title]
v40_features
```

```
[cols=3*,options=header]
```

```

|===
|Name
|Type
|Description

|acl_enabled
|boolean
a|Specifies whether NFSv4.0 ACLs is enabled.

|read_delegation_enabled
|boolean
a|Specifies whether NFSv4.0 Read Delegation is enabled.

|write_delegation_enabled
|boolean
a|Specifies whether NFSv4.0 Write Delegation is enabled.

|===

[#v41_features]
[.api-collapsible-fifth-title]
v41_features

[cols=3*,options=header]
|===
|Name
|Type
|Description

|acl_enabled
|boolean
a|Specifies whether NFSv4.1 or later ACLs is enabled.

|pnfs_enabled
|boolean
a|Specifies whether NFSv4.1 or later Parallel NFS is enabled.

|read_delegation_enabled
|boolean
a|Specifies whether NFSv4.1 or later Read Delegation is enabled.

```

```
|write_delegation_enabled
|boolean
a|Specifies whether NFSv4.1 or later Write Delegation is enabled.
```

```
|===
```

```
[#protocol]
[.api-collapsible-fifth-title]
protocol
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|v3_64bit_identifiers_enabled
|boolean
a|Specifies whether 64-bit support for NFSv3 FSIDs and file IDs is
enabled.
```

```
|v3_enabled
|boolean
a|Specifies whether NFSv3 protocol is enabled.
```

```
|v40_enabled
|boolean
a|Specifies whether NFSv4.0 protocol is enabled.
```

```
|v40_features
|link:#v40_features[v40_features]
a|
```

```
|v41_enabled
|boolean
a|Specifies whether NFSv4.1 or later protocol is enabled.
```

```
|v41_features
|link:#v41_features[v41_features]
a|
```

|v4\_64bit\_identifiers\_enabled  
|boolean  
a|Specifies whether 64-bit support for NFSv4.x FSIDs and file IDs is enabled.

|v4\_id\_domain  
|string  
a|Specifies the domain portion of the string form of user and group names as defined by the NFSv4 protocol.

|===

[#iops\_raw]  
[.api-collapsible-fifth-title]  
iops\_raw

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

[cols=3\*,options=header]

|===

|Name  
|Type  
|Description

|other

|integer

a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.

|read

|integer

a|Performance metric for read I/O operations.

|total

|integer

a|Performance metric aggregated over all types of I/O operations.

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#latency_raw]
[.api-collapsible-fifth-title]
latency_raw
```

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|other
|integer
a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#throughput_raw]
[.api-collapsible-fifth-title]
throughput_raw
```

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#v3]
[.api-collapsible-fifth-title]
v3
```

The NFSv3 operations

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|iops_raw
```

|link:#iops\_raw[iops\_raw]

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

|latency\_raw

|link:#latency\_raw[latency\_raw]

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

|status

|string

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

|throughput\_raw

|link:#throughput\_raw[throughput\_raw]

a|Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

|timestamp

|string

a|The timestamp of the performance data.

|===

[#v4]

[.api-collapsible-fifth-title]

v4

## The NFSv4 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|iops_raw
```

```
|link:#iops_raw[iops_raw]
```

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

```
|latency_raw
```

```
|link:#latency_raw[latency_raw]
```

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

```
|status
```

```
|string
```

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

```
|throughput_raw
```

```
|link:#throughput_raw[throughput_raw]
```

a|Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

```
|timestamp
```

```
|string
```



a|The timestamp of the performance data.

|===

[#v41]

[.api-collapsible-fifth-title]

v41

The NFSv4.1 operations

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|iops\_raw

|link:#iops\_raw[iops\_raw]

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

|latency\_raw

|link:#latency\_raw[latency\_raw]

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

|status

|string

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

```
|throughput_raw
|link:#throughput_raw[throughput_raw]
a|Throughput bytes observed at the storage object. This should be used
along with delta time to calculate the rate of throughput bytes per unit
of time.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#statistics]
[.api-collapsible-fifth-title]
statistics
```

Realtime performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|v3
|link:#v3[v3]
a|The NFSv3 operations
```

```
|v4
|link:#v4[v4]
a|The NFSv4 operations
```

```
|v41
|link:#v41[v41]
a|The NFSv4.1 operations
```

```
|===
```

```

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

|===

```

```

[#transport]
[.api-collapsible-fifth-title]
transport

[cols=3*,options=header]
|===
|Name
|Type
|Description

|tcp_enabled
|boolean
a|Specifies whether TCP transports are enabled on the server.

|udp_enabled
|boolean
a|Specifies whether UDP transports are enabled on the server.

```

```
|===
```

```
[#nfs_service]
```

```
[.api-collapsible-fifth-title]
```

```
nfs_service
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|auth_sys_extended_groups_enabled
```

```
|boolean
```

```
a|Specifies whether or not extended groups support over AUTH_SYS is enabled.
```

```
|enabled
```

```
|boolean
```

```
a|Specifies if the NFS service is administratively enabled.
```

```
|extended_groups_limit
```

```
|integer
```

```
a|Specifies the maximum auxillary groups supported over AUTH_SYS and RPCSEC_GSS.
```

```
|metric
```

```
|link:#metric[metric]
```

```
a|Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.
```

```
|positive_cached_credential_ttl
```

```
|integer
```

```
a|Specifies the time to live value (in msec) of a positive cached credential
```

```
|protocol
|link:#protocol[protocol]
a|

|rquota_enabled
|boolean
a|Specifies whether or not the remote quota feature is enabled.

|showmount_enabled
|boolean
a|Specifies whether or not the showmount feature is enabled.

|state
|string
a|Specifies the state of the NFS service on the SVM. The following values
are supported:
    * online - NFS server is ready to accept client requests.
    * offline - NFS server is not ready to accept client requests.

|statistics
|link:#statistics[statistics]
a|Realtime performance numbers, such as IOPS latency and throughput, for
SVM-NFS protocol.

|svm
|link:#svm[svm]
a|

|transport
|link:#transport[transport]
a|

|vstorage_enabled
|boolean
a|Specifies whether or not the VMware vstorage feature is enabled.

|===

[#_links]
[.api-collapsible-fifth-title]
_links
```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

[#nfs_service]
[.api-collapsible-fifth-title]
nfs_service

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|auth_sys_extended_groups_enabled
|boolean
a|Specifies whether or not extended groups support over AUTH_SYS is
enabled.

|enabled
|boolean
a|Specifies if the NFS service is administratively enabled.

|extended_groups_limit
|integer
a|Specifies the maximum auxillary groups supported over AUTH_SYS and
RPCSEC_GSS.

```

|metric  
|link:#metric[metric]  
a|Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

|positive\_cached\_credential\_ttl  
|integer  
a|Specifies the time to live value (in msec) of a positive cached credential

|protocol  
|link:#protocol[protocol]  
a|

|rquota\_enabled  
|boolean  
a|Specifies whether or not the remote quota feature is enabled.

|showmount\_enabled  
|boolean  
a|Specifies whether or not the showmount feature is enabled.

|state  
|string  
a|Specifies the state of the NFS service on the SVM. The following values are supported:

\*\*\*\*\* online - NFS server is ready to accept client requests.

\*\*\*\*\* offline - NFS server is not ready to accept client requests.

|statistics  
|link:#statistics[statistics]  
a|Realtime performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

|svm  
|link:#svm[svm]  
a|

```
|transport
|link:#transport[transport]
a|
```

```
|vstorage_enabled
|boolean
a|Specifies whether or not the VMware vstorage feature is enabled.
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|arguments
```



```
|array[link:#error_arguments[error_arguments]]
```

```
a|Message arguments
```

```
|code
```

```
|string
```

```
a|Error code
```

```
|message
```

```
|string
```

```
a|Error message
```

```
|target
```

```
|string
```

```
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
```

```
====
```

```
[[IDf5c664dd8f8a8a0240df1d2c99691dcf]]
```

```
= Delete the NFS configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-  
block]#`/protocols/nfs/services/{svm.uuid}`#
```

```
*Introduced In:* 9.6
```

```
Deletes the NFS configuration of an SVM.
```

```
== Related ONTAP commands
```

```
* `vserver nfs delete`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_nfs_services_endpoint_overview.html[DOC  
/protocols/nfs/services]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|
```

```
|===
```

```
== Response
```

Status: 200, Ok

```
== Error
```

Status: Default

```
ONTAP Error Response Codes
```

```
|===
```

```
| Error Code | Description
```

```
| 3276916
```

```
| Vserver is not running
```

```
| 3277008
```

```
| NFS Kerberos must be disabled on all LIFs of Vserver before deleting the  
NFS configuration. When all LIFs are disabled, try the operation
```

```
| 3277009
```

```
| NFS Kerberos realms associated with the Vserver are deleted
```

```
| 3277111
```

```
| Internal error. Failed to remove NFS-specific security trace filter for  
Vserver
```

```

| 3277112
| Internal error. Failed to modify the protocols field of a security trace
filter for Vserver
|===

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#error_arguments]
[.api-collapsible-fifth-title]

```

error\_arguments

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|code

|string

a|Argument code

|message

|string

a|Message argument

|===

[#error]

[.api-collapsible-fifth-title]

error

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|arguments

|array[link:#error\_arguments[error\_arguments]]

a|Message arguments

|code

|string

a|Error code

|message

|string

a|Error message

|target

```

|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

[[IDe8af0dd6ee33a87bb5ac8f15f45748af]]
= Retrieve the NFS configuration for an SVM

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/services/{svm.uuid}`#

*Introduced In:* 9.6

Retrieves the NFS configuration of an SVM.

== Related ONTAP commands

* `vserver nfs show`
* `vserver nfs status`

== Learn more

* xref:{relative_path}protocols_nfs_services_endpoint_overview.html[DOC
/protocols/nfs/services]

== Parameters

[cols=5*,options=header]
|===

|Name
|Type
|In
|Required
|Description

|svm.uuid
|string
|path

```

```
|True
a|

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|auth_sys_extended_groups_enabled
|boolean
a|Specifies whether or not extended groups support over AUTH_SYS is
enabled.

|enabled
|boolean
a|Specifies if the NFS service is administratively enabled.

|extended_groups_limit
|integer
a|Specifies the maximum auxillary groups supported over AUTH_SYS and
RPCSEC_GSS.

|metric
|link:#metric[metric]
a|Historical performance numbers, such as IOPS latency and throughput, for
SVM-NFS protocol.
```

```
|positive_cached_credential_ttl
|integer
a|Specifies the time to live value (in msec) of a positive cached
credential

|protocol
|link:#protocol[protocol]
a|

|rquota_enabled
|boolean
a|Specifies whether or not the remote quota feature is enabled.

|showmount_enabled
|boolean
a|Specifies whether or not the showmount feature is enabled.

|state
|string
a|Specifies the state of the NFS service on the SVM. The following values
are supported:

***** online - NFS server is ready to accept client requests.

***** offline - NFS server is not ready to accept client requests.

|statistics
|link:#statistics[statistics]
a|Realtime performance numbers, such as IOPS latency and throughput, for
SVM-NFS protocol.

|svm
|link:#svm[svm]
a|

|transport
|link:#transport[transport]
a|

|vstorage_enabled
```

|boolean

a|Specifies whether or not the VMware vstorage feature is enabled.

|===

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "extended_groups_limit": "32",
  "metric": {
    "v3": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "duration": "PT15S",
      "iops": {
        "read": "200",
        "total": "1000",
        "write": "100"
      },
      "latency": {
        "read": "200",
        "total": "1000",
        "write": "100"
      },
      "status": "ok",
      "throughput": {
        "read": "200",
        "total": "1000",
        "write": "100"
      },
      "timestamp": "2017-01-25T11:20:13Z"
    },
    "v4": {
      "_links": {
```



```
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"v41": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
},
```

```
    "timestamp": "2017-01-25T11:20:13Z"
  }
},
"positive_cached_credential_ttl": "7200000",
"state": "online",
"statistics": {
  "v3": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
  },
  "v4": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
  },
  "v41": {
    "iops_raw": {
```

```

    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput_raw": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
}
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

```

```
.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====
```

== Definitions

```
[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
```

```
[#href]
[.api-collapsible-fifth-title]
href
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|href
|string
a|
```

```
|===
```

```
[#_links]
[.api-collapsible-fifth-title]
_links
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|self
```

```
|link:#href[href]
```

```
a|
```

```
|===
```

```
[#iops]
```

```
[.api-collapsible-fifth-title]
```

```
iops
```

The rate of I/O operations observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|other
```

```
|integer
```

a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.

```
|read
```

```
|integer
```

a|Performance metric for read I/O operations.

```
|total
```

```
|integer
```

a|Performance metric aggregated over all types of I/O operations.

```
|write
```

```
|integer
```

a|Performance metric for write I/O operations.

```
|===
```

```
[#latency]  
[.api-collapsible-fifth-title]  
latency
```

The round trip latency in microseconds observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|other
```

```
|integer
```

a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.

```
|read
```

```
|integer
```

a|Performance metric for read I/O operations.

```
|total
```

```
|integer
```

a|Performance metric aggregated over all types of I/O operations.

```
|write
```

```
|integer
```

a|Performance metric for write I/O operations.

```
|===
```

```
[#throughput]  
[.api-collapsible-fifth-title]  
throughput
```

The rate of throughput bytes per second observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|read
```

```
|integer
```

```
a|Performance metric for read I/O operations.
```

```
|total
```

```
|integer
```

```
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
```

```
|integer
```

```
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#v3]
```

```
[.api-collapsible-fifth-title]
```

```
v3
```

The NFSv3 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|duration
```

```
|string
```

```
a|The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
```

```
|iops
|link:#iops[iops]
a|The rate of I/O operations observed at the storage object.
```

```
|latency
|link:#latency[latency]
a|The round trip latency in microseconds observed at the storage object.
```

```
|status
|string
a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
```

```
|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#v4]
[.api-collapsible-fifth-title]
v4
```

The NFSv4 operations

```
[cols=3*,options=header]
```



```

|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|duration
|string
a|The duration over which this sample is calculated. The time durations
are represented in the ISO-8601 standard format. Samples can be calculated
over the following durations:

|iops
|link:#iops[iops]
a|The rate of I/O operations observed at the storage object.

|latency
|link:#latency[latency]
a|The round trip latency in microseconds observed at the storage object.

|status
|string
a|Any errors associated with the sample. For example, if the aggregation
of data over multiple nodes fails then any of the partial errors might be
returned, "ok" on success, or "error" on any internal uncategorized
failure. Whenever a sample collection is missed but done at a later time,
it is back filled to the previous 15 second timestamp and tagged with
"backfilled_data". "Inconsistent_delta_time" is encountered when the time
between two collections is not the same for all nodes. Therefore, the
aggregated value might be over or under inflated. "Negative_delta" is
returned when an expected monotonically increasing value has decreased in
value. "Inconsistent_old_data" is returned when one or more nodes do not
have the latest data.

|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.

|timestamp

```

```

|string
a|The timestamp of the performance data.

|===

[#v41]
[.api-collapsible-fifth-title]
v41

The NFSv4.1 operations

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|duration
|string
a|The duration over which this sample is calculated. The time durations
are represented in the ISO-8601 standard format. Samples can be calculated
over the following durations:

|iops
|link:#iops[iops]
a|The rate of I/O operations observed at the storage object.

|latency
|link:#latency[latency]
a|The round trip latency in microseconds observed at the storage object.

|status
|string
a|Any errors associated with the sample. For example, if the aggregation
of data over multiple nodes fails then any of the partial errors might be
returned, "ok" on success, or "error" on any internal uncategorized
failure. Whenever a sample collection is missed but done at a later time,

```

it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

|throughput

|link:#throughput[throughput]

a|The rate of throughput bytes per second observed at the storage object.

|timestamp

|string

a|The timestamp of the performance data.

|===

[#metric]

[.api-collapsible-fifth-title]

metric

Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|v3

|link:#v3[v3]

a|The NFSv3 operations

|v4

|link:#v4[v4]

a|The NFSv4 operations

|v41

```
|link:#v41[v41]
```

```
a|The NFSv4.1 operations
```

```
|===
```

```
[#v40_features]
```

```
[.api-collapsible-fifth-title]
```

```
v40_features
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|acl_enabled
```

```
|boolean
```

```
a|Specifies whether NFSv4.0 ACLs is enabled.
```

```
|read_delegation_enabled
```

```
|boolean
```

```
a|Specifies whether NFSv4.0 Read Delegation is enabled.
```

```
|write_delegation_enabled
```

```
|boolean
```

```
a|Specifies whether NFSv4.0 Write Delegation is enabled.
```

```
|===
```

```
[#v41_features]
```

```
[.api-collapsible-fifth-title]
```

```
v41_features
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|acl_enabled
```

```
|boolean
```

a|Specifies whether NFSv4.1 or later ACLs is enabled.

|pnfs\_enabled

|boolean

a|Specifies whether NFSv4.1 or later Parallel NFS is enabled.

|read\_delegation\_enabled

|boolean

a|Specifies whether NFSv4.1 or later Read Delegation is enabled.

|write\_delegation\_enabled

|boolean

a|Specifies whether NFSv4.1 or later Write Delegation is enabled.

|===

[#protocol]

[.api-collapsible-fifth-title]

protocol

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|v3\_64bit\_identifiers\_enabled

|boolean

a|Specifies whether 64-bit support for NFSv3 FSIDs and file IDs is enabled.

|v3\_enabled

|boolean

a|Specifies whether NFSv3 protocol is enabled.

|v40\_enabled

|boolean

a|Specifies whether NFSv4.0 protocol is enabled.

```

|v40_features
|link:#v40_features[v40_features]
a|

|v41_enabled
|boolean
a|Specifies whether NFSv4.1 or later protocol is enabled.

|v41_features
|link:#v41_features[v41_features]
a|

|v4_64bit_identifiers_enabled
|boolean
a|Specifies whether 64-bit support for NFSv4.x FSIDs and file IDs is
enabled.

|v4_id_domain
|string
a|Specifies the domain portion of the string form of user and group
names as defined by the NFSv4 protocol.

```

```
|===
```

```

[#iops_raw]
[.api-collapsible-fifth-title]
iops_raw

```

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

```
[cols=3*,options=header]
```

```
|===
```

```

|Name
|Type
|Description

```

```
|other
```

```
|integer
```

```

a|Performance metric for other I/O operations. Other I/O operations can be
metadata operations, such as directory lookups and so on.

```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#latency_raw]
[.api-collapsible-fifth-title]
latency_raw
```

The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|other
|integer
a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.
```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
```

```
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#throughput_raw]
[.api-collapsible-fifth-title]
throughput_raw
```

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

```
[cols=3*,options=header]
```

```
|===
|Name
|Type
|Description
```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#v3]
[.api-collapsible-fifth-title]
```



v3

## The NFSv3 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|iops_raw
```

```
|link:#iops_raw[iops_raw]
```

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

```
|latency_raw
```

```
|link:#latency_raw[latency_raw]
```

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

```
|status
```

```
|string
```

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

```
|throughput_raw
```

```
|link:#throughput_raw[throughput_raw]
```

a|Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#v4]
[.api-collapsible-fifth-title]
v4
```

The NFSv4 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|iops_raw
```

```
|link:#iops_raw[iops_raw]
```

```
a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.
```

```
|latency_raw
```

```
|link:#latency_raw[latency_raw]
```

```
a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.
```

```
|status
```

```
|string
```

```
a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not
```

have the latest data.

|throughput\_raw

|link:#throughput\_raw[throughput\_raw]

a|Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

|timestamp

|string

a|The timestamp of the performance data.

|===

[#v41]

[.api-collapsible-fifth-title]

v41

The NFSv4.1 operations

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|iops\_raw

|link:#iops\_raw[iops\_raw]

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

|latency\_raw

|link:#latency\_raw[latency\_raw]

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

|status

|string

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

|throughput\_raw

|link:#throughput\_raw[throughput\_raw]

a|Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

|timestamp

|string

a|The timestamp of the performance data.

|===

[#statistics]

[.api-collapsible-fifth-title]

statistics

Realtime performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|v3

|link:#v3[v3]

a|The NFSv3 operations

```

|v4
|link:#v4[v4]
a|The NFSv4 operations

|v41
|link:#v41[v41]
a|The NFSv4.1 operations

|===

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

|===

[#transport]
[.api-collapsible-fifth-title]
transport

[cols=3*,options=header]
|===
|Name

```

```
|Type
|Description

|tcp_enabled
|boolean
a|Specifies whether TCP transports are enabled on the server.
```

```
|udp_enabled
|boolean
a|Specifies whether UDP transports are enabled on the server.
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
|Name
|Type
```

```

|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[ID5e7d7ddcelaa575146ad72f8e50ef300]]
= Update the NFS configuration for an SVM

[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/nfs/services/{svm.uuid}`#

*Introduced In:* 9.6

Updates the NFS configuration of an SVM.

== Related ONTAP commands

* `vserver nfs modify`
* `vserver nfs on`
* `vserver nfs off`
* `vserver nfs start`
* `vserver nfs stop`

```

== Learn more

\* xref:{relative\_path}protocols\_nfs\_services\_endpoint\_overview.html[DOC  
/protocols/nfs/services]

== Parameters

[cols=5\*,options=header]

|===

|Name

|Type

|In

|Required

|Description

|svm.uuid

|string

|path

|True

a|

|===

== Request Body

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|\_links

|link:#\_links[\_links]

a|

|auth\_sys\_extended\_groups\_enabled

|boolean

a|Specifies whether or not extended groups support over AUTH\_SYS is enabled.

|enabled

|boolean



a|Specifies if the NFS service is administratively enabled.

|extended\_groups\_limit

|integer

a|Specifies the maximum auxiliary groups supported over AUTH\_SYS and RPCSEC\_GSS.

|metric

|link:#metric[metric]

a|Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

|positive\_cached\_credential\_ttl

|integer

a|Specifies the time to live value (in msec) of a positive cached credential

|protocol

|link:#protocol[protocol]

a|

|rquota\_enabled

|boolean

a|Specifies whether or not the remote quota feature is enabled.

|showmount\_enabled

|boolean

a|Specifies whether or not the showmount feature is enabled.

|state

|string

a|Specifies the state of the NFS service on the SVM. The following values are supported:

\*\*\*\*\* online - NFS server is ready to accept client requests.

\*\*\*\*\* offline - NFS server is not ready to accept client requests.

|statistics

|link:#statistics[statistics]

a|Realtime performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

|svm  
|link:#svm[svm]

a|

|transport  
|link:#transport[transport]

a|

|vstorage\_enabled  
|boolean

a|Specifies whether or not the VMware vstorage feature is enabled.

|===

.Example request

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "extended_groups_limit": "32",
  "metric": {
    "v3": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "duration": "PT15S",
      "iops": {
        "read": "200",
        "total": "1000",
        "write": "100"
      },
      "latency": {
        "read": "200",
```

```

    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"v4": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"v41": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",

```

```
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
}
},
"positive_cached_credential_ttl": "7200000",
"state": "online",
"statistics": {
  "v3": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
  },
  "v4": {
    "iops_raw": {
      "read": "200",
      "total": "1000",
      "write": "100"
    },
    "latency_raw": {
      "read": "200",
```

```

        "total": "1000",
        "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
        "read": "200",
        "total": "1000",
        "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
},
"v41": {
    "iops_raw": {
        "read": "200",
        "total": "1000",
        "write": "100"
    },
    "latency_raw": {
        "read": "200",
        "total": "1000",
        "write": "100"
    },
    "status": "ok",
    "throughput_raw": {
        "read": "200",
        "total": "1000",
        "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
}
},
"svm": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
====

== Response

```

Status: 200, Ok

```
== Error
```

## Status: Default

### ONTAP Error Response Codes

```
|===  
| Error Code | Description  
  
| 3276916  
| Vserver is not running  
  
| 3277069  
| Cannot disable TCP because the SnapDiff RPC server is in the \"on\"  
state  
  
| 3277087  
| Attempting to reduce the number of bits used for NFSv3 FSIDs and File  
IDs from 64 to 32 on Vserver. This could result in collisions between  
different File IDs and is not recommended  
  
| 3277088  
| Attempting to increase the number of bits used for NFSv3 FSIDs and File  
IDs from 32 to 64 on Vserver. This could result in older client software  
no longer working with the volumes owned by Vserver  
  
| 3277090  
| Attempting to disallow multiple FSIDs per mount point on Vserver. Since  
this Vserver currently uses 32-bit NFSv3 FSIDs and File IDs, this could  
result in collisions between different File IDs and is not recommended  
  
| 3277099  
| Domain name contains invalid characters or its too short. Allowed  
characters are: alphabetical characters (A-Za-z), numeric characters (0-  
9), minus sign (-), and the period (.). The first character must be  
alphabetical or numeric, last character must not be a minus sign or a  
period. Minimum supported length: 2 characters, maximum of 256 characters  
|===
```

```
[cols=3*,options=header]
```

```
|===  
|Name  
|Type
```

```

|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

```

```
|===
```

```
[#_links]  
[.api-collapsible-fifth-title]  
_links
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|self  
|link:#href[href]  
a|
```

```
|===
```

```
[#iops]  
[.api-collapsible-fifth-title]  
iops
```

The rate of I/O operations observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|other  
|integer
```

a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.

```
|read  
|integer  
a|Performance metric for read I/O operations.
```

```
|total  
|integer  
a|Performance metric aggregated over all types of I/O operations.
```



```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#latency]
[.api-collapsible-fifth-title]
latency
```

The round trip latency in microseconds observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|other
|integer
a|Performance metric for other I/O operations. Other I/O operations can be
metadata operations, such as directory lookups and so on.
```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#throughput]
[.api-collapsible-fifth-title]
throughput
```

The rate of throughput bytes per second observed at the storage object.

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#v3]
[.api-collapsible-fifth-title]
v3
```

The NFSv3 operations

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

|duration  
|string  
a|The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:

|iops  
|link:#iops[iops]  
a|The rate of I/O operations observed at the storage object.

|latency  
|link:#latency[latency]  
a|The round trip latency in microseconds observed at the storage object.

|status  
|string  
a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

|throughput  
|link:#throughput[throughput]  
a|The rate of throughput bytes per second observed at the storage object.

|timestamp  
|string  
a|The timestamp of the performance data.

|===

[#v4]

```
[.api-collapsible-fifth-title]
```

```
v4
```

```
The NFSv4 operations
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|duration
```

```
|string
```

```
a|The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
```

```
|iops
```

```
|link:#iops[iops]
```

```
a|The rate of I/O operations observed at the storage object.
```

```
|latency
```

```
|link:#latency[latency]
```

```
a|The round trip latency in microseconds observed at the storage object.
```

```
|status
```

```
|string
```

```
a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
```

```
|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#v41]
[.api-collapsible-fifth-title]
v41
```

The NFSv4.1 operations

```
[cols=3*,options=header]
```

```
|===
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|duration
|string
a|The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
```

```
|iops
|link:#iops[iops]
a|The rate of I/O operations observed at the storage object.
```

```
|latency
|link:#latency[latency]
a|The round trip latency in microseconds observed at the storage object.
```

```
|status
|string
a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
```

```
|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#metric]
[.api-collapsible-fifth-title]
metric
```

Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|v3
```

```
|link:#v3[v3]
```

```
a|The NFSv3 operations
```

```
|v4
|link:#v4[v4]
a|The NFSv4 operations
```

```
|v41
|link:#v41[v41]
a|The NFSv4.1 operations
```

```
|===
```

```
[#v40_features]
[.api-collapsible-fifth-title]
v40_features
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|acl_enabled
|boolean
a|Specifies whether NFSv4.0 ACLs is enabled.
```

```
|read_delegation_enabled
|boolean
a|Specifies whether NFSv4.0 Read Delegation is enabled.
```

```
|write_delegation_enabled
|boolean
a|Specifies whether NFSv4.0 Write Delegation is enabled.
```

```
|===
```

```
[#v41_features]
[.api-collapsible-fifth-title]
v41_features
```

```
[cols=3*,options=header]
```

```

|===
|Name
|Type
|Description

|acl_enabled
|boolean
a|Specifies whether NFSv4.1 or later ACLs is enabled.

|pnfs_enabled
|boolean
a|Specifies whether NFSv4.1 or later Parallel NFS is enabled.

|read_delegation_enabled
|boolean
a|Specifies whether NFSv4.1 or later Read Delegation is enabled.

|write_delegation_enabled
|boolean
a|Specifies whether NFSv4.1 or later Write Delegation is enabled.

|===

[#protocol]
[.api-collapsible-fifth-title]
protocol

[cols=3*,options=header]
|===
|Name
|Type
|Description

|v3_64bit_identifiers_enabled
|boolean
a|Specifies whether 64-bit support for NFSv3 FSIDs and file IDs is
enabled.

|v3_enabled
|boolean
a|Specifies whether NFSv3 protocol is enabled.

```



```
|v40_enabled
|boolean
a|Specifies whether NFSv4.0 protocol is enabled.
```

```
|v40_features
|link:#v40_features[v40_features]
a|
```

```
|v41_enabled
|boolean
a|Specifies whether NFSv4.1 or later protocol is enabled.
```

```
|v41_features
|link:#v41_features[v41_features]
a|
```

```
|v4_64bit_identifiers_enabled
|boolean
a|Specifies whether 64-bit support for NFSv4.x FSIDs and file IDs is
enabled.
```

```
|v4_id_domain
|string
a|Specifies the domain portion of the string form of user and group
names as defined by the NFSv4 protocol.
```

```
|===
```

```
[#iops_raw]
[.api-collapsible-fifth-title]
iops_raw
```

The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```

|Type
|Description

|other
|integer
a|Performance metric for other I/O operations. Other I/O operations can be
metadata operations, such as directory lookups and so on.

|read
|integer
a|Performance metric for read I/O operations.

|total
|integer
a|Performance metric aggregated over all types of I/O operations.

|write
|integer
a|Performance metric for write I/O operations.

|===

[#latency_raw]
[.api-collapsible-fifth-title]
latency_raw

The raw latency in microseconds observed at the storage object. This
should be divided by the raw IOPS value to calculate the average latency
per I/O operation.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|other
|integer
a|Performance metric for other I/O operations. Other I/O operations can be
metadata operations, such as directory lookups and so on.

```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#throughput_raw]
[.api-collapsible-fifth-title]
throughput_raw
```

Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#v3]
```

```
[.api-collapsible-fifth-title]
```

```
v3
```

The NFSv3 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|iops_raw
```

```
|link:#iops_raw[iops_raw]
```

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

```
|latency_raw
```

```
|link:#latency_raw[latency_raw]
```

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

```
|status
```

```
|string
```

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

```
|throughput_raw
|link:#throughput_raw[throughput_raw]
a|Throughput bytes observed at the storage object. This should be used
along with delta time to calculate the rate of throughput bytes per unit
of time.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#v4]
[.api-collapsible-fifth-title]
v4
```

The NFSv4 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|iops_raw
|link:#iops_raw[iops_raw]
a|The number of I/O operations observed at the storage object. This should
be used along with delta time to calculate the rate of I/O operations per
unit of time.
```

```
|latency_raw
|link:#latency_raw[latency_raw]
a|The raw latency in microseconds observed at the storage object. This
should be divided by the raw IOPS value to calculate the average latency
per I/O operation.
```

```
|status
|string
a|Any errors associated with the sample. For example, if the aggregation
of data over multiple nodes fails then any of the partial errors might be
returned, "ok" on success, or "error" on any internal uncategorized
```

failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

```
|throughput_raw
```

```
|link:#throughput_raw[throughput_raw]
```

a|Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

```
|timestamp
```

```
|string
```

a|The timestamp of the performance data.

```
|===
```

```
[#v41]
```

```
[.api-collapsible-fifth-title]
```

```
v41
```

The NFSv4.1 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|iops_raw
```

```
|link:#iops_raw[iops_raw]
```

a|The number of I/O operations observed at the storage object. This should be used along with delta time to calculate the rate of I/O operations per unit of time.

```
|latency_raw
```

```
|link:#latency_raw[latency_raw]
```

a|The raw latency in microseconds observed at the storage object. This should be divided by the raw IOPS value to calculate the average latency per I/O operation.

|status

|string

a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled\_data". "Inconsistent\_delta\_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative\_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent\_old\_data" is returned when one or more nodes do not have the latest data.

|throughput\_raw

|link:#throughput\_raw[throughput\_raw]

a|Throughput bytes observed at the storage object. This should be used along with delta time to calculate the rate of throughput bytes per unit of time.

|timestamp

|string

a|The timestamp of the performance data.

|===

[#statistics]

[.api-collapsible-fifth-title]

statistics

Realtime performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

[cols=3\*,options=header]

|===

|Name

|Type

```

|Description

|v3
|link:#v3[v3]
a|The NFSv3 operations

|v4
|link:#v4[v4]
a|The NFSv4 operations

|v41
|link:#v41[v41]
a|The NFSv4.1 operations

|===

[#svm]
[.api-collapsible-fifth-title]
svm

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|The name of the SVM.

|uuid
|string
a|The unique identifier of the SVM.

|===

```



```

[#transport]
[.api-collapsible-fifth-title]
transport

[cols=3*,options=header]
|===
|Name
|Type
|Description

|tcp_enabled
|boolean
a|Specifies whether TCP transports are enabled on the server.

|udp_enabled
|boolean
a|Specifies whether UDP transports are enabled on the server.

|===

[#nfs_service]
[.api-collapsible-fifth-title]
nfs_service

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|auth_sys_extended_groups_enabled
|boolean
a|Specifies whether or not extended groups support over AUTH_SYS is
enabled.

|enabled
|boolean
a|Specifies if the NFS service is administratively enabled.

```

|extended\_groups\_limit  
|integer  
a|Specifies the maximum auxillary groups supported over AUTH\_SYS and RPCSEC\_GSS.

|metric  
|link:#metric[metric]  
a|Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

|positive\_cached\_credential\_ttl  
|integer  
a|Specifies the time to live value (in msec) of a positive cached credential

|protocol  
|link:#protocol[protocol]  
a|

|rquota\_enabled  
|boolean  
a|Specifies whether or not the remote quota feature is enabled.

|showmount\_enabled  
|boolean  
a|Specifies whether or not the showmount feature is enabled.

|state  
|string  
a|Specifies the state of the NFS service on the SVM. The following values are supported:

\*\*\*\*\* online - NFS server is ready to accept client requests.

\*\*\*\*\* offline - NFS server is not ready to accept client requests.

|statistics  
|link:#statistics[statistics]  
a|Realtime performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

```
|svm
|link:#svm[svm]
a|
```

```
|transport
|link:#transport[transport]
a|
```

```
|vstorage_enabled
|boolean
a|Specifies whether or not the VMware vstorage feature is enabled.
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```

|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[ID86d86bbdfcd0547087bd3338d6017d5d]]
= Retrieve NFS protocol historical performance metrics

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/nfs/services/{svm.uuid}/metrics`#

*Introduced In:* 9.7

Retrieves historical performance metrics for the NFS protocol of an SVM.

== Parameters

[cols=5*,options=header]
|===

```

```
|Name
|Type
|In
|Required
|Description

|v4.latency.total
|integer
|query
|False
a|Filter by v4.latency.total

* Introduced in: 9.8

|v4.latency.read
|integer
|query
|False
a|Filter by v4.latency.read

* Introduced in: 9.8

|v4.latency.other
|integer
|query
|False
a|Filter by v4.latency.other

* Introduced in: 9.8

|v4.latency.write
|integer
|query
|False
a|Filter by v4.latency.write

* Introduced in: 9.8

|v4.status
|string
|query
|False
```

a|Filter by v4.status

\* Introduced in: 9.8

|v4.iops.total

|integer

|query

|False

a|Filter by v4.iops.total

\* Introduced in: 9.8

|v4.iops.read

|integer

|query

|False

a|Filter by v4.iops.read

\* Introduced in: 9.8

|v4.iops.other

|integer

|query

|False

a|Filter by v4.iops.other

\* Introduced in: 9.8

|v4.iops.write

|integer

|query

|False

a|Filter by v4.iops.write

\* Introduced in: 9.8

|v4.duration

|string

|query

|False

a|Filter by v4.duration

\* Introduced in: 9.8

|v4.throughput.write  
|integer  
|query  
|False  
a|Filter by v4.throughput.write

\* Introduced in: 9.8

|v4.throughput.read  
|integer  
|query  
|False  
a|Filter by v4.throughput.read

\* Introduced in: 9.8

|v4.throughput.total  
|integer  
|query  
|False  
a|Filter by v4.throughput.total

\* Introduced in: 9.8

|v41.iops.total  
|integer  
|query  
|False  
a|Filter by v41.iops.total

\* Introduced in: 9.8

|v41.iops.read  
|integer  
|query  
|False  
a|Filter by v41.iops.read

\* Introduced in: 9.8

```
|v41.iops.other
|integer
|query
|False
a|Filter by v41.iops.other
```

\* Introduced in: 9.8

```
|v41.iops.write
|integer
|query
|False
a|Filter by v41.iops.write
```

\* Introduced in: 9.8

```
|v41.status
|string
|query
|False
a|Filter by v41.status
```

\* Introduced in: 9.8

```
|v41.latency.total
|integer
|query
|False
a|Filter by v41.latency.total
```

\* Introduced in: 9.8

```
|v41.latency.read
|integer
|query
|False
a|Filter by v41.latency.read
```

\* Introduced in: 9.8

```
|v41.latency.other
```



```
|integer
|query
|False
a|Filter by v41.latency.other
```

\* Introduced in: 9.8

```
|v41.latency.write
|integer
|query
|False
a|Filter by v41.latency.write
```

\* Introduced in: 9.8

```
|v41.throughput.write
|integer
|query
|False
a|Filter by v41.throughput.write
```

\* Introduced in: 9.8

```
|v41.throughput.read
|integer
|query
|False
a|Filter by v41.throughput.read
```

\* Introduced in: 9.8

```
|v41.throughput.total
|integer
|query
|False
a|Filter by v41.throughput.total
```

\* Introduced in: 9.8

```
|v41.duration
|string
|query
```

```
|False  
a|Filter by v41.duration
```

```
* Introduced in: 9.8
```

```
|v3.duration  
|string  
|query  
|False  
a|Filter by v3.duration
```

```
|v3.throughput.write  
|integer  
|query  
|False  
a|Filter by v3.throughput.write
```

```
|v3.throughput.read  
|integer  
|query  
|False  
a|Filter by v3.throughput.read
```

```
|v3.throughput.total  
|integer  
|query  
|False  
a|Filter by v3.throughput.total
```

```
|v3.latency.total  
|integer  
|query  
|False  
a|Filter by v3.latency.total
```

```
|v3.latency.read  
|integer  
|query  
|False  
a|Filter by v3.latency.read
```

```
|v3.latency.other
|integer
|query
|False
a|Filter by v3.latency.other
```

```
|v3.latency.write
|integer
|query
|False
a|Filter by v3.latency.write
```

```
|v3.iops.total
|integer
|query
|False
a|Filter by v3.iops.total
```

```
|v3.iops.read
|integer
|query
|False
a|Filter by v3.iops.read
```

```
|v3.iops.other
|integer
|query
|False
a|Filter by v3.iops.other
```

```
|v3.iops.write
|integer
|query
|False
a|Filter by v3.iops.write
```

```
|v3.status
|string
|query
|False
```

a|Filter by v3.status

|timestamp

|string

|query

|False

a|Filter by timestamp

|svm.uuid

|string

|path

|True

a|Unique identifier of the SVM.

|interval

|string

|query

|False

a|The time range for the data. Examples can be 1h, 1d, 1m, 1w, 1y.

The period for each time range is as follows:

\* 1h: Metrics over the most recent hour sampled over 15 seconds.

\* 1d: Metrics over the most recent day sampled over 5 minutes.

\* 1w: Metrics over the most recent week sampled over 30 minutes.

\* 1m: Metrics over the most recent month sampled over 2 hours.

\* 1y: Metrics over the most recent year sampled over a day.

\* Default value: 1

\* enum: ["1h", "1d", "1w", "1m", "1y"]

|return\_timeout

|integer

|query

|False

a|The number of seconds to allow the call to execute before returning.

When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.

\* Default value: 1

\* Max value: 120

\* Min value: 0

```
|fields
|array[string]
|query
|False
a|Specify the fields to return.
```

```
|max_records
|integer
|query
|False
a|Limit the number of records returned.
```

```
|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.
```

```
|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.
```

\* Default value: 1

```
|===
```

```
== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|
```

```
|num_records
|integer
a|Number of records
```

```
|records
|array[link:#records[records]]
a|
```

```
|===
```

.Example response

[%collapsible%closed]

```
=====
```

```
[source,json,subs=+macros]
```

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "v3": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "duration": "PT15S",
      "iops": {
        "read": "200",
        "total": "1000",
        "write": "100"
      },
      "latency": {
        "read": "200",
        "total": "1000",
        "write": "100"
      },
      "status": "ok",
      "throughput": {
```

```
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"v4": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "status": "ok",
  "throughput": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "timestamp": "2017-01-25T11:20:13Z"
},
"v41": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "duration": "PT15S",
  "iops": {
    "read": "200",
    "total": "1000",
    "write": "100"
  },
  "latency": {
    "read": "200",
    "total": "1000",
```

```

        "write": "100"
    },
    "status": "ok",
    "throughput": {
        "read": "200",
        "total": "1000",
        "write": "100"
    },
    "timestamp": "2017-01-25T11:20:13Z"
}
}
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}

```



```

}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

```

```
[#_links]
[.api-collapsible-fifth-title]
_links
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|self
|link:#href[href]
a|
```

```
|===
```

```
[#iops]
[.api-collapsible-fifth-title]
iops
```

The rate of I/O operations observed at the storage object.

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|other
|integer
```

a|Performance metric for other I/O operations. Other I/O operations can be metadata operations, such as directory lookups and so on.

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#latency]
[.api-collapsible-fifth-title]
latency
```

The round trip latency in microseconds observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|other
|integer
a|Performance metric for other I/O operations. Other I/O operations can be
metadata operations, such as directory lookups and so on.
```

```
|read
|integer
a|Performance metric for read I/O operations.
```

```
|total
|integer
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
|integer
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#throughput]
[.api-collapsible-fifth-title]
```

throughput

The rate of throughput bytes per second observed at the storage object.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|read
```

```
|integer
```

```
a|Performance metric for read I/O operations.
```

```
|total
```

```
|integer
```

```
a|Performance metric aggregated over all types of I/O operations.
```

```
|write
```

```
|integer
```

```
a|Performance metric for write I/O operations.
```

```
|===
```

```
[#v3]
```

```
[.api-collapsible-fifth-title]
```

```
v3
```

The NFSv3 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|duration
```

```
|string
a|The duration over which this sample is calculated. The time durations
are represented in the ISO-8601 standard format. Samples can be calculated
over the following durations:
```

```
|iops
|link:#iops[iops]
a|The rate of I/O operations observed at the storage object.
```

```
|latency
|link:#latency[latency]
a|The round trip latency in microseconds observed at the storage object.
```

```
|status
|string
a|Any errors associated with the sample. For example, if the aggregation
of data over multiple nodes fails then any of the partial errors might be
returned, "ok" on success, or "error" on any internal uncategorized
failure. Whenever a sample collection is missed but done at a later time,
it is back filled to the previous 15 second timestamp and tagged with
"backfilled_data". "Inconsistent_delta_time" is encountered when the time
between two collections is not the same for all nodes. Therefore, the
aggregated value might be over or under inflated. "Negative_delta" is
returned when an expected monotonically increasing value has decreased in
value. "Inconsistent_old_data" is returned when one or more nodes do not
have the latest data.
```

```
|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#v4]
[.api-collapsible-fifth-title]
v4
```

## The NFSv4 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
 |_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|duration
```

```
|string
```

```
a|The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
```

```
|iops
```

```
|link:#iops[iops]
```

```
a|The rate of I/O operations observed at the storage object.
```

```
|latency
```

```
|link:#latency[latency]
```

```
a|The round trip latency in microseconds observed at the storage object.
```

```
|status
```

```
|string
```

```
a|Any errors associated with the sample. For example, if the aggregation of data over multiple nodes fails then any of the partial errors might be returned, "ok" on success, or "error" on any internal uncategorized failure. Whenever a sample collection is missed but done at a later time, it is back filled to the previous 15 second timestamp and tagged with "backfilled_data". "Inconsistent_delta_time" is encountered when the time between two collections is not the same for all nodes. Therefore, the aggregated value might be over or under inflated. "Negative_delta" is returned when an expected monotonically increasing value has decreased in value. "Inconsistent_old_data" is returned when one or more nodes do not have the latest data.
```

```
|throughput
```

```
|link:#throughput[throughput]
```

```
a|The rate of throughput bytes per second observed at the storage object.
```

```
|timestamp
```

```
|string
```

```
a|The timestamp of the performance data.
```

```
|===
```

```
[#v41]
```

```
[.api-collapsible-fifth-title]
```

```
v41
```

The NFSv4.1 operations

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|duration
```

```
|string
```

```
a|The duration over which this sample is calculated. The time durations are represented in the ISO-8601 standard format. Samples can be calculated over the following durations:
```

```
|iops
```

```
|link:#iops[iops]
```

```
a|The rate of I/O operations observed at the storage object.
```

```
|latency
```

```
|link:#latency[latency]
```

```
a|The round trip latency in microseconds observed at the storage object.
```

```
|status
```

```
|string
a|Any errors associated with the sample. For example, if the aggregation
of data over multiple nodes fails then any of the partial errors might be
returned, "ok" on success, or "error" on any internal uncategorized
failure. Whenever a sample collection is missed but done at a later time,
it is back filled to the previous 15 second timestamp and tagged with
"backfilled_data". "Inconsistent_delta_time" is encountered when the time
between two collections is not the same for all nodes. Therefore, the
aggregated value might be over or under inflated. "Negative_delta" is
returned when an expected monotonically increasing value has decreased in
value. "Inconsistent_old_data" is returned when one or more nodes do not
have the latest data.
```

```
|throughput
|link:#throughput[throughput]
a|The rate of throughput bytes per second observed at the storage object.
```

```
|timestamp
|string
a|The timestamp of the performance data.
```

```
|===
```

```
[#records]
[.api-collapsible-fifth-title]
records
```

Historical performance numbers, such as IOPS latency and throughput, for SVM-NFS protocol.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|v3
|link:#v3[v3]
a|The NFSv3 operations
```

```
|v4
```



```
|link:#v4[v4]
a|The NFSv4 operations
```

```
|v41
|link:#v41[v41]
a|The NFSv4.1 operations
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
```

```
a|Message arguments
```

```
|code
```

```
|string
```

```
a|Error code
```

```
|message
```

```
|string
```

```
a|Error message
```

```
|target
```

```
|string
```

```
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
```

```
====
```

```
:leveloffset: -1
```

```
= View and create Vscan configuration
```

```
:leveloffset: +1
```

```
[[ID241751231245aacd99ec9413fa16f939]]
```

```
= Protocols Vscan endpoint overview
```

```
== Overview
```

Use Vscan to protect data from being compromised by viruses or other malicious code. Vscan combines best-in-class third party antivirus software with ONTAP features that give you the flexibility you need to control which files get scanned and when. Storage systems offload scanning operations to external servers hosting antivirus software from third party vendors. An Antivirus Connector on the external server handles

communications between the storage system and the antivirus software.

== Examples

=== Retrieving all of the Vscan configurations

----

# The API:

/api/protocols/vscan

# The call:

```
curl -X GET "https://<mgmt-  
ip>/api/protocols/vscan?fields=*&return_records=true&return_timeout=15" -H  
"accept: application/json"
```

# The response:

```
{  
"records": [  
  {  
    "svm": {  
      "uuid": "03ce5c36-f269-11e8-8852-0050568e5298",  
      "name": "vs1"  
    },  
    "enabled": true,  
    "scanner_pools": [  
      {  
        "name": "scanner-1",  
        "servers": [  
          "1.1.1.1",  
          "10.72.204.27"  
        ],  
        "privileged_users": [  
          "cifs\\u1",  
          "cifs\\u2"  
        ],  
        "role": "primary",  
        "cluster": {  
          "name": "Cluster1",  
          "uuid": "0228714d-f268-11e8-8851-0050568e5298"  
        }  
      },  
      {  
        "name": "scanner-2",  
        "servers": [  
          "1.1.1.1",
```

```

    "10.72.204.27"
  ],
  "privileged_users": [
    "cifs\\u1",
    "cifs\\u2"
  ],
  "role": "primary",
  "cluster": {
    "name": "Cluster1",
    "uuid": "0228714d-f268-11e8-8851-0050568e5298"
  }
}
],
"on_access_policies": [
  {
    "name": "default_CIFS",
    "vsName": "vs1",
    "enabled": true,
    "mandatory": true,
    "scope": {
      "max_file_size": 2147483648,
      "include_extensions": [
        "*"
      ],
      "scan_without_extension": true,
      "scan_readonly_volumes": false,
      "only_execute_access": false
    }
  },
  {
    "name": "on-access-test1",
    "vsName": "vs1",
    "enabled": false,
    "mandatory": true,
    "scope": {
      "max_file_size": 10000,
      "exclude_paths": [
        "\\dir"
      ],
      "include_extensions": [
        "mp*",
        "txt"
      ],
      "exclude_extensions": [
        "mp*",
        "txt"
      ]
    }
  }
]

```

```

    ],
    "scan_without_extension": true,
    "scan_readonly_volumes": false,
    "only_execute_access": false
  }
},
{
  "name": "on-access-test2",
  "vsName": "vs1",
  "enabled": false,
  "mandatory": true,
  "scope": {
    "max_file_size": 10000,
    "exclude_paths": [
      "\\dir"
    ],
    "include_extensions": [
      "mp*",
      "txt"
    ],
    "exclude_extensions": [
      "mp*",
      "txt"
    ],
    "scan_without_extension": true,
    "scan_readonly_volumes": false,
    "only_execute_access": false
  }
}
],
"on_demand_policies": [
  {
    "name": "task-1",
    "scan_paths": [
      "/vol1"
    ],
    "log_path": "/vol1",
    "scope": {
      "max_file_size": 10000,
      "exclude_paths": [
        "/vol1"
      ],
      "include_extensions": [
        "vmdk",
        "mp*"
      ]
    }
  ],

```



```

    "role": "idle"
  }
],
"on_access_policies": [
  {
    "name": "default_CIFS",
    "vsName": "vs2",
    "enabled": true,
    "mandatory": true,
    "scope": {
      "max_file_size": 2147483648,
      "include_extensions": [
        "*"
      ],
      "scan_without_extension": true,
      "scan_readonly_volumes": false,
      "only_execute_access": false
    }
  },
  {
    "name": "ap1",
    "vsName": "vs2",
    "enabled": false,
    "mandatory": true,
    "scope": {
      "max_file_size": 2147483648,
      "include_extensions": [
        "*"
      ],
      "scan_without_extension": true,
      "scan_readonly_volumes": false,
      "only_execute_access": false
    }
  }
],
"on_demand_policies": [
  {
    "name": "t1",
    "scan_paths": [
      "/voll"
    ],
    "log_path": "/voll",
    "scope": {
      "max_file_size": 10737418240,
      "include_extensions": [
        "*"
      ]
    }
  }
]

```

```

        ],
        "scan_without_extension": true
    }
}
]
}
],
"num_records": 2
}
-----

```

=== Retrieving all Vscan configurations for a particular SVM

-----

# The API:

/api/protocols/vscan/{svm.uuid}

# The call:

```
curl -X GET "https://<mgmt-ip>/api/protocols/vscan/24c2567a-f269-11e8-8852-0050568e5298?fields=*" -H "accept: application/json"
```

# The response:

```

{
  "svm": {
    "uuid": "24c2567a-f269-11e8-8852-0050568e5298",
    "name": "vs2"
  },
  "enabled": false,
  "scanner_pools": [
    {
      "name": "sp2",
      "servers": [
        "1.1.1.1"
      ],
      "privileged_users": [
        "cifs\\u1"
      ],
      "role": "idle"
    }
  ],
  "on_access_policies": [
    {
      "name": "default_CIFS",
      "vsName": "vs2",
      "enabled": true,

```



```

"mandatory": true,
"scope": {
  "max_file_size": 2147483648,
  "include_extensions": [
    "*"
  ],
  "scan_without_extension": true,
  "scan_readonly_volumes": false,
  "only_execute_access": false
}
},
{
  "name": "ap1",
  "vsName": "vs2",
  "enabled": false,
  "mandatory": true,
  "scope": {
    "max_file_size": 2147483648,
    "include_extensions": [
      "*"
    ],
    "scan_without_extension": true,
    "scan_readonly_volumes": false,
    "only_execute_access": false
  }
}
],
"on_demand_policies": [
  {
    "name": "t1",
    "scan_paths": [
      "/vol1"
    ],
    "log_path": "/vol1",
    "scope": {
      "max_file_size": 10737418240,
      "include_extensions": [
        "*"
      ],
      "scan_without_extension": true
    }
  }
]
}
-----

```

```
=== Creating a Vscan configuration
```

```
----
```

```
# The API:
```

```
/api/protocols/vscan
```

```
# The call:
```

```
curl -X POST "https://<mgmt-ip>/api/protocols/vscan?return_records=true"
-H "accept: application/json" -H "Content-Type: application/json" -d "{
  \"enabled\": true, \"on_access_policies\": [ { \"enabled\": true,
  \"mandatory\": true, \"name\": \"on-access-test\", \"scope\": {
  \"exclude_extensions\": [ \"mp*\", \"txt\" ], \"exclude_paths\": [
  \"\\\\\\\\vol\" ], \"include_extensions\": [ \"mp*\", \"txt\" ],
  \"max_file_size\": 21474, \"only_execute_access\": false,
  \"scan_readonly_volumes\": false, \"scan_without_extension\": true } } ],
  \"on_demand_policies\": [ { \"log_path\": \"/vol\", \"name\": \"task-1\",
  \"scan_paths\": [ \"/vol\" ], \"schedule\": { \"name\": \"daily\",
  \"uuid\": \"d4984822-17b7-11e9-b450-0050568ecd85\" }, \"scope\": {
  \"exclude_extensions\": [ \"mp3\", \"mp4\" ], \"exclude_paths\": [
  \"/vol\" ], \"include_extensions\": [ \"vmdk\", \"mp*\" ],
  \"max_file_size\": 10737, \"scan_without_extension\": true } } ],
  \"scanner_pools\": [ { \"cluster\": { \"name\": \"Cluster1\", \"uuid\":
  \"ab746d77-17b7-11e9-b450-0050568ecd85\" }, \"name\": \"scanner-1\",
  \"privileged_users\": [ \"cifs\\\\\\\\u1\", \"cifs\\\\\\\\u2\" ], \"role\":
  \"primary\", \"servers\": [ \"1.1.1.1\", \"10.72.204.27\" ] } ], \"svm\":
  { \"name\": \"vs1\", \"uuid\": \"b103be27-17b8-11e9-b451-0050568ecd85\"
  } } }
```

```
# The response:
```

```
{
  \"num_records\": 1,
  \"records\": [
    {
      \"svm\": {
        \"uuid\": \"b103be27-17b8-11e9-b451-0050568ecd85\",
        \"name\": \"vs1\"
      },
      \"enabled\": true,
      \"scanner_pools\": [
        {
          \"name\": \"scanner-1\",
          \"servers\": [
            \"1.1.1.1\",
            \"10.72.204.27\"
          ],
        }
      ],
    }
  ]
}
```

```

    "privileged_users": [
      "cifs\\u1",
      "cifs\\u2"
    ],
    "role": "primary",
    "cluster": {
      "name": "Cluster1",
      "uuid": "ab746d77-17b7-11e9-b450-0050568ecd85"
    }
  },
  "on_access_policies": [
    {
      "name": "on-access-test",
      "enabled": true,
      "mandatory": true,
      "scope": {
        "max_file_size": 21474,
        "exclude_paths": [
          "\\vol"
        ],
        "include_extensions": [
          "mp*",
          "txt"
        ],
        "exclude_extensions": [
          "mp*",
          "txt"
        ],
        "scan_without_extension": true,
        "scan_readonly_volumes": false,
        "only_execute_access": false
      }
    }
  ],
  "on_demand_policies": [
    {
      "name": "task-1",
      "scan_paths": [
        "/vol"
      ],
      "log_path": "/vol",
      "schedule": {
        "uuid": "d4984822-17b7-11e9-b450-0050568ecd85",
        "name": "daily"
      }
    }
  ],

```



```

{
  "svm": {
    "uuid": "b103be27-17b8-11e9-b451-0050568ecd85",
    "name": "vs1"
  },
  "scanner_pools": [
    {
      "name": "scanner-1",
      "servers": [
        "1.1.1.1",
        "10.72.204.27"
      ],
      "privileged_users": [
        "cifs\\u1",
        "cifs\\u2"
      ],
      "role": "primary",
      "cluster": {
        "name": "Cluster1",
        "uuid": "ab746d77-17b7-11e9-b450-0050568ecd85"
      }
    },
    {
      "name": "scanner-2",
      "servers": [
        "1.1.1.5",
        "10.72.3.27"
      ],
      "privileged_users": [
        "cifs\\u3",
        "cifs\\u4"
      ],
      "role": "primary",
      "cluster": {
        "name": "Cluster1",
        "uuid": "ab746d77-17b7-11e9-b450-0050568ecd85"
      }
    }
  ]
}
-----

```

=== Creating multiple Vscan On-access policies for a specified SVM

```

-----

# The API:
/api/protocols/vscan

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/vscan?return_records=true"
-H "accept: application/json" -H "Content-Type: application/json" -d "{
\"on_access_policies\": [ { \"enabled\": false, \"mandatory\": true,
\"name\": \"on-access-test11\", \"scope\": { \"exclude_extensions\": [
\"mp*\", \"txt\" ], \"exclude_paths\": [ \"\\\\\\\\vol\" ],
\"include_extensions\": [ \"mp*\", \"txt\" ], \"max_file_size\": 214748,
\"only_execute_access\": false, \"scan_readonly_volumes\": false,
\"scan_without_extension\": true } }, { \"enabled\": false, \"mandatory\":
true, \"name\": \"on-access-test10\", \"scope\": { \"exclude_extensions\":
[ \"mp*\", \"txt\" ], \"exclude_paths\": [ \"\\\\\\\\vol\" ],
\"include_extensions\": [ \"mp*\", \"txt\" ], \"max_file_size\": 21474,
\"only_execute_access\": false, \"scan_readonly_volumes\": false,
\"scan_without_extension\": true } } ], \"svm\": { \"name\": \"vs1\",
\"uuid\": \"b103be27-17b8-11e9-b451-0050568ecd85\" }}"

# The response:
{
"num_records": 1,
"records": [
{
  "svm": {
    "uuid": "b103be27-17b8-11e9-b451-0050568ecd85",
    "name": "vs1"
  },
  "on_access_policies": [
    {
      "name": "on-access-test11",
      "enabled": false,
      "mandatory": true,
      "scope": {
        "max_file_size": 214748,
        "exclude_paths": [
          "\\\vol"
        ],
        "include_extensions": [
          "mp*",
          "txt"
        ],
        "exclude_extensions": [
          "mp*",

```

```

        "txt"
    ],
    "scan_without_extension": true,
    "scan_readonly_volumes": false,
    "only_execute_access": false
}
},
{
    "name": "on-access-test10",
    "enabled": false,
    "mandatory": true,
    "scope": {
        "max_file_size": 21474,
        "exclude_paths": [
            "\\vol"
        ],
        "include_extensions": [
            "mp*",
            "txt"
        ],
        "exclude_extensions": [
            "mp*",
            "txt"
        ],
        "scan_without_extension": true,
        "scan_readonly_volumes": false,
        "only_execute_access": false
    }
}
]
}
]
}
----

=== Creating multiple Vscan On-demand policies for a specified SVM

----

# The API:
/api/protocols/vscan

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/vscan?return_records=true"
-H "accept: application/json" -H "Content-Type: application/json" -d "{
\"on_demand_policies\": [ { \"log_path\": \"/vol\", \"name\": \"task-1\",

```

```
\\"scan_paths\\": [ \"/vol\" ], \\"schedule\\": { \\"name\\": \\"daily\\",
\\"uuid\\": \\"d4984822-17b7-11e9-b450-0050568ecd85\\", \\"scope\\": {
\\"exclude_extensions\\": [ \\"mp3\\", \\"mp4\\", ], \\"exclude_paths\\": [
\\"/voll\\", ], \\"include_extensions\\": [ \\"vmdk\\", \\"mp*\\", ],
\\"max_file_size\\": 107374, \\"scan_without_extension\\": true } }, {
\\"log_path\\": \"/vol\\", \\"name\\": \\"task-2\\", \\"scan_paths\\": [ \"/vol\\",
], \\"scope\\": { \\"exclude_extensions\\": [ \\"mp3\\", \\"mp4\\", ],
\\"exclude_paths\\": [ \"/voll\\", ], \\"include_extensions\\": [ \\"vmdk\\",
\\"mp*\\", ], \\"max_file_size\\": 107374, \\"scan_without_extension\\": true } }
], \\"svm\\": { \\"name\\": \\"vs1\\", \\"uuid\\": \\"b103be27-17b8-11e9-b451-
0050568ecd85\\", } }"
```

# The response:

```
{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "uuid": "b103be27-17b8-11e9-b451-0050568ecd85",
        "name": "vs1"
      },
      "on_demand_policies": [
        {
          "name": "task-1",
          "scan_paths": [
            "/vol"
          ],
          "log_path": "/vol",
          "schedule": {
            "uuid": "d4984822-17b7-11e9-b450-0050568ecd85",
            "name": "daily"
          },
          "scope": {
            "max_file_size": 107374,
            "exclude_paths": [
              "/voll"
            ],
            "include_extensions": [
              "vmdk",
              "mp*"
            ],
            "exclude_extensions": [
              "mp3",
              "mp4"
            ],
            "scan_without_extension": true
          }
        }
      ]
    }
  ]
}
```





```
# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/vscan/03ce5c36-f269-11e8-8852-0050568e5298" -H "accept: application/json" -H "Content-Type: application/json" -d "{\"cache_clear\": true}"
-----
```

=== Deleting the Vscan configuration for a specified SVM

```
-----

# The API:
/api/protocols/vscan/{svm.uuid}
```

```
# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/vscan/03ce5c36-f269-11e8-8852-0050568e5298" -H "accept: application/json"
-----
```

```
[[IDc2198b2c580fd1e993e456e4b58fe17a]]
= Retrieve the Vscan configuration
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/vscan`#
```

\*Introduced In:\* 9.6

Retrieves the Vscan configuration.

This includes scanner-pools, On-Access policies, On-Demand policies, and information about whether a Vscan is enabled or disabled on an SVM.

Important notes:

- \* You can enable only one Vscan configuration at a time for an SVM.
- \* You can only query using `svm.uuid` or `svm.name`.

== Related ONTAP commands

- \* `vserver vscan show`
- \* `vserver vscan scanner-pool show`
- \* `vserver vscan scanner-pool servers show`
- \* `vserver vscan scanner-pool privileged-users show`
- \* `vserver vscan scanner-pool show-active`
- \* `vserver vscan on-access-policy show`

```
* `vserver vscan on-access-policy file-ext-to-exclude show`  
* `vserver vscan on-access-policy file-ext-to-include show`  
* `vserver vscan on-access-policy paths-to-exclude show`  
* `vserver vscan on-demand-task show`
```

== Learn more

```
* xref:{relative_path}protocols_vscan_endpoint_overview.html[DOC  
/protocols/vscan]  
* xref:{relative_path}protocols_vscan_svm.uuid_scanner-  
pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-  
pools]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|on_access_policies.name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by on_access_policies.name
```

```
|on_access_policies.scope.only_execute_access
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|Filter by on_access_policies.scope.only_execute_access
```

```
|on_access_policies.scope.include_extensions
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by on_access_policies.scope.include_extensions
```

```
|on_access_policies.scope.exclude_extensions
```

```
|string
|query
|False
a|Filter by on_access_policies.scope.exclude_extensions

|on_access_policies.scope.scan_readonly_volumes
|boolean
|query
|False
a|Filter by on_access_policies.scope.scan_readonly_volumes

|on_access_policies.scope.exclude_paths
|string
|query
|False
a|Filter by on_access_policies.scope.exclude_paths

|on_access_policies.scope.max_file_size
|integer
|query
|False
a|Filter by on_access_policies.scope.max_file_size

|on_access_policies.scope.scan_without_extension
|boolean
|query
|False
a|Filter by on_access_policies.scope.scan_without_extension

|on_access_policies.mandatory
|boolean
|query
|False
a|Filter by on_access_policies.mandatory

|on_access_policies.enabled
|boolean
|query
|False
a|Filter by on_access_policies.enabled
```

```
|enabled
|boolean
|query
|False
a|Filter by enabled
```

```
|on_demand_policies.scan_paths
|string
|query
|False
a|Filter by on_demand_policies.scan_paths
```

```
|on_demand_policies.log_path
|string
|query
|False
a|Filter by on_demand_policies.log_path
```

```
|on_demand_policies.scope.include_extensions
|string
|query
|False
a|Filter by on_demand_policies.scope.include_extensions
```

```
|on_demand_policies.scope.scan_without_extension
|boolean
|query
|False
a|Filter by on_demand_policies.scope.scan_without_extension
```

```
|on_demand_policies.scope.max_file_size
|integer
|query
|False
a|Filter by on_demand_policies.scope.max_file_size
```

```
|on_demand_policies.scope.exclude_paths
|string
|query
|False
```

```
a|Filter by on_demand_policies.scope.exclude_paths
```

```
|on_demand_policies.scope.exclude_extensions
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by on_demand_policies.scope.exclude_extensions
```

```
|on_demand_policies.schedule.name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by on_demand_policies.schedule.name
```

```
|on_demand_policies.schedule.uuid
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by on_demand_policies.schedule.uuid
```

```
|on_demand_policies.name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by on_demand_policies.name
```

```
|scanner_pools.cluster.name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by scanner_pools.cluster.name
```

```
|scanner_pools.cluster.uuid
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by scanner_pools.cluster.uuid
```

```
|scanner_pools.role
```

```
|string
```

```
|query
|False
a|Filter by scanner_pools.role

|scanner_pools.privileged_users
|string
|query
|False
a|Filter by scanner_pools.privileged_users

|scanner_pools.name
|string
|query
|False
a|Filter by scanner_pools.name

|scanner_pools.servers
|string
|query
|False
a|Filter by scanner_pools.servers

|svm.uuid
|string
|query
|False
a|Filter by svm.uuid

|svm.name
|string
|query
|False
a|Filter by svm.name

|fields
|array[string]
|query
|False
a|Specify the fields to return.
```

```
|max_records
|integer
|query
|False
a|Limit the number of records returned.
```

```
|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.
```

```
* Default value: 1
```

```
|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds. ONTAP
returns earlier if either max records or the end of the collection is
reached.
```

```
* Default value: 1
```

```
* Max value: 120
```

```
* Min value: 0
```

```
|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.
```

```
|===
```

```
== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
```

```
|===
```



```
|Name
|Type
|Description
```

```
 |_links
|link:#_links[_links]
a|
```

```
|num_records
|integer
a|Number of records
```

```
|records
|array[link:#vscan[vscan]]
a|
```

```
|===
```

```
.Example response
[%collapsible%closed]
=====
```

```
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "on_access_policies": {
      "name": "on-access-test",
      "scope": {
        "exclude_extensions": [
          "mp*",
          "txt"
        ]
      }
    }
  }
}
```

```

    "exclude_paths": [
      "\\dir1\\dir2\\name",
      "\\vol\\a b",
      "\\vol\\a,b\\"
    ],
    "include_extensions": [
      "mp*",
      "txt"
    ],
    "max_file_size": "2147483648"
  }
},
"on_demand_policies": {
  "log_path": "/vol0/report_dir",
  "name": "task-1",
  "scan_paths": [
    "/vol1/",
    "/vol2/cifs/"
  ],
  "schedule": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "weekly",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "scope": {
    "exclude_extensions": [
      "mp3",
      "mp4"
    ],
    "exclude_paths": [
      "/vol1/cold-files/",
      "/vol1/cifs/names"
    ],
    "include_extensions": [
      "vmdk",
      "mp*"
    ],
    "max_file_size": "10737418240"
  }
},
"scanner_pools": {
  "cluster": {

```

```

    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "cluster1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "name": "scanner-1",
  "privileged_users": [
    "cifs\\u1",
    "cifs\\u2"
  ],
  "role": "primary",
  "servers": [
    "1.1.1.1",
    "10.72.204.27",
    "vmwin204-27.fsct.nb"
  ]
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]

```

```

a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]

```

```

[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:href[href]
a|

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```
|exclude_extensions  
|array[string]  
a|List of file extensions for which scanning is not performed.
```

```
|exclude_paths  
|array[string]  
a|List of file paths for which scanning must not be performed.
```

```
|include_extensions  
|array[string]  
a|List of file extensions to be scanned.
```

```
|max_file_size  
|integer  
a|Maximum file size, in bytes, allowed for scanning.
```

```
|only_execute_access  
|boolean  
a|Scan only files opened with execute-access.
```

```
|scan_readonly_volumes  
|boolean  
a|Specifies whether or not read-only volume can be scanned.
```

```
|scan_without_extension  
|boolean  
a|Specifies whether or not files without any extension can be scanned.
```

```
|===
```

```
[#vscan_on_access]  
[.api-collapsible-fifth-title]  
vscan_on_access
```

An On-Access policy that defines the scope of an On-Access scan. Use On-Access scanning to check for viruses when clients open, read, rename, or close files over CIFS. By default, ONTAP creates an On-Access policy named "default\_CIFS" and enables it for all the SVMs in a cluster.

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Status of the On-Access Vscan policy

|mandatory
|boolean
a|Specifies if scanning is mandatory. File access is denied if there are
no external virus-scanning servers available for virus scanning.

|name
|string
a|On-Access policy ame

|scope
|link:#scope[scope]
a|

|===

[#schedule]
[.api-collapsible-fifth-title]
schedule

Schedule of the task.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

```

```

|name
|string
a|Job schedule name

|uuid
|string
a|Job schedule UUID

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.

|include_extensions
|array[string]
a|List of file extensions to be scanned.

|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.

|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.

```



```
|===
```

```
[#vscan_on_demand]  
[.api-collapsible-fifth-title]  
vscan_on_demand
```

Use On-Demand scanning to check files for viruses on a schedule. An On-Demand policy defines the scope of an On-Demand scan.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|log_path
```

```
|string
```

```
a|The path from the Vserver root where the task report is created.
```

```
|name
```

```
|string
```

```
a|On-Demand task name
```

```
|scan_paths
```

```
|array[string]
```

```
a|List of paths that need to be scanned.
```

```
|schedule
```

```
|link:#schedule[schedule]
```

```
a|Schedule of the task.
```

```
|scope
```

```
|link:#scope[scope]
```

```
a|
```

```
|===
```

```
[#cluster_reference]  
[.api-collapsible-fifth-title]
```

## cluster\_reference

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
 |_links
```

```
 |link:#_links[_links]
```

```
 a|
```

```
 |name
```

```
 |string
```

```
 a|
```

```
 |uuid
```

```
 |string
```

```
 a|
```

```
|===
```

```
[#vscan_scanner_pool]
```

```
[.api-collapsible-fifth-title]
```

```
vscan_scanner_pool
```

Scanner pool is a set of attributes which are used to validate and manage connections between clustered ONTAP and external virus-scanning server, or "Vscan server".

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
 |cluster
```

```
 |link:#cluster_reference[cluster_reference]
```

```
 a|
```

```
 |name
```

```
 |string
```

```
 a|Specifies the name of the scanner pool. Scanner pool name can be up to 256 characters long and is a string that can only contain any combination of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "_", "-" and ".".
```

```
|privileged_users
|array[string]
a|Specifies a list of privileged users. A valid form of privileged user-
name is "domain-name\user-name". Privileged user-names are stored and
treated as case-insensitive strings. Virus scanners must use one of the
registered privileged users for connecting to clustered Data ONTAP for
exchanging virus-scanning protocol messages and to access file for
scanning, remedying and quarantining operations.
```

```
* example: ["cifs\u1", "cifs\u2"]
```

```
* Introduced in: 9.6
```

```
* x-omitempty: true
```

```
|role
```

```
|string
```

```
a|Specifies the role of the scanner pool. The possible values are:
```

```
*** primary - Always active.
```

```
*** secondary - Active only when none of the primary external virus-
scanning servers are connected.
```

```
*** idle - Always inactive.
```

```
|servers
```

```
|array[string]
```

```
a|Specifies a list of IP addresses or FQDN for each Vscan server host
names which are allowed to connect to clustered ONTAP.
```

```
* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]
```

```
* Introduced in: 9.6
```

```
* x-omitempty: true
```

```
|===
```

```
[#svm]
```

```
[.api-collapsible-fifth-title]
```

```
svm
```

```
SVM, applies only to SVM-scoped objects.
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|The name of the SVM.
```

```
|uuid
```

```
|string
```

```
a|The unique identifier of the SVM.
```

```
|===
```

```
[#vscan]
```

```
[.api-collapsible-fifth-title]
```

```
vscan
```

Vscan can be used to protect data from being compromised by viruses or other malicious code. This combines best-in-class third-party antivirus software with ONTAP features that give you the flexibility you need to control which files get scanned and when. Storage systems offload scanning operations to external servers hosting antivirus software from thirdparty vendors. An Antivirus Connector on the external server handles communications between the storage system and the antivirus software.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```

|cache_clear
|boolean
a|Discards the cached information of the files that have been successfully
scanned. Once the cache is cleared, files are scanned again when they are
accessed. PATCH only

|enabled
|boolean
a|Specifies whether or not Vscan is enabled on the SVM.

|on_access_policies
|array[link:#vscan_on_access[vscan_on_access]]
a|

|on_demand_policies
|array[link:#vscan_on_demand[vscan_on_demand]]
a|

|scanner_pools
|array[link:#vscan_scanner_pool[vscan_scanner_pool]]
a|

|svm
|link:#svm[svm]
a|SVM, applies only to SVM-scoped objects.

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

```

```

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDc7803021509b5e9067979efce29d3125]]

```

= Create a Vscan configuration

```
[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-block]#`/protocols/vscan`#
```

\*Introduced In:\* 9.6

Creates a Vscan configuration, which includes a list of scanner-pools, Vscan On-Access policies and Vscan On-Demand policies. Defines whether the Vscan configuration you create is enabled or disabled for a specified SVM.

Important notes:

- \* You can enable only one Vscan configuration at a time for an SVM.
- \* There needs to be at least one active scanner-pool and one enabled On-Access policy to enable Vscan successfully.
- \* By default, a Vscan is enabled when it's created.
- \* By default, the Vscan On-Access policies created from this endpoint are in the disabled state. You can use the On-Access policy PATCH endpoint to enable a particular On-Access policy. In ONTAP 9.6, only one Vscan On-Access policy can be enabled and only one Vscan On-Demand policy can be scheduled on an SVM.

== Required properties

- \* `svm.uuid` or `svm.name` - Existing SVM in which to create the Vscan configuration.

== Recommended optional properties

- \* `scanner\_pools` - There must be at least one active scanner-pool for Vscan configuration. Created either through Vscan POST operation or scanner-pools POST operation.

== Default property values

If not specified in POST, the following default property value is assigned:

- \* `enabled` - `_true_`

== Related ONTAP commands

- \* `vserver vscan enable`
- \* `vserver vscan scanner-pool create`
- \* `vserver vscan scanner-pool apply-policy`
- \* `vserver vscan scanner-pool servers add`

```
* `vserver vscan scanner-pool privileged-users add`
* `vserver vscan on-access-policy create`
* `vserver vscan on-access-policy file-ext-to-exclude add`
* `vserver vscan on-access-policy file-ext-to-include add`
* `vserver vscan on-access-policy paths-to-exclude add`
* `vserver vscan on-demand-task create`
```

== Learn more

```
* xref:{relative_path}protocols_vscan_endpoint_overview.html[DOC
/protocols/vscan]
* xref:{relative_path}protocols_vscan_svm.uuid_scanner-
pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-
pools]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|return_records
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|The default is false. If set to true, the records are returned.
```

```
* Default value:
```

```
|===
```

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```



```

|_links
|link:#_links[_links]
a|

|cache_clear
|boolean
a|Discards the cached information of the files that have been successfully
scanned. Once the cache is cleared, files are scanned again when they are
accessed. PATCH only

|enabled
|boolean
a|Specifies whether or not Vscan is enabled on the SVM.

|on_access_policies
|array[link:#vscan_on_access[vscan_on_access]]
a|

|on_demand_policies
|array[link:#vscan_on_demand[vscan_on_demand]]
a|

|scanner_pools
|array[link:#vscan_scanner_pool[vscan_scanner_pool]]
a|

|svm
|link:#svm[svm]
a|SVM, applies only to SVM-scoped objects.

|===

.Example request
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "on_access_policies": {

```

```

"name": "on-access-test",
"scope": {
  "exclude_extensions": [
    "mp*",
    "txt"
  ],
  "exclude_paths": [
    "\\dir1\\dir2\\name",
    "\\vol\\a b",
    "\\vol\\a,b\\"
  ],
  "include_extensions": [
    "mp*",
    "txt"
  ],
  "max_file_size": "2147483648"
}
},
"on_demand_policies": {
  "log_path": "/vol0/report_dir",
  "name": "task-1",
  "scan_paths": [
    "/vol1/",
    "/vol2/cifs/"
  ],
  "schedule": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "weekly",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "scope": {
    "exclude_extensions": [
      "mp3",
      "mp4"
    ],
    "exclude_paths": [
      "/vol1/cold-files/",
      "/vol1/cifs/names"
    ],
    "include_extensions": [
      "vmdk",
      "mp*"
    ]
  }
}

```

```

    ],
    "max_file_size": "10737418240"
  }
},
"scanner_pools": {
  "cluster": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "cluster1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "name": "scanner-1",
  "privileged_users": [
    "cifs\\u1",
    "cifs\\u2"
  ],
  "role": "primary",
  "servers": [
    "1.1.1.1",
    "10.72.204.27",
    "vmwin204-27.fsct.nb"
  ]
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
====

== Response

```

Status: 201, Created

```

[cols=3*,options=header]
|====
|Name

```

```

|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#vscan[vscan]]
a|

```

```
|===
```

.Example response

[%collapsible%closed]

```
=====
```

[source,json,subs=+macros]

```

{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "on_access_policies": {
      "name": "on-access-test",
      "scope": {
        "exclude_extensions": [
          "mp*",
          "txt"
        ],
        "exclude_paths": [

```

```

        "\\dir1\\dir2\\name",
        "\\vol\\a b",
        "\\vol\\a,b\\"
    ],
    "include_extensions": [
        "mp*",
        "txt"
    ],
    "max_file_size": "2147483648"
}
},
"on_demand_policies": {
    "log_path": "/vol0/report_dir",
    "name": "task-1",
    "scan_paths": [
        "/vol1/",
        "/vol2/cifs/"
    ],
    "schedule": {
        "_links": {
            "self": {
                "href": "/api/resourcelink"
            }
        },
        "name": "weekly",
        "uuid": "1cd8a442-86d1-11e0-aelc-123478563412"
    },
    "scope": {
        "exclude_extensions": [
            "mp3",
            "mp4"
        ],
        "exclude_paths": [
            "/vol1/cold-files/",
            "/vol1/cifs/names"
        ],
        "include_extensions": [
            "vmdk",
            "mp*"
        ],
        "max_file_size": "10737418240"
    }
},
"scanner_pools": {
    "cluster": {
        "_links": {

```

```

        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "cluster1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"name": "scanner-1",
"privileged_users": [
    "cifs\\u1",
    "cifs\\u2"
],
"role": "primary",
"servers": [
    "1.1.1.1",
    "10.72.204.27",
    "vmwin204-27.fsct.nb"
]
},
"svm": {
    "_links": {
        "self": {
            "href": "/api/resourcelink"
        }
    },
    "name": "svm1",
    "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
}
=====

```

== Error

## Status: Default

```

ONTAP Error Response Codes
//start table
[cols=2*,options=header]
|===
//header
| Error Code | Description
//end header
//end row
//start row

```

```

|10027259 +
//end row
//start row
|A scanner-pool, an On-Access policy, or an On-Demand policy might fail to
get created due to either a systematic error or some hardware failure. The
error code returned details the failure along with the reason for the
failure. For example, if a scanner-pool fails due to an incorrect cluster
name, then the error might read: "Failed to create scanner-pool "scanner-
1". Reason: "Cluster uuid points to different cluster name instead of the
cluster-name supplied.". Retry the operation."
//end row
//start row
|10027260 +
//end row
//start row
|If a scanner-pool, an On-Access policy or an On-Demand policy specified
in the input already exists, then a duplicate error is returned. For
example, if a scanner-pool "scanner-1" already exists for an SVM and is
again specified in the input, the error message will read: " Failed to
create scanner-pool "scanner-1" as the specified entry already exists.
Delete the entry and retry the POST operation."
//end row
//start row
|2621462 +
//end row
//start row
|The specified SVM name is invalid
//end row
//start row
|2621706 +
//end row
//start row
|The specified svm.uuid is either invalid or belongs to a different SVM
//end row
//start row
|10027015 +
//end row
//start row
|Attempting to enable a Vscan but no active scanner-pool exists for the
specified SVM
//end row
//start row
|10027011 +
//end row
//start row
|Attempting to enable a Vscan for an SVM for which no CIFS server exists

```

```
//end row
//start row
|10027023 +
//end row
//start row
|Attempting to enable a Vscan for an SVM for which no active Vscan On-
Access policy exist
//end row
|===
//end table
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

```
====
```

```
== Definitions
```

```
[.api-def-first-level]
```



```

.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```
|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.
```

```
|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.
```

```
|include_extensions
|array[string]
a|List of file extensions to be scanned.
```

```
|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.
```

```
|only_execute_access
|boolean
a|Scan only files opened with execute-access.
```

```
|scan_readonly_volumes
|boolean
a|Specifies whether or not read-only volume can be scanned.
```

```
|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.
```

```
|===
```

```
[#vscan_on_access]
[.api-collapsible-fifth-title]
vscan_on_access
```

An On-Access policy that defines the scope of an On-Access scan. Use On-Access scanning to check for viruses when clients open, read, rename, or close files over CIFS. By default, ONTAP creates an On-Access policy named "default\_CIFS" and enables it for all the SVMs in a cluster.

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Status of the On-Access Vscan policy

|mandatory
|boolean
a|Specifies if scanning is mandatory. File access is denied if there are
no external virus-scanning servers available for virus scanning.

|name
|string
a|On-Access policy ame

|scope
|link:#scope[scope]
a|

|===

[#schedule]
[.api-collapsible-fifth-title]
schedule

Schedule of the task.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

```

```
|name  
|string  
a|Job schedule name
```

```
|uuid  
|string  
a|Job schedule UUID
```

```
|===
```

```
[#scope]  
[.api-collapsible-fifth-title]  
scope
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|exclude_extensions  
|array[string]  
a|List of file extensions for which scanning is not performed.
```

```
|exclude_paths  
|array[string]  
a|List of file paths for which scanning must not be performed.
```

```
|include_extensions  
|array[string]  
a|List of file extensions to be scanned.
```

```
|max_file_size  
|integer  
a|Maximum file size, in bytes, allowed for scanning.
```

```
|scan_without_extension  
|boolean  
a|Specifies whether or not files without any extension can be scanned.
```

```
|===
```

```
[#vscan_on_demand]  
[.api-collapsible-fifth-title]  
vscan_on_demand
```

Use On-Demand scanning to check files for viruses on a schedule. An On-Demand policy defines the scope of an On-Demand scan.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|log_path
```

```
|string
```

```
a|The path from the Vserver root where the task report is created.
```

```
|name
```

```
|string
```

```
a|On-Demand task name
```

```
|scan_paths
```

```
|array[string]
```

```
a|List of paths that need to be scanned.
```

```
|schedule
```

```
|link:#schedule[schedule]
```

```
a|Schedule of the task.
```

```
|scope
```

```
|link:#scope[scope]
```

```
a|
```

```
|===
```

```
[#cluster_reference]
```

```
[.api-collapsible-fifth-title]
```

```
cluster_reference
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|
```

```
|uuid
```

```
|string
```

```
a|
```

```
|===
```

```
[#vscan_scanner_pool]
```

```
[.api-collapsible-fifth-title]
```

```
vscan_scanner_pool
```

Scanner pool is a set of attributes which are used to validate and manage connections between clustered ONTAP and external virus-scanning server, or "Vscan server".

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|cluster
```

```
|link:#cluster_reference[cluster_reference]
```

```
a|
```

```
|name
```

```
|string
```

```
a|Specifies the name of the scanner pool. Scanner pool name can be up to 256 characters long and is a string that can only contain any combination
```

of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "\_", "-" and ".".

|privileged\_users

|array[string]

a|Specifies a list of privileged users. A valid form of privileged user-name is "domain-name\user-name". Privileged user-names are stored and treated as case-insensitive strings. Virus scanners must use one of the registered privileged users for connecting to clustered Data ONTAP for exchanging virus-scanning protocol messages and to access file for scanning, remedying and quarantining operations.

\* example: ["cifs\u1", "cifs\u2"]

\* Introduced in: 9.6

\* x-omitempty: true

|role

|string

a|Specifies the role of the scanner pool. The possible values are:

\*\*\* primary - Always active.

\*\*\* secondary - Active only when none of the primary external virus-scanning servers are connected.

\*\*\* idle - Always inactive.

|servers

|array[string]

a|Specifies a list of IP addresses or FQDN for each Vscan server host names which are allowed to connect to clustered ONTAP.

\* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]

\* Introduced in: 9.6

\* x-omitempty: true

|===

[#svm]

[.api-collapsible-fifth-title]

svm

SVM, applies only to SVM-scoped objects.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|The name of the SVM.
```

```
|uuid
```

```
|string
```

```
a|The unique identifier of the SVM.
```

```
|===
```

```
[#vscan]
```

```
[.api-collapsible-fifth-title]
```

```
vscan
```

Vscan can be used to protect data from being compromised by viruses or other malicious code. This combines best-in-class third-party antivirus software with ONTAP features that give you the flexibility you need to control which files get scanned and when. Storage systems offload scanning operations to external servers hosting antivirus software from thirdparty vendors. An Antivirus Connector on the external server handles communications between the storage system and the antivirus software.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```



```
|cache_clear
|boolean
a|Discards the cached information of the files that have been successfully scanned. Once the cache is cleared, files are scanned again when they are accessed. PATCH only
```

```
|enabled
|boolean
a|Specifies whether or not Vscan is enabled on the SVM.
```

```
|on_access_policies
|array[link:#vscan_on_access[vscan_on_access]]
a|
```

```
|on_demand_policies
|array[link:#vscan_on_demand[vscan_on_demand]]
a|
```

```
|scanner_pools
|array[link:#vscan_scanner_pool[vscan_scanner_pool]]
a|
```

```
|svm
|link:#svm[svm]
a|SVM, applies only to SVM-scoped objects.
```

```
|===
```

```
[#_links]
[.api-collapsible-fifth-title]
_links
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|next
|link:#href[href]
a|
```

```

|self
|link:#href[href]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string

```

```
a|Error code
```

```
|message
```

```
|string
```

```
a|Error message
```

```
|target
```

```
|string
```

```
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
```

```
====
```

```
:leveloffset: -1
```

```
= Manage Vscan configuration
```

```
:leveloffset: +1
```

```
[[ID67ebed08dfc0cd43739d39eea56dda1d]]
```

```
= Protocols Vscan server-status endpoint overview
```

```
== Overview
```

This API is used to display connection status information for the external virus-scanning servers or "Vscan servers".

```
== Examples
```

```
=== Retrieving all fields for the Vscan server status
```

```
'''
```

```
----
```

```

# The API:
/api/protocols/vscan/server_status/

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/vscan/server_status?fields=*"
-H "accept: application/hal+json"

# The response:
{
"records": [
  {
    "svm": {
      "uuid": "86fbc414-f140-11e8-8e22-0050568e0945",
      "name": "vs1",
      "_links": {
        "self": {
          "href": "/api/svm/svms/86fbc414-f140-11e8-8e22-0050568e0945"
        }
      }
    },
    "node": {
      "uuid": "fe696362-f138-11e8-8e22-0050568e0945",
      "name": "Cluster-01",
      "_links": {
        "self": {
          "href": "/api/cluster/nodes/fe696362-f138-11e8-8e22-0050568e0945"
        }
      }
    },
    "ip": "10.141.46.173",
    "type": "primary",
    "state": "disconnected",
    "disconnected_reason": "unknown",
    "_links": {
      "self": {
        "href": "/api/protocols/vscan/server_status/86fbc414-f140-11e8-8e22-0050568e0945/Cluster-01/10.141.46.173"
      }
    }
  },
  {
    "svm": {
      "uuid": "86fbc414-f140-11e8-8e22-0050568e0945",
      "name": "vs1",
      "_links": {

```

```

    "self": {
      "href": "/api/svm/svms/86fbc414-f140-11e8-8e22-0050568e0945"
    }
  },
  "node": {
    "uuid": "fe696362-f138-11e8-8e22-0050568e0945",
    "name": "Cluster-01",
    "_links": {
      "self": {
        "href": "/api/cluster/nodes/fe696362-f138-11e8-8e22-
0050568e0945"
      }
    }
  },
  "ip": "fd20:8b1e:b255:5053::46:173",
  "type": "primary",
  "state": "disconnected",
  "disconnected_reason": "remote_closed",
  "_links": {
    "self": {
      "href": "/api/protocols/vscan/server_status/86fbc414-f140-11e8-
8e22-0050568e0945/Cluster-01/fd20%3A8b1e%3Ab255%3A5053%3A%3A46%3A173"
    }
  }
],
"num_records": 2,
"_links": {
  "self": {
    "href": "/api/protocols/vscan/server_status?fields=*"
  }
}
}
----

'''

=== Retrieving the server status information for the server with IP
address 10.141.46.173

'''

----

# The API:

```

```
/api/protocols/vscan/server_status
```

```
# The call:
```

```
curl -X GET "https://<mgmt-  
ip>/api/protocols/vscan/server_status?ip=10.141.46.173&fields=*" -H  
"accept: application/hal+json"
```

```
# The response:
```

```
{  
  "records": [  
    {  
      "svm": {  
        "uuid": "86fbc414-f140-11e8-8e22-0050568e0945",  
        "name": "vs1",  
        "_links": {  
          "self": {  
            "href": "/api/svm/svms/86fbc414-f140-11e8-8e22-0050568e0945"  
          }  
        }  
      },  
      "node": {  
        "uuid": "fe696362-f138-11e8-8e22-0050568e0945",  
        "name": "Cluster-01",  
        "_links": {  
          "self": {  
            "href": "/api/cluster/nodes/fe696362-f138-11e8-8e22-  
0050568e0945"  
          }  
        }  
      },  
      "ip": "10.141.46.173",  
      "type": "primary",  
      "state": "connected",  
      "update_time": "2018-12-19T08:03:40.988Z",  
      "vendor": "XYZ",  
      "version": "1.12.2",  
      "_links": {  
        "self": {  
          "href": "/api/protocols/vscan/server_status/86fbc414-f140-11e8-  
8e22-0050568e0945/Cluster-01/10.141.46.173"  
        }  
      }  
    }  
  ],  
  "num_records": 1,  
  "_links": {
```

```
"self": {
  "href": "/api/protocols/vscan/server_status?ip=10.141.46.173&fields="
}
}
}
----
'''
```

[[ID28be709cf9e9000e012daf3fcae4b795]]

= Retrieve the Vscan server status

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/vscan/server-status`#

\*Introduced In:\* 9.6

Retrieves a Vscan server status.

== Related ONTAP commands

\* `vserver vscan connection-status show-all`

== Learn more

\* xref:{relative\_path}protocols\_vscan\_server-status\_endpoint\_overview.html[DOC /protocols/vscan/server-status]

== Parameters

[cols=5\*,options=header]

|===

|Name

|Type

|In

|Required

|Description

|node.name

|string

|query

```
|False  
a|Filter by node.name
```

```
|node.uuid  
|string  
|query  
|False  
a|Filter by node.uuid
```

```
|svm.uuid  
|string  
|query  
|False  
a|Filter by svm.uuid
```

```
|svm.name  
|string  
|query  
|False  
a|Filter by svm.name
```

```
|vendor  
|string  
|query  
|False  
a|Filter by vendor
```

```
|state  
|string  
|query  
|False  
a|Filter by state
```

```
|ip  
|string  
|query  
|False  
a|Filter by ip
```

```
|disconnected_reason
```



```
|string  
|query  
|False  
a|Filter by disconnected_reason
```

```
|version  
|string  
|query  
|False  
a|Filter by version
```

```
|update_time  
|string  
|query  
|False  
a|Filter by update_time
```

```
|type  
|string  
|query  
|False  
a|Filter by type
```

```
|fields  
|array[string]  
|query  
|False  
a|Specify the fields to return.
```

```
|max_records  
|integer  
|query  
|False  
a|Limit the number of records returned.
```

```
|return_records  
|boolean  
|query  
|False  
a|The default is true for GET calls. When set to false, only the number  
of records is returned.
```

\* Default value: 1

|return\_timeout  
|integer  
|query  
|False

a|The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.

\* Default value: 1

\* Max value: 120

\* Min value: 0

|order\_by  
|array[string]  
|query  
|False

a|Order results by specified fields and optional [asc|desc] direction. Default direction is 'asc' for ascending.

|===

== Response

Status: 200, Ok

[cols=3\*,options=header]

|===

|Name  
|Type  
|Description

|\_links  
|link:#\_links[\_links]

a|

|num\_records  
|integer  
a|Number of records

```

|records
|array[link:#vscan_server_status[vscan_server_status]]
a|

|===

.Example response
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "node": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "node1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "svm": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "svm1",
      "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
    },
    "type": "primary"
  }
}
=====

== Error

```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
```

```

|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:href[href]
a|

|===

```

```
[#node]
[.api-collapsible-fifth-title]
node
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|name
|string
a|
```

```
|uuid
|string
a|
```

```
|===
```

```
[#svm]
[.api-collapsible-fifth-title]
svm
```

SVM, applies only to SVM-scoped objects.

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|name
|string
a|The name of the SVM.
```

```
|uuid
|string
a|The unique identifier of the SVM.
```

```
|===
```

```
[#vscan_server_status]
[.api-collapsible-fifth-title]
vscan_server_status
```

Displays the connection status information of the external virus-scanning servers.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|disconnected_reason
|string
```

a|Specifies the server disconnected reason.

The following is a list of the possible reasons:

* unknown	- Disconnected, unknown reason.
* vscan_disabled	- Disconnected, Vscan is disabled on the SVM.
* no_data_lif	- Disconnected, SVM does not have data LIF.
* session_uninitialized	- Disconnected, session is not initialized.
* remote_closed	- Disconnected, server has closed the connection.
* invalid_protocol_msg	- Disconnected, invalid protocol message received.
* invalid_session_id	- Disconnected, invalid session ID received.
* inactive_connection	- Disconnected, no activity on connection.
* invalid_user	- Connection request by an invalid user.
* server_removed	- Disconnected, server has been removed from the active Scanners List.

enum:

- \* unknown
- \* vscan\_disabled
- \* no\_data\_lif
- \* session\_uninitialized

```
* remote_closed
* invalid_protocol_msg
* invalid_session_id
* inactive_connection
* invalid_user
* server_removed
```

```
|ip
|string
a|IP address of the Vscan server.
```

```
|node
|link:#node[node]
a|
```

```
|state
|string
a|Specifies the server connection state indicating if it is in the
connected or disconnected state.
The following is a list of the possible states:
```

```
* connected           - Connected
* disconnected         - Disconnected
enum:
* connected
* disconnected
```

```
|svm
|link:#svm[svm]
a|SVM, applies only to SVM-scoped objects.
```

```
|type
|string
a|Server type. The possible values are:
```

```
*** primary - Primary server
*** backup  - Backup server
```

```
|update_time
|string
a|Specifies the time the server is in the connected or disconnected state.
```



```
|vendor
|string
a|Name of the connected virus-scanner vendor.
```

```
|version
|string
a|Version of the connected virus-scanner.
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[ID326e70e562a79e98430b0c76f2617876]]
= Delete a Vscan configuration
```

```
[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}`#
```

\*Introduced In:\* 9.6

Deletes a Vscan configuration.

Important notes:

\* The Vscan DELETE endpoint deletes all of the Vscan configuration of an SVM. It first disables the Vscan and then deletes all of the SVM scanner-pools, On-Access policies, and On-Demand policies.

\* Disable the active Vscan On-Access policy on an SVM before performing the Vscan delete operation on that SVM.

== Related ONTAP commands

```
* `vserver vscan scanner-pool delete`  
* `vserver vscan on-access-policy delete`  
* `vserver vscan on-demand-policy delete`
```

== Learn more

```
* xref:{relative_path}protocols_vscan_endpoint_overview.html[DOC  
/protocols/vscan]  
* xref:{relative_path}protocols_vscan_svm.uuid_scanner-  
pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-  
pools]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```

== Response

Status: 200, Ok

== Error

Status: Default

ONTAP Error Response Codes

```
//start table
```

```
[cols=2*,options=header]
```

```

|===
//header
| Error Code | Description
//end header
//end row
//start row
|10027259 +
//end row
//start row
|A scanner-pool, an On-Access policy, or an On-Demand policy might fail to
get deleted due to either a systematic error or some hardware failure. The
error code returned details the failure along with the reason for the
failure. For example, "Failed to delete On-Access policy "spl". Reason:
"Failed to delete policy. Reason: policy must be disabled before being
deleted.". Retry the operation."
//end row
|===
//end table

```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",

```

```

    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]

```

```
a|Message arguments
```

```
|code
```

```
|string
```

```
a|Error code
```

```
|message
```

```
|string
```

```
a|Error message
```

```
|target
```

```
|string
```

```
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
```

```
====
```

```
[[IDc05f0e8554ffbc0094871ddbfb64a857]]
```

```
= Retrieve the Vscan configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-  
block]#`/protocols/vscan/{svm.uuid}`#
```

```
*Introduced In:* 9.6
```

Retrieves the Vscan configuration for a specified SVM.

This includes scanner-pools, On-Access policies, On-Demand policies, and information about whether a Vscan is enabled or disabled on an SVM.

Important note:

\* You can enable only one Vscan configuration at a time for an SVM.

```
== Related ONTAP commands
```

```
* `vserver vscan show`
```

```
* `vserver vscan scanner-pool show`
```

```
* `vserver vscan scanner-pool servers show`
```

```
* `vserver vscan scanner-pool privileged-users show`
* `vserver vscan scanner-pool show-active`
* `vserver vscan on-access-policy show`
* `vserver vscan on-access-policy file-ext-to-exclude show`
* `vserver vscan on-access-policy file-ext-to-include show`
* `vserver vscan on-access-policy paths-to-exclude show`
* `vserver vscan on-demand-task show`
```

== Learn more

```
* xref:{relative_path}protocols_vscan_endpoint_overview.html[DOC
/protocols/vscan]
* xref:{relative_path}protocols_vscan_svm.uuid_scanner-
pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-
pools]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
|Type
|In
|Required
|Description
```

```
|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.
```

```
|fields
|array[string]
|query
|False
a|Specify the fields to return.
```

```
|===
```

== Response

Status: 200, Ok

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|cache_clear
|boolean
a|Discards the cached information of the files that have been successfully
scanned. Once the cache is cleared, files are scanned again when they are
accessed. PATCH only

|enabled
|boolean
a|Specifies whether or not Vscan is enabled on the SVM.

|on_access_policies
|array[link:#vscan_on_access[vscan_on_access]]
a|

|on_demand_policies
|array[link:#vscan_on_demand[vscan_on_demand]]
a|

|scanner_pools
|array[link:#vscan_scanner_pool[vscan_scanner_pool]]
a|

|svm
|link:#svm[svm]
a|SVM, applies only to SVM-scoped objects.

|===

.Example response
[%collapsible%closed]
=====
[source,json,subs=+macros]

```



```

{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "on_access_policies": {
    "name": "on-access-test",
    "scope": {
      "exclude_extensions": [
        "mp*",
        "txt"
      ],
      "exclude_paths": [
        "\\dir1\\dir2\\name",
        "\\vol\\a b",
        "\\vol\\a,b\\"
      ],
      "include_extensions": [
        "mp*",
        "txt"
      ],
      "max_file_size": "2147483648"
    }
  },
  "on_demand_policies": {
    "log_path": "/vol0/report_dir",
    "name": "task-1",
    "scan_paths": [
      "/vol1/",
      "/vol2/cifs/"
    ],
    "schedule": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "weekly",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "scope": {
      "exclude_extensions": [
        "mp3",
        "mp4"
      ],
    }
  }
}

```

```

    "exclude_paths": [
      "/voll/cold-files/",
      "/voll/cifs/names"
    ],
    "include_extensions": [
      "vmdk",
      "mp*"
    ],
    "max_file_size": "10737418240"
  }
},
"scanner_pools": {
  "cluster": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "cluster1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "name": "scanner-1",
  "privileged_users": [
    "cifs\\u1",
    "cifs\\u2"
  ],
  "role": "primary",
  "servers": [
    "1.1.1.1",
    "10.72.204.27",
    "vmwin204-27.fsct.nb"
  ]
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
====

== Error

```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
```

```

|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.

```

```
|include_extensions
|array[string]
a|List of file extensions to be scanned.
```

```
|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.
```

```
|only_execute_access
|boolean
a|Scan only files opened with execute-access.
```

```
|scan_readonly_volumes
|boolean
a|Specifies whether or not read-only volume can be scanned.
```

```
|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.
```

```
|===
```

```
[#vscan_on_access]
[.api-collapsible-fifth-title]
vscan_on_access
```

An On-Access policy that defines the scope of an On-Access scan. Use On-Access scanning to check for viruses when clients open, read, rename, or close files over CIFS. By default, ONTAP creates an On-Access policy named "default\_CIFS" and enables it for all the SVMs in a cluster.

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Status of the On-Access Vscan policy
```

```
|mandatory
|boolean
a|Specifies if scanning is mandatory. File access is denied if there are
no external virus-scanning servers available for virus scanning.
```

```
|name
|string
a|On-Access policy ame
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

```
[#schedule]
[.api-collapsible-fifth-title]
schedule
```

Schedule of the task.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|name
|string
a|Job schedule name
```

```
|uuid
|string
a|Job schedule UUID
```

```

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.

|include_extensions
|array[string]
a|List of file extensions to be scanned.

|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.

|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.

|===

[#vscan_on_demand]
[.api-collapsible-fifth-title]
vscan_on_demand

```

Use On-Demand scanning to check files for viruses on a schedule. An On-Demand policy defines the scope of an On-Demand scan.

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|log_path
|string
a|The path from the Vserver root where the task report is created.

|name
|string
a|On-Demand task name

|scan_paths
|array[string]
a|List of paths that need to be scanned.

|schedule
|link:#schedule[schedule]
a|Schedule of the task.

|scope
|link:#scope[scope]
a|

|===

[#cluster_reference]
[.api-collapsible-fifth-title]
cluster_reference

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]

```



```
a|
```

```
|name  
|string  
a|
```

```
|uuid  
|string  
a|
```

```
|===
```

```
[#vscan_scanner_pool]  
[.api-collapsible-fifth-title]  
vscan_scanner_pool
```

Scanner pool is a set of attributes which are used to validate and manage connections between clustered ONTAP and external virus-scanning server, or "Vscan server".

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|cluster  
|link:#cluster_reference[cluster_reference]  
a|
```

```
|name  
|string
```

a|Specifies the name of the scanner pool. Scanner pool name can be up to 256 characters long and is a string that can only contain any combination of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "\_", "-" and ".".

```
|privileged_users  
|array[string]
```

a|Specifies a list of privileged users. A valid form of privileged user-name is "domain-name\user-name". Privileged user-names are stored and treated as case-insensitive strings. Virus scanners must use one of the registered privileged users for connecting to clustered Data ONTAP for exchanging virus-scanning protocol messages and to access file for scanning, remedying and quarantining operations.

```
* example: ["cifs\u1", "cifs\u2"]
* Introduced in: 9.6
* x-omitempty: true
```

```
|role
|string
```

a|Specifies the role of the scanner pool. The possible values are:

```
*** primary - Always active.
```

```
*** secondary - Active only when none of the primary external virus-
scanning servers are connected.
```

```
*** idle - Always inactive.
```

```
|servers
```

```
|array[string]
```

a|Specifies a list of IP addresses or FQDN for each Vscan server host names which are allowed to connect to clustered ONTAP.

```
* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]
* Introduced in: 9.6
* x-omitempty: true
```

```
|===
```

```
[#svm]
```

```
[.api-collapsible-fifth-title]
```

```
svm
```

SVM, applies only to SVM-scoped objects.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
|string
a|The name of the SVM.
```

```
|uuid
|string
a|The unique identifier of the SVM.
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[ID2f5ee138b6097563ad7f2c5d97fb9332]]
= Update the Vscan configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}`#
```

\*Introduced In:\* 9.6

Updates the Vscan configuration of an SVM. Allows you to either enable or disable a Vscan, and allows you to clear the Vscan cache that stores the past scanning data for an SVM.

Important note:

\* The Vscan PATCH endpoint does not allow you to modify scanner-pools, On-Demand policies or On-Access policies. Those modifications can only be done through their respective endpoints.

== Related ONTAP commands

```
* `vserver vscan enable`  
* `vserver vscan disable`  
* `vserver vscan reset`
```

== Learn more

```
* xref:{relative_path}protocols_vscan_endpoint_overview.html[DOC  
/protocols/vscan]  
* xref:{relative_path}protocols_vscan_svm.uuid_scanner-  
pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-  
pools]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|cache_clear
|boolean
a|Discards the cached information of the files that have been successfully scanned. Once the cache is cleared, files are scanned again when they are accessed. PATCH only
```

```
|enabled
|boolean
a|Specifies whether or not Vscan is enabled on the SVM.
```

```
|on_access_policies
|array[link:#vscan_on_access[vscan_on_access]]
a|
```

```
|on_demand_policies
|array[link:#vscan_on_demand[vscan_on_demand]]
a|
```

```
|scanner_pools
|array[link:#vscan_scanner_pool[vscan_scanner_pool]]
a|
```

```
|svm
|link:#svm[svm]
a|SVM, applies only to SVM-scoped objects.
```

```
|===
```

```
.Example request
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
{
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "on_access_policies": {
    "name": "on-access-test",
    "scope": {
      "exclude_extensions": [
        "mp*",

```

```

    "txt"
  ],
  "exclude_paths": [
    "\\dir1\\dir2\\name",
    "\\vol\\a b",
    "\\vol\\a,b\\"
  ],
  "include_extensions": [
    "mp*",
    "txt"
  ],
  "max_file_size": "2147483648"
}
},
"on_demand_policies": {
  "log_path": "/vol0/report_dir",
  "name": "task-1",
  "scan_paths": [
    "/vol1/",
    "/vol2/cifs/"
  ],
  "schedule": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    }
  },
  "name": "weekly",
  "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
},
"scope": {
  "exclude_extensions": [
    "mp3",
    "mp4"
  ],
  "exclude_paths": [
    "/vol1/cold-files/",
    "/vol1/cifs/names"
  ],
  "include_extensions": [
    "vmdk",
    "mp*"
  ],
  "max_file_size": "10737418240"
}
},

```

```
"scanner_pools": {
  "cluster": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "cluster1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "name": "scanner-1",
  "privileged_users": [
    "cifs\\u1",
    "cifs\\u2"
  ],
  "role": "primary",
  "servers": [
    "1.1.1.1",
    "10.72.204.27",
    "vmwin204-27.fsct.nb"
  ]
},
"svm": {
  "_links": {
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "name": "svm1",
  "uuid": "02c9e252-41be-11e9-81d5-00a0986138f7"
}
}
====
```

== Response

Status: 200, Ok

== Error

Status: Default

ONTAP Error Response Codes  
//start table



```
[cols=2*,options=header]
|===
//header
| Error Code | Description
//end header
//end row
//start row
|10027015 +
//end row
//start row
|Attempting to enable a Vscan but no active scanner-pool exists for the
specified SVM
//end row
//start row
|10027011 +
//end row
//start row
|Attempting to enable a Vscan for an SVM for which no CIFS server exists
//end row
//start row
|10027023 +
//end row
//start row
|Attempting to enable a Vscan for an SVM for which no active Vscan On-
Access policy exists
//end row
|===
//end table
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===
```

```
.Example error
[%collapsible%closed]
```

```

=====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====

```

```

[#href]
[.api-collapsible-fifth-title]
href

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|href
|string
a|

```

```

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

```

```

[cols=3*,options=header]
|===
|Name

```

```

|Type
|Description

|self
|link:#href[href]
a|

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.

|include_extensions
|array[string]
a|List of file extensions to be scanned.

|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.

|only_execute_access
|boolean
a|Scan only files opened with execute-access.

|scan_readonly_volumes
|boolean

```

a|Specifies whether or not read-only volume can be scanned.

|scan\_without\_extension

|boolean

a|Specifies whether or not files without any extension can be scanned.

|===

[#vscan\_on\_access]

[.api-collapsible-fifth-title]

vscan\_on\_access

An On-Access policy that defines the scope of an On-Access scan. Use On-Access scanning to check for viruses when clients open, read, rename, or close files over CIFS. By default, ONTAP creates an On-Access policy named "default\_CIFS" and enables it for all the SVMs in a cluster.

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|enabled

|boolean

a|Status of the On-Access Vscan policy

|mandatory

|boolean

a|Specifies if scanning is mandatory. File access is denied if there are no external virus-scanning servers available for virus scanning.

|name

|string

a|On-Access policy ame

|scope

|link:#scope[scope]

a|

```

|===

[#schedule]
[.api-collapsible-fifth-title]
schedule

Schedule of the task.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|Job schedule name

|uuid
|string
a|Job schedule UUID

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

```

```
|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.
```

```
|include_extensions
|array[string]
a|List of file extensions to be scanned.
```

```
|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.
```

```
|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.
```

```
|===
```

```
[#vscan_on_demand]
[.api-collapsible-fifth-title]
vscan_on_demand
```

Use On-Demand scanning to check files for viruses on a schedule. An On-Demand policy defines the scope of an On-Demand scan.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|log_path
|string
a|The path from the Vserver root where the task report is created.
```

```
|name
|string
a|On-Demand task name
```

```
|scan_paths
|array[string]
a|List of paths that need to be scanned.
```

```
|schedule
|link:#schedule[schedule]
a|Schedule of the task.
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

```
[#cluster_reference]
[.api-collapsible-fifth-title]
cluster_reference
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|_links
|link:#_links[_links]
a|
```

```
|name
|string
a|
```

```
|uuid
|string
a|
```

```
|===
```

```
[#vscan_scanner_pool]
[.api-collapsible-fifth-title]
vscan_scanner_pool
```

Scanner pool is a set of attributes which are used to validate and manage connections between clustered ONTAP and external virus-scanning server, or "Vscan server".

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|cluster
```

```
|link:#cluster_reference[cluster_reference]
```

```
a|
```

```
|name
```

```
|string
```

```
a|Specifies the name of the scanner pool. Scanner pool name can be up to 256 characters long and is a string that can only contain any combination of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "_", "-" and ".".
```

```
|privileged_users
```

```
|array[string]
```

```
a|Specifies a list of privileged users. A valid form of privileged user-name is "domain-name\user-name". Privileged user-names are stored and treated as case-insensitive strings. Virus scanners must use one of the registered privileged users for connecting to clustered Data ONTAP for exchanging virus-scanning protocol messages and to access file for scanning, remediating and quarantining operations.
```

```
* example: ["cifs\u1", "cifs\u2"]
```

```
* Introduced in: 9.6
```

```
* x-omitempty: true
```

```
|role
```

```
|string
```

```
a|Specifies the role of the scanner pool. The possible values are:
```

```
*** primary - Always active.
```

```
*** secondary - Active only when none of the primary external virus-scanning servers are connected.
```

```
*** idle - Always inactive.
```



```
|servers
|array[string]
a|Specifies a list of IP addresses or FQDN for each Vscan server host
names which are allowed to connect to clustered ONTAP.
```

```
* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]
```

```
* Introduced in: 9.6
```

```
* x-omitempty: true
```

```
|===
```

```
[#svm]
[.api-collapsible-fifth-title]
svm
```

SVM, applies only to SVM-scoped objects.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|The name of the SVM.
```

```
|uuid
```

```
|string
```

```
a|The unique identifier of the SVM.
```

```
|===
```

```
[#vscan]
[.api-collapsible-fifth-title]
vscan
```

Vscan can be used to protect data from being compromised by viruses or other malicious code. This combines best-in-class third-party antivirus software with ONTAP features that give you the flexibility you need to control which files get scanned and when. Storage systems offload scanning operations to external servers hosting antivirus software from thirdparty vendors. An Antivirus Connector on the external server handles communications between the storage system and the antivirus software.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
 |_links
```

```
 |link:#_links[_links]
```

```
 a|
```

```
 |cache_clear
```

```
 |boolean
```

```
 a|Discards the cached information of the files that have been successfully scanned. Once the cache is cleared, files are scanned again when they are accessed. PATCH only
```

```
 |enabled
```

```
 |boolean
```

```
 a|Specifies whether or not Vscan is enabled on the SVM.
```

```
 |on_access_policies
```

```
 |array[link:#vscan_on_access[vscan_on_access]]
```

```
 a|
```

```
 |on_demand_policies
```

```
 |array[link:#vscan_on_demand[vscan_on_demand]]
```

```
 a|
```

```
 |scanner_pools
```

```
 |array[link:#vscan_scanner_pool[vscan_scanner_pool]]
```

```
 a|
```

```
 |svm
```

```
 |link:#svm[svm]
```

```
 a|SVM, applies only to SVM-scoped objects.
```

```
|===
```

```
[#error_arguments]  
[.api-collapsible-fifth-title]  
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|code  
|string  
a|Argument code
```

```
|message  
|string  
a|Message argument
```

```
|===
```

```
[#error]  
[.api-collapsible-fifth-title]  
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|arguments  
|array[link:#error_arguments[error_arguments]]  
a|Message arguments
```

```
|code  
|string  
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
:leveloffset: -1
```

```
= Manage Vscan On-Access policies
```

```
:leveloffset: +1
```

```
[[ID4504344235a24298731747eb3076ddaf]]
```

```
= Protocols Vscan svm.uuid on-access-policies endpoint overview
```

```
== Overview
```

Use Vscan On-Access scanning to actively scan file objects for viruses when clients access files over SMB. To control which file operations trigger a vscan, use Vscan File-Operations Profile (vscan-fileop-profile) option in the CIFS share. The Vscan On-Access policy configuration defines the scope and status of On-Access scanning on file objects. Use this API to retrieve and manage Vscan On-Access policy configurations and Vscan On-Access policy statuses for the SVM.

```
== Examples
```

```
=== Retrieving all fields for all policies of an SVM
```

```
'''
```

----

# The API:

```
/api/protocols/vscan/{svm.uuid}/on-access-policies/
```

# The call:

```
curl -X GET "https://<mgmt-ip>/api/protocols/vscan/{svm.uuid}/on-access-policies?fields=*" -H "accept: application/hal+json"
```

# The response:

```
{
"records": [
  {
    "svm": {
      "uuid": "179d3c85-7053-11e8-b9b8-005056b41bd1",
      "name": "vs1",
      "_links": {
        "self": {
          "href": "/api/svm/svms/179d3c85-7053-11e8-b9b8-005056b41bd1"
        }
      }
    },
    "name": "default_CIFS",
    "enabled": true,
    "mandatory": true,
    "scope": {
      "max_file_size": 2147483648,
      "include_extensions": [
        "*"
      ],
      "scan_without_extension": true,
      "scan_readonly_volumes": false,
      "only_execute_access": false
    },
    "_links": {
      "self": {
        "href": "/api/protocols/vscan/179d3c85-7053-11e8-b9b8-005056b41bd1/on-access-policies/default_CIFS"
      }
    }
  },
  {
    "svm": {
      "uuid": "179d3c85-7053-11e8-b9b8-005056b41bd1",
      "name": "vs1",
```

```

    "_links": {
      "self": {
        "href": "/api/svm/svms/179d3c85-7053-11e8-b9b8-005056b41bd1"
      }
    }
  },
  "name": "on-access-policy",
  "enabled": false,
  "mandatory": true,
  "scope": {
    "max_file_size": 3221225472,
    "exclude_paths": [
      "\\vol\\a b\\",
      "\\vol\\a,b\\"
    ],
    "include_extensions": [
      "mp*",
      "tx*"
    ],
    "exclude_extensions": [
      "mp3",
      "txt"
    ],
    "scan_without_extension": true,
    "scan_readonly_volumes": false,
    "only_execute_access": true
  },
  "_links": {
    "self": {
      "href": "/api/protocols/vscan/179d3c85-7053-11e8-b9b8-005056b41bd1/on-access-policies/on-access-policy"
    }
  }
},
"num_records": 2,
"_links": {
  "self": {
    "href": "/api/protocols/vscan/179d3c85-7053-11e8-b9b8-005056b41bd1/on-access-policies?fields=*"
  }
}
}
}
----
'''

```

```
=== Retrieving the specific On-Access policy associated with the specified
SVM

'''

----

# The API:
/api/protocols/vscan/{svm.uuid}/on-access-policies/{name}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/vscan/179d3c85-7053-11e8-
b9b8-005056b41bd1/on-access-policies/on-access-policy" -H "accept:
application/json"

# The response:
{
  "svm": {
    "uuid": "179d3c85-7053-11e8-b9b8-005056b41bd1",
    "name": "vs1",
    "_links": {
      "self": {
        "href": "/api/svm/svms/179d3c85-7053-11e8-b9b8-005056b41bd1"
      }
    }
  },
  "name": "on-access-policy",
  "enabled": true,
  "mandatory": true,
  "scope": {
    "max_file_size": 3221225472,
    "exclude_paths": [
      "\\vol\\a b\\",
      "\\vol\\a,b\\"
    ],
    "include_extensions": [
      "mp*",
      "tx*"
    ],
    "exclude_extensions": [
      "mp3",
      "txt"
    ],
    "scan_without_extension": true,
    "scan_readonly_volumes": false,
```

```

    "only_execute_access": true
  },
  "_links": {
    "self": {
      "href": "/api/protocols/vscan/179d3c85-7053-11e8-b9b8-005056b41bd1/on-
access-policies/task1"
    }
  }
}
-----

'''

```

=== Creating a Vscan On-Access policy

The Vscan On-Access policy POST endpoint creates an On-Access policy for the specified SVM. Set enabled to "true" to enable scanning on the created policy.

-----

# The API:

```
/api/protocols/vscan/{svm.uuid}/on-access-policies
```

# The call:

```

curl -X POST "https://<mgmt-ip>/api/protocols/vscan/86fbc414-f140-11e8-
8e22-0050568e0945/on-access-policies?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"enabled\":
false, \"mandatory\": true, \"name\": \"on-access-policy\", \"scope\": {
\"exclude_extensions\": [ \"txt\", \"mp3\" ], \"exclude_paths\": [
\"\\\\\\\\dir1\\\\\\\\dir2\\\\\\\\ame\", \"\\\\\\\\vol\\\\\\\\a b\" ], \"include_extensions\":
[ \"mp*\", \"txt\" ], \"max_file_size\": 3221225472,
\"only_execute_access\": true, \"scan_readonly_volumes\": false,
\"scan_without_extension\": true }}"

```

# The response:

```

{
  "num_records": 1,
  "records": [
    {
      "svm": {
        "name": "vs1"
      },
      "name": "on-access-policy",
      "enabled": false,
      "mandatory": true,

```



```

"scope": {
  "max_file_size": 3221225472,
  "exclude_paths": [
    "\\dir1\\dir2\\ame",
    "\\vol\\a b"
  ],
  "include_extensions": [
    "mp*",
    "txt"
  ],
  "exclude_extensions": [
    "txt",
    "mp3"
  ],
  "scan_without_extension": true,
  "scan_readonly_volumes": false,
  "only_execute_access": true
}
]
}
----

'''

=== Creating a Vscan On-Access policy where a number of optional fields
are not specified

'''

----

# The API:
/api/protocols/vscan/{svm.uuid}/on-access-policies

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/vscan/86fbc414-f140-11e8-
8e22-0050568e0945/on-access-policies?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"enabled\":
false, \"mandatory\": true, \"name\": \"on-access-policy\", \"scope\": {
\"exclude_paths\": [ \"\\\\\\\\vol\\\\\\\\a b\", \"\\\\\\\\vol\\\\\\\\a,b\\\\\\\\\" ],
\"max_file_size\": 1073741824, \"scan_without_extension\": true }}"

# The response:
{
"num_records": 1,

```

```

"records": [
  {
    "svm": {
      "name": "vs1"
    },
    "name": "on-access-policy",
    "enabled": false,
    "mandatory": true,
    "scope": {
      "max_file_size": 1073741824,
      "exclude_paths": [
        "\\vol\\a b",
        "\\vol\\a,b\\"
      ],
      "scan_without_extension": true
    }
  }
]
}

```

----

'''

=== Updating a Vscan On-Access policy

The policy being modified is identified by the UUID of the SVM and the policy name.

----

# The API:

```
/api/protocols/vscan/{svm.uuid}/on-access-policies/{name}
```

# The call:

```
curl -X PATCH "https://<mgmt-ip>/api/protocols/vscan/86fbc414-f140-11e8-8e22-0050568e0945/on-access-policies/on-access-policy" -H "accept: application/hal+json" -H "Content-Type: application/json" -d "{ \"scope\": { \"include_extensions\": [ \"txt\" ], \"only_execute_access\": true, \"scan_readonly_volumes\": false, \"scan_without_extension\": true }}"
```

----

'''

=== Deleting a Vscan On-Access policy

The policy to be deleted is identified by the UUID of the SVM and the

policy name.

----

# The API:

/api/protocols/vscan/{svm.uuid}/on-access-policies/{name}

# The call:

```
curl -X DELETE "https://<mgmt-ip>/api/protocols/vscan/86fbc414-f140-11e8-8e22-0050568e0945/on-access-policies/on-access-policy" -H "accept: application/hal+json"
```

----

'''

[[IDd8be31234f330eadd18989c4573f48eb]]

= Retrieve a Vscan On-Access policy

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/vscan/{svm.uuid}/on-access-policies`#

\*Introduced In:\* 9.6

Retrieves the Vscan On-Access policy.

== Related ONTAP commands

- \* `vserver vscan on-access-policy show`
- \* `vserver vscan on-access-policy file-ext-to-include show`
- \* `vserver vscan on-access-policy file-ext-to-exclude show`
- \* `vserver vscan on-access-policy paths-to-exclude show`

== Learn more

\* xref:{relative\_path}protocols\_vscan\_svm.uuid\_on-access-policies\_endpoint\_overview.html[DOC /protocols/vscan/{svm.uuid}/on-access-policies]

== Parameters

[cols=5\*,options=header]

|===

|Name  
|Type  
|In  
|Required  
|Description

|name  
|string  
|query  
|False  
a|Filter by name

|scope.only\_execute\_access  
|boolean  
|query  
|False  
a|Filter by scope.only\_execute\_access

|scope.include\_extensions  
|string  
|query  
|False  
a|Filter by scope.include\_extensions

|scope.exclude\_extensions  
|string  
|query  
|False  
a|Filter by scope.exclude\_extensions

|scope.scan\_readonly\_volumes  
|boolean  
|query  
|False  
a|Filter by scope.scan\_readonly\_volumes

|scope.exclude\_paths  
|string  
|query  
|False  
a|Filter by scope.exclude\_paths

```
|scope.max_file_size
|integer
|query
|False
a|Filter by scope.max_file_size
```

```
|scope.scan_without_extension
|boolean
|query
|False
a|Filter by scope.scan_without_extension
```

```
|mandatory
|boolean
|query
|False
a|Filter by mandatory
```

```
|enabled
|boolean
|query
|False
a|Filter by enabled
```

```
|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.
```

```
|fields
|array[string]
|query
|False
a|Specify the fields to return.
```

```
|max_records
|integer
|query
```

```

|False
a|Limit the number of records returned.

|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.

* Default value: 1

|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
When iterating over a collection, the default is 15 seconds. ONTAP
returns earlier if either max records or the end of the collection is
reached.

* Default value: 1
* Max value: 120
* Min value: 0

|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.

|===

```

== Response

Status: 200, Ok

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```
|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#vscan_on_access[vscan_on_access]]
a|

|===
```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "name": "on-access-test",
    "scope": {
      "exclude_extensions": [
        "mp*",
        "txt"
      ],
      "exclude_paths": [
        "\\dir1\\dir2\\name",
        "\\vol\\a b",
        "\\vol\\a,b\\"
      ],
      "include_extensions": [
        "mp*",
        "txt"
      ]
    }
  }
}
```

```

    "max_file_size": "2147483648"
  }
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block

```



```

====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type

```

|Description

|exclude\_extensions

|array[string]

a|List of file extensions for which scanning is not performed.

|exclude\_paths

|array[string]

a|List of file paths for which scanning must not be performed.

|include\_extensions

|array[string]

a|List of file extensions to be scanned.

|max\_file\_size

|integer

a|Maximum file size, in bytes, allowed for scanning.

|only\_execute\_access

|boolean

a|Scan only files opened with execute-access.

|scan\_readonly\_volumes

|boolean

a|Specifies whether or not read-only volume can be scanned.

|scan\_without\_extension

|boolean

a|Specifies whether or not files without any extension can be scanned.

|===

[#vscan\_on\_access]

[.api-collapsible-fifth-title]

vscan\_on\_access

An On-Access policy that defines the scope of an On-Access scan. Use On-Access scanning to check for viruses when clients open, read, rename, or close files over CIFS. By default, ONTAP creates an On-Access policy named

"default\_CIFS" and enables it for all the SVMs in a cluster.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|enabled
```

```
|boolean
```

```
a|Status of the On-Access Vscan policy
```

```
|mandatory
```

```
|boolean
```

```
a|Specifies if scanning is mandatory. File access is denied if there are no external virus-scanning servers available for virus scanning.
```

```
|name
```

```
|string
```

```
a|On-Access policy ame
```

```
|scope
```

```
|link:#scope[scope]
```

```
a|
```

```
|===
```

```
[#error_arguments]
```

```
[.api-collapsible-fifth-title]
```

```
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|code
```

```
|string
```

```
a|Argument code
```

```
|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDb9fd5e9c3cc66f47417ada2a72179147]]
```

= Create a Vscan On-Access policy

[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-block]#`/protocols/vscan/{svm.uuid}/on-access-policies`#

\*Introduced In:\* 9.6

Creates a Vscan On-Access policy. Created only on a data SVM.

</b>Important notes:

\* You must enable the policy on an SVM before its files can be scanned.  
\* You can enable only one On-Access policy at a time on an SVM. By default, the policy is enabled on creation. \* If the Vscan On-Access policy has been created successfully on an SVM but cannot be enabled due to an error, the Vscan On-Access policy configurations are saved. The Vscan On-Access policy is then enabled using the PATCH operation.

== Required properties

\* `svm.uuid` - Existing SVM in which to create the Vscan On-Access policy.  
\* `name` - Name of the Vscan On-Access policy. Maximum length is 256 characters.

== Default property values

If not specified in POST, the following default property values are assigned:

\* `enabled` - `_true_`  
\* `mandatory` - `_true_`  
\* `include\_extensions` - `_*_`  
\* `max\_file\_size` - `_2147483648_`  
\* `only\_execute\_access` - `_false_`  
\* `scan\_readonly\_volumes` - `_false_`  
\* `scan\_without\_extension` - `_true_`

== Related ONTAP commands

\* `vserver vscan on-access-policy create`  
\* `vserver vscan on-access-policy enable`  
\* `vserver vscan on-access-policy disable`  
\* `vserver vscan on-access-policy file-ext-to-include add`  
\* `vserver vscan on-access-policy file-ext-to-exclude add`  
\* `vserver vscan on-access-policy paths-to-exclude add`

== Learn more

```
* xref:{relative_path}protocols_vscan_svm.uuid_on-access-
policies_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/on-access-
policies]
```

#### == Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|return_records
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|The default is false. If set to true, the records are returned.
```

```
* Default value:
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```

#### == Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|enabled
```

```
|boolean
```

```
a|Status of the On-Access Vscan policy
```

```
|mandatory
|boolean
a|Specifies if scanning is mandatory. File access is denied if there are
no external virus-scanning servers available for virus scanning.
```

```
|name
|string
a|On-Access policy ame
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

```
.Example request
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "name": "on-access-test",
  "scope": {
    "exclude_extensions": [
      "mp*",
      "txt"
    ],
    "exclude_paths": [
      "\\dir1\\dir2\\name",
      "\\vol\\a b",
      "\\vol\\a,b\\"
    ],
    "include_extensions": [
      "mp*",
      "txt"
    ],
    "max_file_size": "2147483648"
  }
}
```

```
====
```

```
== Response
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#vscan_on_access[vscan_on_access]]
a|

|===
```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "name": "on-access-test",
    "scope": {
      "exclude_extensions": [
        "mp*",
        "txt"
      ],
      "exclude_paths": [
        "\\dir1\\dir2\\name",

```



```

        "\\vol\\a b",
        "\\vol\\a,b\\"
    ],
    "include_extensions": [
        "mp*",
        "txt"
    ],
    "max_file_size": "2147483648"
}
}
====

== Error

```

### Status: Default

#### ONTAP Error Response Codes

|===

Error Code	Description
------------	-------------

10027043	
----------	--

10027043	The new On-Access policy cannot be created as the SVM has reached the maximum number of On-Access policies allowed. Delete an existing policy in order to create a new policy
----------	---

10027101	
----------	--

10027101	The file size must be in the range 1KB to 1TB
----------	---

10027107	
----------	--

10027107	The include extensions list cannot be empty. Specify at least one extension for inclusion
----------	---

10027109	
----------	--

10027109	The specified CIFS path is invalid. It must be in the form "\dir1\dir2" or "\dir1\dir2\"
----------	--

10027249	
----------	--

10027249	The On-Access policy created successfully but failed to enable the policy. The reason for enable policy operation failure might be that another policy is enabled. Disable the enabled policy and then enable the newly created policy using the PATCH operation
----------	--

10027253	
----------	--

10027253	The number of paths specified exceeds the configured number of maximum
----------	--

paths. You cannot specify more than the maximum number of configured paths

```
| 10027254
```

```
| The number of extensions specified exceeds the configured maximum number  
of extensions. You cannot specify more than the maximum number of  
configured extensions
```

```
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
```

```
  "error": {
```

```
    "arguments": {
```

```
      "code": "string",
```

```
      "message": "string"
```

```
    },
```

```
    "code": "4",
```

```
    "message": "entry doesn't exist",
```

```
    "target": "uuid"
```

```
  }
```

```
}
```

```
====
```

```
== Definitions
```

```
[.api-def-first-level]
```

```
.See Definitions
```

```
[%collapsible%closed]
```

```
//Start collapsible Definitions block
```

```
====
```

```

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.

|include_extensions
|array[string]
a|List of file extensions to be scanned.

|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.

|only_execute_access
|boolean
a|Scan only files opened with execute-access.

|scan_readonly_volumes
|boolean
a|Specifies whether or not read-only volume can be scanned.

|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.

|===

```

```
[#vscan_on_access]
[.api-collapsible-fifth-title]
vscan_on_access
```

An On-Access policy that defines the scope of an On-Access scan. Use On-Access scanning to check for viruses when clients open, read, rename, or close files over CIFS. By default, ONTAP creates an On-Access policy named "default\_CIFS" and enables it for all the SVMs in a cluster.

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|enabled
|boolean
a|Status of the On-Access Vscan policy
```

```
|mandatory
|boolean
a|Specifies if scanning is mandatory. File access is denied if there are
no external virus-scanning servers available for virus scanning.
```

```
|name
|string
a|On-Access policy ame
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

```
[#href]
[.api-collapsible-fifth-title]
href
```

```
[cols=3*,options=header]
|===
|Name
```

```

|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message

```

```

|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

[[ID6fc65998085d1907307303c2e7591deb]]
= Delete an antivirus On-Access policy configuration

```

```
[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-block]#`/protocols/vscan/{svm.uuid}/on-access-policies/{name}`#
```

\*Introduced In:\* 9.6

Deletes the anti-virus On-Access policy configuration.

== Related ONTAP commands

\* `vserver vscan on-access-policy delete`

== Learn more

\* xref:{relative\_path}protocols\_vscan\_svm.uuid\_on-access-policies\_endpoint\_overview.html[DOC /protocols/vscan/{svm.uuid}/on-access-policies]

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name  
|Type  
|In  
|Required  
|Description
```

```
|name  
|string  
|path  
|True
```

```
a|
```

```
|svm.uuid  
|string  
|path  
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```

== Response

Status: 200, Ok

```
== Error
```

Status: Default

ONTAP Error Response Codes

```
|===
```

```
| Error Code | Description
```

```
| 10027034
```

```
| An On-Access policy associated with an administrative SVM cannot be deleted.
```

```
| 10027040
```

```
| An On-Access policy with a status enabled cannot be deleted. Disable the policy and then delete the policy.
```

```
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
```

```
  "error": {
```

```
    "arguments": {
```

```
      "code": "string",
```

```
      "message": "string"
```

```
    },
```



```
"code": "4",
"message": "entry doesn't exist",
"target": "uuid"
}
}
====
```

== Definitions

```
[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|code
```

```
|string
```

```
a|Argument code
```

```
|message
```

```
|string
```

```
a|Message argument
```

```
|===
```

```
[#error]
```

```
[.api-collapsible-fifth-title]
```

```
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[ID93b06e178f336470841754587d97f2c3]]
= Retrieve the Vscan On-Access policy configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}/on-access-policies/{name}`#
```

```
*Introduced In:* 9.6
```

Retrieves the Vscan On-Access policy configuration of an SVM.

```
== Related ONTAP commands
```

```
* `vserver vscan on-access-policy show`
* `vserver vscan on-access-policy file-ext-to-include show`
* `vserver vscan on-access-policy file-ext-to-exclude show`
* `vserver vscan on-access-policy paths-to-exclude show`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_vscan_svm.uuid_on-access-
policies_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/on-access-
policies]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|name
```

```
|string
```

```
|path
```

```
|True
```

```
a|
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|fields
```

```
|array[string]
```

```
|query
```

```
|False
```

```
a|Specify the fields to return.
```

```
|===
```

== Response

Status: 200, Ok

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|enabled
|boolean
a|Status of the On-Access Vscan policy
```

```
|mandatory
|boolean
a|Specifies if scanning is mandatory. File access is denied if there are
no external virus-scanning servers available for virus scanning.
```

```
|name
|string
a|On-Access policy ame
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

.Example response

[%collapsible%closed]

====

```
[source,json,subs=+macros]
{
  "name": "on-access-test",
  "scope": {
    "exclude_extensions": [
      "mp*",
      "txt"
    ],
    "exclude_paths": [
      "\\dir1\\dir2\\name",
      "\\vol\\a b",
      "\\vol\\a,b\\"
    ],
    "include_extensions": [
      "mp*",
      "txt"
    ],
    "max_file_size": "2147483648"
  }
}
```

```
}  
====  
  
== Error
```

Status: Default, Error

```
[cols=3*,options=header]  
|===  
|Name  
|Type  
|Description  
  
|error  
|link:#error[error]  
a|  
  
|===  
  
.Example error  
[%collapsible%closed]  
====  
[source,json,subs=+macros]  
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}  
====  
  
== Definitions  
  
[.api-def-first-level]  
.See Definitions  
[%collapsible%closed]  
//Start collapsible Definitions block  
====  
[#scope]  
[.api-collapsible-fifth-title]
```

scope

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|exclude_extensions
```

```
|array[string]
```

```
a|List of file extensions for which scanning is not performed.
```

```
|exclude_paths
```

```
|array[string]
```

```
a|List of file paths for which scanning must not be performed.
```

```
|include_extensions
```

```
|array[string]
```

```
a|List of file extensions to be scanned.
```

```
|max_file_size
```

```
|integer
```

```
a|Maximum file size, in bytes, allowed for scanning.
```

```
|only_execute_access
```

```
|boolean
```

```
a|Scan only files opened with execute-access.
```

```
|scan_readonly_volumes
```

```
|boolean
```

```
a|Specifies whether or not read-only volume can be scanned.
```

```
|scan_without_extension
```

```
|boolean
```

```
a|Specifies whether or not files without any extension can be scanned.
```

```
|===
```

```
[#error_arguments]
```

```
[.api-collapsible-fifth-title]
```

```
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|code
```

```
|string
```

```
a|Argument code
```

```
|message
```

```
|string
```

```
a|Message argument
```

```
|===
```

```
[#error]
```

```
[.api-collapsible-fifth-title]
```

```
error
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|arguments
```

```
|array[link:#error_arguments[error_arguments]]
```

```
a|Message arguments
```

```
|code
```

```
|string
```

```
a|Error code
```

```
|message
```

```
|string
```

```
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[ID0146bcbcf841afc734cf011b8cf963c1]]
= Update the Vscan On-Access policy configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}/on-access-policies/{name}`#
```

```
*Introduced In:* 9.6
```

Updates the Vscan On-Access policy configuration and/or enables/disables the Vscan On-Access policy of an SVM. You cannot modify the configurations for an On-Access policy associated with an administrative SVM, although you can enable and disable the policy associated with an administrative SVM.

```
== Related ONTAP commands
```

```
* `vserver vscan on-access-policy modify`
* `vserver vscan on-access-policy enable`
* `vserver vscan on-access-policy disable`
* `vserver vscan on-access-policy file-ext-to-include add`
* `vserver vscan on-access-policy file-ext-to-exclude add`
* `vserver vscan on-access-policy paths-to-exclude add`
* `vserver vscan on-access-policy file-ext-to-include remove`
* `vserver vscan on-access-policy file-ext-to-exclude remove`
* `vserver vscan on-access-policy paths-to-exclude remove`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_vscan_svm.uuid_on-access-
policies_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/on-access-
policies]
```

```
== Parameters
```



```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|name
```

```
|string
```

```
|path
```

```
|True
```

```
a|
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```

```
== Request Body
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|enabled
```

```
|boolean
```

```
a|Status of the On-Access Vscan policy
```

```
|mandatory
```

```
|boolean
```

```
a|Specifies if scanning is mandatory. File access is denied if there are no external virus-scanning servers available for virus scanning.
```

```
|name
```

```
|string
```

```
a|On-Access policy ame
```

```
|scope
```

```
|link:#scope[scope]
```

```
a|
```

```
|===
```

```
.Example request
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{  
  "name": "on-access-test",  
  "scope": {  
    "exclude_extensions": [  
      "mp*",  
      "txt"  
    ],  
    "exclude_paths": [  
      "\\dir1\\dir2\\name",  
      "\\vol\\a b",  
      "\\vol\\a,b\\"  
    ],  
    "include_extensions": [  
      "mp*",  
      "txt"  
    ],  
    "max_file_size": "2147483648"  
  }  
}
```

```
====
```

```
== Response
```

Status: 200, Ok

```
== Error
```

Status: Default

```
ONTAP Error Response Codes
```

|===

| Error Code | Description

| 10027033

| Configurations for an On-Access policy associated with an administrative SVM cannot be modified. However, the policy can be enabled or disabled.

| 10027046

| The specified SVM is not the owner of the specified policy. Check for the correct SVM who owns the policy.

| 10027101

| The file size must be in the range 1KB to 1TB

| 10027107

| The include extensions list cannot be empty. Specify at least one extension for inclusion.

| 10027109

| The specified CIFS path is invalid. It must be in the form "`\dir1\dir2`" or "`\dir1\dir2\`".

| 10027249

| The On-Access policy updated successfully but failed to enable/disable the policy. The reason for an enable policy operation failure might be that another policy is enabled. Disable the already enabled policy and then enable the policy. The reason for a disable policy operation failure might be that Vscan is enabled on the SVM. Disable the Vscan first and then disable the policy.

| 10027250

| The On-Access policy cannot be enabled/disabled. The reason for an enable policy operation failure might be that another policy is enabled. Disable the already enabled policy and then enable the policy. The reason for a disable policy operation failure might be that Vscan is enabled on the SVM. Disable the Vscan and then disable the policy.

| 10027253

| The number of paths specified exceeds the configured maximum number of paths. You cannot specify more than the maximum number of configured paths.

| 10027254

| The number of extensions specified exceeds the configured maximum number of extensions. You cannot specify more than the maximum number of configured extensions.

```

|===

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====
[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===

```

```

|Name
|Type
|Description

|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.

|include_extensions
|array[string]
a|List of file extensions to be scanned.

|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.

|only_execute_access
|boolean
a|Scan only files opened with execute-access.

|scan_readonly_volumes
|boolean
a|Specifies whether or not read-only volume can be scanned.

|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.

|===

[#vscan_on_access]
[.api-collapsible-fifth-title]
vscan_on_access

```

An On-Access policy that defines the scope of an On-Access scan. Use On-

Access scanning to check for viruses when clients open, read, rename, or close files over CIFS. By default, ONTAP creates an On-Access policy named "default\_CIFS" and enables it for all the SVMs in a cluster.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|enabled
```

```
|boolean
```

```
a|Status of the On-Access Vscan policy
```

```
|mandatory
```

```
|boolean
```

```
a|Specifies if scanning is mandatory. File access is denied if there are no external virus-scanning servers available for virus scanning.
```

```
|name
```

```
|string
```

```
a|On-Access policy ame
```

```
|scope
```

```
|link:#scope[scope]
```

```
a|
```

```
|===
```

```
[#error_arguments]
```

```
[.api-collapsible-fifth-title]
```

```
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|code
```

```
|string
```

```
a|Argument code
```

```

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

```

```
:leveloffset: -1
```

```
= Manage Vscan On-Demand policies
```

```
:leveloffset: +1
```

```
[[IDea1bf9fbab8c19c856395ef48e9ebf1c]]
```

```
= Protocols Vscan svm.uuid on-demand-policies endpoint overview
```

```
== Overview
```

Vscan On-Demand scanning is used to check files for viruses on a schedule. For example, it can be used to run scans only in off-peak hours, or to scan very large files that are excluded from an on-access scan. Vscan On-Demand scanning can be used for any path in the SVM namespace.

Vscan On-Demand policy configurations define the scope of a Vscan On-Demand scan. The schedule parameter in the On-Demand policy configuration decides when to execute the task. Schedule can be created using the `/api/clusters/schedule` endpoint and can be assigned on policy create or policy modify. This API is used to retrieve and manage Vscan On-Demand policy configurations. It is also used to schedule the Vscan On-Demand scan.

```
== Examples
```

```
=== Retrieving all fields for all policies of an SVM
```

```
'''
```

```
----
```

```
# The API:
```

```
/api/protocols/vscan/{svm.uuid}/on-demand-policies/
```

```
# The call:
```

```
curl -X GET "https://<mgmt-ip>/api/protocols/vscan/{svm.uuid}/on-demand-policies?fields=*" -H "accept: application/hal+json"
```

```
# The response:
```

```
{
```

```
"records": [
```



```

{
  "svm": {
    "uuid": "86fbc414-f140-11e8-8e22-0050568e0945",
    "name": "vs1",
    "_links": {
      "self": {
        "href": "/api/svm/svms/86fbc414-f140-11e8-8e22-0050568e0945"
      }
    }
  },
  "name": "on-demand-policy1",
  "scan_paths": [
    "/vol1/",
    "/vol2/cifs/"
  ],
  "log_path": "/vol0/report_dir",
  "schedule": {
    "uuid": "f6d0843e-f159-11e8-8e22-0050568e0945",
    "name": "schedule",
    "_links": {
      "self": {
        "href": "/api/cluster/schedules/f6d0843e-f159-11e8-8e22-0050568e0945"
      }
    }
  },
  "scope": {
    "max_file_size": 10737418240,
    "exclude_paths": [
      "/vol1/cold-files/",
      "/vol1/cifs/names"
    ],
    "include_extensions": [
      "vmdk",
      "mp*"
    ],
    "exclude_extensions": [
      "mp3",
      "mp4"
    ],
    "scan_without_extension": false
  },
  "_links": {
    "self": {
      "href": "/api/protocols/vscan/86fbc414-f140-11e8-8e22-0050568e0945/on-demand-policies/policy1"
    }
  }
}

```

```

    }
  },
  {
    "svm": {
      "uuid": "86fbc414-f140-11e8-8e22-0050568e0945",
      "name": "vs1",
      "_links": {
        "self": {
          "href": "/api/svm/svms/86fbc414-f140-11e8-8e22-0050568e0945"
        }
      }
    },
    "name": "on-demand-policy2",
    "scan_paths": [
      "/vol1/",
      "/vol2/cifs/"
    ],
    "log_path": "/report",
    "scope": {
      "max_file_size": 10737418240,
      "include_extensions": [
        "mp*"
      ],
      "scan_without_extension": true
    },
    "_links": {
      "self": {
        "href": "/api/protocols/vscan/86fbc414-f140-11e8-8e22-0050568e0945/on-demand-policies/policy2"
      }
    }
  }
],
"num_records": 2,
"_links": {
  "self": {
    "href": "/api/protocols/vscan/86fbc414-f140-11e8-8e22-0050568e0945/on-demand-policies?fields=*"
  }
}
}
}
----
'''

```

```
=== Retrieving a specific On-Demand policy associated with a specified SVM
```

```
'''
```

```
-----
```

```
# The API:
```

```
/api/protocols/vscan/{svm.uuid}/on-demand-policies/{name}
```

```
# The call:
```

```
curl -X GET "https://<mgmt-ip>/api/protocols/vscan/86fbc414-f140-11e8-8e22-0050568e0945/on-demand-policies/on-demand-task" -H "accept: application/json"
```

```
# The response:
```

```
{  
  "svm": {  
    "uuid": "86fbc414-f140-11e8-8e22-0050568e0945",  
    "name": "vs1",  
    "_links": {  
      "self": {  
        "href": "/api/svm/svms/86fbc414-f140-11e8-8e22-0050568e0945"  
      }  
    }  
  },  
  "name": "on-demand-policy",  
  "scan_paths": [  
    "/voll/cifs"  
  ],  
  "log_path": "/report",  
  "scope": {  
    "max_file_size": 10737418240,  
    "include_extensions": [  
      "vmdk",  
      "mp*"  
    ],  
    "scan_without_extension": true  
  },  
  "_links": {  
    "self": {  
      "href": "/api/protocols/vscan/86fbc414-f140-11e8-8e22-0050568e0945/on-demand-policies/policy2"  
    }  
  }  
}
```

```
-----
```

```
'''  
  
=== Creating a Vscan On-Demand policy
```

The Vscan On-Demand policy POST endpoint creates an On-Demand policy for the specified SVM. Specify the schedule parameter to schedule an On-Demand scan.

```
-----  
  
# The API:  
/api/protocols/vscan/{svm.uuid}/on-demand-policies  
  
# The call:  
curl -X POST "https://<mgmt-ip>/api/protocols/vscan/86fbc414-f140-11e8-8e22-0050568e0945/on-demand-policies?return_records=true" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"log_path\": \"/vol0/report_dir\", \"name\": \"on-demand-policy\", \"scan_paths\": [ \"/vol1/\", \"/vol2/cifs/\" ], \"schedule\": { \"name\": \"weekly\", \"uuid\": \"1cd8a442-86d1-11e0-ae1c-123478563412\" }, \"scope\": { \"exclude_extensions\": [ \"mp3\" ], \"exclude_paths\": [ \"/vol/cold-files/\" ], \"include_extensions\": [ \"vmdk\", \"mp*\" ], \"max_file_size\": 1073741824, \"scan_without_extension\": true }}"  
  
# The response:  
{  
  "num_records": 1,  
  "records": [  
    {  
      "svm": {  
        "name": "vs1"  
      },  
      "name": "on-demand-policy",  
      "scan_paths": [  
        "/vol1/",  
        "/vol2/cifs/"  
      ],  
      "log_path": "/vol0/report_dir",  
      "schedule": {  
        "name": "weekly"  
      },  
      "scope": {  
        "max_file_size": 1073741824,  
        "exclude_paths": [  
          "/vol/cold-files/"  
        ],  
      },  
    },  
  ],  
}
```

```

    "include_extensions": [
        "vmdk",
        "mp*"
    ],
    "exclude_extensions": [
        "mp3"
    ],
    "scan_without_extension": true
}
}
]
}
-----

'''

=== Creating a Vscan On-Demand policy where a number of optional fields
are not specified

'''

-----

# The API:
/api/protocols/vscan/{svm.uuid}/on-demand-policies

# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/vscan/86fbc414-f140-11e8-
8e22-0050568e0945/on-demand-policies?return_records=true" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"log_path\":
\"/report\", \"name\": \"on-demand-policy\", \"scan_paths\": [
\"/voll/cifs/\" ], \"scope\": { \"include_extensions\": [ \"mp*\" ],
\"scan_without_extension\": true }}"

# The response:
{
"num_records": 1,
"records": [
{
  "svm": {
    "name": "vs1"
  },
  "name": "on-demand-policy",
  "scan_paths": [
    "voll/cifs/"
  ],

```

```

    "log_path": "/report",
    "scope": {
      "max_file_size": 10737418240,
      "include_extensions": [
        "vmdk",
        "mp*"
      ],
      "scan_without_extension": true
    }
  }
]
}
-----

'''

=== Updating a Vscan On-Demand policy

The policy being modified is identified by the UUID of the SVM and the
policy name.

-----

# The API:
/api/protocols/vscan/{svm.uuid}/on-demand-policies/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/vscan/86fbc414-f140-11e8-
8e22-0050568e0945/on-demand-policies/on-demand-policy" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"schedule\":
{ \"name\": \"weekly\" }, \"scope\": { \"exclude_extensions\": [ \"mp3\"
], \"exclude_paths\": [ \"/vol/\" ], \"include_extensions\": [ \"vmdk\",
\"mp3\" ], \"scan_without_extension\": true }}"
-----

'''

=== Deleting a Vscan On-Demand policy

The policy to be deleted is identified by the UUID of the SVM and the
policy name.

-----

# The API:
/api/protocols/vscan/{svm.uuid}/on-demand-policies/{name}

```

```

# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/vscan/86fbc414-f140-11e8-8e22-0050568e0945/on-demand-policies/on-demand-policy" -H "accept: application/hal+json"
-----

'''

[[ID887c7c4f49ece1a9a522d00e1f3d95d5]]
= Retrieve a Vscan On-Demand policy

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/vscan/{svm.uuid}/on-demand-policies`#

*Introduced In:* 9.6

Retrieves the Vscan On-Demand policy.

== Related ONTAP commands

* `vserver vscan on-demand-task show`

== Learn more

* xref:{relative_path}protocols_vscan_svm.uuid_on-demand-policies_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/on-demand-policies]

== Parameters

[cols=5*,options=header]
|===
|Name
|Type
|In
|Required
|Description

|scan_paths
|string
|query

```

```
|False
a|Filter by scan_paths

|log_path
|string
|query
|False
a|Filter by log_path

|scope.include_extensions
|string
|query
|False
a|Filter by scope.include_extensions

|scope.scan_without_extension
|boolean
|query
|False
a|Filter by scope.scan_without_extension

|scope.max_file_size
|integer
|query
|False
a|Filter by scope.max_file_size

|scope.exclude_paths
|string
|query
|False
a|Filter by scope.exclude_paths

|scope.exclude_extensions
|string
|query
|False
a|Filter by scope.exclude_extensions

|schedule.name
```



```
|string
|query
|False
a|Filter by schedule.name
```

```
|schedule.uuid
|string
|query
|False
a|Filter by schedule.uuid
```

```
|name
|string
|query
|False
a|Filter by name
```

```
|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.
```

```
|fields
|array[string]
|query
|False
a|Specify the fields to return.
```

```
|max_records
|integer
|query
|False
a|Limit the number of records returned.
```

```
|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number of records is returned.
```

\* Default value: 1

|return\_timeout  
|integer  
|query  
|False

a|The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.

\* Default value: 1

\* Max value: 120

\* Min value: 0

|order\_by  
|array[string]  
|query  
|False

a|Order results by specified fields and optional [asc|desc] direction. Default direction is 'asc' for ascending.

|===

== Response

Status: 200, Ok

[cols=3\*,options=header]

|===

|Name  
|Type  
|Description

|\_links  
|link:#\_links[\_links]

a|

|num\_records  
|integer  
a|Number of records

```

|records
|array[link:#vscan_on_demand[vscan_on_demand]]
a|

|===

.Example response
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "log_path": "/vol0/report_dir",
    "name": "task-1",
    "scan_paths": [
      "/vol1/",
      "/vol2/cifs/"
    ],
    "schedule": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "weekly",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "scope": {
      "exclude_extensions": [
        "mp3",
        "mp4"
      ],
      "exclude_paths": [
        "/vol1/cold-files/",
        "/vol1/cifs/names"
      ],
      "include_extensions": [

```

```

        "vmdk",
        "mp*"
    ],
    "max_file_size": "10737418240"
}
}
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]

```

```

.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#schedule]
[.api-collapsible-fifth-title]
schedule

Schedule of the task.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|Job schedule name

|uuid
|string
a|Job schedule UUID

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]

```

```

|===
|Name
|Type
|Description

|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.

|include_extensions
|array[string]
a|List of file extensions to be scanned.

|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.

|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.

|===

[#vscan_on_demand]
[.api-collapsible-fifth-title]
vscan_on_demand

Use On-Demand scanning to check files for viruses on a schedule. An On-
Demand policy defines the scope of an On-Demand scan.

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|log_path
|string
a|The path from the Vserver root where the task report is created.

|name
|string
a|On-Demand task name

|scan_paths
|array[string]
a|List of paths that need to be scanned.

|schedule
|link:#schedule[schedule]
a|Schedule of the task.

|scope
|link:#scope[scope]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

```



```

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDdab4534d15450b4f996470185dd3459c]]
= Create a Vscan On-Demand policy

[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}/on-demand-policies`#

```

\*Introduced In:\* 9.6

Creates a Vscan On-Demand policy. Created only on a data SVM.

Important notes:

\*\*\* Only one policy can be scheduled at a time on an SVM. Use schedule name or schedule uuid to schedule an On-Demand policy.

\*\*\* Scanning must be enabled on the SVM before the policy is scheduled to run.

\*\*\* The `exclude_extensions` setting overrides the `include_extensions` setting. Set `scan_without_extension` to true to scan files without extensions.

== Required properties

- \* ``svm.uuid`` - Existing SVM in which to create the Vscan On-Demand policy.
- \* ``name`` - Name of the Vscan On-Demand policy. Maximum length is 256 characters.
- \* ``log_path`` - Path from the Vserver root where the On-Demand policy report is created.
- \* ``scan_paths`` - List of paths that need to be scanned.

== Recommended optional properties

- \* ``schedule`` - Scan schedule. It is recommended to set the schedule property, as it dictates when to scan for viruses.

== Default property values

If not specified in POST, the following default property values are assigned:

- \* ``include_extensions`` - `_*_`
- \* ``max_file_size`` - `_10737418240_`
- \* ``scan_without_extension`` - `_true_`

== Related ONTAP commands

- \* ``vserver vscan on-demand-task create``
- \* ``vserver vscan on-demand-task schedule``

== Learn more

- \* `xref:{relative_path}protocols_vscan_svm.uuid_on-demand-`

```
policies_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/on-demand-policies]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|return_records
```

```
|boolean
```

```
|query
```

```
|False
```

a|The default is false. If set to true, the records are returned.

\* Default value:

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

a|UUID of the SVM to which this object belongs.

```
|===
```

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|log_path
```

```
|string
```

a|The path from the Vserver root where the task report is created.

```

|name
|string
a|On-Demand task name

|scan_paths
|array[string]
a|List of paths that need to be scanned.

|schedule
|link:#schedule[schedule]
a|Schedule of the task.

|scope
|link:#scope[scope]
a|

|===

```

.Example request

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```

{
  "log_path": "/vol0/report_dir",
  "name": "task-1",
  "scan_paths": [
    "/vol1/",
    "/vol2/cifs/"
  ],
  "schedule": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "weekly",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "scope": {
    "exclude_extensions": [
      "mp3",
      "mp4"
    ]
  }
}

```

```

    ],
    "exclude_paths": [
        "/vol1/cold-files/",
        "/vol1/cifs/names"
    ],
    "include_extensions": [
        "vmdk",
        "mp*"
    ],
    "max_file_size": "10737418240"
}
}
====

== Response

```

Status: 201, Created

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#vscan_on_demand[vscan_on_demand]]
a|

|===

.Example response
[%collapsible%closed]
====
[source,json,subs=+macros]
{
    "_links": {

```

```
"next": {
  "href": "/api/resourcelink"
},
"self": {
  "href": "/api/resourcelink"
}
},
"records": {
  "log_path": "/vol0/report_dir",
  "name": "task-1",
  "scan_paths": [
    "/vol1/",
    "/vol2/cifs/"
  ],
  "schedule": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "weekly",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "scope": {
    "exclude_extensions": [
      "mp3",
      "mp4"
    ],
    "exclude_paths": [
      "/vol1/cold-files/",
      "/vol1/cifs/names"
    ],
    "include_extensions": [
      "vmdk",
      "mp*"
    ],
    "max_file_size": "10737418240"
  }
}
}
====

== Error
```

Status: Default

## ONTAP Error Response Codes

|===

| Error Code | Description

| 10027101

| The file size must be in the range 1KB to 1TB

| 10027107

| The include extensions list cannot be empty. Specify at least one extension for inclusion.

| 10027164

| An On-Demand policy cannot be scheduled, as the Vscan is disabled. Enable the Vscan and retry the operation.

| 10027167

| The specified schedule does not exist. Create the schedule or create a policy without specifying the schedule.

| 10027168

| The specified scan path does not exist. The scan path must be specified from the root of the SVM, and must begin with UNIX path delimiters (use "`/`" not "`\`")

| 10027169

| The specified scan path is not supported for scanning.

| 10027173

| The new On-Demand policy cannot be created as the SVM has reached the maximum number of On-Demand policies allowed. Delete an existing policy in order to create a new policy.

| 10027174

| The specified exclude path is invalid. The path must be specified from the root of the SVM, and must begin with UNIX path delimiters (use "/" not "\")

| 10027175

| An On-Demand policy cannot be scheduled as the Vserver is not in an operational state.

| 10027176

| The log-path specified does not exist. The log path must be specified from the root of the SVM, and must begin with UNIX path delimiters (use "`/`" not "`\`").

```
| 10027177
| The log path specified is not supported.

| 10027253
| The number of paths specified exceeds the configured maximum number of
paths. You cannot specify more than the maximum number of configured
paths.

| 10027254
| The number of extensions specified exceeds the configured maximum number
of extensions. You cannot specify more than the maximum number of
configured extensions.

| 10027255
| Another policy is already scheduled. Only one policy per SVM is allowed
to be scheduled at any one time. Create a policy without specifying a
schedule.
|===
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
```



```

    }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#schedule]
[.api-collapsible-fifth-title]

```

schedule

Schedule of the task.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
 |_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|Job schedule name
```

```
|uuid
```

```
|string
```

```
a|Job schedule UUID
```

```
|===
```

```
[#scope]
```

```
[.api-collapsible-fifth-title]
```

```
scope
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|exclude_extensions
```

```
|array[string]
```

```
a|List of file extensions for which scanning is not performed.
```

```
|exclude_paths
```

```
|array[string]
```

```
a|List of file paths for which scanning must not be performed.
```

```
|include_extensions
|array[string]
a|List of file extensions to be scanned.
```

```
|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.
```

```
|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.
```

```
|===
```

```
[#vscan_on_demand]
[.api-collapsible-fifth-title]
vscan_on_demand
```

Use On-Demand scanning to check files for viruses on a schedule. An On-Demand policy defines the scope of an On-Demand scan.

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|log_path
|string
a|The path from the Vserver root where the task report is created.
```

```
|name
|string
a|On-Demand task name
```

```
|scan_paths
|array[string]
a|List of paths that need to be scanned.
```

```
|schedule
|link:#schedule[schedule]
a|Schedule of the task.
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

```
[#_links]
[.api-collapsible-fifth-title]
_links
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|next
```

```
|link:#href[href]
```

```
a|
```

```
|self
```

```
|link:#href[href]
```

```
a|
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|code
```

```
|string
```

```
a|Argument code
```

```

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

```

```
[[ID732814ed4829d256ad6b9ad3f4e358f4]]
= Delete a Vscan On-Demand configuration
```

```
[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}/on-demand-policies/{name}`#
```

\*Introduced In:\* 9.6

Deletes the Vscan On-Demand configuration.

== Related ONTAP commands

\* `vserver vscan on-demand-task delete`

== Learn more

\* xref:{relative\_path}protocols\_vscan\_svm.uuid\_on-demand-
policies\_endpoint\_overview.html[DOC /protocols/vscan/{svm.uuid}/on-demand-
policies]

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
|Type
|In
|Required
|Description
```

```
|name
|string
|path
|True
a|
```

```
|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.
```

```
|===
```

```
== Response
```

Status: 200, Ok

```
== Error
```

Status: Default, Error

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```



```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[IDa2bc461ec362cbcb4b93e8e553bf0d6a]]
```

```
= Retrieve the Vscan On-Demand configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-  
block]#`/protocols/vscan/{svm.uuid}/on-demand-policies/{name}`#
```

```
*Introduced In:* 9.6
```

```
Retrieves the Vscan On-Demand configuration of an SVM.
```

```
== Related ONTAP commands
```

```
* `vserver vscan on-demand-task show`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_vscan_svm.uuid_on-demand-  
policies_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/on-demand-  
policies]
```

```
== Parameters
```

```
[cols=5*,options=header]
```

```
|===
```

```
|Name  
|Type  
|In  
|Required  
|Description
```

```
|name
```

```
|string
|path
|True
a|

|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|===

== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|log_path
|string
a|The path from the Vserver root where the task report is created.

|name
|string
a|On-Demand task name

|scan_paths
|array[string]
a|List of paths that need to be scanned.

|schedule
```

```
|link:#schedule[schedule]
```

```
a|Schedule of the task.
```

```
|scope
```

```
|link:#scope[scope]
```

```
a|
```

```
|===
```

```
.Example response
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
```

```
{  
  "log_path": "/vol0/report_dir",  
  "name": "task-1",  
  "scan_paths": [  
    "/vol1/",  
    "/vol2/cifs/"  
  ],  
  "schedule": {  
    "_links": {  
      "self": {  
        "href": "/api/resourcelink"  
      }  
    },  
    "name": "weekly",  
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"  
  },  
  "scope": {  
    "exclude_extensions": [  
      "mp3",  
      "mp4"  
    ],  
    "exclude_paths": [  
      "/vol1/cold-files/",  
      "/vol1/cifs/names"  
    ],  
    "include_extensions": [  
      "vmdk",  
      "mp*"  
    ],  
    "max_file_size": "10737418240"  
  }  
}
```

```
}  
====  
  
== Error
```

Status: Default, Error

```
[cols=3*,options=header]  
|===  
|Name  
|Type  
|Description  
  
|error  
|link:#error[error]  
a|  
  
|===  
  
.Example error  
[%collapsible%closed]  
====  
[source,json,subs=+macros]  
{  
  "error": {  
    "arguments": {  
      "code": "string",  
      "message": "string"  
    },  
    "code": "4",  
    "message": "entry doesn't exist",  
    "target": "uuid"  
  }  
}  
====  
  
== Definitions  
  
[.api-def-first-level]  
.See Definitions  
[%collapsible%closed]  
//Start collapsible Definitions block  
====  
[#href]  
[.api-collapsible-fifth-title]
```

```

href

[cols=3*,options=header]
|===
|Name
|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#schedule]
[.api-collapsible-fifth-title]
schedule

Schedule of the task.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]

```

```

a|

|name
|string
a|Job schedule name

|uuid
|string
a|Job schedule UUID

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.

|include_extensions
|array[string]
a|List of file extensions to be scanned.

|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.

|scan_without_extension
|boolean

```

a|Specifies whether or not files without any extension can be scanned.

|===

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

|===

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

|===

```
[#error]
[.api-collapsible-fifth-title]
error
```

```
[cols=3*,options=header]
```

|===

```
|Name
|Type
|Description
```

```
|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments
```

```
|code
|string
a|Error code
```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[ID1354d159499d04a55f3066e1ff307afc]]
= Update the Vscan On-Demand policy configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}/on-demand-policies/{name}`#
```

```
*Introduced In:* 9.6
```

Updates the Vscan On-Demand policy configuration of an SVM. Use schedule name or schedule UUID to schedule an On-Demand scan.

```
== Related ONTAP commands
```

```
* `vserver vscan on-demand-task modify`
* `vserver vscan on-demand-task schedule`
* `vserver vscan on-demand-task unschedule`
```

```
== Learn more
```

```
* xref:{relative_path}protocols_vscan_svm.uuid_on-demand-
policies_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/on-demand-
policies]
```

```
== Parameters
```

```
[cols=5*,options=header]
```



```
|===
```

```
|Name  
|Type  
|In  
|Required  
|Description
```

```
|name  
|string  
|path  
|True  
a|
```

```
|svm.uuid  
|string  
|path  
|True  
a|UUID of the SVM to which this object belongs.
```

```
|===
```

```
== Request Body
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name  
|Type  
|Description
```

```
|log_path  
|string  
a|The path from the Vserver root where the task report is created.
```

```
|name  
|string  
a|On-Demand task name
```

```
|scan_paths  
|array[string]  
a|List of paths that need to be scanned.
```

```
|schedule
|link:#schedule[schedule]
a|Schedule of the task.
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

.Example request

[%collapsible%closed]

```
=====
```

```
[source,json,subs=+macros]
```

```
{
  "log_path": "/vol0/report_dir",
  "name": "task-1",
  "scan_paths": [
    "/vol1/",
    "/vol2/cifs/"
  ],
  "schedule": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "weekly",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "scope": {
    "exclude_extensions": [
      "mp3",
      "mp4"
    ],
    "exclude_paths": [
      "/vol1/cold-files/",
      "/vol1/cifs/names"
    ],
    "include_extensions": [
      "vmdk",
      "mp*"
    ],
    "max_file_size": "10737418240"
  }
}
```

```
}  
}  
====  
  
== Response
```

Status: 200, Ok

```
== Error
```

Status: Default

#### ONTAP Error Response Codes

```
|====  
| Error Code | Description  
  
| 10027101  
| The file size must be in the range 1KB to 1TB  
  
| 10027107  
| The include extensions list cannot be empty. Specify at least one  
extension for inclusion.  
  
| 10027164  
| An On-Demand policy cannot be scheduled, as the Vscan is disabled.  
Enable the Vscan and retry the operation.  
  
| 10027167  
| The specified schedule does not exist. Create the schedule or create a  
policy without specifying the schedule.  
  
| 10027168  
| The specified scan path does not exist. The scan path must be specified  
from the root of the SVM, and must begin with UNIX path delimiters (use  
"\/" not "\\")  
  
| 10027169  
| The specified scan path is not supported for scanning.  
  
| 10027174  
| The specified exclude path is invalid. The path must be specified from  
the root of the SVM, and must begin with UNIX path delimiters (use "/" not  
"\")
```

```

| 10027175
| An On-Demand policy cannot be scheduled as the SVM is not in an
operational state.

| 10027176
| The log-path specified does not exist. The log path must be specified
from the root of the SVM, and must begin with UNIX path delimiters (use
"/" not "\")

| 10027177
| The log path specified is not supported.

| 10027253
| The number of paths specified exceeds the configured maximum number of
paths. You cannot specify more than the maximum number of configured
paths.

| 10027254
| The number of extensions specified exceeds the configured maximum number
of extensions. You cannot specify more than the maximum number of
configured extensions.

| 10027255
| Another policy is already scheduled. Only one policy per SVM is allowed
to be scheduled at any one time. Update a policy without specifying a
schedule.
|===

```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```

{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

```

== Definitions

```

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====

```

```

[#href]
[.api-collapsible-fifth-title]
href

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|href
|string
a|

```

```

|===

```

```

[#_links]
[.api-collapsible-fifth-title]
_links

```

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|self
|link:#href[href]
a|

|===

[#schedule]
[.api-collapsible-fifth-title]
schedule

Schedule of the task.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|Job schedule name

|uuid
|string
a|Job schedule UUID

|===

[#scope]
[.api-collapsible-fifth-title]
scope

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```
|exclude_extensions
|array[string]
a|List of file extensions for which scanning is not performed.

|exclude_paths
|array[string]
a|List of file paths for which scanning must not be performed.

|include_extensions
|array[string]
a|List of file extensions to be scanned.

|max_file_size
|integer
a|Maximum file size, in bytes, allowed for scanning.

|scan_without_extension
|boolean
a|Specifies whether or not files without any extension can be scanned.

|===

[#vscan_on_demand]
[.api-collapsible-fifth-title]
vscan_on_demand

Use On-Demand scanning to check files for viruses on a schedule. An On-
Demand policy defines the scope of an On-Demand scan.

[cols=3*,options=header]
|===
|Name
|Type
|Description

|log_path
|string
a|The path from the Vserver root where the task report is created.
```

```
|name
|string
a|On-Demand task name

|scan_paths
|array[string]
a|List of paths that need to be scanned.
```

```
|schedule
|link:#schedule[schedule]
a|Schedule of the task.
```

```
|scope
|link:#scope[scope]
a|
```

```
|===
```

```
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|code
|string
a|Argument code
```

```
|message
|string
a|Message argument
```

```
|===
```

```
[#error]
[.api-collapsible-fifth-title]
```



```

error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

:leveloffset: -1

= Manage Vscan scanner-pool configuration

:leveloffset: +1

[[ID88aac23d5513469cbce2bdc04e1db6e7]]
= Protocols Vscan svm.uuid scanner-pools endpoint overview

```

## == Overview

A scanner-pool defines the Vscan servers and privileged users that can connect to SVMs and a scanner policy or role determines whether a scanner-pool is active. You can configure a scanner-pool to be used on the local cluster or any other cluster in an MCC/DR setup.

## == Examples

=== Retrieving all fields for all scanner-pools of an SVM

----

# The API:

```
/api/protocols/vscan/{svm.uuid}/scanner-pools
```

# The call:

```
curl -X GET "https://<mgmt-ip>/api/protocols/vscan/<svm-uuid>/scanner-pools?fields=*&return_records=true&return_timeout=15" -H "accept: application/json"
```

# The response:

```
{
  "records": [
    {
      "svm": {
        "uuid": "0e2f7c91-f227-11e8-9601-0050568ecc06"
      },
      "name": "scanner-1",
      "servers": [
        "1.1.1.1",
        "10.72.204.27"
      ],
      "privileged_users": [
        "cifs\\u1",
        "cifs\\u2"
      ],
      "role": "primary"
    },
    {
      "svm": {
        "uuid": "0e2f7c91-f227-11e8-9601-0050568ecc06"
      },
      "name": "scanner-2",
```

```

    "servers": [
      "1.1.1.1",
      "10.72.204.27"
    ],
    "privileged_users": [
      "cifs\\u1",
      "cifs\\u2"
    ],
    "role": "secondary"
  }
],
"num_records": 2
}
----

=== Retrieving all scanner-pools with _role_ set as _secondary_

----

# The API:
/api/protocols/vscan/{svm.uuid}/scanner-pools

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/vscan/<svm-uuid>/scanner-pools?role=secondary&fields=*&return_records=true&return_timeout=15" -H "accept: application/json"

# The response:
{
"records": [
  {
    "svm": {
      "uuid": "0e2f7c91-f227-11e8-9601-0050568ecc06",
      "name": "vs1"
    },
    "name": "scanner-2",
    "servers": [
      "1.1.1.1",
      "10.72.204.27"
    ],
    "privileged_users": [
      "cifs\\u1",
      "cifs\\u2"
    ],
    "role": "secondary",
    "cluster": {

```

```

        "uuid": "0933f9b5-f226-11e8-9601-0050568ecc06",
        "name": "Cluster3"
    }
}
],
"num_records": 1
}
-----

=== Retrieving the specified scanner-pool associated with an SVM

-----

# The API:
/api/protocols/vscan/{svm.uuid}/scanner-pools/{name}

# The call:
curl -X GET "https://<mgmt-ip>/api/protocols/vscan/0e2f7c91-f227-11e8-9601-0050568ecc06/scanner-pools/scanner-1?fields=*" -H "accept: application/json"

# The response:
{
  "svm": {
    "uuid": "0e2f7c91-f227-11e8-9601-0050568ecc06",
    "name": "vs1"
  },
  "name": "scanner-1",
  "servers": [
    "1.1.1.1",
    "10.72.204.27"
  ],
  "privileged_users": [
    "cifs\\u1",
    "cifs\\u2"
  ],
  "role": "primary",
  "cluster": {
    "uuid": "0933f9b5-f226-11e8-9601-0050568ecc06",
    "name": "Cluster3"
  }
}
-----

=== Creating a scanner-pool for an SVM with all fields specified

```

```
-----  
  
# The API:  
/api/protocols/vscan/{svm.uuid}/scanner-pools/  
  
# The call:  
curl -X POST "https://<mgmt-ip>/api/protocols/vscan/b103be27-17b8-11e9-  
b451-0050568ecd85/scanner-pools?return_records=true" -H "accept:  
application/json" -H "Content-Type: application/json" -d "{ \"cluster\": {  
  \"name\": \"Cluster1\", \"uuid\": \"ab746d77-17b7-11e9-b450-0050568ecd85\"  
}, \"name\": \"test-scanner\", \"privileged_users\": [ \"cifs\\u1\",  
  \"cifs\\u2\" ], \"role\": \"primary\", \"servers\": [ \"1.1.1.1\",  
  \"10.72.204.27\" ]}"
```

```
# The response:  
{  
  "num_records": 1,  
  "records": [  
    {  
      "name": "test-scanner",  
      "servers": [  
        "1.1.1.1",  
        "10.72.204.27"  
      ],  
      "privileged_users": [  
        "cifs\\u1",  
        "cifs\\u2"  
      ],  
      "role": "primary",  
      "cluster": {  
        "uuid": "ab746d77-17b7-11e9-b450-0050568ecd85",  
        "name": "Cluster1"  
      }  
    }  
  ]  
}
```

```
-----  
  
=== Creating a scanner-pool for an SVM with an unspecified role and  
cluster
```

```
-----  
  
# The API:  
/api/protocols/vscan/{svm.uuid}/scanner-pools/
```

```
# The call:
curl -X POST "https://<mgmt-ip>/api/protocols/vscan/b103be27-17b8-11e9-
b451-0050568ecd85/scanner-pools" -H "accept: application/json" -H
"Content-Type: application/json" -d "{ \"name\": \"test-scanner-1\",
\"privileged_users\": [ \"cifs\\\\u1\", \"cifs\\\\u2\" ], \"servers\": [
\"1.1.1.1\", \"10.72.204.27\" ]}"
```

```
# The response:
```

```
{
"num_records": 1,
"records": [
  {
    "name": "test-scanner-1",
    "servers": [
      "1.1.1.1",
      "10.72.204.27"
    ],
    "privileged_users": [
      "cifs\\u1",
      "cifs\\u2"
    ]
  }
]
}
-----
```

```
=== Updating a scanner-pool for an SVM with all of the fields specified
```

```
# The API:
```

```
/api/protocols/vscan/{svm.uuid}/scanner-pools/{name}
```

```
# The call:
```

```
curl -X PATCH "https://<mgmt-ip>/api/protocols/vscan/0e2f7c91-f227-11e8-
9601-0050568ecc06/scanner-pools/test-scanner-1" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"cluster\": {
\"name\": \"Cluster3\", \"uuid\": \"0933f9b5-f226-11e8-9601-0050568ecc06\"
}, \"privileged_users\": [ \"cifs\\\\u1\", \"cifs\\\\u2\" ], \"role\":
\"secondary\", \"servers\": [ \"1.1.1.1\", \"10.72.204.27\" ]}"
```

```
=== Updating the "role" of a scanner-pool for an SVM
```

```
# The API:
/api/protocols/vscan/{svm.uuid}/scanner-pools/{name}

# The call:
curl -X PATCH "https://<mgmt-ip>/api/protocols/vscan/0e2f7c91-f227-11e8-9601-0050568ecc06/scanner-pools/test-scanner-1" -H "accept: application/json" -H "Content-Type: application/json" -d "{ \"cluster\": { \"name\": \"Cluster3\", \"uuid\": \"0933f9b5-f226-11e8-9601-0050568ecc06\" }, \"role\": \"primary\"}"
```

----

=== Deleting a scanner-pool for a specified SVM

----

```
# The API:
/api/protocols/vscan/{svm.uuid}/scanner-pools/{name}
```

```
# The call:
curl -X DELETE "https://<mgmt-ip>/api/protocols/vscan/0e2f7c91-f227-11e8-9601-0050568ecc06/scanner-pools/test-scanner-1" -H "accept: application/json"
```

----

```
[[ID03d58b8a72d5967dbc0de66e17a175cc]]
= Retrieve the Vscan scanner-pool configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-block]#`/protocols/vscan/{svm.uuid}/scanner-pools`#
```

\*Introduced In:\* 9.6

Retrieves the Vscan scanner-pool configuration of an SVM.

== Related ONTAP commands

```
* `vserver vscan scanner-pool show`
* `vserver vscan scanner-pool privileged-users show`
* `vserver vscan scanner-pool servers show`
* `vserver vscan scanner-pool show-active`
```

== Learn more

```
* xref:{relative_path}protocols_vscan_svm.uuid_scanner-  
pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-  
pools]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|cluster.name
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by cluster.name
```

```
|cluster.uuid
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by cluster.uuid
```

```
|role
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by role
```

```
|privileged_users
```

```
|string
```

```
|query
```

```
|False
```

```
a|Filter by privileged_users
```

```
|name
```

```
|string
```

```
|query
```



```
|False
a|Filter by name

|servers
|string
|query
|False
a|Filter by servers

|svm.uuid
|string
|path
|True
a|UUID of the SVM to which this object belongs.

|fields
|array[string]
|query
|False
a|Specify the fields to return.

|max_records
|integer
|query
|False
a|Limit the number of records returned.

|return_records
|boolean
|query
|False
a|The default is true for GET calls. When set to false, only the number
of records is returned.

* Default value: 1

|return_timeout
|integer
|query
|False
a|The number of seconds to allow the call to execute before returning.
```

When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.

- \* Default value: 1
- \* Max value: 120
- \* Min value: 0

```
|order_by
|array[string]
|query
|False
a|Order results by specified fields and optional [asc|desc] direction.
Default direction is 'asc' for ascending.
```

```
|===
```

== Response

Status: 200, Ok

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#vscan_scanner_pool[vscan_scanner_pool]]
a|

|===
```

.Example response  
[%collapsible%closed]

```

====
[source,json,subs=+macros]
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "cluster": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "cluster1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "name": "scanner-1",
    "privileged_users": [
      "cifs\\u1",
      "cifs\\u2"
    ],
    "role": "primary",
    "servers": [
      "1.1.1.1",
      "10.72.204.27",
      "vmwin204-27.fsct.nb"
    ]
  }
}
====

== Error

```

Status: Default, Error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```
|error
|link:#error[error]
a|
```

```
|===
```

```
.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
```

```
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

```
====
```

```
== Definitions
```

```
[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
```

```
====
```

```
[#href]
[.api-collapsible-fifth-title]
href
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|href
|string
a|
```

```

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:href[href]
a|

|self
|link:href[href]
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:href[href]
a|

|===

[#cluster_reference]
[.api-collapsible-fifth-title]
cluster_reference

[cols=3*,options=header]
|===

```

```
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|
```

```
|name
|string
a|
```

```
|uuid
|string
a|
```

```
|===
```

```
[#vscan_scanner_pool]
[.api-collapsible-fifth-title]
vscan_scanner_pool
```

Scanner pool is a set of attributes which are used to validate and manage connections between clustered ONTAP and external virus-scanning server, or "Vscan server".

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
|Type
|Description
```

```
|cluster
|link:#cluster_reference[cluster_reference]
a|
```

```
|name
|string
a|Specifies the name of the scanner pool. Scanner pool name can be up to 256 characters long and is a string that can only contain any combination of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "_", "-" and ".".
```

```
|privileged_users
|array[string]
```

a|Specifies a list of privileged users. A valid form of privileged user-name is "domain-name\user-name". Privileged user-names are stored and treated as case-insensitive strings. Virus scanners must use one of the registered privileged users for connecting to clustered Data ONTAP for exchanging virus-scanning protocol messages and to access file for scanning, remedying and quarantining operations.

\* example: ["cifs\u1", "cifs\u2"]

\* Introduced in: 9.6

\* x-omitempty: true

|role

|string

a|Specifies the role of the scanner pool. The possible values are:

\*\*\* primary - Always active.

\*\*\* secondary - Active only when none of the primary external virus-scanning servers are connected.

\*\*\* idle - Always inactive.

|servers

|array[string]

a|Specifies a list of IP addresses or FQDN for each Vscan server host names which are allowed to connect to clustered ONTAP.

\* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]

\* Introduced in: 9.6

\* x-omitempty: true

|===

[#error\_arguments]

[.api-collapsible-fifth-title]

error\_arguments

[cols=3\*,options=header]

|===

|Name

|Type

|Description

```

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block

```



====

[[IDafe8025175354f13dc098a7283cf9aa4]]

= Create a Vscan scanner-pool configuration for an SVM

[.api-doc-operation .api-doc-operation-post]#POST# [.api-doc-code-block]#`/protocols/vscan/{svm.uuid}/scanner-pools`#

\*Introduced In:\* 9.6

Creates a Vscan scanner-pool configuration for a specified SVM. You can create a scanner-pool with all fields specified or only mandatory fields specified.

Important notes:

- \* A scanner-pool must have servers and privileged users specified.
- \* If the role or cluster is not specified, the scanner-pool is created on the local cluster with the role set as primary.
- \* `Only one of the fields cluster-uuid or cluster-name is required.

== Required properties

- \* `svm.uuid` or `svm.name` - Existing SVM in which to create the Vscan configuration.
- \* `name` - Scanner-pool name.
- \* `privileged\_users` - List of privileged users.
- \* `servers` - List of server IP addresses or FQDNs.

== Recommended optional properties

- \* `role` - Setting a role for a scanner-pool is recommended.
- \* `cluster` - Passing the cluster name or UUID (or both) in a multi-cluster environment is recommended.

== Default property values

If not specified in POST, the following default property values are assigned:

- \* `role` - `_primary_`
- \* `cluster.name` - Local cluster name.
- \* `cluster.uuid` - Local cluster UUID.

== Related ONTAP commands

```
* `vserver vscan scanner-pool create`  
* `vserver vscan scanner-pool apply-policy`  
* `vserver vscan scanner-pool privileged-users add`  
* `vserver vscan scanner-pool servers add`
```

== Learn more

```
* xref:{relative_path}protocols_vscan_svm.uuid_scanner-  
pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-  
pools]
```

== Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|return_records
```

```
|boolean
```

```
|query
```

```
|False
```

```
a|The default is false. If set to true, the records are returned.
```

```
* Default value:
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```

== Request Body

```
[cols=3*,options=header]
```

```
|===
```

```

|Name
|Type
|Description

|cluster
|link:#cluster_reference[cluster_reference]
a|

|name
|string
a|Specifies the name of the scanner pool. Scanner pool name can be up to
256 characters long and is a string that can only contain any combination
of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "_", "-" and ".".

|privileged_users
|array[string]
a|Specifies a list of privileged users. A valid form of privileged user-
name is "domain-name\user-name". Privileged user-names are stored and
treated as case-insensitive strings. Virus scanners must use one of the
registered privileged users for connecting to clustered Data ONTAP for
exchanging virus-scanning protocol messages and to access file for
scanning, remedying and quarantining operations.

* example: ["cifs\u1", "cifs\u2"]
* Introduced in: 9.6
* x-omitempty: true

|role
|string
a|Specifies the role of the scanner pool. The possible values are:

*** primary    - Always active.

*** secondary - Active only when none of the primary external virus-
scanning servers are connected.

*** idle       - Always inactive.

|servers
|array[string]
a|Specifies a list of IP addresses or FQDN for each Vscan server host
names which are allowed to connect to clustered ONTAP.

* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]

```

```
* Introduced in: 9.6
```

```
* x-omitempty: true
```

```
|===
```

```
.Example request
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{
  "cluster": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "cluster1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "name": "scanner-1",
  "privileged_users": [
    "cifs\\u1",
    "cifs\\u2"
  ],
  "role": "primary",
  "servers": [
    "1.1.1.1",
    "10.72.204.27",
    "vmwin204-27.fsct.nb"
  ]
}
```

```
====
```

```
== Response
```

Status: 201, Created

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
a|

|num_records
|integer
a|Number of records

|records
|array[link:#vscan_scanner_pool[vscan_scanner_pool]]
a|

|===
```

.Example response

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "records": {
    "cluster": {
      "_links": {
        "self": {
          "href": "/api/resourcelink"
        }
      },
      "name": "cluster1",
      "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
    },
    "name": "scanner-1",
    "privileged_users": [
      "cifs\\u1",
      "cifs\\u2"
    ],
    "role": "primary",
    "servers": [
      "1.1.1.1",
```

```

    "10.72.204.27",
    "vmwin204-27.fsct.nb"
  ]
}
}
====

== Error

```

### Status: Default

```

ONTAP Error Response Codes
//start table
[cols=2*,options=header]
|===
//header
| Error Code | Description
//end header
//end row
//start row
|10027086 +
//end row
//start row
|The specified list of servers contain one or more entries that cannot be
resolved
//end row
//start row
|10027258 +
//end row
//start row
|The specified cluster_name does not exist
//end row
//start row
|10027256 +
//end row
//start row
|The specified cluster_uuid does not exist
//end row
//start row
|10027257 +
//end row
//start row
|The specified cluster_name and cluster_uuid are valid but belong to
different clusters
//end row

```

```

//start row
|10027248 +
//end row
//start row
|Scanner-pool created successfully but failed to activate
//end row
//start row
|10027107 +
//end row
//start row
|The list of privileged users or list of servers specified is empty
//end row
//start row
|10027108 +
//end row
//start row
|The list of privileged users specified contains an invalid entry
//end row
//start row
|10027063 +
//end row
//start row
|Attempting to modify a scanner-pool on an administrative SVM with a data
SVM
//end row
|===
//end table

```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|error
```

```
|link:#error[error]
```

```
a|
```

```
|===
```

```
.Example error
```

```
[%collapsible%closed]
```

```
=====
```

```
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====
```

== Definitions

```
[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
```

```
[#href]
[.api-collapsible-fifth-title]
href
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description
```

```
|href
|string
a|
```

```
|===
```

```
[_links]
[.api-collapsible-fifth-title]
_links
```

```
[cols=3*,options=header]
|===
|Name
|Type
```



```
|Description
```

```
|self
```

```
|link:#href[href]
```

```
a|
```

```
|===
```

```
[#cluster_reference]
```

```
[.api-collapsible-fifth-title]
```

```
cluster_reference
```

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|_links
```

```
|link:#_links[_links]
```

```
a|
```

```
|name
```

```
|string
```

```
a|
```

```
|uuid
```

```
|string
```

```
a|
```

```
|===
```

```
[#vscan_scanner_pool]
```

```
[.api-collapsible-fifth-title]
```

```
vscan_scanner_pool
```

Scanner pool is a set of attributes which are used to validate and manage connections between clustered ONTAP and external virus-scanning server, or "Vscan server".

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

|Description

|cluster

|link:#cluster\_reference[cluster\_reference]

a|

|name

|string

a|Specifies the name of the scanner pool. Scanner pool name can be up to 256 characters long and is a string that can only contain any combination of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "\_", "-" and ".".

|privileged\_users

|array[string]

a|Specifies a list of privileged users. A valid form of privileged user-name is "domain-name\user-name". Privileged user-names are stored and treated as case-insensitive strings. Virus scanners must use one of the registered privileged users for connecting to clustered Data ONTAP for exchanging virus-scanning protocol messages and to access file for scanning, remedying and quarantining operations.

\* example: ["cifs\u1", "cifs\u2"]

\* Introduced in: 9.6

\* x-omitempty: true

|role

|string

a|Specifies the role of the scanner pool. The possible values are:

\*\*\* primary - Always active.

\*\*\* secondary - Active only when none of the primary external virus-scanning servers are connected.

\*\*\* idle - Always inactive.

|servers

|array[string]

a|Specifies a list of IP addresses or FQDN for each Vscan server host names which are allowed to connect to clustered ONTAP.

\* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]

\* Introduced in: 9.6

\* x-omitempty: true

```

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|next
|link:#href[href]
a|

|self
|link:#href[href]
a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

```

```

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

[[IDb743820a01f7d8fea2acabfcc8b0c739]]
= Delete the Vscan scanner-pool configuration

[.api-doc-operation .api-doc-operation-delete]#DELETE# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}/scanner-pools/{name}`#

*Introduced In:* 9.6

```

Deletes a Vscan scanner-pool configuration.

Important notes:

\* The Vscan scanner-pool DELETE endpoint deletes all of the Vscan scanner-pools for a specified SVM.

\* If a Vscan is enabled, it requires at least one scanner-pool to be in the active state. Therefore, disable Vscan on the specified SVM so all the scanner-pools configured on that SVM can be deleted.

== Related ONTAP commands

\* ``vserver vscan scanner-pool delete``

== Learn more

\* `xref:{relative_path}protocols_vscan_svm.uuid_scanner-pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-pools]`

== Parameters

[cols=5\*,options=header]

|===

|Name

|Type

|In

|Required

|Description

|name

|string

|path

|True

a|

|svm.uuid

|string

|path

|True

a|UUID of the SVM to which this object belongs.

|===

== Response

Status: 200, Ok

== Error

Status: Default

```
ONTAP Error Response Codes
//start table
[cols=2*,options=header]
|===
//header
| Error Code | Description
//end header
//end row
//start row
|10027070 +
//end row
//start row
|Attempting to delete a scanner-pool but it is the only active scanner-
pool for a Vscan enabled on the SVM
//end row
//start row
|10027064 +
//end row
//start row
|Attempting to delete a scanner-pool with a data SVM which was created
with an administrative SVM
//end row
|===
//end table

[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|
```

```

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

```

```

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
=====

[[IDd103dbc92267c25b03d251752ffb58ef]]
= Retrieve the Vscan scanner-pool configuration for an SVM

[.api-doc-operation .api-doc-operation-get]#GET# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}/scanner-pools/{name}`#

```



\*Introduced In:\* 9.6

Retrieves the configuration of a specified scanner-pool of an SVM.

== Related ONTAP commands

```
* `vserver vscan scanner-pool show`  
* `vserver vscan scanner-pool privileged-users show`  
* `vserver vscan scanner-pool servers show`  
* `vserver vscan scanner-pool show-active`
```

== Learn more

```
* xref:{relative_path}protocols_vscan_svm.uuid_scanner-  
pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-  
pools]
```

== Parameters

[cols=5\*,options=header]

|===

Name
Type
In
Required
Description

name
string
path
True
a

svm.uuid
string
path
True
a UUID of the SVM to which this object belongs.

fields
array[string]
query
False
a Specify the fields to return.

```
|===
```

```
== Response
```

Status: 200, Ok

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|cluster
```

```
|link:#cluster_reference[cluster_reference]
```

```
a|
```

```
|name
```

```
|string
```

a|Specifies the name of the scanner pool. Scanner pool name can be up to 256 characters long and is a string that can only contain any combination of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "\_", "-" and ".".

```
|privileged_users
```

```
|array[string]
```

a|Specifies a list of privileged users. A valid form of privileged user-name is "domain-name\user-name". Privileged user-names are stored and treated as case-insensitive strings. Virus scanners must use one of the registered privileged users for connecting to clustered Data ONTAP for exchanging virus-scanning protocol messages and to access file for scanning, remedying and quarantining operations.

```
* example: ["cifs\u1", "cifs\u2"]
```

```
* Introduced in: 9.6
```

```
* x-omitempty: true
```

```
|role
```

```
|string
```

a|Specifies the role of the scanner pool. The possible values are:

```
*** primary - Always active.
```

```
*** secondary - Active only when none of the primary external virus-scanning servers are connected.
```

```
*** idle      - Always inactive.
```

```
|servers
```

```
|array[string]
```

```
a|Specifies a list of IP addresses or FQDN for each Vscan server host names which are allowed to connect to clustered ONTAP.
```

```
* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]
```

```
* Introduced in: 9.6
```

```
* x-omitempty: true
```

```
|===
```

```
.Example response
```

```
[%collapsible%closed]
```

```
====
```

```
[source,json,subs=+macros]
```

```
{  
  "cluster": {  
    "_links": {  
      "self": {  
        "href": "/api/resourcelink"  
      }  
    },  
    "name": "cluster1",  
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"  
  },  
  "name": "scanner-1",  
  "privileged_users": [  
    "cifs\\u1",  
    "cifs\\u2"  
  ],  
  "role": "primary",  
  "servers": [  
    "1.1.1.1",  
    "10.72.204.27",  
    "vmwin204-27.fsct.nb"  
  ]  
}
```

```
====
```

```
== Error
```

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
```

```

|Type
|Description

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#cluster_reference]
[.api-collapsible-fifth-title]
cluster_reference

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|

|uuid
|string

```

```

a|

|===

[#error_arguments]
[.api-collapsible-fifth-title]
error_arguments

[cols=3*,options=header]
|===
|Name
|Type
|Description

|code
|string
a|Argument code

|message
|string
a|Message argument

|===

[#error]
[.api-collapsible-fifth-title]
error

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

```

```
|message
|string
a|Error message
```

```
|target
|string
a|The target parameter that caused the error.
```

```
|===
```

```
//end collapsible .Definitions block
=====
```

```
[[ID706068b498c6604037845b724ae98a48]]
= Update the Vscan scanner-pool configuration for an SVM
```

```
[.api-doc-operation .api-doc-operation-patch]#PATCH# [.api-doc-code-
block]#`/protocols/vscan/{svm.uuid}/scanner-pools/{name}`#
```

```
*Introduced In:* 9.6
```

Updates the Vscan scanner-pool configuration of an SVM.

Important notes:

- \* Along with servers and privileged-users, the role of a scanner-pool can also be updated with the cluster on which a scanner-pool is allowed.
- \* If role is specified and cluster isn't, then role is applied to the local cluster.

== Related ONTAP commands

- \* ``vserver vscan scanner-pool modify``
- \* ``vserver vscan scanner-pool apply-policy``
- \* ``vserver vscan scanner-pool privileged-users add``
- \* ``vserver vscan scanner-pool privileged-users remove``
- \* ``vserver vscan scanner-pool servers remove``
- \* ``vserver vscan scanner-pool servers add``

== Learn more

```
* xref:{relative_path}protocols_vscan_svm.uuid_scanner-  
pools_endpoint_overview.html[DOC /protocols/vscan/{svm.uuid}/scanner-  
pools]
```

#### == Parameters

```
[cols=5*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|In
```

```
|Required
```

```
|Description
```

```
|name
```

```
|string
```

```
|path
```

```
|True
```

```
a|
```

```
|svm.uuid
```

```
|string
```

```
|path
```

```
|True
```

```
a|UUID of the SVM to which this object belongs.
```

```
|===
```

#### == Request Body

```
[cols=3*,options=header]
```

```
|===
```

```
|Name
```

```
|Type
```

```
|Description
```

```
|cluster
```

```
|link:#cluster_reference[cluster_reference]
```

```
a|
```

```
|name
```

```
|string
```

```
a|Specifies the name of the scanner pool. Scanner pool name can be up to
```



256 characters long and is a string that can only contain any combination of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "\_", "-" and ".".

|privileged\_users

|array[string]

a|Specifies a list of privileged users. A valid form of privileged user-name is "domain-name\user-name". Privileged user-names are stored and treated as case-insensitive strings. Virus scanners must use one of the registered privileged users for connecting to clustered Data ONTAP for exchanging virus-scanning protocol messages and to access file for scanning, remedying and quarantining operations.

\* example: ["cifs\u1", "cifs\u2"]

\* Introduced in: 9.6

\* x-omitempty: true

|role

|string

a|Specifies the role of the scanner pool. The possible values are:

\*\*\* primary - Always active.

\*\*\* secondary - Active only when none of the primary external virus-scanning servers are connected.

\*\*\* idle - Always inactive.

|servers

|array[string]

a|Specifies a list of IP addresses or FQDN for each Vscan server host names which are allowed to connect to clustered ONTAP.

\* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]

\* Introduced in: 9.6

\* x-omitempty: true

|===

.Example request

[%collapsible%closed]

====

[source,json,subs=+macros]

```
{
  "cluster": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "cluster1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "name": "scanner-1",
  "privileged_users": [
    "cifs\\u1",
    "cifs\\u2"
  ],
  "role": "primary",
  "servers": [
    "1.1.1.1",
    "10.72.204.27",
    "vmwin204-27.fsct.nb"
  ]
}
====

== Response
```

Status: 200, Ok

```
== Error
```

Status: Default

```
ONTAP Error Response Codes
//start table
[cols=2*,options=header]
|===
//header
| Error Code | Description
//end header
//end row
//start row
|10027258 +
//end row
//start row
```

```
|The specified cluster_name does not exist
//end row
//start row
|10027256 +
//end row
//start row
|The specified cluster_uuid does not exist
//end row
//start row
|10027257 +
//end row
//start row
|The specified cluster_name and cluster_uuid are valid but belong to
different clusters
//end row
//start row
|10027248 +
//end row
//start row
|Scanner-pool updated successfully but failed to apply the specified role
//end row
//start row
|10027107 +
//end row
//start row
|The list of privileged users or list of servers specified is empty
//end row
//start row
|10027108 +
//end row
//start row
|The list of privileged users specified contains an invalid entry
//end row
//start row
|10027063 +
//end row
//start row
|Attempting to modify a scanner-pool on an administrative SVM with a data
SVM
//end row
|===
//end table
```

```
[cols=3*,options=header]
```

```

|===
|Name
|Type
|Description

|error
|link:#error[error]
a|

|===

.Example error
[%collapsible%closed]
=====
[source,json,subs=+macros]
{
  "error": {
    "arguments": {
      "code": "string",
      "message": "string"
    },
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
=====

== Definitions

[.api-def-first-level]
.See Definitions
[%collapsible%closed]
//Start collapsible Definitions block
=====
[#href]
[.api-collapsible-fifth-title]
href

[cols=3*,options=header]
|===
|Name
|Type
|Description

```

```

|href
|string
a|

|===

[#_links]
[.api-collapsible-fifth-title]
_links

[cols=3*,options=header]
|===
|Name
|Type
|Description

|self
|link:#href[href]
a|

|===

[#cluster_reference]
[.api-collapsible-fifth-title]
cluster_reference

[cols=3*,options=header]
|===
|Name
|Type
|Description

|_links
|link:#_links[_links]
a|

|name
|string
a|

|uuid
|string
a|

|===

```

```
[#vscan_scanner_pool]
[.api-collapsible-fifth-title]
vscan_scanner_pool
```

Scanner pool is a set of attributes which are used to validate and manage connections between clustered ONTAP and external virus-scanning server, or "Vscan server".

```
[cols=3*,options=header]
|===
|Name
|Type
|Description

|cluster
|link:#cluster_reference[cluster_reference]
a|
```

```
|name
|string
a|Specifies the name of the scanner pool. Scanner pool name can be up to 256 characters long and is a string that can only contain any combination of ASCII-range alphanumeric characters a-z, A-Z, 0-9), "_", "-" and ".".
```

```
|privileged_users
|array[string]
a|Specifies a list of privileged users. A valid form of privileged user-name is "domain-name\user-name". Privileged user-names are stored and treated as case-insensitive strings. Virus scanners must use one of the registered privileged users for connecting to clustered Data ONTAP for exchanging virus-scanning protocol messages and to access file for scanning, remedying and quarantining operations.
```

```
* example: ["cifs\u1", "cifs\u2"]
* Introduced in: 9.6
* x-omitempty: true
```

```
|role
|string
a|Specifies the role of the scanner pool. The possible values are:
```

```
*** primary - Always active.
```

\*\*\* secondary - Active only when none of the primary external virus-scanning servers are connected.

\*\*\* idle - Always inactive.

|servers

|array[string]

a|Specifies a list of IP addresses or FQDN for each Vscan server host names which are allowed to connect to clustered ONTAP.

\* example: ["1.1.1.1", "10.72.204.27", "vmwin204-27.fsct.nb"]

\* Introduced in: 9.6

\* x-omitempty: true

|===

[#error\_arguments]

[.api-collapsible-fifth-title]

error\_arguments

[cols=3\*,options=header]

|===

|Name

|Type

|Description

|code

|string

a|Argument code

|message

|string

a|Message argument

|===

[#error]

[.api-collapsible-fifth-title]

error

```

[cols=3*,options=header]
|===
|Name
|Type
|Description

|arguments
|array[link:#error_arguments[error_arguments]]
a|Message arguments

|code
|string
a|Error code

|message
|string
a|Error message

|target
|string
a|The target parameter that caused the error.

|===

//end collapsible .Definitions block
====

:leveloffset: -1

:leveloffset: -1

:leveloffset: -1

<<<
*Copyright information*

```

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form



or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b) (3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

\*Trademark information\*

NETAPP, the NETAPP logo, and the marks listed at [link:http://www.netapp.com/TM](http://www.netapp.com/TM)<sup>[http://www.netapp.com/TM^]</sup> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.