# Manage storage aggregate plexes

## REST API reference

NetApp
September 12, 2025

This PDF was generated from https://docs.netapp.com/us-en/ontap-restapi-991/storage_aggregates_aggregate.uuid_plexes_endpoint_overview.html on September 12, 2025. Always check docs.netapp.com for the latest.

# Table of Contents


Manage storage aggregate plexes . . . 1
- Storage aggregates aggregate.uuid plexes endpoint overview . . . 1
  - Overview . . . 1
  - Examples . . . 1
- Retrieve a collection of plexes for an aggregate . . . 3
  - Related ONTAP commands . . . 4
  - Parameters . . . 4
  - Response . . . 7
  - Error . . . 9
  - Definitions . . . 10
- Retrieve a plex specified by the aggregate UUID and plex name . . . 14
  - Related ONTAP commands . . . 14
  - Parameters . . . 14
  - Response . . . 14
  - Error . . . 16
  - Definitions . . . 16

# Manage storage aggregate plexes

## Storage aggregates aggregate.uuid plexes endpoint overview

### Overview

The Storage Aggregate Plex API provides relevant state information for each plex in the aggregate. For each plex, details are provided for the RAID groups in the plex and the disks that make up each RAID group.

### Examples

#### Retrieving the list of plexes in an aggregate

The following example shows the response with the list of plexes in an aggregate:

```
# The API:
/api/storage/aggregates/{uuid}/plexes

# The call:
curl -X GET "https://<mgmt-ip>/api/storage/aggregates/19425837-f2fa-4a9f-
8f01-712f626c983c/plexes" -H "accept: application/json"

# The response:
{
"records": [
  {
    "name": "plex0",
  },
  {
    "name": "plex4",
  }
],
"num_records": 2,
}
```

#### Retrieving a specific plex in an aggregate

The following example shows the response when requesting a specific plex of an aggregate:

```
# The API:
/api/storage/aggregates/{uuid}/plexes/{name}

# The call:
curl -X GET "https://<mgmt-ip>/api/storage/aggregates/19425837-f2fa-4a9f-
```

```
8f01-712f626c983c/plexes/plex0" -H "accept: application/json"

# The response:
{
"aggregate": {
  "uuid": "19425837-f2fa-4a9f-8f01-712f626c983c",
  "name": "test1",
},
"name": "plex0",
"online": true,
"state": "normal",
"pool": "pool0",
"resync": {
  "active": false
},
"raid_groups": [
  {
    "name": "rg0",
    "raid_type": "raid_dp",
    "cache_tier": false,
    "degraded": false,
    "recomputing_parity": {
      "active": false
    },
    "reconstruct": {
      "active": false
    },
    "disks": [
      {
        "position": "dparity",
        "state": "normal",
        "type": "ssd",
        "usable_size": 86769664,
        "disk": {
          "name": "1.1.29",
        }
      },
      {
        "position": "parity",
        "state": "normal",
        "type": "ssd",
        "usable_size": 86769664,
        "disk": {
          "name": "1.1.4",
        }
      },
```

```
      {
        "position": "data",
        "state": "normal",
        "type": "ssd",
        "usable_size": 86769664,
        "disk": {
          "name": "1.1.30",
        }
      },
      {
        "position": "data",
        "state": "normal",
        "type": "ssd",
        "usable_size": 86769664,
        "disk": {
          "name": "1.1.5",
        }
      },
      {
        "position": "data",
        "state": "normal",
        "type": "ssd",
        "usable_size": 86769664,
        "disk": {
          "name": "1.1.31",
        }
      },
      {
        "position": "data",
        "state": "normal",
        "type": "ssd",
        "usable_size": 86769664,
        "disk": {
          "name": "1.1.6",
        }
      }
    ]
  }
],
}
```


# Retrieve a collection of plexes for an aggregate

GET `/storage/aggregates/{aggregate.uuid}/plexes`

**Introduced In:** 9.6

Retrieves the collection of plexes for the specified aggregate.

## Related ONTAP commands

- `storage aggregate plex show`

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| aggregate.uuid | string | path | True | Aggregate UUID |
| pool | string | query | False | Filter by pool |
| resync.active | boolean | query | False | Filter by resync.active |
| resync.percent | integer | query | False | Filter by resync.percent |
| resync.level | string | query | False | Filter by resync.level |
| state | string | query | False | Filter by state |
| name | string | query | False | Filter by name |
| aggregate.name | string | query | False | Filter by aggregate.name |
| online | boolean | query | False | Filter by online |
| raid_groups.recomputing_parity.percent | integer | query | False | Filter by raid_groups.recomputing_parity.percent<br>• Introduced in: 9.7 |
| raid_groups.recomputing_parity.active | boolean | query | False | Filter by raid_groups.recomputing_parity.active<br>• Introduced in: 9.7 |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| raid_groups.reconstruct.active | boolean | query | False | Filter by raid_groups.reconstruct.active<br>• Introduced in: 9.7 |
| raid_groups.reconstruct.percent | integer | query | False | Filter by raid_groups.reconstruct.percent<br>• Introduced in: 9.7 |
| raid_groups.raid_type | string | query | False | Filter by raid_groups.raid_type<br>• Introduced in: 9.9 |
| raid_groups.disks.disk.name | string | query | False | Filter by raid_groups.disks.disk.name<br>• Introduced in: 9.7 |
| raid_groups.disks.type | string | query | False | Filter by raid_groups.disks.type<br>• Introduced in: 9.7 |
| raid_groups.disks.state | string | query | False | Filter by raid_groups.disks.state<br>• Introduced in: 9.7 |
| raid_groups.disks.usable_size | integer | query | False | Filter by raid_groups.disks.usable_size<br>• Introduced in: 9.7 |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| raid_groups.disks.position | string | query | False | Filter by raid_groups.disks.position<br>• Introduced in: 9.7 |
| raid_groups.degraded | boolean | query | False | Filter by raid_groups.degraded<br>• Introduced in: 9.7 |
| raid_groups.cache_tier | boolean | query | False | Filter by raid_groups.cache_tier<br>• Introduced in: 9.7 |
| raid_groups.name | string | query | False | Filter by raid_groups.name<br>• Introduced in: 9.7 |
| fields | array[string] | query | False | Specify the fields to return. |
| max_records | integer | query | False | Limit the number of records returned. |
| return_records | boolean | query | False | The default is true for GET calls. When set to false, only the number of records is returned.<br>• Default value: 1 |

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| return_timeout | integer | query | False | The number of seconds to allow the call to execute before returning. When iterating over a collection, the default is 15 seconds. ONTAP returns earlier if either max records or the end of the collection is reached.<br>• Default value: 1<br>• Max value: 120<br>• Min value: 0 |
| order_by | array[string] | query | False | Order results by specified fields and optional [asc |

## Response

```
Status: 200, Ok
```

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| error | error | |
| num_records | integer | Number of records |
| records | array[plex] | |

**Example response**


```
{
  "_links": {
    "next": {
      "href": "/api/resourcelink"
    },
    "self": {
      "href": "/api/resourcelink"
    }
  },
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  },
  "records": [
    {
      "aggregate": {
        "_links": {
          "self": {
            "href": "/api/resourcelink"
          }
        },
        "name": "aggr1",
        "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
      },
      "name": "plex0",
      "pool": "string",
      "raid_groups": [
        {
          "disks": [
            {
              "disk": {
                "_links": {
                  "self": {
                    "href": "/api/resourcelink"
                  }
                },
                "name": "1.0.1"
```

```
              },
              "position": "string",
              "state": "string",
              "type": "ssd",
              "usable_size": "947912704"
            }
          ],
          "name": "rg0",
          "raid_type": "raid_dp",
          "recomputing_parity": {
            "percent": "10"
          },
          "reconstruct": {
            "percent": "10"
          }
        }
      ],
      "resync": {
        "level": "string",
        "percent": "10"
      },
      "state": "string"
    }
  ]
}
```


## Error

```
Status: Default, Error
```

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**


```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```


## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| next | href | |
| self | href | |

error_arguments

| Name | Type | Description |
|---|---|---|
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
|---|---|---|
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

aggregate

Aggregate

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |

| Name | Type | Description |
|---|---|---|
| uuid | string | |

disk

Disk

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |

raid_group_disk

| Name | Type | Description |
|---|---|---|
| disk | disk | Disk |
| position | string | The position of the disk within the RAID group. |
| state | string | The state of the disk within the RAID group. |
| type | string | Disk interface type |
| usable_size | integer | Size in bytes that is usable by the aggregate. |

recomputing_parity

| Name | Type | Description |
|---|---|---|
| active | boolean | RAID group is recomputing parity |
| percent | integer | Recomputing parity percentage |

reconstruct

| Name | Type | Description |
|---|---|---|
| active | boolean | One or more disks in this RAID group are being reconstructed. |
| percent | integer | Reconstruct percentage |

raid_group

| Name | Type | Description |
|---|---|---|
| cache_tier | boolean | RAID group is a cache tier |
| degraded | boolean | RAID group is degraded. A RAID group is degraded when at least one disk from that group has failed or is offline. |
| disks | array[raid_group_disk] | |
| name | string | RAID group name |
| raid_type | string | RAID type of the raid group. |
| recomputing_parity | recomputing_parity | |
| reconstruct | reconstruct | |

resync

| Name | Type | Description |
|---|---|---|
| active | boolean | Plex is being resynchronized to its mirrored plex |
| level | string | Plex resyncing level |
| percent | integer | Plex resyncing percentage |

plex

| Name | Type | Description |
|---|---|---|
| aggregate | aggregate | Aggregate |
| name | string | Plex name |
| online | boolean | Plex is online |
| pool | string | SyncMirror pool assignment |
| raid_groups | array[raid_group] | |
| resync | resync | |
| state | string | Plex state |

# Retrieve a plex specified by the aggregate UUID and plex name

GET `/storage/aggregates/{aggregate.uuid}/plexes/{name}`

**Introduced In:** 9.6

Retrieves the plex specified by the aggregate UUID and plex name.

## Related ONTAP commands

- `storage aggregate plex show`

## Parameters

| Name | Type | In | Required | Description |
|---|---|---|---|---|
| aggregate.uuid | string | path | True | Aggregate UUID |
| name | string | path | True | Plex name |
| fields | array[string] | query | False | Specify the fields to return. |

## Response

```
Status: 200, Ok
```

| Name | Type | Description |
|---|---|---|
| aggregate | aggregate | Aggregate |
| name | string | Plex name |
| online | boolean | Plex is online |
| pool | string | SyncMirror pool assignment |
| raid_groups | array[raid_group] | |
| resync | resync | |
| state | string | Plex state |

**Example response**


```
{
  "aggregate": {
    "_links": {
      "self": {
        "href": "/api/resourcelink"
      }
    },
    "name": "aggr1",
    "uuid": "1cd8a442-86d1-11e0-ae1c-123478563412"
  },
  "name": "plex0",
  "pool": "string",
  "raid_groups": [
    {
      "disks": [
        {
          "disk": {
            "_links": {
              "self": {
                "href": "/api/resourcelink"
              }
            },
            "name": "1.0.1"
          },
          "position": "string",
          "state": "string",
          "type": "ssd",
          "usable_size": "947912704"
        }
      ],
      "name": "rg0",
      "raid_type": "raid_dp",
      "recomputing_parity": {
        "percent": "10"
      },
      "reconstruct": {
        "percent": "10"
      }
    }
  ],
  "resync": {
    "level": "string",
    "percent": "10"
  },
```

```
  "state": "string"
}
```

## Error

```
Status: Default, Error
```

| Name | Type | Description |
|---|---|---|
| error | error | |

**Example error**

```
{
  "error": {
    "arguments": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "code": "4",
    "message": "entry doesn't exist",
    "target": "uuid"
  }
}
```

## Definitions

**See Definitions**

href

| Name | Type | Description |
|---|---|---|
| href | string | |

_links

| Name | Type | Description |
|---|---|---|
| self | href | |

aggregate

Aggregate

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |
| uuid | string | |

disk

Disk

| Name | Type | Description |
|---|---|---|
| _links | _links | |
| name | string | |

raid_group_disk

| Name | Type | Description |
|---|---|---|
| disk | disk | Disk |
| position | string | The position of the disk within the RAID group. |
| state | string | The state of the disk within the RAID group. |
| type | string | Disk interface type |
| usable_size | integer | Size in bytes that is usable by the aggregate. |

recomputing_parity

| Name | Type | Description |
|---|---|---|
| active | boolean | RAID group is recomputing parity |
| percent | integer | Recomputing parity percentage |

reconstruct

| Name | Type | Description |
|---|---|---|
| active | boolean | One or more disks in this RAID group are being reconstructed. |
| percent | integer | Reconstruct percentage |

raid_group

| Name | Type | Description |
|---|---|---|
| cache_tier | boolean | RAID group is a cache tier |
| degraded | boolean | RAID group is degraded. A RAID group is degraded when at least one disk from that group has failed or is offline. |
| disks | array[raid_group_disk] | |
| name | string | RAID group name |
| raid_type | string | RAID type of the raid group. |
| recomputing_parity | recomputing_parity | |
| reconstruct | reconstruct | |

resync

| Name | Type | Description |
|---|---|---|
| active | boolean | Plex is being resynchronized to its mirrored plex |
| level | string | Plex resyncing level |
| percent | integer | Plex resyncing percentage |

error_arguments

| Name | Type | Description |
| --- | --- | --- |
| code | string | Argument code |
| message | string | Message argument |

error

| Name | Type | Description |
| --- | --- | --- |
| arguments | array[error_arguments] | Message arguments |
| code | string | Error code |
| message | string | Error message |
| target | string | The target parameter that caused the error. |

## Copyright information

Copyright © 2025 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.