



# **RHEL**

## **SAN Host**

NetApp  
May 25, 2022

# Table of Contents

- RHEL ..... 1
  - NVMe-oF Host Configuration for RHEL 8.4 with ONTAP ..... 1
  - NVMe/FC Host Configuration for RHEL 8.3 with ONTAP ..... 14
  - NVMe/FC Host Configuration for RHEL 8.2 with ONTAP ..... 24
  - NVMe/FC Host Configuration for RHEL 8.1 with ONTAP ..... 33

# RHEL

## NVMe-oF Host Configuration for RHEL 8.4 with ONTAP

### Supportability

NVMe over Fabrics or NVMe-oF (including NVMe/FC and other transports) is supported with RHEL 8.4 with ANA (Asymmetric Namespace Access). ANA is the ALUA equivalent in the NVMe-oF environment, and is currently implemented with in-kernel NVMe Multipath. The details for enabling NVMe-oF with in-kernel NVMe Multipath using ANA on RHEL 8.4 and ONTAP as the target has been documented [here](#).

### Features

- Starting RHEL 8.2, `nvme-fc auto-connect` scripts are included in the native `nvme-cli` package. You can rely on these native auto-connect scripts instead of having to install the external vendor provided outbox auto-connect scripts.
- Starting RHEL 8.2, a native `udev` rule is already provided as part of the `nvme-cli` package which enables round-robin load balancing for NVMe multipath. You need not manually create this rule any more (as was done in RHEL 8.1).
- Starting RHEL 8.2, both NVMe and SCSI traffic can be run on the same co-existent host. In fact, that is expected to be the commonly deployed host config for customers. Therefore, for SCSI, you may configure `dm-multipath` as usual for SCSI LUNs resulting in `mpath` devices, whereas NVMe multipath may be used to configure NVMe-oF multipath devices on the host.
- Starting RHEL 8.2, the NetApp plugin in the native `nvme-cli` package is capable of displaying ONTAP details as well for ONTAP namespaces.

### Known limitations

- For RHEL 8.4, in-kernel NVMe multipath remains disabled by default. Therefore, you need to enable it manually.
- NVMe/TCP on RHEL 8.4 remains a Technology Preview feature due to open issues. Refer to the [RHEL 8.4 Release Notes](#) for details.

### Configuration requirements

Refer to the [NetApp Interoperability Matrix](#) for accurate details regarding supported configurations.

### Enable in-kernel NVMe Multipath

1. Install RHEL 8.4 GA on the server. After the installation is complete, verify that you are running the specified RHEL 8.4 GA kernel. See the [NetApp Interoperability Matrix](#) for the most current list of supported versions.
2. After the installation is complete, verify that you are running the specified RHEL 8.4 kernel. See the [NetApp Interoperability Matrix](#) for the most current list of supported versions.

Example:

```
# uname -r
4.18.0-305.el8.x86_64
```

### 3. Install the `nvme-cli` package:

Example:

```
# rpm -qa|grep nvme-cli
nvme-cli-1.12-3.el8.x86_64
```

### 4. Enable in-kernel NVMe multipath:

```
# grubby --args=nvme_core.multipath=Y --update-kernel /boot/vmlinuz-
4.18.0-305.el8.x86_64
```

### 5. On the host, check the host NQN string at `/etc/nvme/hostnqn` and verify that it matches the host NQN string for the corresponding subsystem on the ONTAP array. Example:

```
# cat /etc/nvme/hostnqn
nqn.2014-08.org.nvmexpress:uuid:9ed5b327-b9fc-4cf5-97b3-1b5d986345d1
::> vserver nvme subsystem host show -vserver vs_fcnvme_141
Vserver      Subsystem      Host NQN
-----
vs_fcnvme_14 nvme_141_1     nqn.2014-08.org.nvmexpress:uuid:9ed5b327-
b9fc-4cf5-97b3-1b5d986345d1
```



If the host NQN strings do not match, you should use the `vserver modify` command to update the host NQN string on your corresponding ONTAP NVMe subsystem to match the host NQN string `/etc/nvme/hostnqn` on the host.

### 6. Reboot the host.

If you intend to run both NVMe & SCSI co-existent traffic on the same host, it is recommended to use in-kernel NVMe multipath for ONTAP namespaces and dm-multipath for ONTAP LUNs respectively. This means that the ONTAP namespaces should be excluded from dm-multipath to prevent dm-multipath from claiming these namespace devices. This can be done by adding the `enable_foreign` setting to the `/etc/multipath.conf` file:



```
# cat /etc/multipath.conf
defaults {
    enable_foreign    NONE
}
```

7. Restart the multipathd daemon by running a `systemctl restart multipathd` command to allow the new setting to take effect.

## Configure NVMe/FC

### Broadcom/Emulex

1. Verify that you are using the supported adapter. See the [NetApp Interoperability Matrix](#) for the most current list of supported adapters.

```
# cat /sys/class/scsi_host/host*/modelname
LPe32002-M2
LPe32002-M2
# cat /sys/class/scsi_host/host*/modeldesc
Emulex LightPulse LPe32002-M2 2-Port 32Gb Fibre Channel Adapter
Emulex LightPulse LPe32002-M2 2-Port 32Gb Fibre Channel Adapter
```

2. Verify that you are using the recommended Broadcom lpfc firmware and inbox driver. See the [NetApp Interoperability Matrix](#) for the most current list of supported adapter driver and firmware versions.

```
# cat /sys/class/scsi_host/host*/fwrev
12.8.340.8, sli-4:2:c
12.8.340.8, sli-4:2:c
# cat /sys/module/lpfc/version
0:12.8.0.5
```

3. Verify that `lpfc_enable_fc4_type` is set to 3

```
# cat /sys/module/lpfc/parameters/lpfc_enable_fc4_type
3
```

4. Verify that the initiator ports are up and running, and you are able to see the target LIFs.

```

# cat /sys/class/fc_host/host*/port_name
0x100000109b1c1204
0x100000109b1c1205
# cat /sys/class/fc_host/host*/port_state
Online
Online
# cat /sys/class/scsi_host/host*/nvme_info
NVME Initiator Enabled
XRI Dist lpfc0 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc0 WWPN x100000109b1c1204 WWNN x200000109b1c1204 DID
x011d00 ONLINE
NVME RPORT WWPN x203800a098dfdd91 WWNN x203700a098dfdd91 DID x010c07
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203900a098dfdd91 WWNN x203700a098dfdd91 DID x011507
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000f78 Cmpl 0000000f78 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002fe29bba Issue 000000002fe29bc4 OutIO
0000000000000000a
abort 00001bc7 noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001e15 Err 0000d906
NVME Initiator Enabled
XRI Dist lpfc1 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc1 WWPN x100000109b1c1205 WWNN x200000109b1c1205 DID
x011900 ONLINE
NVME RPORT WWPN x203d00a098dfdd91 WWNN x203700a098dfdd91 DID x010007
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203a00a098dfdd91 WWNN x203700a098dfdd91 DID x012a07
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000fa8 Cmpl 0000000fa8 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002e14f170 Issue 000000002e14f17a OutIO
0000000000000000a
abort 000016bb noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001f50 Err 0000d9f8

```

#### Enable 1MB I/O size (Optional)

ONTAP reports an MDTS (Max Data Transfer Size) of 8 in the Identify Controller data which means the maximum I/O request size should be up to 1 MB. However, to issue I/O requests of size 1 MB for the Broadcom NVMe/FC host, the lpfc parameter `lpfc_sg_seg_cnt` should also be bumped up to 256 from the

default value of 64. Use the following instructions to do so:

1. Append the value 256 in the respective `modprobe lpfc.conf` file:

```
# cat /etc/modprobe.d/lpfc.conf
options lpfc lpfc_sg_seg_cnt=256
```

2. Run a `dracut -f` command, and reboot the host.
3. After reboot, verify that the above setting has been applied by checking the corresponding `sysfs` value:

```
# cat /sys/module/lpfc/parameters/lpfc_sg_seg_cnt
256
```

Now the Broadcom FC-NVMe host should be able to send up to 1MB I/O requests on the ONTAP namespace devices.

## Marvell/QLogic

The native inbox `qla2xxx` driver included in the RHEL 8.4 GA kernel has the latest upstream fixes which are essential for ONTAP support.

1. Verify that you are running the supported adapter driver and firmware versions using the following command:

```
# cat /sys/class/fc_host/host*/symbolic_name
QLE2742 FW:v9.06.02 DVR:v10.02.00.104-k
QLE2742 FW:v9.06.02 DVR:v10.02.00.104-k
```

2. Verify `ql2xnvmeenable` is set which enables the Marvell adapter to function as a NVMe/FC initiator using the following command:

```
# cat /sys/module/qla2xxx/parameters/ql2xnvmeenable
1
```

## Configure NVMe/TCP

Unlike NVMe/FC, NVMe/TCP has no auto-connect functionality. This manifests two major limitations on the Linux NVMe/TCP host:

- **No auto-reconnect after paths get reinstated** NVMe/TCP cannot automatically reconnect to a path that is reinstated beyond the default `ctrl-loss-tmo` timer of 10 minutes following a path down.
- **No auto-connect during host bootup** NVMe/TCP cannot automatically connect during host bootup as well.

To comfortably tide over ONTAP failover events such as SFOs, it is advised to set a longer retry period such as say 30 minutes by tweaking the `ctrl_loss_tmo` timer. Following are the details:

1. Verify whether the initiator port can fetch the discovery log page data across the supported NVMe/TCP LIFs:

```
# nvme discover -t tcp -w 192.168.1.8 -a 192.168.1.51
Discovery Log Number of Records 10, Generation counter 119
====Discovery Log Entry 0====
trtype: tcp
adrfam: ipv4
subtype: nvme subsystem
treq: not specified
portid: 0
trsvcid: 4420
subnqn: nqn.1992-
08.com.netapp:sn.56e362e9bb4f11ebbade039ea165abc:subsystem.nvme_118_tcp
_1
traddr: 192.168.2.56
sectype: none
====Discovery Log Entry 1====
trtype: tcp
adrfam: ipv4
subtype: nvme subsystem
treq: not specified
portid: 1
trsvcid: 4420
subnqn: nqn.1992-
08.com.netapp:sn.56e362e9bb4f11ebbade039ea165abc:subsystem.nvme_118_tcp
_1
traddr: 192.168.1.51
sectype: none
====Discovery Log Entry 2====
trtype: tcp
adrfam: ipv4
subtype: nvme subsystem
treq: not specified
portid: 0
trsvcid: 4420
subnqn: nqn.1992-
08.com.netapp:sn.56e362e9bb4f11ebbade039ea165abc:subsystem.nvme_118_tcp
_2
traddr: 192.168.2.56
sectype: none
...
```



2. Verify that other NVMe/TCP initiator-target LIF combos are able to successfully fetch discovery log page data. For example,

```
# nvme discover -t tcp -w 192.168.1.8 -a 192.168.1.52
# nvme discover -t tcp -w 192.168.2.9 -a 192.168.2.56
# nvme discover -t tcp -w 192.168.2.9 -a 192.168.2.57
```

3. Run `nvme connect-all` command across all the supported NVMe/TCP initiator-target LIFs across the nodes. Ensure you pass a longer `ctrl_loss_tmo` period (such as say 30 minutes, which can be set through `-l 1800`) during the connect-all so that it would retry for a longer period in the event of a path loss. For example,

```
# nvme connect-all -t tcp -w 192.168.1.8 -a 192.168.1.51 -l 1800
# nvme connect-all -t tcp -w 192.168.1.8 -a 192.168.1.52 -l 1800
# nvme connect-all -t tcp -w 192.168.2.9 -a 192.168.2.56 -l 1800
# nvme connect-all -t tcp -w 192.168.2.9 -a 192.168.2.57 -l 1800
```

## Validate NVMe-oF

1. Verify that in-kernel NVMe multipath is indeed enabled by checking:

```
# cat /sys/module/nvme_core/parameters/multipath
Y
```

2. Verify that the appropriate NVMe-oF settings (such as, `model` set to NetApp ONTAP Controller and load balancing `iopolicy` set to round-robin) for the respective ONTAP namespaces properly reflect on the host:

```
# cat /sys/class/nvme-subsystem/nvme-subsys*/model
NetApp ONTAP Controller
NetApp ONTAP Controller

# cat /sys/class/nvme-subsystem/nvme-subsys*/iopolicy
round-robin
round-robin
```

3. Verify that the ONTAP namespaces properly reflect on the host. For example,

```
# nvme list
Node          SN                      Model                      Namespace
-----
/dev/nvme0n1  81CZ5BQuUNfGAAAAAAB  NetApp ONTAP Controller    1

Usage          Format          FW Rev
-----
85.90 GB / 85.90 GB  4 KiB + 0 B  FFFFFFFF
```

Another example:

```
# nvme list
Node          SN                      Model                      Namespace
-----
/dev/nvme0n1  81CYrBQuTHQFAAAAAAAC  NetApp ONTAP Controller    1

Usage          Format          FW Rev
-----
85.90 GB / 85.90 GB  4 KiB + 0 B  FFFFFFFF
```

4. Verify that the controller state of each path is live and has proper ANA status. For example,

```
# nvme list-subsys /dev/nvme1n1
nvme-subsys1 - NQN=nqn.1992-
08.com.netapp:sn.04ba0732530911ea8e8300a098dfdd91:subsystem.nvme_145_1
\
+- nvme2 fc traddr=nn-0x208100a098dfdd91:pn-0x208200a098dfdd91
host_traddr=nn-0x200000109b579d5f:pn-0x100000109b579d5f live non-
optimized
+- nvme3 fc traddr=nn-0x208100a098dfdd91:pn-0x208500a098dfdd91
host_traddr=nn-0x200000109b579d5e:pn-0x100000109b579d5e live non-
optimized
+- nvme4 fc traddr=nn-0x208100a098dfdd91:pn-0x208400a098dfdd91
host_traddr=nn-0x200000109b579d5e:pn-0x100000109b579d5e live optimized
+- nvme6 fc traddr=nn-0x208100a098dfdd91:pn-0x208300a098dfdd91
host_traddr=nn-0x200000109b579d5f:pn-0x100000109b579d5f live optimized
```

Another example:

```
#nvme list-subsys /dev/nvme0n1
nvme-subsys0 - NQN=nqn.1992-
08.com.netapp:sn.37ba7d9cbfba11eba35dd039ea165514:subsystem.nvme_114_tcp
_1
\
+- nvme0 tcp traddr=192.168.2.36 trsvcid=4420 host_traddr=192.168.1.4
live optimized
+- nvme1 tcp traddr=192.168.1.31 trsvcid=4420 host_traddr=192.168.1.4
live optimized
+- nvme10 tcp traddr=192.168.2.37 trsvcid=4420 host_traddr=192.168.1.4
live non-optimized
+- nvme11 tcp traddr=192.168.1.32 trsvcid=4420 host_traddr=192.168.1.4
live non-optimized
+- nvme20 tcp traddr=192.168.2.36 trsvcid=4420 host_traddr=192.168.2.5
live optimized
+- nvme21 tcp traddr=192.168.1.31 trsvcid=4420 host_traddr=192.168.2.5
live optimized
+- nvme30 tcp traddr=192.168.2.37 trsvcid=4420 host_traddr=192.168.2.5
live non-optimized
+- nvme31 tcp traddr=192.168.1.32 trsvcid=4420 host_traddr=192.168.2.5
live non-optimized
```

5. Verify that the NetApp plug-in displays proper values for each ONTAP namespace device. For example,

```

# nvme netapp ontapdevices -o column
Device          Vserver          Namespace Path
-----          -
-----
/dev/nvme1n1 vserver_fcnvme_145 /vol/fcnvme_145_vol_1_0_0/fcnvme_145_ns

NSID  UUID                               Size
----  -
1     23766b68-e261-444e-b378-2e84dbe0e5e1 85.90GB

# nvme netapp ontapdevices -o json
{
  "ONTAPdevices" : [
    {
      "Device" : "/dev/nvme1n1",
      "Vserver" : "vserver_fcnvme_145",
      "Namespace_Path" : "/vol/fcnvme_145_vol_1_0_0/fcnvme_145_ns",
      "NSID" : 1,
      "UUID" : "23766b68-e261-444e-b378-2e84dbe0e5e1",
      "Size" : "85.90GB",
      "LBA_Data_Size" : 4096,
      "Namespace_Size" : 20971520
    }
  ]
}

```

Another example:

```

# nvme netapp ontapdevices -o column
Device          Vserver          Namespace Path
-----
-----
/dev/nvme0n1 vs_tcp_114      /vol/tcpnvme_114_1_0_1/tcpnvme_114_ns

NSID  UUID                               Size
-----
1      a6aee036-e12f-4b07-8e79-4d38a9165686 85.90GB

# nvme netapp ontapdevices -o json
{
  "ONTAPdevices" : [
    {
      "Device" : "/dev/nvme0n1",
      "Vserver" : "vs_tcp_114",
      "Namespace_Path" : "/vol/tcpnvme_114_1_0_1/tcpnvme_114_ns",
      "NSID" : 1,
      "UUID" : "a6aee036-e12f-4b07-8e79-4d38a9165686",
      "Size" : "85.90GB",
      "LBA_Data_Size" : 4096,
      "Namespace_Size" : 20971520
    }
  ]
}

```

## Troubleshooting

Before commencing any troubleshooting for any NVMe/FC failures, ensure that you are running a configuration that is compliant to the IMT specifications and then proceed with the next steps to debug any host side issues.

### LPFC Verbose Logging

1. You can set the `lpfc_log_verbose` driver setting to any of the following values to log NVMe/FC events:

```

#define LOG_NVME 0x00100000 /* NVME general events. */
#define LOG_NVME_DISC 0x00200000 /* NVME Discovery/Connect events. */
#define LOG_NVME_ABTS 0x00400000 /* NVME ABTS events. */
#define LOG_NVME_IOERR 0x00800000 /* NVME IO Error events. */

```

2. After setting any of these values, run `dracut-f` command to recreate the `initramfs` and reboot the host.

### 3. After rebooting, verify the settings:

```
# cat /etc/modprobe.d/lpfc.conf
options lpfc lpfc_log_verbose=0xf00083

# cat /sys/module/lpfc/parameters/lpfc_log_verbose
15728771
```

### qla2xxx Verbose Logging

There is no similar specific qla2xxx logging for NVMe/FC as for lpfc driver. Therefore, you may set the general qla2xxx logging level using the following steps:

1. Append the `ql2xextended_error_logging=0x1e400000` value to the corresponding `modprobe qla2xxx` conf file.
2. Recreate the `initramfs` by running `dracut -f` command and then reboot the host.
3. After reboot, verify that the verbose logging has been applied as follows:

```
# cat /etc/modprobe.d/qla2xxx.conf
options qla2xxx ql2xnvmeenable=1 ql2xextended_error_logging=0x1e400000
# cat /sys/module/qla2xxx/parameters/ql2xextended_error_logging
507510784
```

### Common nvme-cli Errors and Workarounds

The errors displayed by `nvme-cli` during `nvme discover`, `nvme connect` or `nvme connect-all` operations and the workarounds are shown in the following table:

Errors displayed by <code>nvme-cli</code>	Probable cause	Workaround
Failed to write to <code>/dev/nvme-fabrics</code> : Invalid argument	Incorrect syntax	Ensure you are using the correct syntax for the above <code>nvme</code> commands.

Errors displayed by nvme-cli	Probable cause	Workaround
<p>Failed to write to /dev/nvme-fabrics: No such file or directory</p>	<p>Multiple issues could trigger this. Passing wrong arguments to the nvme commands is one of the common causes.</p>	<ul style="list-style-type: none"> <li>• Ensure you have passed the correct arguments (such as, correct WWNN string, WWPN string, and more) to the commands.</li> <li>• If the arguments are correct, but you still see this error, check if the <code>/sys/class/scsi_host/host*/nvme_info</code> output is proper, the NVMe initiator showing as Enabled, and the NVMe/FC target LIFs properly showing up here under the remote ports sections. Example: <div data-bbox="792 583 1489 1850" style="border: 1px solid #ccc; padding: 10px; background-color: #f9f9f9;"> <pre># cat /sys/class/scsi_host/host*/nvme_info NVME Initiator Enabled NVME LPORT lpfc0 WWPN x10000090fae0ec9d WWNN x20000090fae0ec9d DID x012000 ONLINE NVME RPORT WWPN x200b00a098c80f09 WWNN x200a00a098c80f09 DID x010601 TARGET DISCSRVC ONLINE NVME Statistics LS: Xmt 0000000000000006 Cmpl 0000000000000006 FCP: Rd 0000000000000071 Wr 0000000000000005 IO 0000000000000031 Cmpl 00000000000000a6 Outstanding 0000000000000001 NVME Initiator Enabled NVME LPORT lpfc1 WWPN x10000090fae0ec9e WWNN x20000090fae0ec9e DID x012400 ONLINE NVME RPORT WWPN x200900a098c80f09 WWNN x200800a098c80f09 DID x010301 TARGET DISCSRVC ONLINE NVME Statistics LS: Xmt 0000000000000006 Cmpl 0000000000000006 FCP: Rd 0000000000000073 Wr 0000000000000005 IO 0000000000000031 Cmpl 00000000000000a8 Outstanding 0000000000000001`</pre> </div> </li> <li>• If the target LIFs don't show up as above in the <code>nvme_info</code> output, check the <code>/var/log/messages</code> and <code>dmesg</code> output for any suspicious NVMe/FC failures, and report or fix accordingly.</li> </ul>

Errors displayed by <code>nvme-cli</code>	Probable cause	Workaround
No discovery log entries to fetch	Generally seen if the <code>/etc/nvme/hostnqn</code> string has not been added to the corresponding subsystem on the NetApp array or an incorrect <code>hostnqn</code> string has been added to the respective subsystem.	Ensure the exact <code>/etc/nvme/hostnqn</code> string is added to the corresponding subsystem on the NetApp array (verify through the <code>vserver nvme subsystem host show</code> command).
Failed to write to <code>/dev/nvme-fabrics:</code> Operation already in progress	Seen if the controller associations or specified operation is already created or in the process of being created. This could happen as part of the auto-connect scripts installed above.	None. For <code>nvme discover</code> , try running this command after some time. For <code>nvme connect</code> and <code>connect-all</code> , run <code>nvme list</code> command to verify that the namespace devices are already created and displayed on the host.

### When to contact technical support

If you are still facing issues, please collect the following files and command outputs and contact technical support for further triage:

```
cat /sys/class/scsi_host/host*/nvme_info
/var/log/messages
dmesg
nvme discover output as in:
nvme discover --transport=fc --traddr=nn-0x200a00a098c80f09:pn
-0x200b00a098c80f09 --host-traddr=nn-0x20000090fae0ec9d:pn
-0x10000090fae0ec9d
nvme list
nvme list-subsys /dev/nvmeXnY
```

## NVMe/FC Host Configuration for RHEL 8.3 with ONTAP

### Supportability

NVMe/FC is supported on ONTAP 9.6 or later for RHEL 8.3. The RHEL 8.3 host runs both NVMe and SCSI traffic through the same fibre channel (FC) initiator adapter ports. See the [Hardware Universe](#) for a list of supported FC adapters and controllers. For the most current list of supported configurations and versions, see the [NetApp Interoperability Matrix](#).



## Known limitations

For RHEL 8.3, in-kernel NVMe multipath remains disabled by default. Therefore, you need to enable it manually. Steps for doing so are provided in the next section, "Enabling NVMe/FC on RHEL 8.3".

## Enable NVMe/FC on RHEL 8.3

1. Install Red Hat Enterprise Linux 8.3 GA on the server.

If you are upgrading from RHEL 8.2 to RHEL 8.3 using `yum update/upgrade`, your `/etc/nvme/host*` files might be lost. To avoid file loss, do the following:

- a. Backup your `/etc/nvme/host*` files.
- b. If you have a manually edited `udev` rule, remove it:

```
/lib/udev/rules.d/71-nvme-iopolicy-netapp-ONTAP.rules
```

- c. Perform the upgrade.
- d. After the upgrade is complete, run the following command:

```
yum remove nvme-cli
```

- e. Restore the host files at `/etc/nvme/`.

```
yum install nvmecli
```

- f. Copy the original `/etc/nvme/host*` contents from the backup to the actual host files at `/etc/nvme/`.

2. After the installation is complete, verify that you're running the specified Red Hat Enterprise Linux kernel.

```
# uname -r
4.18.0-240.el8.x86_64
```

See the [NetApp Interoperability Matrix](#) for the most current list of supported versions.

3. Install the `nvme-cli` package.

```
# rpm -qa|grep nvme-cli
nvme-cli-1.12-2.el8.x86_64
```

4. Enable in-kernel NVMe multipath.

```
# grubby --args=nvme_core.multipath=Y --update-kernel /boot/vmlinuz-4.18.0-240.el8.x86_64
```

5. On the RHEL 8.3 host, check the host NQN string at `/etc/nvme/hostnqn` and verify that it matches the host NQN string for the corresponding subsystem on the ONTAP array.

```
# cat /etc/nvme/hostnqn
nqn.2014-08.org.nvmexpress:uuid:9ed5b327-b9fc-4cf5-97b3-1b5d986345d1

::> vserver nvme subsystem host show -vserver vs_fcnvme_141

::> vserver nvme subsystem host show -vserver vs_fcnvme_141
Vserver          Subsystem          Host          NQN
-----
vs_fcnvme_141    nvme_141_1          nqn.2014-
08.org.nvmexpress:uuid:9ed5b327-b9fc-4cf5-97b3-1b5d986345d1
```



If the host NQN strings do not match, use the `vserver modify` command to update the host NQN string on the corresponding ONTAP array subsystem to match to host NQN string from `/etc/nvme/hostnqn` on the host.

6. Reboot the host.
7. Update the `enable_foreign` setting (*optional*).



If you intend to run both NVMe and SCSI traffic on the same RHEL 8.3 co-existent host, we recommend you use in-kernel NVMe multipath for ONTAP namespaces and `dm-multipath` for ONTAP LUNs, respectively. You should also blacklist the ONTAP namespaces in `dm-multipath` to prevent `dm-multipath` from claiming these namespace devices. You do this by adding the `enable_foreign` setting to the `/etc/multipath.conf`, as shown below.

```
# cat /etc/multipath.conf
defaults {
    enable_foreign NONE
}
```

8. Restart the `multipathd` daemon by running a `systemctl restart multipathd`.

## Validate NVMe/FC

1. Verify the following NVMe/FC settings.

```
# cat /sys/module/nvme_core/parameters/multipath
Y
```

```
# cat /sys/class/nvme-subsystem/nvme-subsys*/model
NetApp ONTAP Controller
NetApp ONTAP Controller
```

```
# cat /sys/class/nvme-subsystem/nvme-subsys*/iopolicy
round-robin
round-robin
```

## 2. Verify that the namespaces are created and properly discovered on the host.

```
/dev/nvme0n1      814vWBNRwf9HAAAAAAAAAB  NetApp ONTAP Controller
1                85.90 GB / 85.90 GB     4 KiB + 0 B   FFFFFFFF
/dev/nvme0n2      814vWBNRwf9HAAAAAAAAAB  NetApp ONTAP Controller
2                85.90 GB / 85.90 GB     4 KiB + 0 B   FFFFFFFF
/dev/nvme0n3      814vWBNRwf9HAAAAAAAAAB  NetApp ONTAP Controller
3                85.90 GB / 85.90 GB     4 KiB + 0 B   FFFFFFFF
```

## 3. Verify the status of the ANA paths.

```
# nvme list-subsys /dev/nvme0n1
nvme-subsys0 - NQN=nqn.1992-
08.com.netapp:sn.5f5f2c4aa73b11e9967e00a098df41bd:subsystem.nvme_141_1
\
+- nvme0 fc traddr=nn-0x203700a098dfdd91:pn-0x203800a098dfdd91
host_traddr=nn-0x200000109b1c1204:pn-0x100000109b1c1204 live
inaccessible
+- nvme1 fc traddr=nn-0x203700a098dfdd91:pn-0x203900a098dfdd91
host_traddr=nn-0x200000109b1c1204:pn-0x100000109b1c1204 live
inaccessible
+- nvme2 fc traddr=nn-0x203700a098dfdd91:pn-0x203a00a098dfdd91
host_traddr=nn-0x200000109b1c1205:pn-0x100000109b1c1205 live optimized
+- nvme3 fc traddr=nn-0x203700a098dfdd91:pn-0x203d00a098dfdd91
host_traddr=nn-0x200000109b1c1205:pn-0x100000109b1c1205 live optimized
```

## 4. Verify the NetApp plug-in for ONTAP devices.

```
# nvme netapp ontapdevices -o column
```

Device	Vserver	Namespace	Path	Size
NSID	UUID			
-----				
-----				
-----				
/dev/nvme0n1	vs_fcnvme_141			
/vol/fcnvme_141_vol_1_1_0/fcnvme_141_ns		1		72b887b1-5fb6-47b8-be0b-33326e2542e2
				85.90GB
/dev/nvme0n2	vs_fcnvme_141			
/vol/fcnvme_141_vol_1_0_0/fcnvme_141_ns		2		04bf9f6e-9031-40ea-99c7-a1a61b2d7d08
				85.90GB
/dev/nvme0n3	vs_fcnvme_141			
/vol/fcnvme_141_vol_1_1_1/fcnvme_141_ns		3		264823b1-8e03-4155-80dd-e904237014a4
				85.90GB

```

# nvme netapp ontapdevices -o json
{
  "ONTAPdevices" : [
    {
      "Device" : "/dev/nvme0n1",
      "Vserver" : "vs_fcnvme_141",
      "Namespace_Path" : "/vol/fcnvme_141_vol_1_1_0/fcnvme_141_ns",
      "NSID" : 1,
      "UUID" : "72b887b1-5fb6-47b8-be0b-33326e2542e2",
      "Size" : "85.90GB",
      "LBA_Data_Size" : 4096,
      "Namespace_Size" : 20971520
    },
    {
      "Device" : "/dev/nvme0n2",
      "Vserver" : "vs_fcnvme_141",
      "Namespace_Path" : "/vol/fcnvme_141_vol_1_0_0/fcnvme_141_ns",
      "NSID" : 2,
      "UUID" : "04bf9f6e-9031-40ea-99c7-a1a61b2d7d08",
      "Size" : "85.90GB",
      "LBA_Data_Size" : 4096,
      "Namespace_Size" : 20971520
    },
    {
      "Device" : "/dev/nvme0n3",
      "Vserver" : "vs_fcnvme_141",
      "Namespace_Path" : "/vol/fcnvme_141_vol_1_1_1/fcnvme_141_ns",
      "NSID" : 3,
      "UUID" : "264823b1-8e03-4155-80dd-e904237014a4",
      "Size" : "85.90GB",
      "LBA_Data_Size" : 4096,
      "Namespace_Size" : 20971520
    }
  ]
}

```

## Configure the Broadcom FC adapter for NVMe/FC

For the most current list of supported adapters see the see the [NetApp Interoperability Matrix](#).

1. Verify that you are using the supported adapter.

```

# cat /sys/class/scsi_host/host*/modelname
LPe32002-M2
LPe32002-M2

```

```
# cat /sys/class/scsi_host/host*/modeldesc
Emulex LightPulse LPe32002-M2 2-Port 32Gb Fibre Channel Adapter
Emulex LightPulse LPe32002-M2 2-Port 32Gb Fibre Channel Adapter
```

2. Verify that `lpfc_enable_fc4_type` is set to "3".

```
# cat /sys/module/lpfc/parameters/lpfc_enable_fc4_type
3
```

3. Verify that the initiator ports are up and running and can see the target LIFs.

```
# cat /sys/class/fc_host/host*/port_name
0x100000109b1c1204
0x100000109b1c1205
```

```
# cat /sys/class/fc_host/host*/port_state
Online
Online
```

```

# cat /sys/class/scsi_host/host*/nvme_info
NVME Initiator Enabled
XRI Dist lpfc0 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc0 WWPN x100000109b1c1204 WWNN x200000109b1c1204 DID
x011d00 ONLINE
NVME RPORT WWPN x203800a098dfdd91 WWNN x203700a098dfdd91 DID x010c07
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203900a098dfdd91 WWNN x203700a098dfdd91 DID x011507
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000f78 Cmpl 0000000f78 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002fe29bba Issue 000000002fe29bc4 OutIO
0000000000000000a
abort 00001bc7 noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001e15 Err 0000d906
NVME Initiator Enabled
XRI Dist lpfc1 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc1 WWPN x100000109b1c1205 WWNN x200000109b1c1205 DID
x011900 ONLINE
NVME RPORT WWPN x203d00a098dfdd91 WWNN x203700a098dfdd91 DID x010007
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203a00a098dfdd91 WWNN x203700a098dfdd91 DID x012a07
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000fa8 Cmpl 0000000fa8 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002e14f170 Issue 000000002e14f17a OutIO
0000000000000000a
abort 000016bb noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001f50 Err 0000d9f8

```

#### 4. Enable 1 MB I/O size (*optional*).

The `lpfc_sg_seg_cnt` parameter needs to be set to 256 for the `lpfc` driver to issue I/O requests up to 1 MB in size.

```

# cat /etc/modprobe.d/lpfc.conf
options lpfc lpfc_sg_seg_cnt=256

```

#### 5. Run a `dracut -f` command and then reboot the host.

#### 6. After the host boots up, verify that `lpfc_sg_seg_cnt` is set to 256.

```
# cat /sys/module/lpfc/parameters/lpfc_sg_seg_cnt
256
```

7. Verify that you are using the recommended Broadcom lpfc firmware as well as the inbox driver.

```
# cat /sys/class/scsi_host/host*/fwrev
12.8.340.8, sli-4:2:c
12.8.340.8, sli-4:2:c
```

```
# cat /sys/module/lpfc/version
0:12.8.0.1
```

8. Verify that `lpfc_enable_fc4_type` is set to "3".

```
# cat /sys/module/lpfc/parameters/lpfc_enable_fc4_type
3
```

9. Verify that the initiator ports are up and running and can see the target LIFs.

```
# cat /sys/class/fc_host/host*/port_name
0x100000109b1c1204
0x100000109b1c1205
```

```
# cat /sys/class/fc_host/host*/port_state
Online
Online
```



```

# cat /sys/class/scsi_host/host*/nvme_info
NVME Initiator Enabled
XRI Dist lpfc0 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc0 WWPN x100000109b1c1204 WWNN x200000109b1c1204 DID
x011d00 ONLINE
NVME RPORT WWPN x203800a098dfdd91 WWNN x203700a098dfdd91 DID x010c07
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203900a098dfdd91 WWNN x203700a098dfdd91 DID x011507
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000f78 Cmpl 0000000f78 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002fe29bba Issue 000000002fe29bc4 OutIO
0000000000000000a
abort 00001bc7 noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001e15 Err 0000d906
NVME Initiator Enabled
XRI Dist lpfc1 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc1 WWPN x100000109b1c1205 WWNN x200000109b1c1205 DID
x011900 ONLINE
NVME RPORT WWPN x203d00a098dfdd91 WWNN x203700a098dfdd91 DID x010007
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203a00a098dfdd91 WWNN x203700a098dfdd91 DID x012a07
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000fa8 Cmpl 0000000fa8 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002e14f170 Issue 000000002e14f17a OutIO
0000000000000000a
abort 000016bb noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001f50 Err 0000d9f8

```

10. Enable 1 MB I/O size (*optional*).

The `lpfc_sg_seg_cnt` parameter needs to be set to 256 for the `lpfc` driver to issue I/O requests up to 1 MB in size.

```

# cat /etc/modprobe.d/lpfc.conf
options lpfc lpfc_sg_seg_cnt=256

```

11. Run a `dracut -f` command and then reboot the host.

12. After the host boots up, verify that `lpfc_sg_seg_cnt` is set to 256.

```
# cat /sys/module/lpfc/parameters/lpfc_sg_seg_cnt
256
```

## LPFC Verbose Logging

1. You can set the `lpfc_log_verbose` driver setting to any of the following values to log NVMe/FC events.

```
#define LOG_NVME 0x00100000 /* NVME general events. */
#define LOG_NVME_DISC 0x00200000 /* NVME Discovery/Connect events. */
#define LOG_NVME_ABTS 0x00400000 /* NVME ABTS events. */
#define LOG_NVME_IOERR 0x00800000 /* NVME IO Error events. */
```

2. After setting any of these values, run `dracut-f` and reboot host.
3. After rebooting, verify the settings.

```
# cat /etc/modprobe.d/lpfc.conf
options lpfc lpfc_log_verbose=0xf00083

# cat /sys/module/lpfc/parameters/lpfc_log_verbose
15728771
```

## NVMe/FC Host Configuration for RHEL 8.2 with ONTAP

### Supportability

NVMe/FC is supported on ONTAP 9.6 or later for RHEL 8.2. The RHEL 8.2 host runs both NVMe and SCSI traffic through the same fibre channel (FC) initiator adapter ports. See the [Hardware Universe](#) for a list of supported FC adapters and controllers. For the most current list of supported configurations and versions, see the [NetApp Interoperability Matrix](#).

### Known limitations

For RHEL 8.2, in-kernel NVMe multipath remains disabled by default. Therefore, you need to enable it manually. Steps for doing so are provided in the next section, "Enabling NVMe/FC on RHEL 8.2".

### Enable NVMe/FC on RHEL 8.2

1. Install Red Hat Enterprise Linux 8.2 GA on the server.

If you are upgrading from RHEL 8.1 to RHEL 8.2 using `yum update/upgrade`, your `/etc/nvme/host*` files might be lost. To avoid file loss, do the following:

- a. Backup your `/etc/nvme/host*` files.

- b. If you have a manually edited `udev` rule, remove it:

```
/lib/udev/rules.d/71-nvme-iopolicy-netapp-ONTAP.rules
```

- c. Perform the upgrade.

- d. After the upgrade is complete, run the following command:

```
yum remove nvme-cli
```

- e. Restore the host files at `/etc/nvme/`.

```
yum install nvmecli
```

- f. Copy the original `/etc/nvme/host*` contents from the backup to the actual host files at `/etc/nvme/`.

2. After the installation is complete, verify that you are running the specified Red Hat Enterprise Linux kernel.

```
# uname -r  
4.18.0-193.el8.x86_64
```

See the [NetApp Interoperability Matrix](#) for the most current list of supported versions.

3. Install the `nvme-cli` package.

```
# rpm -qa|grep nvme-cli  
nvme-cli-1.9.5.el8.x86_64
```

4. Enable in-kernel NVMe multipath.

```
# grubby --args=nvme_core.multipath=Y --update-kernel /boot/vmlinuz-  
4.18.0-193.el8.x86_64
```

5. On the RHEL 8.2 host, check the host NQN string at `/etc/nvme/hostnqn` and verify that it matches the host NQN string for the corresponding subsystem on the ONTAP array.

```
# cat /etc/nvme/hostnqn
nqn.2014-08.org.nvmexpress:uuid:9ed5b327-b9fc-4cf5-97b3-1b5d986345d1

::> vserver nvme subsystem host show -vserver vs_fcnvme_141
Vserver      Subsystem      Host      NQN
-----
vs_fcnvme_141
  nvme_141_1
    nqn.2014-08.org.nvmexpress:uuid:9ed5b327-b9fc-4cf5-97b3-
1b5d986345d1
```

If the host NQN strings do not match, use the `vserver modify` command to update the host NQN string on the corresponding ONTAP array subsystem to match to host NQN string from `/etc/nvme/hostnqn` on the host.

6. Reboot the host.
7. Update the `enable_foreign` setting (*optional*).

If you intend to run both NVMe and SCSI traffic on the same RHEL 8.2 co-existent host, we recommend you use in-kernel NVMe multipath for ONTAP namespaces and `dm-multipath` for ONTAP LUNs, respectively. You should also blacklist the ONTAP namespaces in `dm-multipath` to prevent `dm-multipath` from claiming these namespace devices. You do this by adding the `enable_foreign` setting to the `/etc/multipath.conf`, as shown below.

```
# cat /etc/multipath.conf
defaults {
    enable_foreign NONE
}
```

8. Restart the `multipathd` daemon by running a `systemctl restart multipathd`.

## Configure the Broadcom FC adapter for NVMe/FC

For the most current list of supported adapters see the see the [NetApp Interoperability Matrix](#).

1. Verify that you are using the supported adapter.

```
# cat /sys/class/scsi_host/host*/modelname
LPe32002-M2
LPe32002-M2
```

```
# cat /sys/class/scsi_host/host*/modeldesc
Emulex LightPulse LPe32002-M2 2-Port 32Gb Fibre Channel Adapter
Emulex LightPulse LPe32002-M2 2-Port 32Gb Fibre Channel Adapter
```

2. Verify that `lpfc_enable_fc4_type` is set to "3".

```
# cat /sys/module/lpfc/parameters/lpfc_enable_fc4_type
3
```

3. Verify that the initiator ports are up and running and can see the target LIFs.

```
# cat /sys/class/fc_host/host*/port_name
0x100000109b1c1204
0x100000109b1c1205
```

```
# cat /sys/class/fc_host/host*/port_state
Online
Online
```

```

# cat /sys/class/scsi_host/host*/nvme_info
NVME Initiator Enabled
XRI Dist lpfc0 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc0 WWPN x100000109b1c1204 WWNN x200000109b1c1204 DID
x011d00 ONLINE
NVME RPORT WWPN x203800a098dfdd91 WWNN x203700a098dfdd91 DID x010c07
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203900a098dfdd91 WWNN x203700a098dfdd91 DID x011507
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000f78 Cmpl 0000000f78 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002fe29bba Issue 000000002fe29bc4 OutIO
0000000000000000a
abort 00001bc7 noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001e15 Err 0000d906
NVME Initiator Enabled
XRI Dist lpfc1 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc1 WWPN x100000109b1c1205 WWNN x200000109b1c1205 DID
x011900 ONLINE
NVME RPORT WWPN x203d00a098dfdd91 WWNN x203700a098dfdd91 DID x010007
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203a00a098dfdd91 WWNN x203700a098dfdd91 DID x012a07
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000fa8 Cmpl 0000000fa8 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002e14f170 Issue 000000002e14f17a OutIO
0000000000000000a
abort 000016bb noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001f50 Err 0000d9f8

```

#### 4. Enable 1 MB I/O size (*optional*).

The `lpfc_sg_seg_cnt` parameter needs to be set to 256 for the `lpfc` driver to issue I/O requests up to 1 MB in size.

```

# cat /etc/modprobe.d/lpfc.conf
options lpfc lpfc_sg_seg_cnt=256

```

#### 5. Run a `dracut -f` command and then reboot the host.

#### 6. After the host boots up, verify that `lpfc_sg_seg_cnt` is set to 256.

```
# cat /sys/module/lpfc/parameters/lpfc_sg_seg_cnt
256
```

7. Verify that you are using the recommended Broadcom lpfc firmware as well as the inbox driver.

```
# cat /sys/class/scsi_host/host*/fwrev
12.6.182.8, sli-4:2:c
12.6.182.8, sli-4:2:c
```

```
# cat /sys/module/lpfc/version
0:12.6.0.2
```

8. Verify that `lpfc_enable_fc4_type` is set to "3".

```
# cat /sys/module/lpfc/parameters/lpfc_enable_fc4_type
3
```

9. Verify that the initiator ports are up and running and can see the target LIFs.

```
# cat /sys/class/fc_host/host*/port_name
0x100000109b1c1204
0x100000109b1c1205
```

```
# cat /sys/class/fc_host/host*/port_state
Online
Online
```

```

# cat /sys/class/scsi_host/host*/nvme_info
NVME Initiator Enabled
XRI Dist lpfc0 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc0 WWPN x100000109b1c1204 WWNN x200000109b1c1204 DID
x011d00 ONLINE
NVME RPORT WWPN x203800a098dfdd91 WWNN x203700a098dfdd91 DID x010c07
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203900a098dfdd91 WWNN x203700a098dfdd91 DID x011507
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000f78 Cmpl 0000000f78 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002fe29bba Issue 000000002fe29bc4 OutIO
0000000000000000a
abort 00001bc7 noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001e15 Err 0000d906
NVME Initiator Enabled
XRI Dist lpfc1 Total 6144 IO 5894 ELS 250
NVME LPORT lpfc1 WWPN x100000109b1c1205 WWNN x200000109b1c1205 DID
x011900 ONLINE
NVME RPORT WWPN x203d00a098dfdd91 WWNN x203700a098dfdd91 DID x010007
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203a00a098dfdd91 WWNN x203700a098dfdd91 DID x012a07
TARGET DISCSRVC ONLINE
NVME Statistics
LS: Xmt 0000000fa8 Cmpl 0000000fa8 Abort 00000000
LS XMIT: Err 00000000 CMPL: xb 00000000 Err 00000000
Total FCP Cmpl 000000002e14f170 Issue 000000002e14f17a OutIO
0000000000000000a
abort 000016bb noxri 00000000 nondlp 00000000 qdepth 00000000 wqerr
00000000 err 00000000
FCP CMPL: xb 00001f50 Err 0000d9f8

```

10. Enable 1 MB I/O size (*optional*).

The `lpfc_sg_seg_cnt` parameter needs to be set to 256 for the `lpfc` driver to issue I/O requests up to 1 MB in size.

```

# cat /etc/modprobe.d/lpfc.conf
options lpfc lpfc_sg_seg_cnt=256

```

11. Run a `dracut -f` command and then reboot the host.

12. After the host boots up, verify that `lpfc_sg_seg_cnt` is set to 256.



```
# cat /sys/module/lpfc/parameters/lpfc_sg_seg_cnt
256
```

## Validate NVMe/FC

1. Verify the following NVMe/FC settings.

```
# cat /sys/module/nvme_core/parameters/multipath
Y
```

```
# cat /sys/class/nvme-subsystem/nvme-subsys*/model
NetApp ONTAP Controller
NetApp ONTAP Controller
```

```
# cat /sys/class/nvme-subsystem/nvme-subsys*/iopolicy
round-robin
round-robin
```

2. Verify that the namespaces are created.

```
# nvme list
Node SN Model Namespace Usage Format FW Rev
-----
/dev/nvme0n1 80BADBKnB/JvAAAAAAAC NetApp ONTAP Controller 1 53.69 GB /
53.69 GB 4 KiB + 0 B FFFFFFFF
```

3. Verify the status of the ANA paths.

```
# nvme list-subsys/dev/nvme0n1
Nvme-subsysf0 - NQN=nqn.1992-
08.com.netapp:sn.341541339b9511e8a9b500a098c80f09:subsystem.rhel_141_nvme_ss_10_0
\
+- nvme0 fc traddr=nn-0x202c00a098c80f09:pn-0x202d00a098c80f09
host_traddr=nn-0x20000090fae0ec61:pn-0x10000090fae0ec61 live optimized
+- nvme1 fc traddr=nn-0x207300a098dfdd91:pn-0x207600a098dfdd91
host_traddr=nn-0x200000109b1c1204:pn-0x100000109b1c1204 live
inaccessible
+- nvme2 fc traddr=nn-0x207300a098dfdd91:pn-0x207500a098dfdd91
host_traddr=nn-0x200000109b1c1205:pn-0x100000109b1c1205 live optimized
+- nvme3 fc traddr=nn-0x207300a098dfdd91:pn-0x207700a098dfdd91 host
traddr=nn-0x200000109b1c1205:pn-0x100000109b1c1205 live inaccessible
```

#### 4. Verify the NetApp plug-in for ONTAP devices.

```
# nvme netapp ontapdevices -o column
Device      Vserver      Namespace Path                      NSID      UUID      Size
-----
/dev/nvme0n1 vs_nvme_10    /vol/rhel_141_vol_10_0/rhel_141_ns_10_0
1           55baf453-f629-4a18-9364-b6aee3f50dad  53.69GB

# nvme netapp ontapdevices -o json
{
  "ONTAPdevices" : [
    {
      "Device" : "/dev/nvme0n1",
      "Vserver" : "vs_nvme_10",
      "Namespace_Path" : "/vol/rhel_141_vol_10_0/rhel_141_ns_10_0",
      "NSID" : 1,
      "UUID" : "55baf453-f629-4a18-9364-b6aee3f50dad",
      "Size" : "53.69GB",
      "LBA_Data_Size" : 4096,
      "Namespace_Size" : 13107200
    }
  ]
}
```

## LPFC Verbose Logging

1. You can set the `lpfc_log_verbose` driver setting to any of the following values to log NVMe/FC events.

```
#define LOG_NVME 0x00100000 /* NVME general events. */
#define LOG_NVME_DISC 0x00200000 /* NVME Discovery/Connect events. */
#define LOG_NVME_ABTS 0x00400000 /* NVME ABTS events. */
#define LOG_NVME_IOERR 0x00800000 /* NVME IO Error events. */
```

2. After setting any of these values, run `dracut-f` and reboot host.
3. After rebooting, verify the settings.

```
# cat /etc/modprobe.d/lpfc.conf
options lpfc lpfc_log_verbose=0xf00083

# cat /sys/module/lpfc/parameters/lpfc_log_verbose
15728771
```

## NVMe/FC Host Configuration for RHEL 8.1 with ONTAP

### Supportability

NVMe/FC is supported on ONTAP 9.6 or later for the following versions of RHEL:

- RHEL 8.1

RHEL 8.1 host can run both NVMe & SCSI traffic through the same fibre channel initiator adapter ports. See the [Hardware Universe](#) for a list of supported FC adapters and controllers.

For the most current list of supported configurations see the [NetApp Interoperability Matrix](#).

### Known limitations

- Native NVMe/FC auto-connect scripts are not available in the `nvme-cli` package. You can use the HBA vendor provided external auto-connect script.
- By default, NVMe multipath is disabled. It must be manually enabled. Steps are provided in the section on Enabling NVMe/FC on RHEL 8.1.
- By default, round-robin load balancing is not enabled. You must write a `udev` rule to enable this functionality. Steps are provided in the section on Enabling NVMe/FC on RHEL 8.1.

### Enable NVMe/FC on RHEL 8.1

1. Install Red Hat Enterprise Linux 8.1 on the server.
2. After the installation is complete, verify that you are running the specified Red Hat Enterprise Linux kernel. See the [NetApp Interoperability Matrix](#) for the most current list of supported versions.

```
# uname -r
4.18.0-147.el8.x86_64
```

3. Install the `nvme-cli-1.8.1-3.el8` package.

```
# rpm -qa|grep nvme-cli
nvme-cli-1.8.1-3.el8.x86_64
```

4. Enable in-kernel NVMe multipath.

```
# grubby --args=nvme_core.multipath=Y --update-kernel /boot/vmlinuz-
4.18.0-147.el8.x86_64
```

5. Add the string below as a separate udev rule at `/lib/udev/rules.d/71-nvme-iopolicy-netapp-ONTAP.rules`. This enables round-robin load balancing for NVMe multipath.

```
# Enable round-robin for NetApp ONTAP
ACTION=="add", SUBSYSTEM=="nvme-subsystem", ATTR{model}=="NetApp ONTAP
Controller", ATTR{iopolicy}="round-robin"
```

6. On the RHEL 8.1 host, check the host NQN string at `/etc/nvme/hostnqn` and verify that it matches the host NQN string for the corresponding subsystem on the ONTAP array.

```
# cat /etc/nvme/hostnqn
nqn.2014-08.org.nvmexpress:uuid:75953f3b-77fe-4e03-bf3c-09d5a156fbcd
```

```
*> vserver nvme subsystem host show -vserver vs_nvme_10
Vserver Subsystem Host NQN
-----
rhel_141_nvme_ss_10_0
nqn.2014-08.org.nvmexpress:uuid:75953f3b-77fe-4e03-bf3c-09d5a156fbcd
```



If the host NQN strings do not match, you should use the `vserver modify` command to update the host NQN string on your corresponding ONTAP array subsystem to match to host NQN string from `/etc/nvme/hostnqn` on the host.

7. Reboot the host.

## Configure the Broadcom FC Adapter for NVMe/FC

1. Verify that you are using the supported adapter. For the most current list of supported adapters see the

## NetApp Interoperability Matrix.

```
# cat /sys/class/scsi_host/host*/modelname
LPe32002-M2
LPe32002-M2
```

```
# cat /sys/class/scsi_host/host*/modeldesc
Emulex LightPulse LPe32002-M2 2-Port 32Gb Fibre Channel Adapter
Emulex LightPulse LPe32002-M2 2-Port 32Gb Fibre Channel Adapter
```

### 2. Copy and install the Broadcom lpfc outbox driver and auto-connect scripts.

```
# tar -xvzf elx-lpfc-dd-rhel8-12.4.243.20-ds-1.tar.gz
# cd elx-lpfc-dd-rhel8-12.4.2453.20-ds-1
# ./elx_lpfc_install-sh -i -n
```



The native drivers that come bundled with the OS are called inbox drivers. If you download the outbox drivers (drivers that are not included with the OS release), an auto-connect script is included in the download and should be installed as part of the driver installation process.

### 3. Reboot the host.

### 4. Verify that you are using the recommended Broadcom lpfc firmware, outbox driver & auto-connect package versions.

```
# cat /sys/class/scsi_host/host*/fwrev
12.4.243.20, sil-4.2.c
12.4.243.20, sil-4.2.c
```

```
# cat /sys/module/lpfc/version
0:12.4.243.20
```

```
# rpm -qa | grep nvmeofc
nvmeofc-connect-12.6.61.0-1.noarch
```

### 5. Verify that lpfc\_enable\_fc4\_type is set to 3.

```
# cat /sys/module/lpfc/parameters/lpfc_enable_fc4_type
3
```

6. Verify that the initiator ports are up and running.

```
# cat /sys/class/fc_host/host*/port_name
0x10000090fae0ec61
0x10000090fae0ec62
```

```
# cat /sys/class/fc_host/host*/port_state
Online
Online
```

7. Verify that the NVMe/FC initiator ports are enabled, running and able to see the target LIFs.

```
# cat /sys/class/scsi_host/host*/nvme_info
NVME Initiator Enabled
XRI Dist lpfc0 Total 6144 NVME 2947 SCSI 2977 ELS 250
NVME LPORT lpfc0 WWPN x10000090fae0ec61 WWNN x20000090fae0ec61 DID
x012000 ONLINE
NVME RPORT WWPN x202d00a098c80f09 WWNN x202c00a098c80f09 DID x010201
TARGET DISCSRVC ONLINE
NVME RPORT WWPN x203100a098c80f09 WWNN x202c00a098c80f09 DID x010601
TARGET DISCSRVC ONLINE
NVME Statistics
...
```

## Validate NVMe/FC

1. Verify the following NVMe/FC settings.

```
# cat /sys/module/nvme_core/parameters/multipath
Y
```

```
# cat /sys/class/nvme-subsystem/nvme-subsys*/model
NetApp ONTAP Controller
NetApp ONTAP Controller
```

```
# cat /sys/class/nvme-subsystem/nvme-subsys*/iopolicy
round-robin
round-robin
```

2. Verify that the namespaces are created.

```
# nvme list
Node SN Model Namespace Usage Format FW Rev
-----
/dev/nvme0n1 80BADBKnB/JvAAAAAAAC NetApp ONTAP Controller 1 53.69 GB /
53.69 GB 4 KiB + 0 B FFFFFFFF
```

3. Verify the status of the ANA paths.

```
# nvme list-subsys/dev/nvme0n1
Nvme-subsysf0 - NQN=nqn.1992-
08.com.netapp:sn.341541339b9511e8a9b500a098c80f09:subsystem.rhel_141_nvme_ss_10_0
\
+- nvme0 fc traddr=nn-0x202c00a098c80f09:pn-0x202d00a098c80f09
host_traddr=nn-0x20000090fae0ec61:pn-0x10000090fae0ec61 live optimized
+- nvme1 fc traddr=nn-0x207300a098dfdd91:pn-0x207600a098dfdd91
host_traddr=nn-0x200000109b1c1204:pn-0x100000109b1c1204 live
inaccessible
+- nvme2 fc traddr=nn-0x207300a098dfdd91:pn-0x207500a098dfdd91
host_traddr=nn-0x200000109b1c1205:pn-0x100000109b1c1205 live optimized
+- nvme3 fc traddr=nn-0x207300a098dfdd91:pn-0x207700a098dfdd91 host
traddr=nn-0x200000109b1c1205:pn-0x100000109b1c1205 live inaccessible
```

4. Verify the NetApp plug-in for ONTAP devices.

```

# nvme netapp ontapdevices -o column
Device      Vserver    Namespace Path                               NSID    UUID          Size
-----
/dev/nvme0n1  vs_nvme_10  /vol/rhel_141_vol_10_0/rhel_141_ns_10_0
1           55baf453-f629-4a18-9364-b6aee3f50dad    53.69GB

# nvme netapp ontapdevices -o json
{
  "ONTAPdevices" : [
    {
      "Device" : "/dev/nvme0n1",
      "Vserver" : "vs_nvme_10",
      "Namespace_Path" : "/vol/rhel_141_vol_10_0/rhel_141_ns_10_0",
      "NSID" : 1,
      "UUID" : "55baf453-f629-4a18-9364-b6aee3f50dad",
      "Size" : "53.69GB",
      "LBA_Data_Size" : 4096,
      "Namespace_Size" : 13107200
    }
  ]
}

```

## Enable 1MB I/O Size for Broadcom NVMe/FC

The `lpfc_sg_seg_cnt` parameter must be set to 256 in order for the host to issue 1MB size I/O.

1. Set the `lpfc_sg_seg_cnt` parameter to 256.

```

# cat /etc/modprobe.d/lpfc.conf
options lpfc lpfc_sg_seg_cnt=256

```

2. Run a `dracut -f` command, and reboot the host.
3. Verify that `lpfc_sg_seg_cnt` is 256.

```

# cat /sys/module/lpfc/parameters/lpfc_sg_seg_cnt
256

```

## LPFC Verbose Logging

1. You can set the `lpfc_log_verbose` driver setting to any of the following values to log NVMe/FC events.



```
#define LOG_NVME 0x00100000 /* NVME general events. */  
#define LOG_NVME_DISC 0x00200000 /* NVME Discovery/Connect events. */  
#define LOG_NVME_ABTS 0x00400000 /* NVME ABTS events. */  
#define LOG_NVME_IOERR 0x00800000 /* NVME IO Error events. */
```

2. After setting any of these values, run `dracut-f` and reboot host.
3. After rebooting, verify the settings.

```
# cat /etc/modprobe.d/lpfc.conf  
options lpfc lpfc_log_verbose=0xf00083  
  
# cat /sys/module/lpfc/parameters/lpfc_log_verbose  
15728771
```

## Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.