Python code samples

ONTAP Select

NetApp
November 08, 2026

This PDF was generated from https://docs.netapp.com/us-en/ontap-select-9191/reference_api_script_cc.html on November 08, 2026. Always check docs.netapp.com for the latest.

Table of Contents

Python code samples . . . 1
- Script to create an ONTAP Select cluster . . . 1
- JSON for script to create an ONTAP Select cluster . . . 8
  - Single-node cluster on ESXi . . . 8
  - Single-node cluster on ESXi using vCenter . . . 10
  - Single-node cluster on KVM . . . 11
- Script to add an ONTAP Select node license . . . 13
- Script to delete an ONTAP Select cluster . . . 16
- Common support Python module for ONTAP Select . . . 18
- Script to resize ONTAP Select cluster nodes . . . 22

Python code samples

Script to create an ONTAP Select cluster

You can use the following script to create a cluster based on parameters defined within the script and a JSON input file.

```
#!/usr/bin/env python
##-----------------------------------------------------------------------
#
# File: cluster.py
#
# (C) Copyright 2019 NetApp, Inc.
#
# This sample code is provided AS IS, with no support or warranties of
# any kind, including but not limited for warranties of
merchantability
# or fitness of any kind, expressed or implied. Permission to use,
# reproduce, modify and create derivatives of the sample code is
granted
# solely for the purpose of researching, designing, developing and
# testing a software application product for use with NetApp products,
# provided that the above copyright notice appears in all copies and
# that the software application product is distributed pursuant to
terms
# no less restrictive than those set forth herein.
#
##-----------------------------------------------------------------------

import traceback
import argparse
import json
import logging

from deploy_requests import DeployRequests


def add_vcenter_credentials(deploy, config):
    """ Add credentials for the vcenter if present in the config """
    log_debug_trace()

    vcenter = config.get('vcenter', None)
    if vcenter and not deploy.resource_exists('/security/credentials',
                                              'hostname', vcenter[
'hostname']):
```

```
35          log_info("Registering vcenter {} credentials".format(vcenter[
'hostname']))
36          data = {k: vcenter[k] for k in ['hostname', 'username',
'password']}
37          data['type'] = "vcenter"
38          deploy.post('/security/credentials', data)
39
40
41  def add_standalone_host_credentials(deploy, config):
42      """ Add credentials for standalone hosts if present in the config.
43          Does nothing if the host credential already exists on the
Deploy.
44      """
45      log_debug_trace()
46
47      hosts = config.get('hosts', [])
48      for host in hosts:
49          # The presense of the 'password' will be used only for
standalone hosts.
50          # If this host is managed by a vcenter, it should not have a
host 'password' in the json.
51          if 'password' in host and not deploy.resource_exists(
'/security/credentials',
52                                                               '
hostname', host['name']):
53              log_info("Registering host {} credentials".format(host[
'name']))
54              data = {'hostname': host['name'], 'type': 'host',
55                      'username': host['username'], 'password': host[
'password']}
56              deploy.post('/security/credentials', data)
57
58
59  def register_unkown_hosts(deploy, config):
60      ''' Registers all hosts with the deploy server.
61          The host details are read from the cluster config json file.
62
63          This method will skip any hosts that are already registered.
64          This method will exit the script if no hosts are found in the
config.
65      '''
66      log_debug_trace()
67
68      data = {"hosts": []}
69      if 'hosts' not in config or not config['hosts']:
70          log_and_exit("The cluster config requires at least 1 entry in
```

```
    the 'hosts' list got {}".format(config))
71
72      missing_host_cnt = 0
73      for host in config['hosts']:
74          if not deploy.resource_exists('/hosts', 'name', host['name']):
75              missing_host_cnt += 1
76              host_config = {"name": host['name'], "hypervisor_type":
    host['type']}
77              if 'mgmt_server' in host:
78                  host_config["management_server"] = host['mgmt_server']
79                  log_info(
80                     "Registering from vcenter {mgmt_server}".format(
    **host))
81
82              if 'password' in host and 'user' in host:
83                  host_config['credential'] = {
84                      "password": host['password'], "username": host[
    'user']}
85
86              log_info("Registering {type} host {name}".format(**host))
87              data["hosts"].append(host_config)
88
89      # only post /hosts if some missing hosts were found
90      if missing_host_cnt:
91          deploy.post('/hosts', data, wait_for_job=True)
92
93
94  def add_cluster_attributes(deploy, config):
95      ''' POST a new cluster with all needed attribute values.
96          Returns the cluster_id of the new config
97      '''
98      log_debug_trace()
99
100     cluster_config = config['cluster']
101     cluster_id = deploy.find_resource('/clusters', 'name',
    cluster_config['name'])
102
103     if not cluster_id:
104         log_info("Creating cluster config named {name}".format(
    **cluster_config))
105
106         # Filter to only the valid attributes, ignores anything else
    in the json
107         data = {k: cluster_config[k] for k in [
108             'name', 'ip', 'gateway', 'netmask', 'ontap_image_version',
    'dns_info', 'ntp_servers']}
```

```
109
110         num_nodes = len(config['nodes'])
111
112         log_info("Cluster properties: {}".format(data))
113
114         resp = deploy.post('/v3/clusters?node_count={}'.format
    (num_nodes), data)
115         cluster_id = resp.headers.get('Location').split('/')[-1]
116
117     return cluster_id
118
119
120 def get_node_ids(deploy, cluster_id):
121     ''' Get the the ids of the nodes in a cluster. Returns a list of
    node_ids.'''
122     log_debug_trace()
123
124     response = deploy.get('/clusters/{}/nodes'.format(cluster_id))
125     node_ids = [node['id'] for node in response.json().get('records')]
126     return node_ids
127
128
129 def add_node_attributes(deploy, cluster_id, node_id, node):
130     ''' Set all the needed properties on a node '''
131     log_debug_trace()
132
133     log_info("Adding node '{}' properties".format(node_id))
134
135     data = {k: node[k] for k in ['ip', 'serial_number', '
    instance_type',
136                                  'is_storage_efficiency_enabled'] if k
    in node}
137     # Optional: Set a serial_number
138     if 'license' in node:
139         data['license'] = {'id': node['license']}
140
141     # Assign the host
142     host_id = deploy.find_resource('/hosts', 'name', node['host_name
    '])
143     if not host_id:
144         log_and_exit("Host names must match in the 'hosts' array, and
    the nodes.host_name property")
145
146     data['host'] = {'id': host_id}
147
148     # Set the correct raid_type
```

```
149     is_hw_raid = not node['storage'].get('disks')  # The presence of a
    list of disks indicates sw_raid
150     data['passthrough_disks'] = not is_hw_raid
151
152     # Optionally set a custom node name
153     if 'name' in node:
154         data['name'] = node['name']
155
156     log_info("Node properties: {}".format(data))
157     deploy.patch('/clusters/{}/nodes/{}'.format(cluster_id, node_id),
    data)
158
159
160 def add_node_networks(deploy, cluster_id, node_id, node):
161     ''' Set the network information for a node '''
162     log_debug_trace()
163
164     log_info("Adding node '{}' network properties".format(node_id))
165
166     num_nodes = deploy.get_num_records('/clusters/{}/nodes'.format
    (cluster_id))
167
168     for network in node['networks']:
169
170         # single node clusters do not use the 'internal' network
171         if num_nodes == 1 and network['purpose'] == 'internal':
172             continue
173
174         # Deduce the network id given the purpose for each entry
175         network_id = deploy.find_resource(
    '/clusters/{}/nodes/{}/networks'.format(cluster_id, node_id),
176                                           'purpose', network['purpose
    '])
177         data = {"name": network['name']}
178         if 'vlan' in network and network['vlan']:
179             data['vlan_id'] = network['vlan']
180
181         deploy.patch('/clusters/{}/nodes/{}/networks/{}'.format
    (cluster_id, node_id, network_id), data)
182
183
184 def add_node_storage(deploy, cluster_id, node_id, node):
185     ''' Set all the storage information on a node '''
186     log_debug_trace()
187
188     log_info("Adding node '{}' storage properties".format(node_id))
```

```
189     log_info("Node storage: {}".format(node['storage']['pools']))
190
191     data = {'pool_array': node['storage']['pools']}  # use all the
    json properties
192     deploy.post(
193         '/clusters/{}/nodes/{}/storage/pools'.format(cluster_id,
    node_id), data)
194
195     if 'disks' in node['storage'] and node['storage']['disks']:
196         data = {'disks': node['storage']['disks']}
197         deploy.post(
198             '/clusters/{}/nodes/{}/storage/disks'.format(cluster_id,
    node_id), data)
199
200
201 def create_cluster_config(deploy, config):
202     ''' Construct a cluster config in the deploy server using the
    input json data '''
203     log_debug_trace()
204
205     cluster_id = add_cluster_attributes(deploy, config)
206
207     node_ids = get_node_ids(deploy, cluster_id)
208     node_configs = config['nodes']
209
210     for node_id, node_config in zip(node_ids, node_configs):
211         add_node_attributes(deploy, cluster_id, node_id, node_config)
212         add_node_networks(deploy, cluster_id, node_id, node_config)
213         add_node_storage(deploy, cluster_id, node_id, node_config)
214
215     return cluster_id
216
217
218 def deploy_cluster(deploy, cluster_id, config):
219     ''' Deploy the cluster config to create the ONTAP Select VMs. '''
220     log_debug_trace()
221     log_info("Deploying cluster: {}".format(cluster_id))
222
223     data = {'ontap_credential': {'password': config['cluster'][
    'ontap_admin_password']}}
224     deploy.post('/clusters/{}/deploy?inhibit_rollback=true'.format
    (cluster_id),
225                 data, wait_for_job=True)
226
227
228 def log_debug_trace():
```

```
    stack = traceback.extract_stack()
    parent_function = stack[-2][2]
    logging.getLogger('deploy').debug('Calling %s()' %
parent_function)


def log_info(msg):
    logging.getLogger('deploy').info(msg)


def log_and_exit(msg):
    logging.getLogger('deploy').error(msg)
    exit(1)


def configure_logging(verbose):
    FORMAT = '%(asctime)-15s:%(levelname)s:%(name)s: %(message)s'
    if verbose:
        logging.basicConfig(level=logging.DEBUG, format=FORMAT)
    else:
        logging.basicConfig(level=logging.INFO, format=FORMAT)
        logging.getLogger('requests.packages.urllib3.connectionpool'
).setLevel(
            logging.WARNING)


def main(args):
    configure_logging(args.verbose)
    deploy = DeployRequests(args.deploy, args.password)

    with open(args.config_file) as json_data:
        config = json.load(json_data)

        add_vcenter_credentials(deploy, config)

        add_standalone_host_credentials(deploy, config)

        register_unkown_hosts(deploy, config)

        cluster_id = create_cluster_config(deploy, config)

        deploy_cluster(deploy, cluster_id, config)


def parseArgs():
    parser = argparse.ArgumentParser(description='Uses the ONTAP
```

```
    Select Deploy API to construct and deploy a cluster.')
273     parser.add_argument('-d', '--deploy', help='Hostname or IP address
    of Deploy server')
274     parser.add_argument('-p', '--password', help='Admin password of
    Deploy server')
275     parser.add_argument('-c', '--config_file', help='Filename of the
    cluster config')
276     parser.add_argument('-v', '--verbose', help='Display extra
    debugging messages for seeing exact API calls and responses',
277                         action='store_true', default=False)
278     return parser.parse_args()
279
280 if __name__ == '__main__':
281     args = parseArgs()
282     main(args)
```

JSON for script to create an ONTAP Select cluster

When creating or deleting an ONTAP Select cluster using the Python code samples, you must provide a JSON file as input to the script. You can copy and modify the appropriate JSON sample based on your deployment plans.

Single-node cluster on ESXi

```
1  {
2    "hosts": [
3      {
4        "password": "mypassword1",
5        "name": "host-1234",
6        "type": "ESX",
7        "username": "admin"
8      }
9    ],
10
11   "cluster": {
12     "dns_info": {
13       "domains": ["lab1.company-demo.com", "lab2.company-demo.com",
14         "lab3.company-demo.com", "lab4.company-demo.com"
15         ],
16
17       "dns_ips": ["10.206.80.135", "10.206.80.136"]
18       },
19       "ontap_image_version": "9.7",
20       "gateway": "10.206.80.1",
21       "ip": "10.206.80.115",
```

```
      "name": "mycluster",
      "ntp_servers": ["10.206.80.183", "10.206.80.142"],
      "ontap_admin_password": "mypassword2",
      "netmask": "255.255.254.0"
  },

  "nodes": [
    {
      "serial_number": "3200000nn",
      "ip": "10.206.80.114",
      "name": "node-1",
      "networks": [
        {
          "name": "ontap-external",
          "purpose": "mgmt",
          "vlan": 1234
        },
        {
          "name": "ontap-external",
          "purpose": "data",
          "vlan": null
        },
        {
          "name": "ontap-internal",
          "purpose": "internal",
          "vlan": null
        }
      ],
      "host_name": "host-1234",
      "is_storage_efficiency_enabled": false,
      "instance_type": "small",
      "storage": {
        "disk": [],
        "pools": [
          {
            "name": "storage-pool-1",
            "capacity": 4802666790125
          }
        ]
      }
    }
  ]
}
```

Single-node cluster on ESXi using vCenter

```
{
  "hosts": [
    {
      "name":"host-1234",
      "type":"ESX",
      "mgmt_server":"vcenter-1234"
    }
  ],

  "cluster": {
    "dns_info": {"domains": ["lab1.company-demo.com", "lab2.company-
demo.com",
      "lab3.company-demo.com", "lab4.company-demo.com"
      ],
      "dns_ips": ["10.206.80.135","10.206.80.136"]
  },

  "ontap_image_version":"9.7",
  "gateway":"10.206.80.1",
  "ip":"10.206.80.115",
  "name":"mycluster",
  "ntp_servers": ["10.206.80.183","10.206.80.142"],
  "ontap_admin_password":"mypassword2",
  "netmask":"255.255.254.0"
  },

  "vcenter": {
    "password":"mypassword2",
    "hostname":"vcenter-1234",
    "username":"selectadmin"
  },

  "nodes": [
    {
      "serial_number": "3200000nn",
      "ip":"10.206.80.114",
      "name":"node-1",
      "networks": [
        {
          "name":"ONTAP-Management",
          "purpose":"mgmt",
          "vlan":null
        },
        {
```

```
          "name": "ONTAP-External",
          "purpose":"data",
          "vlan":null
        },
        {
          "name": "ONTAP-Internal",
          "purpose":"internal",
          "vlan":null
        }
      ],

      "host_name": "host-1234",
      "is_storage_efficiency_enabled": false,
      "instance_type": "small",
      "storage": {
        "disk":[],
        "pools": [
          {
            "name": "storage-pool-1",
            "capacity":5685190380748
          }
        ]
      }
    }
  ]
}
```

Single-node cluster on KVM

```
{
  "hosts": [
    {
      "password": "mypassword1",
      "name":"host-1234",
      "type":"KVM",
      "username":"root"
    }
  ],

  "cluster": {
    "dns_info": {
      "domains": ["lab1.company-demo.com", "lab2.company-demo.com",
        "lab3.company-demo.com", "lab4.company-demo.com"
      ],
```

```
      "dns_ips": ["10.206.80.135", "10.206.80.136"]
    },

    "ontap_image_version": "9.7",
    "gateway":"10.206.80.1",
    "ip":"10.206.80.115",
    "name":"CBF4ED97",
    "ntp_servers": ["10.206.80.183", "10.206.80.142"],
    "ontap_admin_password": "mypassword2",
    "netmask":"255.255.254.0"
  },
  "nodes": [
    {
      "serial_number":"3200000nn",
      "ip":"10.206.80.115",
      "name": "node-1",
      "networks": [
        {
          "name": "ontap-external",
          "purpose": "mgmt",
          "vlan":1234
        },
        {
          "name": "ontap-external",
          "purpose": "data",
          "vlan": null
        },
        {
          "name": "ontap-internal",
          "purpose": "internal",
          "vlan": null
        }
      ],

      "host_name": "host-1234",
      "is_storage_efficiency_enabled": false,
      "instance_type": "small",
      "storage": {
        "disk": [],
        "pools": [
          {
            "name": "storage-pool-1",
            "capacity": 4802666790125
          }
        ]
      }
```

```
    }
  ]
}
```

Script to add an ONTAP Select node license

You can use the following script to add a license for an ONTAP Select node.

```
#!/usr/bin/env python
##-----------------------------------------------------------------------
#
# File: add_license.py
#
# (C) Copyright 2019 NetApp, Inc.
#
# This sample code is provided AS IS, with no support or warranties of
# any kind, including but not limited for warranties of
merchantability
# or fitness of any kind, expressed or implied. Permission to use,
# reproduce, modify and create derivatives of the sample code is
granted
# solely for the purpose of researching, designing, developing and
# testing a software application product for use with NetApp products,
# provided that the above copyright notice appears in all copies and
# that the software application product is distributed pursuant to
terms
# no less restrictive than those set forth herein.
#
##-----------------------------------------------------------------------

import argparse
import logging
import json

from deploy_requests import DeployRequests


def post_new_license(deploy, license_filename):
    log_info('Posting a new license: {}'.format(license_filename))

    # Stream the file as multipart/form-data
    deploy.post('/licensing/licenses', data={},
                files={'license_file': open(license_filename, 'rb')})

    # Alternative if the NLF license data is converted to a string.
```

```
35      # with open(license_filename, 'rb') as f:
36      #     nlf_data = f.read()
37      #     r = deploy.post('/licensing/licenses', data={},
38      #                     files={'license_file': (license_filename,
    nlf_data)})
39
40
41  def put_license(deploy, serial_number, data, files):
42      log_info('Adding license for serial number: {}'.format
    (serial_number))
43
44      deploy.put('/licensing/licenses/{}'.format(serial_number), data
    =data, files=files)
45
46
47  def put_used_license(deploy, serial_number, license_filename,
    ontap_username, ontap_password):
48      ''' If the license is used by an 'online' cluster, a
    username/password must be given. '''
49
50      data = {'ontap_username': ontap_username, 'ontap_password':
    ontap_password}
51      files = {'license_file': open(license_filename, 'rb')}
52
53      put_license(deploy, serial_number, data, files)
54
55
56  def put_free_license(deploy, serial_number, license_filename):
57      data = {}
58      files = {'license_file': open(license_filename, 'rb')}
59
60      put_license(deploy, serial_number, data, files)
61
62
63  def get_serial_number_from_license(license_filename):
64      ''' Read the NLF file to extract the serial number '''
65      with open(license_filename) as f:
66          data = json.load(f)
67
68          statusResp = data.get('statusResp', {})
69          serialNumber = statusResp.get('serialNumber')
70          if not serialNumber:
71              log_and_exit("The license file seems to be missing the
    serialNumber")
72
73          return serialNumber
```

```
74
75
76 def log_info(msg):
77     logging.getLogger('deploy').info(msg)
78
79
80 def log_and_exit(msg):
81     logging.getLogger('deploy').error(msg)
82     exit(1)
83
84
85 def configure_logging():
86     FORMAT = '%(asctime)-15s:%(levelname)s:%(name)s: %(message)s'
87     logging.basicConfig(level=logging.INFO, format=FORMAT)
88     logging.getLogger('requests.packages.urllib3.connectionpool'
   ).setLevel(logging.WARNING)
89
90
91 def main(args):
92     configure_logging()
93     serial_number = get_serial_number_from_license(args.license)
94
95     deploy = DeployRequests(args.deploy, args.password)
96
97     # First check if there is already a license resource for this
   serial-number
98     if deploy.find_resource('/licensing/licenses', 'id',
   serial_number):
99
100         # If the license already exists in the Deploy server,
   determine if its used
101         if deploy.find_resource('/clusters', 'nodes.serial_number',
   serial_number):
102
103             # In this case, requires ONTAP creds to push the license
   to the node
104             if args.ontap_username and args.ontap_password:
105                 put_used_license(deploy, serial_number, args.license,
106                                  args.ontap_username, args
   .ontap_password)
107             else:
108                 print("ERROR: The serial number for this license is in
   use. Please provide ONTAP credentials.")
109         else:
110             # License exists, but its not used
111             put_free_license(deploy, serial_number, args.license)
```

```
    else:
        # No license exists, so register a new one as an available license for later use
        post_new_license(deploy, args.license)


def parseArgs():
    parser = argparse.ArgumentParser(description='Uses the ONTAP Select Deploy API to add or update a new or used NLF license file.')
    parser.add_argument('-d', '--deploy', required=True, type=str, help='Hostname or IP address of ONTAP Select Deploy')
    parser.add_argument('-p', '--password', required=True, type=str, help='Admin password of Deploy server')
    parser.add_argument('-l', '--license', required=True, type=str, help='Filename of the NLF license data')
    parser.add_argument('-u', '--ontap_username', type=str,
                        help='ONTAP Select username with privelege to add the license. Only provide if the license is used by a Node.')
    parser.add_argument('-o', '--ontap_password', type=str,
                        help='ONTAP Select password for the ontap_username. Required only if ontap_username is given.')
    return parser.parse_args()

if __name__ == '__main__':
    args = parseArgs()
    main(args)
```

Script to delete an ONTAP Select cluster

You can use the following CLI script to delete an existing cluster.

```
#!/usr/bin/env python
##------------------------------------------------------------------------
#
# File: delete_cluster.py
#
# (C) Copyright 2019 NetApp, Inc.
#
# This sample code is provided AS IS, with no support or warranties of
# any kind, including but not limited for warranties of merchantability
# or fitness of any kind, expressed or implied. Permission to use,
# reproduce, modify and create derivatives of the sample code is granted
# solely for the purpose of researching, designing, developing and
# testing a software application product for use with NetApp products,
```

```
# provided that the above copyright notice appears in all copies and
# that the software application product is distributed pursuant to terms
# no less restrictive than those set forth herein.
#
##----------------------------------------------------------------------

import argparse
import json
import logging

from deploy_requests import DeployRequests

def find_cluster(deploy, cluster_name):
    return deploy.find_resource('/clusters', 'name', cluster_name)


def offline_cluster(deploy, cluster_id):
    # Test that the cluster is online, otherwise do nothing
    response = deploy.get('/clusters/{}?fields=state'.format(cluster_id))
    cluster_data = response.json()['record']
    if cluster_data['state'] == 'powered_on':
        log_info("Found the cluster to be online, modifying it to be powered_off.")
        deploy.patch('/clusters/{}'.format(cluster_id), {'availability': 'powered_off'}, True)


def delete_cluster(deploy, cluster_id):
    log_info("Deleting the cluster({}).".format(cluster_id))
    deploy.delete('/clusters/{}'.format(cluster_id), True)
    pass


def log_info(msg):
    logging.getLogger('deploy').info(msg)


def configure_logging():
    FORMAT = '%(asctime)-15s:%(levelname)s:%(name)s: %(message)s'
    logging.basicConfig(level=logging.INFO, format=FORMAT)
    logging.getLogger('requests.packages.urllib3.connectionpool').setLevel(logging.WARNING)


```

```
def main(args):
    configure_logging()
    deploy = DeployRequests(args.deploy, args.password)

    with open(args.config_file) as json_data:
        config = json.load(json_data)

        cluster_id = find_cluster(deploy, config['cluster']['name'])

        log_info("Found the cluster {} with id: {}.".format(config['cluster']['name'], cluster_id))

        offline_cluster(deploy, cluster_id)

        delete_cluster(deploy, cluster_id)


def parseArgs():
    parser = argparse.ArgumentParser(description='Uses the ONTAP Select Deploy API to delete a cluster')
    parser.add_argument('-d', '--deploy', required=True, type=str, help='Hostname or IP address of Deploy server')
    parser.add_argument('-p', '--password', required=True, type=str, help='Admin password of Deploy server')
    parser.add_argument('-c', '--config_file', required=True, type=str, help='Filename of the cluster json config')
    return parser.parse_args()

if __name__ == '__main__':
    args = parseArgs()
    main(args)
```

Common support Python module for ONTAP Select

All of the Python scripts use a common Python class in a single module.

```
#!/usr/bin/env python
##-----------------------------------------------------------------------
#
# File: deploy_requests.py
#
# (C) Copyright 2019 NetApp, Inc.
#
# This sample code is provided AS IS, with no support or warranties of
# any kind, including but not limited for warranties of merchantability
```

```
# or fitness of any kind, expressed or implied. Permission to use,
# reproduce, modify and create derivatives of the sample code is granted
# solely for the purpose of researching, designing, developing and
# testing a software application product for use with NetApp products,
# provided that the above copyright notice appears in all copies and
# that the software application product is distributed pursuant to terms
# no less restrictive than those set forth herein.
#
##-----------------------------------------------------------------------

import json
import logging
import requests

requests.packages.urllib3.disable_warnings()

class DeployRequests(object):
    '''
    Wrapper class for requests that simplifies the ONTAP Select Deploy
    path creation and header manipulations for simpler code.
    '''

    def __init__(self, ip, admin_password):
        self.base_url = 'https://{}/api'.format(ip)
        self.auth = ('admin', admin_password)
        self.headers = {'Accept': 'application/json'}
        self.logger = logging.getLogger('deploy')

    def post(self, path, data, files=None, wait_for_job=False):
        if files:
            self.logger.debug('POST FILES:')
            response = requests.post(self.base_url + path,
                                     auth=self.auth, verify=False,
                                     files=files)
        else:
            self.logger.debug('POST DATA: %s', data)
            response = requests.post(self.base_url + path,
                                     auth=self.auth, verify=False,
                                     json=data,
                                     headers=self.headers)

        self.logger.debug('HEADERS: %s\nBODY: %s', self.filter_headers
(response), response.text)
        self.exit_on_errors(response)

        if wait_for_job and response.status_code == 202:
```

```
            self.wait_for_job(response.json())
        return response

    def patch(self, path, data, wait_for_job=False):
        self.logger.debug('PATCH DATA: %s', data)
        response = requests.patch(self.base_url + path,
                                  auth=self.auth, verify=False,
                                  json=data,
                                  headers=self.headers)
        self.logger.debug('HEADERS: %s\nBODY: %s', self.filter_headers
(response), response.text)
        self.exit_on_errors(response)

        if wait_for_job and response.status_code == 202:
            self.wait_for_job(response.json())
        return response

    def put(self, path, data, files=None, wait_for_job=False):
        if files:
            print('PUT FILES: {}'.format(data))
            response = requests.put(self.base_url + path,
                                    auth=self.auth, verify=False,
                                    data=data,
                                    files=files)
        else:
            self.logger.debug('PUT DATA:')
            response = requests.put(self.base_url + path,
                                    auth=self.auth, verify=False,
                                    json=data,
                                    headers=self.headers)

        self.logger.debug('HEADERS: %s\nBODY: %s', self.filter_headers
(response), response.text)
        self.exit_on_errors(response)

        if wait_for_job and response.status_code == 202:
            self.wait_for_job(response.json())
        return response

    def get(self, path):
        """ Get a resource object from the specified path """
        response = requests.get(self.base_url + path, auth=self.auth,
verify=False)
        self.logger.debug('HEADERS: %s\nBODY: %s', self.filter_headers
(response), response.text)
        self.exit_on_errors(response)
```

```
        return response

    def delete(self, path, wait_for_job=False):
        """ Delete's a resource from the specified path """
        response = requests.delete(self.base_url + path, auth=self.auth,
verify=False)
        self.logger.debug('HEADERS: %s\nBODY: %s', self.filter_headers
(response), response.text)
        self.exit_on_errors(response)

        if wait_for_job and response.status_code == 202:
            self.wait_for_job(response.json())
        return response

    def find_resource(self, path, name, value):
        ''' Returns the 'id' of the resource if it exists, otherwise None
'''
        resource = None
        response = self.get('{path}?{field}={value}'.format(
                            path=path, field=name, value=value))
        if response.status_code == 200 and response.json().get(
'num_records') >= 1:
            resource = response.json().get('records')[0].get('id')
        return resource

    def get_num_records(self, path, query=None):
        ''' Returns the number of records found in a container, or None on
error '''
        resource = None
        query_opt = '?{}'.format(query) if query else ''
        response = self.get('{path}{query}'.format(path=path, query
=query_opt))
        if response.status_code == 200 :
            return response.json().get('num_records')
        return None

    def resource_exists(self, path, name, value):
        return self.find_resource(path, name, value) is not None

    def wait_for_job(self, response, poll_timeout=120):
        last_modified = response['job']['last_modified']
        job_id = response['job']['id']

        self.logger.info('Event: ' + response['job']['message'])

        while True:
```

```
            response = self.get('/jobs/{}?fields=state,message&'
                                'poll_timeout={}&last_modified=>={}'
.format(
                                    job_id, poll_timeout, last_modified))

            job_body = response.json().get('record', {})

            # Show interesting message updates
            message = job_body.get('message', '')
            self.logger.info('Event: ' + message)

            # Refresh the last modified time for the poll loop
            last_modified = job_body.get('last_modified')

            # Look for the final states
            state = job_body.get('state', 'unknown')
            if state in ['success', 'failure']:
                if state == 'failure':
                    self.logger.error('FAILED background job.\nJOB: %s',
job_body)
                    exit(1)    # End the script if a failure occurs
                break

    def exit_on_errors(self, response):
        if response.status_code >= 400:
            self.logger.error('FAILED request to URL: %s\nHEADERS: %s
\nRESPONSE BODY: %s',
                              response.request.url,
                              self.filter_headers(response),
                              response.text)
        response.raise_for_status()    # Displays the response error, and
exits the script

    @staticmethod
    def filter_headers(response):
        ''' Returns a filtered set of the response headers '''
        return {key: response.headers[key] for key in ['Location',
'request-id'] if key in response.headers}
```

Script to resize ONTAP Select cluster nodes

You can use the following script to resize the nodes in an ONTAP Select cluster.

```
1 #!/usr/bin/env python
2 ##-----------------------------------------------------------------------
```

```
#
# File: resize_nodes.py
#
# (C) Copyright 2019 NetApp, Inc.
#
# This sample code is provided AS IS, with no support or warranties of
# any kind, including but not limited for warranties of
merchantability
# or fitness of any kind, expressed or implied. Permission to use,
# reproduce, modify and create derivatives of the sample code is
granted
# solely for the purpose of researching, designing, developing and
# testing a software application product for use with NetApp products,
# provided that the above copyright notice appears in all copies and
# that the software application product is distributed pursuant to
terms
# no less restrictive than those set forth herein.
#
##----------------------------------------------------------------------

import argparse
import logging
import sys

from deploy_requests import DeployRequests


def _parse_args():
    """ Parses the arguments provided on the command line when
executing this
        script and returns the resulting namespace. If all required
arguments
        are not provided, an error message indicating the mismatch is
printed and
        the script will exit.
    """

    parser = argparse.ArgumentParser(description=(
        'Uses the ONTAP Select Deploy API to resize the nodes in the
cluster.'
        ' For example, you might have a small (4 CPU, 16GB RAM per
node) 2 node'
        ' cluster and wish to resize the cluster to medium (8 CPU,
64GB RAM per'
        ' node). This script will take in the cluster details and then
perform'
```

```
        ' the operation and wait for it to complete.'
    ))
    parser.add_argument('--deploy', required=True, help=(
        'Hostname or IP of the ONTAP Select Deploy VM.'
    ))
    parser.add_argument('--deploy-password', required=True, help=(
        'The password for the ONTAP Select Deploy admin user.'
    ))
    parser.add_argument('--cluster', required=True, help=(
        'Hostname or IP of the cluster management interface.'
    ))
    parser.add_argument('--instance-type', required=True, help=(
        'The desired instance size of the nodes after the operation is
complete.'
    ))
    parser.add_argument('--ontap-password', required=True, help=(
        'The password for the ONTAP administrative user account.'
    ))
    parser.add_argument('--ontap-username', default='admin', help=(
        'The username for the ONTAP administrative user account.
Default: admin.'
    ))
    parser.add_argument('--nodes', nargs='+', metavar='NODE_NAME',
help=(
        'A space separated list of node names for which the resize
operation'
        ' should be performed. The default is to apply the resize to
all nodes in'
        ' the cluster. If a list of nodes is provided, it must be
provided in HA'
        ' pairs. That is, in a 4 node cluster, nodes 1 and 2
(partners) must be'
        ' resized in the same operation.'
    ))
    return parser.parse_args()


def _get_cluster(deploy, parsed_args):
    """ Locate the cluster using the arguments provided """

    cluster_id = deploy.find_resource('/clusters', 'ip', parsed_args
.cluster)
    if not cluster_id:
        return None
    return deploy.get('/clusters/%s?fields=nodes' % cluster_id).
json()['record']
```

```
76
77
78 def _get_request_body(parsed_args, cluster):
79     """ Build the request body """
80
81     changes = {'admin_password': parsed_args.ontap_password}
82
83     # if provided, use the list of nodes given, else use all the nodes
   in the cluster
84     nodes = [node for node in cluster['nodes']]
85     if parsed_args.nodes:
86         nodes = [node for node in nodes if node['name'] in
   parsed_args.nodes]
87
88     changes['nodes'] = [
89         {'instance_type': parsed_args.instance_type, 'id': node['id']}
   for node in nodes]
90
91     return changes
92
93
94 def main():
95     """ Set up the resize operation by gathering the necessary data
   and then send
96         the request to the ONTAP Select Deploy server.
97     """
98
99     logging.basicConfig(
100         format='[%(asctime)s] [%(levelname)5s] %(message)s', level
   =logging.INFO,)
101
102     logging.getLogger('requests.packages.urllib3').setLevel(logging
   .WARNING)
103
104     parsed_args = _parse_args()
105     deploy = DeployRequests(parsed_args.deploy, parsed_args
   .deploy_password)
106
107     cluster = _get_cluster(deploy, parsed_args)
108     if not cluster:
109         deploy.logger.error(
110             'Unable to find a cluster with a management IP of %s' %
   parsed_args.cluster)
111         return 1
112
113     changes = _get_request_body(parsed_args, cluster)
```

```
114     deploy.patch('/clusters/%s' % cluster['id'], changes,
    wait_for_job=True)
115
116 if __name__ == '__main__':
117     sys.exit(main())
```

Copyright information

Copyright © 2026 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.