



# **Deploy ONTAP tools for VMware vSphere**

## ONTAP tools for VMware vSphere 10

NetApp  
November 12, 2025

# Table of Contents

Deploy ONTAP tools for VMware vSphere . . . . .	1
Quick start for ONTAP tools for VMware vSphere . . . . .	1
High availability (HA) deployment workflow . . . . .	2
ONTAP tools for VMware vSphere requirements and configuration limits . . . . .	3
System requirements . . . . .	3
Minimum storage and application requirements . . . . .	4
Port requirements . . . . .	4
Configuration limits to deploy ONTAP tools for VMware vSphere . . . . .	6
ONTAP tools for VMware vSphere - Storage Replication Adapter (SRA) . . . . .	6
Before you get started... . . . . .	7
Deployment worksheet . . . . .	8
Network firewall configuration . . . . .	9
ONTAP storage settings . . . . .	9
Deploy ONTAP tools for VMware vSphere . . . . .	9
Deployment error codes . . . . .	14

# Deploy ONTAP tools for VMware vSphere

## Quick start for ONTAP tools for VMware vSphere

Set up ONTAP tools for VMware vSphere with this quick start section.

Initially, you'll deploy ONTAP tools for VMware vSphere as a small-sized single node configuration that provides core services to support NFS and VMFS datastores. If you need to expand your configuration to use vVols datastores and high availability (HA), you'll do so after you finish this workflow. For more information, refer to the [HA deployment workflow](#).

1

### Plan your deployment

Verify that your vSphere, ONTAP, and ESXi host versions are compatible with the ONTAP tools version. Allocate sufficient CPU, memory, and disk space. Based on your security rules, you might need to set up firewalls or other security tools to allow network traffic.

Ensure the vCenter Server is installed and accessible.

- [Interoperability Matrix Tool](#)
- [ONTAP tools for VMware vSphere requirements and configuration limits](#)
- [Before you get started](#)

2

### Deploy ONTAP tools for VMware vSphere

Initially, you'll deploy ONTAP tools for VMware vSphere as a small-sized single node configuration that provides core services to support NFS and VMFS datastores. If you plan to expand your configuration to use vVols datastores and high availability (HA), you'll do so after you finish this workflow. To expand to an HA setup, make sure CPU hot-add and memory hot-plug are enabled.

- [Deploy ONTAP tools for VMware vSphere](#)

3

### Add vCenter Server instances

Add vCenter Server instances to ONTAP tools for VMware vSphere to configure, manage, and protect virtual datastores in the vCenter Server environment.

- [Add vCenter Server instances](#)

4

### Configure ONTAP user roles and privileges

Configure new user roles and privileges for managing storage backends using the JSON file provided with ONTAP tools for VMware vSphere.

- [Configure ONTAP user roles and privileges](#)

5

### Configure the storage backends

Add a storage backend to an ONTAP cluster. For multitenancy setups where vCenter acts as the tenant with an associated SVM, use ONTAP tools Manager to add the cluster. Associate the storage backend with the vCenter Server to map it globally to the onboarded vCenter Server instance.

Add the local storage backends with cluster or SVM credentials using the ONTAP tools user interface. These storage backends are limited to a single vCenter. When using cluster credentials locally, the associated SVMs automatically map to the vCenter to manage vVols or VMFS. For VMFS management, including SRA, ONTAP tools supports SVM credentials without needing a global cluster.

- [Add a storage backend](#)
- [Associate the storage backend with a vCenter Server instance](#)

**6**

### **Upgrade the certificates if you're working with multiple vCenter Server instances**

When working with multiple vCenter Server instances, upgrade the self-signed certificate to a certificate authority (CA) signed certificate.

- [Manage certificates](#)

**7**

### **(Optional) Configure SRA protection**

Enable the SRA capability to configure disaster recovery and protect NFS or VMFS datastores.

- [Enable ONTAP tools for VMware vSphere services](#)
- [Configure SRA on the VMware Live Site Recovery appliance](#)

**8**

### **(Optional) Enable SnapMirror active sync protection**

Configure ONTAP tools for VMware vSphere to manage host cluster protection for SnapMirror active sync. Perform the ONTAP cluster and SVM peering in ONTAP systems to use SnapMirror active sync. This applies only to VMFS datastores.

- [Protect using host cluster protection](#)

**9**

### **Set up backup and recovery for your ONTAP tools for VMware vSphere deployment**

Schedule backups of your ONTAP tools for VMware vSphere setup that you can use to recover the setup in case of a failure.

- [Create backup and recover the ONTAP tools setup](#)

## **High availability (HA) deployment workflow**

If you are using vVols datastores, you need to expand the initial deployment of ONTAP tools to a high-availability (HA) configuration and enable the VASA Provider services.

**1**

### **Scale up the deployment**

You can scale up the ONTAP tools for VMware vSphere configuration to increase the number of nodes in the deployment and change the configuration to an HA setup.

- [Change ONTAP tools for VMware vSphere configuration](#)

2

## Enable services

To configure the vVols datastores you must enable the VASA Provider service. Register the VASA provider with vCenter and ensure your storage policies meet the HA requirements, including proper network and storage configurations.

Enable the SRA services to use ONTAP tools Storage Replication Adapter (SRA) for VMware Site Recovery Manager (SRM) or VMware Live Site Recovery (VLSR).

- [Enable VASA Provider and SRA services](#)

3

## Upgrade the certificates

If you're using vVol datastores with multiple vCenter Server instances, upgrade the self-signed certificate to a certificate authority (CA) signed certificate.

- [Manage certificates](#)

# ONTAP tools for VMware vSphere requirements and configuration limits

Before deploying the ONTAP tools for VMware vSphere, you should be familiar with the space requirements for the deployment package and some basic host system requirements.

You can use ONTAP tools for VMware vSphere with VMware vCenter Server Virtual Appliance (vCSA). You should deploy ONTAP tools for VMware vSphere on a supported vSphere client that includes ESXi system.

## System requirements

- **Installation package space requirements per node**
  - 15 GB for thin provisioned installations
  - 348 GB for thick provisioned installations
- **Host system sizing requirements** Recommended memory as per the size of deployment is as shown in the table below. To deploy high availability (HA), you will require three times the appliance size specified in the table.

Type of deployment	CPUs per node	Memory (GB) per node	Disk space (GB) thick provisioned per node
Small	9	18	350
Medium	13	26	350

Large	17	34	350
NOTE: The large deployment is only for HA configuration.			



When backup is enabled, each ONTAP tools cluster needs another 50 GB of space on the datastore where VMs are deployed. Therefore, non-HA requires 400 GB, and HA requires 1100 GB of space in total.

## Minimum storage and application requirements

Storage, host, and applications	Version requirements
ONTAP	9.14.1, 9.15.1, 9.16.0, 9.16.1, and 9.16.1P3  FAS, ASA A-Series, ASA C-Series, AFF A-Series, AFF C-Series, and ASA r2.
ONTAP tools supported ESXi hosts	7.0.3 onwards
ONTAP tools supported vCenter Server	7.0U3 onwards
VASA Provider	3.0
OVA Application	10.4
ESXi host to deploy ONTAP tools virtual machine	7.0U3 and 8.0U3
vCenter Server to deploy ONTAP tools virtual machine	7.0 and 8.0



Beginning with ONTAP tools for VMware vSphere 10.4, the virtual machine hardware is changed from version 10 to 17.

The Interoperability Matrix Tool (IMT) contains the latest information about the supported versions of ONTAP, vCenter Server, ESXi hosts, and plug-in applications.

## Interoperability Matrix Tool

## Port requirements

The following table outlines the network ports that NetApp uses and their purposes. There are three different types of ports:

- External ports: These ports are accessible from outside the Kubernetes cluster or node. They allow services to communicate with external networks or users, enabling integration with systems outside the cluster environment.
- Inter-node ports: These ports enable communication between nodes within the Kubernetes cluster. They are needed for cluster tasks like sharing data and working together. For single-node deployments, inter-node ports are used only within the node and do not need external access. Inter-node ports can accept traffic from outside the cluster. Block inter-node ports from internet access with firewall rules.
- Internal ports: These ports communicate within the Kubernetes cluster using ClusterIP addresses. They are not exposed externally and do not need to be added to firewall rules.



Ensure that all ONTAP tools nodes reside on the same subnet to maintain uninterrupted communication with each other.

<details>  
<summary>Click to expand port requirements table</summary>

Service/Component name	Port	Protocol	Port Type	Description
ntv-gateway-svc (LB)	443, 8443	TCP	External	Pass through port for incoming communication for the VASA Provider service. VASA Provider self-signed certificate and custom CA certificate are hosted on this port.
SSH	22	TCP	External	Secure Shell for remote server login and command execution.
rke2 server	9345	TCP	Inter-node	RKE2 supervisor API (Restrict to trusted networks).
kube-apiserver	6443	TCP	Inter-node	Kubernetes API server port (Restrict to trusted networks).
rpcbind/portmapper	111	TCP/UDP	Inter-node	Used for RPC communication between services.
coredns (DNS)	53	TCP/UDP	Inter-node	Domain Name System (DNS) service for name resolution within the cluster.
NTP	123	UDP	Inter-node	Network Time Protocol (NTP) for time synchronization.
etcd	2379, 2380, 2381	TCP	Inter-node	Key-value store for cluster data.
kube-vip	2112	TCP	Inter-node	Kubernetes API server port.

Service/Component name	Port	Protocol	Port Type	Description
kubelet	10248, 10250	TCP	Inter-node	Kubernetes component
kube-controller	10257	TCP	Inter-node	Kubernetes component
cloud-controller	10258	TCP	Inter-node	Kubernetes component
kube-scheduler	10259	TCP	Inter-node	Kubernetes component
kube-proxy	10249, 10256	TCP	Inter-node	Kubernetes component
calico-node	9091, 9099	TCP	Inter-node	Calico networking component.
containerd	10010	TCP	Inter-node	Container daemon service.
VXLAN (Flannel)	8472	UDP	Inter-node	Overlay network for pod communication.



For HA deployments, ensure UDP port 8472 is open between all nodes. This port enables pod-to-pod communication across nodes; blocking it will interrupt inter-node networking.

## Configuration limits to deploy ONTAP tools for VMware vSphere

You can use the following table as a guide to configure ONTAP tools for VMware vSphere.

Deployment	Type	Number of vVols	Number of hosts
Non-HA	Small (S)	~12K	32
Non-HA	Medium (M)	~24K	64
High-Availability	Small (S)	~24K	64
High-Availability	Medium (M)	~50k	128
High-Availability	Large (L)	~100k	256 [NOTE] The number of hosts in the table shows the total number of host from multiple vCenters.

## ONTAP tools for VMware vSphere - Storage Replication Adapter (SRA)

The following table shows the numbers supported per VMware Live Site Recovery instance using ONTAP tools for VMware vSphere.

vCenter Deployment size	Small	Medium
Total number of virtual machines configured for protection using array-based replication	2000	5000
Total number of array-based replication protection groups	250	250
Total number of protection groups per recovery plan	50	50
Number of replicated datastores	255	255
Number of VMs	4000	7000

The following table shows the number of VMware Live Site Recovery and the corresponding ONTAP tools for VMware vSphere deployment size.

Number of VMware Live Site Recovery instances	ONTAP tools deployment Size
Upto 4	Small
4 to 8	Medium
More than 8	Large

For more information, refer to [Operational Limits of VMware Live Site Recovery](#).

## Before you get started...

Ensure the following requirements are met before you proceed with the deployment:

Requirements	Your status
vSphere version, ONTAP version, and ESXi host version are compatible with the ONTP tools version.	<input type="checkbox"/> Yes <input type="checkbox"/> No
vCenter Server environment is set up and configured	<input type="checkbox"/> Yes <input type="checkbox"/> No
Browser cache is deleted	<input type="checkbox"/> Yes <input type="checkbox"/> No
You have the parent vCenter Server credentials	<input type="checkbox"/> Yes <input type="checkbox"/> No
You have the login credentials for the vCenter Server instance, to which the ONTAP tools for VMware vSphere will connect post-deployment for registration	<input type="checkbox"/> Yes <input type="checkbox"/> No
The domain name on which the certificate is issued is mapped to the virtual IP address in a multi-vCenter deployment where custom CA certificates are mandatory.	<input type="checkbox"/> Yes <input type="checkbox"/> No
You have run the nslookup check on the domain name to check if the domain is getting resolved to the intended IP address.	<input type="checkbox"/> Yes <input type="checkbox"/> No
The certificate is created with the domain name and the ONTAP tools IP address.	<input type="checkbox"/> Yes <input type="checkbox"/> No

Requirements	Your status
ONTAP tools application and internal services are reachable from the vCenter Server.	<input type="checkbox"/> Yes <input type="checkbox"/> No
When using multi-tenant SVMs, you have an SVM management LIF on each SVM.	<input type="checkbox"/> Yes <input type="checkbox"/> No

## Deployment worksheet

### For single node deployment

Use the following worksheet to gather the required information for ONTAP tools for VMware vSphere initial deployment:

Requirement	Your value
IP address for the ONTAP tools application. This is the IP address for accessing the ONTAP tools web interface (load balancer)	
ONTAP tools virtual IP address for internal communication. This IP address is used for internal communication in a setup with multiple ONTAP tools instances. This IP address should not be same as the IP address for the ONTAP tools application.(The Kubernetes Control Plane)	
DNS hostname for the ONTAP tools management node	
Primary DNS server	
Secondary DNS server	
DNS search domain	
IPv4 address for the ONTAP tools management node. It is a unique IPv4 address for the node management interface on the management network.	
Subnet mask for the IPv4 address	
Default gateway for the IPv4 address	
IPv6 address (optional)	
IPv6 prefix length (optional)	
Gateway for the IPv6 address (optional)	



Create DNS records for all the above IP addresses. Before assigning hostnames, map them to the free IP addresses on the DNS. All IP addresses should be on the same VLAN selected for deployment.

### For High availability (HA) deployment

In addition to the single node deployment requirements, you'll need the following information for HA

deployment:

Requirement	Your value
Primary DNS server	
Secondary DNS server	
DNS search domain	
DNS hostname for the second node	
IP address for the second node	
DNS hostname for the third node	
IP address for the third node	

## Network firewall configuration

Open the required ports for the IP addresses in your network firewall. ONTAP tools must be able to reach this LIF through port 443. Refer to [Port requirements](#) for latest updates.

## ONTAP storage settings

To ensure seamless integration of ONTAP storage with ONTAP tools for VMware vSphere, consider the following settings:

- If you are using the Fibre Channel (FC) for storage connectivity, configure the zoning on your FC switches to connect the ESXi hosts with the SVM's FC LIFs. [Learn about FC and FCoE zoning with ONTAP systems](#)
- To use ONTAP tools-managed SnapMirror replication, the ONTAP storage administrator should create [ONTAP cluster peer relationships](#) and [ONTAP intercluster SVM peer relationships](#) in ONTAP before using SnapMirror.

## Deploy ONTAP tools for VMware vSphere

The ONTAP tools for VMware vSphere appliance is deployed as small-sized single node with core services to support NFS and VMFS datastores. The ONTAP tools deployment process might take up to 45 minutes.

### Before you begin

A content library in VMware is a container object which stores VM templates, vApp templates, and other types of files. Deployment with content library provides you with a seamless experience because it is not dependent on the network connectivity.



You should store the content library on a shared datastore so that all hosts within a cluster can access it. Create a content library to store the OVA before configuring the appliance to HA configuration. Do not delete the content library template after deployment.



To enable HA deployment later, do not deploy the virtual machine hosting the ONTAP tools directly on an ESXi host. Deploy it on a cluster or resource pool instead.

If you don't have a content library, follow these steps to create one:

**Create content library** If you plan to use only a small single node deployment, creating a content library is not necessary.

1. Download the file that contains the binaries (.ova) and signed certificates for ONTAP tools for VMware vSphere from the [NetApp Support Site](#).
2. Log in to the vSphere client
3. Select the vSphere client menu and select **Content libraries**.
4. Select **Create** on the right of the page.
5. Provide a name for the library and create the content library.
6. Navigate to the content library you created.
7. Select **Actions** in the right of the page and select **Import item** and import the OVA file.



For more information, refer to [Creating and Using Content Library](#) blog.



Before proceeding with the deployment, set the cluster's Distributed Resource Scheduler (DRS) on the inventory to 'Conservative'. This ensures that VMs are not migrated during the installation.

The ONTAP tools for VMware vSphere is initially deployed as a non-HA setup. To scale to HA deployment, you will need to enable the CPU hot plug and memory hot plugin. You can perform this step as part of the deployment process or edit the VM settings after deployment.

## Steps

1. Download the file that contains the binaries (.ova) and signed certificates for the ONTAP tools for VMware vSphere from the [NetApp Support Site](#). If you have imported the OVA into the content library, you can skip this step and proceed with the next step.
2. Log in to the vSphere server.
3. Navigate to the resource pool, cluster, or host where you intend to deploy the OVA.



Never store ONTAP tools for VMware vSphere virtual machine on vVols datastores that it manages.

4. You can deploy the OVA from the content library or from the local system.

From the local system	From the content library
<ol style="list-style-type: none"><li>a. Right-click and select <b>Deploy OVF template....</b></li><li>b. Choose the OVA file from the URL or browse to its location, then select <b>Next</b>.</li></ol>	<ol style="list-style-type: none"><li>a. Go to your content library and select the library item that you want to deploy.</li><li>b. Select <b>Actions &gt; New VM from this template</b></li></ol>

5. In the **Select a name and folder** field, enter the virtual machine name and choose its location.
  - If you're using the vCenter Server 8.0.3 version, Select the option **Customize this virtual machine's hardware**, which will activate an additional step called **Customize hardware** before proceeding to the **Ready to complete** window.
  - If you're using the vCenter Server 7.0.3 version, follow the steps in the **what's next?** section at the end of deployment.

netapp-ontap-tools-for-vmware-vsphere-10.4-1740090540 - New Virtual Machine from Content Library

1 Select a creation type

2 Select a template

**3 Select a name and folder**

4 Select a compute resource

5 Review details

6 Select storage

7 Ready to complete

Select a name and folder

Specify a unique name and target location

Virtual machine name:

demootv

Select a location for the virtual machine.

vcf-vc01.ontappmtme.openenglab.netapp.com  
Raleigh

Customize the operating system  
 Customize this virtual machine's hardware

CANCEL

BACK

**NEXT**

6. Select a computer resource and select **Next**. Optionally, check the box to **Automatically power on deployed VM**.
7. Review the details of the template and select **Next**.
8. Read and accept the license agreement and select **Next**.
9. Select the storage for the configuration and the disk format and select **Next**.
10. Select the destination network for each source network and select **Next**.
11. In the **Customize template** window, fill in the required fields and select **Next**.

Customize template

NTP Servers  
A comma-separated list of hostnames or IP addresses of NTP servers.  
If left blank, VMware tools based time synchronization will be used

**Deployment Configuration** 2 settings

ONTAP tools IP address\* This will be the primary interface for communication with ONTAP tools

ONTAP tools virtual IP address\* ONTAP tools uses this IP address for internal communication

**Node Configuration** 10 settings

HostName\* \_\_\_\_\_

Primary DNS\* \_\_\_\_\_

Secondary DNS\* \_\_\_\_\_

Search domains\* Specify the search domain name to use when resolving the hostname \_\_\_\_\_

IPv4 address\* \_\_\_\_\_

IPv4 subnet mask\* \_\_\_\_\_

CANCEL BACK NEXT

- The information is validated during installation. If there is a discrepancy, an error message appears on the web console, and you are prompted to correct it.
- Host names must include letters (A-Z, a-z), digits (0-9), and hyphens (-). To configure dual stack, specify the host name mapped to the IPv6 address.




Pure IPv6 is not supported. Mixed mode is supported with VLAN containing both IPv6 and IPv4 addresses.

- ONTAP tools IP address is the primary interface for communicating with ONTAP tools.
- IPv4 is the IP address component of the node configuration, which can be utilized to enable diagnostic shell and SSH access on the node for the purposes of debugging and maintenance.

12. When using the vCenter Server 8.0.3 version, in the **Customize hardware** window, enable the **CPU hot add** and **Memory hot plug** options to allow HA functionality.

## netapp-ontap-tools-for-vmware-vsphere-10.4-1740090540 - New Virtual Machine from Content Library

- 1 Select a creation type
- 2 Select a template
- 3 Select a name and folder
- 4 Select a compute resource
- 5 Review details
- 6 License agreements
- 7 Select storage
- 8 Select networks
- 9 Customize template
- 10 Customize hardware**
- 11 Ready to complete



### 13. Review the details in the **Ready to complete** window, select **Finish**.

As the deployment task gets created, the progress is shown in the vSphere task bar.

### 14. Power on the VM after completing the task if the option to automatically power on the VM was not selected.

You can track the progress of the installation within the VM's web console.

If there are discrepancies in the OVF form, a dialog box will prompt corrective action. Use the tab button to navigate, make the necessary changes, and select **OK**. You have three attempts to resolve any issues. If problems continue after three attempts, the installation process will stop, and it is advised to retry the installation on a new virtual machine.

#### What's next?

If you have deployment ONTAP tools for VMware vSphere with vCenter Server 7.0.3, then follow these steps after the deployment.

1. Log in to the vCenter client
2. Power down the ONTAP tools node.
3. Navigate to the ONTAP tools for VMware vSphere virtual machine under **Inventories** and select the **Edit settings** option.

4. Under the **CPU** options, check the **Enable CPU hot add** checkbox
5. Under the **Memory** options, check the **Enable** checkbox against **Memory hot plug**.

## Deployment error codes

You might encounter error codes during ONTAP tools for VMware vSphere deployment, reboot, and recovery operations. The error codes are five digits long, where the first two digits represent the script that encountered the issue, and the last three digits represent the specific workflow within that script.

All error logs are recorded in the `ansible-perl-errors.log` file to facilitate easy tracking and resolution of issues. This log file contains the error code and the failed Ansible task.



The error codes provided on this page are for reference only. Contact the support team if error persists or if there's no resolution mentioned.

The following table lists the error codes and the corresponding file names.

Error code	Script name
00	firstboot-network-config.pl, mode deploy
01	firstboot-network-config.pl, mode upgrade
02	firstboot-inputs-validation.pl
03	firstboot-deploy-otv-ng.pl, deploy, HA
04	firstboot-deploy-otv-ng.pl, deploy, non-HA
05	firstboot-deploy-otv-ng.pl, reboot
06	firstboot-deploy-otv-ng.pl, upgrade, HA
07	firstboot-deploy-otv-ng.pl, upgrade, non-HA
08	firstboot-otv-recovery.pl
09	post-deploy-upgrade.pl

The last three digits of the error code indicate the specific workflow error within the script:

Deployment error code	Workflow	Resolution
049	For network and validation perl script will assign them as well shortly	-
050	Ssh Key generation failed	Restart the primary virtual machine (VM).
053	Failed installing RKE2	Either run the following and restart the primary VM or redeploy: <code>sudo rke2-killall.sh</code> (all VMs) <code>sudo rke2-uninstall.sh</code> (all VMs).
054	Failed setting kubeconfig	Redeploy

055	Failed deploying registry	If the registry pod is present, wait for the pod to be ready then restart the primary VM or else redeploy.
059	KubeVip deployment has failed	Ensure virtual IP address for Kubernetes control plane and ONTAP tools IP address provided during deployment belong to same VLAN and are free IP addresses. Restart if all the previous points are correct. Else, redeploy.
060	Operator deployment has failed	Restart
061	Services deployment has failed	Perform basic Kubernetes debugging like get pods, get rs, get svc, and so on in ntv-system namespace for more details and error logs at /var/log/ansible-perl-errors.log and /var/log/ansible-run.log and redeploy.
062	ONTAP tools Services deployment has failed	Refer to the error logs at /var/log/ansible-perl-errors.log for more details and redeploy.
065	Swagger page URL is not reachable	Redeploy
066	Post deployment steps for gateway certificate has failed	Do the following to recover/complete the upgrade: * Enable diagnostic shell. * Run 'sudo perl /home/maint/scripts/post-deploy-upgrade.pl --postDeploy' command. * Check the logs at /var/log/post-deploy-upgrade.log.
088	Configuring log rotate for journald has failed	Check the VM network settings that is compatible with the host on which the VM is hosted. You can try to migrate to another host and restart the VM.
089	Changing ownership of summary log rotate config file has failed	Restart the primary VM.
096	Install dynamic storage provisioner	-
108	Seeding script failed	-

Reboot error code	Workflow	Resolution
067	Waiting for rke2-server timed out.	-
101	Failed to Reset Maint/Console user password.	-

102	Failed to Delete password file during reset Maint/Console user password.	-
103	Failed to Update New Maint/Console user password in vault.	-
088	Configuring log rotate for journald has failed.	Check the VM network settings that is compatible with the host on which the VM is hosted. You can try to migrate to another host and restart the VM.
089	Changing ownership of summary log rotate config file has failed.	Restart the VM.

## Copyright information

Copyright © 2025 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—with prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

**LIMITED RIGHTS LEGEND:** Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.