



## **Deploy ONTAP tools**

### **ONTAP tools for VMware vSphere 9.12**

NetApp  
June 11, 2024

This PDF was generated from [https://docs.netapp.com/us-en/ontap-tools-vmware-vsphere-912/deploy/concept\\_how\\_to\\_download\\_ontap\\_tools.html](https://docs.netapp.com/us-en/ontap-tools-vmware-vsphere-912/deploy/concept_how_to_download_ontap_tools.html) on June 11, 2024. Always check docs.netapp.com for the latest.

# Table of Contents

- Deploy ONTAP tools . . . . . 1
  - How to download ONTAP tools . . . . . 1
  - How to deploy ONTAP tools . . . . . 1
  - Enable VASA Provider for configuring virtual datastores . . . . . 3
  - Install the NFS VAAI plug-in . . . . . 3
  - Clear the vSphere cached downloaded plug-in packages . . . . . 4

# Deploy ONTAP tools

## How to download ONTAP tools

You can download the `.zip` file that contains binaries (`.ova`) and signed certificates for the ONTAP tools for VMware vSphere from the [NetApp Support Site](#).

The `.ova` file includes the ONTAP tools. When the deployment is complete, VSC, VASA, and SRA products are installed in your environment. By default, VSC starts working as soon as you decide on the subsequent deployment model and choose whether to enable VASA Provider and SRA based on your requirements.

If you want to enable SRA in your deployment of ONTAP tools, then you must have installed the SRA plug-in on the Site Recovery Manager (SRM) server. You can download the installation file for the SRA plug-in from the **Storage Replication Adapter for ONTAP** menu in the Software Downloads section.

## How to deploy ONTAP tools

You should deploy ONTAP tools in your environment, and specify the required parameters, to be able to use the appliance.

### What you will need

- You must be running a supported release of vCenter Server.



ONTAP tools can be registered either with a Windows deployment of vCenter Server or a VMware vCenter Server Virtual Appliance (vCSA) deployment.

### [Interoperability Matrix Tool](#)

- You must have configured and set up your vCenter Server environment.
- You must have set up an ESXi host for your virtual machine.
- You must have downloaded the `.ova` file.
- You must have the administrator login credentials for your vCenter Server instance.
- You should have logged out of and closed all of the browser sessions of vSphere Client, and deleted the browser cache to avoid any browser cache issue during the deployment of ONTAP tools.
- You must have enabled Internet Control Message Protocol (ICMP).

If ICMP is disabled, then the initial configuration of ONTAP tools fails, and VSC cannot start the VSC and VASA Provider services after deployment. You must manually enable the VSC and VASA Provider services after deployment.

### About this task

If you are deploying a fresh installation of ONTAP tools, then VASA Provider is enabled by default. But in case of an upgrade from an earlier release of the ONTAP tools, the state of VASA Provider is retained and you might need to enable VASA Provider manually.

[Enable VASA Provider for configuring virtual datastores](#)

## Steps

1. Log in to the vSphere Client.
2. Select **Home > Host and Clusters**.
3. Right-click the required datacenter, and then click **Deploy OVF template....**
4. Select the applicable method to provide the deployment file for ONTAP tools, and then click **Next**.

Location	Action
URL	Provide the URL for the .ova file for ONTAP tools.
Folder	Extract the .zip file, which contains the .ova file onto your local system. On the Select an OVF template page, specify the location of the .ova file inside the extracted folder.

5. Enter the details to customize the deployment wizard.

(Optional) In the Configure vCenter or Enable VCF section, select the **Enable VMware Cloud Foundation (VCF)** checkbox and provide a password for ONTAP tools credentials. You do not need to provide IP address but providing a password is mandatory. See the following for complete details.

- [Deployment customization considerations](#)
- [VMware Cloud Foundation mode of deployment for ONTAP tools](#)

6. Review the configuration data, and then click **Next** to finish deployment.

As you wait for deployment to finish, you can view the progress of the deployment from the Tasks tab.

7. Power on the ONTAP tools virtual machine, and then open a console of the virtual machine running the ONTAP tools.
8. Verify that ONTAP tools is running after the deployment is completed.
9. If ONTAP tools is not registered with any vCenter Server, use `https://appliance_ip:8143/Register.html` to register the VSC instance. The Register.html redirects you to the swagger page. From ONTAP tools 9.12 onwards the registration of ONTAP tools with vCenter happens from the swagger page.

Use the POST API to register ONTAP tools with vCenter from 9.12 onwards.

```
/2.0/plugin/vcenter
```

10. Log out and re-log in to the vSphere Client to view the deployed ONTAP tools.

It might take a few minutes for the plug-in to be updated in the vSphere Client.

**Troubleshooting:** If you cannot view the plug-in even after logging in, you must clean the vSphere Client cache.

[Clear the vSphere cached downloaded plug-in packages](#)

## Related information

[Error during fresh deployment of virtual appliance for VSC, VASA Provider, and SRA](#)

# Enable VASA Provider for configuring virtual datastores

The ONTAP tools for VMware vSphere has the VASA Provider capability enabled by default. You can configure VMware Virtual Volumes (vVols) datastores with required storage capability profiles for each vVols datastore.

## What you will need

- You must have set up your vCenter Server instance and configured ESXi.
- You must have deployed ONTAP tools .

## About this task

If the VASA Provider capability is disabled before upgrading to the 9.7.1 release of ONTAP tools , the VASA Provider capability remains disabled after the upgrade. This release allows you to enable vVols replication feature for vVols datastores.

## Steps

1. Log in to the web user interface of VMware vSphere.
2. From the vSphere Client, select **Menu > NetApp ONTAP tools**.
3. Click **Settings**.
4. Click **Manage Capabilities** in the Administrative Settings tab.
5. In the Manage Capabilities dialog box, select the VASA Provider extension to enable.
6. If you want to use replication capability for vVols datastores, then use the **Enable vVols replication** toggle button.
7. Enter the IP address of ONTAP tools and the administrator password, and then click **Apply**.



If VASA Provider status displays as “Offline” even after enabling the VASA Provider extension, then check the ``/var/log/vmware/vmware-sps/sps.log` file for any connection errors with VASA Provider or restart the “vmware-sps” service.

## Related information

[NetApp Support](#)

# Install the NFS VAAI plug-in

You can install the NetApp NFS Plug-in for VMware vStorage APIs for Array Integration (VAAI) using the GUI of ONTAP tools for VMware vSphere.

## What you will need

- You should have downloaded the installation package for the NFS Plug-in for VAAI (`.vib`) from the NetApp Support Site. [NetApp Support](#)
- You should have installed ESXi host 6.5 or later and ONTAP 9.1 or later.
- You should have powered on the ESXi host and mounted an NFS datastore.
- You should have set the values of the `DataMover.HardwareAcceleratedMove`, `DataMover.HardwareAcceleratedInit`, and `VMFS3.HardwareAcceleratedLocking` host settings to “1”.

These values are set automatically on the ESXi host when the Recommended Settings dialog box is updated.

- You should have enabled the `vstorage` option on the storage virtual machine (SVM) by using the `vserver nfs modify -vserver vserver_name -vstorage enabled` command.
- You should have ESXi 7.0 update1 or later if you are using NetApp NFS VAAI plug-in 2.0.
- You should have the vSphere 7.x releases as vSphere 6.5 has been deprecated and vSphere 8.x is not supported.

## Steps

1. Rename the `.vib` file that you downloaded from the NetApp Support Site to `NetAppNasPlugin.vib` to match the predefined name that VSC uses.
2. Click **Settings** in the ONTAP tools home page.
3. Click **NFS VAAI Tools** tab.
4. Click **Change** in the **Existing version** section.
5. Browse and select the renamed `.vib` file, and then click **Upload** to upload the file to ONTAP tools.
6. In the Install on ESXi Hosts section, select the ESXi host on which you want to install the NFS VAAI plug-in, and then click **Install**.

You should follow the on-screen instructions to complete the installation. You can monitor the installation progress in the Tasks section of vSphere Web Client.

7. Reboot the ESXi host after the installation finishes.

When you reboot the ESXi host, VSC automatically detects the NFS VAAI plug-in. You do not have to perform additional steps to enable the plug-in.

## Clear the vSphere cached downloaded plug-in packages

If plug-ins are not updated automatically after deploying or upgrading ONTAP tools, you should clean up the cached download plug-in packages on the browser and on the vCenter Server to resolve vCenter Server plug-in issues.

### Steps

1. Logout from your existing vSphere web client or vSphere-UI.
2. Remove the browser cache.
3. Remove the vSphere Client cached plug-in packages. For VCSA, Perform the following:

- a. SSH into the VCSA appliance.
- b. Stop the VMware vSphere Client service: `service-control --stop vsphere-ui`
- c. Change directories to the vCenter client UI extensions directory: `cd /etc/vmware/vsphere-ui/vc-packages/vsphere-client-serenity`
- d. Remove the cached plug-in packages specific to NetApp using the `rm -rf` commands:  
  
`rm -rf com.netapp.nvpf.webclient-*`  
  
`rm -rf com.netapp.vasa.vvol.webclient-*`  
  
`rm -rf com.netapp.vsch5-*`
- e. Start the VMware vSphere Client service: `service-control --start vsphere-ui`

## Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.