



Configure on-demand scanning

ONTAP 9

NetApp
November 24, 2021

Table of Contents

- Configure on-demand scanning 1
 - Configure on-demand scanning overview 1
 - Create an on-demand task 1
 - Schedule an on-demand task 3
 - Run an on-demand task immediately 4
 - Commands for managing on-demand tasks 5

Configure on-demand scanning

Configure on-demand scanning overview

You can use on-demand scanning to check files for viruses immediately or on a schedule. You might want to run scans only in off-peak hours, for example, or you might want to scan very large files that were excluded from an on-access scan.

You can use a cron schedule to specify when the task runs:

- You can assign a schedule when you create a task.
- You can create a task without assigning a schedule, and use the `vserver vscan on-demand-task schedule` command to assign a schedule.
- You can use the `vserver vscan on-demand-task run` command to run a task immediately, whether or not you have assigned a schedule.

Only one task can be scheduled at a time on an SVM.



On-demand scanning does not support scanning of symbolic links or stream files.

Create an on-demand task

An on-demand task defines the scope of an on-demand scan. You can specify the maximum size of the files to be scanned, the extensions and paths of the files to be included in the scan, and the extensions and paths of the files to be excluded from the scan. Files in subdirectories are scanned by default.

Steps

1. Create an on-demand task:

```
vserver vscan on-demand-task create -vserver data_SVM -task-name task_name
-scan-paths paths_of_files_to_scan -report-directory report_directory_path
-report-expiry-time expiration_time_for_report -schedule cron_schedule -max
-file-size max_size_of_files_to_scan -paths-to-exclude
paths_of_files_to_exclude -file-ext-to-exclude extensions_of_files_to_exclude
-file-ext-to-include extensions_of_files_to_include -scan-files-with-no-ext
true|false -directory-recursion true|false
```

- The `-file-ext-to-exclude` setting overrides the `-file-ext-to-include` setting.
- Set `-scan-files-with-no-ext` to `true` to scan files without extensions. For a complete list of options, see the man page for the command.

The following command creates an on-access task named `Task1` on the `vs1SVM`:

```
cluster1::> vserver vscan on-demand-task create -vserver vs1 -task-name
Task1 -scan-paths "/vol1/", "/vol2/cifs/" -report-directory "/report"
-schedule daily -max-file-size 5GB -paths-to-exclude "/vol1/cold-files/"
-file-ext-to-include "vmdk?", "mp*" -file-ext-to-exclude "mp3", "mp4"
-scan-files-with-no-ext false
[Job 126]: Vscan On-Demand job is queued. Use the "job show -id 126"
command to view the status.
```



You can use the `job show` command to view the status of the job. You can use the `job pause` and `job resume` commands to pause and restart the job, or the `job stop` command to end the job.

2. Verify that the on-demand task has been created: `vserver vscan on-demand-task show -instance data_SVM -task-name task_name`

For a complete list of options, see the man page for the command.

The following command displays the details for the `Task1` task:

```
cluster1::> vserver vscan on-demand-task show -instance vs1 -task-name
Task1

                Vserver: vs1
                Task Name: Task1
                List of Scan Paths: /vol1/, /vol2/cifs/
                Report Directory Path: /report
                Job Schedule: daily
Max File Size Allowed for Scanning: 5GB
                File Paths Not to Scan: /vol1/cold-files/
                File Extensions Not to Scan: mp3, mp4
                File Extensions to Scan: vmdk?, mp*
Scan Files with No Extension: false
                Request Service Timeout: 5m
                Cross Junction: true
                Directory Recursion: true
                Scan Priority: low
                Report Log Level: info
                Expiration Time for Report: -
```

After you finish

You must enable scanning on the SVM before the task is scheduled to run.

Schedule an on-demand task

If you have created an on-demand task without assigning a schedule, or if you want to assign a different schedule to a task, you can use the `vserver vscan on-demand-task schedule` command to assign a schedule to the task.

About this task

The schedule assigned with the `vserver vscan on-demand-task schedule` command overrides a schedule already assigned with the `vserver vscan on-demand-task create` command.

Steps

1. Schedule an on-demand task:

```
vserver vscan on-demand-task schedule -vserver data_SVM -task-name task_name  
-schedule cron_schedule
```

The following command schedules an on-access task named `Task2` on the `vs2SVM`:

```
cluster1::> vserver vscan on-demand-task schedule -vserver vs2 -task  
-name Task2 -schedule daily  
[Job 142]: Vscan On-Demand job is queued. Use the "job show -id 142"  
command to view the status.
```



You can use the `job show` command to view the status of the job. You can use the `job pause` and `job resume` commands to pause and restart the job, or the `job stop` command to end the job.

2. Verify that the on-demand task has been scheduled: `vserver vscan on-demand-task show -instance data_SVM -task-name task_name`

For a complete list of options, see the man page for the command.

The following command displays the details for the `Task 2` task:

```
cluster1::> vserver vscan on-demand-task show -instance vs2 -task-name
Task2

                Vserver: vs2
                Task Name: Task2
                List of Scan Paths: /vol1/, /vol2/cifs/
                Report Directory Path: /report
                Job Schedule: daily
Max File Size Allowed for Scanning: 5GB
                File Paths Not to Scan: /vol1/cold-files/
                File Extensions Not to Scan: mp3, mp4
                File Extensions to Scan: vmdk, mp*
Scan Files with No Extension: false
                Request Service Timeout: 5m
                Cross Junction: true
                Directory Recursion: true
                Scan Priority: low
                Report Log Level: info
```

After you finish

You must enable scanning on the SVM before the task is scheduled to run.

Run an on-demand task immediately

You can run an on-demand task immediately, whether or not you have assigned a schedule.

What you'll need

You must have enabled scanning on the SVM.

Step

1. Run an on-demand task immediately:

```
vserver vscan on-demand-task run -vserver data_SVM -task-name task_name
```

The following command runs an on-access task named `Task1` on the `vs1SVM`:

```
cluster1::> vserver vscan on-demand-task run -vserver vs1 -task-name
Task1
[Job 161]: Vscan On-Demand job is queued. Use the "job show -id 161"
command to view the status.
```



You can use the `job show` command to view the status of the job. You can use the `job pause` and `job resume` commands to pause and restart the job, or the `job stop` command to end the job.

Commands for managing on-demand tasks

You can modify, delete, or unschedule an on-demand task. You can view a summary and details for the task, and manage reports for the task.

| If you want to... | Enter the following command... |
|--|---|
| Modify an on-demand task | <code>vserver vscan on-demand-task modify</code> |
| Delete an on-demand task | <code>vserver vscan on-demand-task delete</code> |
| Unschedule an on-demand task | <code>vserver vscan on-demand-task unschedule</code> |
| View summary and details for an on-demand task | <code>vserver vscan on-demand-task show</code> |
| View on-demand reports | <code>vserver vscan on-demand-task report show</code> |
| Delete on-demand reports | <code>vserver vscan on-demand-task report delete</code> |

For more information about these commands, see the man pages.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.