



Disaster recovery for FlexGroup volumes

ONTAP 9

NetApp
December 07, 2022


Table of Contents

- Disaster recovery for FlexGroup volumes 1
 - Disaster recovery workflow for FlexGroup volumes 1
 - Activate the destination FlexGroup volume 2
 - Reactivate the original source FlexGroup volume after disaster 4
 - Reverse a SnapMirror relationship between FlexGroup volumes during disaster recovery 5

Disaster recovery for FlexGroup volumes

Disaster recovery workflow for FlexGroup volumes

When a disaster strikes on the source FlexGroup volume, you should activate the destination FlexGroup volume and redirect client access. Depending on whether the source FlexGroup volume can be recovered, you should either reactivate the source FlexGroup volume or reverse the SnapMirror relationship.



About this task

Client access to the destination FlexGroup volume is blocked for a brief period when some SnapMirror

operations, such as SnapMirror break and resynchronization, are running. If the SnapMirror operation fails, it is possible that some of the constituents remain in this state and access to the FlexGroup volume is denied. In such cases, you must retry the SnapMirror operation.

Activate the destination FlexGroup volume

When the source FlexGroup volume is unable to serve data due to events such as data corruption, accidental deletion or an offline state, you must activate the destination FlexGroup volume to provide data access until you recover the data on the source FlexGroup volume. Activation involves stopping future SnapMirror data transfers and breaking the SnapMirror relationship.

About this task

You must perform this task from the destination cluster.

Steps

1. Disable future transfers for the FlexGroup volume SnapMirror relationship: `snapmirror quiesce dest_svm:dest_flexgroup`

```
cluster2::> snapmirror quiesce -destination-path vsd:dst
```

2. Break the FlexGroup volume SnapMirror relationship: `snapmirror break dest_svm:dest_flexgroup`

```
cluster2::> snapmirror break -destination-path vsd:dst
```

3. View the status of the SnapMirror relationship: `snapmirror show -expand`

```
cluster2::> snapmirror show -expand
```

```
Progress
Source          Destination Mirror Relationship Total
Last
Path            Type Path          State Status          Progress Healthy
Updated
-----
-----
vss:s           XDP vsd:dst          Broken-off
                  Idle          -              true -
vss:s__0001    XDP vsd:dst__0001    Broken-off
                  Idle          -              true -
vss:s__0002    XDP vsd:dst__0002    Broken-off
                  Idle          -              true -
vss:s__0003    XDP vsd:dst__0003    Broken-off
                  Idle          -              true -
vss:s__0004    XDP vsd:dst__0004    Broken-off
                  Idle          -              true -
vss:s__0005    XDP vsd:dst__0005    Broken-off
                  Idle          -              true -
vss:s__0006    XDP vsd:dst__0006    Broken-off
                  Idle          -              true -
vss:s__0007    XDP vsd:dst__0007    Broken-off
                  Idle          -              true -
vss:s__0008    XDP vsd:dst__0008    Broken-off
                  Idle          -              true -
...

```

The SnapMirror relationship status of each constituent is Broken-off.

4. Verify that the destination FlexGroup volume is read/write: `volume show -vserver svm_name`

```

cluster2::> volume show -vserver vsd
Vserver   Volume      Aggregate   State    Type      Size
Available Used%
-----
vsd       dst         -          online  **RW**    2GB
1.54GB   22%
vsd       d2         -          online  DP         2GB
1.55GB   22%
vsd       root_vs0   aggr1     online  RW         100MB
94.02MB  5%
3 entries were displayed.

```

5. Redirect clients to the destination FlexGroup volume.

Reactivate the original source FlexGroup volume after disaster

When the source FlexGroup volume becomes available, you can resynchronize the original source and original destination FlexGroup volumes. Any new data on the destination FlexGroup volume is lost.

About this task

Any active quota rules on the destination volume are deactivated and the quota rules are deleted before resynchronization is performed.

You can use the `volume quota policy rule create` and `volume quota modify` commands to create and reactivate quota rules after the resynchronization operation is complete.

Steps

1. From the destination cluster, resynchronize the FlexGroup volume SnapMirror relationship: `snapmirror resync -destination-path dst_svm:dest_flexgroup`
2. View the status of the SnapMirror relationship: `snapmirror show -expand`

```
cluster2::> snapmirror show -expand
```

```
Progress
Source          Destination Mirror Relationship Total
Last
Path           Type Path           State Status           Progress Healthy
Updated
-----
-----
vss:s           XDP vsd:dst           Snapmirrored
                Idle              -                true -
vss:s__0001    XDP vsd:dst__0001    Snapmirrored
                Idle              -                true -
vss:s__0002    XDP vsd:dst__0002    Snapmirrored
                Idle              -                true -
vss:s__0003    XDP vsd:dst__0003    Snapmirrored
                Idle              -                true -
vss:s__0004    XDP vsd:dst__0004    Snapmirrored
                Idle              -                true -
vss:s__0005    XDP vsd:dst__0005    Snapmirrored
                Idle              -                true -
vss:s__0006    XDP vsd:dst__0006    Snapmirrored
                Idle              -                true -
vss:s__0007    XDP vsd:dst__0007    Snapmirrored
                Idle              -                true -
vss:s__0008    XDP vsd:dst__0008    Snapmirrored
                Idle              -                true -
...

```

The SnapMirror relationship status of each constituent is Snapmirrored.

Reverse a SnapMirror relationship between FlexGroup volumes during disaster recovery

When a disaster disables the source FlexGroup volume of a SnapMirror relationship, you can use the destination FlexGroup volume to serve data while you repair or replace the source FlexGroup volume. After the source FlexGroup volume is online, you can make the original source FlexGroup volume a read-only destination and reverse the SnapMirror relationship.

About this task

Any active quota rules on the destination volume are deactivated and the quota rules are deleted before resynchronization is performed.

You can use the `volume quota policy rule create` and `volume quota modify` commands to create and reactivate quota rules after the resynchronization operation is complete.

Steps

1. On the original destination FlexGroup volume, remove the data protection mirror relationship between the source FlexGroup volume and the destination FlexGroup volume: `snapmirror delete -destination -path svm_name:volume_name`

```
cluster2::> snapmirror delete -destination-path vsd:dst
```

2. On the original source FlexGroup volume, remove the relationship information from the source FlexGroup volume: `snapmirror release -destination-path svm_name:volume_name -relationship -info-only`

After deleting a SnapMirror relationship, you must remove the relationship information from the source FlexGroup volume before attempting a resynchronization operation.

```
cluster1::> snapmirror release -destination-path vsd:dst -relationship -info-only true
```

3. On the new destination FlexGroup volume, create the mirror relationship: `snapmirror create -source-path src_svm_name:volume_name -destination-path dst_svm_name:volume_name -type XDP -policy MirrorAllSnapshots`

```
cluster1::> snapmirror create -source-path vsd:dst -destination-path vss:src -type XDP -policy MirrorAllSnapshots
```

4. On the new destination FlexGroup volume, resynchronize the source FlexGroup: `snapmirror resync -source-path svm_name:volume_name`

```
cluster1::> snapmirror resync -source-path vsd:dst
```

5. Monitor the SnapMirror transfers: `snapmirror show -expand`


```
cluster2::> snapmirror show -expand
```

Progress

Source		Destination	Mirror	Relationship	Total		
Last							
Path	Type	Path	State	Status	Progress	Healthy	
Updated							
-----	----	-----	-----	-----	-----	-----	-----
vsd:dst	XDP	vss:src	Snapmirrored	Idle	-	true	-
vss:dst__0001	XDP	vss:src__0001	Snapmirrored	Idle	-	true	-
vsd:dst__0002	XDP	vss:src__0002	Snapmirrored	Idle	-	true	-
vsd:dst__0003	XDP	vss:src__0003	Snapmirrored	Idle	-	true	-
vsd:dst__0004	XDP	vss:src__0004	Snapmirrored	Idle	-	true	-
vsd:dst__0005	XDP	vss:src__0005	Snapmirrored	Idle	-	true	-
vsd:dst__0006	XDP	vss:src__0006	Snapmirrored	Idle	-	true	-
vsd:dst__0007	XDP	vss:src__0007	Snapmirrored	Idle	-	true	-
vsd:dst__0008	XDP	vss:src__0008	Snapmirrored	Idle	-	true	-
...							

The SnapMirror relationship status of each constituent shows as Snapmirrored that indicates that the resynchronization was successful.

Copyright information

Copyright © 2022 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.