



SnapCenter 6.1 cmdlets

SnapCenter cmdlets

NetApp
September 29, 2025

Table of Contents

SnapCenter 6.1 cmdlets	1
Implement automatic import module using PowerShell	2
Import the modules using UI	2
Script to update the script to include the Import-Module command	2
Script to update the Windows task scheduler command	2
Script to update the PowerShell profile file	2
SnapCenter Windows disk management cmdlets	4
Add-SdIgroupInitiator	4
Syntax	4
Detailed Description	4
Parameters	4
Examples	5
Add-SdLunMap	5
Syntax	5
Detailed Description	5
Parameters	5
Examples	6
Add-SdPortSetPort	6
Syntax	6
Detailed Description	6
Parameters	6
Examples	7
Connect-SdIscsiTarget	7
Syntax	7
Detailed Description	7
Parameters	7
Examples	8
Connect-SdStorage	8
Syntax	8
Detailed Description	9
Parameters	9
Examples	10
Debug-SdHost	11
Syntax	11
Detailed Description	11
Parameters	11
Examples	11
Delete-SdLUNS	13
Syntax	13
Detailed Description	13
Parameters	13
Examples	13
Disconnect-SdIscsiTarget	13

Syntax	13
Detailed Description	13
Parameters	13
Examples	14
Disconnect-SdStorage	14
Syntax	14
Detailed Description	14
Parameters	14
Examples	15
Dismount-SdClone	15
Syntax	15
Detailed Description	15
Parameters	16
Examples	16
Dismount-SdSnapshot	18
Syntax	18
Detailed Description	18
Parameters	18
Examples	19
Get-SdAluaPaths	20
Syntax	20
Detailed Description	20
Parameters	20
Examples	20
Get-SdDataStores	20
Syntax	20
Detailed Description	20
Parameters	21
Examples	21
Get-SdFCPInitiator	21
Syntax	21
Detailed Description	21
Parameters	21
Examples	21
Get-Sdlgroup	22
Syntax	22
Detailed Description	22
Parameters	22
Examples	22
Get-SdlgroupWithUuid	23
Syntax	23
Detailed Description	23
Parameters	23
Examples	23
Get-SdlInfo	23

Syntax	23
Detailed Description	24
Parameters	24
Examples	24
Get-SdIscsiInitiator	25
Syntax	26
Detailed Description	26
Parameters	26
Examples	26
Get-SdIscsiTarget	26
Syntax	26
Detailed Description	26
Parameters	27
Examples	27
Get-SdLun	27
Syntax	27
Detailed Description	27
Parameters	28
Examples	28
Get-SdLunMap	28
Syntax	28
Detailed Description	28
Parameters	28
Examples	29
Get-SdLunMapWithUuid	29
Syntax	29
Detailed Description	29
Parameters	29
Examples	29
Get-SdLunWithUuid	29
Syntax	29
Detailed Description	30
Parameters	30
Examples	30
Get-SdNfsExport	30
Syntax	30
Detailed Description	30
Parameters	30
Examples	31
Get-SdPlugIn	31
Syntax	31
Detailed Description	31
Parameters	31
Examples	31
Get-SdPlugInResource	31

Syntax	31
Detailed Description	31
Parameters	31
Examples	32
Get-SdPortSet	32
Syntax	32
Detailed Description	32
Parameters	32
Examples	33
Get-SdSMBShadowCopyEmsMessage	33
Syntax	33
Detailed Description	33
Parameters	33
Examples	33
Get-SdSnapMirror	34
Syntax	34
Detailed Description	34
Parameters	34
Examples	35
Get-SdSnapMirrorPolicyRule	36
Syntax	36
Detailed Description	36
Parameters	36
Examples	37
Get-SdSnapshot	38
Syntax	38
Detailed Description	38
Parameters	38
Examples	39
Get-SdStorage	43
Syntax	43
Detailed Description	44
Parameters	44
Examples	45
Get-SdStorageConnectionSetting	46
Syntax	46
Detailed Description	47
Parameters	47
Examples	47
Get-SdVM	48
Syntax	48
Detailed Description	48
Parameters	48
Examples	49
Get-SdVolumeCloneSplit	51

Syntax	51
Detailed Description	51
Parameters	51
Examples	52
Get-SdVolumeCloneSplitEstimate	52
Syntax	52
Detailed Description	52
Parameters	52
Examples	53
Get-SdVsphereSetting	53
Syntax	53
Detailed Description	53
Parameters	53
Examples	53
Invoke-SdEmsAutosupportLog	53
Syntax	53
Detailed Description	53
Parameters	54
Examples	55
Invoke-SdHostVolumeSpaceReclaim	56
Syntax	56
Detailed Description	56
Parameters	56
Examples	57
Invoke-SdSnapMirrorUpdate	57
Syntax	57
Detailed Description	57
Parameters	57
Examples	59
Map-SdLUNS	62
Syntax	62
Detailed Description	62
Parameters	62
Examples	63
Mount-SdClone	63
Syntax	63
Detailed Description	63
Parameters	63
Examples	64
Mount-SdSnapshot	65
Syntax	65
Detailed Description	65
Parameters	65
Examples	67
New-SdBackup	70

Syntax	70
Detailed Description	70
Parameters	70
Examples	71
New-SdIgroup	71
Syntax	71
Detailed Description	71
Parameters	71
Examples	72
New-SdLun	72
Syntax	72
Detailed Description	72
Parameters	72
Examples	73
New-SdPortSet	73
Syntax	73
Detailed Description	73
Parameters	73
Examples	74
New-SdSMBShare	74
Syntax	74
Detailed Description	74
Parameters	74
Examples	77
New-SdSnapshot	77
Syntax	77
Detailed Description	77
Parameters	77
Examples	78
New-SdStorage	79
Syntax	79
Detailed Description	79
Parameters	79
Examples	81
New-SdVolume	84
Syntax	84
Detailed Description	85
Parameters	85
Examples	98
Remove-SdBackup	99
Syntax	99
Detailed Description	99
Parameters	99
Examples	100
Remove-SdIgroup	100

Syntax	100
Detailed Description	100
Parameters	100
Examples	101
Remove-SdLun	101
Syntax	101
Detailed Description	101
Parameters	101
Examples	101
Remove-SdLunMap	102
Syntax	102
Detailed Description	102
Parameters	102
Examples	102
Remove-SdPortSet	102
Syntax	102
Detailed Description	103
Parameters	103
Examples	103
Remove-SdPortSetPort	103
Syntax	103
Detailed Description	103
Parameters	104
Examples	104
Remove-SdSMBShare	104
Syntax	104
Detailed Description	104
Parameters	104
Examples	105
Remove-SdSnapMirrorPolicyRule	105
Syntax	105
Detailed Description	105
Parameters	105
Examples	106
Remove-SdSnapshot	106
Syntax	107
Detailed Description	107
Parameters	107
Examples	107
Remove-SdStorage	108
Syntax	108
Detailed Description	108
Parameters	108
Examples	109
Remove-SdStorageConnectionSetting	109

Syntax	109
Detailed Description	109
Parameters	109
Examples	110
Remove-SdVolume	111
Syntax	111
Detailed Description	111
Parameters	111
Examples	112
Remove-SdVsphereSetting	112
Syntax	112
Detailed Description	112
Parameters	112
Examples	112
Rename-SdIgroup	113
Syntax	113
Detailed Description	113
Parameters	113
Examples	113
Rename-SdSnapshot	114
Syntax	114
Detailed Description	114
Parameters	114
Examples	115
Repair-SdAluaPaths	116
Syntax	116
Detailed Description	116
Parameters	116
Examples	116
Restore-SdPlugInResource	116
Syntax	116
Detailed Description	116
Parameters	117
Examples	117
Restore-SdSnapshot	117
Syntax	117
Detailed Description	117
Parameters	117
Examples	118
Set-SdAluaStateMonitor	119
Syntax	119
Detailed Description	120
Parameters	120
Examples	120
Set-SdDiskDriveLetter	120

Syntax	120
Detailed Description	120
Parameters	121
Examples	121
Set-SdSettings	121
Syntax	121
Detailed Description	121
Parameters	121
Examples	122
Set-SdSnapMirrorPolicyRule	122
Syntax	122
Detailed Description	122
Parameters	122
Examples	123
Set-SdSnapshot	124
Syntax	124
Detailed Description	124
Parameters	125
Examples	125
Set-SdStorageConnectionSetting	126
Syntax	126
Detailed Description	126
Parameters	127
Examples	129
Set-SdStorageSize	131
Syntax	131
Detailed Description	131
Parameters	131
Examples	131
Set-SdVsphereSetting	132
Syntax	132
Detailed Description	132
Parameters	132
Examples	132
Start-SdVolumeCloneSplit	132
Syntax	133
Detailed Description	133
Parameters	133
Examples	133
Stop-SdVolumeCloneSplit	133
Syntax	133
Detailed Description	133
Parameters	133
Examples	134
UnMap-SdLUNS	134

Syntax	134
Detailed Description	134
Parameters	134
Examples	134
SnapCenter data protection cmdlets	135
Add-SmCloneDataSet	135
Syntax	135
Detailed Description	135
Parameters	135
Examples	137
Add-SmCloneJob	140
Syntax	140
Detailed Description	141
Parameters	141
Examples	144
Add-SmCredential	145
Syntax	145
Detailed Description	146
Parameters	146
Examples	146
Add-SmDomain	147
Syntax	147
Detailed Description	147
Parameters	147
Examples	148
Add-SmGroup	150
Syntax	150
Detailed Description	150
Parameters	150
Examples	150
Add-SmGroupToRole	151
Syntax	151
Detailed Description	151
Parameters	151
Examples	151
Add-SmHost	152
Syntax	152
Detailed Description	152
Parameters	152
Examples	153
Add-SmPermissionToRole	159
Syntax	159
Detailed Description	159
Parameters	159
Examples	159

Add-SmPlugin	160
Syntax	160
Detailed Description	160
Parameters	160
Examples	161
Add-SmPolicy	162
Syntax	162
Detailed Description	162
Parameters	162
Examples	168
Add-SmProtectResource	181
Syntax	181
Detailed Description	181
Parameters	181
Examples	185
Add-SmReportSchedule	191
Syntax	191
Detailed Description	192
Parameters	192
Examples	193
Add-SmResource	193
Syntax	194
Detailed Description	194
Parameters	194
Examples	196
Add-SmResourceGroup	206
Syntax	207
Detailed Description	207
Parameters	207
Examples	212
Add-SmResourceToUser	219
Syntax	219
Detailed Description	219
Parameters	219
Examples	220
Add-SmServer	221
Syntax	221
Detailed Description	221
Parameters	221
Examples	221
Add-SmServerCluster	222
Syntax	222
Detailed Description	222
Parameters	223
Examples	223

Add-SmStorageConnection	224
Syntax	224
Detailed Description	225
Parameters	225
Examples	226
Add-SmUser	228
Syntax	228
Detailed Description	228
Parameters	228
Examples	228
Add-SmUserToRole	229
Syntax	229
Detailed Description	229
Parameters	229
Examples	229
Add-SmVerificationServer	230
Syntax	230
Detailed Description	230
Parameters	230
Examples	231
Cancel-SmJob	231
Syntax	232
Detailed Description	232
Parameters	232
Examples	232
Cancel-SmRestoreJob	233
Syntax	233
Detailed Description	233
Parameters	233
Examples	233
Catalog-SmBackupWithOracleRMAN	233
Syntax	233
Detailed Description	233
Parameters	233
Examples	234
Configure-SmDatabase	239
Syntax	239
Detailed Description	239
Parameters	240
Examples	240
Configure-SmOracleDatabase	240
Syntax	241
Detailed Description	241
Parameters	241
Examples	242

Copy-SmPolicy	242
Syntax	242
Detailed Description	242
Parameters	242
Examples	243
Copy-SmRole	244
Syntax	244
Detailed Description	244
Parameters	244
Examples	244
Disable-SmDataCollectionEms	244
Syntax	244
Detailed Description	245
Parameters	245
Examples	245
Enable-SmDataCollectionEms	245
Syntax	245
Detailed Description	245
Parameters	245
Examples	245
Enable-SmRepositoryHAConfig	246
Syntax	246
Detailed Description	246
Parameters	246
Examples	246
Get-SmAlert	246
Syntax	247
Detailed Description	247
Parameters	247
Examples	247
Get-SmAssignedGroups	252
Syntax	252
Detailed Description	252
Parameters	252
Examples	252
Get-SmAssignedRoles	253
Syntax	253
Detailed Description	253
Parameters	253
Examples	254
Get-SmAssignedUsers	255
Syntax	255
Detailed Description	255
Parameters	255
Examples	255

Get-SmAuditSettings	257
Syntax	257
Detailed Description	257
Parameters	257
Examples	257
Get-SmAuditSettings	258
Syntax	258
Detailed Description	258
Parameters	258
Examples	258
Get-SmBackup	259
Syntax	259
Detailed Description	260
Parameters	260
Examples	260
Get-SmBackupReport	261
Syntax	261
Detailed Description	262
Parameters	262
Examples	263
Get-SmBackupsForPointInTimeRecovery	266
Syntax	266
Detailed Description	266
Parameters	266
Examples	268
Get-SmCertificateSettings	270
Syntax	270
Detailed Description	270
Parameters	270
Examples	270
Get-SmClone	271
Syntax	271
Detailed Description	272
Parameters	272
Examples	273
Get-SmCloneJob	275
Syntax	275
Detailed Description	275
Parameters	275
Examples	276
Get-SmCloneReport	276
Syntax	276
Detailed Description	276
Parameters	276
Examples	277

Get-SmCompatibilityFile	279
Syntax	279
Detailed Description	279
Parameters	279
Examples	280
Get-SmConfigSettings	280
Syntax	280
Detailed Description	280
Parameters	280
Examples	281
Get-SmCredential	282
Syntax	283
Detailed Description	283
Parameters	283
Examples	283
Get-SmDataCollectionEmsSchedule	283
Syntax	284
Detailed Description	284
Parameters	284
Examples	284
Get-SmDataCollectionEmsStatus	284
Syntax	284
Detailed Description	284
Parameters	284
Examples	285
Get-SmDataCollectionEmsTarget	285
Syntax	285
Detailed Description	285
Parameters	285
Examples	285
Get-SmDomain	285
Syntax	286
Detailed Description	286
Parameters	286
Examples	286
Get-SmDownloadRepository	287
Syntax	287
Detailed Description	287
Parameters	287
Examples	287
Get-SmDownloads	288
Syntax	288
Detailed Description	288
Parameters	288
Examples	288

Get-SmHost	290
Syntax	290
Detailed Description	290
Parameters	290
Examples	291
Get-SmHostSignature	293
Syntax	293
Detailed Description	293
Parameters	293
Examples	293
Get-SmJobSummaryReport	294
Syntax	294
Detailed Description	294
Parameters	294
Examples	294
Get-SmLoadBalanceNode	296
Syntax	296
Detailed Description	296
Parameters	296
Examples	297
Get-SmLogSettings	297
Syntax	297
Detailed Description	297
Parameters	297
Examples	298
Get-SmLogs	299
Syntax	299
Detailed Description	300
Parameters	300
Examples	300
Get-SmMultiFactorAuthentication	301
Syntax	301
Detailed Description	301
Parameters	301
Examples	301
Get-SmPluginConfiguration	302
Syntax	302
Detailed Description	302
Parameters	302
Examples	302
Get-SmPluginPackage	303
Syntax	303
Detailed Description	303
Parameters	303
Examples	304

Get-SmPluginReport	304
Syntax	304
Detailed Description	305
Parameters	305
Examples	305
Get-SmPolicy	307
Syntax	307
Detailed Description	308
Parameters	308
Examples	308
Get-SmReportSchedule	313
Syntax	313
Detailed Description	313
Parameters	313
Examples	313
Get-SmRepositoryBackups	316
Syntax	317
Detailed Description	317
Parameters	317
Examples	317
Get-SmRepositoryConfig	317
Syntax	317
Detailed Description	317
Parameters	318
Examples	318
Get-SmResourceCredentialName	319
Syntax	319
Detailed Description	319
Parameters	319
Examples	319
Get-SmResourceGroup	320
Syntax	320
Detailed Description	320
Parameters	321
Examples	321
Get-SmResources	323
Syntax	323
Detailed Description	323
Parameters	324
Examples	325
Get-SmRestoreReport	336
Syntax	336
Detailed Description	337
Parameters	337
Examples	338

Get-SmRole	339
Syntax	339
Detailed Description	340
Parameters	340
Examples	340
Get-SmRoleAssignedPermission	342
Syntax	342
Detailed Description	342
Parameters	342
Examples	342
Get-SmRolePermissions	351
Syntax	351
Detailed Description	351
Parameters	351
Examples	351
Get-SmSMTPServer	353
Syntax	353
Detailed Description	353
Parameters	353
Examples	353
Get-SmSchedule	353
Syntax	353
Detailed Description	353
Parameters	354
Examples	354
Get-SmServerConfig	357
Syntax	357
Detailed Description	357
Parameters	357
Examples	357
Get-SmSnapCenterVersion	358
Syntax	358
Detailed Description	358
Parameters	358
Examples	358
Get-SmStorageConnection	358
Syntax	359
Detailed Description	359
Parameters	359
Examples	359
Get-SmTrustedDomains	362
Syntax	362
Detailed Description	362
Parameters	362
Examples	363

Get-SmUserAssignedPermission	363
Syntax	363
Detailed Description	363
Parameters	363
Examples	363
Get-SmUsersAndGroups	370
Syntax	371
Detailed Description	371
Parameters	371
Examples	371
Get-SmVerificationServer	371
Syntax	371
Detailed Description	371
Parameters	372
Examples	372
Install-SmHostPackage	373
Syntax	373
Detailed Description	374
Parameters	374
Examples	375
Invoke-DiagnosticLogCollection	376
Syntax	377
Detailed Description	377
Parameters	377
Examples	377
Invoke-SCVOVAMigration	378
Syntax	378
Detailed Description	378
Parameters	378
Examples	379
Invoke-SmBackupMigration	380
Syntax	380
Detailed Description	380
Parameters	380
Examples	380
Invoke-SmBackupVerification	381
Syntax	381
Detailed Description	381
Parameters	381
Examples	383
Invoke-SmConfigureResources	384
Syntax	384
Detailed Description	385
Parameters	385
Examples	386

Invoke-SmPrimaryBackupsExistenceCheck	387
Syntax	387
Detailed Description	387
Parameters	387
Examples	388
Invoke-SmReportSchedule	389
Syntax	389
Detailed Description	389
Parameters	389
Examples	389
Invoke-SmResourceSplit	389
Syntax	389
Detailed Description	390
Parameters	390
Examples	391
Invoke-SmTechRefreshHost	395
Syntax	395
Detailed Description	395
Parameters	395
Examples	396
Invoke-SmTechRefreshPrimaryStorage	398
Syntax	398
Detailed Description	399
Parameters	399
Examples	399
Invoke-SmTechRefreshSecondaryStorage	401
Syntax	401
Detailed Description	401
Parameters	402
Examples	402
Invoke-Sm_ExecuteQuery	403
Syntax	403
Detailed Description	403
Parameters	403
Examples	403
New-SmAlert	403
Syntax	403
Detailed Description	403
Parameters	403
Examples	404
New-SmBackup	405
Syntax	405
Detailed Description	405
Parameters	405
Examples	407

New-SmClone	409
Syntax	409
Detailed Description	410
Parameters	410
Examples	418
New-SmMountBackup	435
Syntax	435
Detailed Description	435
Parameters	435
Examples	435
New-SmMultifactorAuthenticationMetadata	437
Syntax	437
Detailed Description	437
Parameters	437
Examples	437
New-SmRole	437
Syntax	438
Detailed Description	438
Parameters	438
Examples	438
New-SmServerBackup	441
Syntax	441
Detailed Description	442
Parameters	442
Examples	442
New-SmUnmountBackup	444
Syntax	444
Detailed Description	444
Parameters	444
Examples	445
Open-SmConnection	445
Syntax	445
Detailed Description	445
Parameters	445
Examples	446
Protect-SmRepository	448
Syntax	448
Detailed Description	448
Parameters	448
Examples	448
Refresh-SmBackup	449
Syntax	449
Detailed Description	449
Parameters	449
Examples	449

Refresh-SmSnapLock	449
Syntax	450
Detailed Description	450
Parameters	450
Examples	450
Refresh-SmSyncSnapMirrorBackups	451
Syntax	451
Detailed Description	451
Parameters	451
Examples	451
Remove-SmAlert	452
Syntax	452
Detailed Description	452
Parameters	452
Examples	452
Remove-SmBackup	453
Syntax	453
Detailed Description	453
Parameters	454
Examples	454
Remove-SmClone	456
Syntax	456
Detailed Description	456
Parameters	456
Examples	457
Remove-SmCloneJob	462
Syntax	462
Detailed Description	462
Parameters	463
Examples	463
Remove-SmCredential	463
Syntax	463
Detailed Description	463
Parameters	463
Examples	464
Remove-SmDRFailoverBackups	464
Syntax	464
Detailed Description	464
Parameters	464
Examples	464
Remove-SmDomain	466
Syntax	466
Detailed Description	466
Parameters	467
Examples	467

Remove-SmGroup	467
Syntax	467
Detailed Description	467
Parameters	467
Examples	467
Remove-SmGroupFromRole	468
Syntax	468
Detailed Description	468
Parameters	468
Examples	468
Remove-SmHost	469
Syntax	469
Detailed Description	469
Parameters	469
Examples	470
Remove-SmJobs	474
Syntax	474
Detailed Description	474
Parameters	474
Examples	475
Remove-SmPermissionFromRole	475
Syntax	475
Detailed Description	476
Parameters	476
Examples	476
Remove-SmPlugin	477
Syntax	477
Detailed Description	477
Parameters	477
Examples	477
Remove-SmPluginPackage	478
Syntax	478
Detailed Description	479
Parameters	479
Examples	479
Remove-SmPolicy	479
Syntax	479
Detailed Description	479
Parameters	479
Examples	480
Remove-SmProtectResource	480
Syntax	480
Detailed Description	480
Parameters	480
Examples	481

Remove-SmReportSchedule	482
Syntax	482
Detailed Description	483
Parameters	483
Examples	483
Remove-SmRepositoryProtection	483
Syntax	483
Detailed Description	483
Parameters	483
Examples	483
Remove-SmResource	484
Syntax	484
Detailed Description	484
Parameters	484
Examples	485
Remove-SmResourceCredentialName	486
Syntax	486
Detailed Description	487
Parameters	487
Examples	487
Remove-SmResourceDRMode	487
Syntax	487
Detailed Description	487
Parameters	488
Examples	488
Remove-SmResourceFromUser	489
Syntax	490
Detailed Description	490
Parameters	490
Examples	490
Remove-SmResourceGroup	491
Syntax	491
Detailed Description	491
Parameters	491
Examples	491
Remove-SmRole	492
Syntax	492
Detailed Description	492
Parameters	492
Examples	492
Remove-SmServer	493
Syntax	493
Detailed Description	493
Parameters	493
Examples	493

Remove-SmServerCluster	494
Syntax	494
Detailed Description	494
Parameters	495
Examples	495
Remove-SmStorageConnection	496
Syntax	496
Detailed Description	496
Parameters	497
Examples	497
Remove-SmUser	497
Syntax	497
Detailed Description	498
Parameters	498
Examples	498
Remove-SmUserFromRole	498
Syntax	498
Detailed Description	498
Parameters	499
Examples	499
Remove-SmVerificationServer	500
Syntax	500
Detailed Description	500
Parameters	500
Examples	500
Rename-SmBackup	500
Syntax	501
Detailed Description	501
Parameters	501
Examples	501
Reseed-SmBackup	501
Syntax	501
Detailed Description	502
Parameters	502
Examples	502
Reseed-SmDagReplicaCopy	502
Syntax	502
Detailed Description	502
Parameters	502
Examples	503
Restore-SmBackup	503
Syntax	503
Detailed Description	504
Parameters	504
Examples	508

Restore-SmRepositoryBackup	532
Syntax	532
Detailed Description	532
Parameters	532
Examples	532
Restore-SmServerBackup	533
Syntax	533
Detailed Description	533
Parameters	533
Examples	533
Send-SmDataCollectionEms	535
Syntax	535
Detailed Description	535
Parameters	536
Examples	536
Set-SmAuditSettings	536
Syntax	536
Detailed Description	536
Parameters	536
Examples	537
Set-SmAuditSettings	538
Syntax	538
Detailed Description	538
Parameters	538
Examples	539
Set-SmCertificateSettings	540
Syntax	540
Detailed Description	540
Parameters	541
Examples	541
Set-SmCloneDataSet	543
Syntax	543
Detailed Description	544
Parameters	544
Examples	545
Set-SmCloneJob	548
Syntax	548
Detailed Description	549
Parameters	549
Examples	550
Set-SmConfigSettings	552
Syntax	553
Detailed Description	553
Parameters	553
Examples	553

Set-SmCredential	555
Syntax	555
Detailed Description	555
Parameters	555
Examples	556
Set-SmDataCollectionEmsSchedule	556
Syntax	557
Detailed Description	557
Parameters	557
Examples	557
Set-SmDataCollectionEmsTarget	557
Syntax	557
Detailed Description	558
Parameters	558
Examples	558
Set-SmDatasetMaintenance	558
Syntax	558
Detailed Description	558
Parameters	559
Examples	559
Set-SmDisasterRecovery	559
Syntax	559
Detailed Description	559
Parameters	559
Examples	560
Set-SmDomain	561
Syntax	561
Detailed Description	562
Parameters	562
Examples	563
Set-SmDownloadRepository	564
Syntax	564
Detailed Description	564
Parameters	565
Examples	565
Set-SmESXInfo	565
Syntax	565
Detailed Description	565
Parameters	565
Examples	565
Set-SmHost	566
Syntax	566
Detailed Description	566
Parameters	566
Examples	566

Set-SmLogSettings	567
Syntax	567
Detailed Description	568
Parameters	568
Examples	569
Set-SmMaintenanceMode	570
Syntax	571
Detailed Description	571
Parameters	571
Examples	571
Set-SmMultiFactorAuthentication	571
Syntax	572
Detailed Description	572
Parameters	572
Examples	572
Set-SmPluginConfiguration	575
Syntax	575
Detailed Description	575
Parameters	575
Examples	576
Set-SmPolicy	577
Syntax	577
Detailed Description	577
Parameters	577
Examples	583
Set-SmProtectResource	586
Syntax	586
Detailed Description	587
Parameters	587
Examples	591
Set-SmReportSchedule	592
Syntax	592
Detailed Description	592
Parameters	592
Examples	593
Set-SmRepositoryConfig	594
Syntax	594
Detailed Description	595
Parameters	595
Examples	595
Set-SmRepositoryConfigSettings	600
Syntax	600
Detailed Description	600
Parameters	601
Examples	601

Set-SmRepositoryPassword	601
Syntax	601
Detailed Description	601
Parameters	601
Examples	602
Set-SmResource	602
Syntax	602
Detailed Description	602
Parameters	602
Examples	603
Set-SmResourceCredentialName	609
Syntax	609
Detailed Description	610
Parameters	610
Examples	610
Set-SmResourceGroup	610
Syntax	610
Detailed Description	610
Parameters	611
Examples	615
Set-SmResourceName	617
Syntax	617
Detailed Description	618
Parameters	618
Examples	618
Set-SmRole	618
Syntax	618
Detailed Description	618
Parameters	619
Examples	619
Set-SmSMTPServer	620
Syntax	620
Detailed Description	620
Parameters	620
Examples	621
Set-SmSchedule	621
Syntax	621
Detailed Description	621
Parameters	621
Examples	621
Set-SmServerConfig	622
Syntax	622
Detailed Description	623
Parameters	623
Examples	623

Set-SmStorageConnection	625
Syntax	625
Detailed Description	626
Parameters	626
Examples	627
Start-SmAuditIntegrityCheck	628
Syntax	628
Detailed Description	628
Parameters	628
Examples	628
Stop-SmJob	629
Syntax	629
Detailed Description	629
Parameters	629
Examples	629
Uncatalog-SmBackupWithOracleRMAN	630
Syntax	630
Detailed Description	630
Parameters	630
Examples	630
Uninstall-SmHostPackage	633
Syntax	633
Detailed Description	633
Parameters	634
Examples	634
Update-SmBackup	635
Syntax	635
Detailed Description	635
Parameters	635
Examples	635
Update-SmHostPackage	636
Syntax	636
Detailed Description	636
Parameters	636
Examples	637
Update-SmServerCluster	637
Syntax	637
Detailed Description	637
Parameters	637
Examples	638
Upload-SmPluginPackage	639
Syntax	639
Detailed Description	639
Parameters	640
Examples	640

Legal notices 641

 Copyright 641

 Trademarks 641

 Patents 641

 Privacy policy 641

 Open source 641

SnapCenter 6.1 cmdlets

Implement automatic import module using PowerShell

You must install PowerShell 7 before you upgrade to SnapCenter 6.0 or later. PowerShell 7 does not automatically load the modules. You cannot execute the PowerShell commands without these modules. You can either use the UI or one of the scripts provided in this section to automatically import the modules.

Import the modules using UI

PowerShell 7 installation provides a desktop shortcut on the SnapCenter Server to start and import the module. This shortcut sets up a PowerShell session with the necessary modules that were imported earlier.

Script to update the script to include the Import-Module command

Each script explicitly imports the SnapCenter module before attempting to use its commands. This ensures that the module is loaded regardless of the environment it has run in.

Step

1. Run the following command at the beginning of the PowerShell script:

```
Import-Module SnapCenter -DisableNameChecking
```

Script to update the Windows task scheduler command

You can modify the task in the Task Scheduler to first load the module and then execute the script. This can be done by chaining commands in the 'Actions' settings when you edit the task.

Step

1. Run the following command for the task:

```
"C:\Program Files\PowerShell\7\pwsh.exe" -noe -c "& { . 'C:\Program Files\PowerShell\7\Modules\SnapCenter\Scripts\Initialize-SnapCenterPS-Environment.ps1' 'NetApp'; & '<customer script file path>' }"
```

For example, "C:\Program Files\PowerShell\7\pwsh.exe" -noe -c "& { . 'C:\Program Files\PowerShell\7\Modules\SnapCenter\Scripts\Initialize-SnapCenterPS-Environment.ps1' 'NetApp'; & 'C:\test.ps1' }"

Script to update the PowerShell profile file

To ensure that the SnapCenter module is imported every time a PowerShell session starts, you must edit the PowerShell profile script. This is useful if you have multiple scripts that depend on the SnapCenter module.

Steps

1. Run the following command to create the profile file:

```
notepad $PROFILE
```

This will open the profile file or creates it if it does not exist.

2. Run the following command to check if the SnapCenter module exists before trying to import.

Ensure that you update the path accordingly.

```
$modulePath = 'C:\Program  
Files\PowerShell\7\Modules\SnapCenter\SnapCenter.psd1'  
if (Test-Path $modulePath) {  
  Import-Module $modulePath -DisableNameChecking  
} else {  
  Write-Warning "SnapCenter module not found at path: $modulePath"  
}
```

SnapCenter Windows disk management cmdlets

Add-SdIgroupInitiator

Adds one or more FCP and/or iSCSI initiators to an existing igroup on your storage system.

Syntax

```
Add-SdIgroupInitiator [-Name] <String> [-Initiators] <String[]> [-StorageSystem] <String> [-Validate] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Adds one or more FCP and/or iSCSI initiators to an existing igroup on your storage system. You should not mix FCP and iSCSI initiators on a specified Windows node. You can mix FCP and iSCSI initiators in a clustered scenario on a Windows node.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the igroup to which you want to add an array of FCP or iSCSI initiators.	true	true (ByPropertyName)	
Initiators	Provides a comma-separated list of the FCP or iSCSI initiators you want to add to your igroup.	true	true (ByPropertyName)	
StorageSystem	Specifies the storage system on which your igroup is defined.	true	true (ByPropertyName)	
Validate		false	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Adding an FCP initiator to an igroup

```
PS C:\> Add-SdIgroupInitiator -Name IGroupFCPDemo -Initiators  
"20:00:00:0e:13:75:90:02" -StorageSystem 172.17.168.13
```

This example syntax adds an FCP initiator to the specified igroup.

Example 2: Adding an iSCSI initiator to an igroup

```
PS C:\> Add-SdIgroupInitiator -Name IgroupDemo -Initiators iqn.1991-  
05.com.microsoft:mva-s24-rx200.sddev.mycompany.com -StorageSystem  
172.17.168.13
```

This example syntax adds an iSCSI initiator to the specified igroup.

Example 3: Adding an array of initiators to your igroup

```
PS C:\> Add-SdIgroupInitiator -Name IgroupDemo -Initiators iqn.1991-  
05.com.microsoft:mva-s24-rx200.sddev.mycompany.com, iqn.1991-  
05.com.microsoft:mva-rx200-s4.sddev.mycompany.com -StorageSystem  
172.17.168.13
```

This example syntax adds an array of initiators to the specified igroup.

Add-SdLunMap

Maps your LUN to an igroup.

Syntax

```
Add-SdLunMap [-StorageSystem] <String> [-LunPath] <String> [-Igroup]  
<String> [-Session] <String> [-Host] <String>
```

Detailed Description

Maps your LUN to an igroup. You can use this on the storage system level, for Data ONTAP storage systems. If you are performing provisioning operations, use `New-SdStorage`.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the storage system on which the igroup to which you want to map your LUN is located.	true	true (ByPropertyName)	
LunPath	Specifies the LUN on your storage system.	true	true (ByPropertyName)	
Igroup	Specifies the igroup to which you want to map your LUN.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection. For internal use only.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Mapping a LUN to an igroup on an ONTAP storage system

```
Add-SdLunMap -StorageSystem svm1 -LunPath /vol/vol1/lun1 -Igroup
"myTestIgroup"
```

This example syntax maps the LUN called lun1 to the igroup "myTestIgroup" on svm1.

Add-SdPortSetPort

Adds a port to an existing portset.

Syntax

```
Add-SdPortSetPort [-PortSetName] <String> [-Port] <String> [-
StorageSystem] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Adds a port to an existing portset.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PortSetName	Specifies the name of the portset to which you want to add a new port.	true	true (ByPropertyName)	
Port	Specifies the name of the port you want to add to your portset.	true	true (ByPropertyName)	
StorageSystem	Specifies the storage system on which your portset resides.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection. For internal use only.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Connect-SdIscsiTarget

Establishes a session with your specified iSCSI target.

Syntax

```
Connect-SdIscsiTarget [-TargetNodeAddress] <String> [-TargetPortalAddress] <String> [-TargetPortalPortNumber] <UInt16> [-InitiatorPortalAddress] <String> [-CHAPUserName] <String> [-CHAPPassword] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Establishes a session with your specified iSCSI target.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
TargetNodeAddress	Specifies the target node address.	true	true (ByPropertyName)	
TargetPortalAddress	Specifies the target portal address.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
TargetPortalPortNumber	Specifies the target portal port number.	false	true (ByPropertyName)	
InitiatorPortalAddresses	Specifies the initiator portal address.	false	true (ByPropertyName)	
CHAPUserName	Specifies your CHAP user name.	false	true (ByPropertyName)	
CHAPPassword	Specifies your CHAP password.	false	true (ByPropertyName)	
Session	Specifies the session ID from OpenSmConnection. For internal use only.	false	true (ByPropertyName)	
Host	Specifies the name of the computer or host on which the SnapCenter Plug-in for Microsoft Windows service you want to perform the operation runs. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Connecting to an iSCSI target

```
PS C:\> Connect-SdIscsiTarget -TargetNodeAddress iqn.1992-08.com.netapp:sn.54053432d1f311e19455123478563412:vs.5
-TargetPortalAddress 172.17.175.84 -TargetPortalPortNumber 3260
```

This example syntax connects you to an iSCSI target.

Connect-SdStorage

Connects a Windows disk to a LUN.

Syntax

```
Connect-SdStorage [-Path] <String> [-LunPath] <String> [-StorageSystem] <String> [-SharedDisk] <> [-ClusteredSharedVolume] <> [-Igroup] <String> [-InitiatorInfo] <HostInitiatorInfo> [-PortSet] <String> [-AutoPickPortSet] <> [-AutopickMountPoint] <> [-ResourceGroup] <String> [-RawDeviceMapping] <> [-Datastore] <String> [-FileSystemLabel] <String> [-Session] <String> [-Host] <String>
```


Detailed Description

Connects a dedicated disk, shared disk, or a clustered shared volume based on a LUN.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the drive letter or mount point: D:, D:\	false	true (ByPropertyName)	
LunPath	Specifies your LUN path using this format: /vol/volx/lunx	true	true (ByPropertyName)	
StorageSystem	Specifies the target virtual storage machine that you are going to use for provisioning.	true	true (ByPropertyName)	
SharedDisk	Indicates whether you need to provision your Windows disk as a shared disk.	false	true (ByPropertyName)	
ClusteredSharedVolume	Indicates whether you will provision your Windows disk as a Clustered Shared Volume.	false	true (ByPropertyName)	
Igroup	Specifies the igroup you want to use for mapping the LUN. If not specified, SnapCenter Plug-in for Microsoft Windows automatically manages the igroup for mapping the LUN.	false	true (ByPropertyName)	
InitiatorInfo	Specifies the initiators you want to add to your Igroup.	false	true (ByPropertyName)	
PortSet	Specifies the portset you want to use for binding your igroup. If your igroup is already bound to a different portset, specifying this parameter unbinds your igroup and then binds it to the portset specified here.	false	true (ByPropertyName)	
AutoPickPortSet	Indicates whether you want SnapCenter Plug-in for Microsoft Windows to handle the portset binding automatically.	false	true (ByPropertyName)	
AutopickMountPoint	Specifies whether SnapCenter Plug-in for Windows automatically picks the drive letter/volume mount point for the connected disk.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ResourceGroup	Specifies the Cluster Resource Group you want to use for a shared disk.	false	true (ByPropertyName)	
RawDeviceMapping	Specifies whether the disk is provisioned as RAW device Mapping.	false	true (ByPropertyName)	
Datastore	Specifies whether the datastore is to be used for RDM.	false	true (ByPropertyName)	
FileSystemLabel	Specifies the label you want to attach to your new Windows volume.	false	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies your target host.	false	true (ByPropertyName)	

Examples

Example 1: Connecting to a dedicated Windows disk

```
PS C:\> connect-sdstorage -StorageSystem 172.17.165.31 -path V: -LunPath /vol/santest/b09
```

In this example syntax, you connect to a dedicated disk.

Example 2: Connecting to a shared Windows disk

```
PS C:\> connect-sdstorage -StorageSystem 172.17.165.31 -path V: -LunPath /vol/santest/b09 -SharedDisk -ResourceGroup prod
```

In this example syntax, you connect to a shared disk.

Example 3: Connecting to a Clustered Shared Volume

```
PS C:\> connect-sdstorage -StorageSystem 172.17.165.31 -LunPath /vol/santest/b09 -ClusteredSharedVolume
```

In this example syntax, you connect to a Clustered Shared Volume.

Debug-SdHost

Troubleshoots your system setup.

Syntax

```
Debug-SdHost [-Session] <String> [-Host] <String> [-RuleCategory]
<Category> [-Session] <String> [-Host] <String>
```

Detailed Description

Troubleshoots your system setup. You can use this cmdlet to identify problems with the following rules:a) Validate storage connection settings.b) Export-policy rule.c) SMB share "continuously-available" property.d) SMB share ACL setup.When you are troubleshooting a clustered Data ONTAP environment, run Debug-SdHost on each node of the Windows cluster.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
RuleCategory	Indicates that you want to troubleshoot the specified category only.	false	true (ByPropertyName)	

Examples

Example 1: Debugging your host

```
PS C:\> Debug-SdHost
```

In this example syntax, you have checked your host for the various system setup problems and found errors with the export-policy rule, the SMB share ACL setup rule, and the SMB share "continuously-available" property rule.

```
Rule: Storage connections.
Description : The storage connection rule verifies that the storage
connection settings on your host system are valid and active.
Category: General
Source : NEXTGEN-BOX59
```

```

Severity: Info
Problem : N/A
Impact  : N/A
Resolution : N/A
Message : Success. All your storage connection settings are valid and
active.
Rule: Export-Policy Rule
Description : The export-policy rule verifies that the client trying to
access the data objects is doing so using the SMB protocol.
Category: SMB
Source : NEXTGEN-BOX59
Severity: Info
Problem : N/A
Impact  : N/A
Resolution : N/A
Message : Success. The SMB protocol is set in the export-policy rule of
all the virtual storage servers.
Rule: SMB share ACL setup.
Description : This rule verifies that the share ACL has host permissions,
and if your host is a part of a cluster it verifies that the share has
cluster
permissions.
Category: Hyper_V
Source : NEXTGEN-BOX59
Severity: Error
Problem : Your shares do not have access control set for the host or the
cluster.
Impact : You cannot access these shares from your host.
Resolution : Add the host or the cluster to your share's ACL.
Message : Error. The following shares do not have host or clusters set in
the ACLs: \\CIFS_SERV\admin$,\\CIFS_SERV\ipc$.
Rule: SMB share "continuously-available" property.
Description : This rule verifies that your SMB share contains the
continuously-available property. The continuously-available property is
mandatory for
installating a VM.
Category: Hyper_V
Source : NEXTGEN-BOX59
Severity: Error
Problem : Some of the shares do not contain the continuously-available
property.
Impact : You cannot install a VM on the share.
Resolution : Set the share property to continuously-available.
Message : Error. The following shares do not have continuously-available
property set:
\\CIFS_SERV\admin$,\\CIFS_SERV\sales_dbshare,\\CIFS_SERV\ACL,\\CIFS_SERV\

```

```
qtree,\\CIFS_SERV\ipc$.
```

Delete-SdLUNS

Syntax

```
Delete-SdLUNS [-LunPath] <String[]> [-RestApiURL] <String> [-Session]  
<String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
LunPath		true	true (ByValue, ByPropertyName)	
RestApiURL		true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Disconnect-SdIscsiTarget

Terminates your session with the iSCSI target.

Syntax

```
Disconnect-SdIscsiTarget [-SessionIdentifier] <String> [-  
TargetNodeAddress] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Terminates your session with the iSCSI target.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SessionIdentifier	Specifies the session identifier.	true	true (ByPropertyName)	
TargetNodeAddress	Specifies the target node address.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name of the computer or host on which the SnapCenter Plug-in for Microsoft Windows service you want to perform the operation runs. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Disconnecting from your iSCSI target session

```
PS C:\> Disconnect-SdIscsiTarget -SessionIdentifier fffffa800762f020-4000013700000001 -TargetNodeAddress iqn.1992-08.com.netapp:sn.54053432d1f311e19455123478563412:vs.5
```

This example syntax disconnects you from your iSCSI target session.

Disconnect-SdStorage

Disconnects your storage system from your Windows disk or SMB share.

Syntax

```
Disconnect-SdStorage [-Path] <String> [-IgnoreVolumeMountPoint] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Disconnects your Windows disk or SMB share from your storage system.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies your LUN path or mount point using the format: D:, D:\Mount	true	true (ByPropertyName)	
IgnoreVolumeMount Point		false	true (ByPropertyName)	
Session	Specifies the Session ID from Open-SmConnection	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Disconnecting a storage system from a Windows drive

```
PS C:\> Disconnect-SDStorage -Path K:
```

This example syntax disconnect the specified drive from a storage system.

Example 2: Disconnecting a storage system from a Windows mount point

```
PS C:\> Disconnect-SDStorage -Path K:\Mount
```

This example syntax disconnect the specified Mount Point from a storage system.

Dismount-SdClone

Enables dismounting a cloned storage resource.

Syntax

```
Dismount-SdClone [-ClonePath] <String[]> [-ResourceType] <ResourceType>
[-Session] <String> [-Host] <String>
```

Detailed Description

Enables dismounting a cloned storage resource. This can be a single clone or a comma-separated list of clones of the same resource type. Related cmdlets: Mount-SdClone, Get-SmClone, Remove-SmClone, New-SmClone

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ClonePath	Specifies the path to the clone that you want to dismount. This can be a single clone or a comma-separated list of clones of the same resource type.	true	true (ByValue, ByPropertyName)	
ResourceType	Specifies the type of the resource in the ClonePath parameter. The possible options are: "SDStorageVolume", "SDStorageLunPath", "SDStorageDir".	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the FQDN or IP address of the host on which you want to execute the operation.	false	true (ByPropertyName)	

Examples

Example 1: Dismount a clone from a given cloned path

```
PS C:\> Dismount-SdClone -ClonePath Primary_SVM:/vol/Vol11201210041488133  
-ResourceType SDStorageVolume
```

This example syntax specifies the cloned volume path and the resource type, and dismounts the clone.

```
Vserver : Primary_SVM  
FullPath: Primary_SVM:/vol/Vol11201210041488133  
JunctionPath:  
JunctionParentName :  
SizeTotal : 70931603456  
SizeUsed: 62187937792  
SnapMirrorSource:  
SnapMirrorDest :  
SnapVaultPrimary:  
SnapVaultSecondary :  
FlexCloneEnabled:  
IsFlexClone :  
VolumeSecurityStyle :  
AggregateName : Aggr4  
AggregateUuid : b3525de1-9aa0-46d2-9259-eeaef94d34b0  
FlexCloneLevel :
```


IsLeaf :
VolumeState : online
AggregateAvailableSpace :
ExportPolicy: default
VolumeUuid : fd1bb1d5-528a-11ec-a2a8-00a0986d2568
OwningVserverName : Primary_SVM
VolumeType :
IsProtected : False
StorageVmKey:
VolumeKey :
VolumeInstanceUuid :
Size:
IsRootVolume:
IsSelectable:
StorageKey :
ProtectionStatus:
ComplianceStatus:
StatusMessage :
SVMSloKey :
VolumeSloKey:
SpaceGuarantee :
PhysicalUsed: 7004160
IsFlexGroup :
ResourceType: SDStorageVolume
ResourceName: Primary_SVM:/vol/Vol11201210041488133
Ranges :
Name: Vol11201210041488133
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts :
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject :

Example 2: Dismount a set of clones from the given list of cloned paths

```
PS C:\> Dismount-SdClone -ClonePath
Primary_SVM:/vol/Vol11201212311309514,Primary_SVM:/vol/Vol1120121231535451
5 -ResourceType SDStorageVolume -Verbose
```

This example syntax specifies the list of cloned volume paths and their resource type, and dismounts the clones. The output is shortened for readability.

```
Vserver : Primary_SVM
FullPath: Primary_SVM:/vol/Vol11201212311309514
.....
Vserver : Primary_SVM
FullPath: Primary_SVM:/vol/Vol11201212315354515
.....
VERBOSE: Operation successful.
```

Dismount-SdSnapshot

Facilitates dismounting the list of SMB shares that are mounted from the specified Snapshot copy as a different set of shares. Facilitates dismounting the list of LUNs mounted from the specified Snapshot copies as a different set of LUNs.

Syntax

```
Dismount-SdSnapshot [-Path] <Object[]> [-DeleteParentClones] <> [-
IgnoreVolumeMountPoint] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Facilitates dismounting the list of SMB shares that are mounted from the specified Snapshot copy as a different set of shares. Facilitates dismounting the list of LUNs mounted from the specified Snapshot copies as a different set of LUNs. You can use this cmdlet during backup verification operations. First, you can use Mount-SdSnapshot to mount database and log shares or LUNs from the Snapshot copy. Next, you perform verification operations. After the backup verification is completed, use this cmdlet to dismount the shares/LUNs. If multiple paths contain one or more invalid paths specified in the cmdlet, the command fails for all the paths in the input. Related cmdlets: Mount-SdSnapshot

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies a comma-separated list of SMB shares, disks, or LUN mount points you want to dismount. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByValue, ByPropertyName)	
DeleteParentClones		false	true (ByPropertyName)	
IgnoreVolumeMount Point		false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. For SMB shares, the default is your local machine. For LUNs, you must provide this parameter.	false	true (ByPropertyName)	

Examples

Example 1: Dismounting multiple shares that were mounted from a Snapshot copy

```
PS C:\> Dismount-SdSnapshot -Path
"\\SQLFileserver\DBShareSdClone607fb343_2b3c_41f6_8912_8762a1800290", "\\SQLFileserver\DBShareSdClone6bcf3df5_3384_4ba4_9b33_25bb9636a486"
```

This example syntax specifies how to dismount your Snapshot copies mounted on the specified shares.

Example 2: Dismounting a Snapshot of a LUN

```
PS C:\> Dismount-SdSnapshot -Path I: -Host Host1.DMN.COM
```

This example syntax specifies how to dismount your Snapshot copy mounted on the specified drive.

Example 3: Dismounting multiple mount points

```
PS C:\> Dismount-SdSnapshot -Path
"C:\scmnpt\mpdisk0005\","C:\scmnpt\mpdisk0006\" -Host Host1.DMN.COM
```

This example syntax specifies how to dismount your Snapshot copies mounted on the specified mount points.

Get-SdAluaPaths

Lists all available ALUA-enabled disks and their state.

Syntax

```
Get-SdAluaPaths [-Paths] <String[]> [-Session] <String> [-Host] <String>
```

Detailed Description

Lists all available ALUA-enabled disks and their state.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Paths	Specifies the drive letter or mount point of the file system.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name of the host.	false	true (ByPropertyName)	

Examples

Example 1: Listing all ALUA enabled disks

```
PS C:\> Get-SdAluaPaths
```

This example syntax lists information about all ALUA enabled disks.

Get-SdDataStores

Syntax

```
Get-SdDataStores [-Shared] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Shared		false	false	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Get-SdFCPInitiator

Lists FCP initiators.

Syntax

```
Get-SdFCPInitiator [-Session] <String> [-Host] <String>
```

Detailed Description

Lists FCP initiators.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name of the computer or host on which the SnapCenter Plug-in for Microsoft Windows service you want to perform the operation runs. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Listing all FCP initiators

```
PS C:\> Get-SdFCPInitiator
```

This example syntax displays all your FCP initiators.

Get-SdIgroup

Gets information about available igroups.

Syntax

```
Get-SdIgroup [-Name] <String[]> [-Initiators] <String[]> [-LunPath]
<String> [-StorageSystem] <String> [-Session] <String> [-Host]
<String>
```

Detailed Description

Gets information about available igroups.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the igroups about which you want to retrieve information.	false	true (ByPropertyName)	
Initiators	Specifies any initiators included in the igroup.	false	true (ByPropertyName)	
LunPath	Specifies the LUN on your storage system.	false	true (ByPropertyName)	
StorageSystem	Specifies the storage system on which the igroup resides.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Retrieving igroup information

```
PS C:\> Get-SdIgroup -StorageSystem 172.17.168.13
```

This example syntax retrieves the igroup information for the specified storage system.

Get-SdIgroupWithUuid

Syntax

```
Get-SdIgroupWithUuid [-Name] <String[]> [-Initiators] <String[]> [-LunPath] <String> [-LunUuid] <String> [-StorageSystem] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name		false	true (ByPropertyName)	
Initiators		false	true (ByPropertyName)	
LunPath		false	true (ByPropertyName)	
LunUuid		false	true (ByPropertyName)	
StorageSystem		true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Get-SdInfo

Gets information about the SnapCenter Plug-in for Microsoft Windows instance that you are running.

Syntax

```
Get-SdInfo [-Session] <String> [-Host] <String> [-Details] <> [-Session] <String> [-Host] <String>
```

Detailed Description

You can use this cmdlet to retrieve the version number of the SnapCenter Plug-in for Microsoft Windows instance you are currently running. You can use the Details parameter to get additional information about Snapshot, discovery, virtualization, configuration, storage resolution, SMB shadow copy, SnapRemote, administration, and provisioning services, along with the interface name.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Session	Specifies the session ID from Open-SmConnection..	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
Details	Gets additional information about Snapshot copy, discovery, virtualization, configuration, storage resolution, SMB shadow copy, SnapRemote, administration, and provisioning services, along with the interface name.	false	true (ByPropertyName)	

Examples

Example 1: Getting the details about the SnapCenter Plug-in for Microsoft Windows instance

```
PS C:\> Get-SdInfo -Details
```

This example gets detailed information about the version and services of the SnapCenter Plug-in for Microsoft Windows instance you are running.

```
Get-SdInfo -Details
Version: 7.0.0.5779
Snapshot Service
InterfaceName: SDSnapshot_v1_1
Version: 7.0.0.5779
URLForInterface: net.tcp://localhost:808/SnapDrive/Snapshot
URLForWSDL:
Discovery Service
InterfaceName: SDDiscovery_v10
Version: 7.0.0.5779
URLForInterface: net.tcp://localhost:808/SnapDrive/Discovery
URLForWSDL:
```



```

Virtualization Service
InterfaceName:
SnapDrive.Nsf.Interfaces.Virtualization.IVirtualMachineManagement
Version: 7.0.0.5779
URLForInterface: net.tcp://localhost:808/SnapDrive/Virtualization
URLForWSDL:
Configuration Service
InterfaceName: SnapDrive.Nsf.Interfaces.SDConfiguraiton
Version: 7.0.0.5779
URLForInterface: net.tcp://localhost:808/SnapDrive/Configuration
URLForWSDL:
StorageResolution Service
InterfaceName: SnapDrive.Nsf.Interfaces.SDStorageResolution
Version: 7.0.0.5779
URLForInterface: net.tcp://localhost:808/SnapDrive/StorageResolution
URLForWSDL:
CIFS ShadowCopy Service
InterfaceName: SnapDrive.Nsf.Interfaces.SDCIFSShadowCopyManagement
Version: 7.0.0.5779
URLForInterface:
net.tcp://localhost:808/SnapDrive/CIFSShadowCopyManagement
URLForWSDL:
SnapRemote Service
InterfaceName: SDSnapRemote_v1_3
Version: 7.0.0.5779
URLForInterface: net.tcp://localhost:808/SnapDrive/SnapshotRemote
URLForWSDL:
Administration Service
InterfaceName: SDAdmin_v10
Version: 7.0.0.5779
URLForInterface: net.tcp://localhost:808/SnapDrive/SDAdminNext
URLForWSDL:
InterfaceName: SDAdmin
Version: 7.0.0.5779
URLForInterface: net.tcp://localhost:808/SnapDrive/SDAdminInfo
URLForWSDL:
Provisioning Service
InterfaceName: SnapDrive.Nsf.Interfaces.SDProvisioningManagement
Version: 7.0.0.5779
URLForInterface: net.tcp://localhost:808/SnapDrive/ProvisioningManagement
URLForWSDL:

```

Get-Sdlscsilnitiator

Enumerates information about iSCSI sessions and initiators.

Syntax

```
Get-SdIscsiInitiator [-Session] <String> [-Host] <String>
```

Detailed Description

Enumerates information about iSCSI sessions and initiators.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name of the computer or host on which the SnapDrive service you want to perform the operation runs. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Listing all iSCSI sessions and initiators

```
PS C:\> Get-SdIscsiInitiator
```

In this example syntax, you list all iSCSI sessions and associated initiators.

Get-SdIscsiTarget

Enumerates iSCSI targets on a storage system.

Syntax

```
Get-SdIscsiTarget [-StorageSystemName] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Enumerates iSCSI targets on a storage system.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystemName	Specifies the name of the storage system for which you want to list iSCSI targets.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name of the computer or host on which the SanpCenter Plug-in for Microsoft Windows service you want to perform the operation runs. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Listing all iSCSI targets on a storage system

```
PS C:\> Get-SdIscsiTarget -StorageSystemName vs0
```

In this sample syntax, you get information about iSCSI targets on a specified storage system.

Example 2: Listing all iSCSI targets on a storage system

```
PS C:\> Get-SdIscsiTarget -StorageSystem 172.17.11.122
```

In this sample syntax, you get information about iSCSI targets on a specified storage system.

Get-SdLun

Gets information about the LUNs created on your storage system.

Syntax

```
Get-SdLun [-StorageSystem] <String> [-LunPath] <String> [-Session] <String> [-Host] <String> [-SerialNumber] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Gets information about the LUNs created on your storage system.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the name of the storage system on which your LUN is located.	true	true (ByPropertyName)	
LunPath	Specifies the path of the LUN on your storage system.	false	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
SerialNumber		true	true (ByPropertyName)	

Examples

Get-SdLunMap

Gets information about all the mapped LUNs and the igroups to which they are mapped.

Syntax

```
Get-SdLunMap [-StorageSystem] <String> [-LunPath] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Gets information about all the mapped LUNs and the igroups to which they are mapped.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the storage system on which the igroup, to which you mapped your LUNs, is located.	true	true (ByPropertyName)	
LunPath	Specifies the path of the LUN on your storage system.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Get-SdLunMapWithUuid

Syntax

```
Get-SdLunMapWithUuid [-StorageSystem] <String> [-LunPath] <String> [-LunUuid] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem		true	true (ByPropertyName)	
LunPath		false	true (ByPropertyName)	
LunUuid		false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Get-SdLunWithUuid

Syntax

```
Get-SdLunWithUuid [-StorageSystem] <String> [-LunPath] <String> [-LunUuid] <String> [-Session] <String> [-Host] <String> [-SerialNumber] <String> [-LunUuid] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem		true	true (ByPropertyName)	
LunPath		false	true (ByPropertyName)	
LunUuid		false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	
SerialNumber		true	true (ByPropertyName)	

Examples

Get-SdNfsExport

Syntax

```
Get-SdNfsExport [-DataPaths] <String[]> [-ExportPath] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
DataPaths		true	true (ByValue, ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ExportPath		true	true (ByValue, ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Get-SdPlugIn

Syntax

```
Get-SdPlugIn [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Get-SdPlugInResource

Syntax

```
Get-SdPlugInResource [-Files] <String[]> [-ComputerName] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Files		true	true (ByPropertyName)	
ComputerName		false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Get-SdPortSet

Gets information about available portsets.

Syntax

```
Get-SdPortSet [-PortSetName] <String> [-StorageSystem] <String> [-GetLunMappings] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Gets information about available portsets.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PortSetName	Specifies the name of the portset about which you want to get information.	false	true (ByPropertyName)	
StorageSystem	Specifies the name of the storage system on which your portset resides.	true	true (ByPropertyName)	
GetLunMappings	Indicates that you want to get information about the number of LUN mappings.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Get-SdSMBShadowCopyEmsMessage

Gets SMB shadow copy EMS messages from the event log, so that you can find backup failure details.

Syntax

```
Get-SdSMBShadowCopyEmsMessage [-Path] <Object> [-SearchPattern]  
<String> [-Session] <String> [-Host] <String>
```

Detailed Description

Gets shadow copy EMS messages that contain specified SMB shadow copy ID search criteria from the virtual storage server, so that you can view the SMB shadow copy failure details.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the SMB share path for shadow copy EMS messages. Enter one path only. If you enter more than one path value, the search is performed only on the first path. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByValue, ByPropertyName)	
SearchPattern	Specifies a regular expression search criteria, so that you can search for EMS messages pertaining to a specific backup failure event.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Getting shadow copy EMS messages for a specified ID

```
PS C:\> Get-SdSMBShadowCopyEmsMessage -Path \\10.53.41.218\root
-SearchPattern *9831ed56-ee2e-11e1-994b*
```

Gets shadow copy EMS messages that contains specified SMB shadow copy ID search criteria from the virtual storage server for the SMB shadow copy.

Gets shadow copy EMS messages that contains specified SMB shadow copy ID search criteria from the virtual storage server for the SMB shadow copy.

Example 2: Getting all SMB shadow copy EMS message on a virtual storage server

```
PS C:\> Get-SdSMBShadowCopyEmsMessage -Path \\172.17.165.40\root
-SearchPattern *
```

Gets all shadow copy EMS messages from the virtual storage server for the SMB shadow copy. The message you retrieve looks similar to example 1.

Get-SdSnapMirror

Gets the SnapMirror relationship status for storage system volumes you specify.

Syntax

```
Get-SdSnapMirror [-StorageSystem] <String> [-Volume] <String[]> [-
Session] <String> [-Host] <String>
```

Detailed Description

Gets the SnapMirror relationship status for storage system volumes you specify. If you do not specify any volumes, you retrieve SnapMirror relationships for all registered virtual storage servers. This cmdlet is supported in clustered Data ONTAP 8.2 and later. Related cmdlets: Invoke-SdSnapMirrorUpdate

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the primary storage system name or IP address containing the volumes for which you want to retrieve the SnapMirror relationship status.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Volume	Indicates a comma-separated list of storage system volumes for which you want to retrieve the SnapMirror relationship status.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Getting SnapMirror information for a storage system volume

```
PS C:\> Get-SdSnapMirror -StorageSystem 172.17.162.61 -Volume test_vol1 -Verbose
```

In this example syntax, you retrieve SnapMirror relationship status information for the volume test_vol1.

```
Get-SdSnapMirror -StorageSystem 172.17.162.61 -Volume test_vol1 -Verbose
SnapMirrorRelationshipType : data_protection
SnapMirrorPolicyName      : DPDefault
SnapMirrorRelationship    : vserver : test_vol1 ==> vserver : test_vol2
SnapMirrorState: snapmirrored
SnapMirrorStatus         : Idle
Lag: 0
LagSpecified            : False
BaseSnapshotName         : snapmirror.9a000021-fb71-11e1-8315-123478563412_2147484917.2013-07-19_124400
Message: Success.
```

Example 2: Getting SnapVault information for a storage system volume

```
PS C:\> Get-SdSnapMirror -StorageSystem 172.17.162.61 -Volume snapvault_source -Verbose
```

In this example syntax, you retrieve SnapVault relationship status information for the volume snapvault_source.

```
PS C:\Users\administrator.NEXTGEN> Get-SdSnapMirror -StorageSystem
172.17.162.61 -Volume snapvault_source -Verbose
SnapMirrorRelationshipType : vault
SnapMirrorPolicyName      : XDPDefault
SnapMirrorRelationship    : vserver : snapvault_source ==> vserver :
snapvault_dest
SnapMirrorState: snapmirrored
SnapMirrorStatus        : Idle
Lag: 0
LagSpecified           : False
BaseSnapshotName       : DATA
Message: Success.
```

Get-SdSnapMirrorPolicyRule

Gets the rules for managing Snapshot retention on the SnapVault secondary storage system.

Syntax

```
Get-SdSnapMirrorPolicyRule [-SourceStorageSystem] <String> [-
SourceStorageSystemVolume] <String> [-DestinationStorageSystem]
<String> [-DestinationStorageSystemVolume] <String> [-Session]
<String> [-Host] <String>
```

Detailed Description

Gets the rules for managing Snapshot retention on the SnapVault secondary storage system. Related cmdlets: Set-SdSnapMirrorPolicyRule, Remove-SdSnapMirrorPolicyRule

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SourceStorageSystem	Specifies the primary storage system name containing the source volumes of the SnapMirror relationship for which you want to retrieve the SnapMirror policy rules. IP addresses are not supported.	true	true (ByValue, ByPropertyName)	
SourceStorageSystemVolume	Specifies the source volume of the SnapMirror relationship for which you want to retrieve the SnapMirror policy rules.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
DestinationStorageSystem	Specifies the secondary storage system name containing the destination volumes of the SnapMirror relationship for which you want to retrieve the SnapMirror policy rules. IP addresses are not supported.	true	true (ByValue, ByPropertyName)	
DestinationStorageSystemVolume	Specifies the destination volume of the SnapMirror relationship for which you want to retrieve the SnapMirror policy rules.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Getting SnapMirror policy rule information from the policy for a SnapMirror relationship

```
PS C:\> Get-SdSnapMirrorPolicyRule -SourceStorageSystem vs1
-SourceStorageSystemVolume src_vol -DestinationStorageSystem vs2
-DestinationStorageSystemVolume dest_vol01 -verbose
```

Get the SnapMirror policy rules from the policy on the specified relationship.

```

SnapLabel    : daily
NumberOfSnapsToKeep: 10
PreserveSnaps :
PreserveSnapsSpecified : False
WarnThreshold : 0
SnapMirrorPolicy : snapvault_policy
SnapLabel    : weekly
NumberOfSnapsToKeep: 3
PreserveSnaps :
PreserveSnapsSpecified : False
WarnThreshold : 2
SnapMirrorPolicy : snapvault_policy
SnapLabel    : mothly
NumberOfSnapsToKeep: 4
PreserveSnaps :
PreserveSnapsSpecified : False
WarnThreshold : 3
SnapMirrorPolicy : snapvault_policy
The getting SnapMirror policy rules operation is successful.

```

Get-SdSnapshot

Lists the Snapshot copies for a specified set of volumes, logical disks, or SMB shares.

Syntax

```

Get-SdSnapshot [-Path] <Object[]> [-Snapshot] <String> [-VersionUuid]
<String> [-GetAllSnapshots] <> [-GetSecondarySnapshots] <> [-Session]
<String> [-Host] <String> [-StorageSystem] <String> [-VolumeName]
<String> [-Snapshot] <String> [-VersionUuid] <String> [-
GetAllSnapshots] <> [-GetSecondarySnapshots] <> [-Session] <String>
[-Host] <String>

```

Detailed Description

Lists the Snapshot copies for a specified set of volumes, logical disks, or SMB shares. You can also use this cmdlet to get information about a specific Snapshot copy. Related cmdlets: New-SdSnapshot Remove-SdSnapshot, Rename-SdSnapshot and Restore-SdSnapshot

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies avolumes, logical disks, or a comma-separated list of SMB shares. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByValue, ByPropertyName)	
Snapshot	Names the Snapshot copy about which you want information. If you do not use this parameter, all the Snapshot copies for the specified list of SMB shares, Windows volume, or Windows logical disk is returned.	false	true (ByPropertyName)	
VersionUuid	Indicates the version of the Snapshot copy about which you want information.	false	true (ByPropertyName)	
GetAllSnapshots	Indicates that you want to get information about both primary and secondary Snapshot copies. The default behavior is to enumerate only the primary Snapshot copies.	false	false	
GetSecondarySnapshots	Indicates that you want to retrieve information about secondary Snapshot copies only.	false	false	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
StorageSystem	Specifies the name of the storage system on which the Snapshot copies are located.	true	true (ByValue, ByPropertyName)	
VolumeName	Specifies the name of the volume you are querying.	true	true (ByValue, ByPropertyName)	

Examples

Example 1: Getting Snapshot copies for the specified list of SMB shares

```
PS C:\> Get-SdSnapshot -path "\\CifsServer\sqlshare",
 "\\CifsServer\sqlshare2"
```

This example syntax gets a list of Snapshot copies for the list of SMB shares you provide.

```
PS C:\Users\administrator.NEXTGEN> Get-SdSnapshot -Path
"\CIFS_SERV\snapvault_source", "\CIFS_SERV\test_voll" -Verbose
VERBOSE: Validating input paths.
AccessTime: 1373664154
AccessTimeDT : 7/12/2013 9:22:34 PM
Busy : False
ContainsLunClones :
CumulativePercentageOfTotalBlocks : 0
CumulativePercentageOfUsedBlocks : 1
CumulativeTotalBlocks : 1052076
CumulativeTotalKb : 1077325824
Dependency:
Is7ModeSnapshot : False
PercentageOfTotalBlocks : 0
PercentageOfUsedBlocks: 0
SnapshotInstanceUuid : eb674595-5901-453e-9e83-93322e1f6547
SnapshotOwnersList: {}
TotalBlocks : 296
TotalKb : 303104
SnapshotName : KII
AccessPoint : \CIFS_SERV\snapvault_source
StorageSystemName : vserver1
StorageVolumeName : snapvault_source
VersionUuid : eb674595-5901-453e-9e83-93322e1f6547
AccessTime: 1373664320
AccessTimeDT : 7/12/2013 9:25:20 PM
Busy : False
ContainsLunClones :
CumulativePercentageOfTotalBlocks : 0
CumulativePercentageOfUsedBlocks : 1
CumulativeTotalBlocks : 1051780
CumulativeTotalKb : 1077022720
Dependency:
Is7ModeSnapshot : False
PercentageOfTotalBlocks : 0
PercentageOfUsedBlocks: 0
SnapshotInstanceUuid : 12e542fe-f771-41ed-8ffe-f4a922337c3f
SnapshotOwnersList: {}
TotalBlocks : 116200
TotalKb : 118988800
SnapshotName : Koo
AccessPoint : \CIFS_SERV\snapvault_source
StorageSystemName : vserver1
StorageVolumeName : snapvault_source
```



```
VersionUuid      : 12e542fe-f771-41ed-8ffe-f4a922337c3f
AccessTime: 1373678045
AccessTimeDT    : 7/13/2013 1:14:05 AM
Busy           : False
ContainsLunClones :
CumulativePercentageOfTotalBlocks : 0
CumulativePercentageOfUsedBlocks  : 1
CumulativeTotalBlocks : 935580
CumulativeTotalKb    : 958033920
Dependency:
Is7ModeSnapshot    : False
PercentageOfTotalBlocks : 0
PercentageOfUsedBlocks: 1
SnapshotInstanceUuid : fca29895-f5cf-4737-a1df-e3915ff3e551
SnapshotOwnersList: {}
TotalBlocks       : 935580
TotalKb           : 958033920
SnapshotName      : JI
AccessPoint       : \\CIFS_SERV\snapvault_source
StorageSystemName : vserver1
StorageVolumeName : snapvault_source
VersionUuid      : fca29895-f5cf-4737-a1df-e3915ff3e551
AccessTime: 1374096530
AccessTimeDT    : 7/17/2013 9:28:50 PM
Busy           : False
ContainsLunClones :
CumulativePercentageOfTotalBlocks : 0
CumulativePercentageOfUsedBlocks  : 0
CumulativeTotalBlocks : 9196
CumulativeTotalKb    : 9416704
Dependency:
Is7ModeSnapshot    : False
PercentageOfTotalBlocks : 0
PercentageOfUsedBlocks: 0
SnapshotInstanceUuid : 22e13abf-89bf-442e-9a0a-832dc1d0a534
SnapshotOwnersList: {}
TotalBlocks       : 4180
TotalKb           : 4280320
SnapshotName      : new_SP1
AccessPoint       : \\CIFS_SERV\test_vol1
StorageSystemName : vserver1
StorageVolumeName : test_vol1
VersionUuid      : 22e13abf-89bf-442e-9a0a-832dc1d0a534
AccessTime: 1374263040
AccessTimeDT    : 7/19/2013 7:44:00 PM
Busy           : False
```

```

ContainsLunClones :
CumulativePercentageOfTotalBlocks : 0
CumulativePercentageOfUsedBlocks : 0
CumulativeTotalBlocks : 5016
CumulativeTotalKb : 5136384
Dependency: snapmirror
Is7ModeSnapshot : False
PercentageOfTotalBlocks : 0
PercentageOfUsedBlocks: 0
SnapshotInstanceUuid : 49b7b1cf-9fa2-4737-b3b8-df294bb570ea
SnapshotOwnersList: {}
TotalBlocks : 4168
TotalKb : 4268032
SnapshotName : snapmirror.9a000021-fb71-11e1-8315-
123478563412_2147484917.2013-07-19_124400
AccessPoint : \\CIFS_SERV\test_vol1
StorageSystemName : vserver1
StorageVolumeName : test_vol1
VersionUuid : 49b7b1cf-9fa2-4737-b3b8-df294bb570ea
AccessTime: 1374517978
AccessTimeDT : 7/22/2013 6:32:58 PM
Busy : False
ContainsLunClones :
CumulativePercentageOfTotalBlocks : 0
CumulativePercentageOfUsedBlocks : 0
CumulativeTotalBlocks : 848
CumulativeTotalKb : 868352
Dependency:
Is7ModeSnapshot : False
PercentageOfTotalBlocks : 0
PercentageOfUsedBlocks: 0
SnapshotInstanceUuid : 318d16e2-df58-495c-87ee-cd6a1d054447
SnapshotOwnersList: {}
TotalBlocks : 848
TotalKb : 868352
SnapshotName : local
AccessPoint : \\CIFS_SERV\test_vol1
StorageSystemName : vserver1
StorageVolumeName : test_vol1
VersionUuid : 318d16e2-df58-495c-87ee-cd6a1d054447

```

Example 2: Getting information for the Snapshot copy "test"

```
PS C:\> Get-SdSnapshot -path "\\SQLCifsServer\sqlshare" -snapshot "test"
```

This example syntax gets information for Snapshot copy "test" on the SMB share \\SQLCifsServer\sqlshare.

Example 3: Getting the latest Snapshot backup of the specified SMB share

```
PS C:\> Get-SdSnapshot -path "\\SQLCifsServer\sqlshare" | sort-object  
AccessTimeDT -ascending | select-object -last 1
```

This example syntax gets the latest Snapshot backup of the SMB share \\SQLCifsServer\sqlshare.

Example 4: Getting secondary Snapshot copies for the specified list of SMB shares

```
PS C:\> Get-SdSnapshot -path "\\SQLCifsServer\sqlshare",  
"\\SQLCifsServer\sqlshare2" -GetSecondarySnapshots
```

This example syntax gets a list of secondary Snapshot copies for list of SMB shares that you specify.

Example 5: Getting information for specific Snapshot version for specified SMB share

```
PS C:\> Get-SdSnapshot -path "\\SQLCifsServer\sqlshare"  
-SnapshotVersionUuid "d9bda43e-1e00-4fa9-9c7e-72d8dc5ca0b"
```

This example syntax gets the information for Snapshot copy version "d9bda43e-1e00-4fa9-9c7e-72d8dc5ca0b" on the SMB share \\SQLCifsServer\sqlshare.

Example 6: Getting Snapshot copies for a specified LUN

```
PS C:\> Get-SdSnapshot -path D:
```

This example syntax gets the latest Snapshot copies from the specified disk.

Get-SdStorage

Gets storage system information for Windows disks or SMB shares.

Syntax

```
Get-SdStorage [-StorageSystem] <String[]> [-ComputerName] <String> [-  
ExcludeStorageFootprint] <> [-ExcludeSMB] <> [-ExcludeSAN] <> [-  
GetMirrorInfo] <> [-GetUnmanagedDisks] <> [-CloneLevel] <> [-  
Session] <String> [-Host] <String> [-Path] <Object[]> [-  
ComputerName] <String> [-ExcludeStorageFootprint] <> [-ExcludeSMB] <>  
[-ExcludeSAN] <> [-GetUnmanagedDisks] <> [-CloneLevel] <> [-Session]  
<String> [-Host] <String>
```

Detailed Description

Gets storage system information for Windows disks or SMB shares. You must enable the CSV feature in Windows Server 2008 R2 SP1 if you want to use that feature.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the storage system name or IP address from which you want to get active storage, such as SMB shares. When you use this parameter with ExcludeSMB, this parameter is ignored.	false	true (ByPropertyName)	
ComputerName	Indicates the name of the host from which you want all the LUNs to be returned.	false	true (ByPropertyName)	
ExcludeStorageFoot print	Restricts the storage system path results to the host resource attributes only, and excludes the storage footprint. This parameter is ignored when you specify it with Path.	false	true (ByPropertyName)	
ExcludeSMB	Indicates that you do not want to view information about SMB shares.	false	true (ByPropertyName)	
ExcludeSAN	Indicates that you do not want to view information about LUNs.	false	true (ByPropertyName)	
GetMirrorInfo	Indicates that you want to view volume relationship and state information for the volumes on the source storage resources to which you have provided a path.	false	true (ByPropertyName)	
GetUnmanagedDisk s	Indicates that you want to view information about available unmanaged disks. If a disk is mapped to a LUN on an unregistered storage system, it displays as an unmanaged disk, whether it is or not. If you set the parameter ExcludeSAN, GetUnmanagedDisks is ignored.	false	true (ByPropertyName)	
CloneLevel	If the storage system information is for a clone, specifies the clone level.	false	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
Path	Specifies a list of Windows volumes or SMB share. You cannot mix Windows volumes with SMB shares in the same input path.	false	true (ByPropertyName)	

Examples

Example 1: Getting the storage system for a SMB share

```
PS C:\> Get-SdStorage -Path "\\SQLCifsServer\SalesDBShare"
```

This example syntax gets the storage system path for the SMB share \\SQLCifsServer\SalesDBShare.

Example 2: Getting storage system paths for multiple SMB shares

```
PS C:\> Get-SdStorage -Path
 "\\SQLCifsServer\SalesDBShare", "\\SQLCifsServer2\MarketDBShare"
```

This example syntax gets the storage system path for the SMB Shares \\SQLCifsServer\SalesDBShare and \\SQLCifsServer2\MarketDBShare.

Example 3: Getting detailed information about host and storage system resources

```
PS C:\> Get-SdStorage -Path \\SQLCIFSServer\SalesDBShare |
 %{$_.HostResource,$_.StorageSystemResource}
```

This example syntax gets extended information about the host resource and the storage system resource.

Example 4: Getting all the SMB shares on the specified storage systems

```
PS C:\> Get-SdStorage -StorageSystem "10.225.13.110","172.17.175.75"
-ExcludeSAN
```

This example syntax gets all the SMB shares on storage systems 10.225.13.110 and 172.17.175.75.

Example 5: Getting all Windows disks and SMB shares from registered storage systems

```
PS C:\> Get-SdStorage
```

This example syntax gets all the Windows disks and SMB shares from all registered storage systems.

Example 6: Getting the Windows disks and SMB shares with the host resources details only on the specified storage system

```
PS C:\> Get-SdStorage -StorageSystem 10.225.13.110  
-ExcludeStorageFootprint
```

This example syntax gets information about the host resources for Windows disks and SMB shares on storage system 10.225.13.110. You can use this parameter to help your application achieve better performance if you need information about Windows disks and SMB shares but not their storage footprint.

Example 7: Getting the all the LUNs but not SMB shares

```
PS C:\> Get-SdStorage -ExcludeSMB
```

This example syntax retrieves information about all the LUNs on the local host.

Example 8: Getting volume mirror information

```
PS C:\> (Get-SdStorage -StorageSystem 172.17.165.31  
-GetMirrorInfo).StorageSystemResource.Volume
```

This example syntax uses the -GetMirrorInfo parameter to get volume state and relationship information from the source storage system resource.

Get-SdStorageConnectionSetting

Gets the storage system connection, transport, and credential settings from the configuration repository.

Syntax

```
Get-SdStorageConnectionSetting [-Name] <String[]> [-Session] <String>  
[-Host] <String> [-DefaultSetting] <> [-Session] <String> [-Host]  
<String>
```

Detailed Description

This cmdlet reads the storage system, transport, and credential settings from the configuration repository to make a connection to the storage system. These settings include the storage server name (virtual storage server name or IP,) port, transport type, user login, and password. If you do not include parameters, this cmdlet reads all the storage connection settings from the repository. Related cmdlets: Set-SdStorageConnectionSetting and Remove-SdStorageConnectionSetting

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name or IP address of the storage system (storage controller or virtual storage server) for which you want to retrieve connection settings.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
DefaultSetting	Indicates that you want to view the default storage system connection settings. When you do not specify explicit storage system connection values, you use the default settings.	true	false	

Examples

Example 1: Getting a named connection setting

```
PS C:\> Get-SdStorageConnectionSetting -StorageSystem 'vmStorageServer'
```

This example syntax gets the storage system connection settings for the specified storage system "vmStorageServer".

Storage System Name/IP : vmStorageServer
User : vsadmin
Port : 80
Protocol : Http

Example 2: Getting all connection settings

```
PS C:\> Get-SdStorageConnectionSetting
```

This example syntax retrieves all the storage connection settings.

```
Storage System Name/IP : vmStorageServer
User      : vsadmin
Port     : 80
Protocol  : Http
Storage System Name/IP : vmStorageServer2
User      : vsadmin2
Port     : 443
Protocol  : Https
```

Example 3: Getting the default connection setting

```
PS C:\> Get-SdStorageConnectionSetting -DefaultSetting
```

This example syntax retrieves the default connection settings.

```
User : vsadmin
Port : 80
Protocol : Http
```

Get-SdVM

Lists Hyper-V VMs and their attributes.

Syntax

```
Get-SdVM [-NoStorage] <> [-GetHyperVSnapshot] <> [-Name] <String[]>
[-ComputerName] <String[]> [-Session] <String> [-Host] <String>
```

Detailed Description

Lists Hyper-V VMs and their attributes. Related cmdlets: Get-SdStorage

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
NoStorage	Specifies that you do not want to get the Data ONTAP storage footprint of a share or mount.	false	false	

Name	Description	Required ?	Pipeline Input	Default Value
GetHyperVSnapshot	Specifies that you want to get the Snapshot VHDs, the GUIDs associated with them, and the parent VHD.	false	false	
Name	Specifies the name or GUID of the VM you want to get.	false	true (ByPropertyName)	
ComputerName	Indicates the name of the Hyper-V server on which you want the VMs to be returned.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Listing all HyperV VMs

```
PS C:\> Get-SdVM
```

This example syntax lists all Hyper-V VMs and their attributes.

```
ComputerName Name Guid State Clustered VirtualDisks
```

```
-----
clab-a8-7 vm1 94734822-f2a2-4ddb-9794-8139bc1efb0b Running false {\vs1\share1\vm1\vm1.vhd}
clab-a8-8 vm2 d68f7d2a-31cd-437d-a435-e8757e730a01 Off true {\vs2\share1\vm2\vm2.vhd}
```

Example 2: Listing all HyperV VMs on a specific HyperV server

```
PS C:\> Get-SdVM -ComputerName "clab-a8-8"
```

This examples syntax lists all Hyper-V virtual machines on Hyper-V server clab-a8-8.

```
ComputerName Name Guid State Clustered VirtualDisks
```

```
-----
clab-a8-8 vm2 d68f7d2a-31cd-437d-a435-e8757e730a01 Off true {\vs2\share1\vm2\vm2.vhd}
clab-a8-8 vm3 d68f7d2a-31cd-437d-a435-e8757e730a02 Off false {\vs2\share2\vm3\vm3.vhd}
```

Example 3: Getting the attributes for a VM

```
PS C:\> Get-SdVM -Name vm1 | fl
```

This example syntax gets the attributes of VM vm1.

```
Owner      : clab-a8-7
Guid: 94734822-f2a2-4ddb-9794-8139bc1efb0b
State      : Running
StorageType : NAS
SnapshotAttributes :
SnapDrive.Nsf.Interfaces.Virtualization.SnapshotAttributes
ConfigurationAttributes :
SnapDrive.Nsf.Interfaces.Virtualization.VMConfigurationAttributes
HighlyAvailable : False
HAAttributes:
SnapDrive.Nsf.Interfaces.Virtualization.HighAvailabilityAttributes
StorageFootPrints : {HostResource : \\vs1_cifs\vol2_share
StorageSystemResource : vs1:/vol/vol2/}
VirtualDisks: {\\vs1\share1\vm1\vm1.vhd}
Type: SDHyperv
Name: vm1
```

Example 4: Showing the virtual disks on a VM

```
PS C:\> (Get-SdVM sqltest-vm-01).VirtualDisks
```

This example syntax lists the virtual disks associated with VM sqltest-vm-01.

```
Name      : sqltest-vm-01.vhdx
Type       : SDHyperv
VirtualDisk Location   : \\10.53.14.233\r2
VirtualDisk FullPath   : \\10.53.14.233\r2\sqltest-vm-01\Virtual Hard
Disks\sqltest-vm-01.vhdx
StorageSystemResource  : sqltest-vsim1-bsd.sim.Company.com:/vol/vol2/
StorageSystemResource Type : SDStorageDir
HostResource           : \\10.53.14.233\r2
HostResource Type      : SDSMBShare
BootDisk               : True
```

Example 5: Showing all virtual disks and Snapshot copies on a VM

```
PS C:\> (Get-SdVm -GetHyperVSnapshot vm_clus_smb4).VirtualDisks
```

This example syntax lists all the virtual disks including the Hyper-V Snapshot copies associated with VM vm_clus_smb4.

```

Name      : vm_clus_smb4.vhdx
Type      : SDHyperv
VirtualDisk Location    : \\172.17.175.82\vol3_share
VirtualDisk FullPath    : \\172.17.175.82\vol3_share\vm_clus_smb4\Virtual
Hard Disks\vm_clus_smb4.vhdx
StorageSystemResource   : vs2:/vol/vol3/
StorageSystemResource Type : SDStorageDir
HostResource           : \\172.17.175.82\vol3_share
HostResource Type      : SDSMBShare
BootDisk               : True
Name      : vm_clus_smb4_0F10EBD9-01F5-4546-9A99-49CF2EEAA755.avhdx
Type      : SDHyperv
VirtualDisk Location    : \\172.17.175.82\vol3_share
VirtualDisk FullPath    : \\172.17.175.82\vol3_share\vm_clus_smb4\Virtual
Hard Disks\vm_clus_smb4_0F10EBD9-01F5-4546-9A99-49CF2EEAA755.avhdx
StorageSystemResource   : vs2:/vol/vol3/
StorageSystemResource Type : SDStorageDir
HostResource           : \\172.17.175.82\vol3_share
HostResource Type      : SDSMBShare
BootDisk               : True

```

Get-SdVolumeCloneSplit

Gets information about your clone volume splitting operation status.

Syntax

```

Get-SdVolumeCloneSplit [-JobId] <String[]> [-StorageSystem] <String>
[-Session] <String> [-Host] <String> [-Path] <Object[]> [-Session]
<String> [-Host] <String>

```

Detailed Description

Gets information about your clone volume splitting operation status.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
JobId		true	true (ByPropertyName)	
StorageSystem		true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
Path	Specifies the clone splitting operation about which you want to retrieve status information.	true	true (ByPropertyName)	

Examples

Get-SdVolumeCloneSplitEstimate

Estimates the amount of space you available, before you begin a clone splitting operation.

Syntax

```
Get-SdVolumeCloneSplitEstimate [-Path] <Object[]> [-Session] <String>
[-Host] <String>
```

Detailed Description

Estimates the amount of space you available, before you begin a clone splitting operation.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the path to the volume about which you want to retrieve a space estimate, before you begin a clone splitting operation.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Get-SdVsphereSetting

Syntax

```
Get-SdVsphereSetting [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Invoke-SdEmsAutosupportLog

Facilitates logging Event Management System (EMS) AutoSupport messages.

Syntax

```
Invoke-SdEmsAutosupportLog [-Path] <Object> [-EventId] <Int32> [-EventSource] <String> [-AppVersion] <String> [-Category] <String> [-EventDescription] <String> [-LogLevel] <UInt32> [-GenerateAutosupport] <> [-Session] <String> [-Host] <String> [-StorageSystem] <String> [-EventId] <Int32> [-EventSource] <String> [-AppVersion] <String> [-Category] <String> [-EventDescription] <String> [-LogLevel] <UInt32> [-GenerateAutosupport] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Facilitates logging Event Management System (EMS) AutoSupport messages. You can use this cmdlet to determine the underlying administration server, and to send messages to that server, for your specified SMB share or logical disk. Your application can use this cmdlet to log events with different severity levels in EMS and to send corresponding AutoSupport messages about backup, restore, and similar operations, errors, or failures. Related cmdlets: Get-SdSMBShadowCopyEmsMessage

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the ID for the SMB share, logical disk to which you send the EMS AutoSupport message. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByValue, ByPropertyName)	
EventId	Provides the event ID. This is a user-defined event ID, with a range from 0 to 2 ³² -2.	true	true (ByPropertyName)	
EventSource	Indicates the application invoking the cmdlet.	true	true (ByPropertyName)	
AppVersion	Provides the version of the application invoking the cmdlet.	true	true (ByPropertyName)	
Category	Specifies an application-defined event category.	true	true (ByPropertyName)	
EventDescription	Describes the event you want to log. The event description is an application-defined message.	true	true (ByPropertyName)	
LogLevel	Indicates the EMS message severity. Accepted values are: 0 for "emergency"; 1 for "alert"; 2 for "critical"; 3 for "error"; 4 for "warning"; 5 for "notice"; 6 for "info"; 7 for "debug"	true	true (ByPropertyName)	
GenerateAutosupport	Specifies that you want to generate an AutoSupport message.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
StorageSystem	Names the storage system for resources to which you send the EMS AutoSupport message.	true	true (ByPropertyName)	

Examples

Example 1: Logging a test EMS AutoSupport message

```
PS C:\> Invoke-SdEmsAutosupportLog -Path \\172.17.165.40\root -EventId 111 -EventSource "SDW" -AppVersion "1.0" -Category "test" -EventDescription "This is testing message from NextGenSDW." -LogLevel 6
```

In this example syntax, you send a test EMS log message to the virtual storage server to which the SMB share belongs. The cluster server display the following message:

```
TimeNode Severity Event
-----
8/14/2012 11:47:54 mvaqa-3270-1-01 INFORMATIONAL app.log.info: SNAPMGR-06: SDW 7.0: (111) test: This is testing message from SnapDrive.
```

Example 2: Logging and generating a test EMS AutoSupport message

```
PS C:\> Invoke-SdEmsAutosupportLog -Path \\172.17.165.40\root -EventId 111 -EventSource "SDW" -AppVersion "1.0" -Category "test" -EventDescription "This is testing message from SnapDrive." -LogLevel 6 -GenerateAutosupport
```

In this example syntax, you log a test message in EMS and send an AutoSupport message to the virtual storage server to which the SMB share belongs.

Example 3: Logging a test EMS AutoSupport message in a clustered environment

```
PS C:\> Invoke-SdEmsAutosupportLog -Path E: -EventId 111 -EventSource "SDW" -AppVersion "1.0" -Category "test" -EventDescription "This is testing message from SnapDrive." -LogLevel 6
```

In this example syntax, you send a test EMS log message to the virtual storage server to which the SMB share belongs.

```
The cluster server displays the following message:
TimeNode Severity Event
-----
8/14/2012 11:47:54 mvaqa-3270-1-01 INFORMATIONAL app.log.info: SNAPMGR-06: SDW 7.0: (111) test: This is testing message from SnapDrive.
```

Example 4: Logging a test EMS AutoSupport message using a storage system

```
PS C:\> Invoke-SdEmsAutosupportLog -StorageSystem 172.17.165.39 -EventId 111 -EventSource "SDW" -AppVersion "1.0" -Category "test" -EventDescription "This is testing message from SnapDrive." -LogLevel 6
```

In this example syntax, you send a test EMS log message to the virtual storage server used as the storage system.

The cluster server displays the following message:

```
TimeNode Severity Event
```

```
-----
```

```
----- 11/15/2012 16:13:43 mvaqa-3270-1-02
```

```
INFORMATIONAL app.log.info: CLAB-A13-10: SDW 7.0: (111) test: This is testing message from SnapDrive.
```

Invoke-SdHostVolumeSpaceReclaim

Initiates space reclamation on your host volume.

Syntax

```
Invoke-SdHostVolumeSpaceReclaim [-Path] <String> [-Session] <String> [-Host] <String> [-UnmapSize] <String> [-VdsId] <Guid> [-Session] <String> [-Host] <String> [-UnmapSize] <String>
```

Detailed Description

Initiates space reclamation on your host volume.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	The mount point (i.e. G:\) or path to any file on the volume to process.	true	true (ByValue, ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
UnmapSize	Specifies the size of the blocks you want to reclaim. The size should be greater than 0 and less than 2147483648 bytes.	false	false	
VdsId	Specifies your virtual disk service ID.	true	true (ByValue, ByPropertyName)	

Examples

Example 1: Reclaiming space

```
PS C:\> Invoke-SdHostVolumeSpaceReclaim -Path E:
```

This example syntax reclaims space no longer being used by the host operating system.

Invoke-SdSnapMirrorUpdate

Facilitates updates to mirror and vault relationships, in the context of Windows disks, SMB shares, or clustered Data ONTAP storage system volumes.

Syntax

```
Invoke-SdSnapMirrorUpdate [-Path] <Object> [-MaxTransferRate] <Int64>
[-Snapshot] <String> [-Session] <String> [-Host] <String> [-
SourceStorageSystem] <String> [-SourceVolumeName] <String> [-
DestinationStorageSystemName] <String> [-DestinationStorageVolumeName]
<String> [-MaxTransferRate] <Int64> [-Snapshot] <String> [-Session]
<String> [-Host] <String>
```

Detailed Description

Facilitates updates to mirror and vault relationships, in the context of Windows disks, SMB shares, or clustered Data ONTAP storage system volumes. For the specified resources, you can determine the underlying storage layout and issue SnapMirror updates on the corresponding storage volumes, provided that the SnapMirror relationship is already created and initialized. SnapMirror updates and returns are executed immediately. When you are updating a SnapMirror relationship, you can specify a share, storage system volume, or Windows disk. When you are updating a SnapVault relationship, you can specify a share or storage system volume. Related cmdlets: Restore-SdSnapshot and New-SdSnapshot

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Provides a volume, logical disk, SMB share for which you want SnapMirror updates. You cannot mix a logical disk or mount point with SMB shares in the same input path. When you are updating a SnapMirror relationship, you can specify a share, storage system volume, or Windows disk. When you are updating a SnapVault relationship, you can specify a share or storage system volume.	true	true (ByValue, ByPropertyName)	
MaxTransferRate	Specifies the maximum transfer rate, in bytes per second.	false	true (ByPropertyName)	
Snapshot	Specifies the Snapshot copy you want to transfer. This cmdlet is processed only for vault relationships; in the case of SnapMirror relationships, this parameter is ignored if specified.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	local machine
SourceStorageSystem	Specifies the storage system from which you want to update your SnapMirror relationships.	true	true (ByPropertyName)	
SourceVolumeName	Specifies the volume from which you want to update your SnapMirror relationships.	true	true (ByPropertyName)	
DestinationStorageSystemName	Specifies the storage system on which you want to update your SnapMirror relationships. Must be used in conjunction with DestinationStorageVolumeName. If you do not specify this parameter, all storage system volumes associated with your source storage system and volume are updated.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
DestinationStorageVolumeName	Specifies the volume on which you want to update your SnapMirror relationships. Must be used in conjunction with DestinationStorageSystemName. If you do not specify this parameter, all storage system volumes associated with your source storage system and volume are updated.	false	true (ByPropertyName)	

Examples

Example 1: Updating SnapMirror for a single share

```
PS C:\> Invoke-SdSnapMirrorUpdate -path "\\fileserver\sqlshare"
```

In this example syntax, you determine the underlying storage footprint for \\fileserver\sqlshare, and initiate a SnapMirror update on the underlying volume, provided that the SnapMirror relationship is created and initialized.

```
PS C:\Users\administrator.NEXTGEN> Invoke-SdSnapMirrorUpdate -Path
\\CIFS_SERV\snapvault_source -Verbose
VERBOSE: Validating input paths.
VERBOSE: SMB Share : \\CIFS_SERV\snapvault_source
VERBOSE: Updating SnapMirror.
SnapMirrorRelationshipType :
SnapMirrorPolicyName      :
SnapMirrorRelationship    : vserver : snapvault_source ==> vserver :
snapvault_dest
SnapMirrorState: snapmirrored
SnapMirrorStatus        : Transferring
Lag: 0
LagSpecified           : False
BaseSnapshotName        : local
Message:
VERBOSE: Operation successful.
```

Example 2: Updating your vault for a single share

```
PS C:\> Invoke-SdSnapMirrorUpdate -path "\\fileserver\sqlshare" -snapshot
"weeklybackup"
```

In this example syntax, you determine the underlying storage footprint for \\fileserver\sqlshare, and initiate a

SnapVault update on the underlying volume.

```
PS C:\Users\administrator.NEXTGEN> Invoke-SdSnapMirrorUpdate -Path
\\CIFS_SERV\snapvault_source -Snapshot local -Verbose
VERBOSE: Validating input paths.
VERBOSE: SMB Share : \\CIFS_SERV\snapvault_source
VERBOSE: Updating SnapMirror.
SnapMirrorRelationshipType :
SnapMirrorPolicyName      :
SnapMirrorRelationship    : vserver1 : snapvault_source ==> vserver1 :
snapvault_dest
SnapMirrorState: snapmirrored
SnapMirrorStatus        : Transferring
Lag: 0
LagSpecified           : False
BaseSnapshotName        : DATA
Message:
VERBOSE: Operation successful.
```

Example 3: Updating SnapMirror for a disk

```
PS C:\> Invoke-SdSnapMirrorUpdate -Path E:
```

In this example syntax, you determine the underlying storage footprint for disk drive E:, and initiate a SnapMirror update on the underlying volume, provided that the SnapMirror relationship is created and initialized.

Example 4: Updating all SnapMirror destination storage system volumes

```
PS C:\> Invoke-SdSnapMirrorUpdate -SourceStorageSystem
sdw_jenkins_vserver -SourceVolumeName VOLUME01 -Verbose
```

In this example syntax, you update all destination storage system volumes associated with the source storage system and volume.

```

VERBOSE: Updating Snapmirror..
SnapMirrorRelationshipType :
SnapMirrorPolicyName      :
SnapMirrorRelationship    : sdw_jenkins_vserver : VOLUME01 ==>
sdw_jenkins_vserver      : vserver01
SnapMirrorState: snapmirrored
SnapMirrorStatus        : Transferring
Lag: 0
LagSpecified           : False
BaseSnapshotName       : snapmirror.e0f01251-4d32-11dc-a3b0-
123478563412_2147485514.2013-07-17_143103
Message:
SnapMirrorRelationshipType :
SnapMirrorPolicyName      :
SnapMirrorRelationship    : sdw_jenkins_vserver : VOLUME01 ==>
sdw_jenkins_vserver      : VOLUME01_Sec
SnapMirrorState: snapmirrored
SnapMirrorStatus        : Transferring
Lag: 0
LagSpecified           : False
BaseSnapshotName       : TEST_TEST
Message:
VERBOSE: Operation Successful.

```

Example 5: Updating specified SnapMirror destination storage system volumes

```

PS C:\> Invoke-SdSnapMirrorUpdate -SourceStorageSystem
sdw_jenkins_vserver -SourceVolumeName VOLUME01
-DestinationStorageSystemName sdw_jenkins_vserver
-DestinationStorageVolumeName VOLUME01_Sec -Verbose

```

In this example syntax, you update specific destination storage system volumes associated with the source storage system and volume.

```
VERBOSE: Updating Snapmirror..  
SnapMirrorRelationshipType :  
SnapMirrorPolicyName      :  
SnapMirrorRelationship    : sdw_jenkins_vserver : VOLUME01 ==>  
sdw_jenkins_vserver      : VOLUME01_Sec  
SnapMirrorState: snapmirrored  
SnapMirrorStatus        : Transferring  
Lag: 0  
LagSpecified           : False  
BaseSnapshotName       : TEST_TEST  
Message:  
VERBOSE: Operation Successful.
```

Map-SdLUNS

Syntax

```
Map-SdLUNS [-LunPath] <String[]> [-Initiators] <String> [-  
IgroupProtocol] <IgroupProtocolEnum> [-IgroupOsType] <IgroupOSTypeEnum>  
[-RestApiURL] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
LunPath		true	true (ByValue, ByPropertyName)	
Initiators		true	true (ByPropertyName)	
IgroupProtocol		false	true (ByPropertyName)	
IgroupOsType		false	true (ByPropertyName)	
RestApiURL		true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Mount-SdClone

Enables cloning and mounting a source storage from the specified Snapshot copy.

Syntax

```
Mount-SdClone [-SourcePath] <String[]> [-Snapshot] <String> [-ResourceType] <ResourceType> [-Host] <String> [-Igroup] <String> [-Initiators] <String> [-IgroupProtocol] <IgroupProtocolEnum> [-IgroupOsType] <IgroupOsTypeEnum> [-CheckInitiatorSession] <> [-Session] <String>
```

Detailed Description

Enables cloning and mounting a source storage from the specified Snapshot copy. For a LUN, the cloned volume name is automatically appended with a unique identifier, while the LUN name remains the same. For example: If the original volume is PrimarySVM:/vol/SCE_VOL, the cloned volume name is PrimarySVM:/vol/SCE_VOL1201210041488133. Related cmdlets: Dismount-SdClone, Get-SmClone, Remove-SmClone, New-SmClone

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SourcePath	Specifies a path that you want to clone and mount from the Snapshot copy. For example, the path of a volume.	true	true (ByValue, ByPropertyName)	
Snapshot	Specifies the Snapshot copy that you want to use for cloning and mounting.	true	true (ByPropertyName)	
ResourceType	Specifies the type of the resource in the SourcePath parameter. The possible options are: "SDStorageVolume", "SDStorageLunPath", "SDStorageDir".	false	true (ByPropertyName)	
Host	Specifies the FQDN or IP address of the host on which you want to execute the operation.	false	true (ByPropertyName)	
Igroup		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Initiators		false	true (ByPropertyName)	
IgroupProtocol		false	true (ByPropertyName)	
IgroupOsType		false	true (ByPropertyName)	
CheckInitiatorSession		false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	

Examples

Example 1: Clone a Volume from a given snapshot

```
PS C:\> Mount-SdClone -SourcePath
Primary_SVM:/vol/Vol1_LM_Port_Issue_Test -Snapshot
r70105ec0a5v1_hnk2_com_L__ValidPath_Data_R70105EC0A5V1_05-24-
2021_12.46.42.3914
```

This example syntax specifies the storage volume path and clones the Snapshot copy onto newly cloned volume.

Source Clone

```
Primary_SVM:/vol/Vol1_LM_Port_Issue_Test
Primary_SVM:/vol/Vol1_LM_Port_Issue_Test0525210820263222
```

Example 2: Clone a volume from a given Snapshot copy with the ResourceType and host name specified

```
PS C:\> Mount-SdClone -SourcePath Primary_SVM:/vol/Vol1 -Snapshot
Host1_Policy1_12-01-2021_02.31.22.3854 -ResourceType SDStorageVolume
-Host Host1.DMN.COM -Verbose
```

This example syntax specifies the storage volume path and clones the Snapshot copy to a newly cloned volume with the ResourceType and host name.

VERBOSE: Operation successful.

Source Clone

```
Primary_SVM:/vol/Vol1 Primary_SVM:/vol/Vol11201210243583210
```


Mount-SdSnapshot

Facilitates mounting the list of SMB shares from the specified Snapshot copy as a different set of shares. Facilitates mounting one LUN at a time from the specified Snapshot copy as a different LUN.

Mounting secondary LUN is not supported, Check Example 9

Syntax

```
Mount-SdSnapshot [-Path] <Object[]> [-Snapshot] <String> [-  
StorageSystem] <String> [-VolumeName] <String> [-PrefixForVolumeClone]  
<String> [-MountPath] <Object[]> [-SharedDisk] <> [-  
ClusteredSharedVolume] <> [-AutopickMountPoint] <> [-  
ValidateCloneDepth] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Facilitates mounting the list of SMB shares from the specified Snapshot copy as a different set of shares. Facilitates mounting one LUN at a time from the specified Snapshot copy as a different LUN. You can use this cmdlet to perform backup verification. Mount the database and log shares/LUN from the Snapshot copy and perform the verification operations. For SMB shares, the mounted share names are automatically appended with a unique identifier. For a LUN, the cloned volume name is automatically appended with a unique identifier, while the LUN name remains the same. For example: If the original share is \\SQLFileServer\DBShare, the mounted share name is \\SQLFileServer\DBShare-GUID. (\\SQLFileServer\DBShare-73111E50-E7C2-49B7-8A63-7279512CB09B) If the original LUN is PrimarySVM:/vol/SCE_VOL/lun1, the mounted LUN name is PrimarySVM:/vol/SCE_VOLGUID/lun1. (PrimarySVM:/vol/SCE_VOLSiClone2b77c074_1d9b_4929_9fac_d361bf342794/lun1) The ACLs on the mounted share are the same as the original share. To mount the shares or a LUN from a secondary Snapshot copy, you must specify the storage system and volume. Ensure that the aggregate of the volume that is the source of the FlexClone operation is assigned to the virtual storage server aggregates list. For the 'Path' parameter below, if file system path of the LUN is specified, it can be mounted on the same host as the source LUN. If the complete storage path of the LUN is specified, it can be mounted on the same host or on a different host. To mount the LUN on a different host, an igroup and an iSCSI session should be present for the host that is accessing the SVM, where the source LUN is present. Related cmdlets: Get-SdSnapshot, Remove-SdSnapshot, Rename-SdSnapshot, New-SdSnapshot, Dismount-SdSnapshot

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies a comma-separated list of shares you want to mount from the Snapshot copy. Only one LUN can be mounted at a time. For a LUN, this parameter specifies one value which is the file system path of the LUN in the host machine or the complete storage path of the LUN in the SVM. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByPropertyName)	
Snapshot	Indicates the Snapshot copy that you want to use for mounting the SMB shares/LUN. For SMB shares, you must use a Snapshot copy that is valid for all the shares in your list.	true	true (ByPropertyName)	
StorageSystem	Indicates the name of the storage system in which the Snapshot copy you want to mount is located.	false	true (ByPropertyName)	
VolumeName	Indicates the name of the storage system volume in which the Snapshot copy you want to mount is located.	false	true (ByPropertyName)	
PrefixForVolumeClone	You can use this optional parameter to set a short name for the share on which the Snapshot copy is mounted. For LUNs, use this parameter to prefix the cloned volume name. Use this parameter when you are working on a system with name length restrictions.	false	true (ByPropertyName)	
MountPath	Indicates the drive letter or mountpoint that you want to assign to the disk mounted from the Snapshot copy. For a LUN mount operation, this parameter takes only one destination value.	false	true (ByPropertyName)	
SharedDisk		false	true (ByPropertyName)	
ClusteredSharedVolume		false	true (ByPropertyName)	
AutopickMountPoint	Specifies that the mountpoint is assigned automatically.	false	true (ByPropertyName)	
ValidateCloneDepth		false	false	

Name	Description	Required ?	Pipeline Input	Default Value
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. For SMB shares, the default is your local machine. For a LUN, this parameter must be provided with the hostname.	false	true (ByPropertyName)	

Examples

Example 1: Mounting shares from a specified backup

```
PS C:\> Mount-SdSnapshot -Path
"\\SQLFileserver\DBShare", "\\SQLFileserver\LogShare" -snapshot
"weekly_backup"
```

This example syntax mounts your shares from "weekly_backup".

OriginalResource MountedResource

=====

```
\\SQLFileserver\DBShare \\SQLFileserver\DBShare-A470FF3A-5107-4B6A-B0C1-FB3D8744F14C
\\SQLFileserver\LogShare \\SQLFileserver\DBShare-E6980DF6-3E64-45BD-965A-7F7A9B02156A
```

Example 2: Mounting shares from piped Snapshot copies that start with "weekly" in the name.

```
PS C:\> Get-SdSnapshot \\SQLFileserver\DBShare -Snapshot weekly* | Mount-
SdSnapshot "\\SQLFileserver\dbshare", "\\SQLFileserver\logshare"
```

This example syntax mounts specified shares from Snapshot copies that start with "weekly." The shares you want to mount must be on the same volume.

OriginalResource MountedResource

=====

```
\\SQLFileserver\DBShare \\SQLFileserver\DBShare-A470FF3A-5107-4B6A-B0C1-FB3D8744F14C
\\SQLFileserver\LogShare \\SQLFileserver \DBShareE6980DF6-3E64-45BD-965A-7F7A9B02156A
```

Example 3: Mounting shares from the specified secondary Snapshot copy

```
PS C:\> Mount-SdSnapshot -Path
"\\SQLFileserver\DBShare", "\\SQLFileserver\LogShare" -snapshot
"weekly_snap" -storagesystem mirror_vserver -volume dbmirrorvolume
```

This example mounts the specified shares from the specified secondary Snapshot copy.

OriginalResource MountedResource

=====

\\SQLFileserver\DBShare \\DRSQLFileServer\DBShare-A470FF3A-5107-4B6A-B0C1-FB3D8744F14C
\\SQLFileserver\LogShare \\DRSQLFileServer\DBShare-E6980DF6-3E64-45BD-965A-7F7A9B02156A

Example 4: Mounting shares using a prefix

```
PS C:\> Mount-SdSnapshot -Path \\172.17.165.40\capital_vol_share  
-Snapshot Newtest -PrefixForVolumeClone capitalShare
```

This example syntax creates a short name for the share on which you mount the Snapshot copy.

Resource ConnectedResource

\\172.17.165.40\capital_vol_share \\JENKINS-CIFS\capitalShare030713155542929

Example 5: Mounting a LUN from a specified Snapshot with file system path.

```
PS C:\> Mount-SdSnapshot -Path L: -Snapshot  
Host1_DMN_COM_SLDB3_Host1_06-10-2020_02.51.43.9645 -MountPath I: -Host  
Host1.DMN.COM
```

This example syntax mounts the Snapshot copy specified for the LUN in L: onto I: on the host Host1.DMN.COM.

Resource ConnectedResource

L:\ I:\

Example 6: Mounting a LUN from a specified Snapshot with AutoMount option

```
PS C:\> Mount-SdSnapshot -Path L: -Snapshot  
Host1_DMN_COM_SLDB3_Host1_06-10-2020_02.51.43.9645 -AutopickMountPoint  
-Host Host1.DMN.COM
```

This example syntax mounts the Snapshot copy specified for the LUN in L: onto the automount location "C:\scmnpt\mpdisk0002\" on the host Host1.DMN.COM.

Resource ConnectedResource

L:\ C:\scmnpt\mpdisk0002\

Example 7: Mounting a LUN to a different host with LUN storage path

```
PS C:\> Mount-SdSnapshot -Path PrimarySVM:/vol/SCE_VOL/lun1 -Snapshot
Host1_DMN_COM_SLDB3_Host1_06-10-2020_02.51.43.9645 -MountPath I: -Host
Host2.DMN.COM
```

This example syntax specifies the storage path of the LUN mounted on Host1 and mounts the Snapshot copy onto I: on the host Host2.DMN.COM. The cmdlet is executed on Host2.DMN.COM.

Resource ConnectedResource

L:\I\

Example 8: Mounting a LUN with LUN storage path using Primary SVM

```
PS C:\> Mount-SdSnapshot -Path
Primary_SVM:/vol/Volume_Vault/Volume_Vault_Lun1 -Snapshot
R70105EC0A5V1_SQL2019_SQL_DB1_R70105EC0A5V1_03-15-2021_22.37.23.2993_1
-PrefixForVolumeClone Clone_01292021_2330 -AutopickMountPoint -Verbose
```

This example syntax specifies the storage path of the Primary LUN mounted and mounts the Snapshot copy onto random drive letter on the same host using Primary Storage . The cmdlet is executed on Host1.

```
VERBOSE: Validating input paths.
VERBOSE: LUN: Primary_SVM:/vol/Volume_Vault/Volume_Vault_Lun1
VERBOSE: The Snapshot 'R70105EC0A5V1_SQL2019_SQL_DB1_R70105EC0A5V1_03-15-
2021_22.37.23.2993_1' of Primary_SVM:/vol/Volume_Vault/Volume_Vault_Lun1
will be mounted.
VERBOSE: Drive letter if available or a mount point will be auto-picked
VERBOSE: Mounting the specified resources from the Snapshot copy.
VERBOSE: Operation successful.
Resource    ConnectedResource
-----
Primary_SVM:/vol/Volume_Vault/Volume_Vault_Lun1    C:\scmnpt\mpdisk0006\
```

Example 9: Mounting a LUN with LUN storage path using Secondary Storage fails

```
PS C:\> Mount-SdSnapshot -Path
Secondary_SVM:/vol/Volume_Secondary_Vault/Volume_Secondary_Vault_Lun1
-Snapshot BCHExchDAG2016_Backup_kdcbchexch1_01-29-2021_23.30.20.2845
-PrefixForVolumeClone Clone_01292021_2330 -AutopickMountPoint
```

This example syntax specifies the storage path of the LUN mounted and trying to mount the Snapshot copy with random drive letter on the any host using Secondary Storage . The cmdlet is executed on Host1.

```

Mount-SdSnapshot : Failed to mount the Snapshot copy.Failed to mount the
resource:
Secondary_SVM:/vol/Volume_Secondary_Vault/Volume_Secondary_Vault_Lun1 from
snapshot: BCHExchDAG2016_Backup_kdcbchexch1_01-29-2021_23.30.20.2845.
The source LUN's iGroup does not exist.
Possible Resolution: Make sure that Host to storage connectivity is
available.
At line:1 char:1
+ Mount-SdSnapshot -Path
Secondary_SVM:/vol/Volume_Secondary_Vault/Volume_Secondary_Vault_Lun1 ...
+ ~~~~~
+ CategoryInfo      : InvalidResult:
(SnapDrive.Clien...MountSdSnapshot:MountSdSnapshot) [Mount-SdSnapshot],
Exception
+ FullyQualifiedErrorId : 102,SnapDrive.Client.PSModule.MountSdSnapshot

```

New-SdBackup

Syntax

```

New-SdBackup [-Snapshot] <String> [-ConsistencyGroups]
<NewSdBackup+ConsistencyGroupInfo> [-LUNs] <String> [-NasDirs]
<String> [-DisableFallbackToVolumeSnapshot] <> [-RestApiURL] <String>
[-Session] <String> [-Host] <String>

```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Snapshot		true	true (ByValue, ByPropertyName)	
ConsistencyGroups		false	true (ByPropertyName)	
LUNs		false	true (ByPropertyName)	
NasDirs		false	true (ByPropertyName)	
DisableFallbackToVolumeSnapshot		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
RestApiURL		false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

New-SdIgroup

Creates a new igroup.

Syntax

```
New-SdIgroup [-Name] <String> [-Protocol] <String> [-Type] <String>
[-PortSet] <String> [-Initiators] <String[]> [-StorageSystem]
<String> [-Session] <String> [-Host] <String>
```

Detailed Description

Creates a new igroup.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name for your new igroup.	true	true (ByPropertyName)	
Protocol	Specifies the protocol you want to use with your new igroup.	true	true (ByPropertyName)	
Type	Specifies the type of igroup you want to create.	false	true (ByPropertyName)	
PortSet	Specifies the portset to which you want to add your igroup.	false	true (ByPropertyName)	
Initiators	Specifies any initiators you want to add to your igroup.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the storage system on which you want your igroup to reside.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Creating a new igroup

```
PS C:\> New-SdIgroup -Name IG_Demo -StorageSystem 172.17.168.13
-Initiators ign.1991-05.com.microsoft:mva-s24-rx200.sddev.mycompany.com
-Protocol mixed
```

This example syntax creates a new mixed protocol igroup on the specified storage system.

New-SdLun

Creates a LUN on your storage system.

Syntax

```
New-SdLun [-StorageSystem] <String> [-LunPath] <String> [-Size]
<String> [-Type] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Creates a LUN on your storage system.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the storage system on which you want to create a new LUN.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
LunPath	Specifies the path of the LUN on your storage system. If you are working in an ONTAP environment, specify the path to your LUN. If you are working in a Flashray, specify the LUN name.	true	true (ByPropertyName)	
Size	Specifies the size of your new LUN. Valid size specifications are MB, GB, or TB.	true	true (ByPropertyName)	
Type		false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

New-SdPortSet

Creates a new portset.

Syntax

```
New-SdPortSet [-PortSetName] <String> [-PortSetType] <String> [-StorageSystem] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Creates a new portset.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PortSetName	Specifies the name of the portset you want to create.	true	true (ByPropertyName)	
PortSetType	Specifies the protocol you want to use for your new portset. Valid options are iSCSI, Fibre Channel (FCP), or mixed.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the storage system on which you want your new portset to reside.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

New-SdSMBShare

Provisions SMB shares using templates that encapsulate best practices for provisioning shares for different types of applications.

Syntax

```
New-SdSMBShare [-Name] <String> [-Path] <String> [-CIFSServer]
<String> [-TemplateName] <String> [-ShareProperties] <String[]> [-
SymLinkProperties] <String[]> [-FileUmask] <Int32> [-DirUmask]
<Int32> [-Comment] <String> [-AttributeCacheTtl] <Int32> [-
UserOrGroup] <String> [-Permission] <String> [-Session] <String> [-
Host] <String> [-Name] <String> [-Path] <String> [-StorageSystem]
<String> [-TemplateName] <String> [-ShareProperties] <String[]> [-
SymLinkProperties] <String[]> [-FileUmask] <Int32> [-DirUmask]
<Int32> [-Comment] <String> [-AttributeCacheTtl] <Int32> [-
UserOrGroup] <String> [-Permission] <String> [-Session] <String> [-
Host] <String>
```

Detailed Description

Provisions SMB shares using templates that encapsulate best practices for provisioning shares for different types of applications. Get the provisioning templates from the "templates" folder in your install directory. This cmdlet is supported in clustered Data ONTAP 8.2 and later. Related cmdlets: New-SdVolume

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the SMB share you want to provision. The SMB share name must be a UTF-8 string. You cannot use following characters: control characters from 0x00 to 0x1F, both inclusive, 0x22 (double quotes) and the special characters V[]: <>+ =,; , ?	false	true (ByPropertyName)	
Path	Designates the file system path that is shared through your SMB share.	false	true (ByPropertyName)	
CIFSServer	Specifies the SMB server you want to use for provisioning the share.	false	true (ByPropertyName)	
TemplateName	Specifies the provisioning template name. You should also include the path to the template, if the template resides in a folder other than the Templates folder.	false	true (ByPropertyName)	
ShareProperties	Provides a list of properties for your SMB share. Possible values: "oplocks", "browsable", "showsnapshot", "changenotify", "homedirectory", "attributecache", "continuously-available"	false	true (ByPropertyName)	
SymlinkProperties	Indicates whether you want the symlinks under this shared directory to be hidden, accessible, or read-only (option "read-only" along with option "enable".) Possible values are: "enable", "hide", "read_only"	false	true (ByPropertyName)	
FileUmask	You can use the value of this field to control the file mode creation mask for the SMB share in qtrees with UNIX or mixed security styles. The file mode create mask restricts the initial permissions setting of a newly created file. The input value is a numeric mode comprised of one to three octal digits (0-7), derived by adding up the bits with values 4, 2, and 1. The first digit selects permissions for the user who owns the file: read (4), write (2), and execute (1). The second selects permissions for other users in the file's group, with the same values. The third is for other users not in the file's group, with the same values.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
DirUmask	You can use the value of this field to control the file mode creation mask for the SMB share in qtrees with UNIX or mixed security styles. The mask restricts the initial permissions setting of a newly created directory. The input value is a numeric mode comprising of one to three octal digits (0-7), derived by adding up the bits with values 4, 2, and 1. The first digit selects permissions for the user who owns the file: read (4), write (2), and execute (1); the second selects permissions for other users in the file's group, with the same values; and the third for other users not in the file's group, with the same values.	false	true (ByPropertyName)	
Comment	This optional parameter describes a new SMB share. Your description is visible to SMB clients when they are browsing the virtual storage server's SMB shares.	false	true (ByPropertyName)	
AttributeCacheTtl	Specifies the lifetime of an entry in the file attribute cache, in seconds. You can use this value if you have set the "attributecache" property set for the share. Setting the "attributecache" property improves the performance of certain metadata operations in common workloads. The default is 10 seconds. The value of this field must be in the range of 1 to 86400. Raising this value may improve performance, but it increases the likelihood that you serve stale metadata.	false	true (ByPropertyName)	
UserOrGroup	Specifies the user or group name for which you list the permissions.	false	true (ByPropertyName)	
Permission	Indicates access rights that a user or group has on the defined SMB share. Possible values: "no_access", "read", "change", "full_control".	false	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Indicates the virtual storage server you want to use for provisioning the SMB share. The virtual storage server should already have a SMB server configured. You do not need to use this parameter if the SMB server is qualified.	false	true (ByPropertyName)	

Examples

Example 1: Provisioning SMB shares

```
PS C:\> New-SdSMBShare -Path /Sharename -Name HyperVShare -CIFSServer
HyperVFileServer -TemplateName "C:\Program
Files\NetApp\SnapCenter\SnapCenter Plug-in for Microsoft Windows"
```

This example syntax provisions a SMB share using the specified template.

New-SdSnapshot

Creates Snapshot copies of specified Windows disks or SMB shares.

Syntax

```
New-SdSnapshot [-Path] <Object[]> [-Snapshot] <String> [-
NoCleanUpOnError] <> [-UpdateMirror] <> [-CrashConsistent] <> [-
Session] <String> [-Host] <String>
```

Detailed Description

Creates Snapshot copies of specified Windows disks or SMB shares. Related cmdlets: Get-SdSnapshot, Remove-SdSnapshot and Rename-SdSnapshot

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Provides the volume, logical disk, or a comma-separated list of SMB shares of which you want to make Snapshot copies. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByValue, ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Snapshot	Designates the name of the new Snapshot copy. You cannot use special characters in a Snapshot copy name. If you do not specify a Snapshot copy name, a GUID appended with timestamp is generated and used as the Snapshot copy name.	false	true (ByPropertyName)	A GUID appended with timestamp will be generated and used for the Snapshot copy name
NoCleanUpOnError	Indicates whether you want to delete Snapshot copies if there is an error in backing up one of the specified resources, that results in an incomplete Snapshot backup.	false	true (ByPropertyName)	
UpdateMirror	Initiates a mirror or vault update after your Snapshot operation completes.	false	false	
CrashConsistent		false	false	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Backing up the specified SMB shares

```
PS C:\> New-SdSnapshot -Path
"\\fileserver\sqlshare", "\\fileserver\sqlshare2" -Snapshot "sql_snap"
```

This example syntax backs up the SMB shares by creating Snapshot copies of the corresponding volumes using Snapshot name sql_snap.

Example 2: Backing up the specified disk

```
PS C:\> New-SdSnapshot -Path E: -Snapshot "sql_snap"
```

This example syntax backs up the disk drive by creating Snapshot copies of the corresponding volumes using Snapshot name sql_snap.

New-SdStorage

Provisions a Windows volume or disk on a LUN.

Syntax

```
New-SdStorage [-Path] <String> [-Size] <String> [-LunPath] <String>
[-StorageSystem] <String> [-FileSystemLabel] <String> [-SharedDisk]
<> [-ClusteredSharedVolume] <> [-Igroup] <String> [-InitiatorInfo]
<HostInitiatorInfo> [-PortSet] <String> [-AutopickMountPoint] <> [-
PartitionStyle] <PartitionStyle> [-ResourceGroup] <String> [-Thin] <>
[-AllocationUnitSize] <String> [-RawDeviceMapping] <> [-Datastore]
<String> [-Session] <String> [-Host] <String>
```

Detailed Description

Provisions dedicated disks, shared disks and clustered shared volumes on a LUN.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the drive letter or mount point: D:, D:\Mount	false	true (ByPropertyName)	
Size	Specifies size of the new Windows disk you are provisioning. Supported units: G, T, K, M	true	true (ByPropertyName)	
LunPath	Specifies your LUN path in the following format: /vol/volx/lunx	true	true (ByPropertyName)	
StorageSystem	Specifies the target virtual storage machine you want to use for provisioning.	true	true (ByPropertyName)	
FileSystemLabel	Specifies the label you want to attach to your new Windows volume.	false	true (ByPropertyName)	
SharedDisk	Indicates whether you need to provision your Windows disk as a shared disk.	false	true (ByPropertyName)	
ClusteredSharedVolume	Indicates whether you will provision your Windows disk as a Clustered Shared Volume.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Igroup	Specifies the igroup you want to use for mapping the LUN. If not specified, SnapCenter Plug-in for Mcrsoft Windows automatically manages the igroup for mapping the LUN.	false	true (ByPropertyName)	
InitiatorInfo	Specifies the initiators you want to add to your Igroup.	false	true (ByPropertyName)	
PortSet	Specifies the portset you want to use for binding your Igroup. If yourIgroup is already bound to a different portset, specifying this parameter unbinds your Igroup and then binds it to the portset specified here.	false	true (ByPropertyName)	
AutopickMountPoint	Specifies that the mount point for the new LUN is assigned automatically.	false	true (ByPropertyName)	
PartitionStyle	Indicates whether you want to use GPT or MBR partition style.	false	true (ByPropertyName)	
ResourceGroup	Specifies a Cluster Resource Group for your shared Windows disk.	false	true (ByPropertyName)	
Thin	Indicates whether you want the LUN to be thin provisioned.	false	false	
AllocationUnitSize	Specifies the custom NTFS allocation unit size. Possible values are: 4 KB, 8 KB, 16 KB, 24 KB, 32 KB, and 64 KB. The minimum allocation size is 4 KB, and the maximum is 64 KB. The default value is 4 KB.	false	true (ByPropertyName)	
RawDeviceMapping	Indicates whether the LUN is raw device mapping for VMWare.	false	true (ByPropertyName)	
Datastore	Specifies the Name of the datastore.	false	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies your target host.	false	true (ByPropertyName)	

Examples

Example 1: Provisioning a dedicated Windows disk

```
PS C:\> new-sdstorage -StorageSystem 172.17.165.31 -path V: -LunPath /vol/santest/b09 -size 1G -InitiatorInfo @{Host="R505143C1AAV1.HNK2.COM"; Initiators="iqn.1991-05.com.microsoft:r505143claav1.hnk2.com"}
```

This example syntax creates a new dedicated Windows disk.

Example 2: Provisioning a shared Windows disk

```
PS C:\> new-sdstorage -StorageSystem 172.17.165.31 -path V: -LunPath /vol/santest/b09 -size 1G -SharedDisk -Igroup Windows2012_igroup
```

In this example syntax, you provision a shared disk in "Available storage" resource group.

Example 3: Provisioning a shared Windows disk in an alternate resource group

```
PS C:\> new-sdstorage -StorageSystem 172.17.165.31 -path V: -LunPath /vol/santest/b09 -size 1G -SharedDisk -ResourceGroup prod -Igroup SqlAG_igroup
```

In this example syntax, you provision a shared disk in prod resource group.

Example 4: Provisioning a new Cluster shared volume

```
PS C:\> new-sdstorage -StorageSystem 172.17.165.31 -LunPath /vol/santest/b09 -size 1G -ClusteredSharedVolume -Igroup Windows2012_igroup
```

In this example syntax, you provision a clustered shared volume.

Example 5: Provisioning a RDM disk with other options:(Datastore, FileSystemLabel, filesystemlablename)

```
PS new-sdstorage -storagesystem autof7f8_vsvr1 -path K:\ -LunPath /vol/C227030162240_1_MDML_Log_Vol/Lun1 -size 3G -igroup C227030162240_1 -Thin -RawDeviceMapping -Datastore C227030162240_1VMFS_DS -FileSystemLabel filesystemlablename -PartitionStyle GPT
```

In this example syntax, you provision a RDM disk.

```

                TotalSizeInGB    : 3.00287246704102 GB
UsedSpaceInGB   : 3.00287246704102 GB
Name: K:\
FileSystemIdentifier:
autof7f8_vsvr1:/vol/C227030162240_1_MDML_Log_Vol/Lun1
FileSystemType   : ntfs
MountedFromSnapshot : False
TotalSize       : 3224309760
UsedSpace       : 3224309760
BlockSize       : 4096
Clustered       : False
Expandable      : True
OwnerNode       : False
MountOptions:
MountPaths      : {K:\}
parents :
Message :
ClusterAttributes :
BootFileSystem    : False
BootFileSystemSpecified : False
bIsPathOnCSV: False
bIsPathOnCSVSpecified : True
CSVReparsePointPath :
```

Example 6: Provisioning a RDM disk

```
New-SdStorage -LunPath /vol/Vol_VM180_FC/L2 -Size 1GB -StorageSystem
10.225.21.111 -Igroup Sab_FC_ESX -Path M: -RawDeviceMapping
```

In this example syntax, you provision a RDM disk.

```

                TotalSizeInGB      : 1.00351095199585 GB
UsedSpaceInGB    : 1.00351095199585 GB
Name: M:\
FileSystemIdentifier: sce_svm_1:/vol/Vol_VM180_FC/L2
FileSystemType    : ntfs
MountedFromSnapshot : False
TotalSize        : 1077511680
UsedSpace        : 1077511680
BlockSize        : 4096
Clustered        : False
Expandable       : True
OwnerNode        : False
MountOptions:
MountPaths       : {M:\}
parents :
Message :
ClusterAttributes :
BootFileSystem    : False
BootFileSystemSpecified : False
bIsPathOnCSV: False
bIsPathOnCSVSpecified : True
CSVReparsePointPath :

```

Example 7: Provisioning a RDM/Windows disk with InitiatorInformation

```

$initiatorlist = New-Object Collections.Generic.List[string]
    $initiatorlist.Add("10:00:00:90:fa:a6:32:63")
    $hostname = "Bay8-21264"
    $initiatorInfo = New-Object SMCoreContracts.HostInitiatorInfo
-ArgumentList $hostname, $initiatorlist
    New-SdStorage -LunPath /vol/Abhi_FCOE_Vol1/L5 -Size 1GB
-StorageSystem vs_21264 -Igroup ig_21264 -Path U:\ -InitiatorInfo
$initiatorInfo

```

In this example syntax, you provision a RDM disk.

```

                TotalSizeInGB    : 1.00351095199585 GB
UsedSpaceInGB   : 1.00351095199585 GB
Name: U:\
FileSystemIdentifier: vs_21264:/vol/Abhi_FCOE_VO11/L5
FileSystemType   : ntfs
MountedFromSnapshot : False
TotalSize        : 1077511680
UsedSpace         : 1077511680
BlockSize        : 4096
Clustered         : False
Expandable        : True
OwnerNode         : False
MountOptions:
MountPaths        : {U:\}
parents :
Message :
ClusterAttributes :
BootFileSystem     : False
BootFileSystemSpecified : False
bIsPathOnCSV: False
bIsPathOnCSVSpecified : True
CSVReparsePointPath :
```

New-SdVolume

Provisions volumes using templates that encapsulate best practices for provisioning volumes for different types of applications.

Syntax

```
New-SdVolume [-Name] <String> [-Aggregate] <String> [-Size] <String>
[-JunctionPath] <String> [-StorageSystem] <String> [-TemplateName]
<String> [-Comment] <String> [-AntivirusOnAccessPolicy] <String> [-
ExportPolicy] <String> [-FlexCacheCachePolicy] <String> [-
FlexCacheFillPolicy] <String> [-FlexCacheOriginVolume] <String> [-
GroupId] <Int32> [-IndexDirectoryFormat] <Boolean> [-JunctionActive]
<Boolean> [-MaxDirectorySize] <Decimal> [-NvFailEnabled] <Boolean> [-
SecurityStyle] <String> [-SnapshotPolicy] <String> [-State] <String>
[-Type] <String> [-UnixPermissions] <String> [-UserId] <Int32> [-
VirtualStorageServerRoot] <Boolean> [-QosPolicyGroup] <String> [-
SnapshotCloneDependency] <Boolean> [-EnableSnapdiff] <Boolean> [-
SchedSnapName] <String> [-SpaceGuarantee] <String> [-SnapReserve]
<Int32> [-FractionalReserve] <Int32> [-SpaceMgmtTryFirst] <String> [-
SpaceNearlyFullThresholdPercent] <Int32> [-SpaceFullThresholdPercent]
<Int32> [-Files] <Int32> [-FilesysSizeFixed] <> [-ExtentEnabled]
<String> [-ReadRealloc] <String> [-ExternalCache] <String> [-
VmAlignSector] <Int32> [-VmAlignSuffix] <String> [-AutoSizeMode]
<String> [-MaxAutosize] <String> [-AutosizeIncrement] <String> [-
AutosizeIncrementPercent] <Int32> [-MinAutosize] <String> [-
AutosizeGrowThresholdPercent] <Int32> [-AutosizeShrinkThresholdPercent]
<Int32> [-AutoDeleteEnabled] <> [-Commitment] <String> [-DeferDelete]
<String> [-Deleteorder] <String> [-DeferDeletePrefix] <String> [-
TargetFreeSpace] <Int32> [-Trigger] <String> [-DestroyList] <String>
[-Session] <String> [-Host] <String>
```

Detailed Description

Provisions volumes using templates that encapsulate best practices for provisioning volumes for different types of applications. Gets the provisioning templates from the "templates" folder in your install directory. This cmdlet is supported in clustered Data ONTAP 8.2 and later. Related cmdlets: Remove-SdVolume

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Indicates the name of the new volume.	false	true (ByPropertyName)	
Aggregate	Specifies the name of the containing aggregate.	false	true (ByPropertyName)	
Size	Designates the size of the new volume.	false	true (ByPropertyName)	
JunctionPath	Specifies the junction path at which this volume is to be mounted.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the storage virtual machine for provisioning the storage volume.	false	true (ByPropertyName)	
TemplateName	Indicates the name of the provisioning template. You should qualify path to the template if the template resides in a folder other than SnapDrive Templates folder.	false	true (ByPropertyName)	
Comment	Provides a description for the volume being created.	false	true (ByPropertyName)	
AntivirusOnAccessPolicy	Specifies the name of the Anti-Virus On-Access policy. The default policy name is 'default'.	false	true (ByPropertyName)	
ExportPolicy	Specifies the name of the export policy to be used by NFS/SMB protocols. The default policy name is 'default'.	false	true (ByPropertyName)	
FlexCacheCachePolicy	Specifies the name of the FlexCache cache policy. The default policy name is 'default'.	false	true (ByPropertyName)	
FlexCacheFillPolicy	Specifies the name of the FlexCache prefill policy. The default policy name is 'default'	false	true (ByPropertyName)	
FlexCacheOriginVolume	Specifies the name of the origin volume that contains the authoritative data.	false	true (ByPropertyName)	
GroupId	Specifies the UNIX group ID for the volume. The default value is 0 ('root').	false	true (ByPropertyName)	
IndexDirectoryFormat	Indicates whether you want to enable the index directory format. If true, index directory format is enabled. The default is false.	false	true (ByPropertyName)	
JunctionActive	Indicates whether the mounted volume is accessible. The default is true.	false	true (ByPropertyName)	
MaxDirectorySize	Specifies the maximum size in bytes, to which any directory in this volume can grow.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
NvFailEnabled	Indicates whether you want the controller to identify and attempt to correct NVRAM failure errors. If true, the controller performs additional work at startup and takeover times, if it finds that there has been any potential data loss in this volume due to an NVRAM failure.	false	true (ByPropertyName)	
SecurityStyle	Designates a volume security style.Possible values are: mixed, ntfs, unix.	false	true (ByPropertyName)	
SnapshotPolicy	Specifies the Snapshot copy policy.Default policy is 'default'.	false	true (ByPropertyName)	
State	Indicates the desired state of the volume after it is created.Possible values are: online restricted offline force-online force-offline mixed	false	true (ByPropertyName)	
Type	Specifies the volume type.Possible values are: rw, ls, dp, dc.	false	true (ByPropertyName)	
UnixPermissions	Indicates the UNIX permission bits in an octal string format.	false	true (ByPropertyName)	
UserId	Specifies the UNIX user ID for the volume. The default value is 0 ('root').	false	true (ByPropertyName)	
VirtualStorageServer Root	Indicates whether you want this value to be the namespace root volume. If true, this volume is the namespace root volume of the virtual storage server which owns this volume.The default value is false.	false	true (ByPropertyName)	
QosPolicyGroup	Optionally specifies which QoS policy group to apply to the volume. This policy group defines measurable service level objectives (SLOs) that apply to the storage objects with which the policy group is associated. If you do not assign a policy group to a volume, the system monitors and controls the traffic to the volume. To remove this volume from a policy group, enter the reserved keyword 'none'. This parameter is not supported on Infinite Volumes.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
SnapshotCloneDependency	{on off} - Snapshot Cloning Dependency Specifies whether the LUN clone dependency on Snapshot copies is enabled. If set to on, LUN clone dependency on Snapshot copies is enabled. This parameter is not supported on Infinite Volumes.	false	true (ByPropertyName)	
EnableSnapdiff	{true false} - Create Namespace Mirrors For Snapdiff Use	false	true (ByPropertyName)	
SchedSnapName	{create_time ordinal} - Naming Scheme for Automatic Snapshots Specifies the naming convention for automatic Snapshot copies. If set to create-time, automatic Snapshot copies are named using the format <schedule_name>.yyyy-mm-dd_hhmm. Example: hourly.2010-04-01_0831. If set to ordinal, automatic Snapshot copies are named using the format <schedule_name>.<n>. Example: hourly.3 This parameter is not supported on Infinite Volumes.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
SpaceGuarantee	Specifies the type of volume guarantee the new volume uses. Possible values: none, file, volume. This option controls whether the volume is guaranteed some amount of space in the aggregate. The default is volume, and file and none can be set by the administrator. Volume guaranteed means that the entire size of the volume is preallocated. The file value means that space is preallocated for all the space-reserved files and LUNs within the volume. Storage is not preallocated for files and LUNs that are not space-reserved. Writes to these can fail if the underlying aggregate has no space available to store the written data. This value can be set if fractional reserve is 100. The none value means that no space is preallocated, even if the volume contains space-reserved files or LUNs. If the aggregate is full, space is not available even for space-reserved files and LUNs within the volume. Setting this parameter to file or none enables you to provision more storage than is physically present in the aggregate (thin provisioning). When you use thin provisioning for a volume, it can run out of space even if it has not yet consumed its nominal size and you should carefully monitor space utilization to avoid unexpected errors due to the volume running out of space. For flexible root volumes, to ensure that system files, log files, and cores can be saved, the space-guarantee must be volume. This ensures technical support for the storage system, if a problem occurs. Disk space is preallocated when the volume is brought online and, if not used, returned to the aggregate when the volume is brought offline. It is possible to bring a volume online even when the aggregate has insufficient free space to preallocate to the volume. In this case, no space is preallocated, just as if the none option had been selected. In this situation, the vol options and vol status command display the actual value of the space-guarantee option, but indicate that it is disabled.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
SnapReserve	Optionally specifies the amount of space reserved on the volume for Snapshot copies. The default setting is 5 percent.	false	true (ByPropertyName)	
FractionalReserve	This option changes the amount of space reserved for overwrites of reserved objects (LUNs, files) in a volume. This parameter is not supported on Infinite Volumes. The option is set to 100 by default with guarantee set to volume or file. A setting of 100 means that 100 percent of the required reserved space is actually reserved, so the objects are fully protected for overwrites. The value is set to 0 by default with guarantee set to none. The value can be either 0 or 100 when guarantee is set to volume or none. If guarantee is set to file, 100 is the only allowed value. Using a value of 0 indicates that no space will be reserved for overwrites. This returns the extra space to the available space for the volume, decreasing the total amount of space used. However, this does leave the protected objects in the volume vulnerable to out of space errors. If the percentage is set to 0%, the administrator must monitor the space usage on the volume and take corrective action.	false	true (ByPropertyName)	
SpaceMgmtTryFirst	{volume_grow snap_delete} - Primary Space Management Strategy A flexible volume can be configured to automatically reclaim space in case the volume is about to run out of space, by either increasing the size of the volume using autogrow or deleting Snapshot copies in the volume using Snapshot autodelete. If this option is set to volume_grow the system will try to first increase the size of volume before deleting Snapshot copies to reclaim space. If the option is set to snap_delete the system first automatically deletes Snapshot copies and in case of failure to reclaim space tries to grow the volume. This parameter is not supported on Infinite Volumes.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
SpaceNearlyFullThresholdPercent	Optionally specifies the percentage at which the volume is considered nearly full, and above which an EMS warning is generated. The default value is 95%. Setting this threshold to 0 disables the volume nearly full space alerts. This parameter is not supported on Infinite Volumes.	false	true (ByPropertyName)	
SpaceFullThresholdPercent	Optionally specifies the percentage at which the volume is considered full, and above which a critical EMS error is generated. The default value is 98%. Setting this threshold to 0 disables the volume full space alerts. This parameter is not supported on Infinite Volumes.	false	true (ByPropertyName)	
Files	Optionally specifies the total number of files permitted on the volume. The default setting is 629. This value can be raised but cannot be lowered; the new value must be larger than the current value.	false	true (ByPropertyName)	
FilesysSizeFixed	This option causes the file system to remain the same size and not grow or shrink when a SnapMirrored volume relationship is broken, or when a volume add is performed on it. It is automatically set to true when a volume becomes a SnapMirrored volume. It stays set to true after the SnapMirror break command is issued for the volume. This allows a volume to be SnapMirrored back to the source without needing to add disks to the source volume. If the volume is a traditional volume and the size is larger than the file system size, setting this option to false forces the file system to grow to the size of the volume. If the volume is a flexible volume and the volume size is larger than the file system size, setting this option to false forces the volume size to equal the file system size. The default setting is false.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ExtentEnabled	Setting this option to on or space-optimized enables extents in the volume. This causes application writes to be written in the volume as a write of a larger group of related data blocks called an extent. Using extents may help workloads that perform many small random writes followed by large sequential reads. However, using extents may increase the amount of disk operations performed on the controller, so this option should only be used where this trade-off is desired. If the option is set to space-optimized then the reallocation update will not duplicate blocks from Snapshot copies into the active file system, and will result in conservative space utilization. Using space-optimized may be useful when the volume has Snapshot copies or is a SnapMirror source, when it can reduce the storage used in the volume and the amount of data that SnapMirror must move on the next update. The space-optimized value can result in degraded read performance of Snapshot copies. The default value is off; extents are not used.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ReadRealloc	Setting this option to on or space-optimized enables read reallocation in the volume. This results in the optimization of file layout by writing some blocks to a new location on disk. The layout is updated only after the blocks have been read because of a user read operation, and only when updating their layout will provide better read performance in the future. Using read reallocation may help workloads that perform a mixture of random writes and large sequential reads. If the option is set to space-optimized then the reallocation update will not duplicate blocks from Snapshot copies into the active file system, and will result in conservative space utilization. Using space-optimized may be useful when the volume has Snapshot copies or is a SnapMirror source, when it can reduce the storage used in the volume and the amount of data that SnapMirror must move on the next update. The space-optimized value can result in degraded read performance of Snapshot copies. The default value is off.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ExternalCache	Optionally specifies which WAFL external cache policy to apply to the volume. This parameter is not supported on Infinite Volumes. A WAFL external cache policy defines how the data blocks are cached for this volume. If an external cache policy is not assigned to this volume, the system uses the external cache policy that is assigned to the containing virtual storage server. If an external cache policy is not assigned to the containing virtual storage server, the system uses the default cluster-wide policy. The available WAFL external cache policies are: o Uncached - Caches nothing. o Metadata_Only - Caches indirect blocks and system metafiles. o Normal_Data - Caches indirect blocks, system metafiles, and randomly read user data. o Random_Write_Data - Caches normal data blocks and any blocks read as a result of random writes. o Readahead_Data - Caches normal data blocks and any sequentially read user data blocks. o Most_Data - Caches normal data blocks and any blocks read as a result of random writes or sequential reads. o Lopri_Data - Caches everything. o Default - Current cluster-wide default, which is Normal_Data.	false	true (ByPropertyName)	
VmAlignSector		false	true (ByPropertyName)	
VmAlignSuffix		false	true (ByPropertyName)	
AutoSizeMode	{off grow grow_shrink} - Autosize ModeSpecifies the autosize mode for the volume. The allowed values are grow, grow_shrink, and off. If this parameter is not specified, the existing autosize mode remains in effect. This parameter is not supported in Infinite Volumes. The various autosize modes are explained below: o off - The volume will not grow or shrink in size in response to the amount of used space. o grow - The volume will automatically grow when used space in the volume is above the grow threshold. o grow_shrink - The volume will grow or shrink in size in response to the amount of used space.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
MaxAutosize	Specifies the maximum size to which a flexible volume can grow. The default is 120% of the volume size at creation for a flexible volume, and the greater of the origin volume's size and the current value of max-autosize for a FlexCache volume if a size is not specified upon creation. This parameter is not supported in Infinite Volumes.	false	true (ByPropertyName)	
AutosizeIncrement	The size of the volume is increased by the increment size specified by autosize-increment each time the volume is autogrown. A volume does not automatically grow if the current size of the volume is greater than or equal to the maximum size specified by the max-autosize. The default is 5% of the volume size at the time autosize was enabled for the volume. This parameter is not supported in Infinite Volumes.	false	true (ByPropertyName)	
AutosizeIncrementPercent	The increment percent specified with autosize-increment-percent is converted to a fixed increment size in bytes based on the volume size when volautosize-increment-percent is issued. The size of the volume is increased by the computed increment size each time the volume is autogrown. A volume will not automatically grow if the current size of the volume is greater than or equal to the maximum size specified with the max-autosize parameter. The default is 5% of volume size at the time autosize was enabled for the volume. This parameter is not supported in Infinite Volumes.	false	true (ByPropertyName)	
MinAutosize	{<integer>[KB MB GB TB PB]} - Minimum Autosize Specifies the minimum automatic size to which the volume shrinks. The default value is the volume size at the time when the grow_shrink autosize mode was enabled for the volume. If the volume was created with the grow_shrink autosize mode enabled, then the default minimum size will be equal to the initial volume size. This parameter is not supported in Infinite Volumes.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
AutosizeGrowThresholdPercent	Specifies the used space threshold for the automatic growth of the volume. When the volume used space becomes greater than this threshold, the volume will be grown unless it has reached the maximum autosize. This parameter is not supported in Infinite Volumes.	false	true (ByPropertyName)	
AutosizeShrinkThresholdPercent	Specifies the used space threshold for the automatic shrink of the volume. When the volume used space becomes less than this threshold, the volume will be shrunk unless it has reached the minimum autosize. This parameter is not supported in Infinite Volumes.	false	true (ByPropertyName)	
AutoDeleteEnabled	Specifies whether automatic deletion of Snapshot copies is enabled or disabled. If set to true, automatic deletion of Snapshot copies is enabled. If set to false automatic deletion of Snapshot copies is disabled.	false	true (ByPropertyName)	
Commitment	Specifies which Snapshot copies can be automatically deleted to reclaim back space. When set to try, the Snapshot copies which are not locked by any application are deleted. When set to disrupt, the Snapshot copies which are not locked by Data Backing Functionalities (Volume Clones, LUN Clones, File Clones) are deleted. In disrupt mode, Snapshot locked by Data Protection Utilities like SnapMirror or Volume Move can be deleted. If such a locked Snapshot copy is deleted during the data transfer, the transfer is aborted. When set to destroy, Snapshot copies locked by even the Data Backing Functionalities are deleted.	false	true (ByPropertyName)	
DeferDelete	{scheduled user_created prefix none}} - Defer Delete Specifies which kind of Snapshot copies are deleted in the end. When set to scheduled, scheduled Snapshot copies are deleted in the end. When set to user_created, user Snapshot copies are deleted in the end. When set to prefix, Snapshot copies matching a certain prefix are deleted in the end. When set to none no defer deletion order is honored.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Deleteorder	{newest_first oldest_first} - Delete Order. Specifies whether if the oldest Snapshot copy or the newest Snapshot copy is deleted first.	false	true (ByPropertyName)	
DeferDeletePrefix	Specifies the prefix string for the -defer -delete prefix parameter.	false	true (ByPropertyName)	
TargetFreeSpace	Specifies when you want automatic deletion of Snapshot copies to stop. Depending on the -trigger Snapshot copies are deleted till you reach the target free space percentage.	false	true (ByPropertyName)	
Trigger	{volume snap_reserve space_reserve} - Trigger Specifies the condition which starts the automatic deletion of Snapshot copies. Setting this option to volume triggers automatic deletion of Snapshot copies when the volume reaches threshold capacity and the volume's space reserved for Snapshot copies has been exceeded. Setting the option to snap_reserve triggers automatic deletion of Snapshot copies when the space reserved for Snapshot copies reaches threshold capacity. Setting the option to space_reserve triggers automatic deletion of Snapshot copies when reserved space in the volume reaches threshold capacity and the volume's space reserved for Snapshot copies has been exceeded.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
DestroyList	Specifies a comma-separated list of data backing functions which are affected if automatic deletion of the Snapshot copy backing that service is triggered. Possible values for this option are: vol_clone, lun_clone, file_clone, sfsr, cifs_share, or none. With the exception of none, all options can be combined as a comma-separated list. If you specify vol_clone, the cloned volume backed by the Snapshot copy is deleted. If you specify lun_clone, and the LUN is in the process of being cloned when autodelete is triggered, the cloning operation is aborted. Any access to this LUN results in an error being reported to the client. If you specify file_clone, and the file cloning operation is in progress when autodelete is triggered, the cloning operation is aborted. Any access to this file results in an error being reported to the client. If you specify sfsr, and the file restore is in progress when autodelete is triggered, the restore operation is aborted. If the Snapshot copy is locked either by a lun_clone or file_clone or both, the -destroy-list must be set to lun_clone,file_clone. If the Snapshot copy is locked either by a lun_clone or sfsr operation or both, -destroy-list must be set to lun_clone, file_clone. The options file_clone and sfsr are equivalent to each other. If you set -destroy-list to lun_clone, file_clone and the Snapshot copy is backing a file clone or sfsr operation, both the operations are aborted. This is also the case when you set -destroy-list to lun_clone, sfsr.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Provisioning a storage system volume using a template

```
PS C:\> New-SdVolume -Name sqlldbvolume -Aggregate sqlldbaggregate
-JunctionPath /sqlldbvolume
-TemplateName C:\Program
Files\SnapDrive\Templates\HyperVVHdxProvTemplate.xml -Size 128GB
-StorageSystem sqlvirtualstorageserver
```

This example provisions a storage system volume using the specified template.

```
Name      : sqlldbvolume
Vserver:  sqlvirtualstorageserver
FullPath  : sqlvirtualstorageserver:/vol/sqlldbvolume
JunctionPath  : /sqlldbvolume
JunctionParentName :
SizeTotal   :
SizeUsed    :
SnapMirrorSource  :
SnapMirrorDest   :
SnapVaultPrimary  :
SnapVaultSecondary :
FlexCloneEnabled  :
IsFlexClone:
Style   : ntfs
ResourceType   : SDStorageVolume
ResourceName    : sqlvirtualstorageserver:/vol/sqlldbvolume
Ranges :
```

Remove-SdBackup

Syntax

```
Remove-SdBackup [-Snapshot] <String> [-ResourceName] <String> [-
RestApiURL] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Snapshot		true	true (ByValue, ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ResourceName		true	true (ByPropertyName)	
RestApiURL		false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Remove-SdIgroup

Removes an igroup from your storage system.

Syntax

```
Remove-SdIgroup [-Name] <String> [-StorageSystem] <String> [-Session]
<String> [-Host] <String>
```

Detailed Description

Removes an igroup from your storage system.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the igroup you want to remove from your storage system.	true	true (ByPropertyName)	
StorageSystem	Specifies the storage system from which you want to remove the igroup.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Removing an igroup

```
PS C:\> Remove-SdIgroup -Name IG_Demo -StorageSystem 172.17.168.13
```

This example syntax removes the a specific igroup from the specified storage system.

Remove-SdLun

Removes a LUN from your storage system.

Syntax

```
Remove-SdLun [-StorageSystem] <String> [-LunPath] <String> [-Session]  
<String> [-Host] <String>
```

Detailed Description

Removes a LUN from your storage system.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the storage system on which your LUN is located.	true	true (ByPropertyName)	
LunPath	Specifies the path of the LUN on your storage system. If you are working in an ONTAP environment, specify the path to your LUN. If you are working in a Flashray, specify the LUN name.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Remove-SdLunMap

Unmaps your LUN from your igroup.

Syntax

```
Remove-SdLunMap [-StorageSystem] <String> [-LunPath] <String> [-Igroup] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Unmaps your LUN from your igroup.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the storage system on which the igroup, to which your LUN is mapped, resides.	true	true (ByPropertyName)	
LunPath	Specifies the path of the LUN on your storage system. If you are working in an ONTAP environment, specify the path to your LUN. If you are working in a Flashray, specify the LUN name.	true	true (ByPropertyName)	
Igroup	Specifies the igroup from which you want to unmap your LUN.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Remove-SdPortSet

Deletes a portset.

Syntax

```
Remove-SdPortSet [-PortSetName] <String> [-ForceDestroy] <> [-StorageSystem] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Deletes a portset.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PortSetName	Specifies the name of the portset you want to delete.	true	true (ByPropertyName)	
ForceDestroy	Specifies that you want to forcibly delete a portset.	false	true (ByPropertyName)	
StorageSystem	Specifies the name of the storage system on which the portset you want delete resides.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Remove-SdPortSetPort

Deletes a specified port from your portset.

Syntax

```
Remove-SdPortSetPort [-PortSetName] <String> [-Port] <String> [-StorageSystem] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Deletes a specified port from your portset.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PortSetName	Specifies the name of the portset from which you want to delete a port.	true	true (ByPropertyName)	
Port	Specifies the port you want to delete from your portset.	true	true (ByPropertyName)	
StorageSystem	Specifies the storage system on which your portset resides.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Remove-SdSMBShare

Removes one or more SMB shares from your storage system.

Syntax

```
Remove-SdSMBShare [-Path] <Object[]> [-Session] <String> [-Host] <String>
```

Detailed Description

Removes one or more SMB shares from your storage system. This cmdlet is supported in clustered Data ONTAP 8.2 and later.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies a comma-separated list of SMB shares.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Removing an SMB share

```
PS C:\> Remove-SdSMBShare -Path \\JENKINS-CIFS\RemoveShare03 -Verbose
```

This example syntax removes SMB share "RemoveShare03" from your storage system.

Example 2: Removing multiple SMB shares

```
PS C:\> Remove-SdSMBShare -Path \\JENKINS-
CIFS\RemoveShare01,\\172.17.165.40\RemoveShare02 -Verbose
```

This example syntax removes SMB share "RemoveShare01," and "RemoveShare02" from the your storage system.

Remove-SdSnapMirrorPolicyRule

Removes the rules from the SnapMirror policy associated with the SnapVault relationship.

Syntax

```
Remove-SdSnapMirrorPolicyRule [-SourceStorageSystem] <String> [-
SourceStorageSystemVolume] <String> [-DestinationStorageSystem]
<String> [-DestinationStorageSystemVolume] <String> [-SnapMirrorLabel]
<String[]> [-Session] <String> [-Host] <String>
```

Detailed Description

Removes the rules from the SnapMirror policy associated with the SnapVault relationship. Related cmdlets: Set-SdSnapMirrorPolicyRule, Get-SdSnapMirrorPolicyRule

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SourceStorageSystem	Specifies the primary storage system name containing the source volumes of the SnapMirror relationship for which you want to remove the SnapMirror policy rules. IP addresses are not supported.	true	true (ByValue, ByPropertyName)	
SourceStorageSystemVolume	Specifies the source volume of the SnapMirror relationship for which you want to remove the SnapMirror policy rules.	true	true (ByPropertyName)	
DestinationStorageSystem	Specifies the secondary storage system name containing the destination volumes of the SnapMirror relationship for which you want to remove the SnapMirror policy rules. IP addresses are not supported.	true	true (ByValue, ByPropertyName)	
DestinationStorageSystemVolume	Specifies the destination volume of the SnapMirror relationship for which you want to remove the SnapMirror policy rules.	true	true (ByPropertyName)	
SnapMirrorLabel	Specifies the SnapMirror policy rule which you want to remove.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Removing SnapMirror policy rule information from the policy for a SnapMirror relationship

```
PS C:\> Remove-SdSnapMirrorPolicyRule -SourceStorageSystem vs01
-SourceStorageSystemVolume src_vol01 -DestinationStorageSystem vs02
-DestinationStorageSystemVolume dest_vol01 -SnapMirrorLabel
myWeekly,myMonthly -verbose -Confirm:$false
```

Removes the SnapMirror policy rules (myWeekly, myMonthly) from the policy on the specified relationship.

Remove-SdSnapshot

Removes Snapshot copies created on Windows disks, SMB shares, or storage system volumes.

Syntax

```
Remove-SdSnapshot [-Path] <Object[]> [-Snapshot] <String[]> [-Session]
<String> [-Host] <String>
```

Detailed Description

Removes Snapshot copies created on Windows disks, SMB shares, or storage system volumes. Related cmdlets: New-SdSnapshot, Rename-SdSnapshot, and Restore-SdSnapshot

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the SMB shares, volume, or logical disk for the Snapshot copies you want to delete. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByPropertyName)	
Snapshot	Specifies the list of Snapshot copies you want to delete.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Removing a Snapshot copy on a SMB share

```
PS C:\> Remove-SdSnapshot -Path "\\172.17.12.101\share" -Snapshot
"snapshot_1"
```

This example syntax removes the Snapshot copy snapshot_1 created on SMB share \\172.17.12.101\share.

Example 2: Removing specified Snapshot copies on multiple SMB shares

```
PS C:\> Remove-SdSnapshot -Path
"\\172.17.12.101\share1","\\172.17.12.101\share2" -Snapshot
"snapshot_1","snapshot_2"
```

This example removes Snapshot copies snapshot_1 and snapshot_2 created on SMB shares \\172.17.12.101\share1 and \\172.17.12.101\share2.

Example 3: Removing a new Snapshot copy on a SMB share

```
PS C:\> New-SdSnapshot -Path "\\172.17.12.101\share" | Remove-SdSnapshot
```

This example removes the new Snapshot copy on SMB share \\172.17.12.101\share.

Example 4: Removing a Snapshot copy on a disk

```
PS C:\> Remove-SdSnapshot -Path D: -Snapshot "snapshot_1"
```

This example syntax removes the Snapshot copy snapshot_1 created on the disk drive D:.

Remove-SdStorage

Deletes a LUN and everything associated with it.

Syntax

```
Remove-SdStorage [-Path] <String> [-IgnoreVolumeMountPoint] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Deletes a LUN and everything associated with it.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies you LUN share path using this format: :D	true	true (ByPropertyName)	
IgnoreVolumeMountPoint		false	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Deleting a LUN

```
PS C:\> Remove-SdStorage -Path V:
```

This example syntax deletes the specified LUN.

Remove-SdStorageConnectionSetting

Removes the storage connection, transport, and credential settings from the configuration repository for one or more storage system or virtual storage server.

Syntax

```
Remove-SdStorageConnectionSetting [-StorageSystem] <String[]> [-HostOnly] <> [-PassThru] <> [-LegacyContext] <> [-Session] <String> [-Host] <String> [-All] <> [-HostOnly] <> [-PassThru] <> [-LegacyContext] <> [-Session] <String> [-Host] <String> [-DefaultSetting] <> [-HostOnly] <> [-PassThru] <> [-LegacyContext] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Removes the storage connection, transport and credential settings from the configuration repository for one or more storage system or virtual storage server. Related cmdlets: Set-SdStorageConnectionSetting and Get-SdStorageConnectionSetting

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the name or IP address of the storage system (storage controller or virtual storage server) for which you want to retrieve connection settings.	true	true (ByPropertyName)	
HostOnly	Specifies that you want to remove the storage system credentials only on the cluster node you specify. The default behavior is that HostOnly is not specified, and your storage credential settings are removed from all the nodes in a cluster.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
PassThru	Indicates the output setting objects that you removed from the configuration. These objects are written to the pipeline for further processing.	false	true (ByPropertyName)	false
LegacyContext	For internal use only.	false	false	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
All	Indicates that you want to remove all connection settings, including the default settings, from the configuration repository.	true	true (ByPropertyName)	
DefaultSetting	Indicates that you want to remove the default storage system connection settings.	true	false	

Examples

Example 1: Removing named connection settings

```
PS C:\> Remove-SdStorageSystemSetting -StorageSystem
vmStorageServer,sqlServer -PassThru
```

This example syntax removes the specified vmStorageServer and sqlServer storage system connection settings.

Example 2: Removing all connection settings

```
PS C:\> Remove-SdStorageConnectionSetting -All -PassThru
```

This example syntax removes all the connection settings, including the default connection settings.

Example 3: Removing default storage connection settings

```
PS C:\> Remove-SdStorageConnectionSetting -DefaultSetting -PassThru
```

This example syntax removes the default storage system connection settings. You can use the default settings

to attempt a connection to any system that is not explicitly configured.

Example 4: Removing pipeline storage connection settings

```
PS C:\> $settings = Get-SdStorageConnectionSetting
$settings | Remove-SdStorageConnectionSetting -PassThru -confirm:$false
```

This example syntax retrieves the existing storage connection settings. In this case, they are "vmStorageServer" and "sharePointServer". Then the example pipes those names as the connection settings to be removed. Because the confirm value is false, there is no confirmation prompt and the PassThru switch means it outputs the objects removed.

Remove-SdVolume

Removes a volume from your storage system.

Syntax

```
Remove-SdVolume [-Volume] <String> [-StorageSystem] <String> [-
Session] <String> [-Host] <String>
```

Detailed Description

Removes a volume from your storage system. When you remove a volume using this cmdlet, Remove-SdVolume dismounts your volume, brings it offline, and deletes it. You can remove one volume at a time, only. You cannot remove volumes that are in a SnapMirror relationship. When you remove volumes, any active LUNs or shares on the volume are also removed. This cmdlet is supported in clustered Data ONTAP 8.2 and later. Related cmdlets: New-SdVolume

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Volume	Specifies the name of the volume you want to delete.	true	true (ByValue, ByPropertyName)	
StorageSystem	Specifies the name of the storage system from which you want to delete the volume. You can use the administration interface or the storage system name.	true	true (ByValue, ByPropertyName)	
Session		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Removing a volume

```
PS C:\> Remove-SdVolume -Volume TestRemoval01 -StorageSystem
172.17.165.39 -Verbose
```

This example syntax removes volume TestRemoval01 from storage system 172.17.165.39.

```
VERBOSE: volume 'TestRemoval01' will be removed
Remove-SdVolume
volume 'TestRemoval01' will be removed Do you want to continue?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help
(default is "Y"): y
VERBOSE: Removing volume: TestRemoval01
VERBOSE: Operation Successful.
```

Remove-SdVsphereSetting

Syntax

```
Remove-SdVsphereSetting [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Rename-SdIgroup

Renames your specified igroup.

Syntax

```
Rename-SdIgroup [-Name] <String> [-NewName] <String> [-StorageSystem]
<String> [-Session] <String> [-Host] <String>
```

Detailed Description

Renames your specified igroup.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the igroup you want to rename.	true	true (ByPropertyName)	
NewName	Specifies the new name of the igroup you are renaming.	true	true (ByPropertyName)	
StorageSystem	Specifies the storage system on which the igroup you want to rename is located.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Renaming an igroup

```
PS C:\> Rename-SdIgroup -Name IG_Demo -NewName IG_Demo_Renamed
-StorageSystem 172.17.168.13
```

This examples syntax renames an existing igroup.

Rename-SdSnapshot

Renames Snapshot copies created on a Windows disk or SMB share.

Syntax

```
Rename-SdSnapshot [-Path] <Object[]> [-Snapshot] <String> [-NewName]
<String> [-Session] <String> [-Host] <String> [-StorageSystem]
<String> [-VolumeName] <String> [-Snapshot] <String> [-NewName]
<String> [-Session] <String> [-Host] <String>
```

Detailed Description

Renames Snapshot backups created on a Windows disk or SMB share. Related cmdlets: New-SdSnapshot and Remove-SdSnapshot

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies a list of SMB shares or Windows volumes. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByPropertyName)	
Snapshot	Specifies the name of the Snapshot copy you want to rename.	true	true (ByPropertyName)	
NewName	Indicates the new name of the Snapshot copy.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
StorageSystem	Specifies the name of storage system name for the Snapshot copy you are renaming.	true	true (ByPropertyName)	
VolumeName	Specifies the storage system volume name for the Snapshot copy.	true	true (ByPropertyName)	

Examples

Example 1: Rename a single Snapshot copy

```
PS C:\> Rename-SdSnapshot -Path \\SQLCIFSServer\SalesDBShare -Snapshot  
MySnap -NewName MyNewSnap
```

This example renames a Snapshot copy from MySnap to MyNewSnap.

SnapshotName	AccessPoint	StorageSystemName	Volume
--------------	-------------	-------------------	--------

MyNewSnap	\\SQLCIFSServer\SalesDBShare	MyStorageSystem1	vol1
-----------	------------------------------	------------------	------

Example 2: Rename a Snapshot copy on two SMB shares

```
PS C:\> Rename-SdSnapshot -Path  
\\SQLCIFSServer1\SalesDBShare,\\SQLCIFSServer2\MarketDBShare -Snapshot  
MySnap -NewName MyNewSnap
```

This example renames a Snapshot copy located two SMB shares.

SnapshotName	AccessPoint	StorageSystemName	Volume
--------------	-------------	-------------------	--------

MyNewSnap	\\SQLCIFSServer1\SalesDBShare	MyStorageSystem1	vol1
MyNewSnap	\\SQLCIFSServer2\MarketDBShare	MyStorageSystem2	vol2

Example 3: Rename a Snapshot copy on a specified storage system and volume

```
PS C:\> Rename-SdSnapshot -StorageSystem MyStorageSystem1 -VolumeName  
vol1 -Snapshot MySnap -NewName MyNewSnap
```

This example renames a Snapshot copy from MySnap to MyNewSnap on a specified storage system and volume.

SnapshotName	AccessPoint	StorageSystemName	Volume
--------------	-------------	-------------------	--------

MyNewSnap		MyStorageSystem1	vol1
-----------	--	------------------	------

Example 4: Renames a single Snapshot copy on a disk

```
PS C:\> Rename-SdSnapshot -Path F: -Snapshot MySnap -NewName MyNewSnap
```

This example renames a Snapshot copy on the disk drive :F from MySnap to MyNewSnap.

Repair-SdAluaPaths

Repairs disks with no active/optimized ALUA paths.

Syntax

```
Repair-SdAluaPaths [-Paths] <String[]> [-Session] <String> [-Host]
<String>
```

Detailed Description

Repairs disks with no active/optimized ALUA paths.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Paths	Specifies the drive letter or mount point of the file system to fix a path.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name of the host.	false	true (ByPropertyName)	

Examples

Example 1: Repairing disks with no optimized ALUA paths

```
PS C:\> Repair-SdAluaPaths
```

This example syntax repairs disks with no optimized ALUA paths.

Restore-SdPlugInResource

Syntax

```
Restore-SdPlugInResource [-SnapInfo] <SnapInfo> [-MappingInfo]
<MappingInfo> [-Context] <String> [-Session] <String> [-Host]
<String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SnapInfo		true	true (ByPropertyName)	
MappingInfo		true	true (ByPropertyName)	
Context		false	false	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Restore-SdSnapshot

Restores files and directories from a primary or secondary Snapshot copy, on Windows disks or SMB shares.

Syntax

```
Restore-SdSnapshot [-Path] <Object[]> [-Snapshot] <String> [-StorageSystem] <String> [-VolumeName] <String> [-ForceRestore] <> [-Session] <String> [-Host] <String>
```

Detailed Description

Restores files and directories from a primary or secondary Snapshot copy, on Windows disks or SMB shares. When you are restoring from a Snapshot copy on a share, you can restore everything from that Snapshot copy. When you are restoring from a Snapshot copy in a SAN environment, you can restore disks only. When you are restoring from the secondary Snapshot copy, you must have a CIFS server on the secondary server. When you are restoring multiple files or directories under the same SMB share from your SnapVault secondary, you cannot specify the CIFS server name in the path by referring to IP/Name/Fully qualified domain name (FQDN.) You must specify the CIFS server name using only IP or Name or FQDN. Related cmdlets: New-SdSnapshot and Get-SdSnapshot

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the location of the files, directories, and disks for the Snapshot copies you want to restore. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByPropertyName)	
Snapshot	Specifies the Snapshot copy name you want to restored.	true	true (ByPropertyName)	
StorageSystem	Name of the storage system in which the Snapshot copy specified for the restore operation is located.	false	true (ByPropertyName)	
VolumeName	Name of the storage system volume in which the Snapshot copy specified for the restore operation is located.	false	true (ByPropertyName)	
ForceRestore	Indicates whether the Snapshot copy should be forcibly restored. If you want to overwrite existing versions of the files or directories you are restoring, this parameter is required.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Restoring a Snapshot copy on a SMB share from a Snapshot copy

```
PS C:\> Restore-SdSnapshot -Path "\\172.17.12.101\share\files.txt"
-Snapshot "snapshot_1"
```

This example restores the file named file.txt on SMB share "\\172.17.12.101\share" from specified Snapshot copy "snapshot_1".

Example 2: Restoring a file under a subfolder of a SMB share from a Snapshot copy

```
PS C:\> Restore-SdSnapshot -Path "\\172.17.12.101\share\dir1\file1.txt"
-Snapshot snapshot_1
```

This example restores the file on "\\172.17.12.101\share\dir1\file1.txt" from Snapshot copy snapshot_1.

Example 3: Restoring a directory with its contents under a SMB share from a Snapshot copy

```
PS C:\> Restore-SdSnapshot -Path "\\172.17.12.101\share\folder1\*"
-Snapshot "snapshot_1"
```

This example restores the directory named "folder1" and its contents from the specified Snapshot copy "snapshot_1".

Example 4: Restoring multiple files and directories under a SMB share from a Snapshot copy

```
PS C:\> Restore-SdSnapshot -Path
"\\172.17.12.101\share\file0.txt", "\\172.17.12.101\share\dir1\file1.txt", "
\\172.17.12.101\share\dir2\*", "\\172.17.12.101\share\dir3\*" -Snapshot
snapshot_1
```

This example restores a file named "file0.txt" under the root of the SMB share, a named "file1.txt" under directory "dir1", directory named "dir2" and "dir3" and their contents, from the Snapshot copy named "snapshot_1".

Example 5: Restoring a file on a SMB share from a Snapshot copy on the SnapVault secondary

```
PS C:\> Restore-SdSnapshot -Path "\\172.17.12.101\share\dir1\file1.txt"
-Snapshot "snapshot_1" -StorageSystem 172.17.165.29 -VolumeName
vaultdest_vol
```

This example restores a file named "file1.txt" under directory "dir1" from the Snapshot copy named "snapshot_1" on the SnapVault secondary storage system.

Example 6: Restoring a Snapshot copy on a disk from a Snapshot copy

```
PS C:\> Restore-SdSnapshot -Path E: -Snapshot "snapshot_1"
```

This example restores the Snapshot named file.txt on disk drive E: from specified Snapshot copy "snapshot_1".

Set-SdAluaStateMonitor

Sets the interval for monitoring ALUA path optimization.

Syntax

```
Set-SdAluaStateMonitor [-TimerInterval] <UInt32> [-Session] <String>
[-Host] <String>
```

Detailed Description

Sets the interval for monitoring ALUA path optimization.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
TimerInterval	Sets the time interval, in minutes, for the ALUA state monitor thread. Depending on the interval set, the system performs an optimization check for ALUA paths and repairs the paths as needed.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Example 1: Setting ALUA state monitor with timer interval

```
PS C:\> Set-SdAluaStateMonitor -TimerInterval 10
```

This example syntax sets the ALUA state monitor with the specified timer interval.

Set-SdDiskDriveLetter

Changes the Windows disk drive letter.

Syntax

```
Set-SdDiskDriveLetter [-OldDiskDriveLetter] <String> [-NewDiskDriveLetter] <String> [-Host] <String>
```

Detailed Description

Changes the Windows disk drive letter. This command is supported only for dedicated and shared disk, and not applicable for CSV disk.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
OldDiskDriveLetter	Specifies the drive letter where the disk is mounted currently using the format: D:, D:\	true	true (ByPropertyName)	
NewDiskDriveLetter	Specifies the new drive letter where the disk should be mounted using the format: D:, D:\	true	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Changing a Windows Disk Drive Letter

```
PS C:\> Set-SdDiskDriveLetter -OldDiskDriveLetter L:\ -NewDiskDriveLetter I:\
```

This example changes the drive letter of the specified Windows disk.

```
Change-SdDiskDriveLetter
The Disk drive letter will be changed from L:\ to I:\. Do you want to
continue?
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help
(default is "Y"):Y
Mount point of Disk which was on L:\ has changed to I:\
```

Set-SdSettings

Syntax

```
Set-SdSettings [-EnableUnsupportedCommands] <> [-Session] <String> [-
Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
EnableUnsupportedCommands		false	false	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

Set-SdSnapMirrorPolicyRule

Sets the rules for managing Snapshot retention on the SnapVault secondary storage system.

Syntax

```
Set-SdSnapMirrorPolicyRule [-SourceStorageSystem] <String> [-SourceStorageSystemVolume] <String> [-DestinationStorageSystem] <String> [-DestinationStorageSystemVolume] <String> [-SnapMirrorLabel] <String> [-Retention] <Int32> [-Preserve] <> [-WarnThreshold] <Int32> [-Session] <String> [-Host] <String>
```

Detailed Description

Sets the rules for managing Snapshot retention on the SnapVault secondary storage system. You can create new rules for customizing your virtual storage server level SnapMirror policy. Each SnapMirror policy can have up to 10 rules managing Snapshot copy retention. The default policy rules are daily or weekly Snapshot copy retention, or you can define your own retention rule. You cannot modify cluster-level SnapMirror or SnapVault policies with virtual storage server credentials. Related cmdlets: Remove-SdSnapMirrorPolicyRule, Get-SdSnapMirrorPolicyRule

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SourceStorageSystem	Specifies the primary storage system name containing the source volumes of the SnapMirror relationship for which you want to create or modify the SnapMirror policy rules. IP addresses are not supported.	true	true (ByValue, ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
SourceStorageSystemVolume	Specifies the source volume of the SnapMirror relationship for which you want to create or modify the SnapMirror policy rules.	true	true (ByPropertyName)	
DestinationStorageSystem	Specifies the secondary storage system name containing the destination volumes of the SnapMirror relationship for which you want to create or modify the SnapMirror policy rules. IP addresses are not supported.	true	true (ByValue, ByPropertyName)	
DestinationStorageSystemVolume	Specifies the destination volume of the SnapMirror relationship for which you want to create or modify the SnapMirror policy rules.	true	true (ByPropertyName)	
SnapMirrorLabel	Specifies the SnapMirror policy rule which you want to create or modify.	true	true (ByPropertyName)	
Retention	Specifies the Snapshot copy retention count.	true	true (ByPropertyName)	
Preserve	Specifies whether Snapshot copy preserve is enabled, which determines the behavior when the Snapshot copy retention count is reached on the SnapMirror Vault destination.	false	true (ByPropertyName)	
WarnThreshold	Specifies the warning threshold count.	false	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Setting SnapMirror policy rule information on the policy for a SnapMirror relationship

```
PS C:\> Set-SdSnapMirrorPolicyRule -SourceStorageSystem vs01
-SourceStorageSystemVolume src_vol01 -DestinationStorageSystem vs02
-DestinationStorageSystemVolume dest_vol01 -SnapMirrorLabel myWeekly
-Retention 8 -Preserve -WarnThreshold 3 -verbose -Confirm:$false
```

Create or modify the SnapMirror policy rule "myWeekly" on the policy of the specified relationship.

```
PS C:\Users\administrator.NEXTGEN> Set-SdSnapMirrorPolicyRule
-SourceStorageSystem vserver1 -SourceStorageSystemVolume snapvault_source
-DestinationStorageSystem vserver1 -DestinationStorageSystemVolume snapvault_dest
-SnapMirrorLabel test -Retention 8 -Preserve -WarnThreshold 3 -Verbose
Set-SdSnapMirrorPolicyRule
Set SnapMirror policy rule on vserver1 : snapvault_source ==> vserver1 :
snapvault_dest.
Do you want to continue?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help
(default is "Y"):
VERBOSE: Setting SnapMirror policy rules.
The setting SnapMirror policy rules operation is successful.
VERBOSE: Operation successful.
```

Set-SdSnapshot

Enables backup administrators to more easily attach labels to Snapshot copies and then select the secondary retention bucket by specifying the appropriate label.

Syntax

```
Set-SdSnapshot [-Snapshot] <String> [-Path] <Object[]> [-
SnapMirrorLabel] <String> [-Session] <String> [-Host] <String> [-
Snapshot] <String> [-StorageSystem] <String> [-VolumeName] <String[]>
[-SnapMirrorLabel] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Enables backup administrators to more easily attach labels to Snapshot copies and then select the secondary retention bucket by specifying the appropriate label. You can manage the secondary Snapshot copy retention using SnapMirror policies. A SnapMirror policy defines secondary retention buckets using various rules. A policy can have a maximum of 10 rules. These rules define how many Snapshot copies must be retained for a given Snapshot label and the behavior when the threshold is reached. You can also use rules to define what happens when you reach your Snapshot copy threshold. Based on your rule definitions, either the older Snapshot copies are deleted or your updates fail. You can use this cmdlet to set the Snapshot copy label based on the secondary retention requirements. You can use this cmdlet in clustered Data ONTAP 8.2 and later.

Relate cmdlets: Restore-SdSnapshot, Remove-SdSnapshot, Rename-SdSnapshot, New-SdSnapshot

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Snapshot	Indicates the name of the Snapshot copy to which you want the label to be attached. The Snapshot copy must exist in all the specified volumes.	true	true (ByPropertyName)	
Path	Specifies avolumes, logical disks, or a comma-separated list of SMB shares. You cannot mix a logical disk or mount point with SMB shares in the same input path.	true	true (ByPropertyName)	
SnapMirrorLabel	Specifies the label you want to attach to the Snapshot copy. If you specify an empty string, existing labels are removed.	true	true (ByPropertyName)	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
StorageSystem	Indicates the name of the storage system in which the Snapshot copy resides.	true	true (ByPropertyName)	
VolumeName	Specifies a comma-separated list of the volumes in which the specified Snapshot copy resides.	true	true (ByPropertyName)	

Examples

Example 1: Attaching a label to the specified Snapshot copy

```
PS C:\> Get-SdSnapshot -storagesystem prodvserver -volume voldb,vollog  
-snapshot salesdb_backup | Set-Sdsnapshot -label monthly
```

In this example syntax, you attach labels to the specified Snapshot copies.

Example 2: Making a Snapshot copy and attaching a label to it

```
PS C:\> New-SdSnapshot \\SQLFileserver\DBShare,\\SQLFileserver\LogShare
-Snapshot salesbackup -UpdateMirror | set-Sdsnapshot -Label weekly
```

In this example, you make a Snapshot copy of the specified shares, attach a weekly retention label, and update the mirror relationship.

Example 3: Getting secondary backups and changing their retention label

```
PS C:\> Get-SdSnapshot \\SQLFileserver\DBShare,\\SQLFileserver\LogShare
-GetSecondarySnapshots | set-Sdsnapshot -label monthly
```

In this example, you get secondary backups and change their retention labels.

Set-SdStorageConnectionSetting

Sets up the storage system transport protocols and credential settings.

Syntax

```
Set-SdStorageConnectionSetting [-StorageSystem] <String> [-HostOnly] <>
[-Protocol] <ConnectProtocol> [-Port] <UInt16> [-Credential]
<PSCredential> [-StorageSystemOSType] <String> [-PreferredIP] <String>
[-Timeout] <Int32> [-Force] <> [-LegacyContext] <> [-Session]
<String> [-Host] <String> [-StorageSystem] <String> [-
UseDefaultSetting] <> [-HostOnly] <> [-StorageSystemOSType] <String>
[-PreferredIP] <String> [-Timeout] <Int32> [-Force] <> [-
LegacyContext] <> [-Session] <String> [-Host] <String> [-
SyncClusterNodes] <> [-HostOnly] <> [-Protocol] <ConnectProtocol> [-
Port] <UInt16> [-StorageSystemOSType] <String> [-PreferredIP]
<String> [-Timeout] <Int32> [-Force] <> [-LegacyContext] <> [-
Session] <String> [-Host] <String> [-DefaultSetting] <> [-HostOnly]
<> [-Protocol] <ConnectProtocol> [-Port] <UInt16> [-Credential]
<PSCredential> [-StorageSystemOSType] <String> [-PreferredIP] <String>
[-Timeout] <Int32> [-Force] <> [-LegacyContext] <> [-Session]
<String> [-Host] <String>
```

Detailed Description

Sets up the storage system transport protocols and credential settings. so that you can make connections to a storage system or a virtual storage server later. These settings include the storage system name, port, transport type, user login, password, and timeout. If the settings already exist in the configuration repository for a specified storage system, those settings are replaced. When you are running this parameter in a clustered Data ONTAP environment, you only need to configure your storage connection settings once, rather than on each node of the cluster. If you want to set storage credentials only on a specific host, use the -HostOnly

parameter.Related cmdlets: Get-SdStorageConnectionSetting and Remove-SdStorageConnectionSetting

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem	Specifies the name or IP address of the storage system (storage controller or virtual storage server) for which you want to set connection settings.	true	true (ByPropertyName)	
HostOnly	Specifies that you want to set the storage system credentials only on the cluster node you specify. The default behavior is that HostOnly is not specified, and your storage credential settings are pushed to all the nodes in a cluster.	false	true (ByPropertyName)	
Protocol	Specifies the protocol type you want to use. By default, connections are attempted with a secure HTTPS connection to the storage controller, but it falls back to HTTP if necessary.Specify HTTPS, or HTTP to only use those protocols without any fallback to another protocol. Possible values are: HTTP, HTTPS, RPC.RPC is supported in 7-mode Data ONTAP version 8.0 and 8.1 storage systems only.	false	true (ByPropertyName)	DefaultWithFallback
Port	Specifies the port on which you want to connect to the storage controller. If you do not set this value, the default is 80 for HTTP and 443 for HTTPS. This parameter only applies to HTTP and HTTPS protocols.	false	true (ByPropertyName)	80/443
Credential	Designates the username and password you want to used to authenticate your connection to the storage system.Credentials are not required for the RPC protocol. You may specify credentials, but they will not be saved.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystemOSType	Indicates the storage system OS type. The available types are DataONTAP and Flashray. If no OS type is specified, SnapCenter Plug-in for Microsoft Windows attempts first to connect to a Data ONTAP storage system. If that attempt fails, it then attempts to connect to a FlashRay storage controller. This parameter is optional.	false	true (ByPropertyName)	
PreferredIP		false	true (ByPropertyName)	
Timeout		false	true (ByPropertyName)	
Force	Indicates that you want to override existing storage system connection settings. If -Force is not specified and storage system connection settings already exist, you will be prompted to indicate whether you want to overwrite existing settings.	false	true (ByPropertyName)	
LegacyContext	For internal use only.	false	false	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
UseDefaultSetting	Indicates that you want to use the default storage system connection settings for setting up a new storage system connection. To set up storage system connection using the default settings, enter: Set-StorageConnectionSetting -UseDefaultSetting -StorageSystem	true	true (ByPropertyName)	
SyncClusterNodes		true	false	
DefaultSetting	Sets the default credentials, protocol and port. To specify default values, run: Set-SdStorageConnectionSetting -DefaultSetting -Protocol <HTTPS> -Port <443> -Credential <name>	true	true (ByPropertyName)	

Examples

Example 1: Setting up named storage system connection settings

```
PS C:\> Set-SdStorageConnectionSetting -StorageSystem  
'VirtualStorageServer1' -Protocol https -Credential vsadmin -Port 443
```

This example saves the specified storage system connection settings into the configuration repository. These settings are later used to connect to the VirtualStorageServer1 virtual storage server storage system. You are prompted for the password using the given login of 'vsadmin'.

Storage System Name/IP : VirtualStorageServer1
User : vsadmin
Port : 443
Protocol : Https

Example 2: Saving default connection settings using PowerShell script code

```
PS C:\> $password = ConvertTo-SecureString "p@ssword" -AsPlainText -Force  
$vserver_cred = New-Object -TypeName  
System.Management.Automation.PSCredential -ArgumentList "vsadmin",  
$password  
  
Set-SdStorageConnectionSetting -DefaultSetting -Credential $vserver_cred  
-protocol http
```

This example saves the default settings for later connections to a storage system. It uses a previously configured credential, the HTTP protocol, and the default port.

User : vsadmin
Port : 80
Protocol : Http

Example 3: Modifying existing settings for a new port and protocol

```
PS C:\> $setting = Get-SdStorageConnectionSetting -StorageSystem  
'vmStorageServer'  
  
$setting.Port = 443  
$setting.Protocol = "Https"  
$setting | Set-SdStorageConnectionSetting
```

This example reads the existing settings for "vmStorageServer" and then saves the storage system connection settings back to the configuration with a new port.

Storage System Name/IP : 10.53.41.214
Name : vmStorageServer

Port : 443
Protocol : Https

Example 4: Modifying existing connection settings based on default settings

```
PS C:\> $settingDef = Get-SdStorageConnectionSetting -DefaultSetting

$settingDef.port = 443
$settingDef | Set-SdStorageConnectionSetting -StorageSystem
"exchangeStorageServer"
```

This example retrieves the original default settings and changes the port to 443. Then, it saves the storage system connection settings back to the configuration repository as the new settings used to connect to the "exchangeStorageServer" storage system.

Storage System Name/IP : exchangeStorageServer
User : vsadmin
Port : 443
Protocol : Https

Example 5: Setting default storage system connection settings using DefaultSetting

```
PS C:\> Set-SdStorageConnectionSetting -DefaultSetting -Protocol http
-Credential vsadmin
```

In this example syntax, you use the -DefaultSetting parameter to set your protocol to HTTP, and your user name to "vsadmin".

User : vsadmin
Port : 80
Protocol : Http

Example 6: Using the default settings to establish a storage system connection

```
PS C:\> Set-SdStorageConnectionSetting -UseDefaultSetting -StorageSystem
172.17.165.33
```

In example syntax, you use the -UseDefaultSetting parameter to apply the default credentials, protocol, and port to your storage system.

Storage System Name/IP : 172.17.165.33
User : vsadmin
Port : 80
Protocol : Http

Set-SdStorageSize

Expands or shrinks the size of a Windows disk.

Syntax

```
Set-SdStorageSize [-Path] <String> [-Size] <String> [-Session]
<String> [-Host] <String>
```

Detailed Description

Expands or shrinks the size of a Windows disk.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the drive letter or mount point of the file system you want to resize.	true	true (ByPropertyName)	
Size	Specifies the size to which you want to expand or shrink your Windows disk.	true	false	
Session	Specifies the session ID from Open-SmConnection.	false	true (ByPropertyName)	
Host	Specifies the name of the computer or host on which the SnapDrive service you want to perform the operation runs. The default is your local machine.	false	true (ByPropertyName)	

Examples

Example 1: Resizing a CSV

```
PS C:\> Set-SdStorageSize -path C:\ClusterStorage\Volume1\ -Size 1.1G
-Verbose
```

This example syntax resizes a CSV.

Example 2: Resizing a disk without a mount point

```
PS C:\> Set-SdStorageSize -Path D:\Mount -Size 10G -Shrink -Verbose
```

This example syntax resizes a drive without a mount point.

Example 3: Resize a drive

```
PS C:\> Set-SdStorageSize -Path M:\ -Size 10G -Verbose
```

This example syntax resizes a drive.

Set-SdVsphereSetting

Sets your vSphere user credentials, if vSphere is enabled.

Syntax

```
Set-SdVsphereSetting [-VsphereOrEsxHost] <String> [-Credential]  
<PSCredential> [-Session] <String> [-Host] <String>
```

Detailed Description

Sets your vSphere user credentials, if vSphere is enabled.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
VsphereOrEsxHost	Specifies your vSphere or ESX host, on which you want to set your vSphere credentials.	true	true (ByValue, ByPropertyName)	
Credential	Specifies the user name and password you want to use to access vSphere.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Start-SdVolumeCloneSplit

Starts your clone volume splitting operation.

Syntax

```
Start-SdVolumeCloneSplit [-Path] <Object[]> [-Session] <String> [-Host] <String>
```

Detailed Description

Starts your clone volume splitting operation.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the path to the clone volume you want to split.	true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	

Examples

Stop-SdVolumeCloneSplit

Stops your clone volume splitting operation.

Syntax

```
Stop-SdVolumeCloneSplit [-JobId] <String[]> [-StorageSystem] <String> [-Session] <String> [-Host] <String> [-JobId] <String[]> [-Path] <Object[]> [-Session] <String> [-Host] <String>
```

Detailed Description

Stops your clone volume splitting operation.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
JobId		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
StorageSystem		true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host	Specifies the name or IP address of the host on which you execute the operation. The default is your local machine.	false	true (ByPropertyName)	
Path	Specifies the path to the clone volume you want to stop splitting.	true	true (ByPropertyName)	

Examples

UnMap-SdLUNS

Syntax

```
UnMap-SdLUNS [-LunPath] <String[]> [-Initiators] <String> [-RestApiURL] <String> [-Session] <String> [-Host] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
LunPath		true	true (ByValue, ByPropertyName)	
Initiators		true	true (ByPropertyName)	
RestApiURL		true	true (ByPropertyName)	
Session		false	true (ByPropertyName)	
Host		false	true (ByPropertyName)	

Examples

SnapCenter data protection cmdlets

Add-SmCloneDataSet

Creates a new clone dataset.

Syntax

```
Add-SmCloneDataSet [-DataSetName] <String> [-Description] <String> [-  
PluginCode] <PluginCode> [-Policies] <String> [-CloneToInstance]  
<String> [-Resources] <Hashtable[]> [-Suffix] <String> [-  
SchedulerCredentialName] <String> [-ArchivedLocators] <Hashtable[]> [-  
EnableEmail] <> [-EmailPreference] <SmEmailNotificationPreference> [-  
CreateRemoteClone] <Boolean> [-CustomSnapshotFormat] <String> [-  
CustomText] <String>
```

Detailed Description

Creates a new clone resource group and adds resources to it. Additionally, you can attach policies, set notification settings for Event Management System (EMS) logs, AutoSupport, and email notification. You can also specify clone options including clone server and instance, mount options, and attach a suffix to the clone database name. If you are cloning to a SnapMirror or SnapVault destination, specify the secondary location.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
DataSetName	Specifies the new clone dataset name.	true	true (ByPropertyName)	
Description	Provides an optional description of the resource group you are creating.	false	true (ByPropertyName)	
PluginCode	Specifies the plug-in code of the host for which you are creating a clone resource group. Valid values are SCSQL and SCO.	true	true (ByPropertyName)	
Policies	Specifies one or more policies you want to attach to the dataset. Multiple policies can be added as a comma-separated list.	false	true (ByPropertyName)	
CloneToInstance	Specifies the SQL Server instance that you want to clone to. All databases in the clone resource group are cloned to this instance.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Resources	Specifies the resources you want to add to the clone resource group. You must provide the resource information in a hashtable, and it must contain the resource name and type, as well as the host on which the resource is located. For example, @{"Host"="localhost";"Type"="SQL Database";"Names"="Instance\Database"} Valid Type values are SQL Database and Oracle Database. You can include comma-separated values for Names.	true	true (ByPropertyName)	
Suffix	Provides a clone name suffix. All clones you create with one clone job are appended with the same suffix name.	false	true (ByPropertyName)	
SchedulerCredentialName		false	true (ByPropertyName)	
ArchivedLocators	Specifies in a hashtable the secondary storage system details for each unique primary storage system resource in the resource group. For example:- ArchivedLocators @{Primary="my_vs1:my_vol_iscsi";Secondary="my_vs1:my_vol_iscsi_SECONDARY"}	false	true (ByPropertyName)	
EnableEmail	Specifies whether email notification is enabled. The value is either True or False.	false	false	False
EmailPreference	Specifies when you will receive email notifications. Possible values: Always, Never, OnError, OnErrorOrWarning.	false	false	
CreateRemoteClone	Specifies whether or not you are creating a remote clone. The value is either True or False.	false	false	
CustomSnapshotFormat	Specifies the custom Snapshot copy naming format. For example, -CustomSnapshotFormat '\$CustomText\$ResourceGroup\$Policy\$HostName' -CustomText NetApp	false	true (ByPropertyName)	
CustomText	Specifies the custom text in the custom Snapshot copy naming format.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
EmailBody	Specifies the body of the email.	false	true (ByPropertyName)	
EmailFrom	Specifies the sender's email address.	true	true (ByPropertyName)	
EmailTo	Specifies the recipient's email address.	true	true (ByPropertyName)	
EmailSubject	Specifies the subject of the email.	true	true (ByPropertyName)	
EnableEmailAttachment	Specifies that you are adding an email attachment.	false	true (ByPropertyName)	

Examples

Example 1: Creating a new clone dataset from the primary and adding resources

```
Add-SmCloneDataSet -DataSetName payrollclone_dataset -Description
"Dataset for payroll database" -Policies clonefromprimary_ondemand
-Resources @{"Host"="vise-f3.sddev.mycompany.com";"Type"="SQLDatabases";"Names"="vise-
f3\SQLExpress\payroll,vise-f3\SQLExpress\finance"} -Suffix __clone
-CloneToInstance vise-f3\sqlexpress -AutoAssignMountPoint
```

This example syntax creates a new clone dataset from the primary and adds resources.

```
Description : Dataset for payroll database
CreationTime: 8/5/2015 2:18:38 PM
ModificationTime: 8/5/2015 2:18:38 PM
EnableEmail :
EmailSMTPServer :
EmailFrom :
EmailTo :
EmailSubject:
EnableSysLog:
ProtectionGroupType : Backup
EnableAsupOnFailure :
Policies: {}
HostResourceMapping : {}
Configuration : SMCoreContracts.SmConfiguration
LastBackupStatus:
VerificationServer :
EmailBody :
EmailNotificationPreference :
VerificationServerInfo : SMCoreContracts.SmVerificationServerInfo
SchedulerSQLInstance:
CustomText :
CustomSnapshotFormat:
SearchResources : False
ByPassRunAs : False
IsCustomSnapshot:
MaintenanceStatus : Production
PluginProtectionGroupTypes : {SMSQL}
Name: payrollclone_dataset
Type: Group
Id : 3
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Example 2: Creating a new clone from a secondary clone

```
Add-SmCloneDataSet -DataSetName clone_mdml_ds_mirror -Policies  
SMcln_full_logbkp_winsched -CloneToInstance "mva-m13-u25  
    " -Resources @{"Host"="mva-m13-u25";"Type"="SQL  
Database";"Names"="mva-m13-u25\TEST"} -ArchivedLocators  
@{Primary="rajr_vsl:rajr_vol_iscsi";Secondary=  
    "rajr_vsl:rajr_vol_iscsi_SECONDARY"} -Suffix "_RAJR"
```

This example syntax creates a new clone from a secondary clone using the -ArchivedLocators parameter.

Description :
CreationTime: 5/20/2015 11:10:04 AM
ModificationTime: 5/20/2015 11:10:04 AM
EnableEmail : False
EmailSMTPServer :
EmailFrom :
EmailTo :
EmailSubject:
EnableSysLog: False
ProtectionGroupType : Clone
EnableAsupOnFailure : False
Policies: {SMcln_full_logbkp_winsched}
HostResourceMapping : {}
Configuration : SMCoreContracts.SmCloneConfiguration
LastBackupStatus:
VerificationServer :
EmailBody :
EmailNotificationPreference : Always
VerificationServerInfo :
SchedulerSQLInstance:
CustomText :
CustomSnapshotFormat:
SearchResources : False
ByPassRunAs : False
IsCustomSnapshot: False
MaintenanceStatus : Production
Name: clone_mdml_ds_mirror
Type: Group
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0

Add-SmCloneJob

Creates a new clone job.

Syntax

```
Add-SmCloneJob [-CloneJobName] <String> [-PluginCode] <PluginCode> [-CloneToInstance] <String> [-CloneToHost] <String> [-Description] <String> [-ResourceGroupName] <String> [-Resources] <Hashtable[]> [-EnableAsupOnFailure] <Boolean> [-EnableSysLog] <Boolean> [-EnableEmail] <> [-EmailPreference] <SmEmailNotificationPreference>
```

Detailed Description

Creates a new clone job for the resource group. You can do the following to the clone job: add resources, define specific schedule policy, attach policies, set notification settings for Event Management System (EMS) logs, AutoSupport, send Email notification, specify clone options including clone type and instance, mount options, attach a suffix to the clone job name. Specify the secondary location if you are cloning to a SnapMirror or SnapVault destination.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
CloneJobName	Specifies the name of the clone job.	true	true (ByPropertyName)	
PluginCode	Specifies the plug-in code of the host for which you are creating a clone job. Valid values are SCSQL and SCO.	true	true (ByPropertyName)	
CloneToInstance	Specifies the SQL Server instance that you want to clone to. All databases in the clone resource group are cloned to this instance.	true	true (ByPropertyName)	
CloneToHost	Specifies the host to which you are cloning.	true	true (ByPropertyName)	
Description	Provides an optional description of the clone job you are creating.	false	true (ByPropertyName)	
ResourceGroupName	Provides an optional description of the clone job you are creating.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Resources	Specifies the resources you want to add to the clone resource group. You must provide the resource information in a hashtable, and it must contain the resource name and type, as well as the host on which the resource is located. For example, @{"Host"="localhost";"Type"="SQL Database";"Names"="Instance\Database"} Valid Type values are SQL Database and Oracle Database. You can include comma-separated values for Names.	false	true (ByPropertyName)	
EnableAsupOnFailure	Specifies whether to enable or disable AutoSupport on failure.	false	true (ByPropertyName)	
EnableSysLog	Specifies whether to enable or disable syslog in the storage system.	false	true (ByPropertyName)	
EnableEmail	Specifies whether to enable or disable email notifications.	false	false	
EmailPreference	Specifies when you will receive email notifications. Possible values: Always, Never, OnError, OnErrorOrWarning.	false	false	
AutoAssignMountPoint	Specifies that the file system mount point is assigned automatically.	false	true (ByPropertyName)	
AssignMountPointUnderPath	Specifies that the file system mount point is created automatically under the specified mount path.	false	true (ByPropertyName)	
CloneType		false	true (ByPropertyName)	
Suffix	Provides a clone job name suffix. The clone job you create is appended with the suffix name.	false	true (ByPropertyName)	
ArchivedLocators	Specifies the secondary storage system details for each of the unique primary storage system resource in the dataset. For example: -ArchivedLocators @{"Primary"="my_vs1:my_vol_iscsi";Secondary="my_vs1:my_vol_iscsi_SECONDARY"}	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
CustomSnapshotFormat	Specifies the custom Snapshot copy naming format. For example, -CustomSnapshotFormat '\$CustomText\$ResourceGroup\$Policy\$HostName' -CustomText NetApp	false	true (ByPropertyName)	
CustomText	Specifies the custom text in the custom Snapshot copy naming format.	false	true (ByPropertyName)	
SchedulerCredentialName		false	true (ByPropertyName)	
Schedules	Specifies in a hashtable the schedule for the clone job, including the policy name and the schedule type. For example, -Schedules @{ "PolicyName"="BackupPolicy"; "ScheduleType"="OneTime" } You can specify multiple schedules in a comma-separated list.	false	true (ByPropertyName)	
SchedulerType	Specifies the scheduler type. Possible values are Windows, SQL, and None.	false	true (ByPropertyName)	
SchedulerInstance		false	true (ByPropertyName)	
DeleteCloneOnScheduleExpiry	Specifies that the clone be deleted when the scheduled expiration time is reached.	false	true (ByPropertyName)	
PreScriptCommand	Prescript file UNC path with proper privileges for scripts accessibility, ('\\server\share\path\file' for Universal Naming Convention (UNC) names).	false	true (ByPropertyName)	
PreScriptArguments	Specifies the prescript arguments.	false	true (ByPropertyName)	
PostScriptCommand	Postscript file UNC path with proper privileges for scripts accessibility, ('\\server\share\path\file' for Universal Naming Convention (UNC) names).	false	true (ByPropertyName)	
PostScriptArguments	Specifies postscript arguments.	false	true (ByPropertyName)	
ScriptTimeout	Specifies the number of seconds before a script times out. The default is 60 seconds.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
EmailBody	Specifies the body of the email.	false	true (ByPropertyName)	
EmailFrom	Specifies the sender's email address.	true	true (ByPropertyName)	
EmailTo	Specifies the recipient's email address.	true	true (ByPropertyName)	
EmailSubject	Specifies the subject of the email.	true	true (ByPropertyName)	
EnableEmailAttachment	Specifies whether you are adding an email attachment.	false	true (ByPropertyName)	

Examples

Example 1: Adding a new clone job

```
Add-SmCloneJob -CloneJobName TestCLM1 -PluginCode SCSQL -CloneToInstance
"CsmDevSuman\INST1" -CloneToHost host.example.com -Description 'testing
clm'
    -Resources @{"Host"="CsmDevSuman";"Type"="SQL
Database";"Names"="CsmDevSuman\INST1\TrialDB"} -Suffix "_Clone_July_12"
-AutoAssignMountPoint
```

Example 2: Creating a clone job with hourly schedule policy

```
Add-SmCloneJob -Resources @{"Host"="Cluster50176661";"Type"="SQL
Database";"Names"="SQL12050176661\CLUSINST1\Cluster50176661_MDML_4"}
-CloneJobName 'CloneJob_08767' -PluginCode 'SCSQL' -CloneToInstance
'SQL12050176661\CLUSINST1' -CloneToHost 'Cluster50176661'
-autoassignmountpoint -suffix '_Clone_08767' -schedulingtype 'Windows'
-schedules @{"ScheduleType"="Hourly";"StartTime"="05/30/2019 6:00
AM";"EndTime"="05/30/2019 8:57 AM";"RepeatTask_Every_Hour"="01:00"}
```

Example 3: Creating a clone job with daily schedule policy


```
Add-SmCloneJob -Resources @{"Host"="Cluster50176661";"Type"="SQL
Database";"Names"="SQL12050176661\CLUSINST1\Cluster50176661_MDSL_4"}
-CloneJobName 'CloneJob_00970' -PluginCode 'SCSQL' -CloneToInstance
'SQL12050176661\CLUSINST1' -CloneToHost 'Cluster50176661' -suffix
'_Clone_00970' -archivedlocators
@{Primary="10.225.85.167:QA12050176661_1_MDSL_Data_Log_Vol";Secondary="C_8
4_173_CIT_SVM_2:QA12050176661_1_MDSL_Data_Log_Vol_SV"} -schedulingtype
'Windows' -assignmountpointunderpath
'D:\MSSQL11.CLUSINST1\MSSQL\DATA\Clone10971' -schedules
@{"ScheduleType"="Daily";"StartTime"="05/30/2019 6:25
AM";"EndTime"="05/30/2019 9:22 AM";"daysInterval"="1"} -clonetype 1
```

Example 4: Creating a clone job with weekly schedule policy

```
Add-SmCloneJob -Resources @{"Host"="Cluster50176661";"Type"="SQL
Database";"Names"="SQL12050176661\CLUSINST1\Cluster50176661_MDML_4"}
-CloneJobName 'CloneJob_54758' -PluginCode 'SCSQL' -CloneToInstance
'SQL12050176661\CLUSINST1' -CloneToHost 'Cluster50176661'
-autoassignmountpoint -suffix '_Clone_54758' -schedulingtype 'Windows'
-schedules @{"ScheduleType"="Weekly";"StartTime"="05/30/2019 6:30
AM";"EndTime"="05/30/2019 9:27 AM";"DaysOfTheWeek"="Thursday,Saturday"}
```

Example 5: Creating a clone job with monthly schedule policy

```
Add-SmCloneJob -Resources @{"Host"="Cluster50176661";"Type"="SQL
Database";"Names"="SQL12050176661\CLUSINST1\Cluster50176661_MDML_4"}
-CloneJobName 'CloneJob_02494' -PluginCode 'SCSQL' -CloneToInstance
'SQL12050176661\CLUSINST1' -CloneToHost 'Cluster50176661' -suffix
'_Clone_02494' -assignmountpointunderpath
'D:\MSSQL11.CLUSINST1\MSSQL\DATA\Clone10971' -schedulingtype 'Windows'
-schedules @{"ScheduleType"="Monthly";"StartTime"="05/30/2019 6:40
AM";"EndTime"="05/30/2019 9:37
AM";"MonthsofTheYear"="May, June";"DaysoftheMonth"="30,4,25"}
```

Add-SmCredential

Register the credential with SnapCenter Server.

Syntax

```
Add-SmCredential [-Name] <String> [-Type] <SmAuthMode> [-ClientSecret]
<SecureString> [-TenantId] <String> [-ClientId] <String> [-
InstanceName] <String> [-Credential] <PSCredential> [-
EnableSudoPrivileges] <Boolean> [-AuthenticationType]
<SmAuthenticationType> [-Force] <>
```

Detailed Description

Register the credential with SnapCenter Server. The credentials can be for other plug-ins or for other NetApp cloud storage.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the Credential Account.	true	true (ByPropertyName)	
Type	Specifies the authentication mode.	false	true (ByPropertyName)	
ClientSecret	Specifies the Azure NetApp client secret.	false	true (ByPropertyName)	
TenantId	Specifies the Azure NetApp tenant ID.	false	true (ByPropertyName)	
ClientId	Specifies the Azure NetApp client ID.	false	true (ByPropertyName)	
InstanceName		false	true (ByPropertyName)	
Credential		true	true (ByPropertyName)	
EnableSudoPrivileges		false	true (ByPropertyName)	
Force		false	true (ByPropertyName)	

Examples

Example 1: Create Credential

```
Add-SmCredential -Name RunAs1 -Type Windows -Credential $cred
```

Example 2: Create Azure Credential

```
$clientSecretText = 'd7c7656b-a07a-4es5-b19e-12376bdef493';  
$secureString = ConvertTo-SecureString $clientSecretText -AsPlainText  
-Force;  
Add-SmCredential -Name azure1 -Type AzureCredential -ClientSecret  
$secureString -TenantId c8f6a9b7-8cc7-445b-ac6f-f6e8e13f1ebb -ClientId  
ecadcfb7-b4f1-425f-ae93-bb1ee6084475
```

Note: Add-SmCredential with AzureCredential requires the following mandatory parameters ClientSecret, TenantId, and ClientId.

Example 3: Create AIX Credential

```
Add-SmCredential -Name RunAs2 -CredentialType AIX -Credential $cred
```

Example 4: Create Linux credential with SSH based authentication

```
Add-SmCredential -Name linuxSshBasedRunAs -Type Linux -AuthenticationType  
SshKeyBased -Username scanf -SSHPrivateKeyPath  
"C:\Users\Administrator\passwordfile.txt" -EnableSudoPrivileges $true
```

Note: Add-SmCredential with AuthenticationType as "SshKeyBased" requires the following mandatory parameters Username and SSHPrivateKeyPath(file path which contains private SSH key). By default AuthenticationType is "PasswordBased" which continues to take username and password.

Add-SmDomain

Register a domain with SnapCenter server.

Syntax

```
Add-SmDomain [-Name] <String> [-Protocol] <String> [-FQDN] <String>  
[-IPAddresses] <String> [-DCHostNames] <String>
```

Detailed Description

Register a trusted or untrusted domain with SnapCenter Server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	NETBIOS Name of the domain to be registered. The domain name must not contain special characters like forward slash (/), backslash (\), colon (:), asterisk (*), question mark (?), double quotation mark ("), left angle bracket (<), right angle bracket (>), and vertical bar (). The domain name must not begin with the special character dot (.).	true	true (ByPropertyName)	
Protocol	Protocol of the domain to be registered. By default the protocol value is LDAP. You can specify LDAPS to use the secured windows active directory communication.	false	true (ByPropertyName)	
FQDN	FQDN of the domain to be registered. Used for both LDAP and LDAPS protocol, when you provide the correct FQDN while adding or modifying the domain with LDAP protocol, the domain resolves and the IP address that you might have entered using the IPAddresses parameter is not stored.	true	true (ByPropertyName)	
IPAddresses	Domain IP Addresses of the disjoint domain to be registered. When you provide the correct FQDN while adding or modifying the domain, the domain resolves and the IP address is not stored.	false	true (ByPropertyName)	
DCHostNames	Domain host name of the disjoint or the same domain to be registered. For LDAPS protocol, DCHostNames is a mandatory parameter. The IP address should resolve and the user should not be permitted to manually provide the IP address.	false	true (ByPropertyName)	

Examples

Example 1: Register a trusted domain with SnapCenter Server with LDAP Protocol.

```
Add-SmDomain -Name ad12 -FQDN ad12.test.netapp.com
```

```
Added the domain ad12.  
Id : 0  
Name : ad12  
DomainFQDN : ad12.test.netapp.com  
DCHostIPAddresses :  
TrustedDomains :  
CreatedOn :  
ModifiedOn :  
Port : 389  
Protocol : LDAP  
DCHostNames:
```

Example 2: Register an untrusted domain with SnapCenter Server with LDAP Protocol.

```
Add-SmDomain -Name ad16 -FQDN ad16.test.netapp.com -IPAddresses  
192.160.0.44
```

```
Added the domain ad16.  
Id : 0  
Name : ad16  
DomainFQDN : ad16.test.netapp.com  
DCHostIPAddresses : 192.160.0.44  
TrustedDomains :  
CreatedOn :  
ModifiedOn :  
Port : 389  
Protocol : LDAP  
DCHostNames:
```

Example 3: Register a trusted domain with SnapCenter Server with LDAPS Protocol.

```
Add-SmDomain -Name ad19 -FQDN ad19.test.netapp.com -DCHostNames  
WS9K19DC.ad19.test.netapp.com -Protocol LDAPS
```

```
Added the domain ad19.
Id : 0
Name : ad19
DomainFQDN : ad19.test.netapp.com
DCHostIPAddresses :
TrustedDomains :
CreatedOn :
ModifiedOn :
Port : 636
Protocol : LDAPS
DCHostNames: WS9K19DC.ad19.test.netapp.com
```

Add-SmGroup

Adds an AD group or local group to SnapCenter.

Syntax

```
Add-SmGroup [-Domain] <String> [-Group] <SmString> [-RoleNames]
<SmString>
```

Detailed Description

Adds an Active Directory group or local group to SnapCenter.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Domain	The domain to which the group belongs to. Local group should skip this parameter.	false	true (ByPropertyName)	
Group	Single group or list of groups belonging to the same domain or local host.	true	true (ByPropertyName)	
RoleNames	Single or list of existing pre-canned or custom roles to which group should be added to. At least one role should be specified while adding the group.	true	true (ByPropertyName)	

Examples

Example 1: Adding a single group

```
Add-SmGroup -Group group1 -RoleNames role1,role2 -Domain domain1
```

Example 2: Adding multiple groups of same domain

```
Add-SmGroup -Group group1,group2 -RoleNames role1 -Domain domain1
```

Example 3: Adding local group

```
Add-SmGroup -Group LocalGroup1 -RoleNames role1
```

Add-SmGroupToRole

Adds a group to an existing role.

Syntax

```
Add-SmGroupToRole [-Group] <SmString> [-RoleName] <String> [-Domain] <String>
```

Detailed Description

Adds a group to an existing role. A group is an active directory group that contains users, computers, and other groups. You can use groups to easily assign permissions to a set of users.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Group	Specifies the group you want to add to the role.	true	true (ByPropertyName)	
RoleName	Specifies the name of the role to which you want to add a group.	true	true (ByPropertyName)	
Domain	Specifies the domain to which the group belongs.	false	true (ByPropertyName)	

Examples

Example 1: Adding a group to a role

```
Add-SmGroupToRole -RoleName SnapCenterAdmin -Domain sddev -Group "Domain Admins"
```

This example syntax adds the Domain Admins group to the SnapCenterAdmin role.

SnapCenterAdmin
Domain Admins

Add-SmHost

Registers a standalone host or cluster with SnapCenter.

Syntax

```
Add-SmHost [-HostType] <SmOperatingSystemType> [-HostName] <String> [-CredentialName] <String> [-Port] <UInt16> [-DoNotAddClusterNodes] <> [-SkipPreinstallChecks] <> [-Force] <>
```

Detailed Description

Registers a standalone host or cluster with SnapCenter. You must register hosts with SnapCenter. For example, SnapCenter must be registered before you can perform any data protection jobs. In addition, if no plug-ins are installed on the host you are adding, SnapCenter remotely deploys plug-ins, or upgrades the plug-ins as needed.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostType	Specifies the operating system of the host you are adding. Valid values are AIX, Windows, Linux, and vSphere. The default value is Windows. If you are managing a Windows VM containing RDM or VMDK storage, ensure that you add the vSphere host before creating a backup.	true	true (ByPropertyName)	
HostName	Specifies the name or IP of the cluster or standalone host you want to add.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
CredentialName	Specifies the name of the account that is required to perform application-specific operations in SnapCenter. You can use a credential account to perform application-specific operations within SnapCenter, such as remotely installing plug-ins. Use the Add-SmCredential cmdlet to create a credential account.	false	true (ByPropertyName)	
Port	Specifies the port you want to use for SnapCenter to host agent communication. The default is 8145. Ensure that the firewall is open on both SnapCenter and the remote host to enable host agent communication.	false	true (ByPropertyName)	
DoNotAddClusterNodes	Specifies not to include all nodes in the cluster. If you set the parameter to True, then only the specified host is added. The default value is False, which means that when you provide a cluster name, all nodes in the cluster are added and managed by SnapCenter.	false	true (ByPropertyName)	False
SkipPreinstallChecks	Specifies that host registration prechecks will not be triggered.	false	true (ByPropertyName)	
Force	Switch to disable validation of the host signature.	false	true (ByPropertyName)	

Examples

Example 1: Registering a host with SnapCenter

```
Add-SmHost -HostName C226030161613-1.srqatdom06.local -HostType Windows
-DoNotAddClusterNodes -CredentialName admin
```

This example syntax registers the specified Windows host with SnapCenter.

```
OsInfo : SMCoreContracts.SmOperatingSystemInfo
HostName : C226030161613-1.srqatdom06.local
IP : 10.232.193.208,fd20:8b1e:b255:8029:19a0:6c5e:ae99:79e0
Description:
HostId : 5
DomainName : srqatdom06.local
Version:
Port :
ClusterHost: False
ClusterName:
Members: {}
HostStatus : eHostUp
HostPluginInfos: {}
ColoHost : False
HostConfiguration : SMCoreContracts.SmConfiguration
DiscoverPlugin : False
HostUUID :
HostBIOSID :
HostMaintenanceStatus : Production
IsNLBEnabled : False
VerificationServers:
HypervisorType :
IsHypervisorConfigured : False
Preference : 0
OverallStatus : SMCoreContracts.SmHostOverallStatusInfo
IsCatalogHost : False
Name :
Type :
Id :
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts : {}
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
SizeOfSmObject :
```

Example 2: Registering a host where you deployed SnapCenter Plug-in for VMware vSphere OVA

```
Add-SmHost -HostType VSphere -HostName myHostname -CredentialName  
vmware_admin
```

This example syntax registers vSphere host with SnapCenter.

```
OsInfo : SMCoreContracts.SmOperatingSystemInfo
HostName : myHostname
IP : 10.225.97.14
Description:
HostId : 1
DomainName :
Version:
Port :
ClusterHost: False
ClusterName:
Members: {}
HostStatus : eHostUp
HostPluginInfos: {}
ColoHost : True
HostConfiguration : SMCoreContracts.SmConfiguration
DiscoverPlugin : False
HostUUID :
HostBIOSID :
HostMaintenanceStatus : Production
IsNLBEnabled : False
VerificationServers:
HypervisorType :
IsHypervisorConfigured : False
Preference : 0
OverallStatus : SMCoreContracts.SmHostOverallStatusInfo
IsCatalogHost : False
Name :
Type :
Id :
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts : {}
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
SizeOfSmObject :
```

Example 3: Registering an Exchange DAG with SnapCenter

```
Add-SmHost -HostName EXCH2016DAG -HostType Windows -CredentialName  
domain_admin -Verbose
```

This example syntax registers the specified Exchange DAG with SnapCenter.

Example 4: Registering an AIX host with SnapCenter

```
Add-SmHost -HostType AIX -HostName "aixhostname.fqdn.com" -CredentialName  
cred1
```

This example syntax registers the specified AIX host with SnapCenter.

```
OsInfo : SMCoreContracts.SmOperatingSystemInfo
HostName : aixhostname.fqdn.com
IP : 10.1.0.10
Description:
HostId : 79
DomainName : fqdn.com
Version:
Port :
ClusterHost: False
ClusterName:
Members: {}
HostStatus : eHostUp
HostPluginInfos: {}
ColoHost : True
HostConfiguration : SMCoreContracts.SmConfiguration
DiscoverPlugin : False
HostUUID :
HostBIOSID :
HostMaintenanceStatus : Production
IsNLBEnabled : False
VerificationServers:
HypervisorType :
IsHypervisorConfigured : False
Preference : 0
OverallStatus : SMCoreContracts.SmHostOverallStatusInfo
IsCatalogHost : False
Name :
Type :
Id :
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts : {}
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
SizeOfSmObject :
```

Add-SmPermissionToRole

Adds one or more permissions to a specified role.

Syntax

```
Add-SmPermissionToRole [-RoleName] <String> [-Permissions] <String>
```

Detailed Description

Adds one or more permissions to a specified role. Use the format <SnapCenter Role Name>:<Permission Name> where the SnapCenter role name is Dataset, Policy, Backup, Host, Storage Connection, Clone, Provision, Dashboard, Restore, Reports, Discovery, Plugin Install/Uninstall, Migration, Mount, and Unmount, and the permission name is create, read, update, delete and allow. The following permissions have the Enabled attribute code: Install/Uninstall, Restore, Dashboard, Reports, and Discovery. For example, if you want to give Host create permissions, you would enter: Add-SmPermissionToRole -Permission Host:Create

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
RoleName	Specifies the name of the role to which you want to add permissions.	true	true (ByPropertyName)	
Permissions	Specifies one or more permissions you want to add to a role. Use the format <SnapCenter Role Name>:<Permission Name>. Permissions include: create, read, update, delete and allow.	true	true (ByPropertyName)	

Examples

Example 1: Adding host read, update, and delete permissions to a role

```
Add-SmPermissionToRole -RoleName Admin -Permissions ("Host:read","Host:update","Host:delete")
```

This example syntax adds host read, update and delete permissions to the Admin role.

Example 2: Adding host create permissions to a role

```
Add-SmPermissionToRole -RoleName SnapCenterAdmin -Permissions Host:create
```

This example syntax adds host create permissions to the SnapCenterAdmin role.

SnapCenterAdmin
Host

Example 3: Adding dataset create permissions to a role

```
Add-SmPermissionToRole -RoleName SnapCenterAdmin -Permissions  
DataSet:create
```

This example syntax adds dataset create permission to the SnapCenterAdmin role.

SnapCenterAdmin
DataSet

Add-SmPlugin

Installs or upgrades a plug-in on one or more hosts.

Syntax

```
Add-SmPlugin [-HostNames] <String> [-PluginCodes] <UploadedPluginCode>  
[-PluginVersions] <Hashtable> [-SkipPreinstallChecks] <> [-Force] <>
```

Detailed Description

Installs or upgrades a plug-in on one or more hosts. You must use the Install-SmHostPackage cmdlet to install host plug-in packages and any specified plug-ins on a host before you can install or upgrade a SnapCenter plug-in using the Add-SmPlugin cmdlet.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostNames	Specifies the hosts on which you want to install or upgrade the plug-in. You can specify one host, or multiple, comma-separated host names. Host names must be entered using the format -HostNames @"hostname" when installing to a single host, or -HostNames @"hostname1", "hostname2" when installing to multiple hosts. You can specify the hostname using either the host FQDN or IP address.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
PluginCodes	Specifies the plug-ins you want to install or upgrade. Valid values are SCSQL, SCO, SCE and hana. For custom plug-ins, the value is the custom plug-in name. For example "CustomPlugin1".	true	true (ByPropertyName)	
PluginVersions	Specifies in a hash table the custom plug-in name and the version to add to a host. The PluginVersions parameter uses the format -PluginVersions @{"customplugin1" = "2.0"}	false	true (ByPropertyName)	
SkipPreinstallChecks	Specifies that installation prechecks will not be triggered.	false	true (ByPropertyName)	
Force	Internal switch.	false	true (ByPropertyName)	

Examples

Example 1: Installing SnapCenter Plug-in for Microsoft SQL Server on a host

```
Add-SmPlugin -HostNames @("mywinsrvr2012r2.mycompany.com") -PluginCodes SCSQL
```

This example syntax installs SnapCenter Plug-in for Microsoft SQL on the specified host.

Example 2: Installing SnapCenter Plug-in for Microsoft SQL Server on multiple hosts

```
Add-SmPlugin -HostNames @("mywinsrvr2012r2.mycompany.com",  
"my2winsrvr2012r2.mycompany.com") -PluginCodes SCSQL
```

This example syntax installs SnapCenter Plug-in for SQL Server on the two specified hosts.

Example 3: Adding or upgrading a custom plugin

```
Add-SmPlugin -HostNames myhostname -PluginCodes CustomPlugin  
-PluginVersions @{"CustomPlugin"="2.0"} -Verbose
```

This example syntax adds or upgrades the custom plug-in named "CustomPlugin", version 2.0 to a single host.

Add-SmPolicy

Creates a new backup policy.

Syntax

```
Add-SmPolicy [-PolicyName] <String> [-PolicyType] <SmPolicyType> [-  
PluginPolicyType] <PluginCode> [-Description] <String>
```

Detailed Description

Creates a new backup policy. A policy is a set of rules governing backup jobs. A Policy includes backup type, verification schedules, and pre-script and post-script arguments.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PolicyName	Specifies the name of the policy you are adding.	true	true (ByPropertyName)	
PolicyType	Specifies the policy type. Valid value is Backup.	true	true (ByPropertyName)	
PluginPolicyType	Specifies the type of plug-in. You need to specify a plug-in type because policies are settings that are specific to one type of plug-in. For example, if you want to create a policy for resources contained in a SnapCenter Plug-in for Microsoft SQL Server dataset, the plug-in types are SCSQL and SCO. Available plug-in policy types include SCSQL, SCO, SCU, HANA, SCW, SCE.	true	true (ByPropertyName)	
Description	Provides an optional description of the policy you are adding.	false	true (ByPropertyName)	
UtmType	Type of up to the minute (UTM) retention settings to apply to log backups. Possible values are days and count.	false	true (ByPropertyName)	
UtmCount	Up to the minute (UTM) retention by count.	false	true (ByPropertyName)	
UtmDays	Up to the minute (UTM) retention by days.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
SqlBackupType	SQL backup type. Possible values are LogBackup, FullBackup and FullBackupAndLogBackup.	true	true (ByPropertyName)	
DatabasesPerGroup	Maximum number of databases in a group. This is applicable only for full backup.	false	true (ByPropertyName)	
CopyOnlyBackup	Determines whether the full backup is a copy only backup.	false	true (ByPropertyName)	
AGBackupType	Availability Group backup type. Possible values are UsePreferredBackupReplica and UseSpecifiedBackupReplica.	false	true (ByPropertyName)	
AGBackupReplicaType	Availability Group backup replica type. Possible values are Primary, Secondary and All.	false	true (ByPropertyName)	
AGBackupPriorityMinimum	Availability Group backup minimum priority.	false	true (ByPropertyName)	
AGBackupPriorityMaximum	Availability Group backup maximum priority.	false	true (ByPropertyName)	
CreateLogFolderSnapshot	Creates a Log folder Snapshot copy.	false	true (ByPropertyName)	
EnableLogFolderSnapshotRetention	Enables log folder Snapshot copy retention.	false	true (ByPropertyName)	
DeleteLogFolderSnapshotInExcess		false	true (ByPropertyName)	
DeleteLogFolderSnapshotOlderThan	Deletes log folder Snapshot copies that are older than the specified number of days.	false	true (ByPropertyName)	
VerifyLogBackup	Enables log backup verification after backup.	false	true (ByPropertyName)	
DBCC_NOINDEX	DBCC options NOINDEX.	false	false	
DBCC_ALL_ERROR_MSGS	DBCC options ALL_ERRORMSGs.	false	true (ByPropertyName)	
DBCC_NO_INFOMSGS	DBCC options NO_INFOMSGs.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
DBCC_TABLOCK	DBCC options TABLOCK.	false	true (ByPropertyName)	
DBCC_PHYSICALONLY	DBCC options PHYSICALONLY.	false	true (ByPropertyName)	
UpdateSnapMirrorAfterbackup	Update SnapMirror copy after backup. This option is not applicable for SAP HANA policy of File-Based Backup type.	false	true (ByPropertyName)	
UpdateSnapVaultAfterbackup	Update SnapVault copy after backup. This option is not applicable for SAP HANA policy of File-Based Backup type.	false	true (ByPropertyName)	
MirrorVaultUpdateRetryCount	Number of retries to ensure SnapMirror or SnapVault update is triggered.	false	true (ByPropertyName)	
SnapVaultLabel	Label for SnapVault.	false	true (ByPropertyName)	
AllowSavedStateBackup	Allow saved state backup.	false	true (ByPropertyName)	
DeleteBackupInExcess	Delete backup in excess of specified days, it is applicable to only SnapCenter Plug-in for VMware vSphere, if it is used with other plug-ins it will be ignored.	false	true (ByPropertyName)	
DeleteBackupOlderThan	Delete backups older than specified days, it is applicable to only SnapCenter Plug-in for VMware vSphere, if it is used with other plug-ins it will be ignored.	false	true (ByPropertyName)	
PreScriptCommandVerification	Specifies the path of the prescript that should be run before the backup operation.	false	true (ByPropertyName)	
PreScriptArgumentsVerification	Specifies the prescript arguments.	false	true (ByPropertyName)	
PostScriptCommandVerification	Specifies the path of the postscript that should be run after the backup operation.	false	true (ByPropertyName)	
PostScriptArgumentsVerification		false	true (ByPropertyName)	
ScriptTimeoutVerification		false	true (ByPropertyName)	
ScheduleType	The schedule type. Possible values are None, Hourly, Weekly, Daily, and Monthly.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
RetentionSettings	Specifies in a hashtable the retention settings for the policy.	false	true (ByPropertyName)	
PreScriptCommand	Prescript file UNC path with proper privileges for scripts accessibility, ('\\\\server\\share\\path\\file' for Universal Naming Convention (UNC) names).	false	true (ByPropertyName)	
PreScriptArguments	Specifies the prescript arguments.	false	true (ByPropertyName)	
PostScriptCommand	Postscript file UNC path with proper privileges for scripts accessibility, ('\\\\server\\share\\path\\file' for Universal Naming Convention (UNC) names).	false	true (ByPropertyName)	
PostScriptArguments	Specifies postscript arguments.	false	true (ByPropertyName)	
ScriptTimeout	Specifies script timeout value in seconds.	false	true (ByPropertyName)	
VerificationScheduleType		false	true (ByPropertyName)	
DeleteCloneOnScheduleExpiry	Removes a clone during the last run of a scheduled job.If this parameter is not set, then the last run of a schedule also runs a clone life cycle and creates a cloned database.This parameter does not apply to jobs that are not scheduled or to one time job schedules.	false	true (ByPropertyName)	
BackupPolicyName	Specifies the backup policy name.	true	true (ByPropertyName)	
CloneType	Specifies the clone type. Possible values are Primary and Secondary.	false	true (ByPropertyName)	
VerifyOnSecondary	Specifies whether to verify on secondary or not.	false	false	
NumOfBackups	Number of backups to be verified.	false	false	
PluginParams		false	true (ByPropertyName)	
DominoChangeInfoPath		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
DominoDatabaseType		false	true (ByPropertyName)	
DominolniPath		false	true (ByPropertyName)	
DominoRestoreFilePath		false	true (ByPropertyName)	
DominoRestoreTime		false	true (ByPropertyName)	
Lotus		false	true (ByPropertyName)	
NotesExecDirectory		false	true (ByPropertyName)	
DominoDisableReplication		false	true (ByPropertyName)	
DominolgnoreCorruptedDB		false	true (ByPropertyName)	
DBMCLiCmd		false	true (ByPropertyName)	
HandleLogWriter		false	true (ByPropertyName)	
MaxDBBGServerPrefix		false	true (ByPropertyName)	
MaxDBUpdateHistogram		false	true (ByPropertyName)	
SQLCLiCmd		false	true (ByPropertyName)	
XUserEnable		false	true (ByPropertyName)	
DB2Cmd		false	true (ByPropertyName)	
SybaseISQLCmd		false	true (ByPropertyName)	
SybaseManifest		false	true (ByPropertyName)	
SybaseManifestDelete		false	true (ByPropertyName)	
SybaseManifestFormat		false	true (ByPropertyName)	
SybaseTranDump		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
SybaseTranDumpCompress		false	true (ByPropertyName)	
SybaseTranDumpFormat		false	true (ByPropertyName)	
BackupType	This is a SAP HANA database specific parameter. Specifies the type of SAP HANA backup. The possible values are FileBasedBackup and SnapshotBasedBackup.	true	true (ByPropertyName)	
OracleBackupType	Specifies the Oracle backup type. Backup types include Online, Offline mount, and Offline shutdown.	true	true (ByPropertyName)	
OracleBackupScope	This option is only valid when the backup type is Online. Backup scope values are Full, Data, and Log.	true	true (ByPropertyName)	
OracleSkipPDBSaveState	Enables you to skip PDB save state. This parameter is only available when you select Offline shutdown backup type. Values are True or False.	false	true (ByPropertyName)	
DeleteAllArchiveLogs	Prunes (deletes) all archive logs after Full or Log backups.	false	true (ByPropertyName)	
DeleteArchiveLogsOlderThan	Prunes (deletes) archive logs older than a specified number of days. This parameter supports the use decimals to enable you to specify a fraction of a day. For example, 2.5 represents 2 days and 12 hours, and 0.04 represents 1 hour.	false	true (ByPropertyName)	
DeleteArchiveLogFromAllDestination	This parameter enables pruning of archive logs on a specified destination. If the value is True, archive logs are pruned on all destinations. If the option is False, archive logs are pruned only on backed up destinations.	false	true (ByPropertyName)	
DeleteArchiveLogBackupInExcess	Deletes archive log backup in excess of the specified backup count.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
DeleteArchiveLogBackupOlderThan	Deletes archive log backups that are older than the specified number of days. This parameter supports the use decimals to enable you to specify a fraction of a day. For example, 2.5 represents 2 days and 12 hours, and 0.04 represents 1 hour.	false	true (ByPropertyName)	
CatalogBackupWithOracleRMAN	Specifies that you want to catalog backup using Oracle Recovery Manager (RMAN).	false	true (ByPropertyName)	
ScwBackupType	The SnapCenter Plug-in for Windows backup type. Values are ApplicationConsistent, FilesystemConsistent and CrashConsistent.	true	true (ByPropertyName)	
SceBackupType		true	true (ByPropertyName)	
UtmCounts		false	true (ByPropertyName)	
BackupTruncatedTransactionLog		false	true (ByPropertyName)	
BackupActiveCopies		false	true (ByPropertyName)	
BackupCopiesOnServer		false	true (ByPropertyName)	

Examples

Example 1: Creating a new hourly policy with scheduler type as SQL

```
Add-SmPolicy -PolicyName TESTPolicy - PluginPolicyType SCSQL -PolicyType Backup -SqlBackupType FullBackup -ScheduleType Hourly -Verbose -SchedulerType SQL
```

This example syntax creates a new hourly policy with the SQL scheduler type.

Example 2: Creating an Oracle policy that prunes all archive logs on all destinations, and deletes archive log backups in excess of 5


```
Add-SmPolicy -PolicyName 1 -PolicyType Backup -PluginPolicyType SCO
-OracleBackupType ONLINE -OracleBackupScope FULL -DeleteAllArchiveLogs
$true -DeleteArchiveLogFromAllDestination $true
-DeleteArchiveLogBackupInExcess 5
```

This example syntax creates an Oracle policy that prunes all archive logs on all destinations, and deletes archive log backups in excess of 5.

```
ApplySnapvaultUpdate: False
ApplyRetention      : False
RetentionCount      :
RetentionDays       :
ApplySnapMirrorUpdate : False
SnapVaultLabel      :
MirrorVaultUpdateRetryCount : 3
AppPolicies : {}
Description :
PreScriptPath      :
PreScriptArguments :
PostScriptPath      :
PostScriptArguments :
ScriptTimeout       : 60000
DateModified: 10/5/2015 2:17:57 PM
DateCreated : 10/5/2015 2:17:57 PM
Schedule: SMCoreContracts.SmSchedule
PolicyType : Backup
PluginPolicyType: SCO
Name: 1
Type:
Id : 99
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts : {}
SmOracleBackupType : ONLINE
SmOracleBackupScope: FULL
SmOraclePDBSaveState : True
PruneArchiveLog: True
PruneArchiveLogType: AllLogs
PruneArchiveLogOlderThanDays :
PruneArchiveLogDestinationType : AllDestinations
```

```

DeleteArchiveLogBackup : True
ArchiveLogBackupRetentionType : CountBase
DeleteArchiveLogBackupCounts : 5
DeleteArchiveLogBackupDays :
Name :
Type :
Id :
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts : {}

```

Example 3: Creating a policy for custom plugin DB2 with daily schedule type

```

Add-SMPolicy -PolicyName 'DB2_DAILY_POLICY' -PolicyType 'Backup'
-PluginPolicyType DB2-retentionsettings
@{"BackupType"="DATA";"ScheduleType"="DAILY";"RetentionCount"='3'}
-description 'DB2 daily schedule policy' -schedulescheduletype 'DAILY'

```

This example syntax creates a daily scheduled policy for custom plug-in DB2 with retention count 3

```

ApplyRetention : True
ApplySnapMirrorUpdate : False
ApplySnapvaultUpdate: False
MirrorVaultUpdateRetryCount : 3
RetentionCount : 3
RetentionDays : 0
SnapVaultLabel :
AppPolicies : {}
DateCreated : 8/22/2016 9:37:43 AM
DateModified: 8/22/2016 9:37:43 AM
Description : DB2 daily schedule policy
PluginPolicyType: DB2
PolicyType : Backup
PostScriptArguments :
PostScriptPath :
PreScriptArguments :
PreScriptPath :
Schedules : {}
Schedule: SMCoreContracts.SmSchedule

```

```
ScriptTimeout      : 60
Name: DB2_DAILY_POLICY
Type:
Id   : 18
Host:
UserName:
Passphrase  :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts     : {}
TaskName  :
Hosts     : {}
StartTime :
DaysOfMonth:
MonthsOfTheYear :
DaysInterval : 0
DaysOfTheWeek :
AllowDefaults : False
ReplaceJobIfExists : False
UserName    :
Password    :
SchedulerType : Daily
RepeatTask_Every_Hour :
IntervalDuration :
EndTime     :
LocalScheduler:
AppType     :
AuthMode    :
SchedulerSQLInstance : SMCoreContracts.SmObject
MonthlyFrequency :
ScheduleID: 0
PolicyId    : 18
PluginName  : DB2
PluginParams : SMCoreContracts.SmKeyValueCollection
SmSCBackupType : DataBackup
Name        :
Type        :
Id          :
Host        :
UserName    :
Passphrase  :
Deleted: False
Auth       : SMCoreContracts.SmAuth
IsClone: False
```

```
CloneLevel : 0  
Hosts      : {}
```

Example 4: Creating a new Windows backup policy

```
Add-SmPolicy -PolicyName scw_policy -PolicyType Backup -PluginPolicyType  
SCW -ScwBackupType CrashConsistent
```

This example syntax creates a new Windows backup policy.

```
ApplySnapvaultUpdate : False
ApplyRetention       : False
RetentionCount       :
RetentionDays:
ApplySnapMirrorUpdate: False
SnapVaultLabel       :
MirrorVaultUpdateRetryCount : 3
AppPolicies          : {}
Description           :
PreScriptPath:
PreScriptArguments    :
PostScriptPath        :
PostScriptArguments   :
ScriptTimeout: 60
DateModified          : 5/18/2016 6:36:24 PM
DateCreated           : 5/18/2016 6:36:24 PM
Schedule              : SMCoreContracts.SmSchedule
PolicyType            : Backup
PluginPolicyType      : SDW
Name                  : scw_policy
Type                  :
Id                    : 1
Host                  :
UserName              :
Passphrase            :
Deleted               : False
Auth                  : SMCoreContracts.SmAuth
IsClone               : False
CloneLevel            : 0
Hosts: {}
ScwBackupType         : CrashConsistent
Name                  :
Type                  :
Id                    :
Host                  :
UserName              :
Passphrase            :
Deleted               : False
Auth                  : SMCoreContracts.SmAuth
IsClone               : False
CloneLevel            : 0
Hosts                 : {}
```

Example 5: Creating a new backup policy for SnapCenter Plugin for SAP HANA backup of type FileBasedBackup

```
Add-SmPolicy -PolicyName newpol123 -PolicyType Backup -PluginPolicyType
HANA -BackupType FileBasedBackup
```

This example syntax creates a new backup policy for SnapCenter Plug-in for SAP HANA with FileBasedBackup as the backup type.

```
ApplyRetention      : True
ApplySnapMirrorUpdate : False
ApplySnapvaultUpdate: False
MirrorVaultUpdateRetryCount : 0
RetentionCount      : 7
RetentionDays       : 0
SnapVaultLabel      :
AppPolicies         : {}
DateCreated         : 3/23/2017 10:14:31 PM
DateModified        : 3/23/2017 10:14:31 PM
Description         :
PluginPolicyType    : hana
PolicyType          : Backup
PostScriptArguments :
PostScriptPath      :
PreScriptArguments  :
PreScriptPath       :
Schedules           : {}
Schedule: SMCoreContracts.SmSchedule
ScriptTimeout       : 60
Name: newpol123
Type:
Id : 39
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts     : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
```

```

Retention Settings
BackupType      : DATA
SchedulerType   : None
RetentionCount  : 7
RetentionDays   : 0
VerificationEnabled : False
NodeName:
PolicyId       : 39
PluginName     : hana
PluginParams    : SMCoreContracts.SmKeyValueCollection
SmSCBackupType : FileBasedBackup
Name          :
Type          :
Id            :
Host          :
UserName      :
Passphrase    :
Deleted: False
Auth          : SMCoreContracts.SmAuth
IsClone: False
CloneLevel    : 0
Hosts         : {}
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0

```

Example 6: Creating a new backup policy for SnapCenter Plugin for SAP HANA backup of type SnapshotBasedBackup

```

Add-SmPolicy -PolicyName hana_snapshotbased -PolicyType Backup
-PluginPolicyType HANA -BackupType SnapshotBasedBackup

```

This example syntax creates a new backup policy for SnapCenter Plug-in for SAP HANA with SnapshotBasedBackup as the backup type.

```

ApplyRetention : True
ApplySnapMirrorUpdate : False
ApplySnapvaultUpdate: False
MirrorVaultUpdateRetryCount : 3
RetentionCount : 7
RetentionDays : 0
SnapVaultLabel :
AppPolicies : {}

```

```
DateCreated : 3/23/2017 10:17:30 PM
DateModified: 3/23/2017 10:17:30 PM
Description :
PluginPolicyType: hana
PolicyType : Backup
PostScriptArguments :
PostScriptPath :
PreScriptArguments :
PreScriptPath :
Schedules : {}
Schedule: SMCoreContracts.SmSchedule
ScriptTimeOut : 60
Name: hana_snapshotbased
Type:
Id : 41
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
Retention Settings
BackupType : DATA
SchedulerType : None
RetentionCount : 7
RetentionDays : 0
VerificationEnabled : False
NodeName:
PolicyId : 41
PluginName : hana
PluginParams : SMCoreContracts.SmKeyValueCollection
SmSCBackupType : DataBackup
Name :
Type :
Id :
Host :
UserName :
Passphrase :
Deleted: False
```



```

Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts     : {}
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0

```

Example 7: Adding a policy with a retention based on number of days

```

Add-SMPolicy -PolicyName 'DB2_DAILY_POLICY' -PolicyType 'Backup'
-PluginPolicyType DB2-
    retentionsettings
@{"BackupType"="DATA";"ScheduleType"="DAILY";"RetentionDays"='3'} -
    description 'DB2 daily schedule policy' -schedulescheduletype 'DAILY'

```

Example 8: Creating a new daily policy with SnapLock Retention

```

Add-SmPolicy -PolicyName SCSQL_Snaplock_Policy -PluginPolicyType SCSQL
-PolicyType Backup -SqlBackupType FullBackupAndLogBackup -ScheduleType
Daily -retentionsettings @{"BackupType"="DATA";
"ScheduleType"="DAILY";"RetentionDays"="14";"SnapLockRetentionPeriod"=7;"S
napLockRetentionPeriodType"="Days";"SecondarySnapLockRetentionPeriod"=7;"S
econdarySnapLockRetentionPeriodType"="Days"},@{"BackupType"="LOG";
"ScheduleType"="DAILY";"RetentionCount"="2";"SnapLockRetentionPeriod"=7;"S
napLockRetentionPeriodType"="Days";"SecondarySnapLockRetentionPeriod"=7;"S
econdarySnapLockRetentionPeriodType"="Days"}

```

INFO: Specifying a retention period prevents the Snapshot copies from being deleted until the SnapLock retention period expires. This could lead to retaining a larger number of Snapshot copies than the count specified in the policy.

```

ApplySnapvaultUpdate : False
ApplyRetention       : True
RetentionCount       : 0
RetentionDays: 14
ApplySnapMirrorUpdate:
SnapVaultLabel       :
MirrorVaultUpdateRetryCount : 3
Retentions           : {, , , }
LastBackupStatus     :
LastBackupDate       :

```

```

IncludeAcls      :
AppPolicies     : {}
Description      :
PreScriptPath    :
PreScriptArguments :
PostScriptPath   :
PostScriptArguments :
ScriptTimeout    : 60
DateModified     : 8/13/2023 7:07:48 PM
DateCreated      : 8/13/2023 7:07:48 PM
Schedule         : SMCoreContracts.SmSchedule
PolicyType       : Backup
PluginPolicyType : SMSQL
InBuilt          : False
Schedules: {}
AllowMultipleSchedules : False
Name             : SCSQL_Snaplock_Policy
Type             :
Id               : 10
Host             :
UserName         :
Passphrase       :
Deleted          : False
Auth             : SMCoreContracts.SmAuth
IsClone          : False
CloneLevel       : 0
Hosts: {}
StorageName      :
ResourceGroupNames :
PolicyNames       :
Key              : 0
NsmObjectID      : 0
SizeOfSmObject    : SMCoreContracts.SmObjectSize

Schedules: Daily
Retention Settings
BackupType       : DATA
SchedulerType    : Daily
RetentionCount   : 0
RetentionDays    : 14
VerificationEnabled : False
NodeName         :
SnapLockRetentionPeriod : 7
SnapLockRetentionPeriodType : Days
SecondarySnapLockRetentionPeriod : 7
SecondarySnapLockRetentionPeriodType : Days

```

```

BackupType      : LOG
SchedulerType: Daily
RetentionCount   : 2
RetentionDays: 0
VerificationEnabled : False
NodeName :
SnapLockRetentionPeriod : 7
SnapLockRetentionPeriodType : Days
SecondarySnapLockRetentionPeriod : 7
SecondarySnapLockRetentionPeriodType : Days

BackupType      : LOG_SNAPSHOT
SchedulerType: None
RetentionCount   : 2
RetentionDays: 0
VerificationEnabled : False
NodeName :
SnapLockRetentionPeriod :
SnapLockRetentionPeriodType :

```

Example 9: Creating a policy for UnixFileSystems plug-in

```

Add-SMPolicy -PolicyName 'BackupPS_linuxfs201_LVM1_12648' -PolicyType
'Backup' -Description 'UnixFS backup policy' -PluginPolicyType
'UnixFileSystems'

```

This example syntax creates a new backup policy for UnixFileSystems Plug-in.

```

ApplyRetention : True
ApplySnapMirrorUpdate :
ApplySnapvaultUpdate: False
MirrorVaultUpdateRetryCount : 3
RetentionCount : 2
RetentionDays : 0
SnapVaultLabel :
AppPolicies : {}
DateCreated : 12/12/2023 8:29:27 AM
DateModified: 12/12/2023 8:29:27 AM
Description : UnixFS backup policy
PluginPolicyType: UnixFileSystems
PolicyType : Backup
PostScriptArguments :
PostScriptPath :
PreScriptArguments :

```

```

PreScriptPath    :
Schedules       : {}
Schedule: SMCoreContracts.SmSchedule
ScriptTimeout    : 60
Name: BackupPS_linuxfs201_LVM1_12648
Type:
Id   : 264
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone  : False
CloneLevel : 0
Hosts    : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject :
Schedules :
Retention Settings
BackupType : DATA
SchedulerType : None
RetentionCount : 2
RetentionDays : 0
VerificationEnabled : False
NodeName:
SnapLockRetentionPeriod :
SnapLockRetentionPeriodType :
PluginName : UnixFileSystems
PluginParams : SMCoreContracts.SmKeyValueCollection
PolicyId : 264
SmSCBackupType : DataBackup
Auth : SMCoreContracts.SmAuth
CloneLevel : 0
Deleted: False
Host :
Hosts : {}
Id :
IsClone: False
Key: 0
Name :
NsmObjectID: 0
Passphrase :

```

```

PolicyNames:
ResourceGroupNames :
StorageName:
Type      :
UserName  :

```

Example 10: Adding a SQL policy with object storage backup enabled

```

Add-SmPolicy -PolicyName SCSQL_ObjectStore_Policy -PluginPolicyType SCSQL
-PolicyType Backup -SqlBackupType FullBackup -ScheduleType Daily
-retentionsettings @{"BackupType"="DATA";
"ScheduleType"="DAILY";"RetentionDays"="14";"EnableObjectStorageBackup"="t
rue";"ObjectStorageBackupRetentionDays"="365"}

```

Add-SmProtectResource

Protects a resource so that it is available for backup, restore and clone.

Syntax

```

Add-SmProtectResource [-ArchivedLocators] <Hashtable[]> [-PluginCode]
<PluginCode> [-EnableEmail] <> [-EmailPreference]
<SmEmailNotificationPreference>

```

Detailed Description

Protects a resource so that it is available for backup, restore and clone.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ArchivedLocators	Specifies in a hashtable the secondary storage system details for each unique primary storage system resource in the resource group. For example:- ArchivedLocators @{Primary="my_vs1:my_vol_iscsi";Secondary="my_vs1:my_vol_iscsi_SECONDARY"}	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode	Specifies the plug-in code of the host for which you are creating a backup resource group. Valid values are SCSQL, SCW, and SCO.	true	true (ByPropertyName)	
EnableEmail	Specifies whether to enable or disable email.	false	false	
EmailPreference	Specifies when you will receive e-mail notifications. Possible values: Always, Never, OnError, OnErrorOrWarning.	false	false	
Resources	Specifies the resource you want to protect. You must provide the resource information in a key value format, and it must contain the resource name, type, and the host on which it is located. For example, -Resources@{"Host"="host.example.com"; "Type"="SQL Database"; "Names"="NB-MVA-DEV054\newdb"} For Oracle Database, the format is -Resources @{"Host"="host.example.com"; "Oracle Database"="db"}. For Oracle Application Volume, the format is -Resources @{"Host"="host.example.com"; "Application Volume"="appVol"}.	true	true (ByPropertyName)	
Description	Provides an optional description of the resource to be protected.	false	true (ByPropertyName)	
Tag	Enables you to apply a unique tag to help identify the resources. For example, you can add the tag "HR" to multiple resource groups. You can later search for all resource groups with the "HR" tag.	false	true (ByPropertyName)	
Policies	Specifies the list of policies associated with the resource group. Multiple policies can be added as a comma-separated list.	false	true (ByPropertyName)	
SchedulerCredentialName		false	true (ByPropertyName)	
SchedulerInstance	Specifies the SQL Server Instance where the schedule is created and managed. This is mandatory if the policy has SQL scheduler enabled.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
VerificationServers	Specifies the list of verification servers to be associated with the resource group. Multiple verification servers can be added as a comma-separated list. This parameter is only required when you want to verify backups for SnapCenter Plug-in for Microsoft SQL Server resource groups.	false	true (ByPropertyName)	
CustomSnapshotFormat	Specifies that you want to use a custom Snapshot copy naming format. By default, a timestamp is appended to the Snapshot copy name. Valid values for CustomSnapshotFormat are : \$ResourceGroup, \$Policy, \$HostName, \$ScheduleType, \$CustomText	false	true (ByPropertyName)	
CustomText	Specifies the custom text in the custom Snapshot copy naming format.	false	true (ByPropertyName)	
DeleteBackupForDetachPolicies		false	true (ByPropertyName)	
Schedules	Specifies the schedule parameters to be used in the resource group. Schedule parameters can include the policy name, schedule type, schedule start and end times. You can specify multiple schedules in a comma-separated list, for example:- Schedules @{"PolicyName"="BackupPolicy";"ScheduleType"="OneTime"}, @{"PolicyName"="BackupPolicy";"ScheduleType"="Hourly";"StartTime"=" 05/27/2016 6:13 PM";"EndTime"="05/27/2016 6:30 PM"}	false	true (ByPropertyName)	
SchedulerType	Specifies the scheduler type. Possible values are Windows, SQL, None.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
VerificationSchedules	Specifies the verification schedules you want to add to the resource. The verification schedule includes the following parameters:"VerificationType" which defines if and when verification is performed. The following values are available:VERIFY_SCHEDULEDVERIFY_AFTER_BACKUPNONE"ScheduleType" represents the schedule type for the verification."BackupScheduleType" represents the schedule type for the backup-VerificationServers "WIN-DVGQDI73QR6" needs to be provided in the above command if we are creating verification enabled resource group for SCSQL plugin.	false	true (ByPropertyName)	
BackupArchiveLogsAfterRecentMissingOne	This option is only valid for SCO plugin code. Specifies that you want to backup archive log files, which are created after the most recent missing archive log files and ignore the files created prior to it. If this option is not specified, then all archive log files except the missing archive log files are be backed up.	false	true (ByPropertyName)	
ExcludeArchiveLogPathsFromBackup	This option is only valid for SCO plugin code. Specifies the archive log destinations to be excluded from backup. Archive log files present in the specified destinations will be excluded during log backup. Multiple entries can be specified using comma separated list. For example: -ExcludeArchiveLogPathsFromBackup '/arch/logs/on/local/disk1, '/arch/logs/on/local/disk2'.	false	true (ByPropertyName)	
ConsistencyGroupSnapshot		false	true (ByPropertyName)	
ConsistencyGroupWafSync		false	true (ByPropertyName)	
ConsistencyGroupTimeOut		false	true (ByPropertyName)	
SnapShotCreateCommand		false	true (ByPropertyName)	
UseFileSystemConsistentSnapshot		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
UseSnapcenterWithoutFileSystemConsistency		false	true (ByPropertyName)	
PreAppQuiesceCmd		false	true (ByPropertyName)	
PostAppQuiesceCmd		false	true (ByPropertyName)	
AppQuiesceCmd		false	true (ByPropertyName)	
AppUnQuiesceCmd		false	true (ByPropertyName)	
PreAppUnQuiesceCmd		false	true (ByPropertyName)	
PostAppUnQuiesceCmd		false	true (ByPropertyName)	
PreExitCmd		false	true (ByPropertyName)	
PreSnapshotCmd		false	true (ByPropertyName)	
PostSnapshotCmd		false	true (ByPropertyName)	
ApplgnoreError		false	true (ByPropertyName)	
UseExternalSnapshot		false	true (ByPropertyName)	
ExternalSnapshotRegex		false	true (ByPropertyName)	
ConfigParams		false	true (ByPropertyName)	

Examples

Example 1: Protecting a resource

```
Add-SmProtectResource -PluginCode SCSQL -Policies BackupPolicy
-Resources @{"Host"="host.example.com";"Type"="SQL Database";"Names"="NB-MVA-DEV054\newdb"} -Description test -EnableAsupOnFailure -Schedules
@{"PolicyName"="p2";"ScheduleType"="Monthly";"daysOfTheMonth"="31";"monthsOfTheYear"="August,September";} -SchedulerRunAsName Administrator
-SchedulerType Windows
```

This example syntax protects a resource.

Example 2: Protecting a resource with hourly backup policy

```
Add-SmProtectResource -PluginCode SCSQL -Policies BackupPolicy
    -Resources @{"Host"="host.example.com";"Type"="SQL
Database";"Names"="NBMVA-DEV054\newdb"} -Description test
-EnableAsupOnFailure -schedules
@{"PolicyName"="BackupPolicy";"StartTime"="05/21/2019 7:54
PM";"EndTime"="05/21/2019 8:03
PM";"ScheduleType"="Hourly";"RepeatTask_Every_Hour"="03:00"}
-SchedulerType Windows
```

Example 3: Protecting a resource with daily backup policy

```
Add-SmProtectResource -PluginCode SCSQL -Policies BackupPolicy
    -Resources @{"Host"="host.example.com";"Type"="SQL
Database";"Names"="NBMVA-DEV054\newdb"} -Description test
-EnableAsupOnFailure -schedules
@{"PolicyName"="BackupPolicy";"StartTime"="05/21/2019 8:09
PM";"EndTime"="05/21/2019 9:18
PM";"ScheduleType"="Daily";"daysInterval"="1"} -SchedulerType Windows
```

Example 4: Protecting a resource with weekly backup policy

```
Add-SmProtectResource -PluginCode SCSQL -Policies BackupPolicy
    -Resources @{"Host"="host.example.com";"Type"="SQL
Database";"Names"="NBMVA-DEV054\newdb"} -Description test
-EnableAsupOnFailure -schedules
@{"PolicyName"="BackupPolicy";"StartTime"="05/21/2019 8:24
PM";"EndTime"="05/21/2019 8:41
PM";"ScheduleType"="Weekly";"DaysOfTheWeek"="Tuesday"} -SchedulerType
Windows
```

Example 5: Protecting a resource with monthly backup policy

```
Add-SmProtectResource -PluginCode SCSQL -Policies BackupPolicy
    -Resources @{"Host"="host.example.com";"Type"="SQL
Database";"Names"="NBMVA-DEV054\newdb"} -Description test
-EnableAsupOnFailure -schedules
@{"PolicyName"="BackupPolicy";"StartTime"="05/21/2019 8:51
PM";"EndTime"="05/21/2019 9:18
PM";"ScheduleType"="Monthly";"MonthsOfTheYear"="May, June";"daysOfTheMonth"
="21,26,16"} -SchedulerType Windows
```

Example 6: Protecting a HANA resource

```
Add-SmProtectResource -PluginCode HANA -Resources
@{"Host"="schana02.gdl.englab.netapp.com";"Uid"="MDC\R57"} -Policies
"HANAPOLICY"
```

This example protects a resource.

Tag :
ByPassRunAs : False
Configuration : SMCoreContracts.SmConfiguration
CreationTime: 02-Oct-19 21:47:16
CustomSnapshotFormat:
CustomText :
Description :
EmailBody :
EmailFrom :
EmailNotificationPreference :
EmailSMTPServer :
EmailSubject:
EmailTo :
EnableAsupOnFailure :
EnableEmail :
EnableSysLog:
HostResourceMapping : {}
IsCustomSnapshot:
LastBackupStatus:
MaintenanceStatus : Production
ModificationTime: 02-Oct-19 21:47:16
PluginProtectionGroupTypes : {hana}
Policies: {}
ProtectionGroupType : Backup
SchedulerSQLInstance:
SearchResources : False
VerificationServer :
VerificationServerInfo : SMCoreContracts.SmVerificationServerInfo
Name: schana02_gdl_englab_netapp_com_hana_MDC_R57
Type: Group
Id : 2
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0

Example 7: Protecting an Oracle Application Volume resource

```
Add-SmProtectResource -PluginCode SCO -Resources
@{"Host"="R8092776CF4V1.HNK2.com";"Application Volume"="appVol"} -Policies
"appVolPolicy"
```

This example protects an Oracle application volume resource named appVol.

```
Description :
    CreationTime: 11/4/2021 4:41:46 AM
    ModificationTime: 11/4/2021 4:41:46 AM
    EnableEmail :
    EmailSMTPServer :
    EmailFrom      :
    EmailTo        :
    EmailSubject:
    EnableSysLog:
    ProtectionGroupType : Backup
    EnableAsupOnFailure :
    Policies: {}
    HostResourceMapping : {}
    Configuration      : SMCoreContracts.SmConfiguration
    LastBackupStatus:
    VerificationServer  :
    EmailBody          :
    EmailNotificationPreference :
    VerificationServerInfo :
SMCoreContracts.SmVerificationServerInfo
    SchedulerSQLInstance:
    CustomText          :
    CustomSnapshotFormat:
    SearchResources    : False
    ByPassRunAs         : False
    IsCustomSnapshot:
    MaintenanceStatus   : Production
    PluginProtectionGroupTypes : {SCO}
    Tag :
    IsInternal          : True
    EnableEmailAttachment :
    VerificationSettings: {}
    BackupServers       : {}
    EnableRecentSnapshotNaming :
    Name: R8092776CF4V1_HNK2_com_appVol
    Type: Group
    Id : 178
```

```
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject : SMCoreContracts.SmObjectSize
```

Example 8: Protecting an Oracle Database resource

```
Add-SmProtectResource -PluginCode SCO -Resources
@{"Host"="R8092776CF4V1.HNK2.com";"Oracle Database"="DB16"} -Policies
"dbPolicy"
```

This example protects an Oracle database resource named DB16.

```
Description :
CreationTime: 11/4/2021 5:05:51 AM
ModificationTime: 11/4/2021 5:05:51 AM
EnableEmail :
EmailSMTPServer :
EmailFrom :
EmailTo :
EmailSubject:
EnableSysLog:
ProtectionGroupType : Backup
EnableAsupOnFailure :
Policies: {}
HostResourceMapping : {}
Configuration : SMCoreContracts.SmConfiguration
LastBackupStatus:
VerificationServer :
EmailBody :
EmailNotificationPreference :
VerificationServerInfo :
SMCoreContracts.SmVerificationServerInfo
SchedulerSQLInstance:
```

```

CustomText      :
CustomSnapshotFormat:
SearchResources : False
ByPassRunAs     : False
IsCustomSnapshot:
MaintenanceStatus : Production
PluginProtectionGroupTypes : {SCO}
Tag :
IsInternal      : True
EnableEmailAttachment :
VerificationSettings: {}
BackupServers   : {}
EnableRecentSnapshotNaming :
Name: R8092776CF4V1_HNK2_com_DB16
Type: Group
Id : 179
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject : SMCoreContracts.SmObjectSize

```

Add-SmReportSchedule

Creates a schedule to automatically trigger the reports based on the user privileges.

Syntax

```

Add-SmReportSchedule [-Name] <String> [-Plugin] <PluginCode> [-
ScheduleType] <String> [-DayOfTheWeek] <String> [-DayOfTheMonth]
<String> [-TriggerTime] <String> [-DocumentType] <String> [-
FromEmail] <String> [-Recipients] <String>

```

Detailed Description

Creates a report schedule, which generates daily, weekly, or monthly reports and sends it to the specified e-mail ids as per the user privileges.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specify the name to create a report schedule. A valid schedule name can only include alphabets, numbers, hyphens, and underscores.	true	true (ByPropertyName)	
Plugin	Specify the plug-in code to generate the report. For custom plug-ins, specify the custom plug-in name for example, hana, mysql. Specify 'all' to generate report for "All Plug-ins".	true	true (ByPropertyName)	
ScheduleType	Specify the schedule type. Valid values are 'daily', 'weekly', and 'monthly'.	true	true (ByPropertyName)	
DayOfTheWeek	Specify the day of the week to run the schedule. Valid values are 'monday', 'tuesday', 'wednesday', 'thursday', 'friday', 'saturday', 'sunday'. This field is applicable only for weekly schedule.	false	true (ByPropertyName)	
DayOfTheMonth	Specify the day (number) of the month to run the schedule. The value should be between 0 and 28. Enter zero to run the schedule for the last day of the month. This field is applicable only for monthly schedule.	false	true (ByPropertyName)	
TriggerTime	Specify the TriggerTime HH:MM in 24 Hours format.	true	true (ByPropertyName)	
DocumentType	Specify the format of the report in which report should be sent over e-mail. The valid formats are PDF and CSV. Add the comma separator if both the formats are needed.	true	true (ByPropertyName)	
FromEmail	Specify the e-mail address from which the report has to be sent.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Recipients	Specify the e-mail address to send the report. For multiple e-mail ID's, seperate them by comma.	true	true (ByPropertyName)	

Examples

Example 1: Creating a daily report schedule.

```
Add-SmReportSchedule -Name schedule1 -Plugin SCO -ScheduleType daily
-TriggerTime 1:10 -DocumentType "PDF,CSV" -FromEmail user@domain.com
-Recipients "user1@domain.com,user2@domain.com"
```

This example creates a daily schedule. Pass ScheduleType as 'Daily' and enter the TriggerTime at which the report needs to be generated every day. The report will contain data for the last 24 hours.

Example 2: Creating a weekly report schedule.

```
Add-SmReportSchedule -Name schedule1 -Plugin HANA -ScheduleType weekly
-DayOfTheWeek sunday -TriggerTime 1:10 -DocumentType PDF -FromEmail
user@domain.com -Recipients "user1@domain.com,user2@domain.com"
```

This example creates a weekly schedule for the custom plug-in. Pass the ScheduleType as 'Weekly', enter DayOfTheWeek and TriggerTime at which the schedule should run every week. The report will contain data for the last 7 days. For the 'Plugin' parameter, the custom plug-in name is specified instead of the plug-in code.

Example 3: Creating a monthly report schedule.

```
Add-SmReportSchedule -Name schedule1 -Plugin all -ScheduleType monthly
-DayOfTheMonth 11 -TriggerTime 1:10 -DocumentType CSV -FromEmail
user@domain.com -Recipients "user1@domain.com,user2@domain.com"
```

This example creates a monthly schedule. Pass ScheduleType as 'Monthly', enter DayOfTheMonth and TriggerTime to generate the report. If day of the month is selected as '06', the report will contain data from the last month 6th day to 6th day of the current month. If the day of the month is selected as 'Last Day', report will run on the last day of every month at the specified time. For 'Last Day', report will contain data from 1st of every month to the last day of the month.

Add-SmResource

Creates a custom plug-in resource or an Oracle plug-in application volume resource to be protected.

Syntax

```
Add-SmResource [-HostName] <String> [-PluginCode] <PluginCode> [-CredentialName] <String>
```

Detailed Description

Creates resource of a given ResourceType, where the resource types supported for a custom plug-in are specified as part of the plug-in description file or you can create an Oracle plug-in application volume resource. You can also use the cmdlet to associate storage of type Volume or Qtree or LUN with given resource. If required, you can also specify custom parameters specific to the resource along with a Run As account, which can be used by the plug-in to validate credentials to access the resource.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	The name of the SnapCenter Custom Plug-in or Oracle Plug-in host.	true	true (ByPropertyName)	
PluginCode	The name of the plug-in associated with the resource you are adding. Possible inputs include SCSQL, SCW, SCO, HANA and SCU.	true	true (ByPropertyName)	
CredentialName		false	true (ByPropertyName)	
ResourceType	The type of application object. This parameter does not accept any special characters or spaces. For example, instance, database, or a SAP HANA SingleContainer or MultipleContainers.	true	true (ByPropertyName)	
ResourceName	The name of the application object.	true	true (ByPropertyName)	
StorageFootPrint	Specifies the storage footprint. You enter the storage footprint using the following format: -StorageFootPrint @(@{"VolumeName"="Volume";"StorageSystem"="server"}, @{"LunPath"="/vol/Volume/LunPath";"StorageSystem"="server"}, @{"QtreeName"="qtree";"VolumeName"="volume";"StorageSystem"="server"})	true	true (ByPropertyName)	
MountPoints	Specifies the mount point for the resource.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ResourceSettings	Specifies the custom resource parameters. You enter ResourceSettings in a hastable using key-value pairs. For example:- ResourceSettings @{"Key1" = "Value1"; "Key2" = "Value2"}	false	true (ByPropertyName)	
DatabaseName	SAP HANA Database name.	true	true (ByPropertyName)	
SID	This is a SAP HANA database specific parameter. A SAP HANA system is identified by a unique 3 letter system ID (SID). For example, ABC.	true	true (ByPropertyName)	
UserStoreKeys	Comma separated list of SAP HANA database UserStoreKeys.	true	true (ByPropertyName)	
FileBackupPath	Location of the SAP HANA node on which the SAP HANA File-Based Backup is saved. This is required when EnableFileBackup parameter is set to 'Y'. The path must start with a forward slash and it cannot contain * ? \ " < > characters. If the path is not provided, SAP HANA will use the default path configured on the system. For example, /hana/shared/{SID}/HDB {INSTANCE_ID}/backup/data.	false	true (ByPropertyName)	
FileBackupPrefix	Prefix added to the File-Based Backup name. This is required when EnableFileBackup parameter is set to 'Y'. Use only letters, numbers, and underscores for the prefix of File-Based Backup name. If prefix is not provided, default value will be used.	false	true (ByPropertyName)	
OSDBUser		true	true (ByPropertyName)	
TenantDatabaseName	This is a SAP HANA database specific parameter. It is the name of the tenant database for SAP HANA MultiTenant Database Containers resource type.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
TenantType	This is a SAP HANA database specific parameter. This specifies the tenant type of SAP HANA MultiTenant Database Containers. SingleTenant as tenant type is deprecated. SingleTenant as tenant type is deprecated	true	true (ByPropertyName)	MultiTenant

Examples

Example 1: Adding a resource with a single storage volume

```
Add-SmResource -HostName 'host.example.com' -PluginCode 'DB2'
-ResourceName DB1-ResourceType Database -StorageFootPrint
(@{"VolumeName"="autoVol1";"StorageSystem"="vserver_scauto_primary"})
-Instance db2inst3
```

This example syntax adds a Resource Type Database of Custom plug-in DB2. In this example, the resource parent type is Instance, which is mandatory as indicated by the plug-in descriptor file used during Upload-SmPluginPackage.

Successfully added the following resource

```
PluginName : DB2
Uid: db2inst3\DB1
ParentUid  :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
LastBackupDate :
LastBackupStatus :
IsProtected: False
Name      : DB1
Type      : Database
Id : sccrhelldb2.sccore.test.com\DB2\db2inst3\DB1
Host      : sccrhelldb2.sccore.test.com
UserName   :
Passphrase :
Deleted: False
Auth       : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts      :
```

Example 2: Adding a resource with ResourceType instance containing multiple Storage Type LUNs

```
Add-SmResource -HostName 'host.example.com' -PluginCode 'DB2'
-ResourceName db2inst1 -ResourceType Instance -StorageFootPrint (@(
@{"VolumeName"="DB2_NONRECDB";"LunName"="DB2_NONRECDB";"StorageSystem"="vs
erver_scauto_primary"},
@{"VolumeName"="DB2_NONREC1DB";"LunName"="DB2_NONREC1DB";"StorageSystem"="
vserver_scauto_secondary"},
@{"VolumeName"="DB2_RECDB";"LunName"="DB2_RECDB";"StorageSystem"="vserver_
scauto_primary"}))
```

This example syntax adds a resource with ResourceType for custom Plug-in DB2. ResourceType instance does not have parent Resource type.

The resource named db2inst1 is spread across 3 LUNs of different volumes of same storage system.

Successfully added the following resource

```
PluginName : DB2
Uid: db2inst1
ParentUid  :
SmAppFiles :
SmAppFileStorageGroups : {, , }
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
LastBackupDate :
LastBackupStatus :
IsProtected: False
Name      : db2inst1
Type      : Instance
Id : sccrheldb2.sccore.test.com\DB2\db2inst1
Host      : sccrheldb2.sccore.test.com
UserName   :
Passphrase :
Deleted: False
Auth       : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts      :
```

Example 3: Adding a resource with storage type qtree

```
Add-SmResource -HostName 'sccorelinux188.sccore.test.com' -PluginCode
'DB2' -ResourceName DominoAutoDatabase -ResourceType Database
-StorageFootPrint (@{"QTREENAME
"="inventory_qtree";"VolumeName"="inventory_vol";"StorageSystem"="vserver_
scauto_primary"}) -Instance INST
```

This example syntax adds a resource type of Database for custom plug-in DB2, hosting data on qtree.

```
Cmdlet Output: Successfully added the following resource
PluginName : DummyPlugin
Uid: INST\DominoAutoDatabase
ParentUid  :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
LastBackupDate :
LastBackupStatus :
IsProtected: False
Name      : DominoAutoDatabase
Type      : Database
Id : sccorelinux188.sccore.test.com\DummyPlugin\INST\DominoA
utoDatabase
Host      : sccorelinux188.sccore.test.com
UserName  :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts     :
```

Example 4: Adding a resource that includes a LUN inside a qtree

```
Add-SmResource -HostName "10.236.164.10" -PluginCode HANA -ResourceType
instance -ResourceName mixedres -StorageFootPrint
@(@{"storagesystem"="10.232.206.5";"volumename"="dummyvol"},@{"storagesyst
em"="10.232.206.5";"volumename"="dummyvol2";"lunname"="luninsidevol"},@{"s
toragesystem"="10.232.206.5";"volumename"="dummyvol3";"lunname"="qtreeforl
un\luninsideqtree"},@{"storagesystem"="10.232.206.5";"volumename"="dummyvo
l4";"qtreename"="qtreeinsidevol"})
```

This example adds a resource with custom plug-in resource type that includes a LUN inside a qtree.

Successfully added the following resource

```
PluginName : hana
Uid: A12
ParentUid  :
SmAppFiles :
SmAppFileStorageGroups : {, , }
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
LastBackupDate :
LastBackupStatus :
IsProtected: False
Name      : mixedres
Type      : Instance
Id : sccrhelldb2.sccore.test.com\hana\A12
Host      : sccrhelldb2.sccore.test.com
UserName   :
Passphrase :
Deleted: False
Auth       : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts      :
```

Example 5: Adding a SAP HANA database of SingleContainer type

```
Add-SmResource -HostName 'mva-s63.gdl.englab.netapp.com' -PluginCode
'hana' -SID 'H14' -DatabaseName 'Manual_H14' -ResourceType SingleContainer
-StorageFootPrint
(@{"VolumeName"="R808267D015V1_NFS_H14_SC_DATA_10_229_37_43";"StorageSystem"="10.232.206.133"}) -UserStoreKeys 'KEY01' -OSDBUser 'SYSTEM'
```

This example syntax adds the SingleContainer resource type with specific SID and database name.


```

Successfully added the following resource
PluginName : hana
Uid: H14
ParentUid :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
pluginConfiguration: SMCoreContracts.SmSCSAPHANAResourceParameters
AutoDiscovered : False
IsSelectable : True
IsAuthenticated: False
IsProtected: False
ReplicationEnabled : False
LastBackupDate :
LastBackupStatus :
IsWindowsResource : False
Name : Manual_H14
Type : SingleContainer
Id : mva-s63.gdl.englab.netapp.com\hana\H14
Host : mva-s63.gdl.englab.netapp.com
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts :
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
SizeOfSmObject :

```

Example 6: Adding a SAP HANA Multitenant Database Container resource type

```

Add-SmResource -HostName 'schana02.gdl.englab.netapp.com' -PluginCode
'hana' -DatabaseName MDC -ResourceType MultipleContainers
-StorageFootPrint (
@{"VolumeName"="hana_data2";"StorageSystem"="storage_admin_1"}) -sid 'MT1'
-tenanttype 'MultiTenant' -userstorekeys 'USKMT1' -tenantdatabasename
'MT1' -osdbuser 'root'

```

This example adds a HANA MultiTenant Database Container resource with MultiTenant tenant type. Tenant database names will be detected during backup operations.

```
WARNING: TenantDatabaseName parameter is now deprecated for MultiTenant
database resource, the parameter will be ignored and auto discovered
internally.
Successfully added the following resource
PluginName : hana
Uid: MDC\MT1
ParentUid  :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
pluginConfiguration: SMCoreContracts.SmSCSAPHANAResourceParameters
AutoDiscovered : False
IsSelectable    : True
IsAuthenticated: False
LastBackupDate :
LastBackupStatus :
IsProtected: False
IsWindowsResource : False
Name   : MDC
Type   : MultipleContainers
Id : schana02.gdl.englab.netapp.com\hana\MDC\MT1
Host   : schana02.gdl.englab.netapp.com
UserName :
Passphrase :
Deleted: False
Auth   : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts :
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
SizeOfSmObject :
```

Example 7: Adding an Oracle Application Volume Resource with a volume,lun and qtree

```
Add-SmResource -HostName 'R8092776CF4V1.HNK2.com' -PluginCode 'SCO'
-ResourceName appVol -StorageFootPrint
@(@{"VolumeName"="vol_test1";"StorageSystem"="10.232.206.165"},@{"VolumeName"="vol_test2";"LunName"="lun_test1";"StorageSystem"="10.232.206.165"},@{"Qtreename"="qtree_test1";"VolumeName"="vol_test3";"StorageSystem"="10.232.206.165"})
```

This example adds an Oracle Application Volume Resource which contains a volume, lun, and qtree.

Successfully added the following resource

```
Uid: appVol
    SmAppFileStorageGroups : {, , }
    IsProtected: False
    LastBackupDate :
    LastBackupStatus :
    Name : appVol
    Type : Application Volume
    Id : R8092776CF4V1.HNK2.com\appVol
    Host : R8092776CF4V1.HNK2.com
    UserName :
    Passphrase :
    Deleted: False
    Auth : SMCoreContracts.SmAuth
    IsClone: False
    CloneLevel : 0
    Hosts :
    StorageName:
    ResourceGroupNames :
    PolicyNames:
    Key: 0
    NsmObjectID: 0
    SizeOfSmObject :
```

Example 8: Adding an Oracle Application Volume Resource with a single lun

```
Add-SmResource -HostName 'R8092776CF4V1.HNK2.com' -PluginCode 'SCO'
-ResourceName appVolLun -StorageFootPrint
@{"VolumeName"="vol_test2";"LunName"="lun_test1";"StorageSystem"="10.232.206.165"}
```

This example adds an Oracle Application Volume Resource which contains a single lun

Successfully added the following resource

```
Uid: appVolLun
    SmAppFileStorageGroups : {, , }
    IsProtected: False
    LastBackupDate :
    LastBackupStatus :
    Name : appVolLun
    Type : Application Volume
    Id : R8092776CF4V1.HNK2.com\appVolLun
    Host : R8092776CF4V1.HNK2.com
    UserName :
    Passphrase :
    Deleted: False
    Auth : SMCoreContracts.SmAuth
    IsClone: False
    CloneLevel : 0
    Hosts :
    StorageName:
    ResourceGroupNames :
    PolicyNames:
    Key: 0
    NsmObjectID: 0
    SizeOfSmObject :
```

Example 9: Adding Azure NonDataVolume Resource

```
Add-SmResource -HostName 'scspa2921191001.rtp.openenglab.netapp.com'
-PluginCode 'HANA' -ResourceType 'NonDataVolume' -ResourceName 'R71NDV'
-SID 'R71' -StorageFootPrint
@(@{"StorageConnectionId"=3;"CapacityPool"="manualqospool";"volumeName"="r
avi-16-all"})
```

This example adds an Azure NetApp Volume as NonDataVolume resource

```

Successfully added the following resource
PluginName : hana
Uid: NonDataVolume\R71\R71NDV
ParentUid :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
pluginConfiguration: SMCoreContracts.SmSCSAPHANAResourceParameters
AutoDiscovered : False
IsSelectable : True
IsAuthenticated: False
IsProtected: False
ReplicationEnabled : False
SubType:
LastBackupDate :
LastBackupStatus :
IsWindowsResource : False
Name : R71NDV
Type : NonDataVolume
Id :
scspa2921191001.rtp.openenglab.netapp.com\hana\NonDataVolume\R71\R71NDV
Host : scspa2921191001.rtp.openenglab.netapp.com
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts :
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
SizeOfSmObject :

```

Example 10: Adding Storage Plug-in Resource

```

Add-SmResource -HostName 'scspa2921191001.rtp.openenglab.netapp.com'
-PluginCode 'Storage' -ResourceType 'Storage Resource' -ResourceName
'StorageResTest' -StorageFootPrint
@(@{"VolumeName"="storage_vol_test2";"LunName"="storage_lun_test1";"Storag
eSystem"="10.212.06.135"})

```

This example adds a Storage Plug-in resource

```
Successfully added the following resource
PluginName : Storage
Uid: StorageResTest
ParentUid  :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
pluginConfiguration:
AutoDiscovered : False
IsSelectable   : True
IsAuthenticated: False
IsProtected: False
ReplicationEnabled : False
SubType:
LastBackupDate :
LastBackupStatus :
IsWindowsResource : False
Name : StorageResTest
Type : Storage Resource
Id : scspa2921191001.rtp.openenglab.netapp.com\Storage\StorageResTest
Host : scspa2921191001.rtp.openenglab.netapp.com
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts :
StorageName:
ResourceGroupNames :
PolicyNames:
PolicyMap :
Key: 0
NsmObjectID: 0
SizeOfSmObject :
StorageId :
```

Add-SmResourceGroup

Adds a resource group to SnapCenter.

Syntax

```
Add-SmResourceGroup [-ArchivedLocators] <Hashtable[]> [-ResourceGroupName] <String> [-BackupServers] <SmBackupServer> [-PluginCode] <PluginCode> [-EnableEmail] <> [-EmailPreference] <SmEmailNotificationPreference> [-isInternal] <Boolean>
```

Detailed Description

Creates a new resource group. You can specify policies, schedules, verification schedules, and resources to be associated with the resource group.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ArchivedLocators	Specifies in a hashtable the secondary storage system details for each unique primary storage system resource in the resource group. For example:- ArchivedLocators @{Primary="my_vs1:my_vol_iscsi";Secondary="my_vs1:my_vol_iscsi_SECONDARY"}	false	true (ByPropertyName)	
ResourceGroupName	Specifies the name of the resource group that you want create.	true	true (ByPropertyName)	
BackupServers		false	true (ByPropertyName)	
PluginCode	Specifies the plug-in code of the host for which you are creating a backup resource group. Valid values are SCSQL, SCW, and SCO.	true	true (ByPropertyName)	
EnableEmail	Specifies whether to enable or disable email.	false	false	
EmailPreference	Specifies when you will receive e-mail notifications.Possible values: Always, Never, OnError, OnErrorOrWarning.	false	false	
isInternal		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Resources	Specifies the list of resources to be associated with the resource group. You must provide the resource information in a hashtable, and it must contain the resource name and type, and the host on which it is located. For example, @{"Host"="localhost";"Type"="SQL Database";"Names"="Instance\Database"} For instance-level backup @{"Host"="localhost";"Type"="SQL Instance";"Names"="Instance"} For availability group backup @{"Host"="localhost";"Type"="SQL Availability Group";"Names"="AG1"} For custom plug-in @{"Host"="sccorelinux61.sscore.test.com";"Uid"="inst1\db1"} Valid Type values are: SQL Database, SQL Instance, SQL Availability Group. You can include comma-separated values for Names. For Oracle Database, the format is @{"Host"="host.example.com";"Oracle Database"="db1,db2,.."}. For Oracle Application Volume, the format is @{"Host"="host.example.com";"Application Volume"="appVol1,appVol2,.."}.	true	true (ByPropertyName)	
Description	Specifies an optional description for the new resource group.	false	true (ByPropertyName)	
Tag	Enables you to apply a unique tag to help identify the resource group.	false	true (ByPropertyName)	
Policies	Specifies the list of policies associated with the resource group. Multiple policies can be added as a comma-separated list.	false	true (ByPropertyName)	
SchedulerCredentialName		false	true (ByPropertyName)	
SchedulerInstance	Specifies the SQL Server Instance where the schedule is created and managed. This is mandatory if the policy has SQL scheduler enabled.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
VerificationServers	Specifies the list of verification servers to be associated with the resource group. Multiple verification servers can be added as a comma-separated list. This parameter is only required when you want to verify backups for SnapCenter Plug-in for Microsoft SQL Server resource groups.	false	true (ByPropertyName)	
CustomSnapshotFormat	Specifies that you want to use a custom Snapshot copy naming format. By default, a timestamp is appended to the Snapshot copy name. Valid values for CustomSnapshotFormat are : \$ResourceGroup, \$Policy, \$HostName, \$ScheduleType, \$CustomText	false	true (ByPropertyName)	
CustomText	Specifies the custom text in the custom Snapshot copy naming format.	false	true (ByPropertyName)	
DeleteBackupForDetachPolicies		false	true (ByPropertyName)	
Schedules	Specifies the schedule parameters to be used in the resource group. Schedule parameters can include the policy name, schedule type, schedule start and end times. You can specify multiple schedules in a comma-separated list, for example:- Schedules @{"PolicyName"="BackupPolicy";"ScheduleType"="OneTime"}, @{"PolicyName"="BackupPolicy";"ScheduleType"="Hourly";"StartTime"=" 05/27/2016 6:13 PM";"EndTime"="05/27/2016 6:30 PM"}	false	true (ByPropertyName)	
SchedulerType	Specifies the scheduler type. Possible values are Windows, SQL, None.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
VerificationSchedules	Specifies the verification schedules you want to add to the resource. The verification schedule includes the following parameters:"VerificationType" which defines if and when verification is performed. The following values are available:VERIFY_SCHEDULEDVERIFY_AFTER_BACKUPNONE"ScheduleType" represents the schedule type for the verification."BackupScheduleType" represents the schedule type for the backup-VerificationServers "WIN-DVGQDI73QR6" needs to be provided in the above command if we are creating verification enabled resource group for SCSQL plugin.	false	true (ByPropertyName)	
BackupArchiveLogsAfterRecentMissingOne	This option is only valid for SCO plugin code. Specifies that you want to backup archive log files, which are created after the most recent missing archive log files and ignore the files created prior to it. If this option is not specified, then all archive log files except the missing archive log files are be backed up.	false	true (ByPropertyName)	
ExcludeArchiveLogPathsFromBackup	This option is only valid for SCO plugin code. Specifies the archive log destinations to be excluded from backup. Archive log files present in the specified destinations will be excluded during log backup. Multiple entries can be specified using comma separated list. For example: -ExcludeArchiveLogPathsFromBackup '/arch/logs/on/local/disk1, '/arch/logs/on/local/disk2'.	false	true (ByPropertyName)	
ConsistencyGroupSnapshot		false	true (ByPropertyName)	
ConsistencyGroupWafSync		false	true (ByPropertyName)	
ConsistencyGroupTimeOut		false	true (ByPropertyName)	
SnapshotCreateCommand		false	true (ByPropertyName)	
UseFileSystemConsistentSnapshot	Specifies that you want to use file system consistent Snapshot copy.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
UseSnapcenterWithoutFileSystemConsistency		false	true (ByPropertyName)	
PreAppQuiesceCmd		false	true (ByPropertyName)	
PostAppQuiesceCmd		false	true (ByPropertyName)	
AppQuiesceCmd		false	true (ByPropertyName)	
AppUnQuiesceCmd		false	true (ByPropertyName)	
PreAppUnQuiesceCmd		false	true (ByPropertyName)	
PostAppUnQuiesceCmd		false	true (ByPropertyName)	
PreExitCmd		false	true (ByPropertyName)	
PreSnapshotCmd		false	true (ByPropertyName)	
PostSnapshotCmd		false	true (ByPropertyName)	
ApplgnoreError		false	true (ByPropertyName)	
UseExternalSnapShot		false	true (ByPropertyName)	
ExternalSnapshotRegex		false	true (ByPropertyName)	
ConfigParams		false	true (ByPropertyName)	
EmailBody	Specifies the body of the email.	false	true (ByPropertyName)	
EmailFrom	Specifies the sender's email address.	true	true (ByPropertyName)	
EmailTo	Specifies the recipient's email address.	true	true (ByPropertyName)	
EmailSubject	Specifies the subject of the email.	true	true (ByPropertyName)	
EnableEmailAttachment		false	true (ByPropertyName)	

Examples

Example 1: Creating a new resource group

```
Add-SmResourceGroup -ResourceGroupName DS26 -PluginCode SMSQL -Policies
BackupPolicy -Resources @{"Host"="host.example.com";"Type"="SQL
Database";"Names"="NB-MVA-DEV054\newdb"}
    -Description test -CustomSnapShotFormat abc -CustomText test
-SchedulerRunAsName admin
    -Schedules
@{"PolicyName"="BackupPolicy";"ScheduleType"="OneTime"},
@{"PolicyName"="BackupPolicy";"ScheduleType"="Hourly";"StartTime"="
05/27/2016 6:13 PM";"EndTime"="'05/27/2016 6:30 PM'"}
    -SchedulerType Windows
```

This example syntax creates a new resource group.

Example 2: Adding a resource group for custom plugin with consistency group Snapshot copy enabled

```
Add-SmResourceGroup -ResourceGroupName 'ResourceGroup_with_CG' -Resources
@(@{"Host"="sccorelinux61.sscore.test.com";"Uid"="inst1\db1"},@{"Host"="sc
corelinux61.sscore.test.com";"Uid"="inst1\db2"}) -Policies primaryonly
-consistencygroupsnapshot 1 -usesnapcenterwithoutfilesystemconsistency
-plugincode 'DB2'
```

This example syntax creates a resource group of two DB2 databases with Consistency Group Snapshot copies enabled.

Example 3: Creating a resource group with scheduled verification

```
Add-SmResourceGroup -ResourceGroupName DS26 -PluginCode SMSQL -Policies
BackupPolicy -Resources @{"Host"="host.example.com";"Type"="SQL
Database";"Names"="NB-MVA-DEV054\newdb"} -Description test
-CustomSnapShotFomat abc -CustomText test -SchedulerRunAsName admin
-Schedules @{"PolicyName"="BackupPolicy";"ScheduleType"="OneTime"},
@{"PolicyName"="BackupPolicy";"ScheduleType"="Hourly";"StartTime"="
05/27/2016 6:13 PM";"EndTime"="'05/27/2016 6:30 PM'"} -SchedulerType
Windows -VerificationSchedules
@{"BackupScheduleType"="Hourly";"DeferredBackupCount"="1";"VerificationTyp
e"="VERIFY_SCHEDULED";"VerifyOnSecondary"="true";"BackupPolicyName"="Backu
pPolicy";"ScheduleType"="Weekly";"DaysOfTheWeek"="Monday";"StartTime"="20-
Jul-16 6:42:12 PM";"EndTime"="25-Jul-16 6:42:12
PM"},@{"BackupScheduleType"="Daily";"DeferredBackupCount"="2";"Verificatio
nType"="VERIFY_SCHEDULED";"VerifyOnSecondary"="false";"BackupPolicyName"="
BackupPolicy";"ScheduleType"="Monthly";"StartTime"="20-Jul-16 6:42:12
PM";"EndTime"="25-Jul-16 6:42:12
PM";"MonthofTheYear"="March";"DaysoftheMonth"="15"} -ArchivedLocators
@{Primary="test_vserver:vol_ash_test";Secondary="test_vserver:test_vserver
_vol_ash_test_vault"}
```

This example syntax creates a new resource group with verification.

Example 4: Creating a resource group with scheduled verification and verification after backup

```
Add-SmResourceGroup -ResourceGroupName RG27 -PluginCode SCO -Policies
BackupPolicy -Resources @{"Host"="host.example.com";"Oracle
Database"="newdb"} -Description test -CustomSnapShotFomat abc -CustomText
test -SchedulerRunAsName admin -Schedules
@{"PolicyName"="BackupPolicy";"ScheduleType"="Weekly";"DaysOfTheWeek"="Sun
day"},
@{"PolicyName"="BackupPolicy";"ScheduleType"="Monthly";"StartTime"="
05/27/2016 6:13 PM";"EndTime"="05/27/2016 6:30
PM";"MonthsofTheYear"="March";"DaysoftheMonth"="2"} -SchedulerType Windows
-VerificationSchedules
@{"BackupScheduleType"="Weekly";"DeferredBackupCount"="1";"VerificationTyp
e"="VERIFY_SCHEDULED";"VerifyOnSecondary"="true";"BackupPolicyName"="Backu
pPolicy";"ScheduleType"="Weekly";"DaysOfTheWeek"="Monday";"StartTime"="20-
Jul-16 6:42:12 PM";"EndTime"="25-Jul-16 6:42:12
PM"},@{"BackupScheduleType"="Monthly";"DeferredBackupCount"="2";"Verificat
ionType"="VERIFY_AFTER_BACKUP";"VerifyOnSecondary"="false";"BackupPolicyNa
me"="BackupPolicy"}
```

This example syntax creates a new resource group with scheduled verification and verification after backup.

Example 5: Adding an Always On availability group

```
Add-SmResourceGroup -ResourceGroupName AG_Prod -Resources
@{"Host"="myag1";"Type"="SQL Availability Group";"Names"="AG_Prod"}
-PluginCode SMSQL -Policies "SQL Daily Full" -Schedules
@{"PolicyName"="SQL Daily
Full";"ScheduleType"="Daily";"StartTime"="10/28/2017 6:13
PM";"EndTime"="" } -schedulerType SQL -SchedulerInstance SQL1
```

This example syntax adds an Always On availability group named AG_Prod to a SnapCenter resource group.

Example 6: Adding a resource group for HANA plugin

```
Add-SmResourceGroup -ResourceGroupName '43RG57' -Resources
@{"Host"="schana02.gdl.englab.netapp.com";"Uid"="MDC\R57"} -plugincode
'hana' -Policies 'HANAPOLICY'
```

This example adds a resource group for HANA plug-in.

Tag :
ByPassRunAs : False
Configuration : SMCoreContracts.SmConfiguration
CreationTime: 02-Oct-19 21:38:06
CustomSnapshotFormat:
CustomText :
Description :
EmailBody :
EmailFrom :
EmailNotificationPreference :
EmailSMTPServer :
EmailSubject:
EmailTo :
EnableAsupOnFailure :
EnableEmail :
EnableSysLog:
HostResourceMapping : {}
IsCustomSnapshot:
LastBackupStatus:
MaintenanceStatus : Production
ModificationTime: 02-Oct-19 21:38:06
PluginProtectionGroupTypes : {hana}
Policies: {}
ProtectionGroupType : Backup
SchedulerSQLInstance:
SearchResources : False
VerificationServer :
VerificationServerInfo : SMCoreContracts.SmVerificationServerInfo
Name: 43RG57
Type: Group
Id : 1
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject :

Example 6: Creating a resource group and attaching hourly backup policy

```
Add-SmResourceGroup -ResourceGroupName ResourceGroup1 -Description test
-Resources @{"Host"="C226030161613-1";"Type"="SQL
Database";"Names"="C226030161613-1\NAMEDINST1\C226030161613_1_SDML_1"}
-Policies Full_Backup_Log_Backup_Windows_Schedule_Policy_54615264
-schedulertype 'Windows' -plugincode 'SCSQL' -schedules
@{"PolicyName"="Hourly_Full_log_Backup_Wtih_Ver_Policy_09959383";"StartTim
e"="05/21/2019 7:54 PM";"EndTime"="05/21/2019 8:03
PM";"ScheduleType"="Hourly";"RepeatTask_Every_Hour"="03:00"}
```

Example 7: Creating a resource group and attaching daily backup policy

```
Add-SmResourceGroup -ResourceGroupName ResourceGroup1 -Description
'Backup ResourceGroup with Full and log backup policy with Daily SQL
schedule' -Resources @{"Host"="C226030161613-1";"Type"="SQL
Database";"Names"="C226030161613-1\NAMEDINST1\C226030161613_1_SDML_1"}
-Policies Full_Backup_Log_Backup_SQL_Schedule_Policy_54615264
-schedulerinstance 'C226030161613-1\NAMEDINST1' -plugincode 'SCSQL'
-schedulerrunasname 'DomainRunAs_54615264' -schedulertype 'SQL' -schedules
@{"PolicyName"="Daily_Full_Log_Backup_With_Ver_Policy_09959383";"StartTime
"="05/21/2019 8:09 PM";"EndTime"="05/21/2019 9:18
PM";"ScheduleType"="Daily";"daysInterval"="1"}
```

Example 8: Creating a resource group and attaching weekly backup policy

```
Add-SmResourceGroup -ResourceGroupName ResourceGroup1 -Description
'Backup ResourceGroup with Full and log backup policy with hourly windows
schedule' -Resources @{"Host"="C226030161613-1";"Type"="SQL
Database";"Names"="C226030161613-1\NAMEDINST1\C226030161613_1_SDML_1"}
-Policies Full_Backup_Log_Backup_Windows_Schedule_Policy_54615264
-schedulertype 'Windows' -plugincode 'SCSQL' -schedules
@{"PolicyName"="Weekly_Full_Backup_With_Ver_Policy_09959383";"StartTime"="
05/21/2019 8:24 PM";"EndTime"="05/21/2019 8:41
PM";"ScheduleType"="Weekly";"DaysOfTheWeek"="Tuesday"}
```

Example 9: Creating a resource group and attaching monthly backup policy


```
Add-SmResourceGroup -ResourceGroupName ResourceGroup1 -Description
'Backup ResourceGroup with Full and log backup policy with hourly windows
schedule' -Resources @{"Host"="C226030161613-1";"Type"="SQL
Database";"Names"="C226030161613-1\NAMEDINST1\C226030161613_1_SDML_1"}
-Policies Full_Backup_Log_Backup_Windows_Schedule_Policy_54615264
-schedulertype 'Windows' -plugincode 'SCSQL' -schedules
@{"PolicyName"="Monthly_Full_Backup_With_Ver_Policy_09959383";"StartTime"=
"05/21/2019 8:51 PM";"EndTime"="05/21/2019 9:18
PM";"ScheduleType"="Monthly";"MonthsOfTheYear"="May, June";"daysOfTheMonth"
="21,26,16"}
```

Example 10: Creating a new resource group in SCE plugin

```
Add-SmResourceGroup -ResourceGroupName RGName -Description test -Policies
BackupPolicy -backupservers replicaServers -plugincode SCE -Resources
@{"Host"="host.example.com";"Type"="SnapCenter Plug-in for Microsoft
Exchange Server";"Names"="host.example.com4\newdb"}
```

Example 11: Creating a new resource group for Oracle Plug-in

```
Add-SmResourceGroup -ResourceGroupName 'mixedRG' -Resources
@(@{"Host"="R809278EA03V1.HNK2.com";"Oracle
Database"="DB11,DB12"},@{"Host"="R8092776CF4V1.HNK2.com";"Application
Volume"="appVol1,appVol2"}) -plugincode 'SCO' -Policies 'testPolicy'
```

This example syntax creates a new resource group for Oracle Plug-in containing database and application volume resources.

Example 12: Creating a new resource group for Oracle Plug-in

```
Add-SmResourceGroup -ResourceGroupName 'appVolRG' -Resources
@{"Host"="R8092776CF4V1.HNK2.com";"Application Volume"="appVol1,appVol2"}
-plugincode 'SCO' -Policies 'testPolicy'
```

This example syntax creates a new resource group for Oracle Plug-in with only application volume resources.

Example 6: Adding a resource group for UnixFileSystems plugin

```
Add-SmResourceGroup -ResourceGroupName 'RG_PS_linuxfs201_LVM1_12648'
-Resources
@{"Host"="linuxfs201.gdl.englab.netapp.com";"Type"="UnixFileSystems";Uid="=
"/netapp/VGNFS1/LVM1"} -plugincode 'UnixFileSystems' -Policies
'BackupPS_linuxfs201_LVM1_12648'
```

This example adds a resource group for UnixFileSystems plug-in.

```
Tag :
ByPassRunAs : False
Configuration : SMCoreContracts.SmConfiguration
CreationTime: 12/12/2023 8:29:30 AM
CustomSnapshotFormat:
CustomText :
Description : Creating Resource Group
EmailBody :
EmailFrom :
EmailNotificationPreference :
EmailSMTPServer :
EmailSubject:
EmailTo :
EnableAsupOnFailure :
EnableEmail :
EnableSysLog:
HostResourceMapping : {}
IsCustomSnapshot:
LastBackupStatus:
MaintenanceStatus : Production
ModificationTime: 12/12/2023 8:29:30 AM
PluginProtectionGroupTypes : {UnixFileSystems}
Policies: {}
ProtectionGroupType : Backup
SchedulerSQLInstance:
SearchResources : False
VerificationServer :
VerificationServerInfo :
SMCoreContracts.SmVerificationServerInfo
Name: RG_PS_linuxfs201_LVM1_12648
Type: Group
Id : 173
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
```

```

IsClone : False
CloneLevel : 0
Hosts : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject :

```

Add-SmResourceToUser

Adds resources to an existing user.

Syntax

```

Add-SmResourceToUser [-UserName] <String> [-ResourceNames] <String> [-
ResourceType] <OperationAssignmentType> [-UserGroupObjectType]
<SmUserGroupObjectType>

```

Detailed Description

Adds resources to an existing user. The resources can be a resource group, credential, host, policy, storage connection or plug-in.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
UserName	Name of the domain\user.	true	true (ByPropertyName)	
ResourceNames	Name of the resources to be assigned. You can use a comma to separate multiple resources.	false	true (ByPropertyName)	
ResourceType	The type of resource being added to the user. Possible values are Credential, StorageConnection, Policy, Plugin, Host, and ResourceGroup.	true	true (ByPropertyName)	
UserGroupObjectType	Specifies that the domain\username to which you are adding a resource is a group.	false	true (ByPropertyName)	

Examples

Example 1: Adding a host resource to an user

```
Add-SmResourceToUser -UserName sddev\administrator -ResourceNames clab-a13-13.sddev.mycompany.com -ResourceType Host
```

This example syntax assigns a host resource to the user.

Example 2: Adding a resource group to an user

```
Add-SmResourceToUser -UserName sddev\administrator -ResourceNames FinanceResourceGroup -ResourceType ResourceGroup
```

This example syntax assigns the FinanceResourceGroup resource group to the sddev\administrator user.

Example 3: Adding an credential to an user

```
Add-SmResourceToUser -UserName sddev\administrator -ResourceNames Cred_1 -ResourceType Credential
```

This example syntax assigns the Cred_1 credential resource to the sddev\administrator user.

Example 4: Adding a policy to an user

```
Add-SmResourceToUser -UserName sddev\administrator -ResourceNames testPol -ResourceType Policy
```

This example syntax assigns the testPol policy resource to the sddev\administrator user.

Example 5: Adding a storage connection to an user

```
Add-SmResourceToUser -UserName sddev\administrator -ResourceNames svm1 -ResourceType StorageConnection
```

This example syntax assigns the svm1 storage connection resource to the sddev\administrator user.

Example 6: Adding all the resources to an user

```
Add-SmResourceToUser -UserName sddev\administrator -ResourceType All
```

This example syntax assigns all the resources to the sddev\administrator user.

Add-SmServer

Adds the SC server to the High Availability cluster

Syntax

```
Add-SmServer [-Credential] <PSCredential> [-ServerNameString] <String>
[-ServerIPString] <String> [-CleanUpSecondaryServerSwitchParameter]
<String>
```

Detailed Description

Adds the given SC server to the existing High Availability cluster as secondary node. SnapCenter repository data from primary server will be replicated to the secondary server for HA.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Credential	Provides domain user credentials for the user to setup High Availability cluster configuration.	true	true (ByPropertyName)	
ServerName	Secondary SC server name.	false	false	
ServerIP	Secondary SC server IP Address.	true	false	
CleanUpSecondaryServer	Specifies whether to cleanup secondary server. The value is either True or False.	false	false	

Examples

Example 1: Adding SnapCenter Server to High Availability cluster

```
Add-SmServer -Credential sddev\administrator -ServerIP 10.225.231.149
```

This example Adds SnapCenter Server to High Availability cluster.

```

Name: Adding SC Server 10.225.231.149 to High Availability cluster
Id : 105
StartTime : 9/10/2019 4:11:38 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Running
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 38
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName : NONE
HostId : 0
RoleId :
JobIds : {}
Monitor the progress of job 105 in the Job Monitor page or by running the
cmdlet: 'Get-SmJobSummaryReport -JobId 105'

```

Add-SmServerCluster

Creates the High Availability cluster configuration on the SnapCenter Server.

Syntax

```

Add-SmServerCluster [-Credential] <PSCredential> [-ClusterNameString]
<String> [-ClusterIPString] <String> [-PrimarySCServerIPString]
<String>

```

Detailed Description

Creates High Availability cluster configuration on the SnapCenter Server with the given cluster IP Address. Routing from the cluster URL to SC server(s) should be configured in the Load balancing tool. For the SC Server given IP Address will be included in the HA configuration, if the SC server has more than one IP

Address then choose the one that you want to use for HA configuration and ensure the same IP Address is configured in the load balancing tool.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Credential	Provides domain user credentials for the user to setup High Availability cluster configuration.	true	true (ByPropertyName)	
ClusterName	F5 cluster name.	false	false	
ClusterIP	F5 Cluster IP Address.	true	false	
PrimarySCServerIP	Primary SC Server IP Address.	true	false	

Examples

Example 1: Creating High Availability cluster configuration on the SnapCenter Server

```
Add-SmServerCluster -Credential sddev\administrator -ClusterIP 10.235.236.190 -ClusterName f5pool -PrimarySCServerIP 10.235.236.193
```

This example creates the High Availability cluster configuration on the SnapCenter Server.

```

Name: Configure High Availability for SnapCenter Server
Id   : 21
StartTime   : 9/3/2019 5:25:10 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Running
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 38
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    : NONE
HostId        : 0
RoleId        :
JobIds        : {}

```

Add-SmStorageConnection

Creates a new storage system connection.

Syntax

```

Add-SmStorageConnection [-Storage] <String> [-Port] <UInt16> [-
Protocol] <ConnectProtocol> [-Timeout] <Int32> [-Credential]
<PSCredential> [-PreferredIP] <String> [-DisableAsupOnFailure] <> [-
DisableSysLog] <> [-Type] <StorageSystemType> [-PlatformType]
<String> [-NetAppAccountName] <String> [-CredentialName] <String> [-
CredentialId] <bigint(20)> [-ResourceGroup] <String> [-IsSecondary]
<>

```


Detailed Description

Creates a new storage system connection. You must create your storage system connection in advance of performing any provisioning or data protection jobs.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Storage		true	true (ByPropertyName)	
Port	Specifies the port for the storage system connection. 80 is the default port for HTTP and 443 is the default port for HTTPS.	false	true (ByPropertyName)	
Protocol	Specifies the communication protocol you want to use to connect to the storage system. Valid values is: HTTPS.	true	true (ByPropertyName)	
Timeout	Specifies the storage system connection timeout in seconds. The default timeout is 60 seconds. However, in a scaled environment, increasing the timeout to 300 seconds is recommended.	false	true (ByPropertyName)	60
Credential	Specifies the storage system credentials. You must have created valid storage system credentials in advance.	true	true (ByPropertyName)	
PreferredIP	Specifies the preferred IP address for the storage system management or data LIF IP address.	false	true (ByPropertyName)	
DisableAsupOnFailure	Disables Auto Support in case of any failure.	false	true (ByPropertyName)	
DisableSysLog	Disables system log.	false	true (ByPropertyName)	
Type	Specifies the type of storage being added. Valid value are DataOntap and AzureNetAppAccount.	false	true (ByPropertyName)	
NetAppAccountName	Specifies the Azure NetApp Account Name.	true	true (ByPropertyName)	
CredentialName	Specifies Azure NetApp Credential name.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
CredentialId	Specifies Azure NetApp Credential ID.	false	true (ByPropertyName)	
ResourceGroup	Specifies resource group.	true	true (ByPropertyName)	
SubscriptionId	Specifies Subscription Id.	true	true (ByPropertyName)	
PlatformType	This optional parameter specifies the SVM platform type for licensing purposes. Possible values are Hardware and Software. Hardware indicates that you are using a FAS or All Flash FAS platform. Software indicates that you are using ONTAP Cloud or ONTAP Select. If you specify Type as ONTAP SVM as the storage connection type, and you do not specify PlatformType, the default value is set to Hardware.	false	true (ByPropertyName)	
IsSecondary		false	true (ByPropertyName)	

Examples

Example 1: Creating a new storage system connection

```
Add-SmStorageConnection -SVM neeraj_vs1 -Protocol Https -Timeout 60
```

This example syntax creates a new storage system connection.

```

cmdlet Add-SmStorageConnection at command pipeline position 1
Supply values for the following parameters:
(Type !? for Help.)
Credential
UserName:
Password:
Port: 443
TransportType : Https
ModifyTime : 1/1/0001 12:00:00 AM
Mode:
OntapiMajorVersion :
OntapiMinorVersion :
Version : NetApp Release 8.2.1RC2X9 Cluster-Mode: Mon Jan 13 09:30:32 PST
2014
StorageSystemOSType : DataOntap
Passphrase :
Id : 0
Timeout : 60
Uuid:
OperationContext:
PreferredIpAddress :
Aliases : {neeraj_vs1-mc, neeraj_vs1}
SmIPAddresses : {SMCoreContracts.SmIPAddress,
SMCoreContracts.SmIPAddress, SMCoreContracts.SmIPAddress,
SMCoreContracts.SmIPAddress...}
IPAddresses : {172.17.124.165, 172.17.124.165, 172.17.124.165,
172.17.124.165...}
Name: test_vs1
IsResolved : True
IsValid : True
Identity: test_vs1

```

Example 2: Creating a new Azure NetApp Account using credential name

```

Add-SmStorageConnection -Type AzureNetAppAccount -NetAppAccountName
"azureNetappAccount1" -SubscriptionId 5199ff02-31d1-4a57-afd1-3039bcbdf9aa
-CredentialName "AzureCred1" -ResourceGroup "azure_rgl"

```

This example syntax creates a new Azure NetApp Account using credential name.

Example 3: Creating a new Azure NetApp Account using credential ID

```
Add-SmStorageConnection -Type AzureNetAppAccount -NetAppAccountName
"azureNetappAccount1" -SubscriptionId 5199ff02-31d1-4a57-afd1-3039bcbdf9aa
-CredentialId 1 -ResourceGroup "azure_rg1"
```

This example syntax creates a new Azure NetApp Account using credential ID.

Add-SmUser

Adds AD users or local workgroup users to SnapCenter.

Syntax

```
Add-SmUser [-UserName] <SmString> [-Domain] <String> [-RoleNames]
<SmString>
```

Detailed Description

Adds Active Directory users or local workgroup users to SnapCenter.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
UserName	Single user or list of users belonging to the same domain or workgroup.	true	true (ByPropertyName)	
Domain	Domain to which the user belongs to. Workgroup users should skip this parameter.	false	true (ByPropertyName)	
RoleNames	Single or list of existing pre-canned or custom roles to which the user should be added to. At least one role should be specified while adding the user.	true	true (ByPropertyName)	

Examples

Example 1: Adding a single user

```
Add-SmUser -UserName user1 -RoleNames role1,role2 -Domain domain1
```

Example 2: Adding multiple users of the same domain

```
Add-SmUser -UserName user1,user2 -RoleNames role1 -Domain domain1
```

Example 3: Adding workgroup user

```
Add-SmUser -UserName LocalUser1 -RoleNames role1
```

Add-SmUserToRole

Adds a user to a role.

Syntax

```
Add-SmUserToRole [-UserName] <SmString> [-RoleName] <String> [-Domain]  
<String>
```

Detailed Description

Adds a user to a role.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
UserName	Specifies the domain\user you want to add.	true	true (ByPropertyName)	
RoleName	Specifies the name of the role to which you want to add a user.	true	true (ByPropertyName)	
Domain	The domain to which the user belongs to. Workgroup users should skip this parameter.	false	true (ByPropertyName)	

Examples

Example 1: Adding a user to a role

```
Add-SmUserToRole -UserName snapdrive -Domain sddev -RoleName  
SnapCenterAdmin
```

This example adds the specified user to the SnapCenter Admin role.

Add-SmVerificationServer

Adds a verification server.

Syntax

```
Add-SmVerificationServer [-Name] <String> [-HostName] <String> [-UseDriveLetter] <> [-MountPointPath] <String> [-MaxJobCount] <Int32> [-CredentialName] <String> [-PluginCode] <PluginCode> [-Description] <String>
```

Detailed Description

Adds a verification server. A verification server is used in a SnapCenter Plug-in for Microsoft SQL Server environments to run an integrity check of the backups. It is a SQL Server instance, on which you run backup verification. Verification is a CPU intensive operation, so it is recommended that you set up a dedicated verification server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the SQL Server instance that you want to use as the verification server.	true	true (ByPropertyName)	
HostName	Specifies the host on which you want the verification server to be located. You can have more than one verification server located on the same host.	false	true (ByPropertyName)	
UseDriveLetter	Specifies that you want to use an available drive letter for mounting the Snapshot copy for verification. To perform backup verification, the Snapshot copy is mounted and then DBCC checkdb is run. If you do not specify UseDriveLetter, the Snapshot copy is mounted using a mount point path you specify.	false	true (ByPropertyName)	False
MountPointPath	Species the default mount point path you want to use to mount the Snapshot copy for verification.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
MaxJobCount	Specifies the maximum number of verification jobs that can be run concurrently on the verification server. The default is 1 job. It is recommended that you increase this parameter with caution. The recommended maximum job count is 5.	false	true (ByPropertyName)	1
CredentialName		false	true (ByPropertyName)	
PluginCode	Provides the SnapCenter plug-in code. For example, if you want to use the SnapCenter Plug-in for Microsoft SQL Server, the plug-in code is SCSQL. If you do not specify this parameter, MSFT_SQL is the default.	false	true (ByPropertyName)	
Description	Provides an optional description for the verification server you are setting up.	false	true (ByPropertyName)	

Examples

Example 1: Adding a verification server

```
Add-SmVerificationServer -Name mva-s51/instance1 -HostName mva-s51
-UseDriveLetter -MountPointPath c:\temp -MaxJobCount 1 -PluginCode SCSQL
```

This example syntax adds a verification server.

```
Name: mva-s51/instance1
HostName:
PlugIn :
UseDriveLetterIfAvail : True
DefaultMountPointFolder : c:\temp
MaxJobCount : 1
Description :
EndpointURI :
PluginVersion :
```

Cancel-SmJob

Cancels backup, clone, and verification jobs, which are in queued state. This cmdlet also cancels the running SnapCenter Plug-in for SQL Server and SnapCenter Plug-in for

Oracle backup jobs.

Syntax

```
Cancel-SmJob [-JobId] <Int32> [-Force] <>
```

Detailed Description

Enables you to cancel the queued backup, clone, and verification jobs, as well as the running restore and clone jobs for all plug-ins. You can also cancel the running SnapCenter Plug-in for SQL Server and SnapCenter Plug-in for Oracle backup jobs. This cmdlet does not cancel running backup jobs for SnapCenter Plug-in for Exchange, SnapCenter Plug-in for VMware vSphere, SnapCenter Plug-in for SAP HANA, or SnapCenter Custom Plug-ins. This cmdlet replaces the Cancel-SmQueuedJob cmdlet that was available in earlier versions of SnapCenter.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
JobId	Specifies the ID of the job you want to cancel.	true	false	
Force	This optional parameter cancels a hung job that is running or queued.	false	false	

Examples

Example 1: Canceling a Running/Queued job

```
Cancel-SmJob -JobId 231
```

This example syntax cancels the backup job which is either running or queued.

```
Cancel-SmJob
```

Job 231 will be canceled. Do you want to continue?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Example 2: Canceling a Running/Queued job with Force option

```
Cancel-SmJob -JobId 231 -Force
```

This example syntax cancels the backup job which is hung during canceling or running state.

```
Cancel-SmJob
```

Job 231 will be canceled. Do you want to continue?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Cancel-SmRestoreJob

Cancels the restore jobs, which are in queued state. This cmdlet also cancels the running SnapCenter Plug-in restore jobs.

Syntax

```
Cancel-SmRestoreJob [-JobId] <Int32>
```

Detailed Description

Enables you to cancel the queued restore jobs and the running restore jobs for all the plug-ins.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
JobId		true	false	

Examples

Catalog-SmBackupWithOracleRMAN

Catalogs an Oracle backup.

Syntax

```
Catalog-SmBackupWithOracleRMAN [-PluginCode] <PluginCode> [-BackupId] <String> [-BackupName] <String> [-AppObjectId] <String> [-ArchivedLocators] <Hashtable[]> [-LogArchivedLocators] <Hashtable[]>
```

Detailed Description

Catalogs the Oracle Database backup in SnapCenter with Oracle Recovery Manager (RMAN).

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode	Specifies the plug-in code of the resource to be cataloged.	true	false	

Name	Description	Required ?	Pipeline Input	Default Value
BackupId	Specifies the id of backup that needs to be cataloged.	false	false	
BackupName	Specifies the name of backup that needs to be cataloged.	false	false	
AppObjectId	Specifies the ID of the application object.	false	true (ByPropertyName)	
ArchivedLocators	Specifies the secondary storage system details in a hashtable for each unique primary data storage system resource in the resource group. For example:- ArchivedLocators @{Primary="my_vs1:my_data_vol";Secondary="my_vs1:my_data_vol_SECONDARY"}	false	true (ByPropertyName)	
LogArchivedLocators	Specifies the secondary storage system details in a hashtable for each unique primary log storage system resource in the resource group. For example:- LogArchivedLocators @{Primary="my_vs1:my_log_vol";Secondary="my_vs1:my_log_vol_SECONDARY"}	false	true (ByPropertyName)	

Examples

Example 1: Cataloging a SCO backup using backupId

```
Catalog-SmBackupWithOracleRMAN -PluginCode SCO -BackupId 7
```

This example syntax catalogs a SCO backup using backupId.

```
Name: Cataloging Backup(s)
      scspr1894465002_gdl_englab_netapp_com_TSPITRDB_scspr1894465002_08-06-
2020_01.13.03.7681_1
Id   : 42
StartTime   : 8/7/2020 1:40:18 AM
EndTime    :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible    : True
IsScheduled  : False
PercentageCompleted : 0
Description :
Status      : Queued
Owner       :
Error       :
Priority: None
Tasks      : {}
ParentJobID : 0
EventId    : 0
JobTypeId  : 28
ApisJobKey :
ObjectId   : 0
PluginCode  : SCO
PluginName  : SnapCenter Plug-in for Oracle Database
HostId     : 0
RoleId     :
JobIds     : {}
```

Example 2: Cataloging a SCO backup using backupname

```
Catalog-SmBackupWithOracleRMAN -PluginCode SCO -BackupName
scspr1894465002_gdl_englab_netapp_com_TSPITRDB_scspr1894465002_08-06-
2020_04.13.23.4083_1
```

This example syntax catalogs a SCO backup using backupname.

```
Name: Cataloging Backup(s)
      scspr1894465002_gdl_englab_netapp_com_TSPITRDB_scspr1894465002_08-06-
2020_04.13.23.4083_1
Id   : 44
StartTime   : 8/7/2020 1:45:09 AM
EndTime    :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible    : True
IsScheduled  : False
PercentageCompleted : 0
Description :
Status      : Queued
Owner       :
Error       :
Priority     : None
Tasks       : {}
ParentJobID : 0
EventId     : 0
JobTypeId   : 28
ApisJobKey   :
ObjectId    : 0
PluginCode   : SCO
PluginName   : SnapCenter Plug-in for Oracle Database
HostId      : 0
RoleId      :
JobIds      : {}
```

Example 3: Cataloging a SCO data backup from the secondary mirror location

```
Catalog-SmBackupWithOracleRMAN -PluginCode SCO -BackupName rg1_galaxy-
vm134_08-08-2020_15.11.16.3564_0 -ArchivedLocators
@{Primary="buck.gdl.englab.netapp.com:nasvol14";Secondary="squint:buck_nas
vol14_mirror"}
```

This example syntax catalogs a SCO data backup from the secondary mirror location.

```
Name: Cataloging Backup(s)
  rg1_galaxy-vm134_08-08-2020_15.11.16.3564_0
Id   : 45
StartTime   : 8/7/2020 1:47:09 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 28
ApisJobKey    :
ObjectId      : 0
PluginCode    : SCO
PluginName    : SnapCenter Plug-in for Oracle Database
HostId        : 0
RoleId        :
JobIds        : {}
```

Example 4: Cataloging a SCO log backup from the secondary vault location

```
Catalog-SmBackupWithOracleRMAN -PluginCode SCO -BackupName rg1_galaxy-
vm134_08-08-2020_15.11.16.3564_1 -LogArchivedLocators
@{Primary="buck.gdl.englab.netapp.com:nasvol13";Secondary="squint:buck_nas
vol13_vault"}
```

This example syntax catalogs a SCO log backup from the secondary vault location.

```
Name: Cataloging Backup(s)
  rg1_galaxy-vm134_08-08-2020_15.11.16.3564_1
Id   : 46
StartTime   : 8/7/2020 1:50:09 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 28
ApisJobKey    :
ObjectId      : 0
PluginCode    : SCO
PluginName    : SnapCenter Plug-in for Oracle Database
HostId        : 0
RoleId        :
JobIds        : {}
```

Example 5: Cataloging a SCO data backup for the desired database

```
Catalog-SmBackupWithOracleRMAN -PluginCode SCO -BackupName rg1_galaxy-
vm134_08-08-2020_15.11.16.3574_0 -AppObjectId 'galaxy-
vm134.gdl.englab.netapp.com\DB14'
```

This example syntax catalogs a SCO backup for the desired database.

```
Name: Cataloging Backup(s)
      rg1_galaxy-vm134_08-08-2020_15.11.16.3574_0
Id   : 48
StartTime   : 8/7/2020 1:55:09 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 28
ApisJobKey    :
ObjectId      : 0
PluginCode    : SCO
PluginName    : SnapCenter Plug-in for Oracle Database
HostId        : 0
RoleId        :
JobIds        : {}
```

Configure-SmDatabase

Configures database in SnapCenter.

Syntax

```
Configure-SmDatabase [-PluginCode] <PluginCode> [-ResourceId] <String>
[-HDBSQLUser] <String> [-HDBUserStoreKey] <String> [-PluginCode]
<PluginCode> [-ResourceId] <String> [-CredentialName] <String>
```

Detailed Description

Configure database settings in SnapCenter.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	------------	----------------	---------------

Examples

Example: Configuring HANA resource

```
Configure-SmDatabase -PluginCode HANA -ResourceId "test" -HDBSQLUser "test" -HDBUserStoreKey "test"
```

This example shows how to configure database credentials for HANA Database.

Successfully updated the database configuration details.

Example: Configuring MYSQL resource

```
Configure-SmDatabase -PluginCode MYSQL -ResourceId "lvm-rhel65-71.netapp.com\MySQL\mysqld_3306" -CredentialName "mysql_cred"
```

This example shows how to configure database credentials for MYSQL Database when passing existing credential.

Successfully updated the cluster/instance configuration details.

Example: Configuring POSTGRESQL resource

```
Configure-SmDatabase -PluginCode POSTGRESQL -ResourceId "scs000351114.netapp.com\PostgreSQL\postgres_5432" -CredentialName "postgres_cred"
```

This example shows how to configure database credentials for POSTGRESQL Database when passing existing credential.

Successfully updated the cluster/instance configuration details.

Configure-SmOracleDatabase

Configures Oracle Database in SnapCenter. This includes configuring database authentication with port, ASM authentication with port and Oracle Recovery Manager (RMAN) catalog database. For Oracle RAC database, preferred nodes for backup operation can be configured.

Syntax

```
Configure-SmOracleDatabase [-AppObjectId] <String> [-  
DatabaseCredentialName] <String> [-AsmCredentialName] <String> [-  
OracleRmanCatalogTnsName] <String> [-OracleRmanCatalogCredentialName]  
<String> [-ASMPort] <Int32> [-DatabasePort] <Int32> [-  
OracleRACPreferredNodes] <String>
```

Detailed Description

Configures Oracle Database in SnapCenter. This includes configuring database authentication with port, ASM authentication with port and Oracle Recovery Manager (RMAN) catalog database. For Oracle RAC database, preferred nodes for backup operation can be configured.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
AppObjectId	Specifies the application object identifier of an Oracle Database that needs to be configured. You need to specify the application object identifier format as 'host\database' for Oracle standalone database or 'clustername\database' for Oracle RAC database.	true	true (ByPropertyName)	
DatabaseCredentialName		false	true (ByPropertyName)	
AsmCredentialName		false	true (ByPropertyName)	
OracleRmanCatalogTnsName	Specifies the TNS name of Oracle Recovery Manager (RMAN) catalog database.	false	true (ByPropertyName)	
OracleRmanCatalogCredentialName		false	true (ByPropertyName)	
ASMPort	Specifies the port where the Oracle ASM listener is running.Default: 1521	false	true (ByPropertyName)	1521
DatabasePort	Specifies the port where the Oracle Database listener is running.Default: 1521	false	true (ByPropertyName)	1521

Name	Description	Required ?	Pipeline Input	Default Value
OracleRACPreferredNodes	Specifies one or more Oracle RAC database preferred nodes you want to configure for backup operation. Oracle RAC Nodes must be specified in a comma separated values in the order of their preference.	false	true (ByPropertyName)	

Examples

Example 1: Configure database credentials for Oracle Database.

```
Configure-SmOracleDatabase -AppObjectId host-name\STDDB
-DatabaseRunAsName stddb_cred -DatabasePort 1521
```

This example shows how to configure database credentials for Oracle Database.

Example 2: Configure RAC preferred node settings for Oracle Database.

```
Configure-SmOracleDatabase -AppObjectId oracle-rac-cluster\RACDB
-OracleRACPreferredNodes rac-node1.netapp.com,rac-node3.netapp.com,rac-
node2.netapp.com
```

This example shows how to configure RAC preferred node settings for Oracle Database.

Copy-SmPolicy

Copies an existing policy.

Syntax

```
Copy-SmPolicy [-PolicyName] <String> [-NewPolicyName] <String>
```

Detailed Description

Copies an existing policy, its attributes including retention and replication settings, and its scheduler information.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PolicyName	Specifies the policy you want to copy.	true	true (ByPropertyName)	
NewPolicyName	Specifies the new policy name.	true	true (ByPropertyName)	

Examples

Example 1: Creating a copy of a policy

```
Copy-SmPolicy -PolicyName FinancePolicy -NewPolicyName NewFinancePolicy
```

This example syntax creates a copy of the specified policy.

```
ApplySnapvaultUpdate: False
ApplyRetention      : False
RetentionCount      : 0
RetentionDays       : 0
ApplySnapMirrorUpdate : False
SnapVaultLabel      :
MirrorVaultUpdateRetryCount : 7
AppPolicies         : {}
Description          : FinancePolicy
PreScriptPath        :
PreScriptArguments   :
PostScriptPath       :
PostScriptArguments  :
ScriptTimeout        : 60000
DateModified: 8/4/2015 4:20:51 PM
DateCreated : 8/4/2015 4:20:51 PM
Schedule: SMCoreContracts.SmSchedule
PolicyType      : Backup
PluginPolicyType: SMSQL
Name: NewFinancePolicy
Type:
Id : 2
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Example 2: Discovering SnapCenter for Windows plugin resources on a host

```
Get-SmResources -HostName localhost -PluginCode scw -Verbose
```

This example syntax discovers the resources for the SnapCenter for Windows plug-in on the specified host.

Copy-SmRole

Copies an existing role-based access control (RBAC) role.

Syntax

```
Copy-SmRole [-RoleName] <String> [-NewRoleName] <String>
```

Detailed Description

Copies an existing role-based access control (RBAC) role.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
RoleName	Specifies the name of the existing role.	true	true (ByPropertyName)	
NewRoleName	Specifies the name of the new role.	true	true (ByPropertyName)	

Examples

Example 1: Copying and existing role

```
Copy-SmRole -RoleName 'App Backup and Clone Admin' -NewRoleName  
app_backup_clone_admin_copy
```

This example syntax copies the existing role "App Backup and Clone Admin" to a new role called app_backup_clone_admin_copy.

Disable-SmDataCollectionEms

Disables EMS data collection.

Syntax

```
Disable-SmDataCollectionEms
```

Detailed Description

Disables EMS data collection. EMS data collection occurs weekly, by default. EMS data collection gathers information about Server and plug-in hosts, and available plug-ins.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	------------------

Examples

Example 1: Disabling EMS data collection

```
Disable-SmDataCollectionEms
```

This example syntax disables EMS data collection.

Enable-SmDataCollectionEms

Enables EMS data collection.

Syntax

```
Enable-SmDataCollectionEms
```

Detailed Description

Enables EMS data collection. EMS data collection occurs weekly, by default. EMS data collection gathers information about Server and plug-in hosts, and available plug-ins.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	------------------

Examples

Example 1: Enabling EMS data collection

```
Enable-SmDataCollectionEms
```

This example syntax enables weekly EMS data collection.

Enable-SmRepositoryHAConfig

Enables SnapCenter repository HA configuration.

Syntax

```
Enable-SmRepositoryHAConfig [-SlaveNode] <String>
```

Detailed Description

Enables SnapCenter repository HA configuration.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SlaveNode	Specifies the IP address of the slave node. This IP must not belong to the master node IP or IP of the machine where this cmdlet is running.	true	true (ByPropertyName)	

Examples

Example 1: Enabling SnapCenter repository HA config

```
Enable-SmRepositoryHAConfig -SlaveNode "slave_node_ip_address"
```

This example syntax enables SnapCenter repository HA config. Slave node IP must not belong to the master node IP or IP of the machine where this cmdlet is running. This cmdlet must be executed on the Master (primary) node.

```
Enable-SmRepositoryHAConfig
```

Are you sure you want to enable MySQL HA Configuration ?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

```
SnapCenter repository HA configuration is successfully configured.
```

Get-SmAlert

Get details of the alert(s).

Syntax

```
Get-SmAlert [-AlertId] <String> [-Severity] <SmAlertSeverity> [-Status] <SmAlertStatus> [-EntityType] <SmEntityType> [-SearchText] <String>
```

Detailed Description

Get details of the alerts. This information includes the alert name, description, recommendation, severity, status, entity, etc.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
AlertId	Specify the Id of the alert.	false	true (ByPropertyName)	
Severity	Specify the severity of the alert(s) needs to be filtered. ("Informational", "Warning", "Critical")	false	true (ByPropertyName)	
Status	Specify the status of the alert(s) needs to be filtered. ("New", "Resolved")	false	true (ByPropertyName)	
EntityType	Specify the entity type of the alert(s) needs to be filtered. ("SnapCenterServer", "Host", "StorageSystem")	false	true (ByPropertyName)	
SearchText	Specify the Alert Name or Entity Name needs to be filtered.	false	true (ByPropertyName)	

Examples

Example 1: Get alert by Id

```
Get-SmAlert -AlertId 100
```

This example syntax retrieves the information of an alert.

```
Id : 100
CreatedTime: 12/5/2018 2:47:05 AM
ModifiedTime : 12/5/2018 2:47:05 AM
Name : Aggregate assignment check
Status : New
Severity : Warning
Entity : SMCoreContracts.ConfigCheck.SmEntity
Description: Aggr-list field is not set for the storage virtual machine
Recommendation : To rectify this issue, see
https://kb.netapp.com/app/answers/answer\_view/a\_id/1070989/loc/en\_US
JobId : 2345
Source : Server
EntityType : Host
EntityName : mtme.englab.netapp.com
```

Example 2: Get all alerts

```
Get-SmAlert
```

This example syntax retrieves the information about all alerts.

```
Id : 100
CreatedTime: 12/5/2018 2:47:05 AM
ModifiedTime : 12/5/2018 2:47:05 AM
Name : Aggregate assignment check
Status : New
Severity : Warning
Entity : SMCoreContracts.ConfigCheck.SmEntity
Description: Aggr-list field is not set for the storage virtual machine
Recommendation : To rectify this issue, see
https://kb.netapp.com/app/answers/answer\_view/a\_id/1070989/loc/en\_US
JobId : 2345
Source : Server
EntityType : Host
EntityName : mtme.englab.netapp.com
EntityId : 1
Id : 101
CreatedTime: 12/5/2018 2:48:15 AM
ModifiedTime : 12/5/2018 2:48:15 AM
Name : IMT check - OS platform, version and patches for SCSQL Server
Status : New
Severity : Critical
Entity : SMCoreContracts.ConfigCheck.SmEntity
```



```
Description: Unsupported version of SQL server instance is detected for
the host
Recommendation : Please refer to NetApp Interoperability Matrix Tool for
supported versions
JobId   : 3456
Source  : Server
EntityType : Host
EntityName : mtme.englab.netapp.com
EntityId   : 1
Id       : 102
CreatedTime: 12/5/2018 2:57:23 AM
ModifiedTime   : 12/5/2018 2:57:23 AM
Name          : SVM duplicate Data LIF check
Status        : New
Severity      : Warning
Entity        : SMCOREContracts.ConfigCheck.SmEntity
Description: Cluster Storage Virtual Machines have duplicate IP address
Recommendation : You should ensure that ONTAP Cluster storage virtual
machine network interfaces have unique IP addresses assigned to them
JobId   : 3678
Source  : Server
EntityType : SVM
EntityName : mtme-win2k8r2x64-20.gdl.englab.netapp.com
EntityId   : 1
```

Example 3: Get all the alerts based on severity

```
Get-SmAlert -Severity "Critical"
```

This example syntax retrieves all the critical alerts.

```
Id : 101
CreatedTime: 12/5/2018 2:48:15 AM
ModifiedTime : 12/5/2018 2:48:15 AM
Name : IMT check - OS platform, version and patches for SCSQL Server
Status : New
Severity : Critical
Entity : SMCoreContracts.ConfigCheck.SmEntity
Description: Unsupported version of SQL server instance is detected for
the host
Recommendation : Please refer to NetApp Interoperability Matrix Tool for
supported versions
JobId : 3456
Source : Server
EntityType : Host
EntityName : mtme.englab.netapp.com
EntityId : 1
```

Example 4: Get all the alerts based on status

```
Get-SmAlert -Status "New"
```

This example syntax retrieves all the new alerts.

```
Id : 101
CreatedTime: 12/5/2018 2:48:15 AM
ModifiedTime : 12/5/2018 2:48:15 AM
Name : IMT check - OS platform, version and patches for SCSQL Server
Status : New
Severity : Critical
Entity : SMCoreContracts.ConfigCheck.SmEntity
Description: Unsupported version of SQL server instance is detected for
the host
Recommendation : Please refer to NetApp Interoperability Matrix Tool for
supported versions
JobId : 3456
Source : Server
EntityType : Host
EntityName : mtme.englab.netapp.com
EntityId : 1
```

Example 5: Get all the alerts based on entity

```
Get-SmAlert -EntityType "Host"
```

This example syntax retrieves all the Host related alerts.

```
Id : 101
CreatedTime: 12/5/2018 2:48:15 AM
ModifiedTime : 12/5/2018 2:48:15 AM
Name : IMT check - OS platform, version and patches for SCSQL Server
Status : New
Severity : Critical
Entity : SMCoreContracts.ConfigCheck.SmEntity
Description: Unsupported version of SQL server instance is detected for
the host
Recommendation : Please refer to NetApp Interoperability Matrix Tool for
supported versions
JobId : 3456
Source : Server
EntityType : Host
EntityName : mtme.englab.netapp.com
EntityId : 1
```

Example 6: Get all the alerts based on entity name

```
Get-SmAlert -SearchText "mtme.englab"
```

This example syntax retrieves all the alerts whose entity name contains the text 'mtme.englab'.

```
Id : 101
CreatedTime: 12/5/2018 2:48:15 AM
ModifiedTime : 12/5/2018 2:48:15 AM
Name : IMT check - OS platform, version and patches for SCSQL Server
Status : New
Severity : Critical
Entity : SMCoreContracts.ConfigCheck.SmEntity
Description: Unsupported version of SQL server instance is detected for
the host
Recommendation : Please refer to NetApp Interoperability Matrix Tool for
supported versions
JobId : 3456
Source : Server
EntityType : Host
EntityName : mtme.englab.netapp.com
EntityId : 1
```

Get-SmAssignedGroups

Gets a list off all groups assigned to a role.

Syntax

```
Get-SmAssignedGroups [-RoleName] <String>
```

Detailed Description

Gets a list off all groups assigned to a user.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
RoleName	Specifies the name of the role for which you want to find the assigned groups.	true	true (ByPropertyName)	

Examples

Example 1: Getting groups assigned to a particular role

```
Get-SmAssignedGroups -RoleName SnapcenterAdmin
```

The example syntax gets the groups assigned to the SnapCenterAdmin role.

```
Token      :
TokenHashed : {}
TokenTime   : 8/3/2015 5:07:50 PM
FullName:
Author      :
Domain      : sddev
Description :
TokenNeverExpires : False
IsAdmin     : False
TenantAdmin :
IsNewUser   :
UserGroupObjectType : Group
RoleName:
RoleId      : 0
Name: administrators
Type:
Id          : 3
Host:
UserName:
Passphrase  :
Deleted     : False
Auth: SMCoreContracts.SmAuth
IsClone     : False
CloneLevel  : 0
```

Get-SmAssignedRoles

Gets the roles assigned to a specified user or Active Directory group.

Syntax

```
Get-SmAssignedRoles [-UserName] <String> [-UserGroupObjectType]
<SmUserGroupObjectType>
```

Detailed Description

Gets the roles assigned to a specified user or Active Directory group.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
UserName	Specifies the domain\username for the user about which you want to get role information.	true	true (ByPropertyName)	
UserGroupObjectType	Specifies that the domain\username for which you are requesting role information is a group.	false	true (ByPropertyName)	

Examples

Example 1: Getting roles for a particular user

```
Get-SmAssignedRoles -UserName sddev\administrator
```

This example syntax gets the roles assigned to a user.

```
Description : Overall administrator of SnapCenter system
Name: SnapCenterAdmin
Type: Administrator
Id : 1
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Example 2: Getting roles assigned to a group

```
Get-SmAssignedRoles -UserName sddev\b-grp -UserGroupObjectType Group
```

```
Description :
Name: role1
Type:
Id   : 20
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts    : {}
```

Get-SmAssignedUsers

Gets the users assigned to a specified role.

Syntax

```
Get-SmAssignedUsers [-RoleName] <String>
```

Detailed Description

Gets the users assigned to a specified role.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
RoleName	Specifies the role name.	true	true (ByPropertyName)	

Examples

Example 1: Gets users associated with a role

```
Get-SmAssignedUsers -RoleName SnapCenterAdmin
```

This example syntax gets the users associated with a role.

```
Token      :
TokenHashed : {}
```

```
TokenTime      : 8/3/2015 5:30:59 PM
FullName: sddev\administrator
Author       :
Domain      : sddev
Description   :
TokenNeverExpires : False
IsAdmin      : False
TenantAdmin  :
IsNewUser    :
UserGroupObjectType : User
RoleName:
RoleId       : 0
Name: administrator
Type:
Id          : 1
Host:
UserName:
Passphrase  :
Deleted     : False
Auth: SMCoreContracts.SmAuth
IsClone     : False
CloneLevel  : 0
Token       :
TokenHashed : {}
TokenTime   : 8/3/2015 5:30:59 PM
FullName: sddev\snapdrive
Author      :
Domain     : sddev
Description :
TokenNeverExpires : False
IsAdmin     : False
TenantAdmin :
IsNewUser   :
UserGroupObjectType : User
RoleName:
RoleId      : 0
Name: snapdrive
Type:
Id         : 2
Host:
UserName:
Passphrase :
Deleted    : False
Auth: SMCoreContracts.SmAuth
IsClone    : False
CloneLevel : 0
```


Get-SmAuditSettings

Retrieves Audit configurations and Syslog configurations

Syntax

```
Get-SmAuditSettings
```

Detailed Description

Retrieves below configurations: Audit log related configuration - Maximum File Size, Maximum files to retain, Audit Log file location, Audit Log Checksum file location, Disk Space Limit in Percentage, to raise alert after limit is reached, Option to Enable Audit Integrity Check Schedule, Syslog server related configuration - Option to Enable Syslog Server and update Syslog configuration, Syslog Server Host, Syslog Server Port, Syslog Protocol, Syslog Format

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	------------	----------------	---------------

Examples

Example 1: Getting audit log and syslog server settings

```
Get-SmAuditSettings
```

This example gets audit log and Syslog server settings.

```
MaxFileSize : 50
MaxSizeRollBackups : 10
UniversalTime : False
AuditLogDirectory : C:\Program Files\NetApp\SnapCenter WebApp\audit
AuditChecksumLogDirectory : C:\Program Files\NetApp\SnapCenter
WebApp\auditChecksum
DiskSpaceLimitPercentage : 80
EnableAuditIntegrityCheckSchedule : False
EnableSyslogServer : True
SyslogServerHost : 10.229.39.107
SyslogServerPort : 1468
SyslogProtocol : TCP
SyslogFormat : Rfc5424
```

Example 2: Getting audit log settings and syslog server is disabled

```
Get-SmAuditSettings
```

This example gets audit log settings and Syslog server is disabled.

```
MaxFileSize : 50
MaxSizeRollBackups : 10
UniversalTime : False
AuditLogDirectory : C:\Program Files\NetApp\SnapCenter WebApp\audit
AuditChecksumLogDirectory : C:\Program Files\NetApp\SnapCenter
WebApp\auditChecksum
DiskSpaceLimitPercentage : 80
EnableAuditIntegrityCheckSchedule : False
EnableSyslogServer : False
```

Get-SmAuditSettings

Retrieves Audit configurations and Syslog configurations

Syntax

```
Get-SmAuditSettings
```

Detailed Description

Retrieves below configurations: Audit log related configuration -Maximum File SizeMaximum files to retainAudit Log file locationAudit Log Checksum file locationDisk Space Limit in Percentage, to raise alter after limit is reachedOption to Enable Audit Integrity Check ScheduleSyslog server related configuration -Option to Enable Syslog Server and update Syslog configurationSyslog Server HostSyslog Server PortSyslog ProtocolSyslog Format

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	------------	----------------	---------------

Examples

Example 1: Getting audit log and syslog server settings

```
Get-SmAuditSettings
```

This example gets audit log and Syslog server settings.

```
MaxFileSize : 50
MaxSizeRollBackups : 10
UniversalTime : False
AuditLogDirectory : C:\Program Files\NetApp\SnapCenter WebApp\audit
AuditChecksumLogDirectory : C:\Program Files\NetApp\SnapCenter
WebApp\auditChecksum
DiskSpaceLimitPercentage : 80
EnableAuditIntegrityCheckSchedule : False
EnableSyslogServer : True
SyslogServerHost : 10.229.39.107
SyslogServerPort : 1468
SyslogProtocol : TCP
SyslogFormat : Rfc5424
```

Example 2: Getting audit log settings and syslog server is disabled

```
Get-SmAuditSettings
```

This example gets audit log settings and Syslog server is disabled.

```
MaxFileSize : 50
MaxSizeRollBackups : 10
UniversalTime : False
AuditLogDirectory : C:\Program Files\NetApp\SnapCenter WebApp\audit
AuditChecksumLogDirectory : C:\Program Files\NetApp\SnapCenter
WebApp\auditChecksum
DiskSpaceLimitPercentage : 80
EnableAuditIntegrityCheckSchedule : False
EnableSyslogServer : False
```

Get-SmBackup

Gets information about one or more backups.

Syntax

```
Get-SmBackup [-BackupName] <String> [-BackupId] <String> [-
AppObjectName] <String> [-AppObjectId] <String> [-Secondary] <> [-
CloudProtected] <> [-ObjectStorage ] <> [-Details] <>
```

Detailed Description

Gets information about one or more backups. You can specify whether to include information about secondary backups.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
BackupName	Specifies the name of the backup about which you want to retrieve information.	false	true (ByPropertyName)	
BackupId	Specifies the ID of the backup about which you want to get information.	false	true (ByPropertyName)	
AppObjectName	Specifies the name of the application object.	false	true (ByPropertyName)	
AppObjectId	Specifies the ID of the application object.	false	true (ByPropertyName)	
Secondary	Specifies whether to list only the secondary backups.	false	true (ByPropertyName)	
CloudProtected	Specifies whether to list only the cloud backups.	false	true (ByPropertyName)	
Details		false	true (ByPropertyName)	

Examples

Example 1: Getting information about all backups

```
Get-SmBackup
```

This example syntax gets information about all available backups.

```
BackupId BackupName BackupTime BackupType
```

```
-----  
1 Payroll Dataset_vise-f6_08... 8/4/2015 11:02:32 AM Full Backup  
2 Payroll Dataset_vise-f6_08... 8/4/2015 11:23:17 AM
```

Example 2: Getting information about secondary backups

```
Get-SmBackup -Secondary
```

This example syntax gets information about only secondary backups.

```
BackupId BackupName BackupTime BackupType
-----
1 Payroll Dataset_vise-f6_08... 8/4/2015 11:02:32 AM
```

Example 3: Getting a backup information for a specific backup name

```
Get-SmBackup -BackupName "Payroll Dataset_vise-f6_08-04-
2015_11.02.10.3432"
```

This example syntax gets backup information for the specified backup name.

```
BackupId BackupName BackupTime BackupType
-----
1 Payroll Dataset_vise-f6_08... 8/4/2015 11:02:32 AM
```

Example 4: Getting backup information using the backup ID

```
Get-SmBackup -BackupId 1
```

This example syntax gets backup information using the specified backup ID.

```
BackupId BackupName BackupTime BackupType
-----
1 Payroll Dataset_vise-f6_08... 8/4/2015 11:02:32 AM
```

Example 5: Getting backup information using the resource ID

```
Get-SmBackup -AppObjectId vise-f6\PayrollDatabase
```

This example syntax gets backup information using the specified resource ID.

```
BackupId BackupName BackupTime BackupType
-----
1 Payroll Dataset_vise-f6_08... 8/4/2015 11:02:32 AM Full Backup
2 Payroll Dataset_vise-f6_08... 8/4/2015 11:23:17 AM
```

Get-SmBackupReport

Gets reports about backup operations based on the options you specify.

Syntax

```
Get-SmBackupReport [-FromDateTime] <DateTime> [-ToDateTime] <DateTime>
[-Backup] <String> [-Status] <String> [-Policy] <String> [-
ResourceGroup] <String> [-Resource] <String> [-HostName] <String> [-
Plugin] <PluginCode> [-BackupId] <Int64> [-JobId] <Int64>
```

Detailed Description

Gets reports about backup operations based on the options you specify. You can specify whether you want to get details about a specific backup or a summary of all backups performed using a SnapCenter instance. For any integer value provided for date, value is taken as 1/1/0001 12:00 AM.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
FromDateTime	Specifies that you want to get backup operations reports for backups run between a specified day and time. This option provides the start date and time. You can specify the date and time using any date and time format string. For example, "2/2/2015 8:52PM". If the cmdlet is run from the remote computer, the output will be shown based on the SnapCenter Server time zone.	false	false	
ToDateTime	Specifies that you want to get backup operations reports for backups run between a specified day and time. This option provides the end date and time. You can specify the date and time using any date and time format string. For example, "2/2/2015 8:52PM". If the cmdlet is run from the remote computer, the output will be shown based on the SnapCenter Server time zone.	false	false	
Backup	Specifies that you want to get a detailed backup report for the given backup.	false	true (ByPropertyName)	
Status	Specifies that you want information about backup jobs with a specified status. Valid values are: completed, failed, warning, and canceled.	false	true (ByPropertyName)	
Policy	Specifies that you want reports about backup jobs associated with a specified policy.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ResourceGroup		false	true (ByPropertyName)	
Resource	Specifies the resource for which you want backup reports.	false	true (ByPropertyName)	
HostName	Specifies the name of the host on which the backup was taken.	false	true (ByPropertyName)	
BackupId	ID of the backup for which to get a report.	true	true (ByPropertyName)	
JobId	ID of the backup job for which to get a report.	true	true (ByPropertyName)	
Plugin	Specify the plug-in code to generate the report. For custom plug-ins, specify the custom plug-in name for example, hana, mysql.	false	true (ByPropertyName)	

Examples

Example 1: Getting a backup report for a date range

```
Get-SmBackupReport -FromDate "1/29/2015" -ToDate "2/3/2015"
```

This example syntax gets a report on backups from January 29th 2015 to February 3rd, 2015.

```
SmBackupId    : 113
SmJobId       : 2032
StartDateTime : 2/2/2015 6:57:03 AM
EndDateTime   : 2/2/2015 6:57:11 AM
Duration      : 00:00:07.3060000
CreatedDateTime : 2/2/2015 6:57:23 AM
Status        : Completed
ProtectionGroupName : Clone
SmProtectionGroupId : 34
PolicyName    : Vault
SmPolicyId    : 18
BackupName    : Clone_SCSPR0019366001_02-02-2015_06.57.08
VerificationStatus : NotVerified
PluginCode    : SCC
PluginName    : hana
PluginDisplayName: SAP HANA
JobHost       : R60618C4A79V1
SmBackupId    : 114
SmJobId       : 2183
StartDateTime : 2/2/2015 1:02:41 PM
EndDateTime   : 2/2/2015 1:02:38 PM
Duration      : -00:00:03.2300000
CreatedDateTime : 2/2/2015 1:02:53 PM
Status        : Completed
ProtectionGroupName : Clone
SmProtectionGroupId : 34
PolicyName    : Vault
SmPolicyId    : 18
BackupName    : Clone_SCSPR0019366001_02-02-2015_13.02.45
VerificationStatus : NotVerified
PluginCode    : SCO
PluginName    : Oracle Database
PluginDisplayName: Oracle Database
JobHost       : R60618C4A79V1
```

Example 2: Getting a backup report for a dataset and status type

```
Get-SmBackupReport -Status completed -Dataset Secondary
```

This example syntax gets a report on all backups for dataset "Secondary" that have the "Completed" status.


```
SmBackupId      : 24
SmJobId         : 310
StartDateTime   : 1/12/2015 8:50:49 AM
EndDateTime     : 1/12/2015 8:50:48 AM
Duration        : -00:00:00.6900000
CreatedDateTime : 1/12/2015 8:51:05 AM
Status          : Completed
ProtectionGroupName : Secondary
SmProtectionGroupId : 5
PolicyName      : Vault
SmPolicyId      : 18
BackupName      : Secondary_SCSPR0019366001_01-12-2015_08.50.49
VerificationStatus : NotVerified
PluginCode      : SCC
PluginName      : hana
PluginDisplayName: SAP HANA
JobHost         : R60618C4A79V1
SmBackupId      : 52
SmJobId         : 585
StartDateTime   : 1/15/2015 6:49:07 AM
EndDateTime     : 1/15/2015 6:49:21 AM
Duration        : 00:00:13.8370000
CreatedDateTime : 1/15/2015 6:49:18 AM
Status          : Completed
ProtectionGroupName : Secondary
SmProtectionGroupId : 5
PolicyName      : Vault
SmPolicyId      : 18
BackupName      : Secondary_SCSPR0019366001_01-15-2015_06.49.08
VerificationStatus : NotVerified
PluginCode      : SCO
PluginName      : Oracle Database
PluginDisplayName: Oracle Database
JobHost         : R60618C4A79V1
```

Example 3: Getting a detailed backup report

```
Get-SmBackupReport -BackupName Secondary_SCSPR0019366001_01-15-2015_06.49.08
```

Get a detailed backup for the backup "Secondary_SCSPR0019366001_01-15-2015_06.49.08".

```

BackedUpObjects : {TestDB1, TestDB2, TestDB3, TestDB4...}
FailedObjects: {}
BackupType      : Full Backup
IsScheduled     : False
SmBackupId      : 52
SmJobId         : 585
StartDateTime   : 1/15/2015 6:49:07 AM
EndDateTime     : 1/15/2015 6:49:21 AM
Duration        : 00:00:13.8370000
CreatedDateTime : 1/15/2015 6:49:18 AM
Status          : Completed
ProtectionGroupName : Secondary
SmProtectionGroupId : 5
PolicyName      : Vault
SmPolicyId      : 18
BackupName      : Secondary_SCSPR0019366001_01-15-2015_06.49.08
VerificationStatus : NotVerified
PluginCode      : SCO
PluginName      : Oracle Database
PluginDisplayName: Oracle Database
JobHost         : R60618C4A79V1

```

Get-SmBackupsForPointInTimeRecovery

Get all the backups required to be mounted or cataloged for point in time recovery operation.

Syntax

```

Get-SmBackupsForPointInTimeRecovery [-AppObjectId] <appObject Id> [-
PluginCode] <plugincode> [-BackupId] <String> [-BackupName] <String>
[-OracleUntilScn] <Int64> [-OracleUntilTime] <'yyyy-MM-dd HH:mi:ss'>
[-Archive] <Hashtable[]> [-DisplayInGroups] <> [-OnlyBackupsForMount]
<> [-OnlyBackupsForCatalog] <>

```

Detailed Description

The backups of a tablespace, pluggable database, or tablespace in pluggable database should be cataloged and mounted to perform point in time recovery. This command lists the backups required to be mounted or cataloged based on scn or date and time.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
AppObjectId	Specifies the application object identifier about which you want to get information. Specify the application object identifier format as 'host\database' for Oracle standalone database or 'clustername\database' for Oracle RAC database.	true	false	
PluginCode	Specifies the plugincode.	true	false	
BackupId	Specifies the ID of the backup about which you want to get information.	false	false	
BackupName	Specifies the name of the backup about which you want to retrieve information.	false	true (ByPropertyName)	
OracleUntilScn	Specifies the SCN till which you want to get backups to recover.	false	true (ByPropertyName)	
OracleUntilTime	Specifies the date and time till which you want to get backups to recover. You must specify the date and time in the 'yyyy-MM-dd HH:mm:ss' format. For example: '2020-06-29 20:30:00'	false	true (ByPropertyName)	
Archive	Specifies the secondary (SnapVault or SnapMirror) storage location details (destination volume) for each unique primary storage (source volume).For example: -Archive @{Primary="oracle_vs1:db1_data_vol";Secondary="my_vs1:my_vol_iscsi_SECONDARY"},@{Primary="oracle_vs2:db1_log_vol";Secondary="oracle_vs2_mirror:db1_data_log_mirror"}	false	true (ByPropertyName)	
DisplayInGroups	Set this flag to get the result in groups of mounted or not mounted and cataloged or non cataloged backups.	false	true (ByPropertyName)	
OnlyBackupsForMount	Set this flag to get the result in groups of only mounted or not-mounted backups.	false	true (ByPropertyName)	
OnlyBackupsForCatalog	Set this flag to get the result in groups of only cataloged or non-cataloged backups.	false	true (ByPropertyName)	

Examples

Example 1: Getting backups for Point In Time Recovery Until SCN

```
Get-SmBackupsForPointInTimeRecovery -AppObjectId "linux7-6.gdl.englab.netapp.com\lvm12" -BackupId 5 -PluginCode SCO -OracleUntilScn 2693464
```

This example syntax gets backups for Point In Time Recovery Until SCN 2693464.

```
BackupId : 5
BackupName : linux7-6_gdl_englab_netapp_com_lvm12_linux7-6_08-05-2020_05.21.11.0188_0
BackupType : Oracle Database Data Backup
MountStatus :
CatalogingStatus : NotCataloged
```

Example 2: Getting backups for Point In Time Recovery Until Time

```
Get-SmBackupsForPointInTimeRecovery -AppObjectId "linux7-6.gdl.englab.netapp.com\lvm12" -PluginCode SCO -BackupId 5 -OracleUntilTime "2020-08-05 05:24:40" -OnlyBackupsForCatalog
```

This example syntax gets backups for Point In Time Recovery Until time "2020-08-05 05:24:40"

```

BackupId : 5
BackupName : linux7-6_gdl_englab_netapp_com_lvm12_linux7-6_08-05-
2020_05.21.11.0188_0
BackupType : Oracle Database Data Backup
MountStatus :
CatalogingStatus : NotCataloged
BackupId : 7
BackupName : linux7-6_gdl_englab_netapp_com_lvm12_linux7-6_08-05-
2020_05.21.11.0188_1
BackupType : Oracle Database Log Backup
MountStatus :
CatalogingStatus : NotCataloged
BackupId : 9
BackupName : linux7-6_gdl_englab_netapp_com_lvm12_linux7-6_08-05-
2020_05.21.11.7922_0
BackupType : Oracle Database Data Backup
MountStatus :
CatalogingStatus : NotCataloged
BackupId : 11
BackupName : linux7-6_gdl_englab_netapp_com_lvm12_linux7-6_08-05-
2020_05.21.11.7922_1
BackupType : Oracle Database Log Backup
MountStatus :
CatalogingStatus : NotCataloged

```

Example 3: Getting backups for PITR using secondary locators and Until SCN

```

Get-SmBackupsForPointInTimeRecovery -PluginCode SCO -AppObjectId "linux7-
6.gdl.englab.netapp.com\lvm12" -BackupId 5 -Archive @{Primary="svm1-
scc2554-263-
264:R706221F756V1_NFS_DB_DB1_DATA";Secondary="hnkn_sec:R706221F756V1_NFS_D
B_DB1_DATA_1_dst"},@{Primary="svm1-scc2554-263-
264:R706221F756V1_NFS_DB_DB1_REDO";Secondary="hnkn_sec:R706221F756V1_NFS_D
B_DB1_REDO_dst"},@{Primary="svm1-scc2554-263-
264:R706221F756V1_NFS_DB_DB1_LOG";Secondary="hnkn_sec:R706221F756V1_NFS_DB
_DB1_LOG_1_dst"} -OracleUntilScn 2188355

```

This example syntax gets backups for Point In Time Recovery using secondary locators and Until SCN 2693464.

```
BackupId : 5
BackupName : linux7-6_gdl_englab_netapp_com_lvm12_linux7-6_08-05-
2020_05.21.11.0188_0
BackupType : Oracle Database Data Backup
MountStatus :
CatalogingStatus : NotCataloged
```

Get-SmCertificateSettings

Displays the certificate status for the SnapCenter Server or a SnapCenter plug-in host.

Syntax

```
Get-SmCertificateSettings [-Server] <> [-Host] <> [-HostName]
<String>
```

Detailed Description

Displays the certificate status for the SnapCenter Server or a SnapCenter plug-in host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Server	Displays the certificate status for the server on which SnapCenter is installed.	true	false	
Host	Displays the certificate status for the Snapcenter host.	true	false	
HostName	Specifies the name of the host only when the Host parameter is specified.	true	false	

Examples

Example 1: Displays certificate settings for server

```
Get-SmCertificateSettings -Server
```

This example syntax displays certificate settings for server.

True

Example 2: Displays certificate settings for Host

```
Get-SmCertificateSettings -Host -HostName  
R71104B320CV1.mva.gdl.englab.netapp.com
```

This example syntax displays certificate settings for host.

```
HostName      : R71104B320CV1.mva.gdl.englab.netapp.com  
CAEnabled     : True  
CAStatus      : Connection is broken.  
CAIssues      : Host: R71104B320CV1.mva.gdl.englab.netapp.com.  
Reason: Trusted chain certificates are missing for the  
               certificate  
'R71104B320CV1.mva.gdl.englab.netapp.com'. Check if intermediate and root  
CA certificates  
               exist in the trusted root store.  
  
Name          :  
Type          :  
Id            :  
Host          :  
UserName      :  
Passphrase    :  
Deleted       : False  
Auth          : SMCoreContracts.SmAuth  
IsClone       : False  
CloneLevel    : 0  
Hosts         : {}  
StorageName   :  
ResourceGroupNames :  
PolicyNames   :  
Key           : 0  
NsmObjectID   : 0  
SizeOfSmObject : SMCoreContracts.SmObjectSize
```

Get-SmClone

Gets information about existing clones.

Syntax

```
Get-SmClone [-CloneName] <String> [-CloneId] <String> [-Dataset]
<String> [-BackupName] <String> [-BackupId] <String> [-AppObjectName]
<String> [-AppPluginCode] <PluginCode> [-ListStorageFootprint]
<SwitchParameter>
```

Detailed Description

Gets information about existing clones. You can also search existing clones based on clone name, clone ID, application object, and backup ID.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
CloneName	Specifies that you want information about a single clone.	false	true (ByPropertyName)	
CloneId	Provides a clone ID for the clone about which you want information. You can get the clone ID by running Get-SmClone without any input, and then use the clone ID to retrieve more detailed information about the specified clone.	false	true (ByPropertyName)	
Dataset	Retrieves information based on dataset name.	false	true (ByPropertyName)	
BackupName	Retrieves information based on backup name.	false	true (ByPropertyName)	
BackupId	Retrieves information based on a specified backup ID. Get the backup ID by running Get-SmBackup without parameters.	false	true (ByPropertyName)	
AppObjectName	Retrieves information based on database name.	false	true (ByPropertyName)	
AppPluginCode	Specifies the application plug-in type of the resource. Possible values are SCSQL and SCO.	false	false	
ListStorageFootprint	List the storage footprint information such as storage resource name, type, and junction path in case of volume. This parameter is applicable to SCC plug-in.	false	false	

Examples

Example 1: Retrieving information about all clones

```
Get-SmClone
```

This example syntax retrieves information about all clones.

```
CloneName   : cds__clone__06-18-2015_13.51.03
CloneStartTime : 6/18/2015 1:50:57 PM
CloneEndTime   : 6/18/2015 1:51:03 PM
Databases      : {SourceDB = test,CloneDB = testabcdefg}
CloneId: 4
CloneName     : payrollclone_dataset__clone__08-05-2015_14.41.11
CloneStartTime : 8/5/2015 2:40:41 PM
CloneEndTime   : 8/5/2015 2:41:11 PM
Databases      : {SourceDB = payroll,CloneDB = payroll__clone}
```

Example 2: Retrieving information for a clone dataset

```
Get-SmClone -Dataset payrollclone_dataset
```

This example syntax retrieves information for the specified clone dataset.

```
CloneId: 4
CloneName   : payrollclone_dataset__clone__08-05-2015_14.41.11
CloneStartTime : 8/5/2015 2:40:41 PM
CloneEndTime   : 8/5/2015 2:41:11 PM
Databases      : {SourceDB = payroll,CloneDB = payroll__clone}
```

Example 3: Retrieving clone information for a backup

```
Get-SmClone -BackupName cds_vise-f4_06-18-2015_13.50.52.1978
```

This example syntax retrieves the clone information for the specified backup.

```
CloneId: 3
CloneName  : cds__clone__06-18-2015_13.51.03
CloneStartTime : 6/18/2015 1:50:57 PM
CloneEndTime   : 6/18/2015 1:51:03 PM
Databases    : {SourceDB = test,CloneDB = testabcdefg}
```

Example 4: Getting clone information for a database

```
Get-SmClone -AppObjectName vise-f3\sqlexpress\payroll
```

This example syntax retrieves information for the specified database.

```
CloneId: 4
CloneName  : payrollclone_dataset__clone__08-05-2015_14.41.11
CloneStartTime : 8/5/2015 2:40:41 PM
CloneEndTime   : 8/5/2015 2:41:11 PM
Databases    : {SourceDB = payroll,CloneDB = payroll__clone}
```

Example 5: Retrieving clone information using a backup ID

```
Get-SmClone -BackupId 7
```

This example syntax retrieves clone information using the specified backup ID.

```
CloneId: 4
CloneName  : payrollclone_dataset__clone__08-05-2015_14.41.11
CloneStartTime : 8/5/2015 2:40:41 PM
CloneEndTime   : 8/5/2015 2:41:11 PM
Databases    : {SourceDB = payroll,CloneDB = payroll__clone}
```

Example 6: Retrieving clone information along with storage footprint for HANA plug-in resources

```
Get-SmClone -ListStorageFootprint
```

This example syntax retrieves clone information along with storage footprint for HANA plug-in resources.

```

CloneId   : 38
CloneName: scspr0965644001.gdl.englab.netapp.com_hana_MDC_H14
CloneStartTime   : 11/15/2019 4:15:41 AM
CloneEndTime    : 11/15/2019 4:19:17 AM
Resources: Source = H14, Clone = H14
StorageFootPrint : StorageResourceType : SDStorageDir, StorageResource :
buck.gdl.englab.netapp.com:/vol/NFS_H14_MDCMT_DATA_10_234_131_229111519000
1059572, JunctionPath : /Scb461b683-f1cb-4350-a1a1-0f0d29b62d3f
CloneId   : 39
CloneName: scspr0965644001.gdl.englab.netapp.com_hana_H14
CloneStartTime   : 11/15/2019 5:39:06 AM
CloneEndTime    : 11/15/2019 5:40:06 AM
Resources: Source = H14, Clone = H14
StorageFootPrint : StorageResourceType : SDStorageLunPath, StorageResource
:
buck:/vol/SAN_H14_SC_DATA_10_234_176_1201115190121551593/SAN_H14_SC_DATA_1
0_234_176_120

```

Get-SmCloneJob

Gets information about existing clone jobs.

Syntax

```

Get-SmCloneJob [-PluginCode] <PluginCode> [-ResourceGroupName] <String>
[-Resource] <Hashtable[]>

```

Detailed Description

Gets and displays information about existing clone jobs based on the plug-in code and the resource group.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode		true	true (ByPropertyName)	
ResourceGroupName		false	false	
Resource		false	false	

Examples

- Example 1: Getting information about the existing clone jobs running at the resource group level. -

```
Get-SmCloneJob -ResourceGroupName RG1 -PluginCode SCSQL
```

This example syntax retrieves information about the existing clone jobs running at the resource group level.

CloneJobName	ResourceGroupName	ResourceName
CLMJob	RG1	

- Example 2: Getting information about the existing clone jobs running at the resource level. -

```
Get-SmCloneJob -Resource @{"Host"="R708202074BV1.hnk2.com"; "Type"="SQL Database"; "Names"="R708202074BV1\SQL2019\MDML_DB1"} -PluginCode SCSQL
```

This example syntax gets information about the existing clone jobs running at the resource level.

CloneJobName	ResourceGroupName	ResourceName
cl2	R708202074BV1\SQL2019\MDML_DB1	

Get-SmCloneReport

Get reports about clone operations based on the options you specify.

Syntax

```
Get-SmCloneReport [-FromDateTime] <DateTime> [-ToDateTime] <DateTime> [-ResourceGroup] <String> [-Resource] <String> [-Status] <String> [-HostName] <String> [-Plugin] <PluginCode> [-JobId] <Int64>
```

Detailed Description

Get reports about clone operations based on the options you specify. For any integer value provided for date, value is taken as 1/1/0001 12:00 AM.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
FromDateTime	Specifies that you want to get clone operations reports for clones run between a specified day and time. This option provides the start date and time. You can specify the date and time using the local date and time format string. For example, "2/5/20158:17AM". If the cmdlet is run from the remote computer, the output will be shown based on the SnapCenter Server time zone.	false	false	
ToDateTime	Specifies that you want to get clone operations reports for clones run between a specified day and time. This option provides the end date and time. You can specify the date and time using the local date and time format string. For example "2/5/20159:56AM". If the cmdlet is run from the remote computer, the output will be shown based on the SnapCenter Server time zone.	false	false	
ResourceGroup		false	false	
Resource	Specifies the resource for which you want clone reports.	false	false	
Status	Specifies that you want information about clone jobs with the specified status. Valid values are: completed, failed, warning, and canceled.	false	false	
HostName	Specifies the name of the host on which the clone resides.	false	false	
Plugin	Specify the plug-in code to generate the report. For custom plug-ins, specify the custom plug-in name for example, hana, mysql.	false	false	
JobId	ID of the clone job for which to get a report.	true	false	

Examples

Example 1: Getting a clone report for a date range

```
Get-SmCloneReport -FromDate "7/31/2015" -HostName  
SCSPR0054212005.mycompany.com
```

This command syntax gets a report for all clones after July 31st, 2015 on the given host.

```
SmCloneId      : 1  
SmJobId        : 186  
StartDateTime   : 8/3/2015 2:43:02 PM  
EndDateTime     : 8/3/2015 2:44:08 PM  
Duration        : 00:01:06.6760000  
Status         : Completed  
ProtectionGroupName : Draper  
SmProtectionGroupId : 4  
PolicyName      : OnDemand_Clone  
SmPolicyId      : 4  
BackupPolicyName : OnDemand_Full_Log  
SmBackupPolicyId : 1  
CloneHostName   : SCSPR0054212005.mycompany.com  
CloneHostId     : 4  
CloneName       : Draper__clone__08-03-2015_14.43.53  
SourceResources : {Don, Betty, Bobby, Sally}  
ClonedResources : {Don_DRAPER, Betty_DRAPER, Bobby_DRAPER, Sally_DRAPER}  
SmJobError      :  
PluginCode      : SCO  
PluginName      : Oracle Database  
PluginDisplayName : Oracle Database
```

Example 2: Getting a clone report for a clone job

```
Get-SmCloneReport -JobId 186
```

This command syntax gets a clone report for the given job ID.

```

SmCloneId      : 1
SmJobId        : 186
StartDateTime   : 8/3/2015 2:43:02 PM
EndDateTime     : 8/3/2015 2:44:08 PM
Duration:       00:01:06.6760000
Status         : Completed
ProtectionGroupName : Draper
SmProtectionGroupId : 4
PolicyName      : OnDemand_Clone
SmPolicyId      : 4
BackupPolicyName: OnDemand_Full_Log
SmBackupPolicyId: 1
CloneHostName   : SCSPR0054212005.mycompany.com
CloneHostId     : 4
CloneName       : Draper__clone__08-03-2015_14.43.53
SourceResources : {Don, Betty, Bobby, Sally}
ClonedResources : {Don_DRAPER, Betty_DRAPER, Bobby_DRAPER, Sally_DRAPER}
SmJobError      :
PluginCode      : SCO
PluginName      : Oracle Database
PluginDisplayName : Oracle Database

```

Get-SmCompatibilityFile

Obtains the latest version of the compatibility file from the NetApp Support Site.

Syntax

```
Get-SmCompatibilityFile [-Auth] <String>
```

Detailed Description

Obtains the latest version of the compatibility file from the NetApp Support Site. The compatibility file contains information about the latest supported SnapCenter and plug-in versions. SnapCenter uses this information to identify when component upgrades are available.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Auth	Specifies the authorization token. This is used for executing this cmdlet in scheduled jobs.	false	false	

Examples

Example 1: Gets the latest compatibility file

```
Get-SmCompatibilityFile
```

This example syntax retrieves the latest compatibility file from the NetApp Support Site, and displays the version of the compatibility file now deployed on your system.

Compatibility file version: 1.0.8

Get-SmConfigSettings

Displays the configuration settings for the SnapCenter Server host or a SnapCenter plug-in host.

Syntax

```
Get-SmConfigSettings [-Server] <> [-Key] <String> [-Agent] <> [-  
HostName] <String> [-Key] <String> [-Plugin] <> [-HostName]  
<String> [-PluginCode] <PluginCode> [-Key] <String>
```

Detailed Description

Displays the configuration settings for the SnapCenter Server host or a SnapCenter plug-in host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Server	Displays the configuration values for the server on which SnapCenter is installed.	true	false	
Key	Specifies the configuration key information you want to display. You can specify a specific key name or specify All to display all configuration information. You can specify multiple keys in to double quotation with Comma (like : "RESTTimeout,MaxVerificationJobPerServer").	true	false	
Agent	Displays the configuration values for the SMCORE agent.	true	false	

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Specifies the name or IP address of the host, only when the Agent or Plugin parameters are specified.	true	false	
Plugin	Displays the configuration information of the plug-in host.	true	false	
PluginCode	Specifies which plug-in configuration you want to display. Valid values are SCSQL and SCO.	true	false	

Examples

Example 1: Getting configuration settings on a custom plugin host

```
Get-SmConfigSettings -Agent -HostName SNAPCENTER113.sscore.test.com -Key all
```

This example syntax gets all configuration settings on custom plug-in host.

```
Key: PLUGIN_OPERATION_TIMEOUT_IN_MSEC    Value: 3600000    Details: Plug-in
API operation Timeout
Key: SERVER_API_TIMEOUT_IN_SEC    Value: 180    Details: Web Service API
Timeout
Key: ALLOWED_CMDS    Value: *;    Details: Allowed Host OS Commands
```

Example 2: Getting configuration value for a specific custom plugin configuration parameter

```
Get-SmConfigSettings -Agent -HostName SNAPCENTER113.sscore.test.com -Key
ALLOWED_CMDS
```

This example syntax gets the configuration parameter value for the key ALLOWED_CMDS setting on the custom plug-in host.

```
Key: ALLOWED_CMDS Value: mount *; unmount *; Details: Allowed Host OS Commands
PS C:\Users\administrator.SCCORE>
```

Example 3: Getting a single configuration value for the SnapCenter Server

```
Get-SmConfigSettings -Server -Key WindowsRemoteInstallProcessTimeout
```

This example syntax displays the configuration value for a single SnapCenter Server key.

Key: WindowsRemoteInstallProcessTimeout Value: 900 Details: Windows remote install/uninstall process wait time (in seconds).

Example 4: Getting a more than one configuration values for the SnapCenter Server

```
Get-SmConfigSettings -Server -Key  
"RESTTimeout,MaxVerificationJobPerServer"
```

This example syntax displays the configuration value for a single SnapCenter Server key.

```
Key: RESTTimeoutValue: 10800000 Details: REST Timeout for SnapManager  
proxy (in milliseconds).  
Key: MaxVerificationJobPerServerValue: 20 Details: Maximum verification  
job that can be run per server.
```

Example 5: Getting all configuration settings on a plugin host including custom port

```
Get-SmConfigSettings -Agent 10.236.172.64 -Key all
```

This example syntax displays all the configuration settings for a plug-in host, including the custom SMcore port.

```
Key: SMSServerURL Value: https://WINDOWS-D38M60U.englab.netapp.com:8146  
Details: SMS server url.  
Key: SMSServer Value: localhost Details: SMS server.  
Key: VSCProtocolValue: https Details: VSC protocol.  
Key: RESTTimeoutValue: 10800000 Details: REST Timeout for SMCore proxy  
(in milliseconds).  
Key: RESTConnectionLimitValue: 1500 Details: The maximum number of  
concurrent connections allowed on REST endpoint.  
Key: ServicesBaseAddressValue: https://localhost:8152 Details: Service  
base address.  
Key: SnapCenterServerVersionValue: 1.0.0.0Details: SnapCenter server  
version.  
Key: PSDirectoryValue: WindowsPowerShell\v1.0\Modules\SnapCenter\log  
Details: PS directory.  
Key: smcoreport Value: 8152 Details: SMCore port.
```

Get-SmCredential

Gets credentials of the plug-ins that are registered with the SnapCenter Server.

Syntax

```
Get-SmCredential [-Name] <String>
```

Detailed Description

Gets and displays the credential information of all the plug-ins that are registered with the SnapCenter Server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name		false	true (ByPropertyName)	

Examples

Example 1: Get all Credentials

```
Get-SmCredential
```

Example 2: Get particular Credential

```
Get-SmCredential -Name RunAs1
```

Example 3: Get particular Azure NetApp Credential

```
Get-SmCredential -Name RunAsAzure1
```

```
Output of above Get-SmCredential command:
Id : 3
RunAsName  : RunAsAzure1
OwnerId: 1
AuthMode   : AzureCredential
ClientSecret :
TenantId   : ten
ClientId    : cl
```

Get-SmDataCollectionEmsSchedule

Retrieves the EMS data collection schedule.

Syntax

```
Get-SmDataCollectionEmsSchedule
```

Detailed Description

Retrieves the EMS data collection schedule. By default, EMS data collection occurs every seven days, starting one week from your installation date. You can also configure EMS data collection.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	---------------

Examples

Example 1: Getting the EMS data collection schedule

```
Get-SmDataCollectionEmsSchedule
```

This example syntax retrieves your EMS data collection schedule

```
StartTime DaysInterval
-----
"08/27/2015 2:00 AM"
7
```

Get-SmDataCollectionEmsStatus

Retrieves the EMS data collection status.

Syntax

```
Get-SmDataCollectionEmsStatus
```

Detailed Description

Retrieves the EMS data collection status. Getting the status information shows whether you have enabled or disabled your EMS data collection.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	---------------

Examples

Example 1: Getting EMS data collection status

```
Get-SmDataCollectionEmsStatus
```

This example syntax retrieves your EMS data collection status.

Enabled

True

Get-SmDataCollectionEmsTarget

Gets information about the EMS data collection target.

Syntax

```
Get-SmDataCollectionEmsTarget
```

Detailed Description

Gets information about the EMS data collection target. The EMS data collection target is the storage system to which you want to send the EMS messages.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	------------------

Examples

Example 1: Getting the EMS data collection target storage system

```
Get-SmDataCollectionEmsTarget
```

This example syntax retrieves the EMS collection target storage system

Target

SVM1

Get-SmDomain

Gets all the domains registered with the SnapCenter server.

Syntax

```
Get-SmDomain [-Name] <String>
```

Detailed Description

Gets and displays information of all the domains or a specific domain registered with SnapCenter Server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	NETBIOS Name of the registered domain to get the information.	false	true (ByPropertyName)	

Examples

Example 1: Gets all the domains registered with SnapCenter Server.

```
Get-SmDomain
```

```
Result:
Id : 2
Name   : ad12
DomainFQDN : ad12.test.netapp.com
DCHostIPAddresses :
TrustedDomains :
CreatedOn  : 4/11/2018 10:19:49 PM
ModifiedOn : 4/13/2018 2:37:53 AM
Port      : 389
Protocol   : LDAP
DCHostNames:
Id : 1
Name   : ad19
DomainFQDN : ad19.test.netapp.com
DCHostIPAddresses :
TrustedDomains :
CreatedOn  : 9/22/2021 10:06:34 PM
ModifiedOn : 9/23/2021 6:05:29 AM
Port      : 636
Protocol   : LDAPS
DCHostNames: WS9K19DC.ad19.test.netapp.com
```

Example 2: Get a specific registered domain.

```
Get-SmDomain -Name ad12
```

```
Result:
Id : 2
Name : ad12
DomainFQDN : ad12.test.netapp.com
DCHostIPAddresses :
TrustedDomains :
CreatedOn : 4/11/2018 10:19:49 PM
ModifiedOn : 4/13/2018 2:37:53 AM
Port : 389
Protocol : LDAP
DCHostNames:
```

Get-SmDownloadRepository

Provides the SnapCenter Server repository path on the local host. SnapCenter uses this path to store Compatibility File and plug-in installation packages.

Syntax

```
Get-SmDownloadRepository
```

Detailed Description

Provides the SnapCenter Server repository path on the local host. SnapCenter uses this path to store Compatibility File and plug-in installation packages. You can also use this cmdlet after the Set-SmDownloadRepository cmdlet to verify changes to the installation package download repository.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	---------------

Examples

Example 1: Verifying the plugin installation download repository location

```
Get-SmDownloadRepository
```

This example syntax verifies the location of the plug-in installation download repository.

Get-SmDownloads

Gets a supportability metrics between SnapCenter Server version and plug-in version.

Syntax

```
Get-SmDownloads
```

Detailed Description

Gets and displays the details of plug-in versions supported by SnapCenter Servers.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	------------	----------------	---------------

Examples

- Example: Get the details of all the plug-in versions supported by different SnapCenter Server versions. -

```
Get-SmDownloads
```

This example syntax retrieves the supportability metrics between the SnapCenter Server version and the plug-in version.

```
Compatibility file version: 4.4
SMS_Name: SnapCenter Server 2.0
Version : 2.0.0.2953
SMS_GUID: 166EB1F4-0BD6-434E-B2D3-85F64FF9969B
Family_GUID : 52B25C41-C093-4B94-87AA-CC3004A4482D
NOW_Path: http://mysupport.netapp.com/NOW/cgi-bin/software/
Hash: 123123123123123123
Comments: Supports Windows Server 2012 R2
Downloaded : False
Repository_Path :
SupportedPluginPackages : {, , , ...}
IsCurrent : False
ReleaseVersion : 2.0
Name:
Type:
Id :
```



```
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject : SMCoreContracts.SmObjectSize
SMS_Name: SnapCenter Server 2.0 P1
Version : 2.0.1.21
SMS_GUID: 8DBF2456-EB7E-4E26-A324-0AF8864208D3
Family_GUID : 52B25C41-C093-4B94-87AA-CC3004A4482D
NOW_Path: http://mysupport.netapp.com/NOW/cgi-bin/software/
Hash: 123123123123123123
Comments: Supports Windows Server 2012 R2
Downloaded : False
Repository_Path :
SupportedPluginPackages : {, , , ...}
IsCurrent : False
ReleaseVersion : 2.0.1
Name:
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject : SMCoreContracts.SmObjectSize
SMS_Name: SnapCenter Server 2.0 P2
Version : 2.0.1.26
SMS_GUID: AE5A8605-C9C5-4162-8663-E8D9993AB32A
```

```
Family_GUID : 52B25C41-C093-4B94-87AA-CC3004A4482D
NOW_Path: http://mysupport.netapp.com/NOW/cgi-bin/software/
Hash: 123123123123123123
Comments: Supports Windows Server 2012 R2
Downloaded : False
Repository_Path :
SupportedPluginPackages : {, , , ...}
IsCurrent : False
ReleaseVersion : 2.0.1
Name:
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject : SMCoreContracts.SmObjectSize
Note: This is just snippet of the output.
```

Get-SmHost

Gets information about one or more hosts.

Syntax

```
Get-SmHost [-HostNames] <String> [-IncludePluginInfo] <Boolean> [-
IncludeVerificationServerInfo] <Boolean> [-OsType]
<SmOperatingSystemType> [-PluginCode] <PluginCode>
```

Detailed Description

Gets information about one or more hosts. The information includes the host status and plug-ins on the hosts.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostNames		false	true (ByPropertyName)	
IncludePluginInfo		false	true (ByPropertyName)	
IncludeVerificationServerInfo		false	true (ByPropertyName)	
OsType	Specifies the type of operating system running on the host. Valid values are AIX, Windows, Linux, and vSphere.	false	true (ByPropertyName)	
PluginCode		false	true (ByPropertyName)	

Examples

Example 1: Get a SnapCenter registered AIX host

```
Get-SmHost -HostNames aix207-193.gdl.englab.netapp.com
```

This example syntax gets the registered AIX host.

```
OsInfo : SMCoreContracts.SmOperatingSystemInfo
HostName : aix207-193.gdl.englab.netapp.com
IP : 10.10.207.193
Description:
HostId : 63
DomainName : gdl.englab.netapp.com
Version:
Port : 8145
ClusterHost: False
ClusterName:
Members: {}
HostStatus : eHostUp
HostPluginInfos: {}
ColoHost : False
HostConfiguration :
DiscoverPlugin : False
HostUUID :
HostBIOSID :
HostMaintenanceStatus : Production
IsNLBEnabled : False
VerificationServers:
HypervisorType :
IsHypervisorConfigured : False
Preference : 0
OverallStatus : SMCoreContracts.SmHostOverallStatusInfo
IsCatalogHost : False
Name :
Type :
Id :
Host : gdl.englab.netapp.com
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts :
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
SizeOfSmObject :
```

Get-SmHostSignature

Displays the certificate status for the SnapCenter Server or a SnapCenter plug-in host.

Syntax

```
Get-SmHostSignature [-HostName] <String> [-CredentialName] <String>
```

Detailed Description

Displays the certificate status for the SnapCenter Server or a SnapCenter plug-in host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Specifies the name of the host.	true	false	
CredentialName	Specifies the credential name added to SnapCenter.	true	false	

Examples

Example 1: Displays the host signature of Linux Host

```
Get-SmHostSignature -HostName schana01.gdl.englab.netapp.local  
-CredentialName rootlinux
```

This example syntax displays the host signature of Linux Host.

```
HostName FingerPrint Length HostKeyname  
-----  
schana01.gdl.englab.netapp.local  
9E:81:CB:7E:0B:D1:F5:AD:C1:9B:A9:26:EC:F1:2B:D5256 ssh-ed25519
```

Example 2: Displays the host signature of AIX Host

```
Get-SmHostSignature -HostName sccaixlp2.gdl.englab.netapp.com  
-CredentialName rootaix
```

This example syntax displays the host signature of Linux Host.

```
HostNameFingerPrint Length HostKeyname
-----
sccaixlp2.gdl.englab.netapp.com
18:1C:B9:C3:77:DE:57:EB:BC:D8:E2:8B:64:4E:38:66256 ssh-ed25519
```

Get-SmJobSummaryReport

Initiates a job summary report.

Syntax

```
Get-SmJobSummaryReport [-Date] <DateTime> [-JobId] <Int64>
```

Detailed Description

Initiates a job summary report. A job summary report provides information on every job initiated by SnapCenter on a specified day, along with a breakdown of the job status. The job summary report provides similar data to the job information in the Monitor page of the SnapCenter GUI, however here the job information is limited to one day.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Date	Specifies the day for which you want to initiate the job summary report. If the cmdlet is run from the remote computer, the output will be shown based on the SnapCenter Server time zone.	false	true (ByValue, ByPropertyName)	
JobId	To be deleted.	false	true (ByValue, ByPropertyName)	

Examples

Example 1: Initiating a job summary report for one day

```
Get-SmJobSummaryReport -Date "1/27/2015"
```

This example syntax gets a job summary report of all jobs run on January 27th, 2015.

```

SmJobId: 1750
JobCreatedDateTime :
JobStartDateTime   : 1/27/2015 12:18:13 PM
JobEndDateTime     : 1/27/2015 12:18:24 PM
JobDuration: 00:00:11.1600000
JobName: Backup of dataset 'Test' with policy 'OnDemand'
JobDescription :
Status : Completed
IsScheduled:
JobError   :
JobType: Backup
PolicyName :
SmJobId: 1781
JobCreatedDateTime :
JobStartDateTime   : 1/27/2015 1:07:14 PM
JobEndDateTime     : 1/27/2015 1:07:03 PM
JobDuration: -00:00:10.8830000
JobName: Backup of dataset 'Clone' with policy 'Vault'
JobDescription :
Status : Completed
IsScheduled:
JobError   :
JobType: Backup
PolicyName :

```

Example 2: Initiating a job summary report for failed jobs on a given day

```
Get-SmJobSummaryReport -Date "1/27/2015" | ?{$_.Status -eq "Failed" }
```

Get a job summary report for failed jobs on January 27th, 2015.

```

SmJobId: 1770
JobCreatedDateTime :
JobStartDateTime   : 1/27/2015 1:01:22 PM
JobEndDateTime     :
JobDuration:
JobName: Backup verification of dataset 'Test' with policy
'VerificationDefault'
JobDescription :
Status : Failed
IsScheduled:
JobError   : Verification server(s) are not configured in the dataset
JobType: Dataset
PolicyName :
SmJobId: 1777
JobCreatedDateTime :
JobStartDateTime   : 1/27/2015 1:06:58 PM
JobEndDateTime     :
JobDuration:
JobName: Backup verification of dataset 'Test' with policy
'VerificationDefault'
JobDescription :
Status : Failed
IsScheduled:
JobError   : Verification server(s) are not configured in the dataset
JobType: Dataset
PolicyName :

```

Get-SmLoadBalanceNode

Lists Network Load Balance (NLB) nodes and Application Request Routing (ARR) status for them.

Syntax

```
Get-SmLoadBalanceNode
```

Detailed Description

Lists Network Load Balance (NLB) nodes and Application Request Routing (ARR) status for them.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	------------------

Examples

Example 1: Getting the current NLB nodes and ARR

```
Get-SmLoadBalanceNode
```

This example syntax lists the current Network Load Balance (NLB) nodes and Application Request Routing (ARR) and their status.

Get-SmLogSettings

Retrieves log settings.

Syntax

```
Get-SmLogSettings [-Server] <> [-Agent] <> [-HostName] <String> [-  
Plugin] <> [-HostName] <String> [-PluginCode] <PluginCode>
```

Detailed Description

Retrieves the log settings for SnapCenter, a host, or a plug-in. Log setting determine the log severity level, the maximum file size for the log file, the maximum number of log file backups to retain, and the maximum size for all job log files.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Server	Retrieves log file settings for SnapCenter Server.	true	false	
Agent	Specifies that you want to retrieve log file settings for SnapCenter host agent.	true	false	
HostName	Provides the host name for the SnapCenter host that will capture the log files.	true	false	
Plugin	Specifies that you want to retrieve log file settings for a plug-in.	true	false	

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode	Provides the plug-in code for the plug-in for which you want to retrieve the log file settings. Valid plug-in codes are SCSQL, SCV, and SCO. For custom plug-ins, the plug-in code is the name of the custom plug-in.	true	false	

Examples

Example 1: Getting log file settings for SnapCenter Server

```
Get-SmLogSettings -Server
```

This example syntax retrieves log file settings for SnapCenter Server.

```
LogSettingsId      : 1
LogSettingsType: Server
LogLevel           : All
MaxFileSize        : 10485760
MaxSizeRollBackups : 10
JobLogsMaxFileSize : 104857600
HostId             :
HostName           :
PluginInfoId       :
PluginCode         :
```

Example 2: Getting log file settings for SnapCenter host agent

```
Get-SmLogSettings -Agent -HostName host123
```

This example syntax retrieves log files for the SnapCenter host agent.

```
LogSettingsId : 1
LogSettingsType: Agent
LogLevel      : All
MaxFileSize: 10485760
MaxSizeRollBackups : 10
JobLogsMaxFileSize : 104857600
HostId : 1
HostName : bryankDev
PluginInfoId :
PluginCode :
```

Example 3: Getting log file settings for plugins

```
Get-SmLogSettings -Plugin -PluginCode SCSQL -HostName bryankDev
```

This example syntax retrieves plug-in log file settings.

```
LogSettingsId : 1
LogSettingsType: Plugin
LogLevel      : Info
MaxFileSize: 10485760
MaxSizeRollBackups : 10
JobLogsMaxFileSize : 104857600
HostId : 1
HostName : bryankDev
PluginInfoId : 1
PluginCode : SMSQL
```

Get-SmLogs

Gets SnapCenter log files.

Syntax

```
Get-SmLogs [-Path] <String> [-AllLogs] <> [-Path] <String> [-
ServerLogs] <> [-Path] <String> [-JobId] <Int64> [-Path] <String>
[-PluginId] <Int64> [-Path] <String> [-HostName] <String> [-
PluginCode] <PluginCode>
```

Detailed Description

Gets SnapCenter log files. Log files are returned in a .zip file. You can retrieve all SnapCenter logs, or logs for a individual plug-in or SnapCenter instance. You can also get logs for a specified job.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Specifies the path for the location to which you want the log .zip file to be written.	true	false	
AllLogs	Indicates that you want to receive all SnapCenter logs, which include SnapCenter server, managed host, and plug-in logs.	true	false	
ServerLogs	Indicates that you want to receive logs for the SnapCenter server only.	true	false	
JobId	Indicates that you want to receive information for a specified job ID.	true	false	
PluginId	Indicates that you want to receive information for the specified plug-in ID.	true	false	
HostName	Specifies the host for the plug-in instance for which you want to retrieve logs.	false	false	
PluginCode	Indicates that you want to create log settings pertaining to a specified plug-in instance. Valid plug-in values are SCSQL and SCO. For example, if you want to retrieve the SnapCenter Plug-in for Microsoft SQL Server logs, the plug-in code is SCSQL.	true	false	

Examples

Example 1: Retrieving all logs

```
Get-SmLogs -AllLogs -Path C:\temp\allLogs.zip
```

This example syntax retrieves all log files.

Example 2: Retrieving SnapCenter Server logs

```
Get-SmLogs -Path C:\temp\serverLogs.zip -ServerLogs
```

This example syntax retrieves all Server logs.

Example 3: Retrieving plugin instance logs

```
Get-SmLogs -HostName host123 -Path C:\temp\ssqlLogs.zip -PluginCode  
SCSQL
```

This example syntax retrieves all plug-in instance logs for SnapCenter Plug-in for Microsoft SQL Server.

Example 4: Retrieving logs for a designated job

```
Get-SmLogs -JobId 1234 -Path C:\temp\job_1234.zip
```

This example syntax retrieves logs for job ID 1234.

Get-SmMultiFactorAuthentication

Gets the MFA configuration of the SnapCenter GUI, Rest API, PowerShell and sccli.

Syntax

```
Get-SmMultiFactorAuthentication [-] <>
```

Detailed Description

Gets the MFA configuration of the SnapCenter GUI, Rest API, PowerShell and sccli.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	------------------

Examples

Example 1: Get MultiFactorAuthentication configuration

```
Get-SmMultiFactorAuthentication
```

This example syntax gets the MFA configuration of the SnapCenter GUI, Rest API, PowerShell and sccli.

IsGuiMFAEnabled = True

ADFSSConfigFilePath = C:\\ADFS_metadata\\FederationMetadata.xml

SCConfigFilePath = c:\\ProgramData\\NetApp\\SnapCenter\\Package Repository\\SnapCenterMFAMetadata.xml

IsRestApiMFAEnabled = False

IsCliMFAEnabled = False

ADFSSHostName = adfs19.ad19domain.com

Get-SmPluginConfiguration

Gets the plug-in configuration for a host.

Syntax

```
Get-SmPluginConfiguration [-PluginCode] <PluginCode> [-HostName]  
<String>
```

Detailed Description

Gets the plug-in information for a host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode	The plug-in code. Valid values are SCW, SCSQL, and SCO.	true	true (ByPropertyName)	
HostName	The name of the host on which the plug-in is installed.	true	true (ByPropertyName)	

Examples

Example 1: Getting plugin configuration information for a host

```
Get-SmPluginConfiguration -PluginCode SCSQL -HostName localhost
```

This example syntax gets the SnapCenter plug-in configuration for the specified host.

```

PluginInfoId :
HostName :
PluginName: SnapCenter Plug-in for Microsoft SQL Server
PluginVersion :
InstallPath :
Description :
VendorName:
EndpointURI : http://localhost:809/SqlManagementService
DateCreated :
DateModified :
Message :
Resources : {}
PluginCode: SMSQL
PluginConfiguration : SMCoreContracts.SmSqlConfiguration
ServiceName :
DisplayName :
ServiceStatus : Unavailable
PluginServiceAction : None
Port : 0
GUID :
PluginCompatibilityStatus : None
LicenseType : None
LicenseKey:
PluginInstallStatus : ePluginInstallStatusUnknown
HostMaintenanceStatus : Production
TCPPort : 0
Auth : SMCoreContracts.SmAuth

```

Get-SmPluginPackage

Gets information about plug-in packages that have been uploaded for a specific custom plug-in.

Syntax

```
Get-SmPluginPackage [-PluginName] <String>
```

Detailed Description

Gets information about the plug-in packages that are uploaded for a specific custom plug-in.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginName	Specifies the name of the custom plug-in for which you want to determine the uploaded plug-ins.	false	false	

Examples

Example 1: Get information about a custom plugin package

```
Get-SmPluginPackage -PluginName DB2
```

This example syntax gets all uploaded package version information of the custom plug-in named DB2.

```
CustomPluginName: DB2
CustomPluginVersion : 1.0
CustomPluginType:
OsInfo   : SMCoreContracts.SmOperatingSystemInfo
Resources : {SMCoreContracts.SmSCCustomResourceType}
RequireFileSystemPlugin : False
UploadedFileName: DB2_1.0.zip
CustomPluginDisplayName : IBM DB2
CustomPluginName: DB2
CustomPluginVersion : 2.0
CustomPluginType:
OsInfo   : SMCoreContracts.SmOperatingSystemInfo
Resources : {SMCoreContracts.SmSCCustomResourceType}
RequireFileSystemPlugin : False
UploadedFileName: DB2_2.0.zip
CustomPluginDisplayName : IBM DB2
```

Get-SmPluginReport

Initiates a plug-in report.

Syntax

```
Get-SmPluginReport [-Plugin] <PluginCode> [-HostName] <String> [-ResourceGroup] <String> [-DayCount] <Int32> [-Terse] <>
```


Detailed Description

Initiates a plug-in report. A plug-in report provides backup information about resources managed by a specified SnapCenter plug-in. For example, the report shows you how many SnapCenter Plug-in for Microsoft SQL Server resources have been backed up, which resources have failed backups, which resources are unprotected, and which resources do not have SnapVault updates. This report provides information for a time period you specify. The default time period is 7 days.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Plugin	Specifies the plug-in code for which you want a plug-in activity report. For example, if you want this report for SnapCenter Plug-in for Microsoft SQL Server, enter SCSQL. Valid plug-in values are SCW, SCSQL, and SMO.	true	true (ByPropertyName)	
HostName	Specifies the name of the host on which the plug-in instance is installed. You can specify the host name or IP address if you want to run a plug-in activity report for only one instance of a plug-in.	false	true (ByPropertyName)	
ResourceGroup		false	true (ByPropertyName)	
DayCount	Indicates the number of days for which you want plug-in activity reported. For example, if you want to get information for the last 5 days, enter 5. The default is 7 days.	false	true (ByPropertyName)	
Terse	Indicates that you want to receive only limited information. Specifying terse gives you just the number of databases that are protected, unprotected, with backups that have failed, and that have no SnapVault updates.	false	false	

Examples

Example 1: Getting a plugin report

```
Get-SmPluginReport -Plugin SCSQL
```

This example syntax gets a plug-in report for the SnapCenter Plug-in for Microsoft SQL Server.

```
BackupCount      : 29
AgedBackupCount  : 25
ProtectedObjectCount :
NotBackedUpObjectCount : 0
UnprotectedObjectCount : 1
FailedBackupObjectCount : 0
UnprotectedBackupObjectCount : 0
AllObjectCount   : 6
Backups          : {Test, Test, Test, Test...}
NotBackedUpObjects : {}
UnprotectedObjects : {TestDB6}
FailedBackupObjects : {}
UnprotectedBackupObjects : {}
Result           : SMCoreContracts.SMResult
TotalCount       : 0
DisplayCount     : 0
Context          :
Job              : SMCoreContracts.SmJob
```

Example 2: Getting a plugin report for a specific plugin instance and number of days

```
Get-SmPluginReport -Plugin SCSQL -HostName
SCSPR0019366001.gdl.mycompany.com
```

This example syntax gets a plug-in report for the SnapCenter Plug-in for Microsoft SQL Server.

```
BackupCount      : 29
AgedBackupCount  : 25
ProtectedObjectCount :
NotBackedUpObjectCount : 0
UnprotectedObjectCount : 1
FailedBackupObjectCount : 0
UnprotectedBackupObjectCount : 0
AllObjectCount   : 6
Backups          : {Test, Test, Test, Test...}
NotBackedUpObjects : {}
UnprotectedObjects : {TestDB6}
FailedBackupObjects : {}
UnprotectedBackupObjects : {}
Result           : SMCoreContracts.SMResult
TotalCount       : 0
DisplayCount     : 0
Context          :
Job              : SMCoreContracts.SmJob
```

Example 3: Limiting the amount of information in the plugin report

```
Get-SmPluginReport -Plugin SCSQL -Terse
```

This example syntax gets a plug-in report for the SnapCenter Plug-in for Microsoft SQL Server that only includes resource counts.

```
BackupCount      : 29
AgedBackupCount  : 25
ProtectedObjectCount :
NotBackedUpObjectCount : 0
UnprotectedObjectCount : 1
FailedBackupObjectCount : 0
UnprotectedBackupObjectCount : 0
AllObjectCount   : 6
```

Get-SmPolicy

Retrieves details about one or more policy.

Syntax

```
Get-SmPolicy [-PolicyName] <String> [-DatasetName] <String>
```

Detailed Description

Retrieves details about one or more policy. You can retrieve details about a specific policy or about all policies in a resource group.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PolicyName	Specifies the name of the policy for which you want details.	false	true (ByPropertyName)	
DatasetName	Specifies a dataset. This parameter retrieves policy details for each policy in the dataset.	false	true (ByPropertyName)	

Examples

Example 1: Retrieving information about a policy

```
Get-SmPolicy -PolicyName "Full Backup with Replication"
```

This example syntax gets information about the specified policy.

```
ApplySnapvaultUpdate: True
ApplyRetention      : True
RetentionCount      : 2
RetentionDays       : 0
ApplySnapMirrorUpdate : True
SnapVaultLabel      : OneTime
MirrorVaultUpdateRetryCount : 7
AppPolicies         : {}
Description         :
PreScriptPath       :
PreScriptArguments  :
PostScriptPath      :
PostScriptArguments :
ScriptTimeout       : 60000
DateModified: 6/10/2015 7:18:50 PM
DateCreated : 6/8/2015 11:03:07 PM
Schedule: SMCoreContracts.SmSchedule
PolicyType  : Backup
```

```

PluginPolicyType: SMSQL
Name: Full Backup with Replication
Type:
Id : 1
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
SmSqlBackupType: FullBackup
CopyOnlyBackup : False
CopyOnlyLogBackup : False
UtmType: None
UtmCounts : 7
UtmDays: 14
RunLiveDBCCBefore : False
RunLiveDBCCAfter : False
RetentionType :
TruncateLog: True
VerificationAfterBackup: False
TransLogMark :
TransLogDescription:
AGBackupType : UsePreferredBackupReplica
AGReplicaType : Primary
AGBackupPriorityMin: 1
AGBackupPriorityMax: 100
VerifyLogBackup: False
MaxDbConcurrentBackup : 35
CreateLogFolderSnapshot: True
DeleteLogFolderSnapshot: False
LogFolderSnapshotRetentionType :
LogFolderSnapshotCounts: 0
LogFolderSnapshotDays : 0
DeleteLogInShare : False
LogInShareRetentionType:
LogInShareCounts :
LogInShareDays :
CopyLogToShare : False
CopyLogToShareType :
VerifyPolicy : SMCoreContracts.SmVerificationPolicy
Name :
Type :
Id :
Host :

```

```
UserName      :
Passphrase    :
Deleted: False
Auth         : SMCoreContracts.SmAuth
IsClone: False
CloneLevel   : 0
```

Example 2: Retrieving information for policies in a dataset

```
Get-SmPolicy -DatasetName DB_ON_I_S_DRIVE_ds
```

```
ApplySnapvaultUpdate: True
ApplyRetention      : True
RetentionCount      : 2
RetentionDays       : 0
ApplySnapMirrorUpdate : True
SnapVaultLabel      : OneTime
MirrorVaultUpdateRetryCount : 7
AppPolicies         : {}
Description          :
PreScriptPath        :
PreScriptArguments   :
PostScriptPath       :
PostScriptArguments  :
ScriptTimeOut        : 60000
DateModified: 6/10/2015 7:18:50 PM
DateCreated : 6/8/2015 11:03:07 PM
Schedule: SMCoreContracts.SmSchedule
PolicyType        : Backup
PluginPolicyType: SMSQL
Name: Full Backup with Replication
Type:
Id : 1
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
SmSqlBackupType: FullBackup
CopyOnlyBackup : False
CopyOnlyLogBackup : False
UtmType: None
```

```

UtmCounts    : 7
UtmDays: 14
RunLiveDBCCBefore  : False
RunLiveDBCCAfter   : False
RetentionType  :
TruncateLog: True
VerificationAfterBackup: False
TransLogMark    :
TransLogDescription:
AGBackupType    : UsePreferredBackupReplica
AGReplicaType   : Primary
AGBackupPriorityMin: 1
AGBackupPriorityMax: 100
VerifyLogBackup: False
MaxDbConcurrentBackup  : 35
CreateLogFolderSnapshot: True
DeleteLogFolderSnapshot: False
LogFolderSnapshotRetentionType :
LogFolderSnapshotCounts: 0
LogFolderSnapshotDays  : 0
DeleteLogInShare       : False
LogInShareRetentionType:
LogInShareCounts       :
LogInShareDays         :
CopyLogToShare          : False
CopyLogToShareType     :
VerifyPolicy            : SMCoreContracts.SmVerificationPolicy
Name                    :
Type                    :
Id                      :
Host                    :
UserName                :
Passphrase              :
Deleted: False
Auth                    : SMCoreContracts.SmAuth
IsClone: False
CloneLevel              : 0

```

GetSmPolicy for custom DB2 plugin

```
Get-SmPolicy -PolicyName SECONDARY_SNAPMIRROR
```

Custom plug-in DB2 policy with SnapMirror update enabled

```
BackupType      : DATA
SchedulerType   : None
RetentionCount  : 24
RetentionDays   : 0
VerificationEnabled : False
ApplyRetention  : True
ApplySnapMirrorUpdate : True
ApplySnapvaultUpdate: False
MirrorVaultUpdateRetryCount : 3
RetentionCount  : 24
RetentionDays   : 0
SnapVaultLabel  :
AppPolicies     : {}
DateCreated     : 8/21/2016 4:23:20 PM
DateModified    : 8/21/2016 4:23:20 PM
Description     : testPolicy
PluginPolicyType: DB2
PolicyType      : Backup
PostScriptArguments :
PostScriptPath   :
PreScriptArguments :
PreScriptPath    :
Schedules       : {}
Schedule: SMCoreContracts.SmSchedule
ScriptTimeout    : 60
Name: SECONDARY_SNAPMIRROR
Type:
Id : 23
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts     : {}
PolicyId  : 23
PluginName : DB2
PluginParams : SMCoreContracts.SmKeyValueCollection
Name :
Type :
Id :
Host :
UserName :
Passphrase :
Deleted : False
```



```
Auth : SMCOREContracts.SMAuth
IsClone : False
CloneLevel : 0
Hosts: {}
```

Get-SmReportSchedule

Get the list of report schedules using this cmdlet.

Syntax

```
Get-SmReportSchedule [-Name] <String> [-Plugin] <PluginCode> [-Enabled] <Boolean>
```

Detailed Description

Get the list of report schedules created either by the logged in user or the users with the same role as that of the logged in user.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Get the schedule based on the schedule name.	true	true (ByPropertyName)	
Plugin	Get the schedule based on the Plug-in name. Specify "all" to get the schedules configured with "All Plug-ins" Plug-in.	true	true (ByPropertyName)	
Enabled	Get the schedules for a specific schedule status (enabled or disabled). Pass \$true or 1 to fetch all the enabled schedules and \$false or 0 to fetch all the disabled schedules.	false	true (ByPropertyName)	

Examples

Example 1: Get the details of a specific report schedule.

```
Get-SmReportSchedule -Name schedule1
```

This example gets the details of a specific schedule.

```
ScheduleReportId : 225
ScheduleName      : Schedule1
Enabled           : True
PluginCode        : SCO
PluginName        : Oracle Database
PluginDisplayName : Oracle Database
FormatType        : PDF
DayOfTheWeek      : Monday
DayOfTheMonth     :
TriggerTime       : 21:00
EmailSubject      : SnapCenter Weekly Report for Oracle Database
FromEmail         : user@domain.com
Recipients        : user1@domain.com,user2@domain.com
UserId           : 1
RoleId            : 1
ReportData        : Backup,Clone,Restore,Protection
Frequency         : 9:00 pm Monday every week
CreatedBy         : Administrator
ScheduleType      : Weekly
```

Example 2: Get the report schedules based on plug-in name.

```
Get-SmReportSchedule -Plugin SCO
```

This example gets the list of schedules created for a specific plug-in.

```

ScheduleReportId : 225
ScheduleName : Schedule1
Enabled : True
PluginCode: SCO
PluginName: Oracle Database
PluginDisplayName : Oracle Database
FormatType: PDF
DayOfTheWeek : Monday
DayOfTheMonth :
TriggerTime : 21:00
EmailSubject : SnapCenter Weekly Report for Oracle Database
FromEmail : user@domain.com
Recipients: user1@domain.com,user2@domain.com
UserId: 1
RoleId: 1
ReportData: Backup,Clone,Restore,Protection
Frequency : 9:00 pm Monday every week
CreatedBy : Administrator
ScheduleType : Weekly
ScheduleReportId : 217
ScheduleName : Schedule2
Enabled : True
PluginCode: SCO
PluginName: Oracle Database
PluginDisplayName : Oracle Database
FormatType: PDF
DayOfTheWeek :
DayOfTheMonth :
TriggerTime : 01:01
EmailSubject : SnapCenter Daily Report for Oracle Database
FromEmail : user@domain.com
Recipients: user1@domain.com,user2@domain.com
UserId: 1
RoleId: 1
ReportData:
Frequency : 1:01 am every day
CreatedBy : Administrator
ScheduleType : Daily

```

Example 3: Get the enabled or disabled report schedules.

```
Get-SmReportSchedule -Enabled $true
```

This example gets the list of all enabled schedules. Pass \$true or 1 to fetch all the enabled schedules and

\$false or 0 to fetch all the disabled schedules.

```
ScheduleReportId : 202
ScheduleName      : Schedule3
Enabled           : False
PluginCode        : All
PluginName        : All Plug-ins
PluginDisplayName  : All Plug-ins
FormatType        : PDF
DayOfTheWeek      : Monday
DayOfTheMonth     :
TriggerTime       : 21:00
EmailSubject      : SnapCenter Weekly Report for All Plug-ins
FromEmail         : user@domain.com
Recipients        : user1@domain.com,user2@domain.com
UserId           : 1
RoleId           : 1
ReportData        : Backup,Clone,Restore,Protection
Frequency         : 9:00 pm Monday every week
CreatedBy         : Administrator
ScheduleType      : Weekly
ScheduleReportId  : 221
ScheduleName      : Schedule4
Enabled           : False
PluginCode        : SCO
PluginName        : Oracle Database
PluginDisplayName  : Oracle Database
FormatType        : PDF,CSV
DayOfTheWeek      : monday
DayOfTheMonth     :
TriggerTime       : 01:10
EmailSubject      : SnapCenter Weekly Report for Oracle Database
FromEmail         : user@domain.com
Recipients        : user1@domain.com,user2@domain.com
UserId           : 1
RoleId           : 1
ReportData        :
Frequency         : 1:10 am monday every week
CreatedBy         : Administrator
ScheduleType      : Weekly
```

Get-SmRepositoryBackups

Gets the backup and saves the metadata to the active file system (AFS).

Syntax

```
Get-SmRepositoryBackups [-Hostname] <String> [-SMSbaseUrl] <String>
```

Detailed Description

Gets the backup and saves the metadata to the active file system (AFS).

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Hostname	Specifies the SnapCenter database host name. If the SnapCenter database is hosted by a failover cluster instance (FCI), then specify the FCI owner host name.	false	true (ByPropertyName)	
SMSbaseUrl	Specifies the SnapCenter Server URL. This is required when executing a PowerShell command from a plug-in machine. For example: -SMSbaseUrl https://172.17.166.128:8146	false	true (ByPropertyName)	

Examples

Example 1: Retrieving repository backups

```
Get-SmRepositoryBackups
```

This example syntax retrieves repository backups.

Get-SmRepositoryConfig

Displays the repository configuration information.

Syntax

```
Get-SmRepositoryConfig [-SMSbaseUrl] <String>
```

Detailed Description

Displays the repository configuration information.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SMSbaseUrl	Specifies the SnapCenter Server base URL. The base URL includes the name or IP address of the SnapCenter Server, and, if the remote system is in a different domain from that of the SnapCenter Server, the domain name. For example: https://SNAPCENTER_SERVER_NAME/DOMAIN_NAME .	false	true (ByPropertyName)	

Examples

Example 1: Displaying the MySQL repository details

```
Get-SmRepositoryConfig
```

This example syntax displays the MySQL repository details.

```
ActiveRepository      : 10.236.221.0
ReplicationServers    : 10.236.221.0,10.236.221.34
ReplicationStatus     : Healthy
ReplicationIssues     :
LastSwitchoverTime    : 4/28/2017 7:11:10 AM
```

Example 2: Displaying MySQL repository details from a remote host to SnapCenter using a base URL

```
Get-SmRepositoryConfig -SMSbaseUrl https://10.236.221.75:8146/
```

This example syntax displays the MySQL repository details from a remote host to SnapCenter using the specified base URL.

```
ActiveRepository      : 10.236.221.0
ReplicationServers    : 10.236.221.0,10.236.221.34
ReplicationStatus     : Healthy
ReplicationIssues     :
LastSwitchoverTime    : 4/28/2017 7:11:10 AM
```

Get-SmResourceCredentialName

Gets credential information of the SQL instance that are registered with the SnapCenter Server.

Syntax

```
Get-SmResourceCredentialName [-HostName] <String> [-ResourceName]
<String> [-ResourceId] <String>
```

Detailed Description

Gets and displays the credential information of the SQL instance that are registered with the SnapCenter Server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName		false	true (ByPropertyName)	
ResourceName		false	true (ByPropertyName)	
ResourceId		false	true (ByPropertyName)	

Examples

- **Example : Get the credential information of the SQL instance by the resource name. -**

```
Get-SmResourceCredentialName -ResourceName R708202074BV1\SQL2019
```

This example syntax retrieves the credential information of the SQL instance based on the resource name.

```

Name      : R708202074BV1\SQL2019
Type      : SQL Instance
Id        : 20
Host      : R708202074BV1.HNK2.com
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts     : {}
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
SizeOfSmObject : SMCoreContracts.SmObjectSize
Id        : 3
RunAsName  : Hnkn
AuthMode   : Windows
UserName   : HNK2\administrator
Passphrase :
OwnerId:
HostName   :
InstanceName :
CheckforAdministratorPrivilage : False
TargetURL  :
IsSudoEnabled : False

```

Get-SmResourceGroup

Retrieves details about resource groups.

Syntax

```

Get-SmResourceGroup [-ResourceGroupName] <String> [-ListResources] <>
[-ListConfiguration] <> [-ListPolicies] <>

```

Detailed Description

Retrieves details about resource groups. Entering GetSmResourceGroup with no parameters specifies retrieves information about all resource groups.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ResourceGroupName	Specifies a resource group name for which you want to retrieve details.	false	true (ByPropertyName)	
ListResources	Specifies whether or not resources for a resource group are listed.	false	true (ByPropertyName)	
ListConfiguration	Specifies whether or not configuration information for a resource group is listed.	false	true (ByPropertyName)	
ListPolicies	Specifies whether or not policies in a resource group are listed.	false	true (ByPropertyName)	

Examples

Example 1: Getting all resource group information

```
Get-SmResourceGroup
```

This example syntax retrieves information about all resource groups.

```
Description :
CreationTime: 10/10/2016 4:45:53 PM
ModificationTime: 10/10/2016 4:45:53 PM
EnableEmail : False
EmailSMTPServer :
EmailFrom :
EmailTo :
EmailSubject:
EnableSysLog: False
ProtectionGroupType : Backup
EnableAsupOnFailure : False
Policies: {}
HostResourceMapping : {}
Configuration : SMCOREContracts.SmCloneConfiguration
LastBackupStatus: Completed
VerificationServer :
EmailBody :
EmailNotificationPreference : Never
VerificationServerInfo :
SchedulerSQLInstance:
CustomText :
```

```
CustomSnapshotFormat:
SearchResources : False
ByPassRunAs : False
IsCustomSnapshot:
MaintenanceStatus : Production
PluginProtectionGroupTypes : {SMSQL}
Tag :
IsInternal : False
EnableEmailAttachment : False
VerificationSettings: {}
Name: NFS_DB
Type: Group
Id : 2
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts :
StorageName :
ResourceGroupNames :
PolicyNames :
Description :
CreationTime: 10/10/2016 4:51:36 PM
ModificationTime: 10/10/2016 5:27:57 PM
EnableEmail : False
EmailSMTPServer :
EmailFrom :
EmailTo :
EmailSubject:
EnableSysLog: False
ProtectionGroupType : Backup
EnableAsupOnFailure : False
Policies: {}
HostResourceMapping : {}
Configuration : SMCoreContracts.SmCloneConfiguration
LastBackupStatus: Failed
VerificationServer :
EmailBody :
EmailNotificationPreference : Never
VerificationServerInfo :
SchedulerSQLInstance:
CustomText :
CustomSnapshotFormat:
```

```

SearchResources : False
ByPassRunAs : False
IsCustomSnapshot:
MaintenanceStatus : Production
PluginProtectionGroupTypes : {SMSQL}
Tag :
IsInternal : False
EnableEmailAttachment : False
VerificationSettings: {}
Name: Test
Type: Group
Id : 3
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts :
StorageName :
ResourceGroupNames :
PolicyNames :

```

Get-SmResources

Discovers plug-in resources.

Syntax

```

Get-SmResources [-PluginCode] <PluginCode> [-HostName] <String> [-
UseKnownResources] <SwitchParameter> [-AppObjectType] <String> [-
AppObjectId] <String> [-IsDAG] <SwitchParameter> [-InformationAction]
<ActionPreference> [-InformationVariable] <String> [-WhatIf]
<SwitchParameter> [-Confirm] <SwitchParameter>

```

Detailed Description

Discovers plug-in resources. For SnapCenter Plug-in for Microsoft SQL Server, resources include databases, Availability Groups, and SQL Server instances. You can query one host at a time and return information about any plug-in instances installed on that host. You can use this cmdlet to get detailed information about resources located on the specified host. For SnapCenter Plug-in for Oracle Database, resources include Oracle databases and application volumes. This is useful for creating appropriate disk and SMB shares and to include resources in datasets for later data protection. If a request times out when running this cmdlet, you can add the following rest timeout value key to the out from PowerShell config file located at "C:\Windows\System32\WindowsPowerShell\v1.0\Modules\SnapCenter\SnapManager.PSModule.dll.config":

<add key="RESTTimeout" value="10800000" />

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode	The name of the plug-in for which you want to discover resources. Possible inputs include SCSQL, SCW, SCO, HANA, SCU, SCE, and SP.	true	true (ByPropertyName)	
HostName	Specifies the host name. You can query one host at a time.	true	true (ByPropertyName)	
UseKnownResources	Indicates that you want to return the cached resources. You can use this parameter when you have already queried resources from the SnapCenter GUI. In this case, you receive information only about the already discovered resources. You can use this parameter for resource verification. Oracle application volume resources are manually created by the user. These resources will always be obtained from the SnapCenter database because discovery on host is not applicable for them.	false	true (ByPropertyName)	
AppObjectType	Specifies the type of application object. For example, instance, database, or a SAP HANA SingleContainer or MultipleContainers. For SnapCenter Plug-in for Oracle Database, valid object types are Database and ApplicationVolume.	false	true (ByPropertyName)	
AppObjectId	Specifies the AppObjectId of resource. For example, -AppObjectId MVA-RX200-S13\SQLEXPRESS\DB16. For Oracle databases and application volume resources, the ID is of the format HostName\ResourceName.	false	true (ByPropertyName)	
IsDAG	Required parameter that enables SnapCenter to discover Microsoft Exchange Database Availability Groups (DAGs) when you use the SnapCenter Plug-in for Microsoft Exchange Server.	false	true (ByPropertyName)	
WhatIf		false	false	
Confirm		false	false	

Name	Description	Required ?	Pipeline Input	Default Value
DatabaseName	SAP HANA database name.	false	true (ByValue, ByPropertyName)	
ListStorageFootprint		false	true (ByValue, ByPropertyName)	
SID	This is a SAP HANA database specific parameter. A SAP HANA system is identified by a unique 3 letter system ID (SID). For example, ABC.	false	true (ByValue, ByPropertyName)	
ResourceType	Specifies the type of application object. For example, instance, database, or a SAP HANA SingleContainer or MultipleContainers.	false	true (ByValue, ByPropertyName)	
TenantDatabaseName	This is a SAP HANA database specific parameter. It is the name of the tenant database for SAP HANA Multitenant Database.	false	true (ByValue, ByPropertyName)	
ResourceName	This can be used to filter resources by their names	false	true (ByValue, ByPropertyName)	

Examples

Example 1: Discovering resources on a host

```
Get-SmResources -HostName 'vise-f6.sddev.mycompany.com' -PluginCode
MSFT_SQL
```

This example syntax discovers the resources for the Microsoft SQL plug-in on the specified host.

PluginCode OperationResults

MSFT_SQL {SMCoreContracts.SmObjectOperationResult, SMCoreContract...

Example 2: Listing storage content of custom DB2 plugin resource

```
Get-SmResources -HostName 'sccorelinux61.sccore.test.com' -PluginCode DB2
-AppObjectName financeDB -ListStorageFootprint
```

This example syntax lists resource details along with StorageFoot print details of the custom plug-in resource named financeDB of DB2.

```

Completed Discovering resources: Job Id [123]
ResourceName : financeDB
ResourceVersion :
ResourceId    : sccorelinux61.sscore.test.com\Db2\financeDB
ResourceType : Instance
Protected: No
RunAsName:
ResourceSettings :
MountPaths    :
StorageFootPrint : StorageResourceType : SDStorageDir, StorageResource :
financeDB :/vol/SM1_SRC_sccorelinux61_sscore_test_com

```

Example 3: Listing SAP HANA databases of type SingleContainer

```

Get-SmResources -HostName 'scspr0204312001.gdl.englab.netapp.com'
-PluginCode HANA -AppObjectType SingleContainer

```

This example syntax lists all SAP HANA databases of resource type SingleContainer.

```

Completed Discovering Resources: Job Id [564]
DatabaseName : NonMDC6
SID : LMN
UserStoreKeys:
bGluOGfG3efSlYJZQMqOttTQH5C283MUtNTlOHU1IYhUbAH+zBtCpXAr/v89mO2Is9IoQuNKjO
OGeKD/iv4vYaP+2hK0VNM8YOf8zAU58u24RZGTrLjcLZX0OeH0JwPgGZ5Ljml629LkU7ArBMfW
Xokq6Q==
FileBackupPath : /hana/shared/LMN/HDB01/backup/data
FileBackupPrefix : SnapCenter_
OSDBUser :
ResourceId    : scspr0204312001.gdl.englab.netapp.com\hana\LMN
ResourceUid   : LMN
PluginName    : hana
Host : scspr0204312001.gdl.englab.netapp.com
ResourceType : SingleContainer
Protected: No
RunAsName:
ResourceSettings :
MountPaths    :

```

Example 4: Listing SAP HANA databases of type Multitenant Database Container

```
Get-SmResources -HostName 'scspr0204312001.gdl.englab.netapp.com'  
-PluginCode HANA -AppObjectType MultipleContainers
```

This example syntax lists SAP HANA databases of resource type MultipleContainers.

```
Completed Discovering Resources: Job Id [565]  
DatabaseName : NewRes1  
SID: BGB  
UserStoreKeys :  
YmdiOd9V1LuiyloAsPoQhXb1I32XN8mu4kmsXUT1eWA/wsEBIr0YbxAniqNQCWPJxot/bw24xE  
fTr1IUOuP8wXGP4t/DluFo4HfNIYIpEAQ9BuK9ehMQagGY9DwbsvtTrrueVzPCi0E4LafV4+Ws  
LdLaow==  
FileBackupPath : /hana/shared/PPP/HDB01/backup/data  
FileBackupPrefix : SnapCenter_  
OSDBUser :  
TenantDatabaseName : hhh  
TenantType : SingleTenant  
ResourceId : scspr0204312001.gdl.englab.netapp.com\hana\BGB\hhh  
ResourceUid: BGB\hhh  
PluginName : hana  
Host : scspr0204312001.gdl.englab.netapp.com  
ResourceType : MultipleContainers  
Protected : No  
RunAsName :  
ResourceSettings :  
MountPaths :
```

Example 5: Listing all SAP HANA resources of specified host

```
Get-SmResources -PluginCode 'hana' -HostName  
'schana02.gdl.englab.netapp.com' -UseKnownResources
```

This example lists all the SAP HANA databases of a selected host.

```
Completed Discovering Resources: Job Id [21]  
DatabaseName: R57  
SID : R57  
UserStoreKeys :  
cjU3uItRwnENhBzpUwKFGMsPL+sWzrS0LwLvH+BVhDJEh+hxGEBF00tcKka6ElLUjyXEPDULjX  
dVqw6GmlkIr+UuIa4Zq+pnGKlt0zRbM6E1ZxE8k6r8HElNgHrjY3JUsUvBS7RNQlOirVC6R2n9  
3Qfd9A==  
FileBackupPath :  
FileBackupPrefix: SnapCenter_
```

```

OSDBUser: r57adm
TenantDatabaseNames : {R57, TDB01, TDB02, TDB03}
TenantType : MultiTenant
ResourceId : schana02.gdl.englab.netapp.com\hana\MDC\R57
ResourceUid : MDC\R57
PluginName : hana
Host: schana02.gdl.englab.netapp.com
ResourceType: MultipleContainers
Protected : No
RunAsName :
ResourceSettings:
MountPaths :
DiscoveryType : Auto
IsAuthenticated : Yes
DatabaseName: MDC
SID : MT1
UserStoreKeys :
bXQxDY8049rvqv2jPtrmFNChY9CuhhNBSnsSJ9Fzo13LYquhwnlDknOd+QeJepEFFSIEX0AxR
FcYnQVmlRR5Ky2P3oi2vgEUrPqe0UoHkfBe/QgjDeeaIrBir4CNIiXZVwKFxOm0oLxXcf4Uluo
/amAhw==
FileBackupPath :
FileBackupPrefix: SnapCenter_
OSDBUser: root
TenantDatabaseNames : {}
TenantType : MultiTenant
ResourceId : schana02.gdl.englab.netapp.com\hana\MDC\MT1
ResourceUid : MDC\MT1
PluginName : hana
Host: schana02.gdl.englab.netapp.com
ResourceType: MultipleContainers
Protected : No
RunAsName :
ResourceSettings:
MountPaths :
DiscoveryType : Manual
IsAuthenticated : Not Applicable
DatabaseName : NonMDC_SN
SID : H01
UserStoreKeys:
aDAX85jqzWC0G9U7i7ohDgG1VxG7E8AxaUKyD2BeRnv+fF3sluc9aZDdPUyaWgJwQ5ZAAe0IPB
Y/l1PGkli2DgffnbhPjwu9fPg+nKhlerLyjXp26txx+CJJWHAniekIAsJxLdc9aUrcKO4Xm5N2
wdNgdQ==
FileBackupPath :
FileBackupPrefix : SnapCenter_
OSDBUser : user
ResourceId : schana02.gdl.englab.netapp.com\hana\H01

```



```
ResourceId    : H01
PluginName    : hana
Host : schana02.gdl.englab.netapp.com
ResourceType  : SingleContainer
Protected: No
RunAsName:
ResourceSettings :
MountPaths    :
DiscoveryType: Manual
IsAuthenticated : Not Applicable
```

Example 6: Listing all the resources of a specified resource type

```
Get-SmResources -PluginCode 'hana' -HostName
'schana02.gdl.englab.netapp.com' -UseKnownResources -ResourceType
'MultipleContainers' -DatabaseName 'R57'
```

This example lists all the resources of a specified resource type.

```
Completed Discovering Resources: Job Id [47]
DatabaseName    : R57
SID: R57
UserStoreKeys   :
FileBackupPath  :
FileBackupPrefix : SnapCenter_
OSDBUser       :
TenantDatabaseName :
TenantType      : MultiTenant
ResourceId      : schana02.gdl.englab.netapp.com\hana\MDC\R57
ResourceId      : MDC\R57
PluginName      : hana
Host           : schana02.gdl.englab.netapp.com
ResourceType    : MultipleContainers
Protected       : No
RunAsName       :
ResourceSettings :
MountPaths      :
DiscoveryType    : Auto
IsAuthenticated : No
```

Example 7: Trigger plug-in discovery and list the resources of specified host

```
Get-SmResources -PluginCode 'hana' -HostName  
'schana02.gdl.englab.netapp.com' -UseKnownResources:$false
```

This example syntax lists all resources of specified host.

```
Completed Discovering Resources: Job Id [21]  
DatabaseName: R57  
SID : R57  
UserStoreKeys :  
cjU3uItRwnENhBzpUwKFGMsPL+sWzrS0LwLvH+BVhDJEh+hxGEBF00tcKka6ElLUjyXEPDULjX  
dVqw6GmlkIr+UuIa4Zq+pnGKlt0zRbM6E1ZxE8k6r8HElNgHrjY3JUUsUvBS7RNQlOirVC6R2n9  
3Qfd9A==  
FileBackupPath :  
FileBackupPrefix: SnapCenter_  
OSDBUser: r57adm  
TenantDatabaseNames : {R57, TDB01, TDB02, TDB03}  
TenantType : MultiTenant  
ResourceId : schana02.gdl.englab.netapp.com\hana\MDC\R57  
ResourceUid : MDC\R57  
PluginName : hana  
Host: schana02.gdl.englab.netapp.com  
ResourceType: MultipleContainers  
Protected : No  
RunAsName :  
ResourceSettings:  
MountPaths :  
DiscoveryType : Auto  
IsAuthenticated : Yes  
DatabaseName: MDC  
SID : MT1  
UserStoreKeys :  
bXQxDY8049rvqv2jPtrmFNChT9CuhhNBSnsSJ9Fzo13LYquhwnlDknOd+QeJepEFFSIEX0AxR  
FcYnQVmlRR5Ky2P3oi2vgEUrPqe0UoHkfBe/QgjDeeaIrBir4CNIiXZVwKFxOm0oLxXcf4Uluo  
/amAhw==  
FileBackupPath :  
FileBackupPrefix: SnapCenter_  
OSDBUser: root  
TenantDatabaseNames : {}  
TenantType : MultiTenant  
ResourceId : schana02.gdl.englab.netapp.com\hana\MDC\MT1  
ResourceUid : MDC\MT1  
PluginName : hana  
Host: schana02.gdl.englab.netapp.com  
ResourceType: MultipleContainers  
Protected : No
```

```

RunAsName      :
ResourceSettings:
MountPaths     :
DiscoveryType  : Manual
IsAuthenticated : Not Applicable
DatabaseName   : NonMDC_SN
SID            : H01
UserStoreKeys:
aDAX85jqzWC0G9U7i7ohDgG1VxG7E8AxaUKyD2BeRnv+fF3sluc9aZDdPUyaWgJwQ5ZAAe0IPB
Y/11PGkli2DgffnbhPjwu9fPg+nKh1ErLyjXp26txx+CJJWHAniekIAsJxLdc9aUrcKO4Xm5N2
wdNgdQ==
FileBackupPath :
FileBackupPrefix : SnapCenter_
OSDBUser       : user
ResourceId      : schana02.gdl.englab.netapp.com\hana\H01
ResourceUid     : H01
PluginName      : hana
Host            : schana02.gdl.englab.netapp.com
ResourceType    : SingleContainer
Protected       : No
RunAsName:
ResourceSettings :
MountPaths      :
DiscoveryType: Manual
IsAuthenticated : Not Applicable

```

Example 8: Listing the resources for given sid and resource type

```

Get-SmResources -HostName 'schana02.gdl.englab.netapp.com' -PluginCode
HANA -ResourceType MultipleContainers -UseKnownresources -SID 'R57'
-DatabaseName 'R57'

```

This example lists all the resources of a specified host.

```

Completed Discovering Resources: Job Id [1692]
DatabaseName: R57
SID : R57
UserStoreKeys :
cjU3YuClvIPicEl3zD+B6o/fev9RR0vicLMY9+9iW3DGz0WN1WiAVHFywsnSJh3vlksKbR75f2
klpfhgkI27yTZPxuja5HqHsTQVrW6ZITfirN9hfM6lsHeI38LSBNNaKLCsfU4kk6Okk6QzZL+R
Vthtlg==
FileBackupPath :
FileBackupPrefix: SnapCenter_
OSDBUser: r57adm
TenantDatabaseNames : {R57, TDB01, TDB02, TDB03}
TenantType : MultiTenant
ResourceId : schana02.gdl.englab.netapp.com\hana\MDC\R57
ResourceUid : MDC\R57
PluginName : hana
Host: schana02.gdl.englab.netapp.com
ResourceType: MultipleContainers
Protected : No
RunAsName :
ResourceSettings:
MountPaths :
DiscoveryType : Auto
IsAuthenticated : Yes

```

Example 8: Get details of the specified resource using AppObjectId

```

Get-SmResources -PluginCode 'SCSQL' -HostName
'schana02.gdl.englab.netapp.com' -AppResourceId 'MVA-RX200-
S13\SQLEXPRESS\DB16'

```

This example syntax displays the details of the resources (including cloud protection).

```

DBName: DB16
    DBVersion : 11.0.2100
    DBId      : MVA-RX200-S13\SQLEXPRESS\DB16
    DBType    : SQL Database
    Protected : Yes
    OverallStatus :
    CloudProtected: Yes
    CloudProtectedPolicies : sql_fulllog_backup_policy_daily

```

Example 9: Listing all Oracle Plug-in resources on a specified host

```
Get-SmResources -PluginCode 'SCO' -HostName 'R8092776CF4V1.HNK2.com'  
-UseKnownResources
```

This example lists all the SnapCenter Plug-in for Oracle resources on a specified host.

```
DBName: DB11  
    DBVersion : 19.0.0.0.0  
    DBId      : R8092776CF4V1.HNK2.com\DB11  
    DBType: Oracle Single Instance  
    Protected : No  
    OverallStatus : Not protected  
DBName: DB13  
    DBVersion : 19.0.0.0.0  
    DBId      : R8092776CF4V1.HNK2.com\DB13  
    DBType: Oracle Single Instance  
    Protected : No  
    OverallStatus : Not protected  
Name   : appVolLun  
Uid    : appVolLun  
Id: R8092776CF4V1.HNK2.com\appVolLun  
Type   : Application Volume  
Protected : No  
OverallStatus : Not protected  
Name   : appVol  
Uid    : appVol  
Id: R8092776CF4V1.HNK2.com\appVol  
Type   : Application Volume  
Protected : No  
OverallStatus : Not protected
```

Example 10: Listing all Oracle application volume resources on a specified host

```
Get-SmResources -PluginCode 'SCO' -HostName 'R8092776CF4V1.HNK2.com'  
-UseKnownResources -AppObjectType 'ApplicationVolume'
```

This example lists all the Oracle application volume resources on a specified host.

```
Name : appVolLun
Uid : appVolLun
Id: R8092776CF4V1.HNK2.com\appVolLun
Type : Application Volume
Protected : No
OverallStatus : Not protected
Name : appVol
Uid : appVol
Id: R8092776CF4V1.HNK2.com\appVol
Type : Application Volume
Protected : No
OverallStatus : Not protected
```

Example 11: Listing all Oracle database resources on a specified host

```
Get-SmResources -PluginCode 'SCO' -HostName 'R8092776CF4V1.HNK2.com'
-UseKnownResources -AppObjectType 'Database'
```

This example lists all the Oracle database resources on a specified host.

```
DBName: DB11
DBVersion : 19.0.0.0.0
DBId : R8092776CF4V1.HNK2.com\DB11
DBType: Oracle Single Instance
Protected : No
OverallStatus : Not protected
DBName: DB13
DBVersion : 19.0.0.0.0
DBId : R8092776CF4V1.HNK2.com\DB13
DBType: Oracle Single Instance
Protected : No
OverallStatus : Not protected
```

Example 12: Get Oracle Plug-in resources on a specified host and filter by resource name

```
Get-SmResources -PluginCode 'SCO' -HostName 'R8092776CF4V1.HNK2.com'
-UseKnownResources -AppObjectType 'ApplicationVolume' -ResourceName
'appVolLun'
```

This example gets the SnapCenter Plug-in for Oracle resources on a specified host and filters it by resource name

```
Name   : appVolLun
Uid    : appVolLun
Id: R8092776CF4V1.HNK2.com\appVolLun
Type   : Application Volume
Protected : No
OverallStatus : Not protected
```

Example 13: Trigger Discovery of Oracle Plug-in resources on a specified host and lists them

```
Get-SmResources -PluginCode 'SCO' -HostName 'R8092776CF4V1.HNK2.com'
```

This example triggers discovery of SnapCenter Plug-in for Oracle resources on a specified host and lists them.

```
Completed Discovering Resources: Job Id [3172]
```

```
DBName: DB11
```

```
DBVersion : 19.0.0.0.0
DBId      : R8092776CF4V1.HNK2.com\DB11
DBType: Oracle Single Instance
Protected : No
OverallStatus : Not protected
DBName: DB13
DBVersion : 19.0.0.0.0
DBId      : R8092776CF4V1.HNK2.com\DB13
DBType: Oracle Single Instance
Protected : No
OverallStatus : Not protected
Name      : appVolLun
Uid       : appVolLun
Id: R8092776CF4V1.HNK2.com\appVolLun
Type      : Application Volume
Protected : No
OverallStatus : Not protected
Name      : appVol
Uid       : appVol
Id: R8092776CF4V1.HNK2.com\appVol
Type      : Application Volume
Protected : No
OverallStatus : Not protected
```

Example 14: Trigger plug-in discovery and list the resources of specified host for UnixFileSystems

```
Get-SmResources -PluginName 'UnixFileSystems' -HostName  
'linuxfs.gdl.englab.netapp.com' -UseKnownResources:$false
```

This example triggers discovery of UnixFileSystems Plug-in on a specified host and lists them.

```
Completed Discovering Resources: Job Id [420]  
    ResourceName : /netapp/qtree1  
    ResourceId   :  
linuxfs.gdl.englab.netapp.com\UnixFileSystems\netapp/qtree1  
    ResourceUid  : /netapp/qtree1  
    PluginName   : UnixFileSystems  
    Host         : linuxfs.gdl.englab.netapp.com  
    ResourceType : Path  
    Protected    : Yes  
    RunAsName    :  
    ResourceSettings :  
    MountPaths   :  
    DiscoveryType: Auto  
    IsAuthenticated : Yes  
    ResourceName : /netapp/qtree2  
    ResourceId   :  
linuxfs.gdl.englab.netapp.com\UnixFileSystems\netapp/qtree2  
    ResourceUid  : /netapp/qtree2  
    PluginName   : UnixFileSystems  
    Host         : linuxfs.gdl.englab.netapp.com  
    ResourceType : Path  
    Protected    : Yes  
    RunAsName    :  
    ResourceSettings :  
    MountPaths   :  
    DiscoveryType: Auto  
    IsAuthenticated : Yes
```

Get-SmRestoreReport

Initiates a restore report.

Syntax


```
Get-SmRestoreReport [-JobId] <Int64> [-FromDateTime] <DateTime> [-
ToDateTime] <DateTime> [-Resource] <String> [-Plugin] <PluginCode>
[-HostName] <String>
```

Detailed Description

Initiates a restore report. The restore report tells you which resource was restored on which host and the job status. You can specify the time range for which you want this report. The default time range is the last 7 days. You can also query for restore information about an individual resource. For any integer value provided for date, value is taken as 1/1/0001 12:00 AM.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
JobId	To be deleted.	true	true (ByPropertyName)	
FromDateTime	Specifies that you want to get a restore report for restore jobs run between a specified day and time. This option provides the start date and time. You can specify the date and time using any date and time format string. For example, "2/2/2015 8:52PM". If the cmdlet is run from the remote computer, the output will be shown based on the SnapCenter Server time zone.	false	false	
ToDateTime	Specifies that you want to get a restore report for restore jobs run between a specified day and time. This option provides the end date and time. You can specify the date and time using any date and time format string. For example, "2/2/2015 8:52PM". If the cmdlet is run from the remote computer, the output will be shown based on the SnapCenter Server time zone.	false	false	
Resource	Provides the name of a specific resource for which you want to get a restore report.	false	true (ByPropertyName)	
Plugin	Specify the plug-in code to generate the report. For custom plug-ins, specify the custom plug-in name for example, hana, mysql.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Specifies the name of the host on which the restore was taken.	false	true (ByPropertyName)	

Examples

Example 1: Getting a restore report

```
Get-SmRestoreReport
```

This example syntax gets a restore report.

```
SmJobId      : 2516
StartDateTime : 2/4/2015 1:09:15 PM
EndDateTime   : 2/4/2015 1:09:57 PM
Status: Completed
Resource      : SMCoreContracts.SmObject
RecoveryRequest :
PluginCode: SCO
PluginName: Oracle Database
PluginDisplayName : Oracle Database
SmJobId      : 2535
StartDateTime : 2/5/2015 6:02:19 AM
EndDateTime   : 2/5/2015 6:03:13 AM
Status: Completed
Resource      : SMCoreContracts.SmObject
RecoveryRequest :
PluginCode: SCC
PluginName: SAP HANA
PluginDisplayName : SAP HANA
```

Example 2: Getting a restore report for a specific resource

```
Get-SmRestoreReport -Resource TestDb3
```

This example syntax gets a report on restores performed for the given resource.

```
SmJobId      : 2516
StartDateTime : 2/4/2015 1:09:15 PM
EndDateTime   : 2/4/2015 1:09:57 PM
Status: Completed
Resource      : SMCoreContracts.SmObject
RecoveryRequest :
PluginCode: SCC
PluginName: SAP HANA
PluginDisplayName : SAP HANA
```

Example 3: Getting a restore report for a specific host

```
Get-SmRestoreReport -HostName SCSPR0019366001.gdl.mycompany.com
```

This example syntax gets a restore report for all resources on the given host.

```
SmJobId      : 2516
StartDateTime : 2/4/2015 1:09:15 PM
EndDateTime   : 2/4/2015 1:09:57 PM
Status: Completed
Resource      : SMCoreContracts.SmObject
RecoveryRequest :
PluginCode: SCO
PluginName: Oracle Database
PluginDisplayName : Oracle Database
SmJobId      : 2535
StartDateTime : 2/5/2015 6:02:19 AM
EndDateTime   : 2/5/2015 6:03:13 AM
Status: Completed
Resource      : SMCoreContracts.SmObject
RecoveryRequest :
PluginCode: SCC
PluginName: SAP HANA
PluginDisplayName : SAP HANA
```

Get-SmRole

Get information for one or more RBAC roles.

Syntax

```
Get-SmRole [-Name] <String>
```

Detailed Description

Get information about all the roles associated with SnapCenter. If you specify a specific role, you will return only information about the individual role. This information includes the role description, name.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the role for which you want information. If you do not specify a role name, you will receive information for all available roles.	false	true (ByPropertyName)	

Examples

Example 1: Getting information about all roles

```
Get-SmRole
```

This example syntax retrieves the information about all SnapCenter roles.

Description : Overall administrator of SnapCenter system

Name: SnapCenterAdmin

Type: Administrator

Id : 1

Host:

UserName:

Passphrase :

Deleted : False

Auth: SMCoreContracts.SmAuth

IsClone : False

CloneLevel : 0

Description : Backup and Clone Viewer

Name: Backup and Clone Viewer

Type: Backup and Clone Viewer

Id : 7

Host:

UserName:

Passphrase :

Deleted : False

Auth: SMCoreContracts.SmAuth

IsClone : False

CloneLevel : 0

Description : App Backup and Clone Admin

Name: App Backup and Clone Admin

Type: App Backup and Clone Admin

Id : 8

Host:

UserName:

Passphrase :

Deleted : False

Auth: SMCoreContracts.SmAuth

IsClone : False

CloneLevel : 0

Description : Infrastructure Admin

Name: Infrastructure Admin

Type: Infrastructure Admin

Id : 9

Host:

UserName:

Passphrase :

Deleted : False

Auth: SMCoreContracts.SmAuth

IsClone : False

CloneLevel : 0

Example 2: Getting information about a specific role

```
Get-SmRole -Name "Infrastructure Admin"
```

This example syntax retrieves the information about the specified role.

```
Description : Infrastructure Admin
Name: Infrastructure Admin
Type: Infrastructure Admin
Id : 9
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Get-SmRoleAssignedPermission

Retrieves information about permissions assigned to a designated role.

Syntax

```
Get-SmRoleAssignedPermission [-RoleName] <String>
```

Detailed Description

Retrieves information about permissions assigned to a specified role. The information includes the permission name and its attributes. The attributes are Allow, Create, Read, Update, and Delete.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
RoleName	Specifies the name of the role for which you want permission and permission attribute information.	true	true (ByPropertyName)	

Examples

Example 1: Getting permissions assigned to a role

```
Get-SmRoleAssignedPermission -RoleName SnapCenterAdmin
```

This example syntax gets the permissions assigned to the specified role.

```
AttribCode : create
Name       : DataSet
Type      :
Id        : 1
Host      :
UserName   :
Passphrase :
Deleted    : False
Auth       : SMCoreContracts.SmAuth
IsClone    : False
CloneLevel : 0
AttribCode : delete
Name       : DataSet
Type      :
Id        : 2
Host      :
UserName   :
Passphrase :
Deleted    : False
Auth       : SMCoreContracts.SmAuth
IsClone    : False
CloneLevel : 0
AttribCode : read
Name       : DataSet
Type      :
Id        : 3
Host      :
UserName   :
Passphrase :
Deleted    : False
Auth       : SMCoreContracts.SmAuth
IsClone    : False
CloneLevel : 0
AttribCode : update
Name       : DataSet
Type      :
Id        : 4
Host      :
UserName   :
```

```
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : create
Name      : Policy
Type      :
Id       : 5
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : delete
Name      : Policy
Type      :
Id       : 6
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : update
Name      : Policy
Type      :
Id       : 7
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : Policy
Type      :
Id       : 8
Host      :
UserName   :
Passphrase :
Deleted: False
```



```
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : create
Name       : Backup
Type       :
Id         : 9
Host       :
UserName    :
Passphrase  :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name       : Backup
Type       :
Id         : 10
Host       :
UserName    :
Passphrase  :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : delete
Name       : Backup
Type       :
Id         : 11
Host       :
UserName    :
Passphrase  :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : create
Name       : Host
Type       :
Id         : 13
Host       :
UserName    :
Passphrase  :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
```

```
CloneLevel : 0
AttribCode : delete
Name      : Host
Type      :
Id       : 14
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : Host
Type      :
Id       : 15
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : update
Name      : Host
Type      :
Id       : 16
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : create
Name      : StorageConnection
Type      :
Id       : 17
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : delete
```

```
Name      : StorageConnection
Type      :
Id       : 18
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : StorageConnection
Type      :
Id       : 19
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : update
Name      : StorageConnection
Type      :
Id       : 20
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : create
Name      : Clone
Type      :
Id       : 21
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : delete
Name      : Clone
Type      :
```

```
Id : 22
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name : Clone
Type :
Id : 23
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : update
Name : Clone
Type :
Id : 24
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : create
Name : Provision
Type :
Id : 25
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : delete
Name : Provision
Type :
Id : 26
Host :
```

```
UserName      :
Passphrase    :
Deleted: False
Auth         : SMCoreContracts.SmAuth
IsClone: False
CloneLevel   : 0
AttribCode   : read
Name         : Provision
Type         :
Id           : 27
Host         :
UserName      :
Passphrase    :
Deleted: False
Auth         : SMCoreContracts.SmAuth
IsClone: False
CloneLevel   : 0
AttribCode   : update
Name         : Provision
Type         :
Id           : 28
Host         :
UserName      :
Passphrase    :
Deleted: False
Auth         : SMCoreContracts.SmAuth
IsClone: False
CloneLevel   : 0
AttribCode   : update
Name         : Backup
Type         :
Id           : 45
Host         :
UserName      :
Passphrase    :
Deleted: False
Auth         : SMCoreContracts.SmAuth
IsClone: False
CloneLevel   : 0
AttribCode   : allow
Name         : DashBoard
Type         :
Id           : 51
Host         :
UserName      :
Passphrase    :
```

```
Deleted: False
Auth    : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : allow
Name     : Reports
Type     :
Id      : 52
Host     :
UserName :
Passphrase :
Deleted: False
Auth    : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : allow
Name     : Restore
Type     :
Id      : 53
Host     :
UserName :
Passphrase :
Deleted: False
Auth    : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : allow
Name     : Discovery
Type     :
Id      : 54
Host     :
UserName :
Passphrase :
Deleted: False
Auth    : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : allow
Name     : Plugin_Installation
Type     :
Id      : 58
Host     :
UserName :
Passphrase :
Deleted: False
Auth    : SMCoreContracts.SmAuth
```

```
IsClone: False
CloneLevel : 0
AttribCode : allow
Name      : Migration
Type      :
Id       : 59
Host      :
UserName   :
Passphrase :
Deleted    : False
Auth      : SMCOREContracts.SmAuth
IsClone    : False
CloneLevel : 0
```

Get-SmRolePermissions

Retrieves permissions and associated permission attribute codes available in SnapCenter.

Syntax

```
Get-SmRolePermissions [-Name] <String>
```

Detailed Description

Retrieves permissions and associated permission attribute codes available in SnapCenter. If you specify a permission name, you receive attribute codes associated with that permission. If you do not specify a name, you retrieve all permissions available in SnapCenter.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the Run As account that you want to get information about.	false	true (ByPropertyName)	

Examples

Example 1: Getting information about a specified permission

```
Get-SmRolePermissions -Name DataSet
```

This example syntax lists the information for the specified permission.

PermissionName PermissionCode

DataSet create
DataSet delete
DataSet read
DataSet update

Example 2: Getting a list of permissions available in SnapCenter

```
Get-SmRolePermissions
```

This example syntax displays permissions for all permissions in SnapCenter.

PermissionName PermissionCode

DataSet create
DataSet delete
DataSet read
DataSet update
Policy create
Policy delete
Policy update
Policy read
Backup create
Backup read
Backup delete
Host create
Host delete
Host read
Host update
StorageConnection create
StorageConnection delete
StorageConnection read
StorageConnection update
Clone create
Clone delete
Clone read
Clone update
Provision create
Provision delete
Provision read
Provision update
Backup update
DashBoard allow
Reports allow
Restore allow
Discovery allow
Plugin_Installation allow
Migration allow

Get-SmSMTPServer

Retrieves information about the SMTP server currently configured to send data protection job reports.

Syntax

```
Get-SmSMTPServer
```

Detailed Description

Retrieves information about the SMTP server currently configured to send data protection job reports. The cmdlet displays the name of the SMTP server, the name of the recipient to whom email messages are sent, and the name of the sender. There are no parameters for this cmdlet.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	------------	----------------	---------------

Examples

Example 1: Retrieving SMTP server configuration information

```
Get-SmSMTPServer
```

This example syntax retrieves information about the current SMTP server configuration for SnapCenter.

Get-SmSchedule

Retrieves the schedule information. This command migrates data from SnapManager to SnapCenter plug-in for SQL Server. (This command works only if there are schedules present for SQL Server in SnapManager.)

Syntax

```
Get-SmSchedule [-HostName] <String> [-DisableCurrentGenSchedule] <> [-PluginCode] <PluginCode> [-SMSBaseUrl] <String>
```

Detailed Description

Retrieve the schedule information based on the host name and the plug-in code.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName		true	true (ByPropertyName)	
DisableCurrentGenSchedule		false	true (ByPropertyName)	
PluginCode		true	true (ByPropertyName)	
SMSBaseUrl		false	true (ByPropertyName)	

Examples

- **Example : Retrieve the schedule information based on the host name and the plug-in code. -**

```
Get-SmSchedule -HostName windows2016 -PluginCode SCSQL
```

This example syntax retrieves the schedule information based on the host name and the plug-in code.

```
Schedule detail for the following Resources :  
*****
```

```
Windows2016\INSTANCE1\anul
```

```
Schedule Information :
```

```
*****
```

```
ScheduleStatus : Enabled
```

```
Schedule: Backup Schedule
```

```
BackupType : FullBackupAndLogBackup
```

```
TaskName: New2
```

```
ScheduleType: OneTime
```

```
SchedulerType : WINDOWS
```

```
StartTime : 9/13/2020 11:32:00 PM
```

```
EndTime :
```

```
DaysInterval:
```

```
DaysoftheMonth :
```

```
DaysOfTheWeek :
```

```
IntervalDuration:
```

```
MonthlyFrequency:
```

```
MonthsofTheYear :
```

```
RepeatTask_Every_Hour :
```

```
RepeatTask_Every_Mins :
```

```
SchedulerSQLInstance:
```

```
retention      : {SmPSSnapin.GetSmSchedule+Retention,
SmPSSnapin.GetSmSchedule+Retention,
    SmPSSnapin.GetSmSchedule+Retention}
verificationsettings: SmPSSnapin.GetSmSchedule+VerificationSettings
hasVerificationSettings : False
```

Retention Information :

BackupType : DATA
RetentionCount : 7
RetentionDays : 0

BackupType : LOG
RetentionCount : 0
RetentionDays : 7

BackupType : LOG_SNAPSHOT
RetentionCount : 8
RetentionDays : 0

Schedule detail for the following Resources :

Windows2016\INSTANCE1\anul

Schedule Information :

ScheduleStatus : Enabled
Schedule: Backup Schedule
BackupType : FullBackupAndLogBackup
TaskName: NEW6
ScheduleType: OneTime
SchedulerType : WINDOWS
StartTime : 9/14/2020 4:52:00 AM
EndTime :
DaysInterval:
DaysoftheMonth :
DaysOfTheWeek :
IntervalDuration:
MonthlyFrequency:
MonthsofTheYear :
RepeatTask_Every_Hour :
RepeatTask_Every_Mins :
SchedulerSQLInstance:
retention : {SmPSSnapin.GetSmSchedule+Retention,
SmPSSnapin.GetSmSchedule+Retention,

```

    SmPSSnapin.GetSmSchedule+Retention}
verificationsettings: SmPSSnapin.GetSmSchedule+VerificationSettings
hasVerificationSettings : False

Retention Information :
*****

BackupType : DATA
RetentionCount : 7
RetentionDays : 0

BackupType : LOG
RetentionCount : 0
RetentionDays : 7

BackupType : LOG_SNAPSHOT
RetentionCount : 8
RetentionDays : 0

*****
*****
Schedule detail for the following Resources :
*****

Windows2016\INSTANCE1\anul
Schedule Information :
*****

ScheduleStatus : Enabled
Schedule: Backup Schedule
BackupType : FullBackupAndLogBackup
TaskName: NEW7
ScheduleType: OneTime
SchedulerType : WINDOWS
StartTime : 9/14/2020 4:52:00 AM
EndTime :
DaysInterval:
DaysOfMonth :
DaysOfTheWeek :
IntervalDuration:
MonthlyFrequency:
MonthsofTheYear :
RepeatTask_Every_Hour :
RepeatTask_Every_Mins :
SchedulerSQLInstance:
retention : {SmPSSnapin.GetSmSchedule+Retention,
SmPSSnapin.GetSmSchedule+Retention,
SmPSSnapin.GetSmSchedule+Retention}
verificationsettings: SmPSSnapin.GetSmSchedule+VerificationSettings

```

```
hasVerificationSettings : False
```

```
Retention Information :
```

```
*****
```

```
BackupType : DATA
```

```
RetentionCount : 7
```

```
RetentionDays : 0
```

```
BackupType : LOG
```

```
RetentionCount : 0
```

```
RetentionDays : 7
```

```
BackupType : LOG_SNAPSHOT
```

```
RetentionCount : 8
```

```
RetentionDays : 0
```

```
*****
```

```
*****
```

Get-SmServerConfig

Retrieves information about the SnapCenter version currently configured.

Syntax

```
Get-SmServerConfig
```

Detailed Description

Retrieves information about the SnapCenter version currently configured.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	------------------

Examples

Example : Gets information about the SnapCenter version currently configured.

```
Get-SmServerConfig
```

This example syntax gets information about the SnapCenter version currently configured.

Get-SmSnapCenterVersion

Gets the SnapCenter Server version and build number.

Syntax

```
Get-SmSnapCenterVersion [-] <>
```

Detailed Description

Gets the SnapCenter Server version and build number.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	------------	----------------	---------------

Examples

Example 1: Get SnapCenter Server Version

```
Get-SmSnapCenterVersion
```

This example syntax gets the installed SnapCenter Server version and build number.

```
ServerVersion   : 4.5.0.6127
PluginVersion   :
ProductVersion  : 4.5
ProductName: SnapCenter Server 4.5
Result : SMCoreContracts.SMResult
TotalCount : 0
DisplayCount    : 0
Context:
Job: SMCoreContracts.SmJob
```

Get-SmStorageConnection

Retrieves all storage system connections.

Syntax

```
Get-SmStorageConnection [-Storage] <String> [-StorageType] <String> [-
AzureNetAppAccountId] <bigint(20)>
```

Detailed Description

Retrieves information about available storage system connections. You can get information about a specified storage system, or about all of them.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Storage		false	true (ByPropertyName)	
StorageType	Specifies storage type. Valid values are DataOntap and AzureNetAppAccount.	false	true (ByPropertyName)	
AzureNetAppAccount tId	Specifies Azure NetApp Account ID.	false	true (ByPropertyName)	

Examples

Example 1: Getting storage system connections for a specified storage system

```
Get-SmStorageConnection -SVM 172.17.168.13
```

This example syntax retrieves information for a specified storage system connection.

```
UserName: vsadmin
Password:
Port: 80
TransportType : Http
ModifyTime : 1/1/0001 12:00:00 AM
Mode:
OntapiMajorVersion :
OntapiMinorVersion :
Version : NetApp Release 8.2.2X33 Cluster-Mode: Fri Aug 22 06:04:17 PDT
2014
StorageSystemOSType : DataOntap
Passphrase :
Id : 5
Timeout : 60
Uuid:
OperationContext:
PreferredIpAddress :
Aliases : {}
SmIPAddresses : {SMCoreContracts.SmIPAddress,
SMCoreContracts.SmIPAddress, SMCoreContracts.SmIPAddress,
SMCoreContracts.SmIPAddress...}
IPAddresses : {172.17.168.13, 172.17.168.13, 172.17.168.13,
172.17.168.13...}
Name: mva-dev-3270-02-d1.lab.netapp.com
IsResolved : True
IsValid : True
Identity: mva-dev-3270-02-d1.lab.netapp.com
```

Example 2: Getting storage system connections for all available storage systems

```
Get-SmStorageConnection
```

This example syntax gets information about all available storage system connections.

```
UserName: vsadmin
Password:
Port: 80
TransportType : Http
ModifyTime : 1/1/0001 12:00:00 AM
Mode:
OntapiMajorVersion :
OntapiMinorVersion :
Version :
```



```

StorageSystemOSType :
Passphrase :
Id : 1
Timeout : 60
Uuid:
OperationContext:
PreferredIpAddress :
Aliases : {}
SmIPAddresses : {SMCoreContracts.SmIPAddress,
SMCoreContracts.SmIPAddress, SMCoreContracts.SmIPAddress,
SMCoreContracts.SmIPAddress...}
IPAddresses : {172.17.124.165, 172.17.124.165, 172.17.124.165,
172.17.124.165...}
Name: neeraj_vs1
IsResolved : True
IsValid : True
Identity: neeraj_vs1
UserName: vsadmin
Password:
Port: 80
TransportType : Http
ModifyTime : 1/1/0001 12:00:00 AM
Mode:
OntapiMajorVersion :
OntapiMinorVersion :
Version :
StorageSystemOSType :
Passphrase :
Id : 2
Timeout :
Uuid:
OperationContext:
PreferredIpAddress :
Aliases : {}
SmIPAddresses : {SMCoreContracts.SmIPAddress,
SMCoreContracts.SmIPAddress, SMCoreContracts.SmIPAddress,
SMCoreContracts.SmIPAddress...}
IPAddresses : {10.225.13.49, 10.225.13.49, 10.225.13.49, 10.225.13.49...}
Name: rtp-rr1-d2.gdl.mycompany.com
IsResolved : True
IsValid : True
Identity: rtp-rr1-d2.gdl.mycompany.com

```

Example 3: Getting Azure NetApp Account with specified ID

```
Get-SmStorageConnection -StorageType AzureNetAppAccount
-StorageConnectionId 3
```

This example gets information about Azure NetApp Account with specified Storage connection Id.

```
StorageConnectionId : 3
SubscriptionId       : 398e471c-3b42-4ae7-9b59-ce5bb5e6108d
NetAppAccountName    : poojar_SCSHANA_Account
ResourceGroupName    : poojar
StorageOSType        : AzureNetAppAccount
CredentialName       : HCLMain
CredentialId          : 7
ModifyTime           : 10/18/2023 10:15:48 AM
ModifyTimeTicks      : 638332209480000000
StorageBaseId        : 3
Location              : eastus2
```

Get-SmTrustedDomains

Get the trusted domains details of the specified domain registered with SnapCenter Server.

Syntax

```
Get-SmTrustedDomains [-ParentDomainName] <String> [-Credential]
<PSCredential>
```

Detailed Description

Get the trusted domains of the specified domain.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ParentDomainName	NETBIOS Name of the registered domain.	true	true (ByPropertyName)	
Credential	Credentials of any user in the registered domain.	true	true (ByPropertyName)	

Examples

Example 1: Get the trusted domains of the specified domain registered with SnapCenter Server.

```
Get-SmTrustedDomains -ParentDomainName mva -Credential mva\administrator
```

```
Successfully discovered the trusted domains of the specified domain mva.
Id : 1
Name      : mva
DomainFQDN : mva.gdl.englab.netapp.com
DCHostIPAddresses :
TrustedDomains :
gdl.englab.netapp.com,GDL,nb.englab.netapp.com,NB,ict.englab.netapp.com,ICT,
wbu.englab.netapp.com,WBU,eng.netapp.com,ENG,nane.englab.netapp.com,NANE,
svl.englab.netapp.com,SVL
CreatedOn   : 4/11/2018 10:06:34 PM
ModifiedOn  : 4/20/2018 3:26:40 AM
```

Get-SmUserAssignedPermission

Retrieves information about the permissions associated with a specified user.

Syntax

```
Get-SmUserAssignedPermission [-Name] <String>
```

Detailed Description

Retrieves information about the permissions associated with a specified user.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Names the domain\user about whom you want to retrieve permission information.	true	true (ByPropertyName)	

Examples

Example 1: Getting permissions associated with a user

```
Get-SmUserAssignedPermission -Name sddev\administrator
```

This example syntax displays the permissions associated with the specified user.

```
AttribCode : create
Name       : Backup
Type      :
Id        : 9
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name       : Backup
Type      :
Id        : 10
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name       : Host
Type      :
Id        : 15
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name       : DataSet
Type      :
Id        : 3
Host      :
UserName   :
```

```
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : Provision
Type      :
Id       : 27
Host      :
UserName  :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : Clone
Type      :
Id       : 23
Host      :
UserName  :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : allow
Name      : Discovery
Type      :
Id       : 54
Host      :
UserName  :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : allow
Name      : Restore
Type      :
Id       : 53
Host      :
UserName  :
Passphrase :
Deleted: False
```

```
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : Backup
Type      :
Id       : 10
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : create
Name      : Host
Type      :
Id       : 13
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : delete
Name      : Host
Type      :
Id       : 14
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : Host
Type      :
Id       : 15
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
```

```
CloneLevel : 0
AttribCode : update
Name      : Host
Type      :
Id       : 16
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : DataSet
Type      :
Id       : 3
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : Policy
Type      :
Id       : 8
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : create
Name      : Provision
Type      :
Id       : 25
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : delete
```

```
Name      : Provision
Type      :
Id       : 26
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : Provision
Type      :
Id       : 27
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : update
Name      : Provision
Type      :
Id       : 28
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name      : Clone
Type      :
Id       : 23
Host      :
UserName   :
Passphrase :
Deleted: False
Auth      : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : create
Name      : StorageConnection
Type      :
```



```
Id : 17
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : delete
Name : StorageConnection
Type :
Id : 18
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : read
Name : StorageConnection
Type :
Id : 19
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : update
Name : StorageConnection
Type :
Id : 20
Host :
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
AttribCode : allow
Name : DashBoard
Type :
Id : 51
Host :
```

```
UserName      :
Passphrase    :
Deleted: False
Auth         : SMCoreContracts.SmAuth
IsClone: False
CloneLevel   : 0
AttribCode    : allow
Name         : Discovery
Type         :
Id           : 54
Host         :
UserName      :
Passphrase    :
Deleted: False
Auth         : SMCoreContracts.SmAuth
IsClone: False
CloneLevel   : 0
AttribCode    : allow
Name         : Plugin_Installation
Type         :
Id           : 58
Host         :
UserName      :
Passphrase    :
Deleted: False
Auth         : SMCoreContracts.SmAuth
IsClone: False
CloneLevel   : 0
AttribCode    : allow
Name         : Reports
Type         :
Id           : 52
Host         :
UserName      :
Passphrase    :
Deleted: False
Auth         : SMCoreContracts.SmAuth
IsClone: False
CloneLevel   : 0
```

Get-SmUsersAndGroups

Gets information of the user and the group.

Syntax

```
Get-SmUsersAndGroups [-Type] <FilterType>
```

Detailed Description

Valid session is required to get the information like, user, roles, and domain details.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Type		false	false	

Examples

Example 1: Get the user and the group details

```
Get-SmUsersAndGroups -Type ALL
```

This example syntax gets the information of the user and the group.

```
PS C:\> Get-SmUsersAndGroups -Type ALL
```

```
Name           Type Roles           Domain
----           -
administrator User SnapCenterAdmin exchange1
```

Get-SmVerificationServer

Gets information about existing verification servers.

Syntax

```
Get-SmVerificationServer [-Names] <String>
```

Detailed Description

Gets information about existing verification servers. You can get information about specific servers, or all SnapCenter verification servers.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Names	Specifies the names of the verification server about which you want to get information. If you omit the Names parameter, you get information about all SnapCenter verification servers.	false	true (ByPropertyName)	

Examples

Example 1: Getting information about a specified verification server

```
Get-SmVerificationServer -Names mva-s51, mva-s51/instance1
```

This example syntax gets information about a specified verification server.

```
Name: MVA-S51
HostName: MVA-S51.mva.gdl.mycompany.com
PlugIn : SnapManager for SQL
UseDriveLetterIfAvail : True
DefaultMountPointFolder : c:\abc
MaxJobCount : 1
Description :
EndpointURI : http://localhost:809/SqlManagementService
PluginVersion :
Name: mva-s51/instance1
HostName: MVA-S51.mva.gdl.mycompany.com
PlugIn : SnapManager for SQL
UseDriveLetterIfAvail : True
DefaultMountPointFolder : c:\temp
MaxJobCount : 1
Description :
EndpointURI : http://localhost:809/SqlManagementService
PluginVersion :
```

Example 2: Getting information about all SnapCenter verification servers

```
Get-SmVerificationServer
```

This example syntax gets information about all available verification servers.

```

Name: MVA-S51
HostName: MVA-S51.mva.gdl.mycompany.com
PlugIn : SnapManager for SQL
UseDriveLetterIfAvail : True
DefaultMountPointFolder : c:\abc
MaxJobCount : 1
Description :
EndpointURI : http://localhost:809/SqlManagementService
PluginVersion :
Name: MVA-S57-VM2
HostName: MVA-S57-VM2.mva.gdl.mycompany.com
PlugIn : SnapManager for SQL
UseDriveLetterIfAvail : True
DefaultMountPointFolder : c:\temp
MaxJobCount : 1
Description :
EndpointURI :
PluginVersion :
Name: MVA-S51\MTSHASTA
HostName: MVA-S51.mva.gdl.mycompany.com
PlugIn : SnapManager for SQL
UseDriveLetterIfAvail : True
DefaultMountPointFolder : c:\temp
MaxJobCount : 1
Description :
EndpointURI : http://localhost:809/SqlManagementService
PluginVersion :
Name: mva-s51/instance1
HostName: MVA-S51.mva.gdl.mycompany.com
PlugIn : SnapManager for SQL
UseDriveLetterIfAvail : True
DefaultMountPointFolder : c:\temp
MaxJobCount : 1
Description :
EndpointURI : http://localhost:809/SqlManagementService
PluginVersion :

```

Install-SmHostPackage

Installs or upgrades a host plug-in package on one or more hosts.

Syntax

```
Install-SmHostPackage [-HostNames] <String> [-PluginCodes]
<UploadedPluginCode> [-PluginVersions] <Hashtable> [-InstallPath]
<String> [-SkipPreinstallChecks] <SwitchParameter> [-GMSAName]
<String> [-Force] <SwitchParameter>
```

Detailed Description

Installs or upgrades a host plug-in package on one or more hosts. When specifying multiple hosts, all hosts must have the same OS.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostNames	Specifies the hosts on which you want to install or upgrade the plug-in. You can specify one host, or multiple, comma-separated host names. Host names must be entered using the format -HostNames @"hostname") when installing to a single host, or -HostNames @"hostname1", "hostname2") when installing to multiple hosts. You can specify the hostname using either the host FQDN or IP address.	true	true (ByPropertyName)	
PluginCodes	Specifies the code for one or more plug-ins in the packages that you want to install. The following values are valid: SCSQL, SCO, SCW, SCE and hana. For custom plug-ins, the value is the custom plug-in name. For example "CustomPlugin1". You can use a comma-separated list of plug-in codes to install multiple plug-ins.	true	true (ByPropertyName)	
PluginVersions	Specifies in a hash table the custom plug-in name and the version to install. The PluginVersions parameter uses the format @{"customplugin" = "4.0"}	false	true (ByPropertyName)	
InstallPath	Specifies the plug-in installation path, if the path different from the default.	false	true (ByPropertyName)	
SkipPreinstallChecks	Specifies that installation prechecks will not be triggered.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
GMSAName	Specifies that group Managed Service Account (gMSA) name will be used to run the plug-in services.	false	true (ByPropertyName)	
Force	Internal switch.	false	true (ByPropertyName)	

Examples

Example 1: Installing SnapCenter Plug-in for Microsoft SQL Server and SnapCenter Plug-in for Microsoft Windows on a Windows host

```
Install-SmHostPackage -HostNames @("host2012r2.mycompany.com")
-PluginCodes SCSQL,SCW
```

This example syntax installs SnapCenter Plug-in for Microsoft SQL Server and SnapCenter Plug-in for Windows on the specified host.

Example 2: Installing SnapCenter Plug-in for Microsoft SQL Server and SnapCenter Plug-in for Microsoft Windows on multiple hosts

```
Install-SmHostPackage -HostNames @("sql-1.mycompany.com", "sql-
2.mycompany.com") -PluginCodes SCSQL,SCW
```

This example syntax installs SnapCenter Plug-in for Microsoft SQL Server and SnapCenter Plug-in for Microsoft Windows on multiple hosts.

Example 3: Installing a custom plug-in with SnapCenter Plug-in for Oracle and SnapCenter Plug-in for Unix on a Linux host

```
Install-SmHostPackage -HostNames("scspr0098708001.englab.mycompany.com")
-PluginCodes CustomPlugin1,SCO -InstallPath /opt/NetApp/snapcenter/
-PluginVersions @{"customplugin1" = "2.0"}
```

This example syntax installs a custom plug-in along with SnapCenter Plug-in for Oracle and SnapCenter Plug-in for Unix on a Linux host.

Example 4: Installing SnapCenter Plug-in for Microsoft Exchange Server

```
Install-SmHostPackage -HostNames Exchange2016DAG -PluginCodes SCE,SCW
-Verbose
```

This example syntax installs SnapCenter Plug-in for Microsoft Exchange Server on the specified host.

Example 5: Installing SnapCenter Plug-in for SAP HANA Database on the same Windows host

```
Install-SmHostPackage -HostNames 'Windows.Host.lab.com' -PluginCodes  
hana,SCW
```

This example syntax installs the SnapCenter Plug-in for SAP HANA Database on the same host where SnapCenter Server is installed.

Example 6: Installing SnapCenter Plug-in for SAP HANA database on a remote host

```
Install-SmHostPackage -HostNames 'Host.fqdn.lab.com' -PluginCodes hana
```

This example syntax installs the SnapCenter Plug-in for SAP HANA Database on the specified remote host (Windows and Linux).

Example 7: Installing SnapCenter Plug-in for Microsoft SQL Server and SnapCenter Plug-in for Microsoft Windows on a Windows host to run with group Managed Service Account (gMSA)

```
Install-SmHostPackage -HostNames 'host2012r2.NewDomain.com' -PluginCodes  
SCSQL,SCW -GMSAName 'NewDomain\gMSAName$'
```

This example syntax installs SnapCenter Plug-in for Microsoft SQL Server and SnapCenter Plug-in for Windows to run with the mentioned group Managed Service Account (gMSA) name on the specified host.

Example 8: Installing SnapCenter Plug-in for Oracle Database on a AIX host

```
Install-SmHostPackage -HostNames 'aix207-193.gdl.englab.netapp.com'  
-PluginCodes SCO
```

This example syntax installs the SnapCenter Plug-in for Oracle Database on the specified AIX host.

Example 9: Installing SnapCenter Plug-in for Db2 on a AIX host

```
Install-SmHostPackage -HostNames 'aix207-193.gdl.englab.netapp.com'  
-PluginCodes DB2
```

This example syntax installs the SnapCenter Plug-in for Db2 Database on the specified AIX host.

Invoke-DiagnosticLogCollection

Gets SnapCenter log files.

Syntax

```
Invoke-DiagnosticLogCollection [-SnapCenter] <> [-Hosts] <String> [-svms] <String> [-vcenter] <String> [-joblogs] <Int64> [-Cluster] <String>
```

Detailed Description

Gets SnapCenter log files. Log files are returned in a .zip file. You can retrieve all SnapCenter logs, Svms, Vcenter, Cluster or logs for a individual plug-in or SnapCenter instance. You can also get logs for a specified job.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SnapCenter		false	true (ByPropertyName)	
Hosts		false	true (ByPropertyName)	
svms		false	true (ByPropertyName)	
vcenter		false	true (ByPropertyName)	
joblogs		false	true (ByPropertyName)	
Cluster		false	true (ByPropertyName)	

Examples

Example 1: Retrieving all logs

```
Invoke-DiagnosticLogCollection -SnapCenter
```

This example syntax retrieves all log files.

Example 2: Retrieving logs for a designated jobs

```
Invoke-DiagnosticLogCollection -Joblogs 1234,1235
```

This example syntax retrieves logs for job ID 1234 ad 1235.

Example 3: Retrieving Cluster logs

```
Invoke-DiagnosticLogCollection -Cluster host123
```

This example syntax retrieves all cluster node logs.

Example 4: Retrieving Hosts logs

```
Invoke-DiagnosticLogCollection -Hosts hostname1,hostname2
```

This example syntax retrieves all the hosts server,plugin and config logs.

Example 5: Retrieving svms logs

```
Invoke-DiagnosticLogCollection -svms Vserver1,Vserver2
```

This example syntax retrieves all the vserver logs.

Invoke-SCVOVAMigration

Migrates SCV to the virtual appliance.

Syntax

```
Invoke-SCVOVAMigration [-SourceSCVHost] <String> [-  
DestinationSCVOVAHost] <String> [-OVACredential] <String> [-  
ByPassValidationCheck] <> [-Overwrite] <> [-  
ContinueMigrationOnStorageError] <> [-ScheduleOffsetTime] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SourceSCVHost	The IP or hostname of the SCV host that will be migrated to the NDB host	true	false	
DestinationSCVOVAHost	The IP or hostname of the destination NDB host that the SCV host will be migrated to	true	false	

Name	Description	Required ?	Pipeline Input	Default Value
OVACredential	The name of the Run As credentials to use for connecting to the OVA. These Run As credentials must be created on the SnapCenter Server.	true	false	
ByPassValidationCheck	Skip validation that checks if the source SCV host is registered to the same vCenter as the destination NDB host.	false	false	
Overwrite	If enabled, the MySQL database on the NDB host is completely overwritten with the migrated metadata from the source SCV host. All existing metadata on the NDB host, with the exception of storage connections, is deleted. This parameter is recommended for large scale setups.	false	false	
ContinueMigrationOnStorageError	If enabled, migration continues if there are any errors while migrating storage systems. After migration, you must resolve all storage migration errors. Refer to documentation.	false	false	
ScheduleOffsetTime	Use this parameter if the source SCV host and the destination NDB host are in different time zones. Value should be a positive or negative time offset to adjust scheduled backup run times. Specify time difference in the format hh:mm:ss, such as 06:00:00, or -06:00:00 for a negative value.	false	false	

Examples

Example 1: Only required parameters

```
invoke-SCVOVAMigration -SourceSCVHost 10.225.12.187
-DestinationSCVOVAHost 10.225.43.91 -OVACredential ova
```

Example 2: Including optional parameters

```
invoke-SCVOVAMigration -SourceSCVHost 10.225.12.187
-DestinationSCVOVAHost 10.225.43.91 -OVACredential ova
-ByPassValidationCheck -Overwrite -ContinueMigrationOnStorageError
-ScheduleOffsetTime 06:00:00
```

This example includes the use of all optional parameters. See migration help for information on these parameters.

Invoke-SmBackupMigration

Migrates archived backups from SnapManager for Microsoft SQL Server to SnapCenter Plug-in for SQL Server.

Syntax

```
Invoke-SmBackupMigration [-HostName] <String> [-PluginCode]
<PluginCode> [-SMSBaseUrl] <String>
```

Detailed Description

Invokes the operation of migrating archived backups from SnapManager for Microsoft SQL Server to SnapCenter Plug-in for SQL Server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName		true	true (ByPropertyName)	
PluginCode		true	true (ByPropertyName)	
SMSBaseUrl		false	true (ByPropertyName)	

Examples

Example : Migrates archived backups from SnapManager to SnapCenter Plug-in for Microsoft SQL Server

```
Invoke-SmBackupMigration -HostName
windows2016.smsqlqa3.gdl.englab.netapp.com -PluginCode SCSQL
```

This example syntax invokes the operation of migrating archived backups from SnapManager for Microsoft SQL Server to SnapCenter Plug-in for SQL Server.

Invoke-SmBackupVerification

Initiates a verification job. [This command is being deprecated in Snapcenter 4.4 and the support to the command will be stopped in future releases.]

Syntax

```
Invoke-SmBackupVerification [-DatasetName] <String> [-  
VerificationPolicy] <String> [-BackupPolicies] <String> [-  
ScheduleOnly] <> [-SchedulerCredentialName] <String> [-BackupID]  
<String> [-NumBackups] <Int32> [-Auth] <String> [-IsScheduled]  
<Boolean> [-ClusterName] <String> [-SMSBaseUrl] <String> [-IsNLBHost]  
<Boolean> [-ScheduleName] <String> [-Guid1] <String> [-Guid2]  
<String> [-ScheduleType] <String> [-BackupScheduleType] <String>
```

Detailed Description

Initiates a verification job by specifying the dataset backup you want to verify and the verification policy for the operation. When you start a verification job, the Snapshot copy you specify is mounted. The mount operation creates a clone and the cloned database is attached to the verification server you specified in the verification policy. DBCC checkdb is run and any error are recorded for that particular backup. Once verification has finished, the clone database is deleted and the Snapshot copy is unmounted.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
DatasetName	Specifies the dataset name for the backups you want to verify. You can use the verification policy and the backup policy to govern how many and what kind of dataset backups you want to verify.	true	false	
VerificationPolicy	Specifies the verification policy you want to use during backup verification. The verification policy is used to provide scheduling, replication pre-and post script information, and DBCC CHECK options. A verification policy is required for every verification job.	true	false	
BackupPolicies	Specifies one or more backup policies to select the backups to be verified. For example, if you have a Daily, a Weekly, and a Monthly backup policy attached to a dataset. You can specify Monthly, to just verify the monthly backups.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ScheduleOnly	Indicates that you want to schedule verification jobs for the future, rather than run one now. The scheduling information is in the verification policy you specified with the VerificationPolicy parameter.	false	true (ByPropertyName)	
SchedulerCredentialName		false	true (ByPropertyName)	
BackupID	Specifies a backup ID. This parameter allows you to verify specific backups, rather than a group of backups created for a given dataset. If you use this parameter, you do not need to provide the DatasetName.	false	false	
NumBackups	Indicates the number of backups you want to verify for a given dataset. If provided, this parameter overrides the verification policy settings. This allows to you run quick verification checks, without altering the verification policy.	false	false	
Auth	Provides authorization credentials to run this verification job. Authorization credentials allows you to provide different credentials to run verification operations. You want to provide these credentials when your original PowerShell session does not have sufficient RBAC permissions to run the desired operation.	false	false	
IsScheduled	This is for internal use only. This switch parameter indicates that the verification job has been invoked by a schedule.	false	false	
ClusterName	This is for internal use only. This parameter identifies the cluster host name for which the verification job is scheduled.	false	false	
SMSBaseUrl	This is for internal use only. This parameter identifies the SnapCenter-based URL.	false	false	
IsNLBHost	Internal switch that indicates whether this host is part of Network Load Balancing.	false	false	

Name	Description	Required ?	Pipeline Input	Default Value
ScheduleName	Specifies the name of the schedule you want to use for performing deferred verification jobs.	false	false	
Guid1		false	false	
Guid2		false	false	
ScheduleType		false	false	
BackupScheduleType		false	false	

Examples

Example 1: Verifying backups from a specified backup policy

```
Invoke-SmBackupVerification -DatasetName test -VerificationPolicy verifp
-BackupPolicies backup -Verbose
```

This example syntax verifies backups created by a specific policy.

```
PS C:\Software> Invoke-SmBackupVerification -DatasetName test
-VerificationPolicy verifp -BackupPolicies backup -Verbose
VERBOSE: Start Invoke-SmBackupVerification
VERBOSE: ProcessRecord Invoke-SmBackupVerificaition - Begin
VERBOSE: ProcessRecord Invoke-SmBackupVerificaition - End
VERBOSE: Invoke-SmBackupVerification ended successfully.
```

Example 2: Verifying one backup using a backup ID

```
Invoke-SmBackupVerification -DatasetName test -BackupID 109
-VerificationPolicy verifp -Verbose
```

This example syntax verifies backups using a specific backup ID.

```
VERBOSE: Start Invoke-SmBackupVerification
VERBOSE: ProcessRecord Invoke-SmBackupVerificaition - Begin
VERBOSE: ProcessRecord Invoke-SmBackupVerificaition - End
VERBOSE: Invoke-SmBackupVerification ended successfully.
```

Example 3: Scheduling a backup verification

```
Invoke-SmBackupVerification -DatasetName test -VerificationPolicy verifp  
-BackupPolicies backup -ScheduleOnly -SchedulerRunAsName mvawin -Verbose
```

This example syntax schedules a backup verification job for a future time.

```
VERBOSE: Start Invoke-SmBackupVerification  
VERBOSE: ProcessRecord Invoke-SmBackupVerificaiton - Begin  
VERBOSE: ProcessRecord Invoke-SmBackupVerificaiton - End  
VERBOSE: Invoke-SmBackupVerification ended successfully.
```

Example 4: Running a verification job with alternate authentication credentials

```
Invoke-SmBackupVerification -DatasetName test -VerificationPolicy verifp  
-BackupPolicies backup -Auth mvawin
```

This example syntax runs a verification job with alternate authentication credentials.

Example 5: Verifying your most recent backups

```
Invoke-SmBackupVerification -DatasetName test -VerificationPolicy verifp
```

This example syntax verifies your most recent backups.

Example 6: Overwriting the number of backups to be verified in verification policy

```
Invoke-SmBackupVerification -DatasetName test -VerificationPolicy verifp  
-BackupPolicies backup -NumBackups 1
```

This example syntax overwrites the verification policy specified number of backups to be verified.

Invoke-SmConfigureResources

Moves an existing Microsoft SQL Server database from a local disk to a NetApp LUN.

Syntax


```
Invoke-SmConfigureResources [-Resources] <Hashtable[]> [-DataPath]
<String> [-LogPath] <String> [-Files] <Hashtable[]> [-DeleteOriginal]
<> [-PluginCode] <PluginCode> [-DBCC_NOINDEX] <> [-
DBCC_ALL_ERRORMSGs] <> [-DBCC_NO_INFOMSGs] <> [-DBCC_TABLOCK] <> [-
DBCC_PHYSICALONLY] <> [-UpdateTableStatsBeforeDetach] <> [-
RUnDBCCBeforeMigration] <> [-RunDBCCAfterMigration] <>
```

Detailed Description

Moves an existing Microsoft SQL Server database from a local disk to a NetApp LUN. This cmdlet moves and configures either system or user databases for the following configurations:- Configuration of databases on standalone SQL server instances- Configuration of Availability Group SQL databases.- Configuration of SQL Failover Cluster Instance databases.In an Availability Group, you must run this cmdlet separately on both the primary and secondary nodes to ensure databases are moved for all nodes.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Resources	Specifies the resources, in a hashtable, including host, type, name, files, and destination.Host indicates the name of the host from which the database is being moved.Type is the type of database being moved. The type is SQLDatabase.	true	true (ByValue)	
DataPath	Specifies the destination disk path for database data files to be moved.	false	true (ByValue)	
LogPath	Specifies the destination path to which all the database log files will be moved.	false	true (ByValue)	
Files	Specifies the logical name of the database file and the destination path to which the file will be moved.	false	true (ByValue)	
DeleteOriginal	Specifies that all the database files are deleted from the source location.	false	true (ByValue)	
PluginCode	Specifies the plug-in code of the destination host. The valid code is SMSQL.	true	true (ByValue)	
DBCC_NOINDEX		false	false	
DBCC_ALL_ERROR MSGS		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
DBCC_NO_INFOMSGS		false	true (ByPropertyName)	
DBCC_TABLOCK		false	true (ByPropertyName)	
DBCC_PHYSICALONLY		false	true (ByPropertyName)	
UpdateTableStatsBeforeDetach		false	true (ByPropertyName)	
RUnDBCCBeforeMigration		false	true (ByPropertyName)	
RunDBCCAfterMigration		false	true (ByPropertyName)	

Examples

Example 1: Moving a single database at the database level

```
Invoke-SmConfigureResources -Resources
@{"Host"="scspr0088723007";"Type"="SQL
Database";"Name"="scspr0088723007\INST1\d1"} -DataPath G:\ -Logpath G:\
-PluginCode SMSQL
```

Example 2: Moving multiple databases at the database level

```
Invoke-SmConfigureResources -Resources @{"Host"="nfs1";"Type"="SQL
Database";"Name"="nfs1\SQL12INST1\newnfs"},@{"Host"="nfs1";"Type"="SQL
Database";"Name"="nfs1\SQL12INST1\chk1"} -DataPath E:\ -LogPath E:\
-PluginCode SMSQL
```

Example 3: Moving a single database at the file level

```
Invoke-SmConfigureResources -Resources
@{"Host"="nfs1";"Type"="SQLDatabase";"Name"="nfs1\SQL12INST1\new1";"Files"
=@{"LogicalName"="new1";"Destination"="E:\"},@{"LogicalName"="new1_log";"D
estination"="E:\"},@{"LogicalName"="f";"Destination"="E:\"}}
-DeleteOriginal -PluginCode SMSQL
```

This example syntax moves a single database from on disk to another.

Example 4: Moving multiple databases at the file level

```
Invoke-SmConfigureResources -Resources
@{"Host"="nfs1";"Type"="SQLDatabase";"Name"="nfs1\SQL12INST1\newnfs";"Files"=@{"LogicalName"="newnfs";"Destination"="F:\"},@{"LogicalName"="newnfs_log";"Destination"="E:\"}},@{"Host"="nfs1";"Type"="SQLDatabase";"Name"="nfs1\SQL12INST1\chk1";"Files"=@{"LogicalName"="chk1";"Destination"="F:\"},@{"LogicalName"="chk1_log";"Destination"="F:\"}} -DeleteOriginal -PluginCode SMSQL
```

This example syntax moves multiple database files from one disk to another.

Example 5: Moving a database in a failover cluster instance

```
Invoke-SmConfigureResources -Resources
@{"Host"="Host1";"Type"="SQLDatabase";"Name"="Host1\DB1";"Files"=@{"LogicalName"="DB1";"Destination"="F:\"},@{"LogicalName"="DB1_log";"Destination"="F:\"}},@{"Host"="Host2";"Type"="SQLDatabase";"Name"="Host2\RahulDB";"Files"=@{"LogicalName"="RahulDB";"Destination"="F:\"},@{"LogicalName"="RahulDB_log";"Destination"="F:\"}} -DeleteOriginal -PluginCode SMSQL
```

This example syntax moves a database from one shared volume to another shared volume in a failover cluster instance.

Invoke-SmPrimaryBackupsExistenceCheck

Checks the existence of primary backups on the host and marks the backups as removed for snapshots that are not available in primary storage volumes.

Syntax

```
Invoke-SmPrimaryBackupsExistenceCheck [-HostName] <String>
```

Detailed Description

Checks the existence of primary backups on the host and marks the backups as removed for snapshots that are not available in primary storage volumes.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Name of the host on which the primary backups existence check will be performed.	true	true (ByPropertyName)	

Examples

Example 1: Primary Backups existence check

```
Invoke-SmPrimaryBackupsExistenceCheck -HostName host.mva.gdl.netapp.com
```

```
Initiating Primary Backups Existence Check..
Name: Primary backups existence on host: 'host.mva.gdl.netapp.com'
Id   : 1024
StartTime   : 11/24/2023 5:02:51 AM
EndTime    : 11/24/2023 5:02:51 AM
IsCancellable : False
IsRestartable : False
IsCompleted  : False
IsVisible    : True
IsScheduled  : False
PercentageCompleted : 100
Description  :
Status      : Running
Owner       :
Error       :
Priority     : None
Tasks       : {Precheck validation}
ParentJobID : 0
EventId     : 0
JobTypeId   : 0
ApisJobKey   :
ObjectId     : 0
PluginCode   : NONE
PluginName   : NONE
HostId      : 0
RoleId      :
JobIds      : {}
ScsJobId    :
Invoke-SmPrimaryBackupsExistenceCheck Completed
```

This example checks the existence of primary backups on the host.

Invoke-SmReportSchedule

Run an existing schedule using this cmdlet.

Syntax

```
Invoke-SmReportSchedule [-Name] <String>
```

Detailed Description

Perform an on-demand run operation of an existing schedule using this cmdlet.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specify the schedule name to perform on-demand run operation.	true	true (ByPropertyName)	

Examples

Example 1: Run a report schedule.

```
Invoke-SmReportSchedule -Name schedule1
```

This example runs a report schedule on-demand. Pass name of the schedule to perform on-demand run operation.

Invoke-SmResourceSplit

Initiates the split clone operation.

Syntax

```
Invoke-SmResourceSplit [-Estimate] <> [-AppObjectId] <String> [-CloneName] <String> [-Start] <> [-AppObjectId] <String> [-CloneName] <String> [-DoNotEstimate] <> [-EnableEmail] <> [-EmailPreference] <SmEmailNotificationPreference> [-Stop] <> [-AppObjectId] <String> [-CloneName] <String> [-Status] <> [-AppObjectId] <String> [-CloneName] <String>
```

Detailed Description

You can use SnapCenter to split the database clone from the parent database. The split clone database becomes independent of the original database.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Estimate	Specifies that details be provided for volumes that are being split.	false	true (ByValue)	
AppObjectId	Specifies the AppObjectId of the clone where the split will be performed.	false	true (ByValue)	
CloneName	The name of the clone where the split will be performed.	false	true (ByValue)	
EmailBody		false	true (ByPropertyName)	
EmailFrom		true	true (ByPropertyName)	
EmailTo		true	true (ByPropertyName)	
EmailSubject		true	true (ByPropertyName)	
EnableEmailAttachm ent		false	true (ByPropertyName)	
Start	Triggers the split clone operation.	false	true (ByValue)	
DoNotEstimate	Specifies that details should not be provided for the volumes that are being split.	false	true (ByValue)	
EnableEmail	Enables email notifications.	false	false	
EmailPreference	Specifies when you will received email notifications. Possible values include Always, Never, OnError, OnErrorOrWarning.	false	false	
Stop	Stops the split clone operation.	false	true (ByValue)	
Status	Determines the status of the split clone operation.	false	true (ByValue)	

Examples

Example 1: Clone split estimate

```
Invoke-SmResourceSplit -AppObjectId 'SC14110001040-3\NAMEDINST1\SC14110001040_3_SDML_1_Clone_103255' -Estimate
```

This example syntax displays the estimate details for the volume that is going to be split.

```
Clone Split Estimate Job Summary:
=====
JobId : 221
ListVolumeAggSpaceMapping :
{SC14110001040_3_SDML_Data_Vol1115172233091381,
SC14110001040_3_SDML_Log_Vol1115172233079350}
CanSplit : True
AppObjectId : SC14110001040_3_SDML_1_Clone_103255
CloneName : ResourceGroup_SDML_45212443__clone__11-15-2017_22.33.25
Result: SMCoreContracts.SMResult
TotalCount: 0
DisplayCount : 0
Context :
Job : SMCoreContracts.SmJob
Estimation Details for the volumes involved in Clone Split:
=====
VolumeName: SC14110001040_3_SDML_Data_Vol1115172233091381
RequiredSpace : 24 MB
AggregateName : aggr_anu
AvailableSpaceInAggregate : 3528 GB
StorageSystem : 10.225.85.51
IsVolumeAlreadySplit : False
VolumeName: SC14110001040_3_SDML_Log_Vol1115172233079350
RequiredSpace : 22 MB
AggregateName : aggr_anu
AvailableSpaceInAggregate : 3528 GB
StorageSystem : 10.225.85.51
IsVolumeAlreadySplit : False
```

Example 2: Clone split status

```
Invoke-SmResourceSplit -CloneName
'Resource_Group_Instance_45212443__clone__11-15-2017_22.44.24' -Status
```

This example syntax displays the status of a clone split operation.

Clone Split Status Job Summary:

=====

JobId: 237

AppObjectId : SC14110001040_3_MD SL_4_Clone_104322

CloneName: Resource_Group_Instance_45212443__clone__11-15-2017_22.44.24

Result : SMCoreContracts.SMResult

TotalCount : 0

DisplayCount : 0

Example 3: Starting a clone split operation

```
Invoke-SmResourceSplit -CloneName
```

```
'Resource_Group_Instance_45212443__clone__11-15-2017_22.44.24'
```

```
-confirm:$false -Start
```

This example syntax starts a clone split operation.

Clone Split Start Job Summary:

=====

JobId: 238

AppObjectId : SC14110001040_3_MD SL_4_Clone_104322

CloneName: Resource_Group_Instance_45212443__clone__11-15-2017_22.44.24

Result : SMCoreContracts.SMResult

TotalCount : 0

DisplayCount : 0

Context :

Job : SMCoreContracts.SmJob

Example 4: Stopping a clone split operation

```
Invoke-SmResourceSplit -AppObjectId 'SC14110001040-
```

```
3\NAMEDINST1\SC14110001040_3_MD ML_4_Clone_105129' -Stop
```

This example syntax stops a clone split operation.


```

Clone Split Stop Job Summary:
=====
JobId: 246
AppObjectId : SC14110001040_3_MDML_4_Clone_105129
CloneName: Resource_Group_Instance_45212443__clone__11-15-2017_22.52.47
Result : SMCoreContracts.SMResult
TotalCount : 0
DisplayCount : 0
Context :
Job : SMCoreContracts.SmJob

```

Example 5: Clone split estimate for a SAP HANA MultiTenant Database Container resource clone

```

Invoke-SmResourceSplit -Estimate -CloneName
SNAPCENTER40.sscore.test.com\hana\H30\H30_cn

```

This example syntax displays the estimate details for the volume that is going to be split. CloneName may be obtained by running the Get-SmClone command.

```

Clone Split Stop Job Summary:
=====
JobId : 773
ListVolumeAggSpaceMapping : {ng_pvol04021807440550}
CanSplit : True
AppObjectId : H30_cn
CloneName : SNAPCENTER40.sscore.test.com\hana\H30\H30_cn
Result: SMCoreContracts.SMResult
TotalCount: 0
DisplayCount : 0
Context :
Job : SMCoreContracts.SmJob
Estimation Details for the volumes involved in Clone Split:
=====
VolumeName: ng_pvol04021807440550
RequiredSpace : 48 MB
AggregateName : aggr1_old
AvailableSpaceInAggregate : 4670 GB
StorageSystem : 10.200.200.100
IsVolumeAlreadySplit : False

```

Example 6: Starting a clone split operation for a SAP HANA MultiTenant Database Container resource clone

```
Invoke-SmResourceSplit -start -CloneName  
SNAPCENTER40.sscore.test.com\hana\H30\H30_cn
```

This example syntax starts a clone split operation. CloneName may be obtained by running the Get-SmClone command.

```
This may take several minutes to complete for large volumes. All backups  
taken on the clone will be deleted  
Do you still want to continue?  
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help  
(default is "Y"):  
Clone Split Start Job Summary:  
=====
```

JobId:	774
AppObjectId	: H30_cn
CloneName:	SNAPCENTER40.sscore.test.com\hana\H30\H30_cn
Result	: SMCoreContracts.SMResult
TotalCount	: 0
DisplayCount	: 0
Context	:
Job	: SMCoreContracts.SmJob

Example 7: Stopping a clone split operation for a SAP HANA MultiTenant Database Container resource clone

```
Invoke-SmResourceSplit -stop -CloneName  
SNAPCENTER40.sscore.test.com\hana\H30\H30_cn
```

This example syntax stops a clone split operation. CloneName may be obtained by running the Get-SmClone command

```
Clone Split Stop Job Summary:
=====
JobId: 775
AppObjectId : H30_cn
CloneName: SNAPCENTER40.sscore.test.com\hana\H30\H30_cn
Result : SMCoreContracts.SMResult
TotalCount : 0
DisplayCount : 0
Context :
Job : SMCoreContracts.SmJob
```

Invoke-SmTechRefreshHost

Perform tech refresh of source host with destination host.

Syntax

```
Invoke-SmTechRefreshHost [-OldHostName] <String> [-NewHostName]
<String> [-IsDryRun] <Boolean> [-AutoMigrateManuallyAddedResource]
<Boolean> [-SQLInstanceMapping] <Hashtable[]>
```

Detailed Description

Perform tech refresh of source host with destination host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
OldHostName	Specify the name of source host whose resources needs to be relinked.	true	true (ByPropertyName)	
NewHostName	Specify the name of destination host where you want to relink the resources of the source host.	true	true (ByPropertyName)	
IsDryRun	Specify whether you want to perform a dry run to find the matching resources without relinking them.	false	true (ByPropertyName)	True
AutoMigrateManuallyAddedResource	Specify whether you want to migrate unmatched manually added resources.	false	true (ByPropertyName)	False

Name	Description	Required ?	Pipeline Input	Default Value
SQLInstanceMapping	Specify the list of SQL instance mapping, if resource is being migrated to another instance on new host. You must provide the instance mapping in a hashtable, and it must contain the OldInstanceName and NewInstanceName. For example, @{OldInstanceName="instance1";NewInstanceName="instance1_new"}, @{OldInstanceName="instance2";NewInstanceName="instance2_new"} You can include comma-separated values for multiple instance mapping.	false	true (ByPropertyName)	

Examples

Example 1: Tech refresh of old host with new host.

```
Invoke-SmTechRefreshHost -OldHostName host.mva.gdl.netapp.com
-NewHostName hostNew.mva.gdl.netapp.com -IsDryRun 0
-AutoMigrateManuallyAddedResource 1
```

```
Initiating host tech refresh..
Name: Tech refresh of host 'host.mva.gdl.netapp.com' with host
'hostNew.mva.gdl.netapp.com'
Id : 811
StartTime : 9/11/2023 6:10:43 PM
EndTime : 9/11/2023 6:10:43 PM
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 100
Description :
Status : Running
Owner :
Error :
Priority: None
Tasks : {Precheck validation}
ParentJobID : 0
EventId : 0
JobTypeId : 10
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName : NONE
HostId : 0
RoleId :
JobIds : {}
ScsJobId:
Invoke-SmTechRefreshHost Completed
```

This example does a tech refresh of old host with new host

Example 2: Tech refresh of old host with new host when SQL resource is migrated from one instance to another

```
Invoke-SmTechRefreshHost -OldHostName host.mva.gdl.netapp.com
-NewHostName hostNew.mva.gdl.netapp.com -IsDryRun 0
-AutoMigrateManuallyAddedResource 1
-SQLInstanceMapping
@{"OldInstanceName"="instance1";"NewInstanceName"="instance1_new"},@{"OldI
nstanceName"="instance2";"NewInstanceName"="instance2_new"}
```

```

Initiating host tech refresh..
Name: Tech refresh of host 'host.mva.gdl.netapp.com' with host
'hostNew.mva.gdl.netapp.com'
Id : 811
StartTime : 9/11/2023 6:10:43 PM
EndTime : 9/11/2023 6:10:43 PM
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 100
Description :
Status : Running
Owner :
Error :
Priority: None
Tasks : {Precheck validation}
ParentJobID : 0
EventId : 0
JobTypeId : 10
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName : NONE
HostId : 0
RoleId :
JobIds : {}
ScsJobId:
Invoke-SmTechRefreshHost Completed

```

This example does a tech refresh of old host with new host

Invoke-SmTechRefreshPrimaryStorage

Perform storage tech refresh of host.

Syntax

```

Invoke-SmTechRefreshPrimaryStorage [-HostName] <String> [-IsDryRun]
<Boolean> [-ChangedNDVMapping] <Hashtable[]>

```

Detailed Description

Perform storage tech refresh of host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Specify the host name on which storage refresh has to be done.	true	true (ByPropertyName)	
IsDryRun	Specify whether you want to perform a dry run to find the list of resources for which storage has changed. By default, the value of dry run is set to true.	false	true (ByPropertyName)	True
ChangedNDVMapping	Specify the list of Non Data Volumes(NDV) mapping if NDV resource is being migrated from one set of volumes to another set. You must provide the NDVs mapping in a hashtable, and it must contain the OldVolumePath and NewVolumePath. For example,@{"OldVolumePath"="SVM1:/vol/myVol1";"OldVolumePath"="SVM2:/vol/myVol1_new"},@{"OldVolumePath"="SVM3:/vol/myVol2";"OldVolumePath"="SVM4:/vol/myVol2_new"} You can include comma-separated values for multiple NDVs mapping.	false	true (ByPropertyName)	

Examples

Example 1: Storage tech refresh of host.

```
Invoke-SmTechRefreshPrimaryStorage -HostName host.mva.gdl.netapp.com  
-IsDryRun 0
```

```
Initiating storage tech refresh..  
Name: Tech refresh of storage in host 'host.mva.gdl.netapp.com'  
Id : 984  
StartTime : 10/26/2023 5:02:14 AM  
EndTime : 10/26/2023 5:02:14 AM  
IsCancellable : False  
IsRestartable : False  
IsCompleted : False  
IsVisible : True  
IsScheduled : False  
PercentageCompleted : 100  
Description :  
Status : Running  
Owner :  
Error :  
Priority: None  
Tasks : {}  
ParentJobID : 0  
EventId : 0  
JobTypeId : 52  
ApisJobKey :  
ObjectId: 0  
PluginCode : NONE  
PluginName : NONE  
HostId : 0  
RoleId :  
JobIds : {}  
ScsJobId:  
Invoke-SmTechRefreshPrimaryStorage Completed
```

This example does a tech refresh of the storage in the host.

Example 2: Storage tech refresh of host.

```
Invoke-SmTechRefreshPrimaryStorage -HostName host.mva.gdl.netapp.com  
-IsDryRun 0 -ChangedNDVMapping  
@{"OldVolumePath"="SVM1:/vol/myVol1";"NewVolumePath"="SVM2:/vol/myVol1_new"  
"},@{"OldVolumePath"="SVM3:/vol/myVol2";"NewVolumePath"="SVM4:/vol/myVol2_  
new"}
```



```
Initiating storage tech refresh..  
Name: Tech refresh of storage in host 'host.mva.gdl.netapp.com'  
Id : 984  
StartTime : 10/26/2023 5:02:14 AM  
EndTime : 10/26/2023 5:02:14 AM  
IsCancellable : False  
IsRestartable : False  
IsCompleted : False  
IsVisible : True  
IsScheduled : False  
PercentageCompleted : 100  
Description :  
Status : Running  
Owner :  
Error :  
Priority: None  
Tasks : {}  
ParentJobID : 0  
EventId : 0  
JobTypeId : 52  
ApisJobKey :  
ObjectId: 0  
PluginCode : NONE  
PluginName : NONE  
HostId : 0  
RoleId :  
JobIds : {}  
ScsJobId:  
Invoke-SmTechRefreshPrimaryStorage Completed
```

This example does a Tech refresh of storage in the host.

Invoke-SmTechRefreshSecondaryStorage

Starts tech refresh on secondary storage.

Syntax

```
Invoke-SmTechRefreshSecondaryStorage [-HostName] <String>
```

Detailed Description

Starts tech refresh on secondary storage..

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Specify the host name on which storage refresh has to be done.	true	true (ByPropertyName)	

Examples

Example 1: Tech Refresh Secondary Storage

```
Invoke-SmTechRefreshSecondaryStorage
```

```
Initiating secondary storage tech refresh..  
Name:  
Id   : 393  
StartTime   :  
EndTime    :  
IsCancellable : False  
IsRestartable : False  
IsCompleted : False  
IsVisible    : True  
IsScheduled  : False  
PercentageCompleted : 0  
Description :  
Status      : Running  
Owner       :  
Error       :  
Priority     : None  
Tasks       : {}  
ParentJobID : 0  
EventId     : 0  
JobTypeId   :  
ApisJobKey  :  
ObjectId    : 0  
PluginCode  : NONE  
PluginName  :  
HostId     : 0  
RoleId     :  
JobIds      : {}  
ScsJobId:  
Invoke-SmTechRefreshSecondaryStorage Completed
```

This example does secondary storage tech refresh.

Invoke-Sm_ExecuteQuery

This is a test cmdlet, for QA use only.

Syntax

```
Invoke-Sm_ExecuteQuery [-Query] <String>
```

Detailed Description

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Query		true	true (ByPropertyName)	

Examples

New-SmAlert

Create new alert.

Syntax

```
New-SmAlert [-Name] <String> [-Description] <String> [-Recommendation] <String> [-Severity] <SmAlertSeverity> [-Status] <SmAlertStatus> [-EntityType] <SmEntityType> [-EntityName] <String> [-JobId] <String> [-Source] <SmAlertSource>
```

Detailed Description

To create new alert, Valid connection is required. You should provide alert severity like Informational, Warning or Critical and EntityType can be All, SnapCenterServer, Host or StorageSystem. The Source parameter should be ConfigurationChecker or SnapCenterServer.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name		true	true (ByPropertyName)	
Description		true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Recommendation		true	true (ByPropertyName)	
Severity		true	true (ByPropertyName)	
Status		false	true (ByPropertyName)	
EntityType		true	true (ByPropertyName)	
EntityName		false	true (ByPropertyName)	
JobId		true	true (ByPropertyName)	
Source		true	true (ByPropertyName)	

Examples

Example 1: Create new alert

```
New-SmAlert -Name TestAlert -Description ForSnapCenter -Recommendation
AnyRecom -Severity Informational -Status New -EntityType Host -EntityName
WIN-SCServer.Domain1.com -JobId 162 -Source SnapCenterServer
```

This example syntax creates an alert.

Id :

```
CreatedTime: 1/1/0001 12:00:00 AM
ModifiedTime : 1/1/0001 12:00:00 AM
Name : TestAlert
Status : New
Severity : Informational
Entity : SMCoreContracts.ConfigCheck.SmEntity
Description: ForSnapCenter
Recommendation : AnyRecom
JobId : 162
Source : SnapCenterServer
IsRulePassed : False
EntityType : Host
EntityName : WIN-SCServer.Domain1.com
EntityId :
Username :
Password :
Port :
```

New-SmBackup

Initiates a new Snapshot copy job.

Syntax

```
New-SmBackup [-Resources] <Hashtable[]> [-DatasetName] <String> [-
ResourceGroupName] <String> [-Policy] <String> [-Auth] <String> [-
IsScheduled] <Boolean> [-ClusterName] <String> [-SMSBaseUrl] <String>
[-IsNLBHost] <Boolean> [-ScheduleName] <String> [-ScheduleType]
<SmSchedulerType> [-Guid1] <String> [-Guid2] <String> [-
SnapshotLabel] <SmSPSSnapShotLabel> [-HostName] <String> [-
VerifyOnSecondary] <> [-EnableVerification] <>
```

Detailed Description

Initiates a new Snapshot copy job on the provided resource or the resources mapped to the provided resource group.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Resources	Specifies the resource which you want to backup. For Oracle Application Volume resource, format is -Resources @{"Host"="host1";"Application Volume"="appVol1"}	false	true (ByPropertyName)	
DatasetName	Names the dataset you want to back up.	false	false	
ResourceGroupName		false	false	
Policy	Specifies the policy you want to use for the backup operation.	true	false	
Auth	This parameter is for internal use only.	false	false	
IsScheduled	Internal switch to determine Cmdlet invocation by scheduler.	false	false	
ClusterName	Internal switch for identifying the cluster host.	false	false	
SMSBaseUrl	Internal switch that points to the SMS Base URL.	false	false	
IsNLBHost	Internal switch that indicates whether this host is part of NLB.	false	false	
ScheduleName	Internal switch that indicates schedule name.	false	false	
ScheduleType		false	false	
Guid1		false	false	
Guid2		false	false	
SnapShotLabel		false	false	
HostName	Determines the host name (FQDN) for which the backup job has been scheduled.	false	false	
VerifyOnSecondary	Specifies whether verification is enabled on secondary storage.	false	false	
EnableVerification	Specifies whether verification of backups is enabled. Values are either \$True or \$False.	false	false	

Examples

Example 1: Backing up a resource group

```
New-SMBackup -ResourceGroupName FullOnlineDataset1 -Policy  
FullBackupPolicy
```

This example syntax backs up the specified resource group.

Example 2: Backing up resources

```
New-SMBackup -Policy FullBackupPolicy -Resources  
@{"Host"="scspr0101826001-sumanr.lab.netapp.com";"Oracle Database"="ong"}
```

This example syntax backs up the specified resources.

Example 3: Enabling verification of a backup

```
New-SMBackup -EnableVerification $true -VerifyOnSecondary $true -Policy  
FullBackupPolicy -Resources @{"Host"="scspr0101826001-  
sumanr.lab.netapp.com";"Oracle Database"="ong"}
```

This example syntax backs up the specified resources and verifies the backup when it completes.

Example 4: Triggering a new backup of the HANA resource

```
New-SMBackup -Resources  
@{"Host"="schana02.gdl.englab.netapp.com";"Uid"="MDC\R57";"PluginName"="ha  
na"} -Policy "HANAPOLICY"
```

This example backs up the specified resources.

```
Name: Backup of Resource Group
'schana02_gdl_englab_netapp_com_hana_MDC_R57' with policy 'HANAPOLICY'
Id : 25
StartTime : 02-Oct-19 21:49:46
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 0
ApisJobKey :
ObjectId: 0
PluginCode : SCC
PluginName : PluginCreator
HostId : 0
RoleId :
JobIds : {}
```

Example 5: Backing up an Oracle Application Volume Resource

```
New-SMBackup -Policy ndvpolicy -Resources
@{"Host"="R809278EA03V1.HNK2.com";"Application Volume"="appVol1"}
```

This example syntax backs up the specified Oracle Application Volume resource.

Example 6: Triggering a new backup of the UnixFileSystems resource

```
New-SMBackup -ResourceGroupName "RG_PS_linuxfs201_LVM1_12648" -Policy
"BackupPS_linuxfs201_LVM1_12648"
```

This example backs up the specified resources.


```
Name: Backup of Resource Group 'RG_PS_linuxfs201_LVM1_12648'
with policy
                                     'BackupPS_linuxfs201_LVM1_12648'
Id      : 2759
StartTime    : 12/12/2023 8:29:33 AM
EndTime      :
IsCancellable : False
IsRestartable : False
IsCompleted   : False
IsVisible     : True
IsScheduled   : False
PercentageCompleted : 0
Description   :
Status        : Queued
Owner         :
Error         :
Priority      : None
Tasks         : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 0
ApisJobKey    :
ObjectId      : 0
PluginCode    : SCC
PluginName    : PluginCreator
HostId        : 0
RoleId        :
JobIds        : {}
ScsJobId      :
```

New-SmClone

Initiates a clone operation.

Syntax

```

New-SmClone [-DatasetName] <String> [-Policy] <String> [-
AppPluginCode] <PluginCode> [-PDBName] <String> [-PDBCloneName]
<String> [-CDBTargetSID] <String> [-PdbstoBeExcluded] <String> [-
OpenPluggableDatabaseAfterClone] <Boolean> [-
SkipTempTablesTempFileCreation] <> [-LogArchivedLocators]
<Hashtable[]> [-Auth] <String> [-IsScheduled] <Boolean> [-
ClusterName] <String> [-SMSBaseUrl] <String> [-IsNLBHost] <Boolean>
[-ScheduleName] <String> [-CreateRemoteClone] <Boolean> [-Guid1]
<String> [-Guid2] <String> [-BackupName] <String> [-Resources]
<Hashtable[]> [-AppPluginCode] <PluginCode> [-CloneUidString] <String>
[-CloneToInstance] <String> [-AutoAssignMountPoint] <> [-
ArchivedLocators] <Hashtable[]> [-AssignMountPointUnderPath] <String>
[-Suffix] <String> [-LogArchivedLocators] <Hashtable[]> [-
LogRestoreType] <SmSqlLogRestoreType> [-LogCutOffDateTime] <DateTime>
[-LogCount] <Int32> [-Auth] <String> [-IsScheduled] <Boolean> [-
ClusterName] <String> [-SMSBaseUrl] <String> [-IsNLBHost] <Boolean>
[-ScheduleName] <String> [-CloneLastBackup] <Int32> [-
CreateRemoteClone] <Boolean> [-Guid1] <String> [-Guid2] <String> [-
CloneName] <String> [-EnableEmail] <> [-PreScriptCommand] <String>
[-PreScriptArguments] <String> [-PostScriptCommand] <String> [-
PostScriptArguments] <String> [-ScriptTimeOut] <Int32> [-
PreCloneScriptPath] <String> [-PostCloneScriptPath] <String> [-
MountCommands] <String>

```

Detailed Description

Initiates a clone operation. You can initiate a clone job from either a clone dataset or an existing backup.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
DatasetName	Specifies the name of the clone dataset.	true	false	
Policy	Specifies the clone policy you want to use.	true	false	
AppPluginCode	Specifies the application plug-in type of the resource. Possible values are SMSQL and SCO.	true	false	
PDBName	Source Oracle pluggable database name.	false	false	
PDBCloneName	Pluggable Clone Oracle pluggable database name.	false	false	

Name	Description	Required ?	Pipeline Input	Default Value
CDBTargetSID	Target container database SID.	false	false	
PdbsToBeExcluded	List of Oracle pluggable databases to be excluded from newly cloned container database.	false	false	
OpenPluggableDatabaseAfterClone	To open pluggable database after clone creation.	false	false	
SkipTempTablespaceTempFileCreation	Skips creating a tempfile for the default temporary tablespace of the cloned database.	false	true (ByPropertyName)	
LogArchivedLocators	Specifies the secondary storage system details for each unique primary storage system resource in the dataset. For example:-LogArchivedLocators @ {Primary="my_vs1:my_vol_iscsi";Secondary="my_vs1:my_vol_iscsi_SECONDARY"}	false	false	
Auth	This parameter is for internal use only.	false	false	
IsScheduled	This parameter is for internal use only.	false	false	
ClusterName	This parameter is for internal use only.	false	false	
SMSBaseUrl	This parameter is for internal use only.	false	false	
IsNLBHost		false	false	
ScheduleName		false	false	
CreateRemoteClone		false	true (ByPropertyName)	
Guid1		false	false	
Guid2		false	false	
OracleUntilCancel	Specifies recovery will be performed using the latest available log backup. If archive log pruning is configured, the latest log backup having archive logs prior to pruning is selected for recovery.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
OracleUntilScn	Specifies the SCN of logs till which you want to recover the cloned Oracle Database.	false	true (ByPropertyName)	
OracleUntilTime	Specifies the date and time till which you want to recover the cloned Oracle Database. You must specify the date and time in the 'MM-dd-yyyy HH:mm:ss' format. For example: '07/02/2018 06:12:15'.	false	true (ByPropertyName)	
ExternalArchiveLogMountPaths	Specifies the alternate paths for archive logs to be used for recovery. Multiple alternate archive log paths can be specified in a comma separated list.	false	true (ByPropertyName)	
DataFilesMountPaths	Specifies, in a hash table, the destination mount path, source directory path, and disk location type. For example: @{"DestinationMountPath"="/mnt/db12c_data_STAND";"SourceDirectoryPath"=" /mnt/db12c_data";"DiskLocationType"="MountPoint"}	false	true (ByPropertyName)	
DatabaseSID	Specifies the Oracle system ID, which is used to uniquely identify a particular database. The maximum length of a clone SID is 8 characters. Example: -DatabaseSID STAND	true	true (ByPropertyName)	
DisableArchiveLogMode	Specify if archive log mode to be disabled.	false	true (ByPropertyName)	
EnableOSAuthentication		false	true (ByPropertyName)	
OracleOsUserName	Specifies the OS user name. For example: -OracleOsUserName oracle	true	true (ByPropertyName)	
OracleOsUserGroup	Specifies the name of the Oracle OS user group. For example: oinstall	true	true (ByPropertyName)	
databaseLoginUserName	Specifies the login name of the database user.	false	true (ByPropertyName)	
databaseLoginPassword	Specifies the database user's login password.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
OracleVersion	Specifies the Oracle version.Example: -OracleVersion 12.1.0.2	false	true (ByPropertyName)	
OracleHome	Specifies the Oracle home directory.Example: -OracleHome /ora01/app/oracle/product/11.2.0/db_1	false	true (ByPropertyName)	
ControlFileConfiguration	Specifies the path for the control file in a hash table.For example: -ControlFileConfiguration @{"FilePath"="/mnt/db12c_data_STAND/STAND/control/control01.ctl"}, @{"FilePath"="/mnt/db12c_data_STAND/STAND/control/control02.ctl"}	true	true (ByPropertyName)	
RedoLogFileConfiguration	Specifies the redo log file details in a hash table. The following parameters are required: FilePath, RedologNumber, TotalSize, BlockSize.The following is an example of using the RedoLogFileConfiguration parameter:- RedoLogFileConfiguration@{"FilePath"="/mnt/db12c_data_STAND/STAND/redo01.log";"RedologNumber"="1";"BlockSize"="512";"TotalSize"="50"}, @{"FilePath"="/mnt/db12c_data_STAND/STAND/redo02.log";"RedologNumber"="2";"BlockSize"="512";"TotalSize"="50"}, @{"FilePath"="/mnt/db12c_data_STAND/STAND/redo03.log";"RedologNumber"="3";"BlockSize"="512";"TotalSize"="50"}	true	true (ByPropertyName)	
PostCloneSqlQueries	Specifies any post-clone SQL queries. Multiple queries are separated by a semicolon ';'. ;	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
CustomParameters	Specifies custom parameters in a hash table. At least one custom parameter is required. For example: -CustomParameters @{"Key" = "audit_file_dest"; "Value" = "/u01/app/oracle/admin/DB12C/adump_STAND"}, @{"Key" = "log_archive_dest_1"; "Value" = "LOCATION=/u01/app/oracle/product/12.1.0.2/db_1/STAND"} You can use this parameter when you have a clone of a clone that fails with the error "ORA-00058: DB_BLOCK_SIZE must be 32768 to mount this database (not 8192)" to explicitly pass the custom parameter, for example: -CustomParameters @{"Key" = "DB_BLOCK_SIZE "; "Value" = "value"} and substituting the correct block size.	false	true (ByPropertyName)	
RenamePDBConfiguration	Renames the PDB configuration in a hash table using the following format: -RenamePDBConfiguration @{"CurrentName" = "", "NewName" = ""}	false	true (ByPropertyName)	
SkipRecovery	Indicates that you want to skip the recovery operation of the cloned database.	false	false	
DatabasePort		false	true (ByPropertyName)	
ASMPort		false	true (ByPropertyName)	
DatabaseCredentialName		false	true (ByPropertyName)	
AsmCredentialName		false	true (ByPropertyName)	
SkipNIDCreation	To skip new DBID creation for the cloned Oracle Database.	false	true (ByPropertyName)	
EmailBody		false	true (ByPropertyName)	
EmailFrom	Specifies the sender's e-mail address.	true	true (ByPropertyName)	
EmailTo	Specifies the recipient's e-mail address.	true	true (ByPropertyName)	
EmailSubject	Specifies the subject of the e-mail.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
EnableEmailAttachm ent		false	true (ByPropertyName)	
BackupName	Specifies the name of the backup from which you want to clone. The following is an example of a SnapCenter Plug-in for Oracle Database backup name:- BackupName CDBPS_scomaddev_04-07-2016_06.14.38.8575_0	false	false	
Resources	Specifies the list of resources from which to clone. Use the Resources parameter when you are creating a clone from an existing backup. You must provide the resource information in a hashtable, and it must contain the resource name and type, as well as the host on which the resource is located. For example, @{"Host"="localhost";"Type"="SQL Database";"Names"="Instance\Database"} Valid Type value are SQL Database, Oracle Database, Windows Filesystem. For Oracle Database, the format is -Resources @{"Host"="host.example.com";"Oracle Database"="db"}. For Oracle Application Volume, the format is -Resources @{"Host"="host.example.com";"Application Volume"="appVol"}.	true	false	
CloneToInstance	Specifies the SQL Server instance that you want to clone to. All databases in the clone dataset are cloned to this instance. For Oracle application volume resource, it specifies the host on which clone should be mounted.	true	true (ByPropertyName)	
AutoAssignMountPoi nt	Specifies that the file system mount point is assigned automatically.	false	true (ByPropertyName)	
ArchivedLocators	Specifies the secondary storage system details for each unique primary storage system resource in the dataset. For example:-ArchivedLocators @{"Primary"="my_vs1:my_vol_iscsi";"Secondary"="my_vs1:my_vol_iscsi_SECONDARY"}	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
AssignMountPointUnderPath	Specifies that the file system mount point is created automatically under the specified mount path.	false	true (ByPropertyName)	
CloneUid	Provide a target HANA clone UID. Use this parameter if you are creating a HANA clone on the same host as that of the source. You can use the -CloneUid parameter only with a HANA resource.	true	true (ByPropertyName)	
CloneInstance	Provide a target DB2 clone instance name. Use this parameter if you are creating a DB2 clone on the different host as that of the source. You can use the -CloneInstance parameter only with a DB2 Database resource.	false	true (ByPropertyName)	
Suffix	Provides a clone name suffix. All clones you create with one clone job are appended with the same suffix name. Use this parameter if you are creating a clone from an existing backup. You can use the -suffix parameter or the -clonename parameter, but not both.	false	true (ByPropertyName)	
LogRestoreType	Specifies the recovery type for clones. Valid values are, the roll forward time, the number of logs to roll forward, or that you want to roll all logs forward.	false	true (ByPropertyName)	
LogCutOffDateTime	When you specify the date and time in the LogRestoreType parameter, you can use LogCutOffDateTime parameter to indicate the cut off time. If the server and plug-in host are in different time zones, the input must be as per the plug-in host time zone.	false	true (ByPropertyName)	
LogCount	When you specify a number of logs in LogRestoreType, use LogCount to specify the number of logs you want to roll forward.	false	true (ByPropertyName)	
CloneLastBackup		false	false	
CloneName	Enables you to specify a new name for the cloned database or resource. You can use the -clonename parameter or the -suffix parameter, but not both.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Port	Provide a target port for clone. Use this parameter if you are creating a PostgreSQL cluster or MySQL instance clone. You can use the -Port parameter only with a PostgreSQL cluster or MySQL instance resource.	false	true (ByPropertyName)	
EnableEmail	Specifies whether to enable or disable e-mail.	false	false	
PreScriptCommand	Specifies commands that are executed before the restore operation.	false	true (ByPropertyName)	
PreScriptArguments	Specifies arguments to the prescript command.	false	true (ByPropertyName)	
PostScriptCommand	Specifies the commands that are executed after the restore operation.	false	true (ByPropertyName)	
PostScriptArguments	Specifies the arguments to the postscript command.	false	true (ByPropertyName)	
PreCloneScriptPath	This is an Oracle Application Volume specific parameter. It specifies absolute path of the executable script to be run before Clone operation. The script should be located either at /var/opt/snapcenter/spl/scripts/ or any directory inside the path on the Oracle Plug-in host.	false	true (ByPropertyName)	
PostCloneScriptPath	This is an Oracle Application Volume specific parameter. It specifies absolute path of the executable script to be run after Clone operation. The script should be located either at /var/opt/snapcenter/spl/scripts/ or any directory inside the path on the Oracle Plug-in host.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
MountCommands	This is an Oracle Application Volume specific parameter. It specifies commands to mount a file system to a the Clone Host. Mount command format is : mount <Source_SVM>:%<SOURCE_VOLUME_NAME>_Clone <mount_directory> To clone from secondary, the secondary volume name will be the SOURCE_VOLUME_NAME. Enter multiple mount commands separated by semi colon (;).	false	true (ByPropertyName)	
ScriptTimeOut	Specifies the maximum time to wait for the script to complete before timing out.	false	true (ByPropertyName)	
InitiatorName	Specifies the iSCSI IQN or FCP WWPN of the host on which the new clone will be created.	false	true (ByPropertyName)	
IgroupProtocol	Specifies the Igroup protocol type (mixed, fcp, or iscsi) to be used for the new clone.	false	true (ByPropertyName)	
NFSEExportIPs	Specifies the comma separated host name or IP address on which the cloned volumes are exported.	false	true (ByPropertyName)	
ThroughputMibps	Specifies the capacity pool throughput in Mibps for Manual QoS Capacity Pool.	false	true (ByPropertyName)	
CloneSource	Determines the source volume backup type. Valid values are PRIMARY or SECONDARY or OBJECT_STORAGE	false	true (ByPropertyName)	

Examples

Example 1: Creating a clone from a dataset

```
New-SmClone -DatasetName payrollclone_dataset -Policy
clonefromprimary_ondemand
```

This example syntax creates a new clone using the 'payrollclone_dataset' dataset and policy 'clonefromprimary_ondemand'.

```

Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Name: Clone life cycle of dataset 'payrollclone_dataset' with policy
'clonefromprimary_ondemand'
Id           : 85
StartTime    : 8/5/2015 2:21:06 PM
EndTime      :
IsCancellable : False
IsRestartable : False
IsCompleted  : False
IsVisible     : False
IsScheduled  : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId      : 0

```

Example 2: Creating a clone from backup with all logs

```

New-SmClone -BackupName payroll_dataset_vise-f3_08-05-2015_15.28.28.9774
-Resources @{"Host"="vise-f3.sddev.mycompany.com";"Type"="SQL
Database";"Names"="vise-f3\SQLExpress\payroll"} -CloneToInstance vise-
f3\sqlexpress -AutoAssignMountPoint -Suffix _clonefrombackup
-LogRestoreType All -Policy clonefromprimary_ondemand

```

This example syntax creates a clone from the specified backup with all logs.

```

Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Clones       : {}

```

Example 3: Creating a clone from backup with the specified number of logs

```
New-SmClone -BackupName payroll_dataset_vise-f3_08-05-2015_15.28.28.9774
-Resources @{
    Host="vise-f3.sddev.mycompany.com";"Type"="SQL
Database";"Names"="vise-f3\SQLExpress\payroll"} -CloneToInstance vise-f
3\sqlexpress -AutoAssignMountPoint -Suffix _clonefrombackup1
-LogRestoreType ByTransactionLogs -LogCount 2 -Policy clone
fromprimary_ondemand
```

This example syntax creates a clone from backup with the specified number of logs.

```
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Clones       : {}
```

Example 4: Creating a clone from backup with no logs

```
New-SmClone -BackupName payroll_dataset_vise-f3_08-05-2015_15.28.28.9774
-Resources @{
    Host="vise-f3.sddev.mycompany.com";"Type"="SQL
Database";"Names"="vise-f3\SQLExpress\payroll"} -CloneToInstance vise-
3\sqlexpress -AutoAssignMountPoint -Suffix _clonefrombackup1
-LogRestoreType None -Policy clonefromprimary_ondemand
```

This example syntax creates a clone from the specified backup with no logs.

```
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Clones       : {}
```

Example 5: Creating a clone to Microsoft SQL Server instance

```
New-SmClone -BackupName "BackupDS1_NY-VM-SC-SQL_12-08-2015_09.00.24.8367"
-Resources @{"host"="ny-vm-sc-sql";"Type"="SQL Database";"Names"="ny-vm-
sc-sql\AdventureWorks2012_data"} -AppPluginCode SMSQL -CloneToInstance
"ny-vm-sc-sql" -Suffix _CLPOSH -AutoAssignMountPoint
-AssignMountPointUnderPath "C:\SCMounts"
```

This example syntax creates a clone to the specified Microsoft SQL Server instance.

Example 6: Creating an on demand clone of DB2 resource on alternate host from primary storage

```
New-SmClone -BackupName
Verify_Clone_frombackup_Multiple_vols_with_resources_Alternate_Host_sscore
linux61_08-21-2016_19.04.14.6011 -Resources
@(@{"Host"="sccorelinux61.sscore.test.com";"Uid"="db2inst1\TESTDB"})
-CloneToInstance sscore146.sscore.test.com -CloneName 'TESTDB'
-CloneInstance 'db2inst1' -AppPluginCode 'DB2'
```

This example syntax creates a clone of the resource, hosted on Storage type NFS, and creates a new clone on an alternate host, which takes clone instance name and clone database name of target host

```

Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Clones       : {}
Name: Clone from backup
'Verify_Clone_frombackup_Multiple_vols_with_resources_Alternate_Host_sccorelinux61_08-21-2016_19.04.14.6011'
Id          : 61043
StartTime    : 5/21/2024 7:05:11 PM
EndTime      :
IsCancellable : False
IsRestartable : False
IsCompleted   : False
IsVisible     : True
IsScheduled   : False
PercentageCompleted : 0
Description   :
Status        : Queued
Owner         :
Error         :
Priority: None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
PluginCode    : NONE
PluginName    :

```

Example 7: Creating an on demand clone from Secondary Storage for custom plugin resource

```

New-SmClone -BackupName
Verify_clone_secondary_SM_on_Qtree_unix_sccorelinux61_08-21-
2016_16.57.18.8490 -Resources
@{"Host"="sccorelinux61.sccore.test.com";"Uid"="QTREESM1"}
-CloneToInstance sccorelinux61.sccore.test.com -Suffix '_QtreeClone4'
-preclonecreatecommands 'mkdir /qtreeVol6_clone' -ArchivedLocators (
@{Primary="vserver_scauto_secondary:qtree_vol6_sccorelinux61_sccore_test_c
om";Secondary="vserver_scauto_primary:qtree_vol6SM_sccorelinux61_sccore_te
st_com"}) -AutoAssignMountPoint -AppPluginCode 'DB2' -mountcommand 'mount
vserver_scauto_primary:%qtree_vol6_sccorelinux61_sccore_test_com/qtreeVol6
_Clone /qtreeVol6_clone'

```

Clone QTree to same host from Secondary Storage using mount command.

At run-time, %qtree_vol6_sccorelinux61_sccore_test_com (source volume name) will resolve to new cloned volume name and new clone exported QTree will be mounted on folder "/qtreeVol6_clone

Example 8: Creating a clone of an ASM database

```
New-SmClone -BackupName "RG_084825_rhel68_asmsan_03-04-2017_08.49.52.1104_0" -AppPluginCode SCO -DatabaseSID clone -Resources @{"Host"="10.228.9.250";"Oracle Database"="sandb"} -AutoAssignMountPoint -CloneToInstance 10.228.9.250 -ControlFileConfiguration @{"FilePath"="/home/oracle/control01.ctl"} -RedoLogFileConfiguration @{"FilePath"="/home/oracle/redo03.log";"RedologNumber"="3";"TotalSize"="50";"BlockSize"="512"},@{"FilePath"="/home/oracle/redo02.log";"RedologNumber"="2";"TotalSize"="50";"BlockSize"="512"},@{"FilePath"="/home/oracle/redo01.log";"RedologNumber"="1";"TotalSize"="50";"BlockSize"="512"} -CustomParameters @{"Key" = "audit_file_dest";"Value"="/var/test"}
```

This example syntax creates a clone of an Automatic Storage Management (ASM) database.

Example 9: Creating a clone using a Windows file system resource

```
New-SmClone -CloneLastBackup 0 -Resources @{"Host"="localhost";"Type"="Windows Filesystem";"Names"="F:\"} -AppPluginCode SCW -AssignMountPointUnderPath C:\scmnpt\ -CloneToHost localhost
```

Example 10: Creating a remote clone

```
New-SmClone -BackupName SQL-Prod_mydb_SQL_Prod_10-23-2017_15.56.12.1837 -AppPluginCode SMSQL -Suffix _clone2 -Resources (@{"Host"="SQL-PROD";"Type"="SQL Database";"Names"="SQL-PRD\mydb"}) -CloneToInstance SQL-PRD -ArchivedLocators (@{Primary="svm1:sql_data";Secondary="svm1-dr:sql_data_vault"},@{Primary="svm1:sql_log";Secondary="svm1-dr:sql_log_vault"}) -AutoAssignMountPoint
```

This example syntax creates a clone from secondary storage with the following details:

Primary data volume path: svm1:sql_data

Secondary data volume path: svm1-dr:sql_data_vault

Primary log volume path: svm1:sql_log

Secondary log volume path: svm1-dr:sql_log_vault

The "ArchivedLocators" attribute is populated as a hash table with Primary and Secondary values for each volume that hosts the SQL database you want to clone.

Example 11: Creating an on demand clone for HANA database from primary backup and using NFSExportIPs to export the cloned volumes

```
New-SmClone -BackupName
cn2_sscore_test_com_hana_NonDataVolume_C21_CN_cn2_06-21-2018_03.21.14.6261
-Resources @{"Host"="cn2";"UID"="NonDataVolume\C21\CN"}
           -AppPluginCode HANA -CloneToInstance rhel182
-CloneUid="NonDataVolume\C22" -nfsexportips
"RHEL182,10.232.206.116,sscorelinux61.sscore.test.com" -mountcommand
"mount 10.232.206.5:%cn_p2_Clone /cn_vol_test"
```

Clone from primary storage using NFS Export IP field to specify the comma separated host name or IP address on which the cloned volumes are exported

Example 12: Creating a HANA Clone on same centralized host with mount command, NFS Export IPs and QoS

```
New-SmClone -BackupName "mva-s63_gdl_englab_com_hana_MDC_H14_mva-s63_03-
22-2021_05.43.49.8438" -Resources
@{"Host"="schana01.gdl.englab.netapp.com";"Uid"="MDC\R70"}
-CloneToInstance "mva-s63.gdl.englab.com" -AppPluginCode HANA -CloneUid
"MDC\H70"
-NFSExportIPs "10.232.206.116,mva-s63.gdl.englab.com" -mountcommand
"mount 10.232.206.5:%cn_p2_Clone /cn_vol_test"
-ThroughputMibps 1.56
```

HANA clone will be created using the same centralized host. In case of the same host, use -CloneUid paramter to specify the target clone UID.

Example 13: Creating an on demand clone for HANA database from secondary backup and using NFSExportIPs to export the cloned volumes

```
New-SmClone -BackupName
cn2_sscore_test_com_hana_NonDataVolume_C21_CN_cn2_06-21-2018_03.21.14.6261
-Resources @{"Host"="cn2";"UID"="NonDataVolume\C21\CN"}
           -AppPluginCode HANA -CloneToInstance rhel182
-CloneUid="NonDataVolume\C22" -ArchivedLocators
@{"primary"="vs_test1:cn_p2";"secondary"="vs_test1:cn_p2_vault1"}
-nfsexportips "RHEL182,10.232.206.116,sscorelinux61.sscore.test.com"
-mountcommand "mount 10.232.206.5:%cn_p2_Clone /cn_vol_test"
```

Clone from secondary storage backup using NFS Export IP field to specify the comma separated host name or IP address on which the cloned volumes are exported

Example 14: Creating an Oracle database clone from secondary using LogArchivedLocators

```
New-SmClone -OracleOsUserName oracle -OracleOsUserGroup oinstall
-BackupName "auto-nfs_gdl_englab_netapp_com_nasdb_05-02-
2018_08.39.11.5184_0" -AppPluginCode SCO -DatabaseSID Clon32 -Resources
@{"Host"="auto-nfs.gdl.englab.netapp.com";"Oracle Database"="nasdb"}
-AutoAssignMountPoint -CloneToInstance auto-nfs.gdl.englab.netapp.com
-ControlFileConfiguration
@{"FilePath"="/mnt/Data_Clone32/Clone32/control/control01.ctl"}
-RedoLogFileConfiguration
@{"FilePath"="/mnt/Data_Clone32/Clone32/redolog/redo01.log";"RedologNumber"=
"3";"TotalSize"="50";"BlockSize"="512"},@{"FilePath"="/MntPt_StaDB/Data_Cl
on32/Clone32/redolog/redo02.log";"RedologNumber"="2";"TotalSize"="50";"Bloc
kSize"="512"},@{"FilePath"="/MntPt_StaDB/Data_Clone32/Clone32/redolog/redo03
.log";"RedologNumber"="1";"TotalSize"="50";"BlockSize"="512"}
-CustomParameters @{"Key" = "audit_file_dest";"Value"="/var/test"}
-archivedlocators
@{Primary="10.225.118.251:auto_nfs_data";Secondary="ongqathree_man:ongqaone
_man_auto_nfs_data_vault"} -logarchivedlocators
@{Primary="10.225.118.251:auto_nfs_log";Secondary="ongqathree_man:ongqaone
_man_auto_nfs_log_vault"}
```

This example uses the -LogArchivedLocators to create an Oracle database clone from secondary storage.

Example 15: Creating an SQL clone using the clonename parameter to specify a new clone name

```
New-SmClone -BackupName SCNEW3_INSTANCE1_SCNEW3_MDML2_SCNEW3_02-28-
2018_02.27.53
.7034 -Resources @{"Host"="SCNEW3";"Type"="SQL
Database";"Names"="SCNEW3\INSTANCE1\SCNEW3_MDML2"} -CloneToInstance SCNE
W3\INSTANCE1 -clonename '_Clone_035231' -LogRestoreType 'None'
-AutoAssignMountPoint -AppPluginCode 'SCSQL'
```

This example creates a new clone _Clone_035231 using the -clonename parameter.

Example 16: Creating an ASM Oracle database clone using the backupname parameter

```

New-SmClone -OracleOsUserName oracle -OracleOsUserGroup oinstall
-BackupName "scodev-us1_gdl_englab_netapp_com_asmud2_scodev-us1_04-13-
2020_08.15.50.6683_0" -AppPluginCode SCO -DatabaseSID abc3 -Resources
@{"Host"="scodev-us1.gdl.englab.netapp.com";"Oracle Database"="asmud2"}
-AutoAssignMountPoint -CloneToInstance scodev-us1.gdl.englab.netapp.com
-DataFilesMountPaths
@{"DestinationMountPath"="SC_2443056968_abc3";"DiskLocationType"="Asm_Disk
Group";"SourceDirectoryPath"="DATAUDEV2"} -ControlFileConfiguration
@{"FilePath"="+SC_2443056968_abc3/abc3/control/control01.ctl"}
-RedoLogFileConfiguration
@{"FilePath"="+SC_2443056968_abc3/abc3/redolog/redo03.log";"RedologNumber"
="3";"TotalSize"="50";"BlockSize"="512"},@{"FilePath"="+SC_2443056968_abc3
/abc3/redolog/redo02.log";"RedologNumber"="2";"TotalSize"="50";"BlockSize"
="512"},@{"FilePath"="+SC_2443056968_abc3/abc3/redolog/redo01.log";"Redolo
gNumber"="1";"TotalSize"="50";"BlockSize"="512"} -CustomParameters
@{"Key" =
"audit_file_dest";"Value"="/ora01/app/oracle_software/oracle_base/admin/ab
c3/adump"};

```

This example creates a new ASM Oracle database clone abc3 using the -BackupName parameter.

Example 17: Creating an Oracle PDB clone

```

New-SmClone -OracleOsUserName oracle -OracleOsUserGroup oinstall
-BackupName "R706261C8F1V1_ZCDB1_R706261C8F1V1_08-03-2020_03.36.23.5540_0"
-AppPluginCode SCO -PDBName PDB3 -PDBCloneName SCJOBID -CDBTargetSID ZCDB1
-OpenPluggableDatabaseAfterClone -Resources @{"Host"="scodev-
us1.gdl.englab.netapp.com";"Oracle Database"="asmud2"}
-AutoAssignMountPoint -CloneToInstance scodev-us1.gdl.englab.netapp.com
-DataFilesMountPaths
@{"DestinationMountPath"="SC_2443056968_abc3";"DiskLocationType"="Asm_Disk
Group";"SourceDirectoryPath"="DATAUDEV2"} -ControlFileConfiguration
@{"FilePath"="+SC_2443056968_abc3/abc3/control/control01.ctl"}
-RedoLogFileConfiguration
@{"FilePath"="+SC_2443056968_abc3/abc3/redolog/redo03.log";"RedologNumber"
="3";"TotalSize"="50";"BlockSize"="512"},@{"FilePath"="+SC_2443056968_abc3
/abc3/redolog/redo02.log";"RedologNumber"="2";"TotalSize"="50";"BlockSize"
="512"},@{"FilePath"="+SC_2443056968_abc3/abc3/redolog/redo01.log";"Redolo
gNumber"="1";"TotalSize"="50";"BlockSize"="512"} -CustomParameters
@{"Key" =
"audit_file_dest";"Value"="/ora01/app/oracle_software/oracle_base/admin/ab
c3/adump"};

```

This example creates an Oracle PDB clone.

Example 18: Cloning an Oracle Application Volume from backup

```
New-SmClone -AppPluginCode SCO -BackupName
"R8092776CF4V1_HNK2_com_appVol1_R8092776CF4V1_11-06-2021_03.04.13.5289"
-Resources @{"Host"="R8092776CF4V1.HNK2.com";"Application
Volume"="appVol1"} -CloneName testExampleClone -CloneToInstance
R8092776CF4V1.HNK2.com -PreCloneScriptPath
"/var/opt/snapcenter/spl/scripts/preClone.sh" -MountCommands "mount
Test_SVM:%vol_test1_Clone /mnt/test" -PostCloneScriptPath
"/var/opt/snapcenter/spl/scripts/postClone.sh"
```

This example clones an Oracle Application Volume from backup.

Example 19: Cloning an Oracle Application Volume from secondary storage backup

```
New-SmClone -AppPluginCode SCO -BackupName
"R8092776CF4V1_HNK2_com_appVol1_R8092776CF4V1_11-06-2021_03.04.13.5289"
-Resources @{"Host"="R8092776CF4V1.HNK2.com";"Application
Volume"="appVol1"} -CloneName testExampleClone -CloneToInstance
R8092776CF4V1.HNK2.com -ArchivedLocators
@{"primary"="Source_SVM:vol_source";"secondary"="Dest_SVM:vol_source_dest"
}
```

This example clones an Oracle Application Volume from secondary storage backup.

Example 20: Creating a clone from a primary backup for UnixFileSystems plug-in

```
New-SmClone -AppPluginCode UnixFileSystems -BackupName
"RG_PS_linuxfs201_LVM1_12648_linuxfs201_12-12-2023_05.31.08.1302"
-Resources
@{"Host"="linuxfs.gdl.englab.netapp.com";"Uid"="/netapp/VGNFS1/LVM1"}
-suffix _Suffix_PrimPS_linuxfs201_LVM1_12648 -CloneToHost
linuxfs.gdl.englab.netapp.com
```

This example syntax creates a new clone using the backup and given suffix.

```
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Clones       : {}
Name: Clone from backup
'RG_PS_linuxfs201_LVM1_12648_linuxfs201_12-12-2023_05.31.08.1302'
Id          : 2763
StartTime    : 12/12/2023 8:32:40 AM
EndTime      :
IsCancellable : False
IsRestartable : False
IsCompleted  : False
IsVisible     : True
IsScheduled   : False
PercentageCompleted : 0
Description   :
Status        : Queued
Owner         :
Error         :
Priority: None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 6
ApisJobKey    :
ObjectId: 0
PluginCode    : SCC
PluginName    : PluginCreator
HostId        : 0
RoleId        :
JobIds        : {}
ScsJobId:
```

Example 21: Creating a clone from a secondary backup for UnixFileSystems plug-in

```
New-SmClone -AppPluginCode UnixFileSystems -BackupName
"RG_PS_linuxfs201_LVM1_12648_linuxfs201_12-12-2023_05.31.08.1302"
-Resources
@{"Host"="linuxfs.gdl.englab.netapp.com";"Uid"="/netapp/VGNFS1/LVM1"}
-ArchivedLocators
@{"primary"="Source_SVM:vol_source";"secondary"="Dest_SVM:vol_source_dest"
} -AutoAssignMountPoint -clonename
/netapp/VGNFS1/ClnName_Sec_PS_linuxfs_LVM1_12648
```

This example syntax creates a new clone using the secondary backup and given clonename.

```

Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Clones       : {}
Name: Clone from backup
'RG_PS_linuxfs_LVM1_12648_linuxfs201_12-12-2023_05.31.08.1302'
Id           : 2783
StartTime    : 12/12/2023 8:32:40 AM
EndTime      :
IsCancellable : False
IsRestartable : False
IsCompleted  : False
IsVisible     : True
IsScheduled  : False
PercentageCompleted : 0
Description   :
Status        : Queued
Owner         :
Error         :
Priority      : None
Tasks         : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 6
ApisJobKey    :
ObjectId      : 0
PluginCode    : SCC
PluginName    : PluginCreator
HostId        : 0
RoleId        :
JobIds        : {}
ScsJobId      :

```

Example 22: Creating an on demand clone of PostgreSQL resource on alternate host from primary storage

```

New-SmClone -AppPluginCode PostgreSQL -BackupName
"shivahel2_rtp_openenglab_netapp_com_PostgreSQL_postgres_5432_shivahel2_
06-26-2024_00_33_41_1570" -Resources
@{"Host"="shivahel2.rtp.openenglab.netapp.com";"Uid"="postgres_5432"}
-Port 2345 -CloneToHost shivahel30.rtp.openenglab.netapp.com

```

This example syntax creates a clone of the resource, hosted on Storage type NFS, and creates a new clone on an alternate host, which takes clone cluster name appended with port number of target host

```
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Clones       : {}
Name: Clone from backup
'shivarhel2_rtp_openenglab_netapp_com_PostgreSQL_postgres_5432_shivarhel2_
06-26-2024_00_33_41_1570'
Id          : 109
StartTime    : 6/27/2024 1:49:58 AM
EndTime      :
IsCancellable : False
IsRestartable : False
IsCompleted   : False
IsVisible     : True
IsScheduled   : False
PercentageCompleted : 0
Description   :
Status        : Queued
Owner         :
Error         :
Priority: None
Tasks         : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 6
ApisJobKey    :
ObjectId: 0
PluginCode    : SCC
PluginName    : PluginCreator
HostId        : 0
RoleId        :
JobIds        : {}
ScsJobId:
MaxJobsInQueue : 0
JobTags       :
Tags: {}
WaitForTags   :
ResourceId    :
QueueTimeoutMins: 0
ProtectiongroupID :
PolicyID:
```


Example 23: Creating an on demand clone of MySQL resource on alternate host from primary storage

```
New-SmClone -AppPluginCode MySQL -BackupName  
"scs000211748_gdl_englab_netapp_com_MySQL_mysql_d_3306_scs000211748_06-26-  
2024_06.08.35.4307" -Resources  
@{"Host"="scs000211748.gdl.englab.netapp.com";"Uid"="mysqld_3306"} -Port  
3320 -CloneToHost shivarhel30.rtp.openenglab.netapp.com
```

This example syntax creates a clone of the resource, hosted on Storage type NFS, and creates a new clone on an alternate host, which takes clone instance name appended with port number of target host

```
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Clones       : {}
Name: Clone from backup
'scs000211748_gdl_englab_netapp_com_MySQL_mysqlid_3306_scs000211748_06-26-
2024_06.08.35.4307'
Id          : 460
StartTime    : 6/28/2024 11:49:58 AM
EndTime      :
IsCancellable : False
IsRestartable : False
IsCompleted   : False
IsVisible     : True
IsScheduled   : False
PercentageCompleted : 0
Description   :
Status        : Queued
Owner         :
Error         :
Priority: None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 6
ApisJobKey    :
ObjectId: 0
PluginCode    : SCC
PluginName    : PluginCreator
HostId        : 0
RoleId        :
JobIds        : {}
ScsJobId:
MaxJobsInQueue : 0
JobTags       :
Tags: {}
WaitForTags   :
ResourceId     :
QueueTimeoutMins: 0
ProtectiongroupID :
PolicyID:
```

New-SmMountBackup

Initiates a mount operation for a given backup.

Syntax

```
New-SmMountBackup [-BackupName] <String> [-HostName] <String> [-AppObjectId] <String> [-ArchivedLocators] <Hashtable[]> [-AsmCredentialName] <String> [-AsmPort] <Int32>
```

Detailed Description

Initiates a mount operation for a given backup.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
BackupName	Specifies the name of the backup being mounted.	true	true (ByPropertyName)	
HostName	Specifies the name of the host on which you want to mount the backup.	true	true (ByPropertyName)	
AppObjectId	Specifies the application object name and type. For example: -AppObjectId "linux.serengeti.com\orcl"	true	true (ByPropertyName)	
ArchivedLocators	Specifies in a hash table, the primary and secondary storage system and volume locations. For example:-ArchivedLocators @{Primary="my_vs1:my_vol_iscsi";Secondary="my_vs1:my_vol_iscsi_SECONDARY"}	false	true (ByPropertyName)	
AsmCredentialName		false	false	
AsmPort	Specifies the port on which the Oracle ASM instance is available.	false	false	

Examples

Example 1: Mounting a backup

```
New-SmMountBackup -BackupName dailyset1_linux_10-12-2015_18.19.07.1866_0
-HostName linux.serengeti.com -AppObjectId "linux.serengeti.com\orcl"
```

This example syntax mounts an Oracle backup.

Example 2: Mounting an ASM database backup using a Run As account and port

```
New-SmMountBackup -BackupName "dbMigSrcAsm_Dataset_scspr0070373002_12-14-
2015_09.56.41.
7460_0" -HostName "scspr0070373002.gdl.netapp.com" -AppObjectId
"scspr0070373002.gdl.netapp.com\dbMigSrcA
sm" -ASMRunAsName "mounter" -ASMPort 1521
```

This example syntax mounts an ASM database backup using the specified ASM Run As account and port.

```
Mount started successfully
Name: Mount Backup dbMigSrcAsm_Dataset_scspr0070373002_12-14-
2015_09.56.41.7460_0
Id : 1479
StartTime : 12/14/2015 10:01:43 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : False
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
```

Example 3: Mounting a backup using archived locators

```
New-SmMountBackup -BackupName dailyset1_linux_10-12-2015_18.19.07.1866_0
-HostName linux.serengeti.com -AppObjectId "linux.serengeti.com\orcl"
-ArchivedLocators @{Primary="test_vsl:test1_vol";Secondary=
"test_vsl:test1_vol_SECONDARY"}
```

This example syntax mounts a backup using archived locators.

New-SmMultifactorAuthenticationMetadata

To create the metadata required to setup the MFA for SnapCenter in a specified location.

Syntax

```
New-SmMultifactorAuthenticationMetadata [-Path] <>
```

Detailed Description

To create the metadata required to setup MFA for SnapCenter in the specified location.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	Create SnapCenter MFA metadata at the specified path.	false	false	

Examples

Example 1: Create SnapCenter MFA metadata at default location

```
New-SmMultifactorAuthenticationMetadata
```

This example syntax creates SnapCenter MFA metadata at default location.

SnapCenter MFA Metadata: SnapCenterMFAMetadata.xml successfully generated at:
c:\ProgramData\NetApp\SnapCenter\Package Repository

Example 2: Create SnapCenter MFA metadata at specified location

```
New-SmMultifactorAuthenticationMetadata -Path C:\SC_metadata
```

This example syntax creates SnapCenter MFA metadata at specified location.

SnapCenter MFA Metadata: SnapCenterMFAMetadata.xml successfully generated at: C:\SC_metadata

New-SmRole

Enables you to create a role, assign users, assign groups, and assign permissions.

Syntax

```
New-SmRole [-Name] <String> [-Description] <String> [-Permissions]
<String> [-AssignedUsers] <String> [-AssignedGroups] <String> [-
SharedObjects] <>
```

Detailed Description

Enables you to create a role, assign users, assign groups, and assign permissions.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the new role.	true	true (ByPropertyName)	
Description	Specifies an optional description of the role.	false	true (ByPropertyName)	
Permissions	Specifies what permissions are assigned to the role.	false	true (ByPropertyName)	
AssignedUsers	Specifies users assigned to the role.	false	true (ByPropertyName)	
AssignedGroups	Specifies groups assigned to the role.	false	true (ByPropertyName)	
SharedObjects		false	true (ByPropertyName)	

Examples

Example 1: Creating a new role

```
New-SmRole -Name TestRole
```

This example syntax creates a new role with the specified name.

```
Description :
Name: TestRole
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Example 2: Creating a new role and assigning a user

```
New-SmRole -Name TestRoleWithUser -AssignedUsers sddev\snapdrive
```

This example syntax creates a new role and assigns the specified user.

```
Description :
Name: TestRoleWithUser
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Example 3: Creating a new role and assigning multiple users

```
New-SmRole -Name TestRoleWithUsers -AssignedUsers
"sddev\administrator,sddev\snapdrive"
```

This example syntax creates a new role and assigns multiple users to the role.

```
Description :
Name: TestRoleWithUsers
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Example 4: Creating a new role and assigning a group

```
New-SmRole -Name TestRoleWithGroup -AssignedGroups sddev\administrators
```

This example syntax creates a new role and assigns the specified group to the role.

```
Description :
Name: TestRoleWithGroup
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Example 5: Creating a role and assigning multiple groups

```
New-SmRole -Name TestRoleWithGroups -AssignedGroups
"sddev\administrators, sddev\Domain Admins"
```

This example syntax creates a new role and assigns multiple groups to the role.


```
Description :
Name: TestRoleWithGroups
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Example 6: Creating a new role and assigning permissions

```
New-SmRole -Name TestRoleWithGroups -AssignedGroups
"sddev\administrators, sddev\Domain Admins"
```

This example syntax creates a new role and assigns the specified permissions the groups assigned to the role.

```
PS C:\> New-SmRole -Name TestRoleWithPermissions -Permissions "Host: read,
update, delete, create;dataset: read, update, create, delete;manageusergroup:
allow;Plugin_Installation: read, update"
Description :
Name: TestRoleWithPermissions
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

New-SmServerBackup

Creates a SnapCenter Server backup.

Syntax

```
New-SmServerBackup [-TargetPath] <String> [-TakeConfigBackupInHosts]
<SwitchParameter>
```

Detailed Description

Backups the SnapCenter Server at specified path.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
TargetPath	Specify the path where SnapCenter Server backup should be created.	true	true (ByPropertyName)	
TakeConfigBackupInHosts	Take backup of configs in all hosts.	false	false	

Examples

Example 1: Creating a SnapCenter Server backup

```
New-SmServerBackup -TargetPath E:\Data
```

This example creates a SnapCenter Server backup.

```
Name: SnapCenter Server backup
Id   : 55
StartTime   : 8/30/2023 5:48:43 PM
EndTime    : 8/30/2023 5:48:43 PM
IsCancellable   : False
IsRestartable   : False
IsCompleted    : False
IsVisible      : True
IsScheduled     : False
PercentageCompleted : 100
Description   :
Status       : Running
Owner        :
Error        :
Priority      : None
Tasks        : {Precheck validation}
ParentJobID   : 0
EventId      : 0
JobTypeId     : 0
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    : NONE
HostId       : 0
RoleId       :
JobIds       : {}
ScsJobId      :
```

Example 2: Creating SnapCenter Server backup and host configuration files

```
New-SmServerBackup -TargetPath E:\Data -TakeConfigBackupInHosts
```

This example backs up the SnapCenter Server and the configuration files from all the hosts.

```
Name: SnapCenter Server backup
Id   : 55
StartTime   : 8/30/2023 5:48:43 PM
EndTime    : 8/30/2023 5:48:43 PM
IsCancellable   : False
IsRestartable   : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 100
Description   :
Status       : Running
Owner        :
Error        :
Priority      : None
Tasks        : {Precheck validation}
ParentJobID   : 0
EventId      : 0
JobTypeId     : 0
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    : NONE
HostId       : 0
RoleId       :
JobIds       : {}
ScsJobId      :
```

New-SmUnmountBackup

Initiates an unmount operation.

Syntax

```
New-SmUnmountBackup [-BackupName] <String>
```

Detailed Description

Initiates an unmount operation.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
BackupName	Specifies the name of the backup you want to unmount.	true	true (ByPropertyName)	

Examples

Example 1: Unmounting a backup

```
New-SmUnmountBackup -BackupName my_linux_10-20-2015_14.07.32.8158_0
```

This example syntax unmounts a mounted Oracle backup.

Open-SmConnection

Initiates a PowerShell connection session with SnapCenter, for a specified user.

Syntax

```
Open-SmConnection [-Credential] <PSCredential> [-SMSbaseUrl] <String>
[-Port] <String> [-RoleName] <String> [-AccessToken] <String>
```

Detailed Description

Initiates a PowerShell connection session with SnapCenter, for a specified user. The session is valid for 24 hours. To end a PowerShell connection session, exit PowerShell by either entering the Exit command at the PowerShell prompt, or by closing the PowerShell window. You can open separate PowerShell sessions to the same SnapCenter Server by using different user credentials for each session.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Credential	Provides domain user credentials for the user for whom you wish to establish a PowerShell session.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
SMSbaseUrl	Specifies the SnapCenter Server base URL. The base URL includes the name or IP address of the SnapCenter Server, and, if the remote system is in a different domain from that of the SnapCenter Server, the domain name. For example: https://SNAPCENTER_SERVER_NAME/DOMAIN_NAME .	false	true (ByPropertyName)	
Port	Enables you to specify the port number when the port is different than the default of 8146.	false	true (ByPropertyName)	
RoleName	If a user is assigned to multiple roles, specifies the role with which you want to log in.	false	true (ByPropertyName)	
AccessToken	Provides AccessToken parameter value from ADFS for MFA login in PowerShell.	false	true (ByPropertyName)	

Examples

Example 1: Opening a PowerShell session

```
Open-SmConnection
```

This command syntax opens a PowerShell session.

Example 2: Opening a PowerShell session with a specific role

```
Open-SmConnection -Credential sddev\administrator
```

This command syntax opens a PowerShell session for the specified role.

Example 3: Opening a PowerShell session to SnapCenter Server from a remote host using the SnapCenter Server name and domain in the base URL

```
Open-SmConnection -SMSbaseUrl https://SnapCenterServer1 -RoleName "SnapCenterAdmin"
```

This example syntax opens a PowerShell session to SnapCenter from a remote host in a different domain

Example 4: Opening a PowerShell session from a remote host to SnapCenter using the SnapCenter Server IP address in the base URL

This example syntax opens a PowerShell session to SnapCenter from a remote host using the SnapCenter Server IP address in the base URL.

Protect-SmRepository

Sets the configuration that is required to create a backup of the SnapCenter database.

Syntax

```
Protect-SmRepository [-HostName] <String> [-Path] <String> [-Schedule]
<Hashtable> [-RetentionCount] <Int32>
```

Detailed Description

Sets the configuration that is required to create a backup of the SnapCenter database.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Specifies the SnapCenter database host name. If the SnapCenter database is hosted by a failover cluster instance (FCI), then specify the FCI owner host name.	true	true (ByPropertyName)	
Path	Specifies the NetApp destination disk path where MySQL dumps are stored. Virtual disks are not supported.	true	true (ByPropertyName)	
Schedule	Specifies in a hash table the schedule to use when backing up the repository. For example: -Schedule @{"ScheduleType"="hourly";"StartTime"="10/21/2016 5:18 PM"}	true	true (ByPropertyName)	
RetentionCount	Specifies the number of backups to retain. By default, 7 backups are retained.	false	true (ByPropertyName)	

Examples

Example 1: Configuring a database backup for MySQL DB

```
Protect-SmRepository -HostName NB-MVA-DEV057.nbsdsm.mycompany.netapp.in
-Path E:\DATA -Schedule @{"ScheduleType"="hourly";"StartTime"="10/21/2016
5:18 PM"}
```

This example syntax configures an hourly backup for the file system specified and uses the Path argument to indicate the NetApp disk path where the repository DB dumps will be placed.

Refresh-SmBackup

Clears the stale backup entries from the SnapCenter Server.

Syntax

```
Refresh-SmBackup [-AppObjectList] <String> [-CleanupAllObjects] <> [-Auth] <String>
```

Detailed Description

Clears the stale backup entries from the SnapCenter Server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
AppObjectList		false	true (ByPropertyName)	
CleanupAllObjects		false	true (ByPropertyName)	
Auth		false	true (ByPropertyName)	

Examples

Example 1: Clears the stale backup entries from the SnapCenter Server for all resources

```
Refresh-SmBackup -CleanupAllObjects
```

This example syntax clears the stale backup entries from the SnapCenter Server for all resources.

Example 2: Clears the stale backup entries from the SnapCenter Server by resource name

```
Refresh-SmBackup -AppObjectList R708202074BV1\SQL2019\MDSL_DB3
```

This example syntax clears the stale backup entries from the SnapCenter Server by resource name.

Refresh-SmSnapLock

Updates the SnapLock settings for backups through ONTAP.

Syntax

```
Refresh-SmSnapLock [-AppObjectList] <String> [-All] <> [-Auth]  
<String>
```

Detailed Description

Updates the SnapLock settings for primary as well as secondary backups including SnapLock for SnapVault through ONTAP.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
AppObjectList	Object id list	false	true (ByPropertyName)	
All	Refresh SnapLock Settings for all objects.	false	true (ByPropertyName)	
Auth	Authentication	false	true (ByPropertyName)	

Examples

Example 1: Updates the SnapLock settings for all the resources in the SnapCenter Server

```
Refresh-SmSnapLock -All
```

This example syntax updates the SnapLock settings for all the resources in the SnapCenter Server through ONTAP.

Example 2: Updates the SnapLock settings by resource name

```
Refresh-SmSnapLock -AppObjectList R708202074BV1\SQL2019\MDSL_DB3
```

This example syntax updates the SnapLock settings by resource name through ONTAP.

Example 3: Updates the SnapLock settings by resource name list

```
Refresh-SmSnapLock -AppObjectList  
R708202074BV1\SQL2019\MDSL_DB1,R708202074BV1\SQL2019\MDSL_DB2
```

This example syntax updates the SnapLock settings by resource name list through ONTAP.

Refresh-SmSyncSnapMirrorBackups

Sync the snapmirror backups.

Syntax

```
Refresh-SmSyncSnapMirrorBackups [-AppObjectList] <String> [-  
RefreshAllObjects] <>
```

Detailed Description

In a snapmirror active sync relationship when one site is down, backups are taken on the site which is up and running. When the site comes back online, ONTAP resync backups from the current primary to replica site which SnapCenter is not aware of. Executing this commandlet shall ensure consistency between ONTAP and SnapCenter for Application consistent backups across primary and replica site.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
AppObjectList	Object id list	false	true (ByPropertyName)	
RefreshAllObjects	Refresh backups for all app objects.	false	true (ByPropertyName)	

Examples

Example 1: Refresh sync backups of all the resources in the SnapCenter Server

```
Refresh-SmSyncSnapMirrorBackups -RefreshAllObjects
```

This example syntax sync all backups for all the resources in the SnapCenter Server through ONTAP.

Example 2: Refresh sync backups by resource name

```
Refresh-SmSyncSnapMirrorBackups -AppObjectList  
R708202074BV1\SQL2019\MDSL_DB3
```

This example syntax sync all backups by resource name through ONTAP.

Example 3: Refresh sync backups by resource name list

```
Refresh-SmSyncSnapMirrorBackups -AppObjectList  
R708202074BV1\SQL2019\MDSL_DB1,R708202074BV1\SQL2019\MDSL_DB2
```

This example syntax sync all backups by resource name list through ONTAP.

Remove-SmAlert

Removes the alert(s) from SnapCenter.

Syntax

```
Remove-SmAlert [-AlertIds] <String> [-EntityType] <SmEntityType> [-  
EntityName] <String> [-Severity] <SmAlertSeverity>
```

Detailed Description

Removes the alert(s) from SnapCenter. Either Alert Id(s) or Entity Type and Entity Name or Severity must be provided!

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
AlertIds	Specify the list of alert ids to be deleted.	false	true (ByPropertyName)	
EntityType	Specify the entity type of the alert(s) needs to be deleted. ("Server", "Host", "Storage")	false	true (ByPropertyName)	
EntityName	Specify the entity name of the alert(s) needs to be deleted.	false	true (ByPropertyName)	
Severity	Specify the severity of the alert(s) needs to be deleted. "Informational", "Warning", "Critical")	false	true (ByPropertyName)	

Examples

Example 1: Remove one or more alerts by id(s)

```
Remove-SmAlert -AlertIds 100,101
```

This example syntax removes the specified alerts from SnapCenter.

Remove-SmAlert

Are you sure you want to remove the alert(s) ?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Example 2: Remove one or more alerts by id(s) without confirmation dialogue

```
Remove-SmAlert -AlertIds 100,101 -Confirm:$false
```

This example syntax removes the specified alerts from SnapCenter.

Example 1: Remove one or more alerts by EntityType and EntityName

```
Remove-SmAlert -EntityType Host -EntityName mtme.englab.netapp.com
```

This example syntax removes all the alerts of the given Host.

Remove-SmAlert

Are you sure you want to remove the alert(s) ?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Example 1: Remove one or more alerts by Severity

```
Remove-SmAlert -Severity Warning
```

This example syntax removes all the warning alerts.

Remove-SmAlert

Are you sure you want to remove the alert(s) ?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Remove-SmBackup

Removes one or more backup.

Syntax

```
Remove-SmBackup [-BackupNames] <String> [-BackupIds] <String> [-DeleteSecondaryMetadata] <> [-CleanupSecondaryBackups] <> [-SourceVolumes] <String> [-CleanupBackups] <> [-Force] <> [-Auth] <String> [-AppObjectId] <String>
```

Detailed Description

Removes one or more backup.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
BackupNames	Specifies the list of backup names to be deleted.	false	true (ByPropertyName)	
BackupIds	Specifies the list of backup ids to be deleted.	false	true (ByPropertyName)	
DeleteSecondaryMetadata	Specifies that the secondary backup metadata should be deleted.	false	true (ByPropertyName)	
CleanupSecondaryBackups	Specifies that the secondary backups that have no secondary Snapshot copies are cleaned up.	false	true (ByPropertyName)	
SourceVolumes	Specifies the source volumes whose secondary volumes are deleted. Use this option to clean-up the secondary backup metadata for the deleted volumes.	false	true (ByPropertyName)	
CleanupBackups	This cmdlet cleans up the backups that do not have Snapshot copies.	false	true (ByPropertyName)	
Force	Forces the removal of a backup.	false	true (ByPropertyName)	
Auth		false	true (ByPropertyName)	
AppObjectId		false	true (ByPropertyName)	

Examples

Example 1: Removing multiple backups using the backup ID

```
Remove-SmBackup -BackupIds 3,4
```

This example syntax removes multiple backups using the backup IDs.

Remove-SmBackup

Are you sure want to remove the backup(s).

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

Example 2: Removing multiple backups using the backup name

```
Remove-SmBackup -BackupNames "Payroll Dataset_vise-f6_08-04-2015_12.01.56.2744","Payroll Dataset_vise f6_08-04-2015_12.02.27.8732"
```

```
Remove-SmBackup
Are you sure want to remove the backup(s).
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help
(default is "Y"):
BackupResult : {}
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
```

Example 3: Removing secondary backup metadata

```
Remove-SmBackup -BackupIds 1 -DeleteSecondaryMetadata
```

This example syntax removes secondary backup metadata.

```
Remove-SmBackup
Are you sure want to remove the backup(s).
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help
(default is "Y"):
BackupResult : {}
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
```

Example 4: Cleaning up secondary backups without a confirm dialogue

```
Remove-SmBackup -CleanupSecondaryBackups -Confirm:$false
```

This example syntax cleans up secondary backups that do not have secondary Snapshot copies.

```
BackupResult : {}
Result       : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
```

Example 5: Cleaning up secondary backups where secondary volume is deleted

```
Remove-SmBackup -CleanupSecondaryBackups -SourceVolumes
SVM1:Volume1,SVM2:Volume2
```

This example syntax cleans up the secondary backups that do not have any secondary snapshot copies or the secondary volumes are deleted for the specified source volumes.

```
BackupResult : {}
Result       : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
```

Remove-SmClone

Removes an existing clone.

Syntax

```
Remove-SmClone [-CloneName] <String> [-PluginCode] <PluginCode> [-
CloneAppObjectId] <String> [-Force] <> [-IsOracleAppVol] <String> [-
PreCloneDeleteScriptPath] <String> [-UnMountCommands] <String>
```

Detailed Description

Removes an existing clone.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
CloneName	Specifies the name of the clone you want to remove.	false	false	
PluginCode	Specifies the plug-in code for the plug-in host whose clone you want to remove.	true	false	
CloneAppObjectId	Specifies the ID of the clone application object.	false	false	
Force	Enables you to unregister a clone that has been removed outside of SnapCenter.	false	true (ByPropertyName)	
IsOracleAppVol	This is a Oracle Application Volume specific parameter. It specifies the flag which enables to provide Pre-clone Deletion script and Unmount cmds to be run before Oracle Application Volume Clone Deletion.	false	true (ByPropertyName)	
PreCloneDeleteScriptPath	This is an Oracle Application Volume specific parameter and IsOracleAppVol flag needs to be set to use this. It specifies absolute path of the executable script to be run before Clone deletion. The script should be located either at /var/opt/snapcenter/spl/scripts/ or any directory inside the path on the Oracle Plug-in host.	false	true (ByPropertyName)	
UnMountCommands	This is an Oracle Application Volume specific parameter and IsOracleAppVol flag needs to be set to use this. It specifies commands to unmount a file system from the Clone Host before Clone deletion. Enter multiple mount commands separated by semi colon (;).	false	true (ByPropertyName)	

Examples

Example 1: Removing a clone

```
Remove-SmClone -CloneName payrollclone_dataset__clone__08-05-2015_14.41.11
```

This example syntax removes the specified clone.

```
Remove-SmClone
Are you sure you want to remove the clone?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help
(default is "Y"): y
Name: Deleting clone 'payrollclone_dataset__clone__08-05-2015_14.41.11'
Id : 91
StartTime : 8/5/2015 2:47:14 PM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : False
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
```

Example 2: Removing a clone without the confirm dialogue

```
Remove-SmClone -CloneName payrollclone_dataset__clone__08-05-
2015_14.41.11 -Confirm:$false
```

This example syntax removes the specified clone.

```
Name: Deleting clone 'payrollclone_dataset__clone__08-05-2015_14.41.11'
Id   : 91
StartTime   : 8/5/2015 2:47:14 PM
EndTime    :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible   : False
IsScheduled : False
PercentageCompleted : 0
Description :
Status      : Queued
Owner       :
Error       :
Priority: None
Tasks       : {}
ParentJobID : 0
EventId     : 0
```

Example 3: Removing an Oracle Application Volume clone with PreCloneDeletion Script and Unmount Command

```
Remove-SmClone -CloneName R8092776CF4V1_HNK2_com_appVol4__clone__3221_11-
06-2021_05.57.33 -PluginCode SCO -IsOracleAppVol -PreCloneDeleteScriptPath
"/var/opt/snapcenter/spl/scripts/preCloneDel.sh" -UnMountCommands "umount
/mnt/test"
```

This example syntax removes the specified Oracle Application Volume clone, PreCloneDeletion Script and Unmount Command are specified.

```

Remove-SmClone
    Are you sure you want to remove the clone?
    [Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend
[?] Help (default is "Y"):
    Name: Deleting clone
'R8092776CF4V1_HNK2_com_appVol4__clone__3221_11-06-2021_05.57.33'
    Id : 3222
    StartTime : 11/6/2021 6:35:42 AM
    EndTime :
    IsCancellable : False
    IsRestartable : False
    IsCompleted : False
    IsVisible : True
    IsScheduled : False
    PercentageCompleted : 0
    Description :
    Status : Queued
    Owner :
    Error :
    Priority: None
    Tasks : {}
    ParentJobID : 0
    EventId : 0
    JobTypeId : 7
    ApisJobKey :
    ObjectId: 0
    PluginCode : SCO
    PluginName : SnapCenter Plug-in for Oracle Database
    HostId : 0
    RoleId :
    JobIds : {}

```

Example 4: Removing an Oracle Application Volume clone

```

Remove-SmClone -CloneName R8092776CF4V1_HNK2_com_appVol4__clone__3221_11-
06-2021_05.57.33 -PluginCode SCO

```

This example syntax removes the specified Oracle Application Volume clone.

```

Remove-SmClone
    Are you sure you want to remove the clone?
    [Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend
[?] Help (default is "Y"):
    Name: Deleting clone
'R8092776CF4V1_HNK2_com_appVol4__clone__3221_11-06-2021_05.57.33'
    Id : 3222
    StartTime : 11/6/2021 6:35:42 AM
    EndTime :
    IsCancellable : False
    IsRestartable : False
    IsCompleted : False
    IsVisible : True
    IsScheduled : False
    PercentageCompleted : 0
    Description :
    Status : Queued
    Owner :
    Error :
    Priority: None
    Tasks : {}
    ParentJobID : 0
    EventId : 0
    JobTypeId : 7
    ApisJobKey :
    ObjectId: 0
    PluginCode : SCO
    PluginName : SnapCenter Plug-in for Oracle Database
    HostId : 0
    RoleId :
    JobIds : {}

```

Example 5: Removing a UnixFileSystems plug-in clone without the confirm dialogue

```

Remove-SmClone -CloneName
'RG_PS_linuxfs201_LVM1_12648__clone__2763__netapp_VGNFS1_LVM1_12-12-
2023_12.04.17' -PluginCode 'UnixFileSystems' -Confirm:$false

```

This example syntax removes the specified clone.

```

        Name: Deleting clone
'RG_PS_linuxfs201_LVM1_12648__clone__2763__netapp_VGNFS1_LVM1_12-12-
2023_12.04.17'
        Id   : 2764
        StartTime   : 12/12/2023 8:37:14 AM
        EndTime     :
        IsCancellable   : False
        IsRestartable  : False
        IsCompleted   : False
        IsVisible      : True
        IsScheduled    : False
        PercentageCompleted : 0
        Description   :
        Status        : Queued
        Owner         :
        Error         :
        Priority       : None
        Tasks         : {}
        ParentJobID   : 0
        EventId       : 0
        JobTypeId     : 7
        ApisJobKey    :
        ObjectId      : 0
        PluginCode    : SCC
        PluginName    : PluginCreator
        HostId        : 0
        RoleId        :
        JobIds        : {}
        ScsJobId      :

```

Remove-SmCloneJob

Removes an existing clone job.

Syntax

```
Remove-SmCloneJob [-CloneJobName] <String>
```

Detailed Description

Removes an existing clone job based on the name of the clone job provided.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
CloneJobName		true	true (ByPropertyName)	

Examples

- Example 1: Remove a clone job by clone job name -

```
Remove-SmCloneJob -CloneJobName cl2
```

This example syntax removes a clone job based on the name of the clone job provided.

```
Remove-SmCloneJob
```

Are you sure you want to perform this action?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): Y

No clones associated with 'cl2' Resource Group.

Deleted Protection Group 'cl2' successfully.

Deleted clone policy 'cl2_ClonePolicy' successfully.

- Example 2: Removes a clone job by clone job name without a confirmation dialogue. -

```
Remove-SmCloneJob -CloneJobName cl2 -Confirm:$false
```

This example syntax removes a clone job based on the name of the clone job provided.

Remove-SmCredential

Unregister a registered credential.

Syntax

```
Remove-SmCredential [-Name] <String>
```

Detailed Description

Remove a registered credential from the SnapCenter Server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name		true	true (ByPropertyName)	

Examples

Example 1: Remove Credential

```
Remove-SmCredential -Name RunAs1
```

Remove-SmDRFailoverBackups

After failback, delete special backups taken during failover.

Syntax

```
Remove-SmDRFailoverBackups [-AppObjectId] <> [-AppObjectId] <> [-BackupNames] <> [-AppObjectId] <> [-Primary] <>
```

Detailed Description

After failback, delete special backups taken during failover.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
AppObjectId	Specifies the application object identifier of an SQL database.	true	true (ByPropertyName)	
BackupNames	Specifies one or more backups of an application object to delete.	false	true (ByPropertyName)	
BackupIds	Specifies one or more backups of an application object to delete.	false	true (ByPropertyName)	
Primary	Specifies to delete backups from the primary storage.	false	true (ByPropertyName)	

Examples

Example 1: Delete all special backups of the SQL resources after failback from secondary

```
Remove-SmDRFailoverBackups -AppObjectId Host1\Inst\DB1
```

This example syntax deletes all the special backup of the resource from the storage where the backup was taken (secondary storage).

```
Remove-SmDRFailoverBackups
Are you sure you want to remove the backups?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?]
Help (default is "Y"): yes
Result : SMCoreContracts.SMResult
TotalCount : 0
DisplayCount : 0
Context :
Job : SMCoreContracts.SmJob
```

Example 2: Delete few special backups of the SQL resource after failback

```
Remove-SmDRFailoverBackups -AppObjectId Host1\Inst\DB1 -BackupNames
Backup1,Backup2
```

This example syntax deletes the specified special backups from the storage where the backup was taken (secondary storage).

```
Remove-SmDRFailoverBackups
Are you sure you want to remove the backups?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?]
Help (default is "Y"): yes
Result : SMCoreContracts.SMResult
TotalCount : 0
DisplayCount : 0
Context :
Job : SMCoreContracts.SmJob
```

Example 3: Delete all special backups of the SQL resources after failback from the secondary and the primary.

```
Remove-SmDRFailoverBackups -AppObjectId Host1\Inst\DB1 -Primary
```

This example syntax removes all the resource backups taken during failover from the secondary and the primary storage. For SnapMirror relationship, during subsequent SnapMirror update, deleted backups in the primary storage will be reflected in the secondary storage.

```

Remove-SmDRFailoverBackups
Are you sure you want to remove the backups?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?]
Help (default is "Y"): yes
Result : SMCoreContracts.SMResult
TotalCount : 0
DisplayCount : 0
Context :
Job : SMCoreContracts.SmJob

```

Example 4: Delete few special backups of the SQL resources after failback from the secondary and the primary.

```

Remove-SmDRFailoverBackups -AppObjectId Host1\Inst\DB1 -BackupNames
Backup1,Backup2 -Primary

```

This example syntax removes all the resource backups taken during failover from the secondary and the primary storage. For SnapMirror relationship, during subsequent SnapMirror update, deleted backups in the primary storage will be reflected in the secondary storage.

```

Remove-SmDRFailoverBackups
Are you sure you want to remove the backups?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?]
Help (default is "Y"): yes
Result : SMCoreContracts.SMResult
TotalCount : 0
DisplayCount : 0
Context :
Job : SMCoreContracts.SmJob

```

Remove-SmDomain

Unregister a registered domain.

Syntax

```

Remove-SmDomain [-Name] <String>

```

Detailed Description

Remove a registered domain from SnapCenter server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	NETBIOS Name of the registered domain to be removed.	true	true (ByPropertyName)	

Examples

Example 1: Unregister a registered domain from SnapCenter Server.

```
Remove-SmDomain -Name dom-newad01
```

Remove-SmDomain

The domain "dom-newad01" will be unregistered from SnapCenter Server and the domain users will no longer be able to access the SnapCenter Server.

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Remove-SmGroup

Removes an AD group or local group from SnapCenter.

Syntax

```
Remove-SmGroup [-Group] <SmString> [-Domain] <String>
```

Detailed Description

Removes an Active Directory group or local group from SnapCenter.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Group	Single group or list of groups belonging to the same domain or local host.	true	true (ByPropertyName)	
Domain	The domain to which the group belongs to. Local group should skip this parameter.	false	true (ByPropertyName)	

Examples

Example 1: Removing a single group

```
Remove-SmGroup -Group group1 -Domain domain1
```

Example 2: Removing multiple groups of same domain

```
Remove-SmGroup -Group group1,group2 -Domain domain1
```

Example 3: Removing a local group

```
Remove-SmGroup -Group LocalGroup1
```

Remove-SmGroupFromRole

Removes a group from a specified role.

Syntax

```
Remove-SmGroupFromRole [-Domain] <String> [-Group] <SmString> [-  
RoleName] <String>
```

Detailed Description

Removes a group from a specified role.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Domain	Specifies the domain to which the group belongs.	false	true (ByPropertyName)	
Group	Specifies the group you want to remove from the role.	true	true (ByPropertyName)	
RoleName	Specifies the name of the role from which you want to remove a group.	true	true (ByPropertyName)	

Examples

Example 1: Removing a group from a role

```
Remove-SmGroupFromRole -Domain sddev -Group administrators -RoleName  
SnapcenterAdmin
```

This example syntax removes the specified group from the SnapCenterAdmin role.

Remove-SmGroupFromRole

Are you sure you want to unassign the group from role?.

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Successfully UnAssigned Group From Role

Example 2: Removing a group from a role without confirm dialogue

```
Remove-SmGroupFromRole -Domain sddev -Group administrators -RoleName  
SnapcenterAdmin -Confirm:$false
```

This example syntax removes the specified group from the SnapCenterAdmin role.

Successfully UnAssigned Group From Role

Remove-SmHost

Removes one or more hosts from SnapCenter.

Syntax

```
Remove-SmHost [-HostNames] <String> [-Force] <> [-PluginCode]  
<PluginCode>
```

Detailed Description

Removes one or more hosts from SnapCenter. Note: For this command to succeed, the host you are removing must be resolvable in DNS or in the SnapCenter Server's hosts file. This applies even when you use the -force option.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostNames	Specifies one or more hosts that you want to remove. You can remove a cluster and all its nodes by specifying the cluster name.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Force	Forces the removal of discovered resources and hosts. For Oracle databases, if the backup is cataloged, and you force deletion of a host, cataloged backups associated with that host are not uncataloged. Therefore, if you want to force delete an Oracle database host, you must first uncatalog all the cataloged backups for that host before forcing the deletion of the host.	false	true (ByPropertyName)	
PluginCode	Provides the plug-in code for the host you want to remove. Valid plug-in codes include SCSQL, SCO and SCV. For example, if you want to remove SnapCenter Plug-in for Microsoft SQL Server host, the plug-in code is SCSQL.	false	true (ByPropertyName)	
DoNotIncludeCluster Nodes	Specifies that the host plug-in packages are not uninstalled from cluster nodes. If you set the parameter to True, then the host package is uninstalled only from the specified host. The default value is False, which means that when you provide a cluster name, the host package is uninstalled from all nodes in the cluster.	false	true (ByPropertyName)	

Examples

Example 1: Removing a host without backups or clones

```
Remove-smhost -HostNames localhost
```

This example syntax removes a host from SnapCenter.

```
Remove-SmHost
Are you sure you want to remove the host and its resources.?
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help
(default is "Y"): yName: Remove Host 'HostName'
Id : 44390
StartTime : 4/17/2017 2:07:51 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 10
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName :
```

Example 2: Removing a host without a confirm dialogue

```
Remove-smhost -HostNames localhost -Confirm:$false
```

This example syntax removes a host from SnapCenter.

```
Name: Remove Host 'Host name'
Id   : 44391
StartTime   : 4/17/2017 2:08:50 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 10
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    :
```

Example 3: Removing a host with backups and clones

```
Remove-smhost -HostNames localhost -Force
```

Delete the resource backups and clones associated with this host as part of the delete host operation.


```
Remove-SmHost
Are you sure you want to remove the host and its resources.?
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help
(default is "Y"): yName: Remove Host 'HostName'
Id : 44392
StartTime : 4/17/2017 2:10:09 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 10
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName :
```

Example 4: Removing a host with clones on an alternate host

```
Remove-smhost -HostNames localhost -Force -ForceDeleteClones
```

Delete resources that are cloned or mounted on an alternate host as part of the delete host operation.

```

Remove-SmHost
Are you sure you want to remove the host and its resources.?
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help
(default is "Y"): yName: Remove Host 'HostName'
Id      : 44392
StartTime    : 4/17/2017 2:10:09 AM
EndTime     :
IsCancellable : False
IsRestartable : False
IsCompleted  : False
IsVisible    : True
IsScheduled  : False
PercentageCompleted : 0
Description  :
Status       : Queued
Owner        :
Error        :
Priority     : None
Tasks        : {}
ParentJobID  : 0
EventId      : 0
JobTypeId    : 10
ApisJobKey   :
ObjectId     : 0
PluginCode   : NONE
PluginName   :

```

Remove-SmJobs

Removes completed jobs.

Syntax

```

Remove-SmJobs [-JobId] <Int32> [-StartTime] <DateTime> [-EndTime]
<DateTime> [-Auth] <String>

```

Detailed Description

Removes completed jobs using either the job ID of a specific job or all jobs within a specified date and time.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
JobId	Specifies the ID of the job you want to remove.	false	false	
StartTime	Specifies that jobs completed after the specified date and time should be removed.	false	false	
EndTime	Specifies that jobs completed before the specified date and time should be removed.	false	false	
Auth		false	false	

Examples

Example 1: Removing a job using a specific job ID

```
Remove-SmJobs -JobId 1002
```

This example syntax removes the job associated with the specified job ID.

Remove-SmJobs

Are you sure want to remove all the jobs(s) ?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Example 2: Removing jobs completed within specific start and end dates without a confirm dialogue

```
Remove-SmJobs -StartTime 02/12/2015 -EndTime 07/02/2015 -Confirm:$false
```

This example syntax removes jobs completed between the specified beginning and end dates.

Remove-SmPermissionFromRole

Removes one or more permissions from a specified role.

Syntax

```
Remove-SmPermissionFromRole [-RoleName] <String> [-Permissions]
<String>
```

Detailed Description

Removes one or more permissions from a specified role. Use the format <SnapCenter Resource Name>:<Permission Name> where the SnapCenter Resource name is Dataset, Policy, Backup, Host, Storage Connection, Clone, Provision, Dashboard, Restore, Reports, Discovery, Plugin Install/Uninstall, Migration, Mount, and Unmount, and the permission name is create, read, update, delete and allow.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
RoleName	Specifies the name of the role from which you want to remove permissions.	true	true (ByPropertyName)	
Permissions	Specifies one or more permissions you want to remove from a role. Use the format <SnapCenter Role Name>:<Permission Name>. Permission include: create, read, update, delete and allow.	true	true (ByPropertyName)	

Examples

Example 1: Removing a specific permission from a role

```
Remove-SmPermissionFromRole -RoleName "Infrastructure Admin" -Permissions  
DataSet:create
```

This example syntax removes the specified permission from a role.

Remove-SmPermissionFromRole

Are you sure you want to unassign the permission from role?.

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Example 2: Removing a specific permission from a role without a confirm dialogue

```
Remove-SmPermissionFromRole -RoleName "Infrastructure Admin" -Permissions  
DataSet:create -Confirm:$false
```

This example syntax removes the specified permission from a role.

Example 3: Removing multiple permissions from a role

```
Remove-SmPermissionFromRole -RoleName "Infrastructure Admin"  
-Permissions("Host:read","Host:update","Host:delete")
```

This example syntax removes multiple permissions from a role.

Remove-SmPlugin

Removes the specified plug-ins on one or more hosts.

Syntax

```
Remove-SmPlugin [-HostNames] <String> [-PluginCodes] <PluginCode> [-Force] <>
```

Detailed Description

Removes the specified plug-ins on one or more hosts.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostNames	Name of one or more hosts from which you want to uninstall the specified plug-ins.	true	true (ByPropertyName)	
PluginCodes	Provides the code for the plug-in you want to uninstall. Valid plug-in codes include SCSQL, SCO, SCE and hana. For custom plug-ins, the value is the custom plug-in name. For example "CustomPlugin1". For example, if you want to uninstall SnapCenter Plug-in for Microsoft SQL Server, the plug-in code is SCSQL.	true	true (ByPropertyName)	
Force	Internal switch.	false	true (ByPropertyName)	

Examples

Example 1: Uninstalling SnapCenter Plug-in for Microsoft SQL Server from a host

```
Remove-SmPlugin -HostNames myHostname -PluginCodes SCSQL
```

This command syntax uninstalls SnapCenter Plug-in for Microsoft SQL Server from the specified host.

Remove-SmPlugin

Are you sure you want to uninstall plugin(s) from the host(s)?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

Example 2: Uninstall single plug-in from a single host without a confirmation dialogue

```
Remove-SmPlugin -HostNames host.example.com -PluginCodes DB2 -Verbose  
-Confirm:$false
```

Uninstall single Plug-in from single host

```
VERBOSE: Start Remove-SmPlugin  
Name: Plug-in Uninstallation on host  
'scspn0115971001.lab.eng.btc.netapp.in'  
Id : 56  
StartTime : 6/16/2016 1:37:25 AM  
EndTime :  
IsCancellable : False  
IsRestartable : False  
IsCompleted : False  
IsVisible : True  
IsScheduled : False  
PercentageCompleted : 0  
Description :  
Status : Queued  
Owner :  
Error :  
Priority: None  
Tasks : {}  
ParentJobID : 0  
EventId : 0
```

Example 3: Uninstall multiple plug-ins from multiple hosts without the confirm dialogue

```
Remove-SmPlugin -Hostnames myhostname1,myhostname2 -PluginCodes  
DB2,MongoDB -Confirm:$false
```

One main job will be created for removing plug-ins from the hosts. Separate tasks will be created for removing each of the plug-in from the host.

Remove-SmPluginPackage

Removes a custom plug-in package from the SnapCenter repository.

Syntax

```
Remove-SmPluginPackage [-PluginName] <String> [-PluginVersion] <String>
```

Detailed Description

Removes a custom plug-in package from the SnapCenter repository.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginName	Specifies the name of the plug-in package you want to remove.	true	false	
PluginVersion	Specifies the version of the plug-in you want to remove.	true	false	

Examples

Example 1: Removing a custom plugin package

```
Remove-SmPluginPackage -PluginName CustomPlugin -PluginVersion 1.0
```

This example syntax removes the 1.0 plug-in version of the custom plug-in named CustomPlugin from the SnapCenter repository.

Remove-SmPolicy

Removes one or more policies from SnapCenter.

Syntax

```
Remove-SmPolicy [-PolicyNames] <String>
```

Detailed Description

Removes one or more policies from SnapCenter. In order to delete policies from SnapCenter, you must have already detached them from any datasets with which they are associated.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PolicyNames	Identifies the policy you want to delete. You can provide an individual policy name or a comma-separated list.	true	true (ByPropertyName)	

Examples

Example 1: Deleting a policy from SnapCenter

```
Remove-SmPolicy -PolicyNames 'SQL Full Backup'
```

This example syntax removes a specified policy.

Remove-SmPolicy

Are you sure you want to remove the dataset policy. Its association with dataset also gets removed.?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

Example 1: Deleting a policy from SnapCenter without confirmation dialogue

```
Remove-SmPolicy -PolicyNames 'SQL Full Backup' -Confirm:$false
```

This example syntax removes a specified policy.

Remove-SmProtectResource

This command helps remove the protection for the resources.

Syntax

```
Remove-SmProtectResource [-Resources] <Hashtable[]> [-Force] <> [-UnmanageOnly] <>
```

Detailed Description

Remove-SmProtectResource removes the protection for the resources provided.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Resources	The list of protected resources from which protection will be removed. You must provide the resource information in a hashtable, and it must contain the resource name and type, as well as the host on which the resource is located. For example, @{"Host"="localhost";"Type"="SQL Database";"Names"="Instance\Database"} Valid Type values are: SQL Database, SQL Instance, SQL Availability Group. You can include comma-separated values for Names. For Oracle Database, the format is -Resources @{"Host"="host.example.com";"Oracle Database"="db1"}. For Oracle Application Volume, the format is -Resources @{"Host"="host.example.com";"Application Volume"="appVol1"}.	true	true (ByPropertyName)	
Force	The force flag indicates that the protection will be deleted even if it has an associated policy and backup.	false	true (ByPropertyName)	
UnmanageOnly		false	true (ByPropertyName)	

Examples

Example 1: Removes the protection of the resources

```
Remove-SmProtectResource -Resources
@{"Host"="test.mycompany.com";"Type"="SQLDatabases";"Names"="test\SQLExpress\inst1"},@{"Host"="test.mycompany.com";"Type"="SQLDatabases";"Names"="test\SQLExpress\inst2"} -Force
```

This example syntax removes the protection of the two resources

Remove-SmProtectResource

Are you sure you want to delete the Protection of the selected resource?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

Example 1: Removes the protection of the resources without confirmation dialogue

```
Remove-SmProtectResource -Resources
@{"Host"="test.mycompany.com";"Type"="SQLDatabases";"Names"="test\SQLExpress\inst1"},@{"Host"="test.mycompany.com";"Type"="SQLDatabases";"Names"="test\SQLExpress\inst2"} -Force -Confirm:$false
```

This example syntax removes the protection of the two resources

Example 3: Unprotecting a single volume

```
Remove-SmProtectResource -Resources
@{"Type"="StorageVolume";"ResourceGuids"="f37b4bae-72a2-48b3-8504-7cc8eef15031";}
```

Example 4: Unprotecting multiple volumes

```
Remove-SmProtectResource -Resources
@{"Type"="StorageVolume";"ResourceGuids"="f37b4bae-72a2-48b3-8504-7cc8eef15031,b806a86a-1374-4be1-bb83-fc0d33947a97";}
```

Example 5: Removes the protection of the Oracle Application Volume resources

```
Remove-SmProtectResource -Resources
@(@{"Host"="R8092776CF4V1.HNK2.com";"ApplicationVolume"="appVol1"},@{"Host"="R8092776CF4V1.HNK2.com";"ApplicationVolume"="appVol2"})
```

This example syntax removes the protection of the two Oracle application volume resources

Remove-SmProtectResource

Are you sure you want to delete the Protection of the selected resource?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

Remove-SmReportSchedule

Delete a report schedule using this cmdlet.

Syntax

```
Remove-SmReportSchedule [-Name] <String>
```

Detailed Description

Delete an existing report schedule using this cmdlet.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specify the schedule name to delete it.	true	true (ByPropertyName)	

Examples

Example 1: Delete a report schedule.

```
Remove-SmReportSchedule -Name schedule1
```

This example deletes a report schedule. Pass the name of the schedule to delete it.

Remove-SmRepositoryProtection

Removes the protection for the NSM database from SnapCenter Server.

Syntax

```
Remove-SmRepositoryProtection
```

Detailed Description

Removes the protection for NSM database from SnapCenter Server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	------------	----------------	---------------

Examples

Example : Removes the protection for the MySQL database from SnapCenter Server.

```
Remove-SmRepositoryProtection
```

This example syntax removes the protection for the MySQL database from SnapCenter Server.

Remove-SmResource

Removes a custom plug-in resource or an Oracle plug-in application volume resource.

Syntax

```
Remove-SmResource [-HostName] <String> [-PluginCode] <PluginCode>
```

Detailed Description

Enables you to delete a custom plug-in resource or an Oracle plug-in application volume resource from SnapCenter. This deletes only the SnapCenter object, not the actual application object. If the resource is protected, then the resource is only soft-deleted and is available for recall Undo-Resource cmdlet; otherwise, the resource is permanently deleted from SnapCenter.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Specifies the name of host from which you want to remove the resource.	true	true (ByPropertyName)	
PluginCode	Specifies the name of the plug-in associated with the resource you are removing. Possible inputs include HANA or any SCC Custom Plug-in name or SCO.	true	true (ByPropertyName)	
ResourceType	The type of application object. For example, instance, database, or a SAP HANA SingleContainer or MultipleContainers. This parameter is not applicable for Oracle application volume resource.	true	true (ByPropertyName)	
ResourceName	Specifies the name of the resource which you want to remove.	true	true (ByPropertyName)	
SID	This is a SAP HANA database specific parameter. A SAP HANA system is identified by a unique 3 letter system ID (SID). For example, ABC.	true	true (ByPropertyName)	
TenantDatabaseName	This is a SAP HANA database specific parameter. It is the name of the tenant database for SAP HANA Multitenant Database.	false	true (ByPropertyName)	

Examples

Remove a custom plugin resource

```
Remove-SmResource -HostName 'sccorelinux188.sscore.test.com' -PluginCode  
'DB2' -Instance INST -ResourceType Database -ResourceName Db1
```

Remove a resource of type Database of custom plug-in type DB2

A resource will be soft deleted (marked as deleted) if the resource being deleted contains backup or is protected.

Successfully removed Inventory sccorelinux188.sscore.test.com:DB2:INST1\Db1

Remove a custom plugin resource without confirmation dialogue

```
Remove-SmResource -HostName 'sccorelinux188.sscore.test.com' -PluginCode  
'DB2' -Instance INST -ResourceType Database -ResourceName Db1  
-Confirm:$false
```

Remove a resource of type Database of custom plug-in type DB2

A resource will be soft deleted (marked as deleted) if the resource being deleted contains backup or is protected.

Remove-SmResource

Are you sure you want to remove the resource?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

```
Successfully removed Inventory  
sccorelinux188.sscore.test.com:DB2:INST1\Db1
```

Remove SAP HANA Multitenant Database Container

```
Remove-SmResource -HostName 'scspr0204312001.gdl.englab.netapp.com'  
-PluginCode 'hana' -ResourceType MultipleContainers -SID NBC  
-TenantDatabaseName ttt
```

Remove Multitenant Database Container of SnapCenter Plug-in for SAP HANA. A resource will be soft deleted (marked as deleted) if the resource being deleted contains backup or is protected.

Remove-SmResource

Are you sure you want to remove the resource?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

```
Successfully removed Inventory  
scspr0204312001.gdl.englab.netapp.com:hana:NBC\ttt
```

Remove SingleContainer SAP HANA Database

```
Remove-SmResource -HostName 'scspr0204312001.gdl.englab.netapp.com'  
-PluginCode 'hana' -ResourceType SingleContainer -SID H14
```

Remove SingleContainer database of SnapCenter Plug-in for SAP HANA.
A resource will be soft deleted (marked as deleted) if the resource being deleted contains backup or is protected.

Remove-SmResource

Are you sure you want to remove the resource?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

```
Successfully removed Inventory  
scspr0204312001.gdl.englab.netapp.com:hana:H14
```

Removes an Oracle Application Volume resource

```
Remove-SmResource -HostName 'R8092776CF4V1.HNK2.com' -PluginCode 'SCO'  
-ResourceName 'appVol'
```

Removes an Oracle application volume resource.
A resource will be soft deleted (marked as deleted) if the resource being deleted contains backup or is protected.

Remove-SmResource

Are you sure you want to remove the resource : 'appVol' ?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

Successfully removed resource R8092776CF4V1.HNK2.com:SCO:appVol

Remove-SmResourceCredentialName

Unregister a registered SQL instance credential.

Syntax

```
Remove-SmResourceCredentialName [-ResourceName] <String>
```

Detailed Description

Unregister a registered SQL instance credential based on the parameters provided.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ResourceName		true	true (ByPropertyName)	

Examples

- **Example 1: Removes a registered SQL instance credential by the SQL instance name. -**

```
Remove-SmResourceCredentialName -ResourceName R708202074BV1\SQL2019
```

This example syntax removes a registered SQL instance credential based on the SQL instance name provided.

```
Remove-SmResourceCredentialName
```

Are you sure you want to perform this action?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): Y

Example 2: Removes a registered SQL instance credential by the SQL instance name without a confirmation dialogue.

```
Remove-SmResourceCredentialName -ResourceName R708202074BV1\SQL2019  
-Confirm:$false
```

This example syntax removes a registered SQL instance credential based on the SQL instance name provided.

Remove-SmResourceDRMode

Remove resources from disaster recovery mode.

Syntax

```
Remove-SmResourceDRMode [-HostNames] <> [-AppObjectIds] <>
```

Detailed Description

Remove the resources from disaster recovery mode.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostNames	Specifies one or more hosts (FQDN) to remove all the resources of the hosts from disaster recovery mode.	true	true (ByPropertyName)	
AppObjectIds	Specifies one or more application object identifier of an SQL database to remove from disaster recovery mode.	true	true (ByPropertyName)	

Examples

Example 1: Removing all resources of the host from disaster recovery mode

```
Remove-SmResourceDRMode -HostNames host1.gdl.netapp.com
```

This example syntax removes all the resources of the host from disaster recovery mode.

```
Result      : SMCoreContracts.SMResult
TotalCount  : 0
DisplayCount : 0
Context     :
Job         : SMCoreContracts.SmJob
```

Example 2: Removing all resources of multiple hosts from disaster recovery mode

```
Remove-SmResourceDRMode -HostNames
host1.gdl.netapp.com,host2.gdl.netapp.com
```

This example syntax removes all the resources of hosts from disaster recovery mode.

```
Result      : SMCoreContracts.SMResult
TotalCount  : 0
DisplayCount : 0
Context     :
Job         : SMCoreContracts.SmJob
```

Example 3: Removing all resources of the cluster host from disaster recovery mode


```
Remove-SmResourceDRMode -HostNames  
Clusterhost.netapp.com,Node1.netapp.com,Node2.netapp.com
```

This example syntax removes all the resources of cluster host from disaster recovery mode. Specify cluster host with all the nodes.

```
Result      : SMCoreContracts.SMResult  
TotalCount   : 0  
DisplayCount : 0  
Context      :  
Job          : SMCoreContracts.SmJob
```

Example 4: Removing SQL resource from disaster recovery mode

```
Remove-SmResourceDRMode -AppObjectIds Host1/Inst1/DB1
```

This example syntax removes SQL resource from disaster recovery mode.

```
Result      : SMCoreContracts.SMResult  
TotalCount   : 0  
DisplayCount : 0  
Context      :  
Job          : SMCoreContracts.SmJob
```

Example 5: Removing multiple SQL resources from disaster recovery mode

```
Remove-SmResourceDRMode -AppObjectIds Host1/Inst1/DB1,Host1/Inst1/DB2
```

This example syntax removes SQL resources from disaster recovery mode.

```
Result      : SMCoreContracts.SMResult  
TotalCount   : 0  
DisplayCount : 0  
Context      :  
Job          : SMCoreContracts.SmJob
```

Remove-SmResourceFromUser

Removes a SnapCenter resource assigned to specified user.

Syntax

```
Remove-SmResourceFromUser [-UserName] <String> [-ResourceNames]
<String> [-ResourceType] <OperationAssignmentType> [-
UserGroupObjectType] <SmUserGroupObjectType>
```

Detailed Description

Remove a SnapCenter resource assigned to specified user.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
UserName	Name of the domain\user.	true	true (ByPropertyName)	
ResourceNames	Name of the resources to be removed. Allow comma seperated resources names.The resource name is the policy name, resource group name, storage connection name, credential name, host name or IP address, or plug-in name created by the user.	true	true (ByPropertyName)	
ResourceType	Type of resource. The SnapCenter resource types are Credential, Host, ResourceGroup, Policy, StorageConnection or Plugin.	true	true (ByPropertyName)	
UserGroupObjectType	Specifies the user type whose resources are removed. Possible values are User or Group.	false	true (ByPropertyName)	

Examples

Example 1: Removing a specific resource from a user

```
Remove-SmResourceFromUser -ResourceNames PayrollDataset -ResourceType
ResourceGroup -UserName mva\administrator
```

This example syntax removes the specified resource name from the user indicated.

Remove-SmResourceFromUser

Are you sure want to perform this action?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):y

Example 2: Removing a specific resource from a user without confirmation dialogue

```
Remove-SmResourceFromUser -ResourceNames PayrollDataset -ResourceType  
ResourceGroup -UserName mva\administrator -Confirm:$false
```

This example syntax removes the specified resource name from the user indicated.

Example 3: Removing a specific resource from a group.

```
Remove-SmResourceFromUser -ResourceNames PayrollDataset -ResourceType  
ResourceGroup -UserName mva\group1 -UserGroupObjectType Group
```

This example syntax removes the specified resource name from the identified group.

Remove-SmResourceGroup

Removes a resource group.

Syntax

```
Remove-SmResourceGroup [-ResourceGroupNames] <String> [-Force] <>
```

Detailed Description

Enables you to delete a resource group from SnapCenter based on the resource group name provided.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ResourceGroupNames		true	true (ByPropertyName)	
Force		false	true (ByPropertyName)	

Examples

- Example 1: Removes a resource group by the resource group name -

```
Remove-SmResourceGroup -ResourceGroupNames RG2
```

This example syntax removes a resource group from SnapCenter based on the resource group name provided.

Remove-SmResourceGroup

Are you sure you want to delete the Resource Group selected?Resource Group will be removed from all the member hosts of the Resource Group. The backups of the Resource Group will be deleted when the Resource Group is removed. Also all the association of policy with this Resource Group will be detached.

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): Y

- **Example 2: Removes the resource group by resource group name without a confirmation dialogue.** -

```
Remove-SmResourceGroup -ResourceGroupNames RG2 -Confirm:$false
```

This example syntax removes a resource group from SnapCenter based on the resource group name provided.

Remove-SmRole

Removes an RBAC role.

Syntax

```
Remove-SmRole [-Name] <String>
```

Detailed Description

Removes an RBAC role.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Names the RBAC role you want to delete.	true	true (ByPropertyName)	

Examples

Example 1: Removing a specific role

```
Remove-SmRole -Name BackupAdmin
```

This example syntax removes the specified role from SnapCenter.

Remove-SmRole

Are you sure you want to remove the role ?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Example 2: Removing a specific role without confirmation dialogue

```
Remove-SmRole -Name BackupAdmin -Confirm:$false
```

This example syntax removes the specified role from SnapCenter.

Remove-SmServer

Removes the SC server from the High Availability cluster.

Syntax

```
Remove-SmServer [-Credential] <PSCredential> [-ServerNameString]  
<String> [-ServerIPString] <String>
```

Detailed Description

Removes the given SC server from the High Availability cluster. The SC server should be removed from the load balancing configuration and, SnapCenter should be uninstalled on the server to be removed.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Credential	Provides domain user credentials for the user to remove High Availability cluster configuration.	true	true (ByPropertyName)	
ServerName	Secondary SC server name.	false	false	
ServerIP	Secondary SC server IP Address.	true	false	

Examples

Example 1: Removing SnapCenter Server from High Availability cluster

```
Remove-SmServer -Credential sddev\administrator -ServerIP 10.225.231.178  
-ServerName SecondServer.domain.com
```

This example removes SnapCenter Server from High Availability cluster.

```

Remove-SmServer -ServerIP 10.225.231.178
WARNING: Uninstallation of SnapCenter Server on secondary node is
recommended.
Name: Removing SnapCenter Server 10.225.231.178 from High Availability
Cluster
Id      : 1606
StartTime    : 9/25/2019 1:23:11 AM
EndTime     :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 100
Description   :
Status       : Running
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId      : 0
JobTypeId     : 38
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    : NONE
HostId       : 0
RoleId        :
JobIds        : {}

```

Remove-SmServerCluster

Removes the High Availability cluster configuration on the SnapCenter Server

Syntax

```

Remove-SmServerCluster [-Credential] <PSCredential> [-ClusterNameString]
<String> [-ClusterIPString] <String>

```

Detailed Description

Removes the High Availability cluster configuration on the SnapCenter Server. This can be used to convert to Standalone configuration.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Credential	Provides domain user credentials for the user to remove High Availability cluster configuration.	true	true (ByPropertyName)	
ClusterName	F5 cluster name.	false	false	
ClusterIP	F5 Cluster IP Address.	true	false	

Examples

Example 1: Removing High Availability cluster configuration on the SnapCenter Server

```
Remove-SmServerCluster -Credential sddev\administrator -ClusterIP  
10.235.236.190 -ClusterName f5pool
```

This removes the High Availability cluster configuration on the SnapCenter Server.

```

Name: Remove High Availability for SnapCenter Server
Id   : 972
StartTime   : 10/5/2019 6:19:26 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Running
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 38
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    : NONE
HostId        : 0
RoleId        :
JobIds        : {}
Monitor the progress of job 972 in the Job Monitor page or by running the
cmdlet: 'Get-SmJobSummaryReport -JobId 972'

```

Remove-SmStorageConnection

Removes a storage system connection.

Syntax

```

Remove-SmStorageConnection [-Storage] <String> [-AzureNetAppAccountIds]
<bigint(20)>

```

Detailed Description

Removes a storage system connection. You can remove one storage system connection at a time.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Storage		false	true (ByPropertyName)	

Examples

Example 1: Removing a storage system connection

```
Remove-SmStorageConnection -SVM 172.17.168.13
```

This example syntax removes a storage system connection

```
Remove-SmStorageConnection
```

Are you sure you want to remove the storage connection?

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

Remove Storage connection successful

Example 2: Removing a storage system connection without confirmation dialogue

```
Remove-SmStorageConnection -SVM 172.17.168.13 -Confirm:$false
```

This example syntax removes a storage system connection

Remove Storage connection successful

Example 3: Removing Azure NetApp Account

```
Remove-SmStorageconnection -AzureNetAppAccountIds 1
```

This example removes Azure NetApp Accounts with specified Azure NetApp Account IDs.

Remove-SmUser

Removes AD users or local workgroup users from SnapCenter.

Syntax

```
Remove-SmUser [-UserName] <SmString> [-Domain] <String>
```

Detailed Description

Removes Active Directory users or local workgroup users from SnapCenter.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
UserName	Single user or list of users belonging to the same domain or workgroup.	true	true (ByPropertyName)	
Domain	The domain to which the user belongs to. Workgroup users should skip this parameter.	false	true (ByPropertyName)	

Examples

Example 1: Removing a single user 1

```
Remove-SmUser -UserName user1 -Domain domain1
```

Example 2: Removing multiple users of same domain 2

```
Remove-SmUser -UserName user1,user2 -Domain domain1
```

Example 3: Removing workgroup user

```
Remove-SmUser -UserName LocalUser1
```

Remove-SmUserFromRole

Deletes a user from an RBAC role.

Syntax

```
Remove-SmUserFromRole [-UserName] <SmString> [-RoleName] <String> [-Domain] <String>
```

Detailed Description

Deletes a user from an RBAC role.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
UserName	Specifies the user you want to remove from the RBAC role.	true	true (ByPropertyName)	
RoleName	Specifies the name of the role from which you want to remove the user.	true	true (ByPropertyName)	
Domain	Domain to which user belongs to. Workgroup users should skip this parameter.	false	true (ByPropertyName)	

Examples

Example 1: Deleting a role from a specific user

```
Remove-SmUserFromRole -UserName administrator -Domain mva -RoleName BackupAdmin
```

This example syntax removes the specified user from a role.

```
Remove-SmUserFromRole
```

Are you sure you want to unassign the user from role?.

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y

```
BackupAdmin
```

```
mva\administrator
```

Example 2: Deleting a role from a specific user without confirmation dialogue

```
Remove-SmUserFromRole -UserName administrator -Domain mva -RoleName BackupAdmin -Confirm:$false
```

This example syntax removes the specified user from a role.

```
Remove-SmUserFromRole
```

```
BackupAdmin
```

```
mva\administrator
```

```
===
```

Remove-SmVerificationServer

Removes one or more verification servers.

Syntax

```
Remove-SmVerificationServer [-Names] <String>
```

Detailed Description

Removes one or more verification servers. When you run Remove-SmVerificationServer, you do not remove the SQL Server instance you are using as the verification server, you simply remove the verification server settings so that the SQL Server instance can no longer be used as a SnapCenter verification server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Names	Specifies the names of the verification server or servers you want to remove.	true	true (ByPropertyName)	

Examples

Example 1: Removing a verification server

```
Remove-SmVerificationServer -Names mva-s51/instance1
```

This example syntax removes a verification server.

```
Remove-SmVerificationServer
Are you sure you want to remove the host and its resources.?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y
```

Example 2: Removing a verification server without confirmation dialogue

```
Remove-SmVerificationServer -Names mva-s51/instance1 -Confirm:$false
```

This example syntax removes a verification server.

.

Rename-SmBackup

Renames an existing backup.

Syntax

```
Rename-SmBackup [-BackupName] <String> [-NewBackupName] <String> [-  
PluginType] <PluginCode>
```

Detailed Description

Renames an existing backup.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
BackupName	Name of the existing backup.	true	false	
NewBackupName	The new name you will give the backup.	true	false	
PluginType	Provides the SnapCenter plug-in type. You can specify one of the following: SCSQL or SCW.	true	false	

Examples

Example 1: Renames an existing backup

```
Rename-SmBackup -BackupName SQL_DATASET_CLONE_csmdev-smsql-02_08-03-  
2015_13.45.19.4400  
                -NewBackupName SQL_DATASET_CLONE_RENAMED -PluginType SCSQL  
-Verbose
```

This example command syntax renames an existing backup to a new name that you specify.

VERBOSE: Start Rename-SmBackup

VERBOSE: Rename-SmBackup ended successfully.

Reseed-SmBackup

Restores the particular database and joins it back to the Availability Group.

Syntax

```
Reseed-SmBackup [-PluginCode] <PluginCode> [-AppObjectId] <String> [-  
BackupName] <String>
```

Detailed Description

Restores the particular database and joins it back to the Availability Group. This operation is supported only with the database of secondary replica.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode		false	false	
AppObjectId		true	false	
BackupName		false	false	

Examples

Example 1: Reseed Secondary Database of an availability Group

```
Reseed-SmBackup -AppObjectId CHAN-  
New\INST4\Auto_DB_CHAN_ESX7_INST1_MDML_1
```

This example syntax reseeds the secondary copy of the database mentioned by the appobjectId and brings it to sync with primary database and joins the database back to Availability Group.

Reseed-SmDagReplicaCopy

This command will restore or reseed the failed copy of the database.

Syntax

```
Reseed-SmDagReplicaCopy [-ReplicaHost] <String> [-Database] <String>  
[-BackupHost] <String>
```

Detailed Description

Restores an unhealthy replica by using either the most recent copy on the same host or the most recent copy from an alternate host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ReplicaHost		true	false	
Database		true	false	
BackupHost		false	false	

Examples

Example 1: Reseed a replica

```
reseed-SmDagReplicaCopy -ReplicaHost "mva-rx200.netapp.com" -Database  
execdb -BackupHost "mva-rx201.netapp.com"
```

Restore-SmBackup

Restores a backup.

Syntax

```
Restore-SmBackup [-PluginCode] <PluginCode> [-AppObjectId] <String> [-  
BackupId] <String> [-BackupName] <String> [-LogRestoreType]  
<SmSqlLogRestoreType> [-RestoreWhenOnline] <> [-  
RetainReplicationSettings] <> [-CreateTransactionLog] <> [-  
FailOnTransactionLogBackupFailure] <> [-RecoveryModel]  
<SmSqlRecoveryModel> [-UndoLogDirectory] <String> [-Archive]  
<Hashtable[]> [-AuxiliaryDestination] <String> [-LogArchive]  
<Hashtable[]> [-AlternatePath] <Hashtable[]> [-LogCount] <Int32> [-  
LogCutOffDateTime] <DateTime> [-FailOnLogBackupFailure] <> [-  
SceRecoveryModel] <SCERecoveryModel> [-ExistingFiles] <> [-TargetHost]  
<String> [-NoVerify] <> [-IsRecoverMount] <> [-PreScriptCommand]  
<String> [-PreScriptArguments] <String> [-SQLInstanceName] <String>  
[-DatabaseName] <String> [-CustomLogDirectory] <String> [-  
RecoveryTypeHanaRecoveryType] <HanaRecoveryType> [-  
RecoveryTypePostgreSQLRecoveryType] <PostgreSQLRecoveryType> [-  
RecovertimezoneString] <> [-TenantDatabaseNameString] <String> [-  
VolumeRevertSwitchParameter] <> [-PostScriptCommand] <String> [-  
PostScriptArguments] <String> [-ScriptTimeout] <Int32> [-  
OracleControlFileRestore] <> [-OracleFullRestore] <> [-  
OracleSkipRecovery] <> [-OracleUntilScn] <Int64> [-OracleTablespaces]  
<String> [-OracleChangeState] <> [-OraclePluggableDatabases] <String>  
[-AlternateArchiveLogsPath] <String> [-OracleOpenDatabaseAfterRecovery]  
<> [-OracleUntilTime] <DateTime> [-RestoreLastBackup] <Int32> [-  
RestoreOnClusterHost] <String> [-RestoreOracleRedoLogFile] <> [-  
OracleOpenPluggableDatabasesAfterRecovery] <> [-  
OracleOpenTablespacesAfterRecovery] <> [-ForceInplaceRestore] <> [-  
PluginCreatorCustomRestoreParams] <Hashtable> [-EnableEmail] <> [-  
EmailPreference] <SmEmailNotificationPreference>
```

Detailed Description

Restores a backup. You can specify whether to restore log files or not, and the types of log files. You can restore databases even if existing databases are online.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode	Specifies the plug-in code of the resource to be restored. Valid plug-in codes are SCW and SCSQL.	true	false	
AppObjectId	Specifies the ID of the application object.	true	false	
BackupId	Specifies the ID of the backup to use for restore.	false	false	
BackupName	Specifies the name of the backup to use for restore.	false	false	
LogRestoreType	Specifies the log restore type. User can choose to apply no logs, all logs or specific logs.	false	false	
RestoreWhenOnline	Restore databases even if existing databases are online.	false	false	
RetainReplicationSettings	Retain SQL database replication settings.	false	false	
CreateTransactionLog	Create transaction log backup before restore.	false	false	
FailOnTransactionLogBackupFailure	Quit restore if transaction log backup fails before restore.	false	false	
RecoveryModel	Specifies the SQL recovery model for applying logs.	false	false	
UndoLogDirectory	Specifies a location where the standby files are created, so that the recovery effects can be reversed.	false	false	
Archive	Specifies the secondary storage system details for restore.	false	false	

Name	Description	Required ?	Pipeline Input	Default Value
AlternatePath	Specifies an alternate location to restore the database.	false	false	
LogCount	Specifies the number of logs to apply.	false	false	
AuxiliaryDestination	Auxiliary destination on the database host required to perform Oracle point in time recovery.	false	false	
LogArchive	Specify the archive location of the archive logs from where the Oracle database resource is to be restored	false	false	
LogCutOffDateTime	Specifies the cutoff time to restore the database. If the server and plug-in host are in different time zones, the input must be as per the plug-in host time zone.	false	false	
FailOnLogBackupFailure		false	false	
ScnRecoveryModel		false	false	
ExistingFiles	Restore from Existing files specified in AlternatePath.	false	false	
TargetHost		false	false	
NoVerify		false	false	
IsRecoverMount		false	false	
PreScriptCommand	Specifies commands that get executed before the restore operation.	false	true (ByPropertyName)	
PreScriptArguments	Specifies arguments to the prescript command.	false	true (ByPropertyName)	
SQLInstanceName	Specifies the SQL Server instance to which the database is restored in an alternate path scenario.	false	false	
DatabaseName	Specifies the new database name when restoring the database to an alternate path.	false	false	

Name	Description	Required ?	Pipeline Input	Default Value
CustomLogDirectory	This parameter is required for specifying a custom path, either a network share path or a drive path, where you have stored the logs. This parameter is used for restore operations from both primary and secondary copies.	false	false	
RecoveryType	Specifies the recovery type for HANA resources.	false	false	
Recovertimezone	Timezone of the client. This parameter is applicable to HANA plug-in resource when the RecoveryType specified is 'RecoverUntilDateTime'. Acceptable format: GMT+HH:MM or GMT-HH:MM.	false	false	
TenantDatabaseName	Name of the HANA tenant database to be restored. This parameter is applicable to MultiTenant Database Containers resources. No recovery will be performed for the specified tenant database.	false	false	
VolumeRevert	Enables file system restore in case of Complete Restore for Auto-discovered resources. This parameter is used mainly for auto-discovered resource backups and this option can be used to prevent volume based restore and cleaning up of later backups if an older backup is selected for restore.	false	false	
PostScriptCommand	Specifies the commands that get executed after the restore operation.	false	true (ByPropertyName)	
PostScriptArguments	Specifies the arguments to the postscript command.	false	true (ByPropertyName)	
ScriptTimeout	Specifies the maximum timeout to wait for the script to complete.	false	true (ByPropertyName)	
OracleControlFileRestore	Indicates that you want to restore the Oracle control file.	false	false	
OracleFullRestore	Indicates that you want to perform a full Oracle database restore.	false	false	

Name	Description	Required ?	Pipeline Input	Default Value
OracleSkipRecovery	Indicates that you want to skip Oracle database recovery.	false	false	
OracleUntilScn	Indicates that you want to restore to a specific System Change Number.	false	false	
OracleTablespaces	Indicates the Pluggable database (PDB) tablespaces to be restored.	false	false	
OracleChangeState	Indicates that the database state should be changed to the state required to perform restore and recovery operations. The states of a database from higher to lower are open, mounted, started, and shutdown.	false	false	
OraclePluggableDatabases	Indicates the Pluggable databases to be restored.	false	false	
AlternateArchiveLogPath	Indicates an alternate archive logs path.	false	false	
OracleOpenDatabaseAfterRecovery	Specifies that the databases must be opened after recovery is performed.	false	false	
OracleUntilTime		false	false	
RestoreLastBackup	Restore the Nth Backup of a resource with provided AppObjectId. For example, value entered as 5 with AppObjectId "testResource", it will restore the 5th backup for resource found with AppObjectId "testResource" provided that at least 5 backups are available.	false	false	
RestoreOnClusterHost	Specifies the cluster node on which the restore operation must be performed. You must specify this option only for an Oracle RAC database. If this option is not specified, restore operation is performed on the node where the backup was created.	false	false	
RestoreOracleRedoLogFile	Indicates that you want to restore Oracle redo log files. Redo log file restore is only supported for Data Guard and Active Data Guard standby database.	false	false	

Name	Description	Required ?	Pipeline Input	Default Value
OracleOpenPluggableDatabasesAfterRecovery	Specifies that the pluggable databases must be opened after recovery is performed.	false	false	
OracleOpenTablespacesAfterRecovery	Specifies that the tablespaces must be opened after recovery is performed.	false	false	
ForceInplaceRestore	Indicates that you want to perform in-place restore and bypass all restore validations.	false	false	
PluginCreatorCustomRestoreParams		false	false	
EnableEmail	Enables e-mail.	false	false	
EmailPreference	Specifies when you will receive e-mail notifications. Possible values: Always, Never, OnError, OnErrorOrWarning.	false	false	
EmailFrom	Specifies the sender's e-mail address.	true	true (ByPropertyName)	
EmailTo	Specifies the recipient's e-mail address.	true	true (ByPropertyName)	
EmailSubject	Specifies the e-mail subject.	true	true (ByPropertyName)	
EnableEmailAttachment	Enables email attachments.	false	true (ByPropertyName)	

Examples

Example 1: Restoring from a primary backup

```
PS C:\> Restore-SmBackup -PluginCode SCSQL -AppObjectId 'vise-f6\PayrollDatabase' -BackupName 'NetApp_PayrollDataset_Backup Policy_vise-f6_NetApp_08-07-2015_08.48.59.6962' -RestoreWhenOnline
```

This example syntax restores from a primary backup.

```
Name: Restore 'vise-f6\PayrollDatabase'
Id   : 199
StartTime   : 8/7/2015 9:21:36 AM
EndTime    :
IsCancellable   : False
IsRestartable   : False
IsCompleted    : False
IsVisible      : False
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId      : 0
```

Example 2: Restoring to an alternate path from a primary

```
PS C:\> Restore-SmBackup -PluginCode SCSQL -AppObjectId 'vise-
f6\PayrollDatabase' -BackupName 'NetApp_PayrollDataset_Backup Policy_vise-f6_NetApp_08-07-
2015_08.48.59.6962' -AlternatePath @{Source='I:\PayrollDatab
ase.mdf';Destination='H:\PayrollDatabase_copy_log.mdf'},@{Source='I:\Payro
llDatabase_log.ldf';Destination='H:\PayrollDat
abase_copy_log.ldf'} -SQLInstanceName 'vise-f6\BRAVEHEART'
-DatabaseName 'PayrollDatabase_copy'
```

This example syntax restores a backup to an alternate path

```
Name: Restore 'vise-f6\PayrollDatabase'
Id   : 203
StartTime   : 8/7/2015 9:30:32 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : False
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID  : 0
EventId      : 0
```

Example 3: Restoring from a secondary backup

```
PS C:\> Restore-SmBackup -PluginCode SCSQL -AppObjectId 'vise-
f6\PayrollDatabase' -BackupName 'NetApp_PayrollDataset_Backup Policy_vise-f6_NetApp_08-07-
2015_08.48.59.6962' -Archive @{Primary="rtp-rr1-d2.gdl.englab.netapp.com:vol_src";Secondary="vs1:vs1_vol_src_vault"}
-RestoreWhenOnline
```

This example syntax restores from a secondary backup.

```
Name: Restore 'vise-f6\PayrollDatabase'
Id : 208
StartTime : 8/7/2015 9:40:12 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : False
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
```

Example 4: Removing a Run As account from a resource

```
PS C:\> Restore-SmBackup -PluginCode SCSQL -AppObjectId 'vise-
f6\PayrollDatabase' -BackupName 'Mycompany_PayrollDataset_Backup Policy_vise-f6_Mycompany_08-
07-2015_08.48.59.6962' -Archive @{Primary="rtp-rr1-
d2.gdl.mycompany.com:vol_src";Secondary="vs1:vs1_vol_src_vault"}
-RestoreWhenOnline -AlternatePath @{Source='I:\PayrollDatabase.
mdf';Destination='H:\PayrollDatabase_copy_log.mdf'},@{Source='I:\PayrollDa
tabase_log.ldf';Destination='H:\PayrollDatabas
e_copy_log.ldf'} -SQLInstanceName 'vise-f6\BRAVEHEART'
-DatabaseName 'PayrollDatabase_copy'
```

This example syntax removes a Run As account from a resource.

```

Name: Restore 'vise-f6\PayrollDatabase'
Id : 210
StartTime : 8/7/2015 9:46:54 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : False
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0

```

Example 5: Restore complete Resource of Custom plugin DB2 from Primary Storage

```

Restore-SmBackup -PluginCode 'DB2' -AppObjectId
'sccorelinux61.sscore.test.com\DB2\NTP\DB1' -BackupId 191 -Confirm:$false
-mountcommands 'sh /var/opt/mountCmd.sh' -unmountcommands 'sh
/var/opt/unmountCmd.sh'

```

Restore complete Resource of type Database of Custom plug-in DB2 from Primary Storage with mount and unmount commands

Example 6: Restore Complete custom plugin resource from Secondary storage

```

Restore-SmBackup -PluginCode 'DB2' -AppObjectId
'sccorelinux61.sscore.test.com\DB2\SECONDARYSMSV1' -BackupId 198
-Confirm:$false -customrestoreparams @{"KEY_PARAM1"="CUSTPARAM1"}
-prescriptarguments 'PreScriptCommand > PreScriptCommand.txt'
-prescriptcommand echo -postscriptarguments 'PostScriptCommand >
PostScriptCommand.txt' -postscriptcommand echo -Archive @(
@{"Primary"="vserver_scauto_primary:SMSV1_SRC_sccorelinux61_sscore_test_co
m";"Secondary"="vserver_scauto_primary:SMSV1_DST3_sccorelinux61_sscore_tes
t_com"})

```

Restore Complete custom plug-in resource from Secondary storage with custom key-value pairs and pre-post commands

Example 7: Restore files/LUNs from Primary storage of Custom plugin resource

```
Restore-SmBackup -PluginCode 'DB2' -AppObjectId  
'sccorelinux61.sscore.test.com\DB2\RVOL' -BackupId 313 -Confirm:$false  
-path  
vserver_scauto_primary:/vol/ng_rvol1_sccorelinux61_sscore_test_com/file1,v  
server_scauto_primary:/vol/ng_rvol2_sccorelinux61_sscore_test_com/file1
```

Restoring multiples files from multiple/single volumes can be combined together

Example 8: Restoring to a cluster host

```
Restore-SmBackup -PluginCode 'SCO' -AppObjectId 'smo-suse-  
11g.gdl.englab.netapp.com\itdb' -BackupName 96skdb_smo-suse-11g_02-15-  
2017_18.11.43.3978_0 -oraclechangestate -RestoreOnClusterHost  
'clusterhost.com'
```

Restore to a cluster host. This is applicable only for Oracle RAC Database.

Example 9: After restore change the state of tablespaces to online

```
Restore-SmBackup -PluginCode 'SCO' -AppObjectId  
'scspr0198204001.gdl.englab.netapp.com\itdb' -BackupName  
rg1_scspr0198204001_02-15-2017_16.53.38.9804_0 -oraclechangestate  
-OracleOpenTablespacesAfterRecovery -OracleTablespaces newts  
-ForceInplaceRes
```

After restoring the database, changes the state of the tablespaces to online

Example 10: After restore change the state of PDBS to read write

```
Restore-SmBackup -PluginCode 'SCO' -AppObjectId 'smo-suse-  
11g.gdl.englab.netapp.com\skdb' -BackupName 96skdb_smo-suse-11g_02-16-  
2017_17.46.09.0207_0 -oraclechangestate -OraclePluggableDatabases  
'SKPDB1','SKPDB2' -OracleOpenPluggableDatabasesAfterRecovery
```

After restoring the database, changes the state of the PDBS to read write.

Example 11: Restoring from existing files specified in alternate path from a primary

```
PS C:\> Restore-SmBackup -PluginCode SCSQL -AppObjectId 'vise-
f6\PayrollDatabase' -BackupNam
e 'NetApp_PayrollDataset_Backup Policy_vise-f6_NetApp_08-07-
2015_08.48.59.6962' -AlternatePath @{Source='I:\PayrollDatab
ase.mdf';Destination='H:\PayrollDatabase_copy_log.mdf'},@{Source='I:\Payro
llDatabase_log.ldf';Destination='H:\PayrollDat
abase_copy_log.ldf'} -SQLInstanceName 'vise-f6\BRAVEHEART'
-DatabaseName 'PayrollDatabase_copy' -ExistingFiles
```

This example syntax restores a backup using existing files specified alternate path

```
Name: Restore 'vise-f6\PayrollDatabase'
Id : 203
StartTime : 8/7/2015 9:30:32 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : False
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
```

Example 12: Restore files/LUNs from Primary storage of Custom plugin resource using All File Restore option

```
Restore-SmBackup -PluginCode 'DummyPlugin' -AppObjectId
'scclinux1.scc.test.com\DummyPlugin\RNVOL' -BackupId 313 -Confirm:$false
-AllFileRestorePath
vserver_scauto_primary:/vol/ng_rvol1_scclinux1_scc_test_com
```

All File Restore can be performed on multiple volumes and on multiple Vservers by providing a comma separated list of volume paths from which All File Restore is to be performed

Example 13: Restore files from Primary storage of SAP HANA MultiTenant Database Container resource using All File Restore option

```
Restore-SmBackup -PluginCode 'hana' -AppObjectId  
scspr43002.scc.test.com\hana\R01\R01 -BackupId 313 -Confirm:$false  
-AllFileRestorePath vs_test:/vol/cn_p1,vs_test:/vol/cn_p2
```

All File Restore can be performed on multiple volumes and on multiple Vservers by providing a comma separated list of volume paths from which All File Restore is to be performed

Example 14: Restore files and LUNs from a Primary storage of SAP HANA MultiTenant Database Container resource

```
Restore-SmBackup -PluginCode 'hana' -AppObjectId  
scspr043002.scc.test.com\hana\R01\R01 -BackupId 3 -Confirm:$false  
-AllFileRestorePath vs_test:/vol/cn_p1 -Path  
vs_test:/vol/cn_lun_vol/cn_lun
```

All File Restore can be performed on multiple volumes and on multiple Vservers by providing a comma separated list of volume paths from which All File Restore is to be performed. Lun path can be provided as a value for Path parameter.

```
Name: Restore 'scspr043002.scc.test.com\hana\R01\R01'
Id   : 1363
StartTime   : 9/28/2019 10:22:11 AM
EndTime    :
IsCancellable   : False
IsRestartable   : False
IsCompleted    : False
IsVisible      : True
IsScheduled     : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 1
ApisJobKey    :
ObjectId      : 0
PluginCode    : SCC
PluginName    : PluginCreator
HostId        : 0
RoleId        :
JobIds        : {}
```

Example 15: Restore LUNs from a specific backup of SAP HANA MultiTenant Database Containers resource

```
Restore-SmBackup -PluginCode 'hana' -BackupName
'schana02_gdl_englab_netapp_com_hana_MDC_R70_schana02_08-19-
2019_21.07.33.2537' -AppObjectId
'schana02.gdl.englab.netapp.com\hana\MDC\R70' -RecoveryType
RecoverToSpecificBackup
```

Restore performed to specific backup on Hana resource.

```
Name: Restore 'schana02.gdl.englab.netapp.com\hana\MDC\R70'
Id   : 1363
StartTime   : 9/30/2019 12:40:44 PM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId      : 0
JobTypeId     : 1
ApisJobKey    :
ObjectId      : 0
PluginCode    : SCC
PluginName    : PluginCreator
HostId       : 0
RoleId       :
JobIds       : {}
```

Example 16: Restore the HANA resource to a specific date or time (Point in time restore)

```
Restore-SmBackup -PluginCode 'hana' -AppObjectId
'AutoMTSles253\hana\MDC\MT1' -BackupId '469' -Confirm:$false
-recovertimezone 'GMT+05:30' -recoveruntiltime '10/01/19 05:46:21 AM'
-recoverytype RecoverUntilDateTime
```

Restore performed to a specific date or time on a HANA resource.

```
Name: Restore 'AutoMTSles253\hana\MDC\MT1'
Id : 1371
StartTime : 9/30/2019 12:59:42 PM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 1
ApisJobKey :
ObjectId: 0
PluginCode : SCC
PluginName : PluginCreator
HostId : 0
RoleId :
JobIds : {}
```

Example 17: Restoring to a custom log directory

```
Restore-SmBackup -PluginCode SCSQL -AppObjectId 'RAHUL-123-123\INSTANCE2\db1' BackupName 'RAHUL-123-123_INSTANCE2_db1_SQL-123-123_06-18-2018_15.53.55.4944 -AlternatePath @{Source='F:\New folder\db1.mdf';Destination='C:\rtah\db1.mdf'},@{Source='F:\New folder\db1_log.ldf';Destination='C:\rtah\db1_log.ldf'} -SQLInstanceName 'RX200-WHQL10\INST' -DatabaseName 'DB1_RTAAH' -TargetHost 'rx200-whql10.sdwdc.netapp.com' -LogRestoreType All -CustomLogDirectory "\\STAB-VM1\net share" -Archive @{Primary="RAHUL_fs1-smhv:Rahul_scsql";Secondary="RAHUL_fs.1-smhv:RAHUL_fs1-smhv_Rahul_scsql_vault"}
```

This example syntax specifies a custom log directory when restoring backups.

```
Name:      : Restore 'RAHUL-123-123\INSTANCE2\db1' to instance 'RX200-
WHQL10\INST'
Id       : 48
StartTime    : 6/20/2018 1:31:25 AM
EndTime     :
IsCancellable : False
IsRestartable : False
IsVisible    : True
IsScheduled  : False
PercentageCompleted : 0
Description  :
Status      : Queued
Owner       :
Error       :
Priority: None
Tasks      : {}
ParentJobID : 0
EventId    : 0
JobTypeId  : 1
ApisJobKey  :
ObjectId: 0
PluginCode  : SCSQL
PluginName  : SnapCenter Plug-in for Microsoft SQL Server
HostId     : 0
RoleId     :
```

Example 18: Trigger file system restore without volume based restore

```
Restore-SmBackup -BackupName 'vp-
hana1_gdl_englab_netapp_com_hana_MDC_N92_vp-hana1_08-20-
2019_22.35.52.9698' -PluginCode HANA -AppObjectId 'vp-
hana1.gdl.englab.netapp.com\hana\MDC\N92'-RecoveryType SkipRecovery
-VolumeRevert
```

This example syntax supports file system restore without volume based restore.

```
Name:      : Restore 'vp-hana1.gdl.englab.netapp.com\hana\MDC\N92'
Id       : 77
StartTime  : 6/22/2018 1:55:10 AM
EndTime    :
IsCancellable : False
IsRestartable : False
IsVisible   : True
IsScheduled  : False
PercentageCompleted : 0
Description :
Status      : Queued
Owner       :
Error       :
Priority     : None
Tasks       : {}
ParentJobID : 0
EventId     : 0
JobTypeId   : 1
ApisJobKey   :
ObjectId    : 0
PluginCode   : SCC
PluginName   : hana
HostId      : 0
RoleId      :
```

Example 19: Trigger tenant database restore

```
Restore-SmBackup -BackupName 'vp-
hana1_gdl_englab_netapp_com_hana_MDC_N92_vp-hana1_08-20-
2019_22.35.52.9698' -PluginCode HANA -AppObjectId 'vp-
hana1.gdl.englab.netapp.com\hana\MDC\N92'-RecoveryType SkipRecovery
-TenantDatabaseName N92
```

This example syntax restores the given tenant database.


```
Name:      : Restore 'vp-hana1.gdl.englab.netapp.com\hana\MDC\N92'
Id       : 78
StartTime  : 6/23/2019 1:55:10 AM
EndTime    :
IsCancellable : False
IsRestartable : False
IsVisible    : True
IsScheduled  : False
PercentageCompleted : 0
Description :
Status      : Queued
Owner       :
Error       :
Priority     : None
Tasks       : {}
ParentJobID : 0
EventId     : 0
JobTypeId   : 1
ApisJobKey   :
ObjectId     : 0
PluginCode   : SCC
PluginName   : hana
HostId      : 0
RoleId      :
```

Example 20: Trigger HANA database restore with all logs

```
Restore-SmBackup -PluginCode 'HANA' -AppObjectId
'R708057AFB8V1\hana\MDC\H14' -BackupName
'R708057AFB8V1_hana_MDC_H14_R708057AFB8V1_08-25-2020_03.02.03.7780'
-RecoveryType RecoverToMostRecentState -InitializeLogArea
```

This example syntax restores the given HANA database.

```
Name: Restore 'R708057AFB8V1\hana\MDC\H14'
Id   : 8025
StartTime   : 8/25/2020 3:49:10 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 1
ApisJobKey    :
ObjectId      : 0
PluginCode    : SCC
PluginName    : PluginCreator
HostId        : 0
RoleId        :
JobIds        : {}
```

Example 21: Oracle Tablespace point in time recovery (TSPITR)

```
Restore-SmBackup -PluginCode SCO -AppObjectId
'SLES11SP4NONE.gdl.englab.netapp.com\PITNASDB' -BackupId 65
-AuxiliaryDestination '/mnt/auxDest' -OracleTablespaces TS1
-OracleUntilScn 987450
```

This example syntax performs an Oracle point in time recovery for a tablespace using SCN.

```
Name: Restore 'SLES11SP4NONE.gdl.englab.netapp.com\PITNASDB'
Id : 208
StartTime : 9/11/2020 9:40:12 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : False
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
```

Example 22: Oracle Pluggable database point in time recovery

```
Restore-SmBackup -PluginCode SCO -AppObjectId
'SLES11SP4NONE.gdl.englab.netapp.com\PITNASDB' -BackupId 65
-AuxiliaryDestination '/mnt/auxDest' -OraclePluggableDatabases PDBUNQ
-OracleUntilScn 987450
```

This example syntax performs an Oracle point in time recovery for a Pluggable database(PDB) using SCN.

```
Name: Restore 'SLES11SP4NONE.gdl.englab.netapp.com\PITNASDB'
Id   : 209
StartTime   : 9/11/2020 10:40:12 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : False
IsScheduled    : False
PercentageCompleted : 0
Description    :
Status        : Queued
Owner         :
Error         :
Priority       : None
Tasks         : {}
ParentJobID   : 0
EventId       : 0
```

Example 23: Oracle point in time recovery for tablespace of a pluggable database (TSPITR)

```
Restore-SmBackup -PluginCode SCO -AppObjectId
'SLES11SP4NONE.gdl.englab.netapp.com\PITNASDB' -BackupId 65
-AuxiliaryDestination '/mnt/auxDest' -OracleTablespaces TS109
-OraclePluggableDatabases PDBUNQ --OracleUntilTime '2020-09-11 20:39:00'
```

This example syntax performs an Oracle point in time recovery for a tablespace belonging to a pluggable database(PDB) using time.

```
Name: Restore 'SLES11SP4NONE.gdl.englab.netapp.com\PITNASDB'
Id   : 210
StartTime   : 9/11/2020 10:40:12 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : False
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority     : None
Tasks       : {}
ParentJobID  : 0
EventId     : 0
```

Example 24: Oracle Tablespace point in time recovery (TSPITR) from secondary

```
Restore-SmBackup -PluginCode SCO -AppObjectId
'SLES11SP4NONE.gdl.englab.netapp.com\PITNASDB' -BackupId 65
-AuxiliaryDestination '/mnt/auxDest' -OracleTablespaces TS23
-OracleUntilScn 987450 -Archive @{Primary="svm1-scc2554-263-
264:R706221F756V1_NFS_DB_DB1_DATA";Secondary="hnkn_sec:R706221F756V1_NFS_D
B_DB1_DATA_dst"} -LogArchive @{Primary="svm1-scc2554-263-
264:R706221F756V1_NFS_DB_DB1_LOG";Secondary="hnkn_sec:R706221F756V1_NFS_DB
_DB1_LOG_mirror"}
```

This example syntax performs an Oracle point in time recovery for a tablespace using SCN from secondary.

```
Name: Restore 'SLES11SP4NONE.gdl.englab.netapp.com\PITNASDB'
Id   : 232
StartTime   : 9/11/2020 11:40:12 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : False
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
```

Example 25: Restoring from a primary backup for UnixFileSystems plug-in

```
PS C:\> Restore-SmBackup -PluginCode UnixFileSystems -AppObjectId
'linuxfs201.gdl.englab.netapp.com\UnixFileSystems\/netapp/VGNFS1/LVM1'
-BackupId 580 -Confirm:$false
```

This example syntax restores from a primary backup.

```

        Name: Restore
'linuxfs201.gdl.englab.netapp.com\UnixFileSystems\/netapp/VGNFS1/LVM1'
    Id      : 2772
    StartTime    : 12/12/2023 9:29:34 AM
    EndTime      :
    IsCancellable    : False
    IsRestartable    : False
    IsCompleted      : False
    IsVisible        : True
    IsScheduled      : False
    PercentageCompleted : 0
    Description      :
    Status           : Queued
    Owner            :
    Error            :
    Priority          : None
    Tasks            : {}
    ParentJobID      : 0
    EventId          : 0
    JobTypeId        : 1
    ApisJobKey        :
    ObjectId          : 0
    PluginCode        : SCC
    PluginName        : PluginCreator
    HostId           : 0
    RoleId           :
    JobIds           : {}
    ScsJobId         :

```

Example 26: Restoring from a secondary backup for UnixFileSystems plug-in

```

PS C:\> Restore-SmBackup -PluginCode UnixFileSystems -AppObjectId
'linuxfs201.gdl.englab.netapp.com\UnixFileSystems\/netapp/VGNFS1/LVM1'
-BuildId 580 -Confirm:$false -Archive
@{Primary="Dest_SVM:vol_source_dest";Secondary="Dest_SVM:vol_source_dest"}

```

This example syntax restores from a secondary backup.

```
Name: Restore
'linuxfs201.gdl.englab.netapp.com\UnixFileSystems\ /netapp/VGNFS1/LVM1 '
Id : 2783
StartTime : 12/12/2023 9:58:19 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 1
ApisJobKey :
ObjectId: 0
PluginCode : SCC
PluginName : PluginCreator
HostId : 0
RoleId :
JobIds : {}
ScsJobId:
```

Example 27: Trigger PostgreSQL cluster restore with all logs

```
Restore-SmBackup -PluginCode 'PostgreSQL' -AppObjectId
'shivarhel2.rtp.openenglab.netapp.com\PostgreSQL\postgres_5432'
-BackupName
'shivarhel2_rtp_openenglab_netapp_com_PostgreSQL_postgres_5432_shivarhel2_
06-26-2024_00_33_41_1570' -RecoveryType RecoverToMostRecentState
-Confirm:$false
```

This example syntax restores the given PostgreSQL cluster to the most recent state.


```

        Name: Restore
'shivarhel2.rtp.openenglab.netapp.com\PostgreSQL\postgres_5432'
        Id : 110
        StartTime : 6/27/2024 2:11:04 AM
        EndTime :
        IsCancellable : False
        IsRestartable : False
        IsCompleted : False
        IsVisible : True
        IsScheduled : False
        PercentageCompleted : 0
        Description :
        Status : Queued
        Owner :
        Error :
        Priority: None
        Tasks : {}
        ParentJobID : 0
        EventId : 0
        JobTypeId : 1
        ApisJobKey :
        ObjectId: 0
        PluginCode : SCC
        PluginName : PluginCreator
        HostId : 0
        RoleId :
        JobIds : {}
        ScsJobId:
        MaxJobsInQueue : 0
        JobTags :
        Tags: {}
        WaitForTags :
        ResourceId :
        QueueTimeoutMins: 0
        ProtectiongroupID :
        PolicyID:

```

Example 28: Restore the PostgreSQL resource to a specific date or time (Point in time restore)

```

Restore-SmBackup -PluginCode 'PostgreSQL' -AppObjectId
'shivarhel2.rtp.openenglab.netapp.com\PostgreSQL\postgres_5432' -BackupId
'70' -Confirm:$false -recoveruntiltime '2024-06-10T03:27:00' -recoverytype
RecoverUntilDateTime

```

Restore performed to a specific date or time on a PostgreSQL resource.

```
Name: Restore
'shivarhel2.rtp.openenglab.netapp.com\PostgreSQL\postgres_5432'
Id   : 111
StartTime   : 6/27/2024 2:15:35 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted   : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority: None
Tasks       : {}
ParentJobID  : 0
EventId      : 0
JobTypeId    : 1
ApisJobKey   :
ObjectId     : 0
PluginCode   : SCC
PluginName   : PluginCreator
HostId       : 0
RoleId       :
JobIds       : {}
ScsJobId     :
MaxJobsInQueue : 0
JobTags      :
Tags: {}
WaitForTags  :
ResourceId   :
QueueTimeoutMins: 0
ProtectiongroupID :
PolicyID:
```

Example 28: Trigger MySQL instance complete restore

```
Restore-SmBackup -PluginCode 'MySQL' -AppObjectId  
'scs000211748.gdl.englab.netapp.com\MySQL\mysqld_3306' -BackupName  
'scs000211748_gdl_englab_netapp_com_MySQL_mysqld_3306_scs000211748_06-26-  
2024_06.08.35.4307'
```

This example syntax restores the given MySQL Instance from the primary backup.

```
Name: Restore 'scs000211748.gdl.englab.netapp.com\MySQL\mysqld_3306'  
Id : 461  
StartTime : 6/28/2024 11:11:04 AM  
EndTime :  
IsCancellable : False  
IsRestartable : False  
IsCompleted : False  
IsVisible : True  
IsScheduled : False  
PercentageCompleted : 0  
Description :  
Status : Queued  
Owner :  
Error :  
Priority: None  
Tasks : {}  
ParentJobID : 0  
EventId : 0  
JobTypeId : 1  
ApisJobKey :  
ObjectId: 0  
PluginCode : SCC  
PluginName : PluginCreator  
HostId : 0  
RoleId :  
JobIds : {}  
ScsJobId:  
MaxJobsInQueue : 0  
JobTags :  
Tags: {}  
WaitForTags :  
ResourceId :  
QueueTimeoutMins: 0  
ProtectiongroupID :  
PolicyID:
```

Restore-SmRepositoryBackup

Restores the SnapCenter database.

Syntax

```
Restore-SmRepositoryBackup [-HostName] <String> [-SMSbaseUrl] <String>
[-BackupPath] <String> [-BackupName] <String> [-RestoreFileSystem] <>
```

Detailed Description

Restores the SnapCenter database.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Specifies the SnapCenter database host name. If the SnapCenter database is hosted by a failover cluster instance (FCI), then specify the FCI owner host name.	true	true (ByPropertyName)	
SMSbaseUrl	Specifies the SnapCenter Server URL. This URL is required when you are executing the PowerShell command from a database host.	false	true (ByPropertyName)	
BackupPath	Specifies the path where the SnapCenter repository is stored.	false	true (ByPropertyName)	
BackupName	Specifies the name of the backup to restore.	true	true (ByPropertyName)	
RestoreFileSystem	Specifies that the file system can be restored when backups are missing.	false	true (ByPropertyName)	

Examples

Example 1: Restoring a database backup

```
Restore-SmRepositoryBackup -BackupName MYSQL_DS_SC_Repository_mva-x3550-
s09_09-15-2016_10.32.00.4445
```

This example syntax restores the specified database backup.

You can retrieve `-BackupName` by using `Get-smRepositoryBackups`.

Restore-SmServerBackup

Restores an existing SnapCenter Server backup.

Syntax

```
Restore-SmServerBackup [-BackupPath] <String> [-BackupName] <String>
[-SkipSMSURLUpdateInHosts] <SwitchParameter>
```

Detailed Description

Restores an existing SnapCenter Server backup.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
BackupPath	Specify the path where the SnapCenter Server backup is stored.	true	true (ByPropertyName)	
BackupName	Specify the name of the SnapCenter Server backup that needs to be restored.	true	true (ByPropertyName)	
SkipSMSURLUpdateInHosts	Skip SnapCenter Server URL update in all hosts	false	false	

Examples

Example 1: Restoring a SnapCenter Server backup

```
Restore-SmServerBackup -BackupPath E:\Data -BackupName smhv-rx200-8.HNK2.COM_08-30-2023_19.34.55.0827
```

This example restores the SnapCenter Server backup from the specified path and updates the new SnapCenter URL in all the hosts.

```
Name: Restore SnapCenter Server backup
Id   : 60
StartTime   : 8/30/2023 8:24:19 PM
EndTime    : 8/30/2023 8:24:20 PM
IsCancellable   : False
IsRestartable   : False
IsCompleted    : False
IsVisible      : True
IsScheduled     : False
PercentageCompleted : 100
Description   :
Status       : Running
Owner        :
Error        :
Priority      : None
Tasks        : {Prepare for restore job}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 1
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    : NONE
HostId        : 0
RoleId        :
JobIds        : {}
ScsJobId      :
```

Example 2: Restoring a SnapCenter Server backup

```
Restore-SmServerBackup -BackupPath E:\Data -BackupName smhv-rx200-
8.HNK2.COM_08-30-2023_19.34.55.0827 -SkipSMSURLUpdateInHosts
```

This example restores the SnapCenter Server backup from the specified path and skips updating the new SnapCenter URL in all the hosts

```
Name: Restore SnapCenter Server backup
Id   : 60
StartTime   : 8/30/2023 8:24:19 PM
EndTime    : 8/30/2023 8:24:20 PM
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 100
Description :
Status   : Running
Owner    :
Error    :
Priority: None
Tasks    : {Prepare for restore job}
ParentJobID : 0
EventId  : 0
JobTypeId   : 1
ApisJobKey  :
ObjectId: 0
PluginCode  : NONE
PluginName  : NONE
HostId     : 0
RoleId     :
JobIds     : {}
ScsJobId:
```

Send-SmDataCollectionEms

Starts the EMS data collection process. This is primarily an internal cmdlet and generally should not be used by customers.

Syntax

```
Send-SmDataCollectionEms
```

Detailed Description

Starts the EMS data collection process. EMS data collection messages are sent by default on a weekly basis. You can use the Set-SmDataCollectionEmsSchedule cmdlet to change the default schedule. This is primarily an internal cmdlet and generally should not be used by customers.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	------------	----------------	---------------

Examples

Set-SmAuditSettings

Sets Audit configurations and Syslog configurations

Syntax

```
Set-SmAuditSettings [-MaxFileSize] <Int64> [-MaxSizeRollBackups]
<Int32> [-AuditLogDirectory] <String> [-UniversalTime] <Boolean> [-
AuditChecksumLogDirectory] <String> [-DiskSpaceLimitPercentage] <Int32>
[-EnableAuditIntegrityCheckSchedule] <Boolean> [-EnableSyslogServer]
<Boolean> [-SyslogServerHost] <String> [-SyslogServerPort] <Int32> [-
SyslogProtocol] <SyslogProtocols> [-SyslogFormat] <SyslogFormats>
```

Detailed Description

Sets below configurations Audit related configuration - Maximum File Size Maximum files to retain Audit Log file location Audit Log Checksum file location DiskSpaceLimitPercentage Option to Enable Audit Integrity Check Schedule Syslog server related configuration - Option to Enable Syslog Server Syslog Server Host Syslog Server Port Syslog Protocol Syslog Format

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
MaxFileSize	The maximum size in MB that the log file is allowed to reach before being rolled over to backup files.	true	false	
MaxSizeRollBackups	The number of roll over audit files that are retained.	true	false	
AuditLogDirectory	The location where audit files are generated.	true	false	
UniversalTime	Enables message logging in UTC time for installations in different geographical locations. Use \$True to enable UniversalTime or \$False to disable UniversalTime.	false	false	

Name	Description	Required ?	Pipeline Input	Default Value
AuditChecksumLog Directory	The location where audit checksum files are generated.	true	false	
DiskSpaceLimitPercentage	Disk space usage limit in percentage, after limit is reached alerts are raised.	true	false	
EnableAuditIntegrityCheckSchedule	To Enable scheduled audit integrity check. Possible values are \$True and \$False.	true	false	
EnableSyslogServer	Switch to Enable forwarding audit logs to syslog server.	true	false	
SyslogServerHost	Syslog server IP address or Server name.	false	false	
SyslogServerPort	Syslog server Port. Possible values can range between 0 - 65535.	false	false	
SyslogProtocol	Syslog server Protocol. Possible values are UDP, TCP and TLS12.	false	false	
SyslogFormat	Syslog server messages format. Possible values are Rfc5424 and Rfc3164.	false	false	

Examples

Example 1: Setting audit log and syslog server settings

```
Set-SmAuditSettings -MaxFileSize 50
-MaxSizeRollBackups 10
-AuditLogDirectory 'C:\Program Files\NetApp\SnapCenter WebApp\audit'
-AuditChecksumLogDirectory 'C:\Program Files\NetApp\SnapCenter
WebApp\auditChecksum'
-DiskSpaceLimitPercentage 80
-EnableAuditIntegrityCheckSchedule $False
-EnableSyslogServer
-SyslogServerHost 10.229.39.107
-SyslogServerPort 1468
-SyslogProtocol TCP
-SyslogFormat Rfc5424
```

This example sets audit log and syslog server settings.

```

MaxFileSize : 50
MaxSizeRollBackups : 10
UniversalTime : False
AuditLogDirectory : C:\Program Files\NetApp\SnapCenter WebApp\audit
AuditChecksumLogDirectory : C:\Program Files\NetApp\SnapCenter
WebApp\auditChecksum
DiskSpaceLimitPercentage : 80
EnableAuditIntegrityCheckSchedule : False
EnableSyslogServer : True
SyslogServerHost : 10.229.39.107
SyslogServerPort : 1468
SyslogProtocol : TCP
SyslogFormat : Rfc5424

```

Set-SmAuditSettings

Sets Audit configurations and Syslog configurations

Syntax

```

Set-SmAuditSettings [-MaxFileSize] <Int64> [-MaxSizeRollBackups]
<Int32> [-AuditLogDirectory] <String> [-UniversalTime] <Boolean> [-
AuditChecksumLogDirectory] <String> [-DiskSpaceLimitPercentage] <Int32>
[-EnableAuditIntegrityCheckSchedule] <Boolean> [-EnableSyslogServer]
<Boolean> [-SyslogServerHost] <String> [-SyslogServerPort] <Int32> [-
SyslogProtocol] <SyslogProtocols> [-SyslogFormat] <SyslogFormats>

```

Detailed Description

Sets below configurations Audit related configuration - Maximum File Size Maximum files to retain Audit Log file location Audit Log Checksum file location DiskSpaceLimitPercentage Option to Enable Audit Integrity Check Schedule Syslog server related configuration - Option to Enable Syslog Server Syslog Server Host Syslog Server Port Syslog Protocol Syslog Format

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
MaxFileSize	The maximum size in MB that the log file is allowed to reach before being rolled over to backup files.	true	false	
MaxSizeRollBackups	The number of roll over audit files that are retained.	true	false	

Name	Description	Required ?	Pipeline Input	Default Value
AuditLogDirectory	The location where audit files are generated.	true	false	
UniversalTime	Enables message logging in UTC time for installations in different geographical locations. Use \$True to enable UniversalTime or \$False to disable UniversalTime.	false	false	
AuditChecksumLog Directory	The location where audit checksum files are generated.	true	false	
DiskSpaceLimitPercentage	Disk space usage limit in percentage, after limit is reached alerts are raised.	true	false	
EnableAuditIntegrity CheckSchedule	To Enable scheduled audit integrity check. Possible values are \$True and \$False.	true	false	
EnableSyslogServer	Switch to Enable forwarding audit logs to syslog server.	true	false	
SyslogServerHost	Syslog server IP address or Server name.	false	false	
SyslogServerPort	Syslog server Port. Possible values can range between 0 - 65535.	false	false	
SyslogProtocol	Syslog server Protocol. Possible values are UDP, TCP and TLS12.	false	false	
SyslogFormat	Syslog server messages format. Possible values are Rfc5424 and Rfc3164.	false	false	

Examples

Example 1: Setting audit log and syslog server settings

```
Set-SmAuditSettings -MaxFileSize 50
-MaxSizeRollBackups 10
-AuditLogDirectory 'C:\Program Files\NetApp\SnapCenter WebApp\audit'
-AuditChecksumLogDirectory 'C:\Program Files\NetApp\SnapCenter
WebApp\auditChecksum'
-DiskSpaceLimitPercentage 80
-EnableAuditIntegrityCheckSchedule $False
-EnableSyslogServer
-SyslogServerHost 10.229.39.107
-SyslogServerPort 1468
-SyslogProtocol TCP
-SyslogFormat Rfc5424
```

This example sets audit log and syslog server settings.

```
MaxFileSize : 50
MaxSizeRollBackups : 10
UniversalTime : False
AuditLogDirectory : C:\Program Files\NetApp\SnapCenter WebApp\audit
AuditChecksumLogDirectory : C:\Program Files\NetApp\SnapCenter
WebApp\auditChecksum
DiskSpaceLimitPercentage : 80
EnableAuditIntegrityCheckSchedule : False
EnableSyslogServer : True
SyslogServerHost : 10.229.39.107
SyslogServerPort : 1468
SyslogProtocol : TCP
SyslogFormat : Rfc5424
```

Set-SmCertificateSettings

Enables you to modify the certificate settings for the SnapCenter Server host or a SnapCenter plug-in host.

Syntax

```
Set-SmCertificateSettings [-Server] <> [-Enable] <> [-Disable] <> [-
Host] <> [-HostName] <String> [-Enable] <> [-Disable] <>
```

Detailed Description

Enables you to modify the certificate settings for the SnapCenter Server host or a SnapCenter plug-in host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Server	Enables the Snapcenter server to perform SSL Secure validations.	true	false	
Host	Specifies that you want to perform SSL Secure validations on Snapcenter Host.	true	false	
HostName	Specifies the name of the host on which you want to perform SSL Secure validations.	true	false	
Enable	Specifies the Snapcenter server or host to enable SSL Secure validations.	true	false	
Disable	Specifies the Snapcenter server or host to disable SSL Secure validations.	true	false	

Examples

Example 1: Updating certificate settings for server

```
Set-SmCertificateSettings -Server -Enable
```

This example syntax sets certificate settings for server. Enables the server to perform SSL secure validations.

```
Name: Enabling certificate validation on server
      Id      : 51
      StartTime    : 3/12/2021 1:42:58 PM
      EndTime      : 3/12/2021 1:42:59 PM
      IsCancellable : False
      IsRestartable : False
      IsCompleted   : False
      IsVisible     : True
      IsScheduled   : False
      PercentageCompleted : 100
      Description   :
      Status        : Completed
      Owner         :
      Error         :
      Priority       : None
      Tasks         : {}
      ParentJobID   : 0
      EventId       : 0
      JobTypeId     : 38
      ApisJobKey    :
      ObjectId      : 0
      PluginCode    : NONE
      PluginName    : NONE
      HostId        : 0
      RoleId        :
      JobIds        : {}
```

Example 2: Updating certificate settings for Host

```
Set-SmCertificateSettings -Host -HostName
R71104B320CV1.mva.gdl.englab.netapp.com -Enable
```

This example syntax sets certificate settings for host. Enables the host to perform SSL secure validations.

Name: Enabling certificate validation on Host
R71104B320CV1.mva.gdl.englab.netapp.com

Id : 52
StartTime : 3/12/2021 1:47:06 PM
EndTime : 3/12/2021 1:47:13 PM
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 100
Description :
Status : Completed
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 38
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName : NONE
HostId : 0
RoleId :
JobIds : {}

Set-SmCloneDataSet

Modifies an existing clone dataset.

Syntax

```
Set-SmCloneDataSet [-DataSetName] <String> [-Description] <String> [-  
Policies] <String> [-PluginCode] <PluginCode> [-CloneToInstance]  
<String> [-Resources] <Hashtable[]> [-Suffix] <String> [-  
SchedulerCredentialName] <String> [-ArchivedLocators] <Hashtable[]> [-  
EnableEmail] <> [-EmailPreference] <SmEmailNotificationPreference> [-  
EmailFrom] <String> [-EmailTo] <String> [-EmailSubject] <String> [-  
EmailBody] <String> [-CustomSnapshotFormat] <String> [-CustomText]  
<String> [-RemoveCustomSnapshot] <>
```

Detailed Description

Modifies an existing clone dataset.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
DataSetName	Specifies the name of the clone dataset you want to modify.	true	true (ByPropertyName)	
Description	Modifies the optional description of the clone dataset.	false	true (ByPropertyName)	
Policies	Modifies which policies are attached to the clone dataset.	false	true (ByPropertyName)	
PluginCode		true	true (ByPropertyName)	
CloneToInstance	Changes the SQL Server instance that you want to clone to. All databases in the clone dataset are cloned to this instance.	true	true (ByPropertyName)	
Resources	Modifies the list of resources you want to add to the clone dataset. You must provide the resource information in a hashtable, and it must contain the resource name and type, and the host on which it is located. For example, @{"Host"="localhost";"Type"="SQL Database";"Names"="Instance\Database"} Valid Type values are: SQL Database, SQL Instance, SQL Availability Group. You can include comma-separated values for Names.	true	true (ByPropertyName)	
Suffix	Modifies a clone name suffix. All clones you create with one clone job are appended with the same suffix name.	false	true (ByPropertyName)	
SchedulerCredential Name		false	true (ByPropertyName)	
ArchivedLocators		false	true (ByPropertyName)	
EnableEmail	Specifies whether to enable or disable e-mail.	false	false	

Name	Description	Required ?	Pipeline Input	Default Value
EmailPreference	Specifies when you will receive e-mail notifications. Possible values: Always, Never, OnError, OnErrorOrWarning.	false	false	
EmailFrom	Specifies the sender's e-mail address.	false	true (ByPropertyName)	
EmailTo	Specifies the recipient's e-mail address.	false	true (ByPropertyName)	
EmailSubject	Specifies the subject of the e-mail.	false	true (ByPropertyName)	
EmailBody	Specifies the body of the e-mail.	false	true (ByPropertyName)	
CustomSnapshotFormat	Specifies the custom Snapshot copy naming format.	false	true (ByPropertyName)	
CustomText	Specifies the custom text in the custom Snapshot copy naming format.	false	true (ByPropertyName)	
RemoveCustomSnapshot	Specifies the removal of the custom Snapshot copy naming format associated with the dataset.	false	true (ByPropertyName)	

Examples

Example 1: Modifying a clone dataset with a new suffix

```
Set-SmCloneDataSet -DataSetName payroll_dataset -Resources
@{"Host"="vise-f3.sddev.mycompany.com";"Type"="SQLDatabases";"Names"="vise-f3\SQLExpress\payroll"} -CloneToInstance vise-f4\sqlexpress -Suffix __
newSuffix
```

This example syntax modifies a clone dataset by adding a new suffix.

Description :
CreationTime: 8/6/2015 2:27:08 PM
ModificationTime: 8/6/2015 2:27:08 PM
EnableEmail :
EmailSMTPServer :
EmailFrom :
EmailTo :
EmailSubject:
EnableSysLog: False
ProtectionGroupType : Clone
EnableAsupOnFailure : False
Policies: {}
HostResourceMapping : {}
Configuration : SMCoreContracts.SmCloneConfiguration
LastBackupStatus:
VerificationServer :
EmailBody :
EmailNotificationPreference :
VerificationServerInfo :
SchedulerSQLInstance:
CustomText :
CustomSnapshotFormat:
SearchResources : False
ByPassRunAs : False
IsCustomSnapshot:
MaintenanceStatus : Production
PluginProtectionGroupTypes :
Name: payroll_dataset
Type: Group
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0

Example 2: Modifying a clone dataset

```
Set-SmCloneDataSet -DataSetName payroll_dataset -Resources
@{"Host"="vise-
f3.sddev.mycompany.com";"Type"="SQLDatabases";"Names"="vise-
f3\SQLExpress\payroll,vise-f3\SQLExpress\edrive"} -CloneToInstance vise-
f3\sqlexpress
```

This example syntax modifies a clone dataset

```
Description :
CreationTime: 8/6/2015 3:06:25 PM
ModificationTime: 8/6/2015 3:06:25 PM
EnableEmail :
EmailSMTPServer :
EmailFrom :
EmailTo :
EmailSubject:
EnableSysLog: False
ProtectionGroupType : Clone
EnableAsupOnFailure : False
Policies: {}
HostResourceMapping : {}
Configuration : SMCoreContracts.SmCloneConfiguration
LastBackupStatus:
VerificationServer :
EmailBody :
EmailNotificationPreference :
VerificationServerInfo :
SchedulerSQLInstance:
CustomText :
CustomSnapshotFormat:
SearchResources : False
ByPassRunAs : False
IsCustomSnapshot:
MaintenanceStatus : Production
PluginProtectionGroupTypes :
Name: payroll_dataset
Type: Group
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Set-SmCloneJob

Modifies an existing clone job.

Syntax

```
Set-SmCloneJob [-CloneJobName] <String> [-PluginCode] <PluginCode> [-CloneToInstance] <String> [-CloneToHost] <String> [-Description] <String> [-ResourceGroupName] <String> [-Resources] <Hashtable[]> [-EnableAsupOnFailure] <Boolean> [-EnableSysLog] <Boolean> [-EnableEmail] <> [-EmailPreference] <SmEmailNotificationPreference>
```

Detailed Description

Modifies an existing clone job based on the parameters provided.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
CloneJobName		true	true (ByPropertyName)	
PluginCode		true	true (ByPropertyName)	
CloneToInstance		true	true (ByPropertyName)	
CloneToHost		true	true (ByPropertyName)	
Description		false	true (ByPropertyName)	
ResourceGroupName		false	true (ByPropertyName)	
Resources		false	true (ByPropertyName)	
EnableAsupOnFailure		false	true (ByPropertyName)	
EnableSysLog		false	true (ByPropertyName)	
EnableEmail		false	false	
EmailPreference		false	false	
AutoAssignMountPoint		false	true (ByPropertyName)	
AssignMountPointUnderPath		false	true (ByPropertyName)	
CloneType		false	true (ByPropertyName)	
Suffix		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ArchivedLocators		false	true (ByPropertyName)	
CustomSnapshotFormat		false	true (ByPropertyName)	
CustomText		false	true (ByPropertyName)	
SchedulerCredentialName		false	true (ByPropertyName)	
Schedules		false	true (ByPropertyName)	
SchedulerType		false	true (ByPropertyName)	
SchedulerInstance		false	true (ByPropertyName)	
DeleteCloneOnScheduleExpiry		false	true (ByPropertyName)	
PreScriptCommand		false	true (ByPropertyName)	
PreScriptArguments		false	true (ByPropertyName)	
PostScriptCommand		false	true (ByPropertyName)	
PostScriptArguments		false	true (ByPropertyName)	
ScriptTimeOut		false	true (ByPropertyName)	
EmailBody		false	true (ByPropertyName)	
EmailFrom		true	true (ByPropertyName)	
EmailTo		true	true (ByPropertyName)	
EmailSubject		true	true (ByPropertyName)	
EnableEmailAttachment		false	true (ByPropertyName)	

Examples

- Example 1: Modifying a clone job to add a suffix. -

```
Set-SmCloneJob -ResourceGroupName RG1 -CloneJobName CLMJob -PluginCode
SCSQL -CloneToInstance R708202074BV1\SQL2019 -CloneToHost
R708202074BV1.hnk2.com -Suffix _clone_001
```

This example syntax modifies a clone job by adding a new suffix.

```
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Name: Clone life cycle of Resource Group 'CLMJob' with policy
'CLMJob_ClonePolicy'
Id           : 151
StartTime    : 8/25/2020 6:14:05 AM
EndTime      :
IsCancellable : False
IsRestartable : False
IsCompleted   : False
IsVisible     : True
IsScheduled   : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 8
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    : NONE
HostId       : 0
RoleId       :
JobIds        : {}
```

- Example 2: Modifying a clone job -

```
Set-SmCloneJob -ResourceGroupName RG1 -CloneJobName CLMJob -PluginCode
SCSQL -CloneToInstance
R708202074BV1\SQL2019 -CloneToHost R708202074BV1.hnk2.com
-AssignMountPointUnderPath 'C:\work' -Suffix _clone_001
```

This example syntax modifies a clone job.

```
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
Name: Clone life cycle of Resource Group 'CLMJob' with policy
'CLMJob_ClonePolicy'
Id           : 157
StartTime    : 8/25/2020 6:17:34 AM
EndTime      :
IsCancellable : False
IsRestartable : False
IsCompleted   : False
IsVisible     : True
IsScheduled   : False
PercentageCompleted : 0
Description   :
Status       : Queued
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 8
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    : NONE
HostId        : 0
RoleId        :
JobIds        : {}
```

Set-SmConfigSettings

Enables you to modify the configuration settings for the SnapCenter Server host or a SnapCenter plug-in host.

Syntax

```
Set-SmConfigSettings [-Server] <> [-configSettings] <Hashtable> [-Agent] <> [-HostName] <String> [-configSettings] <Hashtable> [-Plugin] <> [-HostName] <String> [-PluginCode] <PluginCode> [-configSettings] <Hashtable>
```

Detailed Description

Enables you to modify the configuration settings for the SnapCenter Server host or a SnapCenter plug-in host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Server	Modifies the configuration values for the server on which SnapCenter is installed.	true	false	
configSettings	Specifies in a hash table the configuration settings you want to modify.	true	false	
Agent	Specifies that you want to modify configuration values for the SMCore agent.	true	false	
HostName	Specifies the name of the host on which you want to modify configuration settings.	true	false	
Plugin	Specifies that you want to modify the configuration information of the plug-in host.	true	false	
PluginCode	Specifies the plug-in code for the plug-in host for which you are modifying configuration settings.	true	false	

Examples

Example 1: Modifying multiple configuration settings for a custom plugin

```
Set-SmConfigSettings -Agent -HostName SNAPCENTER113.sccore.test.com  
-configSettings @{"SERVER_API_TIMEOUT_IN_SEC"="300";"ALLOWED_CMDS"="mount  
*; unmount *"}>
```

This example syntax sets 2 configuration settings key-values for a custom plug-in.

Name Value

SERVER_API_TIMEOUT_IN_SEC 300

ALLOWED_CMDS mount *; unmount *

Example 2: Modifying a single configuration setting on the SnapCenter Server

```
Set-SmConfigSettings -Server -configSettings  
@{"WindowsRemoteInstallProcessTimeout"="900"}
```

This example syntax modifies the specified configuration setting on the SnapCenter Server.

Name Value

WindowsRemoteInstallProcess... 900

Example 3: Setting the chunk size for which files are grouped for a directory restore from primary storage

```
Set-SmConfigSettings -Server -configSettings  
@{"PrimaryRestoreFileChunkSize"="500";}
```

This example syntax specifies the file chunk size to restore from primary storage. The default primary restore chunk is 500. You can increase or decrease the chunk size, but the size must be greater than 0.

Example 4: Setting the chunk size for which files are grouped for a directory restore from secondary storage

```
Set-SmConfigSettings -Server -configSettings @{"  
SecondaryRestoreFileChunkSize "="8";}
```

This example syntax specifies the file chunk size to restore from secondary storage. The default secondary restore chunk is 8. You can increase or decrease the chunk size, but the size must be greater than 0.

Example 5: Setting a custom port

```
Set-SmConfigSettings -Agent -configSettings @{"PORT"="8174"} -HostName  
SNAPCENTER113.sscore.test.com
```

This example syntax specifies the custom port number for the SMCore agent as 8174.

Name Value

PORT 8174

Example 6: Setting load sharing mirror retry

```
Set-SmConfigSettings -Agent -configSettings @{"lsmsleep"="9997"}  
-HostName localhost
```

This example syntax sets the load sharing mirror retry time to 9997 milliseconds to enable load sharing mirrors to finish updating before retrying mount or restore operations.

Name Value

lsmsleep 9997

Example 7: Setting the access method of SQL log backups for reseed and restore operations of availability group database

```
Set-SmConfigSettings -Server -configSettings  
@{"ReseedLogBackupMount"="true"}
```

The example syntax sets the log backup's access as mount and copy for restore and reseed operations of availability group database. Setting the flag to true indicates that the SQL availability group database reseed and restore operations should mount the log backups on the target host rather than accessing them as a network share.

The default value is "false".

Set-SmCredential

Modify a credential registered with the SnapCenter Server.

Syntax

```
Set-SmCredential [-Name] <String> [-Type] <SmAuthMode> [-ClientSecret]  
<SecureString> [-TenantId] <String> [-ClientId] <String> [-  
InstanceName] <String> [-Force] <> [-Credential] <PSCredential>
```

Detailed Description

Modify a credential registered with the SnapCenter Server. It could be for other plug-ins or for other NetApp cloud storage.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the Credential Account.	true	true (ByPropertyName)	
Type	Specifies the authentication mode.	true	true (ByPropertyName)	
ClientSecret	Specifies the Azure NetApp client secret.	false	true (ByPropertyName)	
TenantId	Specifies the Azure NetApp tenant ID.	false	true (ByPropertyName)	
ClientId	Specifies the Azure NetApp client ID.	false	true (ByPropertyName)	
InstanceName		false	true (ByPropertyName)	
Force		false	true (ByPropertyName)	
Credential		true	true (ByPropertyName)	

Examples

Example 1: Set Azure Credential

```
Set-SmCredential -Name azure -Type AzureCredential -ClientSecret
99634c34-6d2a-9jfb-a47b-0jhg9710037d -TenantId 25434c84-982a-9jfb-a47b-
0h6f97076037d -ClientId 87dg98hg-6e2a-498b-m33b-0p2a97134756
```

Example 2: Modify AIX Credential

```
Set-SmCredential -Name 'RunAs1' -CredentialType 'AIX'
```

Example 3: Modify Authentication Type for Linux Credential

```
Set-SmCredential -Name LinuxPasswordBasedRunAs -Type Linux
-AuthenticationType SshKeyBased -Username scanf -SSHPrivateKeyPath
"C:\Users\Administrator\passwordfile.txt"
```

Set-SmDataCollectionEmsSchedule

Sets your EMS data collection schedule.

Syntax

```
Set-SmDataCollectionEmsSchedule [-CredentialName] <String> [-  
DaysInterval] <Int16> [-StartDateTime] <DateTime>
```

Detailed Description

Sets your EMS data collection schedule. When scheduling EMS data collection you must configure a Run As account. You can configure the start date and time, as well as the frequency of the EMS data collection.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
CredentialName		true	false	
DaysInterval	Specifies the frequency with which you want to run EMS data collection, in days. The default is every 7 days.	true	false	
StartDateTime	Specifies the date and time you want to start EMS data collection. For example, -StartDateTime "6/20/2015 1:00 AM"	false	false	

Examples

Example 1: Configuring the EMS data collection schedule

```
Set-SmDataCollectionEmsSchedule -DaysInterval 14 -RunAs runas_name  
-StartDateTime "6/20/2015 1:00 AM"
```

This example syntax configures your EMS data collection schedule to run every two weeks, starting on June 20th at 1:00 am, and provides a valid Run As account name.

Set-SmDataCollectionEmsTarget

Specifies the target storage system to which you want to send your EMS data collection messages.

Syntax

```
Set-SmDataCollectionEmsTarget [-Target] <String>
```

Detailed Description

Specifies the target storage system to which you want to send your EMS data collection messages. You are not required to set up the EMS data collection target storage system. If you omit the EMS data collection target, SnapCenter sends the EMS storage collection messages to the first in your list of storage system connections, and retries subsequent connections upon failure.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Target	Specifies your target storage system name. If you need to identify the storage system name, run Get-SmStorageConnection to view a list of storage system names.	true	false	

Examples

Example 1: Setting the EMS data collection target storage system

```
Set-SmDataCollectionEmsTarget -Target SVM1
```

This example syntax sets the target storage system to which you want to send your EMS data collection messages.

Target

SVM1

Set-SmDatasetMaintenance

Sets a dataset to maintenance or production mode.

Syntax

```
Set-SmDatasetMaintenance [-DatasetName] <String> [-MaintenanceStatus]  
<SmMaintenanceStatus>
```

Detailed Description

Sets a dataset to maintenance or production mode. No scheduled jobs are executed for a dataset in maintenance mode.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
DatasetName	The dataset name.	true	true (ByPropertyName)	
MaintenanceStatus	The maintenance status of the dataset. The maintenance status is Production or UnderMaintenance.	true	true (ByPropertyName)	

Examples

Example 1: Setting a dataset to production mode

```
Set-SmDatasetMaintenance -DatasetName Payroll_Dataset -MaintenanceStatus  
Production
```

This example syntax set the specified dataset to production mode.

Set-SmDisasterRecovery

Enables storage disaster recovery.

Syntax

```
Set-SmDisasterRecovery [-Enable] <> [-Disable] <>
```

Detailed Description

Enables or disables storage disaster recovery.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Enable	Specifies the SnapCenter Server to enable storage disaster recovery.	true	false	
Disable	Specifies the SnapCenter Server to disable storage disaster recovery.	true	false	

Examples

Example 1: Enabling storage disaster recovery

```
Set-SmDisasterRecovery -Enable
```

This example syntax enables storage disaster recovery.

```
Set-SmDisasterRecovery
Before enabling this option, make sure all the SCSQL resources are online
and active on the secondary storage.Are you sure you want to enable
disaster recovery??
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help
(default is "Y"):
Name:
Id   : 1971
StartTime   :
EndTime   :
IsCancellable   : False
IsRestartable   : False
IsCompleted   : False
IsVisible   : True
IsScheduled   : False
PercentageCompleted   : 0
Description   :
Status   : Running
Owner   :
Error   :
Priority: None
Tasks   : {}
ParentJobID   : 0
EventId   : 0
JobTypeId   :
ApisJobKey   :
ObjectId: 0
PluginCode   : NONE
PluginName   :
HostId   : 0
RoleId   :
JobIds   :
    ErrorRecords   : {}
_message   :
_errorCode   : 0
```


Example 2: Disabling storage disaster recovery

```
Set-SmDisasterRecovery -Disable
```

This example syntax disables storage disaster recovery.

Name:

```
Id      : 1970
StartTime :
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible    : True
IsScheduled  : False
PercentageCompleted : 0
Description :
Status      : Running
Owner       :
Error       :
Priority     : None
Tasks       : {}
ParentJobID : 0
EventId     : 0
JobTypeId   :
ApisJobKey   :
ObjectId     : 0
PluginCode   : NONE
PluginName   :
HostId       : 0
RoleId       :
JobIds       :
ErrorRecords : {}
_message    :
_errorCode   : 0
```

Set-SmDomain

Modify a domain registered with SnapCenter Server.

Syntax

```
Set-SmDomain [-Name] <String> [-Protocol] <String> [-FQDN] <String>
[-IPAddresses] <String> [-DCHostNames] <String> [-Credential]
<PSCredential>
```

Detailed Description

Modify a domain registered with SnapCenter Server.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	NETBIOS name of the registered domain to be modified.	true	true (ByPropertyName)	
Protocol	Protocol of the domain to be modified.By default the protocol value is LDAP. You can specify LDAPS to use the secured windows active directory communication.	false	true (ByPropertyName)	
FQDN	FQDN of the domain to be modified.Used for both LDAP and LDAPS protocol, when you provide the correct FQDN while adding or modifying the domain with LDAP protocol, the domain resolves and the IP address that you might have entered using the IPAddresses parameter is not stored.	false	true (ByPropertyName)	
IPAddresses	Domain IP Addresses of the disjoint domain to be modified.When you provide the correct FQDN while adding or modifying the domain, the domain resolves and the IP address is not stored.	false	true (ByPropertyName)	
DCHostNames	Domain host name of the disjoint or the same domain to be modified.For LDAPS protocol, DCHostNames is a mandatory parameter. The IP address should resolve and the user should not be permitted to manually provide the IP address.	false	true (ByPropertyName)	
Credential	Provides local workgorup administrator credentials to execute a Set-SmDomain cmdlet.This is an optional parameter only can exercise if Open-SmConnection is broken due to Active Directory connectivity using LDAPS protocol.	false	true (ByPropertyName)	

Examples

Example 1: Modify a domain registered with SnapCenter Server.

```
Set-SmDomain -Name ad12 -FQDN ad12.test.netapp.com -IPAddresses  
192.168.0.44
```

```
Modified the domain ad12.  
Id : 0  
Name : ad12  
DomainFQDN : ad12.test.netapp.com  
DCHostIPAddresses : 192.168.0.44  
TrustedDomains :  
CreatedOn :  
ModifiedOn :  
Port : 389  
Protocol : LDAP  
DCHostNames:
```

Example 2: Modifying a registered domain protocol from LDAP to LDAPS.

```
Set-SmDomain -Name ad12 -DCHostNames WS2K12DC.ad12.test.netapp.com  
-Protocol LDAPS
```

```
Modified the domain ad12.  
Id : 0  
Name : ad12  
DomainFQDN : ad12.test.netapp.com  
DCHostIPAddresses : 192.168.0.44  
TrustedDomains :  
CreatedOn :  
ModifiedOn :  
Port : 636  
Protocol : LDAPS  
DCHostNames: WS2K12DC.ad12.test.netapp.com
```

Example 3: Modifying a registered domain protocol from LDAPS to LDAP.

```
Set-SmDomain -Name ad12
```

```
Modified the domain ad12.
Id : 0
Name : ad12
DomainFQDN : ad12.test.netapp.com
DCHostIPAddresses :
TrustedDomains :
CreatedOn :
ModifiedOn :
Port : 389
Protocol : LDAP
DCHostNames:
```

Example 4: Execute Set-SmDomain when Open-SmConnection is broken due to Active directory.

```
Set-SmDomain -Name ad12 -FQDN ad12.test.netapp.com -Credential
administrator
```

```
Modified the domain ad12.
Id : 0
Name : ad12
DomainFQDN : ad12.test.netapp.com
DCHostIPAddresses :
TrustedDomains :
CreatedOn :
ModifiedOn :
Port : 389
Protocol : LDAP
DCHostNames:
```

Set-SmDownloadRepository

Modifies the location of the installation package download repository.

Syntax

```
Set-SmDownloadRepository [-Path] <String>
```

Detailed Description

Modifies the location of the installation package download repository.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Path	New plug-in repository path.	true	true (ByPropertyName)	

Examples

Example 1: Modifying the installation download repository location

```
Set-SmDownloadRepository -Path "c:\inetpub\wwroot\SnapCenter\Repository"
```

This example syntax specifies a new repository location.

Set-SmESXInfo

Updates the parent ESX information for SQL hosts.

Syntax

```
Set-SmESXInfo [-HostName] <String>
```

Detailed Description

Updates the parent ESX information for SQL hosts. The host must be of SQL type.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	The name of the SQL host.	true	true (ByPropertyName)	

Examples

Example 1: Updating the parent ESX information for an SQL host

```
Set-SmESXInfo -HostName csmdev-smsql-02.sddev.mycompany.com -Verbose
```

This example syntax updates the parent ESX information for the specified SQL host.

```
VERBOSE: Start Set-SmESXInfo  
ESX information updated successfully
```

VERBOSE: Set-SmESXInfo ended successfully.

Set-SmHost

Modifies either the port or the group Managed Service Account (gMSA) or the credential name of the host.

Syntax

```
Set-SmHost [-HostName] <String> [-Port] <UInt16> [-CredentialName]
<String> [-UseGMSA] <Boolean> [-GMSAName] <String> [-
PushServerCredentialsToSCV] <SwitchParameter> [-Force]
<SwitchParameter>
```

Detailed Description

Modifies either the port or the group Managed Service Account (gMSA) or the credential name of the host. Only one parameter can be modified at a time.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	The name of the host whose port or credential name will be modified.	true	true (ByPropertyName)	
Port	The port to be modified.	false	true (ByPropertyName)	
CredentialName	The credential name to be modified.	false	true (ByPropertyName)	
UseGMSA	Modify the plug-in services logon from gMSA to domain or LocalSystem.	false	true (ByPropertyName)	
GMSAName	The group Managed Service Account (gMSA) name to be modified.	false	true (ByPropertyName)	
PushServerCredentialsToSCV	Push the credentials to the SCV host.	false	true (ByPropertyName)	
Force		false	true (ByPropertyName)	

Examples

Example 1: Modifying port from 8145 to 8185

```
Set-SmHost -HostName h1 -Port 8185
```

This example modifies the port of host h1 to 8185.

Example 2: Modifying credential name from RunAs1 to RunAs2

```
Set-SmHost -HostName h1 -CredentialName RunAs2
```

This example modifies the credential name of host h1 to RunAs2.

Example 3: Modifying group Managed Service Account (gMSA) name from NewDomain\gMSAName1\$ to NewDomain\gMSAName2\$

```
Set-SmHost -HostName h1.NewDomain.com -UseGMSA:$true -GMSAName  
NewDomain\gMSAName2$
```

This example modifies the gMSA name for host h1.NewDomain.com to NewDomain\gMSAName2\$.

Example 4: Disabling group Managed Service Account (gMSA)

```
Set-SmHost -HostName h1.NewDomain.com -UseGMSA:$false
```

This example disables the gMSA and modifies the plug-in services to Domain or LocalSystem for host h1.NewDomain.com.

Set-SmLogSettings

Sets the log file retention for SnapCenter, hosts, and plug-ins.

Syntax

```
Set-SmLogSettings [-Server] <> [-MaxFileSize] <Int64> [-  
MaxSizeRollBackups] <Int32> [-JobLogsMaxFileSize] <Int64> [-LogLevel]  
<LogLevel> [-UniversalTime] <Boolean> [-Agent] <> [-HostName]  
<String> [-MaxFileSize] <Int64> [-MaxSizeRollBackups] <Int32> [-  
JobLogsMaxFileSize] <Int64> [-LogLevel] <LogLevel> [-UniversalTime]  
<Boolean> [-Plugin] <> [-HostName] <String> [-PluginCode]  
<PluginCode> [-MaxFileSize] <Int64> [-MaxSizeRollBackups] <Int32> [-  
JobLogsMaxFileSize] <Int64> [-LogLevel] <LogLevel> [-UniversalTime]  
<Boolean>
```

Detailed Description

Sets the log file retention for SnapCenter, hosts, and plug-ins. Log file settings govern log severity level, the maximum log file size, the maximum number of log file backups to retain, and the maximum size for all the job log files.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Server	Indicates that you want to create log settings for the SnapCenter server.	true	false	
MaxFileSize	The log file size that triggers a roll over.	true	false	
MaxSizeRollBackups	The number of roll over log files that are retained.	true	false	
JobLogsMaxFileSize	Specifies the maximum file size of all job log files. Job logs are created on an individual job basis. JobLogsMaxFileSize specifies the total size for all job log files. When job log files exceed the maximum size, the oldest files are deleted.	true	false	
LogLevel	Sets the log severity level. Valid values are: all, debug, info, warn, error, fatal, or off.	true	false	
UniversalTime	Enables message logging in UTC time for installations in different geological locations. Use \$True to enable UniversalTime or \$False to disable UniversalTime.	false	false	
Agent	Indicates the SnapCenter agent on which you want to create the log settings. Possible values are -server, -host, or -plugin.	true	false	
HostName	Specifies the host name on which the log files are created. The host should be part of the SnapCenter managed host list and the host is required when you want to create log settings for the SnapCenter host agent or plug-ins.	true	false	
Plugin	Indicates that you want to specify log file settings for a plug-in host.	true	false	

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode	Indicates the plug-in code for the plug-in host on which you want to specify log settings. Valid plug-in values are SCSQL, SCO, SCV.	true	false	

Examples

Example 1: Setting SnapCenter server log settings

```
Set-SmLogSettings -JobLogsMaxFileSize 100MB -LogLevel All -MaxFileSize 10MB -MaxSizeRollBackups 10 -Server
```

This example syntax sets SnapCenter server log settings.

```
LogSettingsId : 1
LogSettingsType: Server
LogLevel      : All
MaxFileSize   : 10485760
MaxSizeRollBackups : 10
JobLogsMaxFileSize : 104857600
HostId        :
HostName      :
PluginInfoId   :
PluginCode     : NONE
```

Example 2: Setting plugin log settings

```
Set-SmLogSettings -Plugin -PluginCode SMSQL -HostName host123
-JobLogsMaxFileSize 100MB -LogLevel Info -MaxFileSize 10MB
-MaxSizeRollBackups 10
```

This example syntax sets plug-in log settings.

```
LogSettingsId : 1
LogSettingsType: Plugin
LogLevel      : Info
MaxFileSize: 10485760
MaxSizeRollBackups : 10
JobLogsMaxFileSize : 104857600
HostId :
HostName      :
PluginInfoId  :
PluginCode    : SMSQL
```

Example 3: Setting SnapCenter host agent log settings

```
Set-SmLogSettings -Agent -HostName bryankDev -JobLogsMaxFileSize 100MB
-LogLevel Info -MaxFileSize 10MB -MaxSizeRollBackups 10
```

This example syntax sets plug-in log settings.

```
LogSettingsId : 1
LogSettingsType: Agent
LogLevel      : Info
MaxFileSize: 10485760
MaxSizeRollBackups : 10
JobLogsMaxFileSize : 104857600
HostId :
HostName      :
PluginInfoId  :
PluginCode    : NONE
```

Example 4: Setting log messaging to UTC time

```
Set-SmLogSettings -Agent -HostName <plugin-hostname> -JobLogsMaxFileSize
10MB -LogLevel Debug -MaxFileSize 10MB -MaxSizeRollBackups 10
-UniversalTime $True
```

This example syntax sets log messaging to Universal time.

Set-SmMaintenanceMode

Sets a host to maintenance or production mode.

Syntax

```
Set-SmMaintenanceMode [-HostNames] <String> [-MaintenanceStatus]
<SmMaintenanceStatus>
```

Detailed Description

Sets a host to maintenance or production mode. No scheduled jobs are executed for a host in maintenance mode.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostNames	The names of the hosts for which you want to change the maintenance mode.	true	true (ByPropertyName)	
MaintenanceStatus	Specifies the maintenance status of the specified hosts. The maintenance status is Production or UnderMaintenance.	true	true (ByPropertyName)	

Examples

Example 1: Setting a host to production mode

```
Set-SmMaintenanceMode -HostNames @("SQL_Host") -MaintenanceStatus
Production
```

This example syntax sets the specified host to production mode.

Example 2: Setting multiple hosts to maintenance mode

```
Set-SmMaintenanceMode -HostNames @("SQL_Host", "Verification_Host")
-MaintenanceStatus UnderMaintenance
```

This example syntax sets the specified hosts to maintenance mode.

Set-SmMultiFactorAuthentication

To Enable or disable the MFA feature or to configure the MFA for the SnapCenter GUI, Rest API, PowerShell and sccli.

Syntax

```
Set-SmMultiFactorAuthentication [-IsGuiMFAEnabled] <> [-IsRestApiMFAEnabled ] <> [-IsCliMFAEnabled ] <> [-Path] <> [-Path] <> [-IsGuiMFAEnabled] <> [-IsRestApiMFAEnabled ] <> [-IsCliMFAEnabled ] <>
```

Detailed Description

To enable or disable the MFA feature or to configure the MFA for the SnapCenter GUI, Rest API, PowerShell and sccli.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
IsGuiMFAEnabled	Specifies the SnapCenter Server to enable or disable MFA for the SnapCenter GUI.	false	false	
IsRestApiMFAEnabled	Specifies the SnapCenter Server to enable or disable MFA for the SnapCenter Rest API.	false	false	
IsCliMFAEnabled	Specifies the SnapCenter Server to enable or disable MFA for the SnapCenter PowerShell and sccli.	false	false	
Path	Configure the MFA for the SnapCenter Server login with specified AD FS metadata file path.	false	false	

Examples

Example 1: Enabling MultiFactorAuthentication for GUI, Rest API, PowerShell and sccli

```
Set-SmMultiFactorAuthentication -IsGuiMFAEnabled $true  
-IsRestApiMFAEnabled $true -IsCliMFAEnabled $true -Path  
C:\ADFS_metadata\FederationMetadata.xml
```

This example syntax enables MFA for SnapCenter GUI, Rest API, PowerShell and sccli configured with specified AD FS metadata file path.

IsGuiMFAEnabled = True

ADFSConfigFilePath = C:\ADFS_metadata\FederationMetadata.xml

SCConfigFilePath = c:\ProgramData\NetApp\SnapCenter\Package Repository\SnapCenterMFAMetadata.xml

IsRestApiMFAEnabled = True

IsCliMFAEnabled = True

ADFSHostName = adfs19.ad19domain.com

Example 2: Disabling MultiFactorAuthentication for SnapCenter GUI

```
Set-SmMultiFactorAuthentication -IsGuiMFAEnabled $false
```

This example syntax disables MFA for SnapCenter GUI.

IsGuiMFAEnabled = False

ADFSConfigFilePath = null

SCConfigFilePath = null

IsRestApiMFAEnabled = False

IsCliMFAEnabled = False

ADFSHostName = null

Example 3: Enabling MultiFactorAuthentication for Rest API PowerShell and sccli

```
Set-SmMultiFactorAuthentication -IsRestApiMFAEnabled $true  
-IsCliMFAEnabled $true -Path C:\ADFS_metadata\FederationMetadata.xml
```

This example syntax enables MFA for SnapCenter Rest API, PowerShell and sccli configured with specified AD FS metadata file path.

IsGuiMFAEnabled = False

ADFSConfigFilePath = C:\ADFS_metadata\FederationMetadata.xml

SCConfigFilePath = null

IsRestApiMFAEnabled = True

IsCliMFAEnabled = True

ADFSHostName = adfs19.ad19domain.com

Example 4: Enabling MultiFactorAuthentication only for PowerShell and sccli

```
Set-SmMultiFactorAuthentication -IsCliMFAEnabled $true -Path  
C:\ADFS_metadata\FederationMetadata.xml
```

This example syntax enables MFA for SnapCenter PowerShell and sccli configured with specified AD FS metadata file path.

IsGuiMFAEnabled = False

ADFSSConfigFilePath = C:\ADFS_metadata\FederationMetadata.xml

SCConfigFilePath = null

IsRestApiMFAEnabled = False

IsCliMFAEnabled = True

ADFSSHostName = adfs19.ad19domain.com

Example 5: Disabling MultiFactorAuthentication for GUI, Rest API, PowerShell and sccli

```
Set-SmMultiFactorAuthentication -IsGuiMFAEnabled $False  
-IsRestApiMFAEnabled $False -IsCliMFAEnabled $False
```

This example syntax disables MFA for SnapCenter GUI, Rest API, PowerShell and sccli.

IsGuiMFAEnabled = False

ADFSSConfigFilePath = null

SCConfigFilePath = null

IsRestApiMFAEnabled = False

IsCliMFAEnabled = False

ADFSSHostName = null

Example 6: Disabling MultiFactorAuthentication for Only for Rest API

```
Set-SmMultiFactorAuthentication -IsRestApiMFAEnabled $False
```

This example syntax disables MFA only for SnapCenter Rest API.

IsGuiMFAEnabled = True

ADFSSConfigFilePath = C:\ADFS_metadata\FederationMetadata.xml

SCConfigFilePath = null

IsRestApiMFAEnabled = False

IsCliMFAEnabled = True

ADFSSHostName = adfs19.ad19domain.com

Example 7: Update MultiFactorAuthentication configuration

```
Set-SmMultiFactorAuthentication -Path C:\data\FederationMetadata.xml
```

This example syntax updates MFA configuration for SnapCenter configured with specified AD FS metadata file path.

IsGuiMFAEnabled = True

ADFSConfigFilePath = C:\\data\\FederationMetadata.xml

SCConfigFilePath = null

IsRestApiMFAEnabled = False

IsCliMFAEnabled = False

ADFSSHostName = adfs19.ad19domain.com

Set-SmPluginConfiguration

Sets the host plug-in configuration.

Syntax

```
Set-SmPluginConfiguration [-PluginCode] <PluginCode> [-HostName]  
<String> [-HostLogFolders] <Hashtable[]> [-FCIInstanceLogFolders]  
<Hashtable[]> [-IgnoreVscConfiguredCheck] <Boolean>
```

Detailed Description

Sets the host plug-in configuration.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode	Specifies the plug-in type. Valid types are SCW and SCSQL.	true	true (ByPropertyName)	
HostName	Specifies the host name for which you are setting the plug-in configuration.	true	true (ByPropertyName)	
HostLogFolders	Specifies the host log folders.	false	true (ByPropertyName)	
FCIInstanceLogFolders	Specifies the FCI instance log folders.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
IgnoreVscConfigure dCheck		false	true (ByValue, ByPropertyName)	

Examples

Example 1: Setting the plugin configuration for a standalone host

```
Set-SmPluginConfiguration -PluginCode SCSQL -HostName localhost
-HostLogFolders @{"Host"="vise-f6";"Log Folder"="S:\LOGBACKUP"}
```

This example syntax sets the plug-in configuration for the specified standalone host.

Set-SmPluginConfiguration

SnapCenter has detected that your host is running on a VM. If you use an VMDK or RDM environment, you must add a Virtual Storage Console for vSphere type host; however, if your VM uses iSCSI direct attached disks, you can proceed with the existing host setup.

```
Choose Yes, if you are using a VM in a VMDK or RDM environment
Choose No, if you are using a VM with iSCI direct attached disks only
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default
is "Y"):
```

Example 2: Setting the plugin configuration for a cluster host

```
Set-SmPluginConfiguration -PluginCode SCSQL
-HostName V67VMCLUS -HostLogFolders @{"Host"="v6vmw2012r2";"Log
Folder"="S:\LogBackup"},@{"Host"="v7vmw2012r2";"Log
Folder"="S:\LogBackup"} -FCIInstanceLogFolders @{"FCI Instance"="vise-
f6\FCIInstance";"Log Folder"="R:\"}
```

This example syntax sets the plug-in configuration for the specified cluster.

Set-SmPluginConfiguration

SnapCenter has detected that your host is running on a VM. If you use an VMDK or RDM environment, you must add a Virtual Storage Console for vSphere type host; however, if your VM uses iSCSI direct attached disks, you can proceed with the existing host setup.

```
Choose Yes, if you are using a VM in a VMDK or RDM environment
Choose No, if you are using a VM with iSCI direct attached disks only
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default
is "Y"):
```


Set-SmPolicy

Modifies an existing policy.

Syntax

```
Set-SmPolicy [-PolicyName] <String> [-PolicyType] <SmPolicyType> [-  
PluginPolicyType] <PluginCode> [-Description] <String>
```

Detailed Description

Modifies an existing policy.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PolicyName	Specifies the policy you want to change.	true	true (ByPropertyName)	
PolicyType	Specifies the policy type. Valid value is Backup.	true	true (ByPropertyName)	
PluginPolicyType	Specifies the type of plug-in. You need to specify a plug-in type because policies are settings that are specific to one type of plug-in. Valid plug-in policies types are SCSQL, SCO and HANA.	true	true (ByPropertyName)	
Description	Specifies an optional description of the policy.	false	true (ByPropertyName)	
UtmType	Type of up to the minute (UTM) retention settings to apply to log backups. Possible values are days and count.	false	true (ByPropertyName)	
UtmCount	Up to the minute (UTM) retention by count.	false	true (ByPropertyName)	
UtmDays	Up to the minute (UTM) retention by days.	false	true (ByPropertyName)	
SqlBackupType	SQL backup type. Possible values are LogBackup, FullBackup, and FullBackupAndLogBackup.	true	true (ByPropertyName)	
DatabasesPerGroup	Maximum number of databases in a group. This is applicable only for full backup.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
CopyOnlyBackup	Determines whether the full backup is a copy only backup.	false	true (ByPropertyName)	
AGBackupType	Availability Group backup type. Possible values are UsePreferredBackupReplica and UseSpecifiedBackupReplica.	false	true (ByPropertyName)	
AGBackupReplicaType	Availability Group backup replica type. Possible values are Primary, Secondary, and All.	false	true (ByPropertyName)	
AGBackupPriorityMinimum	Availability Group backup minimum priority.	false	true (ByPropertyName)	
AGBackupPriorityMaximum	Availability Group backup maximum priority.	false	true (ByPropertyName)	
CreateLogFolderSnapshot	Create Log folder Snapshot copy.	false	true (ByPropertyName)	
EnableLogFolderSnapshotRetention	Enable Log folder Snapshot copy retention.	false	true (ByPropertyName)	
DeleteLogFolderSnapshotInExcess	Delete log folder Snapshot copies in excess of specified count. If other options are specified, then that will be ignored and only the log snapshot retention value will get modified.	false	true (ByPropertyName)	
DeleteLogFolderSnapshotOlderThan	Delete log folder Snapshot copies that are older than specified days.	false	true (ByPropertyName)	
VerifyLogBackup	Enable log backup verification after backup.	false	true (ByPropertyName)	
DBCC_NOINDEX	DBCC options NOINDEX.	false	false	
DBCC_ALL_ERROR_MSGS	DBCC options ALL_ERRORMSGs.	false	true (ByPropertyName)	
DBCC_NO_INFOMSGS	DBCC options NO_INFOMSGs.	false	true (ByPropertyName)	
DBCC_TABLOCK	DBCC options TABLOCK.	false	true (ByPropertyName)	
DBCC_PHYSICALONLY	DBCC options PHYSICALONLY.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
UpdateSnapMirrorAfterBackup	Update SnapMirror copy after backup. This option is not applicable for SAP HANA policy of File-Based Backup type.	false	true (ByPropertyName)	
UpdateSnapVaultAfterBackup	Update SnapVault copy after backup. This option is not applicable for SAP HANA policy of File-Based Backup type.	false	true (ByPropertyName)	
MirrorVaultUpdateRetryCount	Number of retries to ensure SnapMirror or SnapVault update is triggered.	false	true (ByPropertyName)	
SnapVaultLabel	Label for SnapVault copy.	false	true (ByPropertyName)	
AllowSavedStateBackup	Allow saved state backup.	false	true (ByPropertyName)	
DeleteBackupInExcess	Delete backup in excess of specified days, it is applicable to only SnapCenter Plug-in for VMware vSphere, if it is used with other plug-ins it will be ignored.	false	true (ByPropertyName)	
DeleteBackupOlderThan	Delete backups older than specified days, it is applicable to only SnapCenter Plug-in for VMware vSphere, if it is used with other plug-ins it will be ignored.	false	true (ByPropertyName)	
PreScriptCommandVerification		false	true (ByPropertyName)	
PreScriptArgumentsVerification		false	true (ByPropertyName)	
PostScriptCommandVerification		false	true (ByPropertyName)	
PostScriptArgumentsVerification		false	true (ByPropertyName)	
ScriptTimeoutVerification		false	true (ByPropertyName)	
ScheduleType	The schedule type. Possible values are None, Hourly, Weekly, Daily, and Monthly.	false	true (ByPropertyName)	
RetentionSettings	Specifies in a hashtable the retention settings for the policy.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
PreScriptCommand	Prescript file UNC path with proper privileges for scripts accessibility, ('\\server\share\path\file' for Universal Naming Convention (UNC) names).	false	true (ByPropertyName)	
PreScriptArguments	Specifies the prescript arguments.	false	true (ByPropertyName)	
PostScriptCommand	Postscript file UNC path with proper privileges for scripts accessibility, ('\\server\share\path\file' for Universal Naming Convention (UNC) names).	false	true (ByPropertyName)	
PostScriptArguments	Specifies the postscript arguments.	false	true (ByPropertyName)	
ScriptTimeout	Specifies script timeout value in seconds.	false	true (ByPropertyName)	
VerificationScheduleType	Specifies when to run verification.	false	true (ByPropertyName)	
DeleteCloneOnScheduleExpiry	Removes a clone during the last run of a scheduled job.If this parameter is not set, then the last run of a schedule also runs a clone life cycle and creates a cloned database.This parameter does not apply to jobs that are not scheduled or to one time job schedules.	false	true (ByPropertyName)	
BackupPolicyName	Specifies the backup policy name.	true	true (ByPropertyName)	
CloneType	Specifies the clone type. Possible values are Primary and Secondary.	false	true (ByPropertyName)	
VerifyOnSecondary	Specifies whether to verify on Secondary or not.	false	false	
NumOfBackups	Number of backups to be verified.	false	false	
PluginParams		false	true (ByPropertyName)	
DominoChangeInfoPath		false	true (ByPropertyName)	
DominoDatabaseType		false	true (ByPropertyName)	
DominolniniPath		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
DominoRestoreFilePath		false	true (ByPropertyName)	
DominoRestoreTime		false	true (ByPropertyName)	
Lotus		false	true (ByPropertyName)	
NotesExecDirectory		false	true (ByPropertyName)	
DominoDisableReplication		false	true (ByPropertyName)	
DominolgnoreCorruptedDB		false	true (ByPropertyName)	
DBMCLiCmd		false	true (ByPropertyName)	
HandleLogWriter		false	true (ByPropertyName)	
MaxDBBGServerPrefix		false	true (ByPropertyName)	
MaxDBUpdateHistLog		false	true (ByPropertyName)	
SQLCLiCmd		false	true (ByPropertyName)	
XUserEnable		false	true (ByPropertyName)	
DB2Cmd		false	true (ByPropertyName)	
SybaseISQLCmd		false	true (ByPropertyName)	
SybaseManifest		false	true (ByPropertyName)	
SybaseManifestDelete		false	true (ByPropertyName)	
SybaseManifestFormat		false	true (ByPropertyName)	
SybaseTranDump		false	true (ByPropertyName)	
SybaseTranDumpCompress		false	true (ByPropertyName)	
SybaseTranDumpFormat		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
OracleBackupType	Modifies the Oracle backup type. Type values are Online, Offline mount, and Offline shutdown.	true	true (ByPropertyName)	
OracleBackupScope	Modifies the Oracle backup scope. This parameter is only valid when the backup type is Online. Backup scope values are Full, Data, and Log.	true	true (ByPropertyName)	
OracleSkipPDBSaveState	Modifies the skip PDB save state. This parameter is only available when you select Offline shutdown backup type. Values are either True or False.	false	true (ByPropertyName)	
DeleteAllArchiveLogs	Prunes (deletes) all archive logs after Full or Log backups.	false	true (ByPropertyName)	
DeleteArchiveLogsOlderThan	Modifies the number of days before archive logs older than a specified number of days are pruned (deleted). This parameter supports the use decimals to enable you to specify a fraction of a day. For example, 2.5 represents 2 days and 12 hours, and 0.04 represents 1 hour.	false	true (ByPropertyName)	
DeleteArchiveLogFromAllDestination	Modifies whether archive logs are pruned on all destinations or only on backed up destinations. If the value is True, archive logs are pruned on all destinations. If the value is False, archive logs are pruned only on backed up destinations.	false	true (ByPropertyName)	
DeleteArchiveLogBackupInExcess	Modifies the number of archive log backups deleted in excess of the specified backup count.	false	true (ByPropertyName)	
DeleteArchiveLogBackupOlderThan	Modifies the number of archive log backups deleted that are older than the specified number of days. This parameter supports the use decimals to enable you to specify a fraction of a day. For example, 2.5 represents 2 days and 12 hours, and 0.04 represents 1 hour.	false	true (ByPropertyName)	
CatalogBackupWithOracleRMAN		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ScwBackupType	Specifies the type of SnapCenter for Windows backup. Valid values are CrashConsistent and FilesystemConsistent.	true	true (ByPropertyName)	
SceBackupType	Specifies the backup type you want SnapCenter for Microsoft Exchange Plug-in to use.	true	true (ByPropertyName)	
UtmCounts		false	true (ByPropertyName)	
BackupTruncatedTransactionLog		false	true (ByPropertyName)	
BackupActiveCopies		false	true (ByPropertyName)	
BackupCopiesOnServer		false	true (ByPropertyName)	
BackupType	This is a SAP HANA database specific parameter. Specifies the type of SAP HANA backup. The possible values are FileBasedBackup and SnapshotBasedBackup.	true	true (ByPropertyName)	

Examples

Example 1: Modifying an existing Microsoft SQL policy

```
Set-SmPolicy -PolicyName test -PluginPolicyType SCSQL -PolicyType Backup
-SqlBackupType FullBackup -ScheduleType Hourly -DaysInterval 8 -StartTime
$SystemTime -EndTime $SystemTimeExpire -SchedulerType SQL
```

This example syntax modifies an existing Microsoft SQL policy.

Example 2: Modifying an existing Oracle policy

```
Set-SmPolicy -PolicyName 1 -PolicyType Backup -PluginPolicyType SCO
-OracleBackupType ONLINE -OracleBackupScope FULL -DeleteAllArchiveLogs
$true -DeleteArchiveLogFromAllDestination $true
-DeleteArchiveLogBackupInExcess 5
```

Modifies an existing Oracle policy.

Example 3: Modifying an existing Windows backup policy

```
Set-SmPolicy -PolicyName scw_policy3 -PolicyType Backup -PluginPolicyType  
SCW -ScwBackupType CrashConsistent
```

This example syntax modifies an existing Windows SCW policy.

Example 4: Modifying an existing SAP HANA backup policy of type SnapshotBasedBackup

```
Set-SmPolicy -PolicyName hana_snapshotbased -PolicyType Backup  
-PluginPolicyType HANA -BackupType SnapshotBasedBackup  
-UpdateSnapMirrorAfterbackup $true -UpdateSnapVaultAfterbackup $true  
-SnapVaultLabel slabel
```

This example syntax modifies an existing SAP HANA backup policy of type SnapshotBasedBackup.

Example 5: Modifying an existing Microsoft SQL policy with SnapLock Retention

```
Set-SmPolicy -PolicyName SCSQL_Snaplock_Policy -PluginPolicyType SCSQL  
-PolicyType Backup -SqlBackupType FullBackupAndLogBackup -ScheduleType  
Daily -retentionsettings @{"BackupType"="DATA";  
"ScheduleType"="DAILY";"RetentionDays"="16";"SnapLockRetentionPeriod"=16;"  
SnapLockRetentionPeriodType"="Days"},@{"BackupType"="LOG";  
"ScheduleType"="DAILY";"RetentionCount"="9";"SnapLockRetentionPeriod"=16;"  
SnapLockRetentionPeriodType"="Days"}
```

INFO: Specifying a retention period prevents the Snapshot copies from being deleted until the SnapLock retention period expires. This could lead to retaining a larger number of Snapshot copies than the count specified in the policy.

```
ApplySnapvaultUpdate: False  
ApplyRetention      : True  
RetentionCount      : 0  
RetentionDays       : 16  
ApplySnapMirrorUpdate : False  
SnapVaultLabel      :  
MirrorVaultUpdateRetryCount : 3  
Retentions          : {, , }  
LastBackupStatus:  
LastBackupDate      :  
IncludeAcls         :  
AppPolicies         : {}  
Description         :  
PreScriptPath       :
```



```

PreScriptArguments  :
PostScriptPath      :
PostScriptArguments :
ScriptTimeOut       : 60
DateModified: 8/13/2023 6:56:10 PM
DateCreated  : 8/13/2023 6:56:10 PM
Schedule: SMCoreContracts.SmSchedule
PolicyType   : Backup
PluginPolicyType: SMSQL
InBuilt      : False
Schedules    : {}
AllowMultipleSchedules : False
Name: SCSQL_Snaplock_Policy
Type:
Id   : 4
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
Hosts     : {}
StorageName :
ResourceGroupNames :
PolicyNames :
Key : 0
NsmObjectID : 0
SizeOfSmObject : SMCoreContracts.SmObjectSize

Retention Settings
BackupType : DATA
SchedulerType : Daily
RetentionCount : 0
RetentionDays : 16
VerificationEnabled : False
NodeName:
SnapLockRetentionPeriod : 16
SnapLockRetentionPeriodType : Days

BackupType : LOG
SchedulerType : Daily
RetentionCount : 9
RetentionDays : 0
VerificationEnabled : False
NodeName:

```

```

SnapLockRetentionPeriod : 16
SnapLockRetentionPeriodType : Days

BackupType : LOG_SNAPSHOT
SchedulerType : None
RetentionCount : 2
RetentionDays : 0
VerificationEnabled : False
NodeName:
SnapLockRetentionPeriod :
SnapLockRetentionPeriodType :

```

Example 6: Modifying the Snapshot copy log retention

```

Set-SMPolicy -PolicyName 'Log_policy_1' -PolicyType 'Backup' -Description
'log backup Policy' -retentionsettings
@{"BackupType"="DATA";"RetentionCount"="2"},@{"BackupType"="LOG";"RetentionCount"="2"},@{"BackupType"="LOG_SNAPSHOT";"RetentionCount"="3"}
-pluginpolicytype 'SCSQL' -sqlbackuptype 'logbackup'

```

This example modifies the Snapshot copy log retention. When you change the retention setting, you must also specify the other cmdlet parameters, otherwise, the current settings will override the default settings.

Example 7: Modifying log snapshot copy retention value without resetting the other policy settings

```

Set-SmPolicy -PolicyName 'test' -PolicyType Backup -PluginPolicyType
'SCSQL' -DeleteLogFolderSnapshotInExcess 2 -SqlBackupType
'fullbackupandlogbackup'

```

This example modifies the log snapshot copy retention value. If other policy options are specified then these options will be ignored and only retention value will be modified.

Set-SmProtectResource

Modifies policies and schedules of the resource.

Syntax

```

Set-SmProtectResource [-ArchivedLocators] <Hashtable[]> [-PluginCode]
<PluginCode> [-EnableEmail] <> [-EmailPreference]
<SmEmailNotificationPreference> [-RemoveCustomSnapShot] <>

```

Detailed Description

Modifies policies and schedules of the resource.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ArchivedLocators	Specifies in a hashtable the secondary storage system details for each unique primary storage system resource in the resource group. For example:- ArchivedLocators @{Primary="my_vs1:my_vol_iscsi";Secondary="my_vs1:my_vol_iscsi_SECONDARY"}	false	true (ByPropertyName)	
PluginCode	Specifies the plug-in code of the host for which you are creating a backup resource group. Valid values are SCSQL, SCW, and SCO.	true	true (ByPropertyName)	
EnableEmail	Specifies whether to enable or disable email.	false	false	
EmailPreference	Specifies when you will receive e-mail notifications. Possible values: Always, Never, OnError, OnErrorOrWarning.	false	false	
RemoveCustomSnapshot	Specifies removal of the custom naming format of the Snapshot copy.	false	true (ByPropertyName)	
BackupArchiveLogsAfterRecentMissingOne	This option is only valid for SCO plugin code. Specifies that you want to backup archive log files, which are created after the most recent missing archive log files and ignore the files created prior to it. If this option is not specified, then all archive log files except the missing archive log files are backed up.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ExcludeArchiveLogPathsFromBackup	This option is only valid for SCO plugin code. Specifies the archive log destinations to be excluded from backup. Archive log files present in the specified destinations will be excluded during log backup. Multiple entries can be specified using comma separated list. For example: -ExcludeArchiveLogPathsFromBackup '/arch/logs/on/local/disk1, /arch/logs/on/local/disk2'.	false	true (ByPropertyName)	
Resources	Specifies the resource you want to protect. You must provide the resource information in a key value format, and it must contain the resource name, type, and the host on which it is located. For example, -Resource@{"Host"="host.example.com";"Type"="SQL Database";"Names"="NB-MVA-DEV054\newdb"} For Oracle Database, the format is -Resources @{"Host"="host.example.com";"Oracle Database"="db"}. For Oracle Application Volume, the format is -Resources @{"Host"="host.example.com";"Application Volume"="appVol"}.	true	true (ByPropertyName)	
Description	Modifies policies and schedules of the resource.	false	true (ByPropertyName)	
Tag	Enables you to apply a unique tag to help identify the resources.	false	true (ByPropertyName)	
Policies	Specifies the list of policies associated with the resource group. Multiple policies can be added as a comma-separated list.	false	true (ByPropertyName)	
SchedulerCredentialName		false	true (ByPropertyName)	
SchedulerInstance	Specifies the SQL Server Instance where the schedule is created and managed. This is mandatory if the policy has SQL scheduler enabled.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
VerificationServers	Specifies the list of verification servers to be associated with the resource group. Multiple verification servers can be added as a comma-separated list. This parameter is only required when you want to verify backups for SnapCenter Plug-in for Microsoft SQL Server resource groups.	false	true (ByPropertyName)	
CustomSnapshotFormat	Specifies that you want to use a custom Snapshot copy naming format. By default, a timestamp is appended to the Snapshot copy name. Valid values for CustomSnapshotFormat are : \$ResourceGroup, \$Policy, \$HostName, \$ScheduleType, \$CustomText	false	true (ByPropertyName)	
CustomText	Specifies the custom text in the custom Snapshot copy naming format.	false	true (ByPropertyName)	
DeleteBackupForDetachPolicies		false	true (ByPropertyName)	
Schedules	Specifies the schedule parameters to be used in the resource group. Schedule parameters can include the policy name, schedule type, schedule start and end times. You can specify multiple schedules in a comma-separated list, for example:- Schedules @{"PolicyName"="BackupPolicy";"ScheduleType"="OneTime"}, @{"PolicyName"="BackupPolicy";"ScheduleType"="Hourly";"StartTime"=" 05/27/2016 6:13 PM";"EndTime"="05/27/2016 6:30 PM"}	false	true (ByPropertyName)	
SchedulerType	Specifies the scheduler type. Possible values are Windows, SQL, None.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
VerificationSchedules	Specifies the verification schedules you want to add to the resource. The verification schedule includes the following parameters:"VerificationType" which defines if and when verification is performed. The following values are available:VERIFY_SCHEDULEDVERIFY_AFTER_BACKUPNONE"ScheduleType" represents the schedule type for the verification."BackupScheduleType" represents the schedule type for the backup-VerificationServers "WIN-DVGQDI73QR6" needs to be provided in the above command if we are creating verification enabled resource group for SCSQL plugin.Example:- VerificationSchedules @{"BackupScheduleType"="Hourly";"DeferredBackupCount"="1";"VerificationType"="VERIFY_SCHEDULED";"VerifyOnSecondary"="true";"BackupPolicyName"="sco_20july";"ScheduleType"="Weekly";"DaysOfTheWeek"="Monday";"StartTime"="20-Jul-16 6:42:12 PM";"EndTime"="25-Jul-16 6:42:12 PM"}	false	true (ByPropertyName)	
ConsistencyGroupSnapshot		false	true (ByPropertyName)	
ConsistencyGroupWafSync		false	true (ByPropertyName)	
ConsistencyGroupTimeout		false	true (ByPropertyName)	
SnapShotCreateCommand		false	true (ByPropertyName)	
UseFileSystemConsistentSnapshot		false	true (ByPropertyName)	
UseSnapcenterWithoutFileSystemConsistency		false	true (ByPropertyName)	
PreAppQuiesceCmd		false	true (ByPropertyName)	
PostAppQuiesceCmd		false	true (ByPropertyName)	
AppQuiesceCmd		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
AppUnQuiesceCmd		false	true (ByPropertyName)	
PreAppUnQuiesceCmd		false	true (ByPropertyName)	
PostAppUnQuiesceCmd		false	true (ByPropertyName)	
PreExitCmd		false	true (ByPropertyName)	
PreSnapshotCmd		false	true (ByPropertyName)	
PostSnapshotCmd		false	true (ByPropertyName)	
ApplgnoreError		false	true (ByPropertyName)	
UseExternalSnapShot		false	true (ByPropertyName)	
ExternalSnapshotRegex		false	true (ByPropertyName)	
ConfigParams		false	true (ByPropertyName)	

Examples

Example 1: Modifying the Protection of a resource

```
Set-SmProtectResource -PluginCode SCSQL -Policies BackupPolicy
-Resources @{"Host"="host.example.com";"Type"="SQL Database";"Names"="NB-MVA-DEV054\newdb"} -Description "The protection of the resource is
modified"
-EnableAsupOnFailure
```

This example syntax modifies the protection of a resource.

Example 2

```
Set-SmProtectResource -Resources
@(@{"Host"="sccorelinux188.sccore.test.com";"Uid"="Set_CG_Timeout6";"Type"
="Instance";"Names"="Set_CG_Timeout6"}) -PluginCode 'DummyPlugin'
-consistencygrouptimeout 'Medium'
```

Example 3: Enable email during protecting resource

```
Set-SmProtectResource -PluginCode 'HANA' -Resources
@{"Host"="hanahost01.testlab.netapp.com";"Uid"="MDC\R71"}
    -EnableEmail -EmailPreference OnErrorOrWarning -EmailFrom
'snapcenter@netapp.com' -EmailTo 'backupteam@netapp.com' -EmailSubject
'SnapCenter HANA Backup Failure'
```

This example syntax enables email notification during the protection of a HANA resource.

Example 4: Modifying the Protection of an Oracle Application Volume resource

```
Set-SmProtectResource -PluginCode SCO -Policies "appVolPolicyModified"
-Resources @{"Host"="R8092776CF4V1.HNK2.com";"Application
Volume"="appVol"} -Description "protection is modified"
```

This example syntax modifies the protection policy of an Oracle application volume resource.

Set-SmReportSchedule

Modify the report schedule using this cmdlet.

Syntax

```
Set-SmReportSchedule [-Name] <String> [-Plugin] <PluginCode> [-
Enabled] <Boolean> [-ScheduleType] <String> [-DayOfTheWeek] <String>
[-DayOfTheMonth] <String> [-TriggerTime] <String> [-DocumentType]
<String> [-FromEmail] <String> [-Recipients] <String>
```

Detailed Description

Modify the report schedule by passing the required schedule name and the parameters. This command can be used to enable or disable a schedule.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specify the name of the schedule to be modified.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
Plugin	Specify the plug-in code to generate the report. For custom plug-ins, specify the custom plug-in name for example, hana, mysql. Specify 'all' to generate report for "All Plug-ins".	true	true (ByPropertyName)	
Enabled	Specify the state as \$true or 1 to enable the schedule and \$false or 0 to disable the schedule. Disabled schedules will not be triggered.	false	true (ByPropertyName)	
ScheduleType	Specify the schedule type. Valid values are 'daily', 'weekly', and 'monthly'.	true	true (ByPropertyName)	
DayOfTheWeek	Specify the day of the week to run the schedule. Valid values are 'monday', 'tuesday', 'wednesday', 'thursday', 'friday', 'saturday', 'sunday'. This field is applicable only for weekly schedule.	false	true (ByPropertyName)	
DayOfTheMonth	Specify the day (number) of the month to run the schedule. The value should be between 0 and 28. Enter zero to run the schedule for the last day of the month. This field is applicable only for monthly schedule.	false	true (ByPropertyName)	
TriggerTime	Specify the TriggerTime HH:MM in 24 Hours format.	true	true (ByPropertyName)	
DocumentType	Specify the format of the report to be sent over e-mail. The valid formats are PDF and CSV. Add the comma separator if both the formats are needed.	true	true (ByPropertyName)	
FromEmail	Specify the e-mail address from which the report has to be sent.	true	true (ByPropertyName)	
Recipients	Specify the e-mail address to send the report. For multiple e-mail ID's, separate them by comma.	true	true (ByPropertyName)	

Examples

Example 1: Modifying plug-in of a report schedule.

```
Set-SmReportSchedule -Name schedule1 -Plugin SCO
```

This example modifies the plug-in of an existing schedule to 'SCO'. Plug-in value can be any specific plug-in or 'all'. Specify 'all', to generate the report for all the configured plug-ins. For the custom plug-ins specify the plug-in name instead of the plug-in code for example, hana, mysql.

Example 2: Modifying frequency of a report schedule.

```
Set-SmReportSchedule -Name schedule1 -ScheduleType weekly -DayOfTheWeek  
sunday -TriggerTime 1:10
```

This example modifies the frequency of an existing schedule to weekly. The ScheduleType, DayOfTheWeek/DayOfTheMonth, and TriggerTime constitutes a frequency, hence all these values should be specified to modify the frequency.

Example 3: Modifying From and Recipients e-mail id(s) of a report schedule.

```
Set-SmReportSchedule -Name schedule1 -FromEmail user@domain.com  
-Recipients "user1@domain.com,user2@domain.com"
```

This example modifies From and Recipients e-mail ids of an existing schedule. FromEmail can be any single valid e-mail id and Recipients can be a single or multiple comma separated e-mail ids.

Example 4: Disabling a report schedule.

```
Set-SmReportSchedule -Name schedule1 -Enabled $false
```

This example disables a report schedule. The parameter \$true or 1 will enable the schedule and \$false or 0 will disable the schedule. Disabled schedules will not be triggered.

Set-SmRepositoryConfig

Enables you to rebuild the slave repository from the master repository and enables you to fail over the repository to the specified node.

Syntax

```
Set-SmRepositoryConfig [-ServerToRebuild] <String> [-Force] <> [-  
RebuildSlave] <> [-Force] <> [-ActiveMaster] <String> [-Force] <>  
[-Credential] <PSCredential> [-SMSbaseUrl] <String>
```

Detailed Description

Enables you to rebuild the slave repository from the master repository and enables you to fail over the repository to the specified node.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ServerToRebuild	Specifies the slave node for which you want to rebuild its repository from the master repository.	true	true (ByPropertyName)	
Force	Specifies that you want to force failover even when the slave repository data is not in sync with the master repository data.NOTE: Forcing failover might result in data loss.	false	true (ByPropertyName)	
RebuildSlave	Specifies that SnapCenter automatically identifies the slave node for which to rebuild the repository from the master repository.	true	true (ByPropertyName)	
ActiveMaster	Specifies the slave node that should become the master node.	true	true (ByPropertyName)	
Credential	Enables you to provide domain user credentials required to perform failover operations.	false	true (ByPropertyName)	
SMSbaseUrl	Specifies the SnapCenter Server base URL. The base URL includes the name or IP address of the SnapCenter Server, and, if the remote system is in a different domain than the SnapCenter Server, the domain name. For example: https://SNAPCENTER_SERVER_NAME/DOMAIN_NAME .	false	true (ByPropertyName)	

Examples

Example 1: Failover SnapCenter repository to the specified database server

```
Set-SmRepositoryConfig -ActiveMaster 10.236.221.0 -Credential  
mva\administrator
```

This example syntax fails over the SnapCenter repository to the specified database server.

```
Set-SmRepositoryConfig
Are you sure want to failover SnapCenter repository to '10.236.221.0'?
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help
(default is "Y"): Y
Name: SnapCenter Repository Failover to host '10.236.221.0'
Id : 25
StartTime : 4/28/2017 8:20:35 AM
EndTime : 4/28/2017 8:20:35 AM
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 100
Description :
Status : Completed
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 35
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName :
```

Example 2: Rebuilding a specified slave repository

```
Set-SmRepositoryConfig -ServerToRebuild 10.236.221.34
```

This example syntax rebuilds the specified slave repository.

```
Set-SmRepositoryConfig
Are you sure want to rebuild SnapCenter repository on host
'10.236.221.34'?
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help
(default is "Y"):
Name: SnapCenter Repository Rebuild on host '10.236.221.34' for High
Availability
Id : 17
StartTime : 4/28/2017 8:15:12 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 35
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName :
```

Example 3: Rebuilding the current slave repository

```
Set-SmRepositoryConfig -RebuildSlave
```

This example syntax rebuilds the current slave repository.

```
Set-SmRepositoryConfig
Are you sure want to rebuild SnapCenter passive repository?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help
(default is "Y"): Y
Name: SnapCenter Repository Rebuild on host '10.236.221.34' for High
Availability
Id : 11
StartTime : 4/28/2017 8:12:25 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Queued
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 35
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName :
```

Example 4: Failing over the SnapCenter repository to the specified database server from a remote host to SnapCenter using a base URL

```
Set-SmRepositoryConfig -ActiveMaster 10.236.221.34 -Credential
mva\administrator -SMSbaseUrl https://10.236.221.75:8146/
```

This example syntax fails over the SnapCenter repository to the specified database server from a remote host to SnapCenter using a base URL.

```

Set-SmRepositoryConfig
Are you sure want to failover SnapCenter repository to '10.236.221.34'?
[Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend  [?] Help
(default is "Y"): Y
Name: SnapCenter Repository Failover to host '10.236.221.34'
Id : 20
StartTime : 4/28/2017 8:17:47 AM
EndTime : 4/28/2017 8:17:47 AM
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 100
Description :
Status : Completed
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 35
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName :

```

Example 5: Forcing SnapCenter repository failover with possibility of data loss

```

Set-SmRepositoryConfig -ActiveMaster 10.236.221.34 -Credential
mva\administrator -SMSbaseUrl https://10.236.221.75:8146/ -Force

```

This example syntax forces a SnapCenter repository failover even though data loss might occur.

```
Set-SmRepositoryConfig
There could be a possible data loss after SnapCenter repository failover
to '10.236.221.34'
Do you still want to continue?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help
(default is "Y"): Y
Name: SnapCenter Repository Failover to host '10.236.221.34'
Id : 32
StartTime : 4/28/2017 8:24:48 AM
EndTime : 4/28/2017 8:24:48 AM
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 100
Description :
Status : Completed
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 35
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName :
```

Set-SmRepositoryConfigSettings

Enables you to set MySQL High Availability repository configuration settings for the SnapCenter Server host.

Syntax

```
Set-SmRepositoryConfigSettings [-NLBClusterIP] <String> [-NLBNodeIPs]
<String>
```

Detailed Description

Enables you to set MySQL High Availability repository configuration settings for the SnapCenter Server host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
NLBClusterIP	Specifies the NLB Cluster IP address to which the SnapCenter Server NLB host is configured.	true	true (ByPropertyName)	
NLBNodeIPs	Specifies the list of NLB node IP addresses that are part of the NLB Cluster.	true	true (ByPropertyName)	

Examples

Example 1: Set MySQL High Availability repository configuration settings

```
Set-SmRepositoryConfigSettings -NLBClusterIP 10.236.221.0 -NLBNodeIPs 10.236.221.10,10.236.221.11
```

This example syntax sets the MySQL High Availability repository configuration settings.

Set-SmRepositoryPassword

Enables you to set the repository password for the SnapCenter Server host.

Syntax

```
Set-SmRepositoryPassword [-NewPassword] <SecureString> [-ConfirmPassword] <SecureString>
```

Detailed Description

Enables you to set the repository password for the SnapCenter Server host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
NewPassword	Specifies the new password to be configured for the repository.	true	false	
ConfirmPassword	Specifies the confirmation password to be configured for the repository.	true	false	

Examples

Example 1: Set the MySQL repository password

```
Set-SmRepositoryPassword
```

This example syntax sets the MySQL repository password to the specified value.

Set-SmResource

Modifies custom plug-in resource or an Oracle plug-in application volume resource settings.

Syntax

```
Set-SmResource [-UndoDeletion] <> [-ResourceId] <String> [-HostName]
<String> [-PluginCode] <PluginCode> [-ResourceId] <String> [-
HostName] <String> [-PluginCode] <PluginCode> [-RunAsName] <String>
```

Detailed Description

Used for modifying allowed attributes of a custom plug-in resource or an Oracle plug-in application volume resource. Also used for re-adding a resource that was soft deleted (resource which is protected).

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
UndoDeletion		false	true (ByPropertyName)	
ResourceId	: System-generated unique ID of a resource. For Oracle Application Volume Resource, its resource ID is of the format HostName\ResourceName.	false	true (ByPropertyName)	
HostName	Specifies the name or IP address of the host, only when the Agent or Plugin parameters are specified.	true	true (ByPropertyName)	
PluginCode	Specifies which plug-in configuration you want to modify. Possible inputs include MSFT_SQL, SCW, SCO, HANA and SCU. For example, for SnapCenter Plug-in for Microsoft SQL Server instances, the plug-in code is MSFT_SQL.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
RunAsName		false	true (ByPropertyName)	
TenantDatabaseName	This is a SAP HANA database specific parameter. It is the name of the tenant database. This parameter is deprecated for MultiTenant database container resources, it will be ignored and auto discovered internally.	false	true (ByPropertyName)	
TenantType	This is a SAP HANA database specific parameter. This specifies the tenant type of SAP HANA Multitenant Database Container. SingleTenant as tenant type is deprecated. SingleTenant as tenant type is deprecated	true	true (ByPropertyName)	MultiTenant

Examples

Example 1: Modifying custom plugin DB2 resource

```
Set-SmResource -HostName 'sccorelinux188.sscore.test.com' -PluginCode
'DB2' -ResourceName Database1 -ResourceType Database -StorageFootPrint
(@{"QTREE_NAME"="inventory_vol_sec";"VolumeName"="inventory_vol";"StorageS
ystem"="vserver_scauto_secondary"}) -Instance INST
```

Modify Storage footprint for Database of DB2 plug-in

```

Cmdlet Output: Successfully updated the resource
PluginName : DB2
Uid: INST\Database1
ParentUid  :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
LastBackupDate :
LastBackupStatus :
IsProtected: False
Name : Database1
Type : Database
Id : sccorelinux188.sccore.test.com\DummyPlugin\INST\DominoA
utoDatabase
Host : sccorelinux188.sccore.test.com
UserName :
Passphrase :
Deleted: False
Auth :
IsClone: False
CloneLevel : 0
Hosts :

```

Example 2: Modifying SAP HANA Multitenant Database Container

```

Set-SmResource -HostName 'scspr0204312001.gdl.englab.netapp.com'
-ResourceId 'scspr0204312001.gdl.englab.netapp.com\hana\MDC\M01'
-PluginCode 'hana' -DatabaseName 'newname' -ResourceType
'MultipleContainers' -SID 'M01' -TenantType 'SingleTenant'

```

Modify DatabaseName for SAP HANA database of type MultipleContainers.

```

cmdlet Set-SmResource at command pipeline position 1
Successfully updated the resource
PluginName : hana
Uid: MDC\M01
ParentUid  :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
pluginConfiguration: SMCoreContracts.SmSCSAPHANAResourceParameters
LastBackupDate :
LastBackupStatus :
IsProtected: False
IsWindowsResource : False
Name : newname
Type : MultipleContainers
Id : scspr0204312001.gdl.englab.netapp.com\hana\MDC\M01
Host : scspr0204312001.gdl.englab.netapp.com
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts :
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0

```

Example 3: Undo SmResource deletion

```

Set-SmResource -HostName 'sccorelinux188.sccore.test.com' -PluginCode
'DB2' -ResourceName Database1 -UndoDeletion

```

Adds the deleted resource and is available for protection.

Example 4: Edit the database name and HDB Secure User Store Key for MultiTenant database container with multi tenants resource type.

```
Set-SmResource -HostName 'vp-hana2.gdl.englab.netapp.com' -PluginCode
'HANA' -DatabaseName MDC_MT_modified_again -ResourceType
MultipleContainers -StorageFootPrint
(@{'VolumeName'='VP_HANA2_data';'StorageSystem'='buck.gdl.englab.netapp.co
'}) -sid 'A12' -userstorekeys 'A12KEY_modified_again' -TenantType
'MultiTenant'
```

This sets the database name and HDB Userstore Key for MultiTenant database container with multi tenants resource type.

```
cmdlet Set-SmResource at command pipeline position 1
Successfully updated the resource
PluginName : hana
Uid: MBC\A12
ParentUid :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
pluginConfiguration: SMCoreContracts.SmSCSAPHANAResourceParameters
LastBackupDate :
LastBackupStatus :
IsProtected: False
IsWindowsResource : False
Name : MDC_MT_modified_again
Type : MultipleContainers
Id : vp-hana2.gdl.englab.netapp.com\hana\MDC\A12
Host : vp-hana2.gdl.englab.netapp.com
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts :
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
```

Example 5: Edit the database name and HDB User Store Key for single tenant resource type.

```
Set-SmResource -HostName 'vp-hana2.gdl.englab.netapp.com' -PluginCode
'HANA' -DatabaseName MDC_ST_modified -ResourceType MultipleContainers
-StorageFootPrint
(@{'VolumeName'='lun_vol';'StorageSystem'='10.232.206.5'}) -sid 'A12'
-userstorekeys 'A12KEY_modified' -TenantType 'SingleTenant'
-TenantDatabaseName 'TDB'
```

This sets the database name and HDB User Store Key for single tenant resource type. In this example, the tenant database name is required to edit the resource, which is added in SnapCenter Server v4.2 or earlier.

```
cmdlet Set-SmResource at command pipeline position 1
Successfully updated the resource
PluginName : hana
Uid: TDB
ParentUid :
SmAppFiles :
SmAppFileStorageGroups : {}
PluginParams : SMCoreContracts.SmKeyValueCollection
MountPaths :
pluginConfiguration: SMCoreContracts.SmSCSAPHANAResourceParameters
LastBackupDate :
LastBackupStatus :
IsProtected: False
IsWindowsResource : False
Name : MDC_ST_modified
Type : MultipleContainers
Id : vp-hana2.gdl.englab.netapp.com\hana\TDB
Host : vp-hana2.gdl.englab.netapp.com
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts :
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
```

Example 6: Edit an Oracle Application Volume Resource storage footprint

```
Set-SmResource -HostName 'R8092776CF4V1.HNK2.com' -PluginCode 'SCO'
-ResourceName appVol -StorageFootPrint
@(@{"VolumeName"="vol_test1";"StorageSystem"="10.232.206.165"},@{"VolumeName"="vol_test2";"LunName"="lun_test2";"StorageSystem"="10.232.206.165"},@{"QtreenName"="qtree_test1";"VolumeName"="vol_test3";"StorageSystem"="10.232.206.165"})
```

This example modifies storage footprint of an Oracle Application Volume Resource

```
Set-SmResource
Are you sure you want to modify the resource : 'appVol' ?
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend
[?] Help (default is "Y"): Y
Successfully updated the resource

Uid: appVol
SmAppFileStorageGroups : {, , }
IsProtected: False
LastBackupDate :
LastBackupStatus :
Name : appVol
Type : Application Volume
Id : R8092776CF4V1.HNK2.com\appVol
Host : R8092776CF4V1.HNK2.com
UserName :
Passphrase :
Deleted: False
Auth : SMCoreContracts.SmAuth
IsClone: False
CloneLevel : 0
Hosts :
StorageName:
ResourceGroupNames :
PolicyNames:
Key: 0
NsmObjectID: 0
SizeOfSmObject :
```

Example 7: Edit hostname and resource name of an Oracle Application Volume Resource

```
Set-SmResource -HostName 'R809278EA03V1.HNK2.com' -PluginCode 'SCO'
-ResourceName appVolModified -ResourceId R8092776CF4V1.HNK2.com\appVol
```


This example modifies hostname and resource name of an Oracle Application Volume Resource

```
Set-SmResource
    Are you sure you want to modify the resource : 'appVol' ?
    [Y] Yes  [A] Yes to All  [N] No  [L] No to All  [S] Suspend
[?] Help (default is "Y"): Y
    Successfully updated the resource
    Uid: appVolModified
    SmAppFileStorageGroups : {}
    IsProtected: False
    LastBackupDate :
    LastBackupStatus :
    Name : appVolModified
    Type : Application Volume
    Id : R809278EA03V1.HNK2.com\appVolMo
    Host : R809278EA03V1.HNK2.com
    UserName :
    Passphrase :
    Deleted: False
    Auth : SMCoreContracts.SmAuth
    IsClone: False
    CloneLevel : 0
    Hosts :
    StorageName:
    ResourceGroupNames :
    PolicyNames:
    Key: 0
    NsmObjectID: 0
    SizeOfSmObject :
```

Example 8: Undo soft deletion of an Oracle Application Volume resource

```
Set-SmResource -HostName 'R809278EA03V1.HNK2.com' -PluginCode 'SCO'
-ResourceName appVol1 -UndoDeletion
```

Adds the deleted Oracle Application Volume resource and is available for protection.

Set-SmResourceCredentialName

Set the credential for the SQL instance registered with the SnapCenter Server.

Syntax

```
Set-SmResourceCredentialName [-ResourceAuths] <Hashtable[]>
```

Detailed Description

Set the credential for the SQL instance registered with the SnapCenter Server based on the credential information provided.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ResourceAuths		true	true (ByPropertyName)	

Examples

- Example : Setting the credential for the SQL instance by RunAs ID. -

```
Set-SmResourceCredentialName -ResourceAuths  
@{"CredentialId"="3";"Names"="R708202074BV1\SQL2019";}
```

This example syntax sets the credential for the SQL instance registered with the SnapCenter Server based on the RunAs ID provided.

AppObject Auth

SMCoreContracts.SmObject SMCoreContracts.SmAuth

Set-SmResourceGroup

Modifies a resource group.

Syntax

```
Set-SmResourceGroup [-ArchivedLocators] <Hashtable[]> [-  
ResourceGroupName] <String> [-PluginCode] <PluginCode> [-EnableEmail]  
<> [-EmailPreference] <SmEmailNotificationPreference> [-  
RemoveCustomSnapshot] <> [-BackupServers] <SmBackupServer>
```

Detailed Description

Modifies a resource group. You can modify policies, schedules, verification schedules, and resources associated with the resource group.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ArchivedLocators	Specifies in a hashtable the secondary storage system details for each unique primary storage system resource in the resource group. For example:- ArchivedLocators @{Primary="my_vs1:my_vol_iscsi";Secondary="my_vs1:my_vol_iscsi_SECONDARY"}	false	true (ByPropertyName)	
ResourceGroupName	Specifies the name of the resource group that you want to modify.	true	true (ByPropertyName)	
PluginCode	Specifies the plug-in code of the host for which you are modifying a backup resource group. Valid values are SCSQL, SCW, and SCO.	true	true (ByPropertyName)	
EnableEmail	Specifies whether to enable or disable email.	false	false	
EmailPreference	Specifies when you will receive e-mail notifications. Possible values: Always, Never, OnError, OnErrorOrWarning.	false	false	
RemoveCustomSnapshot		false	true (ByPropertyName)	
BackupArchiveLogsAfterRecentMissingOne	This option is only valid for SCO plugin code. Specifies that you want to backup archive log files, which are created after the most recent missing archive log files and ignore the files created prior to it. If this option is not specified, then all archive log files except the missing archive log files are backed up.	false	true (ByPropertyName)	
ExcludeArchiveLogPathsFromBackup	This option is only valid for SCO plugin code. Specifies the archive log destinations to be excluded from backup. Archive log files present in the specified destinations will be excluded during log backup. Multiple entries can be specified using comma separated list. For example: -ExcludeArchiveLogPathsFromBackup '/arch/logs/on/local/disk1, '/arch/logs/on/local/disk2'.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
BackupServers		false	true (ByPropertyName)	
Resources	Specifies the list of resources to be associated with the resource group. You must provide the resource information in a hashtable, and it must contain the resource name and type, and the host on which it is located. For example, @{"Host"="localhost","Type"="SQL Database","Names"="Instance\Database"} For instance-level backup @{"Host"="localhost","Type"="SQL Instance","Names"="Instance"} For availability group backup @{"Host"="localhost","Type"="SQL Availability Group","Names"="AG1"} Valid Type values are: SQL Database, SQL Instance, SQL Availability Group. You can include comma-separated values for Names. For Oracle Database, the format is @{"Host"="host.example.com","Oracle Database"="db1,db2,.."}. For Oracle Application Volume, the format is @{"Host"="host.example.com","Application Volume"="appVol1,appVol2,.."}.	true	true (ByPropertyName)	
Description	Specifies an optional description for the new resource group.	false	true (ByPropertyName)	
Tag	Enables you to apply a unique tag to help identify the resource group.	false	true (ByPropertyName)	
Policies	Specifies the list of policies associated with the resource group. Multiple policies can be added as a comma-separated list.	false	true (ByPropertyName)	
SchedulerCredentialName		false	true (ByPropertyName)	
SchedulerInstance	Specifies the SQL Server Instance where the schedule is created and managed. This is mandatory if the policy has SQL scheduler enabled.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
VerificationServers	Specifies the list of verification servers to be associated with the resource group. Multiple verification servers can be added as a comma-separated list. This parameter is only required when you want to verify backups for SnapCenter Plug-in for Microsoft SQL Server resource groups.	false	true (ByPropertyName)	
CustomSnapshotFormat	Specifies that you want to use a custom Snapshot copy naming format. By default, a timestamp is appended to the Snapshot copy name. Valid values for CustomSnapshotFormat are : \$ResourceGroup, \$Policy, \$HostName, \$ScheduleType, \$CustomText	false	true (ByPropertyName)	
CustomText	Specifies the custom text in the custom Snapshot copy naming format.	false	true (ByPropertyName)	
DeleteBackupForDetachedPolicies	Deletes backups for the detached policies.	false	true (ByPropertyName)	
Schedules	Specifies the schedule parameters to be used in the resource group. Schedule parameters can include the policy name, schedule type, schedule start and end times. You can specify multiple schedules in a comma-separated list, for example:- Schedules @{"PolicyName"="BackupPolicy";"ScheduleType"="OneTime"}, @{"PolicyName"="BackupPolicy";"ScheduleType"="Hourly";"StartTime"=" 05/27/2016 6:13 PM";"EndTime"="05/27/2016 6:30 PM"}	false	true (ByPropertyName)	
SchedulerType	Specifies the scheduler type. Possible values are Windows, SQL, None.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
VerificationSchedules	Specifies the verification schedules you want to add to the resource. The verification schedule includes the following parameters:"VerificationType" which defines if and when verification is performed. The following values are available:VERIFY_SCHEDULEDVERIFY_AFTER_BACKUPNONE"ScheduleType" represents the schedule type for the verification."BackupScheduleType" represents the schedule type for the backup-VerificationServers "WIN-DVGQDI73QR6" needs to be provided in the above command if we are creating verification enabled resource group for SCSQL plugin.Example:- VerificationSchedules @{"BackupScheduleType"="Hourly";"DeferredBackupCount"="1";"VerificationType"="VERIFY_SCHEDULED";"VerifyOnSecondary"="true";"BackupPolicyName"="sco_20july";"ScheduleType"="Weekly";"DaysOfTheWeek"="Monday";"StartTime"="20-Jul-16 6:42:12 PM";"EndTime"="25-Jul-16 6:42:12 PM"}	false	true (ByPropertyName)	
ConsistencyGroupSnapshot		false	true (ByPropertyName)	
ConsistencyGroupWafSync		false	true (ByPropertyName)	
ConsistencyGroupTimeout		false	true (ByPropertyName)	
SnapShotCreateCommand		false	true (ByPropertyName)	
UseFileSystemConsistentSnapshot		false	true (ByPropertyName)	
UseSnapcenterWithoutFileSystemConsistency		false	true (ByPropertyName)	
PreAppQuiesceCmd		false	true (ByPropertyName)	
PostAppQuiesceCmd		false	true (ByPropertyName)	
AppQuiesceCmd		false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
AppUnQuiesceCmd		false	true (ByPropertyName)	
PreAppUnQuiesceCmd		false	true (ByPropertyName)	
PostAppUnQuiesceCmd		false	true (ByPropertyName)	
PreExitCmd		false	true (ByPropertyName)	
PreSnapshotCmd		false	true (ByPropertyName)	
PostSnapshotCmd		false	true (ByPropertyName)	
ApplgnoreError		false	true (ByPropertyName)	
UseExternalSnapShot		false	true (ByPropertyName)	
ExternalSnapshotRegex		false	true (ByPropertyName)	
ConfigParams		false	true (ByPropertyName)	

Examples

Example 1: Modifying a custom Snapshot copy format

```
Set-SmResourceGroup -ResourceGroupName PayrollDataset
-CustomSnapshotFormat '$CustomText
$Dataset$Policy$HostName' -CustomText NetApp
```

This example syntax modifies a custom Snapshot copy format.

Example 2: Modifying a HANA custom Snapshot copy format

```
Set-SmResourceGroup -ResourceGroupName "RG1" -PluginCode HANA
-Resources
@{"Host"="hanahost01.testlab.netapp.com";"Uid"="MDC\R71"}
-CustomSnapshotFormat '$CustomText $Dataset$Policy$HostName'
-CustomText NetApp
```

This example syntax modifies a HANA custom Snapshot copy format.

Example 3: Deleting associated backups when detaching a policy from a resource group

```
Set-SmResourceGroup -ResourceGroupName "RG1" -PluginCode SCSQL
-Resources
    @{"Host"="WIN-DVGQDI73QR6";"Type"="SQL Database";"Names"="WIN-
DVGQDI73QR6\INST_SQL12\DB123} -Policy poly_full
    -DeleteBackupForDetachPolicies 1
```

This example syntax modifies a resource group to delete the backups associated with the policy when detaching the policy.

Example 4: Modifying an Oracle Plug-in resource group

```
Set-SmResourceGroup -ResourceGroupName 'mixedRG' -Resources
@(@{"Host"="R809278EA03V1.HNK2.com";"Oracle
Database"="DB11,DB12"},@{"Host"="R8092776CF4V1.HNK2.com";"Application
Volume"="appVol1,appVol3"}) -plugincode 'SCO' -Policies
'appVolPolicyModified'
```

This example syntax modifies the policy and resources of an Oracle Plug-in resource group.

Example 5: Modifying an UnixFileSystems Plug-in resource group

```
Set-SmResourceGroup -ResourceGroupName 'RG_PS_linuxfs201_LVM1_12648'
-Resources
@{"Host"="linuxfs201.gdl.englab.netapp.com";"Type"="UnixFileSystems";"uid"
="/netapp/VGNFS1/LVM1"} -plugincode 'UnixFileSystems' -Policies
'BackupPS_linuxfs201_LVM1_12648,Modified_BackupPS_linuxfs201_LVM1_12648'
```

This example syntax modifies the policy and resources of an UnixFileSystems Plug-in resource group.

```
Tag :
ByPassRunAs : False
Configuration : SMCoreContracts.SmBackupConfiguration
CreationTime: 12/12/2023 8:31:06 AM
CustomSnapshotFormat:
CustomText :
Description : Modifying UFS Resource Group
EmailBody :
EmailFrom :
EmailNotificationPreference :
EmailSMTPServer :
EmailSubject:
EmailTo :
```



```

    EnableAsupOnFailure :
    EnableEmail :
    EnableSysLog:
    HostResourceMaping  : {}
    IsCustomSnapshot:
    LastBackupStatus:
    MaintenanceStatus   : Production
    ModificationTime: 12/12/2023 8:31:06 AM
    PluginProtectionGroupTypes : {UnixFileSystems}
    Policies: {BackupPS_linuxfs201_LVM1_12648,
Modified_BackupPS_linuxfs201_LVM1_12648}
    ProtectionGroupType : Backup
    SchedulerSQLInstance:
    SearchResources : False
    VerificationServer :
    VerificationServerInfo :
    Name: RG_PS_linuxfs201_LVM1_12648
    Type: Group
    Id :
    Host:
    UserName:
    Passphrase :
    Deleted : False
    Auth: SMCoreContracts.SmAuth
    IsClone : False
    CloneLevel : 0
    Hosts :
    StorageName :
    ResourceGroupNames :
    PolicyNames :
    Key : 0
    NsmObjectID : 0
    SizeOfSmObject :

```

Set-SmResourceName

Enables you to set the system name for the specified HANA resource.

Syntax

```

Set-SetSmResourceName [-HostName] <SecureString> [-PluginCode]
<SecureString> [-ResourceId] <SecureString> [-ResourceName]
<SecureString>

```

Detailed Description

Enables you to set the resource name for the specified HANA resource. This cmdlet is applicable to auto discovered SAP-HANA resources only.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostName	Specifies the name or IP of the cluster or standalone host you want to add.	true	false	
PluginCode	Specifies the plug-in code of the host. Valid value is HANA.	true	false	
ResourceId	Unique ID of a HANA resource	true	false	
ResourceName	Specifies the new resource name.	true	false	

Examples

Example 1: Set the Resource Name of HANA resource

```
Set-SmResourceName -HostName "host01213.snapcenter.local" -PluginCode  
HANA -ResourceId "host01213.snapcenter.local\hana\MDC\R70" -ResourceName  
"NewResourceName"
```

This example syntax sets the resource name to the specified value.

Set-SmRole

Modifies an existing role.

Syntax

```
Set-SmRole [-Name] <String> [-Description] <String> [-Permissions]  
<String> [-AssignedUsers] <String> [-AssignedGroups] <String> [-  
SharedObjects] <> [-DeleteSharedObjects] <>
```

Detailed Description

Modifies an existing role. Enables you to modify assigned groups and users to the role, and to modify assigned SnapCenter resource permissions.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Name	Specifies the name of the role you want to modify.	true	true (ByPropertyName)	
Description	Describes the role you want to modify.	false	true (ByPropertyName)	
Permissions	Specifies the permissions for the role: Example: host:read,create,delete,update;dataset:create,update,dashboard,allowUse the format [<SnapCenter Resource Name>:<permission1 name>,<permission2 name>,...];[<SnapCenter Resource Name>...]]Permission settings for multiple SnapCenter resource names must be separated by ","The SnapCenter resource name is DataSet, Policy, Backup, Host, StorageConnection, Clone, Provision, DashBoard, Restore, Reports, Discovery, Plugin_Installation or Migration.The permission name is create, read, update, delete or allow.	false	true (ByPropertyName)	
AssignedUsers	Specifies users to be assigned to the role: Example: domain1\user1,domain2\user2	false	true (ByPropertyName)	
AssignedGroups	Specifies groups to be assigned to the role: Example: domain1\group1,domain2\group2	false	true (ByPropertyName)	
SharedObjects		false	true (ByPropertyName)	
DeleteSharedObjects		false	true (ByPropertyName)	

Examples

Example 1: Modify a role and assigning permissions, users, and groups

```
set-smrole -Name PayrollAppAdmin -Description "Manage payroll backup operations" -Permissions "DashBoard:allow;manageusergroup:allow;Plugin_Installation:read,update;DataSet:create,read,update,delete" -AssignedUsers "sddev\administrator" -AssignedGroups "mva\Administrators"
```

This example syntax modifies an existing role and assigns the specified permissions, users, and groups to the role.

```
Description : Manage payroll backup operations
Name: PayrollAppAdmin
Type:
Id :
Host:
UserName:
Passphrase :
Deleted : False
Auth: SMCoreContracts.SmAuth
IsClone : False
CloneLevel : 0
```

Set-SmSMTPServer

Specifies the SMTP server to use for sending data protection job reports to yourself or to others.

Syntax

```
Set-SmSMTPServer [-SMTPServerName] <String> [-EmailFrom] <String> [-
EmailTo] <String> [-IsSendEmail] <> [-EmailSubject] <String>
```

Detailed Description

Specifies the SMTP server to use for sending data protection job reports to yourself or to others. The settings are applied globally for any SnapCenter job for which you configure email notification.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
SMTPServerName	Specifies the name of the SMTP server.	true	true (ByPropertyName)	
EmailFrom	Specifies the sender's email address. This parameter is required when you configure an SMTP server.	true	true (ByPropertyName)	
EmailTo	Specifies the recipient's email address. This parameter is required when you configure an SMTP server.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
IsSendEmail	When specified, sends email to the SMTP server specified. This parameter is optional.	false	false	
EmailSubject	Specifies the subject of the email. This parameter is optional.	false	false	

Examples

Example 1

```
Set-SmSMTPServer smtp.gdl.englab.netapp.com -EmailFrom zhimao@netapp.com
-EmailTo zhimao@netapp.com -IsSendEmail -EmailSubject Hello
```

Set-SmSchedule

Creates a schedule using information you provide and also cleans up secondary backups according to that schedule.

Syntax

```
Set-SmSchedule [-ScheduleInformation] <Hashtable> [-TaskName] <String>
```

Detailed Description

Creates a schedule using information you provide and also cleans up secondary backups according to that schedule.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
ScheduleInformation	Specifies mandatory schedule information in a hashtable.	true	true (ByPropertyName)	
TaskName	Specifies the mandatory task name.	true	true (ByPropertyName)	

Examples

Example 1: Setting a schedule to remove secondary backups

```
Set-SmSchedule -ScheduleInformation
@{"ScheduleType"="Hourly";"StartTime"="10:10 AM" ;"EndTime"="11:00
AM";"RepeatTask_Every_Hour"="00:15"} -TaskName
SnapCenter_RemoveSecondaryBackup
```

This example syntax creates an hourly schedule with the task name SnapCenter_RemoveSecondaryBackup that repeats every 15 minutes.

```
TaskName      : SnapCenter_RemoveSecondaryBackup
Hosts         : {}
StartTime     : 5/14/2017 10:10:00 AM
DaysOfMonth   :
MonthsOfYear  :
DaysInterval  :
DaysOfWeek    :
AllowDefaults : False
ReplaceJobIfExist : False
UserName      :
Password      :
SchedulerType : Hourly
RepeatTask_Every_Hour : 0
IntervalDuration :
EndTime       : 5/14/2017 11:00:00 AM
LocalScheduler: False
AppType       : False
AuthMode      :
SchedulerSQLInstance : SMCoreContracts.SmObject
MonthlyFrequency :
Hour          : 0
Minute        : 0
NodeName      :
ScheduleID    : 0
RepeatTask_Every_Mins : 15
```

Set-SmServerConfig

Updates the SnapCenter Server URL in all or specified plug-in hosts.

Syntax

```
Set-SmServerConfig [-Credential] <PSCredential> [-  
UpdateSMSbaseUrlSwitchParameter] <SwitchParameter> [-HostNamesString]  
<String> [-OverwriteSmsUrlString] <String>
```

Detailed Description

Updates the SnapCenter Server URL in all or specified plug-in hosts.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Credential	Provide user credentials to update SnapCenter Server URL.	true	true (ByPropertyName)	
UpdateSMSbaseUrl	Update SnapCenter Server URL.	true	false	
HostNames	Specify comma separated host names.	false	false	
OverwriteSmsUrl	Overwrites SnapCenter Server URL.	false	false	

Examples

Example 1: Updating SnapCenter Server URL in all the plug-in hosts

```
Set-SmServerConfig -Credential sddev\administrator -UpdateSMSbaseUrl
```

This example updates the SnapCenter Server URL in all the plug-in hosts

```
Name: Configuring for SnapCenter Server URL
Id   : 21
StartTime   : 9/3/2019 5:25:10 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description   :
Status       : Running
Owner        :
Error        :
Priority      : None
Tasks        : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 38
ApisJobKey    :
ObjectId      : 0
PluginCode    : NONE
PluginName    : NONE
HostId        : 0
RoleId        :
JobIds        : {}
```

Example 2: Updating SnapCenter Server URL in the specified plug-in hosts

```
Set-SmServerConfig -UpdateSMSbaseUrl -HostNames 10.225.13.94,10.225.13.96
```

This example updates the SnapCenter Server URL in the specified plug-in hosts.


```

Name: Configuring for SnapCenter Server URL
Id : 21
StartTime : 9/3/2019 5:25:10 AM
EndTime :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible : True
IsScheduled : False
PercentageCompleted : 0
Description :
Status : Running
Owner :
Error :
Priority: None
Tasks : {}
ParentJobID : 0
EventId : 0
JobTypeId : 38
ApisJobKey :
ObjectId: 0
PluginCode : NONE
PluginName : NONE
HostId : 0
RoleId :
JobIds : {}

```

Set-SmStorageConnection

Modifies your existing storage system connections.

Syntax

```

Set-SmStorageConnection [-Storage] <String> [-Port] <UInt16> [-
Protocol] <ConnectProtocol> [-Timeout] <Int32> [-Credential]
<PSCredential> [-PreferredIP] <String> [-DisableAsupOnFailure] <> [-
DisableSysLog] <> [-Type] <StorageSystemType> [-NetAppAccountName]
<String> [-CredentialName] <String> [-StorageConnectionId]
<bigint(20)> [-CredentialId] <bigint(20)> [-ResourceGroup] <String>
[-SubscriptionId] <String> [-PlatformType] <String> [-IsSecondary] <>
[-RediscoverSVM] <>

```

Detailed Description

Modifies your existing storage system connections. You must create your storage system connection in advance of performing any provisioning or data protection jobs.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Storage		true	true (ByPropertyName)	
Port	Specifies the port for the storage system connection. 80 is the default port and is used if you omit the Port parameter.	false	true (ByPropertyName)	
Protocol	Specifies the communication protocol you want to use to connect to the storage system. Valid values is: HTTPS.	false	true (ByPropertyName)	
Timeout	Specifies the storage system timeout in seconds.	false	true (ByPropertyName)	
Credential	Specifies your storage system credentials. You must have created valid storage system credentials in advance.	false	true (ByPropertyName)	
PreferredIP	Specifies the preferred IP address for the storage system management or data LIF IP address.	false	true (ByPropertyName)	
DisableAsupOnFailure		false	true (ByPropertyName)	
DisableSysLog		false	true (ByPropertyName)	
Type	Specifies the type of storage.	false	true (ByPropertyName)	
NetAppAccountName	Specifies the Azure NetApp Account name.	false	true (ByPropertyName)	
StorageConnectionId	Specifies the Azure NetApp Account ID.	false	true (ByPropertyName)	
CredentialName	Specifies the Azure NetApp Credential name.	false	true (ByPropertyName)	
CredentialId	Specifies the Azure credential ID.	false	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
ResourceGroup	Specifies the resource group.	false	true (ByPropertyName)	
PlatformType	This optional parameter specifies the SVM platform type for licensing purposes. Possible values are Hardware and Software. Hardware indicates that you are using a FAS or All Flash FAS platform. Software indicates that you are using ONTAP Cloud or ONTAP Select. If you specify Type as ONTAP SVM as the storage connection type, and you do not specify PlatformType, the default value is set to Hardware.	false	true (ByPropertyName)	
IsSecondary		false	true (ByPropertyName)	
RediscoverSVM	This parameter is being deprecated in Snapcenter 6.1 and will no longer be supported in subsequent versions.	false	true (ByPropertyName)	

Examples

Example 1: Modifying a storage system connection

```
Set-SmStorageConnection -SVM 172.17.168.13 -Port 80 -Protocol Http
-Timeout 70
```

This example syntax modifies an existing storage system connection.

cmdlet Set-SmStorageConnection at command pipeline position 1

Supply values for the following parameters:

(Type !? for Help.)

Credential:

Set Storage connection successful

Example 2: Modifying a Azure NetApp Account

```
Set-SmStorageConnection -Type AzureNetAppAccount -StorageConnectionId 1
-NetAppAccountName "azureNetappAccount1_modified" -SubscriptionId
86c6cad7-8a2b-4c90-af3e-ba367c6dee47 -CredentialName "AzureCred1_modified"
-ResourceGroup "azure_rg1_modified"
```

This example modifies an existing Azure NetApp Account.

Example 3: Modifying a Azure NetApp Account

```
Set-SmStorageConnection -Type AzureNetAppAccount -StorageConnectionId 1  
-NetAppAccountName "azureNetappAccount1_modified" -CredentialId 2  
-ResourceGroup "azure_rgl_modified"
```

This example modifies an existing Azure NetApp Account.

Start-SmAuditIntegrityCheck

Triggers integrity check on Audit log files

Syntax

```
Start-SmAuditIntegrityCheck
```

Detailed Description

Triggers integrity check on Audit log files. Raises SnapCenter alert and Sends Email if integrity check fails

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
------	-------------	---------------	----------------	------------------

Examples

Example 1: Start Audit integrity check

```
Start-SmAuditIntegrityCheck
```

This example starts audit integrity check.

```
Name: Audit Log Integrity Check
Id   : 17
StartTime   : 12/14/2022 6:32:03 AM
EndTime    : 12/14/2022 6:32:03 AM
IsCancellable   : False
IsRestartable   : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 100
Description   :
Status       : Completed
```

Stop-SmJob

Stops a job that is in progress.

Syntax

```
Stop-SmJob [-JobId] <Int32>
```

Detailed Description

Stops a job that is in progress.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
JobId	The ID associated with the job you want to stop.	false	false	

Examples

Example 1: Stopping a job

```
Stop-SmJob -JobId 1002
```

This example syntax stops a job for the job ID specified.

Uncatalog-SmBackupWithOracleRMAN

Uncatalog Oracle backup(s).

Syntax

```
Uncatalog-SmBackupWithOracleRMAN [-PluginCode] <PluginCode> [-BackupIds]
<String> [-BackupNames] <String> [-AppObjectId] <String>
```

Detailed Description

Uncatalogs the Oracle Database backup(s) in SnapCenter with Oracle Recovery Manager (RMAN).

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
PluginCode	Specifies the plug-in code of the resource to be cataloged.	true	false	
BackupIds	Specifies the id of backup that need to be uncataloged. Multiple backup ids can be specified in a comma separated list.	false	false	
BackupNames	Specifies the name of the backup that need to be uncataloged. Multiple backup names can be specified in a comma separated list.	false	false	
AppObjectId	Specifies the ID of the application object.	false	true (ByPropertyName)	

Examples

Example 1: Uncataloging a SCO backup using backupId

```
Uncatalog-SmBackupWithOracleRMAN -PluginCode SCO -BackupId 7
```

This example syntax uncatalogs a SCO backup using backupId.

```
Name: Uncataloging Backup(s)
      scspr1894465002_gdl_englab_netapp_com_TSPITRDB_scspr1894465002_08-06-
2020_01.13.03.7681_1
Id   : 48
StartTime   : 8/7/2020 2:11:00 AM
EndTime    :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible    : True
IsScheduled  : False
PercentageCompleted : 0
Description :
Status      : Queued
Owner       :
Error       :
Priority: None
Tasks      : {}
ParentJobID : 0
EventId    : 0
JobTypeId  : 29
ApisJobKey :
ObjectId   : 0
PluginCode  : SCO
PluginName  : SnapCenter Plug-in for Oracle Database
HostId     : 0
RoleId     :
JobIds     : {}
```

Example 2: Uncataloging a SCO backup using backupname

```
Uncatalog-SmBackupWithOracleRMAN -PluginCode SCO -BackupName
scspr1894465002_gdl_englab_netapp_com_TSPITRDB_scspr1894465002_08-06-
2020_04.13.23.4083_1
```

This example syntax uncatalogs a SCO backup using backupname.

```
Name: Uncataloging Backup(s)
      scspr1894465002_gdl_englab_netapp_com_TSPITRDB_scspr1894465002_08-06-
2020_04.13.23.4083_1
Id   : 46
StartTime   : 8/7/2020 2:05:40 AM
EndTime    :
IsCancellable : False
IsRestartable : False
IsCompleted : False
IsVisible    : True
IsScheduled  : False
PercentageCompleted : 0
Description :
Status      : Queued
Owner       :
Error       :
Priority     : None
Tasks       : {}
ParentJobID : 0
EventId     : 0
JobTypeId   : 29
ApisJobKey   :
ObjectId     : 0
PluginCode   : SCO
PluginName   : SnapCenter Plug-in for Oracle Database
HostId      : 0
RoleId      :
JobIds      : {}
```

Example 3: Uncataloging a SCO backup for the desired database

```
Uncatalog-SmBackupWithOracleRMAN -PluginCode SCO -BackupName rg1_galaxy-
vm134_08-08-2020_15.11.16.3564_0 -AppObjectId 'galaxy-
vm134.gdl.englab.netapp.com\DB14'
```

This example syntax uncatalogs a SCO backup for the desired database.


```
Name: Uncataloging Backup(s)
    rg1_galaxy-vm134_08-08-2020_15.11.16.3564_1
Id   : 50
StartTime   : 8/7/2020 2:10:40 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled    : False
PercentageCompleted : 0
Description    :
Status        : Queued
Owner         :
Error         :
Priority       : None
Tasks         : {}
ParentJobID   : 0
EventId       : 0
JobTypeId     : 29
ApisJobKey    :
ObjectId      : 0
PluginCode    : SCO
PluginName    : SnapCenter Plug-in for Oracle Database
HostId        : 0
RoleId        :
JobIds        : {}
```

Uninstall-SmHostPackage

Uninstalls all host plug-in components from one or more hosts.

Syntax

```
Uninstall-SmHostPackage [-HostNames] <String> [-ApplicationCode]
<PluginCode> [-Force] <>
```

Detailed Description

Uninstalls all host plug-in components from one or more hosts. Because this cmdlet removes all host package components, you must confirm this operation before the uninstall proceeds with either Yes or No. The default is Yes.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostNames	Name of one or more hosts from which you want to uninstall all host package components. Host names must be entered using the format -HostNames @("hostname") when uninstalling from a single host, or -HostNames @("hostname1", "hostname2") when uninstalling from multiple hosts. You can specify the hostname using either the host FQDN or IP address.	true	true (ByPropertyName)	
ApplicationCode	Specifies the application code being uninstalled from the host. The valid values are SCW, SCSQL, SCO, and SCV. For custom plug-ins, enter the name of the custom plug-in. You must specify -ApplicationCode when using Oracle Real Application Clusters (RAC) to ensure that all nodes in the cluster are upgraded. If -ApplicationCode is not specified, the host package is uninstalled from only one RAC node.	false	true (ByPropertyName)	
Force		false	true (ByPropertyName)	
DoNotIncludeCluster Nodes	Specifies that host plug-in packages are not uninstalled on cluster nodes.	false	true (ByPropertyName)	

Examples

Example 1: Uninstalling all host package components from a host

```
Uninstall-SmHostPackage -HostNames @("host2012r2.mycompany.com")
```

This example syntax removes all host package components from the specified host.

Example 2: Uninstalling all host packages from multiple hosts

```
Uninstall-SmHostPackage -HostNames @("sql-1.mycompany.com", "sql-2.mycompany.com")
```

This example syntax uninstalls all host packages from the specified hosts.

Example 3: Uninstalling all host packages from an Oracle RAC

```
Uninstall-SmHostPackage -HostNames host.example.com -ApplicationCode SCO
```

This example syntax uninstalled all host packages from the specified host and uses the SCO application code to ensure that packages on all RAC nodes are uninstalled.

Update-SmBackup

Updates the raw device mapping (RDM) information of a backup.

Syntax

```
Update-SmBackup [-BackupId] <Int64> [-BackupName] <String> [-  
AccessPath] <String> [-DataStoreName] <String> [-RdmFileName]  
<String>
```

Detailed Description

Updates the raw device mapping (RDM) information of a backup.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
BackupId	Specifies the ID of the backup to update.	false	false	
BackupName	Specifies the name of the backup to update.	false	false	
AccessPath	Specifies the RDM file system's drive letter or mount point.	true	false	
DataStoreName	Specifies the datastore of the RDM file at the time of the backup.	true	false	
RdmFileName	Specifies the RDM file path at the time of the backup.	true	false	

Examples

Example 1: Update RDM information to backup

```
Update-SmBackup -BackupId 20 -AccessPath R:\ -DataStoreName "csmdev-SMSQL-ds02"
               -RdmFileName "[csmdev-SMSQL-ds02] csmdev-SMSQL-vm02\csmdev-SMSQL-vm02_1.vmdk"
```

```
Result      : SMCoreContracts.SMResult
TotalCount   : 0
DisplayCount : 0
Context      :
Job          : SMCoreContracts.SmJob
```

Update-SmHostPackage

Updates existing host plug-ins package for one or more specified hosts to the currently available plug-ins package version.

Syntax

```
Update-SmHostPackage [-HostNames] <String> [-SkipPreinstallChecks] <>
[-Force] <>
```

Detailed Description

Updates existing host plug-ins package for one or more specified hosts to the currently available plug-ins package version.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
HostNames	Name of one or more hosts for which you want to update the host package.Specifies the hosts on which you want to update the host package. You can specify one host, or multiple, comma-separated host names.Host names must be entered using the format -HostNames @"(hostname)" when installing to a single host, or -HostNames @"(hostname1", "hostname2") when installing to multiple hosts. You can specify the hostname using either the host FQDN or IP address.	true	true (ByPropertyName)	

Name	Description	Required ?	Pipeline Input	Default Value
SkipPreinstallChecks	Specifies that installation prechecks will not be triggered.	false	true (ByPropertyName)	
Force	Internal switch.	false	true (ByPropertyName)	

Examples

Example 1: Updating the host plug-ins package on a host

```
Update-SmHostPackage -HostNames @("host2012r2.mycompany.com")
```

This example syntax updates an existing host plug-ins package on a host to the currently available version.

Example 2: Updating the host plugin package on multiple hosts

```
Update-SmHostPackage -HostNames @("sql-1.mycompany.com", "sql-2.mycompany.com")
```

This example syntax updates existing host plug-in packages on multiple hosts to the currently available version.

Update-SmServerCluster

Updates the High Availability cluster configuration on the SnapCenter Server

Syntax

```
Update-SmServerCluster [-Credential] <PSCredential> [-ClusterNameString] <String> [-ClusterIPString] <String>
```

Detailed Description

Updates the High Availability cluster configuration on the SnapCenter Server. This can be used to update the cluster name or cluster IP Address.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
Credential	Provides domain user credentials for the user to update High Availability cluster configuration.	true	true (ByPropertyName)	
ClusterName	F5 cluster name.	false	false	
ClusterIP	F5 Cluster IP Address.	true	false	

Examples

Example 1: Updates High Availability cluster configuration on the SnapCenter Server

```
Update-SmServerCluster -Credential sddev\administrator -ClusterName
Sab_Pool_Update -ClusterIP 10.225.231.160
```

This example updates the High Availability cluster configuration on the SnapCenter Server.

```
Name: Modify High Availability for SnapCenter Server Configuration
Id   : 59
StartTime   : 10/7/2019 3:31:55 AM
EndTime    :
IsCancellable   : False
IsRestartable  : False
IsCompleted    : False
IsVisible      : True
IsScheduled     : False
PercentageCompleted : 0
Description    :
Status        : Running
Owner         :
Error         :
Priority       : None
Tasks         : {Update HA Parameters in SC Repository}
ParentJobID    : 0
EventId       : 0
JobTypeId      : 38
ApisJobKey     :
ObjectId       : 0
PluginCode     : NONE
PluginName     : NONE
HostId        : 0
RoleId        :
JobIds        : {}
Monitor the progress of job 59 in the Job Monitor page or by running the
cmdlet: 'Get-SmJobSummaryReport -JobId 59'
```

Upload-SmPluginPackage

Uploads a custom plug-in package to SnapCenter.

Syntax

```
Upload-SmPluginPackage [-FullPath] <String>
```

Detailed Description

A custom-developed plug-in is zipped along with plug-in description file. This zip file is uploaded to SnapCenter and is later pushed to specified host.

Parameters

Name	Description	Required ?	Pipeline Input	Default Value
FullPath	Specifies the path to the custom plug-in zip file.	true	false	

Examples

Example 1: Uploading a plugin from SnapCenter Server

```
Open-SmConnection -Credential nbsdsm\administrator
PS C:\Users\administrator.NBSDSM> Upload-SmPluginPackage
-AbsolutePath c:\Mongo1.zip
```

Uploading Custom named Mongo, version 1.0 from SnapCenter Server Host.

```
Successfully uploaded the plug-in package.
CustomPluginName: Mongo
CustomPluginVersion : 1.0
CustomPluginType: Mongo
OsInfo   : SMCoreContracts.SmOperatingSystemInfo
Resources : {SMCoreContracts.SmSCCustomResourceType}
RequireFileSystemPlugin : False
UploadedFileName: Mongo_1.0.zip
```

Example 2: Uploading a plugin from a nonSnapCenter Server Windows host

```
Upload-SmPluginPackage -AbsolutePath c:\customplugin\MongoDB_1.zip
-UserCredential nbsdsm\administrator
```

This example syntax uploads a custom plug-in named MongoDB, version 1.0 from a non-SnapCenter Server Windows Host.

```
Successfully uploaded the plug-in package.
CustomPluginName: MongoDB
CustomPluginVersion : 1.0
CustomPluginType: Perl
OsInfo   : SMCoreContracts.SmOperatingSystemInfo
Resources : {SMCoreContracts.SmSCCustomResourceType}
RequireFileSystemPlugin : False
UploadedFileName: DB2_1.0.zip
```


Legal notices

Legal notices provide access to copyright statements, trademarks, patents, and more.

Copyright

<https://www.netapp.com/company/legal/copyright/>

Trademarks

NETAPP, the NETAPP logo, and the marks listed on the NetApp Trademarks page are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.

<https://www.netapp.com/company/legal/trademarks/>

Patents

A current list of NetApp owned patents can be found at:

<https://www.netapp.com/pdf.html?item=/media/11887-patentspage.pdf>

Privacy policy

<https://www.netapp.com/company/legal/privacy-policy/>

Open source

Notice files provide information about third-party copyright and licenses used in NetApp software.

[Notice for SnapCenter 6.1](#)

Copyright information

Copyright © 2025 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.