

Understanding enabling or disabling of data protection in profile

SnapManager Oracle

Aksel Davis January 29, 2021

Table of Contents

Understanding enabling or disabling of data protection in profile	
---	--

Understanding enabling or disabling of data protection in profile

You can enable or disable data protection while creating or updating a database profile.

To create a protected backup of a database on the secondary storage resources, database administrators and storage administrators perform the following actions.

If you want to	Then
Create or edit a profile	 Enable backup protection to the secondary storage. If you are using Data ONTAP operating in 7-Mode and have installed Protection Manager, you can select the policies created by the storage or backup administrator in Protection Manager. If you are using Data ONTAP operating in 7-Mode and protection is enabled, SnapManager creates a dataset for the database. A dataset consists of a collection of storage sets along with configuration information associated with their data. The storage sets associated with a dataset include a primary storage set used to export data to clients, and the set of replicas and archives that exist on other storage sets. Datasets represent exportable user data. If the administrator disables protection for a database, SnapManager deletes the dataset. If you are using ONTAP, you must select either the SnapManager_cDOT_Mirror or SnapManager_cDOT_Vault policy depending on the SnapMirror or SnapVault relationship created. When you disable backup protection, a warning message is displayed stating that the dataset will be deleted and restoring or cloning backups for this profile will not be possible.
View the profile	Because the storage administrator has not yet assigned storage resources to implement the protection policy, the profile shows up as nonconformant in both the SnapManager graphical user interface and the profile show command output.

If you want to	Then
Assign storage resources in the Protection Manager Management Console	In the Protection Manager Management Console, the storage administrator views the unprotected dataset and assigns a resource pool for each node of the dataset that is associated with the profile. The storage administrator then makes sure that secondary volumes are provisioned and protection relationships are initialized.
View the conformant profile in SnapManager	In SnapManager, the database administrator sees that the profile has changed to conformant state in both the graphical user interface and in the profile show command output, indicating that resources were assigned.
Create the backup	Select full backup.
	 Also, select whether the backup should be protected and select the primary retention class (for example, hourly or daily).
	 If you are using Data ONTAP operating in 7-Mode and want to protect the backup immediately to secondary storage overriding the Protection Manager protection schedule, specify the -protectnow option.
	 If you are using ONTAP and want to protect the backup immediately to the secondary storage, specify the protect option.
	The protectnow option is not applicable in clustered Data ONTAP.
View the backup	The new backup is shown as scheduled for protection, but not yet protected (in the SnapManager interface and in the backup show command output). The Protection state is shown as "Not protected".
View the backup list	After the storage administrator verifies that the backup has been copied to secondary storage, SnapManager changes the backup Protection state from "Not protected" to "Protected".

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.