



Create pretask, post-task, and policy scripts

SnapManager for SAP

NetApp
February 20, 2023

Table of Contents

- Create pretask, post-task, and policy scripts 1
 - About this task 1
 - Sample script 2
 - Operations in task scripts 4
 - Variables available in the task scripts for the backup operation 6
 - Variables available in the task scripts for the restore operation 9
 - Variables available in the task scripts for clone operation 11
 - Error handling in custom scripts 12

Create pretask, post-task, and policy scripts

SnapManager enables you to create the scripts for the preprocessing activity, the post-processing activity, and policy tasks of the backup, restore, and clone operations. You must place the scripts in the correct installation directory to execute the preprocessing activity, post-processing activity, and policy tasks of the SnapManager operation.

About this task

Pretask and post-task script content

All scripts must include the following:

- Specific operations (check, describe, and execute)
- (Optional) Predefined environment variables
- Specific error handling code (return code (rc))



You must include correct error handling code to validate the script.

You can use the pretask scripts for many purposes, for example, cleaning up a disk space before the SnapManager operation starts. You can also use the post-task scripts, for instance, to estimate whether SnapManager has enough disk space to complete the operation.

Policy task script content

You can execute the policy script without using specific operations such as check, describe, and execute. The script includes the predefined environmental variables (optional) and specific error handling code.

The policy script is executed before the backup, restore, and clone operations.

Supported format

A command file with a .cmd extension can be used as the prescript and post-script.



If you select the shell script file, the SnapManager operation does not respond. To resolve this, you must provide the command file in the plug-in directory, and perform the SnapManager operation again.

Script installation directory

The directory in which you install the script affects how it is used. You can place the scripts in the directory and execute the script before or after the backup, restore, or clone operation takes place. You must place the script in the directory specified in the table and use it on an optional basis when you specify the backup, restore, or clone operation.



You must ensure that the plugins directory has the executable permission before using the scripts for the SnapManager operation.

Activity	Backup	Restore	Clone
Preprocessing	<default_installation_directory>\plugins\backup\create\pre	<default_installation_directory>\plugins\restore\create\pre	<default_installation_directory>\plugins\clone\create\pre
Post-processing	<default_installation_directory>\plugins\backup\create\post	<default_installation_directory>\plugins\restore\create\post	<default_installation_directory>\plugins\clone\create\post
Policy-based	<default_installation_directory>\plugins\backup\create\policy	<default_installation_directory>\plugins\restore\create\policy	<default_installation_directory>\plugins\clone\create\policy

Sample scripts locations

The following are some samples of the pretask and post-task scripts for the backup and clone operations available in the installation directory path:

- <default_installation_directory>\plugins\examples\backup\create\pre
- <default_installation_directory>\plugins\examples\backup\create\post
- <default_installation_directory>\plugins\examples\clone\create\pre
- <default_installation_directory>\plugins\examples\clone\create\post

What you can change in the script

If you are creating a new script, you can change only the describe and execute operations. Each script must contain the following variables: `context`, `timeout`, and `parameter`.

The variables you have described in the describe function of the script must be declared at the start of the script. You can add new parameter values in `parameter=()` and then use the parameters in the execute function.

Sample script

The following is a sample script with a user-specified return code for estimating the space in the SnapManager host:

```
@echo off
REM $Id:
//depot/prod/capstan/Rcapstan_ganges/src/plugins/windows/examples/clone/create/policy/validate_sid.cmd#1 $
REM $Revision: #1 $ $Date: 2011/12/06 $
REM
REM
set /a EXIT=0
```

```

set name="Validate SID"
set description="Validate SID used on the target system"
set parameter=()

rem reserved system IDs
set INVALID_SIDS=("ADD" "ALL" "AND" "ANY" "ASC" "COM" "DBA" "END" "EPS"
"FOR" "GID" "IBM" "INT" "KEY" "LOG" "MON" "NIX" "NOT" "OFF" "OMS" "RAW"
"ROW" "SAP" "SET" "SGA" "SHG" "SID" "SQL" "SYS" "TMP" "UID" "USR" "VAR")

if /i "%1" == "-check" goto :check
if /i "%1" == "-execute" goto :execute
if /i "%1" == "-describe" goto :describe

:usage:
    echo usage: %0 "{ -check | -describe | -execute }"
    set /a EXIT=99
    goto :exit

:check
    set /a EXIT=0
    goto :exit

:describe
    echo SM_PI_NAME:%name%
    echo SM_PI_DESCRIPTION:%description%
    set /a EXIT=0
    goto :exit

:execute
    set /a EXIT=0

    rem SM_TARGET_SID must be set
    if "%SM_TARGET_SID%" == "" (
        set /a EXIT=4
        echo SM_TARGET_SID not set
        goto :exit
    )

    rem exactly three alphanumeric characters, with starting with a letter
    echo %SM_TARGET_SID% | findstr "\<[a-zA-Z][a-zA-Z0-9][a-zA-Z0-9]\>"
>nul
    if %ERRORLEVEL% == 1 (
        set /a EXIT=4
        echo SID is defined as a 3 digit value starting with a letter.
[%SM_TARGET_SID%] is not valid.
        goto :exit
    )

```

```

)

rem not a SAP reserved SID
echo %INVALID_SIDS% | findstr /i \"%SM_TARGET_SID%\" >nul
if %ERRORLEVEL% == 0 (
    set /a EXIT=4
    echo SID [%SM_TARGET_SID%] is reserved by SAP
    goto :exit
)

goto :exit

:exit
echo Command complete.
exit /b %EXIT%

```

Operations in task scripts

The pretask or post-task scripts that you create must follow a standard SnapManager for SAP plug-in structure.

The pretask and post-task scripts must include the following operations:

- check
- describe
- execute

If any one of these operations is not specified in the pretask or post-task script, then the script becomes invalid.

When you run the `smsap plugin check` command for the pretask or post-task scripts, the returned status of the scripts display error (because the returned status value is not zero).

Operation	Description
check	The SnapManager server runs the <code>plugin.sh -check</code> command to ensure that the system has execution permission on the plug-in scripts. You might also include file permission checking on the remote system.

Operation	Description
describe	<p>The SnapManager server runs the <code>plugin.sh -describe</code> command to obtain information about your script and match the elements provided by the specification file. Your plug-in script must contain the following description information:</p> <ul style="list-style-type: none"> • <code>SM_PI_NAME</code>: Script name. You must provide a value for this parameter. • <code>SM_PI_DESCRIPTION</code>: Description of the script's purpose. You must provide a value for this parameter. • <code>SM_PI_CONTEXT</code>: Context in which the script should run—for example, <code>root</code> or <code>orasis</code>. You must provide a value for this parameter. • <code>SM_PI_TIMEOUT</code>: The maximum time (in milliseconds) that SnapManager should wait for the script to complete processing and terminate execution. You must provide a value for this parameter. • <code>SM_PI_PARAMETER</code>: One or more custom parameters necessary for your plug-in script to perform processing. Each parameter should be listed in a new output line and include the name of the parameter and a description. When the script completes processing, the parameter value will be provided to your script by an environment variable. <p>The following is the sample output of the <code>Followup_activities</code> script.</p> <pre style="background-color: #f0f0f0; padding: 10px;"> plugin.sh - describe SM_PI_NAME:Followup_activities SM_PI_DESCRIPTION:this script contains follow-up activities to be executed after the clone create operation. SM_PI_CONTEXT:root SM_PI_TIMEOUT:60000 SM_PI_PARAMETER:SCHEMAOWNER:Name of the database schema owner. Command complete.</pre>




Operation	Description
execute	The SnapManager server runs the <code>plugin.sh -execute</code> command to start your script to execute the script.





Variables available in the task scripts for the backup operation

SnapManager provides context information in the form of environment variables related to the backup operation that is being performed. For example, your script can retrieve the name of the original host, the name of the retention policy, and the label of the backup.

The following table lists the environment variables that you can use in your scripts:

Variables	Description	Format
<i>SM_OPERATION_ID</i>	Specifies the ID of the current operation	string
<i>SM_PROFILE_NAME</i>	Specifies the name of the profile used	string
<i>SM_SID</i>	Specifies the system identifier of the database	string
<i>SM_HOST</i>	Specifies the host name of the database	string
<i>SM_OS_USER</i>	Specifies the operating system (OS) owner of the database	string
<i>SM_OS_GROUP</i>	Specifies the OS group of the database	string
<i>SM_BACKUP_TYPE</i>	Specifies the type of the backup (online, offline, or auto)	string
<i>SM_BACKUP_LABEL</i>	Specifies the label of the backup	string
<i>SM_BACKUP_ID</i>	Specifies the ID of the backup	string
<i>SM_BACKUP_RETENTION</i>	Specifies the retention period	string
<i>SM_BACKUP_PROFILE</i>	Specifies the profile used for this backup	string

Variables	Description	Format
<i>SM_ALLOW_DATABASE_SHUTDOWN</i>	Specifies if you want to start up or shut down the database. If required, you can use the <code>-force</code> option from the command-line interface.	boolean
<i>SM_BACKUP_SCOPE</i>	Specifies the scope of the backup (full or partial)	string
<i>SM_TARGET_FILER_NAME</i>	Specifies the target storage system name  If more than one storage system is used, then the storage system names must be separated by commas.	string
<i>SM_TARGET_VOLUME_NAME</i>	Specifies the target volume name  The target volume name must be prefixed with storage device name, for example, <code>SM_TARGET_FILER_NAME/SM_TARGET_VOLUME_NAME</code> .	string
<i>SM_HOST_FILE_SYSTEM</i>	Specifies the host file system	string
<i>SM_SNAPSHOT_NAMES</i>	Specifies the Snapshot list  Name of the Snapshot copies must be prefixed with the storage system name and volume name. Names of the Snapshot copies are separated by commas.	string array


Variables	Description	Format
<i>SM_ARCHIVE_LOGS_DIRECTORY</i>	Specifies the archive logs directory <div style="border-left: 1px solid #ccc; padding-left: 10px; margin-top: 10px;">  <p>If the archive logs are located in more than one directory, then the names of those directories are separated by commas.</p> </div>	string array
<i>SM_REDO_LOGS_DIRECTORY</i>	Specifies the redo logs directory <div style="border-left: 1px solid #ccc; padding-left: 10px; margin-top: 10px;">  <p>If the redo logs are located in more than one directory, then the names of those directories are separated by commas.</p> </div>	string array
<i>SM_CONTROL_FILES_DIRECTORY</i>	Specifies the control files directory <div style="border-left: 1px solid #ccc; padding-left: 10px; margin-top: 10px;">  <p>If the control files are located in more than one directory, then the names of those directories are separated by commas.</p> </div>	string array
<i>SM_DATA_FILES_DIRECTORY</i>	Specifies the data files directory <div style="border-left: 1px solid #ccc; padding-left: 10px; margin-top: 10px;">  <p>If the data files are located in more than one directory, then the names of those directories are separated by commas.</p> </div>	string array
<i>user_defined</i>	Specifies additional parameters defined by the user. User-defined parameters are not available for plug-ins that are used as policies.	user-defined




Variables available in the task scripts for the restore operation

SnapManager provides context information in the form of environment variables related to the restore operation that is being performed. For example, your script can retrieve the name of the original host and the label of the backup that is restored.

The following table lists the environment variables that you can use in your scripts:

Variables	Description	Format
<i>SM_OPERATION_ID</i>	Specifies the ID of the current operation	string
<i>SM_PROFILE_NAME</i>	Specifies the name of the profile used	string
<i>SM_HOST</i>	Specifies the host name of the database	string
<i>SM_OS_USER</i>	Specifies the operating system (OS) owner of the database	string
<i>SM_OS_GROUP</i>	Specifies the OS group of the database	string
<i>SM_BACKUP_TYPE</i>	Specifies the type of the backup (online, offline, or auto)	string
<i>SM_BACKUP_LABEL</i>	Specifies the backup label	string
<i>SM_BACKUP_ID</i>	Specifies the backup ID	string
<i>SM_BACKUP_PROFILE</i>	Specifies the profile used for the backup	string
<i>SM_RECOVERY_TYPE</i>	Specifies the recovery configuration information	string
<i>SM_VOLUME_RESTORE_MODE</i>	Specifies the volume restore configuration	string

Variables	Description	Format
<i>SM_TARGET_FILER_NAME</i>	<p>Specifies the target storage system name</p> <p> If more than one storage system is used, then the storage system names must be separated by commas.</p>	string
<i>SM_TARGET_VOLUME_NAME</i>	<p>Specifies the target volume name</p> <p> The target volume name must be prefixed with storage device name, for example, <i>SM_TARGET_FILER_NAME/SM_TARGET_VOLUME_NAME</i>.</p>	string
<i>SM_HOST_FILE_SYSTEM</i>	<p>Specifies the host file system</p>	string
<i>SM_SNAPSHOT_NAMES</i>	<p>Specifies the Snapshot list</p> <p> Name of the Snapshot copies must be prefixed with the storage system name and volume name. Names of the Snapshot copies are separated by commas.</p>	string array
<i>SM_ARCHIVE_LOGS_DIRECTORY</i>	<p>Specifies the archive logs directory</p> <p> If the archive logs are located in more than one directory, then the names of those directories are separated by commas.</p>	string array

Variables	Description	Format
<i>SM_REDO_LOGS_DIRECTORY</i>	<p>Specifies the redo logs directory</p> <p> If the redo logs are located in more than one directory, then the names of those directories are separated by commas.</p>	string array
<i>SM_CONTROL_FILES_DIRECTORY</i>	<p>Specifies the control files directory</p> <p> If the control files are located in more than one directory, then the names of those directories are separated by commas.</p>	string array
<i>SM_DATA_FILES_DIRECTORY</i>	<p>Specifies the data files directory</p> <p> If the data files are located in more than one directory, then the names of those directories are separated by commas.</p>	string array

Variables available in the task scripts for clone operation

SnapManager provides context information in the form of environment variables related to the clone operation being performed. For example, your script can retrieve the name of the original host, the name of the clone database, and the label of the backup.

The following table lists the environment variables that you can use in your scripts:

Variables	Description	Format
<i>SM_ORIGINAL_SID</i>	SID of the original database	string
<i>SM_ORIGINAL_HOST</i>	Host name associated with the original database	string
<i>SM_ORIGINAL_OS_USER</i>	OS owner of the original database	string

Variables	Description	Format
<i>SM_ORIGINAL_OS_GROUP</i>	OS group of the original database	string
<i>SM_TARGET_SID</i>	SID of the clone database	string
<i>SM_TARGET_HOST</i>	Host name associated with the clone database	string
<i>SM_TARGET_OS_USER</i>	OS owner of the clone database	string
<i>SM_TARGET_OS_GROUP</i>	OS group of the clone database	string
<i>SM_TARGET_DB_PORT</i>	Port of the target database	integer
<i>SM_TARGET_GLOBAL_DB_NAME</i>	Global database name of the target database	string
<i>SM_BACKUP_LABEL</i>	Label of the backup used for the clone	string

Error handling in custom scripts

SnapManager processes the custom script based on the specific return codes. For example, if your custom script returns a value of 0, 1, 2, or 3, SnapManager continues with the clone process. The return code also influences how SnapManager processes and returns the standard output of your script execution.

Return code	Description	Continue processing the operation
0	The script completed successfully.	Yes
1	The script completed successfully, with informational messages.	Yes
2	The script completed, but includes warnings	Yes
3	The script fails, but the operation continues.	Yes
4 or >4	The script fails and the operation stops.	No

Copyright information

Copyright © 2023 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.