



Reference

Astra Trident

NetApp
October 31, 2024

Table of Contents

- Reference 1
 - Astra Trident ports 1
 - Astra Trident REST API 1
 - Command-line options 2
 - Kubernetes and Trident objects 3
 - Pod Security Standards (PSS) and Security Context Constraints (SCC) 15

Reference

Astra Trident ports

Learn more about the ports that Astra Trident uses for communication.

Astra Trident ports

Astra Trident communicates over the following ports:

Port	Purpose
8443	Backchannel HTTPS
8001	Prometheus metrics endpoint
8000	Trident REST server
17546	Liveness/readiness probe port used by Trident daemonset pods



The liveness/readiness probe port can be changed during installation using the `--probe-port` flag. It is important to make sure this port isn't being used by another process on the worker nodes.

Astra Trident REST API

While [tridentctl commands and options](#) are the easiest way to interact with the Astra Trident REST API, you can use the REST endpoint directly if you prefer.

When to use the REST API

REST API is useful for advanced installations that use Astra Trident as a standalone binary in non-Kubernetes deployments.

For better security, the Astra Trident REST API is restricted to localhost by default when running inside a pod. To change this behavior, you need to set Astra Trident's `-address` argument in its pod configuration.

Using REST API

For examples of how these APIs are called, pass the debug (`-d`) flag. For more information, refer to [Manage Astra Trident using tridentctl](#).

The API works as follows:

GET

GET `<trident-address>/trident/v1/<object-type>`

Lists all objects of that type.

GET <trident-address>/trident/v1/<object-type>/<object-name>

Gets the details of the named object.

POST

POST <trident-address>/trident/v1/<object-type>

Creates an object of the specified type.

- Requires a JSON configuration for the object to be created. For the specification of each object type, refer to [Manage Astra Trident using tridentctl](#).
- If the object already exists, behavior varies: backends update the existing object, while all other object types will fail the operation.

DELETE

DELETE <trident-address>/trident/v1/<object-type>/<object-name>

Deletes the named resource.



Volumes associated with backends or storage classes will continue to exist; these must be deleted separately. For more information, refer to [Manage Astra Trident using tridentctl](#).

Command-line options

Astra Trident exposes several command-line options for the Trident orchestrator. You can use these options to modify your deployment.

Logging

-debug

Enables debugging output.

-loglevel <level>

Sets the logging level (debug, info, warn, error, fatal). Defaults to info.

Kubernetes

-k8s_pod

Use this option or `-k8s_api_server` to enable Kubernetes support. Setting this causes Trident to use its containing pod's Kubernetes service account credentials to contact the API server. This only works when Trident runs as a pod in a Kubernetes cluster with service accounts enabled.

-k8s_api_server <insecure-address:insecure-port>

Use this option or `-k8s_pod` to enable Kubernetes support. When specified, Trident connects to the Kubernetes API server using the provided insecure address and port. This allows Trident to be deployed outside of a pod; however, it only supports insecure connections to the API server. To connect securely, deploy Trident in a pod with the `-k8s_pod` option.

Docker

-volume_driver <name>

Driver name used when registering the Docker plugin. Defaults to `netapp`.

-driver_port <port-number>

Listen on this port rather than a UNIX domain socket.

-config <file>

Required; you must specify this path to a backend configuration file.

REST

-address <ip-or-host>

Specifies the address on which Trident's REST server should listen. Defaults to `localhost`. When listening on `localhost` and running inside a Kubernetes pod, the REST interface isn't directly accessible from outside the pod. Use `-address ""` to make the REST interface accessible from the pod IP address.



Trident REST interface can be configured to listen and serve at `127.0.0.1` (for IPv4) or `:::1` (for IPv6) only.

-port <port-number>

Specifies the port on which Trident's REST server should listen. Defaults to `8000`.

-rest

Enables the REST interface. Defaults to `true`.

Kubernetes and Trident objects

You can interact with Kubernetes and Trident using REST APIs by reading and writing resource objects. There are several resource objects that dictate the relationship between Kubernetes and Trident, Trident and storage, and Kubernetes and storage. Some of these objects are managed through Kubernetes and the others are managed through Trident.

How do the objects interact with one another?

Perhaps the easiest way to understand the objects, what they are for, and how they interact, is to follow a single request for storage from a Kubernetes user:

1. A user creates a `PersistentVolumeClaim` requesting a new `PersistentVolume` of a particular size from a Kubernetes `StorageClass` that was previously configured by the administrator.
2. The Kubernetes `StorageClass` identifies Trident as its provisioner and includes parameters that tell Trident how to provision a volume for the requested class.
3. Trident looks at its own `StorageClass` with the same name that identifies the matching `Backends` and `StoragePools` that it can use to provision volumes for the class.
4. Trident provisions storage on a matching backend and creates two objects: a `PersistentVolume` in

Kubernetes that tells Kubernetes how to find, mount, and treat the volume, and a volume in Trident that retains the relationship between the `PersistentVolume` and the actual storage.

5. Kubernetes binds the `PersistentVolumeClaim` to the new `PersistentVolume`. Pods that include the `PersistentVolumeClaim` mount that `PersistentVolume` on any host that it runs on.
6. A user creates a `VolumeSnapshot` of an existing PVC, using a `VolumeSnapshotClass` that points to Trident.
7. Trident identifies the volume that is associated with the PVC and creates a snapshot of the volume on its backend. It also creates a `VolumeSnapshotContent` that instructs Kubernetes on how to identify the snapshot.
8. A user can create a `PersistentVolumeClaim` using `VolumeSnapshot` as the source.
9. Trident identifies the required snapshot and performs the same set of steps involved in creating a `PersistentVolume` and a `Volume`.



For further reading about Kubernetes objects, we highly recommend that you read the [Persistent Volumes](#) section of the Kubernetes documentation.

Kubernetes `PersistentVolumeClaim` objects

A Kubernetes `PersistentVolumeClaim` object is a request for storage made by a Kubernetes cluster user.

In addition to the standard specification, Trident allows users to specify the following volume-specific annotations if they want to override the defaults that you set in the backend configuration:

Annotation	Volume Option	Supported Drivers
<code>trident.netapp.io/fileSystem</code>	<code>fileSystem</code>	ontap-san, solidfire-san,ontap-san-economy
<code>trident.netapp.io/cloneFromPVC</code>	<code>cloneSourceVolume</code>	ontap-nas, ontap-san, solidfire-san, azure-netapp-files, gcp-cvs, ontap-san-economy
<code>trident.netapp.io/splitOnClone</code>	<code>splitOnClone</code>	ontap-nas, ontap-san
<code>trident.netapp.io/protocol</code>	<code>protocol</code>	any
<code>trident.netapp.io/exportPolicy</code>	<code>exportPolicy</code>	ontap-nas, ontap-nas-economy, ontap-nas-flexgroup
<code>trident.netapp.io/snapshotPolicy</code>	<code>snapshotPolicy</code>	ontap-nas, ontap-nas-economy, ontap-nas-flexgroup, ontap-san
<code>trident.netapp.io/snapshotReserve</code>	<code>snapshotReserve</code>	ontap-nas, ontap-nas-flexgroup, ontap-san, gcp-cvs
<code>trident.netapp.io/snapshotDirectory</code>	<code>snapshotDirectory</code>	ontap-nas, ontap-nas-economy, ontap-nas-flexgroup

Annotation	Volume Option	Supported Drivers
trident.netapp.io/unixPermissions	unixPermissions	ontap-nas, ontap-nas-economy, ontap-nas-flexgroup
trident.netapp.io/blockSize	blockSize	solidfire-san

If the created PV has the `Delete` reclaim policy, Trident deletes both the PV and the backing volume when the PV becomes released (that is, when the user deletes the PVC). Should the delete action fail, Trident marks the PV as such and periodically retries the operation until it succeeds or the PV is manually deleted. If the PV uses the `Retain` policy, Trident ignores it and assumes the administrator will clean it up from Kubernetes and the backend, allowing the volume to be backed up or inspected before its removal. Note that deleting the PV does not cause Trident to delete the backing volume. You should remove it using the REST API (`tridentctl`).

Trident supports the creation of Volume Snapshots using the CSI specification: you can create a Volume Snapshot and use it as a Data Source to clone existing PVCs. This way, point-in-time copies of PVs can be exposed to Kubernetes in the form of snapshots. The snapshots can then be used to create new PVs. Take a look at `On-Demand Volume Snapshots` to see how this would work.

Trident also provides the `cloneFromPVC` and `splitOnClone` annotations for creating clones. You can use these annotations to clone a PVC without having to use the CSI implementation.

Here is an example: If a user already has a PVC called `mysql`, the user can create a new PVC called `mysqlclone` by using the annotation, such as `trident.netapp.io/cloneFromPVC: mysql`. With this annotation set, Trident clones the volume corresponding to the `mysql` PVC, instead of provisioning a volume from scratch.

Consider the following points:

- We recommend cloning an idle volume.
- A PVC and its clone should be in the same Kubernetes namespace and have the same storage class.
- With the `ontap-nas` and `ontap-san` drivers, it might be desirable to set the PVC annotation `trident.netapp.io/splitOnClone` in conjunction with `trident.netapp.io/cloneFromPVC`. With `trident.netapp.io/splitOnClone` set to `true`, Trident splits the cloned volume from the parent volume and thus, completely decoupling the life cycle of the cloned volume from its parent at the expense of losing some storage efficiency. Not setting `trident.netapp.io/splitOnClone` or setting it to `false` results in reduced space consumption on the backend at the expense of creating dependencies between the parent and clone volumes such that the parent volume cannot be deleted unless the clone is deleted first. A scenario where splitting the clone makes sense is cloning an empty database volume where it's expected for the volume and its clone to greatly diverge and not benefit from storage efficiencies offered by ONTAP.

The `sample-input` directory contains examples of PVC definitions for use with Trident. Refer to [\[Trident Volume objects\]](#) for a full description of the parameters and settings associated with Trident volumes.

Kubernetes PersistentVolume objects

A Kubernetes `PersistentVolume` object represents a piece of storage that is made available to the Kubernetes cluster. It has a lifecycle that is independent of the pod that uses it.



Trident creates `PersistentVolume` objects and registers them with the Kubernetes cluster automatically based on the volumes that it provisions. You are not expected to manage them yourself.

When you create a PVC that refers to a Trident-based `StorageClass`, Trident provisions a new volume using the corresponding storage class and registers a new PV for that volume. In configuring the provisioned volume and corresponding PV, Trident follows the following rules:

- Trident generates a PV name for Kubernetes and an internal name that it uses to provision the storage. In both cases, it is assuring that the names are unique in their scope.
- The size of the volume matches the requested size in the PVC as closely as possible, though it might be rounded up to the nearest allocatable quantity, depending on the platform.

Kubernetes `StorageClass` objects

Kubernetes `StorageClass` objects are specified by name in `PersistentVolumeClaims` to provision storage with a set of properties. The storage class itself identifies the provisioner to be used and defines that set of properties in terms the provisioner understands.

It is one of two basic objects that need to be created and managed by the administrator. The other is the Trident backend object.

A Kubernetes `StorageClass` object that uses Trident looks like this:

```
apiVersion: storage.k8s.io/v1
kind: StorageClass
metadata:
  name: <Name>
provisioner: csi.trident.netapp.io
mountOptions: <Mount Options>
parameters:
  <Trident Parameters>
allowVolumeExpansion: true
volumeBindingMode: Immediate
```

These parameters are Trident-specific and tell Trident how to provision volumes for the class.

The storage class parameters are:

Attribute	Type	Required	Description
attributes	map[string]string	no	See the attributes section below
storagePools	map[string]StringList	no	Map of backend names to lists of storage pools within

Attribute	Type	Required	Description
additionalStoragePools	map[string]StringList	no	Map of backend names to lists of storage pools within
excludeStoragePools	map[string]StringList	no	Map of backend names to lists of storage pools within

Storage attributes and their possible values can be classified into storage pool selection attributes and Kubernetes attributes.

Storage pool selection attributes

These parameters determine which Trident-managed storage pools should be utilized to provision volumes of a given type.

Attribute	Type	Values	Offer	Request	Supported by
media ¹	string	hdd, hybrid, ssd	Pool contains media of this type; hybrid means both	Media type specified	ontap-nas, ontap-nas-economy, ontap-nas-flexgroup, ontap-san, solidfire-san
provisioningType	string	thin, thick	Pool supports this provisioning method	Provisioning method specified	thick: all ontap; thin: all ontap & solidfire-san
backendType	string	ontap-nas, ontap-nas-economy, ontap-nas-flexgroup, ontap-san, solidfire-san, gcp-cvs, azure-netapp-files, ontap-san-economy	Pool belongs to this type of backend	Backend specified	All drivers
snapshots	bool	true, false	Pool supports volumes with snapshots	Volume with snapshots enabled	ontap-nas, ontap-san, solidfire-san, gcp-cvs
clones	bool	true, false	Pool supports cloning volumes	Volume with clones enabled	ontap-nas, ontap-san, solidfire-san, gcp-cvs

Attribute	Type	Values	Offer	Request	Supported by
encryption	bool	true, false	Pool supports encrypted volumes	Volume with encryption enabled	ontap-nas, ontap-nas-economy, ontap-nas-flexgroups, ontap-san
IOPS	int	positive integer	Pool is capable of guaranteeing IOPS in this range	Volume guaranteed these IOPS	solidfire-san

¹: Not supported by ONTAP Select systems

In most cases, the values requested directly influence provisioning; for instance, requesting thick provisioning results in a thickly provisioned volume. However, an Element storage pool uses its offered IOPS minimum and maximum to set QoS values, rather than the requested value. In this case, the requested value is used only to select the storage pool.

Ideally, you can use `attributes` alone to model the qualities of the storage you need to satisfy the needs of a particular class. Trident automatically discovers and selects storage pools that match *all* of the `attributes` that you specify.

If you find yourself unable to use `attributes` to automatically select the right pools for a class, you can use the `storagePools` and `additionalStoragePools` parameters to further refine the pools or even to select a specific set of pools.

You can use the `storagePools` parameter to further restrict the set of pools that match any specified `attributes`. In other words, Trident uses the intersection of pools identified by the `attributes` and `storagePools` parameters for provisioning. You can use either parameter alone or both together.

You can use the `additionalStoragePools` parameter to extend the set of pools that Trident uses for provisioning, regardless of any pools selected by the `attributes` and `storagePools` parameters.

You can use the `excludeStoragePools` parameter to filter the set of pools that Trident uses for provisioning. Using this parameter removes any pools that match.

In the `storagePools` and `additionalStoragePools` parameters, each entry takes the form `<backend>:<storagePoolList>`, where `<storagePoolList>` is a comma-separated list of storage pools for the specified backend. For example, a value for `additionalStoragePools` might look like `ontapnas_192.168.1.100:aggr1,aggr2;solidfire_192.168.1.101:bronze`. These lists accept regex values for both the backend and list values. You can use `tridentctl get backend` to get the list of backends and their pools.

Kubernetes attributes

These attributes have no impact on the selection of storage pools/backends by Trident during dynamic provisioning. Instead, these attributes simply supply parameters supported by Kubernetes Persistent Volumes. Worker nodes are responsible for filesystem create operations and might require filesystem utilities, such as `xfsprogs`.

Attribute	Type	Values	Description	Relevant Drivers	Kubernetes Version
fsType	string	ext4, ext3, xfs, etc.	The file system type for block volumes	solidfire-san, ontap-nas, ontap-nas-economy, ontap-nas-flexgroup, ontap-san, ontap-san-economy	All
allowVolumeExpansion	boolean	true, false	Enable or disable support for growing the PVC size	ontap-nas, ontap-nas-economy, ontap-nas-flexgroup, ontap-san, ontap-san-economy, solidfire-san, gcp-cvs, azure-netapp-files	1.11+
volumeBindingMode	string	Immediate, WaitForFirstConsumer	Choose when volume binding and dynamic provisioning occurs	All	1.19 - 1.26

- The `fsType` parameter is used to control the desired file system type for SAN LUNs. In addition, Kubernetes also uses the presence of `fsType` in a storage class to indicate a filesystem exists. Volume ownership can be controlled using the `fsGroup` security context of a pod only if `fsType` is set. Refer to [Kubernetes: Configure a Security Context for a Pod or Container](#) for an overview on setting volume ownership using the `fsGroup` context. Kubernetes will apply the `fsGroup` value only if:



- `fsType` is set in the storage class.
- The PVC access mode is RWO.

For NFS storage drivers, a filesystem already exists as part of the NFS export. In order to use `fsGroup` the storage class still needs to specify a `fsType`. You can set it to `nfs` or any non-null value.

- Refer to [Expand volumes](#) for further details on volume expansion.
- The Trident installer bundle provides several example storage class definitions for use with Trident in `sample-input/storage-class-*.yaml`. Deleting a Kubernetes storage class causes the corresponding Trident storage class to be deleted as well.

Kubernetes VolumeSnapshotClass objects

Kubernetes `VolumeSnapshotClass` objects are analogous to `StorageClasses`. They help define multiple classes of storage and are referenced by volume snapshots to associate the snapshot with the required snapshot class. Each volume snapshot is associated with a single volume snapshot class.

A `VolumeSnapshotClass` should be defined by an administrator in order to create snapshots. A volume snapshot class is created with the following definition:

```
apiVersion: snapshot.storage.k8s.io/v1
kind: VolumeSnapshotClass
metadata:
  name: csi-snapclass
driver: csi.trident.netapp.io
deletionPolicy: Delete
```

The `driver` specifies to Kubernetes that requests for volume snapshots of the `csi-snapclass` class are handled by Trident. The `deletionPolicy` specifies the action to be taken when a snapshot must be deleted. When `deletionPolicy` is set to `Delete`, the volume snapshot objects as well as the underlying snapshot on the storage cluster are removed when a snapshot is deleted. Alternatively, setting it to `Retain` means that `VolumeSnapshotContent` and the physical snapshot are retained.

Kubernetes `VolumeSnapshot` objects

A Kubernetes `VolumeSnapshot` object is a request to create a snapshot of a volume. Just as a PVC represents a request made by a user for a volume, a volume snapshot is a request made by a user to create a snapshot of an existing PVC.

When a volume snapshot request comes in, Trident automatically manages the creation of the snapshot for the volume on the backend and exposes the snapshot by creating a unique `VolumeSnapshotContent` object. You can create snapshots from existing PVCs and use the snapshots as a `DataSource` when creating new PVCs.



The lifecycle of a `VolumeSnapshot` is independent of the source PVC: a snapshot persists even after the source PVC is deleted. When deleting a PVC which has associated snapshots, Trident marks the backing volume for this PVC in a **Deleting** state, but does not remove it completely. The volume is removed when all the associated snapshots are deleted.

Kubernetes `VolumeSnapshotContent` objects

A Kubernetes `VolumeSnapshotContent` object represents a snapshot taken from an already provisioned volume. It is analogous to a `PersistentVolume` and signifies a provisioned snapshot on the storage cluster. Similar to `PersistentVolumeClaim` and `PersistentVolume` objects, when a snapshot is created, the `VolumeSnapshotContent` object maintains a one-to-one mapping to the `VolumeSnapshot` object, which had requested the snapshot creation.

The `VolumeSnapshotContent` object contains details that uniquely identify the snapshot, such as the `snapshotHandle`. This `snapshotHandle` is a unique combination of the name of the PV and the name of the `VolumeSnapshotContent` object.

When a snapshot request comes in, Trident creates the snapshot on the backend. After the snapshot is created, Trident configures a `VolumeSnapshotContent` object and thus exposes the snapshot to the Kubernetes API.



Typically, you do not need to manage the `VolumeSnapshotContent` object. An exception to this is when you want to [import a volume snapshot](#) created outside of Astra Trident.

Kubernetes CustomResourceDefinition objects

Kubernetes Custom Resources are endpoints in the Kubernetes API that are defined by the administrator and are used to group similar objects. Kubernetes supports the creation of custom resources for storing a collection of objects. You can obtain these resource definitions by running `kubectl get crds`.

Custom Resource Definitions (CRDs) and their associated object metadata are stored by Kubernetes in its metadata store. This eliminates the need for a separate store for Trident.

Astra Trident uses CustomResourceDefinition objects to preserve the identity of Trident objects, such as Trident backends, Trident storage classes, and Trident volumes. These objects are managed by Trident. In addition, the CSI volume snapshot framework introduces some CRDs that are required to define volume snapshots.

CRDs are a Kubernetes construct. Objects of the resources defined above are created by Trident. As a simple example, when a backend is created using `tridentctl`, a corresponding `tridentbackends` CRD object is created for consumption by Kubernetes.

Here are a few points to keep in mind about Trident's CRDs:

- When Trident is installed, a set of CRDs are created and can be used like any other resource type.
- When uninstalling Trident by using the `tridentctl uninstall` command, Trident pods are deleted but the created CRDs are not cleaned up. Refer to [Uninstall Trident](#) to understand how Trident can be completely removed and reconfigured from scratch.

Astra Trident StorageClass objects

Trident creates matching storage classes for Kubernetes StorageClass objects that specify `csi.trident.netapp.io` in their provisioner field. The storage class name matches that of the Kubernetes StorageClass object it represents.



With Kubernetes, these objects are created automatically when a Kubernetes StorageClass that uses Trident as a provisioner is registered.

Storage classes comprise a set of requirements for volumes. Trident matches these requirements with the attributes present in each storage pool; if they match, that storage pool is a valid target for provisioning volumes using that storage class.

You can create storage class configurations to directly define storage classes by using the REST API. However, for Kubernetes deployments, we expect them to be created when registering new Kubernetes StorageClass objects.

Astra Trident backend objects

Backends represent the storage providers on top of which Trident provisions volumes; a single Trident instance can manage any number of backends.



This is one of the two object types that you create and manage yourself. The other is the Kubernetes `StorageClass` object.

For more information about how to construct these objects, refer to [configuring backends](#).

Astra Trident `StoragePool` objects

Storage pools represent the distinct locations available for provisioning on each backend. For ONTAP, these correspond to aggregates in SVMs. For NetApp HCI/SolidFire, these correspond to administrator-specified QoS bands. For Cloud Volumes Service, these correspond to cloud provider regions. Each storage pool has a set of distinct storage attributes, which define its performance characteristics and data protection characteristics.

Unlike the other objects here, storage pool candidates are always discovered and managed automatically.

Astra Trident `Volume` objects

Volumes are the basic unit of provisioning, comprising backend endpoints, such as NFS shares and iSCSI LUNs. In Kubernetes, these correspond directly to `PersistentVolumes`. When you create a volume, ensure that it has a storage class, which determines where that volume can be provisioned, along with a size.



- In Kubernetes, these objects are managed automatically. You can view them to see what Trident provisioned.
- When deleting a PV with associated snapshots, the corresponding Trident volume is updated to a **Deleting** state. For the Trident volume to be deleted, you should remove the snapshots of the volume.

A volume configuration defines the properties that a provisioned volume should have.

Attribute	Type	Required	Description
version	string	no	Version of the Trident API ("1")
name	string	yes	Name of volume to create
storageClass	string	yes	Storage class to use when provisioning the volume
size	string	yes	Size of the volume to provision in bytes
protocol	string	no	Protocol type to use; "file" or "block"
internalName	string	no	Name of the object on the storage system; generated by Trident
cloneSourceVolume	string	no	ontap (nas, san) & solidfire-*: Name of the volume to clone from
splitOnClone	string	no	ontap (nas, san): Split the clone from its parent

Attribute	Type	Required	Description
snapshotPolicy	string	no	ontap-*: Snapshot policy to use
snapshotReserve	string	no	ontap-*: Percentage of volume reserved for snapshots
exportPolicy	string	no	ontap-nas*: Export policy to use
snapshotDirectory	bool	no	ontap-nas*: Whether the snapshot directory is visible
unixPermissions	string	no	ontap-nas*: Initial UNIX permissions
blockSize	string	no	solidfire-*: Block/sector size
fileSystem	string	no	File system type

Trident generates `internalName` when creating the volume. This consists of two steps. First, it prepends the storage prefix (either the default `trident` or the prefix in the backend configuration) to the volume name, resulting in a name of the form `<prefix>-<volume-name>`. It then proceeds to sanitize the name, replacing characters not permitted in the backend. For ONTAP backends, it replaces hyphens with underscores (thus, the internal name becomes `<prefix>_<volume-name>`). For Element backends, it replaces underscores with hyphens.

You can use volume configurations to directly provision volumes using the REST API, but in Kubernetes deployments we expect most users to use the standard Kubernetes `PersistentVolumeClaim` method. Trident creates this volume object automatically as part of the provisioning process.

Astra Trident Snapshot objects

Snapshots are a point-in-time copy of volumes, which can be used to provision new volumes or restore state. In Kubernetes, these correspond directly to `VolumeSnapshotContent` objects. Each snapshot is associated with a volume, which is the source of the data for the snapshot.

Each `Snapshot` object includes the properties listed below:

Attribute	Type	Required	Description
version	String	Yes	Version of the Trident API ("1")
name	String	Yes	Name of the Trident snapshot object
internalName	String	Yes	Name of the Trident snapshot object on the storage system

Attribute	Type	Required	Description
volumeName	String	Yes	Name of the Persistent Volume for which the snapshot is created
volumeInternalName	String	Yes	Name of the associated Trident volume object on the storage system



In Kubernetes, these objects are managed automatically. You can view them to see what Trident provisioned.

When a Kubernetes `VolumeSnapshot` object request is created, Trident works by creating a snapshot object on the backing storage system. The `internalName` of this snapshot object is generated by combining the prefix `snapshot-` with the UID of the `VolumeSnapshot` object (for example, `snapshot-e8d8a0ca-9826-11e9-9807-525400f3f660`). `volumeName` and `volumeInternalName` are populated by getting the details of the backing volume.

Astra Trident `ResourceQuota` object

The Trident daemonset consumes a `system-node-critical` Priority Class—the highest Priority Class available in Kubernetes—to ensure Astra Trident can identify and clean up volumes during graceful node shutdown and allow Trident daemonset pods to preempt workloads with a lower priority in clusters where there is high resource pressure.

To accomplish this, Astra Trident employs a `ResourceQuota` object to ensure a "system-node-critical" Priority Class on the Trident daemonset is satisfied. Prior to deployment and daemonset creation, Astra Trident looks for the `ResourceQuota` object and, if not discovered, applies it.

If you need more control over the default Resource Quota and Priority Class, you can generate a `custom.yaml` or configure the `ResourceQuota` object using Helm chart.

The following is an example of a `ResourceQuota` object prioritizing the Trident daemonset.

```
apiVersion: <version>
kind: ResourceQuota
metadata:
  name: trident-csi
  labels:
    app: node.csi.trident.netapp.io
spec:
  scopeSelector:
    matchExpressions:
      - operator : In
        scopeName: PriorityClass
        values: ["system-node-critical"]
```

For more information on Resource Quotas, refer to [Kubernetes: Resource Quotas](#).

Clean up ResourceQuota if installation fails

In the rare case where installation fails after the ResourceQuota object is created, first try [uninstalling](#) and then reinstall.

If that doesn't work, manually remove the ResourceQuota object.

Remove ResourceQuota

If you prefer to control your own resource allocation, you can remove the Astra Trident ResourceQuota object using the command:

```
kubectl delete quota trident-csi -n trident
```

Pod Security Standards (PSS) and Security Context Constraints (SCC)

Kubernetes Pod Security Standards (PSS) and Pod Security Policies (PSP) define permission levels and restrict the behavior of pods. OpenShift Security Context Constraints (SCC) similarly define pod restriction specific to the OpenShift Kubernetes Engine. To provide this customization, Astra Trident enables certain permissions during installation. The following sections detail the permissions set by Astra Trident.



PSS replaces Pod Security Policies (PSP). PSP was deprecated in Kubernetes v1.21 and will be removed in v1.25. For more information, Refer to [Kubernetes: Security](#).

Required Kubernetes Security Context and Related Fields

Permission	Description
Privileged	CSI requires mount points to be Bidirectional, which means the Trident node pod must run a privileged container. For more information, refer to Kubernetes: Mount propagation .
Host networking	Required for the iSCSI daemon. <code>iscsiadm</code> manages iSCSI mounts and uses host networking to communicate with the iSCSI daemon.
Host IPC	NFS uses interprocess communication (IPC) to communicate with the NFSD.
Host PID	Required to start <code>rpc-statd</code> for NFS. Astra Trident queries host processes to determine if <code>rpc-statd</code> is running before mounting NFS volumes.

Permission	Description
Capabilities	The <code>SYS_ADMIN</code> capability is provided as part of the default capabilities for privileged containers. For example, Docker sets these capabilities for privileged containers: <code>CapPrm: 0000003fffffffffff</code> <code>CapEff: 0000003fffffffffff</code>
Seccomp	Seccomp profile is always "Unconfined" in privileged containers; therefore, it cannot be enabled in Astra Trident.
SELinux	On OpenShift, privileged containers are run in the <code>spc_t</code> ("Super Privileged Container") domain, and unprivileged containers are run in the <code>container_t</code> domain. On <code>containerd</code> , with <code>container-selinux</code> installed, all containers are run in the <code>spc_t</code> domain, which effectively disables SELinux. Therefore, Astra Trident does not add <code>seLinuxOptions</code> to containers.
DAC	Privileged containers must be run as root. Non-privileged containers run as root to access unix sockets required by CSI.

Pod Security Standards (PSS)

Label	Description	Default
<code>pod-security.kubernetes.io/enforce</code>	Allows the Trident Controller and nodes to be admitted into the install namespace.	<code>enforce: privileged</code>
<code>pod-security.kubernetes.io/enforce-version</code>	Do not change the namespace label.	<code>enforce-version: <version of the current cluster or highest version of PSS tested.></code>



Changing the namespace labels can result in pods not being scheduled, an "Error creating: ..." or, "Warning: trident-csi-...". If this happens, check if the namespace label for `privileged` was changed. If so, reinstall Trident.

Pod Security Policies (PSP)

Field	Description	Default
<code>allowPrivilegeEscalation</code>	Privileged containers must allow privilege escalation.	<code>true</code>
<code>allowedCSIDrivers</code>	Trident does not use inline CSI ephemeral volumes.	Empty

Field	Description	Default
allowedCapabilities	Non-privileged Trident containers do not require more capabilities than the default set and privileged containers are granted all possible capabilities.	Empty
allowedFlexVolumes	Trident does not make use of a FlexVolume driver , therefore they are not included in the list of allowed volumes.	Empty
allowedHostPaths	The Trident node pod mounts the node's root filesystem, therefore there is no benefit to setting this list.	Empty
allowedProcMountTypes	Trident does not use any ProcMountTypes.	Empty
allowedUnsafeSysctls	Trident does not require any unsafe sysctls.	Empty
defaultAddCapabilities	No capabilities are required to be added to privileged containers.	Empty
defaultAllowPrivilegeEscalation	Allowing privilege escalation is handled in each Trident pod.	false
forbiddenSysctls	No sysctls are allowed.	Empty
fsGroup	Trident containers run as root.	RunAsAny
hostIPC	Mounting NFS volumes requires host IPC to communicate with nfsd	true
hostNetwork	iscsiadm requires the host network to communicate with the iSCSI daemon.	true
hostPID	Host PID is required to check if rpc-statd is running on the node.	true
hostPorts	Trident does not use any host ports.	Empty
privileged	Trident node pods must run a privileged container in order to mount volumes.	true
readOnlyRootFilesystem	Trident node pods must write to the node filesystem.	false
requiredDropCapabilities	Trident node pods run a privileged container and cannot drop capabilities.	none
runAsGroup	Trident containers run as root.	RunAsAny
runAsUser	Trident containers run as root.	runAsAny

Field	Description	Default
runtimeClass	Trident does not use RuntimeClasses.	Empty
seLinux	Trident does not set <code>seLinuxOptions</code> because there are currently differences in how container runtimes and Kubernetes distributions handle SELinux.	Empty
supplementalGroups	Trident containers run as root.	RunAsAny
volumes	Trident pods require these volume plugins.	hostPath, projected, emptyDir

Security Context Constraints (SCC)

Labels	Description	Default
allowHostDirVolumePlugin	Trident node pods mount the node's root filesystem.	true
allowHostIPC	Mounting NFS volumes requires host IPC to communicate with <code>nfsd</code> .	true
allowHostNetwork	<code>iscsiadm</code> requires the host network to communicate with the iSCSI daemon.	true
allowHostPID	Host PID is required to check if <code>rpc-statd</code> is running on the node.	true
allowHostPorts	Trident does not use any host ports.	false
allowPrivilegeEscalation	Privileged containers must allow privilege escalation.	true
allowPrivilegedContainer	Trident node pods must run a privileged container in order to mount volumes.	true
allowedUnsafeSysctls	Trident does not require any unsafe <code>sysctls</code> .	none
allowedCapabilities	Non-privileged Trident containers do not require more capabilities than the default set and privileged containers are granted all possible capabilities.	Empty
defaultAddCapabilities	No capabilities are required to be added to privileged containers.	Empty
fsGroup	Trident containers run as root.	RunAsAny

Labels	Description	Default
groups	This SCC is specific to Trident and is bound to its user.	Empty
readOnlyRootFilesystem	Trident node pods must write to the node filesystem.	false
requiredDropCapabilities	Trident node pods run a privileged container and cannot drop capabilities.	none
runAsUser	Trident containers run as root.	RunAsAny
seLinuxContext	Trident does not set <code>seLinuxOptions</code> because there are currently differences in how container runtimes and Kubernetes distributions handle SELinux.	Empty
seccompProfiles	Privileged containers always run "Unconfined".	Empty
supplementalGroups	Trident containers run as root.	RunAsAny
users	One entry is provided to bind this SCC to the Trident user in the Trident namespace.	n/a
volumes	Trident pods require these volume plugins.	hostPath, downwardAPI, projected, emptyDir

Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.