



# **Enable Storage Replication Adapter**

VSC, VASA Provider, and SRA 9.7

NetApp  
June 11, 2024

# Table of Contents

- Enable Storage Replication Adapter ..... 1
- Configure SRA on the SRM Appliance ..... 2
- Update Storage Replication Adapter (SRA) credentials ..... 3

# Enable Storage Replication Adapter

The virtual appliance for Virtual Storage Console (VSC), VASA Provider, and Storage Replication Adapter (SRA) provides the option to enable the SRA capability to be used with VSC to configure disaster recovery.

## Before you begin

- You must have set up your vCenter Server instance and configured ESXi.
- You must have deployed the virtual appliance for VSC, VASA Provider, and SRA.
- You must have downloaded the `.msi` file for the SRA plug-in, or the `.tar.gz` file for SRM appliance only if you want to configure the Site Recovery Manager (SRM) disaster recovery solution.

[Site Recovery Manager Installation and Configuration Site Recovery Manager 8.2](#) has more information.

## About this task

The flexibility to enable VASA Provider and SRA capabilities enables you to execute only the workflows that you require for your enterprise.

## Steps

1. Log in to the web user interface of VMware vSphere.
2. From the vSphere Client, click **Menu > Virtual Storage Console**.
3. Click **Settings**.
4. Click **Manage Capabilities** in the **Administrative Settings** tab.
5. In the **Manage Capabilities** dialog box, select the SRA extension want to enable.
6. Enter the IP address of the virtual appliance for VSC, VASA Provider, and SRA and the administrator password, and then click **Apply**.
7. You can use one of the following methods to deploy SRA:

Option	Description
For Windows SRM	<ol style="list-style-type: none"><li>a. Double-click the downloaded <code>.msi</code> installer for the SRA plug-in.</li><li>b. Follow the on-screen instructions.</li><li>c. Enter the IP address and password of your deployed virtual appliance.</li></ol>

Option	Description
For SRM appliance	<ol style="list-style-type: none"> <li>a. Access the SRM appliance page, and then go to <b>Storage Replication Adapters</b> page of SRM appliance.</li> <li>b. Click <b>New Adapter</b>.</li> <li>c. Upload the .tar.gz installer for the SRA plug-in to SRM.</li> <li>d. Rescan the adapters to verify that the details are updated in the SRM <b>Storage Replication Adapters</b> page.</li> </ol>

You must log out of the vSphere Client, and then log in again to verify that your selected extension is available for configuration.

### Related information

[Configure Storage Replication Adapter for disaster recovery](#)

## Configure SRA on the SRM Appliance

After you have deployed the SRM Appliance, you should configure SRA on the SRM Appliance. The successful configuration of SRA enables SRM Appliance to communicate with SRA for disaster recovery management. You should store the virtual appliance for VSC, VASA Provider, and SRA credentials (IP address and administrator password) in the SRM Appliance to enable communication between SRM Appliance and SRA.

### Before you begin

You should uploaded the `tar.gz` file to SRM Appliance.

### About this task

The configuration of SRA on SRM Appliance stores the SRA credentials in the SRM Appliance.

### Steps

1. Log in using administrator account to the SRM Appliance using `putty`.
2. Switch to the root user using the command: `su root`
3. At the log location enter the command to get the docker ID used by SRA `docker ps -l`
4. To login to the container ID, enter command `docker exec -it -u srm <container id> sh`
5. Configure SRM with the virtual appliance for VSC, VASA Provider, and SRA IP address and password using the command: `perl command.pl -I <va-IP> administrator <va-password>`

A success message confirming that the storage credentials are stored is displayed. SRA can communicate with SRA server using the provided IP address, port and credentials.

# Update Storage Replication Adapter (SRA) credentials

For SRM to communicate with SRA, you should update SRA credentials on the SRM server if you have modified the credentials.

## Before you begin

You should have executed the steps mentioned in the topic "Configuring SRA on SRM appliance".

## [Configure SRA on the SRM Appliance](#)

### Steps

1. Delete the contents of the `/srm/sra/conf` directory using:
  - a. `cd /srm/sra/conf`
  - b. `rm -rf *`
2. Execute the perl command to configure SRA with the new credentials:
  - a. `cd /srm/sra/`
  - b. `perl command.pl -l <va-IP> administrator <va-password>`

## Copyright information

Copyright © 2024 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

## Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.