



Configuring a database user on DataFabric Manager

OnCommand Workflow Automation 5.1

NetApp
May 03, 2022

Table of Contents

- Configuring a database user on DataFabric Manager 1
 - Configure a database user by running ocsetup on Windows..... 1
 - Configure a database user by running ocsetup on Linux..... 1

Configuring a database user on DataFabric Manager

You must create a database user on DataFabric Manager 5.x to configure read-only access of the DataFabric Manager 5.x database to OnCommand Workflow Automation.

Configure a database user by running ocsetup on Windows

You can run the ocsetup file on the DataFabric Manager 5.x server to configure read-only access of the DataFabric Manager 5.x database to OnCommand Workflow Automation.

Steps

1. Download the wfa_ocsetup.exe file to a directory in the DataFabric Manager 5.x server from the following location: `https://WFA_Server_IP/download/wfa_ocsetup.exe`.

WFA_Server_IP is the IP address (IPv4 or IPv6 address) of your WFA server.

If you have specified a non-default port for WFA, you must include the port number as follows:
`https://wfa_server_ip:port/download/wfa_ocsetup.exe`.

port is the TCP port number that you have used for the WFA server during installation.

If you are specifying an IPv6 address, you must enclose it with square brackets.

2. Double-click the wfa_ocsetup.exe file.
3. Read the information in the setup wizard and click **Next**.
4. Browse or type the OpenJDK location and click **Next**.
5. Enter a user name and password to override the default credentials.

A new database user account is created with access to the DataFabric Manager 5.x database.



If you do not create a user account, the default credentials are used. You must create a user account for security purposes.

6. Click **Next** and review the results.
7. Click **Next**, and then click **Finish** to complete the wizard.

Configure a database user by running ocsetup on Linux

You can run the ocsetup file on the DataFabric Manager 5.x server to configure read-only access of the DataFabric Manager 5.x database to OnCommand Workflow Automation.

Steps

1. Download the wfa_ocsetup.sh file to your home directory on the DataFabric Manager 5.x server using the following command in the terminal:

```
wget https://WFA_Server_IP/download/wfa_ocsetup.sh
```

WFA_Server_IP is the IP address (IPv4 or IPv6 address) of your WFA server.

If you have specified a non-default port for WFA, you must include the port number as follows:

```
wget https://wfa_server_ip:port/download/wfa_ocsetup.sh
```

port is the TCP port number that you have used for the WFA server during installation.

If you are specifying an IPv6 address, you must enclose it with square brackets.

2. Use the following command in the terminal to change the wfa_ocsetup.sh file to an executable: `chmod +x wfa_ocsetup.sh`
3. Run the script by entering the following in the terminal:

```
./wfa_ocsetup.sh OpenJDK_path
```

OpenJDK_path is the path to OpenJDK.

```
/opt/NTAPdfm/java
```

The following output is displayed in the terminal, indicating a successful setup:

```
Verifying archive integrity... All good.
Uncompressing WFA OnCommand Setup.....
*** Welcome to OnCommand Setup Utility for Linux ***
    <Help information>
*** Please override the default credentials below ***
Override DB Username [wfa] :
```

4. Enter a user name and password to override the default credentials.

A new database user account is created with access to the DataFabric Manager 5.x database.



If you do not create a user account, the default credentials are used. You must create a user account for security purposes.

The following output is displayed in the terminal, indicating a successful setup:

```
***** Start of response from the database *****
>>> Connecting to database
<<< Connected
*** Dropped existing 'wfa' user
=== Created user 'username'
>>> Granting access
<<< Granted access
***** End of response from the database *****
***** End of Setup *****
```

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.