



Storage VM administration

Amazon FSx for NetApp ONTAP

NetApp
February 02, 2026

This PDF was generated from <https://docs.netapp.com/us-en/workload-fsx-ontap/replicate-svm-to-file-system.html> on February 02, 2026. Always check docs.netapp.com for the latest.

Table of Contents

Storage VM administration	1
Replicate a storage VM to another FSx for ONTAP file system	1
Configure and update Active Directory for a storage VM	2
Manage storage VM tags in NetApp Workload Factory	3
Reset the storage VM password in NetApp Workload Factory	3
Delete a storage VM in NetApp Workload Factory	4

Storage VM administration

Replicate a storage VM to another FSx for ONTAP file system

Replicating a storage VM to another FSx for ONTAP file system in NetApp Workload Factory provides a protective layer of data access in case of data loss. This operation replicates all volumes in one storage VM to another FSx for ONTAP file system.

Before you begin

To replicate a storage VM to another FSx for ONTAP file system, you must associate a link. [Learn how to associate an existing link or to create and associate a new link](#). After the link associates, return to this operation.

Steps

1. Log in using one of the [console experiences](#).
2. Select the menu and then select **Storage**.
3. From the Storage menu, select **FSx for ONTAP**.
4. From **FSx for ONTAP**, select the actions menu of the file system with the storage VM to replicate and then select **Manage**.
5. In the file system overview under Storage VMs, select **Manage**.
6. On the Manage storage VMs screen, select the actions menu of the storage VM to replicate an SVM for, then select **Advanced actions > Replicate storage VM**.
7. On the Replicate data page, under Replication target, provide the following:
 - a. **FSx for ONTAP file system**: Select credentials, region, and FSx for ONTAP file system name for the target FSx for ONTAP file system.
 - b. **Storage VM name**: Select the storage VM from the dropdown menu.
 - c. **Volume name**: The target volume name is generated automatically with the following format {OriginalVolumeName}_copy.
 - d. **Tiering policy**: Select the tiering policy for the data stored in the target volume.

Auto is the default tiering policy when creating a volume using the Workload Factory FSx for ONTAP user interface. For more information about volume tiering policies, refer to [Volume storage capacity](#) in AWS FSx for NetApp ONTAP documentation.

- e. **Max transfer rate**: Select **Limited** and enter the max transfer limit in MB/s. Alternatively, select **Unlimited**.

Without a limit, network and application performance might decline. Alternatively, we recommend an unlimited transfer rate for FSx for ONTAP file systems for critical workloads, for example, those that are used primarily for disaster recovery.

8. Under Replication settings, provide the following:
 - a. **Replication interval**: Select the frequency that snapshots are transferred from the source volume to the target volume.
 - b. **Long-term retention**: Optionally, enable snapshots for long-term retention.

If you enable long-term retention, then select an existing policy or create a new policy to define the snapshots to replicate and the number to retain.

- i. For **Choose an existing policy**, select an existing policy from the dropdown menu.
- ii. For **Create a new policy**, provide the following:
 - A. **Policy name**: Enter a policy name.
 - B. **Snapshot policies**: In the table, select the snapshot policy frequency and the number of copies to retain. You can select more than one snapshot policy.

9. Select **Create**.

Result

All volumes within the storage VM are replicated to the target file system.

Configure and update Active Directory for a storage VM

Configure and update Active Directory for a storage VM in an FSx for ONTAP file system in NetApp Workload Factory.

About this task

The same steps apply for configuring and updating Active Directory for a storage VM.

Steps

1. Log in using one of the [console experiences](#).
2. Select the menu and then select **Storage**.
3. From the Storage menu, select **FSx for ONTAP**.
4. From **FSx for ONTAP**, select the actions menu of the file system with the storage VM to update and then select **Manage**.
5. In the file system overview under Storage VMs, select **Manage**.
6. From the Manage storage VMs screen, select the actions menu of the storage VM to configure Active Directory for, then select **Basic actions > Manage AD configuration**.
7. On the Manage AD configuration page, provide the following:
 - a. **Active Directory domain to join**: Enter the fully qualified domain name (FQDN) of your Active Directory.
 - b. **DNS IP addresses**: Enter up to three IP addresses separated by commas.
 - c. **SMB server NetBIOS name**: Enter the SMB server NetBIOS name of the Active Directory computer object to create for your storage VM. This is the name of this SVM in Active Directory.
 - d. **User name**: Enter the user name of the service account in your existing Active Directory.

Do not include a domain prefix or suffix. For EXAMPLE\ADMIN, use ADMIN.

- e. **Password**: Enter the password for the service account.
- f. **Organization unit (OU)**: Enter the organization unit.

The OU is the distinguished path name of the organizational unit to which you want to join your file system.

g. **Delegated administrators group:** Optionally, enter the delegated file system administrators group.

The delegated administrators group is the name of the group in your Active Directory that can administer your file system.

If you are using AWS Managed Microsoft AD, you must specify a group such as AWS Delegated FSx Administrators, AWS Delegated Administrators, or a custom group with delegated permissions to the OU.

If you are connecting to a self-managed AD, use the name of the group in your AD. The default group is Domain Admins.

8. Select **Apply**.

Manage storage VM tags in NetApp Workload Factory

Tags can help you categorize your resources. You can add, edit, and remove tags for a storage VM at any time in NetApp Workload Factory.

Steps

1. Log in using one of the [console experiences](#).
2. Select the menu and then select **Storage**.
3. From the Storage menu, select **FSx for ONTAP**.
4. From **FSx for ONTAP**, select the actions menu of the file system with the storage VM to update and then select **Manage**.
5. In the file system overview under Storage VMs, select **Manage**.
6. From the Manage storage VMs screen, select the actions menu of the storage VM to edit tags for, then select **Basic actions > Edit storage VM tags**.
7. On the Edit storage VM tags page, add, edit, or remove tags.

The maximum number of tags you can apply to a storage VM is 50.

8. Select **Apply**.

Reset the storage VM password in NetApp Workload Factory

Reset the password for a storage VM in NetApp Workload Factory when necessary.

Steps

1. Log in using one of the [console experiences](#).
2. Select the menu and then select **Storage**.
3. From the Storage menu, select **FSx for ONTAP**.
4. From **FSx for ONTAP**, select the actions menu of the file system with the storage VM password to reset and then select **Manage**.
5. In the file system overview under Storage VMs, select **Manage**.

6. From the Manage storage VMs screen, select the actions menu of the storage VM to reset the password for, then select **Basic actions > Reset password**.
7. In the Reset password dialog, provide the following:
 - a. **New password**: Enter a new password for the storage VM.
 - b. **Confirm password**: Enter the new password again to confirm.
8. Select **Apply**.

Delete a storage VM in NetApp Workload Factory

Delete a storage VM (SVM) that you no longer require from an FSx for ONTAP file system configuration.

Before you begin

Review the following before you delete a storage VM:

- Make sure that no applications are accessing the data in the SVM.
- Delete all non-root volumes attached to the SVM.

Steps

1. Log in using one of the [console experiences](#).
2. Select the menu and then select **Storage**.
3. From the Storage menu, select **FSx for ONTAP**.
4. From **FSx for ONTAP**, select the actions menu of the file system to update and then select **Manage**.
5. In the file system overview under Storage VMs, select **Manage**.
6. On the Manage storage VMs screen, select the actions menu of the storage VM to delete.
7. Select **Delete storage VM**.
8. In the Delete storage VM dialog, type “delete” to delete the storage VM.
9. Select **Delete** to confirm.

Copyright information

Copyright © 2026 NetApp, Inc. All Rights Reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

LIMITED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (b)(3) of the Rights in Technical Data -Noncommercial Items at DFARS 252.227-7013 (FEB 2014) and FAR 52.227-19 (DEC 2007).

Data contained herein pertains to a commercial product and/or commercial service (as defined in FAR 2.101) and is proprietary to NetApp, Inc. All NetApp technical data and computer software provided under this Agreement is commercial in nature and developed solely at private expense. The U.S. Government has a non-exclusive, non-transferrable, nonsublicensable, worldwide, limited irrevocable license to use the Data only in connection with and in support of the U.S. Government contract under which the Data was delivered. Except as provided herein, the Data may not be used, disclosed, reproduced, modified, performed, or displayed without the prior written approval of NetApp, Inc. United States Government license rights for the Department of Defense are limited to those rights identified in DFARS clause 252.227-7015(b) (FEB 2014).

Trademark information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.