



# Token

## Astra Automation

NetApp  
June 28, 2024

# 目录

|  |    |
|--|----|
| Token .....                                    | 1  |
| Token overview .....                           | 1  |
| Create a new token for a user in a group ..... | 1  |
| List the tokens for a user in a group .....    | 9  |
| Retrieve a token for a user in a group .....   | 18 |
| Modify a token for a user in a group .....     | 24 |
| Delete a token for a user in a group .....     | 32 |
| Create a new token for a user .....            | 35 |
| List the tokens for a user .....               | 44 |
| Retrieve a token .....                         | 53 |
| Modify a token .....                           | 59 |
| Delete a token .....                           | 67 |

# Token

## Token overview

The Token API enables users to create and manage API access tokens.

## Create a new token for a user in a group

POST /accounts/{account\_id}/core/v1/groups/{group\_id}/users/{user\_id}/tokens

Indicates desired values for the Token API resource to be created.

### Parameters

| Name       | Type   | In   | Required | Description   |
|------------|--------|------|----------|---|
| account_id | string | path | True     | ID of the containing account resource<br><ul style="list-style-type: none"><li>example: <code>{{.Account}}</code></li></ul> |
| group_id   | string | path | True     | ID of the containing group resource   |
| user_id    | string | path | True     | ID of the containing user resource  |

### Request Body

Indicates desired values for the Token API resource to be created.

| Name    | Type   | Required | Description  |
|---------|--------|----------|--|
| type    | string | True     | Media type of the resource. Defined values are:<br><ul style="list-style-type: none"><li>"application/astra-token"</li></ul> |
| version | string | True     | Version of the resource. Defined values are:<br><ul style="list-style-type: none"><li>"1.0"</li></ul>                        |

| Name     | Type                                       | Required | Description  |
|----------|--|----------|--|
| name     | string                                     | True     | <p>JSON string containing a token name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li> </ul>  |
| metadata | <a href="#">type_astra_metadata_update</a> | False    | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

### Example request

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "name": "Snapshot Script"
}
```

### Response

Status: 201, Returns the newly created token resource in the JSON response body.

| Name    | Type   | Required | Description  |
|---------|--------|----------|--|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-token"</li></ul>  |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"><li>• "1.0"</li></ul>   |
| id      | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the UUIDv4 Schema</li></ul>  |
| name    | string | True     | JSON string containing a token name. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li><li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li></ul> |
| userID  | string | True     | JSON string containing the UUID for the user that the token is associated with. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the Astra Identifier Schema</li></ul>  |

| Name     | Type                                       | Required | Description  |
|----------|--|----------|--|
| token    | string                                     | True     | <p>JSON string containing a base64-encoded system-generated API token. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the base64 Encoded Data Schema</li> </ul>  |
| metadata | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

### Example response

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "id": "822fab12-c224-5d1f-8118-5fb5d2def8b9",
  "name": "Snapshot Script",
  "userID": "09f8933c-ad74-4f4e-8ef5-1ffaa0fb8e9b",
  "token": "QSBKV1QgVG9rZW4gd291bGQgZ28gaGVyZS4=",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 409, Conflict

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden



| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

### See Definitions

type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

invalidFields

| Name   | Type   | Required | Description                                  |
|--------|--------|----------|--|
| name   | string | True     | Name of the invalid request body field       |
| reason | string | True     | Reason why the request body field is invalid |

# List the tokens for a user in a group

GET /accounts/{account\_id}/core/v1/groups/{group\_id}/users/{user\_id}/tokens

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name       | Type   | In    | Required | Description   |
|------------|--------|-------|----------|---|
| account_id | string | path  | True     | ID of the containing account resource<br><ul style="list-style-type: none"><li>example: <code>{{.Account}}</code></li></ul>   |
| group_id   | string | path  | True     | ID of the containing group resource   |
| user_id    | string | path  | True     | ID of the containing user resource  |
| include    | string | query | False    | Indicates which fields should be returned when listing a collection.<br><br>URL examples:<br>"include=id",<br>"include=id,name"<br><br>OpenAPI examples:<br>"id"<br><ul style="list-style-type: none"><li>example: <code>id,name</code></li></ul> |
| limit      | string | query | False    | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples:<br>"limit=2"<br><br>OpenAPI examples:<br>"2"  |

| Name    | Type   | In    | Required | Description  |
|---------|--------|-------|----------|--|
| filter  | string | query | False    | <p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> <li>• eq - Equality</li> <li>• lt/gt - Less than/Greater than</li> <li>• lte/gte - Less than or equals to/Greater than or equals to</li> </ul> <p>URL example:<br/>"filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples:<br/>"field eq 'value'"</p> |
| orderBy | string | query | False    | <p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples:<br/>"orderBy=name",<br/>"orderBy=name%20desc"</p> <p>OpenAPI examples:<br/>"name desc"</p>   |
| skip    | string | query | False    | <p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples:<br/>"skip=1"</p> <p>OpenAPI examples:<br/>"1"</p>  |

| Name     | Type   | In    | Required | Description  |
|----------|--------|-------|----------|--|
| count    | string | query | False    | Indicates if the total number of resources should be returned in the metadata object.<br><br>URL examples:<br>"count=true"<br><br>OpenAPI examples:<br>"true"  |
| continue |        | query | False    | Indicates the token to resume listing from.<br><br>URL examples:<br>"continue=<continue token="" from="" collection="" metadata=""></continue><br><br>OpenAPI examples:<br>"<continue token="" from="" collection="" metadata=""></continue>&lt;/continue&gt;" |

## Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name     | Type   | Required | Description |
|----------|--|----------|-------------|
| items    | array[Any of: <a href="#">token_1.0_get_response_body</a> , array[]] | True     |             |
| metadata | <a href="#">type_astra_metadata_list</a>                             | True     |             |

## Example response

```
{
  "type": "application/astra-tokens",
  "version": "1.0",
  "items": [
    [
      "4e99da96-152e-4aee-9207-4b6d04d2238d",
      "Snapshot Script"
    ],
    [
      "43ab09af-e558-4b1b-a6d5-49df7c39f22c",
      "Snapshot Taker"
    ],
    [
      "cca48856-9e25-4170-b49a-d32265c5e5f1",
      "Volume Checker"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```



**Definitions**

## See Definitions

### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

### token\_1.0\_get\_response\_body

| Name    | Type   | Required | Description   |
|---------|--------|----------|---|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-token"</li></ul>                     |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"><li>• "1.0"</li></ul>  |
| id      | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the UUIDv4 Schema</li></ul> |

| Name     | Type                                       | Required | Description   |
|----------|--|----------|---|
| name     | string                                     | True     | <p>JSON string containing a token name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li> </ul>   |
| userID   | string                                     | True     | <p>JSON string containing the UUID for the user that the token is associated with. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>  |
| metadata | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

type\_astra\_metadata\_list

| Name     | Type   | Required | Description |
|----------|--------|----------|-------------|
| continue | string | False    |             |

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| count                 | number                  | False    |             |
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

## Retrieve a token for a user in a group

GET

```
/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/tokens/{token_id}
```

Returns the stored Token API resource in the JSON response body.

- The "token" key/value will not be returned.

### Parameters

| Name       | Type   | In   | Required | Description   |
|------------|--------|------|----------|---|
| account_id | string | path | True     | ID of the containing account resource<br><br>• example:<br>{{.Account}} |
| group_id   | string | path | True     | ID of the containing group resource                                     |
| user_id    | string | path | True     | ID of the containing user resource                                      |

| Name     | Type   | In   | Required | Description                        |
|----------|--------|------|----------|------------------------------------|
| token_id | string | path | True     | ID of the token collection to list |

## Response

Status: 200

Returns the stored Token API resource in the JSON response body.

- The "token" key/value will not be returned.

| Name    | Type   | Required | Description  |
|---------|--------|----------|--|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "application/astra-token"</li> </ul>  |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>• "1.0"</li> </ul>   |
| id      | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>• Conforms to the UUIDv4 Schema</li> </ul>  |
| name    | string | True     | JSON string containing a token name. Defined values are: <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li> </ul> |

| Name     | Type                                       | Required | Description  |
|----------|--|----------|--|
| userID   | string                                     | True     | <p>JSON string containing the UUID for the user that the token is associated with. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>   |
| metadata | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

### Example response

```

{
  "type": "application/astra-token",
  "version": "1.0",
  "id": "822fab12-c224-5d1f-8118-5fb5d2def8b9",
  "name": "Snapshot Script",
  "userID": "09f8933c-ad74-4f4e-8ef5-1ffaa0fb8e9b",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}

```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

| Name   | Type   | Required | Description |
|--------|--------|----------|-------------|
| type   | string | True     |             |
| title  | string | True     |             |
| detail | string | True     |             |



| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

### Definitions

## See Definitions

type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

## Modify a token for a user in a group

PUT

```
/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/tokens/{token_id}
```

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

### Parameters

| Name       | Type   | In   | Required | Description   |
|------------|--------|------|----------|---|
| account_id | string | path | True     | ID of the containing account resource<br><br>• example:<br>{{.Account}} |
| group_id   | string | path | True     | ID of the containing group resource                                     |
| user_id    | string | path | True     | ID of the containing user resource                                      |
| token_id   | string | path | True     | ID of the token collection to list                                      |

## Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

| Name    | Type   | Required | Description  |
|---------|--------|----------|--|
| type    | string | True     | Media type of the resource. Defined values are:<br><br>• "application/astra-token"                     |
| version | string | True     | Version of the resource. Defined values are:<br><br>• "1.0"  |
| id      | string | False    | Globally unique identifier of the resource. Defined values are:<br><br>• Conforms to the UUIDv4 Schema |

| Name     | Type                       | Required | Description  |
|----------|----------------------------|----------|--|
| name     | string                     | False    | <p>JSON string containing a token name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li> </ul>  |
| userID   | string                     | False    | <p>JSON string containing the UUID for the user that the token is associated with. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>   |
| metadata | type_astra_metadata_update | False    | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

### Example request

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "name": "New Token Name"
}
```

### Response

Status: 204, Indicates if the token resource was updated.

### Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 409, Conflict

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| type  | string | True     |             |
| title | string | True     |             |

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

### Definitions



## See Definitions

### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

### invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

### invalidFields

| Name   | Type   | Required | Description                                  |
|--------|--------|----------|--|
| name   | string | True     | Name of the invalid request body field       |
| reason | string | True     | Reason why the request body field is invalid |

# Delete a token for a user in a group

DELETE

```
/accounts/{account_id}/core/v1/groups/{group_id}/users/{user_id}/tokens/{token_id}
```

Removes the specified Token API resource.

## Side Effects

- The corresponding API token credential is removed from the credential service as a side effect.

## Parameters

| Name       | Type   | In   | Required | Description   |
|------------|--------|------|----------|---|
| account_id | string | path | True     | ID of the containing account resource<br><ul style="list-style-type: none"><li>• example: <code>{{.Account}}</code></li></ul> |
| group_id   | string | path | True     | ID of the containing group resource   |
| user_id    | string | path | True     | ID of the containing user resource  |
| token_id   | string | path | True     | ID of the token collection to list  |

## Response

Status: 204, Indicates if the token resource was deleted.

## Response

Status: 401, Unauthorized

| Name   | Type   | Required | Description |
|--------|--------|----------|-------------|
| type   | string | True     |             |
| title  | string | True     |             |
| detail | string | True     |             |
| status | string | True     |             |

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

## Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

## Definitions

### See Definitions

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

## Create a new token for a user

POST /accounts/{account\_id}/core/v1/users/{user\_id}/tokens

Indicates desired values for the Token API resource to be created.

### Parameters

| Name       | Type   | In   | Required | Description   |
|------------|--------|------|----------|---|
| account_id | string | path | True     | ID of the containing account resource<br><ul style="list-style-type: none"><li>example: <code>{{.Account}}</code></li></ul> |
| user_id    | string | path | True     | ID of the containing user resource  |

### Request Body

Indicates desired values for the Token API resource to be created.

| Name     | Type                                       | Required | Description   |
|----------|--|----------|---|
| type     | string                                     | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>"application/astra-token"</li> </ul>   |
| version  | string                                     | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>"1.0"</li> </ul>  |
| name     | string                                     | True     | JSON string containing a token name. Defined values are: <ul style="list-style-type: none"> <li>Minimum length: 1</li> <li>Maximum length: 63</li> <li>This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li> </ul>  |
| metadata | <a href="#">type_astra_metadata_update</a> | False    | Client and service-specified metadata associated with the resource. Defined values are: <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

## Example request

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "name": "Snapshot Script"
}
```

## Response

Status: 201, Returns the newly created token resource in the JSON response body.

| Name    | Type   | Required | Description  |
|---------|--------|----------|--|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>"application/astra-token"</li></ul>  |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"><li>"1.0"</li></ul>   |
| id      | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>Conforms to the UUIDv4 Schema</li></ul>  |
| name    | string | True     | JSON string containing a token name. Defined values are: <ul style="list-style-type: none"><li>Minimum length: 1</li><li>Maximum length: 63</li><li>This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li></ul> |

| Name     | Type                       | Required | Description   |
|----------|----------------------------|----------|---|
| userID   | string                     | True     | <p>JSON string containing the UUID for the user that the token is associated with. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>  |
| token    | string                     | True     | <p>JSON string containing a base64-encoded system-generated API token. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the base64 Encoded Data Schema</li> </ul>   |
| metadata | type_astra_metadata_update | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |



## Example response

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "id": "822fab12-c224-5d1f-8118-5fb5d2def8b9",
  "name": "Snapshot Script",
  "userID": "09f8933c-ad74-4f4e-8ef5-1ffaa0fb8e9b",
  "token": "QSBKV1QgVG9rZW4gd291bGQgZ28gaGVyZS4=",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

## Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 409, Conflict

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| type  | string | True     |             |
| title | string | True     |             |

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

### Definitions

## See Definitions

### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

### invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

### invalidFields

| Name   | Type   | Required | Description                                  |
|--------|--------|----------|--|
| name   | string | True     | Name of the invalid request body field       |
| reason | string | True     | Reason why the request body field is invalid |

# List the tokens for a user

GET /accounts/{account\_id}/core/v1/users/{user\_id}/tokens

Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

## Parameters

| Name       | Type   | In    | Required | Description   |
|------------|--------|-------|----------|---|
| account_id | string | path  | True     | ID of the containing account resource<br><ul style="list-style-type: none"><li>example: <code>{{.Account}}</code></li></ul>   |
| user_id    | string | path  | True     | ID of the containing user resource  |
| include    | string | query | False    | Indicates which fields should be returned when listing a collection.<br><br>URL examples:<br>"include=id",<br>"include=id,name"<br><br>OpenAPI examples:<br>"id"<br><ul style="list-style-type: none"><li>example: <code>id,name</code></li></ul> |
| limit      | string | query | False    | Indicates the maximum number of resources to return when listing a collection.<br><br>URL examples:<br>"limit=2"<br><br>OpenAPI examples:<br>"2"  |

| Name    | Type   | In    | Required | Description  |
|---------|--------|-------|----------|--|
| filter  | string | query | False    | <p>Indicates which fields should be matched in order to return a resource when listing a collection.</p> <p>Supported operators are:</p> <ul style="list-style-type: none"> <li>• eq - Equality</li> <li>• lt/gt - Less than/Greater than</li> <li>• lte/gte - Less than or equals to/Greater than or equals to</li> </ul> <p>URL example:<br/>"filter=field%20eq%20%27value%27"</p> <p>OpenAPI examples:<br/>"field eq 'value'"</p> |
| orderBy | string | query | False    | <p>Indicates the sort order of resource when listing a collection.</p> <p>URL examples:<br/>"orderBy=name",<br/>"orderBy=name%20desc"</p> <p>OpenAPI examples:<br/>"name desc"</p>   |
| skip    | string | query | False    | <p>Indicates the number of resources to skip over when listing a collection.</p> <p>URL examples:<br/>"skip=1"</p> <p>OpenAPI examples:<br/>"1"</p>  |

| Name     | Type   | In    | Required | Description  |
|----------|--------|-------|----------|--|
| count    | string | query | False    | Indicates if the total number of resources should be returned in the metadata object.<br><br>URL examples:<br>"count=true"<br><br>OpenAPI examples:<br>"true"  |
| continue |        | query | False    | Indicates the token to resume listing from.<br><br>URL examples:<br>"continue=<continue token="" from="" collection="" metadata=""></continue><br><br>OpenAPI examples:<br>"<continue token="" from="" collection="" metadata=""></continue>&lt;/continue&gt;" |

## Response

Status: 200, Returns a JSON array of all matching resources in the collection. If individual fields are specified in the request, the items JSON array will contain the fields requested for each matching resource in the order specified.

| Name     | Type   | Required | Description |
|----------|--|----------|-------------|
| items    | array[Any of: <a href="#">token_1.0_get_response_body</a> , array[]] | True     |             |
| metadata | <a href="#">type_astra_metadata_list</a>                             | True     |             |



## Example response

```
{
  "type": "application/astra-tokens",
  "version": "1.0",
  "items": [
    [
      "4e99da96-152e-4aee-9207-4b6d04d2238d",
      "Snapshot Script"
    ],
    [
      "43ab09af-e558-4b1b-a6d5-49df7c39f22c",
      "Snapshot Taker"
    ],
    [
      "cca48856-9e25-4170-b49a-d32265c5e5f1",
      "Volume Checker"
    ]
  ],
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

# Definitions

## See Definitions

### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

### token\_1.0\_get\_response\_body

| Name    | Type   | Required | Description   |
|---------|--------|----------|---|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-token"</li></ul>                     |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"><li>• "1.0"</li></ul>  |
| id      | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the UUIDv4 Schema</li></ul> |

| Name     | Type                                       | Required | Description   |
|----------|--|----------|---|
| name     | string                                     | True     | <p>JSON string containing a token name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li> </ul>   |
| userID   | string                                     | True     | <p>JSON string containing the UUID for the user that the token is associated with. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>  |
| metadata | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

type\_astra\_metadata\_list

| Name     | Type   | Required | Description |
|----------|--------|----------|-------------|
| continue | string | False    |             |

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| count                 | number                  | False    |             |
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

## Retrieve a token

GET /accounts/{account\_id}/core/v1/users/{user\_id}/tokens/{token\_id}

Returns the stored Token API resource in the JSON response body.

- The "token" key/value will not be returned.

### Parameters

| Name       | Type   | In   | Required | Description   |
|------------|--------|------|----------|---|
| account_id | string | path | True     | ID of the containing account resource<br><br>• example:<br>{{.Account}} |
| user_id    | string | path | True     | ID of the containing user resource                                      |
| token_id   | string | path | True     | ID of the token collection to list                                      |

### Response

Status: 200

Returns the stored Token API resource in the JSON response body.

- The "token" key/value will not be returned.

| Name    | Type   | Required | Description  |
|---------|--------|----------|--|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"><li>• "application/astra-token"</li></ul>  |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"><li>• "1.0"</li></ul>   |
| id      | string | True     | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the UUIDv4 Schema</li></ul>  |
| name    | string | True     | JSON string containing a token name. Defined values are: <ul style="list-style-type: none"><li>• Minimum length: 1</li><li>• Maximum length: 63</li><li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li></ul> |
| userID  | string | True     | JSON string containing the UUID for the user that the token is associated with. Defined values are: <ul style="list-style-type: none"><li>• Conforms to the Astra Identifier Schema</li></ul>  |



| Name     | Type                                       | Required | Description   |
|----------|--|----------|---|
| metadata | <a href="#">type_astra_metadata_update</a> | True     | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

### Example response

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "id": "822fab12-c224-5d1f-8118-5fb5d2def8b9",
  "name": "Snapshot Script",
  "userID": "09f8933c-ad74-4f4e-8ef5-1ffaa0fb8e9b",
  "metadata": {
    "labels": [],
    "creationTimestamp": "2022-10-06T20:58:16.305662Z",
    "modificationTimestamp": "2022-10-06T20:58:16.305662Z",
    "createdBy": "8f84cf09-8036-51e4-b579-bd30cb07b269"
  }
}
```

### Response

Status: 401, Unauthorized

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| type  | string | True     |             |
| title | string | True     |             |

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

## Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

## Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

## Example error response

```
{
  "type": "https://astra.netapp.io/problems/2",
  "title": "Collection not found",
  "detail": "The collection specified in the request URI wasn't
found.",
  "status": "404"
}
```

## Definitions

## See Definitions

### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

### invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

## Modify a token

PUT /accounts/{account\_id}/core/v1/users/{user\_id}/tokens/{token\_id}

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

## Parameters

| Name       | Type   | In   | Required | Description  |
|------------|--------|------|----------|--|
| account_id | string | path | True     | ID of the containing account resource <ul style="list-style-type: none"> <li>example: <code>{{.Account}}</code></li> </ul> |
| user_id    | string | path | True     | ID of the containing user resource   |
| token_id   | string | path | True     | ID of the token collection to list   |

## Request Body

Replaces the entire stored resource with the supplied JSON request body while preserving key values that are not user-modifiable.

| Name    | Type   | Required | Description   |
|---------|--------|----------|---|
| type    | string | True     | Media type of the resource. Defined values are: <ul style="list-style-type: none"> <li>"application/astra-token"</li> </ul>                     |
| version | string | True     | Version of the resource. Defined values are: <ul style="list-style-type: none"> <li>"1.0"</li> </ul>  |
| id      | string | False    | Globally unique identifier of the resource. Defined values are: <ul style="list-style-type: none"> <li>Conforms to the UUIDv4 Schema</li> </ul> |

| Name     | Type                       | Required | Description  |
|----------|----------------------------|----------|--|
| name     | string                     | False    | <p>JSON string containing a token name. Defined values are:</p> <ul style="list-style-type: none"> <li>• Minimum length: 1</li> <li>• Maximum length: 63</li> <li>• This string is internally validated to prevent XSS, Unicode, directory traversal, and SQL-injection attacks.</li> </ul>  |
| userID   | string                     | False    | <p>JSON string containing the UUID for the user that the token is associated with. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Identifier Schema</li> </ul>   |
| metadata | type_astra_metadata_update | False    | <p>Client and service-specified metadata associated with the resource. Defined values are:</p> <ul style="list-style-type: none"> <li>• Conforms to the Astra Metadata Schema. If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.</li> </ul> |

## Example request

```
{
  "type": "application/astra-token",
  "version": "1.0",
  "name": "New Token Name"
}
```

## Response

Status: 204, Indicates if the token resource was updated.

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

## Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

## Response

Status: 400, Bad request



| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 409, Conflict

| Name          | Type                 | Required | Description                         |
|---------------|----------------------|----------|-------------------------------------|
| type          | string               | True     |                                     |
| title         | string               | True     |                                     |
| detail        | string               | True     |                                     |
| status        | string               | True     |                                     |
| correlationID | string               | False    |                                     |
| invalidFields | array[invalidFields] | False    | List of invalid request body fields |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/10",
  "title": "JSON resource conflict",
  "detail": "The request body JSON contains a field that conflicts with
an idempotent value.",
  "status": "409"
}
```

### Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| type  | string | True     |             |
| title | string | True     |             |

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

### Definitions

## See Definitions

### type\_astra\_label

| Name  | Type   | Required | Description |
|-------|--------|----------|-------------|
| name  | string | True     |             |
| value | string | True     |             |

### type\_astra\_metadata\_update

Client and service-specified metadata associated with the resource. Defined values are:

- Conforms to the Astra Metadata Schema If not specified on create, a metadata object will be created with no labels. If not specified on update, the metadata object's labels, creationTimestamp and createdBy, will be preserved without modification.

| Name                  | Type                    | Required | Description |
|-----------------------|-------------------------|----------|-------------|
| labels                | array[type_astra_label] | False    |             |
| creationTimestamp     | string                  | False    |             |
| modificationTimestamp | string                  | False    |             |
| createdBy             | string                  | False    |             |
| modifiedBy            | string                  | False    |             |

### invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |

### invalidFields

| Name   | Type   | Required | Description                                  |
|--------|--------|----------|--|
| name   | string | True     | Name of the invalid request body field       |
| reason | string | True     | Reason why the request body field is invalid |

# Delete a token

DELETE /accounts/{account\_id}/core/v1/users/{user\_id}/tokens/{token\_id}

Removes the specified Token API resource.

## Side Effects

- The corresponding API token credential is removed from the credential service as a side effect.

## Parameters

| Name       | Type   | In   | Required | Description   |
|------------|--------|------|----------|---|
| account_id | string | path | True     | ID of the containing account resource<br><ul style="list-style-type: none"><li>• example: <code>{{.Account}}</code></li></ul> |
| user_id    | string | path | True     | ID of the containing user resource  |
| token_id   | string | path | True     | ID of the token collection to list  |

## Response

Status: 204, Indicates if the token resource was deleted.

## Response

Status: 401, Unauthorized

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/3",
  "title": "Missing bearer token",
  "detail": "The request is missing the required bearer token.",
  "status": "401"
}
```

### Response

Status: 400, Bad request

| Name          | Type                 | Required | Description                      |
|---------------|----------------------|----------|----------------------------------|
| type          | string               | True     |                                  |
| title         | string               | True     |                                  |
| detail        | string               | True     |                                  |
| status        | string               | True     |                                  |
| correlationID | string               | False    |                                  |
| invalidParams | array[invalidParams] | False    | List of invalid query parameters |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/5",
  "title": "Invalid query parameters",
  "detail": "The supplied query parameters are invalid.",
  "status": "400"
}
```

### Response

Status: 403, Forbidden

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example response

```
{
  "type": "https://astra.netapp.io/problems/11",
  "title": "Operation not permitted",
  "detail": "The requested operation isn't permitted.",
  "status": "403"
}
```

### Error

Status: 404, Not found

| Name          | Type   | Required | Description |
|---------------|--------|----------|-------------|
| type          | string | True     |             |
| title         | string | True     |             |
| detail        | string | True     |             |
| status        | string | True     |             |
| correlationID | string | False    |             |

### Example error response

```
{
  "type": "https://astra.netapp.io/problems/1",
  "title": "Resource not found",
  "detail": "The resource specified in the request URI wasn't found.",
  "status": "404"
}
```

# Definitions

## See Definitions

invalidParams

| Name   | Type   | Required | Description                               |
|--------|--------|----------|---|
| name   | string | True     | Name of the invalid query parameter       |
| reason | string | True     | Reason why the query parameter is invalid |



## 版权信息

版权所有 © 2024 NetApp, Inc.。保留所有权利。中国印刷。未经版权所有者事先书面许可，本档中受版权保护的任何部分不得以任何形式或通过任何手段（图片、电子或机械方式，包括影印、录音、录像或存储在电子检索系统中）进行复制。

从受版权保护的 NetApp 资料派生的软件受以下许可和免责声明的约束：

本软件由 NetApp 按“原样”提供，不含任何明示或暗示担保，包括但不限于适销性以及针对特定用途的适用性的隐含担保，特此声明不承担任何责任。在任何情况下，对于因使用本软件而以任何方式造成的任何直接性、间接性、偶然性、特殊性、惩罚性或后果性损失（包括但不限于购买替代商品或服务；使用、数据或利润方面的损失；或者业务中断），无论原因如何以及基于何种责任理论，无论出于合同、严格责任或侵权行为（包括疏忽或其他行为），NetApp 均不承担责任，即使已被告知存在上述损失的可能性。

NetApp 保留在不另行通知的情况下随时对本文档所述的任何产品进行更改的权利。除非 NetApp 以书面形式明确同意，否则 NetApp 不承担因使用本文档所述产品而产生的任何责任或义务。使用或购买本产品不表示获得 NetApp 的任何专利权、商标权或任何其他知识产权许可。

本手册中描述的产品可能受一项或多项美国专利、外国专利或正在申请的专利的保护。

有限权利说明：政府使用、复制或公开本文档受 DFARS 252.227-7013（2014 年 2 月）和 FAR 52.227-19（2007 年 12 月）中“技术数据权利 — 非商用”条款第 (b)(3) 条规定的限制条件的约束。

本文档中所含数据与商业产品和/或商业服务（定义见 FAR 2.101）相关，属于 NetApp, Inc. 的专有信息。根据本协议提供的所有 NetApp 技术数据和计算机软件具有商业性质，并完全由私人出资开发。美国政府对这些数据的使用权具有非排他性、全球性、受限且不可撤销的许可，该许可既不可转让，也不可再许可，但仅限在与交付数据所依据的美国政府合同有关且受合同支持的情况下使用。除本文档规定的情形外，未经 NetApp, Inc. 事先书面批准，不得使用、披露、复制、修改、操作或显示这些数据。美国政府对国防部的授权仅限于 DFARS 的第 252.227-7015(b)（2014 年 2 月）条款中明确的权利。

## 商标信息

NetApp、NetApp 标识和 <http://www.netapp.com/TM> 上所列的商标是 NetApp, Inc. 的商标。其他公司和产品名称可能是其各自所有者的商标。